HTML Part -2

1. Comments in HTML

HTML supports comments in two ways:

a. Single Line Comment:

Used to comment a single line. Starts with <!-- and ends with -->.

```
<!-- This is a single line comment -->
```

b. Multi-Line Comment:

Used to comment multiple lines. Also starts with <!-- and ends with -->.

```
<!--
This is a multi-line comment.
You can write many lines here.
-->
```

---

2. File Paths in HTML

File paths are used to link to external resources such as images, stylesheets, scripts, etc.

a. Relative Paths:

Refers to the location of the file relative to the current HTML document.

- From the same directory:

```
<img src="image.jpg" alt="Image">
```

- From a subdirectory:

```
<link rel="stylesheet" href="css/style.css">
```

- From the parent directory:

```
<script src="../scripts/script.js"></script>
```

- From the root directory:

```
<a href="/home.html">Home</a>
```

GANESH DUTT

b. Absolute Paths:

Specifies the full URL of a resource.

<img src="https://example.com/images/image.jpg" alt="Image">

c. Root-Relative Paths:

Starts from the root of the site.

<img src="/images/image.jpg" alt="Image">

---

3. Iframes in HTML

The <iframe> element is used to embed another HTML page within the current one.

Key Attributes:

- *src: Specifies the URL of the document to embed.*
- *width & height: Set the size of the frame.*
- *frameborder: "0" means no border, "1" shows a border.*
- *scrolling: Controls scrollbars (auto, yes, no).*

Example:

```
<iframe src="https://ganeshdutt.netlify.app" width="800" height="600"
frameborder="0" scrolling="auto"></iframe>
```

---

4. HTML Tables

Tables are used to display tabular data.

Basic Tags:

- *<table>: Creates the table.*
- *<tr>: Creates a row.*
- *<th>: Creates a header cell.*
- *<td>: Creates a data cell.*

GANESH DUTT

Example:

```
<table>
  <tr>
    <th>Heading 1</th>
    <th>Heading 2</th>
    <th>Heading 3</th>
  </tr>
  <tr>
    <td>Data 1</td>
    <td>Data 2</td>
    <td>Data 3</td>
  </tr>
</table>
```

Additional Tags:

- *<thead>: Groups table header content.*
- *<tbody>: Groups table body content.*
- *<tfoot>: Groups table footer content.*
- *<caption>: Title of the table.*

Example with Attributes:

```
<table border="1" cellpadding="5" width="100%">
  <thead>
    <tr><th>Header 1</th><th>Header 2</th></tr>
  </thead>
  <tbody>
    <tr><td>Row 1</td><td>Data 1</td></tr>
  </tbody>
  <tfoot>
    <tr><td colspan="2">Footer</td></tr>
```

```
  </tfoot>
</table>
```

rowspan & colspan:

- *rowspan: Spans a cell over multiple rows.*
- *colspan: Spans a cell over multiple columns.*

```
<table>
  <tr>
    <th>Name</th>
    <th colspan="2">Contact Info</th>
  </tr>
  <tr>
    <td rowspan="2">Ganesh</td>
    <td>ganesh@example.com</td>
    <td>9999999999</td>
  </tr>
  <tr>
    <td>another@example.com</td>
    <td>8888888888</td>
  </tr>
</table>
```

---

5. Lists in HTML

Used to display items in list form.

a. Ordered List (<ol>):

Shows items in a numbered format.

```
<ol>
  <li>Item 1</li>
  <li>Item 2</li>
```

```
</ol>
```

b. Unordered List (<ul>):

Shows items with bullet points.

```
<ul>
  <li>Item A</li>
  <li>Item B</li>
</ul>
```

c. Definition List (<dl>):

Used for definitions.

```
<dl>
  <dt>HTML</dt>
  <dd>HyperText Markup Language</dd>
</dl>
```

d. Nested List:

List within a list.

```
<ol>
  <li>Main Item 1</li>
  <li>Main Item 2
    <ul>
      <li>Sub Item A</li>
      <li>Sub Item B</li>
    </ul>
  </li>
</ol>
```