

Control of Swarm of Mobile Robots in Unknown Environment

Aman Sharma
B. Pranay
K. Naga Ganesh
Tejkaran Charan

Under the Supervision of
Mr. Matam Manjunath
Department of Electrical and Electronics Engineering,
National Institute of Technology Goa.

April 7, 2014

Overview

- 1 Consensus problem
- 2 Formulations Presented So Far
- 3 MASON
- 4 Flocking
- 5 Go To Goal and Obstacle Avoidance Task Functions

Consensus problem

- A multi robot system (MRS) consists of N mobile robots and let $\mathbf{x} = [\mathbf{x}_1^T \mathbf{x}_2^T \cdots \mathbf{x}_N^T]^T$, where $\mathbf{x}_i \in \mathbb{R}^2$ denotes the position coordinates of i^{th} robot.
- A task can be modelled as driving the MRS from an initial state \mathbf{x}_0 to a final state \mathbf{x}_f
- Let initial state be \mathbf{x}_0 and final state be $\mathbf{x}_f = [\mathbf{c}^T \mathbf{c}^T \cdots \mathbf{c}^T]^T$, where $\mathbf{c} \in \mathbb{R}^2$

$$\mathbf{u}_i = \dot{\mathbf{x}}_i = k_p(\mathbf{c} - \mathbf{x}_i),$$

$$\dot{\mathbf{x}} = k_p(\mathbf{A}\mathbf{x} + \mathbf{b})$$

$$\mathbf{A} = \begin{bmatrix} -1 & 0 & 0 & \cdots & 0 \\ 0 & -1 & 0 & \cdots & 0 \\ \vdots & & & & \\ 0 & \cdots & 0 & -1 & 0 \\ 0 & 0 & 0 & \cdots & -1 \end{bmatrix} \text{ and } \mathbf{b} = \begin{bmatrix} \mathbf{c} \\ \mathbf{c} \\ \vdots \\ \mathbf{c} \end{bmatrix}, \quad (1)$$

where $\mathbf{A} \in \mathbb{R}^{2N \times 2N}$ and $\mathbf{b} \in \mathbb{R}^{2N}$

Objective

- 1 To drive the state of MRS from \mathbf{x}_0 to \mathbf{x}_f
- 2 Avoid intermittent obstacles.
- 3 Avoid collisions with neighboring robots.

Objective

- ① To drive the state of MRS from \mathbf{x}_0 to \mathbf{x}_f
- ② Avoid intermittent obstacles.
- ③ Avoid collisions with neighboring robots.

Challenge

- Generating appropriate control signals to satisfy all the aforementioned objectives simultaneously

Objective

- ① To drive the state of MRS from \mathbf{x}_0 to \mathbf{x}_f
- ② Avoid intermittent obstacles.
- ③ Avoid collisions with neighboring robots.

Challenge

- Generating appropriate control signals to satisfy all the aforementioned objectives simultaneously
- Handling conflicting tasks

Objective


- ① To drive the state of MRS from \mathbf{x}_0 to \mathbf{x}_f
- ② Avoid intermittent obstacles.
- ③ Avoid collisions with neighboring robots.


Challenge

- Generating appropriate control signals to satisfy all the aforementioned objectives simultaneously
- Handling conflicting tasks
- NSB at rescue.....

Formulations Presented So Far

- Swarm robotics
- Decentralized and centralized architecture
- Indeterminate systems
- Notion of Null Space behavioral control







Show simulation video 1.

MASON

MASON is a discrete-event multiagent simulation **Library** in Java
Environment



Controller



Some of inbuild functions used

Steppable(class)
Simstate(class)
doLoop(Name.class,args)
Jframe,controller

Task function associated with Flocking

$$\sigma_{2i} = \|\mathbf{x}_i - \mathbf{x}_j\|$$

$$\mathbf{J}_{2i} = \left[\frac{\mathbf{x}_i - \mathbf{x}_j}{\|\mathbf{x}_i - \mathbf{x}_j\|} \right]^T = \hat{\mathbf{r}}_{2i}^T$$

$$\mathbf{J}_{2i}^+ = \hat{\mathbf{r}}_{2i} \cdot \hat{\mathbf{r}}_{2i}^T$$

$$\sigma_{2d_i} = d$$

$$\mathbf{u}_{RA_i} = \mathbf{v}_{2i} = J_{2i}^+ \Lambda_f (d - \|\mathbf{x}_i - \mathbf{x}_j\|)$$

$$\mathcal{N}_{2i} = \mathcal{N}(\mathbf{J}_{2i}) = \mathbf{I} - \hat{\mathbf{r}}_{1i} \cdot \hat{\mathbf{r}}_{1i}^T$$

Task function associated with Go To Goal and Obstacle Avoidance

Obstacle Avoidance

$$\sigma_{1i} = ||\mathbf{x}_i - \mathbf{x}_{ob}||$$

$$\mathbf{J}_{1i} = \left[\frac{\mathbf{x}_i - \mathbf{x}_{ob}}{||\mathbf{x}_i - \mathbf{x}_{ob}||} \right]^T = \hat{\mathbf{r}}_{1i}^T$$

$$\mathbf{J}_{1i}^+ = \hat{\mathbf{r}}_{1i} \cdot \hat{\mathbf{r}}_{1i}^T$$

$$\sigma_{2d_i} = d$$

$$\mathbf{v}_{1i} = \mathbf{u}_{OA_i} = J_{1i}^+ \Lambda_{ob}(d - ||\mathbf{x}_i - \mathbf{x}_{ob}||)$$

$$\mathcal{N}_{1i} = \mathcal{N}(\mathbf{J}_{1i}) = \mathbf{I} - \hat{\mathbf{r}}_{1i} \cdot \hat{\mathbf{r}}_{1i}^T$$

Go To Goal


$$\sigma_{3i} = \mathbf{x}_i$$

$$\sigma_{2d_i} = \mathbf{x}_g$$


$$J_{3i} = \mathbf{I} = J_{3i}^+$$

$$\mathbf{v}_{3i} = \mathbf{u}_{GTG_i} = \Lambda_{GTG}(\mathbf{x}_g - \mathbf{x}_i)$$

Parameters	Value
Simulation Platform	MATLAB 2012a
No. of Robots (N)	3
Position of Robot 1 (\mathbf{x}_1)	$[0 \ 4]^T$
Position of Robot 2 (\mathbf{x}_2)	$[8 \ 4]^T$
Position of Robot 3 (\mathbf{x}_3)	$[9 \ 7]^T$
Position of Obstacle 1	$[2 \ 5]^T$
Position of Obstacle 2	$[4 \ 7]^T$
Position of Obstacle 3	$[6 \ 6]^T$
Position of Obstacle 4	$[8 \ 8]^T$
Rendezvous point	$[5 \ 9]^T$
Go to Goal Proportional gain	0.4
Safe distance	1
Obstacle Avoidance Proportional gain	1



Parameters	Value
Simulation Platform	MATLAB 2012a
No. of Robots (N)	3
Position of Robot 1 (\mathbf{x}_1)	$[5.5 \ 5]^T$
Position of Robot 2 (\mathbf{x}_2)	$[6.5 \ 5]^T$
Position of Robot 3 (\mathbf{x}_3)	$[5 \ 5.5]^T$
Position of Robot 4 (\mathbf{x}_4)	$[5 \ 6.5]^T$
Position of Robot 5 (\mathbf{x}_5)	$[6 \ 6]^T$
Position of Robot 6 (\mathbf{x}_6)	$[5 \ 5]^T$
Rendezvous point	$[10 \ 10]^T$
Go to Goal Proportional gain	0.8
Safe distance	1
Obstacle Avoidance Proportional gain	1.2



Modes of operation

- ① No Robot sensed in the vicinity: $\mathbf{v}_{d_i} = \mathbf{u}_{GTG_i}$
- ② One neighboring robot sensed: $\mathbf{v}_{d_i} = \mathbf{u}_{RA_i} + \mathcal{N}_{2_i} \cdot \mathbf{u}_{GTG_i}$
- ③ More than one neighboring robot sensed:

$$\mathbf{v}_{d_i} = \mathbf{u}_{RA'_i} + \mathcal{N}'_{2_i} \cdot \left(\mathbf{u}_{RA''_2} + \mathcal{N}''_{2_i} \cdot \mathbf{u}_{GTG_i} \right)$$

Mode of Operation

- ① **No obstacle or other robot sensed** : $\mathbf{v}_{d_i} = \mathbf{u}_{GTG_i}$
- ② **Only obstacle sensed** : $\mathbf{v}_{d_i} = \mathbf{u}_{OA_i} + \mathcal{N}_{1_i} \cdot \mathbf{u}_{GTG_i}$
- ③ **Only other robot sensed**: $\mathbf{v}_{d_i} = \mathbf{u}_{RA_i} + \mathcal{N}_{2_i} \cdot \mathbf{u}_{GTG_i}$
- ④ **Both obstacle and other robot sensed**:
$$\mathbf{v}_{d_i} = \mathbf{u}_{OA_i} + \mathcal{N}_{1_i} \cdot (\mathbf{u}_{RA_i} + \mathcal{N}_{2_i} \cdot \mathbf{u}_{GTG_i})$$

References

- Gianluca Antonelli, Filippo Arrichiello, Stefano Chiaverini, The Null-Space-Based Behavioral Control for Mobile Robots, Proceedings 2005 IEEE International Symposium on Computational Intelligence in Robotics and Automation June 2730, 2005, Espoo, Finland.
- Bishop, B. E. (2003). On the use of redundant manipulator techniques for control of platoons of cooperating robotic vehicles. IEEE Transactions on Systems, Man and Cybernetics, 33(5), 608-615.
- Multiagent Simulation and the MASON Library, Sean Luke, Department of Computer Science, George Mason University.
- Alessandro Marino, A Null-Space-based Behavioral Approach to Multi-Robot Patrolling, Ph.D. Thesis, Università degli Studi della Basilicata.
- Chiaverini, S. (1997). Singularity-robust task-priority redundancy resolution for real-time kinematic control of robot manipulators. IEEE Transactions on Robotics and Automation, 13(3), 398-410.
- Gianluca Antonelli, Filippo Arrichiello, Stefano Chiaverini, Flocking for multi-robot systems via the Null-Space-based Behavioral control, Swarm Intell (2010) 4: 37-56.
- Nakamura, Y., Hanafusa, H., Yoshikawa, T. (1987). Task-priority based redundancy control of robot manipulators. The International Journal of Robotics Research, 6(2), 3-15.