

# Rajalakshmi Engineering College

Name: Ganesh Raghav C  
Email: 240701138@rajalakshmi.edu.in  
Roll no:  
Phone: 6382988302  
Branch: REC  
Department: CSE - Section 10  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 6\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Arun wants to calculate the age gap between the grandfather and the son and determine the father's age after 5 years.

Your task is to assist him in developing a program using three classes: GrandFather, Father, and Son, where the GrandFather stores the grandfather's age, the Father extends GrandFather to include the father's age and calculates his age after 5 years, and Son extends Father to include the son's age and calculate the age difference between the grandfather and the son.

##### ***Input Format***

The input consists of three integers representing the ages of the grandfather, father, and son, one per line.

### ***Output Format***

The first line of output prints "Grandfather and son's age gap:" followed by an integer representing the age gap between the grandfather and the son, ending with "years".

The second line prints "Father's Age:" followed by an integer representing the father's age after 5 years, ending with "years".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 50

30

3

Output: Grandfather and son's age gap: 47 years

Father's Age: 35 years

### ***Answer***

```
import java.util.Scanner;

// You are using Java
class Son{
    int a,b,c;
    void setGrandfatherAge(int a){
        this.a=a;
    }
    void setFatherAge(int b){
        this.b=b;
    }
    void setSonAge(int c){
        this.c=c;
    }
    int calculateGrandfatherSonAgeDifference(){
        return a-c;
    }
    int calculateFatherAgeAfter5Years(){
        return b+5;
    }
}
```

```

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        Son son = new Son();

        int grandfatherAge = scanner.nextInt();
        son.setGrandfatherAge(grandfatherAge);

        int fatherAge = scanner.nextInt();
        son.setFatherAge(fatherAge);

        int sonAge = scanner.nextInt();
        son.setSonAge(sonAge);

        System.out.println("Grandfather and son's age gap: "+
            son.calculateGrandfatherSonAgeDifference() + " years");

        int fatherAgeAfter5Years = son.calculateFatherAgeAfter5Years();
        System.out.println("Father's Age: " + fatherAgeAfter5Years + " years");
    }
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Teena's retail store has implemented a Loyalty Points System to reward customers based on their spending. The program calculates and displays the loyalty points based on whether the customer is a regular or a premium customer.

For regular customers (class Customer), the loyalty points are calculated as:

Loyalty points = amount spent / 10

For premium customers (class PremiumCustomer, which inherits from Customer), the loyalty points are calculated as:

Loyalty points = 2 \* (amount spent / 10)

The program should use method overriding for premium customers to

calculate their loyalty points. The method that needs to be overridden is calculateLoyaltyPoints in the Customer class.

### ***Input Format***

The first line of input consists of an integer representing the amount spent by the customer.

The second line consists of a string representing the premium customer status:

- "yes" if the customer is a premium customer.
- "no" if the customer is not a premium customer.

### ***Output Format***

The output should display the loyalty points earned based on the amount spent and the customer type.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 50

yes

Output: 10

### ***Answer***

```
import java.util.Scanner;

// You are using Java
class Customer {
    int calculateLoyaltyPoints(int r){
        return r/10;
    }
}

class PremiumCustomer extends Customer {
    int calculateLoyaltyPoints(int r){
        return 2*(r/10);
    }
}
```

```

public class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        int amountSpent = scanner.nextInt();

        String isPremium = scanner.next().toLowerCase();

        Customer customer;

        if (isPremium.equals("yes")) {
            customer = new PremiumCustomer();
        } else {
            customer = new Customer();
        }

        int loyaltyPoints = customer.calculateLoyaltyPoints(amountSpent);

        System.out.println(loyaltyPoints);
    }
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Bob has been tasked with creating a program using CircleUtils class to calculate and display the circumference and area of the circle.

The program should allow Bob to input the radius of a circle as both an integer and a double and compute both the circumference and area of the circle using separate overloaded methods:

calculateCircumference- To calculate the circumference using the formula  $2 * 3.14 * radius$   
 calculateArea- To calculate the area  $3.14 * radius * radius$

Write a program to help Bob.

#### ***Input Format***

The first line of input consists of an integer m, representing the radius of the circle as a whole number.

The second line consists of a double value  $n$ , representing the radius of the circle as a decimal number.

### ***Output Format***

The first line of output displays two space-separated double values, rounded to two decimal places, representing the circumference of the circle with the integer radius and the double radius, respectively.

The second line displays two space-separated double values, rounded to two decimal places, representing the area of the circle with the integer radius and the double radius, respectively.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5

3.50

Output: 31.40 21.98

78.50 38.47

### ***Answer***

```
import java.util.Scanner;
```

```
// You are using Java
```

```
import java.util.*;
```

```
class CircleUtils {
```

```
    public double calculateCircumference(int radius) {
```

```
        return 2 * 3.14 * radius;
```

```
    }
```

```
    public double calculateCircumference(double radius) {
```

```
        return 2 * 3.14 * radius;
```

```
    }
```

```
    public double calculateArea(int radius) {
```

```
        return 3.14 * radius * radius;
```

```
    }
```

```

    public double calculateArea(double radius) {
        return 3.14 * radius * radius;
    }
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);

        int radiusInt = scanner.nextInt();
        double radiusDouble = scanner.nextDouble();

        CircleUtils circleUtils = new CircleUtils();

        double circumferenceInt = circleUtils.calculateCircumference(radiusInt);
        double circumferenceDouble =
circleUtils.calculateCircumference(radiusDouble);
        double areaInt = circleUtils.calculateArea(radiusInt);
        double areaDouble = circleUtils.calculateArea(radiusDouble);

        System.out.format("%.2f %.2f\n", circumferenceInt, circumferenceDouble);
        System.out.format("%.2f %.2f", areaInt, areaDouble);

        scanner.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Mary is managing a business and wants to analyze its profitability. She operates both a regular business model and a seasonal business model. To assess profitability, she uses a program that calculates and compares the profit margins for both models based on revenue and cost.

The program defines:

BusinessUtility class with a method calculateMargin(double revenue, double cost). SeasonalBusinessUtility (inherits from BusinessUtility) and

overrides `calculateMargin(double revenue, double cost)`, adding a seasonal adjustment of 10% to the base margin. `ProfitabilityChecker` class with a method `checkProfitability(double regularMargin)`, which prints "Business is profitable." if the regular margin is 10% or more, otherwise prints "Business is not profitable.".

Mary inputs revenue and cost, and the program compute and display the regular and seasonal margins using:

$$\text{Margin} = ((\text{Revenue} - \text{Cost}) / \text{Revenue}) \times 100$$

$$\text{Seasonal Margin} = \text{Margin} + 10$$

### ***Input Format***

The first line of input consists of a double value *r*, representing the revenue.

The second line consists of a double value *c*, representing the cost.

### ***Output Format***

The first line prints a double value, representing the regular profit margin, rounded to two decimal places, in the format: "Regular Margin: X. XX%", where X.XX denotes the calculated regular margin.

The second line prints a double value, representing the seasonal profit margin, rounded to two decimal places, in the format: "Seasonal Margin: X. XX%", where X.XX denotes the calculated seasonal margin.

The third line prints a string, indicating whether the business is profitable or not profitable, based on the regular margin.

If the regular margin is less than 10, print "Business is not profitable.". If it is 10 or greater, print "Business is profitable."

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 1000.0  
800.0



Output: Regular Margin: 20.00%  
Seasonal Margin: 30.00%  
Business is profitable.

### **Answer**

```
import java.util.Scanner;

// You are using Java
import java.util.*;

class BusinessUtility {
    public double calculateMargin(double revenue, double cost) {
        return ((revenue - cost) / revenue) * 100;
    }
}

class SeasonalBusinessUtility extends BusinessUtility {
    @Override
    public double calculateMargin(double revenue, double cost) {
        double margin = super.calculateMargin(revenue, cost);
        return margin + 10;
    }
}

class ProfitabilityChecker {
    public void checkProfitability(double regularMargin) {
        if (regularMargin >= 10)
            System.out.println("Business is profitable.");
        else
            System.out.println("Business is not profitable.");
    }
}

class Main {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        double revenue = scanner.nextDouble();
        double cost = scanner.nextDouble();
        BusinessUtility business = new BusinessUtility();
        SeasonalBusinessUtility seasonalBusiness = new
SeasonalBusinessUtility();
        double regularMargin = business.calculateMargin(revenue, cost);
```

```
        double seasonalMargin = seasonalBusiness.calculateMargin(revenue,
cost);

        System.out.printf("Regular Margin: %.2f%%\n", regularMargin);
        System.out.printf("Seasonal Margin: %.2f%%\n", seasonalMargin);

        ProfitabilityChecker checker = new ProfitabilityChecker();
        checker.checkProfitability(regularMargin);
        scanner.close();
    }
}
```

**Status :** Correct

**Marks :** 10/10