				LI	GHT F	IXTURE	SCH	EDUL	.E			
MARK	SYMBOL	DESCRIPTION	DIFFUSERV	NO.	CRI	TYPE	FIXTURE VOLTAGE	TOTAL WATTS	FINISH	MOUNTING	MANUFACTURER- MODEL NO.	REMARKS
L-1 L-28	GEE INTERNOTI DEGIGN DOCUMENTS	GCE INTERIOR DEBIGN DOCUMENTS	-	- NO.	- CHI		-	-	-	-	-	CCC INTERIOR DEGIC DOCUMENTS
L-29	<u>Q</u>	UNIT ENTRY LIGHT	-	-	-	-	-	-	-	-	-	SEE INTERIOR DESIG DOCUMENTS
L 90	0	GENERAL RECESSED CAN LIGHTING	MATTE DIFFUSED	1	3000K	INTEGRAL LED	MVOLT	13	WHITE	RECESSED	LITHONIA LDN4-AL01-90K- L04-WR-LD-MVO LT-LIGZ-90CRI	SEE INTERIOR DESIG DOCUMENTS
L-30E	•	GENERAL HECESSED CAN LIGHTING	MATTE DIFFUSED	1	3000K	INTEGRAL LED	MVOLT	13	WHITE	RECESSED	LITHONIA - LIDN4-ALD1-3UK- LIJ4-WH-LIJ-MNO LT-UGZ-E10WCP -90C/N	PROVIDE WHERE INDICATED
L-31	Ø	GENERAL RECESSED CAN LIGHTING	MATTE DIFFUSED	1	3000K	INTEGRAL LED	MVOLT	13	BLACK	RECESSED	LITHONIA - LDN4-AL01-30K- LD4-BR-LD-MWOL 1-UGZ-90UHI	SEE INTERIOR DESIG DOCUMENTS
L-31E	•	GENERAL RECESSED CAN UGHTING	MATTE DIFFUSED	1	3000K	INTEGRAL LED	MVOLT	13	BLACK	RECESSED	LITHONIA - LDN4-AL01-30K- L04-BR-LD-MVOL T-UGZ-E10WCP- 90CRI	PROVIDE WHERE INDICATED
L-32	SEE INTERIOR DESIGN DOCUMENTS	PIN LICHT	PINHOLE W/SHIELD	1	3000K	R20 LED	120	8	WHITE	NECESED	JUNO - IC1 SERIES CAN WITH 13 WH TRIM	SEE INTERIOR DESIG DOCUMENTS
L-33 - L-39	RESERVED FOR FUTURE USE	-	-	-	-	-	-	-	-	-	-	=
L-40	0	ELEVATOR THRESHOLD LIGHT	FROSTED GLASS	1	3000K	INTEGRAL LED	120	18.5	WHITE	FLUSH	SATCO - BLINK 9' ROUND S20236	TO PROVIDE 16 FC A 9 MOUNTING HEIGH
L-41	П	BUILDING ENTRY SCUNCE	CLEAR GLASS PHISMATIC	1	3000K	INTEGRAL LED	120	20	TBD	WALL	TBD	WALL LIGHT - WET HATED
L-42		GENERAL SERVICE/ MECHANICAL ROOM LIGHTING	WHITE FROSTED POLYCAR- BONATE	1	4000K	LED PANEL	120	54	WHITE	FLUSH	UTHONIA - FMI 4W 4R 5000LM 840 TD	RASIS OF DESIGN - DAMP RATED
L-43		SI AIHWELL LIGHTING	UNEAH FAGETED AGRYLIC	1	SUUUK	IN IEGHAL LED	MVULI	39.0	WHILE	WALL MOUNT	LIHUNIA - WL4-40L-SLD- LP630-MSD7- DIM56	BASIS OF DESIGN - DAMP RATED
L-44	•	GENERAL LIGHTING LED PUCK	DIFFUSED POLY- STYRENE	1	3000K	INTEGRAL LED	120	13.5	WHITE	FLUSH	SATCO - BLINK 7" ROUND S21543	PROVIDE \$29346 SPACER, WHERE REQUIRED
L-45	•	LED PUCK WITH BATTERY BACKUP ACCESSORY	POLY- STYRENE	1	9000K	INTEGRAL LED	120	19.5	WHITE	FLUSH	SATCO - BUNK 7º ROUND S21543	PROVIDE \$20044 BATTERY BACKUP MODULE
L-46	<b>+</b>	GARAGE GENERAL LIGHTING LEU PLICK	DIFFUSED POLY- STYHENE	1	3000K	INTEGRAL LED	120	13.5	WHITE	FLUSH	SATCO - BLINK 7" HOUND S21543	PHOVIDE S28946 SPACEH, WHEHE HEQUINED
1.47		GARAGE POLE LIGHT - DOURLE HEAD - WET RATED	CLEAR	6 PER HEAD	4000K	INTEGRAL I FD PANEL	917	78 ¥ 2 = 156	BRONZE	10'4' SQUARE SIFFI POST	2 X RAR . AI FDXT78N/ PCS2	GARAGE ROOF POL LICHTS - PROVIDE S HEADS ON 10' 4" SQUARE STEEL POS
L-48		PAHKING GARAGE LUMINAIRE - WET BATED	MULYGAH- BONATE	1	JOUUK	IN LIGHAL LED	120-277	52	-	PLUSH (PROVIDE STAND-OFFS AS REQUIRED)	LITHUNIA - GSVT-L46-0000L M-WVOLT-33K-60 CRI-3BOR10	PARKING GARAGE LIGHTING

MARK	SYMBOL	DESCRIPTION	DIFFUSER/		LAMP	FIXTURE			FINISH	MOUNTING	MANUFACTURER-	DEMARKS
			REFLECTOR	NO.	CRI	TYPE	VOLTAGE	WATTS	PINISH	MOUNTING	MODEL NO.	HEMPHAS
U-L-1	ф·	DECONATIVE PENDANT	-	-	3000K	-	120	-	GEE INTERIOR DESIGN DOCUMENTS	DESIGN DESIGN DOCUMENTS	DESIGN DESIGN DOCUMENTS	DOCUMENTS
U-L-2	-	LIGHTED MIRROR	-	-	3000K	-	120	-	SEE INTERIOR DESIGN DOCUMENTS	SEE INTERIOR DESIGN DOCUMENTS	SEE INTERIOR DESIGN DOCUMENTS	SEE INTERIOR DE DOCUMENTS
UL3		LED TAPE LIGHT	POLYPRO PYLENE	1	3000K	INTEGRAL LED	120	2.7 PER FT.	ECONOMY EXTRUSION W/ LENS - FF1-AAFR-1M	UNDERCABINET	TRULUX STL-WW-100	UNDERCABINE LIGHTING; PROV ALL NECESSAL ACCESSORIE
U-L-4		CELING FAN W/ INTEGRAL LIGHT KIT	FROSTED	1	3000K	INTEGRAL	120	15	BLACK	FLUSH - DOWNROD AS HEQUINED	TBD	CELLING FAN V INTEGRAL LIGHT PHOVIDE SING GANG WALL CON
ULS	¢	LED PUCK	FROSTED	1	3000K	INTEGRAL I FIT	120	15	WHITE	FLUSH	TBD	UNIT GENERA LIGHTING
U-L-6	<b></b>	SHOWER/ PATRO/BALCONY LED PUCK	PHUSTED	1	3000K	INTEGRAL LED	120	15	WHILE	HLUSH	IRD	DAMP-HATEL

MARK	SYMBOL.	DESCRIPTION	DIFFUSER/ REFLECTOR		LA	MP	FIXTURE TOTAL	TOTAL	FINIOH	MOUNTING	MANUFACTURER- MODEL NO.	REMARKS
				NO.	CRI	TYPE	VOLTAGE	WATTS				
GL 1	=-	DAMP RATED EXIT SIGN - UNIVERSAL SINGLE OR DOUBLE SIDED	N/A			LED	120 277	6	CLEAR OR MIRROR W/ GREEN I FTTFRS	UNIVERSAL TOP OR END OR BACK SURFACE	LITHONIA LIGHTING - EDG-1-G-EL OR EDG-2-GMR-EL	VERIFY FINISH/COLI WITH INTERIORS/ ARCHITECT/ OWNE
EL-E	_	WET-HATED EXIT SIGN - UNIVERSAL SINGLE OR DOUBLE SIDED	N/A	-	-	LED	120-277	5	WHITE W/ GREEN LETTERS	UNIVERGAL - TOP OR END OR BACK SURFACE	LITHONIA LIGHTING - WLTE W 1 G EL OR WLTE-W-2-G-EL	VERIFY FINISH VOOL WITH INTERIORS/ ARCHITECT/ OWNE
EL-3	~-	EMERGENCY LIGHT - DAMP DATED	N/A	2		LED	120-277	7	WHITE	SURFACE	LITHONIA LIGHTING - ELM4L	VERIFY FINISH/COLI WITH INTERIORS/ AND INTEGT/ OWNE
EL-4	•	EMERGENCY LIGHT - WET RATED	N/A	2	-	LED	120-277	7	WHITE	SURFACE	LITHONIA LIGHTING - WLTLI GY MR	VERIFY FINISH/COLO WITH INTERIORS/ ARCHITECT/ OWNE
EL-5	_	EMERGENCY LIGHT - WET RATED	N/A	2		LED	120-277	6	BRONZE	SURFACE (WALL)	LITHONIA LIGHTING - AFO-DB-MVOLT- N-SD	VERIFY FINISH/COLO WITH INTERIORS/ ARCHITECT/ OWNE

SEE INTERIOR DESIGN DOCUMENTS AND LANDSCAPE ARCHITECT'S DOCUMENTS FOR ADDITIONAL LIGHT FIXTURES.