

Sensor Signal Processing

Prof. Dr.-Ing. Andreas König
Lehrstuhl Integrierte Sensorsysteme



FB Elektrotechnik und Informationstechnik
Technische Universität Kaiserslautern

Fall Semester 2005



Course Contents

1. Introduction
2. Signal Processing and Analysis
3. Feature Computation
4. Cluster Analysis
5. Dimensionality Reduction Techniques
6. Data Visualization & Analysis
7. Classification Techniques
8. Sensor Fusion
9. Systematic Design of Sensor Systems
10. Outlook


7. Classification Techniques

- 7.1 Introduction
- 7.2 Statistical parametric methods
- 7.3 Statistical nonparametric methods
- 7.4 Neural networks
- 7.5 Rule-based approaches
- 7.6 Evaluation Techniques
- 7.7 Summary


Motivation

Sensor Signal Processing Classification Techniques


- After signal processing, feature computation, and condensing or compression of the data the data is subject to **classification**
- In classification **unknown data** is **affiliated to classes** according to previous construction of a **classifier**



Data




Class affiliation



- For **known class affiliation** (ground truth), **classifier performance** can be **assessed** !

Motivation

- Classification can be understood as a special case of general function approximation
- Function values are limited to discrete numbers (class numbers)



- Commonly, integer values of class labels are represented as 1-of-L-coding to avoid spurious neighborhood relations in processing

Motivation

- Class labels formally are denoted as

$$\begin{aligned} \Omega &= \{\omega_1, \omega_2, \dots, \omega_L\} \\ &\quad \Downarrow \quad \Downarrow \quad \Downarrow \\ l &\in \{1, 2, \dots, L\} \end{aligned} \quad (7.2)$$

- Alternatively, the target vectors \mathbf{y} , based on 1-of-L-coding, are employed


$$\begin{aligned} \Omega &= \{\omega_1, \omega_2, \dots, \omega_L\} \\ &\quad \Downarrow \quad \Downarrow \quad \Downarrow \\ l &\in \left\{ \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ \vdots & \vdots & \dots \\ 0 & 0 & 1 \end{bmatrix} \right\} \end{aligned} \quad (7.3)$$

- This representation is favorable for unbiased cost function computation

Sensor Signal Processing Classification Techniques

Motivation

- The construction of a classifier will be regarded in particular for the case of the common **machine learning** paradigm learning from examples




© Andreas König Slide7-7

Sensor Signal Processing Classification Techniques

Motivation

- System to be trained by presentation of examples, i.e. pairs of measurement data and affiliated meaning



- The system is adapted until it gives the correct answer (in tolerable limits)

© Andreas König Slide7-8

Motivation

- Statistical motivation according to Bayes-theory:

$$P(x, \omega) = P(x | \omega) \cdot P(\omega) = P(\omega | x) \cdot P(x) \quad (7.4)$$

Marginal distribution
Class specific probability
A priori probability
A posteriori probability
Pattern probability


- Class specific, a priori, and pattern probabilities are assumed to be known
- Class affiliation of new data requires the computation (estimation) of the a posteriori probability for each class and determine the maximum:

$$P(\omega_c | x) = \max_{j=0}^N \left(P(\omega_j | x) = \frac{P(x | \omega_j) \cdot P(\omega_j)}{P(x)} \right) \quad (7.5)$$

- Index c implies the class index of the class with the highest a posteriori value, i.e. the most probable affiliation of the pattern

Motivation


- A classification system or a classifier can be defined by the following structure:



Sensor Signal Processing Classification Techniques

Motivation

- Unfortunately, the class specific, a priori, and pattern probabilities are commonly unknown and have to be estimated from examples for classification




© Andreas König Slide7-11

Sensor Signal Processing Classification Techniques

Motivation

- Numerous options to define estimation functions
- Taxonomy of important classification methods:





© Andreas König Slide7-12

Parametric Methods

- The Bayes-Normal distribution Classifier (BAC) assumes Gaussian distributions for the classes
- The decision function are determined as



$$\hat{d}_i(\vec{x}) = \frac{P(\omega_i)}{\sqrt{(2\pi)^N \det K_i}} e^{-\frac{1}{2}(\vec{x} - \vec{\mu}_i)^T K_i^{-1} (\vec{x} - \vec{\mu}_i)} \quad (7.6)$$



© Andreas König Slide7-13

Parametric Methods

- The intersections of two class region probability distribution functions (pdf) define the class borders as lines of equiprobability



- Parabolic class boundaries result in the two-dimensional example
- In the case of more than two classes, class regions are defined by intersections of resulting parabolic functions

© Andreas König Slide7-14

Parametric Methods


Sensor Signal Processing Classification Techniques

- Assuming equal a priori values for all classes return the Maximum-Likelihood-Classifier (MLC):

$$\hat{d}_i(\vec{x}) = -\frac{1}{2} \ln(\det K_i) - \frac{1}{2} (\vec{x} - \vec{\mu}_i)^T K_i^{-1} (\vec{x} - \vec{\mu}_i) \quad (7.7)$$

- Assuming further equal covariance for all classes return the Mahalanobis-Classifer (MAC):

$$\hat{d}_i(\vec{x}) = -\frac{1}{2} (\vec{x} - \vec{\mu}_i)^T K^{-1} (\vec{x} - \vec{\mu}_i) \quad (7.8)$$




© Andreas König Slide7-15

Parametric Methods

Sensor Signal Processing Classification Techniques

- Assuming further the covariance matrix to be the identity matrix return the **Centroid** or **Euclidean Distance Classifier** (EAC):

$$\hat{d}_i(\vec{x}) = \|\vec{x} - \vec{\mu}_i\|^2 = \sum_{j=0}^{N-1} (x_j - \mu_j)^2 \quad (7.9)$$



- Simplifying the metric returns the **City-Block-Classifer** (CBC):

$$\hat{d}_i(\vec{x}) = \sum_{j=0}^{N-1} |x_j - \mu_j| \quad (7.10)$$

© Andreas König Slide7-16

Nonparametric Methods


- Parametric methods condense all the sample set information into few model parameters and perform a global pdf estimation
- In contrast, nonparametric methods perform a local pdf estimation:

$$p(\vec{x}) = \frac{k(\vec{x})}{N \cdot \nu} \quad (7.11)$$

- Assumption of either fixed volume ν or fixed number of patterns k
- The **Parzen-window classifier** bases on the first alternative

$$p_{Parzen}(\vec{x}) = \frac{1}{N \cdot h_N^M} \sum_{i=1}^N \kappa\left(\frac{\vec{x} - \vec{x}_i}{h_N}\right) \quad (7.12)$$


- In the simplest case the kernels used in (7.12) could be Gaussian functions:



© Andreas König Slide7-17

Nonparametric Methods

- The kernel width must be adapted to data density
- k-nearest-neighbor classifiers (kNN) under control of the **parameter k** estimate the density and determine the class affiliation of a new pattern by evaluating the k-nearest-neighbors




$$p_{kNN}(\vec{x}) = \frac{k-1}{N \cdot \nu(\vec{x})} \quad (7.13)$$

- kNN training means storage of all patterns !
- Two basic variations: **voting** and volumetric kNN


© Andreas König Slide7-18

- Sketch of class boundary for k=1 **1NN-classification**



- Class-specific Voronoi tessellation defines the class borders in this case

- Edited-Nearest-Neighbor-classification (ENN, Devijver and Kittler, 1980)
- For k=1 resubstitution is guaranteed, however generalization can be affected by this over-specialization in following situations:



- Automatic determination of the outliers in the data set:

$$G_{ENN} = \frac{kNN_{\omega_j = \omega_j}}{kNN_{\omega_j \neq \omega_j}} \quad (7.14)$$

- k neighbors determined and investigated for class affiliation
- **Elimination** if same to different class affiliations are below threshold:


$$G_{ENN} < \Theta \quad (7.15)$$

- Edited sample set is **reduced**, **resubstitution no longer assured**, **generalization** generally **improved** by outlier elimination (rf. q₀)

Nonparametric Methods

Sensor Signal Processing Classification Techniques

- Condensed-Nearest-Neighbor-classification (CoNN, Hart, 1968)
- The complete storage in kNN requires large memory & long computation
- Reduction by limiting storage to vectors defining class boundary



Pseudo-Code of CoNN algorithm:

1. Initially empty classifier
2. Get first (next) pattern x_i
3. 1-NN-classify sample set pattern
If correct_classification goto 4
Else Insert pattern x_i ; goto 2
4. If all_patterns_corr_class
break;
Else goto 2


- Algorithm reduces effort but depends on sample set presentation order and leaves redundancy in the CoNN; recall by 1-NN mandatory !

© Andreas König Slide7-21

Nonparametric Methods

Sensor Signal Processing Classification Techniques

- Condensed-Nearest-Neighbor-classification (CoNN, Hart, 1968)
- Step-wise demonstration:



Pseudo-Code of CoNN algorithm:

1. Initially empty classifier
2. Get first (next) pattern x_i
3. 1-NN-classify sample set pattern
If correct_classification goto 4
Else Insert pattern x_i ; goto 2
4. If all_patterns_corr_class
break;
Else goto 2


- All class 3 patterns in the following will be classified correctly

© Andreas König Slide7-22

Nonparametric Methods

Sensor Signal Processing Classification Techniques

- Condensed-Nearest-Neighbor-classification (CoNN, Hart, 1968)
- Sketch of potential final solution:



Pseudo-Code of CoNN algorithm:

1. Initially empty classifier
2. Get first (next) pattern x_i
3. 1-NN-classify sample set
If correct_classification goto 4
Else Insert pattern x_i ; goto 2
4. If all_patterns_corr_class
break;
Else goto 2


- Removal of existing redundancy by following step

© Andreas König Slide7-23

Nonparametric Methods

Sensor Signal Processing Classification Techniques

- Reduced-Nearest-Neighbor-classification (RNN, Gates, 1972)
- Addition of a removal step to clean reference vector set from redundant instances, i.e., vectors not required for **perfect resubstitution**



Pseudo-Code of RNN algorithm:

1. Run CoNN algorithm
2. Tentatively remove first (next) reference vector r_i
3. 1-NN-classify all sample set patterns
If correct_classification permanently remove r_i ; goto 4
Else restore r_i ; goto 4
4. If last_ref_vec break;
Else goto 2



- CoNN **redundancy eliminated**, strong dependence on presentation order
- Alternatively, CoNN and RNN steps can be interleaved in a modified, potentially faster algorithm, however, limit cycles can occur (rf. q_s)

© Andreas König Slide7-24

Nonparametric Methods

Sensor Signal Processing Classification Techniques

- QuickCog example for Iris data:



- With the given settings, 10 reference vectors are chosen ($q_s=0.906666$)

© Andreas König Slide7-25

Nonparametric Methods

Sensor Signal Processing Classification Techniques

- A traditional method in OCR used for nonparametric classification, based on function approximation approach, is the **polynomial classifier**

$$\hat{d}_i(\vec{x}) = a_{0,i} + a_{1,i} \cdot x_1 + a_{2,i} \cdot x_2 + \dots + a_{N,i} \cdot x_N + \quad (7.16)$$

$$a_{N+1,i} \cdot x_1^2 + a_{N+2,i} \cdot x_1 \cdot x_2 + \dots$$

- Expressing (7.14) by new coordinates results in

$$\vec{v} = (v_1, v_2, \dots, v_p) = (1, x_1, x_2, \dots, x_N, x_1^2, x_1 \cdot x_2, \dots) \quad (7.17)$$

$$\vec{\tilde{d}} = A^T \cdot \vec{v}(\vec{x}) \quad (7.18)$$

- LMS-optimization to determine polynomial coefficients of A
- Similarity to dot product neuron with **nonlinear synapses** !
- Excessive growth of variables in (7.15) for increasing order G of polynomial:



$$p = \binom{N+G}{G} = \frac{(N+G)!}{N! \cdot G!} \quad (7.19)$$

- Data compression/term selection, G 1-3 (Schürmann, Kressel)

© Andreas König Slide7-26

Neural Networks

- Simple dot product neurons can serve as linear classifiers




- A single neuron can separate a linear separable problem with a separating line (plane, hyperplane)
- Logical combinations of a layer allow tackling non-linear problems !

© Andreas König Slide7-27

Neural Networks

- A **multilayer perceptron** with **backpropagation algorithm** serves as a classifier for non-linear separable problems:




- Training bases on the approach introduced in section 5
- Choice of hidden layer size and learning parameters can be difficult
- **Resubstitution** not guaranteed, **generalization** can be surprising

© Andreas König Slide7-28

Neural Networks

Sensor Signal Processing Classification Techniques

- A learning vector quantization network (LVQ) employs winner-take-all mechanism that leaves but the strongest response active:




- Adjusting of a fixed number, commonly randomly or by SOM training initialized vectors
- Recall via 1-NN classification

© Andreas König Slide7-29

Neural Networks

Sensor Signal Processing Classification Techniques

- Basic LVQ-1 learning method [Kohonen 1989]
- Iterative presentation of training data and WTA-computation finding $w_c(t)$




- Dead reference vectors w_i can occur, sufficient no. per class not assured
- Different initialization, e.g., RNN, could be suitable
- Basic methods extended by improved versions LVQ2/2.1 & LVQ3

© Andreas König Slide7-30

Neural Networks

- A special class of ANN consists of a **kernel layer** and an **output layer**




- The Restricted-Coulomb-Energy network (RCE) employs step functions in the kernel layer and or-gate or summation of activated kernel neurons
- The network is generated from scratch by (patented) dynamic training

© Andreas König Slide7-31

Neural Networks

- **RCE-training** is part of the **Nestor-Learning-System (NLS)**
- Dynamic placement and scaling of hyperspheres:



Pseudo-Code of RCE algorithm:


- Initially empty classifier
- Get first (next) pattern x_i
- RCE-classify pattern
 - If *correct_classification* goto 4
 - Else If *unknown* Insert x_i ; goto 2
 - Else If *ambiguous* reduce radii of r_i with $\omega_i \neq \omega_j$; goto 2
 - Else (*misclassification*) reduce radii of r_i with $\omega_i \neq \omega_j$; Insert x_i ; goto 2
- If all_patterns_corr_class break; Else goto 2

- Result strongly depends on presentation order (Pro-RCE extension)
- Insertion only does not remove redundant neurons
- Classification resolving by voting or kernel based pdf estimation (PRCE)
- Additional attributes **unknown** and **uncertain/ambiguous**

© Andreas König Slide7-32

Neural Networks

- The Radial-Basis-Function network (RBF) employs (commonly **Gaussian**) **kernel functions** in the kernel layer and **dot product output layer neurons**




- RBF-networks are also **universal function approximators** !
- Number of kernels fixed by choice and random initialization or SOM

© Andreas König Slide7-33

Neural Networks

- **RBF-training** on a fixed hidden layer might not be efficient
- Dynamic training algorithms for function approximation and classification
- The first one is Platt's Resource-Allocation-Network RAN



Pseudo-Code of **principle RAN** algorithm:

- Initially empty kernel layer
- Get first (next) pattern x_i
- Compute output value
If $Error > \varepsilon$ & $d > \delta$
 Insert x_i as new kernel;
 $\sigma_j = \min(\kappa \bullet \delta, \kappa \bullet d)$
 Adapt output layer weights ... ;
- If $sum_err < \varepsilon$ break;
 Else $\delta = \delta \bullet e^{-1/\tau}$; goto 2


- Fast (evolving) training, insertion only does not remove redundant neurons
- Classification by determination of maximum pdf; background applicable !
- Training for all RBF-parameters can be achieved by gradient descent !
- Smooth and well-generalizing behavior of RBF-networks

© Andreas König Slide7-34

Neural Networks

Sensor Signal Processing Classification Techniques

- Probabilistic-Neural-Networks of Specht resemble Parzen-Window:




- Each training data vector is stored as Gaussian kernel with **fixed global σ**
- According to class labels, kernel are wired to pdf summation nodes
- Explicit cost or a priori weighting can be employed before pdf max-of-L

© Andreas König Slide7-35

Rule-based Approaches

Sensor Signal Processing Classification Techniques

- Inherently, **rules can be extracted/employed** in classification problems
- **Decision trees** are one common example for crisp techniques:



- Decision trees construction by dedicated **machine learning algorithm** (Idx,y)
- **Knowledge application/extraction**; hybrid combinations feasible
- Fuzzy and neuro-fuzzy approaches extend the classification approach

© Andreas König Slide7-36


Evaluation Techniques

Sensor Signal Processing Classification Techniques

- The performance of a classification system as well as of a classifier is assessed by the **classification rate**
- Based on the available *ground truth* of a test data set, the number of correctly classified patterns vs. the total pattern number is computed and given in %
- More detail about confusion between classes is given by the **confusion matrix** (Mechatronic example):

Confusion matrix

```
Class1 (50) : 0 (R) 100 0 0 0
Class2 (100): 0 (R) 0 100 0 0
Class3 (150): 0 (R) 0 4.660 95.330 0
Class4 (25) : 0 (R) 0 0 8 92
Classification rate: 97.231 %
```




- The confusion matrix indicates the additional option of **rejection**

© Andreas König Slide7-37

Evaluation Techniques

Sensor Signal Processing Classification Techniques

- Several situations can occur, where the decision of the classifier could be doubtful (pattern close to the decision boundary or **far from training data**)



- Rejection criterion:

$$\text{MAX: } \hat{d}_{\max} < \Theta \quad (7.11)$$

$$\text{DIF: } (\hat{d}_{\max} - \hat{d}_{2\text{nd max}}) < \Theta \quad (7.12)$$

$$\text{RAD: } \begin{aligned} D_{NN} &> D_{\max} \\ R_{NN} &> R_{\max} \end{aligned} \quad (7.13)$$


- Guessing can be avoided by rejection (Decision can always be enforced)
- Contradictions can be resolved on higher level (**fusion aspects !**)

© Andreas König Slide7-38

Evaluation Techniques

Sensor Signal Processing Classification Techniques

- The location and identification of misclassifications in feature space and in the example database, e.g., corresponding raw image, is salient
- Feature space **visualization techniques** allow just this:



- Misclassified patterns can rapidly be investigated for cause elimination

© Andreas König Slide7-39

Summary

Sensor Signal Processing Classification Techniques

- The chapter gave a **survey** of the **concepts** and common **conventional** as well as **neural classification methods**
- Recently, powerful techniques, such as the **support vector machines** have extended the available method pool
- In practical **application**, the choice of approach should be governed by the need and complexity of the underlying problem and data
- For a system well optimized in the first stages the **simplest choice** will provide **robustness and good performance**
- For small data sets, **appropriate partitioning in training and test data** is not feasible
- For statistical meaningful evaluation **leave-one-out techniques** (LOO) are commonly applied
- In addition to **rejection threshold**, also the **notion of cost** can be introduced into the design of the discussed classifier models

© Andreas König Slide7-40