

Sensor Signal Processing

Prof. Dr.-Ing. Andreas König
Lehrstuhl Integrierte Sensorsysteme



FB Elektrotechnik und Informationstechnik
Technische Universität Kaiserslautern

Fall Semester 2005



Course Contents

1. Introduction
2. Signal Processing and Analysis
3. Feature Computation
4. Cluster Analysis
5. Dimensionality Reduction Techniques
6. Data Visualization & Analysis
7. Classification Techniques
8. Sensor Fusion
9. Systematic Design of Sensor Systems
10. Outlook


6. Data Visualization & Analysis

- 6.1 Motivation
- 6.2 Interactive visualization
- 6.3 Component planes
- 6.4 Grid modes
- 6.5 Attributes & hierarchical access
- 6.6 Interactive Navigation
- 6.7 Mapping reliability
- 6.8 Tools
- 6.9 Applications
- 6.10 Summary

Motivation

Sensor Signal Processing Data Visualization

- Design decisions at multiple steps of system design require insight into the potentially complex nature of underlying data:



Motivation

- [illegible]

- © Andreas König Slide6-5


Motivation

-
- Table representation
- Feature space visualization
- Violin Database

Sensor Signal Processing Data Visualization

Motivation

- Relation to **general data analysis**:
- Ubiquitousness of the dimensionality reduction problem




© Andreas König Slide6-7

Sensor Signal Processing Data Visualization

Motivation

- Inclusion of additional attribute information




© Andreas König Slide6-8

Motivation

- Finding the Relevant Information – Choice of Approach


Means to determine salient variables v_i that are

- ▶ significant
- ▶ redundant
- ▶ irrelevant
- ▶ correlated



Motivation

- Finding the Relevant Information – Automatic Machine-Centered Approach




Automatic assessment of v_i :

- ▶ Statistical approaches
- ▶ Clustering
- ▶ Rule extraction

Motivation


- Finding the Relevant Information – Interactive Human-Centered Approach



© Andreas König Slide6-11

Interactive Visualization


- Dimensionality reduction and visualization by manual feature selection
- Visualization by multiple (linked) pairwise plots, six for Iris data:
- Sideviews of hypercube
- Views grow with $\frac{M(M-1)}{2}$
- Limited applicability
- Gets intractable for data with $M \gg 1$
- A priori knowledge required
- **Better:** Automatic feature selection or projection, e.g., NLM



© Andreas König Slide6-12

Interactive Visualization


- Applicability of dimensionality reduction methods for visualization:



- A plethora of methods can be observed in the literature & on the tool market
- What motivates the choice of a method (method combination) for application ?

Interactive Visualization


- Taxonomy of Visualization Techniques:



Interactive Visualization

Sensor Signal Processing Data Visualization

- Interactive Data Visualization and Explorative Analysis Architecture




- Visualization standard: Static (2D-) scatter plot
- Advanced Visualization by enhanced user interaction & CAD-functionality

© Andreas König Slide6-15

Component Planes

Sensor Signal Processing Data Visualization


- Generalization from SOM [component planes](#)
- The values of one feature are displayed at the projection points
- Like [Hinton diagrams](#)
- Several planes can be displayed and analysed
- Correlating and salient features can be detected
- Multicomponent plots exploit human texture perception for analysis



© Andreas König Slide6-16

Component Planes

- Extension to Multi-component plot based on radar-plot concept:




- Weight Icons
- Iconified radar plot at each projection point
- Denoted as *Snow-Flakes*

© Andreas König Slide6-17

Grid Modes

- Different grid modes for auxiliary (approximated) boundary information:


- Grid modes complementing the SOM mesh
- Sequence order of data vectors can be displayed
- Voronoi tessellation give exact quantization and 1-NN classification boundaries for 2D-data
- An adequate idea is given for projection of multidimensional data



© Andreas König Slide6-18

Grid Modes

- Detection of **Outliers** and **Identical Vectors** by Visualization
- Outliers and identical vectors are pathological cases for system design
- At high point densities mutual occlusion of points becomes a problem




- Variable-sized fields and colored class-specific VT can alleviate this problem
- Outliers and isolated vectors in different class regions can easily be identified
- Identical vectors are marked by an hexagonal shape
- Stacking by mouse click rotates identical or strongly occluding vectors
- **Fast troubleshooting:** Pathological vectors can be tracked-back in the database

© Andreas König Slide6-19

Attributes & Hierarchical Access

- Attribute Display and Hierarchical Database Access




© Andreas König Slide6-20

Interactive Navigation

Sensor Signal Processing Data Visualization

- Interactive Navigation and Hierarchical Analysis
- The methods described so far alleviate first insight in the data structure
- For very large data sets with considerable local density variations, analysis on a single scale will not be feasible
- Global to local analysis across scales (zoom/pan) offers superior performance:




- Focus of interest can conveniently be shifted across scales by zooming in or out and in the same scale by shifting the navigation window
- Descending down to local detail, mapping quality and errors become an issue

© Andreas König Slide6-21

Interactive Navigation

Sensor Signal Processing Data Visualization

- Different implementation in QuickCog with pop-up navigation window and drag&drop navigation




- Scale is preset from menu entry or interactively by mouse operation

© Andreas König Slide6-22

Mapping Reliability

- Assessment of Mapping Quality and Mapping Errors
- With increasing intrinsic dimension, all mapping methods will introduce mapping errors
- Visualization results may be subject to twists and distortions that can lead to invalid conclusion drawing & corrupt knowledge acquisition
- How can mapping quality be measured and mapping faults be disclosed ?
- **First proposed measure:** Distance preservation E with

$$E = \frac{1}{c} \sum_{j=1}^N \sum_{i=1}^j \frac{(d_{X_{ij}} - d_{Y_{ij}})^2}{d_{X_{ij}}} \quad (6.1)$$



© Andreas König Slide6-23

Mapping Reliability

- **Second proposed measure:** Topology preservation q_m with

$$q_m = \frac{1}{3n * N} \sum_{i=1}^N q_{m_i} \quad (6.2)$$

- Local quality q_{m_i} is computed by determining the n -nearest-neighbors NN_{ji} of the i th pattern ($i \in [1, n], j \in [1, N]$)
- Rank order of the nearest-neighbors in \mathbf{X} and \mathbf{Y} are compared and q_{m_i} values are assigned according to the following simple assignment scheme:

$$\begin{aligned} q_{m_i} &= 3 && \text{if } NN_{ji} \text{ in } \mathbf{X} = NN_{ji} \text{ in } \mathbf{Y} \\ q_{m_i} &= 2 && \text{if } NN_{ji} \text{ in } \mathbf{X} = NN_{jl} \text{ in } \mathbf{Y} \text{ with } l \in [1, n]; j \neq i \\ q_{m_i} &= 1 && \text{if } NN_{ji} \text{ in } \mathbf{X} = NN_{jt} \text{ in } \mathbf{Y} \text{ with } t \in [n, m]; n < m \\ q_{m_i} &= 0 && \text{else} \end{aligned}$$

- The topology preservation measure q_m returns 1.0 for perfect preservation


© Andreas König Slide6-24

Mapping Reliability

- For typical parameter settings $n=4$ and $m=10$ an application example for *Iris*train and *Mech*₁ data is given:

Data set	NLM		Visor	
	q_m	E	q_m	E
<i>Iris</i> train	0.6667	0.0098	0.6711	0.0093
<i>Mech</i> ₁	0.4527	0.0933	0.4207	0.1628


- In addition to the global measures E and q_m , local information for each point in the projection can be computed by local distance preservation E_i and local topology preservation q_{mi}
- These can be superimposed on the mapping:
- Local mapping faults can be disclosed
- $O(N^2)$ complexity of the quality measure !
- Consumes more time than the mapping itself
- **Remedy:** Fast interactive local alternative



© Andreas König Slide6-25

Mapping Reliability

- Validation of mapping quality by **actual local neighborhood display**




- The actual nearest neighbors in **X** are computed for an interactively chosen pattern
- The projection points corresponding to these NN in **Y** are threaded by a red line in the visualization
- This discloses mapping errors at **low computational cost** for valid conclusion drawing and knowledge acquisition
- Similar to q_{mi}
- Compatible with navigation & hierarchical analysis

© Andreas König Slide6-26


Mapping Reliability

- Alternative **ALND** implementations:



- Diminishing linewidth with growing distance from reference point improves the visualization

- Instead of point threading by a polyline, a pairwise connection can be beneficial & more lucid




© Andreas König Slide6-27

Hierarchical Visualization

- None of the presented methods will return in general a satisfying global and local mapping quality
- Three main strategies for improving mapping quality can be observed:

- 1) Hierarchical clustering and mapping of the data
- 2) **Hierarchical mapping & navigation approach:**
- 3) Global to local shift of the mapping stress implemented by a limited or shrinking neighborhood during the mapping computation




© Andreas König Slide6-28


Hierarchical Visualization

Sensor Signal Processing Data Visualization

- Advanced Projection and Visualization Techniques: [Example of Case 2](#)



- Artificial 3D sphere data
- Points distributed only on the sphere shell
- Intrinsically 3D data !
- Mapping error to 2D unavoidable
- Sphere is flattened: ROI contains vectors from front & rear
- Recomputation separates data !



© Andreas König Slide6-29

Hierarchical Visualization

Sensor Signal Processing Data Visualization

- Advanced Projection and Visualization Techniques: [Example of Case 1](#)
- Computational effort & mapping quality can be traded-off in a hierarchical data clustering and mapping approach
- Data is first quantized by SOM, c-means, or other clustering method
- Then, the K centroids of the quantized data are mapped by NLM
- The complete data set is then mapped by NLM(R)
- Considerable speed-up can be achieved:

$$SMF = \frac{SA_{complete}}{SA_{hier}} \quad (6.3)$$

$$with \quad SA_{complete} = iterations * \frac{N * (N - 1)}{2}$$

$$and \quad SA_{hier} = iter_t * \frac{K * (K - 1)}{2} + iter_r * N * K$$


- Obviously, K controls computational effort & mapping quality
- The required computational effort for clustering must be included

© Andreas König Slide6-30

Hierarchical Visualization

Sensor Signal Processing Data Visualization

- Hierarchical Mapping of Iris Based on NLM and NLMR




© Andreas König Slide6-31

Hierarchical Visualization

Sensor Signal Processing Data Visualization


- Hierarchical Mapping of Iris Based on NLM and BP network



© Andreas König Slide6-32

Hierarchical Visualization

- Hierarchical Mapping of Mechatronic Based on NLM and NLMR




- Mechatronic (1775 samples, 24-D) data
- $K=64$ centroids, $SMF=26.73$ ($K=3$, $SMF=591$!)

© Andreas König Slide6-33

Hierarchical Visualization

- Visual Assessment of Hierarchical Mappings:



© Andreas König Slide6-34

Hierarchical Visualization

Sensor Signal Processing Data Visualization

- Quantitative Assessment of Hierarchical Mapping
- The introduced distance & topology preservation measures are employed for quantitative comparison of three regarded data sets:

Data set	Mapping	E	q_m
Iris data	NLM	0.01439	0.6366
Iris data	NLM(R)	0.01791	0.5000
Iris data	BP	0.66365	0.4794
<i>Mechatronic</i>	NLM	0.02875	0.1671
<i>Mechatronic</i>	NLM(R)	0.05713	0.1130
<i>Mechatronic</i>	BP	0.75846	0.1059
RIAD	NLM	0.05116	0.2421
RIAD	NLM(R)	0.10400	0.1754
RIAD	BP	0.14935	0.1340


- The hierarchical mapping approach based on NLM & NLM(R) outperforms the NLM & ANN approach in terms of complexity, speed, user convenience, and results

© Andreas König Slide6-35

Hierarchical Visualization

Sensor Signal Processing Data Visualization

- Mapping Quality vs. Computational Expense in Hierarchical Mapping
- The introduced distance & topology preservation measures are employed for quantitative comparison of three regarded data sets:




- Gradual increase of topology preservation & decrease of distance preservation error can be observed for increasing K. Nonmonotonicity is due to chosen clustering procedures (single runs)

© Andreas König Slide6-36

Sensor Signal Processing Data Visualization

Tools

- Tools for Interactive Multivariate Data Visualization: **WeightWatcher**
- **Research objective:** Achievement of a transparent & intuitive MMI to access and analyse multivariate data for information processing
- Employment of efficient projection techniques, enhanced user interaction, and CAD-inspired functionality
- Optimum exploitation of the remarkable human perceptive and associative capabilities
- Thus, the **WeightWatcher (WW)** was conceived for visual analysis of neural networks
- The concept was generalized to arbitrary multivariate data sets
- WW is part of QuickCog, a platform for fast & transparent design of vision & cognition systems




© Andreas König Slide6-37

Sensor Signal Processing Data Visualization

Tools

- WW in QuickCog serves for **feature space visualization & assessment**
- All described visualization techniques are implemented by WW
- The QuickMine-Toolbox comprises projection & clustering methods with WW
- An MS-Excel-Macro allows import of arbitrary application data
- QuickMine can be employed for general data visualization & analysis tasks




© Andreas König Slide6-38

Tools

➤ Tools for Interactive Multivariate Data Visualization: **Acoustic Navigator**

- AN is dedicated to **psychoacoustics & sound engineering**
- Integrated in the processing hierarchy of PATS system
- Combines **visualization & auralization** in the analysis process
- Global & local sound data visualization
- Search functions & directed navigation
- Tentative edit functions for complex **pattern synthesis** [Sammon 69]



© Andreas König Slide6-39

Applications


Benefits of Dimensionality Reduction and Visualization for the Rapid Design of Vision & Cognition Systems:

- Clustering & structure in the data can be observed
- Discriminance of the computed feature set can be assessed
- Assessment of different feature computation methods is feasible
- Open-loop parameter optimization for feature computation is feasible
- Interactive selection of significant features by WW component planes
- Outliers & identicals can be easily identified and eliminated from the data set
- Human errors during data acquisition, labeling & filing can be detected
- Large unlabeled or partially labeled data sets can be manually or semi-automatically according to human to the human observation of data structure and implied similarity in the projection
- Classification errors can be spatially located in the feature space projection
- Understanding of design problems & trouble shooting is alleviated

© Andreas König Slide6-40

Applications

- Application Examples: BGA X-Ray Inspection in Electronics Manufacturing



- Misclassifications & outliers can be tracked-back in the database by mouseclick in the WW display
- System design, validation, optimization, and trouble shooting is alleviated

© Andreas König Slide6-41



Applications

- Application Example: Eye-Tracking System (s. Introduction)

FS for Eye-Shape Classification:

- FSSPEA finds best solution
- Generalization is affected !
- SFS solution for HW-design

Feature space for FSSPEA



Method	Train	Test	Features
ORG	0.992500	0.981667	24
SFS	0.997500	0.928333	3
SBS	0.989333	0.981667	12
PM	0.997500	0.959167	6
SGA	0.997333	0.969167	12
FSSPEA	0.997500	0.928333	3



© Andreas König Slide6-42

Applications

- Application Example: [Eye-Tracking System Hardware](#)

RNN Low-Power Analog Eye-Shape Classifier:

- 12-D Gabor jet reduced to 6 features by AFS
- RNN constrained to Manhattan distance, $T_{\text{RNN}}=6$
- 6 bit RAMDACs for weights
- AMS 0.6 μm CUQ CMOS-technology
- Cell size 1595 μm x 184 μm (conservative)
- Power dissipation 348,9 nW, $3,5 \times 10^{-10}$ J
- Classification speed: 1ms/pattern, R=100%



© Andreas König Slide6-43

Summary

- This chapter gave an introduction to and a focused survey of the principles and techniques for [interactive visualization of multivariate data](#)
- The strong [relation](#) with [dimensionality reduction techniques](#), in particular distance preserving mappings, was pointed out
- Various auxiliary visualization modes for [components](#), [grids](#), [attributes](#), [hierarchical database access](#) and [outlier detection](#) were presented
- In particular, the issue of ubiquitous [mapping errors](#) was addressed and [quantitative](#) as well as [fast visual assessment criteria](#) were introduced
- Improvement of the concept by [hierarchical approaches](#) was introduced
- Two dedicated tools, the [WeightWatcher](#) & the [Acoustic Navigator](#) were presented
- Application examples were given, e.g., [rapid prototyping](#) and [transparent design of recognition systems](#)

© Andreas König Slide6-44