



- Most useful for General Incubation.
- Double wall construction with Inner made of Stainless Steel – 304 grade & Exterior of CRCA steel with powder coat finish.
- High density glass wool insulation between the walls to prevent heat dissipation.
- A transparent full length Acrylic inner door is provided to have a clear inner view of the samples put in, without disturbing the thermal conditions inside the incubator.
- A fully insulated door with sturdy S. S. hinges, S. S. Latch handle lock and gasket which acts as a perfect sealant.
- Heating elements are made of high grade Nichrome wire and are placed at the bottom, of the unit.
- Temperature Range : 5°C above ambient to 60°C.
- Temperature controlled by Capillary Thermostat with +/- 2° C accuracy.
- Gravity convection.
- Shelves are made of galvanized wire mesh.
- Operates on 230 Volts AC Single phase 50 Hz.

OPTIONAL ACCESSORIES :

- Dual display Microprocessor based PID Temperature Controller & PT-100 sensor with $\pm 1^{\circ}\text{C}$ accuracy.
- Air circulation by Motorized blower.
- PID temperature controller with timer of 999 minutes.
- Stainless Steel Rod shelves.

MODEL	WORKING SIZE (W X D X H)		CAPACITY	RATING	SHELVES
	INCH	CM			
LLBI-1	12 X 12 X 12	30 X 30 X 30	27 LTRS	250 W.	1 NOS.
LLBI-2	14 X 14 X 14	35 X 35 X 35	45 LTRS	300 W.	2 NOS.
LLBI-3	18 X 18 X 18	45 X 45 X 45	90 LTRS	400 W.	3 NOS.
LLBI-4	18 X 18 X 24	45 X 45 X 60	120 LTRS	750 W.	3 NOS.
LLBI-5	24 X 24 X 24	60 X 60 X 60	220 LTRS	1000 W.	3 NOS.
LLBI-6	24 X 18 X 36	60 X 45 X 90	250 LTRS	1250 W.	3 NOS.
LLBI-7	24 X 24 X 36	60 X 60 X 90	325 LTRS	1500 W.	4 NOS.