



- Double Walled construction, Inner chamber made of Stainless steel - 304 grade & Outer CRCA Steel - powder coat finished.
- Interior made of Stainless Steel – 304/316 grade and Exterior of Stainless Steel 304 grade matt finish in all GMP Models.
- Units are highly insulated with compressed Glass wool between the walls to minimize the heat exchange.
- A key lockable insulated door having magnetic gasket seals the door gaps perfectly.
- Toughened glass window allows clear observation of specimens.
- Illumination lamp fitted for clear visibility.
- Mechanical convection system (Motorized Blower) ensures even air distribution within the chamber.
- Heating by long life S. S. tubular air heaters.
- Cooling is done by hermetically sealed Emerson Copland make compressor utilizing CFC Free R-134 A refrigerant.
- Temperature Range : 5° C to 60° C.
- Temperature controlled by Dual display Microprocessor based PID Temperature Controller & PT – 100 sensor with +/- 0.5° C Accuracy.
- Digital Timer of 999 Minutes for timed shaking with audio visual alarm.
- Shaking mechanism comprises of Variable speed PMDC geared motor with Eccentric orbital drive.
- Shaking amplitude: 25 MM.
- Shaking speed can be controlled by means of Digital RPM Indicator cum Controller between 20 RPM to 250 RPM.
- Universal Platform to accommodate interchangeable lotus clamps of assorted sizes for different capacities of flasks.
- Adjustable & removable S.S. Rod shelves for Holding Petri Dishes & Flasks.
- Operates on 230 Volts AC Single phase 50 Hz.

APPLICATION:

Orbital Shaking Incubators are specifically designed to have combined advantage of closely controlled incubation with orbital shaking applications required in fermentation studies, tissue cultures, enzyme reactions, life science and biotechnology research labs.

MODEL	OSI-1	OSI-2
WORKING SPACE (W X D X H)	45 X 45 X 50 CM	55 X 55 X 70 CM
CAPACITY	100 LTRS	200 LTRS
UNIVERSAL PLATFORM SIZE	35 X 35 CM	45 X 45 CM
MAXIMUM		
NO OF		
CLAMPS		
100 ML	16	25
250 ML	09	16
500 ML	09	16
1000 ML	04	09
MAXIMUM SHAKING CAPACITY	5 LTRS	10 LTRS
NO. OF TRAYS	1	2

SAFETY :-

- Redundant high temperature safety system automatically cuts-off power to heaters if temperature exceeds 70°C.
- Overload protection relay & time delay for compressor.

N. B. : S. S. lotus clamps to be ordered separately.