

## ROTARY SHAKER / ORBITAL SHAKER : HEAVY DUTY



- Useful for Shaking in Research Institutions, Chemical & Agriculture Laboratories.
- The housing made of CRCA Steel - powder coat finished.
- Universal Platform made from S.S. 304 grade to accommodate interchangeable lotus clamps of assorted sizes for different capacity of flasks.
- Shaking Speed can be controlled by Digital RPM Indicator cum Controller between 20 RPM to 250 RPM.
- Permanent Magnet D. C. (PMDC) geared motor for shaking with eccentric orbital drive.
- Shaking Stroke: 25 MM.
- Operates on 230 Volts AC Single phase 50 Hz.

| MODEL  | UNIVERSAL PLATFORM SIZE | MAXIMUM NO OF CLAMPS |        |        |         |
|--------|-------------------------|----------------------|--------|--------|---------|
|        |                         | 100 ML               | 250 ML | 500 ML | 1000 ML |
| LROS-1 | 350 X 350 MM            | 16                   | 9      | 9      | 4       |
| LROS-2 | 450 X 450 MM            | 25                   | 16     | 16     | 9       |
| LROS-3 | 600 X 600 MM            | 64                   | 36     | 25     | 16      |
| LROS-4 | 750 X 750 MM            | 81                   | 49     | 36     | 25      |
| LROS-5 | 900 X 900 MM            | 100                  | 64     | 49     | 36      |

### OPTIONAL ACCESSORIES :

A. Digital Timer for Timed shaking process of 999 Minutes.

N. B.: A. S. S. Lotus clamps for holding the flasks in the shakers to be ordered separately.

B. Reciprocal shakers are also available.

## SHAKING WATER BATH



### APPLICATION :

Bath designed for studies on Tissue metabolism, Enzymes and Protein coagulation & experiments requiring Shaking of subject matter at constant speed under the controlled temperature environment.

### OPTIONAL ACCESSORIES:

A. Digital Timer of 999 Minutes for timed shaking process.

- Double walled construction, Argon welded leak proof Inner tank made of Stainless steel-304 grade & Exterior made of CRCA Steel- powder coat finished.
- Hinged Pyramid shape lid provided avoids evaporation of water and makes condensed water to fall back in the bath.
- Shaking tray consist of Lotus clamps to hold Conical flask.
- Shaking mechanism comprises of Variable speed PMDC geared motor fixed on right side & coupled to the shaking tray which shakes linearly.
- Shaking Stroke : 25 MM.
- Shaking speed can be controlled by means of Variable frequency drive with Digital RPM Indication between 50 RPM to 150 RPM.
- Temperature controlled by Dual display Microprocessor based PID Temperature controller & PT – 100 Sensor.
- Temperature Range : 5° C above ambient to 95° C.  $\pm$  1° C.
- Operates on 230 Volts AC Single phase 50 Hz.

| MODEL      | BATH SIZE W X D X H | CAPACITY                            | RATING  | MAXIMUM SHAKING CAPACITY |
|------------|---------------------|-------------------------------------|---------|--------------------------|
| LSWB-1 S/G | 16" X 12" X 10"     | 100 ML X 12 Nos.<br>250 ML X 6 Nos. | 1000 W. | 1.5 Ltrs.                |
| LSWB-2 S/G | 18" X 14" X 10"     | 500 ML X 6 Nos.                     | 1500 W. | 2 Ltrs                   |
| LSWB-3 S/G | 20" X 16" X 10"     | 250 ML X 12 Nos.                    | 2000 W. | 3 Ltrs                   |