



SIMATS Online Programming Lab

C PROGRAMMING



BUCHUPALLI GANGA JAYADEV REDDY
192472248RB



CO3 - AT3 - Mock Interview

[← Back](#)

QUESTIONS

Q1

MOCK INTERVIEW

100 marks



1/1 answered

Q1 MOCK INTERVIEW

100 marks

1. What is the difference between an array and a variable?
2. What is meant by the base address of an array?
3. What happens if an array size is not specified during initialization?
4. How are 2D arrays stored in memory?
5. Give one real-life application of multidimensional arrays.
6. Why do arrays start from index 0 instead of 1?
7. Which engineering fields commonly use multidimensional arrays?
8. Can a multidimensional array have more than three dimensions?
9. Why are images stored as multidimensional arrays?
10. What is row-major order?
11. Does C use row-major or column-major order?
12. Why can't arrays return multiple values?
13. What happens when array bounds are exceeded?
14. Why are strings stored as character arrays?
15. Explain the difference between `char str[]` and `char *str`.
16. Can two-dimensional arrays be passed to functions?
17. When would a linked list outperform an array?

18. Differentiate gets(), fgets(), scanf(), and getchar().

Your Answer

1. Difference between an array and a variable:
A variable can store only a single value at a time, whereas an array is a collection of multiple values of the same data type stored under a single name using contiguous memory locations.

 Save Answer

© 2026 **SIMATS Online Lab**. All rights reserved.