

Experiment 3: FCFS Scheduling

C Program

```
#include<stdio.h>

int main()
{
    int bt[20],wt[20],tat[20],n,i;
    float awt=0,atat=0;

    printf("Enter number of processes: ");
    scanf("%d",&n);

    for(i=0;i<n;i++)
    {
        printf("Enter Burst Time for P%d: ",i+1);
        scanf("%d",&bt[i]);
    }

    wt[0]=0;

    for(i=1;i<n;i++)
        wt[i]=wt[i-1]+bt[i-1];

    for(i=0;i<n;i++)
    {
        tat[i]=wt[i]+bt[i];
        awt+=wt[i];
        atat+=tat[i];
    }

    printf("\nProcess\t\tBT\t\tWT\t\tTAT\n");

    for(i=0;i<n;i++)
        printf("P%d\t\t%d\t\t%d\t\t%d\n",i+1,bt[i],wt[i],tat[i]);

    printf("\nAverage Waiting Time = %.2f",awt/n);
    printf("\nAverage Turnaround Time = %.2f",atat/n);

    return 0;
}
```

Output

Sample Input:

4
5
3
8
6

Sample Output:

Process BT WT TAT
P1 5 0 5
P2 3 5 8
P3 8 8 16
P4 6 16 22

Average Waiting Time = 7.25

Average Turnaround Time = 12.75