OMX-5DOF

6-DOF Upgraded Edition

5dof configuration

Key Features

- *Not specified*

Applications

- *Not specified*

Performance

Max TCP speed	0.30 m/s
Max joint speed	275.0°/s
Mounting Options	Tabletop or fixed base
Noise Level	¡ 60 dB(A)
Orientational Accuracy	± 0.560 °
Positional Accuracy	± 0.454 mm

General Specification

Payload	0.3 kg (at max reach)
Reach	342 mm
Degrees of Freedom	6
Configuration	Articulated Manipulator
Repeatability	±2.697 mm
Footprint	Ø150 mm

*Payload includes end-effector weight. Reach defined as maximum distance from base to TCP.

Joint Specifications

Joint	Working Range	Max Speed	Peak Torque
Joint1	$-180°$ to $180°$	275°/s	1000.0 Nm
Joint2	$-86°$ to $86°$	275°/s	1000.0 Nm
Joint3	$-86°$ to $80°$	275°/s	1000.0 Nm
Joint4	$-97°$ to $113°$	275°/s	1000.0 Nm
Gripper Left Joint	$-1°$ to $1°$	275°/s	1000.0 Nm
Gripper Right Joint	$-1°$ to $1°$	275°/s	1000.0 Nm

*Gripper provides additional actuation DOF. Torque values are derived from manufacturer datasheets.

Control System

Supported OS	Ubuntu 22.04 / 24.04
Middleware	ROS 2 (Humble / Jazzy)
Motion Planning	MoveIt 2 (OMPL)
Controller	ros2_control
Simulation	Gazebo (Ignition)
Programming	Python, C++ APIs
Interface	USB / Serial (via controller)

Actuators

Actuator Type	DYNAMIXEL Smart Servo
Motor Models	XM430-W350-T / XL430-W250-T
Control Mode	Position / Velocity / Current
Communication	TTL Multi-Drop Bus
Feedback	Absolute Contactless Encoder

Electrical Specifications

Input voltage	12 V DC
Power supply	12 V, 5 A adapter
Typical power	35 W
Maximum power	120 W (peak load)
Digital I/O	Available via external controller

Physical & Kinematics

Materials	High-strength polymer (PLA) + metal fasteners
Cable length	1 m
Total Weight	$\approx$ 0.63 kg
IP Rating	IP20
Operating Temp	0 °C to 45 °C
Humidity	5% to 85% (non-condensing)

Safety & Compliance

Safety rating	Uncertified (Research use only)
Architecture	Software-limited force/torque feedback (PL-b equivalent)
Protection	Configurable joint, velocity, and torque limits
E-Stop	Software-triggered (external hardware optional)

Known Limitations

- 0
- Limited stiffness due to 3D-printed PLA structure
- Accuracy subject to standard Dynamixel gear backlash

Documentation & Resources

GitHub Repository
Access source code, ROS 2 packages, setup guides, and updates.
github.com/KMTI-ROBOPARADIGM/omx-wrist-roll-original

Package Contents

- 6-DOF Robotic Arm & Gripper
- 12V Power Adapter
- Communication Cable
- Mounting Hardware
- Quick start guide / documentation

Contact & Origin

Lab/Entity	**AutoCert Lab**
Contact	research@domain.edu
Location	India