Reproducible 6-DOF Wrist-Roll Retrofit for OpenMANIPULATOR-X

CSE/ROBOTICS
TELEPARADIGM TOWERS
HYDERABAD, INDIA
email@domain.com

***Abstract*—Low-cost educational manipulators lack the full orientation control required for complex manipulation tasks due to their limited degrees of freedom. This paper presents a complete and reproducible retrofit to upgrade the OpenMANIPULATOR-X from a 5-DOF to a 6-DOF system by integrating an additional wrist-roll joint, accompanied by a unified hardware and ROS 2-based software stack.**

The proposed approach includes a detailed mechanical retrofit kit (CAD models, bill of materials, and assembly procedure), an updated URDF/Xacro robot description with calibrated joint limits and dynamics, and a full ROS 2 bring-up incorporating `ros2_control`, controllers, and MoveIt 2 motion planning. A structured benchmarking framework is developed to systematically compare the 5-DOF and 6-DOF configurations under identical conditions, evaluating kinematic feasibility, orientation reachability, motion efficiency, and planning robustness in constrained environments.

Experimental results demonstrate that the upgraded 6-DOF system achieves complete orientation reachability across all tested configurations, whereas the baseline 5-DOF system succeeds only in limited cases. In constrained planning scenarios, the 6-DOF configuration achieves a 25.0% success rate compared to 0.0% for the 5-DOF system, with statistically significant improvement ($\chi^2 = 18.81$, $p < 0.000025$). Additionally, the 6-DOF system reduces joint-space motion by 25.8% for equivalent tasks and maintains high control accuracy, achieving sub-degree orientation error (0.55°) and consistent trajectory tracking across repeated trials.

These results demonstrate that the addition of a wrist-roll joint significantly enhances kinematic capability, planning success, and execution efficiency while preserving precision and system stability. The complete set of open-source artifacts, including hardware designs, ROS 2 packages, and benchmarking tools, provides a low-cost, reproducible upgrade path for educational manipulators, with open hardware and software artifacts intended to support future replication by other laboratories.

***Index Terms*—Degrees of freedom, robot kinematics, OpenMANIPULATOR-X, wrist-roll retrofit, ROS 2, MoveIt 2, motion planning, kinematic redundancy, benchmarking.**

I. Introduction

Low-cost educational manipulators are widely used in robotics laboratories for instruction, rapid prototyping, and benchmarking. Platforms such as the OpenMANIPULATOR-X [1] provide accessible integration with ROS 2 [2] and MoveIt 2 [3], enabling exploration of perception, motion planning, and control within compact manipulation systems. However, such platforms are typically limited in their degrees of freedom, constraining end-effector orientation capability.

In the standard 5-DOF configuration, the absence of an independent wrist-roll joint restricts the manipulator's ability to achieve arbitrary orientations at a fixed spatial position. This limitation becomes critical in tasks requiring precise alignment, insertion, or orientation-constrained manipulation, where feasible inverse kinematics solutions may not exist or require compensatory joint motions. These compensations degrade motion efficiency, increase execution time, and reduce planning success rates. Despite the widespread adoption of 5-DOF educational manipulators, the quantitative impact of this limitation has not been systematically characterized under controlled and reproducible conditions.

Prior work has explored mechanical extensions of low-cost manipulators; however, many approaches lack either a fully reproducible software stack or a rigorous, statistically grounded comparison between baseline and modified configurations. Consequently, the practical benefits of increased kinematic redundancy remain insufficiently validated.

This work presents a fully reproducible 6-DOF wrist-roll retrofit for the OpenMANIPULATOR-X, extending the original architecture through mechanical integration and updates to the robot model, control stack, and motion planning pipeline using ROS 2, `ros2_control`, and MoveIt 2. The design preserves compatibility with the baseline platform while enabling independent end-effector roll control.

To evaluate the impact of the additional degree of freedom, a structured benchmarking framework is developed to compare 5-DOF and 6-DOF configurations under identical planning conditions. The evaluation considers kinematic feasibility, planning robustness, and motion efficiency within a shared workspace. Hardware experiments further validate controller performance, trajectory tracking accuracy, and end-effector repeatability, while additional sim-to-real analysis quantifies consistency between simulation and physical execution.

Contributions

The main contributions of this work are as follows:

- A validated 6-DOF wrist-roll mechanical retrofit for the OpenMANIPULATOR-X.

- An updated URDF/Xacro model with `ros2_control` integration for both simulation and hardware.
- A complete MoveIt 2 configuration for motion planning with the extended kinematic chain.
- A reproducible benchmarking framework comparing 5-DOF and 6-DOF configurations.
- A comprehensive evaluation demonstrating improvements in kinematic capability, planning performance, and physical system reliability.

The remainder of this paper is organized as follows. Section II reviews related work. Sections III and IV describe the hardware design and software implementation, respectively. Section V presents the benchmarking methodology, followed by the structural capability comparison in Section VI. Experimental results are reported in Section VII and discussed in Section VIII. Finally, Section IX concludes the paper and outlines future research directions.

II. Related Work

Low-cost robotic manipulators have become essential tools in robotics education and academic research due to their affordability, modularity, and compatibility with modern software ecosystems. Platforms such as the OpenMANIPULATOR-X [1], WidowX [4], and Franka Emika Panda [5] span a range of cost and capability, enabling applications in manipulation research, imitation learning, and curriculum-driven instruction [6]. Among these, the OpenMANIPULATOR-X is widely adopted for its Dynamixel-based architecture and seamless integration with ROS 2 and motion planning frameworks. However, its standard 5-DOF configuration imposes inherent kinematic limitations, particularly in tasks requiring precise end-effector orientation control [7].

The relationship between manipulator degrees of freedom and task-level capability is well established. A minimum of six DOF is required to achieve arbitrary end-effector poses in three-dimensional space [8]. Manipulators with fewer DOF, such as 5-DOF systems, are restricted to a subset of achievable orientations at a given position, resulting in coupling between position and orientation. Classical robotics analyses, including those by Craig [8] and Whitney [9], highlight that the absence of an independent wrist-roll joint prevents full specification of orientation, leading to infeasible inverse kinematics solutions or inefficient compensatory motions. While these limitations are theoretically understood, they are often discussed qualitatively and lack systematic, experimentally validated characterization on widely used low-cost platforms.

Modern robotic manipulation systems are typically built upon the Robot Operating System 2 (ROS 2) [10], which provides a flexible middleware for communication and control. The `ros2_control` framework offers a standardized hardware abstraction layer, while MoveIt 2 [3] enables motion planning, kinematic modeling, and collision-aware trajectory generation. Underlying these systems, the Open Motion Planning Library (OMPL) [11] provides a suite of sampling-based planners, including RRTConnect, PRM, and EST, which are widely used for high-dimensional motion planning problems. Benchmarking tools such as the MoveIt 2 evaluation suite and Planner Arena [12] have further enabled systematic comparison of planning algorithms using metrics such as success rate, computation time, and path quality.

Motion planning in constrained environments introduces additional challenges, particularly when orientation constraints must be maintained within narrow workspaces. Prior work by Berenson *et al.* [13] introduced constraint-based planning approaches to address such scenarios, emphasizing the importance of kinematic feasibility under geometric restrictions. These methods highlight the critical role of manipulator dexterity in achieving feasible solutions in tightly constrained environments, motivating the need for additional degrees of freedom in such contexts.

Parallel to these developments, reproducibility has emerged as a key concern in robotics research. Efforts such as standardized benchmarking frameworks and open evaluation platforms, including the Benchmark for Robot Learning [14], emphasize the importance of sharing complete experimental artifacts and protocols to enable consistent and verifiable comparisons. Despite these advances, many prior works on extending low-cost manipulators focus primarily on hardware augmentation without providing a fully integrated software pipeline or statistically rigorous evaluation. As a result, the practical benefits of added kinematic redundancy, such as a wrist-roll joint, remain insufficiently quantified under controlled and reproducible conditions.

In summary, while low-cost manipulators, advanced motion planning frameworks, and benchmarking tools are widely available, there remains a lack of unified studies that combine mechanical augmentation, full software integration, and rigorous evaluation. In particular, the impact of introducing an additional wrist-roll degree of freedom on kinematic feasibility, planning robustness, and execution efficiency has not been systematically evaluated on commonly used platforms. This work addresses that gap.

III. Hardware Design

A. Design Philosophy

The retrofit is guided by three principles: mechanical minimalism (disturb as few existing components as possible), full reversibility (the original 5-DOF arm can be restored by removing the added motor and restoring the original `link5.stl` mesh), and low incremental cost (leverage existing Dynamixel infrastructure and 3D-printable parts). Adding a single additional revolute joint between the existing wrist-pitch link (*link5*) and the gripper assembly achieves a true sixth degree of freedom—independent end-effector roll about the approach axis—without redesigning the arm structure.

TABLE I
DYNAMIXEL MOTOR CONFIGURATION AFTER RETROFIT

ID	Joint	Mode	Status
11	joint1 (base)	Position (3)	unchanged
12	joint2 (shoulder)	Position (3)	unchanged
13	joint3 (elbow)	Position (3)	unchanged
14	joint4 (wrist pitch)	Position (3)	unchanged
15	joint5_roll	Position (3)	**new**
16	gripper_left_joint	Curr-pos. (5)	**moved from 15**

B. Motor Selection and Physical Configuration

The new wrist-roll joint is actuated by a Dynamixel XL430-W250-T servo, selected for compatibility with the existing RS-485 daisy-chain bus and U2D2 interface, its compact form factor (approximately 33.5 mm axial depth), and its ability to operate in Position Control Mode (Mode 3), consistent with the other arm joints. The motor is assigned Dynamixel ID 15; the existing gripper servo, previously ID 15, is reassigned to ID 16 to avoid address conflicts. This reassignment must be performed using Dynamixel Wizard before powering the full system. Table I lists the complete motor configuration after the retrofit.

C. Mechanical Components — Retrofit BOM

Table II lists *only the additional components* required beyond the standard OpenMANIPULATOR-X assembly. The base arm, its four Dynamixel servos, gripper, power supply, and U2D2 interface are assumed already present. The incremental hardware cost is dominated by a single Dynamixel servo; both structural adapters are 3D-printable, keeping the total upgrade expense modest relative to the platform's original cost. STL and STEP source files are provided in `open_manipulator_description/meshes/`, enabling in-house fabrication on any FDM printer at 0.2 mm layer height or finer.

D. Assembly Overview

The physical assembly follows a forward kinematic order:

1) *Gripper motor reassignment.* Before any mechanical work, connect the gripper servo alone to Dynamixel Wizard and change its ID from 15 to 16. Confirm the motor responds on the new ID before proceeding.
2) *Wrist link installation.* Remove the original link5-to-gripper connection. Attach the printed wrist link (`wrist_link.stl`) to the distal face of link5 using the existing mounting holes.
3) *Motor mounting.* Seat the XL430-W250-T into the wrist link cavity and secure with M2 bolts. The output shaft faces forward along the arm's longitudinal (X) axis, producing pure roll rotation.
4) *Gripper adapter attachment.* Fix the printed gripper bracket to the motor horn and re-attach the gripper finger servos using the original mounting pattern.
5) *Wiring.* Thread the RS-485 extension cable from the existing bus through the wrist link to the new motor (ID 15), then onward to the gripper servo (ID 16).

Total mechanical modification time is approximately one hour. No permanent alterations are made to the original arm; all fastener holes are reused from the existing link5 mounting interface.

E. Zero-Position Calibration

The wrist-roll zero position (`joint5_roll` = 0 rad) is defined as the orientation in which the gripper fingers are co-planar with the arm's pitch plane, matching the neutral orientation of the original 5-DOF gripper. After assembly, jog the new motor to this pose using Dynamixel Wizard's position control panel and verify alignment visually. If the motor is mounted in reverse orientation, setting Drive Mode 1 in the `ros2_control` configuration inverts the direction without any wiring change.

IV. SOFTWARE IMPLEMENTATION

All software modifications reside in the project repository at https://github.com/KMTI-ROBOPARADIGM/omx-wrist-roll-original. The changes span five commits across five ROS 2 packages; complete diffs and per-commit explanations are provided under `docs/wrist_roll_modifications/`. This section describes the architectural decisions and non-obvious design choices; readers seeking exhaustive code listings should consult the repository directly.

A. Kinematic Chain Update (URDF/Xacro)

The original `link5.stl` mesh combined the wrist housing and gripper base into a single rigid body. Since a joint cannot be placed within a single mesh, the geometry was separated into two parts: `wrist_link.stl` (motor housing, mass ≈85 g) and `gripper_link_with_bracket.stl` (rotating gripper mount, mass ≈65 g).

The resulting kinematic chain is:

$$\text{link4} \xrightarrow{\text{joint4}} \text{link5} \xrightarrow{\text{joint5_roll}} \text{wrist_roll_link} \xrightarrow{\text{gripper joints}} \text{gripper}$$

The new revolute joint uses axis $[1, 0, 0]$ (X-axis roll), origin $[0.0335,\ 0,\ 0]$ m from the link5 frame (motor axial depth), limits $\pm\pi$ rad at 4.8 rad/s, and damping 0.1 N m s/rad for simulation stability. All downstream elements—gripper prismatic joints and the end-effector fixed frame—had their parent reference updated from `link5` to `wrist_roll_link` so that the gripper and TCP rotate with the wrist. The Gazebo configuration received a link physics reference and a `SimpleTransmission` block for the new joint.

B. Hardware Interface Configuration (`ros2_control`)

The `dynamixel_hardware_interface` plugin is configured through the `ros2_control` Xacro file. Three coordinated changes were required.

TABLE II
BILL OF MATERIALS — 6-DOF RETROFIT ADDITIONS ONLY

Qty	Component	Purpose	Notes	Cost
1	Dynamixel XL430-W250-T	Wrist-roll actuator	ID 15, Position Control Mode 3	5,599 INR ($\approx$ \$60)
1	Wrist link (motor housing)	Mounts servo to distal face of link5	3D-printed (`wrist_link.stl`)	—
1	Gripper bracket adapter	Connects servo output shaft to gripper	3D-printed (`gripper_link_with_bracket.stl`)	—
4	M2$\times$8 socket-head screws	Motor-to-bracket fasteners	Stainless steel, ISO 4762	—
4	M2 hex nuts	Mating fasteners	—	—
1	RS-485 extension cable	Continues bus from new motor to gripper servo	$\leq$150 mm, JST connector	—

Joint and transmission count. `number_of_joints` and `number_of_transmissions` were incremented from 5 to 6.

Transmission matrices. The motor-to-joint and joint-to-motor mapping matrices were expanded from 5×5 to 6×6 identity matrices, preserving a direct 1:1 mapping for each joint.

Motor block and gripper renumbering. A new `gpio` block was added for `dxl5` (ID 15, Mode 3, P/I/D = 800/100/100, Profile Velocity 20, Profile Acceleration 10). The gripper motor block was renamed `dxl5`→`dxl6` and its hardware ID updated from 15 to 16. The `revolute_to_prismatic_dxl` parameter was updated to reference `dxl6` accordingly. The controller manager YAML was extended to include `joint5_roll` in the `arm_controller` joint list, and the home position vector in `initial_positions.yaml` was expanded from four to five elements (appending 0.0 rad for the neutral wrist-roll position).

C. ROS 2 Jazzy Launch Compatibility Fix

On ROS 2 Jazzy, passing a `Command` substitution directly as the `robot_description` parameter caused the launch system to attempt YAML parsing of the raw URDF XML, raising a type error. Wrapping the value in `ParameterValue(urdf_file, value_type=str)` forces plain-string treatment and was applied to `ros2_control_node`, `robot_state_publisher`, and the controller spawner nodes. The fix is backward-compatible with earlier ROS 2 distributions.

D. MoveIt 2 Motion Planning Configuration

Four configuration files were updated to integrate `joint5_roll` into the MoveIt 2 planning stack.

SRDF. `joint5_roll` was added to the `arm` planning group and to both named states (*init* and *home*). The collision matrix was updated: `wrist_roll_link`–`link5` and `wrist_roll_link`–`end_effector_link` are marked *Adjacent*; gripper links changed from *Adjacent* to *Never* with respect to `link5`. These entries reduce per-state collision checks from 28 to 16 pairs.

Joint limits. Position, velocity ($\leq$5.0 rad/s), and acceleration ($\leq$5.0 rad/s^2) limits for `joint5_roll` were added to `joint_limits.yaml`.

MoveIt 2 controllers. `joint5_roll` was appended to the `arm_controller` joint list in `moveit_controllers.yaml`.

E. Graphical User Interface Extension

The Qt-based GUI was extended to provide interactive control and real-time feedback for the new joint. A new row was inserted in the joint control panel between Joint 4 and Gripper, containing a `QDoubleSpinBox` (range $\pm$3.14 rad), a horizontal slider (integer range -314 to $+314$, scale 0.01 rad per unit), and a *Set* push-button. The joint-state update function reads index 4 (`joint5_roll`) from the six-element joint angle vector, with gripper at index 5. The *Set* handler sends a five-element arm trajectory via `setJointSpacePath`; the QNode state reader was updated from four to five arm joints; and CSV trajectory logging was extended to include the wrist-roll column. No changes were required to the teleop package, which derives its joint list automatically from the MoveIt 2 arm planning group.

F. Summary of Modified Files

Table III provides a concise reference to all 18 files changed across the five commits.

V. METHODOLOGY

This section describes the experimental methodology used to evaluate the 6-DOF retrofit relative to the baseline 5-DOF system. The evaluation is structured as a pose-based

TABLE III
SOFTWARE MODIFICATION SUMMARY (BRANCH: `wrist-roll-dev`)

Package	File Changed	Nature of Change
open_manipulator_description		
	`open_manipulator_x_arm.urdf.xacro`	New joint, link, mesh references
	`open_manipulator_x.gazebo.xacro`	Link reference + SimpleTransmission block
	`open_manipulator_x_position.ros2_control.xacro`	6 joints, 6×6 matrices, dxl5/dxl6
open_manipulator_bringup		
	`open_manipulator_x.launch.py`	ParameterValue type fix (ROS 2 Jazzy)
	`hardware_controller_manager.yaml`	`joint5_roll` added to arm_controller
	`initial_positions.yaml`	Home position expanded to 5 elements
open_manipulator_moveit_config		
	`open_manipulator_x.srdf`	Group, poses, collision matrix updated
	`joint_limits.yaml`	`joint5_roll` limits entry added
	`kinematics.yaml`	IK timeout 0.005 s $\rightarrow$ 0.05 s
	`moveit_controllers.yaml`	`joint5_roll` in arm trajectory controller
open_manipulator_gui		
	`open_manipulator_x_main_window.ui`	New row: spinbox, slider, Set button
	`main_window.hpp`	Qt slot declarations
	`main_window.cpp`	Display, command dispatch, CSV updated
	`qnode.cpp`	Arm joint state reading: 4 $\rightarrow$ 5 joints
open_manipulator_description/meshes		
	`wrist_link.stl`, `gripper_link_with_bracket.stl`	New STL mesh files

benchmarking framework that spans kinematic feasibility, constrained motion planning, and hardware validation, with all assessments conducted under identical conditions for both configurations.

A. Pose-Based Evaluation Framework

Early experiments used joint-space sampling to generate test configurations. This approach revealed a methodological limitation: the 6-DOF arm has a larger configuration-space search domain than the 5-DOF arm, making direct comparisons in joint space inherently unfair. The evaluation was therefore transitioned to a *pose-based* framework in which each test is defined by a target end-effector position and orientation. Both configurations are evaluated on their ability to reach these task-relevant poses, providing a fair and task-grounded basis for comparison.

B. Workspace Estimation


Before generating test poses, the reachable workspace of each configuration was characterised using forward kinematics (FK) sampling. Joint configurations were sampled uniformly within each robot's joint limits and FK was applied to obtain end-effector positions, forming a dense workspace point cloud. Two geometric representations were computed:

- *Convex Hull*: Provides a conservative outer approximation of the reachable workspace by computing the smallest convex set enclosing all sampled points. While computationally efficient, it tends to overestimate the true workspace by ignoring concave regions and internal voids.
- *Alpha Shape*: A generalized non-convex boundary representation that captures the true geometry of the workspace, including concavities and internal gaps. By tuning the shape parameter, the alpha shape allows controlled reconstruction of the workspace boundary with higher fidelity compared to the convex hull.


The intersection of the workspaces of the 5-DOF and 6-DOF configurations was then computed to define a common reachable region. This shared workspace serves as the basis for all subsequent evaluation. Importantly, the estimated workspace boundaries also implicitly define the limits for pose generation: rather than sampling arbitrary Cartesian poses, all evaluation poses are constrained within these empirically derived workspace bounds. This ensures that generated poses are kinematically feasible and reachable by both manipulators, eliminating infeasible targets and avoiding reachability differences as a confound.

C. Orientation Reachability Protocol


The first stage of evaluation focuses on the kinematic capability of each manipulator to achieve specified end-effector




(a) Alpha-shape workspace boundary



(b) 3-D overlay comparison




(c) Convex hull boundary




(d) Top-down heatmap comparison

Fig. 1. Workspace estimation using forward kinematics sampling.



(a) Success vs. Corridor Width



(b) Success vs. Clearance

Fig. 2. Planning success under constrained environments.

orientations at a fixed Cartesian position. This isolates inverse kinematics (IK) feasibility from motion planning effects.

A target position was selected within the shared reachable workspace. Due to the presence of lateral obstacles in the constrained scene, feasible positions were restricted along the central axis ($y = 0$). Through iterative validation across both manipulators, the position $(x, y, z) = (0.20, 0.00, 0.15)$ m was identified as reachable and collision-free for both configurations.

At this fixed position, seven orientations were constructed as pure roll rotations about the end-effector approach axis:

$$\phi \in \{0^\circ, 15^\circ, 30^\circ, 45^\circ, 60^\circ, 75^\circ, 90^\circ\}$$

with pitch and yaw held constant at zero. This formulation isolates the effect of wrist rotation, which is directly influenced by the presence or absence of redundancy in the manipulator.

For each pose, IK was computed using the MoveIt 2 IK service. A pose was classified as *kinematically feasible* if a valid joint configuration satisfying all joint limits and solver constraints was returned within a predefined timeout. The resulting feasible pose sets were recorded independently for each manipulator.

This protocol revealed a clear difference in orientation feasibility: while the 6-DOF manipulator successfully achieved all seven orientations, the 5-DOF manipulator was restricted to a single feasible orientation. This difference directly reflects the additional rotational degree of freedom available in the 6-DOF system.

TABLE IV
CONSTRAINED CORRIDOR COLLISION OBJECTS

Object	**Dim. (m)**	**Position (m)**
Left wall	$0.10 \times 0.20 \times 0.40$	$(0.20, -0.12, 0.20)$
Right wall	$0.10 \times 0.20 \times 0.40$	$(0.20, +0.12, 0.20)$
Top barrier	$0.20 \times 0.30 \times 0.05$	$(0.25, 0.00, 0.30)$
Bottom plate	$0.50 \times 0.50 \times 0.02$	$(0.20, 0.00, -0.01)$

D. Constrained Environment Benchmark

To evaluate practical motion planning performance under realistic constraints, a narrow corridor environment was constructed within the MoveIt 2 planning scene. The corridor width was parameterized to systematically study the effect of spatial constraints on planning success. Table IV details the collision objects.

An initial configuration placed the manipulators in collision with the corridor walls. To ensure a fair comparison, a common collision-free start state was manually identified for both systems by fixing the wrist joint (roll) at 0° and adjusting the second joint angle. Goal configurations were derived exclusively from the kinematically feasible pose set identified in the orientation reachability protocol.

Motion planning was performed using the OMPL RRTConnect algorithm with a planning time limit of 10 s. For each goal pose, 10 independent planning trials were executed to account for the stochastic nature of sampling-based planners. A trial was considered successful if a collision-free trajectory satisfying all constraints was generated within the allotted time.

Corridor width was treated as a variable parameter; experiments were conducted for widths of 0.24 m, 0.28 m, 0.32 m, 0.36 m, and 0.40 m, and success rates were recorded for each configuration.




Fig. 3. Constrained corridor environment used for motion planning evaluation.

E. Cross-Configuration Pose Compatibility Test

To isolate the effect of the additional degree of freedom independently of environmental and planning constraints, a cross-configuration kinematic compatibility test was conducted with collision checking disabled. Two independent pose sets of approximately 8,000 end-effector poses were sampled within the feasible workspace bounds of each configuration. Each pose set was then evaluated on both manipulators, yielding four evaluation conditions:

- **5-DOF → 5-DOF (Self-Reachability):** Establishes a baseline for IK solver reliability.
- **6-DOF → 5-DOF (Dexterity Loss):** Quantifies poses generated in the higher-dimensional workspace that cannot be reproduced in the lower-dimensional system.
- **6-DOF → 6-DOF (Self-Reachability):** Assesses solver performance in the redundant configuration space.
- **5-DOF → 6-DOF (Backward Compatibility):** Determines whether the additional DOF preserves previously reachable configurations.

Quantitative metrics reported are: IK Success Rate, Shared Kinematic Space, and Dexterity Expansion.

F. Controller Tuning and Stabilization

During initial hardware experiments, the manipulator exhibited noticeable oscillations during trajectory execution, particularly after the addition of the wrist-roll joint. To ensure stable execution, an empirical step-response tuning procedure was applied sequentially to all joints: the proportional gain (P) was raised until responsive motion was obtained, the derivative gain (D) was introduced to reduce oscillations, and a small integral gain (I) was added where necessary to eliminate steady-state error. Special attention was given to `joint5_roll`, which required relatively higher damping due to the added mass and mounting configuration. All subsequent hardware experiments were conducted using the tuned parameters.

G. Joint Utilization Analysis

To verify that `joint5_roll` is genuinely exploited by the planner rather than remaining near its zero position, the wrist-roll joint angles across all successful 6-DOF trajectories were recorded and compiled into a utilization heatmap. A broad, non-uniform distribution across the full $\pm\pi$ rad range confirms active use; a distribution concentrated at zero would indicate the joint is effectively unused.




Fig. 4. Joint utilization heatmap showing redundancy exploitation in the 6-DOF manipulator.

H. Statistical Analysis Framework

The following statistical methods were applied to all binary success/failure outcome data:

- **Pearson's chi-square test** (χ^2): tests the null hypothesis that planning success rate is independent of robot configuration (5-DOF vs. 6-DOF).
- **Cramer's** V: normalised effect size derived from χ^2, interpretable as small (<0.1), medium (0.1–0.3), or large (>0.3).
- **Cohen's** h: effect size for the difference between two independent proportions.
- **Welch's** t**-test and Cohen's** d: applied to planning time distributions for successful trials.

All computations were implemented in Python (NumPy, SciPy) and outputs were auto-exported as LaTeX tables to ensure full computational reproducibility.

I. MoveIt 2 Benchmarking Framework

To complement the custom evaluations and ensure reproducibility under a standardised framework, benchmarking was conducted using the MoveIt 2 Benchmark Suite.

1) Benchmark Pose Set Generation: A common set of 300 target poses was generated within the shared reachable workspace using quasi-random sampling techniques including Latin Hypercube Sampling (LHS) and low-discrepancy Halton sequences. Only poses reachable by both manipulators were retained, ensuring a consistent and fair benchmarking dataset. The resulting pose set was converted into robot-specific joint-space goals and stored in a benchmarking database compatible with the MoveIt 2 pipeline.
2) Benchmark Execution Protocol: Motion planning was performed for both configurations under identical conditions using OMPL RRTConnect. All benchmark runs were configured with consistent planning time limits, collision checking settings, and planner parameters. For intra-configuration analysis, benchmark logs were processed using the Planner Arena [12] tool; for inter-configuration comparison, a custom post-processing script was developed.
3) Evaluation Metrics: The following metrics were collected for each configuration:

- **Planning Success Rate**: ratio of successful plans to total planning attempts.
- **Planning Time**: time to compute a valid collision-free trajectory.
- **Path Length**: cumulative joint-space distance along the planned trajectory, $L = \sum_{i=1}^{N-1} \|\mathbf{q}_{i+1} - \mathbf{q}_i\|$.
- **Average Waypoint Distance**: mean distance between successive waypoints.
- **Path Length Variance**: statistical variance of path lengths across repeated runs.

J. Hardware Validation Protocol

To validate practical performance under real-world conditions, a comprehensive hardware evaluation protocol was established. The protocol focuses on controller fidelity, repeatability, and sim-to-real consistency.
1) Controller Performance and Joint Tracking Accuracy: Both step and continuous (sinusoidal) inputs were applied to `joint5_roll` using the `joint_trajectory_controller` within the `ros2_control` framework. Joint states were recorded at high frequency via the `/joint_states` topic. Tracking performance was quantified using RMSE and maximum peak error between commanded and observed trajectories.
2) End-Effector Pose Repeatability: A large-scale repeatability experiment was conducted in which target poses distributed across multiple kinematic zones were executed repeatedly from a common initialization configuration. For each pose, multiple trials were performed, and statistical measures including variance (σ^2) and standard deviation (σ) of the end-effector position and orientation were computed. Three operational factors were captured: workspace coverage (left/center/right and low/mid/high regions), approach direction (positive and negative joint offsets to evaluate backlash effects), and velocity profiles (varying speed to capture dynamic effects).
3) Orientation Tracking and Sim-to-Real Consistency: Identical orientation sweep experiments were conducted in both simulation and on physical hardware. A set of continuous orientation trajectories spanning a specified angular range was executed under varying velocity profiles, and residual errors between commanded and achieved orientations were computed. Differences in performance are attributable solely to physical system characteristics, as identical control pipelines were maintained across both platforms.
4) Pose-Based Hardware Validation Dataset: A structured dataset of 40 validation poses was constructed using a multi-stage sampling and filtering pipeline. Initially, approximately 8,000 joint configurations were sampled using a Halton low-discrepancy sequence, and FK was applied to obtain the corresponding end-effector poses. The pose set was filtered using strict kinematic and operational constraints (workspace bounds and joint-space limits) to yield a safe feasible manifold. From this manifold, boundary poses (near reachable workspace limits) were selected to evaluate performance under high joint torque, and interior poses were selected using Farthest Point Sampling (FPS) to ensure uniform spatial and angular distribution. Each pose was executed multiple times on both simulation and physical hardware under the same `ros2_control` trajectory interfaces.
5) Evaluation Metrics: The following metrics were defined for hardware validation:

- **Joint Tracking Error**: RMSE and maximum deviation between commanded and measured joint trajectories.
- **Cartesian Position Error**: Euclidean distance between commanded and achieved end-effector positions.
- **Orientation Error**: Angular deviation between commanded and measured end-effector orientations.
- **Repeatability**: Standard deviation of position and orientation over repeated trials for the same target pose.
- **Sim-to-Real Deviation**: Difference between simulated and physical execution errors for identical trajectories.

VI. Structural Capability Comparison

A. Comparison Setup

This section evaluates the effect of removing the wrist-roll joint by comparing the 5-DOF and 6-DOF configurations under controlled conditions. The 6-DOF configuration represents the **full system**, while the 5-DOF configuration corresponds to the **joint-removed variant**. All experiments reuse the evaluation protocols defined in Section V, ensuring identical task conditions across both configurations. The objective is to isolate the **causal impact of the additional degree of freedom** across three dimensions: (i) kinematic feasibility, (ii) motion planning performance, and (iii) practical utilization during execution.

B. Effect of DOF Removal on Orientation Reachability

We first evaluate the effect of removing the wrist-roll joint on IK feasibility for orientation-constrained tasks. At the fixed

TABLE V
IK FEASIBILITY COMPARISON: 5-DOF VS. 6-DOF

Config.	0°	15°	30°	45°	60°	75°	90°	Total
5-DOF (joint removed)	✓	×	×	×	×	×	×	1/7
6-DOF (full)	✓	✓	✓	✓	✓	✓	✓	7/7

TABLE VI
CROSS-CONFIGURATION KINEMATIC COMPATIBILITY ANALYSIS

Evaluation Condition	Poses	Success	Rate
5-DOF → 5-DOF (Self-Reachability)	7339	6908	94.13%
6-DOF → 5-DOF (Cross-Reachability)	7239	0	0.00%

Derived Metric	Value
Shared Kinematic Space	0.00%
Dexterity Expansion (6-DOF vs. 5-DOF)	100.00%

Cartesian position, seven target orientations were defined as roll rotations about the end-effector axis. Table V reports the feasibility results.

The 6-DOF manipulator achieves **complete orientation coverage**, whereas the 5-DOF system is restricted to a single feasible orientation. This limitation is **structural rather than algorithmic**: no IK solution exists for non-zero roll at a fixed position in a chain lacking an independent wrist-roll joint. Removing `joint5_roll` reduces orientation feasibility from **100% to 14.3%**, consistent with the theoretical requirement of six DOF for arbitrary end-effector orientation.

C. Effect of DOF Removal on Motion Planning and Cross-Configuration Capability

To isolate the effect of the additional degree of freedom from planning and environmental constraints, we leverage the cross-configuration pose evaluation defined in Section V. Table VI reports the results.

The 5-DOF system achieves a high IK success rate of 94.13% on its own pose distribution, confirming solver reliability. However, when evaluated on poses generated from the 6-DOF configuration, the success rate drops to 0%, indicating that the 6-DOF manifold lies entirely outside the feasible manifold of the 5-DOF system. The shared kinematic space is effectively zero, and all evaluated poses represent configurations intrinsically unreproducible without the additional degree of freedom.

These observations yield two key insights. **Backward Compatibility:** the 6-DOF system does not exhibit any advantage when restricted to 5-DOF-compatible tasks, confirming that the additional DOF does not artificially inflate performance under equivalent constraints. **Dexterity Expansion:** the 5-DOF system is unable to reproduce any poses generated from the 6-DOF configuration, demonstrating that a substantial portion of the task space is **inherently unreachable** without the wrist-roll joint.

Critically, the observed performance gap is not attributable to planner stochasticity, parameter tuning, or environmental factors. Instead, it arises from a **structural difference in kinematic expressiveness** between the two configurations, consistent with the absence of an independent wrist-roll joint in the 5-DOF chain.

TABLE VII
SUMMARY OF DOF REMOVAL ANALYSIS WITH CROSS-CONFIGURATION METRICS

Metric	6-DOF (Full)	5-DOF (Joint Removed)
IK Feasibility (7 poses)	7/7 (100%)	1/7 (14.3%)
Planning Success (Constrained)	25.0%	0.0%
Self-Reachability (IK Success Rate)	—	94.13%
Cross-Reachability (6→5 DOF)	—	0.00%
Shared Kinematic Space	—	0.00%
Orientation Coverage	Full (±180°)	0° only
Joint Utilization	Active	Absent

D. Mechanism Validation: Joint Utilization Analysis

To verify that the additional degree of freedom is actively exploited—rather than remaining redundant—the distribution of wrist-roll joint values across all successful 6-DOF trajectories was analyzed. The observed distribution spans the full range $[-\pi, +\pi]$, with higher density in regions corresponding to high-roll goal orientations. No successful trajectory maintains a near-zero roll throughout execution, confirming that the planner systematically leverages the additional joint to reorient the end-effector, avoid collisions in constrained geometry, and expand the feasible solution space.

E. Comparison Summary

Table VII consolidates the impact of removing the wrist-roll degree of freedom across all evaluated dimensions.

Removing the wrist-roll joint eliminates feasibility for the tested non-zero-roll orientations and constrained-corridor goals, consistent with the theoretical requirement of six DOF for arbitrary end-effector orientation (Craig [8]; Whitney [9]). These results are consistent with the theoretical necessity of a sixth DOF for orientation-complete manipulation, and demonstrate this necessity empirically within the tested corridor and orientation-reachability protocols.

VII. RESULTS

This section reports all experimental outcomes in the order of the evaluation protocols defined in Section V. Results are organised into three groups: (i) simulation-based kinematic and planning benchmarks, (ii) hardware validation on the physical arm, and (iii) a sim-to-real comparison. Quantitative results are accompanied by confidence intervals and effect-size statistics throughout.

A. Orientation Reachability (IK Feasibility)

Table VIII reports the IK feasibility outcome at the test position $(x, y, z) = (0.20, 0.00, 0.15)$ m for each of the seven pure-roll orientations.

The 5-DOF arm achieves a feasible IK solution only at 0° roll. This is a structural constraint, not an algorithmic limitation: no IK solution exists for non-zero roll at a fixed Cartesian position in a chain lacking an independent wrist-roll joint. The 6-DOF

TABLE VIII
IK FEASIBILITY RESULTS BY ROLL ORIENTATION

Config.	0°	15°	30°	45°	60°	75°	90°	**Total**
5-DOF	✓	×	×	×	×	×	×	1/7
6-DOF	✓	✓	✓	✓	✓	✓	✓	7/7

TABLE IX
CROSS-CONFIGURATION KINEMATIC COMPATIBILITY

Condition	**Arm**	**Poses**	**Solved**	**Rate**
5-DOF → 5-DOF (self)	5-DOF	7339	6908	94.13%
6-DOF → 5-DOF (cross)	5-DOF	7239	0	0.00%
Shared kinematic space				0.00%
Dexterity expansion (6-DOF vs. 5-DOF)				100.00%

arm produces valid configurations at all seven orientations — a 7× improvement in orientation coverage (14.3% → 100%).

B. Cross-Configuration Kinematic Compatibility

Table IX reports IK success rates from the cross-configuration pose transfer evaluation. In total, 7,339 poses drawn from the 5-DOF feasible manifold and 7,239 poses drawn from the 6-DOF manifold were evaluated on both arms.

The 5-DOF arm solves 94.13% of its own poses, confirming solver reliability within its own feasible manifold. When evaluated on 6-DOF poses, the 5-DOF arm achieves 0%, meaning the 6-DOF manifold lies entirely outside the 5-DOF feasible set. Adding the wrist-roll joint expands the reachable orientation manifold to include non-zero-roll poses, which are structurally unreachable by the 5-DOF configuration; the cross-configuration test (Table IX) confirms this expansion empirically.

C. Motion Planning in the Constrained Corridor

Table X reports per-orientation planning outcomes for the narrow corridor environment (corridor width 0.24 m), with 10 RRTConnect trials per goal.

Two results are notable. First, the 0°-roll goal — the only one kinematically reachable by the 5-DOF arm — yields 0% planning success for both arms at this corridor width, establishing that corridor navigation requires orientation variation, not merely IK feasibility. Second, the 6-DOF arm's success is concentrated at high roll angles (60°–90°, 60–80% per goal), where `joint5_roll` aligns the gripper with the corridor walls and opens collision-free approach geometries unavailable at lower roll angles.

The refined larger benchmark (112 trials for 6-DOF, 70 for 5-DOF) confirmed these findings:

- **6-DOF:** 28/112 successes, **25.0%** (95% CI: 17.9%–33.8%).
- **5-DOF:** 0/70 successes, **0.0%** (95% CI: 0.0%–5.2%).

TABLE X
PER-ORIENTATION PLANNING RESULTS — CONSTRAINED CORRIDOR (10 TRIALS PER GOAL, WIDTH 0.24 M)

Goal (Roll)	**Trials**	**Successes**	**Rate**
6-DOF arm			
0°	10	0	0%
15°	10	0	0%
30°	10	0	0%
45°	10	0	0%
60°	10	8	80%
75°	10	7	70%
90°	10	6	60%
6-DOF total	**70**	**21**	**30.0%**
5-DOF arm			
0°	10	0	0%
5-DOF total	**10**	**0**	**0.0%**

TABLE XI
STATISTICAL TEST RESULTS — REFINED BENCHMARK

Statistic	**Value**	**Interpretation**
$\chi^2(1)$	18.81	Test statistic
p-value	1.4×10^{-5}	$\ll 0.05$; highly significant
Cramer's V	0.321	Medium-to-large effect
Cohen's h	1.107	Large effect ($h > 0.8$)
6-DOF rate	25.0%	28/112 trials
6-DOF 95% CI	17.9%–33.8%	Wilson score
5-DOF rate	0.0%	0/70 trials
5-DOF 95% CI	0.0%–5.2%	Wilson score

D. Statistical Analysis


Table XI reports the complete statistical test results for the refined benchmark.

The chi-square test strongly rejects independence between configuration and planning success ($p = 1.4 \times 10^{-5}$). Cramer's $V = 0.321$ indicates a medium-to-large practical effect; Cohen's $h = 1.107$ places the proportional gap firmly in the large-effect category. The non-overlapping Wilson intervals provide visual corroboration independent of the formal test.


E. Workspace Analysis and Joint Utilization

Forward kinematics sampling ($N = 8{,}000$) showed that the 6-DOF arm's positional reachable volume matches the 5-DOF arm's — the added joint contributes orientation flexibility, not positional reach. The corridor test position $(0.20, 0.00, 0.15)$ m was verified to lie in the shared reachable workspace, ruling out positional reachability differences as a confound.

Analysis of the 21 successful 6-DOF trajectories confirmed active utilization of `joint5_roll`: values across all waypoints spanned a broad range with density concentrated in the



(a) Heatmap Analysis



(b) Temporal Trends

Fig. 5. Controller performance and joint tracking accuracy.


$[0.5,\ 1.8]$ rad region (approximately 28°–103°). No successful trajectory kept the joint at zero throughout its execution, confirming the joint is genuinely exploited rather than kinematically passive.

F. Hardware Validation Results

Hardware validation was conducted on the physical retrofitted arm using the protocol defined in Section V. A total of 120 target poses were executed on both the simulation model and the physical arm under identical control pipelines. Table XII reports all hardware validation metrics side by side for simulation and real execution.

Feasibility. Planning feasibility is 100% for both platforms, confirming that all 120 poses are kinematically valid and the controller correctly executes planned trajectories without abort.

Position accuracy. Simulation achieves a mean Euclidean error of 0.0504 mm (essentially numerical precision), while the physical arm achieves 7.85 mm mean error with a maximum of 26.6 mm. Under the strict 5 mm threshold, only 40.0% of physical executions pass, compared to 100% in simulation. This gap is attributable to physical factors absent from the idealised model: joint compliance, Dynamixel gear backlash,



(a) Heatmap Analysis

(b) Temporal Trends

(c) Distribution

Fig. 6. End-effector pose repeatability analysis.

structural flex under gravity loading, and unmodeled friction in the RS-485 daisy-chain transmission.

Regional analysis. Boundary poses achieve a 19.44% strict success rate on physical hardware vs. 48.81% for interior poses. Boundary poses impose higher joint torques and more extended configurations, amplifying the effect of structural compliance and gravity-induced deflection.

Orientation fidelity. 97.5% of physical executions satisfy the 5° constraint, with a mean angular error of only 1.89°. Compared to simulation (0.014°), the angular error is 136× larger in absolute terms, yet it remains sub-2° in magnitude and fails the 5° threshold for only 2.5% of trials. This indicates that `joint5_roll` and the arm's rotational joints track commanded orientations with substantially better fidelity than they achieve Cartesian position.

Repeatability. The mean spatial standard deviation on the real arm is ±1.03 mm. While the absolute value confirms the sim-to-real gap, ±1 mm-class repeatability is broadly consistent with published characterizations of Dynamixel-based manipulators at similar payload and configuration ranges.

Execution time. The physical arm completes trajectories in 6.68 s on average, 2.08 s faster than simulation. This is expected: the simulation includes ROS 2 middleware overhead, trajectory interpolation within MoveIt 2, and visualisation updates absent during physical execution. The execution-time gap is not a performance concern.

G. Summary of Quantitative Outcomes

Table XIII consolidates all primary quantitative results — simulation benchmarks and hardware validation — for direct reference.

VIII. Discussion


A. Three Complementary Lines of Evidence

The results deliver a consistent conclusion through three independent lines of evidence.


Kinematic evidence. The IK feasibility results (Table VIII) demonstrate a 7× improvement in orientation coverage (1/7 →

TABLE XII
HARDWARE VALIDATION METRICS: SIMULATION VS. REAL ROBOT (120 POSES)


Metric	Simulation	Real Robot	Gap
Feasibility and Execution Success			
Sim-to-real feasibility rate	100.0%	100.0%	0.0 pp
Strict position success (<5 mm)	100.0%	40.0%	−60.0 pp
Orientation success (<5°)	100.0%	97.5%	−2.5 pp
Cartesian Position Accuracy			
Mean Euclidean gap	0.0504 mm	7.8490 mm	×156
Max Euclidean gap	0.1490 mm	26.6263 mm	×179
Boundary region mean error	0.0690 mm	8.7966 mm	×127
Interior region mean error	0.0424 mm	7.4429 mm	×176
Boundary success rate (<5 mm)	100.0%	19.44%	−80.6 pp
Interior success rate (<5 mm)	100.0%	48.81%	−51.2 pp
Repeatability and Orientation Fidelity			
Mean spatial std dev (repeatability)	±0.0055 mm	±1.0322 mm	×188
Mean angular error	0.0139°	1.8878°	×136
Kinematic Performance			
Average trajectory execution time	8.761 s	6.681 s	−2.08 s




(a) Heatmap Analysis




(b) Temporal Trends



(c) Distribution



(d) Heatmap (grouped)



(e) Trends (grouped)

Fig. 7. Orientational fidelity analysis.

7/7). This is an exact, planner-independent result: the absence of a wrist-roll joint imposes a hard mathematical constraint on the 5-DOF IK solution manifold. No algorithm can overcome it.

Planning evidence. The improvement from 0.0% to 25.0–30.0% planning success in the constrained corridor translates the kinematic advantage into a task-level benefit. Crucially, even the 0°-roll goal — the only one the 5-DOF arm can reach — yields 0% planning success for the 5-DOF arm in the corridor. The failure is geometric, not kinematic.

Statistical evidence. The chi-square test ($\chi^2(1) = 18.81$, $p = 1.4 \times 10^{-5}$) and effect sizes (Cramer's $V = 0.321$, Cohen's $h = 1.107$) confirm the performance gap is not a sampling artifact. Non-overlapping 95% CIs provide additional visual confirmation.

B. The Role of Wrist-Roll Redundancy

Planning success for the 6-DOF arm peaks at the most demanding orientations (60°–90°, 60–80% per goal) and is zero at the simplest (0°–45°). This counter-intuitive pattern reflects corridor geometry: at high roll angles, `joint5_roll` aligns the gripper approximately parallel to the corridor walls, reducing the effective distal cross-section and opening collision-free approach trajectories that are geometrically blocked when the gripper is perpendicular to the walls. This result articulates a broader principle: the practical value of kinematic redundancy is task- and environment-specific. It is highest precisely where the baseline system has no alternative approach geometry available.

C. Dexterity Expansion and Kinematic Separability

The cross-configuration test (Table IX) yields a shared kinematic space of 0% and dexterity expansion of 100%: the 6-DOF and 5-DOF feasible manifolds are entirely disjoint in the evaluated orientation space. Adding the wrist-roll joint

TABLE XIII
COMPLETE SUMMARY OF QUANTITATIVE RESULTS

Metric	5-DOF (Joint Removed)	6-DOF (Full)	Note
Simulation — Kinematic and Planning			
IK feasibility (7 orientations)	1/7 (14.3%)	7/7 (100%)	Structurally exact
Cross-config. IK (6-DOF → 5-DOF)	0/7239 (0.0%)	—	100% dexterity expansion
Planning success (initial)	0/10 (0.0%)	21/70 (30.0%)	$\chi^2 = 4.2$, $p = 0.04$
Planning success (refined)	0/70 (0.0%)	28/112 (25.0%)	$\chi^2 = 18.81$, $p < 0.00002$
Planning 95% CI	0.0%–5.2%	17.9%–33.8%	Non-overlapping
Cramer's V	0.321 (medium-to-large)		—
Cohen's h	1.107 (large, $h > 0.8$)		—
Orientation coverage	0° only	Full $\pm 180^\circ$	—
Hardware Validation — 6-DOF Physical Arm (120 poses)			
Planning feasibility	—	100.0%	Sim and real
Strict position success (<5 mm)	—	40.0%	Real; 100% in sim
Orientation success ($<5^\circ$)	—	97.5%	Real; 100% in sim
Mean Cartesian error	—	7.85 mm	Real; 0.05 mm in sim
Repeatability (σ)	—	± 1.03 mm	Real; ± 0.006 mm in sim
Mean angular error	—	1.89°	Real; 0.014° in sim

expands the reachable orientation manifold to include non-zero-roll poses, which are structurally unreachable by the 5-DOF configuration; the cross-configuration test (Table IX) confirms this expansion empirically. Within the tested orientation and corridor conditions, the retrofit expands the feasible task space rather than incrementally improving performance on an already-shared task set.

D. Sim-to-Real Analysis

The hardware validation results (Table XII) reveal a nuanced sim-to-real profile that distinguishes between position accuracy and orientation fidelity.

Position accuracy gap is significant. The mean Cartesian error increases from 0.05 mm in simulation to 7.85 mm on the physical arm — a factor of $\sim$156. Under the 5 mm strict threshold, the physical success rate falls from 100% to 40.0%. The primary contributors are Dynamixel gear backlash and structural compliance that accumulate along the kinematic chain, particularly under gravity loading at extended configurations. Boundary poses, which impose higher joint torques, show substantially lower success rates (19.44%) than interior poses (48.81%), consistent with this interpretation.

Orientation fidelity is preserved. Despite the position accuracy gap, 97.5% of physical executions satisfy the 5° orientation constraint, with a mean angular error of 1.89°. Orientation is controlled primarily by `joint5_roll` (a compact, low-inertia distal joint) and the distal wrist joints, which carry less load and exhibit less compliance than the proximal shoulder and elbow joints. The mechanical advantage of the distal position insulates rotational control from the compliance effects that dominate position error.

Repeatability is adequate. The ± 1.03 mm spatial standard deviation on the physical arm, while $\sim 188\times$ larger than in simulation, falls within the commonly accepted repeatability range for Dynamixel-based platforms of comparable scale. It is sufficient for tasks where orientation alignment matters more than sub-millimetre Cartesian precision.

Execution time. The physical arm completes trajectories 2.08 s faster on average than the simulation (6.68 s vs. 8.76 s). This gap arises from ROS 2 middleware, visualisation, and trajectory interpolation overhead present in simulation but not on hardware, and does not reflect a real-world performance advantage.

Summary of the sim-to-real gap. The gap is real and non-trivial for position accuracy; it is acceptable for orientation accuracy. For applications where the primary benefit of the 6-DOF retrofit is orientation freedom — the stated purpose of this work — the physical arm delivers the capability at an operationally useful level (97.5% orientation success, 1.89° mean error).

E. Practical Implications for Low-Cost Manipulator Design

Within the evaluated orientation-reachability and corridor-planning benchmarks, the additional DOF determines whether the tested goals are reachable at all, rather than merely improving performance on goals reachable by both configurations. Extending this finding to concrete manipulation tasks (e.g., insertion, cap alignment) is left to future work.

Orientation and position are decoupled in practice. The hardware results demonstrate that the wrist-roll joint delivers its primary benefit — orientation control — with high fidelity

even when absolute Cartesian position accuracy is limited by platform compliance.

Low cost and high capability are compatible. The total hardware addition costs approximately 5,599 INR (<$70 USD), both mechanical adapters are 3D-printable, and assembly requires approximately one hour. This yields a 7× expansion in orientation coverage under the tested protocol, suggesting feasibility for orientation-constrained task classes (e.g., insertion, alignment) that remain to be directly validated.

Reproducibility requires a full stack. This work provides URDF/Xacro, `ros2_control`, MoveIt 2, GUI, and benchmarking scripts as open artifacts, enabling other laboratories to replicate both the retrofit and its evaluation with minimal incremental effort.

F. Future Work

- **Closed-loop Cartesian control**: Incorporating a Cartesian position feedback loop — via visual markers or a force-torque sensor — to reduce the physical position error from ∼7.9 mm toward the <5 mm target across all workspace regions.
- **Roll-critical task evaluation**: Benchmarking on tasks that inherently require wrist roll (tube insertion, cap alignment, bolt rotation) to demonstrate operational benefit beyond corridor navigation.
- **Multi-planner benchmarking**: Extension of the MoveIt 2 Benchmark Suite runs to PRM*, LazyPRM, and LBKPIECE to characterise planning improvement across the full planner landscape.
- **Learning pipeline integration**: Integration with imitation learning or reinforcement learning pipelines to demonstrate that the richer $SO(2)$ roll action space enables more capable manipulation policies.

IX. Conclusion

This work presented a systematic retrofit of a 5-DOF manipulator into a 6-DOF system and evaluated its impact through kinematic analysis, motion planning benchmarks, and real-world validation. The results demonstrate that the addition of a wrist-roll joint leads to an expansion of the reachable orientation space, with cross-configuration analysis revealing a complete absence of shared kinematic solutions between the two configurations under the evaluated orientation protocol.

The observed gains reflect an expansion in kinematic expressiveness rather than an incremental performance improvement, indicating feasibility for orientation-constrained goals that are structurally infeasible for the 5-DOF system. These findings illustrate the role of kinematic completeness in constrained manipulation scenarios and motivate further evaluation on concrete task-level benchmarks.

Future work will explore dynamic task execution, optimization of planning strategies, and deployment in more complex real-world environments.

References

[1] ROBOTIS, "OpenMANIPULATOR-X e-manual," https://emanual.robotis.com/docs/en/platform/openmanipulator_x/overview/, 2023, accessed: 2024.

[2] A. Al-Batati *et al.*, "ROS 2-based control and evaluation of low-cost educational manipulators," in *Proc. IEEE Int. Conf. Robotics and Automation (ICRA) Workshop on Accessible Robotics*, 2024.

[3] S. Chitta, I. Sucan, and S. Cousins, "MoveIt!: ROS-based motion planning for mobile manipulation," vol. 19, no. 1, 2012, pp. 18–19.

[4] T. Z. Zhao, V. Kumar, S. Levine, and C. Finn, "Learning fine-grained bimanual manipulation with low-cost hardware," in *Proc. Robotics: Science and Systems (RSS)*, 2023.

[5] Franka Robotics, "Franka emika Panda robot documentation," https://frankaemika.github.io/docs/, 2023, accessed: 2024.

[6] K. Muepu *et al.*, "Toward reproducible low-cost manipulation benchmarks: Lessons from educational platforms," in *Proc. IEEE Int. Conf. Robotics and Automation (ICRA)*, 2025.

[7] A. Norton *et al.*, "Developing affordable, reproducible robotic manipulation platforms for academic research," in *Proc. IEEE/RSJ Int. Conf. Intelligent Robots and Systems (IROS) Workshop*, 2020.

[8] J. J. Craig, *Introduction to Robotics: Mechanics and Control*, 3rd ed. Upper Saddle River, NJ: Pearson Prentice Hall, 2005.

[9] D. E. Whitney, "Resolved motion rate control of manipulators and human prostheses," *IEEE Transactions on Man-Machine Systems*, vol. 10, no. 2, pp. 47–53, 1969.

[10] S. Macenski, T. Foote, B. Gerkey, C. Lalancette, and W. Woodall, "Robot operating system 2: Design, architecture, and uses in the wild," *Science Robotics*, vol. 7, no. 66, p. eabm6074, 2022.

[11] I. A. Sucan, M. Moll, and L. E. Kavraki, "The Open Motion Planning Library," *IEEE Robotics & Automation Magazine*, vol. 19, no. 4, pp. 72–82, 2012.

[12] M. Moll, I. A. Sucan, and L. E. Kavraki, "Planner arena: Online benchmarking for motion planning algorithms," http://plannerarena.org, 2015, accessed: 2024.

[13] D. Berenson, S. S. Srinivasa, and J. J. Kuffner, "Task space regions: A framework for pose-constrained manipulation planning," *International Journal of Robotics Research*, vol. 30, no. 12, pp. 1435–1460, 2011.

[14] T. Yu, D. Quillen, Z. He, R. Julian, K. Hausman, C. Finn, and S. Levine, "Meta-World: A benchmark and evaluation for multi-task and meta reinforcement learning," arXiv:1910.10897, 2019.