Autonomous Driving (Case Study) **Due** Aug 2, 1:59 PM +07 Graded Quiz • 45 min Congratulations! You passed! GRADE Keep Learning 100% TO PASS 80% or higher **Autonomous Driving (Case Study)**

LATEST SUBMISSION GRADE 100% 1. To help you practice strategies for machine learning, in this week we'll present another scenario and ask how you would act. We think this "simulator" of working in a machine learning project will give a task of what leading a machine learning

You are employed by a startup building self-driving cars. You are in charge of detecting road signs (stop sign, pedestrian crossing sign, construction ahead sign) and traffic signals (red and green lights) in images. The goal is to recognize which of these objects appear in each image. As an example, the above image contains a pedestrian crossing sign and red traffic lights

project could be like!

'pedestrian crossing sign" $v^{(i)} =$ 'construction ahead sign" "red traffic light" "green traffic light" Your 100,000 labeled images are taken using the front-facing camera of your car. This is also the distribution of data you care most about doing well on. You think you might be able to get a much larger dataset off the internet, that could be

"stop sign"

helpful for training even if the distribution of internet data is not the same. You are just getting started on this project. What is the first thing you do? Assume each of the steps below would take about an equal amount of time (a few days). Spend a few days checking what is human-level performance for these tasks so that you can get an accurate estimate of Bayes error. Spend a few days getting the internet data, so that you understand better what data is available. data per unit time you can collect.

Spend a few days collecting more data using the front-facing camera of your car, to better understand how much Spend a few days training a basic model and see what mistakes it makes. ✓ Correct As discussed in lecture, applied ML is a highly iterative process. If you train a basic model and carry out error

analysis (see what mistakes it makes) it will help point you in more promising directions. 2. Your goal is to detect road signs (stop sign, pedestrian crossing sign, construction ahead sign) and traffic signals (red and green lights) in images. The goal is to recognize which of these objects appear in each image. You plan to use a deep

neural network with ReLU units in the hidden layers. problem. True/False?

For the output layer, a softmax activation would be a good choice for the output layer because this is a multi-task learning True False

✓ Correct Softmax would be a good choice if one and only one of the possibilities (stop sign, speed bump, pedestrian crossing, green light and red light) was present in each image.

· Each image's labels precisely indicate the presence of any specific road signs and traffic signals or combinations of

Choose the training set to be the 900,000 images from the internet along with 80,000 images from your car's front-

facing camera. The 20,000 remaining images will be split equally in dev and test sets.

3. You are carrying out error analysis and counting up what errors the algorithm makes. Which of these datasets do you

think you should manually go through and carefully examine, one image at a time? 10,000 randomly chosen images 10,000 images on which the algorithm made a mistake 500 randomly chosen images

✓ Correct Focus on images that the algorithm got wrong. Also, 500 is enough to give you a good initial sense of the error statistics. There's probably no need to look at 10,000, which will take a long time. 4. After working on the data for several weeks, your team ends up with the following data: 100,000 labeled images taken using the front-facing camera of your car. 900,000 labeled images of roads downloaded from the internet.

500 images on which the algorithm made a mistake

Because this is a multi-task learning problem, you need to have all your $y^{(i)}$ vectors fully labeled. If one example is equal then the learning algorithm will not be able to use that example. True/False?

✓ Correct As seen in the lecture on multi-task learning, you can compute the cost such that it is not influenced by the fact that some entries haven't been labeled. 5. The distribution of data you care about contains images from your car's front-facing camera; which comes from a different distribution than the images you were able to find and download off the internet. How should you split the dataset into train/dev/test sets?

False

distribution but that it has never seen before. You have a large variance problem because your training error is quite higher than the human-level error. You have a large data-mismatch problem because your model does a lot better on the training-dev set than on the dev set Correct

Correct

answers are also correct or incorrect. We recommend that you spend time reading the feedback for this quiz, to understand what issues that you will want to consider when you are building your own machine learning project.

2.2% would be a reasonable estimate of the minimum amount this windshield wiper could improve performance. 2.2% would be a reasonable estimate of how much this windshield wiper will improve performance. 2.2% would be a reasonable estimate of how much this windshield wiper could worsen performance in the worst

case.

Correct

 So long as the synthesized fog looks realistic to the human eye, you can be confident that the synthesized data is accurately capturing the distribution of real foggy images (or a subset of it), since human vision is very accurate for the problem you're solving. There is little risk of overfitting to the 1,000 pictures of fog so long as you are combining it with a much larger (>>1,000) of clean/non-foggy images. Adding synthesized images that look like real foggy pictures taken from the front-facing camera of your car to

✓ Correct Yes. If the synthesized images look realistic, then the model will just see them as if you had added useful data to identify road signs and traffic signals in a foggy weather. I will very likely help. 11. After working further on the problem, you've decided to correct the incorrectly labeled data on the dev set. Which of these statements do you agree with? (Check all that apply). You do not necessarily need to fix the incorrectly labeled data in the training set, because it's okay for the training

Yes because you want to make sure that your dev and test data come from the same distribution for your What do you tell your colleague? Recommend that she try multi-task learning instead of transfer learning using all the data. She should try using weights pre-trained on your dataset, and fine-tuning further with the yellow-light dataset.

✓ Correct

from the same distribution.

You cannot help her because the distribution of data you have is different from hers, and is also lacking the yellow label. If she has (say) 10,000 images of yellow lights, randomly sample 10,000 images from your dataset and put your and her data together. This prevents your dataset from "swamping" the yellow lights dataset. ✓ Correct Yes. You have trained your model on a huge dataset, and she has a small dataset. Although your labels are

Correct

different, the parameters of your model have been trained to recognize many characteristics of road and traffic images which will be useful for her problem. This is a perfect case for transfer learning, she can start with a model with the same architecture as yours, change what is after the last hidden layer and initialize it with your trained parameters. 13. Another colleague wants to use microphones placed outside the car to better hear if there are other vehicles around you. For example, if there is a police vehicle behind you, you would be able to hear their siren. However, they don't have much to train this audio system. How can you help? significantly less promising. significantly less promising.

probably impossible to use transfer learning or multi-task learning. 14. To recognize red and green lights, you have been using this approach: • (A) Input an image (x) to a neural network and have it directly learn a mapping to make a prediction as to whether there's a red light and/or green light (y). A teammate proposes a different, two-step approach: • (B) In this two-step approach, you would first (i) detect the traffic light in the image (if any), then (ii) determine the color of the illuminated lamp in the traffic light. output end. True/False? True False

✓ Correct 15. Approach A (in the question above) tends to be more promising than approach B if you have a _ Large bias problem. Large training set Multi-task learning problem. Problem with a high Bayes error.

✓ Correct

amount of data.

Mix all the 100,000 images with the 900,000 images you found online. Shuffle everything. Split the 1,000,000 images dataset into 980,000 for the training set, 10,000 for the dev set and 10,000 for the test set. Choose the training set to be the 900,000 images from the internet along with 20,000 images from your car's frontfacing camera. The 80,000 remaining images will be split equally in dev and test sets. Mix all the 100,000 images with the 900,000 images you found online. Shuffle everything. Split the 1,000,000 images dataset into 600,000 for the training set, 200,000 for the dev set and 200,000 for the test set. ✓ Correct Yes. As seen in lecture, it is important that your dev and test set have the closest possible distribution to "real"data. It is also important for the training set to contain enough "real"-data to avoid having a data-mismatch problem. 6. Assume you've finally chosen the following split between of the data: Dataset: Contains: 940,000 images randomly picked from (900,000 internet images + 60,000 car's front-facing camera images) 20,000 images randomly picked from (900,000 internet images + 60,000 car's Trainingfront-facing camera images) Dev 20,000 images from your car's front-facing camera Dev 20,000 images from the car's front-facing camera Test You also know that human-level error on the road sign and traffic signals classification task is around 0.5%. Which of the following are True? (Check all that apply). You have a large variance problem because your model is not generalizing well to data from the same training

Your algorithm overfits the dev set because the error of the dev and test sets are very close. You have a large avoidable-bias problem because your training error is quite a bit higher than the human-level error. ✓ Correct 7. Based on the table from the previous question, a friend thinks that the training data distribution is much easier than the dev/test distribution. What do you think? There's insufficient information to tell if your friend is right or wrong. Your friend is right. (I.e., Bayes error for the training data distribution is probably lower than for the dev/test distribution.) Your friend is wrong. (I.e., Bayes error for the training data distribution is probably higher than for the dev/test distribution.)

both distributions. 8. You decide to focus on the dev set and check by hand what are the errors due to. Here is a table summarizing your discoveries: Overall dev set error 15.3% Errors due to incorrectly labeled data 4.1% Errors due to foggy pictures 8.0% Errors due to rain drops stuck on your car's front-facing camera 2.2% Errors due to other causes 1.0% In this table, 4.1%, 8.0%, etc. are a fraction of the total dev set (not just examples your algorithm mislabeled). For example, about 8.0/15.3 = 52% of your errors are due to foggy pictures. The results from this analysis implies that the team's highest priority should be to bring more foggy pictures into the training set so as to address the 8.0% of errors in that category. True/False? Additional Note: there are subtle concepts to consider with this question, and you may find arguments for why some

True because it is greater than the other error categories added together (8.0 > 4.1 + 2.2 + 1.0).

First start with the sources of error that are least costly to fix.

make the best use of the team's time.

The algorithm does better on the distribution of data it trained on. But you don't know if it's because it trained

on that no distribution or if it really is easier. To get a better sense, measure human-level error separately on

False because it depends on how easy it is to add foggy data. If foggy data is very hard and costly to collect, it might not be worth the team's effort. ✓ Correct correct: feedback: This is the correct answer. You should consider the tradeoff between the data accessibility and potential improvement of your model trained on this additional data. 9. You can buy a specially designed windshield wiper that help wipe off some of the raindrops on the front-facing camera. Based on the table from the previous question, which of the following statements do you agree with? 2.2% would be a reasonable estimate of the maximum amount this windshield wiper could improve performance.

True because it is the largest category of errors. We should always prioritize the largest category of error as this will

10. You decide to use data augmentation to address foggy images. You find 1,000 pictures of fog off the internet, and "add" them to clean images to synthesize foggy days, like this: image from foggy image from synthesized front-facing camera the internet foggy image Which of the following statements do you agree with?

training dataset won't help the model improve because it will introduce avoidable-bias.

Yes. You will probably not improve performance by more than 2.2% by solving the raindrops problem. If your

a specially designed windshield wiper that removes the raindrops.

dataset was infinitely big, 2.2% would be a perfect estimate of the improvement you can achieve by purchasing

set distribution to differ from the dev and test sets. Note that it is important that the dev set and test set have the same distribution. ✓ Correct True, deep learning algorithms are quite robust to having slightly different train and dev distributions. You should correct incorrectly labeled data in the training set as well so as to avoid your training set now being even more different from your dev set. You should also correct the incorrectly labeled data in the test set, so that the dev and test sets continue to come

algorithm to make your team's iterative development process is efficient. You should not correct the incorrectly labeled data in the test set, so that the dev and test sets continue to come from the same distribution. 12. So far your algorithm only recognizes red and green traffic lights. One of your colleagues in the startup is starting to work on recognizing a yellow traffic light. (Some countries call it an orange light rather than a yellow light; we'll use the US convention of calling it yellow.) Images containing yellow lights are quite rare, and she doesn't have enough data to build a good model. She hopes you can help her out using transfer learning.

Transfer learning from your vision dataset could help your colleague get going faster. Multi-task learning seems Multi-task learning from your vision dataset could help your colleague get going faster. Transfer learning seems Either transfer learning or multi-task learning could help our colleague get going faster. Neither transfer learning nor multi-task learning seems promising. Yes. The problem he is trying to solve is quite different from yours. The different dataset structures make it

Between these two, Approach B is more of an end-to-end approach because it has distinct steps for the input end and the Yes. (A) is an end-to-end approach as it maps directly the input (x) to the output (y).

Yes. In many fields, it has been observed that end-to-end learning works better in practice, but requires a large

(fill in the blank). 1 / 1 point

1 / 1 point

1 / 1 point

1/1 point

1 / 1 point

1 / 1 point

1/1 point

Error of the

algorithm:

9.1%

14.3%

14.8%

1/1 point

1 / 1 point





1 / 1 point



1 / 1 point





1 / 1 point

1 / 1 point

