

Unix-like Operating Systems

Exit status, command test, flow control.

Jan Trdlička



Czech Technical University in Prague, Faculty of Information Technology
Department of Computer Systems

Contents

- 1 Exit status
- 2 Command test and `if`
- 3 Loop `for`

Exit status

- What is the exit status?
- What is the meaning of exit status of the following commands?

- ```
PASS=/etc/passwd
grep ^root: "$PASS" ; echo $?
```

- ```
grep ^rooooot: "$PASS" ; echo $?
```

- ```
grep ^root: /etc/foo ; echo $?
```

- ```
~/.bash_history ; echo $?
```

- What is the meaning of exit status of the following commands?

- `winzip ; echo $?`

- `ls -lR / ^C ; echo $?`

Command test and if

- Create a shell script `list1.bash` that requires one argument.
 - If the argument is missing or if there are more arguments, then the script prints the following error and exits with exit status 1.

```
Usage: ./list1.bash directory_name
```

- If the argument is a name of a directory and the directory is readable, then the scripts lists its contents by command `ls -la`. Otherwise the script prints the following error and exits with exit status 2.

```
./list1.bash: "foo" is not readable directory
```

- Change the access permissions of the script by the following command

```
chmod 755 list1.bash
```

- Run the script by the following command

```
./list1.bash
```

Command test and if

Loop for

- Modify previous shell script such that for every regular readable file in the directory it will print file type (output from command file).
- Example of script output

```
$> ../list2.bash /usr/bin/ | head

/usr/bin/[: ELF 64-bit LSB executable, x86-64, version 1 (SYSV), dynamically linked
/usr/bin/411toppm: ELF 64-bit LSB executable, x86-64, version 1 (SYSV), dynamically
/usr/bin/7z: POSIX shell script, ASCII text executable
/usr/bin/7za: POSIX shell script, ASCII text executable
/usr/bin/a2p: ELF 64-bit LSB executable, x86-64, version 1 (SYSV), dynamically
/usr/bin/aa-easyprof: Python script, ASCII text executable
/usr/bin/abs2rel: Lua script, ASCII text executable
/usr/bin/aclocal: awk script, ASCII text
/usr/bin/aclocal-1.13: awk script, ASCII text
/usr/bin/aconnect: ELF 64-bit LSB executable, x86-64, version 1 (SYSV), dynamically
```

Loop for