



Common techniques used in malware

4.12.2023

Jan Rubín

Agenda

- What is obfuscation
 - Common techniques
 - Examples
- What are anti- tricks
 - Common techniques
 - Examples
- How to deal with obfuscation and anti- tricks
 - Hands-on analysis


What is obfuscation?

What is obfuscation?

- Let P be a set of all programs and T a set of transformations such as:
 - $T_i: P \rightarrow P$
- T_i is an obfuscation transformation if and only if:
 - $out(T_i(P_k)) == out(P_k)$
 - Analysis of $T_i(P_k)$ should be *harder* than analysis of P_k
- T_i is considered efficient if the knowledge of $T_i(P_k)$ is equivalent to having a black-box oracle of P_k
- ...

What is obfuscation?

- Let P be a set of all programs a
 - $T_i: P \rightarrow P$
- T_i is an obfuscation transformation
 - $out(T_i(P_k)) == out(P_k)$
 - Analysis of $T_i(P_k)$ should be *hard*
- T_i is considered efficient if the
- ...



having a black-box oracle of P_k

What is obfuscation

- It might be difficult to theoretically (formally) define obfuscation
 - Code/binary transformation which makes analyst's work more difficult
 - Hides the true information
 - Hides the true behavior
- In general – cat and mouse game
 - Malware author creates a new technique
 - Malware researcher analyses the technique and solves the puzzle
 - It is very hard to automate the deobfuscation without any previous manual analysis
- It is also used by the good guys!
 - Protecting industrial secrets, discouraging from attacks, etc.

Common obfuscation techniques

There is no “complete list” of obfuscations

Common obfuscation techniques

There is no “complete list” of obfuscations

- Strings
 - Encryption, hashing, encoding, byte arrays, ...

Common obfuscation techniques

There is no “complete list” of obfuscations

- Strings
 - Encryption, hashing, encoding, byte arrays, ...
- Packers and crypters
 - UPX, custom packers and crypters

Common obfuscation techniques

There is no “complete list” of obfuscations

- Strings
 - Encryption, hashing, encoding, byte arrays, ...
- Packers and crypters
 - UPX, custom packers and crypters
- Opaque predicates
 - Creates a “dead branch” which doesn’t do anything (it is never triggered)
 - Analyst doesn’t know this at first – the predicate can be calculated with a very robust algorithm

Common obfuscation techniques

There is no “complete list” of obfuscations

- Strings
 - Encryption, hashing, encoding, byte arrays, ...
- Packers and crypters
 - UPX, custom packers and crypters
- Opaque predicates
 - Creates a “dead branch” which doesn’t do anything (it is never triggered)
 - Analyst doesn’t know this at first – the predicate can be calculated with a very robust algorithm
- Code virtualizations and protectors
 - VMProtect, ASProtect, Themida, Enigma, ...

Common obfuscation techniques


There is no “complete list” of obfuscations

- Strings
 - Encryption, hashing, encoding, byte arrays, ...
- Packers and crypters
 - UPX, custom packers and crypters
- Opaque predicates
 - Creates a “dead branch” which doesn’t do anything (it is never triggered)
 - Analyst doesn’t know this at first – the predicate can be calculated with a very robust algorithm
- Code virtualizations and protectors
 - VMProtect, ASProtect, Themida, Enigma, ...
- Every technique can be both easy and very hard to solve
 - Depends on the knowledge and sophistication of the author

Common obfuscation techniques

There is no “complete list” of obfuscations

- Strings
 - Encryption, hashing
- Packers and crypters
 - UPX, custom packers
- Opaque predicates
 - Creates a “dead block”
 - Analyst doesn’t know what it does
- Code virtualization
 - VMProtect, ASProtect
- Every technique can be combined
 - Depends on the knowledge and sophistication of the author



Obfuscation examples (1)

Byte arrays

- String obfuscation – byte arrays
 - kernel32.dll
 - CreateFileA
- The string cannot be searched
 - SHIFT+F12
 - Thus, it also has no xrefs

```
mov     bl, 65h ; 'e'
push    eax
mov     [esp+38h+LibFileName], 68h ; 'k'
mov     byte ptr [esp+38h+var_23], bl
mov     byte ptr [esp+38h+var_23+1], 72h ; 'r'
mov     byte ptr [esp+38h+var_23+2], 6Eh ; 'n'
mov     byte ptr [esp+38h+var_23+3], bl
mov     byte ptr [esp+38h+var_1F], 6Ch ; 'l'
mov     byte ptr [esp+38h+var_1F+1], 33h ; '3'
mov     byte ptr [esp+38h+var_1F+2], 32h ; '2'
mov     byte ptr [esp+38h+var_1F+3], 2Eh ; '.'
mov     byte ptr [esp+38h+var_1B], 64h ; 'd'
mov     byte ptr [esp+38h+var_1B+1], 6Ch ; 'l'
mov     byte ptr [esp+38h+var_1B+2], 6Ch ; 'l'
call    ds:LoadLibraryA
lea     ecx, [esp+34h+LibFileName]
push    ecx
push    eax
mov     [esp+3Ch+LibFileName], 43h ; 'C'
mov     byte ptr [esp+3Ch+var_23], 72h ; 'r'
mov     byte ptr [esp+3Ch+var_23+1], bl
mov     byte ptr [esp+3Ch+var_23+2], 61h ; 'a'
mov     byte ptr [esp+3Ch+var_23+3], 74h ; 't'
mov     byte ptr [esp+3Ch+var_1F], bl
mov     byte ptr [esp+3Ch+var_1F+1], 46h ; 'F'
mov     byte ptr [esp+3Ch+var_1F+2], 69h ; 'i'
mov     byte ptr [esp+3Ch+var_1F+3], 6Ch ; 'l'
mov     byte ptr [esp+3Ch+var_1B], bl
mov     byte ptr [esp+3Ch+var_1B+1], 41h ; 'A'
mov     byte ptr [esp+3Ch+var_1B+2], 0
call    ds:GetProcAddress
```

Obfuscation examples (2)

String encoding and execution

```
loc_4013EC:      ; nShowCmd
                push    0
                push    0 ; lpDirectory
                push    offset Parameters ; "-nop -noni -e JABwAHAAaQBkAD0AKABHAGUAd..."
                push    offset File ; "powershell.exe"
                push    offset Operation ; "runas"
                push    0 ; hwnd
                call     ds:ShellExecuteW
                mov     [ebp+ms_exc.registration.TryLevel], 0FFFFFFEh
                push    1D4C0h ; dwMilliseconds
                call     ds:Sleep
```

Parameters:

```
; DATA XREF: _main+90fo
text "UTF-16LE", '-nop -noni -e JABwAHAAaQBkAD0AKABHAGUAdAAtAfCAbQBpA'
text "UTF-16LE", 'E8AYgBqAGUAYwB0ACAAdwBpAG4AMwAyAF8AcABYAG8AYwB1AHMA'
text "UTF-16LE", 'cwAgAC0AZgBpAGwAdAB1AHIAIAAIAFAAcgBvAGMAZQBzAHMASQB'
text "UTF-16LE", 'EAD0AJABQAEkARAAIAcKALgBQAGEAcgB1AG4AdABQAHIAbwBjAG'
text "UTF-16LE", 'UAcwBzAEkARAAKACQAcABwAD0AKABHAGUAdAAtAfCAbQBpAE8AY'
text "UTF-16LE", 'gBqAGUAYwB0ACAAdwBpAG4AMwAyAF8AcABYAG8AYwB1AHMAcwAg'
text "UTF-16LE", 'AC0AZgBpAGwAdAB1AHIAIAAIAFAAcgBvAGMAZQBzAHMASQBzEAD0'
text "UTF-16LE", 'AJABwAHAAaQBkACIAKQAKACQAYQAGAD0AIAbBAFMAeQBzAHQAZQ'
text "UTF-16LE", 'BtAC4ASQBPAc4ARgBpAGwAZQBdAD0A0gBSAGUAYQBkAEEAbABsA'
text "UTF-16LE", 'EIAeQB0AGUAcwA0ACQAcABwAC4AUABhAHQAaAaPAA0AJABhACAA'
text "UTF-16LE", 'PQAgAFsAUwB5AHMAdAB1AG0ALgBUAGUAeAB0AC4ARQBuAGMAbwB'
text "UTF-16LE", 'kAGkAbgBnAF0A0gA6AEeAUwBDAEKASQAUeAcAZQB0AFMAdbYAG'
text "UTF-16LE", 'kAbgBnACgAJABhAFsAMAB4ADEANABDADYANwAuAC4AJABhAC4Ab'
text "UTF-16LE", 'AB1AG4AZwB0AGgAXQApAA0AJABmACAAPQAGAFsAUwB5AHMAdAB1'
text "UTF-16LE", 'AG0ALgBUAGUAeAB0AC4ARQBuAGMAbwBkAGkAbgBnAF0A0gA6AEe'
text "UTF-16LE", 'AUwBDAEKASQAUeAcAZQB0AFMAdbYAGkAbgBnACgAlwBTAHkAcw'
text "UTF-16LE", 'B0AGUAbQAuAEMAbwBuAHYAZQByAHQAXQA6AD0ARgByAG8AbQBcA'
text "UTF-16LE", 'GEAcwB1ADYANABTAHQAcgBpAG4AZwA0ACQAYQApACkACgBpAGUA'
text "UTF-16LE", 'eAAGACQAZgAKAFIAZQBtAG8AdgB1AC0ASQB0AGUAbQAuAGAMoiAOK'
text "UTF-16LE", 'CrAdigJwACABhAHQAaAAgACQAcABwAC4AUABhAHQAaAAKAA==',0
```

- -nop -noni -e
 - NoProfile
 - NonInteractive
 - EncodedCommand
- Base64 encoded script
 - Executes the next stage

```
$ppid=(Get-WmiObject win32_process -filter "ProcessID=$PID").ParentProcessID
$pp=(Get-WmiObject win32_process -filter "ProcessID=$ppid")
$a = [System.IO.File]::ReadAllBytes($pp.Path)
$a = [System.Text.Encoding]::ASCII.GetString($a[0x14C67..$a.length])
$f = [System.Text.Encoding]::ASCII.GetString([System.Convert]::FromBase64String($a))
iex $f
Remove-Item -Path $pp.Path
```

Obfuscation examples (3)

Import by hash

- Very common technique
- Instead of importing the function by name, its hash is used
 - Thus, there is no function name (string) present in the binary
 - For example, VirtualAlloc will be displayed as a “random-looking” number
 - In our example (see next slides), the function wsprintfA has a hash 0DE00957h
 - The author has to manually iterate through all the exports from the DLL and calculate hashes in advance
- Without debugging (or resolving functions manually), the analyst has almost no information which functions are called in the program!
- It is very robust obfuscation if analyst doesn't know how to deobfuscate it

Obfuscation examples (3)

Import by hash

- Very common technique
- Instead of importing the function by name, its hash is used

```
mov     edx, 0DE00957h
mov     ecx, esi
mov     [ebx+254h], esi
call    get_address_from_hash
mov     edx, 0DE2C957h
mov     [ebx+258h], eax
mov     ecx, esi
call    get_address_from_hash
mov     edx, 0BDD2D0D8h
mov     [ebx+25Ch], eax
mov     ecx, esi
call    get_address_from_hash
mov     edx, 0FC12C65Fh
mov     [ebx+260h], eax
mov     ecx, esi
call    get_address_from_hash
mov     [ebx+264h], eax
mov     edx, 0FC10065Fh
mov     ecx, esi
call    get_address_from_hash
mov     ecx, ebx
mov     [ebx+268h], eax
```

```
mov     edi, ecx
mov     [ebp+var_8], edx
xor     edx, edx
mov     eax, [edi+3Ch]
mov     eax, [eax+edi+78h]
add     eax, edi
mov     ecx, [eax+1Ch]
mov     ebx, [eax+20h]
add     ecx, edi
mov     [ebp+var_14], ecx
add     ebx, edi
mov     ecx, [eax+24h]
mov     eax, [eax+18h]
add     ecx, edi
mov     [ebp+var_C], ebx
mov     [ebp+var_10], ecx
mov     [ebp+var_4], eax
test    eax, eax
jz      short loc_40146A
```

```
loc_401433:
mov     esi, [ebx+edx*4]
xor     ebx, ebx
add     esi, edi
mov     cl, [esi]
test    cl, cl
jz      short loc_40145D
```

```
loc_401440:
lea     eax, [ecx-41h]
cmp     al, 19h
ja      short loc_40144A
```

```
add     cl, 20h ; ' '
```

```
loc_40144A:
movsx   eax, cl
xor     ebx, eax
rol     ebx, 0Dh
inc     ebx
inc     esi
mov     cl, [esi]
test    cl, cl
jnz     short loc_401440
```

Obfuscation examples (3)

Import by hash

- Let's deobfuscate the structure by explaining what specific pointers mean
- Deobfuscation process is based on more advanced knowledge of MS internals
- All the information can be found in MSDN in the section "PE format"
 - <https://docs.microsoft.com/en-us/windows/win32/debug/pe-format#export-directory-table>

```

mov     edi, ecx
mov     [ebp+var_8], edx
xor     edx, edx
mov     eax, [edi+3Ch]
mov     eax, [eax+edi+78h]
add     eax, edi
mov     ecx, [eax+1Ch]
mov     ebx, [eax+20h]
add     ecx, edi
mov     [ebp+var_14], ecx
add     ebx, edi
mov     ecx, [eax+24h]
mov     eax, [eax+18h]
add     ecx, edi
mov     [ebp+var_C], ebx
mov     [ebp+var_10], ecx
mov     [ebp+var_4], eax
test    eax, eax
jz      short loc_40146A

```

```

mov     edi, ecx ; EDI - Base
mov     [ebp+var_parametr_hash], edx
xor     edx, edx
mov     eax, [edi+3Ch] ; Offset to PE
mov     eax, [eax+edi+78h] ; RVA to the export directory table
add     eax, edi ; Address of export directory table
mov     ecx, [eax+IMAGE_EXPORT_DIRECTORY.AddressOfFunctions]
mov     ebx, [eax+IMAGE_EXPORT_DIRECTORY.AddressOfNames]
add     ecx, edi
mov     [ebp+var_export_address_table], ecx
add     ebx, edi
mov     ecx, [eax+IMAGE_EXPORT_DIRECTORY.AddressOfNameOrdinals]
mov     eax, [eax+IMAGE_EXPORT_DIRECTORY.NumberOfNames]
add     ecx, edi
mov     [ebp+var_name_pointer_RVA], ebx
mov     [ebp+var_ordinal_table], ecx
mov     [ebp+var_number_of_name_pointers], eax
test    eax, eax
jz      short loc_40146A

```

```

loc_401433:
mov     esi, [ebx+edx*4]
xor     ebx, ebx
add     esi, edi
mov     cl, [esi]
test    cl, cl
jz      short loc_40145D

```

```

loc_401433:          ; esi - RVA of the name of the current function
mov     esi, [ebx+edx*4]
xor     ebx, ebx
add     esi, edi ; esi - pointer to the name of the current function
mov     cl, [esi] ; cl - First character
test    cl, cl
jz      short loc_40145D

```

```

loc_401440:
lea     eax, [ecx-41h]
cmp     al, 19h
ja      short loc_40144A

```

```

loc_401440:
lea     eax, [ecx-41h]
cmp     al, 19h
ja      short loc_40144A

```

```

add     cl, 20h ; ' '

```

```

add     cl, 20h ; ' ' ; Case insensitive

```

```

loc_40144A:
movsx   eax, cl
xor     ebx, eax
rol     ebx, 00h
inc     ebx
inc     esi
mov     cl, [esi]
test    cl, cl
jnz     short loc_401440

```

```


loc_40144A:
movsx   eax, cl
xor     ebx, eax
rol     ebx, 00h
inc     ebx
inc     esi
mov     cl, [esi]
test    cl, cl ; Until null byte
jnz     short loc_401440

```

Obfuscation examples (3)

Import by hash

- We have 2 arrays and 1 table
 - Names of functions
 - Ordinals of functions (uses the same indexing!)
 - Table with function addresses sorted by ordinals
- The function address is returned as a “cascade” of three queries
 - Get the index of the matched function by name
 - Use this index to get the ordinal
 - Use the ordinal to get the function offset



Obfuscation examples (3)

Import by hash

- In practice, we want to see this information without the need of debugging the sample every time
 - However, to get this information, we need to debug the program at least once to fill all the fields from the hashing algorithm (or reimplement the algorithm and calculate the values manually)
- How to do it in IDA:
 - Debug the function so all the correct addresses are returned
 - Select the resolved and saved addresses in memory
 - We know which these are, they are saved every time by the malware, e.g. [ebx+25Ch]
 - (Optionally) Run a native IDA script `%IDA%\idc\renimp.idc`
 - Renames entries of a dynamically built import table (beautifies the resolved addresses)

```
mov     edx, 0DE2C957h  
[ebx+25Ch]  
mov     ecx, esi  
call    get_address_from_hash  
[ebx+25Ch]  
mov     [ebx+25Ch], eax
```

```
00C0FEA8 dd offset kernel32_GetFileSize  
00C0FEAC dd offset kernel32_CreateFileMappingA  
00C0FEB0 dd offset kernel32_MapViewOfFile
```



```
00C0FEA8 ; DWORD (__stdcall *GetFileSize)(HANDLE hFile, LPDWORD lpFileSizeHigh)  
00C0FEA8 GetFileSize dd offset kernel32_GetFileSize  
00C0FEAC ; HANDLE (__stdcall *CreateFileMappingA)(HANDLE hFile, LPSECURITY_ATTRIBUTES lpFileMappingAttributes,  
00C0FEAC CreateFileMappingA dd offset kernel32_CreateFileMappingA  
00C0FEB0 ; LPVOID (__stdcall *MapViewOfFile)(HANDLE hFileMappingObject, DWORD dwDesiredAccess, DWORD dwFileOff  
00C0FEB0 MapViewOfFile dd offset kernel32_MapViewOfFile
```

- We can now select these resolved names once again and create a structure from them
 - “Create structure from selection”
- Apply the structure (press “t”) to every [ebx+offset] to see the function names
- Debugger -> Take memory snapshot -> Loader segments

Obfuscation examples (3)

Import by hash

```
mov     edx, 0DE00957h
mov     ecx, esi
mov     [ebx+254h], esi
call    get_address_from_hash
mov     edx, 0DE2C957h
mov     [ebx+258h], eax
mov     ecx, esi
call    get_address_from_hash
mov     edx, 0BDD2D0D8h
mov     [ebx+25Ch], eax
mov     ecx, esi
call    get_address_from_hash
mov     edx, 0FC12C65Fh
mov     [ebx+260h], eax
mov     ecx, esi
call    get_address_from_hash
mov     [ebx+264h], eax
mov     edx, 0FC10065Fh
mov     ecx, esi
call    get_address_from_hash
mov     ecx, ebx
mov     [ebx+268h], eax
```

```
mov     edx, 0DE00957h
mov     ecx, esi
mov     [ebx+struct_0.user32], esi
call    get_address_from_hash
mov     edx, 0DE2C957h
mov     [ebx+struct_0.wsprintfA], eax
mov     ecx, esi
call    get_address_from_hash
mov     edx, 0BDD2D0D8h
mov     [ebx+struct_0.wsprintfW], eax
mov     ecx, esi
call    get_address_from_hash
mov     edx, 0FC12C65Fh
mov     [ebx+struct_0.GetDesktopWindow], eax
mov     ecx, esi
call    get_address_from_hash
mov     [ebx+struct_0.MessageBoxA], eax
mov     edx, 0FC10065Fh
mov     ecx, esi
call    get_address_from_hash
mov     ecx, ebx
mov     [ebx+struct_0.MessageBoxW], eax
```

- Additional useful information can be found on MSDN
 - <https://docs.microsoft.com/en-us/windows/win32/debug/pe-format#export-directory-table>

Obfuscation examples (4)


VMProtect

- VMProtected coinminer

Obfuscation examples (4)

VM

- VI




```
004013A2 in: 1 out: 15
004013A2 50      push eax
004013A3 c88c000000 call 0x401434
00401434 55      push ebp
00401435 8bec    mov ebp, esp
00401437 81ccc8010000 sub esp, 0x1c8
0040143D a108244500 mov eax, dword ptr [0x452408]
00401442 53      push ebx
00401443 56      push esi
00401444 8b7508    mov esi, dword ptr [ebp + 8]
00401447 57      push edi
00401448 6a07    push 7
0040144A 59      pop ecx
0040144B 8d7dd4    lea edi, dword ptr [ebp - 0x2c]
0040144E 8945f8    mov dword ptr [ebp - 8], eax
00401451 33db      xor ebx, ebx
00401453 f3a5      rep movsd dword ptr es:[edi], dword ptr [esi]
00401455 8b45d8    mov eax, dword ptr [ebp - 0x28]
00401458 8b55dc    mov edx, dword ptr [ebp - 0x24]
0040145B 8bf0      mov esi, eax
0040145D 8bfa      mov edi, edx
0040145F c1e60d    shl esi, 0xd
00401462 b900304500 mov ecx, 0x453000
00401467 895dfc    mov dword ptr [ebp - 4], ebx
0040146A c1e70d    shl edi, 0xd
0040146D 03f1      add esi, ecx
0040146F 03f9      add edi, ecx
00401471 8d4dd8    lea ecx, dword ptr [ebp - 0x28]
00401474 890d54441000 mov dword ptr [0x414454], ecx
0040147A 8b4dd4    mov ecx, dword ptr [ebp - 0x2c]
0040147D 83c1fe    add ecx, -2
00401480 83f941    cmp ecx, 0x41
00401483 087cc1400000 ja 0x402957
00401489 ff248d69294000 jmp dword ptr [ecx*4 + 0x402969]
```


Obfusca

VMProtect

- VMProtected



Obfusca

VMProtect

- VMProtected



Obfuscation examples (5)


Psychological warfare

- <https://github.com/xoreaxeaxeax/REpsych>

Obfuscation examples (5)

Psychological warfare


- <https://github.com/xoreaxeaxeax/REpsych>



Obfuscation examples (5)

Psychological warfare


- <https://github.com/xoreaxeaxeax/REpsych>



Obfuscation examples (5)

Psychological warfare

- <https://github.com/xoreaxeaxeax/REpsych>




Obfuscation examples (5)

Psychological warfare

- <https://github.com/xoreaxeaxeax/REpsych>

```
lea     ecx, [eax+ebx*4]          mul
movzx   eax, bh                  movzx
jz      e_24_26                  jz


e_24_25:                          e_24_
v7readsub132ps xmm0, xmm1, xmmword ptr cs:[edi+esi*4+805E0B4h] v7read
805E0B4h]                         lea
shl     ebx, 12h                 mul
add     ebx, ecx                 movzx
movzx   eax, bh                 sub
mov     al, 0                    mov
lea     eax, [ecx+edx*4]          movzx
lea     eax, [ecx+edx*4]          movzx
movzx   ecx, dh                 shl
dec     ecx                     lea
shr     eax, 1                   sub
mov     eax, 4BA23077h           shl
shl     edx, 8                   lea
test    edx, eax                lea
lea     eax, [ecx+edx*4]          add
movzx   ecx, dh                 movzx
lea     ebx, [ecx+ecx]           mul
shr     eax, 9                   test
mov     eax, 8C317A9Bh           and
or      eax, 8A686D6Fh           movzx
mul     eax                      lea
lea     edx, [ebp+0Ch]           movzx
mov     ch, 6                    mul
movzx   eax, bh                 shr
lea     edx, [eax+eax]           shl
lea     edx, [ebp+0Ch]           lea
dec     ecx                     add
movzx   eax, bl                 shr
jz      e_25_26                  jz
```



Obfuscation examples (5)

Psychological warfare

- <https://github.com/xoreaxeaxeax/REpsych>



Anti- tricks

- The most common categories:
 - Anti-VM
 - Anti-Debug
 - Anti-Emulation

Anti- tricks

- The most common categories:
 - Anti-VM
 - Anti-Debug
 - Anti-Emulation
- Analyst uses anti-anti- tricks to counter anti- tricks

Anti- tricks

- The most common categories:
 - Anti-VM
 - Anti-Debug
 - Anti-Emulation
- Analyst uses anti-anti- tricks to counter anti- tricks



Anti- tricks

- The most common categories:
 - Anti-VM
 - Anti-Debug
 - Anti-Emulation
- Analyst uses anti-anti- tricks to counter anti- tricks
- Depending on the anti- trick, some steps can be performed:
 - Simply skip the problematic part while debugging (CTRL+N changes EIP)
 - Patch the binary
 - Modify registers (function parameters or return values)
 - Change the dependency/configuration files
 - ...

Anti-VM example

Checks on `cpuid`

- Input parameter: EAX
 - EAX=1 will request the processor information (= signature of the CPU)
- Outputs:
 - EDX
 - ECX – this is what we want
 - EBX
- We are interested in the most significant bit of the ECX register
 - So called the **Hypervisor bit**
 - Set as 1 if it is VM
 - Set as 0 otherwise
- More info: <https://en.wikipedia.org/wiki/CPUID>

```
_EAX = 1;  
__asm { cpuid }  
return _ECX >> 0x1F;
```

Anti-Debug examples

Many, many methods exist

- GetTickCount, timestamping
- API hammering
- Checking for specific processes
- Throwing exceptions
- Multi-threading
- Attaching own debugger
- ...


Anti-Debug examples

Detecting analyst's tools

```
loc_4602D3:
mov     byte ptr [ebp-1A51h], 0
xor     edi, edi
mov     dword ptr [ebp-1A40h], offset aTaskmgrExe ; "taskmgr.exe"
mov     dword ptr [ebp-1A3Ch], offset aProcexpExe ; "procexp.exe"
mov     dword ptr [ebp-1A38h], offset aProcexp64Exe ; "procexp64.exe"
mov     dword ptr [ebp-1A34h], offset aProcess Hacker ; "processhacker.exe"
mov     dword ptr [ebp-1A30h], offset aProcmonExe ; "procmon.exe"
mov     dword ptr [ebp-1A2Ch], offset aWiresharkExe ; "wireshark.exe"
mov     dword ptr [ebp-1A28h], offset aVncExe ; "vnc.exe"
mov     dword ptr [ebp-1A24h], offset aAnvirExe ; "anvir.exe"
nop     dword ptr [eax+00h]
```

- Malware periodically scans running processes or opened windows
 - In a separate thread
- When any such activity is detected, malware stops/hides its malicious functionality

```
push    100h
push    eax
push    offset aUsername ; "%USERNAME%"
call    esi
push    100h
lea     eax, [ebp-418h]
push    eax
push    offset aComputername ; "%COMPUTERNAME%"
call    esi
mov     esi, ds:wsprintfW
lea     eax, [ebp-218h]
push    eax
lea     eax, [ebp-418h]
push    eax
lea     eax, [ebp-1270h]
push    offset aProcess Hacker [%s\\%s]
push    eax ; LPWSTR
call    esi ; wsprintfW
lea     eax, [ebp-218h]
push    eax
lea     eax, [ebp-418h]
push    eax
lea     eax, [ebp-1A20h]
push    offset aProcess HackerS_0 ; "Process Hacker [%s\\%s]+ (Administrator"...
push    eax ; LPWSTR
call    esi ; wsprintfW
lea     eax, [ebp-218h]
push    eax
lea     eax, [ebp-418h]
push    eax
lea     eax, [ebp-0AC0h]
push    offset aProcess Explorer ; "Process Explorer - Sysinternals: www.sy"...
push    eax ; LPWSTR
call    esi ; wsprintfW
mov     esi, ds:FindWindowW
lea     eax, [ebp-1270h]
add     esp, 30h
push    eax ; lpWindowName
push    0 ; lpClassName
call    esi ; FindWindowW
test    eax, eax
jnz     short loc_460419
```



```
lea     eax, [ebp-1A20h]
push    eax
push    0
call    esi ; FindWindowW
test    eax, eax
```

Anti-Emulation examples

- Using a huge number of instructions in the code
 - Emulated code is (much) slower
- API hammering
- Using “uncommon” API calls that are not implemented in the emulator
 - Emulator will usually return some kind of default value
 - Malware can expect different value
 - Not all API functions are even documented on MSDN!


Practical example



GandCrab's crypter

- Let's analyze one of the most notorious ransomwares – **GandCrab**
 - First observed around January 2018
 - Author(s) claim they earned \$2 billion dollars
 - Very hard to estimate the actual amount, they are most likely lying
 - The malware group announced a shut down of their operations (May 31st, 2019)
 - Shifted their focus on developing new malware
 - Sodinokibi ransomware (REvil)
- Let's focus on the obstacles the author(s) implemented
 - `ea4c6d2ca13c2f09468e8be10d931c46bcec8964b2db6b9ba224a45f367e655d *sample_gandcrab.dat`

Practical example

GandCrab's crypter

- Let's analyze one of the most notorious
 - First observed around January 2018
 - Author(s) claim they earned \$2 billion dollars
 - Very hard to estimate the actual amount, they are
 - The malware group announced a shutdown
 - Shifted their focus on developing new malware
 - Sodinokibi ransomware (REvil)
- Let's focus on the obstacles the author(s) faced
 - `ea4c6d2ca13c2f09468e8be10d931c46bcecd`  Avast Threat Labs



Practical example

Used tools

- IDA Free
- CFF Explorer
- HxD

Practical example

Used IDA shortcuts

Shortcut	Functionality
N	Rename
X	Show cross-references
R	Convert to ASCII (if possible)
H	Convert Hex <-> Dec
O	Convert to offset
?	Evaluate expression
U	Undefine data blob/code
?	Declare a function with parameters

Shortcut	Functionality
CTRL+N	Change EIP to cursor's address
F2	Set a breakpoint
F9/F4	Run program/Run program until cursor
F7/F8	Step into/Step over

Shortcut	Functionality
ALT+M	Create an address bookmark
CTRL+M	Show existing address bookmarks
ALT+S	Set segment attributes
ALT+L	Select area
CTRL+S	Choose segment
SHIFT+E	Export data/dump bytes to disk

“Homework”

- Download a crackme from Course Pages or come to my desk after this presentation
 - 172237b73a3c52b3238330273ba4a7a3ae92fa22b8bf0fee4d5403b7c553dddb *itsaunixsystem.exe
- Solve the crackme and send me your solution
 - rubinjan+rev@protonmail.com
- Don't forget to attach your CV :-)

Thank you!

Jan Rubín

Malware Researcher

jan.rubin@gendigital.com

rubinjan@protonmail.com



[@JanRubin](https://twitter.com/JanRubin)



[@JanRubin](https://github.com/JanRubin)

www.avast.com

www.gendigital.com

Gen™

GenDigital.com