

```

1  # Main Loop
2  initial_sketch = lean_compiler.check(initial_file)
3  population.initialize(initial_sketch)
4  launch prover_subagents(N, population) # Create prover agents
5  launch rater_subagents(M, population) # Create rater agents
6  await population.contains_sorry_free_proof()
7
8  # Prover subagent, run asynchronously
9  def prover_step(sketch):
10     session = LlmSketcher(sketch) # Start an LLM session
11     while tool_call := session.recv():
12         if tool_call.is_alphaproof(): # Call AlphaProof
13             proofs = [alphaproof.solve(g) for g in unsolved_goals(sketch)]
14             sketch, feedback = incorporate_proofs(proofs, sketch)
15         elif tool_call.is_search_replace(): # Call search-and-replace
16             sketch, feedback = search_replace_then_compile(sketch, tool_call)
17             session.send(feedback)
18     if lean_compiler.verify_integrity(sketch): # Check for hacks
19         population.add(sketch)
20         return not sketch.contains_sorry()
21     return False
22
23  def prover_subagent():
24     while within_budget():
25         sketch = population.sample(strategy=p_uct) # Sample a sketch
26         if prover_step(sketch):
27             break
28
29  # Rater agent, run asynchronously
30  def rater_subagent():
31     s1, ..., sP = sketch_db.get_sketches_for_ranking()
32     ranks = llm_rater.rank(s1, ..., sP)
33     sketch_db.update_elo(ranks)

```