


腾讯云数据库 TDSQL MySQL 版 分布式 V10.3.22.8/集中式 V8.0.22.8

错误信息参考



文档版本: 发布日期:

版权声明

本文档著作权归腾讯云计算(北京)有限责任公司(以下简称"腾讯云")单独所有,未经腾讯云事先书面许可,任何主体不得以任何方式或理由使用本文档,包括但不限于复制、修改、传播、公开、剽窃全部或部分本文档内容。

本文档及其所含内容均属腾讯云内部资料,并且仅供腾讯云指定的主体查看。如果您非经腾讯云授权而获得本文档的全部或部分内容,敬请予以删除,切勿以复制、披露、传播等任何方式使用本文档或其任何内容,亦请切勿依本文档或其任何内容而采取任何行动。

商标声明

Tencent 腾讯



"腾讯"、"腾讯云"及其它腾讯云服务相关的商标、标识等均为腾讯云及其关联公司各自所有。若本文档涉及第三方主体的商标,则应依法由其权利人所有。

免责声明

本文档旨在向客户介绍本文档撰写时,腾讯云相关产品、服务的当时的整体概况,部分产品或服务在后续可能因技术调整或项目设计等任何原因,导致其服务内容、标准等有所调整。因此,本文档仅供参考,腾讯云不对其准确性、适用性或完整性等做任何保证。您所购买、使用的腾讯云产品、服务的种类、内容、服务标准等,应以您和腾讯云之间签署的合同约定为准,除非双方另有约定,否则,腾讯云对本文档内容不做任何明示或默示的承诺或保证。

修订记录

文档版本 发布日期 修订人 修订内容

目录

修订记录ii
目录iii
前言iv
1 Proxy 错误信息参考1
2 DB 错误信息参考12
2.1 错误码及错误信息汇总 0113
2.2 错误码及错误信息汇总 02
2.3 错误码及错误信息汇总 0362
2.4 错误码及错误信息汇总 04
2.5 错误码及错误信息汇总 05136
2.6 错误码及错误信息汇总 06169
2.7 错误码及错误信息汇总 07199
2.8 错误码及错误信息汇总 08
2.9 错误码及错误信息汇总 09272
2.10 错误码及错误信息汇总 10
2.11 错误码及错误信息汇总 11
2.12 错误码及错误信息汇总 12
2.13 错误码及错误信息汇总 13410
3 赤兔管理系统错误信息参考427

错误信息参考 前言

前言

文档目的

本文档用于帮助用户掌握云产品的操作方法与注意事项。

目标读者

本文档主要适用于如下对象群体:

- 客户
- 交付 PM
- 交付技术架构师
- 交付工程师
- 产品交付架构师
- 研发工程师
- 运维工程师

符号约定

本文档中可能采用的符号约定如下:

符号	说明
① 说明:	表示是正文的附加信息,是对正文的强调和补充。
⚠ 注意:	表示有低度的潜在风险,主要是用户必读或较关键信息,若用户忽略注意消息,可能会因误操作而带来一定的不良后果或者无法成功操作。
♀ 警告:	表示有中度的潜在风险,例如用户应注意的高危操作,如果忽视这些文本,可能导致设备损坏、数据丢失、设备性能降低或不可预知的结果。
❷ 禁止:	表示有高度潜在危险,例如用户应注意的禁用操作,如果不能避免,会导致系统崩溃、数据丢失且无法修复等严重问题。

1 Proxy 错误信息参考

错误 码	错误信息	详解/处理方案	事务状态	分类
600	ER_PROXY_GRAM_ERROR_BEGIN	语法错误的起始错 误,内部使用		系统 相关
601	ER_PROXY_SANITY_ERROR	语句执行时完整性检查失败,例如: db name is too long		语法 相关
602	ER_PROXY_SQL_TYPE_NOT_SUPP ORT	sql 类型不支持		语法 相关
603	ER_PROXY_ORDERBY_INDEX_NE G	使用序列方式排序 时,传入为负值		语法 相关
604	ER_PROXY_SQL_NOT_SUPPORT_ ORDERBY_2	内部使用,目前无效		语法 相关
605	ER_PROXY_ORDERBY_INDEX_TO O_BIG	使用序列方式排序 时,传入为值大于列 数量		语法 相关
606	ER_PROXY_GROUPBY_INDEX_NE G	使用序列方式分组 时,传入为负值		语法 相关
607	ER_PROXY_GROUPBY_INDEX_TO O_BIG	使用序列方式分组 时,传入为值大于列 数量		语法 相关
608	ER_PROXY_GROUPBY_TYPE_UNS UPPORT	不支持的 group by 用法		语法 相关
609	ER_PROXY_GET_AUTO_ID_FAILE D	获取 autoinc 值失败		执行 相关
610	ER_PROXY_TEANS_ROLLED_BAC K	事务已经被回滚	回滚	事务 相关
611	ER_PROXY_ONE_SET	应该被发往一个后端 sql 发往了多个后端 server		执行 相关

612	ER_PROXY_CLIENT_HS_ERROR	解析客户端握手包出错		系统 相关
613	ER_PROXY_ACCESS_DENIED_ER ROR	链接 MYSQL 时,加密的密码长度错误		语法 相关
614	ER_PROXY_TRANS_NOT_ALLOW ED	事务中不允许执行的命令	不影响事 务,需检 查业务逻 辑	事务相关
615	ER_PROXY_TRANS_READ_ONLY	只读事务中不允许执 行的命令	不影响事 务,需检 查业务逻 辑	事务 相关
616	ER_PROXY_TRANS_ERROR_DIFFE NT_SET	非 xa 事务中,只读 sql 使用了多个后端	不影响事 务,需检 查业务逻 辑	事务相关
617	ER_PROXY_STRICT_ERROR	strict 模式下,一次仅 允许修改一个 set		执行 相关
618	ER_PROXY_SC_TOO_LONG	后端断开时间过长, 断开链接		系统 相关
619	ER_PROXY_START_TRANS_FAILE D	开启新的 xa 事务失败	不影响事	事务 相关
620	ER_PROXY_SC_RETRY	DB与PROXY断连,但是此时事务正在处于commit或者rollback状态,业务需要重复执行xacommit或者xarollback。也就是重试上一条sql。业务使用xabegin;xaend;会出现该错误码,不建议使用该模式。	状态未知	事务相关
621	ER_PROXY_SC_TRANS_IN_ROLLB ACK_ONLY	DB 和 PROXY 断连, 当前事务处于 rollback 状态,只能发	回滚	事务相关

		送 rollback 处理。业 务使用 xa begin; xa end;会出现该错误 码,不建议使用该模 式。		
622	ER_PROXY_SC_COMMIT_LATER	DB与PROXY断连, 事务将会提交(agent 将会补提交,需要等 待n秒,具体看 agent 配置)	提交	事务 相关
623	ER_PROXY_SC_ROLLBACL_LATE R	DB与PROXY断连, 事务会回滚。事务在 等待一定的时候内, 会回滚,该时间配置 在 agent 配置中 (<xa>标签)。业务 需要等待,不需要处 理该错误。</xa>	回滚	事务 相关
624	ER_PROXY_SC_IN_COMMIT_OR_ ROLLBACK	DB与PROXY断连, 当前事务状态未知。 需要业务介入处理	状态未知	事务相关
625	ER_PROXY_SC_NEED_ROLLBACK	server 已经 close,需要回滚当前事务	需要检查,手动 回滚	事务相关
626	ER_PROXY_SC_STATE_WILL_ROL LBACK	server 已经 close,当 前事务回滚	回滚	事务相关
627	ER_PROXY_XA_UNSUPPORT	xa 目前不支持的命令		语法 相关
628	ER_PROXY_XA_INVALID_COMM AND	xa 命令不合法		语法 相关
629	ER_PROXY_XA_GTID_INIT_ERRO R	gtid log 初始化失败	不影响事务	事务相关
630	ER_PROXY_XA_GET_SET_IP_POR T_FAILED	获取 set 地址失败		执行 相关
631	ER_PROXY_XA_UPDATE_GTID_L OG_FAILED	更新 gtid log 失败	不影响事	事务 相关

632	ER_PROXY_MYSQL_PARSER_ERR OR	mysql 解析失败,返 回详细错误信息	语法 相关
633	ER_PROXY_ILLEGAL_ID	kill id 不合法	执行
033	EK_FROXT_ILLEGAL_ID	KIII IQ 小台法	相关
634	ER_PROXY_NOT_SUPPORT_CURS	暂不支持游标	语法
034	OR	省个义分册你	
635	ER PROXY UNKNOWN PREPARE	为 5 的 2000 不明确	相关 执行
033	_HANDLER	执行的 prepare 不明确	相关
636	ER_PROXY_SET_PARA_FAIL	Prepared_statement 传	执行
		参失败	相关
637	ER_PROXY_SUBPARTITION_DEA	只能更新一个	语法
	Y	subpartition 表,或	相关
		noshard 表和 global 表	
		混用	
638	ER_PROXY_NO_SUBPARTITION_R	没有获取到二级分区	执行
	OUTE	表的路由信息	相关
639	ER_PROXY_LOCK_MORE_TABLE	一次只可以锁定一张	执行
		二级分区表	相关
640	ER_PROXY_GET_ROUTER_LOCK_	获取路由锁失败	执行
	FAIL		相关
641	ER_PROXY_PART_NAME_EMPTY	分区名为空	执行
			相关
642	ER_PROXY_SUB_PART_TABLE_IS	没有二级分区表	执行
	_NONE		相关
643	ER_PROXY_PART_TYPE_DENY	表现有分区类型与	执行
		alter 分区类型不符	相关
644	ER_PROXY_PART_NAME_ILLEGA	分区名不合法	执行
	L		相关
645	ER_PROXY_DROP_ALL_PARTITIO	删除所有分区失败,	执行
	N_FAIL	尝试直接删除表	相关
646	ER_PROXY_GET_OLD_PART_NUM	获取表的分片数失败	执行
	_FAIL		相关
647	ER_PROXY_EMPTY_SQL	empty sql,不会返回	语法
		给客户端	相关
648	ER_PROXY_ERROR_SHARDKEY	shardkey 必须为某一	执行
		列	相关

649	ER_PROXY_ERROR_SUB_SHARDK EY	二级分表键错误		执行 相关
650	ER_PROXY_SQLUSE_NOT_SUPPO RT	proxy 不支持当前语 法		语法 相关
651	ER_PROXY_DBFW_WHITE_LIST_ DENY	被 sql 防火墙白名单 拦截		执行 相关
652	ER_PROXY_DBFW_DENY	被防火墙拦截		执行 相关
653	ER_PROXY_INCORRECT_ARGS	stmt 参数不正确		语法 相关
654	ER_PROXY_SYSTABLE_UNSUPPO RT_NON_READ_SQL	不支持非只读 sql 访问系统表		执行 相关
655	ER_PROXY_INVALID_ARG_FOR_ GTID_STATE	gtid_state() 参数不合 法,内部使用	不影响事	事务相关
656	ER_PROXY_SHARD_JOIN_UNSUPP ORT_TYPE	shard join 暂不支持的 用法		语法 相关
657	ER_PROXY_RECURSIVE_JOIN_DE NY	递归 join 不支持		语法 相关
658	ER_PROXY_JOIN_INTERNAL_ERR OR	join 异常		执行 相关
659	ER_PROXY_SQL_TOO_COMPLEX	sql 太复杂, groupshard 暂不支持		语法 相关
660	ER_PROXY_TABLE_NOT_EXIST	表不存在		执行 相关
661	ER_PROXY_CANT_SET_GLOBAL_ AUTOCOMMIT_GS	groupshard 中配置全 局 auto commit 失败	不影响事务	事务相关
662	ER_PROXY_INVALID_VALUE_FO R_AUTOCOMMIT	autocommit		语法 相关
663	ER_PROXY_XID_ERROR	xid 不合法	不影响事	事务 相关
664	ER_PROXY_XID_GENERAT_FAILE	xid 不能由用户指定	不影响事	事务

	D		务	相关
665	ER_PROXY_CANT_EXEC_IN_INTE R_TRANS	命令不能在事务内部执行	不影响事 务,需检 查业务逻 辑	事务相关
666	ER_PROXY_XID_TIME_ERROR	全局事务时间戳检查 失败	不影响事务	事务 相关
667	ER_PROXY_XID_TIMEDIFF_TOO_ LONG	全局事务时间戳检查 失败(timediff> 1800s)	不影响事务	事务相关
668	ER_PROXY_SAVEPOINT_NOT_EXI ST	SAVEPOINT 不存在,链接不在事务中或回滚	不影响事 务,需检 查业务逻 辑	事务相关
669	ER_PROXY_SC_TRANS_IN_ROLLE D	由于 server 已经 close,事务回滚	回滚	事务 相关
670	ER_PROXY_CANT_BOOST_IN_TR ANS	事务中不允许执行 xa BOOST	不影响事 务	事务 相关
671	ER_PROXY_TRANS_EXPECTED	事务状态非预期	状态未知	事务 相关
672	ER_PROXY_EXTERNAL_TRANS	外部 xa 中不允许执行	不影响事 务	事务 相关
673	ER_PROXY_AUTO_INC_FAIL	处理自增字段失败		执行 相关
674	ER_PROXY_CHECK_JOIN_FAIL	proxy 不支持该 join 操作		语法 相关
675	ER_PROXY_ALTER_STEP_FAIL	修改自增值步长失败		执行 相关
676	ER_PROXY_UNSUPPORT_NS_IN_I NSERT	当前 insert 不支持非 分区表与广播表		语法 相关
677	ER_PROXY_ALTER_SEQ_ID_FAIL	修改 seq id 失败		执行 相关
678	ER_PROXY_ALTER_ID_ILLEGAL	修改 seq id 值为非法		执行

		值	相关
679	ER_PROXY_CANT_CHANGE_STEP	当前 autoinc 值不支持 修改步长	执行 相关
680	ER_PROXY_TABLE_TYPE_NOT_M ATCH	不允许在 noshard 实 例中操作 shard 类型 表	执行 相关
681	ER_PROXY_NO_SK	系统是否只允许带 shardkey 的 SQL 执行	语法 相关
682	ER_PROXY_COMBINE_SQL_KEY	聚合 sql 失败,proxy 识别语法失败	执行 相关
683	ER_PROXY_GET_SK_ERROR	获取 shardkey 的值或 者范围失败	执行 相关
684	ER_PROXY_DDL_DENY	ddl 无法处理 noshard 和 global 表	执行 相关
685	ER_PROXY_SHADKEY_ERROR	只定义,未启用: SQL should not relate to subpartition tables	执行 相关
686	ER_PROXY_TOO_MUCH_TABLES	Group 中表的总数目 不能超过 max_table 的限制	未分类
687	ER_PROXY_TABLE_EXISTED	表已经存在	执行 相关
688	ER_PROXY_CREATE_STABLE_FAI LED	不能使用当前语法创 建表	执行 相关
689	ER_PROXY_SHOW_FAILED	/*proxy*/相关命令失 败	执行 相关
690	ER_PROXY_SET_FAILED	/*proxy*/相关命令失 败	执行 相关
691	ER_PROXY_UNLOCK_FORMAT_E RROR	router 相关命令格式 不正确	语法 相关
692	ER_PROXY_UNLOCK_ROUTER_F AIL	router 加锁失败(zk 操作)	未分类
693	ER_PROXY_LOCK_ROUTER_FAIL	router 解锁失败(zk 操作)	未分类
694	ER_PROXY_PROXY_CMD_FAIL	不支持的命令	语法 相关

695	ER_PROXY_PROCESS_RULE_FILE _FAILED	sql 防火墙规则检查错 误		执行 相关
696	ER_PROXY_GET_AUTO_NUM_ER ROR	获取 auto inc 值失败		执行 相关
697	ER_PROXY_SEQUENCE_NOT_EXI ST	Sequence 不存在		执行 相关
698	ER_PROXY_SEQUENCE_ERROR	Sequence 不合法		执行 相关
699	ER_PROXY_SEQUENCE_ALREAD Y_EXIST	Sequence 已经存在		执行 相关
700	ER_PROXY_SQL_RETRY	sql还未提交或回滚	状态未知	事务 相关
701	ER_PROXY_XA2PC_ABORT	两阶段提交失败,事 务会回滚。事务在等 待一定的时候内,会 回滚,该时间配置在 agent 配置中(<xa>标 签)。业务需要等 待,不需要处理该错 误。</xa>	回滚	事务相关
702	ER_PROXY_XA2PC_COMMIT	两阶段提交失败,事 务将会提交(agent 将 会补提交,需要等待 n 秒,具体看 agent 配 置)	提交	事务相关
703	ER_PROXY_XA2PC_UNCERTAIN	两阶段提交失败,事 务状态未知。	状态未知	事务相关
704	ER_PROXY_KILL_ERROR	找不到要 kill 的 ID		执行 相关
705	ER_PROXY_TRACE_DENY	当前 sql 不支持 trace		语法 相关
706	ER_PROXY_SQL_IMCOMPLETE	连接已中断,事务可能不完整	状态未知	事务相关
709	ER_PROXY_SHARDKEY_HASH_E RROR	无法计算当前数据分 片键,		执行 相关

		set 匹配失败	
710	ER_PROXY_VIEW_UNSUPPORTED	视图不支持当前操作	语法 相关
711	ER_PROXY_GLOBAL_PARTITION_ ERROR	查询一级分区表名失 败	执行 相关
712	ER_PROXY_RENAME_TABLE	修改表名失败	执行 相关
713	ER_PROXY_LOCK_TABLE	锁定表失败	执行 相关
714	ER_PROXY_MC_DISCONNECT	一致性读连接 Meta cluster 失败	执行 相关
715	ER_PROXY_UK_ERROR	唯一索引错误	语法 相关
716	ER_PROXY_ZOOKEEPER_ERROR	访问 zk 失败	系统 相关
717	ER_PROXY_IS_REBALANCE	表正在 rebalancing 扩容中	系统 相关
718	ER_PROXY_GET_DDL_ERROR	获取 DDL 信息报错	语法 相关
719	ER_PROXY_INVALID_DDL_ID	无效 DDL 任务 ID	语法 相关
720	ER_ROUTE_DDL_BEGIN	DDL 错误的起始错误,内部使用	系统 相关
721	ER_ROUTE_DDL_SYSTEM_ERROR E	DDL 任务,系统报错	语法 相关
722	ER_ROUTE_DDL_DB_INCONSISTE NT	DDL 任务,发现数据 节点表结构有存在不 一致,请检查	语法 相关
723	ER_ROUTE_DDL_NOT_SUPPORT	DDL 任务,不支持的 表分区类型	语法 相关
724	ER_ROUTE_DDL_SUBPARTITION_ TABLENUMBER_INCONSISTENT	DDL 任务,每个节点 下的子分区不相等, 需要确认	语法 相关
725	ER_ROUTE_DDL_LOCK_SUBPART ITION_ZKNODE_FAILED	DDL 任务,锁表的 zk 表分区节点失败	语法 相关

726	ER_ROUTE_DDL_UNLOCK_SUBPA RTITION_ZKNODE_FAILED	DDL 任务,解锁 zk 表分区节点失败	语法 相关
740	ER_ROUTE_DDL_END	DDL 错误的终止,内 部使用	系统 相关
741	ER_PROXY_DDL_POST_QUEUE_E RROR	proxy 系统错误,请 求 DDL 队列失败, 需要重试	系统 相关
742	ER_PROXY_DROP_TEMPORARY_ TABLE	没有对应的原始和临时表,导致无法删除此表	系统 相关
900	ER_PROXY_SYSTEM_ERROR_BEG IN	系统错误的起始,内 部使用	系统 相关
901	ER_PROXY_SLICING	slice 被修改,可能在 扩容阶段,当前 sql 禁止执行	执行 相关
902	ER_PROXY_NO_DEFAULT_SET	无法获取当前 set 名称	系统 相关
903	ER_PROXY_GET_ADDRESS_FAILE D	还未初始化完成,获 取后端地址失败,稍 后重试	系统 相关
904	ER_PROXY_SQL_SIZE_ERROR_IN_ GET_CANDIDATE_ADDRESS	获取后端地址出错 (发往后端个数不正 确)	系统 相关
905	ER_PROXY_GET_ADDRESS_ERRO R	获取后端地址出错	系统 相关
906	ER_PROXY_CANDIDATE_ADDRES S_EMPTY	未获取到后端地址	系统 相关
907	ER_PROXY_CANT_GET_SOCK	socket 获取失败	系统 相关
908	ER_PROXY_GET_SET_SOCK_FAIL	socket 获取失败	系统 相关
909	ER_PROXY_CONNECT_ERROR	后端连接失败	系统 相关
910	ER_PROXY_NO_SQL_ASSIGN_TO_ SET	系统错误,SQL 没有 指定要发送的数据节 点	系统 相关

911	ER_PROXY_STATUS_ERROR	group 状态异常,断 开链接	系统 相关
912	ER_PROXY_CONN_BROKEN_ERR OR	server close,sql 状态 不正常	系统 相关
913	ER_PROXY_UNKNOWN_ERROR	proxy 未知错误(可 能为异常引起)	未分类
914	ER_PROXY_ALL_SLAVES_UNAVA ILABLE	所有只读节点不可用	系统 相关
915	ER_PROXY_ALL_SLAVES_CHANG E	只读节点由于变更断 开连接	系统 相关
916	ER_PROXY_ERROR_END	错误码的最后一个, 内部使用	系统 相关

2 DB 错误信息参考

错误消息示例

TDSQL 错误消息视情况输出到对应日志文件、client 显示、应用程序中。

1. 错误日志消息示例:

2018-10-28T13:01:32.735983Z 0 [Note][MY-010303] [Server] Skipping generation of SSL certificates as options related to SSL are specified.

2018-10-02T03:20:39.410387Z 768 [ERROR][MY-010045] [Server] Event Scheduler: [evtuser@localhost][myschema.e daily] Unknowndatabase 'mydb'

2. client 返回消息示例:

> use test1:

ERROR1049 (42000): Unknown database 'test1'

3. 应用返回消息示例:

ERROR jTPCCTData: set_1655570914_1:Lock waittimeout exceeded; try restarting transaction com.mysql.cj.jdbc.exceptions.MySQLTransactionRollbackException:set_1655570914_1:Lock wait timeout exceeded; try restarting transaction

```
atcom.mysql.cj.jdbc.exceptions.SQLError.createSQLException(SQLError.java:123) atcom.mysql.cj.jdbc.exceptions.SQLError.createSQLException(SQLError.java:97) at
```

com.mysql.cj.jdbc.exceptions.SQLExceptionsMapping.translateException(SQLExceptionsMapping.java:122)

atcom.mysql.cj.jdbc.ClientPreparedStatement.executeInternal(ClientPreparedStatement.java:97

atcom.mysql.cj.jdbc.ClientPreparedStatement.executeUpdateInternal(ClientPreparedStatement.java:1113)

at

com.mysql.cj.jdbc.ClientPreparedStatement.executeUpdateInternal(ClientPreparedStatement.java:10 61)

atcom.mysql.cj.jdbc.ClientPreparedStatement.executeLargeUpdate(ClientPreparedStatement.ja va:1381)

atcom.mysql.cj.jdbc.ClientPreparedStatement.executeUpdate(ClientPreparedStatement.java:1046)

```
atjTPCCTData.executePayment(jTPCCTData.java:767)
```

atjTPCCTData.execute(jTPCCTData.java:99)

atjTPCCTerminal.executeTransactions(jTPCCTerminal.java:160)

atjTPCCTerminal.run(jTPCCTerminal.java:88)

atjava.base/java.lang.Thread.run(Thread.java:833)

2.1 错误码及错误信息汇总 01

TDSQL 每条服务器错误消息都包括错误代码、SQLSTATE 值和消息字符串。

Error number: 1002; Symbol:ER_NO; SQLSTATE: HY000

Message: NO

用于构建其他消息。

Error number: 1003; Symbol:ER_YES; SQLSTATE: HY000

Message: YES

用于构建其他消息。

扩展的解释格式生成注释消息。 ER_YES 在随后的 SHOW WARNINGS 输出中用于这些消息的代码列。

Error number: 1004; Symbol:ER CANT CREATE FILE; SQLSTATE: HY000

Message: Can't create file '%s' (errno: %d - %s) 由于无法创建或复制某些操作所需的文件而发生。

可能原因:源文件权限问题;目标文件已存在但不可写。

Error number: 1005; Symbol: ER CANT CREATE TABLE; SQLSTATE: HY000

Message: Can't create table '%s' (errno: %d - %s)

可能原因: 当无法创建表时, InnoDB 会报告此错误。 如果错误消息涉及错误 150, 则表创建失败, 因为未正确形成外键约 束。 如果错误消息涉及错误 -1, 则表创建可能失败, 因为该表包含与内部 InnoDB 表的名称匹配的列名称。

Error number: 1006; Symbol: ER CANT CREATE DB; SQLSTATE: HY000

Message: Can't create database '%s' (errno: %d - %s)

Error number: 1007; Symbol: ER_DB_CREATE_EXISTS; SQLSTATE: HY000

Message: Can't create database '%s'; database exists

可能原因与处理方法: 尝试创建数据库失败, 因为数据库已经存在。

如果您确实要替换现有数据库,请先删除数据库,或者如果要保留现有数据库而不使语句产

生错误,则将 IF NOT EXISTS 子句添加到 CREATE DATABASE 语句。

Error number: 1008; Symbol: ER_DB_DROP_EXISTS; SQLSTATE: HY000

Message: Can't drop database '%s'; database doesn't exist

Error number: 1010; Symbol:ER DB DROP RMDIR; SQLSTATE: HY000

Message: Error dropping database(can't rmdir '%s', errno: %d - %s)

Error number: 1012; Symbol:ER CANT FIND SYSTEM REC; SQLSTATE: HY000

Message: Can't read record in system table

可能原因与处理方法: 当 InnoDB 不可用时, InnoDB 返回尝试访问 InnoDB

INFORMATION SCHEMA 表。

Error number: 1013; Symbol: ER CANT GET STAT; SQLSTATE: HY000

Message: Can't get status of '%s' (errno: %d - %s)

Error number: 1015; Symbol: ER_CANT_LOCK; SQLSTATE: HY000

Message: Can't lock file (errno: %d - %s)

Error number: 1016; Symbol: ER CANT OPEN FILE; SQLSTATE: HY000

Message: Can't open file: '%s' (errno: %d - %s)

可能原因与处理方法: 当无法找到 InnoDB 数据文件中的表时, InnoDB 会报告此错误。

Error number: 1017; Symbol: ER FILE NOT FOUND; SQLSTATE: HY000

Message: Can't find file: '%s' (errno: %d - %s)

Error number: 1018; Symbol: ER_CANT_READ_DIR; SQLSTATE: HY000

Message: Can't read dir of '%s' (errno: %d - %s)

Error number: 1020; Symbol: ER CHECKREAD; SQLSTATE: HY000

Message: Record has changed since last read in table '%s'

Error number: 1022; Symbol: ER_DUP_KEY; SQLSTATE: 23000

Message: Can't write; duplicate key in table '%s'

Error number: 1024; Symbol: ER ERROR ON READ; SQLSTATE: HY000

Message: Error reading file '%s' (errno: %d - %s)

Error number: 1025; Symbol: ER ERROR ON RENAME; SQLSTATE: HY000

Message: Error on rename of '%s' to '%s' (errno: %d - %s)

Error number: 1026; Symbol: ER ERROR_ON_WRITE; SQLSTATE: HY000

Message: Error writing file '%s' (errno: %d - %s)

Error number: 1027; Symbol: ER_FILE_USED; SQLSTATE: HY000

Message: '%s' is locked against change

Error number: 1028; Symbol: ER FILSORTABORT; SQLSTATE: HY000

Message: Sort aborted

前 说明:

ER FILSORT ABORT was removed after 8.0.18.

Error number: 1030; Symbol: ER GET ERRNO; SQLSTATE: HY000

Message: Got error %d - '%s' from storage engine

可能原因与处理方法: 检查 %d 值以了解操作系统错误的含义。 例如,28 表示您的磁盘空间

已用完。

Error number: 1031; Symbol: ER ILLEGAL HA; SQLSTATE: HY000

Message: Table storage engine for '%s' doesn't have this option

Error number: 1032; Symbol: ER_KEY_NOT_FOUND; SQLSTATE: HY000

Message: Can't find record in '%s'

Error number: 1033; Symbol: ER NOT FORM FILE; SQLSTATE: HY000

Message: Incorrect information in file: '%s'

Error number: 1034; Symbol: ER NOT KEYFILE; SQLSTATE: HY000

Message: Incorrect key file for table '%s'; try to repair it

Error number: 1035; Symbol: ER OLD KEYFILE; SQLSTATE: HY000

Message: Old key file for table '%s'; repair it!

Error number: 1036; Symbol: ER_OPEN_AS_READONLY; SQLSTATE: HY000

Message: Table '%s' is read only

Error number: 1037; Symbol: ER_OUTOFMEMORY; SQLSTATE: HY001 Message: Out of memory; restart server and try again (needed %d bytes)

Error number: 1038; Symbol: ER OUT OF SORTMEMORY; SQLSTATE: HY001

Message: Out of sort memory, consider increasing server sort buffer size

Error number: 1040; Symbol: ER CON COUNT ERROR; SQLSTATE: 08004

Message: Too many connections

Error number: 1041; Symbol: ER OUT OF RESOURCES; SQLSTATE: HY000

Message: Out of memory; check if mysqld or some other process uses all available memory; if not, you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space

Error number: 1042; Symbol: ER BAD HOST ERROR; SQLSTATE: 08S01

Message: Can't get hostname for your address

Error number: 1043; Symbol: ER HANDSHAKE ERROR; SQLSTATE: 08S01

Message: Bad handshake

Error number: 1044; Symbol: ER DBACCESS DENIED ERROR; SQLSTATE: 42000

Message: Access denied for user '%s'@'%s' to database '%s'

Error number: 1045; Symbol: ER ACCESS DENIED ERROR; SQLSTATE: 28000

Message: Access denied for user '%s'@'%s' (using password: %s)

Error number: 1046; Symbol: ER NO DB ERROR; SQLSTATE: 3D000

Message: No database selected

Error number: 1047; Symbol: ER UNKNOWN COM ERROR; SQLSTATE: 08S01

Message: Unknown command

Error number: 1048; Symbol: ER BAD NULL ERROR; SQLSTATE: 23000

Message: Column '%s' cannot be null

Error number: 1049; Symbol: ER BAD DB ERROR; SQLSTATE: 42000

Message: Unknown database '%s'

Error number: 1050; Symbol: ER TABLE EXISTS_ERROR; SQLSTATE: 42S01

Message: Table '%s' already exists

Error number: 1051; Symbol: ER BAD TABLE ERROR; SQLSTATE: 42S02

Message: Unknown table '%s'

Error number: 1052; Symbol: ER NON UNIQ ERROR; SQLSTATE: 2300

Message: Column '%s' in %s is ambiguous

%s = column name

%s = location of column (for example, "field list")

可能原因与处理方法:列出现在没有适当限定的查询中,例如在选择列表或 ON 子句中。示例:

> SELECT i FROM t INNER JOIN t AS t2;

ERROR 1052 (23000): Column 'i' in field list is ambiguous

> SELECT * FROM t LEFT JOIN t AS t2 ON i = i;

ERROR 1052 (23000): Column 'i' in on clause is ambiguous

处理方法:

使用适当的表名限定列:

> SELECT t2.i FROM t INNER JOIN t AS t2;

修改查询以避免需要限定: > SELECT * FROM t LEFT JOIN t AS t2 USING (i);

Error number: 1053; Symbol:ER_SERVER_SHUTDOWN; SQLSTATE: 08S01

Message: Server shutdownin progress

Error number: 1054; Symbol: ER BAD FIELD ERROR; SQLSTATE: 42S22

Message: Unknown column '%s' in '%s'

Error number: 1055; Symbol: ER_WRONG_FIELD_WITH_GROUP; SQLSTATE: 42000

Message: '%s' isn't in GROUP BY

Error number: 1056; Symbol: ER WRONG GROUP FIELD; SQLSTATE: 42000

Message: Can't group on '%s'

Error number: 1057; Symbol: ER WRONG SUM SELECT; SQLSTATE: 42000

Message: Statement has sum functions and columns in same statement

Error number: 1058; Symbol: ER WRONG VALUE COUNT; SQLSTATE: 21S01

Message: Column count doesn't match value count

Error number: 1059; Symbol: ER TOO LONG IDENT; SQLSTATE: 42000

Message: Identifier name '%s' is too long

Error number: 1060; Symbol: ER DUP FIELDNAME; SQLSTATE: 42S21

Message: Duplicate column name '%s'

Error number: 1061; Symbol: ER DUP KEYNAME; SQLSTATE: 42000

Message: Duplicate key name '%s'

Error number: 1062; Symbol: ER_DUP_ENTRY; SQLSTATE: 23000

Message: Duplicate entry '%s' for key %d

The message returned with this error uses the format string for

ER DUP ENTRY WITH KEY NAME.

Error number: 1063; Symbol: ER WRONG FIELD SPEC; SQLSTATE: 42000

Message: Incorrect column specifier for column '%s'

Error number: 1064; Symbol: ER PARSE ERROR; SQLSTATE: 42000

Message: %s near '%s' at line %d

Error number: 1065; Symbol: ER EMPTY QUERY; SQLSTATE: 42000

Message: Query was empty

Error number: 1066; Symbol: ER_NONUNIQ_TABLE; SQLSTATE: 42000

Message: Not unique table/alias: '%s'

Error number: 1067; Symbol: ER INVALID DEFAULT; SQLSTATE: 42000

Message: Invalid default value for '%s'

Error number: 1068; Symbol: ER MULTIPLE PRI KEY; SQLSTATE: 42000

Message: Multiple primary key defined

Error number: 1069; Symbol: ER TOO MANY KEYS; SQLSTATE: 42000

Message: Too many keys specified; max %d keys allowed

Error number: 1070; Symbol: ER TOO MANY KEY PARTS; SQLSTATE: 42000

Message: Too many key parts specified; max %d parts allowed

Error number: 1071; Symbol: ER TOO LONG KEY; SQLSTATE: 42000

Message: Specified key was too long; max key length is %d bytes

Error number: 1072; Symbol: ER KEY COLUMN DOES NOT EXITS; SQLSTATE: 42000

Message: Key column '%s' doesn't exist in table

Error number: 1073; Symbol: ER BLOB USED AS KEY; SQLSTATE: 42000

Message: BLOB column '%s' can't be used in key specification with the used table type

Error number: 1074; Symbol: ER_TOO_BIG_FIELDLENGTH; SQLSTATE: 42000

Message: Column length too big for column '%s' (max = %lu); use BLOB or TEXT instead

Error number: 1075; Symbol: ER WRONG AUTO KEY; SQLSTATE: 42000

Message: Incorrect table definition; there can be only one auto column and it must be defined as a

key

Error number: 1076; Symbol: ER READY; SQLSTATE: HY000

Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d

Error number: 1077; Symbol: ER NORMAL SHUTDOWN; SQLSTATE: HY000

Message: %s: Normal shutdown

ER NORMAL SHUTDOWN was removed after 8.0.4.

Error number: 1079; Symbol: ER SHUTDOWN COMPLETE; SQLSTATE: HY000

Message: %s: Shutdown complete

Error number: 1080; Symbol: ER FORCING CLOSE; SQLSTATE: 08S01

Message: %s: Forcing close of thread %ld user: '%s'

Error number: 1081; Symbol: ER IPSOCK ERROR; SQLSTATE: 08S01

Message: Can't create IP socket

Error number: 1082; Symbol: ER_NO_SUCH_INDEX; SQLSTATE: 42S12

Message: Table '%s' has no index like the one used in CREATE INDEX; recreate the table

Error number: 1083; Symbol: ER WRONG FIELD TERMINATORS; SQLSTATE: 42000

Message: Field separator argument is not what is expected; check the manual

Error number: 1084; Symbol: ER BLOBS AND NO TERMINATED; SQLSTATE: 42000

Message: You can't use fixed rowlength with BLOBs; please use 'fields terminated by'

Error number: 1085; Symbol: ER TEXTFILE NOT READABLE; SQLSTATE: HY000

Message: The file '%s' must be in the database directory or be readable by all

Error number: 1086; Symbol: ER FILE EXISTS ERROR; SQLSTATE: HY000

Message: File '%s' already exists

Error number: 1087; Symbol: ER_LOAD_INFO; SQLSTATE: HY000 Message: Records: %ld Deleted: %ld Skipped: %ld Warnings: %ld

Error number: 1088; Symbol: ER ALTER INFO; SQLSTATE: HY000

Message: Records: %ld Duplicates: %ld

Error number: 1089; Symbol: ER_WRONG_SUB_KEY; SQLSTATE: HY000

Message: Incorrect prefix key; the used key part isn't a string, the used length is longer than the key

part, or the storage engine doesn't support unique prefix keys

Error number: 1090; Symbol: ER_CANT_REMOVE_ALL_FIELDS; SQLSTATE: 42000 Message: You can't delete all columns with ALTER TABLE; use DROP TABLE instead

Error number: 1091; Symbol: ER CANT DROP FIELD OR KEY; SQLSTATE: 42000

Message: Can't DROP '%s'; check that column/key exists

Error number: 1092; Symbol: ER_INSERT_INFO; SQLSTATE: HY000

Message: Records: %ld Duplicates: %ld Warnings: %ld

Error number: 1093; Symbol: ER UPDATE TABLE USED; SQLSTATE: HY000

Message: You can't specify target table '%s' for update in FROM clause

可能原因与处理方法:尝试在单个语句中选择和修改同一个表时会发生此错误。如果选择尝试发生在派生表中,您可以通过设置 optimizer_switch 系统变量的 derived_merge 标志来强制子查询被具体化到临时表中来避免此错误,这实际上会导致它与修改后的表不同.

Error number: 1094; Symbol: ER NO SUCH THREAD; SQLSTATE: HY000

Message: Unknown thread id: %lu

Error number: 1095; Symbol: ER_KILL_DENIED_ERROR; SQLSTATE: HY000

Message: You are not owner of thread %lu

Error number: 1096; Symbol: ER NO TABLES USED; SQLSTATE: HY000

Message: No tables used

Error number: 1097; Symbol: ER TOO BIG SET; SQLSTATE: HY000

Message: Too many strings for column %s and SET

Error number: 1098; Symbol: ER NO UNIQUE LOGFILE; SQLSTATE: HY000

Message: Can't generate a unique log-filename %s.(1-999)

Error number: 1099; Symbol: ER TABLE NOT LOCKED FOR WRITE; SQLSTATE: HY000

Message: Table '%s' was locked with a READ lock and can't be updated

Error number: 1100; Symbol: ER TABLE NOT LOCKED; SQLSTATE: HY000

Message: Table '%s' was not locked with LOCK TABLES

Error number: 1101; Symbol: ER_BLOB_CANT_HAVE_DEFAULT; SQLSTATE: 42000 Message: BLOB, TEXT, GEOMETRY or JSON column '%s' can't have a default value

Error number: 1102; Symbol: ER WRONG DB NAME; SQLSTATE: 42000

Message: Incorrect database name '%s'

Error number: 1103; Symbol: ER WRONG TABLE NAME; SQLSTATE: 42000

Message: Incorrect table name '%s'

Error number: 1104; Symbol: ER_TOO BIG SELECT; SQLSTATE: 42000

Message: The SELECT would examine more than MAX_JOIN_SIZE rows; check your WHERE

and use SET SQL BIG SELECTS=1 or SET MAX JOIN SIZE=# if the SELECT is okay

Error number: 1105; Symbol: ER UNKNOWN ERROR; SQLSTATE: HY000

Message: Unknown error

Error number: 1106; Symbol: ER UNKNOWN PROCEDURE; SQLSTATE: 42000

Message: Unknown procedure '%s'

Error number: 1107; Symbol: ER WRONG PARAMCOUNT TO PROCEDURE; SQLSTATE:

42000

Message: Incorrect parameter count to procedure '%s'

Error number: 1108; Symbol: ER_WRONG_PARAMETERS_TO_PROCEDURE; SQLSTATE:

HY000

Message: Incorrect parameters to procedure '%s'

Error number: 1109; Symbol: ER UNKNOWN TABLE; SQLSTATE: 42S02

Message: Unknown table '%s' in %s

Error number: 1110; Symbol: ER FIELD SPECIFIED TWICE; SQLSTATE: 42000

Message: Column '%s' specified twice

Error number: 1111; Symbol: ER_INVALID_GROUP_FUNC_USE; SQLSTATE: HY000

Message: Invalid use of group function

Error number: 1112; Symbol: ER UNSUPPORTED EXTENSION; SQLSTATE: 42000

Message: Table '%s' uses an extension that doesn't exist in this MySQL version

Error number: 1113; Symbol: ER TABLE MUST HAVE COLUMNS; SQLSTATE: 42000

Message: A table must have at least 1 column

Error number: 1114; Symbol: ER RECORD FILE FULL; SQLSTATE: HY000

Message: The table '%s' is full

InnoDB reports this error when the system tablespace runs out of free space. Reconfigure the system

tablespace to add a new data file.

Error number: 1115; Symbol: ER_UNKNOWN_CHARACTER_SET; SQLSTATE: 42000

Message: Unknown character set: '%s'

Error number: 1116; Symbol: ER TOO MANY TABLES; SQLSTATE: HY000

Message: Too many tables; MySQL can only use %d tables in a join

Error number: 1117; Symbol: ER TOO MANY FIELDS; SQLSTATE: HY000

Message: Too many columns

Error number: 1118; Symbol: ER TOO BIG ROWSIZE; SQLSTATE: 42000

Message: Row size too large. The maximum row size for the used table type, not counting BLOBs,

is %ld. This includes storage overhead, check the manual. You have to change some columns to

TEXT or BLOBs

Error number: 1119; Symbol: ER STACK OVERRUN; SQLSTATE: HY000

Message: Thread stack overrun: Used: %ld of a %ld stack. Use 'mysqld --thread stack=#' to specify

a bigger stack if needed

Error number: 1120; Symbol: ER_WRONG_OUTER_JOIN; SQLSTATE: 42000

Message: Cross dependency found in OUTER JOIN; examine your ON conditions

ER WRONG OUTER JOIN was removed after 8.0.0.

Error number: 1120; Symbol: ER WRONG OUTER JOIN UNUSED; SQLSTATE: 42000

Message: Cross dependency found in OUTER JOIN; examine your ON conditions

ER WRONG OUTER JOIN UNUSED was added in 8.0.1.

Error number: 1121; Symbol: ER NULL COLUMN IN INDEX; SQLSTATE: 42000

Message: Table handler doesn't support NULL in given index. Please change column '%s' to be NOT NULL or use another handler

Error number: 1122; Symbol: ER CANT FIND UDF; SQLSTATE: HY000

Message: Can't load function '%s'

Error number: 1123; Symbol: ER CANT INITIALIZE UDF; SQLSTATE: HY000

Message: Can't initialize function '%s'; %s

Error number: 1124; Symbol: ER UDF NO PATHS; SQLSTATE: HY000

Message: No paths allowed for shared library

Error number: 1125; Symbol: ER UDF EXISTS; SQLSTATE: HY000

Message: Function '%s' already exists

Error number: 1126; Symbol: ER CANT OPEN LIBRARY; SQLSTATE: HY000

Message: Can't open shared library '%s' (errno: %d %s)

Error number: 1127; Symbol: ER_CANT_FIND DL ENTRY; SQLSTATE: HY000

Message: Can't find symbol '%s' in library

Error number: 1128; Symbol: ER_FUNCTION_NOT_DEFINED; SQLSTATE: HY000

Message: Function '%s' is not defined

Error number: 1129; Symbol: ER HOST IS BLOCKED; SQLSTATE: HY000

Message: Host '%s' is blocked because of many connection errors; unblock with 'mysqladmin flush-

hosts'

Error number: 1130; Symbol: ER HOST NOT PRIVILEGED; SQLSTATE: HY000

Message: Host '%s' is not allowed to connect to this MySQL server

Error number: 1131; Symbol: ER_PASSWORD_ANONYMOUS_USER; SQLSTATE: 42000

Message: You are using MySQL as an anonymous user and anonymous users are not allowed to

change passwords

Error number: 1132; Symbol: ER PASSWORD NOT ALLOWED; SQLSTATE: 42000

Message: You must have privileges to update tables in the mysql database to be able to change

passwords for others

Error number: 1133; Symbol: ER PASSWORD NO MATCH; SQLSTATE: 42000

Message: Can't find any matching row in the user table

Error number: 1134; Symbol: ER UPDATE INFO; SQLSTATE: HY000

Message: Rows matched: %ld Changed: %ld Warnings: %ld

Error number: 1135; Symbol: ER CANT CREATE THREAD; SQLSTATE: HY000

Message: Can't create a new thread (errno %d); if you are not out of available memory, you can

consult the manual for a possible OS-dependent bug

Error number: 1136; Symbol: ER WRONG VALUE COUNT ON ROW; SQLSTATE: 21S01

Message: Column count doesn't match value count at row %ld

Error number: 1137; Symbol: ER CANT REOPEN TABLE; SQLSTATE: HY000

Message: Can't reopen table: '%s'

Error number: 1138; Symbol: ER INVALID USE OF NULL; SQLSTATE: 22004

Message: Invalid use of NULL value

Error number: 1139; Symbol: ER REGEXP ERROR; SQLSTATE: 42000

Message: Got error '%s' from regexp

Error number: 1140; Symbol: ER_MIX_OF_GROUP_FUNC_AND_FIELDS; SQLSTATE: 42000

Message: Mixing of GROUP columns (MIN(),MAX(),COUNT(),...) with no GROUP columns is

illegal if there is no GROUP BY clause

Error number: 1141; Symbol: ER NONEXISTING GRANT; SQLSTATE: 42000

Message: There is no such grant defined for user '%s' on host '%s'

Error number: 1142; Symbol: ER TABLEACCESS DENIED ERROR; SQLSTATE: 42000

Message: %s command denied to user '%s'@'%s' for table '%s'

Error number: 1143; Symbol: ER COLUMNACCESS DENIED ERROR; SQLSTATE: 42000

Message: %s command denied to user '%s'@'%s' for column '%s' in table '%s'

Error number: 1144; Symbol: ER_ILLEGAL_GRANT_FOR_TABLE; SQLSTATE: 42000

Message: Illegal GRANT/REVOKE command; please consult the manual to see which privileges

can be used

Error number: 1145; Symbol: ER GRANT WRONG HOST OR USER; SQLSTATE: 42000

Message: The host or user argument to GRANT is too long

Error number: 1146; Symbol: ER_NO_SUCH_TABLE; SQLSTATE: 42S02

Message: Table '%s.%s' doesn't exist

Error number: 1147; Symbol: ER NONEXISTING TABLE GRANT; SQLSTATE: 42000

Message: There is no such grant defined for user '%s' on host '%s' on table '%s'

Error number: 1148; Symbol: ER NOT ALLOWED COMMAND; SQLSTATE: 42000

Message: The used command is not allowed with this MySQL version

Error number: 1149; Symbol: ER SYNTAX ERROR; SQLSTATE: 42000

Message: You have an error in your SQL syntax; check the manual that corresponds to your MySQL

server version for the right syntax to use

Error number: 1152; Symbol: ER ABORTING CONNECTION; SQLSTATE: 08S01

Message: Aborted connection %ld to db: '%s' user: '%s' (%s)

Error number: 1153; Symbol: ER NET PACKET TOO LARGE; SQLSTATE: 08S01

Message: Got a packet bigger than 'max allowed packet' bytes

Error number: 1154; Symbol: ER NET READ ERROR FROM PIPE; SQLSTATE: 08S01

Message: Got a read error from the connection pipe

Error number: 1155; Symbol: ER_NET_FCNTL_ERROR; SQLSTATE: 08S01

Message: Got an error from fcntl()

Error number: 1156; Symbol: ER NET PACKETS OUT OF ORDER; SQLSTATE: 08S01

Message: Got packets out of order

Error number: 1157; Symbol: ER_NET_UNCOMPRESS_ERROR; SQLSTATE: 08S01

Message: Couldn't uncompress communication packet

Error number: 1158; Symbol: ER NET READ ERROR; SQLSTATE: 08S01

Message: Got an error reading communication packets

Error number: 1159; Symbol: ER NET READ INTERRUPTED; SQLSTATE: 08S01

Message: Got timeout reading communication packets

Error number: 1160; Symbol: ER NET ERROR ON WRITE; SQLSTATE: 08S01

Message: Got an error writing communication packets

Error number: 1161; Symbol: ER NET WRITE INTERRUPTED; SQLSTATE: 08S01

Message: Got timeout writing communication packets

Error number: 1162; Symbol: ER TOO LONG STRING; SQLSTATE: 42000

Message: Result string is longer than 'max allowed packet' bytes

Error number: 1163; Symbol: ER_TABLE_CANT_HANDLE_BLOB; SQLSTATE: 42000

Message: The used table type doesn't support BLOB/TEXT columns

Error number: 1164; Symbol: ER TABLE CANT HANDLE AUTO INCREMENT; SQLSTATE:

42000

Message: The used table type doesn't support AUTO INCREMENT columns

Error number: 1166; Symbol: ER WRONG COLUMN NAME; SQLSTATE: 42000

Message: Incorrect column name '%s'

Error number: 1167; Symbol: ER WRONG KEY COLUMN; SQLSTATE: 42000

Message: The used storage engine can't index column '%s'

Error number: 1168; Symbol: ER WRONG MRG TABLE; SQLSTATE: HY000

Message: Unable to open underlying table which is differently defined or of non-MyISAM type or

doesn't exist

Error number: 1169; Symbol: ER DUP UNIQUE; SQLSTATE: 23000

Message: Can't write, because of unique constraint, to table '%s'

Error number: 1170; Symbol: ER_BLOB_KEY_WITHOUT_LENGTH; SQLSTATE: 42000

Message: BLOB/TEXT column '%s' used in key specification without a key length

Error number: 1171; Symbol: ER PRIMARY CANT HAVE NULL; SQLSTATE: 42000

Message: All parts of a PRIMARY KEY must be NOT NULL; if you need NULL in a key, use

UNIQUE instead

Error number: 1172; Symbol: ER TOO MANY ROWS; SQLSTATE: 42000

Message: Result consisted of more than one row

Error number: 1173; Symbol: ER REQUIRES PRIMARY KEY; SQLSTATE: 42000

Message: This table type requires a primary key

Error number: 1175; Symbol: ER_UPDATE_WITHOUT_KEY_IN_SAFE_MODE; SQLSTATE:

HY000

Message: You are using safe update mode and you tried to update a table without a WHERE that

uses a KEY column. %s

Error number: 1176; Symbol: ER KEY DOES NOT EXITS; SQLSTATE: 42000

Message: Key '%s' doesn't exist in table '%s'

Error number: 1177; Symbol: ER CHECK NO SUCH TABLE; SQLSTATE: 42000

Message: Can't open table

Error number: 1178; Symbol: ER CHECK NOT IMPLEMENTED; SQLSTATE: 42000

Message: The storage engine for the table doesn't support %s

Error number: 1179; Symbol: ER CANT DO THIS DURING AN TRANSACTION;

SQLSTATE: 25000

Message: You are not allowed to execute this command in a transaction

Error number: 1180; Symbol: ER ERROR DURING COMMIT; SQLSTATE: HY000

Message: Got error %d - '%s' during COMMIT

Error number: 1181; Symbol: ER_ERROR_DURING_ROLLBACK; SQLSTATE: HY000

Message: Got error %d - '%s' during ROLLBACK

Error number: 1182; Symbol: ER ERROR DURING FLUSH LOGS; SQLSTATE: HY000

Message: Got error %d during FLUSH LOGS

Error number: 1184; Symbol: ER NEW ABORTING CONNECTION; SQLSTATE: 08S01

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s)

Error number: 1188; Symbol: ER MASTER; SQLSTATE: HY000

Message: Error from master: '%s'

Error number: 1189; Symbol: ER MASTER NET READ; SQLSTATE: 08S01

Message: Net error reading from master

Error number: 1190; Symbol: ER MASTER NET WRITE; SQLSTATE: 08S01

Message: Net error writing to master

Error number: 1191; Symbol: ER FT MATCHING KEY NOT FOUND; SQLSTATE: HY000

Message: Can't find FULLTEXT index matching the column list

Error number: 1192; Symbol: ER LOCK OR ACTIVE TRANSACTION; SQLSTATE: HY000

Message: Can't execute the given command because you have active locked tables or an active

transaction

Error number: 1193; Symbol: ER UNKNOWN SYSTEM VARIABLE; SQLSTATE: HY000

Message: Unknown system variable '%s'

Error number: 1194; Symbol: ER CRASHED ON USAGE; SQLSTATE: HY000

Message: Table '%s' is marked as crashed and should be repaired

Error number: 1195; Symbol: ER CRASHED ON REPAIR; SQLSTATE: HY000

Message: Table '%s' is marked as crashed and last (automatic?) repair failed

Error number: 1196; Symbol: ER WARNING NOT COMPLETE ROLLBACK; SQLSTATE:

HY000

Message: Some non-transactional changed tables couldn't be rolled back

Error number: 1197; Symbol: ER_TRANS_CACHE_FULL; SQLSTATE: HY000

Message: Multi-statement transaction required more than 'max_binlog_cache_size' bytes of storage;

increase this mysqld variable and try again

Error number: 1199; Symbol: ER SLAVE NOT RUNNING; SQLSTATE: HY000

Message: This operation requires a running slave; configure slave and do START SLAVE

Error number: 1200; Symbol: ER_BAD_SLAVE; SQLSTATE: HY000

Message: The server is not configured as slave; fix in config file or with CHANGE MASTER TO

Error number: 1201; Symbol: ER_MASTER_INFO; SQLSTATE: HY000

Message: Could not initialize master info structure; more error messages can be found in the MySQL

error log

Error number: 1202; Symbol: ER SLAVE THREAD; SQLSTATE: HY000

Message: Could not create slave thread; check system resources

Error number: 1203; Symbol: ER TOO MANY USER CONNECTIONS; SQLSTATE: 42000

Message: User %s already has more than 'max user connections' active connections

Error number: 1204; Symbol: ER SET CONSTANTS ONLY; SQLSTATE: HY000

Message: You may only use constant expressions with SET

Error number: 1205; Symbol: ER LOCK WAIT TIMEOUT; SQLSTATE: HY000

Message: Lock wait timeout exceeded; try restarting transaction

可能原因及解决办法: 当锁定等待超时到期时,InnoDB 会报告此错误。等待太久的语句被回滚(不是整个事务)。 如果 SQL 语句应该等待更长的时间等待其他事务完成,您可以增加 innodb_lock_wait_timeout 配置选项的值,或者如果太多长时间运行的事务导致锁定问题并降低繁忙系统上的并发性,则可以减小它。

Error number: 1206; Symbol: ER_LOCK_TABLE_FULL; SQLSTATE: HY000

Message: The total number of locks exceeds the lock table size

可能原因及解决办法:当锁的总数超过用于管理锁的内存量时,InnoDB 会报告此错误。为避免此错误,请增加 innodb_buffer_pool_size 的值。在单个应用程序中,解决方法可能是将大型操作分解为较小的部分。例如,如果大型 INSERT 发生错误,请执行几个较小的INSERT 操作。

Error number: 1207; Symbol: ER_READ_ONLY_TRANSACTION; SQLSTATE: 25000 Message: Update locks cannot be acquired during a READ UNCOMMITTED transaction

Error number: 1210; Symbol: ER WRONG ARGUMENTS; SQLSTATE: HY000

Message: Incorrect arguments to %s

Error number: 1211; Symbol: ER_NO_PERMISSION_TO_CREATE_USER; SQLSTATE: 42000 Message: '%s'@'%s' is not allowed to create new users

Error number: 1213; Symbol: ER_LOCK_DEADLOCK; SQLSTATE: 40001

Message: Deadlock found when trying to get lock; try restarting transaction 可能原因及解决办法: 当事务遇到死锁并自动回滚时,InnoDB 会报告此错误,以便您的应用程序可以采取纠正措施。 要从此错误中恢复,请再次运行此事务中的所有操作。 当事务之间的锁请求以不一致的顺序到达时,就会发生死锁。 回滚的事务释放了它所有的锁,而另一个事务现在可以获得它请求的所有锁。 因此,当您重新运行已回滚的事务时,它可能必须等待其他事务完成,但通常不会再次发生死锁。 如果您经常遇到死锁,请使遇到问题的不同事务或应用程序之间的锁定操作顺序(LOCK TABLES、SELECT ... FOR UPDATE等)保持一

致。

Error number: 1214; Symbol: ER_TABLE_CANT_HANDLE_FT; SQLSTATE: HY000

Message: The used table type doesn't support FULLTEXT indexes

Error number: 1215; Symbol: ER CANNOT ADD FOREIGN; SQLSTATE: HY000

Message: Cannot add foreign key constraint

Error number: 1216; Symbol: ER NO REFERENCED ROW; SQLSTATE: 23000

Message: Cannot add or update a child row: a foreign key constraint fails

可能原因及解决办法: 当您尝试添加行但没有父行并且外键约束失败时, InnoDB 会报告此错

误。首先添加父行。

Error number: 1217; Symbol: ER ROW IS REFERENCED; SQLSTATE: 23000

Message: Cannot delete or update a parent row: a foreign key constraint fails

当您尝试删除具有子项的父行并且外键约束失败时, InnoDB 会报告此错误。 先删除子行。

Error number: 1218; Symbol: ER CONNECT TO MASTER; SQLSTATE: 08S01

Message: Error connecting to master: %s

Error number: 1220; Symbol: ER_ERROR_WHEN_EXECUTING_COMMAND; SQLSTATE:

HY000

Message: Error when executing command %s: %s

Error number: 1221; Symbol: ER WRONG USAGE; SQLSTATE: HY000

Message: Incorrect usage of %s and %s

Error number: 1222; Symbol: ER WRONG NUMBER OF COLUMNS IN SELECT;

SQLSTATE: 21000

Message: The used SELECT statements have a different number of columns

Error number: 1223; Symbol: ER CANT UPDATE WITH READLOCK; SQLSTATE: HY000

Message: Can't execute the query because you have a conflicting read lock

Error number: 1224; Symbol: ER MIXING NOT ALLOWED; SQLSTATE: HY000

Message: Mixing of transactional and non-transactional tables is disabled

Error number: 1225; Symbol: ER DUP ARGUMENT; SQLSTATE: HY000

Message: Option '%s' used twice in statement

Error number: 1226; Symbol: ER USER LIMIT REACHED; SQLSTATE: 42000

Message: User '%s' has exceeded the '%s' resource (current value: %ld)

Error number: 1227; Symbol: ER SPECIFIC ACCESS DENIED ERROR; SQLSTATE: 42000

Message: Access denied; you need (at least one of) the %s privilege(s) for this operation

Error number: 1228; Symbol: ER LOCAL VARIABLE; SQLSTATE: HY000

Message: Variable '%s' is a SESSION variable and can't be used with SET GLOBAL

Error number: 1229; Symbol: ER GLOBAL VARIABLE; SQLSTATE: HY000

Message: Variable '%s' is a GLOBAL variable and should be set with SET GLOBAL

Error number: 1230; Symbol: ER NO DEFAULT; SQLSTATE: 42000

Message: Variable '%s' doesn't have a default value

Error number: 1231; Symbol: ER WRONG VALUE FOR VAR; SQLSTATE: 42000

Message: Variable '%s' can't be set to the value of '%s'

Error number: 1232; Symbol: ER WRONG TYPE FOR VAR; SQLSTATE: 42000

Message: Incorrect argument type to variable '%s'

Error number: 1233; Symbol: ER VAR CANT BE READ; SQLSTATE: HY000

Message: Variable '%s' can only be set, not read

Error number: 1234; Symbol: ER CANT USE OPTION HERE; SQLSTATE: 42000

Message: Incorrect usage/placement of '%s'

Error number: 1235; Symbol: ER NOT SUPPORTED YET; SQLSTATE: 42000

Message: This version of MySQL doesn't yet support '%s'

Error number: 1236; Symbol: ER_MASTER_FATAL_ERROR_READING_BINLOG; SQLSTATE:

HY000

Message: Got fatal error %d from master when reading data from binary log: '%s'

Error number: 1237; Symbol: ER SLAVE IGNORED TABLE; SQLSTATE: HY000

Message: Slave SQL thread ignored the query because of replicate-*-table rules

Error number: 1238; Symbol: ER INCORRECT GLOBAL LOCAL VAR; SQLSTATE: HY000

Message: Variable '%s' is a %s variable

Error number: 1239; Symbol: ER WRONG FK DEF; SQLSTATE: 42000

Message: Incorrect foreign key definition for '%s': %s

Error number: 1240; Symbol: ER KEY REF DO NOT MATCH TABLE REF; SQLSTATE:

HY000

Message: Key reference and table reference don't match

Error number: 1241; Symbol: ER OPERAND COLUMNS; SQLSTATE: 21000

Message: Operand should contain %d column(s)

Error number: 1242; Symbol: ER SUBQUERY NO 1 ROW; SQLSTATE: 21000

Message: Subquery returns more than 1 row

Error number: 1243; Symbol: ER_UNKNOWN_STMT_HANDLER; SQLSTATE: HY000

Message: Unknown prepared statement handler (%.*s) given to %s

Error number: 1244; Symbol: ER CORRUPT HELP DB; SQLSTATE: HY000

Message: Help database is corrupt or does not exist

Error number: 1246; Symbol: ER AUTO CONVERT; SQLSTATE: HY000

Message: Converting column '%s' from %s to %s

Error number: 1247; Symbol: ER ILLEGAL REFERENCE; SQLSTATE: 42S22

Message: Reference '%s' not supported (%s)

Error number: 1248; Symbol: ER DERIVED MUST HAVE ALIAS; SQLSTATE: 42000

Message: Every derived table must have its own alias

Error number: 1249; Symbol: ER SELECT REDUCED; SQLSTATE: 01000

Message: Select %u was reduced during optimization

Error number: 1250; Symbol: ER TABLENAME NOT ALLOWED HERE; SQLSTATE: 42000

Message: Table '%s' from one of the SELECTs cannot be used in %s

Error number: 1251; Symbol: ER NOT SUPPORTED AUTH MODE; SQLSTATE: 08004

Message: Client does not support authentication protocol requested by server; consider upgrading

MySQL client

Error number: 1252; Symbol: ER SPATIAL CANT HAVE NULL; SQLSTATE: 42000

Message: All parts of a SPATIAL index must be NOT NULL

Error number: 1253; Symbol: ER COLLATION CHARSET MISMATCH; SQLSTATE: 42000

Message: COLLATION '%s' is not valid for CHARACTER SET '%s'

Error number: 1256; Symbol: ER TOO BIG FOR UNCOMPRESS; SQLSTATE: HY000

Message: Uncompressed data size too large; the maximum size is %d (probably, length of

uncompressed data was corrupted)

Error number: 1257; Symbol: ER ZLIB Z MEM ERROR; SQLSTATE: HY000

Message: ZLIB: Not enough memory

Error number: 1258; Symbol: ER ZLIB Z BUF ERROR; SQLSTATE: HY000

Message: ZLIB: Not enough room in the output buffer (probably, length of uncompressed data was

corrupted)

Error number: 1259; Symbol: ER_ZLIB_Z_DATA_ERROR; SQLSTATE: HY000

Message: ZLIB: Input data corrupted

Error number: 1260; Symbol: ER CUT VALUE GROUP CONCAT; SQLSTATE: HY000

Message: Row %u was cut by GROUP CONCAT()

Error number: 1261; Symbol: ER WARN TOO FEW RECORDS; SQLSTATE: 01000

Message: Row %ld doesn't contain data for all columns

Error number: 1262; Symbol: ER WARN TOO MANY RECORDS; SQLSTATE: 01000

Message: Row %ld was truncated; it contained more data than there were input columns

Error number: 1263; Symbol: ER_WARN_NULL_TO_NOTNULL; SQLSTATE: 22004 Message: Column set to default value; NULL supplied to NOT NULL column '%s' at row %ld

Error number: 1264; Symbol: ER_WARN_DATA_OUT_OF_RANGE; SQLSTATE: 22003 Message: Out of range value for column '%s' at row %ld

Error number: 1265; Symbol: WARN DATA TRUNCATED; SQLSTATE: 01000

Message: Data truncated for column '%s' at row %ld

Error number: 1266; Symbol: ER_WARN_USING_OTHER_HANDLER; SQLSTATE: HY000 Message: Using storage engine %s for table '%s'

Error number: 1267; Symbol: ER_CANT_AGGREGATE_2COLLATIONS; SQLSTATE: HY000

Message: Illegal mix of collations (%s,%s) and (%s,%s) for operation '%s'

Error number: 1269; Symbol: ER_REVOKE_GRANTS; SQLSTATE: HY000 Message: Can't revoke all privileges for one or more of the requested users

Error number: 1270; Symbol: ER_CANT_AGGREGATE_3COLLATIONS; SQLSTATE: HY000 Message: Illegal mix of collations (%s,%s), (%s,%s), (%s,%s) for operation '%s'

Error number: 1271; Symbol: ER_CANT_AGGREGATE_NCOLLATIONS; SQLSTATE: HY000 Message: Illegal mix of collations for operation '%s'

Error number: 1272; Symbol: ER_VARIABLE_IS_NOT_STRUCT; SQLSTATE: HY000 Message: Variable '%s' is not a variable component (can't be used as XXXX.variable name)

Error number: 1273; Symbol: ER_UNKNOWN_COLLATION; SQLSTATE: HY000 Message: Unknown collation: '%s'

Error number: 1274; Symbol: ER_SLAVE_IGNORED_SSL_PARAMS; SQLSTATE: HY000 Message: SSL parameters in CHANGE MASTER are ignored because this MySQL slave was compiled without SSL support; they can be used later if MySQL slave with SSL is started

Error number: 1275; Symbol: ER_SERVER_IS_IN_SECURE_AUTH_MODE; SQLSTATE: HY000

Message: Server is running in --secure-auth mode, but '%s'@'%s' has a password in the old format; please change the password to the new format

(说明:

ER_SERVER_IS_IN_SECURE_AUTH_MODE was removed after 8.0.15.

Error number: 1276; Symbol: ER_WARN_FIELD_RESOLVED; SQLSTATE: HY000 Message: Field or reference '%s%s%s%s' of SELECT #%d was resolved in SELECT #%d

Error number: 1277; Symbol: ER_BAD_SLAVE_UNTIL_COND; SQLSTATE: HY000 Message: Incorrect parameter or combination of parameters for START SLAVE UNTIL

Error number: 1278; Symbol: ER_MISSING_SKIP_SLAVE; SQLSTATE: HY000 Message: It is recommended to use --skip-replica-start when doing step-by-step replication with START SLAVE UNTIL; otherwise, you will get problems if you get an unexpected slave's mysqld restart

Error number: 1279; Symbol: ER_UNTIL_COND_IGNORED; SQLSTATE: HY000 Message: SQL thread is not to be started so UNTIL options are ignored

Error number: 1280; Symbol: ER WRONG NAME FOR INDEX; SQLSTATE: 42000

Message: Incorrect index name '%s'

Error number: 1281; Symbol: ER_WRONG_NAME_FOR_CATALOG; SQLSTATE: 42000

Message: Incorrect catalog name '%s'

Error number: 1282; Symbol: ER_WARN_QC_RESIZE; SQLSTATE: HY000 Message: Query cache failed to set size %lu; new query cache size is %lu

🛈 说明:

ER_WARN_QC_RESIZE was removed after 8.0.2.

Error number: 1283; Symbol: ER_BAD_FT_COLUMN; SQLSTATE: HY000

Message: Column '%s' cannot be part of FULLTEXT index

Error number: 1284; Symbol: ER UNKNOWN KEY CACHE; SQLSTATE: HY000

Message: Unknown key cache '%s'

Error number: 1285; Symbol: ER_WARN_HOSTNAME_WONT_WORK; SQLSTATE: HY000 Message: MySQL is started in --skip-name-resolve mode; you must restart it without this switch for this grant to work

Error number: 1286; Symbol: ER UNKNOWN STORAGE ENGINE; SQLSTATE: 42000

Message: Unknown storage engine '%s'

Error number: 1287; Symbol: ER_WARN_DEPRECATED_SYNTAX; SQLSTATE: HY000 Message: '%s' is deprecated and will be removed in a future release. Please use %s instead

Error number: 1288; Symbol: ER_NON_UPDATABLE_TABLE; SQLSTATE: HY000 Message: The target table %s of the %s is not updatable

Error number: 1289; Symbol: ER_FEATURE_DISABLED; SQLSTATE: HY000 Message: The '%s' feature is disabled; you need MySQL built with '%s' to have it working

Error number: 1290; Symbol: ER_OPTION_PREVENTS_STATEMENT; SQLSTATE: HY000 Message: The MySQL server is running with the %s option so it cannot execute this statement

Error number: 1291; Symbol: ER_DUPLICATED_VALUE_IN_TYPE; SQLSTATE: HY000 Message: Column '%s' has duplicated value '%s' in %s

Error number: 1292; Symbol: ER_TRUNCATED_WRONG_VALUE; SQLSTATE: 22007 Message: Truncated incorrect %s value: '%s'

Error number: 1294; Symbol: ER_INVALID_ON_UPDATE; SQLSTATE: HY000 Message: Invalid ON UPDATE clause for '%s' column

Error number: 1295; Symbol: ER_UNSUPPORTED_PS; SQLSTATE: HY000 Message: This command is not supported in the prepared statement protocol yet

Error number: 1296; Symbol: ER_GET_ERRMSG; SQLSTATE: HY000 Message: Got error %d '%s' from %s

Error number: 1297; Symbol: ER_GET_TEMPORARY_ERRMSG; SQLSTATE: HY000 Message: Got temporary error %d '%s' from %s

Error number: 1298; Symbol: ER_UNKNOWN_TIME_ZONE; SQLSTATE: HY000 Message: Unknown or incorrect time zone: '%s'

Error number: 1299; Symbol: ER_WARN_INVALID_TIMESTAMP; SQLSTATE: HY000 Message: Invalid TIMESTAMP value in column '%s' at row %ld

Error number: 1300; Symbol: ER_INVALID_CHARACTER_STRING; SQLSTATE: HY000 Message: Invalid %s character string: '%s'

Error number: 1301; Symbol: ER_WARN_ALLOWED_PACKET_OVERFLOWED; SQLSTATE: HY000

Message: Result of %s() was larger than max allowed packet (%ld) - truncated

Error number: 1302; Symbol: ER CONFLICTING DECLARATIONS; SQLSTATE: HY000

Message: Conflicting declarations: '%s%s' and '%s%s'

Error number: 1303; Symbol: ER SP NO RECURSIVE CREATE; SQLSTATE: 2F003

Message: Can't create a %s from within another stored routine

Error number: 1304; Symbol: ER SP ALREADY EXISTS; SQLSTATE: 42000

Message: %s %s already exists

2.2 错误码及错误信息汇总 02

Error number: 1305; Symbol: ER SP DOES NOT EXIST; SQLSTATE: 42000

Message: %s %s does not exist

Error number: 1306; Symbol: ER SP DROP FAILED; SQLSTATE: HY000

Message: Failed to DROP %s %s

Error number: 1307; Symbol: ER SP STORE FAILED; SQLSTATE: HY000

Message: Failed to CREATE %s %s

Error number: 1308; Symbol: ER SP LILABEL MISMATCH; SQLSTATE: 42000

Message: %s with no matching label: %s

Error number: 1309; Symbol: ER SP LABEL REDEFINE; SQLSTATE: 42000

Message: Redefining label %s

Error number: 1310; Symbol: ER SP LABEL MISMATCH; SQLSTATE: 42000

Message: End-label %s without match

Error number: 1311; Symbol: ER SP UNINIT VAR; SQLSTATE: 01000

Message: Referring to uninitialized variable %s

Error number: 1312; Symbol: ER_SP_BADSELECT; SQLSTATE: 0A000 Message: PROCEDURE %s can't return a result set in the given context

Error number: 1313; Symbol: ER SP BADRETURN; SQLSTATE: 42000

Message: RETURN is only allowed in a FUNCTION

Error number: 1314; Symbol: ER SP BADSTATEMENT; SQLSTATE: 0A000

Message: %s is not allowed in stored procedures

Error number: 1315; Symbol: ER_UPDATE_LOG_DEPRECATED_IGNORED; SQLSTATE: 42000

Message: The update log is deprecated and replaced by the binary log; SET SQL_LOG_UPDATE has been ignored.

Error number: 1316; Symbol: ER_UPDATE_LOG_DEPRECATED_TRANSLATED; SQLSTATE: 42000

Message: The update log is deprecated and replaced by the binary log; SET SQL_LOG_UPDATE has been translated to SET SQL_LOG_BIN.

Error number: 1317; Symbol: ER_QUERY_INTERRUPTED; SQLSTATE: 70100 Message: Query execution was interrupted

Error number: 1318; Symbol: ER_SP_WRONG_NO_OF_ARGS; SQLSTATE: 42000 Message: Incorrect number of arguments for %s %s; expected %u, got %u

Error number: 1319; Symbol: ER_SP_COND_MISMATCH; SQLSTATE: 42000 Message: Undefined CONDITION: %s

Error number: 1320; Symbol: ER_SP_NORETURN; SQLSTATE: 42000 Message: No RETURN found in FUNCTION %s

Error number: 1321; Symbol: ER_SP_NORETURNEND; SQLSTATE: 2F005 Message: FUNCTION %s ended without RETURN

Error number: 1322; Symbol: ER_SP_BAD_CURSOR_QUERY; SQLSTATE: 42000 Message: Cursor statement must be a SELECT

Error number: 1323; Symbol: ER_SP_BAD_CURSOR_SELECT; SQLSTATE: 42000 Message: Cursor SELECT must not have INTO

Error number: 1324; Symbol: ER_SP_CURSOR_MISMATCH; SQLSTATE: 42000

Message: Undefined CURSOR: %s

Error number: 1325; Symbol: ER_SP_CURSOR_ALREADY_OPEN; SQLSTATE: 24000 Message: Cursor is already open

Error number: 1326; Symbol: ER_SP_CURSOR_NOT_OPEN; SQLSTATE: 24000 Message: Cursor is not open

Error number: 1327; Symbol: ER SP UNDECLARED VAR; SQLSTATE: 42000

Message: Undeclared variable: %s

Error number: 1328; Symbol: ER SP WRONG NO OF FETCH ARGS; SQLSTATE: HY000

Message: Incorrect number of FETCH variables

Error number: 1329; Symbol: ER SP FETCH NO DATA; SQLSTATE: 02000

Message: No data - zero rows fetched, selected, or processed

Error number: 1330; Symbol: ER SP DUP PARAM; SQLSTATE: 42000

Message: Duplicate parameter: %s

Error number: 1331; Symbol: ER SP DUP VAR; SQLSTATE: 42000

Message: Duplicate variable: %s

Error number: 1332; Symbol: ER SP DUP COND; SQLSTATE: 42000

Message: Duplicate condition: %s

Error number: 1333; Symbol: ER SP DUP CURS; SQLSTATE: 42000

Message: Duplicate cursor: %s

Error number: 1334; Symbol: ER SP CANT ALTER; SQLSTATE: HY000

Message: Failed to ALTER %s %s

Error number: 1335; Symbol: ER SP SUBSELECT NYI; SQLSTATE: 0A000

Message: Subquery value not supported

Error number: 1336; Symbol: ER STMT NOT ALLOWED IN SF OR TRG; SQLSTATE:

0A000

Message: %s is not allowed in stored function or trigger

Error number: 1337; Symbol: ER_SP_VARCOND_AFTER_CURSHNDLR; SQLSTATE: 42000

Message: Variable or condition declaration after cursor or handler declaration

Error number: 1338; Symbol: ER SP CURSOR AFTER HANDLER; SQLSTATE: 42000

Message: Cursor declaration after handler declaration

Error number: 1339; Symbol: ER SP CASE NOT FOUND; SQLSTATE: 20000

Message: Case not found for CASE statement

Error number: 1340; Symbol: ER FPARSER TOO BIG FILE; SQLSTATE: HY000

Message: Configuration file '%s' is too big

Error number: 1341; Symbol: ER FPARSER BAD HEADER; SQLSTATE: HY000

Message: Malformed file type header in file '%s'

Error number: 1342; Symbol: ER FPARSER EOF IN COMMENT; SQLSTATE: HY000

Message: Unexpected end of file while parsing comment '%s'

Error number: 1343; Symbol: ER FPARSER ERROR IN PARAMETER; SQLSTATE: HY000

Message: Error while parsing parameter '%s' (line: '%s')

Error number: 1344; Symbol: ER FPARSER EOF IN UNKNOWN PARAMETER; SQLSTATE:

HY000

Message: Unexpected end of file while skipping unknown parameter '%s'

Error number: 1345; Symbol: ER VIEW NO EXPLAIN; SQLSTATE: HY000

Message: EXPLAIN/SHOW can not be issued; lacking privileges for underlying table

Error number: 1347; Symbol: ER WRONG OBJECT; SQLSTATE: HY000

Message: '%s.%s' is not %s

可能原因及解决办法:命名对象对于尝试对其进行的操作类型不正确。它必须是指定类型的对象。示例: HANDLER OPEN 需要一个基表,而不是视图。如果尝试在作为数据字典表上的视图实现的 INFORMATION SCHEMA 表上失败。

Error number: 1348; Symbol: ER NONUPDATEABLE COLUMN; SQLSTATE: HY000

Message: Column '%s' is not updatable

Error number: 1350; Symbol: ER VIEW SELECT CLAUSE; SQLSTATE: HY000

Message: View's SELECT contains a '%s' clause

Error number: 1351; Symbol: ER_VIEW_SELECT_VARIABLE; SQLSTATE: HY000

Message: View's SELECT contains a variable or parameter

Error number: 1352; Symbol: ER_VIEW_SELECT_TMPTABLE; SQLSTATE: HY000

Message: View's SELECT refers to a temporary table '%s'

Error number: 1353; Symbol: ER VIEW WRONG LIST; SQLSTATE: HY000

Message: In definition of view, derived table or common table expression, SELECT list and column

names list have different column counts

Error number: 1354; Symbol: ER WARN VIEW MERGE; SQLSTATE: HY000

Message: View merge algorithm can't be used here for now (assumed undefined algorithm)

Error number: 1355; Symbol: ER WARN VIEW WITHOUT KEY; SQLSTATE: HY000

Message: View being updated does not have complete key of underlying table in it

Error number: 1356; Symbol: ER VIEW INVALID; SQLSTATE: HY000

Message: View '%s.%s' references invalid table(s) or column(s) or function(s) or definer/invoker of

view lack rights to use them

Error number: 1357; Symbol: ER SP NO DROP SP; SQLSTATE: HY000

Message: Can't drop or alter a %s from within another stored routine

Error number: 1359; Symbol: ER TRG ALREADY EXISTS; SQLSTATE: HY000

Message: Trigger already exists

Error number: 1360; Symbol: ER_TRG_DOES_NOT_EXIST; SQLSTATE: HY000

Message: Trigger does not exist

Error number: 1361; Symbol: ER_TRG_ON_VIEW_OR_TEMP_TABLE; SQLSTATE: HY000

Message: Trigger's '%s' is view or temporary table

Error number: 1362; Symbol: ER TRG CANT CHANGE ROW; SQLSTATE: HY000

Message: Updating of %s row is not allowed in %strigger

Error number: 1363; Symbol: ER TRG NO SUCH ROW IN TRG; SQLSTATE: HY000

Message: There is no %s row in %s trigger

Error number: 1364; Symbol: ER_NO_DEFAULT_FOR_FIELD; SQLSTATE: HY000

Message: Field '%s' doesn't have a default value

Error number: 1365; Symbol: ER DIVISION BY ZERO; SQLSTATE: 22012

Message: Division by 0

Error number: 1366; Symbol: ER_TRUNCATED_WRONG_VALUE_FOR_FIELD; SQLSTATE:

HY000

Message: Incorrect %s value: '%s' for column '%s' at row %ld

Error number: 1367; Symbol: ER ILLEGAL VALUE FOR TYPE; SQLSTATE: 22007

Message: Illegal %s '%s' value found during parsing

Error number: 1368; Symbol: ER_VIEW_NONUPD_CHECK; SQLSTATE: HY000

Message: CHECK OPTION on non-updatable view '%s.%s'

Error number: 1369; Symbol: ER VIEW CHECK FAILED; SQLSTATE: HY000

Message: CHECK OPTION failed '%s.%s'

Error number: 1370; Symbol: ER PROCACCESS DENIED ERROR; SQLSTATE: 42000

Message: %s command denied to user '%s'@'%s' for routine '%s'

Error number: 1371; Symbol: ER RELAY LOG FAIL; SQLSTATE: HY000

Message: Failed purging old relay logs: %s

Error number: 1373; Symbol: ER UNKNOWN TARGET BINLOG; SQLSTATE: HY000

Message: Target log not found in binlog index

Error number: 1374; Symbol: ER IO ERR LOG INDEX READ; SQLSTATE: HY000

Message: I/O error reading log index file

Error number: 1375; Symbol: ER BINLOG PURGE PROHIBITED; SQLSTATE: HY000

Message: Server configuration does not permit binlog purge

Error number: 1376; Symbol: ER FSEEK FAIL; SQLSTATE: HY000

Message: Failed on fseek()

Error number: 1377; Symbol: ER BINLOG PURGE FATAL ERR; SQLSTATE: HY000

Message: Fatal error during log purge

Error number: 1378; Symbol: ER LOG IN USE; SQLSTATE: HY000

Message: A purgeable log is in use, will not purge

Error number: 1379; Symbol: ER_LOG_PURGE_UNKNOWN_ERR; SQLSTATE: HY000

Message: Unknown error during log purge

Error number: 1380; Symbol: ER RELAY LOG INIT; SQLSTATE: HY000

Message: Failed initializing relay log position: %s

Error number: 1381; Symbol: ER NO BINARY LOGGING; SQLSTATE: HY000

Message: You are not using binary logging

Error number: 1382; Symbol: ER_RESERVED_SYNTAX; SQLSTATE: HY000

Message: The '%s' syntax is reserved for purposes internal to the MySQL server

Error number: 1390; Symbol: ER_PS_MANY_PARAM; SQLSTATE: HY000

Message: Prepared statement contains too many placeholders

Error number: 1391; Symbol: ER KEY PART 0; SQLSTATE: HY000

Message: Key part '%s' length cannot be 0

Error number: 1392; Symbol: ER VIEW CHECKSUM; SQLSTATE: HY000

Message: View text checksum failed

Error number: 1393; Symbol: ER_VIEW_MULTIUPDATE; SQLSTATE: HY000 Message: Can not modify more than one base table through a join view '%s.%s'

Error number: 1394; Symbol: ER VIEW NO INSERT FIELD LIST; SQLSTATE: HY000

Message: Can not insert into join view '%s.%s' without fields list

Error number: 1395; Symbol: ER VIEW DELETE MERGE VIEW; SQLSTATE: HY000

Message: Can not delete from join view '%s.%s'

Error number: 1396; Symbol: ER CANNOT USER; SQLSTATE: HY000

Message: Operation %s failed for %s

Error number: 1397; Symbol: ER_XAER NOTA; SQLSTATE: XAE04

Message: XAER NOTA: Unknown XID

Error number: 1398; Symbol: ER_XAER_INVAL; SQLSTATE: XAE05 Message: XAER INVAL: Invalid arguments (or unsupported command)

Error number: 1399; Symbol: ER XAER RMFAIL; SQLSTATE: XAE07

Message: XAER RMFAIL: The command cannot be executed when global transaction is in the %s

state

Error number: 1400; Symbol: ER_XAER_OUTSIDE; SQLSTATE: XAE09 Message: XAER_OUTSIDE: Some work is done outside global transaction

Error number: 1401; Symbol: ER XAER RMERR; SQLSTATE: XAE03

Message: XAER RMERR: Fatal error occurred in the transaction branch - check your data for

consistency

Error number: 1402; Symbol: ER XA RBROLLBACK; SQLSTATE: XA100

Message: XA RBROLLBACK: Transaction branch was rolled back

Error number: 1403; Symbol: ER NONEXISTING PROC GRANT; SQLSTATE: 42000

Message: There is no such grant defined for user '%s' on host '%s' on routine '%s'

Error number: 1404; Symbol: ER_PROC_AUTO_GRANT_FAIL; SQLSTATE: HY000

Message: Failed to grant EXECUTE and ALTER ROUTINE privileges

Error number: 1405; Symbol: ER PROC AUTO REVOKE FAIL; SQLSTATE: HY000

Message: Failed to revoke all privileges to dropped routine

Error number: 1406; Symbol: ER DATA TOO LONG; SQLSTATE: 22001

Message: Data too long for column '%s' at row %ld

Error number: 1407; Symbol: ER SP BAD SQLSTATE; SQLSTATE: 42000

Message: Bad SQLSTATE: '%s'

Error number: 1408; Symbol: ER STARTUP; SQLSTATE: HY000

Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s

Error number: 1409; Symbol: ER LOAD FROM FIXED SIZE ROWS TO VAR; SQLSTATE:

HY000

Message: Can't load value from file with fixed size rows to variable

Error number: 1410; Symbol: ER_CANT_CREATE_USER_WITH_GRANT; SQLSTATE: 42000

Message: You are not allowed to create a user with GRANT

Error number: 1411; Symbol: ER_WRONG_VALUE_FOR_TYPE; SQLSTATE: HY000

Message: Incorrect %s value: '%s' for function %s

Error number: 1412; Symbol: ER TABLE DEF CHANGED; SQLSTATE: HY000

Message: Table definition has changed, please retry transaction

Error number: 1413; Symbol: ER SP DUP HANDLER; SQLSTATE: 42000

Message: Duplicate handler declared in the same block

Error number: 1414; Symbol: ER_SP_NOT_VAR_ARG; SQLSTATE: 42000

Message: OUT or INOUT argument %d for routine %s is not a variable or NEW pseudo-variable in

BEFORE trigger

Error number: 1415; Symbol: ER SP NO RETSET; SQLSTATE: 0A000

Message: Not allowed to return a result set from a %s

Error number: 1416; Symbol: ER CANT CREATE GEOMETRY OBJECT; SQLSTATE: 22003

Message: Cannot get geometry object from data you send to the GEOMETRY field

Error number: 1418; Symbol: ER BINLOG UNSAFE ROUTINE; SQLSTATE: HY000

Message: This function has none of DETERMINISTIC, NO SQL, or READS SQL DATA in its declaration and binary logging is enabled (you *might* want to use the less safe log bin trust function creators variable)

Error number: 1419; Symbol: ER_BINLOG_CREATE_ROUTINE_NEED_SUPER; SQLSTATE: HY000

Message: You do not have the SUPER privilege and binary logging is enabled (you *might* want to use the less safe log bin trust function creators variable)

Error number: 1421; Symbol: ER_STMT_HAS_NO_OPEN_CURSOR; SQLSTATE: HY000 Message: The statement (%lu) has no open cursor.

Error number: 1422; Symbol: ER_COMMIT_NOT_ALLOWED_IN_SF_OR_TRG; SQLSTATE: HY000

Message: Explicit or implicit commit is not allowed in stored function or trigger.

Error number: 1423; Symbol: ER_NO_DEFAULT_FOR_VIEW_FIELD; SQLSTATE: HY000 Message: Field of view '%s.%s' underlying table doesn't have a default value

Error number: 1424; Symbol: ER_SP_NO_RECURSION; SQLSTATE: HY000 Message: Recursive stored functions and triggers are not allowed.

Error number: 1425; Symbol: ER_TOO_BIG_SCALE; SQLSTATE: 42000 Message: Too big scale %d specified for column '%s'. Maximum is %lu.

Error number: 1426; Symbol: ER_TOO_BIG_PRECISION; SQLSTATE: 42000 Message: Too-big precision %d specified for '%s'. Maximum is %lu.

Error number: 1427; Symbol: ER_M_BIGGER_THAN_D; SQLSTATE: 42000 Message: For float(M,D), double(M,D) or decimal(M,D), M must be >= D (column '%s').

Error number: 1428; Symbol: ER_WRONG_LOCK_OF_SYSTEM_TABLE; SQLSTATE: HY000 Message: You can't combine write-locking of system tables with other tables or lock types

Error number: 1429; Symbol: ER_CONNECT_TO_FOREIGN_DATA_SOURCE; SQLSTATE: HY000

Message: Unable to connect to foreign data source: %s

Error number: 1430; Symbol: ER_QUERY_ON_FOREIGN_DATA_SOURCE; SQLSTATE: HY000

Message: There was a problem processing the query on the foreign data source. Data source error: %s

Error number: 1431; Symbol: ER_FOREIGN_DATA_SOURCE_DOESNT_EXIST; SQLSTATE: HY000

Message: The foreign data source you are trying to reference does not exist. Data source error: %s

Error number: 1432; Symbol: ER_FOREIGN_DATA_STRING_INVALID_CANT_CREATE; SQLSTATE: HY000

Message: Can't create federated table. The data source connection string '%s' is not in the correct format

Error number: 1433; Symbol: ER_FOREIGN_DATA_STRING_INVALID; SQLSTATE: HY000 Message: The data source connection string '%s' is not in the correct format

Error number: 1435; Symbol: ER_TRG_IN_WRONG_SCHEMA; SQLSTATE: HY000 Message: Trigger in wrong schema

Error number: 1436; Symbol: ER_STACK_OVERRUN_NEED_MORE; SQLSTATE: HY000 Message: Thread stack overrun: %ld bytes used of a %ld byte stack, and %ld bytes needed. Use 'mysqld --thread stack=#' to specify a bigger stack.

Error number: 1437; Symbol: ER_TOO_LONG_BODY; SQLSTATE: 42000 Message: Routine body for '%s' is too long

Error number: 1438; Symbol: ER_WARN_CANT_DROP_DEFAULT_KEYCACHE; SQLSTATE: HY000

Message: Cannot drop default keycache

Error number: 1439; Symbol: ER_TOO_BIG_DISPLAYWIDTH; SQLSTATE: 42000 Message: Display width out of range for column '%s' (max = %lu)

Error number: 1440; Symbol: ER_XAER_DUPID; SQLSTATE: XAE08

Message: XAER DUPID: The XID already exists

Error number: 1441; Symbol: ER_DATETIME_FUNCTION_OVERFLOW; SQLSTATE: 22008 Message: Datetime function: %s field overflow

Error number: 1442; Symbol: ER_CANT_UPDATE_USED_TABLE_IN_SF_OR_TRG; SQLSTATE: HY000

Message: Can't update table '%s' in stored function/trigger because it is already used by statement which invoked this stored function/trigger.

Error number: 1443; Symbol: ER_VIEW_PREVENT_UPDATE; SQLSTATE: HY000

Message: The definition of table '%s' prevents operation %s on table '%s'.

Error number: 1444; Symbol: ER PS NO RECURSION; SQLSTATE: HY000

Message: The prepared statement contains a stored routine call that refers to that same statement. It's not allowed to execute a prepared statement in such a recursive manner

Error number: 1445; Symbol: ER SP CANT SET AUTOCOMMIT; SQLSTATE: HY000

Message: Not allowed to set autocommit from a stored function or trigger

Error number: 1447; Symbol: ER_VIEW_FRM_NO_USER; SQLSTATE: HY000

Message: View '%s'.'%s' has no definer information (old table format). Current user is used as

definer. Please recreate the view!

Error number: 1448; Symbol: ER_VIEW_OTHER_USER; SQLSTATE: HY000 Message: You need the SUPER privilege for creation view with '%s'@'%s' definer

Error number: 1449; Symbol: ER NO SUCH USER; SQLSTATE: HY000

Message: The user specified as a definer ('%s'@'%s') does not exist

Error number: 1450; Symbol: ER FORBID SCHEMA CHANGE; SQLSTATE: HY000

Message: Changing schema from '%s' to '%s' is not allowed.

Error number: 1451; Symbol: ER ROW IS REFERENCED 2; SQLSTATE: 23000

Message: Cannot delete or update a parent row: a foreign key constraint fails (%s)

可能原因及解决办法: 当您尝试删除具有子项的父行并且外键约束失败时,InnoDB 会报告此

错误。先删除子行。

Error number: 1452; Symbol: ER NO REFERENCED ROW 2; SQLSTATE: 23000

Message: Cannot add or update a child row: a foreign key constraint fails (%s)

可能原因及解决办法: 当您尝试添加行但没有父行并且外键约束失败时, InnoDB 会报告此错

误。首先添加父行。

Error number: 1453; Symbol: ER SP BAD VAR SHADOW; SQLSTATE: 42000

Message: Variable '%s' must be quoted with `...`, or renamed

Error number: 1454; Symbol: ER_TRG_NO_DEFINER; SQLSTATE: HY000

Message: No definer attribute for trigger '%s'.'%s'. It's disallowed to create trigger without definer.

Error number: 1455; Symbol: ER OLD FILE FORMAT; SQLSTATE: HY000

Message: '%s' has an old format, you should re-create the '%s' object(s)

Error number: 1456; Symbol: ER SP RECURSION LIMIT; SQLSTATE: HY000

Message: Recursive limit %d (as set by the max_sp_recursion_depth variable) was exceeded for routine %s

Error number: 1458; Symbol: ER SP WRONG NAME; SQLSTATE: 42000

Message: Incorrect routine name '%s'

Error number: 1459; Symbol: ER_TABLE_NEEDS_UPGRADE; SQLSTATE: HY000 Message: Table upgrade required. Please do "REPAIR TABLE `%s`" or dump/reload to fix it!

Error number: 1460; Symbol: ER SP NO AGGREGATE; SQLSTATE: 42000

Message: AGGREGATE is not supported for stored functions

Error number: 1461; Symbol: ER_MAX_PREPARED_STMT_COUNT_REACHED; SQLSTATE:

42000

Message: Can't create more than max prepared stmt count statements (current value: %lu)

Error number: 1462; Symbol: ER VIEW_RECURSIVE; SQLSTATE: HY000

Message: '%s'.'%s' contains view recursion

Error number: 1463; Symbol: ER NON GROUPING FIELD USED; SQLSTATE: 42000

Message: Non-grouping field '%s' is used in %s clause

Error number: 1464; Symbol: ER TABLE CANT HANDLE SPKEYS; SQLSTATE: HY000

Message: The used table type doesn't support SPATIAL indexes

Error number: 1465; Symbol: ER NO TRIGGERS ON SYSTEM SCHEMA; SQLSTATE:

HY000

Message: Triggers can not be created on system tables

Error number: 1466; Symbol: ER REMOVED SPACES; SQLSTATE: HY000

Message: Leading spaces are removed from name '%s'

Error number: 1467; Symbol: ER_AUTOINC_READ_FAILED; SQLSTATE: HY000

Message: Failed to read auto-increment value from storage engine

Error number: 1468; Symbol: ER USERNAME; SQLSTATE: HY000

Message: user name

Error number: 1469; Symbol: ER HOSTNAME; SQLSTATE: HY000

Message: host name

Error number: 1470; Symbol: ER WRONG STRING LENGTH; SQLSTATE: HY000

Message: String '%s' is too long for %s (should be no longer than %d)

Error number: 1471; Symbol: ER NON INSERTABLE TABLE; SQLSTATE: HY000

Message: The target table %s of the %s is not insertable-into

Error number: 1472; Symbol: ER ADMIN WRONG MRG TABLE; SQLSTATE: HY000

Message: Table '%s' is differently defined or of non-MyISAM type or doesn't exist

Error number: 1473; Symbol: ER TOO HIGH LEVEL OF NESTING FOR SELECT;

SQLSTATE: HY000

Message: Too high level of nesting for select

Error number: 1474; Symbol: ER NAME BECOMES EMPTY; SQLSTATE: HY000

Message: Name '%s' has become "

Error number: 1475; Symbol: ER_AMBIGUOUS_FIELD_TERM; SQLSTATE: HY000

Message: First character of the FIELDS TERMINATED string is ambiguous; please use non-

optional and non-empty FIELDS ENCLOSED BY

Error number: 1476; Symbol: ER FOREIGN SERVER EXISTS; SQLSTATE: HY000

Message: The foreign server, %s, you are trying to create already exists.

Error number: 1477; Symbol: ER FOREIGN SERVER DOESNT EXIST; SQLSTATE: HY000

Message: The foreign server name you are trying to reference does not exist. Data source error: %s

Error number: 1478; Symbol: ER ILLEGAL HA CREATE OPTION; SQLSTATE: HY000

Message: Table storage engine '%s' does not support the create option '%s'

Error number: 1479; Symbol: ER PARTITION REQUIRES VALUES ERROR; SQLSTATE:

HY000

Message: Syntax error: %s PARTITIONING requires definition of VALUES %s for each partition

Error number: 1480; Symbol: ER PARTITION WRONG VALUES ERROR; SQLSTATE:

HY000

Message: Only %s PARTITIONING can use VALUES %s in partition definition

Error number: 1481; Symbol: ER PARTITION MAXVALUE ERROR; SQLSTATE: HY000

Message: MAXVALUE can only be used in last partition definition

Error number: 1484; Symbol: ER PARTITION WRONG NO PART ERROR; SQLSTATE:

HY000

Message: Wrong number of partitions defined, mismatch with previous setting

Error number: 1485; Symbol: ER_PARTITION_WRONG_NO_SUBPART_ERROR; SQLSTATE:

HY000

Message: Wrong number of subpartitions defined, mismatch with previous setting

Error number: 1486; Symbol: ER WRONG EXPR IN PARTITION FUNC ERROR;

SQLSTATE: HY000

Message: Constant, random or timezone-dependent expressions in (sub)partitioning function are not

allowed

Error number: 1488; Symbol: ER FIELD NOT FOUND PART ERROR; SQLSTATE: HY000

Message: Field in list of fields for partition function not found in table

Error number: 1490; Symbol: ER INCONSISTENT PARTITION INFO ERROR; SQLSTATE:

HY000

Message: The partition info in the frm file is not consistent with what can be written into the frm file

Error number: 1491; Symbol: ER PARTITION FUNC NOT ALLOWED ERROR; SQLSTATE:

HY000

Message: The %s function returns the wrong type

Error number: 1492; Symbol: ER PARTITIONS MUST BE DEFINED ERROR; SQLSTATE:

HY000

Message: For %s partitions each partition must be defined

Error number: 1493; Symbol: ER RANGE NOT INCREASING ERROR; SQLSTATE: HY000

Message: VALUES LESS THAN value must be strictly increasing for each partition

Error number: 1494; Symbol: ER INCONSISTENT TYPE OF FUNCTIONS ERROR;

SQLSTATE: HY000

Message: VALUES value must be of same type as partition function

Error number: 1495; Symbol: ER_MULTIPLE_DEF_CONST_IN_LIST_PART_ERROR;

SOLSTATE: HY000

Message: Multiple definition of same constant in list partitioning

Error number: 1496; Symbol: ER PARTITION ENTRY ERROR; SQLSTATE: HY000

Message: Partitioning can not be used stand-alone in query

Error number: 1497; Symbol: ER_MIX_HANDLER_ERROR; SQLSTATE: HY000 Message: The mix of handlers in the partitions is not allowed in this version of MySQL

Error number: 1498; Symbol: ER_PARTITION_NOT_DEFINED_ERROR; SQLSTATE: HY000 Message: For the partitioned engine it is necessary to define all %s

Error number: 1499; Symbol: ER_TOO_MANY_PARTITIONS_ERROR; SQLSTATE: HY000 Message: Too many partitions (including subpartitions) were defined

Error number: 1500; Symbol: ER_SUBPARTITION_ERROR; SQLSTATE: HY000 Message: It is only possible to mix RANGE/LIST partitioning with HASH/KEY partitioning for subpartitioning

Error number: 1501; Symbol: ER_CANT_CREATE_HANDLER_FILE; SQLSTATE: HY000 Message: Failed to create specific handler file

Error number: 1502; Symbol: ER_BLOB_FIELD_IN_PART_FUNC_ERROR; SQLSTATE: HY000 Message: A BLOB field is not allowed in partition function

Error number: 1503; Symbol: ER_UNIQUE_KEY_NEED_ALL_FIELDS_IN_PF; SQLSTATE: HY000

Message: A %s must include all columns in the table's partitioning function (prefixed columns are not considered).

Error number: 1504; Symbol: ER_NO_PARTS_ERROR; SQLSTATE: HY000 Message: Number of %s = 0 is not an allowed value

Error number: 1505; Symbol: ER_PARTITION_MGMT_ON_NONPARTITIONED; SQLSTATE: HY000

Message: Partition management on a not partitioned table is not possible

Error number: 1506; Symbol: ER_FOREIGN_KEY_ON_PARTITIONED; SQLSTATE: HY000 Message: Foreign keys are not yet supported in conjunction with partitioning

Error number: 1507; Symbol: ER_DROP_PARTITION_NON_EXISTENT; SQLSTATE: HY000 Message: Error in list of partitions to %s

Error number: 1508; Symbol: ER_DROP_LAST_PARTITION; SQLSTATE: HY000 Message: Cannot remove all partitions, use DROP TABLE instead

Error number: 1509; Symbol: ER_COALESCE_ONLY_ON_HASH_PARTITION; SQLSTATE: HY000

Message: COALESCE PARTITION can only be used on HASH/KEY partitions

Error number: 1510; Symbol: ER REORG HASH ONLY ON SAME NO; SQLSTATE: HY000

Message: REORGANIZE PARTITION can only be used to reorganize partitions not to change their numbers

Error number: 1511; Symbol: ER_REORG_NO_PARAM_ERROR; SQLSTATE: HY000 Message: REORGANIZE PARTITION without parameters can only be used on auto-partitioned tables using HASH PARTITIONs

Error number: 1512; Symbol: ER_ONLY_ON_RANGE_LIST_PARTITION; SQLSTATE: HY000 Message: %s PARTITION can only be used on RANGE/LIST partitions

Error number: 1513; Symbol: ER_ADD_PARTITION_SUBPART_ERROR; SQLSTATE: HY000 Message: Trying to Add partition(s) with wrong number of subpartitions

Error number: 1514; Symbol: ER_ADD_PARTITION_NO_NEW_PARTITION; SQLSTATE: HY000

Message: At least one partition must be added

Error number: 1515; Symbol: ER_COALESCE_PARTITION_NO_PARTITION; SQLSTATE: HY000

Message: At least one partition must be coalesced

Error number: 1516; Symbol: ER_REORG_PARTITION_NOT_EXIST; SQLSTATE: HY000 Message: More partitions to reorganize than there are partitions

Error number: 1517; Symbol: ER_SAME_NAME_PARTITION; SQLSTATE: HY000 Message: Duplicate partition name %s

Error number: 1518; Symbol: ER_NO_BINLOG_ERROR; SQLSTATE: HY000 Message: It is not allowed to shut off binlog on this command

Error number: 1519; Symbol: ER_CONSECUTIVE_REORG_PARTITIONS; SQLSTATE: HY000 Message: When reorganizing a set of partitions they must be in consecutive order

Error number: 1520; Symbol: ER_REORG_OUTSIDE_RANGE; SQLSTATE: HY000 Message: Reorganize of range partitions cannot change total ranges except for last partition where it can extend the range

Error number: 1521; Symbol: ER_PARTITION_FUNCTION_FAILURE; SQLSTATE: HY000 Message: Partition function not supported in this version for this handler

Error number: 1523; Symbol: ER_LIMITED_PART_RANGE; SQLSTATE: HY000 Message: The %s handler only supports 32 bit integers in VALUES

Error number: 1524; Symbol: ER_PLUGIN_IS_NOT_LOADED; SQLSTATE: HY000

Message: Plugin '%s' is not loaded

Error number: 1525; Symbol: ER WRONG VALUE; SQLSTATE: HY000

Message: Incorrect %s value: '%s'

Error number: 1526; Symbol: ER NO PARTITION FOR GIVEN VALUE; SQLSTATE: HY000

Message: Table has no partition for value %s

Error number: 1527; Symbol: ER FILEGROUP OPTION ONLY ONCE; SQLSTATE: HY000

Message: It is not allowed to specify %s more than once

Error number: 1528; Symbol: ER CREATE FILEGROUP FAILED; SQLSTATE: HY000

Message: Failed to create %s

Error number: 1529; Symbol: ER DROP FILEGROUP FAILED; SQLSTATE: HY000

Message: Failed to drop %s

Error number: 1530; Symbol: ER_TABLESPACE_AUTO_EXTEND_ERROR; SQLSTATE:

HY000

Message: The handler doesn't support autoextend of tablespaces

Error number: 1531; Symbol: ER WRONG SIZE NUMBER; SQLSTATE: HY000

Message: A size parameter was incorrectly specified, either number or on the form 10M

Error number: 1532; Symbol: ER SIZE OVERFLOW ERROR; SQLSTATE: HY000

Message: The size number was correct but we don't allow the digit part to be more than 2 billion

Error number: 1533; Symbol: ER ALTER FILEGROUP FAILED; SQLSTATE: HY000

Message: Failed to alter: %s

Error number: 1534; Symbol: ER_BINLOG_ROW_LOGGING_FAILED; SQLSTATE: HY000

Message: Writing one row to the row-based binary log failed

Error number: 1537; Symbol: ER EVENT ALREADY EXISTS; SQLSTATE: HY000

Message: Event '%s' already exists

Error number: 1539; Symbol: ER EVENT DOES NOT EXIST; SQLSTATE: HY000

Message: Unknown event '%s'

Error number: 1542; Symbol: ER EVENT INTERVAL NOT POSITIVE OR TOO BIG;

SOLSTATE: HY000

Message: INTERVAL is either not positive or too big

Error number: 1543; Symbol: ER EVENT ENDS BEFORE STARTS; SQLSTATE: HY000

Message: ENDS is either invalid or before STARTS

Error number: 1544; Symbol: ER EVENT EXEC TIME IN THE PAST; SQLSTATE: HY000

Message: Event execution time is in the past. Event has been disabled

Error number: 1551; Symbol: ER EVENT SAME NAME; SQLSTATE: HY000

Message: Same old and new event name

Error number: 1553; Symbol: ER_DROP_INDEX_FK; SQLSTATE: HY000

Message: Cannot drop index '%s': needed in a foreign key constraint

可能原因及解决方法: 当您尝试删除可以强制执行特定引用约束的最后一个索引时,InnoDB 会报告此错误。

为了获得 DML 语句的最佳性能,InnoDB 要求在外键列上存在索引,以便父表上的 UPDATE 和 DELETE 操作可以轻松检查子表中是否存在相应的行。 TDSQL 在需要时自动创建或删除此类索引,这是 CREATE TABLE、CREATE INDEX 和 ALTER TABLE 语句的副作用。删除索引时,InnoDB 会检查该索引是否用于检查外键约束。 如果有另一个索引可用于强制执行相同的约束,则删除该索引仍然可以。 InnoDB 阻止您删除可以强制执行特定引用约束的最后一个索引。

Error number: 1554; Symbol: ER_WARN_DEPRECATED_SYNTAX_WITH_VER; SQLSTATE: HY000

Message: The syntax '%s' is deprecated and will be removed in MySQL %s. Please use %s instead

Error number: 1556; Symbol: ER_CANT_LOCK_LOG_TABLE; SQLSTATE: HY000 Message: You can't use locks with log tables.

Message. You can't use locks with log tables.

Error number: 1557; Symbol: ER_FOREIGN_DUPLICATE_KEY_OLD_UNUSED; SQLSTATE: 23000

Message: Upholding foreign key constraints for table '%s', entry '%s', key %d would lead to a duplicate entry

Error number: 1558; Symbol: ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE;

SQLSTATE: HY000

Message: The column count of mysql.%s is wrong. Expected %d, found %d. Created with

MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

Error number: 1559; Symbol: ER TEMP TABLE PREVENTS SWITCH OUT OF RBR;

SOLSTATE: HY000

Message: Cannot switch out of the row-based binary log format when the session has open

temporary tables

ER TEMP TABLE PREVENTS SWITCH OUT OF RBR was removed after 8.0.12.

Error number: 1560; Symbol:

ER STORED FUNCTION PREVENTS SWITCH BINLOG FORMAT; SQLSTATE: HY000

Message: Cannot change the binary logging format inside a stored function or trigger

Error number: 1562; Symbol: ER PARTITION NO TEMPORARY; SQLSTATE: HY000

Message: Cannot create temporary table with partitions

Error number: 1563; Symbol: ER_PARTITION_CONST_DOMAIN_ERROR; SQLSTATE: HY000

Message: Partition constant is out of partition function domain

Error number: 1564; Symbol: ER PARTITION FUNCTION IS NOT ALLOWED; SQLSTATE:

HY000

Message: This partition function is not allowed

Error number: 1565; Symbol: ER DDL LOG ERROR; SQLSTATE: HY000

Message: Error in DDL log

(说明:

ER DDL LOG ERROR was removed after 8.0.1.

Error number: 1566; Symbol: ER NULL IN VALUES LESS THAN; SQLSTATE: HY000

Message: Not allowed to use NULL value in VALUES LESS THAN

Error number: 1567; Symbol: ER WRONG PARTITION NAME; SQLSTATE: HY000

Message: Incorrect partition name

Error number: 1568; Symbol: ER CANT CHANGE TX CHARACTERISTICS; SQLSTATE:

25001

Message: Transaction characteristics can't be changed while a transaction is in progress

Error number: 1569; Symbol: ER DUP ENTRY AUTOINCREMENT CASE; SQLSTATE:

HY000

Message: ALTER TABLE causes auto_increment resequencing, resulting in duplicate entry '%s' for

key '%s'

Error number: 1571; Symbol: ER EVENT SET VAR ERROR; SQLSTATE: HY000

Message: Error during starting/stopping of the scheduler. Error code %u

Error number: 1572; Symbol: ER PARTITION MERGE ERROR; SQLSTATE: HY000

Message: Engine cannot be used in partitioned tables

Error number: 1575; Symbol: ER BASE64 DECODE ERROR; SQLSTATE: HY000

Message: Decoding of base64 string failed

Error number: 1576; Symbol: ER EVENT RECURSION FORBIDDEN; SQLSTATE: HY000

Message: Recursion of EVENT DDL statements is forbidden when body is present

Error number: 1578; Symbol: ER_ONLY_INTEGERS_ALLOWED; SQLSTATE: HY000

Message: Only integers allowed as number here

Error number: 1579; Symbol: ER UNSUPORTED LOG ENGINE; SQLSTATE: HY000

Message: This storage engine cannot be used for log tables

Error number: 1580; Symbol: ER_BAD_LOG_STATEMENT; SQLSTATE: HY000

Message: You cannot '%s' a log table if logging is enabled

Error number: 1581; Symbol: ER CANT RENAME LOG TABLE; SQLSTATE: HY000

Message: Cannot rename '%s'. When logging enabled, rename to/from log table must rename two

tables: the log table to an archive table and another table back to '%s'

Error number: 1582; Symbol: ER WRONG PARAMCOUNT TO NATIVE FCT; SQLSTATE:

42000

Message: Incorrect parameter count in the call to native function '%s'

Error number: 1583; Symbol: ER WRONG PARAMETERS TO NATIVE FCT; SQLSTATE:

42000

Message: Incorrect parameters in the call to native function '%s'

Error number: 1584; Symbol: ER_WRONG_PARAMETERS_TO_STORED_FCT; SQLSTATE:

42000

Message: Incorrect parameters in the call to stored function %s

Error number: 1585; Symbol: ER NATIVE FCT NAME COLLISION; SQLSTATE: HY000

Message: This function '%s' has the same name as a native function

Error number: 1586; Symbol: ER DUP ENTRY WITH KEY NAME; SQLSTATE: 23000

Message: Duplicate entry '%s' for key '%s'

The format string for this error is also used with ER DUP ENTRY.

Error number: 1587; Symbol: ER BINLOG PURGE EMFILE; SQLSTATE: HY000

Message: Too many files opened, please execute the command again

Error number: 1588; Symbol: ER_EVENT_CANNOT_CREATE_IN_THE_PAST; SQLSTATE:

HY000

Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The

event was dropped immediately after creation.

Error number: 1589; Symbol: ER_EVENT_CANNOT_ALTER_IN_THE_PAST; SQLSTATE:

HY000

Message: Event execution time is in the past and ON COMPLETION NOT PRESERVE is set. The

event was not changed. Specify a time in the future.

Error number: 1591; Symbol: ER_NO_PARTITION_FOR_GIVEN_VALUE_SILENT;

SQLSTATE: HY000

Message: Table has no partition for some existing values

Error number: 1592; Symbol: ER BINLOG UNSAFE STATEMENT; SQLSTATE: HY000

Message: Unsafe statement written to the binary log using statement format since

BINLOG FORMAT = STATEMENT. %s

Error number: 1593; Symbol: ER BINLOG FATAL ERROR; SQLSTATE: HY000

Message: Fatal error: %s

ER BINLOG FATAL ERROR was added in 8.0.11.

Error number: 1598; Symbol: ER_BINLOG_LOGGING_IMPOSSIBLE; SQLSTATE: HY000

Message: Binary logging not possible. Message: %s

Error number: 1599; Symbol: ER VIEW NO CREATION CTX; SQLSTATE: HY000

Message: View '%s'.'%s' has no creation context

Error number: 1600; Symbol: ER_VIEW_INVALID_CREATION_CTX; SQLSTATE: HY000

Message: Creation context of view '%s'.'%s' is invalid

Error number: 1602; Symbol: ER TRG CORRUPTED FILE; SQLSTATE: HY000

Message: Corrupted TRG file for table '%s'.'%s'

Error number: 1603; Symbol: ER TRG NO CREATION CTX; SQLSTATE: HY000

Message: Triggers for table '%s'.'%s' have no creation context

Error number: 1604; Symbol: ER TRG INVALID CREATION CTX; SQLSTATE: HY000

Message: Trigger creation context of table '%s'.'%s' is invalid

Error number: 1605; Symbol: ER EVENT INVALID CREATION CTX; SQLSTATE: HY000

Message: Creation context of event '%s'.'%s' is invalid

Error number: 1606; Symbol: ER TRG CANT OPEN TABLE; SQLSTATE: HY000

Message: Cannot open table for trigger '%s'.'%s'

Error number: 1609; Symbol:

ER_NO_FORMAT_DESCRIPTION_EVENT_BEFORE_BINLOG_STATEMENT; SQLSTATE:

HY000

Message: The BINLOG statement of type '%s' was not preceded by a format description BINLOG

statement.

Error number: 1610; Symbol: ER_SLAVE_CORRUPT_EVENT; SQLSTATE: HY000

Message: Corrupted replication event was detected

Error number: 1612; Symbol: ER_LOG_PURGE_NO_FILE; SQLSTATE: HY000

Message: Being purged log %s was not found

Error number: 1613; Symbol: ER XA RBTIMEOUT; SQLSTATE: XA106

Message: XA RBTIMEOUT: Transaction branch was rolled back: took too long

Error number: 1614; Symbol: ER XA RBDEADLOCK; SQLSTATE: XA102

Message: XA RBDEADLOCK: Transaction branch was rolled back: deadlock was detected

Error number: 1615; Symbol: ER NEED REPREPARE; SQLSTATE: HY000

Message: Prepared statement needs to be re-prepared

Error number: 1617; Symbol: WARN NO MASTER INFO; SQLSTATE: HY000

Message: The master info structure does not exist

Error number: 1618; Symbol: WARN_OPTION_IGNORED; SQLSTATE: HY000

Message: <%s> option ignored

Error number: 1619; Symbol: ER PLUGIN DELETE BUILTIN; SQLSTATE: HY000

Message: Built-in plugins cannot be deleted

Error number: 1620; Symbol: WARN PLUGIN BUSY; SQLSTATE: HY000

Message: Plugin is busy and will be uninstalled on shutdown

Error number: 1621; Symbol: ER_VARIABLE_IS_READONLY; SQLSTATE: HY000

Message: %s variable '%s' is read-only. Use SET %s to assign the value

 $Error\ number:\ 1622;\ Symbol:\ ER_WARN_ENGINE_TRANSACTION_ROLLBACK;\ SQLSTATE:$

HY000

Message: Storage engine %s does not support rollback for this statement. Transaction rolled back

and must be restarted

Error number: 1624; Symbol: ER SLAVE HEARTBEAT VALUE OUT OF RANGE;

SQLSTATE: HY000

Message: The requested value for the heartbeat period is either negative or exceeds the maximum

allowed (%s seconds).

Error number: 1625; Symbol: ER NDB REPLICATION_SCHEMA_ERROR; SQLSTATE: HY000

Message: Bad schema for mysql.ndb replication table. Message: %s

Error number: 1626; Symbol: ER CONFLICT FN PARSE ERROR; SQLSTATE: HY000

Message: Error in parsing conflict function. Message: %s

Error number: 1627; Symbol: ER EXCEPTIONS WRITE ERROR; SQLSTATE: HY000

Message: Write to exceptions table failed. Message: %s

Error number: 1628; Symbol: ER_TOO_LONG_TABLE_COMMENT; SQLSTATE: HY000

Message: Comment for table '%s' is too long (max = %lu)

Error number: 1629; Symbol: ER TOO LONG FIELD COMMENT; SQLSTATE: HY000

Message: Comment for field '%s' is too long (max = %lu)

Error number: 1630; Symbol: ER_FUNC_INEXISTENT_NAME_COLLISION; SQLSTATE:

42000

Message: FUNCTION %s does not exist. Check the 'Function Name Parsing and Resolution' section

in the Reference Manual

Error number: 1631; Symbol: ER_DATABASE_NAME; SQLSTATE: HY000

Message: Database

Error number: 1632; Symbol: ER TABLE NAME; SQLSTATE: HY000

Message: Table

Error number: 1633; Symbol: ER PARTITION NAME; SQLSTATE: HY000

Message: Partition

Error number: 1634; Symbol: ER SUBPARTITION NAME; SQLSTATE: HY000

Message: Subpartition

Error number: 1635; Symbol: ER TEMPORARY NAME; SQLSTATE: HY000

Message: Temporary

Error number: 1636; Symbol: ER RENAMED NAME; SQLSTATE: HY000

Message: Renamed

Error number: 1637; Symbol: ER TOO MANY CONCURRENT TRXS; SQLSTATE: HY000

Message: Too many active concurrent transactions

Error number: 1638; Symbol: WARN NON ASCII SEPARATOR NOT IMPLEMENTED;

SQLSTATE: HY000

Message: Non-ASCII separator arguments are not fully supported

Error number: 1639; Symbol: ER_DEBUG_SYNC_TIMEOUT; SQLSTATE: HY000

Message: debug sync point wait timed out

Error number: 1640; Symbol: ER DEBUG SYNC HIT LIMIT; SQLSTATE: HY000

Message: debug sync point hit limit reached

Error number: 1641; Symbol: ER DUP SIGNAL SET; SQLSTATE: 42000

Message: Duplicate condition information item '%s'

Error number: 1642; Symbol: ER SIGNAL WARN; SQLSTATE: 01000

Message: Unhandled user-defined warning condition

Error number: 1643; Symbol: ER_SIGNAL_NOT_FOUND; SQLSTATE: 02000

Message: Unhandled user-defined not found condition

Error number: 1644; Symbol: ER SIGNAL EXCEPTION; SQLSTATE: HY000

Message: Unhandled user-defined exception condition

Error number: 1645; Symbol: ER RESIGNAL WITHOUT ACTIVE HANDLER; SQLSTATE:

0K000

Message: RESIGNAL when handler not active

Error number: 1646; Symbol: ER SIGNAL BAD CONDITION TYPE; SQLSTATE: HY000

Message: SIGNAL/RESIGNAL can only use a CONDITION defined with SQLSTATE

Error number: 1647; Symbol: WARN COND ITEM TRUNCATED; SQLSTATE: HY000

Message: Data truncated for condition item '%s'

Error number: 1648; Symbol: ER COND ITEM TOO LONG; SQLSTATE: HY000

Message: Data too long for condition item '%s'

Error number: 1649; Symbol: ER UNKNOWN LOCALE; SQLSTATE: HY000

Message: Unknown locale: '%s'

Error number: 1650; Symbol: ER SLAVE IGNORE SERVER IDS; SQLSTATE: HY000

Message: The requested server id %d clashes with the slave startup option --replicate-same-server-id

Error number: 1651; Symbol: ER_QUERY_CACHE_DISABLED; SQLSTATE: HY000 Message: Query cache is disabled; restart the server with query cache type=1 to enable it

(i) 说明:

ER_QUERY_CACHE_DISABLED was removed after 8.0.2.

Error number: 1652; Symbol: ER_SAME_NAME_PARTITION_FIELD; SQLSTATE: HY000

Message: Duplicate partition field name '%s'

Error number: 1653; Symbol: ER PARTITION COLUMN LIST ERROR; SQLSTATE: HY000

Message: Inconsistency in usage of column lists for partitioning

Error number: 1654; Symbol: ER WRONG TYPE COLUMN VALUE ERROR; SQLSTATE:

HY000

Message: Partition column values of incorrect type

Error number: 1655; Symbol: ER TOO MANY PARTITION FUNC FIELDS ERROR;

SQLSTATE: HY000

Message: Too many fields in '%s'

Error number: 1656; Symbol: ER MAXVALUE IN VALUES IN; SQLSTATE: HY000

Message: Cannot use MAXVALUE as value in VALUES IN

Error number: 1657; Symbol: ER TOO MANY VALUES ERROR; SQLSTATE: HY000

Message: Cannot have more than one value for this type of %s partitioning

Error number: 1658; Symbol: ER_ROW_SINGLE_PARTITION_FIELD_ERROR; SQLSTATE:

HY000

Message: Row expressions in VALUES IN only allowed for multi-field column partitioning

Error number: 1659; Symbol: ER_FIELD_TYPE_NOT_ALLOWED_AS_PARTITION_FIELD;

SQLSTATE: HY000

Message: Field '%s' is of a not allowed type for this type of partitioning

Error number: 1660; Symbol: ER_PARTITION_FIELDS_TOO_LONG; SQLSTATE: HY000

Message: The total length of the partitioning fields is too large

Error number: 1661; Symbol: ER_BINLOG_ROW_ENGINE_AND_STMT_ENGINE; SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since both row-incapable engines and statement-incapable engines are involved.

Error number: 1662; Symbol: ER_BINLOG_ROW_MODE_AND_STMT_ENGINE; SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = ROW and at least one table uses a storage engine limited to statement-based logging.

Error number: 1663; Symbol: ER_BINLOG_UNSAFE_AND_STMT_ENGINE; SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since statement is unsafe, storage engine is limited to statement-based logging, and BINLOG FORMAT = MIXED. %s

Error number: 1664; Symbol: ER_BINLOG_ROW_INJECTION_AND_STMT_ENGINE; SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since statement is in row format and at least one table uses a storage engine limited to statement-based logging.

Error number: 1665; Symbol: ER_BINLOG_STMT_MODE_AND_ROW_ENGINE; SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT = STATEMENT and at least one table uses a storage engine limited to row-based logging.%s

Error number: 1666; Symbol: ER_BINLOG_ROW_INJECTION_AND_STMT_MODE; SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since statement is in row format and BINLOG_FORMAT = STATEMENT.

Error number: 1667; Symbol:

ER_BINLOG_MULTIPLE_ENGINES_AND_SELF_LOGGING_ENGINE; SQLSTATE: HY000 Message: Cannot execute statement: impossible to write to binary log since more than one engine is involved and at least one engine is self-logging.

Error number: 1668; Symbol: ER BINLOG UNSAFE LIMIT; SQLSTATE: HY000

Message: The statement is unsafe because it uses a LIMIT clause. This is unsafe because the set of rows included cannot be predicted.

Error number: 1670; Symbol: ER_BINLOG_UNSAFE_SYSTEM_TABLE; SQLSTATE: HY000 Message: The statement is unsafe because it uses the general log, slow query log, or performance schema table(s). This is unsafe because system tables may differ on slaves.

Error number: 1671; Symbol: ER_BINLOG_UNSAFE_AUTOINC_COLUMNS; SQLSTATE: HY000

Message: Statement is unsafe because it invokes a trigger or a stored function that inserts into an AUTO INCREMENT column. Inserted values cannot be logged correctly.

Error number: 1672; Symbol: ER_BINLOG_UNSAFE_UDF; SQLSTATE: HY000 Message: Statement is unsafe because it uses a UDF which may not return the same value on the slave.

Error number: 1673; Symbol: ER_BINLOG_UNSAFE_SYSTEM_VARIABLE; SQLSTATE: HY000

Message: Statement is unsafe because it uses a system variable that may have a different value on the slave.

Error number: 1674; Symbol: ER_BINLOG_UNSAFE_SYSTEM_FUNCTION; SQLSTATE: HY000

Message: Statement is unsafe because it uses a system function that may return a different value on the slave.

Error number: 1675; Symbol: ER_BINLOG_UNSAFE_NONTRANS_AFTER_TRANS; SQLSTATE: HY000

Message: Statement is unsafe because it accesses a non-transactional table after accessing a transactional table within the same transaction

Error number: 1676; Symbol: ER_MESSAGE_AND_STATEMENT; SQLSTATE: HY000 Message: %s Statement: %s

2.3 错误码及错误信息汇总 03

Error number: 1677; Symbol: ER_SLAVE_CONVERSION_FAILED; SQLSTATE: HY000 Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'

(说明:

ER_SLAVE_CONVERSION_FAILED was removed after 8.0.4.

Error number: 1678; Symbol: ER SLAVE CANT CREATE CONVERSION; SQLSTATE:

HY000

Message: Can't create conversion table for table '%s.%s'

Error number: 1679; Symbol:

ER INSIDE TRANSACTION PREVENTS SWITCH BINLOG FORMAT; SQLSTATE: HY000

Message: Cannot modify @@session.binlog format inside a transaction

Error number: 1680; Symbol: ER PATH LENGTH; SQLSTATE: HY000

Message: The path specified for %s is too long.

Error number: 1681; Symbol: ER WARN DEPRECATED SYNTAX NO REPLACEMENT;

SQLSTATE: HY000

Message: '%s' is deprecated and will be removed in a future release.

Error number: 1682; Symbol: ER WRONG NATIVE TABLE STRUCTURE; SQLSTATE:

HY000

Message: Native table '%s'.'%s' has the wrong structure

Error number: 1683; Symbol: ER WRONG PERFSCHEMA USAGE; SQLSTATE: HY000

Message: Invalid performance_schema usage.

Error number: 1684; Symbol: ER WARN I S SKIPPED TABLE; SQLSTATE: HY000

Message: Table '%s'.'%s' was skipped since its definition is being modified by concurrent DDL

statement

Error number: 1685; Symbol:

ER INSIDE TRANSACTION PREVENTS SWITCH BINLOG DIRECT; SQLSTATE: HY000

Message: Cannot modify @@session.binlog direct non transactional updates inside a transaction

Error number: 1686; Symbol:

ER STORED FUNCTION PREVENTS SWITCH BINLOG DIRECT; SQLSTATE: HY000

Message: Cannot change the binlog direct flag inside a stored function or trigger

Error number: 1687; Symbol: ER SPATIAL MUST HAVE GEOM COL; SQLSTATE: 42000

Message: A SPATIAL index may only contain a geometrical type column

Error number: 1688; Symbol: ER TOO LONG INDEX COMMENT; SQLSTATE: HY000

Message: Comment for index '%s' is too long (max = %lu)

Error number: 1689; Symbol: ER LOCK ABORTED; SQLSTATE: HY000

Message: Wait on a lock was aborted due to a pending exclusive lock

Error number: 1690; Symbol: ER DATA OUT OF RANGE; SQLSTATE: 22003

Message: %s value is out of range in '%s'

Error number: 1691; Symbol: ER WRONG SPVAR TYPE IN LIMIT; SQLSTATE: HY000

Message: A variable of a non-integer based type in LIMIT clause

🛈 说明:

ER_WRONG_SPVAR_TYPE_IN_LIMIT was removed after 8.0.21.

Error number: 1692; Symbol:

ER BINLOG UNSAFE MULTIPLE ENGINES AND SELF LOGGING ENGINE;

SQLSTATE: HY000

Message: Mixing self-logging and non-self-logging engines in a statement is unsafe.

Error number: 1693; Symbol: ER_BINLOG_UNSAFE_MIXED_STATEMENT; SQLSTATE:

HY000

Message: Statement accesses nontransactional table as well as transactional or temporary table, and

writes to any of them.

Error number: 1694; Symbol:

ER INSIDE TRANSACTION PREVENTS SWITCH SQL_LOG_BIN; SQLSTATE: HY000

Message: Cannot modify @@session.sql log bin inside a transaction

Error number: 1695; Symbol:

ER STORED FUNCTION PREVENTS SWITCH SQL LOG BIN; SQLSTATE: HY000

Message: Cannot change the sql log bin inside a stored function or trigger

Error number: 1696; Symbol: ER FAILED READ FROM PAR FILE; SQLSTATE: HY000

Message: Failed to read from the .par file

Error number: 1697; Symbol: ER VALUES IS NOT INT TYPE ERROR; SQLSTATE: HY000

Message: VALUES value for partition '%s' must have type INT

Error number: 1698; Symbol: ER ACCESS DENIED NO PASSWORD ERROR; SQLSTATE:

28000

Message: Access denied for user '%s'@'%s'

Error number: 1699; Symbol: ER SET PASSWORD AUTH PLUGIN; SQLSTATE: HY000

Message: SET PASSWORD has no significance for users authenticating via plugins

6 说明:

ER SET PASSWORD AUTH PLUGIN was removed after 8.0.28.

Error number: 1701; Symbol: ER TRUNCATE ILLEGAL FK; SQLSTATE: 42000

Message: Cannot truncate a table referenced in a foreign key constraint (%s)

Error number: 1702; Symbol: ER PLUGIN IS PERMANENT; SQLSTATE: HY000

Message: Plugin '%s' is force plus permanent and can not be unloaded

Error number: 1703; Symbol: ER SLAVE HEARTBEAT VALUE OUT OF RANGE MIN;

SQLSTATE: HY000

Message: The requested value for the heartbeat period is less than 1 millisecond. The value is reset to

0, meaning that heartbeating will effectively be disabled.

Error number: 1704; Symbol: ER SLAVE HEARTBEAT VALUE OUT OF RANGE MAX;

SQLSTATE: HY000

Message: The requested value for the heartbeat period exceeds the value of 'replica net timeout'

seconds. A sensible value for the period should be less than the timeout.

Error number: 1705; Symbol: ER_STMT_CACHE_FULL; SQLSTATE: HY000

Message: Multi-row statements required more than 'max binlog stmt cache size' bytes of storage;

increase this mysqld variable and try again

Error number: 1706; Symbol: ER MULTI UPDATE KEY CONFLICT; SQLSTATE: HY000

Message: Primary key/partition key update is not allowed since the table is updated both as '%s' and

'%s'.

Error number: 1707; Symbol: ER TABLE NEEDS REBUILD; SQLSTATE: HY000

Message: Table rebuild required. Please do "ALTER TABLE `%s` FORCE" or dump/reload to fix it!

Error number: 1708; Symbol: WARN OPTION BELOW LIMIT; SQLSTATE: HY000

Message: The value of '%s' should be no less than the value of '%s'

Error number: 1709; Symbol: ER INDEX COLUMN TOO LONG; SQLSTATE: HY000

Message: Index column size too large. The maximum column size is %lu bytes.

Error number: 1710; Symbol: ER ERROR IN TRIGGER BODY; SQLSTATE: HY000

Message: Trigger '%s' has an error in its body: '%s'

Error number: 1711; Symbol: ER ERROR IN UNKNOWN TRIGGER BODY; SQLSTATE:

HY000

Message: Unknown trigger has an error in its body: '%s'

Error number: 1712; Symbol: ER INDEX CORRUPT; SQLSTATE: HY000

Message: Index %s is corrupted

Error number: 1713; Symbol: ER UNDO RECORD TOO BIG; SQLSTATE: HY000

Message: Undo log record is too big.

Error number: 1714; Symbol: ER_BINLOG_UNSAFE_INSERT_IGNORE_SELECT; SQLSTATE: HY000

Message: INSERT IGNORE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on master and the slave

Error number: 1715; Symbol: ER_BINLOG_UNSAFE_INSERT_SELECT_UPDATE; SQLSTATE: HY000

Message: INSERT... SELECT... ON DUPLICATE KEY UPDATE is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are updated. This order cannot be predicted and may differ on master and the slave.

Error number: 1716; Symbol: ER_BINLOG_UNSAFE_REPLACE_SELECT; SQLSTATE: HY000 Message: REPLACE... SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on master and the slave.

Error number: 1717; Symbol: ER BINLOG_UNSAFE_CREATE_IGNORE_SELECT;

SQLSTATE: HY000

Message: CREATE... IGNORE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are ignored. This order cannot be predicted and may differ on master and the slave.

Error number: 1718; Symbol: ER BINLOG UNSAFE CREATE REPLACE SELECT;

SQLSTATE: HY000

Message: CREATE... REPLACE SELECT is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are replaced. This order cannot be predicted and may differ on master and the slave.

Error number: 1719; Symbol: ER_BINLOG_UNSAFE_UPDATE_IGNORE; SQLSTATE: HY000 Message: UPDATE IGNORE is unsafe because the order in which rows are updated determines which (if any) rows are ignored. This order cannot be predicted and may differ on master and the slave.

Error number: 1720; Symbol: ER PLUGIN NO UNINSTALL; SQLSTATE: HY000

Message: Plugin '%s' is marked as not dynamically uninstallable. You have to stop the server to uninstall it.

Error number: 1721; Symbol: ER PLUGIN NO INSTALL; SQLSTATE: HY000

Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install

it.

Error number: 1722; Symbol: ER_BINLOG_UNSAFE_WRITE_AUTOINC_SELECT;

SQLSTATE: HY000

Message: Statements writing to a table with an auto-increment column after selecting from another table are unsafe because the order in which rows are retrieved determines what (if any) rows will be written. This order cannot be predicted and may differ on master and the slave.

Error number: 1723; Symbol: ER_BINLOG_UNSAFE_CREATE_SELECT_AUTOINC;

SQLSTATE: HY000

Message: CREATE TABLE... SELECT... on a table with an auto-increment column is unsafe because the order in which rows are retrieved by the SELECT determines which (if any) rows are inserted. This order cannot be predicted and may differ on master and the slave.

Error number: 1724; Symbol: ER_BINLOG_UNSAFE_INSERT_TWO_KEYS; SQLSTATE: HY000

Message: INSERT... ON DUPLICATE KEY UPDATE on a table with more than one UNIQUE KEY is unsafe

Error number: 1725; Symbol: ER_TABLE_IN_FK_CHECK; SQLSTATE: HY000

Message: Table is being used in foreign key check.

Error number: 1726; Symbol: ER_UNSUPPORTED_ENGINE; SQLSTATE: HY000

Message: Storage engine '%s' does not support system tables. [%s.%s]

Error number: 1727; Symbol: ER_BINLOG_UNSAFE_AUTOINC_NOT_FIRST; SQLSTATE:

HY000

Message: INSERT into autoincrement field which is not the first part in the composed primary key is unsafe.

Error number: 1728; Symbol: ER_CANNOT_LOAD_FROM_TABLE_V2; SQLSTATE: HY000 Message: Cannot load from %s.%s. The table is probably corrupted

Error number: 1729; Symbol: ER_MASTER_DELAY_VALUE_OUT_OF_RANGE; SQLSTATE: HY000

Message: The requested value %s for the master delay exceeds the maximum %u

Error number: 1730; Symbol:

 $ER_ONLY_FD_AND_RBR_EVENTS_ALLOWED_IN_BINLOG_STATEMENT; SQLSTATE:$

HY000

Message: Only Format description log event and row events are allowed in BINLOG statements

(but %s was provided)

Error number: 1731; Symbol: ER PARTITION EXCHANGE DIFFERENT OPTION;

SQLSTATE: HY000

Message: Non matching attribute '%s' between partition and table

Error number: 1732; Symbol: ER PARTITION EXCHANGE PART TABLE; SQLSTATE:

HY000

Message: Table to exchange with partition is partitioned: '%s'

Error number: 1733; Symbol: ER PARTITION EXCHANGE TEMP TABLE; SQLSTATE:

HY000

Message: Table to exchange with partition is temporary: '%s'

Error number: 1734; Symbol: ER PARTITION INSTEAD OF SUBPARTITION; SQLSTATE:

HY000

Message: Subpartitioned table, use subpartition instead of partition

Error number: 1735; Symbol: ER UNKNOWN PARTITION; SQLSTATE: HY000

Message: Unknown partition '%s' in table '%s'

Error number: 1736; Symbol: ER TABLES DIFFERENT METADATA; SQLSTATE: HY000

Message: Tables have different definitions

Error number: 1737; Symbol: ER ROW DOES NOT MATCH PARTITION; SQLSTATE:

HY000

Message: Found a row that does not match the partition

Error number: 1738; Symbol: ER BINLOG CACHE SIZE GREATER THAN MAX;

SOLSTATE: HY000

Message: Option binlog cache size (%lu) is greater than max binlog cache size (%lu); setting

binlog cache size equal to max binlog cache size.

Error number: 1739; Symbol: ER_WARN_INDEX_NOT_APPLICABLE; SQLSTATE: HY000

Message: Cannot use %s access on index '%s' due to type or collation conversion on field '%s'

Error number: 1740; Symbol: ER PARTITION EXCHANGE FOREIGN KEY; SQLSTATE:

HY000

Message: Table to exchange with partition has foreign key references: '%s'

Error number: 1742; Symbol: ER RPL INFO DATA TOO LONG; SQLSTATE: HY000

Message: Data for column '%s' too long

Error number: 1745; Symbol: ER BINLOG STMT CACHE SIZE GREATER THAN MAX;

SQLSTATE: HY000

Message: Option binlog_stmt_cache_size (%lu) is greater than max_binlog_stmt_cache_size (%lu);

setting binlog stmt cache size equal to max binlog stmt cache size.

Error number: 1746; Symbol: ER CANT UPDATE TABLE IN CREATE TABLE SELECT;

SQLSTATE: HY000

Message: Can't update table '%s' while '%s' is being created.

Error number: 1747; Symbol: ER_PARTITION_CLAUSE_ON_NONPARTITIONED; SQLSTATE:

HY000

Message: PARTITION () clause on non partitioned table

Error number: 1748; Symbol: ER ROW DOES NOT MATCH GIVEN PARTITION SET;

SQLSTATE: HY000

Message: Found a row not matching the given partition set

Error number: 1750; Symbol: ER CHANGE RPL INFO REPOSITORY FAILURE; SQLSTATE:

HY000

Message: Failure while changing the type of replication repository: %s.

Error number: 1751; Symbol:

ER WARNING NOT COMPLETE ROLLBACK WITH CREATED TEMP TABLE;

SQLSTATE: HY000

Message: The creation of some temporary tables could not be rolled back.

Error number: 1752; Symbol:

ER WARNING NOT COMPLETE ROLLBACK WITH DROPPED TEMP TABLE;

SOLSTATE: HY000

Message: Some temporary tables were dropped, but these operations could not be rolled back.

Error number: 1753; Symbol: ER MTS FEATURE IS NOT SUPPORTED; SQLSTATE: HY000

Message: %s is not supported in multi-threaded slave mode. %s

Error number: 1754; Symbol: ER_MTS_UPDATED_DBS_GREATER_MAX; SQLSTATE: HY000 Message: The number of modified databases exceeds the maximum %d; the database names will not be included in the replication event metadata.

Error number: 1755; Symbol: ER MTS CANT PARALLEL; SQLSTATE: HY000

Message: Cannot execute the current event group in the parallel mode. Encountered event %s, relay-

log name %s, position %s which prevents execution of this event group in parallel mode.

Reason: %s.

Error number: 1756; Symbol: ER MTS INCONSISTENT DATA; SQLSTATE: HY000

Message: %s

Error number: 1757; Symbol: ER FULLTEXT NOT SUPPORTED WITH PARTITIONING;

SQLSTATE: HY000

Message: FULLTEXT index is not supported for partitioned tables.

Error number: 1758; Symbol: ER DA INVALID CONDITION NUMBER; SQLSTATE: 35000

Message: Invalid condition number

Error number: 1759; Symbol: ER INSECURE PLAIN TEXT; SQLSTATE: HY000

Message: Sending passwords in plain text without SSL/TLS is extremely insecure.

Error number: 1760; Symbol: ER_INSECURE_CHANGE_MASTER; SQLSTATE: HY000 Message: Storing MySQL user name or password information in the master info repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START SLAVE; see the 'START SLAVE Syntax' in the MySQL Manual for more information.

Error number: 1761; Symbol: ER FOREIGN DUPLICATE KEY WITH CHILD INFO;

SQLSTATE: 23000

Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in table

'%s', key '%s'

Error number: 1762; Symbol: ER FOREIGN DUPLICATE KEY WITHOUT CHILD INFO;

SQLSTATE: 23000

Message: Foreign key constraint for table '%s', record '%s' would lead to a duplicate entry in a child

table

Error number: 1763; Symbol: ER_SQLTHREAD_WITH_SECURE_SLAVE; SQLSTATE: HY000

Message: Setting authentication options is not possible when only the Slave SQL Thread is being

started.

Error number: 1764; Symbol: ER TABLE HAS NO FT; SQLSTATE: HY000

Message: The table does not have FULLTEXT index to support this query

Error number: 1765; Symbol: ER VARIABLE NOT SETTABLE IN SF OR TRIGGER;

SOLSTATE: HY000

Message: The system variable %s cannot be set in stored functions or triggers.

Error number: 1766; Symbol: ER VARIABLE NOT SETTABLE IN TRANSACTION;

SQLSTATE: HY000

Message: The system variable %s cannot be set when there is an ongoing transaction.

Error number: 1769; Symbol: ER SET STATEMENT CANNOT INVOKE FUNCTION;

SQLSTATE: HY000

Message: The statement 'SET %s' cannot invoke a stored function.

Error number: 1770; Symbol:

ER GTID NEXT CANT BE AUTOMATIC IF GTID NEXT LIST IS NON NULL;

SQLSTATE: HY000

Message: The system variable @@SESSION.GTID NEXT cannot be 'AUTOMATIC' when

@@SESSION.GTID NEXT LIST is non-NULL.

Error number: 1772; Symbol: ER MALFORMED GTID SET SPECIFICATION; SQLSTATE:

HY000

Message: Malformed GTID set specification '%s'.

Error number: 1773; Symbol: ER MALFORMED GTID SET ENCODING; SQLSTATE: HY000

Message: Malformed GTID set encoding.

Error number: 1774; Symbol: ER MALFORMED GTID SPECIFICATION; SQLSTATE: HY000

Message: Malformed GTID specification '%s'.

Error number: 1775; Symbol: ER GNO EXHAUSTED; SQLSTATE: HY000

Message: Impossible to generate GTID: the integer component reached the maximum value. Restart

the server with a new server uuid.

Error number: 1776; Symbol: ER_BAD_SLAVE_AUTO_POSITION; SQLSTATE: HY000

Message: Parameters MASTER LOG FILE, MASTER LOG POS, RELAY LOG FILE and

RELAY LOG POS cannot be set when MASTER AUTO POSITION is active.

Error number: 1777; Symbol: ER AUTO POSITION REQUIRES GTID MODE NOT OFF;

SQLSTATE: HY000

Message: CHANGE MASTER TO MASTER AUTO POSITION = 1 cannot be executed because

@@GLOBAL.GTID MODE = OFF.

Error number: 1778; Symbol:

ER_CANT_DO_IMPLICIT_COMMIT_IN_TRX_WHEN_GTID_NEXT_IS_SET; SQLSTATE:

HY000

Message: Cannot execute statements with implicit commit inside a transaction when

@@SESSION.GTID NEXT == 'UUID:NUMBER'.

Error number: 1779; Symbol:

ER GTID MODE ON REQUIRES ENFORCE GTID CONSISTENCY ON; SQLSTATE:

HY000

Message: GTID MODE = ON requires ENFORCE GTID CONSISTENCY = ON.

Error number: 1781; Symbol:

ER_CANT_SET_GTID_NEXT_TO_GTID_WHEN_GTID_MODE_IS_OFF; SQLSTATE: HY000

Message: @@SESSION.GTID NEXT cannot be set to UUID:NUMBER when

@@GLOBAL.GTID MODE = OFF.

Error number: 1782; Symbol:

ER CANT SET GTID NEXT TO ANONYMOUS WHEN GTID MODE IS ON;

SQLSTATE: HY000

Message: @@SESSION.GTID NEXT cannot be set to ANONYMOUS when

@@GLOBAL.GTID_MODE = ON.

Error number: 1783; Symbol:

ER CANT SET GTID NEXT LIST TO NON NULL WHEN GTID MODE IS OFF;

SQLSTATE: HY000

Message: @@SESSION.GTID NEXT LIST cannot be set to a non-NULL value when

@@GLOBAL.GTID MODE = OFF.

Error number: 1785; Symbol: ER GTID UNSAFE NON TRANSACTIONAL TABLE;

SQLSTATE: HY000

Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.

Error number: 1786; Symbol: ER GTID UNSAFE CREATE SELECT; SQLSTATE: HY000

Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.

Error number: 1787; Symbol:

ER GTID UNSAFE CREATE DROP TEMPORARY TABLE IN TRANSACTION;

SQLSTATE: HY000

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE can only be executed outside transactional context. These statements are also not allowed in a function or trigger because functions and triggers are also considered to be multi-statement transactions.

6 说明:

ER_GTID_UNSAFE_CREATE_DROP_TEMPORARY_TABLE_IN_TRANSACTION was removed after 8.0.12.

Error number: 1788; Symbol:

ER_GTID_MODE_CAN_ONLY_CHANGE_ONE_STEP_AT_A_TIME; SQLSTATE: HY000 Message: The value of @@GLOBAL.GTID_MODE can only be changed one step at a time: OFF <-> OFF_PERMISSIVE <-> ON_PERMISSIVE <-> ON. Also note that this value must be stepped up or down simultaneously on all servers. See the Manual for instructions.

Error number: 1789; Symbol: ER_MASTER_HAS_PURGED_REQUIRED_GTIDS; SQLSTATE: HY000

Message: Cannot replicate because the master purged required binary logs. Replicate the missing transactions from elsewhere, or provision a new slave from backup. Consider increasing the master's binary log expiration period. %s

Error number: 1790; Symbol: ER_CANT_SET_GTID_NEXT_WHEN_OWNING_GTID; SQLSTATE: HY000

Message: @@SESSION.GTID_NEXT cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.

Error number: 1791; Symbol: ER_UNKNOWN_EXPLAIN_FORMAT; SQLSTATE: HY000 Message: Unknown EXPLAIN format name: '%s'

Error number: 1792; Symbol: ER_CANT_EXECUTE_IN_READ_ONLY_TRANSACTION; SQLSTATE: 25006

Message: Cannot execute statement in a READ ONLY transaction.

Error number: 1793; Symbol: ER_TOO_LONG_TABLE_PARTITION_COMMENT; SQLSTATE: HY000

Message: Comment for table partition '%s' is too long (max = %lu)

Error number: 1794; Symbol: ER_SLAVE_CONFIGURATION; SQLSTATE: HY000 Message: Slave is not configured or failed to initialize properly. You must at least set --server-id to enable either a master or a slave. Additional error messages can be found in the MySQL error log.

Error number: 1795; Symbol: ER INNODB FT LIMIT; SQLSTATE: HY000

Message: InnoDB presently supports one FULLTEXT index creation at a time

Error number: 1796; Symbol: ER_INNODB_NO_FT_TEMP_TABLE; SQLSTATE: HY000

Message: Cannot create FULLTEXT index on temporary InnoDB table

Error number: 1797; Symbol: ER INNODB FT WRONG DOCID COLUMN; SQLSTATE:

HY000

Message: Column '%s' is of wrong type for an InnoDB FULLTEXT index

Error number: 1798; Symbol: ER INNODB FT WRONG DOCID INDEX; SQLSTATE: HY000

Message: Index '%s' is of wrong type for an InnoDB FULLTEXT index

Error number: 1799; Symbol: ER_INNODB_ONLINE_LOG_TOO_BIG; SQLSTATE: HY000

Message: Creating index '%s' required more than 'innodb online alter log max size' bytes of

modification log. Please try again.

Error number: 1800; Symbol: ER UNKNOWN ALTER ALGORITHM; SQLSTATE: HY000

Message: Unknown ALGORITHM '%s'

Error number: 1801; Symbol: ER UNKNOWN ALTER LOCK; SQLSTATE: HY000

Message: Unknown LOCK type '%s'

Error number: 1802; Symbol: ER MTS CHANGE MASTER CANT RUN WITH GAPS;

SQLSTATE: HY000

Message: CHANGE MASTER cannot be executed when the slave was stopped with an error or

killed in MTS mode. Consider using RESET SLAVE or START SLAVE UNTIL.

Error number: 1803; Symbol: ER MTS RECOVERY FAILURE; SQLSTATE: HY000

Message: Cannot recover after SLAVE errored out in parallel execution mode. Additional error

messages can be found in the MySQL error log.

Error number: 1804; Symbol: ER MTS RESET WORKERS; SQLSTATE: HY000

Message: Cannot clean up worker info tables. Additional error messages can be found in the MySQL

error log.

Error number: 1805; Symbol: ER COL COUNT DOESNT MATCH CORRUPTED V2;

SQLSTATE: HY000

Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably

corrupted

Error number: 1806; Symbol: ER SLAVE SILENT RETRY TRANSACTION; SQLSTATE:

HY000

Message: Slave must silently retry current transaction

Error number: 1807; Symbol: ER DISCARD FK CHECKS RUNNING; SQLSTATE: HY000

Message: There is a foreign key check running on table '%s'. Cannot discard the table.

Error number: 1808; Symbol: ER TABLE SCHEMA MISMATCH; SQLSTATE: HY000

Message: Schema mismatch (%s)

Error number: 1809; Symbol: ER TABLE IN SYSTEM TABLESPACE; SQLSTATE: HY000

Message: Table '%s' in system tablespace

Error number: 1810; Symbol: ER_IO_READ_ERROR; SQLSTATE: HY000

Message: IO Read error: (%lu, %s) %s

Error number: 1811; Symbol: ER IO WRITE ERROR; SQLSTATE: HY000

Message: IO Write error: (%lu, %s) %s

Error number: 1812; Symbol: ER TABLESPACE MISSING; SQLSTATE: HY000

Message: Tablespace is missing for table %s.

Error number: 1813; Symbol: ER TABLESPACE EXISTS; SQLSTATE: HY000

Message: Tablespace '%s' exists.

Error number: 1814; Symbol: ER TABLESPACE DISCARDED; SQLSTATE: HY000

Message: Tablespace has been discarded for table '%s'

Error number: 1815; Symbol: ER INTERNAL ERROR; SQLSTATE: HY000

Message: Internal error: %s

Error number: 1816; Symbol: ER INNODB IMPORT ERROR; SQLSTATE: HY000

Message: ALTER TABLE %s IMPORT TABLESPACE failed with error %lu: '%s'

Error number: 1817; Symbol: ER_INNODB_INDEX_CORRUPT; SQLSTATE: HY000

Message: Index corrupt: %s

Error number: 1818; Symbol: ER INVALID YEAR COLUMN LENGTH; SQLSTATE: HY000

Message: Invalid display width. Use YEAR instead.

Error number: 1819; Symbol: ER NOT VALID PASSWORD; SQLSTATE: HY000

Message: Your password does not satisfy the current policy requirements

Error number: 1820; Symbol: ER MUST CHANGE PASSWORD; SQLSTATE: HY000

Message: You must reset your password using ALTER USER statement before executing this statement.

Error number: 1821; Symbol: ER FK NO INDEX CHILD; SQLSTATE: HY000

Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the foreign

table '%s'

Error number: 1822; Symbol: ER FK NO INDEX PARENT; SQLSTATE: HY000

Message: Failed to add the foreign key constraint. Missing index for constraint '%s' in the referenced

table '%s'

Error number: 1823; Symbol: ER_FK_FAIL_ADD_SYSTEM; SQLSTATE: HY000

Message: Failed to add the foreign key constraint '%s' to system tables

Error number: 1824; Symbol: ER_FK_CANNOT_OPEN_PARENT; SQLSTATE: HY000

Message: Failed to open the referenced table '%s'

Error number: 1825; Symbol: ER_FK_INCORRECT_OPTION; SQLSTATE: HY000

Message: Failed to add the foreign key constraint on table '%s'. Incorrect options in FOREIGN KEY

constraint '%s'

Error number: 1826; Symbol: ER FK DUP NAME; SQLSTATE: HY000

Message: Duplicate foreign key constraint name '%s'

Error number: 1827; Symbol: ER PASSWORD FORMAT; SQLSTATE: HY000

Message: The password hash doesn't have the expected format.

Error number: 1828; Symbol: ER FK COLUMN CANNOT DROP; SQLSTATE: HY000

Message: Cannot drop column '%s': needed in a foreign key constraint '%s'

Error number: 1829; Symbol: ER FK COLUMN CANNOT DROP CHILD; SQLSTATE: HY000

Message: Cannot drop column '%s': needed in a foreign key constraint '%s' of table '%s'

Error number: 1830; Symbol: ER_FK_COLUMN_NOT_NULL; SQLSTATE: HY000

Message: Column '%s' cannot be NOT NULL: needed in a foreign key constraint '%s' SET NULL

Error number: 1831; Symbol: ER DUP INDEX; SQLSTATE: HY000

Message: Duplicate index '%s' defined on the table '%s.%s'. This is deprecated and will be

disallowed in a future release.

Error number: 1832; Symbol: ER FK COLUMN CANNOT CHANGE; SQLSTATE: HY000

Message: Cannot change column '%s': used in a foreign key constraint '%s'

Error number: 1833; Symbol: ER_FK_COLUMN_CANNOT_CHANGE_CHILD; SQLSTATE: HY000

Message: Cannot change column '%s': used in a foreign key constraint '%s' of table '%s'

Error number: 1835; Symbol: ER_MALFORMED_PACKET; SQLSTATE: HY000

Message: Malformed communication packet.

Error number: 1836; Symbol: ER READ ONLY MODE; SQLSTATE: HY000

Message: Running in read-only mode

Error number: 1837; Symbol: ER_GTID_NEXT_TYPE_UNDEFINED_GROUP; SQLSTATE: HY000

Message: When @@SESSION.GTID_NEXT is set to a GTID, you must explicitly set it to a different value after a COMMIT or ROLLBACK. Please check GTID_NEXT variable manual page for detailed explanation. Current @@SESSION.GTID_NEXT is '%s'.

ER GTID NEXT TYPE UNDEFINED GROUP was removed after 8.0.4.

Error number: 1837; Symbol: ER_GTID_NEXT_TYPE_UNDEFINED_GTID; SQLSTATE: HY000 Message: When @@SESSION.GTID_NEXT is set to a GTID, you must explicitly set it to a different value after a COMMIT or ROLLBACK. Please check GTID_NEXT variable manual page for detailed explanation. Current @@SESSION.GTID_NEXT is '%s'.

ER GTID NEXT TYPE UNDEFINED GTID was added in 8.0.11.

Error number: 1838; Symbol: ER_VARIABLE_NOT_SETTABLE_IN_SP; SQLSTATE: HY000 Message: The system variable %s cannot be set in stored procedures.

Error number: 1840; Symbol:

ER_CANT_SET_GTID_PURGED_WHEN_GTID_EXECUTED_IS_NOT_EMPTY; SQLSTATE: HY000

Message: @@GLOBAL.GTID_PURGED can only be set when @@GLOBAL.GTID_EXECUTED is empty.

Error number: 1841; Symbol:

ER_CANT_SET_GTID_PURGED_WHEN_OWNED_GTIDS_IS_NOT_EMPTY; SQLSTATE: HY000

Message: @@GLOBAL.GTID_PURGED can only be set when there are no ongoing transactions (not even in other clients).

Error number: 1842; Symbol: ER_GTID_PURGED_WAS_CHANGED; SQLSTATE: HY000 Message: @@GLOBAL.GTID_PURGED was changed from '%s' to '%s'.

Error number: 1843; Symbol: ER_GTID_EXECUTED_WAS_CHANGED; SQLSTATE: HY000 Message: @@GLOBAL.GTID EXECUTED was changed from '%s' to '%s'.

Error number: 1844; Symbol: ER_BINLOG_STMT_MODE_AND_NO_REPL_TABLES;

SQLSTATE: HY000

Message: Cannot execute statement: impossible to write to binary log since BINLOG_FORMAT =

STATEMENT, and both replicated and non replicated tables are written to.

Error number: 1845; Symbol: ER ALTER OPERATION NOT SUPPORTED; SQLSTATE:

0A000

Message: %s is not supported for this operation. Try %s.

Error number: 1846; Symbol: ER ALTER OPERATION NOT SUPPORTED REASON;

SQLSTATE: 0A000

Message: %s is not supported. Reason: %s. Try %s.

Error number: 1847; Symbol: ER ALTER OPERATION NOT SUPPORTED REASON COPY;

SQLSTATE: HY000

Message: COPY algorithm requires a lock

Error number: 1848; Symbol:

ER ALTER OPERATION NOT SUPPORTED REASON PARTITION; SQLSTATE: HY000

Message: Partition specific operations do not yet support LOCK/ALGORITHM

Error number: 1849; Symbol:

ER ALTER OPERATION NOT SUPPORTED REASON FK RENAME; SQLSTATE: HY000

Message: Columns participating in a foreign key are renamed

Error number: 1850; Symbol:

ER ALTER OPERATION NOT SUPPORTED REASON COLUMN TYPE; SQLSTATE:

HY000

Message: Cannot change column type INPLACE

Error number: 1851; Symbol:

ER ALTER OPERATION NOT SUPPORTED REASON FK CHECK; SQLSTATE: HY000

Message: Adding foreign keys needs foreign key checks=OFF

Error number: 1853; Symbol: ER ALTER OPERATION NOT SUPPORTED REASON NOPK;

SQLSTATE: HY000

Message: Dropping a primary key is not allowed without also adding a new primary key

Error number: 1854; Symbol:

ER ALTER OPERATION NOT SUPPORTED REASON AUTOINC; SQLSTATE: HY000

Message: Adding an auto-increment column requires a lock

Error number: 1855; Symbol:

ER ALTER OPERATION NOT SUPPORTED REASON HIDDEN FTS; SQLSTATE: HY000

Message: Cannot replace hidden FTS DOC ID with a user-visible one

Error number: 1856; Symbol:

ER ALTER OPERATION NOT SUPPORTED REASON CHANGE FTS; SQLSTATE: HY000

Message: Cannot drop or rename FTS_DOC_ID

Error number: 1857; Symbol: ER ALTER OPERATION NOT SUPPORTED REASON FTS;

SQLSTATE: HY000

Message: Fulltext index creation requires a lock

Error number: 1858; Symbol:

ER SQL SLAVE SKIP COUNTER NOT SETTABLE IN GTID MODE; SQLSTATE: HY000

Message: sql slave skip counter can not be set when the server is running with

@@GLOBAL.GTID_MODE = ON. Instead, for each transaction that you want to skip, generate an

empty transaction with the same GTID as the transaction

ER_SQL_SLAVE_SKIP_COUNTER_NOT_SETTABLE_IN_GTID_MODE was removed after

8.0.22.

Error number: 1859; Symbol: ER DUP UNKNOWN IN INDEX; SQLSTATE: 23000

Message: Duplicate entry for key '%s'

Error number: 1860; Symbol: ER IDENT CAUSES TOO LONG PATH; SQLSTATE: HY000

Message: Long database name and identifier for object resulted in path length exceeding %d

characters. Path: '%s'.

Error number: 1861; Symbol:

ER ALTER OPERATION NOT SUPPORTED REASON_NOT_NULL; SQLSTATE: HY000

Message: cannot silently convert NULL values, as required in this SQL MODE

Error number: 1862; Symbol: ER MUST CHANGE PASSWORD LOGIN; SQLSTATE: HY000

Message: Your password has expired. To log in you must change it using a client that supports

expired passwords.

Error number: 1863; Symbol: ER_ROW_IN_WRONG_PARTITION; SQLSTATE: HY000

Message: Found a row in wrong partition %s

Error number: 1864; Symbol: ER_MTS_EVENT_BIGGER_PENDING_JOBS_SIZE_MAX; SQLSTATE: HY000

Message: Cannot schedule event %s, relay-log name %s, position %s to Worker thread because its size %lu exceeds %lu of replica pending jobs size max.

Error number: 1866; Symbol: ER_BINLOG_LOGICAL_CORRUPTION; SQLSTATE: HY000 Message: The binary log file '%s' is logically corrupted: %s

Error number: 1867; Symbol: ER_WARN_PURGE_LOG_IN_USE; SQLSTATE: HY000 Message: file %s was not purged because it was being read by %d thread(s), purged only %d out of %d files.

Error number: 1868; Symbol: ER_WARN_PURGE_LOG_IS_ACTIVE; SQLSTATE: HY000 Message: file %s was not purged because it is the active log file.

Error number: 1869; Symbol: ER_AUTO_INCREMENT_CONFLICT; SQLSTATE: HY000 Message: Auto-increment value in UPDATE conflicts with internally generated values

Error number: 1870; Symbol: WARN_ON_BLOCKHOLE_IN_RBR; SQLSTATE: HY000 Message: Row events are not logged for %s statements that modify BLACKHOLE tables in row format. Table(s): '%s'

Error number: 1871; Symbol: ER_SLAVE_MI_INIT_REPOSITORY; SQLSTATE: HY000 Message: Slave failed to initialize master info structure from the repository

Error number: 1872; Symbol: ER_SLAVE_RLI_INIT_REPOSITORY; SQLSTATE: HY000 Message: Slave failed to initialize relay log info structure from the repository

Error number: 1873; Symbol: ER_ACCESS_DENIED_CHANGE_USER_ERROR; SQLSTATE: 28000

Message: Access denied trying to change to user '%s'@'%s' (using password: %s). Disconnecting.

Error number: 1874; Symbol: ER_INNODB_READ_ONLY; SQLSTATE: HY000 Message: InnoDB is in read only mode.

Error number: 1875; Symbol: ER_STOP_SLAVE_SQL_THREAD_TIMEOUT; SQLSTATE: HY000

Message: STOP SLAVE command execution is incomplete: Slave SQL thread got the stop signal, thread is busy, SQL thread will stop once the current task is complete.

Error number: 1876; Symbol: ER_STOP_SLAVE_IO_THREAD_TIMEOUT; SQLSTATE: HY000

Message: STOP SLAVE command execution is incomplete: Slave IO thread got the stop signal, thread is busy, IO thread will stop once the current task is complete.

Error number: 1877; Symbol: ER TABLE CORRUPT; SQLSTATE: HY000

Message: Operation cannot be performed. The table '%s.%s' is missing, corrupt or contains bad data.

Error number: 1878; Symbol: ER_TEMP_FILE_WRITE_FAILURE; SQLSTATE: HY000 Message: Temporary file write failure.

Error number: 1879; Symbol: ER_INNODB_FT_AUX_NOT_HEX_ID; SQLSTATE: HY000 Message: Upgrade index name failed, please use create index(alter table) algorithm copy to rebuild index.

Error number: 1880; Symbol: ER_OLD_TEMPORALS_UPGRADED; SQLSTATE: HY000 Message: TIME/TIMESTAMP/DATETIME columns of old format have been upgraded to the new format.

Error number: 1881; Symbol: ER_INNODB_FORCED_RECOVERY; SQLSTATE: HY000 Message: Operation not allowed when innodb_force_recovery > 0.

Error number: 1882; Symbol: ER_AES_INVALID_IV; SQLSTATE: HY000 Message: The initialization vector supplied to %s is too short. Must be at least %d bytes long

Error number: 1883; Symbol: ER_PLUGIN_CANNOT_BE_UNINSTALLED; SQLSTATE: HY000 Message: Plugin '%s' cannot be uninstalled now. %s

Error number: 1884; Symbol:

ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_GTID_GROUP; SQLSTATE: HY000

Message: Cannot execute statement because it needs to be written to the binary log as multiple statements, and this is not allowed when @@SESSION.GTID_NEXT == 'UUID:NUMBER'. ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_GTID_GROUP was removed after 8.0.4.

Error number: 1884; Symbol:

ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_ASSIGNED_GTID; SQLSTATE: HY000

Message: Cannot execute statement because it needs to be written to the binary log as multiple statements, and this is not allowed when @@SESSION.GTID_NEXT == 'UUID:NUMBER'. ER_GTID_UNSAFE_BINLOG_SPLITTABLE_STATEMENT_AND_ASSIGNED_GTID was added in 8.0.11.

Error number: 1885; Symbol: ER_SLAVE_HAS_MORE_GTIDS_THAN_MASTER; SQLSTATE: HY000

Message: Slave has more GTIDs than the master has, using the master's SERVER_UUID. This may indicate that the end of the binary log was truncated or that the last binary log file was lost, e.g., after a power or disk failure when sync_binlog != 1. The master may or may not have rolled back transactions that were already replicated to the slave. Suggest to replicate any transactions that master has rolled back from slave to master, and/or commit empty transactions on master to account for transactions that have been committed on master but are not included in GTID EXECUTED.

Error number: 1886; Symbol: ER MISSING KEY; SQLSTATE: HY000

Message: The table '%s.%s' does not have the necessary key(s) defined on it. Please check the table definition and create index(s) accordingly.

ER MISSING KEY was added in 8.0.4.

Error number: 1887; Symbol: WARN_NAMED_PIPE_ACCESS_EVERYONE; SQLSTATE: HY000

Message: Setting named_pipe_full_access_group='%s' is insecure. Consider using a Windows group with fewer members.

WARN NAMED PIPE ACCESS EVERYONE was added in 8.0.17.

Error number: 3000; Symbol: ER FILE CORRUPT; SQLSTATE: HY000

Message: File %s is corrupted

Error number: 3001; Symbol: ER ERROR ON MASTER; SQLSTATE: HY000

Message: Query partially completed on the master (error on master: %d) and was aborted. There is a chance that your master is inconsistent at this point. If you are sure that your master is ok, run this query manually on the slave and then restart the slave with SET GLOBAL SQL REPLICA SKIP COUNTER=1; START SLAVE;. Query:'%s'

Error number: 3003; Symbol: ER_STORAGE_ENGINE_NOT_LOADED; SQLSTATE: HY000 Message: Storage engine for table '%s'.'%s' is not loaded.

Error number: 3004; Symbol: ER GET STACKED DA WITHOUT ACTIVE HANDLER;

SOLSTATE: 0Z002

Message: GET STACKED DIAGNOSTICS when handler not active

Error number: 3005; Symbol: ER_WARN_LEGACY_SYNTAX_CONVERTED; SQLSTATE:

HY000

Message: %s is no longer supported. The statement was converted to %s.

Error number: 3006; Symbol: ER_BINLOG_UNSAFE_FULLTEXT_PLUGIN; SQLSTATE: HY000

Message: Statement is unsafe because it uses a fulltext parser plugin which may not return the same value on the slave.

Error number: 3007; Symbol: ER_CANNOT_DISCARD_TEMPORARY_TABLE; SQLSTATE:

HY000

Message: Cannot DISCARD/IMPORT tablespace associated with temporary table

Error number: 3008; Symbol: ER_FK_DEPTH_EXCEEDED; SQLSTATE: HY000

Message: Foreign key cascade delete/update exceeds max depth of %d.

Error number: 3009; Symbol: ER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2;

SQLSTATE: HY000

Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d,

now running %d. Please perform the MySQL upgrade procedure.

Error number: 3010; Symbol: ER WARN TRIGGER DOESNT HAVE CREATED; SQLSTATE:

HY000

Message: Trigger %s.%s.%s does not have CREATED attribute.

Error number: 3011; Symbol: ER REFERENCED TRG DOES NOT EXIST; SQLSTATE:

HY000

Message: Referenced trigger '%s' for the given action time and event type does not exist.

Error number: 3012; Symbol: ER EXPLAIN NOT SUPPORTED; SQLSTATE: HY000

Message: EXPLAIN FOR CONNECTION command is supported only for

SELECT/UPDATE/INSERT/DELETE/REPLACE

Error number: 3013; Symbol: ER INVALID FIELD SIZE; SQLSTATE: HY000

Message: Invalid size for column '%s'.

Error number: 3014; Symbol: ER MISSING HA CREATE OPTION; SQLSTATE: HY000

Message: Table storage engine '%s' found required create option missing

Error number: 3015; Symbol: ER ENGINE OUT OF MEMORY; SQLSTATE: HY000

Message: Out of memory in storage engine '%s'.

Error number: 3016; Symbol: ER PASSWORD EXPIRE ANONYMOUS USER; SQLSTATE:

HY000

Message: The password for anonymous user cannot be expired.

Error number: 3017; Symbol: ER SLAVE SQL THREAD MUST STOP; SQLSTATE: HY000

Message: This operation cannot be performed with a running slave sql thread; run STOP SLAVE SQL THREAD first

Error number: 3018; Symbol: ER_NO_FT_MATERIALIZED_SUBQUERY; SQLSTATE: HY000 Message: Cannot create FULLTEXT index on materialized subquery

Error number: 3019; Symbol: ER_INNODB_UNDO_LOG_FULL; SQLSTATE: HY000 Message: Undo Log error: %s

Error number: 3020; Symbol: ER_INVALID_ARGUMENT_FOR_LOGARITHM; SQLSTATE: 2201E

Message: Invalid argument for logarithm

Error number: 3021; Symbol: ER_SLAVE_CHANNEL_IO_THREAD_MUST_STOP; SQLSTATE: HY000

Message: This operation cannot be performed with a running slave in thread; run STOP SLAVE IO THREAD FOR CHANNEL '%s' first.

Error number: 3022; Symbol: ER_WARN_OPEN_TEMP_TABLES_MUST_BE_ZERO; SQLSTATE: HY000

Message: This operation may not be safe when the slave has temporary tables. The tables will be kept open until the server restarts or until the tables are deleted by any replicated DROP statement. Suggest to wait until replica open temp tables = 0.

Error number: 3023; Symbol: ER_WARN_ONLY_MASTER_LOG_FILE_NO_POS; SQLSTATE: HY000

Message: CHANGE MASTER TO with a MASTER_LOG_FILE clause but no MASTER_LOG_POS clause may not be safe. The old position value may not be valid for the new binary log file.

Error number: 3024; Symbol: ER_QUERY_TIMEOUT; SQLSTATE: HY000 Message: Query execution was interrupted, maximum statement execution time exceeded

Error number: 3025; Symbol: ER_NON_RO_SELECT_DISABLE_TIMER; SQLSTATE: HY000 Message: Select is not a read only statement, disabling timer

Error number: 3026; Symbol: ER_DUP_LIST_ENTRY; SQLSTATE: HY000 Message: Duplicate entry '%s'.

Error number: 3028; Symbol: ER_AGGREGATE_ORDER_FOR_UNION; SQLSTATE: HY000 Message: Expression #%u of ORDER BY contains aggregate function and applies to a UNION, EXCEPT or INTERSECT

Error number: 3029; Symbol: ER_AGGREGATE_ORDER_NON_AGG_QUERY; SQLSTATE: HY000

Message: Expression #%u of ORDER BY contains aggregate function and applies to the result of a non-aggregated query

Error number: 3030; Symbol: ER_SLAVE_WORKER_STOPPED_PREVIOUS_THD_ERROR; SQLSTATE: HY000

Message: Slave worker has stopped after at least one previous worker encountered an error when replica-preserve-commit-order was enabled. To preserve commit order, the last transaction executed by this thread has not been committed. When restarting the slave after fixing any failed threads, you should fix this worker as well

Error number: 3031; Symbol: ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER; SQLSTATE: HY000

Message: slave preserve commit order is not supported %s.

ER_DONT_SUPPORT_SLAVE_PRESERVE_COMMIT_ORDER was removed after 8.0.25.

Error number: 3031; Symbol: ER_DONT_SUPPORT_REPLICA_PRESERVE_COMMIT_ORDER; SQLSTATE: HY000

Message: replica preserve commit order is not supported %s.

ER DONT SUPPORT REPLICA PRESERVE COMMIT ORDER was added in 8.0.26.

Error number: 3032; Symbol: ER_SERVER_OFFLINE_MODE; SQLSTATE: HY000

Message: The server is currently in offline mode

Error number: 3033; Symbol: ER_GIS_DIFFERENT_SRIDS; SQLSTATE: HY000

Message: Binary geometry function %s given two geometries of different srids: %u and %u, which should have been identical.

Geometry values passed as arguments to spatial functions must have the same SRID value.

Error number: 3034; Symbol: ER_GIS_UNSUPPORTED_ARGUMENT; SQLSTATE: HY000

Message: Calling geometry function %s with unsupported types of arguments.

A spatial function was called with a combination of argument types that the function does not support.

Error number: 3035; Symbol: ER_GIS_UNKNOWN_ERROR; SQLSTATE: HY000

Message: Unknown GIS error occurred in function %s.

Error number: 3036; Symbol: ER_GIS_UNKNOWN_EXCEPTION; SQLSTATE: HY000

Message: Unknown exception caught in GIS function %s.

Error number: 3037; Symbol: ER GIS INVALID DATA; SQLSTATE: 22023

Message: Invalid GIS data provided to function %s.

A spatial function was called with an argument not recognized as a valid geometry value.

Error number: 3038; Symbol: ER BOOST GEOMETRY EMPTY INPUT EXCEPTION;

SQLSTATE: HY000

Message: The geometry has no data in function %s.

Error number: 3039; Symbol: ER BOOST GEOMETRY CENTROID EXCEPTION;

SQLSTATE: HY000

Message: Unable to calculate centroid because geometry is empty in function %s.

Error number: 3040; Symbol:

ER BOOST GEOMETRY OVERLAY INVALID INPUT EXCEPTION; SQLSTATE: HY000

Message: Geometry overlay calculation error: geometry data is invalid in function %s.

Error number: 3041; Symbol: ER BOOST GEOMETRY TURN INFO EXCEPTION;

SQLSTATE: HY000

Message: Geometry turn info calculation error: geometry data is invalid in function %s.

Error number: 3042; Symbol:

ER BOOST GEOMETRY SELF INTERSECTION POINT EXCEPTION; SQLSTATE: HY000

Message: Analysis procedures of intersection points interrupted unexpectedly in function %s.

Error number: 3043; Symbol: ER BOOST GEOMETRY UNKNOWN EXCEPTION;

SQLSTATE: HY000

Message: Unknown exception thrown in function %s.

Error number: 3044; Symbol: ER STD BAD ALLOC ERROR; SQLSTATE: HY000

Message: Memory allocation error: %s in function %s.

Error number: 3045; Symbol: ER STD DOMAIN ERROR; SQLSTATE: HY000

Message: Domain error: %s in function %s.

Error number: 3046; Symbol: ER STD LENGTH ERROR; SQLSTATE: HY000

Message: Length error: %s in function %s.

Error number: 3047; Symbol: ER STD INVALID ARGUMENT; SQLSTATE: HY000

Message: Invalid argument error: %s in function %s.

Error number: 3048; Symbol: ER STD OUT OF RANGE ERROR; SQLSTATE: HY000

Message: Out of range error: %s in function %s.

Error number: 3049; Symbol: ER STD OVERFLOW ERROR; SQLSTATE: HY000 Message: Overflow error: %s in function %s.

Error number: 3050; Symbol: ER STD RANGE ERROR; SQLSTATE: HY000

Message: Range error: %s in function %s.

Error number: 3051; Symbol: ER STD UNDERFLOW ERROR; SQLSTATE: HY000

Message: Underflow error: %s in function %s.

Error number: 3052; Symbol: ER STD LOGIC ERROR; SQLSTATE: HY000

Message: Logic error: %s in function %s.

Error number: 3053; Symbol: ER STD RUNTIME ERROR; SQLSTATE: HY000

Message: Runtime error: %s in function %s.

Error number: 3054; Symbol: ER STD UNKNOWN EXCEPTION; SQLSTATE: HY000

Message: Unknown exception: %s in function %s.

Error number: 3055; Symbol: ER GIS DATA WRONG ENDIANESS; SQLSTATE: HY000

Message: Geometry byte string must be little endian.

Error number: 3056; Symbol: ER CHANGE MASTER PASSWORD LENGTH; SQLSTATE:

HY000

Message: The password provided for the replication user exceeds the maximum length of 32

characters

Error number: 3057; Symbol: ER USER LOCK WRONG NAME; SQLSTATE: 42000

Message: Incorrect user-level lock name '%s'.

Error number: 3058; Symbol: ER USER LOCK DEADLOCK; SQLSTATE: HY000

Message: Deadlock found when trying to get user-level lock; try rolling back transaction/releasing locks and restarting lock acquisition.

This error is returned when the metdata locking subsystem detects a deadlock for an attempt to

acquire a named lock with GET LOCK.

Error number: 3059; Symbol: ER REPLACE INACCESSIBLE ROWS; SQLSTATE: HY000

Message: REPLACE cannot be executed as it requires deleting rows that are not in the view

Error number: 3060; Symbol: ER ALTER OPERATION NOT SUPPORTED REASON GIS;

SOLSTATE: HY000

Message: Do not support online operation on table with GIS index

密级: 公开 文档版本() 8 7

Error number: 3061; Symbol: ER_ILLEGAL_USER_VAR; SQLSTATE: 42000

Message: User variable name '%s' is illegal

Error number: 3062; Symbol: ER GTID MODE OFF; SQLSTATE: HY000

Message: Cannot %s when GTID MODE = OFF.

Error number: 3064; Symbol: ER INCORRECT TYPE; SQLSTATE: HY000

Message: Incorrect type for argument %s in function %s.

Error number: 3065; Symbol: ER_FIELD_IN_ORDER_NOT_SELECT; SQLSTATE: HY000 Message: Expression #%u of ORDER BY clause is not in SELECT list, references column '%s' which is not in SELECT list; this is incompatible with %s

Error number: 3066; Symbol: ER_AGGREGATE_IN_ORDER_NOT_SELECT; SQLSTATE: HY000

Message: Expression #%u of ORDER BY clause is not in SELECT list, contains aggregate function; this is incompatible with %s

Error number: 3067; Symbol: ER INVALID RPL WILD TABLE FILTER PATTERN;

SQLSTATE: HY000

Message: Supplied filter list contains a value which is not in the required format

'db pattern.table pattern'

Error number: 3068; Symbol: ER NET OK PACKET TOO LARGE; SQLSTATE: 08S01

Message: OK packet too large

Error number: 3069; Symbol: ER_INVALID_JSON_DATA; SQLSTATE: HY000

Message: Invalid JSON data provided to function %s: %s

Error number: 3070; Symbol: ER_INVALID_GEOJSON_MISSING_MEMBER; SQLSTATE:

HY000

Message: Invalid GeoJSON data provided to function %s: Missing required member '%s'

Error number: 3071; Symbol: ER_INVALID_GEOJSON_WRONG_TYPE; SQLSTATE: HY000 Message: Invalid GeoJSON data provided to function %s: Member '%s' must be of type '%s'

Error number: 3072; Symbol: ER_INVALID_GEOJSON_UNSPECIFIED; SQLSTATE: HY000 Message: Invalid GeoJSON data provided to function %s

Error number: 3073; Symbol: ER_DIMENSION_UNSUPPORTED; SQLSTATE: HY000 Message: Unsupported number of coordinate dimensions in function %s: Found %u, expected %u

Error number: 3074; Symbol: ER_SLAVE_CHANNEL_DOES_NOT_EXIST; SQLSTATE: HY000 Message: Slave channel '%s' does not exist.

Error number: 3076; Symbol: ER SLAVE CHANNEL NAME INVALID OR TOO LONG;

SQLSTATE: HY000

Message: Couldn't create channel: Channel name is either invalid or too long.

Error number: 3077; Symbol: ER SLAVE NEW CHANNEL WRONG REPOSITORY;

SQLSTATE: HY000

Message: To have multiple channels, repository cannot be of type FILE; Please check the repository

configuration and convert them to TABLE.

Error number: 3079; Symbol: ER_SLAVE_MULTIPLE_CHANNELS_CMD; SQLSTATE: HY000 Message: Multiple channels exist on the slave. Please provide channel name as an argument.

Error number: 3080; Symbol: ER_SLAVE_MAX_CHANNELS_EXCEEDED; SQLSTATE: HY000 Message: Maximum number of replication channels allowed exceeded.

Error number: 3081; Symbol: ER_SLAVE_CHANNEL_MUST_STOP; SQLSTATE: HY000 Message: This operation cannot be performed with running replication threads; run STOP SLAVE FOR CHANNEL '%s' first

Error number: 3082; Symbol: ER_SLAVE_CHANNEL_NOT_RUNNING; SQLSTATE: HY000 Message: This operation requires running replication threads; configure slave and run START SLAVE FOR CHANNEL '%s'

Error number: 3083; Symbol: ER_SLAVE_CHANNEL_WAS_RUNNING; SQLSTATE: HY000 Message: Replication thread(s) for channel '%s' are already running.

Error number: 3084; Symbol: ER_SLAVE_CHANNEL_WAS_NOT_RUNNING; SQLSTATE: HY000

Message: Replication thread(s) for channel '%s' are already stopped.

Error number: 3085; Symbol: ER_SLAVE_CHANNEL_SQL_THREAD_MUST_STOP; SQLSTATE: HY000

Message: This operation cannot be performed with a running slave sql thread; run STOP SLAVE SQL THREAD FOR CHANNEL '%s' first.

Error number: 3086; Symbol: ER_SLAVE_CHANNEL_SQL_SKIP_COUNTER; SQLSTATE: HY000

Message: When sql_replica_skip_counter > 0, it is not allowed to start more than one SQL thread by using 'START SLAVE [SQL_THREAD]'. Value of sql_replica_skip_counter can only be used by one SQL thread at a time. Please use 'START SLAVE [SQL_THREAD] FOR CHANNEL' to start the SQL thread which will use the value of sql_replica_skip_counter.

Error number: 3087; Symbol: ER_WRONG_FIELD_WITH_GROUP_V2; SQLSTATE: HY000 Message: Expression #%u of %s is not in GROUP BY clause and contains nonaggregated column '%s' which is not functionally dependent on columns in GROUP BY clause; this is incompatible with sql mode=only full group by

Error number: 3088; Symbol: ER_MIX_OF_GROUP_FUNC_AND_FIELDS_V2; SQLSTATE: HY000

Message: In aggregated query without GROUP BY, expression #%u of %s contains nonaggregated column '%s'; this is incompatible with sql_mode=only_full_group_by

Error number: 3089; Symbol: ER_WARN_DEPRECATED_SYSVAR_UPDATE; SQLSTATE: HY000

Message: Updating '%s' is deprecated. It will be made read-only in a future release.

Error number: 3090; Symbol: ER_WARN_DEPRECATED_SQLMODE; SQLSTATE: HY000 Message: Changing sql mode '%s' is deprecated. It will be removed in a future release.

Error number: 3091; Symbol: ER_CANNOT_LOG_PARTIAL_DROP_DATABASE_WITH_GTID; SQLSTATE: HY000

Message: DROP DATABASE failed; some tables may have been dropped but the database directory remains. The GTID has not been added to GTID_EXECUTED and the statement was not written to the binary log. Fix this as follows: (1) remove all files from the database directory %s; (2) SET GTID NEXT='%s'; (3) DROP DATABASE `%s`.

Error number: 3092; Symbol: ER_GROUP_REPLICATION_CONFIGURATION; SQLSTATE: HY000

Message: The server is not configured properly to be an active member of the group. Please see more details on error log.

Error number: 3093; Symbol: ER_GROUP_REPLICATION_RUNNING; SQLSTATE: HY000 Message: The START GROUP_REPLICATION command failed since the group is already running.

Error number: 3094; Symbol: ER_GROUP_REPLICATION_APPLIER_INIT_ERROR; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed as the applier module failed to start.

Error number: 3095; Symbol:

ER_GROUP_REPLICATION_STOP_APPLIER_THREAD_TIMEOUT; SQLSTATE: HY000 Message: The STOP GROUP_REPLICATION command execution is incomplete: The applier thread got the stop signal while it was busy. The applier thread will stop once the current task is complete.

Error number: 3096; Symbol:

ER_GROUP_REPLICATION_COMMUNICATION_LAYER_SESSION_ERROR; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed as there was an error when initializing the group communication layer.

Error number: 3097; Symbol:

ER_GROUP_REPLICATION_COMMUNICATION_LAYER_JOIN_ERROR; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed as there was an error when joining the communication group.

Error number: 3098; Symbol: ER_BEFORE_DML_VALIDATION_ERROR; SQLSTATE: HY000 Message: The table does not comply with the requirements by an external plugin.

Error number: 3099; Symbol: ER_PREVENTS_VARIABLE_WITHOUT_RBR; SQLSTATE: HY000

Message: Cannot change the value of variable %s without binary log format as ROW. transaction write set extraction option value is set and binlog format is not ROW.

Error number: 3100; Symbol: ER_RUN_HOOK_ERROR; SQLSTATE: HY000 Message: Error on observer while running replication hook '%s'.

Error number: 3102; Symbol: ER_GENERATED_COLUMN_FUNCTION_IS_NOT_ALLOWED; SQLSTATE: HY000

Message: Expression of generated column '%s' contains a disallowed function.

Error number: 3103; Symbol:

ER_UNSUPPORTED_ALTER_INPLACE_ON_VIRTUAL_COLUMN; SQLSTATE: HY000 Message: INPLACE ADD or DROP of virtual columns cannot be combined with other ALTER TABLE actions

Error number: 3104; Symbol: ER_WRONG_FK_OPTION_FOR_GENERATED_COLUMN; SQLSTATE: HY000

Message: Cannot define foreign key with %s clause on a generated column.

Error number: 3105; Symbol: ER NON DEFAULT VALUE FOR GENERATED COLUMN;

SOLSTATE: HY000

Message: The value specified for generated column '%s' in table '%s' is not allowed.

Error number: 3106; Symbol: ER UNSUPPORTED ACTION ON GENERATED COLUMN;

SQLSTATE: HY000

Message: '%s' is not supported for generated columns.

Error number: 3107; Symbol: ER_GENERATED_COLUMN_NON_PRIOR; SQLSTATE: HY000 Message: Generated column can refer only to generated columns defined prior to it.

可能原因和解决方法:要解决此问题,请更改表定义以将每个生成的列定义为晚于它所引用的任何生成列。

Error number: 3108; Symbol: ER_DEPENDENT_BY_GENERATED_COLUMN; SQLSTATE: HY000

Message: Column '%s' has a generated column dependency.

可能原因和解决方法:如果另一列引用了生成的列,则不能删除或重命名它。您也必须删除这些列,或者重新定义它们以不引用生成的列。

Error number: 3109; Symbol: ER_GENERATED_COLUMN_REF_AUTO_INC; SQLSTATE: HY000

Message: Generated column '%s' cannot refer to auto-increment column.

Error number: 3110; Symbol: ER_FEATURE_NOT_AVAILABLE; SQLSTATE: HY000 Message: The '%s' feature is not available; you need to remove '%s' or use MySQL built with '%s'

Error number: 3111; Symbol: ER_CANT_SET_GTID_MODE; SQLSTATE: HY000 Message: SET @@GLOBAL.GTID MODE = %s is not allowed because %s.

Error number: 3112; Symbol: ER_CANT_USE_AUTO_POSITION_WITH_GTID_MODE_OFF; SQLSTATE: HY000

Message: The replication receiver thread%s cannot start in AUTO_POSITION mode: this server uses @@GLOBAL.GTID MODE = OFF.

Error number: 3116; Symbol:

ER_CANT_ENFORCE_GTID_CONSISTENCY_WITH_ONGOING_GTID_VIOLATING_TX;

SQLSTATE: HY000

Message: Cannot set ENFORCE_GTID_CONSISTENCY = ON because there are ongoing transactions that violate GTID consistency.

(i) 说明:

ER_CANT_SET_ENFORCE_GTID_CONSISTENCY_ON_WITH_ONGOING_GTID_VIOLATIN G TRANSACTIONS 已重命名为

ER CANT ENFORCE GTID CONSISTENCY WITH ONGOING GTID VIOLATING TX.

Error number: 3117; Symbol:

ER ENFORCE GTID CONSISTENCY WARN WITH ONGOING GTID VIOLATING TX;

SOLSTATE: HY000

Message: There are ongoing transactions that violate GTID consistency.

(i) 说明:

ER_SET_ENFORCE_GTID_CONSISTENCY_WARN_WITH_ONGOING_GTID_VIOLATING_ TRANSACTIONS 已重命名为

ER ENFORCE GTID CONSISTENCY WARN WITH ONGOING GTID VIOLATING TX.

Error number: 3118; Symbol: ER_ACCOUNT_HAS_BEEN_LOCKED; SQLSTATE: HY000

Message: Access denied for user '%s'@'%s'. Account is locked.

可能原因和解决办法:该帐户被 CREATE USER ... ACCOUNT LOCK 或 ALTER USER ... ACCOUNT LOCK 锁定。管理员可以使用 ALTER USER ... ACCOUNT UNLOCK 将其解锁。

Error number: 3119; Symbol: ER_WRONG_TABLESPACE_NAME; SQLSTATE: 42000

Message: Incorrect tablespace name '%s'

Error number: 3120; Symbol: ER TABLESPACE IS NOT EMPTY; SQLSTATE: HY000

Message: Tablespace '%s' is not empty.

Error number: 3121; Symbol: ER WRONG FILE NAME; SQLSTATE: HY000

Message: Incorrect File Name '%s'.

Error number: 3122; Symbol:

ER BOOST GEOMETRY INCONSISTENT TURNS EXCEPTION; SQLSTATE: HY000

Message: Inconsistent intersection points.

Error number: 3123; Symbol: ER WARN OPTIMIZER HINT SYNTAX ERROR; SQLSTATE:

HY000

Message: Optimizer hint syntax error

Error number: 3124; Symbol: ER WARN BAD MAX EXECUTION TIME; SQLSTATE: HY000

Message: Unsupported MAX EXECUTION TIME

Error number: 3125; Symbol: ER_WARN_UNSUPPORTED_MAX_EXECUTION_TIME;

SOLSTATE: HY000

Message: MAX_EXECUTION_TIME hint is supported by top-level standalone SELECT statements

only

The MAX EXECUTION TIME optimizer hint is supported only for SELECT statements.

Error number: 3126; Symbol: ER WARN CONFLICTING HINT; SQLSTATE: HY000

Message: Hint %s is ignored as conflicting/duplicated

Error number: 3127; Symbol: ER_WARN_UNKNOWN_QB_NAME; SQLSTATE: HY000

Message: Query block name %s is not found for %s hint

Error number: 3128; Symbol: ER UNRESOLVED HINT NAME; SQLSTATE: HY000

Message: Unresolved name %s for %s hint

Error number: 3129; Symbol: ER WARN ON MODIFYING GTID EXECUTED TABLE;

SQLSTATE: HY000

Message: Please do not modify the %s table. This is a mysql internal system table to store GTIDs for

committed transactions. Modifying it can lead to an inconsistent GTID state.

Error number: 3130; Symbol: ER_PLUGGABLE_PROTOCOL_COMMAND_NOT_SUPPORTED;

SQLSTATE: HY000

Message: Command not supported by pluggable protocols

Error number: 3131; Symbol: ER_LOCKING_SERVICE_WRONG_NAME; SQLSTATE: 42000

Message: Incorrect locking service lock name '%s'.

可能原因和解决方法: 锁定服务名称被指定为 NULL、空字符串或长度超过 64 个字符的字符

串。 命名空间和锁名称必须是非 NULL、非空且长度不超过 64 个字符。

Error number: 3132; Symbol: ER LOCKING SERVICE DEADLOCK; SQLSTATE: HY000

Message: Deadlock found when trying to get locking service lock; try releasing locks and restarting

lock acquisition.

Error number: 3133; Symbol: ER LOCKING SERVICE TIMEOUT; SQLSTATE: HY000

Message: Service lock wait timeout exceeded.

Error number: 3134; Symbol: ER GIS MAX POINTS IN GEOMETRY OVERFLOWED;

SQLSTATE: HY000

Message: Parameter %s exceeds the maximum number of points in a geometry (%lu) in function %s.

Error number: 3135; Symbol: ER SQL MODE MERGED; SQLSTATE: HY000

Message: 'NO_ZERO_DATE', 'NO_ZERO_IN_DATE' and 'ERROR_FOR_DIVISION_BY_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.

Error number: 3136; Symbol: ER_VTOKEN_PLUGIN_TOKEN_MISMATCH; SQLSTATE: HY000

Message: Version token mismatch for %.*s. Correct value %.*s

可能原因和解决方法:客户端已将其 version_tokens_session系统变量设置为它需要服务器匹配的令牌列表,但服务器令牌列表至少有一个匹配的令牌名称,其值不同于客户端所需的值。

Error number: 3137; Symbol: ER_VTOKEN_PLUGIN_TOKEN_NOT_FOUND; SQLSTATE: HY000

Message: Version token %.*s not found.

可能原因和解决方法:客户端已将其 version_tokens_session 系统变量设置为它需要服务器匹配的令牌列表,但服务器令牌列表至少缺少这些令牌之一。

Error number: 3138; Symbol: ER_CANT_SET_VARIABLE_WHEN_OWNING_GTID; SQLSTATE: HY000

Message: Variable %s cannot be changed by a client that owns a GTID. The client owns %s. Ownership is released on COMMIT or ROLLBACK.

Error number: 3139; Symbol: ER_SLAVE_CHANNEL_OPERATION_NOT_ALLOWED;

SQLSTATE: HY000

Message: %s cannot be performed on channel '%s'.

Error number: 3140; Symbol: ER_INVALID_JSON_TEXT; SQLSTATE: 22032 Message: Invalid JSON text: "%s" at position %u in value for column '%s'.

Error number: 3141; Symbol: ER_INVALID_JSON_TEXT_IN_PARAM; SQLSTATE: 22032 Message: Invalid JSON text in argument %u to function %s: "%s" at position %u.%s

Error number: 3142; Symbol: ER_INVALID_JSON_BINARY_DATA; SQLSTATE: HY000 Message: The JSON binary value contains invalid data.

Error number: 3143; Symbol: ER_INVALID_JSON_PATH; SQLSTATE: 42000 Message: Invalid JSON path expression. The error is around character position %u.%s

Error number: 3144; Symbol: ER_INVALID_JSON_CHARSET; SQLSTATE: 22032 Message: Cannot create a JSON value from a string with CHARACTER SET '%s'.

Error number: 3145; Symbol: ER_INVALID_JSON_CHARSET_IN_FUNCTION; SQLSTATE: 22032

Message: Invalid JSON character data provided to function %s: '%s'; utf8 is required.

Error number: 3146; Symbol: ER_INVALID_TYPE_FOR_JSON; SQLSTATE: 22032 Message: Invalid data type for JSON data in argument %u to function %s; a JSON string or JSON type is required.

Error number: 3147; Symbol: ER_INVALID_CAST_TO_JSON; SQLSTATE: 22032 Message: Cannot CAST value to JSON.

Error number: 3148; Symbol: ER_INVALID_JSON_PATH_CHARSET; SQLSTATE: 42000 Message: A path expression must be encoded in the utf8 character set. The path expression '%s' is encoded in character set '%s'.

Error number: 3149; Symbol: ER_INVALID_JSON_PATH_WILDCARD; SQLSTATE: 42000 Message: In this situation, path expressions may not contain the * and ** tokens or an array range.

Error number: 3150; Symbol: ER_JSON_VALUE_TOO_BIG; SQLSTATE: 22032 Message: The JSON value is too big to be stored in a JSON column.

Error number: 3151; Symbol: ER_JSON_KEY_TOO_BIG; SQLSTATE: 22032 Message: The JSON object contains a key name that is too long.

Error number: 3152; Symbol: ER_JSON_USED_AS_KEY; SQLSTATE: 42000 Message: JSON column '%s' supports indexing only via generated columns on a specified JSON path.

Error number: 3153; Symbol: ER_JSON_VACUOUS_PATH; SQLSTATE: 42000 Message: The path expression '\$' is not allowed in this context.

Error number: 3154; Symbol: ER_JSON_BAD_ONE_OR_ALL_ARG; SQLSTATE: 42000 Message: The oneOrAll argument to %s may take these values: 'one' or 'all'.

Error number: 3155; Symbol: ER_NUMERIC_JSON_VALUE_OUT_OF_RANGE; SQLSTATE: 22003

Message: Out of range JSON value for CAST to %s%s from column %s at row %ld

Error number: 3156; Symbol: ER_INVALID_JSON_VALUE_FOR_CAST; SQLSTATE: 22018 Message: Invalid JSON value for CAST to %s%s from column %s at row %ld

Error number: 3157; Symbol: ER_JSON_DOCUMENT_TOO_DEEP; SQLSTATE: 22032 Message: The JSON document exceeds the maximum depth.

Error number: 3158; Symbol: ER_JSON_DOCUMENT_NULL_KEY; SQLSTATE: 22032 Message: JSON documents may not contain NULL member names.

Error number: 3159; Symbol: ER_SECURE_TRANSPORT_REQUIRED; SQLSTATE: HY000 Message: Connections using insecure transport are prohibited while --require_secure_transport=ON. 可能原因和解决方法: 使用 require_secure_transport 系统变量,客户端只能使用安全传输进行连接。 符合条件的连接是那些使用 SSL、Unix 套接字文件或共享内存的连接。

Error number: 3160; Symbol: ER_NO_SECURE_TRANSPORTS_CONFIGURED; SQLSTATE: HY000

Message: No secure transports (SSL or Shared Memory) are configured, unable to set -- require secure transport=ON.

可能原因和解决方法:如果服务器不支持至少一种安全传输,则无法启用 require_secure_transport 系统变量。使用所需的 SSL 密钥/证书配置服务器以启用 SSL 连接,或启用 shared memory 系统变量以启用共享内存连接。

Error number: 3161; Symbol: ER_DISABLED_STORAGE_ENGINE; SQLSTATE: HY000 Message: Storage engine %s is disabled (Table creation is disallowed). 可能原因和解决方法: 尝试使用 disabled_storage_engines 系统变量值中列出的存储引擎创建表或表空间,或将现有表或表空间更改为此类引擎。选择不同的存储引擎。

Error number: 3162; Symbol: ER_USER_DOES_NOT_EXIST; SQLSTATE: HY000 Message: Authorization ID %s does not exist.

Error number: 3163; Symbol: ER_USER_ALREADY_EXISTS; SQLSTATE: HY000 Message: Authorization ID %s already exists.

Error number: 3164; Symbol: ER_AUDIT_API_ABORT; SQLSTATE: HY000 Message: Aborted by Audit API ('%s';%d).

可能原因和解决方法: 此错误表示审计插件终止了事件的执行。 该消息通常指示事件子类名 称和数字状态值。

Error number: 3165; Symbol: ER_INVALID_JSON_PATH_ARRAY_CELL; SQLSTATE: 42000 Message: A path expression is not a path to a cell in an array.

Error number: 3166; Symbol: ER_BUFPOOL_RESIZE_INPROGRESS; SQLSTATE: HY000 Message: Another buffer pool resize is already in progress.

Error number: 3167; Symbol: ER_FEATURE_DISABLED_SEE_DOC; SQLSTATE: HY000 Message: The '%s' feature is disabled; see the documentation for '%s'

Error number: 3168; Symbol: ER SERVER ISNT AVAILABLE; SQLSTATE: HY000

Message: Server isn't available

Error number: 3169; Symbol: ER_SESSION_WAS_KILLED; SQLSTATE: HY000

Message: Session was killed

Error number: 3170; Symbol: ER CAPACITY EXCEEDED; SQLSTATE: HY000

Message: Memory capacity of %llu bytes for '%s' exceeded. %s

Error number: 3171; Symbol: ER_CAPACITY_EXCEEDED_IN_RANGE_OPTIMIZER;

SQLSTATE: HY000

Message: Range optimization was not done for this query.

Error number: 3173; Symbol:

ER_CANT_WAIT_FOR_EXECUTED_GTID_SET_WHILE_OWNING_A_GTID; SQLSTATE:

HY000

Message: The client holds ownership of the GTID %s. Therefore, WAIT_FOR_EXECUTED_GTID_SET cannot wait for this GTID.

Error number: 3174; Symbol: ER CANNOT ADD FOREIGN BASE COL VIRTUAL;

SQLSTATE: HY000

Message: Cannot add foreign key on the base column of indexed virtual column.

Error number: 3175; Symbol: ER CANNOT CREATE VIRTUAL INDEX CONSTRAINT;

SQLSTATE: HY000

Message: Cannot create index on virtual column whose base column has foreign constraint.

Error number: 3176; Symbol: ER_ERROR_ON_MODIFYING_GTID_EXECUTED_TABLE;

SQLSTATE: HY000

Message: Please do not modify the %s table with an XA transaction. This is an internal system table used to store GTIDs for committed transactions. Although modifying it can lead to an inconsistent GTID state, if necessary you can modify it with a non-XA transaction.

Error number: 3177; Symbol: ER LOCK REFUSED BY ENGINE; SQLSTATE: HY000

Message: Lock acquisition refused by storage engine.

2.4 错误码及错误信息汇总 04

Error number: 3178; Symbol:

ER UNSUPPORTED ALTER ONLINE ON VIRTUAL COLUMN; SQLSTATE: HY000

Message: ADD COLUMN col...VIRTUAL, ADD INDEX(col)

Error number: 3179; Symbol: ER MASTER KEY ROTATION NOT SUPPORTED BY SE;

SQLSTATE: HY000

Message: Master key rotation is not supported by storage engine.

Error number: 3181; Symbol: ER MASTER KEY ROTATION BINLOG FAILED; SQLSTATE:

HY000

Message: Write to binlog failed. However, master key rotation has been completed successfully.

Error number: 3182; Symbol: ER MASTER KEY ROTATION SE UNAVAILABLE;

SQLSTATE: HY000

Message: Storage engine is not available.

Error number: 3183; Symbol: ER_TABLESPACE_CANNOT_ENCRYPT; SQLSTATE: HY000

Message: This tablespace can't be encrypted.

Error number: 3184; Symbol: ER INVALID ENCRYPTION OPTION; SQLSTATE: HY000

Message: Invalid encryption option.

Error number: 3185; Symbol: ER_CANNOT_FIND_KEY_IN_KEYRING; SQLSTATE: HY000 Message: Can't find master key from keyring, please check in the server log if a keyring is loaded

and initialized successfully.

Error number: 3186; Symbol: ER CAPACITY EXCEEDED IN PARSER; SQLSTATE: HY000

Message: Parser bailed out for this query.

Error number: 3187; Symbol: ER UNSUPPORTED ALTER ENCRYPTION INPLACE;

SQLSTATE: HY000

Message: Cannot alter encryption attribute by inplace algorithm.

Error number: 3188; Symbol: ER KEYRING UDF KEYRING SERVICE ERROR; SQLSTATE:

HY000

Message: Function '%s' failed because underlying keyring service returned an error. Please check if a

keyring is installed and that provided arguments are valid for the keyring you are using.

Error number: 3189; Symbol: ER USER COLUMN OLD LENGTH; SQLSTATE: HY000

Message: It seems that your db schema is old. The %s column is 77 characters long and should be 93

characters long. Please perform the MySQL upgrade procedure.

Error number: 3190; Symbol: ER CANT RESET MASTER; SQLSTATE: HY000

Message: RESET MASTER is not allowed because %s.

 $Error\ number:\ 3191;\ Symbol:\ ER_GROUP_REPLICATION_MAX_GROUP_SIZE;\ SQLSTATE:$

HY000

Message: The START GROUP_REPLICATION command failed since the group already has 9

members.

Error number: 3192; Symbol: ER CANNOT ADD FOREIGN BASE COL STORED;

SQLSTATE: HY000

Message: Cannot add foreign key on the base column of stored column.

Error number: 3193; Symbol: ER TABLE REFERENCED; SQLSTATE: HY000

Message: Cannot complete the operation because table is referenced by another connection.

Error number: 3197; Symbol: ER_XA_RETRY; SQLSTATE: HY000

Message: The resource manager is not able to commit the transaction branch at this time. Please retry

later.

Error number: 3198; Symbol: ER_KEYRING_AWS_UDF_AWS_KMS_ERROR; SQLSTATE:

HY000

Message: Function %s failed due to: %s.

Error number: 3199; Symbol: ER BINLOG UNSAFE XA; SQLSTATE: HY000

Message: Statement is unsafe because it is being used inside a XA transaction. Concurrent XA

transactions may deadlock on slaves when replicated using statements.

Error number: 3200; Symbol: ER UDF ERROR; SQLSTATE: HY000

Message: %s UDF failed; %s

Error number: 3201; Symbol: ER KEYRING MIGRATION FAILURE; SQLSTATE: HY000

Message: Can not perform keyring migration: %s

Error number: 3202; Symbol: ER KEYRING ACCESS DENIED ERROR; SQLSTATE: 42000

Message: Access denied; you need %s privileges for this operation

Error number: 3203; Symbol: ER KEYRING MIGRATION STATUS; SQLSTATE: HY000

Message: Keyring migration %s.

Error number: 3218; Symbol:

ER AUDIT LOG UDF READ INVALID MAX ARRAY LENGTH ARG VALUE;

SQLSTATE: HY000

Message: Invalid "max array length" argument value.

Error number: 3231; Symbol: ER WRITE SET EXCEEDS LIMIT; SQLSTATE: HY000 Message: The size of writeset data for the current transaction exceeds a limit imposed by an external component. If using Group Replication check 'group replication transaction size limit'.

Error number: 3235; Symbol: ER AES INVALID KDF NAME; SOLSTATE: HY000 Message: KDF method name is not valid. Please use hkdf or pbkdf2 hmac method name

Error number: 3236; Symbol: ER AES INVALID KDF ITERATIONS; SQLSTATE: HY000 Message: For KDF method pbkdf2 hmac iterations value less than 1000 or more than 65535 is not allowed due to security reasons. Please provide iterations >= 1000 and iterations < 65535

Error number: 3237; Symbol: WARN AES KEY SIZE; SQLSTATE: HY000 Message: AES key size should be %d bytes length or secure KDF methods hkdf or pbkdf2 hmac should be used, please provide exact AES key size or use KDF methods for better security.

Error number: 3238; Symbol: ER AES INVALID KDF OPTION SIZE; SQLSTATE: HY000 Message: KDF option size is invalid, please provide valid size < %d bytes and not NULL

Error number: 3500; Symbol: ER UNSUPPORT COMPRESSED TEMPORARY TABLE; SQLSTATE: HY000

Message: CREATE TEMPORARY TABLE is not allowed with ROW FORMAT=COMPRESSED or KEY BLOCK SIZE.

Error number: 3501; Symbol: ER ACL OPERATION FAILED; SQLSTATE: HY000 Message: The ACL operation failed due to the following error from SE: errcode %d - %s

Error number: 3502; Symbol: ER UNSUPPORTED INDEX ALGORITHM; SQLSTATE: HY000 Message: This storage engine does not support the %s index algorithm, storage engine default was used instead.

Error number: 3503; Symbol: ER NO SUCH DB; SQLSTATE: 42Y07

Message: Database '%s' doesn't exist

Error number: 3504; Symbol: ER TOO BIG ENUM; SQLSTATE: HY000

Message: Too many enumeration values for column %s.

Error number: 3505; Symbol: ER TOO LONG SET ENUM VALUE; SQLSTATE: HY000 Message: Too long enumeration/set value for column %s.

Error number: 3506; Symbol: ER INVALID DD OBJECT; SQLSTATE: HY000

Message: %s dictionary object is invalid. (%s)

密级: 公开 文档版本() 101

Error number: 3507; Symbol: ER UPDATING DD TABLE; SQLSTATE: HY000

Message: Failed to update %s dictionary object.

Error number: 3508; Symbol: ER INVALID DD OBJECT ID; SQLSTATE: HY000

Message: Dictionary object id (%lu) does not exist.

Error number: 3509; Symbol: ER INVALID DD OBJECT NAME; SQLSTATE: HY000

Message: Dictionary object name '%s' is invalid. (%s)

Error number: 3510; Symbol: ER TABLESPACE MISSING WITH NAME; SQLSTATE: HY000

Message: Tablespace %s doesn't exist.

Error number: 3511; Symbol: ER TOO LONG ROUTINE COMMENT; SQLSTATE: HY000

Message: Comment for routine '%s' is too long (max = %lu)

Error number: 3512; Symbol: ER SP LOAD FAILED; SQLSTATE: HY000

Message: Failed to load routine '%s'.

Error number: 3513; Symbol: ER INVALID BITWISE_OPERANDS_SIZE; SQLSTATE: HY000

Message: Binary operands of bitwise operators must be of equal length

Error number: 3514; Symbol: ER_INVALID_BITWISE_AGGREGATE_OPERANDS_SIZE;

SOLSTATE: HY000

Message: Aggregate bitwise functions cannot accept arguments longer than 511 bytes; consider

using the SUBSTRING() function

Error number: 3515; Symbol: ER WARN UNSUPPORTED HINT; SQLSTATE: HY000

Message: Hints aren't supported in %s

Error number: 3516; Symbol: ER UNEXPECTED GEOMETRY_TYPE; SQLSTATE: 22S01

Message: %s value is a geometry of unexpected type %s in %s.

Error number: 3517; Symbol: ER_SRS_PARSE_ERROR; SQLSTATE: SR002

Message: Can't parse the spatial reference system definition of SRID %u.

Error number: 3518; Symbol: ER SRS PROJ PARAMETER MISSING; SQLSTATE: SR003

Message: The spatial reference system definition for SRID %u does not specify the mandatory %s

(EPSG %u) projection parameter.

Error number: 3519; Symbol: ER_WARN_SRS_NOT_FOUND; SQLSTATE: 01000

Message: There's no spatial reference system with SRID %u.

Error number: 3520; Symbol: ER_SRS_NOT_CARTESIAN; SQLSTATE: 22S00

Message: Function %s is only defined for Cartesian spatial reference systems, but one of its

arguments is in SRID %u, which is not Cartesian.

Error number: 3521; Symbol: ER_SRS_NOT_CARTESIAN_UNDEFINED; SQLSTATE: SR001

Message: Function %s is only defined for Cartesian spatial reference systems, but one of its

arguments is in SRID %u, which has not been defined.

Error number: 3522; Symbol: ER PK INDEX CANT BE INVISIBLE; SQLSTATE: HY000

Message: A primary key index cannot be invisible

Error number: 3523; Symbol: ER_UNKNOWN_AUTHID; SQLSTATE: HY000

Message: Unknown authorization ID '%s'@'%s'

Error number: 3524; Symbol: ER FAILED ROLE GRANT; SQLSTATE: HY000

Message: Failed to grant %s` to %s

Error number: 3525; Symbol: ER OPEN ROLE TABLES; SQLSTATE: HY000

Message: Failed to open the security system tables

Error number: 3526; Symbol: ER FAILED DEFAULT ROLES; SQLSTATE: HY000

Message: Failed to set default roles

Error number: 3527; Symbol: ER COMPONENTS NO SCHEME; SQLSTATE: HY000

Message: Cannot find schema in specified URN: '%s'.

Error number: 3528; Symbol: ER_COMPONENTS_NO_SCHEME_SERVICE; SQLSTATE:

HY000

Message: Cannot acquire scheme load service implementation for schema '%s' in specified URN:

'%s'.

Error number: 3529; Symbol: ER COMPONENTS CANT LOAD; SQLSTATE: HY000

Message: Cannot load component from specified URN: '%s'.

Error number: 3530; Symbol: ER ROLE NOT GRANTED; SQLSTATE: HY000

Message: '%s'@'%s' is not granted to '%s'@'%s'

Error number: 3531; Symbol: ER FAILED REVOKE ROLE; SQLSTATE: HY000

Message: Could not revoke role from '%s'@'%s'

Error number: 3532; Symbol: ER RENAME ROLE; SQLSTATE: HY000

Message: Renaming of a role identifier is forbidden

Error number: 3533; Symbol:

ER COMPONENTS CANT ACQUIRE SERVICE IMPLEMENTATION; SQLSTATE: HY000

Message: Cannot acquire specified service implementation: '%s'.

Error number: 3534; Symbol: ER COMPONENTS CANT SATISFY DEPENDENCY;

SQLSTATE: HY000

Message: Cannot satisfy dependency for service '%s' required by component '%s'.

Error number: 3535; Symbol:

ER COMPONENTS LOAD CANT REGISTER SERVICE IMPLEMENTATION; SQLSTATE:

HY000

Message: Cannot register service implementation '%s' provided by component '%s'.

Error number: 3536; Symbol: ER_COMPONENTS_LOAD_CANT_INITIALIZE; SQLSTATE:

HY000

Message: Initialization method provided by component '%s' failed.

Error number: 3537; Symbol: ER COMPONENTS UNLOAD NOT LOADED; SQLSTATE:

HY000

Message: Component specified by URN '%s' to unload has not been loaded before.

Error number: 3538; Symbol: ER COMPONENTS UNLOAD CANT DEINITIALIZE;

SQLSTATE: HY000

Message: De-initialization method provided by component '%s' failed.

Error number: 3539; Symbol: ER COMPONENTS CANT RELEASE SERVICE; SQLSTATE:

HY000

Message: Release of previously acquired service implementation failed.

Error number: 3540; Symbol: ER_COMPONENTS_UNLOAD_CANT_UNREGISTER_SERVICE;

SQLSTATE: HY000

Message: Unregistration of service implementation '%s' provided by component '%s' failed during

unloading of the component.

Error number: 3541; Symbol: ER COMPONENTS CANT UNLOAD; SQLSTATE: HY000

Message: Cannot unload component from specified URN: '%s'.

Error number: 3542; Symbol: ER_WARN UNLOAD THE NOT PERSISTED; SQLSTATE:

HY000

Message: The Persistent Dynamic Loader was used to unload a component '%s', but it was not used to load that component before.

Error number: 3543; Symbol: ER_COMPONENT_TABLE_INCORRECT; SQLSTATE: HY000 Message: The mysql.component table is missing or has an incorrect definition.

Error number: 3544; Symbol: ER_COMPONENT_MANIPULATE_ROW_FAILED; SQLSTATE: HY000

Message: Failed to manipulate component '%s' persistence data. Error code %d from storage engine.

Error number: 3545; Symbol: ER_COMPONENTS_UNLOAD_DUPLICATE_IN_GROUP;

SQLSTATE: HY000

Message: The component with specified URN: '%s' was specified in group more than once.

Error number: 3546; Symbol: ER CANT SET GTID PURGED DUE SETS CONSTRAINTS;

SQLSTATE: HY000

Message: @@GLOBAL.GTID PURGED cannot be changed: %s

Error number: 3547; Symbol: ER CANNOT LOCK USER MANAGEMENT CACHES;

SQLSTATE: HY000

Message: Can not lock user management caches for processing.

Error number: 3548; Symbol: ER SRS NOT FOUND; SQLSTATE: SR001

Message: There's no spatial reference system with SRID %u.

Error number: 3549; Symbol: ER_VARIABLE NOT PERSISTED; SQLSTATE: HY000

Message: Variables cannot be persisted. Please retry.

Error number: 3550; Symbol: ER IS QUERY INVALID CLAUSE; SQLSTATE: HY000

Message: Information schema queries do not support the '%s' clause.

Error number: 3551; Symbol: ER UNABLE TO STORE STATISTICS; SQLSTATE: HY000

Message: Unable to store dynamic %s statistics into data dictionary.

Error number: 3552; Symbol: ER_NO_SYSTEM_SCHEMA_ACCESS; SQLSTATE: HY000

Message: Access to system schema '%s' is rejected.

Error number: 3553; Symbol: ER NO SYSTEM TABLESPACE ACCESS; SQLSTATE: HY000

Message: Access to system tablespace '%s' is rejected.

Error number: 3554; Symbol: ER NO SYSTEM TABLE ACCESS; SQLSTATE: HY000

Message: Access to %s '%s.%s' is rejected.

Error number: 3555; Symbol:

ER NO SYSTEM TABLE ACCESS FOR DICTIONARY TABLE; SQLSTATE: HY000

Message: data dictionary table

Error number: 3556; Symbol: ER NO SYSTEM TABLE ACCESS FOR SYSTEM TABLE;

SQLSTATE: HY000 Message: system table

Error number: 3557; Symbol: ER NO SYSTEM TABLE ACCESS FOR TABLE; SQLSTATE:

HY000

Message: table

Error number: 3558; Symbol: ER_INVALID_OPTION_KEY; SQLSTATE: 22023

Message: Invalid option key '%s' in function %s.

Error number: 3559; Symbol: ER INVALID OPTION VALUE; SQLSTATE: 22023

Message: Invalid value '%s' for option '%s' in function '%s'.

Error number: 3560; Symbol: ER INVALID OPTION KEY VALUE PAIR; SQLSTATE: 22023

Message: The string '%s' is not a valid key %c value pair in function %s.

Error number: 3561; Symbol: ER_INVALID_OPTION_START_CHARACTER; SQLSTATE:

22023

Message: The options argument in function %s starts with the invalid character '%c'.

Error number: 3562; Symbol: ER INVALID OPTION END CHARACTER; SQLSTATE: 22023

Message: The options argument in function %s ends with the invalid character '%c'.

Error number: 3563; Symbol: ER INVALID OPTION CHARACTERS; SQLSTATE: 22023

Message: The options argument in function %s contains the invalid character sequence '%s'.

Error number: 3564; Symbol: ER DUPLICATE OPTION KEY; SQLSTATE: 22023

Message: Duplicate option key '%s' in funtion '%s'...

Error number: 3565; Symbol: ER WARN SRS NOT FOUND AXIS ORDER; SQLSTATE:

01000

Message: There's no spatial reference system with SRID %u. The axis order is unknown.

Error number: 3566; Symbol: ER NO ACCESS TO NATIVE FCT; SQLSTATE: HY000

Message: Access to native function '%s' is rejected.

Error number: 3567; Symbol: ER_RESET_MASTER_TO_VALUE_OUT_OF_RANGE;

SQLSTATE: HY000

Message: The requested value '%llu' for the next binary log index is out of range. Please use a value

between '1' and '%lu'.

Error number: 3568; Symbol: ER UNRESOLVED TABLE LOCK; SQLSTATE: HY000

Message: Unresolved table name %s in locking clause.

Error number: 3569; Symbol: ER DUPLICATE TABLE LOCK; SQLSTATE: HY000

Message: Table %s appears in multiple locking clauses.

Error number: 3570; Symbol: ER_BINLOG_UNSAFE_SKIP_LOCKED; SQLSTATE: HY000 Message: Statement is unsafe because it uses SKIP LOCKED. The set of inserted values is non-deterministic.

Error number: 3571; Symbol: ER BINLOG UNSAFE NOWAIT; SQLSTATE: HY000

Message: Statement is unsafe because it uses NOWAIT. Whether the command will succeed or fail is not deterministic.

Error number: 3572; Symbol: ER LOCK NOWAIT; SQLSTATE: HY000

Message: Statement aborted because lock(s) could not be acquired immediately and NOWAIT is set.

Error number: 3573; Symbol: ER CTE RECURSIVE REQUIRES UNION; SQLSTATE: HY000

Message: Recursive Common Table Expression '%s' should contain a UNION

Error number: 3574; Symbol: ER_CTE_RECURSIVE_REQUIRES_NONRECURSIVE_FIRST;

SQLSTATE: HY000

Message: Recursive Common Table Expression '%s' should have one or more non-recursive query

blocks followed by one or more recursive ones

Error number: 3575; Symbol: ER_CTE_RECURSIVE_FORBIDS_AGGREGATION; SQLSTATE:

HY000

Message: Recursive Common Table Expression '%s' can contain neither aggregation nor window

functions in recursive query block

Error number: 3576; Symbol: ER CTE RECURSIVE FORBIDDEN JOIN ORDER; SQLSTATE:

HY000

Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table must neither be in the right argument of a LEFT JOIN, nor be forced to be non-first with join order hints

 $Error\ number:\ 3577;\ Symbol:\ ER_CTE_RECURSIVE_REQUIRES_SINGLE_REFERENCE;$

SQLSTATE: HY000

Message: In recursive query block of Recursive Common Table Expression '%s', the recursive table

must be referenced only once, and not in any subquery

Error number: 3578; Symbol: ER SWITCH TMP ENGINE; SQLSTATE: HY000

Message: '%s' requires @@internal tmp disk storage engine=InnoDB

Error number: 3579; Symbol: ER WINDOW NO SUCH WINDOW; SQLSTATE: HY000

Message: Window name '%s' is not defined.

Error number: 3580; Symbol: ER WINDOW CIRCULARITY IN WINDOW GRAPH;

SQLSTATE: HY000

Message: There is a circularity in the window dependency graph.

Error number: 3581; Symbol: ER WINDOW NO CHILD PARTITIONING; SQLSTATE: HY000

Message: A window which depends on another cannot define partitioning.

Error number: 3582; Symbol: ER WINDOW NO INHERIT FRAME; SQLSTATE: HY000

Message: Window '%s' has a frame definition, so cannot be referenced by another window.

Error number: 3583; Symbol: ER WINDOW NO REDEFINE ORDER BY; SQLSTATE: HY000

Message: Window '%s' cannot inherit '%s' since both contain an ORDER BY clause.

Error number: 3584; Symbol: ER WINDOW FRAME START ILLEGAL; SQLSTATE: HY000

Message: Window '%s': frame start cannot be UNBOUNDED FOLLOWING.

Error number: 3585; Symbol: ER WINDOW FRAME END ILLEGAL; SQLSTATE: HY000

Message: Window '%s': frame end cannot be UNBOUNDED PRECEDING.

Error number: 3586; Symbol: ER WINDOW FRAME ILLEGAL; SQLSTATE: HY000

Message: Window '%s': frame start or end is negative, NULL or of non-integral type

Error number: 3587; Symbol: ER WINDOW RANGE FRAME ORDER TYPE; SQLSTATE:

HY000

Message: Window '%s' with RANGE N PRECEDING/FOLLOWING frame requires exactly one

ORDER BY expression, of numeric or temporal type

Error number: 3588; Symbol: ER WINDOW RANGE FRAME TEMPORAL TYPE;

SQLSTATE: HY000

Message: Window '%s' with RANGE frame has ORDER BY expression of datetime type. Only

INTERVAL bound value allowed.

Error number: 3589; Symbol: ER_WINDOW_RANGE_FRAME_NUMERIC_TYPE; SQLSTATE: HY000

Message: Window '%s' with RANGE frame has ORDER BY expression of numeric type, INTERVAL bound value not allowed.

Error number: 3590; Symbol: ER_WINDOW_RANGE_BOUND_NOT_CONSTANT; SQLSTATE: HY000

Message: Window '%s' has a non-constant frame bound.

Error number: 3591; Symbol: ER_WINDOW_DUPLICATE_NAME; SQLSTATE: HY000 Message: Window '%s' is defined twice.

Error number: 3592; Symbol: ER_WINDOW_ILLEGAL_ORDER_BY; SQLSTATE: HY000

Message: Window '%s': ORDER BY or PARTITION BY uses legacy position indication which is not supported, use expression.

ER WINDOW ILLEGAL ORDER BY was added in 8.0.2.

Error number: 3593; Symbol: ER_WINDOW_INVALID_WINDOW_FUNC_USE; SQLSTATE: HY000

Message: You cannot use the window function '%s' in this context.'

Error number: 3594; Symbol: ER_WINDOW_INVALID_WINDOW_FUNC_ALIAS_USE; SQLSTATE: HY000

Message: You cannot use the alias '%s' of an expression containing a window function in this context.'

Error number: 3595; Symbol:

ER_WINDOW_NESTED_WINDOW_FUNC_USE_IN_WINDOW_SPEC; SQLSTATE: HY000 Message: You cannot nest a window function in the specification of window '%s'.

Error number: 3596; Symbol: ER_WINDOW_ROWS_INTERVAL_USE; SQLSTATE: HY000 Message: Window '%s': INTERVAL can only be used with RANGE frames.

Error number: 3597; Symbol: ER_WINDOW_NO_GROUP_ORDER; SQLSTATE: HY000 Message: ASC or DESC with GROUP BY isn't allowed with window functions; put ASC or DESC in ORDER BY

Error number: 3597; Symbol: ER_WINDOW_NO_GROUP_ORDER_UNUSED; SQLSTATE: HY000

Message: ASC or DESC with GROUP BY isn't allowed with window functions; put ASC or DESC in ORDER BY

Error number: 3598; Symbol: ER_WINDOW_EXPLAIN_JSON; SQLSTATE: HY000 Message: To get information about window functions use EXPLAIN FORMAT=JSON

Error number: 3599; Symbol: ER_WINDOW_FUNCTION_IGNORES_FRAME; SQLSTATE: HY000

Message: Window function '%s' ignores the frame clause of window '%s' and aggregates over the whole partition

Error number: 3600; Symbol: ER_WINDOW_SE_NOT_ACCEPTABLE; SQLSTATE: HY000 Message: Windowing requires @@internal tmp mem storage engine=TempTable.

Error number: 3600; Symbol: ER_WL9236_NOW_UNUSED; SQLSTATE: HY000 Message: Windowing requires @@internal tmp mem storage engine=TempTable.

Error number: 3601; Symbol: ER_INVALID_NO_OF_ARGS; SQLSTATE: HY000 Message: Too many arguments for function %s: %lu; maximum allowed is %s.

Error number: 3602; Symbol: ER_FIELD_IN_GROUPING_NOT_GROUP_BY; SQLSTATE: HY000

Message: Argument #%u of GROUPING function is not in GROUP BY

Error number: 3603; Symbol: ER_TOO_LONG_TABLESPACE_COMMENT; SQLSTATE: HY000

Message: Comment for tablespace '%s' is too long (max = %lu)

Error number: 3604; Symbol: ER_ENGINE_CANT_DROP_TABLE; SQLSTATE: HY000 Message: Storage engine can't drop table '%s'

Error number: 3605; Symbol: ER_ENGINE_CANT_DROP_MISSING_TABLE; SQLSTATE: HY000

Message: Storage engine can't drop table '%s' because it is missing. Use DROP TABLE IF EXISTS to remove it from data-dictionary.

Error number: 3606; Symbol: ER_TABLESPACE_DUP_FILENAME; SQLSTATE: HY000 Message: Duplicate file name for tablespace '%s'

Error number: 3607; Symbol: ER_DB_DROP_RMDIR2; SQLSTATE: HY000 Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.

Error number: 3608; Symbol: ER_IMP_NO_FILES_MATCHED; SQLSTATE: HY000

Message: No SDI files matched the pattern '%s'

Error number: 3609; Symbol: ER_IMP_SCHEMA_DOES_NOT_EXIST; SQLSTATE: HY000

Message: Schema '%s', referenced in SDI, does not exist.

Error number: 3610; Symbol: ER IMP TABLE ALREADY EXISTS; SQLSTATE: HY000

Message: Table '%s.%s', referenced in SDI, already exists.

Error number: 3611; Symbol: ER_IMP_INCOMPATIBLE_MYSQLD_VERSION; SQLSTATE:

HY000

Message: Imported mysqld version (%llu) is not compatible with current (%llu)

Error number: 3612; Symbol: ER IMP INCOMPATIBLE DD VERSION; SQLSTATE: HY000

Message: Imported dd version (%u) is not compatible with current (%u)

Error number: 3613; Symbol: ER IMP INCOMPATIBLE SDI VERSION; SQLSTATE: HY000

Message: Imported sdi version (%llu) is not compatible with current (%llu)

Error number: 3614; Symbol: ER WARN INVALID HINT; SQLSTATE: HY000

Message: Invalid number of arguments for hint %s

Error number: 3615; Symbol: ER_VAR DOES NOT EXIST; SQLSTATE: HY000

Message: Variable %s does not exist in persisted config file

Error number: 3616; Symbol: ER LONGITUDE OUT OF RANGE; SQLSTATE: 22S02

Message: Longitude %f is out of range in function %s. It must be within (%f, %f].

Error number: 3617; Symbol: ER LATITUDE OUT OF RANGE; SQLSTATE: 22S03

Message: Latitude %f is out of range in function %s. It must be within [%f, %f].

Error number: 3618; Symbol: ER_NOT_IMPLEMENTED_FOR_GEOGRAPHIC_SRS;

SOLSTATE: 22S00

Message: %s(%s) has not been implemented for geographic spatial reference systems.

Error number: 3619; Symbol: ER ILLEGAL PRIVILEGE LEVEL; SQLSTATE: HY000

Message: Illegal privilege level specified for %s

Error number: 3620; Symbol: ER NO SYSTEM VIEW ACCESS; SQLSTATE: HY000

Message: Access to system view INFORMATION SCHEMA.'%s' is rejected.

Error number: 3621; Symbol: ER COMPONENT FILTER FLABBERGASTED; SQLSTATE:

HY000

Message: The log-filter component "%s" got confused at "%s" ...

Error number: 3622; Symbol: ER PART EXPR TOO LONG; SQLSTATE: HY000

Message: Partitioning expression is too long.

Error number: 3623; Symbol: ER UDF DROP DYNAMICALLY REGISTERED; SQLSTATE:

HY000

Message: DROP FUNCTION can't drop a dynamically registered user defined function

Error number: 3624; Symbol: ER UNABLE TO STORE COLUMN STATISTICS; SQLSTATE:

HY000

Message: Unable to store column statistics for column '%s' in table '%s'.'%s'

Error number: 3625; Symbol: ER UNABLE TO UPDATE COLUMN STATISTICS;

SQLSTATE: HY000

Message: Unable to update column statistics for column '%s' in table '%s'.'%s'

Error number: 3626; Symbol: ER UNABLE TO DROP COLUMN STATISTICS; SQLSTATE:

HY000

Message: Unable to remove column statistics for column '%s' in table '%s'.'%s'

Error number: 3627; Symbol: ER UNABLE TO BUILD HISTOGRAM; SQLSTATE: HY000

Message: Unable to build histogram statistics for column '%s' in table '%s'.'%s'

Error number: 3628; Symbol: ER MANDATORY ROLE; SQLSTATE: HY000

Message: The role %s is a mandatory role and can't be revoked or dropped. The restriction can be

lifted by excluding the role identifier from the global variable mandatory roles.

Error number: 3629; Symbol: ER MISSING TABLESPACE FILE; SQLSTATE: HY000

Message: Tablespace '%s' does not have a file named '%s'

Error number: 3630; Symbol: ER PERSIST ONLY ACCESS DENIED ERROR; SQLSTATE:

42000

Message: Access denied; you need %s privileges for this operation

Error number: 3631; Symbol: ER CMD NEED SUPER; SQLSTATE: HY000

Message: You need the SUPER privilege for command '%s'

Error number: 3632; Symbol: ER PATH IN DATADIR; SQLSTATE: HY000

Message: Path is within the current data directory '%s'

Error number: 3633; Symbol: ER_DDL_IN_PROGRESS; SQLSTATE: HY000 Message: Concurrent DDL is performed during the operation. Please try again.

Error number: 3633; Symbol: ER_CLONE_DDL_IN_PROGRESS; SQLSTATE: HY000

Message: Concurrent DDL is performed during clone operation. Please try again.

Error number: 3634; Symbol: ER_TOO_MANY_CONCURRENT_CLONES; SQLSTATE: HY000

Message: Too many concurrent clone operations. Maximum allowed - %d.

Error number: 3634; Symbol: ER_CLONE_TOO_MANY_CONCURRENT_CLONES;

SQLSTATE: HY000

Message: Too many concurrent clone operations. Maximum allowed - %d.

Error number: 3635; Symbol: ER APPLIER LOG EVENT VALIDATION ERROR;

SQLSTATE: HY000

Message: The table in transaction %s does not comply with the requirements by an external plugin.

Error number: 3636; Symbol: ER_CTE_MAX_RECURSION_DEPTH; SQLSTATE: HY000 Message: Recursive query aborted after %u iterations. Try increasing @@cte_max_recursion_depth to a larger value.

Error number: 3637; Symbol: ER_NOT_HINT_UPDATABLE_VARIABLE; SQLSTATE: HY000 Message: Variable %s cannot be set using SET_VAR hint.

Error number: 3638; Symbol: ER_CREDENTIALS_CONTRADICT_TO_HISTORY; SQLSTATE: HY000

Message: Cannot use these credentials for '%.*s@%.*s' because they contradict the password history policy

Error number: 3639; Symbol: ER_WARNING_PASSWORD_HISTORY_CLAUSES_VOID; SQLSTATE: HY000

Message: Non-zero password history clauses ignored for user '%s'@'%s' as its authentication plugin %s does not support password history

Error number: 3640; Symbol: ER_CLIENT_DOES_NOT_SUPPORT; SQLSTATE: HY000 Message: The client doesn't support %s

Error number: 3641; Symbol: ER_I_S_SKIPPED_TABLESPACE; SQLSTATE: HY000 Message: Tablespace '%s' was skipped since its definition is being modified by concurrent DDL statement

Error number: 3642; Symbol: ER_TABLESPACE_ENGINE_MISMATCH; SQLSTATE: HY000 Message: Engine '%s' does not match stored engine '%s' for tablespace '%s'

Error number: 3643; Symbol: ER_WRONG_SRID_FOR_COLUMN; SQLSTATE: HY000 Message: The SRID of the geometry does not match the SRID of the column '%s'. The SRID of the geometry is %lu, but the SRID of the column is %lu. Consider changing the SRID of the geometry or the SRID property of the column.

Error number: 3644; Symbol: ER_CANNOT_ALTER_SRID_DUE_TO_INDEX; SQLSTATE: HY000

Message: The SRID specification on the column '%s' cannot be changed because there is a spatial index on the column. Please remove the spatial index before altering the SRID specification.

Error number: 3645; Symbol: ER_WARN_BINLOG_PARTIAL_UPDATES_DISABLED; SQLSTATE: HY000

Message: When %s, the option binlog_row_value_options=%s will be ignored and updates will be written in full format to binary log.

Error number: 3646; Symbol: ER_WARN_BINLOG_V1_ROW_EVENTS_DISABLED; SQLSTATE: HY000

Message: When %s, the option log_bin_use_v1_row_events=1 will be ignored and row events will be written in new format to binary log.

Error number: 3647; Symbol:

 $\label{lem:condition} \begin{tabular}{l} ER_WARN_BINLOG_PARTIAL_UPDATES_SUGGESTS_PARTIAL_IMAGES; SQLSTATE: \\ HY000 \end{tabular}$

Message: When %s, the option binlog_row_value_options=%s will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to binlog row value options is limited to less than 50%%.

Error number: 3648; Symbol: ER_COULD_NOT_APPLY_JSON_DIFF; SQLSTATE: HY000 Message: Could not apply JSON diff in table %.*s, column %s.

Error number: 3649; Symbol: ER_CORRUPTED_JSON_DIFF; SQLSTATE: HY000 Message: Corrupted JSON diff for table %.*s, column %s.

Error number: 3650; Symbol: ER_RESOURCE_GROUP_EXISTS; SQLSTATE: HY000 Message: Resource Group '%s' exists

Error number: 3651; Symbol: ER_RESOURCE_GROUP_NOT_EXISTS; SQLSTATE: HY000 Message: Resource Group '%s' does not exist.

Error number: 3652; Symbol: ER INVALID VCPU ID; SQLSTATE: HY000

Message: Invalid cpu id %u

Error number: 3653; Symbol: ER INVALID VCPU RANGE; SQLSTATE: HY000

Message: Invalid VCPU range %u-%u

Error number: 3654; Symbol: ER_INVALID_THREAD_PRIORITY; SQLSTATE: HY000 Message: Invalid thread priority value %d for %s resource group %s. Allowed range is [%d, %d].

Error number: 3655; Symbol: ER_DISALLOWED_OPERATION; SQLSTATE: HY000

Message: %s operation is disallowed on %s

Error number: 3656; Symbol: ER RESOURCE GROUP BUSY; SQLSTATE: HY000

Message: Resource group %s is busy.

Error number: 3657; Symbol: ER RESOURCE GROUP DISABLED; SQLSTATE: HY000

Message: Resource group %s is disabled.

Error number: 3658; Symbol: ER FEATURE UNSUPPORTED; SQLSTATE: HY000

Message: Feature %s is unsupported (%s).

Error number: 3659; Symbol: ER ATTRIBUTE IGNORED; SQLSTATE: HY000

Message: Attribute %s is ignored (%s).

Error number: 3660; Symbol: ER INVALID THREAD ID; SQLSTATE: HY000

Message: Invalid thread id (%llu).

Error number: 3661; Symbol: ER_RESOURCE_GROUP_BIND_FAILED; SQLSTATE: HY000

Message: Unable to bind resource group %s with thread id (%llu).(%s).

Error number: 3662; Symbol: ER INVALID USE OF FORCE OPTION; SQLSTATE: HY000

Message: Option FORCE invalid as DISABLE option is not specified.

Error number: 3663; Symbol: ER GROUP REPLICATION COMMAND FAILURE;

SQLSTATE: HY000

Message: The %s command encountered a failure. %s

Error number: 3664; Symbol: ER SDI OPERATION FAILED; SQLSTATE: HY000

Message: Failed to %s SDI '%s.%s' in tablespace '%s'.

Error number: 3665; Symbol: ER MISSING JSON TABLE VALUE; SQLSTATE: 22035

Message: Missing value for JSON TABLE column '%s'

Error number: 3666; Symbol: ER_WRONG_JSON_TABLE_VALUE; SQLSTATE: 2203F

Message: Can't store an array or an object in the scalar JSON_TABLE column '%s'

Error number: 3667; Symbol: ER TF MUST HAVE ALIAS; SQLSTATE: 42000

Message: Every table function must have an alias

Error number: 3668; Symbol: ER_TF_FORBIDDEN_JOIN_TYPE; SQLSTATE: HY000 Message: INNER or LEFT JOIN must be used for LATERAL references made by '%s'

Error number: 3669; Symbol: ER JT VALUE OUT OF RANGE; SQLSTATE: 22003

Message: Value is out of range for JSON_TABLE's column '%s'

Error number: 3670; Symbol: ER_JT_MAX_NESTED_PATH; SQLSTATE: 42000 Message: More than supported %u NESTED PATHs were found in JSON TABLE '%s'

Error number: 3671; Symbol:

ER PASSWORD EXPIRATION NOT SUPPORTED BY AUTH METHOD; SQLSTATE:

HY000

Message: The selected authentication method %.*s does not support password expiration

Error number: 3672; Symbol: ER_INVALID_GEOJSON_CRS_NOT_TOP_LEVEL; SQLSTATE: HY000

Message: Invalid GeoJSON data provided to function %s: Member 'crs' must be specified in the top level object.

Error number: 3673; Symbol: ER BAD NULL ERROR NOT IGNORED; SQLSTATE: 23000

Message: Column '%s' cannot be null

Error number: 3674; Symbol: WARN_USELESS_SPATIAL_INDEX; SQLSTATE: HY000 Message: The spatial index on column '%s' will not be used by the query optimizer since the column does not have an SRID attribute. Consider adding an SRID attribute to the column.

Error number: 3675; Symbol: ER DISK FULL NOWAIT; SQLSTATE: HY000

Message: Create table/tablespace '%s' failed, as disk is full

Error number: 3676; Symbol: ER PARSE ERROR IN DIGEST FN; SQLSTATE: HY000

Message: Could not parse argument to digest function: "%s".

Error number: 3677; Symbol: ER UNDISCLOSED PARSE ERROR IN DIGEST FN;

SOLSTATE: HY000

Message: Could not parse argument to digest function.

Error number: 3678; Symbol: ER_SCHEMA_DIR_EXISTS; SQLSTATE: HY000

Message: Schema directory '%s' already exists. This must be resolved manually (e.g. by moving the

schema directory to another location).

Error number: 3679; Symbol: ER SCHEMA DIR MISSING; SQLSTATE: HY000

Message: Schema directory '%s' does not exist

Error number: 3680; Symbol: ER SCHEMA DIR CREATE FAILED; SQLSTATE: HY000

Message: Failed to create schema directory '%s' (errno: %d - %s)

Error number: 3681; Symbol: ER SCHEMA DIR UNKNOWN; SQLSTATE: HY000

Message: Schema '%s' does not exist, but schema directory '%s' was found. This must be resolved

manually (e.g. by moving the schema directory to another location).

Error number: 3682; Symbol: ER ONLY IMPLEMENTED FOR SRID 0 AND 4326;

SQLSTATE: 22S00

Message: Function %s is only defined for SRID 0 and SRID 4326.

Error number: 3683; Symbol:

ER_BINLOG_EXPIRE_LOG_DAYS_AND_SECS_USED_TOGETHER; SQLSTATE: HY000

Message: The option expire_logs_days and binlog_expire_logs_seconds cannot be used together.

Please use binlog expire logs seconds to set the expire time (expire logs days is deprecated)

Error number: 3684; Symbol: ER REGEXP STRING NOT TERMINATED; SQLSTATE: HY000

Message: An output string could not be zero-terminated because the length exceeds the buffer

capacity.

Error number: 3684; Symbol: ER REGEXP BUFFER OVERFLOW; SQLSTATE: HY000

Message: The result string is larger than the result buffer.

Error number: 3685; Symbol: ER REGEXP ILLEGAL ARGUMENT; SQLSTATE: HY000

Message: Illegal argument to a regular expression.

Error number: 3686; Symbol: ER REGEXP INDEX OUTOFBOUNDS ERROR; SQLSTATE:

HY000

Message: Index out of bounds in regular expression search.

Error number: 3687; Symbol: ER REGEXP INTERNAL ERROR; SQLSTATE: HY000

Message: Internal error in the regular expression library.

Error number: 3688; Symbol: ER_REGEXP_RULE_SYNTAX; SQLSTATE: HY000

Message: Syntax error in regular expression on line %u, character %u.

Error number: 3689; Symbol: ER_REGEXP_BAD_ESCAPE_SEQUENCE; SQLSTATE: HY000 Message: Unrecognized escape sequence in regular expression.

Error number: 3690; Symbol: ER_REGEXP_UNIMPLEMENTED; SQLSTATE: HY000 Message: The regular expression contains a feature that is not implemented in this library version.

Error number: 3691; Symbol: ER_REGEXP_MISMATCHED_PAREN; SQLSTATE: HY000 Message: Mismatched parenthesis in regular expression.

Error number: 3692; Symbol: ER_REGEXP_BAD_INTERVAL; SQLSTATE: HY000 Message: Incorrect description of a {min,max} interval.

Error number: 3693; Symbol: ER_REGEXP_MAX_LT_MIN; SQLSTATE: HY000 Message: The maximum is less than the minumum in a {min,max} interval.

Error number: 3694; Symbol: ER_REGEXP_INVALID_BACK_REF; SQLSTATE: HY000 Message: Invalid back-reference in regular expression.

Error number: 3695; Symbol: ER_REGEXP_LOOK_BEHIND_LIMIT; SQLSTATE: HY000 Message: The look-behind assertion exceeds the limit in regular expression.

Error number: 3696; Symbol: ER_REGEXP_MISSING_CLOSE_BRACKET; SQLSTATE: HY000 Message: The regular expression contains an unclosed bracket expression.

Error number: 3697; Symbol: ER_REGEXP_INVALID_RANGE; SQLSTATE: HY000 Message: The regular expression contains an [x-y] character range where x comes after y.

Error number: 3698; Symbol: ER_REGEXP_STACK_OVERFLOW; SQLSTATE: HY000 Message: Overflow in the regular expression backtrack stack.

Error number: 3699; Symbol: ER_REGEXP_TIME_OUT; SQLSTATE: HY000 Message: Timeout exceeded in regular expression match.

Error number: 3700; Symbol: ER_REGEXP_PATTERN_TOO_BIG; SQLSTATE: HY000 Message: The regular expression pattern exceeds limits on size or complexity.

Error number: 3701; Symbol: ER_CANT_SET_ERROR_LOG_SERVICE; SQLSTATE: HY000 Message: Value for %s got confusing at or around "%s". Syntax may be wrong, component may not be INSTALLed, or a component that does not support instances may be listed more than once.

Error number: 3702; Symbol: ER EMPTY PIPELINE FOR ERROR LOG SERVICE;

SOLSTATE: HY000

Message: Setting an empty %s pipeline disables error logging!

Error number: 3703; Symbol: ER COMPONENT FILTER DIAGNOSTICS; SQLSTATE: HY000

Message: filter %s: %s

Error number: 3704; Symbol: ER INNODB CANNOT BE IGNORED; SQLSTATE: HY000

Message: ignore-builtin-innodb is ignored and will be removed in future releases.

Error number: 3704; Symbol: ER_NOT_IMPLEMENTED_FOR_CARTESIAN_SRS; SQLSTATE:

22S00

Message: %s(%s) has not been implemented for Cartesian spatial reference systems.

Error number: 3705; Symbol: ER NOT IMPLEMENTED FOR PROJECTED SRS; SQLSTATE:

22S00

Message: %s(%s) has not been implemented for projected spatial reference systems.

Error number: 3706; Symbol: ER NONPOSITIVE RADIUS; SQLSTATE: 22003

Message: Invalid radius provided to function %s: Radius must be greater than zero.

Error number: 3707; Symbol: ER RESTART SERVER FAILED; SQLSTATE: HY000

Message: Restart server failed (%s).

Error number: 3708; Symbol: ER SRS MISSING MANDATORY ATTRIBUTE; SQLSTATE:

SR006

Message: Missing mandatory attribute %s.

Error number: 3709; Symbol: ER SRS MULTIPLE ATTRIBUTE DEFINITIONS; SQLSTATE:

SR006

Message: Multiple definitions of attribute %s.

Error number: 3710; Symbol: ER SRS NAME CANT BE EMPTY OR WHITESPACE;

SOLSTATE: SR006

Message: The spatial reference system name can't be an empty string or start or end with whitespace.

Error number: 3711; Symbol:

ER SRS ORGANIZATION CANT BE EMPTY OR WHITESPACE; SQLSTATE: SR006

Message: The organization name can't be an empty string or start or end with whitespace.

Error number: 3712; Symbol: ER SRS ID ALREADY EXISTS; SQLSTATE: SR004

Message: There is already a spatial reference system with SRID %u.

Error number: 3713; Symbol: ER_WARN_SRS_ID_ALREADY_EXISTS; SQLSTATE: 01S00 Message: There is already a spatial reference system with SRID %u.

Error number: 3714; Symbol: ER_CANT_MODIFY_SRID_0; SQLSTATE: SR000 Message: SRID 0 is not modifiable.

Error number: 3715; Symbol: ER_WARN_RESERVED_SRID_RANGE; SQLSTATE: 01S01 Message: The SRID range [%u, %u] has been reserved for system use. SRSs in this range may be added, modified or removed without warning during upgrade.

Error number: 3716; Symbol: ER_CANT_MODIFY_SRS_USED_BY_COLUMN; SQLSTATE: SR005

Message: Can't modify SRID %u. There is at least one column depending on it.

Error number: 3717; Symbol: ER_SRS_INVALID_CHARACTER_IN_ATTRIBUTE; SQLSTATE: SR006

Message: Invalid character in attribute %s.

Error number: 3718; Symbol: ER_SRS_ATTRIBUTE_STRING_TOO_LONG; SQLSTATE: SR006 Message: Attribute %s is too long. The maximum length is %u characters.

Error number: 3719; Symbol: ER_DEPRECATED_UTF8_ALIAS; SQLSTATE: HY000 Message: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.

Error number: 3720; Symbol: ER_DEPRECATED_NATIONAL; SQLSTATE: HY000 Message: NATIONAL/NCHAR/NVARCHAR implies the character set UTF8MB3, which will be replaced by UTF8MB4 in a future release. Please consider using CHAR(x) CHARACTER SET UTF8MB4 in order to be unambiguous.

Error number: 3721; Symbol: ER_INVALID_DEFAULT_UTF8MB4_COLLATION; SQLSTATE: HY000

Message: Invalid default collation %s: utf8mb4_0900_ai_ci or utf8mb4_general_ci expected

Error number: 3722; Symbol: ER_UNABLE_TO_COLLECT_LOG_STATUS; SQLSTATE: HY000 Message: Unable to collect information for column '%s': %s.

Error number: 3723; Symbol: ER_RESERVED_TABLESPACE_NAME; SQLSTATE: HY000 Message: The table '%s' may not be created in the reserved tablespace '%s'.

Error number: 3724; Symbol: ER_UNABLE_TO_SET_OPTION; SQLSTATE: HY000

Message: This option cannot be set %s.

Error number: 3725; Symbol: ER_SLAVE_POSSIBLY_DIVERGED_AFTER_DDL; SQLSTATE: HY000

Message: A commit for an atomic DDL statement was unsuccessful on the master and the slave. The slave supports atomic DDL statements but the master does not, so the action taken by the slave and master might differ. Check that their states have not diverged before proceeding.

Error number: 3726; Symbol: ER_SRS_NOT_GEOGRAPHIC; SQLSTATE: 22S00 Message: Function %s is only defined for geographic spatial reference systems, but one of its arguments is in SRID %u, which is not geographic.

Error number: 3727; Symbol: ER_POLYGON_TOO_LARGE; SQLSTATE: 22023 Message: Function %s encountered a polygon that was too large. Polygons must cover less than half

the planet.

Error number: 3728; Symbol: ER_SPATIAL_UNIQUE_INDEX; SQLSTATE: HY000

Message: Spatial indexes can't be primary or unique indexes.

Error number: 3729; Symbol: ER INDEX TYPE NOT SUPPORTED FOR SPATIAL INDEX;

SQLSTATE: HY000

Message: The index type %s is not supported for spatial indexes.

Error number: 3730; Symbol: ER_FK_CANNOT_DROP_PARENT; SQLSTATE: HY000 Message: Cannot drop table '%s' referenced by a foreign key constraint '%s' on table '%s'.

Error number: 3731; Symbol: ER GEOMETRY PARAM LONGITUDE OUT OF RANGE;

SOLSTATE: 22S02

Message: A parameter of function %s contains a geometry with longitude %f, which is out of range.

It must be within (%f, %f].

Error number: 3732; Symbol: ER GEOMETRY PARAM LATITUDE OUT OF RANGE;

SQLSTATE: 22S03

Message: A parameter of function %s contains a geometry with latitude %f, which is out of range. It

must be within [%f, %f].

Error number: 3733; Symbol: ER FK CANNOT USE VIRTUAL COLUMN; SQLSTATE:

HY000

Message: Foreign key '%s' uses virtual column '%s' which is not supported.

Error number: 3734; Symbol: ER FK NO COLUMN PARENT; SQLSTATE: HY000

Message: Failed to add the foreign key constraint. Missing column '%s' for constraint '%s' in the referenced table '%s'

Error number: 3735; Symbol: ER_CANT_SET_ERROR_SUPPRESSION_LIST; SQLSTATE: HY000

Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not correspond to an error-log message.

Error number: 3736; Symbol: ER_SRS_GEOGCS_INVALID_AXES; SQLSTATE: SR002 Message: The spatial reference system definition for SRID %u specifies invalid geographic axes '%s' and '%s'. One axis must be NORTH or SOUTH and the other must be EAST or WEST.

Error number: 3737; Symbol: ER_SRS_INVALID_SEMI_MAJOR_AXIS; SQLSTATE: SR002 Message: The length of the semi-major axis must be a positive number.

Error number: 3738; Symbol: ER_SRS_INVALID_INVERSE_FLATTENING; SQLSTATE: SR002 Message: The inverse flattening must be larger than 1.0, or 0.0 if the ellipsoid is a sphere.

Error number: 3739; Symbol: ER_SRS_INVALID_ANGULAR_UNIT; SQLSTATE: SR002 Message: The angular unit conversion factor must be a positive number.

Error number: 3740; Symbol: ER_SRS_INVALID_PRIME_MERIDIAN; SQLSTATE: SR002 Message: The prime meridian must be within (-180, 180] degrees, specified in the SRS angular unit.

Error number: 3741; Symbol: ER_TRANSFORM_SOURCE_SRS_NOT_SUPPORTED; SQLSTATE: 22S00

Message: Transformation from SRID %u is not supported.

Error number: 3742; Symbol: ER_TRANSFORM_TARGET_SRS_NOT_SUPPORTED;

SQLSTATE: 22S00

Message: Transformation to SRID %u is not supported.

Error number: 3743; Symbol: ER_TRANSFORM_SOURCE_SRS_MISSING_TOWGS84;

SOLSTATE: 22S00

Message: Transformation from SRID %u is not supported. The spatial reference system has no TOWGS84 clause.

Error number: 3744; Symbol: ER_TRANSFORM_TARGET_SRS_MISSING_TOWGS84; SQLSTATE: 22S00

Message: Transformation to SRID %u is not supported. The spatial reference system has no TOWGS84 clause.

Error number: 3745; Symbol:

ER_TEMP_TABLE_PREVENTS_SWITCH_SESSION_BINLOG_FORMAT; SQLSTATE: HY000 Message: Changing @@session.binlog_format is disallowed when the session has open temporary table(s). You could wait until these temporary table(s) are dropped and try again.

Error number: 3746; Symbol:

ER_TEMP_TABLE_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT; SQLSTATE: HY000 Message: Changing @@global.binlog_format or @@persist.binlog_format is disallowed when any replication channel has open temporary table(s). You could wait until Replica_open_temp_tables = 0 and try again

Error number: 3747; Symbol:

 $\label{lem:continuous} \begin{tabular}{l} ER_RUNNING_APPLIER_PREVENTS_SWITCH_GLOBAL_BINLOG_FORMAT; SQLSTATE: \\ HY000 \end{tabular}$

Message: Changing @@global.binlog_format or @@persist.binlog_format is disallowed when any replication channel applier thread is running. You could execute STOP SLAVE SQL_THREAD and try again.

Error number: 3748; Symbol:

ER CLIENT GTID UNSAFE CREATE DROP TEMP TABLE IN TRX IN SBR;

SQLSTATE: HY000

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional context when @@session.binlog format=STATEMENT.

Error number: 3750; Symbol: ER TABLE WITHOUT PK; SQLSTATE: HY000

Message: Unable to create or change a table without a primary key, when the system variable 'sql_require_primary_key' is set. Add a primary key to the table or unset this variable to avoid this message. Note that tables without a primary key can cause performance problems in row-based replication, so please consult your DBA before changing this setting.

Error number: 3751; Symbol: WARN DATA TRUNCATED FUNCTIONAL INDEX;

SQLSTATE: 01000

Message: Data truncated for functional index '%s' at row %ld

Error number: 3751; Symbol: ER WARN DATA TRUNCATED FUNCTIONAL INDEX;

SQLSTATE: 01000

Message: Data truncated for functional index '%s' at row %ld

Error number: 3752; Symbol: ER WARN DATA OUT OF RANGE FUNCTIONAL INDEX;

SOLSTATE: 22003

Message: Value is out of range for functional index '%s' at row %ld

Error number: 3753; Symbol:

ER_FUNCTIONAL_INDEX_ON_JSON_OR_GEOMETRY_FUNCTION; SQLSTATE: 42000 Message: Cannot create a functional index on a function that returns a JSON or GEOMETRY value.

Error number: 3754; Symbol: ER FUNCTIONAL INDEX REF AUTO INCREMENT;

SQLSTATE: HY000

Message: Functional index '%s' cannot refer to an auto-increment column.

Error number: 3755; Symbol: ER_CANNOT_DROP_COLUMN_FUNCTIONAL_INDEX;

SQLSTATE: HY000

Message: Cannot drop column '%s' because it is used by a functional index. In order to drop the

column, you must remove the functional index.

Error number: 3756; Symbol: ER FUNCTIONAL INDEX PRIMARY KEY; SQLSTATE: HY000

Message: The primary key cannot be a functional index

Error number: 3757; Symbol: ER_FUNCTIONAL_INDEX_ON_LOB; SQLSTATE: HY000 Message: Cannot create a functional index on an expression that returns a BLOB or TEXT. Please

consider using CAST.

Error number: 3758; Symbol: ER_FUNCTIONAL_INDEX_FUNCTION_IS_NOT_ALLOWED;

SOLSTATE: HY000

Message: Expression of functional index '%s' contains a disallowed function.

Error number: 3759; Symbol: ER FULLTEXT FUNCTIONAL INDEX; SQLSTATE: HY000

Message: Fulltext functional index is not supported.

Error number: 3760; Symbol: ER SPATIAL FUNCTIONAL INDEX; SQLSTATE: HY000

Message: Spatial functional index is not supported.

Error number: 3761; Symbol: ER WRONG KEY COLUMN FUNCTIONAL INDEX;

SQLSTATE: HY000

Message: The used storage engine cannot index the expression '%s'.

Error number: 3762; Symbol: ER_FUNCTIONAL_INDEX_ON_FIELD; SQLSTATE: HY000

Message: Functional index on a column is not supported. Consider using a regular index instead.

Error number: 3763; Symbol:

ER GENERATED COLUMN NAMED FUNCTION IS NOT ALLOWED; SQLSTATE:

HY000

Message: Expression of generated column '%s' contains a disallowed function: %s.

Error number: 3764; Symbol: ER_GENERATED_COLUMN_ROW_VALUE; SQLSTATE: HY000 Message: Expression of generated column '%s' cannot refer to a row value.

Error number: 3765; Symbol: ER_GENERATED_COLUMN_VARIABLES; SQLSTATE: HY000 Message: Expression of generated column '%s' cannot refer user or system variables.

Error number: 3766; Symbol: ER_DEPENDENT_BY_DEFAULT_GENERATED_VALUE; SQLSTATE: HY000

Message: Column '%s' of table '%s' has a default value expression dependency and cannot be dropped or renamed.

Error number: 3767; Symbol: ER_DEFAULT_VAL_GENERATED_NON_PRIOR; SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer to a column defined after it if that column is a generated column or has an expression as default value.

Error number: 3768; Symbol: ER_DEFAULT_VAL_GENERATED_REF_AUTO_INC; SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer to an auto-increment column.

Error number: 3769; Symbol:

ER_DEFAULT_VAL_GENERATED_FUNCTION_IS_NOT_ALLOWED; SQLSTATE: HY000 Message: Default value expression of column '%s' contains a disallowed function.

Error number: 3770; Symbol:

 $\label{lem:condition} \begin{tabular}{l} ER_DEFAULT_VAL_GENERATED_NAMED_FUNCTION_IS_NOT_ALLOWED; SQLSTATE: \\ HY000 \end{tabular}$

Message: Default value expression of column '%s' contains a disallowed function: %s.

Error number: 3771; Symbol: ER_DEFAULT_VAL_GENERATED_ROW_VALUE; SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer to a row value.

Error number: 3772; Symbol: ER_DEFAULT_VAL_GENERATED_VARIABLES; SQLSTATE: HY000

Message: Default value expression of column '%s' cannot refer user or system variables.

Error number: 3773; Symbol: ER_DEFAULT_AS_VAL_GENERATED; SQLSTATE: HY000 Message: DEFAULT function cannot be used with default value expressions

Error number: 3774; Symbol:

ER UNSUPPORTED ACTION ON DEFAULT VAL GENERATED; SQLSTATE: HY000

Message: '%s' is not supported for default value expressions.

Error number: 3775; Symbol:

ER_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION; SQLSTATE:

HY000

Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with

expression as DEFAULT.

Error number: 3776; Symbol: ER FK CANNOT CHANGE ENGINE; SQLSTATE: HY000

Message: Cannot change table's storage engine because the table participates in a foreign key

constraint.

Error number: 3777; Symbol: ER_WARN_DEPRECATED_USER_SET_EXPR; SQLSTATE:

HY000

Message: Setting user variables within expressions is deprecated and will be removed in a future release. Consider alternatives: 'SET variable=expression, ...', or 'SELECT expression(s) INTO

variables(s)'.

Error number: 3778; Symbol: ER_WARN_DEPRECATED_UTF8MB3_COLLATION;

SQLSTATE: HY000

Message: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using

UTF8MB4 with an appropriate collation instead.

Error number: 3779; Symbol: ER WARN DEPRECATED NESTED COMMENT SYNTAX;

SQLSTATE: HY000

Message: Nested comment syntax is deprecated and will be removed in a future release.

Error number: 3780; Symbol: ER FK INCOMPATIBLE COLUMNS; SQLSTATE: HY000

Message: Referencing column '%s' and referenced column '%s' in foreign key constraint '%s' are

incompatible.

Error number: 3781; Symbol: ER GR HOLD WAIT TIMEOUT; SQLSTATE: HY000

Message: Timeout exceeded for held statement while new Group Replication primary member is

applying backlog.

Error number: 3782; Symbol: ER GR HOLD KILLED; SQLSTATE: HY000

Message: Held statement aborted because Group Replication plugin got shut down or thread was

killed while new primary member was applying backlog.

Error number: 3783; Symbol: ER GR HOLD MEMBER STATUS ERROR; SQLSTATE: HY000

Message: Held statement was aborted due to member being in error state, while backlog is being applied during Group Replication primary election.

Error number: 3784; Symbol: ER_RPL_ENCRYPTION_FAILED_TO_FETCH_KEY; SQLSTATE: HY000

Message: Failed to fetch key from keyring, please check if keyring is loaded.

Error number: 3785; Symbol: ER_RPL_ENCRYPTION_KEY_NOT_FOUND; SQLSTATE: HY000 Message: Can't find key from keyring, please check in the server log if a keyring is loaded and initialized successfully.

Error number: 3786; Symbol: ER_RPL_ENCRYPTION_KEYRING_INVALID_KEY; SQLSTATE: HY000

Message: Fetched an invalid key from keyring.

Error number: 3787; Symbol: ER_RPL_ENCRYPTION_HEADER_ERROR; SQLSTATE: HY000 Message: Error reading a replication log encryption header: %s.

Error number: 3788; Symbol: ER_RPL_ENCRYPTION_FAILED_TO_ROTATE_LOGS;

SQLSTATE: HY000

Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem and rotate the logs manually.

Error number: 3789; Symbol: ER RPL ENCRYPTION KEY EXISTS UNEXPECTED;

SQLSTATE: HY000

Message: Key %s exists unexpected.

Error number: 3790; Symbol: ER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY;

SQLSTATE: HY000

Message: Failed to generate key, please check if keyring is loaded.

Error number: 3791; Symbol: ER RPL ENCRYPTION FAILED TO STORE KEY; SQLSTATE:

HY000

Message: Failed to store key, please check if keyring is loaded.

Error number: 3792; Symbol: ER RPL ENCRYPTION FAILED TO REMOVE KEY;

SQLSTATE: HY000

Message: Failed to remove key, please check if keyring is loaded.

Error number: 3793; Symbol: ER RPL ENCRYPTION UNABLE TO CHANGE OPTION;

SOLSTATE: HY000

Message: Failed to change binlog encryption value. %s.

Error number: 3794; Symbol: ER_RPL_ENCRYPTION_MASTER_KEY_RECOVERY_FAILED;

SQLSTATE: HY000

Message: Unable to recover binlog encryption master key, please check if keyring is loaded.

Error number: 3795; Symbol:

ER_SLOW_LOG_MODE_IGNORED_WHEN_NOT_LOGGING_TO_FILE; SQLSTATE: HY000 Message: slow query log file format changed as requested, but setting will have no effect when not actually logging to a file.

Error number: 3796; Symbol: ER_GRP_TRX_CONSISTENCY_NOT_ALLOWED; SQLSTATE: HY000

Message: The option group replication consistency cannot be used on the current member state.

Error number: 3797; Symbol: ER_GRP_TRX_CONSISTENCY_BEFORE; SQLSTATE: HY000 Message: Error while waiting for group transactions commit on group_replication_consistency= 'BEFORE'.

Error number: 3798; Symbol: ER_GRP_TRX_CONSISTENCY_AFTER_ON_TRX_BEGIN; SQLSTATE: HY000

Message: Error while waiting for transactions with group_replication_consistency= 'AFTER' to commit.

Error number: 3799; Symbol: ER_GRP_TRX_CONSISTENCY_BEGIN_NOT_ALLOWED; SQLSTATE: HY000

Message: The Group Replication plugin is stopping, therefore new transactions are not allowed to start.

Error number: 3800; Symbol: ER_FUNCTIONAL_INDEX_ROW_VALUE_IS_NOT_ALLOWED; SOLSTATE: HY000

Message: Expression of functional index '%s' cannot refer to a row value.

Error number: 3801; Symbol: ER_RPL_ENCRYPTION_FAILED_TO_ENCRYPT; SQLSTATE: HY000

Message: Failed to encrypt content to write into binlog file: %s.

Error number: 3802; Symbol: ER_PAGE_TRACKING_NOT_STARTED; SQLSTATE: HY000 Message: Page Tracking is not started yet.

Error number: 3803; Symbol: ER_PAGE_TRACKING_RANGE_NOT_TRACKED; SQLSTATE: HY000

Message: Tracking was not enabled for the LSN range specified

Error number: 3804; Symbol: ER_PAGE_TRACKING_CANNOT_PURGE; SQLSTATE: HY000 Message: Cannot purge data when concurrent clone is in progress. Try later.

Error number: 3805; Symbol:

ER_RPL_ENCRYPTION_CANNOT_ROTATE_BINLOG_MASTER_KEY; SQLSTATE: HY000 Message: Cannot rotate binary log master key when 'binlog-encryption' is off.

Error number: 3806; Symbol:

ER_BINLOG_MASTER_KEY_RECOVERY_OUT_OF_COMBINATION; SQLSTATE: HY000 Message: Unable to recover binary log master key, the combination of new_master_key_seqno=%u, master_key_seqno=%u and old_master_key_seqno=%u are wrong.

Error number: 3807; Symbol:

ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_OPERATE_KEY; SQLSTATE: HY000 Message: Failed to operate binary log master key on keyring, please check if keyring is loaded. The statement had no effect: the old binary log master key is still in use, the keyring, binary and relay log files are unchanged, and the server could not start using a new binary log master key for encrypting new binary and relay log files.

Error number: 3808; Symbol:

ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_ROTATE_LOGS; SQLSTATE: HY000 Message: Failed to rotate one or more binary or relay log files. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.

Error number: 3809; Symbol:

ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_REENCRYPT_LOG; SQLSTATE: HY000

Message: %s. A new binary log master key was generated and will be used to encrypt new binary and relay log files. There may still exist binary or relay log files using the previous binary log master key.

Error number: 3810; Symbol:

ER BINLOG MASTER KEY ROTATION FAIL TO CLEANUP UNUSED KEYS;

SQLSTATE: HY000

Message: Failed to remove unused binary log encryption keys from the keyring, please check if keyring is loaded. The unused binary log encryption keys may still exist in the keyring, and they will be removed upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

Error number: 3811; Symbol:

ER_BINLOG_MASTER_KEY_ROTATION_FAIL_TO_CLEANUP_AUX_KEY; SQLSTATE: HY000

Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

Error number: 3812; Symbol: ER NON BOOLEAN EXPR FOR CHECK CONSTRAINT;

SQLSTATE: HY000

Message: An expression of non-boolean type specified to a check constraint '%s'.

Error number: 3813; Symbol:

ER_COLUMN_CHECK_CONSTRAINT_REFERENCES_OTHER_COLUMN; SQLSTATE:

HY000

Message: Column check constraint '%s' references other column.

Error number: 3814; Symbol:

ER_CHECK_CONSTRAINT_NAMED_FUNCTION_IS_NOT_ALLOWED; SQLSTATE: HY000

Message: An expression of a check constraint '%s' contains disallowed function: %s.

Error number: 3815; Symbol: ER_CHECK_CONSTRAINT_FUNCTION_IS_NOT_ALLOWED;

SOLSTATE: HY000

Message: An expression of a check constraint '%s' contains disallowed function.

Error number: 3816; Symbol: ER_CHECK_CONSTRAINT_VARIABLES; SQLSTATE: HY000 Message: An expression of a check constraint '%s' cannot refer to a user or system variable.

Error number: 3817; Symbol: ER_CHECK_CONSTRAINT_ROW_VALUE; SQLSTATE: HY000 Message: Check constraint '%s' cannot refer to a row value.

Error number: 3818; Symbol:

ER_CHECK_CONSTRAINT_REFERS_AUTO_INCREMENT_COLUMN; SQLSTATE: HY000 Message: Check constraint '%s' cannot refer to an auto-increment column.

Error number: 3819; Symbol: ER_CHECK_CONSTRAINT_VIOLATED; SQLSTATE: HY000 Message: Check constraint '%s' is violated.

Error number: 3820; Symbol: ER_CHECK CONSTRAINT REFERS UNKNOWN COLUMN;

SQLSTATE: HY000

Message: Check constraint '%s' refers to non-existing column '%s'.

Error number: 3821; Symbol: ER_CHECK_CONSTRAINT_NOT_FOUND; SQLSTATE: HY000 Message: Check constraint '%s' is not found in the table.

Error number: 3822; Symbol: ER_CHECK_CONSTRAINT_DUP_NAME; SQLSTATE: HY000 Message: Duplicate check constraint name '%s'.

Error number: 3823; Symbol:

ER_CHECK_CONSTRAINT_CLAUSE_USING_FK_REFER_ACTION_COLUMN; SQLSTATE: HY000

Message: Column '%s' cannot be used in a check constraint '%s': needed in a foreign key constraint '%s' referential action.

Error number: 3824; Symbol: WARN_UNENCRYPTED_TABLE_IN_ENCRYPTED_DB; SQLSTATE: HY000

Message: Creating an unencrypted table in a database with default encryption enabled.

Error number: 3825; Symbol: ER_INVALID_ENCRYPTION_REQUEST; SQLSTATE: HY000 Message: Request to create %s table while using an %s tablespace.

Error number: 3826; Symbol: ER_CANNOT_SET_TABLE_ENCRYPTION; SQLSTATE: HY000 Message: Table encryption differ from its database default encryption, and user doesn't have enough privilege.

Error number: 3827; Symbol: ER_CANNOT_SET_DATABASE_ENCRYPTION; SQLSTATE: HY000

Message: Database default encryption differ from 'default_table_encryption' setting, and user doesn't have enough privilege.

Error number: 3828; Symbol: ER_CANNOT_SET_TABLESPACE_ENCRYPTION; SQLSTATE: HY000

Message: Tablespace encryption differ from 'default_table_encryption' setting, and user doesn't have enough privilege.

Error number: 3829; Symbol: ER_TABLESPACE_CANNOT_BE_ENCRYPTED; SQLSTATE: HY000

Message: This tablespace can't be encrypted, because one of table's schema has default encryption OFF and user doesn't have enough privilege.

Error number: 3830; Symbol: ER_TABLESPACE_CANNOT_BE_DECRYPTED; SQLSTATE: HY000

Message: This tablespace can't be decrypted, because one of table's schema has default encryption ON and user doesn't have enough privilege.

Error number: 3831; Symbol: ER_TABLESPACE_TYPE_UNKNOWN; SQLSTATE: HY000 Message: Cannot determine the type of the tablespace named '%s'.

Error number: 3832; Symbol: ER_TARGET_TABLESPACE_UNENCRYPTED; SQLSTATE:

HY000

Message: Source tablespace is encrypted but target tablespace is not.

Error number: 3833; Symbol: ER_CANNOT_USE_ENCRYPTION_CLAUSE; SQLSTATE: HY000

Message: ENCRYPTION clause is not valid for %s tablespace.

Error number: 3834; Symbol: ER_INVALID_MULTIPLE_CLAUSES; SQLSTATE: HY000 Message: Multiple %s clauses

Error number: 3835; Symbol: ER_UNSUPPORTED_USE_OF_GRANT_AS; SQLSTATE: HY000 Message: GRANT ... AS is currently supported only for global privileges.

Error number: 3836; Symbol:

ER_UKNOWN_AUTH_ID_OR_ACCESS_DENIED_FOR_GRANT_AS; SQLSTATE: HY000 Message: Either some of the authorization IDs in the AS clause are invalid or the current user lacks privileges to execute the statement.

Error number: 3837; Symbol: ER_DEPENDENT_BY_FUNCTIONAL_INDEX; SQLSTATE: HY000

Message: Column '%s' has a functional index dependency and cannot be dropped or renamed.

Error number: 3838; Symbol: ER_PLUGIN_NOT_EARLY; SQLSTATE: HY000 Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load,

Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load, keyring migration etc.

Error number: 3839; Symbol: ER_INNODB_REDO_LOG_ARCHIVE_START_SUBDIR_PATH; SQLSTATE: HY000

Message: Redo log archiving start prohibits path name in 'subdir' argument

Error number: 3840; Symbol: ER INNODB REDO LOG ARCHIVE START TIMEOUT;

SQLSTATE: HY000

Message: Redo log archiving start timed out

Error number: 3841; Symbol: ER INNODB REDO LOG ARCHIVE DIRS INVALID;

SOLSTATE: HY000

Message: Server variable 'innodb redo log archive dirs' is NULL or empty

Error number: 3842; Symbol: ER INNODB REDO LOG ARCHIVE LABEL NOT FOUND;

SQLSTATE: HY000

Message: Label '%s' not found in server variable 'innodb redo log archive dirs'

Error number: 3843; Symbol: ER INNODB REDO LOG ARCHIVE DIR EMPTY; SQLSTATE:

HY000

Message: Directory is empty after label '%s' in server variable 'innodb redo log archive dirs'

Error number: 3844; Symbol: ER INNODB REDO LOG ARCHIVE NO SUCH DIR;

SQLSTATE: HY000

Message: Redo log archive directory '%s' does not exist or is not a directory

Error number: 3845; Symbol: ER INNODB REDO LOG ARCHIVE DIR CLASH; SQLSTATE:

HY000

Message: Redo log archive directory '%s' is in, under, or over server directory '%s' - '%s'

Error number: 3846; Symbol: ER INNODB REDO LOG ARCHIVE DIR PERMISSIONS;

SQLSTATE: HY000

Message: Redo log archive directory '%s' is accessible to all OS users

Error number: 3847; Symbol: ER INNODB REDO LOG ARCHIVE FILE CREATE;

SOLSTATE: HY000

Message: Cannot create redo log archive file '%s' (OS errno: %d - %s)

Error number: 3848; Symbol: ER INNODB REDO LOG ARCHIVE ACTIVE; SQLSTATE:

HY000

Message: Redo log archiving has been started on '%s' - Call innodb redo log archive stop() first

Error number: 3849; Symbol: ER INNODB REDO LOG ARCHIVE INACTIVE; SQLSTATE:

HY000

Message: Redo log archiving is not active

Error number: 3850; Symbol: ER INNODB REDO LOG ARCHIVE FAILED; SQLSTATE:

HY000

Message: Redo log archiving failed: %s

Error number: 3851; Symbol: ER INNODB REDO LOG ARCHIVE SESSION; SQLSTATE:

HY000

Message: Redo log archiving has not been started by this session

Error number: 3852; Symbol: ER STD REGEX ERROR; SQLSTATE: HY000

Message: Regex error: %s in function %s.

Error number: 3853; Symbol: ER_INVALID_JSON_TYPE; SQLSTATE: 22032 Message: Invalid JSON type in argument %u to function %s; an %s is required.

Error number: 3854; Symbol: ER CANNOT CONVERT STRING; SQLSTATE: HY000

Message: Cannot convert string '%s' from %s to %s

Error number: 3855; Symbol: ER_DEPENDENT_BY_PARTITION_FUNC; SQLSTATE: HY000 Message: Column '%s' has a partitioning function dependency and cannot be dropped or renamed.

Error number: 3856; Symbol: ER_WARN_DEPRECATED_FLOAT_AUTO_INCREMENT; SQLSTATE: HY000

Message: AUTO_INCREMENT support for FLOAT/DOUBLE columns is deprecated and will be removed in a future release. Consider removing AUTO INCREMENT from column '%s'.

Error number: 3857; Symbol: ER_RPL_CANT_STOP_SLAVE_WHILE_LOCKED_BACKUP; SQLSTATE: HY000

Message: Cannot stop the slave SQL thread while the instance is locked for backup. Try running `UNLOCK INSTANCE` first.

Error number: 3858; Symbol: ER_WARN_DEPRECATED_FLOAT_DIGITS; SQLSTATE: HY000 Message: Specifying number of digits for floating point data types is deprecated and will be removed in a future release.

Error number: 3859; Symbol: ER_WARN_DEPRECATED_FLOAT_UNSIGNED; SQLSTATE: HY000

Message: UNSIGNED for decimal and floating point data types is deprecated and support for it will be removed in a future release.

Error number: 3860; Symbol: ER_WARN_DEPRECATED_INTEGER_DISPLAY_WIDTH;

SQLSTATE: HY000

Message: Integer display width is deprecated and will be removed in a future release.

Error number: 3861; Symbol: ER_WARN_DEPRECATED_ZEROFILL; SQLSTATE: HY000 Message: The ZEROFILL attribute is deprecated and will be removed in a future release. Use the LPAD function to zero-pad numbers, or store the formatted numbers in a CHAR column.

Error number: 3862; Symbol: ER CLONE DONOR; SQLSTATE: HY000

Message: Clone Donor Error: %s.

Error number: 3863; Symbol: ER CLONE PROTOCOL; SQLSTATE: HY000

Message: Clone received unexpected response from Donor: %s.

Error number: 3864; Symbol: ER_CLONE_DONOR_VERSION; SQLSTATE: HY000 Message: Clone Donor MySQL version: %s is different from Recipient MySQL version %s.

Error number: 3865; Symbol: ER_CLONE_OS; SQLSTATE: HY000 Message: Clone Donor OS: %s is different from Recipient OS: %s.

Error number: 3866; Symbol: ER_CLONE_PLATFORM; SQLSTATE: HY000 Message: Clone Donor platform: %s is different from Recipient platform: %s.

Error number: 3867; Symbol: ER_CLONE_CHARSET; SQLSTATE: HY000

Message: Clone Donor collation: %s is unavailable in Recipient.

Error number: 3868; Symbol: ER_CLONE_CONFIG; SQLSTATE: HY000

Message: Clone Configuration %s: Donor value: %s is different from Recipient value: %s.

Error number: 3869; Symbol: ER_CLONE_SYS_CONFIG; SQLSTATE: HY000

Message: Clone system configuration: %s

Error number: 3870; Symbol: ER CLONE PLUGIN MATCH; SQLSTATE: HY000

Message: Clone Donor plugin %s is not active in Recipient.

Error number: 3871; Symbol: ER CLONE LOOPBACK; SQLSTATE: HY000

Message: Clone cannot use loop back connection while cloning into current data directory.

Error number: 3872; Symbol: ER CLONE ENCRYPTION; SQLSTATE: HY000

Message: Clone needs SSL connection for encrypted table.

Error number: 3873; Symbol: ER_CLONE_DISK_SPACE; SQLSTATE: HY000 Message: Clone estimated database size is %s. Available space %s is not enough.

Error number: 3874; Symbol: ER CLONE IN PROGRESS; SQLSTATE: HY000

Message: Concurrent clone in progress. Please try after clone is complete.

Error number: 3875; Symbol: ER CLONE DISALLOWED; SQLSTATE: HY000

Message: The clone operation cannot be executed when %s.

Error number: 3876; Symbol: ER CANNOT GRANT ROLES TO ANONYMOUS USER;

SQLSTATE: HY000

Message: Cannot grant roles to an anonymous user.

Error number: 3877; Symbol: ER SECONDARY ENGINE PLUGIN; SQLSTATE: HY000

Message: %s

2.5 错误码及错误信息汇总 05

Error number: 3878; Symbol: ER SECOND PASSWORD CANNOT BE EMPTY; SQLSTATE:

HY000

Message: Empty password can not be retained as second password for user '%s'@'%s'.

Error number: 3879; Symbol: ER DB ACCESS DENIED; SQLSTATE: HY000

Message: Access denied for AuthId `%s`@`%s` to database '%s'.

Error number: 3880; Symbol:

ER DA AUTH ID WITH SYSTEM USER PRIV IN MANDATORY ROLES; SQLSTATE:

HY000

Message: Cannot set mandatory roles: AuthId '%s'@'%s' has '%s' privilege.

Error number: 3881; Symbol: ER DA RPL GTID TABLE CANNOT OPEN; SQLSTATE:

HY000

Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.

Error number: 3882; Symbol: ER_GEOMETRY_IN_UNKNOWN_LENGTH_UNIT; SQLSTATE:

SU001

Message: The geometry passed to function %s is in SRID 0, which doesn't specify a length unit.

Can't convert to '%s'.

Error number: 3883; Symbol: ER DA PLUGIN INSTALL ERROR; SQLSTATE: HY000

Message: Error installing plugin '%s': %s

Error number: 3884; Symbol: ER NO SESSION TEMP; SQLSTATE: HY000

Message: Storage engine could not allocate temporary tablespace for this session.

Error number: 3885; Symbol: ER DA UNKNOWN ERROR NUMBER; SQLSTATE: HY000

Message: Got unknown error: %d

Error number: 3886; Symbol: ER COLUMN CHANGE SIZE; SQLSTATE: HY000

Message: Could not change column '%s' of table '%s'. The resulting size of index '%s' would exceed

the max key length of %d bytes.

Error number: 3887; Symbol: ER REGEXP INVALID CAPTURE GROUP NAME;

SQLSTATE: HY000

Message: A capture group has an invalid name.

Error number: 3888; Symbol: ER DA SSL LIBRARY ERROR; SQLSTATE: HY000

Message: Failed to set up SSL because of the following SSL library error: %s

Error number: 3889; Symbol: ER SECONDARY ENGINE; SQLSTATE: HY000

Message: Secondary engine operation failed. %s.

Error number: 3890; Symbol: ER SECONDARY ENGINE DDL; SQLSTATE: HY000

Message: DDLs on a table with a secondary engine defined are not allowed.

Error number: 3891; Symbol: ER_INCORRECT_CURRENT_PASSWORD; SQLSTATE: HY000

Message: Incorrect current password. Specify the correct password which has to be replaced.

Error number: 3892; Symbol: ER_MISSING_CURRENT_PASSWORD; SQLSTATE: HY000

Message: Current password needs to be specified in the REPLACE clause in order to change it.

Error number: 3893; Symbol: ER CURRENT PASSWORD NOT REQUIRED; SQLSTATE:

HY000

Message: Do not specify the current password while changing it for other users.

Error number: 3894; Symbol:

ER PASSWORD CANNOT BE RETAINED ON PLUGIN CHANGE; SQLSTATE: HY000

Message: Current password can not be retained for user '%s'@'%s' because authentication plugin is

being changed.

Error number: 3895; Symbol: ER CURRENT PASSWORD CANNOT BE RETAINED;

SQLSTATE: HY000

Message: Current password can not be retained for user '%s'@'%s' because new password is empty.

Error number: 3896; Symbol: ER PARTIAL REVOKES EXIST; SQLSTATE: HY000

Message: At least one partial revoke exists on a database. The system variable '@@partial revokes'

must be set to ON.

Error number: 3897; Symbol:

ER CANNOT GRANT SYSTEM PRIV TO MANDATORY ROLE; SQLSTATE: HY000

Message: AuthId `%s`@`%s` is set as mandatory_roles. Cannot grant the '%s' privilege.

Error number: 3898; Symbol: ER XA REPLICATION FILTERS; SQLSTATE: HY000

Message: The use of replication filters with XA transactions is not supported, and can lead to an

undefined state in the replication slave.

Error number: 3899; Symbol: ER UNSUPPORTED SQL MODE; SQLSTATE: HY000

Message: sql mode=0x%08x is not supported.

Error number: 3900; Symbol: ER REGEXP INVALID FLAG; SQLSTATE: HY000

Message: Invalid match mode flag in regular expression.

Error number: 3901; Symbol: ER PARTIAL REVOKE AND DB GRANT BOTH EXISTS;

SQLSTATE: HY000

Message: '%s' privilege for database '%s' exists both as partial revoke and mysql.db simultaneously.

It could mean that the 'mysql' schema is corrupted.

Error number: 3902; Symbol: ER UNIT NOT FOUND; SQLSTATE: SU001

Message: There's no unit of measure named '%s'.

Error number: 3903; Symbol: ER INVALID JSON VALUE FOR FUNC INDEX; SQLSTATE:

22018

Message: Invalid JSON value for CAST for functional index '%s'.

Error number: 3904; Symbol: ER_JSON_VALUE_OUT_OF_RANGE_FOR_FUNC_INDEX;

SQLSTATE: 22003

Message: Out of range JSON value for CAST for functional index '%s'.

Error number: 3905; Symbol: ER EXCEEDED MV KEYS NUM; SQLSTATE: HY000

Message: Exceeded max number of values per record for multi-valued index '%s' by %u value(s).

Error number: 3906; Symbol: ER EXCEEDED MV KEYS SPACE; SQLSTATE: HY000

Message: Exceeded max total length of values per record for multi-valued index '%s' by %u bytes.

Error number: 3907; Symbol: ER FUNCTIONAL INDEX DATA IS TOO LONG; SQLSTATE:

22001

Message: Data too long for functional index '%s'.

Error number: 3908; Symbol: ER WRONG MVI VALUE; SQLSTATE: HY000

Message: Cannot store an array or an object in a scalar key part of the index '%s'.

Error number: 3909; Symbol: ER WARN FUNC INDEX NOT APPLICABLE; SQLSTATE:

HY000

Message: Cannot use functional index '%s' due to type or collation conversion.

Error number: 3910; Symbol: ER GRP RPL UDF ERROR; SQLSTATE: HY000

Message: The function '%s' failed. %s

Error number: 3911; Symbol: ER UPDATE GTID PURGED WITH GR; SQLSTATE: HY000

Message: Cannot update GTID PURGED with the Group Replication plugin running

Error number: 3912; Symbol: ER_GROUPING_ON_TIMESTAMP_IN_DST; SQLSTATE: HY000 Message: Grouping on temporal is non-deterministic for timezones having DST. Please consider switching to UTC for this query.

Error number: 3913; Symbol: ER_TABLE_NAME_CAUSES_TOO_LONG_PATH; SQLSTATE: HY000

Message: Long database name and identifier for object resulted in a path length too long for table '%s'. Please check the path limit for your OS.

Error number: 3914; Symbol: ER_AUDIT_LOG_INSUFFICIENT_PRIVILEGE; SQLSTATE: HY000

Message: Request ignored for '%s'@'%s'. Role needed to perform operation: '%s'

Error number: 3916; Symbol: ER_DA_GRP_RPL_STARTED_AUTO_REJOIN; SQLSTATE: HY000

Message: Started auto-rejoin procedure attempt %lu of %lu

Error number: 3917; Symbol: ER_SYSVAR_CHANGE_DURING_QUERY; SQLSTATE: HY000 Message: A plugin was loaded or unloaded during a query, a system variable table was changed.

Error number: 3918; Symbol: ER_GLOBSTAT_CHANGE_DURING_QUERY; SQLSTATE: HY000

Message: A plugin was loaded or unloaded during a query, a global status variable was changed.

 $Error\ number:\ 3919;\ Symbol:\ ER_GRP_RPL_MESSAGE_SERVICE_INIT_FAILURE;$

SOLSTATE: HY000

Message: The START GROUP REPLICATION command failed to start its message service.

Error number: 3920; Symbol:

 $ER_CHANGE_MASTER_WRONG_COMPRESSION_ALGORITHM_CLIENT; SQLSTATE:$

HY000

Message: Invalid MASTER COMPRESSION ALGORITHMS '%s' for channel '%s'.

Error number: 3921; Symbol:

ER_CHANGE_MASTER_WRONG_COMPRESSION_LEVEL_CLIENT; SQLSTATE: HY000 Message: Invalid MASTER_ZSTD_COMPRESSION_LEVEL_%u for channel '%s'.

Error number: 3922; Symbol: ER WRONG COMPRESSION ALGORITHM CLIENT;

SOLSTATE: HY000

Message: Invalid compression algorithm '%s'.

Error number: 3923; Symbol: ER WRONG COMPRESSION LEVEL CLIENT; SQLSTATE:

HY000

Message: Invalid zstd compression level for algorithm '%s'.

Error number: 3924; Symbol:

ER CHANGE MASTER WRONG COMPRESSION ALGORITHM LIST CLIENT;

SQLSTATE: HY000

Message: Specified compression algorithm list '%s' exceeds total count of 3 for channel '%s'.

Error number: 3925; Symbol:

ER CLIENT PRIVILEGE CHECKS USER CANNOT BE ANONYMOUS; SQLSTATE:

HY000

Message: PRIVILEGE CHECKS USER for replication channel '%s' was set to ``@`%s`, but

anonymous users are disallowed for PRIVILEGE CHECKS USER.

Error number: 3926; Symbol: ER CLIENT PRIVILEGE CHECKS USER DOES NOT EXIST;

SQLSTATE: HY000

Message: PRIVILEGE CHECKS USER for replication channel '%s' was set to `%s`@`%s`, but this

is not an existing user.

Error number: 3927; Symbol: ER CLIENT PRIVILEGE CHECKS USER CORRUPT;

SOLSTATE: HY000

Message: Invalid, corrupted PRIVILEGE CHECKS USER was found in the replication

configuration repository for channel '%s'. Use CHANGE MASTER TO

PRIVILEGE CHECKS USER to correct the configuration.

Error number: 3928; Symbol:

ER CLIENT PRIVILEGE CHECKS USER NEEDS RPL APPLIER PRIV; SQLSTATE:

HY000

Message: PRIVILEGE CHECKS USER for replication channel '%s' was set to `%s`@`%s`, but this

user does not have REPLICATION APPLIER privilege.

Error number: 3929; Symbol: ER WARN DA PRIVILEGE NOT REGISTERED; SQLSTATE:

HY000

Message: Dynamic privilege '%s' is not registered with the server.

Error number: 3930; Symbol: ER CLIENT KEYRING UDF KEY INVALID; SQLSTATE:

HY000

Message: Function '%s' failed because key is invalid.

Error number: 3931; Symbol: ER CLIENT KEYRING UDF KEY TYPE INVALID;

SOLSTATE: HY000

Message: Function '%s' failed because key type is invalid.

Error number: 3932; Symbol: ER CLIENT KEYRING UDF KEY TOO LONG; SQLSTATE:

HY000

Message: Function '%s' failed because key length is too long.

Error number: 3933; Symbol: ER CLIENT KEYRING UDF KEY TYPE TOO LONG;

SQLSTATE: HY000

Message: Function '%s' failed because key type is too long.

Error number: 3934; Symbol:

ER JSON SCHEMA VALIDATION ERROR WITH DETAILED REPORT; SQLSTATE:

HY000

Message: %s.

Error number: 3935; Symbol: ER_DA_UDF_INVALID_CHARSET_SPECIFIED; SQLSTATE:

HY000

Message: Invalid character set '%s' was specified. It must be either character set name or collation

name as supported by server.

Error number: 3936; Symbol: ER_DA_UDF_INVALID_CHARSET; SQLSTATE: HY000 Message: Invalid character set '%s' was specified. It must be a character set name as supported by

server.

Error number: 3937; Symbol: ER_DA_UDF_INVALID_COLLATION; SQLSTATE: HY000 Message: Invalid collation '%s' was specified. It must be a collation name as supported by server.

Error number: 3938; Symbol: ER DA UDF INVALID EXTENSION ARGUMENT TYPE;

SQLSTATE: HY000

Message: Invalid extension argument type '%s' was specified. Refer the MySQL manual for the valid

UDF extension arguments type.

Error number: 3939; Symbol: ER MULTIPLE CONSTRAINTS WITH SAME NAME;

SQLSTATE: HY000

Message: Table has multiple constraints with the name '%s'. Please use constraint specific '%s'

clause.

Error number: 3940; Symbol: ER CONSTRAINT NOT FOUND; SQLSTATE: HY000

Message: Constraint '%s' does not exist.

Error number: 3941; Symbol:

ER_ALTER_CONSTRAINT_ENFORCEMENT_NOT_SUPPORTED; SQLSTATE: HY000 Message: Altering constraint enforcement is not supported for the constraint '%s'. Enforcement state alter is not supported for the PRIMARY, UNIQUE and FOREIGN KEY type constraints.

Error number: 3942; Symbol:

ER_TABLE_VALUE_CONSTRUCTOR_MUST_HAVE_COLUMNS; SQLSTATE: HY000 Message: Each row of a VALUES clause must have at least one column, unless when used as source in an INSERT statement.

Error number: 3943; Symbol:

ER_TABLE_VALUE_CONSTRUCTOR_CANNOT_HAVE_DEFAULT; SQLSTATE: HY000 Message: A VALUES clause cannot use DEFAULT values, unless used as a source in an INSERT statement.

Error number: 3944; Symbol:

ER_CLIENT_QUERY_FAILURE_INVALID_NON_ROW_FORMAT; SQLSTATE: HY000 Message: The query does not comply with variable require_row_format restrictions.

Error number: 3945; Symbol: ER_REQUIRE_ROW_FORMAT_INVALID_VALUE; SQLSTATE: HY000

Message: The requested value %s is invalid for REQUIRE_ROW_FORMAT, must be either 0 or 1.

Error number: 3946; Symbol: ER_FAILED_TO_DETERMINE_IF_ROLE_IS_MANDATORY; SQLSTATE: HY000

Message: Failed to acquire lock on user management service, unable to determine if role `%s`@`%s` is mandatory

Error number: 3947; Symbol: ER_FAILED_TO_FETCH_MANDATORY_ROLE_LIST;

SQLSTATE: HY000

Message: Failed to acquire lock on user management service, unable to fetch mandatory role list

Error number: 3948; Symbol: ER_CLIENT_LOCAL_FILES_DISABLED; SQLSTATE: 42000 Message: Loading local data is disabled; this must be enabled on both the client and server sides

Error number: 3949; Symbol: ER_IMP_INCOMPATIBLE_CFG_VERSION; SQLSTATE: HY000 Message: Failed to import %s because the CFG file version (%u) is not compatible with the current version (%u)

Error number: 3950; Symbol: ER DA OOM; SQLSTATE: HY000

Message: Out of memory

Error number: 3951; Symbol: ER DA UDF INVALID ARGUMENT TO SET CHARSET;

SOLSTATE: HY000

Message: Character set can be set only for the UDF argument type STRING.

Error number: 3952; Symbol: ER DA UDF INVALID RETURN TYPE TO SET CHARSET;

SQLSTATE: HY000

Message: Character set can be set only for the UDF RETURN type STRING.

Error number: 3953; Symbol: ER MULTIPLE INTO CLAUSES; SQLSTATE: HY000

Message: Multiple INTO clauses in one query block.

Error number: 3954; Symbol: ER MISPLACED INTO; SQLSTATE: HY000

Message: Misplaced INTO clause, INTO is not allowed inside subqueries, and must be placed at end

of UNION clauses.

Error number: 3955; Symbol:

ER_USER_ACCESS_DENIED_FOR_USER_ACCOUNT_BLOCKED_BY_PASSWORD_LOCK;

SQLSTATE: HY000

Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining)

due to %u consecutive failed logins.

Error number: 3956; Symbol: ER WARN DEPRECATED YEAR UNSIGNED; SQLSTATE:

HY000

Message: UNSIGNED for the YEAR data type is deprecated and support for it will be removed in a

future release.

Error number: 3957; Symbol: ER CLONE NETWORK PACKET; SQLSTATE: HY000

Message: Clone needs max_allowed_packet value to be %u or more. Current value is %u

Error number: 3958; Symbol: ER SDI OPERATION FAILED MISSING RECORD;

SQLSTATE: HY000

Message: Failed to %s sdi for %s.%s in %s due to missing record.

Error number: 3959; Symbol: ER DEPENDENT BY CHECK CONSTRAINT; SQLSTATE:

HY000

Message: Check constraint '%s' uses column '%s', hence column cannot be dropped or renamed.

Error number: 3960; Symbol: ER GRP OPERATION NOT ALLOWED GR MUST STOP;

SQLSTATE: HY000

Message: This operation cannot be performed while Group Replication is running; run STOP

GROUP REPLICATION first

Error number: 3961; Symbol:

ER_WARN_DEPRECATED_JSON_TABLE_ON_ERROR_ON_EMPTY; SQLSTATE: HY000 Message: Specifying an ON EMPTY clause after the ON ERROR clause in a JSON_TABLE column definition is deprecated syntax and will be removed in a future release. Specify ON EMPTY before ON ERROR instead.

Error number: 3962; Symbol: ER_WARN_DEPRECATED_INNER_INTO; SQLSTATE: HY000 Message: The INTO clause is deprecated inside query blocks of query expressions and will be removed in a future release. Please move the INTO clause to the end of statement instead.

Error number: 3963; Symbol:

ER_WARN_DEPRECATED_VALUES_FUNCTION_ALWAYS_NULL; SQLSTATE: HY000 Message: The VALUES function is deprecated and will be removed in a future release. It always returns NULL in this context. If you meant to access a value from the VALUES clause of the INSERT statement, consider using an alias (INSERT INTO ... VALUES (...) AS alias) and reference alias.col instead of VALUES(col) in the ON DUPLICATE KEY UPDATE clause.

Error number: 3964; Symbol: ER_WARN_DEPRECATED_SQL_CALC_FOUND_ROWS;

SQLSTATE: HY000

Message: SQL CALC FOUND ROWS is deprecated and will be removed in a future release.

Consider using two separate queries instead.

Error number: 3965; Symbol: ER_WARN_DEPRECATED_FOUND_ROWS; SQLSTATE: HY000 Message: FOUND_ROWS() is deprecated and will be removed in a future release. Consider using COUNT(*) instead.

Error number: 3966; Symbol: ER MISSING JSON VALUE; SQLSTATE: 22035

Message: No value was found by '%s' on the specified path.

Error number: 3967; Symbol: ER MULTIPLE JSON VALUES; SQLSTATE: 22034

Message: More than one value was found by '%s' on the specified path.

Error number: 3968; Symbol: ER HOSTNAME TOO LONG; SQLSTATE: HY000

Message: Hostname cannot be longer than %d characters.

Error number: 3969; Symbol: ER_WARN_CLIENT_DEPRECATED_PARTITION_PREFIX_KEY; SQLSTATE: HY000

Message: Column '%s.%s.%s' having prefix key part '%s(%u)' is ignored by the partitioning function. Use of prefixed columns in the PARTITION BY KEY() clause is deprecated and will be removed in a future release.

Error number: 3970; Symbol: ER_GROUP_REPLICATION_USER_EMPTY_MSG; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed since the username provided for recovery channel is empty.

Error number: 3971; Symbol: ER_GROUP_REPLICATION_USER_MANDATORY_MSG; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed since the USER option was not provided with PASSWORD for recovery channel.

Error number: 3972; Symbol: ER_GROUP_REPLICATION_PASSWORD_LENGTH; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed since the password provided for the recovery channel exceeds the maximum length of 32 characters.

Error number: 3973; Symbol: ER_SUBQUERY_TRANSFORM_REJECTED; SQLSTATE: HY000 Message: Statement requires a transform of a subquery to a non-SET operation (like IN2EXISTS, or subquery-to-LATERAL-derived-table). This is not allowed with optimizer switch 'subquery to derived' on

Error number: 3974; Symbol: ER_DA_GRP_RPL_RECOVERY_ENDPOINT_FORMAT; SQLSTATE: HY000

Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma separated, list of endpoints (IP:port)

Error number: 3975; Symbol: ER_DA_GRP_RPL_RECOVERY_ENDPOINT_INVALID; SQLSTATE: HY000

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on are valid recovery endpoints.

Error number: 3976; Symbol: ER_WRONG_VALUE_FOR_VAR_PLUS_ACTIONABLE_PART; SQLSTATE: HY000

Message: Variable '%s' cannot be set to the value of '%s'. %s

Error number: 3977; Symbol:

ER_STATEMENT_NOT_ALLOWED_AFTER_START_TRANSACTION; SQLSTATE: HY000 Message: Only BINLOG INSERT, COMMIT and ROLLBACK statements are allowed after CREATE TABLE with START TRANSACTION statement.

Error number: 3978; Symbol: ER_FOREIGN_KEY_WITH_ATOMIC_CREATE_SELECT; SQLSTATE: HY000

Message: Foreign key creation is not allowed with CREATE TABLE as SELECT and CREATE TABLE with START TRANSACTION statement.

Error number: 3979; Symbol: ER NOT ALLOWED WITH START TRANSACTION;

SQLSTATE: HY000

Message: START TRANSACTION clause cannot be used %s

Error number: 3980; Symbol: ER INVALID JSON ATTRIBUTE; SQLSTATE: HY000

Message: Invalid json attribute, error: "%s" at pos %u: '%s'

Error number: 3981; Symbol: ER ENGINE ATTRIBUTE NOT SUPPORTED; SQLSTATE:

HY000

Message: Storage engine '%s' does not support ENGINE ATTRIBUTE.

Error number: 3982; Symbol: ER INVALID USER ATTRIBUTE JSON; SQLSTATE: HY000

Message: The user attribute must be a valid JSON object

Error number: 3983; Symbol: ER_INNODB_REDO_DISABLED; SQLSTATE: HY000

Message: Cannot perform operation as InnoDB redo logging is disabled. Please retry after enabling

redo log with ALTER INSTANCE

Error number: 3984; Symbol: ER_INNODB_REDO_ARCHIVING_ENABLED; SQLSTATE:

HY000

Message: Cannot perform operation as InnoDB is archiving redo log. Please retry after stopping redo

archive by invoking innodb redo log archive stop()

Error number: 3985; Symbol: ER MDL OUT OF RESOURCES; SQLSTATE: HY000

Message: Not enough resources to complete lock request.

Error number: 3986; Symbol: ER IMPLICIT COMPARISON FOR JSON; SQLSTATE: HY000

Message: Evaluating a JSON value in SQL boolean context does an implicit comparison against

JSON integer 0; if this is not what you want, consider converting JSON to a SQL numeric type with

JSON VALUE RETURNING

Error number: 3987; Symbol: ER FUNCTION DOES NOT SUPPORT CHARACTER SET;

SQLSTATE: HY000

Message: The function %s does not support the character set '%s'.

Error number: 3988; Symbol: ER IMPOSSIBLE STRING CONVERSION; SQLSTATE: HY000

Message: Conversion from collation %s into %s impossible for %s

Error number: 3989; Symbol: ER SCHEMA READ ONLY; SQLSTATE: HY000

Message: Schema '%s' is in read only mode.

Error number: 3990; Symbol: ER_RPL_ASYNC_RECONNECT_GTID_MODE_OFF; SQLSTATE: HY000

Message: Failed to enable Asynchronous Replication Connection Failover feature. The CHANGE MASTER TO SOURCE_CONNECTION_AUTO_FAILOVER = 1 can only be set when @@GLOBAL.GTID MODE = ON.

Error number: 3991; Symbol: ER_RPL_ASYNC_RECONNECT_AUTO_POSITION_OFF;

SQLSTATE: HY000

Message: Failed to enable Asynchronous Replication Connection Failover feature. The CHANGE

MASTER TO SOURCE_CONNECTION_AUTO_FAILOVER = 1 can only be set when

MASTER AUTO POSITION option of CHANGE MASTER TO is enabled.

Error number: 3992; Symbol:

ER_DISABLE_GTID_MODE_REQUIRES_ASYNC_RECONNECT_OFF; SQLSTATE: HY000 Message: The @@GLOBAL.GTID_MODE = %s cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE MASTER TO

SOURCE CONNECTION AUTO FAILOVER = 1.

Error number: 3993; Symbol:

 $\label{lem:connect_off} ER_DISABLE_AUTO_POSITION_REQUIRES_ASYNC_RECONNECT_OFF; SQLSTATE: \\ HY0000$

Message: CHANGE MASTER TO MASTER_AUTO_POSITION = 0 cannot be executed because Asynchronous Replication Connection Failover is enabled i.e. CHANGE MASTER TO SOURCE_CONNECTION_AUTO_FAILOVER = 1.

Error number: 3994; Symbol: ER_INVALID_PARAMETER_USE; SQLSTATE: HY000 Message: Invalid use of parameters in '%s'

Error number: 3995; Symbol: ER_CHARACTER_SET_MISMATCH; SQLSTATE: HY000 Message: Character set '%s' cannot be used in conjunction with '%s' in call to %s.

Error number: 3996; Symbol: ER_WARN_VAR_VALUE_CHANGE_NOT_SUPPORTED; SQLSTATE: HY000

Message: Changing %s not supported on this platform. Falling back to the default.

Error number: 3997; Symbol: ER_INVALID_TIME_ZONE_INTERVAL; SQLSTATE: HY000 Message: Invalid time zone interval: '%s'

Error number: 3998; Symbol: ER_INVALID_CAST; SQLSTATE: HY000

Message: Cannot cast value to %s.

Error number: 3999; Symbol: ER_HYPERGRAPH_NOT_SUPPORTED_YET; SQLSTATE: 42000 Message: The hypergraph optimizer does not yet support '%s'

Error number: 4000; Symbol: ER_WARN_HYPERGRAPH_EXPERIMENTAL; SQLSTATE: HY000

Message: The hypergraph optimizer is highly experimental and is meant for testing only. Do not enable it unless you are a MySQL developer.

Error number: 4001; Symbol: ER_DA_NO_ERROR_LOG_PARSER_CONFIGURED; SQLSTATE: HY000

Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance schema.error log.

Error number: 4002; Symbol: ER_DA_ERROR_LOG_TABLE_DISABLED; SQLSTATE: HY000 Message: None of the log-sinks selected in @@global.log_error_services supports writing to the performance schema. The server will not be able to make the current runs' error events available in performance_schema.error_log. To change this, add a log-sink that supports the performance schema to @@global.log_error_services.

Error number: 4003; Symbol: ER_DA_ERROR_LOG_MULTIPLE_FILTERS; SQLSTATE: HY000 Message: @@global.log_error_services lists more than one log-filter service. This is discouraged as it will make it hard to understand which rule in which filter affected a log-event.

Error number: 4004; Symbol: ER_DA_CANT_OPEN_ERROR_LOG; SQLSTATE: HY000 Message: Could not open file '%s' for error logging%s%s

Error number: 4005; Symbol: ER_USER_REFERENCED_AS_DEFINER; SQLSTATE: HY000 Message: User %s is referenced as a definer account in %s.

Error number: 4006; Symbol: ER_CANNOT_USER_REFERENCED_AS_DEFINER; SQLSTATE: HY000

Message: Operation %s failed for %s as it is referenced as a definer account in %s.

Error number: 4007; Symbol: ER_REGEX_NUMBER_TOO_BIG; SQLSTATE: HY000 Message: Decimal number in regular expression is too large.

Error number: 4008; Symbol: ER_SPVAR_NONINTEGER_TYPE; SQLSTATE: HY000 Message: The variable "%s" has a non-integer based type

Error number: 4009; Symbol: WARN_UNSUPPORTED_ACL_TABLES_READ; SQLSTATE: HY000

Message: Reads with serializable isolation/SELECT FOR SHARE are not supported for ACL tables.

Error number: 4010; Symbol: ER_BINLOG_UNSAFE_ACL_TABLE_READ_IN_DML_DDL; SQLSTATE: HY000

Message: The statement is unsafe because it updates a table depending on ACL table read operation. As storage engine row locks are skipped for ACL table, it may not have same effect on master and slave.

Error number: 4011; Symbol: ER_STOP_REPLICA_MONITOR_IO_THREAD_TIMEOUT; SQLSTATE: HY000

Message: STOP REPLICA command execution is incomplete: Replica Monitor thread got the stop signal, thread is busy, Monitor thread will stop once the current task is complete.

Error number: 4012; Symbol: ER_STARTING_REPLICA_MONITOR_IO_THREAD; SQLSTATE: HY000

Message: The Replica Monitor thread failed to start.

Error number: 4013; Symbol:

ER_CANT_USE_ANONYMOUS_TO_GTID_WITH_GTID_MODE_NOT_ON; SQLSTATE: HY000

Message: Replication cannot start%s with

ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID> as this server uses @@GLOBAL.GTID_MODE <> ON.

Error number: 4014; Symbol:

 $\label{lem:combine_anonymous_to_gtid_and_autoposition; sqlstate: $HY000$$

Message: The options ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID> and MASTER_AUTO_POSITION = 1 cannot be used together.

Error number: 4015; Symbol:

ER_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_REQUIRES_GTID_MODE_ON; SQLSTATE: HY000

Message: CHANGE MASTER TO ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID> cannot be executed because @@GLOBAL.GTID MODE <> ON.

Error number: 4016; Symbol:

ER_SQL_SLAVE_SKIP_COUNTER_USED_WITH_GTID_MODE_ON; SQLSTATE: HY000 Message: The value of sql_slave_skip_counter will only take effect for channels running with ASSIGN GTIDS TO ANONYMOUS TRANSACTIONS <> OFF.

Error number: 4016; Symbol:

ER_SQL_REPLICA_SKIP_COUNTER_USED_WITH_GTID_MODE_ON; SQLSTATE: HY000 Message: The value of sql_replica_skip_counter will only take effect for channels running with ASSIGN GTIDS TO ANONYMOUS TRANSACTIONS <> OFF.

Error number: 4017; Symbol:

ER_USING_ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS_AS_LOCAL_OR_UUID; SQLSTATE: HY000

Message: Using ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS creates limitations on the replication topology - you cannot fail over between downstream and upstream servers. Only use this option if it is not possible to enable GTIDs on the source, for instance, because of lack of permissions. If possible, use the procedure for enabling GTID transactions online instead, as described in the documentation.

Error number: 4018; Symbol:

ER_CANT_SET_ANONYMOUS_TO_GTID_AND_WAIT_UNTIL_SQL_THD_AFTER_GTIDS; SQLSTATE: HY000

Message: WAIT_UNTIL_SQL_THREAD_AFTER_GTIDS cannot be used on a channel configured with ASSIGN GTIDS TO ANONYMOUS TRANSACTIONS = LOCAL|<UUID>

Error number: 4019; Symbol:

ER_CANT_SET_SQL_AFTER_OR_BEFORE_GTIDS_WITH_ANONYMOUS_TO_GTID; SQLSTATE: HY000

Message: The SQL_AFTER_GTIDS or SQL_BEFORE_GTIDS clauses for START REPLICA cannot be used when the replication channel is configured with

ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>.

Error number: 4020; Symbol:

ER_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME; SQLSTATE: HY000

Message: Replication '%s' is configured with

ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID> where the UUID value is equal to the group_replication_group_name

Error number: 4021; Symbol: ER_CANT_USE_SAME_UUID_AS_GROUP_NAME; SQLSTATE: HY000

Message: CHANGE MASTER TO ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = <UUID> cannot be executed because the UUID value is equal to the group replication group name.

Error number: 4022; Symbol: ER_GRP_RPL_RECOVERY_CHANNEL_STILL_RUNNING; SQLSTATE: HY000

Message: The group_replication_recovery channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.

Error number: 4023; Symbol: ER INNODB INVALID AUTOEXTEND SIZE VALUE;

SQLSTATE: HY000

Message: AUTOEXTEND SIZE should be a multiple of %uM

Error number: 4024; Symbol: ER INNODB INCOMPATIBLE WITH TABLESPACE;

SQLSTATE: HY000

Message: InnoDB: "%s" not allowed with general tablespaces

Error number: 4025; Symbol: ER INNODB AUTOEXTEND SIZE OUT OF RANGE;

SQLSTATE: HY000

Message: AUTOEXTEND SIZE value should be between %uM and %uM

Error number: 4026; Symbol: ER CANNOT USE AUTOEXTEND SIZE CLAUSE; SQLSTATE:

HY000

Message: AUTOEXTEND SIZE clause is not valid for %s tablespace.

Error number: 4027; Symbol: ER ROLE GRANTED TO ITSELF; SQLSTATE: HY000

Message: User account %s is directly or indirectly granted to the role %s. The GRANT would create

a loop

 $Error\ number:\ 4028;\ Symbol:\ ER_TABLE_MUST_HAVE_A_VISIBLE_COLUMN;\ SQLSTATE:$

HY000

Message: A table must have at least one visible column.

Error number: 4029; Symbol: ER INNODB COMPRESSION FAILURE; SQLSTATE: HY000

Message: Compression failed with the following error: %s

Error number: 4030; Symbol:

ER_WARN_ASYNC_CONN_FAILOVER_NETWORK_NAMESPACE; SQLSTATE: HY000

Message: The parameter network namespace is reserved for future use. Please use the CHANGE

REPLICATION SOURCE command to set channel network namespace parameter.

Error number: 4031; Symbol: ER CLIENT INTERACTION TIMEOUT; SQLSTATE: HY000

Message: The client was disconnected by the server because of inactivity. See wait_timeout and

interactive timeout for configuring this behavior.

Error number: 4032; Symbol: ER INVALID CAST TO GEOMETRY; SQLSTATE: 22S01

Message: Invalid cast from %s to %s.

Error number: 4033; Symbol: ER_INVALID_CAST_POLYGON_RING_DIRECTION;

SQLSTATE: 22S04

Message: Invalid cast from %s to %s. A polygon ring is in the wrong direction.

Error number: 4034; Symbol: ER_GIS_DIFFERENT_SRIDS_AGGREGATION; SQLSTATE:

22S05

Message: Arguments to function %s contains geometries with different SRIDs: %u and %u. All

geometries must have the same SRID.

Error number: 4035; Symbol: ER_RELOAD_KEYRING_FAILURE; SQLSTATE: HY000

Message: Keyring reload failed. Please check error log for more details.

Error number: 4036; Symbol: ER SDI GET KEYS INVALID TABLESPACE; SQLSTATE:

HY000

Message: Tablespace '%s' is invalid for SDI operations.

Error number: 4037; Symbol:

ER_CHANGE_RPL_SRC_WRONG_COMPRESSION_ALGORITHM_SIZE; SQLSTATE: HY000

Message: Value too long setting SOURCE_COMPRESSION_ALGORITHMS option to a %d chars

long string for channel '%s'.

Error number: 4038; Symbol:

ER WARN DEPRECATED TLS VERSION FOR CHANNEL CLI; SQLSTATE: HY000

Message: A deprecated TLS version %s is enabled for channel %s. Please use TLSv1.2 or higher.

Error number: 4039; Symbol: ER CANT USE SAME UUID AS VIEW CHANGE UUID;

SQLSTATE: HY000

Message: CHANGE REPLICATION SOURCE TO

ASSIGN GTIDS TO ANONYMOUS TRANSACTIONS = <UUID> cannot be executed because

the UUID value is equal to the group replication view change uuid.

Error number: 4040; Symbol:

ER ANONYMOUS TO GTID UUID SAME AS VIEW CHANGE UUID; SQLSTATE:

HY000

Message: Replication '%s' is configured with

ASSIGN GTIDS TO ANONYMOUS TRANSACTIONS = <UUID> where the UUID value is

equal to the group replication view change uuid

Error number: 4041; Symbol: ER GRP RPL VIEW CHANGE UUID FAIL GET VARIABLE;

SQLSTATE: HY000

Message: Unable to retrieve group_replication_view_change_uuid variable during server checks on replication operations.

Error number: 4042; Symbol: ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS; SOLSTATE: HY000

Message: Both audit_log_max_size and audit_log_prune_seconds are set to non-zero. audit_log_max_size takes precedence and audit_log_prune_seconds is ignored

Error number: 4043; Symbol:

ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE; SQLSTATE: HY000 Message: audit_log_rotate_on_size is not granular enough for the value of audit_log_max_size supplied. Should be at least %d times smaller.

Error number: 4044; Symbol: ER_KERBEROS_CREATE_USER; SQLSTATE: HY000 Message: Create/Alter user has failed, Configured user realm as authentication string is empty, Please make sure to configure authentication string as user realm.

Error number: 4045; Symbol: ER_INSTALL_PLUGIN_CONFLICT_CLIENT; SQLSTATE: HY000

Message: Cannot install the %s plugin when the %s plugin is installed.

Error number: 4046; Symbol: ER_DA_ERROR_LOG_COMPONENT_FLUSH_FAILED; SQLSTATE: HY000

Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush filed-based logs may affect log-rotation.

Error number: 4047; Symbol:

ER_WARN_SQL_AFTER_MTS_GAPS_GAP_NOT_CALCULATED; SQLSTATE: HY000 Message: The until clause SQL_AFTER_MTS_GAPS is being used for channel '%s' when GTID_MODE = ON and SOURCE_AUTO_POSITION=1 meaning the server did not compute internally what gaps may exist in the relay log transaction execution. To close any execution gaps use either the SQL_BEFORE_GTIDS or SQL_AFTER_GTIDS until clause.

Error number: 4048; Symbol: ER_INVALID_ASSIGNMENT_TARGET; SQLSTATE: 42000 Message: Invalid target for assignment in INSERT or UPDATE statement '%s'.

Error number: 4049; Symbol: ER_OPERATION_NOT_ALLOWED_ON_GR_SECONDARY; SQLSTATE: HY000

Message: This operation cannot be performed on a Group Replication secondary member, it must be done on the group primary.

Error number: 4050; Symbol:

ER_GRP_RPL_FAILOVER_CHANNEL_STATUS_PROPAGATION; SQLSTATE: HY000 Message: Unable to propagate the SOURCE_CONNECTION_AUTO_FAILOVER value for channel '%s' to group replication members. Please retry the operation.

Error number: 4051; Symbol:

 $\label{log_format_unix_timestamp_only_when_json; sqlstate: $$HY000$$

Message: audit log format unix timestamp is applicable only when audit log format = JSON.

Error number: 4052; Symbol: ER_INVALID_MFA_PLUGIN_SPECIFIED; SQLSTATE: HY000 Message: Invalid plugin "%s" specified as %d factor during "%s".

Error number: 4053; Symbol: ER_IDENTIFIED_BY_UNSUPPORTED; SQLSTATE: HY000 Message: IDENTIFIED BY clause during "%s" not supported for plugin "%s".

Error number: 4054; Symbol: ER_INVALID_PLUGIN_FOR_REGISTRATION; SQLSTATE: HY000

Message: This operation is not supported for plugin "%s".

Error number: 4055; Symbol: ER_PLUGIN_REQUIRES_REGISTRATION; SQLSTATE: HY000 Message: Authentication plugin requires registration. Please refer ALTER USER syntax or set -- fido-register-factor command line option to do registration.

Error number: 4056; Symbol: ER_MFA_METHOD_EXISTS; SQLSTATE: HY000 Message: %d factor authentication method exists. Please do ALTER USER... DROP %d factor before doing this operation OR do ALTER USER... MODIFY %d factor... to modify existing %d factor authentication method.

Error number: 4057; Symbol: ER_MFA_METHOD_NOT_EXISTS; SQLSTATE: HY000 Message: %d factor authentication method doesn't exist. Please do ALTER USER... ADD %d factor... before doing this operation.

Error number: 4058; Symbol: ER_AUTHENTICATION_POLICY_MISMATCH; SQLSTATE: HY000

Message: %d factor authentication method does not match against authentication policy. Please refer @@authentication_policy system variable.

Error number: 4059; Symbol: ER_PLUGIN_REGISTRATION_DONE; SQLSTATE: HY000 Message: The registration for %d factor authentication method is already completed. You cannot perform registration multiple times.

Error number: 4060; Symbol: ER_INVALID_USER_FOR_REGISTRATION; SQLSTATE: HY000 Message: The registration operation is not allowed for user '%s'@'%s'. The operation can only be performed in user's own session.

Error number: 4061; Symbol: ER_USER_REGISTRATION_FAILED; SQLSTATE: HY000 Message: Authentication plugin's registration failed.

Error number: 4062; Symbol: ER_MFA_METHODS_INVALID_ORDER; SQLSTATE: HY000 Message: %d factor authentication method should be added before %d factor authentication method.

Error number: 4063; Symbol: ER_MFA_METHODS_IDENTICAL; SQLSTATE: HY000 Message: Authentication factor should be different.

Error number: 4064; Symbol:

ER_INVALID_MFA_OPERATIONS_FOR_PASSWORDLESS_USER; SQLSTATE: HY000 Message: The operation "%s" cannot be performed for user '%s'@'%s' configured to connect without a password.

Error number: 4065; Symbol:

ER_CHANGE_REPLICATION_SOURCE_NO_OPTIONS_FOR_GTID_ONLY; SQLSTATE: HY000

Message: GTID_ONLY cannot be enabled for replication channel '%s'. You need GTID_MODE = ON, SOURCE_AUTO_POSITION = 1 and REQUIRE_ROW_FORMAT = 1.

Error number: 4066; Symbol:

ER_CHANGE_REP_SOURCE_CANT_DISABLE_REQ_ROW_FORMAT_WITH_GTID_ONLY; SQLSTATE: HY000

Message: REQUIRE_ROW_FORMAT cannot be disabled for replication channel '%s' when GTID ONLY=1.

Error number: 4067; Symbol:

 $ER_CHANGE_REP_SOURCE_CANT_DISABLE_AUTO_POSITION_WITH_GTID_ONLY;$

SQLSTATE: HY000

Message: SOURCE_AUTO_POSITION cannot be disabled for replication channel '%s' when GTID ONLY=1.

Error number: 4068; Symbol:

 $ER_CHANGE_REP_SOURCE_CANT_DISABLE_GTID_ONLY_WITHOUT_POSITIONS;$

SQLSTATE: HY000

Message: When disabling GTID_ONLY and SOURCE_AUTO_POSITION FOR CHANNEL '%s' you must provide SOURCE_LOG_FILE and SOURCE_LOG_POS as source positions are invalid.

Error number: 4069; Symbol:

ER CHANGE REP SOURCE CANT_DISABLE_AUTO_POS_WITHOUT_POSITIONS;

SOLSTATE: HY000

Message: When disabling SOURCE AUTO POSITION FOR CHANNEL '%s' you must provide

SOURCE LOG FILE and SOURCE LOG POS as source positions are invalid.

Error number: 4070; Symbol:

ER_CHANGE_REP_SOURCE_GR_CHANNEL_WITH_GTID_MODE_NOT_ON; SQLSTATE:

HY000

Message: When configuring a group replication channel you must do it when GTID MODE = ON.

Error number: 4071; Symbol: ER CANT USE GTID ONLY WITH GTID MODE NOT ON;

SQLSTATE: HY000

Message: Replication cannot start%s with GTID ONLY = 1 as this server uses

@@GLOBAL.GTID MODE <> ON.

Error number: 4072; Symbol:

ER WARN C DISABLE GTID ONLY WITH SOURCE AUTO POS INVALID POS;

SQLSTATE: HY000

Message: The replication positions relative to the source may be out-of-date on channel '%s', due to the use of GTID_ONLY=1. The out-of-date positions can still be used in some cases so, in order to update them, we suggest that you start the replication to receive and apply at least one transaction, which will set the positions to valid values.

Error number: 4073; Symbol: ER DA SSL FIPS MODE ERROR; SQLSTATE: HY000

Message: SSL fips mode error: %s

Error number: 4074; Symbol: ER_VALUE_OUT_OF_RANGE; SQLSTATE: HY000

Message: %s=%llu is outside the valid range [%llu,%llu]. %llu will be used.

Error number: 4075; Symbol: ER_FULLTEXT_WITH_ROLLUP; SQLSTATE: HY000

Message: MATCH does not support ROLLUP columns.

Error number: 4076; Symbol: ER REGEXP MISSING RESOURCE; SQLSTATE: HY000

Message: Missing locale resource in regular expression library.

Error number: 4077; Symbol: ER WARN REGEXP USING DEFAULT; SQLSTATE: HY000

Message: Regular expression library used default (root) locale.

Error number: 4078; Symbol: ER REGEXP MISSING FILE; SQLSTATE: HY000

Message: Missing data file in regular expression library.

Error number: 4079; Symbol: ER_WARN_DEPRECATED_COLLATION; SQLSTATE: HY000 Message: '%s' is a collation of the deprecated character set %s. Please consider using %s with an appropriate collation instead.

Error number: 4080; Symbol: ER_CONCURRENT_PROCEDURE_USAGE; SQLSTATE: HY000 Message: The %s was called when there was already another concurrent call to this procedure. No action was taken. Wait for other calls to %s to finish before retrying.

Error number: 4081; Symbol: ER_DA_GLOBAL_CONN_LIMIT; SQLSTATE: HY000 Message: Connection closed. Global connection memory limit %llu bytes exceeded. Consumed %llu bytes.

Error number: 4082; Symbol: ER DA CONN LIMIT; SQLSTATE: HY000

Message: Connection closed. Connection memory limit %llu bytes exceeded. Consumed %llu bytes.

Error number: 4083; Symbol:

ER ALTER OPERATION NOT SUPPORTED REASON COLUMN TYPE INSTANT;

SQLSTATE: HY000

Message: Need to rebuild the table to change column type

Error number: 4084; Symbol: ER_WARN_SF_UDF_NAME_COLLISION; SQLSTATE: HY000 Message: This function '%s' has the same name as a loadable function (UDF). To invoke the stored function, it is necessary to qualify it with the schema name.

Error number: 4085; Symbol: ER_CANNOT_PURGE_BINLOG_WITH_BACKUP_LOCK; SQLSTATE: HY000

Message: Could not purge binary logs since another session is executing LOCK INSTANCE FOR BACKUP. Wait for that session to release the lock.

Error number: 4086; Symbol: ER_TOO_MANY_WINDOWS; SQLSTATE: HY000 Message: Too many windows in SELECT: %d. Maximum allowed is %d. Use named windows to share windows between window functions.

Error number: 4087; Symbol: ER_MYSQLBACKUP_CLIENT_MSG; SQLSTATE: HY000 Message: %s

Error number: 4088; Symbol: ER_COMMENT_CONTAINS_INVALID_STRING; SQLSTATE: HY000

Message: Comment for %s '%s' contains an invalid %s character string: '%s'.

Error number: 4089; Symbol: ER_DEFINITION_CONTAINS_INVALID_STRING; SQLSTATE: HY000

Message: Definition of %s '%s.%s' contains an invalid %s character string: '%s'.

Error number: 4090; Symbol:

ER CANT EXECUTE COMMAND WITH ASSIGNED GTID NEXT; SQLSTATE: HY000

Message: Can't execute the given command when @@SESSION.GTID NEXT ==

'UUID:NUMBER'.

Error number: 4091; Symbol: ER_XA_TEMP_TABLE; SQLSTATE: HY000

Message: XA: Temporary tables cannot be accessed inside XA transactions when

xa detach on prepare=ON

Error number: 4092; Symbol: ER_INNODB_MAX_ROW_VERSION; SQLSTATE: HY000

Message: Maximum row versions reached for table %s. No more columns can be added or dropped instantly. Please use COPY/INPLACE.

Error number: 4093; Symbol: ER INNODB INSTANT ADD NOT SUPPORTED MAX SIZE;

SQLSTATE: HY000

Message: Column can't be added with ALGORITHM=INSTANT as after this max possible row size

crosses max permissible row size. Try ALGORITHM=INPLACE/COPY.

Error number: 4094; Symbol:

ER OPERATION NOT ALLOWED WHILE PRIMARY CHANGE IS RUNNING;

SOLSTATE: HY000

Message: All queries have been blocked while function 'group_replication_set_as_primary()' is

executing. Please refer timeout parameter of function 'group replication set as primary()'.

Error number: 4095; Symbol: ER WARN DEPRECATED DATETIME DELIMITER;

SOLSTATE: HY000

Message: Delimiter '%s' in position %d in datetime value '%s' at row %d is deprecated. Prefer the

standard '%c'.

Error number: 4096; Symbol: ER WARN DEPRECATED SUPERFLUOUS DELIMITER;

SQLSTATE: HY000

Message: Delimiter '%s' in position %d in datetime value '%s' at row %d is superfluous and is

deprecated. Please remove.

Error number: 4097; Symbol: ER CANNOT PERSIST SENSITIVE VARIABLES; SQLSTATE:

HY000

Message: Cannot persist SENSITIVE system variable '%s' because keyring component support is

unavailable.

Error number: 4098; Symbol:

ER_WARN_CANNOT_SECURELY_PERSIST_SENSITIVE_VARIABLES; SQLSTATE: HY000 Message: SENSITIVE system variable '%s' was persisted without encryption. Consider restarting server with keyring component support to persist SENSITIVE variables securely.

Error number: 4099; Symbol: ER_WARN_TRG_ALREADY_EXISTS; SQLSTATE: HY000 Message: Trigger '%s' already exists on the table '%s'.'%s'.

Error number: 4100; Symbol:

 $ER_IF_NOT_EXISTS_UNSUPPORTED_TRG_EXISTS_ON_DIFFERENT_TABLE; SQLSTATE: \\ HY000$

Message: Trigger '%s'.'%s' already exists on a different table. The 'IF NOT EXISTS' clause is only supported for triggers associated with the same table.

Error number: 4101; Symbol:

ER IF NOT EXISTS UNSUPPORTED UDF NATIVE FCT NAME COLLISION;

SQLSTATE: HY000

Message: This function '%s' has the same name as a native function. The 'IF NOT EXISTS' clause is not supported while creating a loadable function with the same name as a native function.

Error number: 4102; Symbol: ER_SET_PASSWORD_AUTH_PLUGIN_ERROR; SQLSTATE: HY000

Message: SET PASSWORD has no significance for user '%s'@'%s' as the authentication method used doesn't store authentication data in the MySQL server. Please consider using ALTER USER instead if you want to change authentication parameters.

Error number: 4103; Symbol: ER_REDUCED_DBLWR_FILE_CORRUPTED; SQLSTATE: HY000

Message: Cannot recover from detect_only doublewrite buffer as page %u from batch doublewrite file is corrupted.

Error number: 4104; Symbol: ER_REDUCED_DBLWR_PAGE_FOUND; SQLSTATE: HY000 Message: Database page corruption of tablespace %s space_id: %u page_num: %u. Cannot recover it from the doublewrite buffer because it was written in detect_only-doublewrite mode.

Error number: 4105; Symbol: ER_SRS_INVALID_LATITUDE_OF_ORIGIN; SQLSTATE: SR002 Message: Latitude of origin must be within [-90, 90] degrees, specified in the SRS angular unit.

Error number: 4106; Symbol: ER_SRS_INVALID_LONGITUDE_OF_ORIGIN; SQLSTATE: SR002

Message: Longitude of origin must be within (-180, 180] degrees, specified in the SRS angular unit.

Error number: 4107; Symbol: ER_SRS_UNUSED_PROJ_PARAMETER_PRESENT; SQLSTATE: SR002

Message: The spatial reference system definition for SRID %u contains unused projection parameter "%s".

Error number: 4108; Symbol: ER_GIPK_COLUMN_EXISTS; SQLSTATE: HY000 Message: Failed to generate invisible primary key. Column 'my row id' already exists.

Error number: 4109; Symbol: ER_GIPK_FAILED_AUTOINC_COLUMN_EXISTS; SQLSTATE: HY000

Message: Failed to generate invisible primary key. Auto-increment column already exists.

Error number: 4110; Symbol: ER_GIPK_COLUMN_ALTER_NOT_ALLOWED; SQLSTATE: HY000

Message: Altering generated invisible primary key column 'my row id' is not allowed.

Error number: 4111; Symbol: ER_DROP_PK_COLUMN_TO_DROP_GIPK; SQLSTATE: HY000 Message: Please drop primary key column to be able to drop generated invisible primary key.

Error number: 4112; Symbol: ER_CREATE_SELECT_WITH_GIPK_DISALLOWED_IN_SBR; SQLSTATE: HY000

Message: Generating an invisible primary key for a table created using CREATE TABLE ... SELECT ... is disallowed when binlog_format=STATEMENT. It cannot be guaranteed that the SELECT retrieves rows in the same order on source and replica. Therefore, it cannot be guaranteed that the value generated for the generated implicit primary key column will be the same on source and replica for all rows. Use binlog_format=ROW or MIXED to execute this statement.

Error number: 4113; Symbol: ER_DA_EXPIRE_LOGS_DAYS_IGNORED; SQLSTATE: HY000 Message: The option expire_logs_days cannot be used together with option binlog expire logs seconds. To set one, first unset the other by setting it to 0.

Error number: MY-010000; Symbol: ER_PARSER_TRACE; SQLSTATE: XX999 Message: Parser saw: %s

Error number: MY-010001; Symbol: ER_BOOTSTRAP_CANT_THREAD; SQLSTATE: HY000 Message: Can't create thread to handle bootstrap (errno: %d)

Error number: MY-010002; Symbol: ER_TRIGGER_INVALID_VALUE; SQLSTATE: HY000 Message: Trigger for table '%s'.'%s': invalid %s value (%s).

Error number: MY-010003; Symbol: ER_OPT_WRONG_TREE; SQLSTATE: HY000 Message: Wrong tree: %s

Error number: MY-010004; Symbol: ER DD FAILSAFE; SQLSTATE: HY000

Message: Error: Invalid %s

Error number: MY-010005; Symbol: ER DD NO WRITES NO REPOPULATION; SQLSTATE:

HY000

Message: Skip re-populating collations and character sets tables in %s%sread-only mode.

Error number: MY-010006; Symbol: ER_DD_VERSION_FOUND; SQLSTATE: HY000 Message: Using data dictionary with version '%d'.

Error number: MY-010007; Symbol: ER_DD_VERSION_INSTALLED; SQLSTATE: HY000 Message: Installed data dictionary with version %d

Error number: MY-010008; Symbol: ER_DD_VERSION_UNSUPPORTED; SQLSTATE: HY000 Message: Data Dictionary version '%d' not supported.

Error number: MY-010009; Symbol: ER_LOG_SYSLOG_FACILITY_FAIL; SQLSTATE: HY000 Message: Failed to set syslog facility to "%s", setting to "%s" (%d) instead.

Error number: MY-010010; Symbol: ER_LOG_SYSLOG_CANNOT_OPEN; SQLSTATE: HY000 Message: Cannot open %s; check privileges, or remove syseventlog from --log-error-services!

Error number: MY-010011; Symbol: ER_LOG_SLOW_CANNOT_OPEN; SQLSTATE: HY000 Message: either restart the query logging by using "SET GLOBAL SLOW_QUERY_LOG=ON" or

Error number: MY-010012; Symbol: ER_LOG_GENERAL_CANNOT_OPEN; SQLSTATE: HY000

Message: either restart the query logging by using "SET GLOBAL GENERAL LOG=ON" or

Error number: MY-010013; Symbol: ER_LOG_CANNOT_WRITE; SQLSTATE: HY000 Message: Failed to write to %s: %s

Error number: MY-010014; Symbol: ER_RPL_ZOMBIE_ENCOUNTERED; SQLSTATE: HY000 Message: While initializing dump thread for slave with %s <%s>, found a zombie dump thread with the same %s. Master is killing the zombie dump thread(%u).

Error number: MY-010015; Symbol: ER_RPL_GTID_TABLE_CANNOT_OPEN; SQLSTATE: HY000

Message: Gtid table is not ready to be used. Table '%s.%s' cannot be opened.

Error number: MY-010016; Symbol: ER_SYSTEM_SCHEMA_NOT_FOUND; SQLSTATE:

HY000

Message: System schema directory does not exist.

Error number: MY-010017; Symbol: ER DD INIT UPGRADE FAILED; SQLSTATE: HY000

Message: Error in initializing dictionary, upgrade will do a cleanup and exit

Error number: MY-010018; Symbol: ER_VIEW_UNKNOWN_CHARSET_OR_COLLATION;

SQLSTATE: HY000

Message: View '%s'.'%s': unknown charset name and/or collation name (client: '%s'; connection:

'%s').

Error number: MY-010019; Symbol: ER_DD_VIEW_CANT_ALLOC_CHARSET; SQLSTATE:

HY000

Message: Error in allocating memory for character set name for view %s.%s.

Error number: MY-010020; Symbol: ER DD INIT FAILED; SQLSTATE: HY000

Message: Data Dictionary initialization failed.

Error number: MY-010021; Symbol: ER DD UPDATING PLUGIN MD FAILED; SQLSTATE:

HY000

Message: Failed to update plugin metadata in dictionary tables.

Error number: MY-010022; Symbol: ER DD POPULATING TABLES FAILED; SQLSTATE:

HY000

Message: Failed to Populate DD tables.

Error number: MY-010023; Symbol: ER DD VIEW CANT CREATE; SQLSTATE: HY000

Message: Error in Creating View %s.%s

Error number: MY-010024; Symbol: ER DD METADATA NOT FOUND; SQLSTATE: HY000

Message: Unable to start server. Cannot find the meta data for data dictionary table '%s'.

Error number: MY-010025; Symbol: ER DD CACHE NOT EMPTY AT SHUTDOWN;

SQLSTATE: HY000

Message: Dictionary cache not empty at shutdown.

Error number: MY-010026; Symbol: ER DD OBJECT REMAINS; SQLSTATE: HY000

Message: Dictionary objects used but not released.

Error number: MY-010027; Symbol: ER_DD_OBJECT_REMAINS_IN_RELEASER; SQLSTATE:

HY000

Message: Dictionary objects left in default releaser.

Error number: MY-010028; Symbol: ER DD OBJECT RELEASER REMAINS; SQLSTATE:

HY000

Message: Dictionary object auto releaser not deleted

Error number: MY-010029; Symbol: ER DD CANT GET OBJECT KEY; SQLSTATE: HY000

Message: Error: Unable to create primary object key

Error number: MY-010030; Symbol: ER DD CANT CREATE OBJECT KEY; SQLSTATE:

HY000

Message: Error: Unable to create object key

Error number: MY-010031; Symbol: ER CANT CREATE HANDLE MGR THREAD;

SQLSTATE: HY000

Message: Can't create handle manager thread (errno= %d)

Error number: MY-010032; Symbol: ER_RPL_REPO_HAS_GAPS; SQLSTATE: HY000

Message: It is not possible to change the type of the relay log's repository because there are workers'

repositories with gaps. Please, fix the gaps first before doing such change.

Error number: MY-010033; Symbol:

ER INVALID VALUE FOR ENFORCE GTID CONSISTENCY; SQLSTATE: HY000

Message: option 'enforce-gtid-consistency': value '%s' was not recognized. Setting enforce-gtid-

consistency to OFF.

Error number: MY-010034; Symbol: ER CHANGED ENFORCE GTID CONSISTENCY;

SOLSTATE: HY000

Message: Changed ENFORCE GTID CONSISTENCY from %s to %s.

Error number: MY-010035; Symbol: ER CHANGED GTID MODE; SQLSTATE: HY000

Message: Changed GTID MODE from %s to %s.

Error number: MY-010036; Symbol: ER DISABLED STORAGE ENGINE AS DEFAULT;

SQLSTATE: HY000

Message: %s is set to a disabled storage engine %s.

Error number: MY-010037; Symbol: ER DEBUG SYNC HIT; SQLSTATE: HY000

Message: Debug sync points hit: %s

Error number: MY-010038; Symbol: ER DEBUG SYNC EXECUTED; SQLSTATE: HY000

Message: Debug sync points executed: %s

Error number: MY-010039; Symbol: ER_DEBUG_SYNC_THREAD_MAX; SQLSTATE: HY000 Message: Debug sync points max active per thread: %s

Error number: MY-010040; Symbol: ER_DEBUG_SYNC_OOM; SQLSTATE: HY000 Message: Debug Sync Facility disabled due to lack of memory.

Error number: MY-010041; Symbol: ER_CANT_INIT_TC_LOG; SQLSTATE: HY000 Message: Can't init tc log

Error number: MY-010042; Symbol: ER_EVENT_CANT_INIT_QUEUE; SQLSTATE: HY000 Message: Event Scheduler: Can't initialize the execution queue

Error number: MY-010043; Symbol: ER_EVENT_PURGING_QUEUE; SQLSTATE: HY000 Message: Event Scheduler: Purging the queue. %u events

Error number: MY-010044; Symbol: ER_EVENT_LAST_EXECUTION; SQLSTATE: HY000 Message: Event Scheduler: Last execution of %s.%s. %s

Error number: MY-010045; Symbol: ER_EVENT_MESSAGE_STACK; SQLSTATE: HY000 Message: %*s

Error number: MY-010046; Symbol: ER_EVENT_EXECUTION_FAILED; SQLSTATE: HY000 Message: Event Scheduler: [%s].[%s.%s] event execution failed.

Error number: MY-010047; Symbol: ER_CANT_INIT_SCHEDULER_THREAD; SQLSTATE: HY000

Message: Event Scheduler: Cannot initialize the scheduler thread

Error number: MY-010048; Symbol: ER_SCHEDULER_STOPPED; SQLSTATE: HY000 Message: Event Scheduler: Stopped

Error number: MY-010049; Symbol: ER_CANT_CREATE_SCHEDULER_THREAD; SOLSTATE: HY000

Message: Event scheduler: Failed to start scheduler, Can not create thread for event scheduler (errno=%d)

Error number: MY-010050; Symbol: ER_SCHEDULER_WAITING; SQLSTATE: HY000 Message: Event Scheduler: Waiting for the scheduler thread to reply

Error number: MY-010051; Symbol: ER_SCHEDULER_STARTED; SQLSTATE: HY000 Message: Event Scheduler: scheduler thread started with id %u

Error number: MY-010052; Symbol: ER_SCHEDULER_STOPPING_FAILED_TO_GET_EVENT;

SQLSTATE: HY000

Message: Event Scheduler: Serious error during getting next event to execute. Stopping

Error number: MY-010053; Symbol:

ER SCHEDULER STOPPING FAILED TO CREATE WORKER; SQLSTATE: HY000

Message: Event scheduler::execute top: Can not create event worker thread (errno=%d). Stopping

event scheduler

Error number: MY-010054; Symbol: ER SCHEDULER KILLING; SQLSTATE: HY000

Message: Event Scheduler: Killing the scheduler thread, thread id %u

Error number: MY-010055; Symbol: ER UNABLE TO RESOLVE IP; SQLSTATE: HY000

Message: IP address '%s' could not be resolved: %s

Error number: MY-010056; Symbol: ER UNABLE TO RESOLVE HOSTNAME; SQLSTATE:

HY000

Message: Host name '%s' could not be resolved: %s

Error number: MY-010057; Symbol: ER HOSTNAME RESEMBLES IPV4; SQLSTATE: HY000

Message: IP address '%s' has been resolved to the host name '%s', which resembles IPv4-address

itself.

Error number: MY-010058; Symbol: ER HOSTNAME DOESNT RESOLVE TO; SQLSTATE:

HY000

Message: Hostname '%s' does not resolve to '%s'.

Error number: MY-010059; Symbol: ER ADDRESSES FOR HOSTNAME HEADER;

SQLSTATE: HY000

Message: Hostname '%s' has the following IP addresses:

Error number: MY-010060; Symbol: ER_ADDRESSES_FOR_HOSTNAME_LIST_ITEM;

SOLSTATE: HY000

Message: - %s

Error number: MY-010061; Symbol: ER TRG WITHOUT DEFINER; SQLSTATE: HY000

Message: Definer clause is missing in Trigger of Table %s. Rebuild Trigger to fix definer.

Error number: MY-010062; Symbol: ER TRG NO CLIENT CHARSET; SQLSTATE: HY000

Message: Client character set is missing for trigger of table %s. Using default character set.

Error number: MY-010063; Symbol: ER PARSING VIEW; SQLSTATE: HY000

Message: Error in parsing view %s.%s

Error number: MY-010064; Symbol: ER_COMPONENTS_INFRASTRUCTURE_BOOTSTRAP;

SQLSTATE: HY000

Message: Failed to bootstrap components infrastructure.

Error number: MY-010065; Symbol: ER COMPONENTS INFRASTRUCTURE SHUTDOWN;

SQLSTATE: HY000

Message: Failed to shutdown components infrastructure.

Error number: MY-010066; Symbol: ER COMPONENTS PERSIST LOADER BOOTSTRAP;

SQLSTATE: HY000

Message: Failed to bootstrap persistent components loader.

Error number: MY-010067; Symbol: ER DEPART WITH GRACE; SQLSTATE: HY000

Message: Giving %d client threads a chance to die gracefully

Error number: MY-010068; Symbol: ER CA SELF SIGNED; SQLSTATE: HY000

Message: CA certificate %s is self signed.

Error number: MY-010069; Symbol: ER_SSL_LIBRARY_ERROR; SQLSTATE: HY000

Message: Failed to set up SSL because of the following SSL library error: %s

Error number: MY-010070; Symbol: ER NO THD NO UUID; SQLSTATE: HY000

Message: Failed to generate a server UUID because it is failed to allocate the THD.

Error number: MY-010071; Symbol: ER_UUID_SALT; SQLSTATE: HY000

Message: Salting uuid generator variables, current pid: %lu, server start time: %lu,

bytes sent: %llu,

Error number: MY-010072; Symbol: ER UUID IS; SQLSTATE: HY000

Message: Generated uuid: '%s', server_start_time: %lu, bytes_sent: %llu

Error number: MY-010073; Symbol: ER UUID INVALID; SQLSTATE: HY000

Message: The server uuid stored in auto.cnf file is not a valid UUID.

Error number: MY-010074; Symbol: ER UUID SCRUB; SQLSTATE: HY000

Message: Garbage characters found at the end of the server_uuid value in auto.cnf file. It should be

of length '%d' (UUID_LENGTH). Clear it and restart the server.

Error number: MY-010075; Symbol: ER_CREATING_NEW_UUID; SQLSTATE: HY000

Message: No existing UUID has been found, so we assume that this is the first time that this server has been started. Generating a new UUID: %s.

Error number: MY-010076; Symbol: ER_CANT_CREATE_UUID; SQLSTATE: HY000 Message: Initialization of the server's UUID failed because it could not be read from the auto.cnf file. If this is a new server, the initialization failed because it was not possible to generate a new UUID.

Error number: MY-010077; Symbol: ER_UNKNOWN_UNSUPPORTED_STORAGE_ENGINE;

SQLSTATE: HY000

Message: Unknown/unsupported storage engine: %s

Error number: MY-010078; Symbol: ER SECURE AUTH VALUE UNSUPPORTED;

SQLSTATE: HY000

Message: Unsupported value 0 for secure-auth

Error number: MY-010079; Symbol: ER_INVALID_INSTRUMENT; SQLSTATE: HY000 Message: Invalid instrument name or value for performance schema instrument '%s'

Error number: MY-010080; Symbol: ER_INNODB_MANDATORY; SQLSTATE: HY000 Message: The use of InnoDB is mandatory since MySQL 5.7. The former options like '-- innodb=0/1/OFF/ON' or '--skip-innodb' are ignored.

 $Error\ number:\ MY-010082;\ Symbol:\ ER_OLD_PASSWORDS_NO_MIDDLE_GROUND;$

SQLSTATE: HY000

Message: Invalid old passwords mode: 1. Valid values are 2 and 0

Error number: MY-010083; Symbol: ER_VERBOSE_REQUIRES_HELP; SQLSTATE: HY000 Message: --verbose is for use with --help; did you mean --log-error-verbosity?

Error number: MY-010084; Symbol: ER_POINTLESS_WITHOUT_SLOWLOG; SQLSTATE: HY000

Message: options --log-slow-admin-statements, --log-queries-not-using-indexes and --log-slow-replica-statements have no effect if --slow-query-log is not set

Error number: MY-010085; Symbol: ER_WASTEFUL_NET_BUFFER_SIZE; SQLSTATE: HY000 Message: net_buffer_length (%lu) is set to be larger than max_allowed_packet (%lu). Please rectify.

Error number: MY-010086; Symbol: ER_DEPRECATED_TIMESTAMP_IMPLICIT_DEFAULTS; SQLSTATE: HY000

Message: TIMESTAMP with implicit DEFAULT value is deprecated. Please use -- explicit_defaults_for_timestamp server option (see documentation for more details).

Error number: MY-010087; Symbol: ER_FT_BOOL_SYNTAX_INVALID; SQLSTATE: HY000 Message: Invalid ft-boolean-syntax string: %s

Error number: MY-010088; Symbol: ER_CREDENTIALLESS_AUTO_USER_BAD; SQLSTATE: HY000

Message: 'NO AUTO CREATE USER' sql mode was not set.

Error number: MY-010089; Symbol: ER_CONNECTION_HANDLING_OOM; SQLSTATE: HY000

Message: Could not allocate memory for connection handling

Error number: MY-010090; Symbol: ER_THREAD_HANDLING_OOM; SQLSTATE: HY000 Message: Could not allocate memory for thread handling

Error number: MY-010091; Symbol: ER_CANT_CREATE_TEST_FILE; SQLSTATE: HY000 Message: Can't create test file %s

Error number: MY-010092; Symbol: ER_CANT_CREATE_PID_FILE; SQLSTATE: HY000 Message: Can't start server: can't create PID file: %s

Error number: MY-010093; Symbol: ER_CANT_REMOVE_PID_FILE; SQLSTATE: HY000 Message: Unable to delete pid file: %s

Error number: MY-010094; Symbol: ER_CANT_CREATE_SHUTDOWN_THREAD; SQLSTATE: HY000

Message: Can't create thread to handle shutdown requests (errno= %d)

Error number: MY-010095; Symbol: ER_SEC_FILE_PRIV_CANT_ACCESS_DIR; SQLSTATE: HY000

Message: Failed to access directory for --secure-file-priv. Please make sure that directory exists and is accessible by MySQL Server. Supplied value : %s

Error number: MY-010096; Symbol: ER_SEC_FILE_PRIV_IGNORED; SQLSTATE: HY000 Message: Ignoring --secure-file-priv value as server is running with --initialize(-insecure).

Error number: MY-010097; Symbol: ER_SEC_FILE_PRIV_EMPTY; SQLSTATE: HY000 Message: Insecure configuration for --secure-file-priv: Current value does not restrict location of generated files. Consider setting it to a valid, non-empty path.

Error number: MY-010098; Symbol: ER_SEC_FILE_PRIV_NULL; SQLSTATE: HY000 Message: --secure-file-priv is set to NULL. Operations related to importing and exporting data are disabled

Error number: MY-010099; Symbol: ER SEC FILE PRIV DIRECTORY INSECURE;

SQLSTATE: HY000

Message: Insecure configuration for --secure-file-priv: %s is accessible through --secure-file-priv.

Consider choosing a different directory.

Error number: MY-010100; Symbol: ER SEC FILE PRIV CANT STAT; SQLSTATE: HY000

Message: Failed to get stat for directory pointed out by --secure-file-priv

Error number: MY-010101; Symbol: ER SEC FILE PRIV DIRECTORY PERMISSIONS;

SQLSTATE: HY000

Message: Insecure configuration for --secure-file-priv: Location is accessible to all OS users.

Consider choosing a different directory.

Error number: MY-010102; Symbol: ER SEC FILE PRIV ARGUMENT TOO LONG;

SQLSTATE: HY000

Message: Value for --secure-file-priv is longer than maximum limit of %d

Error number: MY-010103; Symbol: ER CANT CREATE NAMED PIPES THREAD;

SQLSTATE: HY000

Message: Can't create thread to handle named pipes (errno= %d)

Error number: MY-010104; Symbol: ER CANT CREATE TCPIP THREAD; SQLSTATE:

HY000

Message: Can't create thread to handle TCP/IP (errno= %d)

Error number: MY-010105; Symbol: ER_CANT_CREATE_SHM_THREAD; SQLSTATE: HY000

Message: Can't create thread to handle shared memory (errno= %d)

2.6 错误码及错误信息汇总 06

Error number: MY-010106; Symbol: ER CANT CREATE INTERRUPT THREAD; SQLSTATE:

HY000

Message: Can't create interrupt-thread (error %d, errno: %d)

Error number: MY-010107; Symbol: ER WRITABLE CONFIG REMOVED; SQLSTATE:

HY000

Message: World-writable config file '%s' has been removed.

Error number: MY-010108; Symbol: ER CORE VALUES; SQLSTATE: HY000

Message: setrlimit could not change the size of core files to 'infinity'; We may not be able to generate a core file on signals

Error number: MY-010109; Symbol: ER_WRONG_DATETIME_SPEC; SQLSTATE: HY000 Message: Wrong date/time format specifier: %s

Error number: MY-010110; Symbol: ER_RPL_BINLOG_FILTERS_OOM; SQLSTATE: HY000 Message: Could not allocate replication and binlog filters: %s

Error number: MY-010111; Symbol: ER_KEYCACHE_OOM; SQLSTATE: HY000 Message: Cannot allocate the keycache

Error number: MY-010112; Symbol: ER_CONFIRMING_THE_FUTURE; SQLSTATE: HY000 Message: Current time has got past year 2038. Validating current time with %d iterations before initiating the normal server shutdown process.

Error number: MY-010113; Symbol: ER_BACK_IN_TIME; SQLSTATE: HY000 Message: Iteration %d: Obtained valid current time from system

Error number: MY-010114; Symbol: ER_FUTURE_DATE; SQLSTATE: HY000 Message: Iteration %d: Current time obtained from system is greater than 2038

Error number: MY-010115; Symbol: ER_UNSUPPORTED_DATE; SQLSTATE: HY000 Message: This MySQL server doesn't support dates later then 2038

Error number: MY-010116; Symbol: ER_STARTING_AS; SQLSTATE: HY000 Message: %s (mysqld %s) starting as process %lu

Error number: MY-010117; Symbol: ER_SHUTTING_DOWN_SLAVE_THREADS; SQLSTATE: HY000

Message: Shutting down slave threads

Error number: MY-010118; Symbol: ER_DISCONNECTING_REMAINING_CLIENTS;

SOLSTATE: HY000

Message: Forcefully disconnecting %d remaining clients

Error number: MY-010119; Symbol: ER_ABORTING; SQLSTATE: HY000

Message: Aborting

Error number: MY-010120; Symbol: ER BINLOG END; SQLSTATE: HY000

Message: Binlog end

Error number: MY-010121; Symbol: ER_CALL_ME_LOCALHOST; SQLSTATE: HY000 Message: gethostname failed, using '%s' as hostname

Error number: MY-010122; Symbol: ER_USER_REQUIRES_ROOT; SQLSTATE: HY000 Message: One can only use the --user switch if running as root

Error number: MY-010123; Symbol: ER_REALLY_RUN_AS_ROOT; SQLSTATE: HY000 Message: Fatal error: Please read "Security" section of the manual to find out how to run mysqld as root!

Error number: MY-010124; Symbol: ER_USER_WHAT_USER; SQLSTATE: HY000 Message: Fatal error: Can't change to run as user '%s'; Please check that the user exists!

Error number: MY-010125; Symbol: ER_TRANSPORTS_WHAT_TRANSPORTS; SQLSTATE: HY000

Message: Server is started with --require-secure-transport=ON but no secure transports (SSL or Shared Memory) are configured.

Error number: MY-010126; Symbol: ER_FAIL_SETGID; SQLSTATE: HY000 Message: setgid: %s

Error number: MY-010127; Symbol: ER_FAIL_SETUID; SQLSTATE: HY000 Message: setuid: %s

Error number: MY-010128; Symbol: ER_FAIL_SETREGID; SQLSTATE: HY000 Message: setregid: %s

Error number: MY-010129; Symbol: ER_FAIL_SETREUID; SQLSTATE: HY000 Message: setreuid: %s

Error number: MY-010130; Symbol: ER_FAIL_CHROOT; SQLSTATE: HY000 Message: chroot: %s

Error number: MY-010131; Symbol: ER_WIN_LISTEN_BUT_HOW; SQLSTATE: HY000 Message: TCP/IP, --shared-memory, or --named-pipe should be configured on NT OS

Error number: MY-010132; Symbol: ER_NOT_RIGHT_NOW; SQLSTATE: HY000 Message: CTRL-C ignored during startup

Error number: MY-010133; Symbol: ER_FIXING_CLIENT_CHARSET; SQLSTATE: HY000 Message: '%s' can not be used as client character set. '%s' will be used as default client character set.

Error number: MY-010134; Symbol: ER OOM; SQLSTATE: HY000

Message: Out of memory

Error number: MY-010135; Symbol: ER FAILED TO LOCK MEM; SQLSTATE: HY000

Message: Failed to lock memory. Errno: %d

Error number: MY-010136; Symbol: ER MYINIT FAILED; SQLSTATE: HY000

Message: my init() failed.

Error number: MY-010137; Symbol: ER BEG INITFILE; SQLSTATE: HY000

Message: Execution of init file \'%s\' started.

Error number: MY-010138; Symbol: ER END INITFILE; SQLSTATE: HY000

Message: Execution of init file \'%s\' ended.

Error number: MY-010139; Symbol: ER CHANGED MAX OPEN FILES; SQLSTATE: HY000

Message: Changed limits: max open files: %lu (requested %lu)

Error number: MY-010140; Symbol: ER CANT INCREASE MAX OPEN FILES; SQLSTATE:

HY000

Message: Could not increase number of max open files to more than %lu (request: %lu)

Error number: MY-010141; Symbol: ER CHANGED MAX CONNECTIONS; SQLSTATE:

HY000

Message: Changed limits: max connections: %lu (requested %lu)

Error number: MY-010142; Symbol: ER CHANGED TABLE OPEN CACHE; SQLSTATE:

HY000

Message: Changed limits: table open cache: %lu (requested %lu)

Error number: MY-010143; Symbol: ER THE USER ABIDES; SQLSTATE: HY000

Message: Ignoring user change to '%s' because the user was set to '%s' earlier on the command line

Error number: MY-010144; Symbol: ER RPL CANT ADD DO TABLE; SQLSTATE: HY000

Message: Could not add do table rule '%s'!

Error number: MY-010145; Symbol: ER RPL CANT ADD IGNORE TABLE; SQLSTATE:

HY000

Message: Could not add ignore table rule '%s'!

Error number: MY-010146; Symbol: ER_TRACK_VARIABLES_BOGUS; SQLSTATE: HY000

Message: The variable session_track_system_variables either has duplicate values or invalid values.

Error number: MY-010147; Symbol: ER_EXCESS_ARGUMENTS; SQLSTATE: HY000 Message: Too many arguments (first extra is '%s').

Error number: MY-010148; Symbol: ER_VERBOSE_HINT; SQLSTATE: HY000

Message: Use --verbose --help to get a list of available options!

Error number: MY-010149; Symbol: ER CANT READ ERRMSGS; SQLSTATE: HY000

Message: Unable to read errmsg.sys file

Error number: MY-010150; Symbol: ER CANT INIT DBS; SQLSTATE: HY000

Message: Can't init databases

Error number: MY-010151; Symbol: ER_LOG_OUTPUT_CONTRADICTORY; SQLSTATE:

HY000

Message: There were other values specified to log-output besides NONE. Disabling slow and general

logs anyway.

Error number: MY-010152; Symbol: ER_NO_CSV_NO_LOG_TABLES; SQLSTATE: HY000

Message: CSV engine is not present, falling back to the log files

Error number: MY-010153; Symbol: ER_RPL_REWRITEDB_MISSING_ARROW; SQLSTATE:

HY000

Message: Bad syntax in replicate-rewrite-db - missing '->'!

Error number: MY-010154; Symbol: ER RPL REWRITEDB EMPTY FROM; SQLSTATE:

HY000

Message: Bad syntax in replicate-rewrite-db - empty FROM db!

Error number: MY-010155; Symbol: ER RPL REWRITEDB_EMPTY_TO; SQLSTATE: HY000

Message: Bad syntax in replicate-rewrite-db - empty TO db!

Error number: MY-010156; Symbol: ER_LOG_FILES_GIVEN_LOG_OUTPUT_IS_TABLE;

SOLSTATE: HY000

Message: Although a path was specified for the %s, log tables are used. To enable logging to files

use the --log-output=file option.

Error number: MY-010157; Symbol: ER LOG FILE INVALID; SQLSTATE: HY000

Message: Invalid value for %s: %s

Error number: MY-010158; Symbol:

ER_LOWER_CASE_TABLE_NAMES_CS_DD_ON_CI_FS_UNSUPPORTED; SQLSTATE: HY000

Message: The server option 'lower_case_table_names' is configured to use case sensitive table names but the data directory is on a case-insensitive file system which is an unsupported combination. Please consider either using a case sensitive file system for your data directory or switching to a case-insensitive table name mode.

Error number: MY-010159; Symbol: ER_LOWER_CASE_TABLE_NAMES_USING_2;

SQLSTATE: HY000

Message: Setting lower_case_table_names=2 because file system for %s is case insensitive

Error number: MY-010160; Symbol: ER_LOWER_CASE_TABLE_NAMES_USING_0; SQLSTATE: HY000

Message: lower_case_table_names was set to 2, even though your the file system '%s' is case sensitive. Now setting lower case table names to 0 to avoid future problems.

Error number: MY-010161; Symbol: ER_NEED_LOG_BIN; SQLSTATE: HY000 Message: You need to use --log-bin to make %s work.

Error number: MY-010162; Symbol: ER_NEED_FILE_INSTEAD_OF_DIR; SQLSTATE: HY000 Message: Path '%s' is a directory name, please specify a file name for %s option

Error number: MY-010163; Symbol: ER_LOG_BIN_BETTER_WITH_NAME; SQLSTATE: HY000

Message: No argument was provided to --log-bin, and --log-bin-index was not used; so replication may break when this MySQL server acts as a master and has his hostname changed!! Please use '--log-bin=%s' to avoid this problem.

Error number: MY-010164; Symbol: ER_BINLOG_NEEDS_SERVERID; SQLSTATE: HY000 Message: You have enabled the binary log, but you haven't provided the mandatory server-id. Please refer to the proper server start-up parameters documentation

Error number: MY-010165; Symbol: ER_RPL_CANT_MAKE_PATHS; SQLSTATE: HY000 Message: Unable to create replication path names: out of memory or path names too long (path name exceeds %d).

Error number: MY-010166; Symbol: ER_CANT_INITIALIZE_GTID; SQLSTATE: HY000 Message: Failed to initialize GTID structures.

Error number: MY-010167; Symbol: ER_CANT_INITIALIZE_EARLY_PLUGINS; SQLSTATE: HY000

Message: Failed to initialize early plugins.

Error number: MY-010168; Symbol: ER_CANT_INITIALIZE_BUILTIN_PLUGINS; SQLSTATE:

HY000

Message: Failed to initialize builtin plugins.

Error number: MY-010169; Symbol: ER CANT INITIALIZE DYNAMIC PLUGINS;

SQLSTATE: HY000

Message: Failed to initialize dynamic plugins.

Error number: MY-010170; Symbol: ER_PERFSCHEMA_INIT_FAILED; SQLSTATE: HY000

Message: Performance schema disabled (reason: init failed).

Error number: MY-010171; Symbol: ER_STACKSIZE_UNEXPECTED; SQLSTATE: HY000

Message: Asked for %lu thread stack, but got %ld

Error number: MY-010172; Symbol: ER CANT SET DATADIR; SQLSTATE: HY000

Message: failed to set datadir to %s

Error number: MY-010173; Symbol: ER CANT STAT DATADIR; SQLSTATE: HY000

Message: Can't read data directory's stats (%d): %s. Assuming that it's not owned by the same

user/group

Error number: MY-010174; Symbol: ER CANT CHOWN DATADIR; SQLSTATE: HY000

Message: Can't change data directory owner to %s

Error number: MY-010175; Symbol: ER CANT SET UP PERSISTED VALUES; SQLSTATE:

HY000

Message: Setting persistent options failed.

Error number: MY-010176; Symbol: ER CANT SAVE GTIDS; SQLSTATE: HY000

Message: Failed to save the set of Global Transaction Identifiers of the last binary log into the mysql.gtid_executed table while the server was shutting down. The next server restart will make another attempt to save Global Transaction Identifiers into the table.

Error number: MY-010177; Symbol: ER AUTH CANT SET DEFAULT PLUGIN; SQLSTATE:

HY000

Message: Can't start server: Invalid value for --default-authentication-plugin

Error number: MY-010178; Symbol: ER CANT JOIN SHUTDOWN THREAD; SQLSTATE:

HY000

Message: Could not join %sthread. error:%d

Error number: MY-010179; Symbol: ER_CANT_HASH_DO_AND_IGNORE_RULES;

SQLSTATE: HY000

Message: An error occurred while building do_table and ignore_table rules to hashes for global

replication filter.

Error number: MY-010180; Symbol: ER CANT OPEN CA; SQLSTATE: HY000

Message: Error opening CA certificate file

Error number: MY-010181; Symbol: ER CANT ACCESS CAPATH; SQLSTATE: HY000

Message: Error accessing directory pointed by --ssl-capath

Error number: MY-010182; Symbol: ER_SSL_TRYING_DATADIR_DEFAULTS; SQLSTATE:

HY000

Message: Found %s, %s and %s in data directory. Trying to enable SSL support using them.

Error number: MY-010183; Symbol: ER AUTO OPTIONS FAILED; SQLSTATE: HY000

Message: Failed to create %s(file: '%s', errno %d)

Error number: MY-010184; Symbol: ER CANT INIT TIMER; SQLSTATE: HY000

Message: Failed to initialize timer component (errno %d).

Error number: MY-010185; Symbol: ER SERVERID TOO LARGE; SQLSTATE: HY000

Message: server-id configured is too large to represent with server-id-bits configured.

Error number: MY-010186; Symbol: ER DEFAULT SE UNAVAILABLE; SQLSTATE: HY000

Message: Default%s storage engine (%s) is not available

Error number: MY-010187; Symbol: ER CANT OPEN ERROR LOG; SQLSTATE: HY000

Message: Could not open file '%s' for error logging%s%s

Error number: MY-010188; Symbol: ER INVALID ERROR LOG NAME; SQLSTATE: HY000

Message: Invalid log file name after expanding symlinks: '%s'

Error number: MY-010189; Symbol: ER RPL INFINITY DENIED; SQLSTATE: HY000

Message: using --replicate-same-server-id in conjunction with --log-replica-updates is impossible, it

would lead to infinite loops in this server.

Error number: MY-010190; Symbol: ER RPL INFINITY IGNORED; SQLSTATE: HY000

Message: using --replicate-same-server-id in conjunction with --log-replica-updates would lead to infinite loops in this server. However this will be ignored as the --log-bin option is not defined or

your server is running with global transaction identiers enabled.

Error number: MY-010192; Symbol: ER_TABLE_CHECK_INTACT; SQLSTATE: HY000 Message: %s

Error number: MY-010193; Symbol: ER_DD_TABLESPACE_NOT_FOUND; SQLSTATE: HY000 Message: Unable to start server. The data dictionary tablespace '%s' does not exist.

Error number: MY-010194; Symbol: ER_DD_TRG_CONNECTION_COLLATION_MISSING; SQLSTATE: HY000

Message: Connection collation is missing for trigger of table %s. Using default connection collation.

Error number: MY-010195; Symbol: ER_DD_TRG_DB_COLLATION_MISSING; SQLSTATE: HY000

Message: Database collation is missing for trigger of table %s. Using Default character set.

Error number: MY-010196; Symbol: ER_DD_TRG_DEFINER_OOM; SQLSTATE: HY000 Message: Error in Memory allocation for Definer %s for Trigger.

Error number: MY-010197; Symbol: ER_DD_TRG_FILE_UNREADABLE; SQLSTATE: HY000 Message: Error in reading %s.TRG file.

Error number: MY-010198; Symbol: ER_TRG_CANT_PARSE; SQLSTATE: HY000 Message: Error in parsing Triggers from %s.TRG file.

Error number: MY-010199; Symbol: ER_DD_TRG_CANT_ADD; SQLSTATE: HY000 Message: Error in creating DD entry for Trigger %s.%s

Error number: MY-010200; Symbol: ER_DD_CANT_RESOLVE_VIEW; SQLSTATE: HY000 Message: Resolving dependency for the view '%s.%s' failed. View is no more valid to use

Error number: MY-010201; Symbol: ER_DD_VIEW_WITHOUT_DEFINER; SQLSTATE: HY000 Message: %s.%s has no definer (as per an old view format). Current user is used as definer. Please recreate the view.

Error number: MY-010202; Symbol: ER_PLUGIN_INIT_FAILED; SQLSTATE: HY000 Message: Plugin '%s' init function returned error.

Error number: MY-010203; Symbol: ER_RPL_TRX_DELEGATES_INIT_FAILED; SQLSTATE: HY000

Message: Initialization of transaction delegates failed. Please report a bug.

Error number: MY-010204; Symbol:

ER RPL BINLOG STORAGE DELEGATES INIT FAILED; SQLSTATE: HY000

Message: Initialization binlog storage delegates failed. Please report a bug.

Error number: MY-010205; Symbol:

ER RPL BINLOG TRANSMIT DELEGATES INIT FAILED; SQLSTATE: HY000

Message: Initialization of binlog transmit delegates failed. Please report a bug.

Error number: MY-010206; Symbol: ER RPL BINLOG RELAY DELEGATES INIT FAILED;

SQLSTATE: HY000

Message: Initialization binlog relay IO delegates failed. Please report a bug.

Error number: MY-010207; Symbol: ER RPL PLUGIN FUNCTION FAILED; SQLSTATE:

HY000

Message: Run function '...' in plugin '%s' failed

Error number: MY-010208; Symbol: ER SQL HA READ FAILED; SQLSTATE: HY000

Message: mysql ha read: Got error %d when reading table '%s'

Error number: MY-010209; Symbol: ER SR BOGUS VALUE; SQLSTATE: HY000

Message: Stored routine '%s'.'%s': invalid value in column %s.

Error number: MY-010210; Symbol: ER SR INVALID CONTEXT; SQLSTATE: HY000

Message: Invalid creation context '%s.%s'.

Error number: MY-010211; Symbol: ER READING TABLE FAILED; SQLSTATE: HY000

Message: Got error %d when reading table '%s'

Error number: MY-010212; Symbol: ER DES FILE WRONG KEY; SQLSTATE: HY000

Message: load des file: Found wrong key number: %c

Error number: MY-010213; Symbol: ER CANT SET PERSISTED; SQLSTATE: HY000

Message: Failed to set persisted options.

Error number: MY-010214; Symbol: ER JSON PARSE ERROR; SQLSTATE: HY000

Message: Persisted config file is corrupt. Please ensure mysqld-auto.cnf file is valid JSON.

Error number: MY-010215; Symbol: ER CONFIG OPTION WITHOUT GROUP; SQLSTATE:

HY000

Message: Found option without preceding group in config file

Error number: MY-010216; Symbol: ER VALGRIND DO QUICK LEAK CHECK; SQLSTATE:

HY000

Message: VALGRIND_DO_QUICK_LEAK_CHECK

Error number: MY-010217; Symbol: ER VALGRIND COUNT LEAKS; SQLSTATE: HY000

Message: VALGRIND COUNT LEAKS reports %lu leaked bytes for query '%.*s'

Error number: MY-010218; Symbol:

ER LOAD DATA INFILE FAILED IN UNEXPECTED WAY; SQLSTATE: HY000

Message: LOAD DATA INFILE in the slave SQL Thread can only read from --replica-load-tmpdir.

Please, report a bug.

Error number: MY-010219; Symbol: ER UNKNOWN ERROR NUMBER; SQLSTATE: HY000

Message: Got unknown error: %d

Error number: MY-010220; Symbol: ER UDF CANT ALLOC FOR STRUCTURES;

SQLSTATE: HY000

Message: Can't allocate memory for udf structures

Error number: MY-010221; Symbol: ER UDF CANT ALLOC FOR FUNCTION; SQLSTATE:

HY000

Message: Can't alloc memory for udf function: '%s'

Error number: MY-010222; Symbol: ER UDF INVALID ROW IN FUNCTION TABLE;

SQLSTATE: HY000

Message: Invalid row in mysql.func table for function '%s'

Error number: MY-010223; Symbol: ER_UDF_CANT_OPEN_FUNCTION_TABLE; SQLSTATE:

HY000

Message: Could not open the mysql.func table. Please perform the MySQL upgrade procedure.

Error number: MY-010224; Symbol: ER XA RECOVER FOUND TRX IN SE; SQLSTATE:

HY000

Message: Found %d prepared transaction(s) in %s

Error number: MY-010225; Symbol: ER XA RECOVER FOUND XA TRX; SQLSTATE:

HY000

Message: Found %d prepared XA transactions

Error number: MY-010226; Symbol: ER XA IGNORING XID; SQLSTATE: HY000

Message: ignore xid %s

Error number: MY-010227; Symbol: ER_XA_COMMITTING_XID; SQLSTATE: HY000

Message: commit xid %s

Error number: MY-010228; Symbol: ER XA ROLLING BACK XID; SQLSTATE: HY000

Message: rollback xid %s

Error number: MY-010229; Symbol: ER XA STARTING RECOVERY; SQLSTATE: HY000

Message: Starting XA crash recovery...

Error number: MY-010230; Symbol: ER XA NO MULTI 2PC HEURISTIC RECOVER;

SQLSTATE: HY000

Message: --tc-heuristic-recover rollback strategy is not safe on systems with more than one 2-phase-

commit-capable storage engine. Aborting crash recovery.

Error number: MY-010231; Symbol: ER_XA_RECOVER_EXPLANATION; SQLSTATE: HY000 Message: Found %d prepared transactions! It means that mysqld was not shut down properly last time and critical recovery information (last binlog or %s file) was manually deleted after a crash. You have to start mysqld with --tc-heuristic-recover switch to commit or rollback pending transactions.

Error number: MY-010232; Symbol: ER_XA_RECOVERY_DONE; SQLSTATE: HY000

Message: XA crash recovery finished.

Error number: MY-010233; Symbol: ER TRX GTID COLLECT REJECT; SQLSTATE: HY000

Message: Failed to collect GTID to send in the response packet!

Error number: MY-010234; Symbol: ER SQL AUTHOR DEFAULT ROLES FAIL;

SOLSTATE: HY000

Message: MYSQL.DEFAULT ROLES couldn't be updated for authorization identifier %s

Error number: MY-010235; Symbol: ER SQL USER TABLE CREATE WARNING;

SQLSTATE: HY000

Message: Following users were specified in CREATE USER IF NOT EXISTS but they already exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication

information (if any) for them: %s

Error number: MY-010236; Symbol: ER_SQL_USER_TABLE_ALTER_WARNING; SQLSTATE:

HY000

Message: Following users were specified in ALTER USER IF EXISTS but they do not exist. Corresponding entry in binary log used default authentication plugin '%s' to rewrite authentication information (if any) for them: %s

Error number: MY-010237; Symbol: ER ROW IN WRONG PARTITION PLEASE REPAIR;

SOLSTATE: HY000

Message: Table '%s' corrupted: row in wrong partition: %s -- Please REPAIR the table!

Error number: MY-010238; Symbol: ER MYISAM CRASHED ERROR IN THREAD;

SQLSTATE: HY000

Message: Got an error from thread id=%u, %s:%d

Error number: MY-010239; Symbol: ER MYISAM CRASHED ERROR IN; SQLSTATE: HY000

Message: Got an error from unknown thread, %s:%d

Error number: MY-010240; Symbol: ER TOO MANY STORAGE ENGINES; SQLSTATE:

HY000

Message: Too many storage engines!

Error number: MY-010241; Symbol: ER SE TYPECODE CONFLICT; SQLSTATE: HY000

Message: Storage engine '%s' has conflicting typecode. Assigning value %d.

Error number: MY-010242; Symbol: ER TRX WRITE SET OOM; SQLSTATE: HY000

Message: Out of memory on transaction write set extraction

Error number: MY-010243; Symbol: ER_HANDLERTON_OOM; SQLSTATE: HY000

Message: Unable to allocate memory for plugin '%s' handlerton.

Error number: MY-010244; Symbol: ER CONN SHM LISTENER; SQLSTATE: HY000

Message: Shared memory setting up listener

Error number: MY-010245; Symbol: ER_CONN_SHM_CANT_CREATE_SERVICE; SQLSTATE:

HY000

Message: Can't create shared memory service: %s.: %s

Error number: MY-010246; Symbol: ER CONN SHM CANT CREATE CONNECTION;

SQLSTATE: HY000

Message: Can't create shared memory connection: %s.: %s

Error number: MY-010247; Symbol: ER CONN PIP CANT CREATE EVENT; SQLSTATE:

HY000

Message: Can't create event, last error=%u

Error number: MY-010248; Symbol: ER CONN PIP CANT CREATE PIPE; SQLSTATE:

HY000

Message: Can't create new named pipe!: %s

Error number: MY-010249; Symbol: ER_CONN_PER_THREAD_NO_THREAD; SQLSTATE:

HY000

Message: Can't create thread to handle new connection(errno= %d)

Error number: MY-010250; Symbol: ER CONN_TCP_NO_SOCKET; SQLSTATE: HY000

Message: Failed to create a socket for %s '%s': errno: %d.

Error number: MY-010251; Symbol: ER CONN TCP CREATED; SQLSTATE: HY000

Message: Server socket created on IP: '%s'.

Error number: MY-010252; Symbol: ER CONN TCP ADDRESS; SQLSTATE: HY000

Message: Server hostname (bind-address): '%s'; port: %d

Error number: MY-010253; Symbol: ER CONN TCP IPV6 AVAILABLE; SQLSTATE: HY000

Message: IPv6 is available.

Error number: MY-010254; Symbol: ER CONN TCP IPV6 UNAVAILABLE; SQLSTATE:

HY000

Message: IPv6 is not available.

Error number: MY-010255; Symbol: ER CONN TCP ERROR WITH STRERROR; SQLSTATE:

HY000

Message: Can't create IP socket: %s

Error number: MY-010256; Symbol: ER CONN TCP CANT RESOLVE HOSTNAME;

SQLSTATE: HY000

Message: Can't start server: cannot resolve hostname!

Error number: MY-010257; Symbol: ER CONN TCP IS THERE ANOTHER USING PORT;

SQLSTATE: HY000

Message: Do you already have another mysqld server running on port: %d?

Error number: MY-010258; Symbol:

ER CONN UNIX IS THERE ANOTHER USING SOCKET; SQLSTATE: HY000

Message: Do you already have another mysqld server running on socket: %s?

Error number: MY-010259; Symbol: ER CONN UNIX PID CLAIMED SOCKET FILE;

SQLSTATE: HY000

Message: Another process with pid %d is using unix socket file.

Error number: MY-010260; Symbol: ER_CONN_TCP_CANT_RESET_V6ONLY; SQLSTATE: HY000

Message: Failed to reset IPV6_V6ONLY flag (error: %d). The server will listen to IPv6 addresses only.

Error number: MY-010261; Symbol: ER_CONN_TCP_BIND_RETRY; SQLSTATE: HY000 Message: Retrying bind on TCP/IP port %u

Error number: MY-010262; Symbol: ER_CONN_TPC_BIND_FAIL; SQLSTATE: HY000 Message: Can't start server: Bind on TCP/IP port: %s

Error number: MY-010262; Symbol: ER_CONN_TCP_BIND_FAIL; SQLSTATE: HY000 Message: Can't start server: Bind on TCP/IP port: %s

Error number: MY-010263; Symbol: ER_CONN_TCP_IP_NOT_LOGGED; SQLSTATE: HY000 Message: Fails to print out IP-address.

Error number: MY-010264; Symbol: ER_CONN_TCP_RESOLVE_INFO; SQLSTATE: HY000 Message: - '%s' resolves to '%s';

Error number: MY-010265; Symbol: ER_CONN_TCP_START_FAIL; SQLSTATE: HY000 Message: Can't start server: listen() on TCP/IP port: %s

Error number: MY-010266; Symbol: ER_CONN_TCP_LISTEN_FAIL; SQLSTATE: HY000 Message: listen() on TCP/IP failed with error %d

Error number: MY-010267; Symbol: ER_CONN_UNIX_PATH_TOO_LONG; SQLSTATE: HY000 Message: The socket file path is too long (> %u): %s

Error number: MY-010268; Symbol: ER_CONN_UNIX_LOCK_FILE_FAIL; SQLSTATE: HY000 Message: Unable to setup unix socket lock file.

Error number: MY-010269; Symbol: ER_CONN_UNIX_NO_FD; SQLSTATE: HY000 Message: Can't start server: UNIX Socket: %s

Error number: MY-010270; Symbol: ER_CONN_UNIX_NO_BIND_NO_START; SQLSTATE: HY000

Message: Can't start server : Bind on unix socket: %s

Error number: MY-010271; Symbol: ER_CONN_UNIX_LISTEN_FAILED; SQLSTATE: HY000 Message: listen() on Unix socket failed with error %d

Error number: MY-010272; Symbol: ER CONN UNIX LOCK FILE GIVING UP; SQLSTATE:

HY000

Message: Unable to create unix socket lock file %s after retries.

Error number: MY-010273; Symbol: ER CONN UNIX LOCK FILE CANT CREATE;

SQLSTATE: HY000

Message: Could not create unix socket lock file %s.

Error number: MY-010274; Symbol: ER CONN UNIX LOCK FILE CANT OPEN;

SQLSTATE: HY000

Message: Could not open unix socket lock file %s.

Error number: MY-010275; Symbol: ER CONN UNIX LOCK FILE CANT READ;

SQLSTATE: HY000

Message: Could not read unix socket lock file %s.

Error number: MY-010276; Symbol: ER CONN UNIX LOCK FILE EMPTY; SQLSTATE:

HY000

Message: Unix socket lock file is empty %s.

Error number: MY-010277; Symbol: ER CONN UNIX LOCK FILE PIDLESS; SQLSTATE:

HY000

Message: Invalid pid in unix socket lock file %s.

Error number: MY-010278; Symbol: ER CONN UNIX LOCK FILE CANT WRITE;

SQLSTATE: HY000

Message: Could not write unix socket lock file %s errno %d.

Error number: MY-010279; Symbol: ER CONN UNIX LOCK FILE CANT DELETE;

SQLSTATE: HY000

Message: Could not remove unix socket lock file %s errno %d.

Error number: MY-010280; Symbol: ER_CONN_UNIX_LOCK_FILE_CANT_SYNC;

SQLSTATE: HY000

Message: Could not sync unix socket lock file %s errno %d.

Error number: MY-010281; Symbol: ER CONN UNIX LOCK FILE CANT CLOSE;

SQLSTATE: HY000

Message: Could not close unix socket lock file %s errno %d.

Error number: MY-010282; Symbol: ER CONN SOCKET SELECT FAILED; SQLSTATE:

HY000

Message: mysqld: Got error %d from select

Error number: MY-010283; Symbol: ER CONN SOCKET ACCEPT FAILED; SQLSTATE:

HY000

Message: Error in accept: %s

Error number: MY-010284; Symbol: ER_AUTH_RSA_CANT_FIND; SQLSTATE: HY000 Message: RSA %s key file not found: %s. Some authentication plugins will not work.

Error number: MY-010285; Symbol: ER_AUTH_RSA_CANT_PARSE; SQLSTATE: HY000 Message: Failure to parse RSA %s key (file exists): %s: %s

Error number: MY-010286; Symbol: ER_AUTH_RSA_CANT_READ; SQLSTATE: HY000 Message: Failure to read key file: %s

Error number: MY-010287; Symbol: ER_AUTH_RSA_FILES_NOT_FOUND; SQLSTATE: HY000

Message: RSA key files not found. Some authentication plugins will not work.

Error number: MY-010288; Symbol: ER_CONN_ATTR_TRUNCATED; SQLSTATE: HY000 Message: Connection attributes of length %lu were truncated (%d bytes lost) for connection %llu, user %s@%s (as %s), auth: %s

Error number: MY-010289; Symbol: ER_X509_CIPHERS_MISMATCH; SQLSTATE: HY000 Message: X.509 ciphers mismatch: should be '%s' but is '%s'

Error number: MY-010290; Symbol: ER_X509_ISSUER_MISMATCH; SQLSTATE: HY000 Message: X.509 issuer mismatch: should be '%s' but is '%s'

Error number: MY-010291; Symbol: ER_X509_SUBJECT_MISMATCH; SQLSTATE: HY000 Message: X.509 subject mismatch: should be '%s' but is '%s'

Error number: MY-010292; Symbol: ER_AUTH_CANT_ACTIVATE_ROLE; SQLSTATE: HY000 Message: Failed to activate default role %s for %s

Error number: MY-010293; Symbol: ER_X509_NEEDS_RSA_PRIVKEY; SQLSTATE: HY000 Message: Could not generate RSA private key required for X.509 certificate.

Error number: MY-010294; Symbol: ER_X509_CANT_WRITE_KEY; SQLSTATE: HY000 Message: Could not write key file: %s

Error number: MY-010295; Symbol: ER_X509_CANT_CHMOD_KEY; SQLSTATE: HY000

Message: Could not set file permission for %s

Error number: MY-010296; Symbol: ER_X509_CANT_READ_CA_KEY; SQLSTATE: HY000

Message: Could not read CA key file: %s

Error number: MY-010297; Symbol: ER X509 CANT READ CA CERT; SQLSTATE: HY000

Message: Could not read CA certificate file: %s

Error number: MY-010298; Symbol: ER X509 CANT CREATE CERT; SQLSTATE: HY000

Message: Could not generate X.509 certificate.

Error number: MY-010299; Symbol: ER X509 CANT WRITE CERT; SQLSTATE: HY000

Message: Could not write certificate file: %s

Error number: MY-010300; Symbol: ER AUTH CANT CREATE RSA PAIR; SQLSTATE:

HY000

Message: Could not generate RSA Private/Public key pair

Error number: MY-010301; Symbol: ER AUTH CANT WRITE PRIVKEY; SQLSTATE: HY000

Message: Could not write private key file: %s

Error number: MY-010302; Symbol: ER AUTH CANT WRITE PUBKEY; SQLSTATE: HY000

Message: Could not write public key file: %s

Error number: MY-010303; Symbol:

ER AUTH SSL CONF PREVENTS CERT GENERATION; SQLSTATE: HY000

Message: Skipping generation of SSL certificates as options related to SSL are specified.

Error number: MY-010304; Symbol: ER AUTH USING EXISTING CERTS; SQLSTATE:

HY000

Message: Skipping generation of SSL certificates as certificate files are present in data directory.

Error number: MY-010305; Symbol: ER AUTH CERTS SAVED TO DATADIR; SQLSTATE:

HY000

Message: Auto generated SSL certificates are placed in data directory.

Error number: MY-010306; Symbol: ER AUTH CERT GENERATION DISABLED;

SQLSTATE: HY000

Message: Skipping generation of SSL certificates as --auto generate certs is set to OFF.

Error number: MY-010307; Symbol: ER AUTH RSA CONF PREVENTS KEY GENERATION;

SQLSTATE: HY000

Message: Skipping generation of RSA key pair through %s as options related to RSA keys are specified.

Error number: MY-010308; Symbol:

ER AUTH KEY GENERATION SKIPPED PAIR PRESENT; SQLSTATE: HY000

Message: Skipping generation of RSA key pair through %s as key files are present in data directory.

Error number: MY-010309; Symbol: ER_AUTH_KEYS_SAVED_TO_DATADIR; SQLSTATE: HY000

Message: Auto generated RSA key files through %s are placed in data directory.

Error number: MY-010310; Symbol: ER_AUTH_KEY_GENERATION_DISABLED; SQLSTATE: HY000

Message: Skipping generation of RSA key pair as %s is set to OFF.

Error number: MY-010311; Symbol:

ER_AUTHCACHE_PROXIES_PRIV_SKIPPED_NEEDS_RESOLVE; SQLSTATE: HY000 Message: 'proxies priv' entry '%s@%s %s@%s' ignored in --skip-name-resolve mode.

Error number: MY-010312; Symbol: ER_AUTHCACHE_PLUGIN_MISSING; SQLSTATE: HY000

Message: The plugin '%.*s' used to authenticate user '%s'@'%.*s' is not loaded. Nobody can currently login using this account.

Error number: MY-010313; Symbol: ER_AUTHCACHE_PLUGIN_CONFIG; SQLSTATE: HY000 Message: The plugin '%s' is used to authenticate user '%s'@'%.*s', %s configured. Nobody can currently login using this account.

Error number: MY-010314; Symbol: ER_AUTHCACHE_ROLE_TABLES_DODGY; SQLSTATE: HY000

Message: Could not load mysql.role_edges and mysql.default_roles tables. ACL DDLs will not work unless mysql upgrade is executed.

Error number: MY-010315; Symbol: ER_AUTHCACHE_USER_SKIPPED_NEEDS_RESOLVE; SQLSTATE: HY000

Message: 'user' entry '%s@%s' ignored in --skip-name-resolve mode.

Error number: MY-010316; Symbol: ER_AUTHCACHE_USER_TABLE_DODGY; SQLSTATE: HY000

Message: Fatal error: Could not read the column 'authentication_string' from table 'mysql.user'. Please perform the MySQL upgrade procedure.

Error number: MY-010317; Symbol:

ER_AUTHCACHE_USER_IGNORED_DEPRECATED_PASSWORD; SQLSTATE: HY000 Message: User entry '%s'@'%s' has a deprecated pre-4.1 password. The user will be ignored and no one can login with this user anymore.

Error number: MY-010318; Symbol: ER_AUTHCACHE_USER_IGNORED_NEEDS_PLUGIN; SQLSTATE: HY000

Message: User entry '%s'@'%s' has an empty plugin value. The user will be ignored and no one can login with this user anymore.

Error number: MY-010319; Symbol:

ER AUTHCACHE USER IGNORED INVALID PASSWORD; SQLSTATE: HY000

Message: Found invalid password for user: '%s@%s'; Ignoring user

Error number: MY-010320; Symbol:

ER_AUTHCACHE_EXPIRED_PASSWORD_UNSUPPORTED; SQLSTATE: HY000 Message: 'user' entry '%s@%s' has the password ignore flag raised, but its authentication plugin doesn't support password expiration. The user id will be ignored.

Error number: MY-010321; Symbol: ER_NO_SUPER_WITHOUT_USER_PLUGIN; SQLSTATE: HY000

Message: Some of the user accounts with SUPER privileges were disabled because of empty mysql.user.plugin value. If you are upgrading from MySQL 5.6 to MySQL 5.7 it means that substitution for the empty plugin column was not possible. Probably because of pre 4.1 password hash. If your account is disabled you will need to perform the MySQL upgrade procedure. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.

Error number: MY-010322; Symbol: ER AUTHCACHE DB IGNORED EMPTY NAME;

SQLSTATE: HY000

Message: Found an entry in the 'db' table with empty database name; Skipped

Error number: MY-010323; Symbol: ER_AUTHCACHE_DB_SKIPPED_NEEDS_RESOLVE;

SQLSTATE: HY000

Message: 'db' entry '%s %s@%s' ignored in --skip-name-resolve mode.

Error number: MY-010324; Symbol:

ER_AUTHCACHE_DB_ENTRY_LOWERCASED_REVOKE_WILL_FAIL; SQLSTATE: HY000 Message: 'db' entry '%s %s@%s' had database in mixed case that has been forced to lowercase because lower_case_table_names is set. It will not be possible to remove this privilege using REVOKE.

Error number: MY-010325; Symbol: ER_AUTHCACHE_TABLE_PROXIES_PRIV_MISSING; SQLSTATE: HY000

Message: The system table mysql.proxies_priv is missing. Please perform the MySQL upgrade procedure.

Error number: MY-010326; Symbol:

ER AUTHCACHE CANT OPEN AND LOCK PRIVILEGE TABLES; SQLSTATE: HY000

Message: Fatal error: Can't open and lock privilege tables: %s

Error number: MY-010327; Symbol: ER AUTHCACHE CANT INIT GRANT SUBSYSTEM;

SQLSTATE: HY000

Message: Fatal: can't initialize grant subsystem - '%s'

Error number: MY-010328; Symbol:

ER AUTHCACHE PROCS PRIV SKIPPED NEEDS RESOLVE; SQLSTATE: HY000

Message: 'procs priv' entry '%s %s@%s' ignored in --skip-name-resolve mode.

Error number: MY-010329; Symbol:

 $ER_AUTHCACHE_PROCS_PRIV_ENTRY_IGNORED_BAD_ROUTINE_TYPE; SQLSTATE:$

HY000

Message: 'procs priv' entry '%s' ignored, bad routine type

Error number: MY-010330; Symbol:

ER AUTHCACHE TABLES PRIV SKIPPED NEEDS RESOLVE; SQLSTATE: HY000

Message: 'tables_priv' entry '%s %s@%s' ignored in --skip-name-resolve mode.

Error number: MY-010331; Symbol:

ER_USER_NOT_IN_EXTRA_USERS_BINLOG_POSSIBLY_INCOMPLETE; SQLSTATE:

HY000

Message: Failed to add %s in extra users. Binary log entry may miss some of the users.

Error number: MY-010332; Symbol: ER DD SCHEMA NOT FOUND; SQLSTATE: HY000

Message: Unable to start server. The data dictionary schema '%s' does not exist.

Error number: MY-010333; Symbol: ER DD TABLE NOT FOUND; SQLSTATE: HY000

Message: Unable to start server. The data dictionary table '%s' does not exist.

Error number: MY-010334; Symbol: ER DD SE INIT FAILED; SQLSTATE: HY000

Message: Failed to initialize DD Storage Engine

Error number: MY-010335; Symbol: ER_DD_ABORTING_PARTIAL_UPGRADE; SQLSTATE:

HY000

Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the upgrade process again.

Error number: MY-010336; Symbol: ER_DD_FRM_EXISTS_FOR_TABLE; SQLSTATE: HY000 Message: Found .frm file with same name as one of the Dictionary Tables.

Error number: MY-010337; Symbol: ER_DD_CREATED_FOR_UPGRADE; SQLSTATE: HY000 Message: Created Data Dictionary for upgrade

Error number: MY-010338; Symbol: ER_ERRMSG_CANT_FIND_FILE; SQLSTATE: HY000 Message: Can't find error-Message file '%s'. Check error-Message file location and 'lc-Messages-dir' configuration directive.

Error number: MY-010339; Symbol: ER_ERRMSG_LOADING_55_STYLE; SQLSTATE: HY000 Message: Using pre 5.5 semantics to load error Messages from %s. If this is not intended, refer to the documentation for valid usage of --lc-Messages-dir and --language parameters.

Error number: MY-010340; Symbol: ER_ERRMSG_MISSING_IN_FILE; SQLSTATE: HY000 Message: Error Message file '%s' had only %d error Messages, but it should contain at least %d error Messages. Check that the above file is the right version for this program!

Error number: MY-010341; Symbol: ER_ERRMSG_OOM; SQLSTATE: HY000 Message: Not enough memory for Messagefile '%s'

Error number: MY-010342; Symbol: ER_ERRMSG_CANT_READ; SQLSTATE: HY000 Message: Can't read from Messagefile '%s'

Error number: MY-010343; Symbol: ER_TABLE_INCOMPATIBLE_DECIMAL_FIELD; SQLSTATE: HY000

Message: Found incompatible DECIMAL field '%s' in %s; Please do "ALTER TABLE `%s` FORCE" to fix it!

Error number: MY-010344; Symbol: ER_TABLE_INCOMPATIBLE_YEAR_FIELD; SQLSTATE: HY000

Message: Found incompatible YEAR(x) field '%s' in %s; Please do "ALTER TABLE `%s` FORCE" to fix it!

Error number: MY-010345; Symbol: ER_INVALID_CHARSET_AND_DEFAULT_IS_MB; SQLSTATE: HY000

Message: '%s' had no or invalid character set, and default character set is multi-byte, so character column sizes may have changed

Error number: MY-010346; Symbol: ER_TABLE_WRONG_KEY_DEFINITION; SQLSTATE:

Message: Found wrong key definition in %s; Please do "ALTER TABLE `%s` FORCE " to fix it!

Error number: MY-010347; Symbol: ER_CANT_OPEN_FRM_FILE; SQLSTATE: HY000 Message: Unable to open file %s

Error number: MY-010348; Symbol: ER_CANT_READ_FRM_FILE; SQLSTATE: HY000 Message: Error in reading file %s

Error number: MY-010349; Symbol: ER_TABLE_CREATED_WITH_DIFFERENT_VERSION; SQLSTATE: HY000

Message: Table '%s' was created with a different version of MySQL and cannot be read

Error number: MY-010350; Symbol: ER_VIEW_UNPARSABLE; SQLSTATE: HY000 Message: Unable to read view %s

Error number: MY-010351; Symbol: ER_FILE_TYPE_UNKNOWN; SQLSTATE: HY000 Message: File %s has unknown type in its header.

Error number: MY-010352; Symbol: ER_INVALID_INFO_IN_FRM; SQLSTATE: HY000 Message: Incorrect information in file %s

Error number: MY-010353; Symbol: ER_CANT_OPEN_AND_LOCK_PRIVILEGE_TABLES; SOLSTATE: HY000

Message: Can't open and lock privilege tables: %s

Error number: MY-010354; Symbol:

ER_AUDIT_PLUGIN_DOES_NOT_SUPPORT_AUDIT_AUTH_EVENTS; SQLSTATE: HY000 Message: Plugin '%s' cannot subscribe to MYSQL_AUDIT_AUTHORIZATION events. Currently not supported.

Error number: MY-010355; Symbol: ER_AUDIT_PLUGIN_HAS_INVALID_DATA; SQLSTATE: HY000

Message: Plugin '%s' has invalid data.

Error number: MY-010356; Symbol: ER_TZ_OOM_INITIALIZING_TIME_ZONES; SQLSTATE: HY000

Message: Fatal error: OOM while initializing time zones

Error number: MY-010357; Symbol: ER_TZ_CANT_OPEN_AND_LOCK_TIME_ZONE_TABLE; SQLSTATE: HY000

Message: Can't open and lock time zone table: %s trying to live without them

Error number: MY-010358; Symbol: ER TZ OOM LOADING LEAP SECOND TABLE;

SQLSTATE: HY000

Message: Fatal error: Out of memory while loading mysql.time zone leap second table

Error number: MY-010359; Symbol:

ER TZ TOO MANY LEAPS IN LEAP SECOND TABLE; SQLSTATE: HY000 Message: Fatal error: While loading mysql.time zone leap second table: too much leaps

Error number: MY-010360; Symbol: ER TZ ERROR LOADING LEAP SECOND TABLE;

SQLSTATE: HY000

Message: Fatal error: Error while loading mysql.time zone leap second table

Error number: MY-010361; Symbol:

ER TZ UNKNOWN OR ILLEGAL DEFAULT TIME ZONE; SQLSTATE: HY000

Message: Fatal error: Illegal or unknown default time zone '%s'

Error number: MY-010362; Symbol: ER_TZ_CANT_FIND_DESCRIPTION FOR TIME ZONE;

SQLSTATE: HY000

Message: Can't find description of time zone '%.*s'

Error number: MY-010363; Symbol:

ER TZ CANT FIND DESCRIPTION FOR TIME ZONE ID; SQLSTATE: HY000

Message: Can't find description of time zone '%u'

Error number: MY-010364; Symbol:

ER TZ TRANSITION TYPE TABLE TYPE TOO LARGE; SQLSTATE: HY000

Message: Error while loading time zone description from mysql.time zone transition type table: too

big transition type id

Error number: MY-010365; Symbol:

ER TZ TRANSITION TYPE TABLE ABBREVIATIONS EXCEED SPACE; SQLSTATE:

HY000

Message: Error while loading time zone description from mysql.time zone transition type table: not

enough room for abbreviations

Error number: MY-010366; Symbol: ER TZ TRANSITION TYPE TABLE LOAD ERROR;

SQLSTATE: HY000

Message: Error while loading time zone description from mysql.time zone transition type table

密级: 公开 文档版本() 192

Error number: MY-010367; Symbol:

ER TZ TRANSITION TABLE TOO MANY TRANSITIONS; SQLSTATE: HY000

Message: Error while loading time zone description from mysql.time zone transition table: too

much transitions

Error number: MY-010368; Symbol:

ER TZ TRANSITION TABLE BAD TRANSITION TYPE; SQLSTATE: HY000

Message: Error while loading time zone description from mysql.time zone transition table: bad

transition type id

Error number: MY-010369; Symbol: ER TZ TRANSITION TABLE LOAD ERROR;

SQLSTATE: HY000

Message: Error while loading time zone description from mysql.time zone transition table

Error number: MY-010370; Symbol: ER TZ NO TRANSITION TYPES IN TIME ZONE;

SQLSTATE: HY000

Message: loading time zone without transition types

Error number: MY-010371; Symbol: ER TZ OOM LOADING TIME ZONE DESCRIPTION;

SQLSTATE: HY000

Message: Out of memory while loading time zone description

Error number: MY-010372; Symbol: ER TZ CANT BUILD MKTIME MAP; SQLSTATE:

HY000

Message: Unable to build mktime map for time zone

Error number: MY-010373; Symbol: ER TZ OOM WHILE LOADING TIME ZONE;

SOLSTATE: HY000

Message: Out of memory while loading time zone

Error number: MY-010374; Symbol: ER TZ OOM WHILE SETTING TIME ZONE;

SQLSTATE: HY000

Message: Fatal error: Out of memory while setting new time zone

Error number: MY-010375; Symbol:

ER SLAVE SQL THREAD STOPPED UNTIL CONDITION BAD; SQLSTATE: HY000

Message: Slave SQL thread is stopped because UNTIL condition is bad(%s:%llu).

Error number: MY-010376; Symbol:

ER_SLAVE_SQL_THREAD_STOPPED_UNTIL_POSITION_REACHED; SQLSTATE: HY000

Message: Slave SQL thread stopped because it reached its UNTIL position %llu

Error number: MY-010377; Symbol:

 $ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_ALREADY_APPLIED; SQLSTATE:$

HY000

Message: Slave SQL thread stopped because UNTIL SQL BEFORE GTIDS %s is already applied

Error number: MY-010378; Symbol:

ER_SLAVE_SQL_THREAD_STOPPED_BEFORE_GTIDS_REACHED; SQLSTATE: HY000 Message: Slave SQL thread stopped because it reached UNTIL SQL BEFORE GTIDS %s

Error number: MY-010379; Symbol:

ER_SLAVE_SQL_THREAD_STOPPED_AFTER_GTIDS_REACHED; SQLSTATE: HY000 Message: Slave SQL thread stopped because it reached UNTIL SQL_AFTER_GTIDS %s

Error number: MY-010380; Symbol:

ER_SLAVE_SQL_THREAD_STOPPED_GAP_TRX_PROCESSED; SQLSTATE: HY000 Message: Slave SQL thread stopped according to UNTIL SQL_AFTER_MTS_GAPS as it has processed all gap transactions left from the previous slave session.

Error number: MY-010381; Symbol: ER_GROUP_REPLICATION_PLUGIN_NOT_INSTALLED; SQLSTATE: HY000

Message: Group Replication plugin is not installed.

Error number: MY-010382; Symbol: ER_GTID_ALREADY_ADDED_BY_USER; SQLSTATE: HY000

Message: The transaction owned GTID is already in the %s table, which is caused by an explicit modifying from user client.

Error number: MY-010383; Symbol:

ER_FAILED_TO_DELETE_FROM_GTID_EXECUTED_TABLE; SQLSTATE: HY000

Message: Failed to delete the row: '%s' from the gtid executed table.

Error number: MY-010384; Symbol: ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE;

SQLSTATE: HY000

Message: Failed to compress the gtid_executed table.

Error number: MY-010385; Symbol:

ER_FAILED_TO_COMPRESS_GTID_EXECUTED_TABLE_OOM; SQLSTATE: HY000 Message: Failed to compress the gtid_executed table, because it is failed to allocate the THD.

Error number: MY-010386; Symbol:

 $\label{eq:compression} ER_FAILED_TO_INIT_THREAD_ATTR_FOR_GTID_TABLE_COMPRESSION; SQLSTATE: HY000$

Message: Failed to initialize thread attribute when creating compression thread.

Error number: MY-010387; Symbol:

ER FAILED TO CREATE GTID TABLE COMPRESSION THREAD; SQLSTATE: HY000

Message: Can not create thread to compress gtid executed table (errno= %d)

Error number: MY-010388; Symbol:

ER FAILED TO JOIN GTID TABLE COMPRESSION THREAD; SQLSTATE: HY000

Message: Could not join gtid executed table compression thread. error:%d

Error number: MY-010389; Symbol: ER NPIPE FAILED TO INIT SECURITY DESCRIPTOR;

SQLSTATE: HY000

Message: Can't start server: Initialize security descriptor: %s

Error number: MY-010390; Symbol: ER_NPIPE_FAILED_TO_SET_SECURITY_DESCRIPTOR;

SQLSTATE: HY000

Message: Can't start server : Set security descriptor: %s

Error number: MY-010391; Symbol: ER_NPIPE_PIPE ALREADY IN USE; SQLSTATE: HY000

Message: Can't start server : Named Pipe "%s" already in use.

Error number: MY-010405; Symbol: ER RPL CANT OPEN INFO TABLE; SQLSTATE: HY000

Message: Info table is not ready to be used. Table '%s.%s' cannot be opened.

Error number: MY-010406; Symbol: ER RPL CANT SCAN INFO TABLE; SQLSTATE: HY000

Message: Info table is not ready to be used. Table '%s.%s' cannot be scanned.

Error number: MY-010407; Symbol: ER RPL CORRUPTED INFO TABLE; SQLSTATE:

HY000

Message: Corrupted table %s.%s. Check out table definition.

Error number: MY-010408; Symbol: ER RPL CORRUPTED KEYS IN INFO TABLE;

SQLSTATE: HY000

Message: Info table has a problem with its key field(s). Table '%s.%s' expected field #%u to be '%s'

but found '%s' instead.

Error number: MY-010409; Symbol: ER RPL WORKER ID IS; SQLSTATE: HY000

Message: Choosing worker id %lu, the following is going to be %lu

Error number: MY-010410; Symbol: ER RPL INCONSISTENT TIMESTAMPS IN TRX;

SQLSTATE: HY000

Message: Transaction is tagged with inconsistent logical timestamps: sequence_number (%lld) <= last committed (%lld)

Error number: MY-010411; Symbol: ER RPL INCONSISTENT SEQUENCE NO IN TRX;

SQLSTATE: HY000

Message: Transaction's sequence number is inconsistent with that of a preceding one:

sequence number (%lld) <= previous sequence number (%lld)

Error number: MY-010412; Symbol:

ER_RPL_CHANNELS_REQUIRE_TABLES_AS_INFO_REPOSITORIES; SQLSTATE: HY000 Message: For the creation of replication channels the master info and relay log info repositories must

be set to TABLE

Error number: MY-010413; Symbol:

ER_RPL_CHANNELS_REQUIRE_NON_ZERO_SERVER_ID; SQLSTATE: HY000 Message: For the creation of replication channels the server id must be different from 0

Error number: MY-010414; Symbol: ER RPL REPO SHOULD BE TABLE; SQLSTATE:

HY000

Message: Slave: Wrong repository. Repository should be TABLE

Error number: MY-010415; Symbol: ER_RPL_ERROR_CREATING_MASTER_INFO;

SOLSTATE: HY000

Message: Error creating master info: %s.

Error number: MY-010416; Symbol:

ER RPL ERROR CHANGING MASTER INFO REPO TYPE; SQLSTATE: HY000

Message: Error changing the type of master info's repository: %s.

Error number: MY-010417; Symbol:

ER_RPL_CHANGING_RELAY_LOG_INFO_REPO_TYPE_FAILED_DUE_TO_GAPS;

SQLSTATE: HY000

Message: It is not possible to change the type of the relay log repository because there are workers repositories with possible execution gaps. The value of --relay_log_info_repository is altered to one of the found Worker repositories. The gaps have to be sorted out before resuming with the type change.

Error number: MY-010418; Symbol: ER RPL ERROR CREATING RELAY LOG INFO;

SQLSTATE: HY000

Message: Error creating relay log info: %s.

Error number: MY-010419; Symbol:

ER RPL ERROR CHANGING RELAY LOG INFO REPO TYPE; SQLSTATE: HY000

Message: Error changing the type of relay log info's repository: %s.

Error number: MY-010420; Symbol:

ER RPL FAILED TO DELETE FROM SLAVE WORKERS INFO REPOSITORY;

SQLSTATE: HY000

Message: Could not delete from Slave Workers info repository.

Error number: MY-010421; Symbol:

ER RPL FAILED TO RESET STATE IN SLAVE INFO REPOSITORY; SQLSTATE: HY000

Message: Could not store the reset Slave Worker state into the slave info repository.

Error number: MY-010422; Symbol: ER RPL ERROR CHECKING REPOSITORY;

SQLSTATE: HY000

Message: Error in checking %s repository info type of %s.

Error number: MY-010423; Symbol: ER RPL SLAVE GENERIC MESSAGE; SQLSTATE:

HY000

Message: Slave: %s

Error number: MY-010424; Symbol:

ER RPL SLAVE COULD NOT CREATE CHANNEL LIST; SQLSTATE: HY000

Message: Slave: Could not create channel list

Error number: MY-010425; Symbol:

ER_RPL_MULTISOURCE_REQUIRES_TABLE_TYPE_REPOSITORIES; SQLSTATE: HY000 Message: Slave: This slave was a multisourced slave previously which is supported only by both TABLE based master info and relay log info repositories. Found one or both of the info repos to be type FILE. Set both repos to type TABLE.

Error number: MY-010426; Symbol:

ER_RPL_SLAVE_FAILED_TO_INIT_A_MASTER_INFO_STRUCTURE; SQLSTATE: HY000 Message: Slave: Failed to initialize the master info structure for channel '%s'; its record may still be present in 'mysql.slave master info' table, consider deleting it.

Error number: MY-010427; Symbol:

ER RPL SLAVE FAILED TO INIT MASTER INFO STRUCTURE; SQLSTATE: HY000

Message: Failed to initialize the master info structure%s

Error number: MY-010428; Symbol:

ER RPL SLAVE FAILED TO CREATE CHANNEL FROM MASTER INFO; SQLSTATE:

HY000

Message: Slave: Failed to create a channel from master info table repository.

Error number: MY-010429; Symbol: ER RPL FAILED TO CREATE NEW INFO FILE;

SQLSTATE: HY000

Message: Failed to create a new info file (file '%s', errno %d)

Error number: MY-010430; Symbol:

ER RPL FAILED TO CREATE CACHE FOR INFO FILE; SQLSTATE: HY000

Message: Failed to create a cache on info file (file '%s')

Error number: MY-010431; Symbol: ER RPL FAILED TO OPEN INFO FILE; SQLSTATE:

HY000

Message: Failed to open the existing info file (file '%s', errno %d)

Error number: MY-010432; Symbol: ER_RPL_GTID_MEMORY_FINALLY_AVAILABLE;

SQLSTATE: HY000

Message: Server overcomes the temporary 'out of memory' in '%d' tries while allocating a new chunk

of intervals for storing GTIDs.

Error number: MY-010433; Symbol: ER SERVER COST UNKNOWN COST CONSTANT;

SQLSTATE: HY000

Message: Unknown cost constant "%s" in mysql.server cost table

Error number: MY-010434; Symbol: ER SERVER COST INVALID COST CONSTANT;

SOLSTATE: HY000

Message: Invalid value for cost constant "%s" in mysql.server cost table: %.1f

Error number: MY-010435; Symbol: ER ENGINE COST UNKNOWN COST CONSTANT;

SQLSTATE: HY000

Message: Unknown cost constant "%s" in mysql.engine_cost table

Error number: MY-010436; Symbol: ER ENGINE COST UNKNOWN STORAGE ENGINE;

SQLSTATE: HY000

Message: Unknown storage engine "%s" in mysql.engine cost table

Error number: MY-010437; Symbol: ER ENGINE COST INVALID DEVICE TYPE FOR SE;

SOLSTATE: HY000

Message: Invalid device type %d for "%s" storage engine for cost constant "%s" in

mysql.engine cost table

Error number: MY-010438; Symbol:

 $ER_ENGINE_COST_INVALID_CONST_CONSTANT_FOR_SE_AND_DEVICE; SQLSTATE:$

HY000

Message: Invalid value for cost constant "%s" for "%s" storage engine and device type %d in

mysql.engine cost table: %.1f

Error number: MY-010439; Symbol: ER_SERVER_COST_FAILED_TO_READ; SQLSTATE:

HY000

Message: Error while reading from mysql.server cost table.

Error number: MY-010440; Symbol: ER ENGINE COST FAILED TO READ; SQLSTATE:

HY000

Message: Error while reading from mysql.engine cost table.

Error number: MY-010441; Symbol: ER_FAILED_TO_OPEN_COST_CONSTANT_TABLES;

SQLSTATE: HY000

Message: Failed to open optimizer cost constant tables

2.7 错误码及错误信息汇总 07

Error number: MY-010442; Symbol:

ER RPL UNSUPPORTED UNIGNORABLE EVENT IN STREAM; SQLSTATE: HY000

Message: Unsupported non-ignorable event fed into the event stream.

Error number: MY-010443; Symbol: ER_RPL_GTID_LOG_EVENT_IN_STREAM; SQLSTATE:

HY000

Message: GTID LOG EVENT or ANONYMOUS GTID LOG EVENT is not expected in an

event stream %s.

Error number: MY-010444; Symbol: ER RPL UNEXPECTED BEGIN IN STREAM;

SOLSTATE: HY000

Message: QUERY(BEGIN) is not expected in an event stream in the middle of a %s.

Error number: MY-010445; Symbol:

ER RPL UNEXPECTED COMMIT ROLLBACK OR XID LOG EVENT IN STREAM;

SQLSTATE: HY000

Message: QUERY(COMMIT or ROLLBACK) or XID LOG EVENT is not expected in an event

stream %s.

Error number: MY-010446; Symbol: ER RPL UNEXPECTED XA ROLLBACK IN STREAM;

SQLSTATE: HY000

Message: QUERY(XA ROLLBACK) is not expected in an event stream %s.

Error number: MY-010447; Symbol:

ER EVENT EXECUTION FAILED CANT AUTHENTICATE USER; SQLSTATE: HY000

Message: Event Scheduler: [%s].[%s.%s] execution failed, failed to authenticate the user.

Error number: MY-010448; Symbol:

ER_EVENT_EXECUTION_FAILED_USER_LOST_EVEN_PRIVILEGE; SQLSTATE: HY000 Message: Event Scheduler: [%s].[%s.%s] execution failed, user no longer has EVENT privilege.

Error number: MY-010449; Symbol: ER EVENT ERROR DURING COMPILATION;

SQLSTATE: HY000

Message: Event Scheduler: %serror during compilation of %s.%s

Error number: MY-010450; Symbol: ER_EVENT_DROPPING; SQLSTATE: HY000

Message: Event Scheduler: Dropping %s.%s

Error number: MY-010452; Symbol: ER RPL INCOMPATIBLE DECIMAL IN RBR;

SQLSTATE: HY000

Message: In RBR mode, Slave received incompatible DECIMAL field (old-style decimal field) from Master while creating conversion table. Please consider changing datatype on Master to new style decimal by executing ALTER command for column Name: %s.%s.%s.

Error number: MY-010453; Symbol: ER_INIT_ROOT_WITHOUT_PASSWORD; SQLSTATE: HY000

Message: root@localhost is created with an empty password! Please consider switching off the -- initialize-insecure option.

Error number: MY-010454; Symbol:

ER INIT GENERATING TEMP PASSWORD FOR ROOT; SQLSTATE: HY000

Message: A temporary password is generated for root@localhost: %s

Error number: MY-010455; Symbol: ER_INIT_CANT_OPEN_BOOTSTRAP_FILE; SQLSTATE:

HY000

Message: Failed to open the bootstrap file %s

Error number: MY-010456; Symbol: ER_INIT_BOOTSTRAP_COMPLETE; SQLSTATE: HY000

Message: Bootstrapping complete

Error number: MY-010457; Symbol: ER_INIT_DATADIR_NOT_EMPTY_WONT_INITIALIZE;

SOLSTATE: HY000

Message: --initialize specified but the data directory has files in it. Aborting.

Error number: MY-010458; Symbol: ER INIT DATADIR EXISTS WONT INITIALIZE;

SQLSTATE: HY000

Message: --initialize specified on an existing data directory.

Error number: MY-010459; Symbol:

ER INIT DATADIR EXISTS AND PATH TOO LONG WONT INITIALIZE; SQLSTATE:

HY000

Message: --initialize specified but the data directory exists and the path is too long. Aborting.

Error number: MY-010460; Symbol:

ER INIT DATADIR EXISTS AND NOT WRITABLE WONT INITIALIZE; SQLSTATE:

HY000

Message: --initialize specified but the data directory exists and is not writable. Aborting.

Error number: MY-010461; Symbol: ER INIT CREATING DD; SQLSTATE: HY000

Message: Creating the data directory %s

Error number: MY-010462; Symbol: ER RPL BINLOG STARTING DUMP; SQLSTATE:

HY000

Message: Start binlog dump to master thread id(%u) slave server(%u), pos(%s, %llu)

Error number: MY-010463; Symbol: ER RPL BINLOG MASTER SENDS HEARTBEAT;

SQLSTATE: HY000

Message: master sends heartbeat Message

Error number: MY-010464; Symbol:

ER RPL BINLOG SKIPPING REMAINING HEARTBEAT INFO; SQLSTATE: HY000

Message: the rest of heartbeat info skipped ...

Error number: MY-010465; Symbol:

ER RPL BINLOG MASTER USES CHECKSUM AND SLAVE CANT; SQLSTATE: HY000

Message: Master is configured to log replication events with checksum, but will not send such events

to slaves that cannot process them

Error number: MY-010467; Symbol: ER KILLING THREAD; SQLSTATE: HY000

Message: Killing thread %lu

Error number: MY-010468; Symbol: ER DETACHING SESSION LEFT BY PLUGIN;

SQLSTATE: HY000

Message: Plugin %s is deinitializing a thread but left a session attached. Detaching it forcefully.

Error number: MY-010469; Symbol: ER CANT DETACH SESSION LEFT BY PLUGIN;

SOLSTATE: HY000

Message: Failed to detach the session.

Error number: MY-010470; Symbol: ER DETACHED SESSIONS LEFT BY PLUGIN;

SQLSTATE: HY000

Message: Closed forcefully %u session%s left opened by plugin %s

Error number: MY-010471; Symbol:

ER FAILED TO DECREMENT_NUMBER_OF_THREADS; SQLSTATE: HY000

Message: Failed to decrement the number of threads

Error number: MY-010472; Symbol: ER PLUGIN DID NOT DEINITIALIZE THREADS;

SQLSTATE: HY000

Message: Plugin %s did not deinitialize %u threads

Error number: MY-010473; Symbol: ER KILLED THREADS OF PLUGIN; SQLSTATE: HY000

Message: Killed %u threads of plugin %s

Error number: MY-010517; Symbol: ER DBUG CHECK SHARES OPEN; SQLSTATE: HY000

Message: dbug check shares open:

Error number: MY-010518; Symbol: ER DBUG CHECK SHARES INFO; SQLSTATE: HY000

Message: %s.%s: state: %s(%u) use count: %u

Error number: MY-010519; Symbol: ER DBUG CHECK SHARES DROPPED; SQLSTATE:

HY000

Message: dbug check shares dropped:

Error number: MY-010520; Symbol: ER INVALID OR OLD TABLE OR DB NAME;

SQLSTATE: HY000

Message: Invalid (old?) table or database name '%s'

Error number: MY-010521; Symbol: ER TC RECOVERING AFTER CRASH USING;

SQLSTATE: HY000

Message: Recovering after a crash using %s

Error number: MY-010522; Symbol:

ER_TC_CANT_AUTO_RECOVER_WITH_TC_HEURISTIC_RECOVER; SQLSTATE: HY000

Message: Cannot perform automatic crash recovery when --tc-heuristic-recover is used

Error number: MY-010523; Symbol: ER TC BAD MAGIC IN TC LOG; SQLSTATE: HY000

Message: Bad magic header in tc log

Error number: MY-010524; Symbol:

ER TC NEED N SE SUPPORTING 2PC FOR RECOVERY; SQLSTATE: HY000

Message: Recovery failed! You must enable exactly %d storage engines that support two-phase

commit protocol

Error number: MY-010525; Symbol:

ER TC RECOVERY FAILED THESE ARE YOUR OPTIONS; SQLSTATE: HY000

Message: Crash recovery failed. Either correct the problem (if it's, for example, out of memory error)

and restart, or delete to log and start mysqld with --tc-heuristic-recover={commit|rollback}

Error number: MY-010526; Symbol: ER TC HEURISTIC RECOVERY MODE; SQLSTATE:

HY000

Message: Heuristic crash recovery mode

Error number: MY-010527; Symbol: ER TC HEURISTIC RECOVERY FAILED; SQLSTATE:

HY000

Message: Heuristic crash recovery failed

Error number: MY-010528; Symbol:

ER TC RESTART WITHOUT TC HEURISTIC RECOVER; SQLSTATE: HY000

Message: Please restart mysqld without --tc-heuristic-recover

Error number: MY-010529; Symbol:

ER RPL SLAVE FAILED TO CREATE OR RECOVER INFO REPOSITORIES;

SQLSTATE: HY000

Message: Failed to create or recover replication info repositories.

Error number: MY-010530; Symbol:

ER RPL SLAVE AUTO POSITION IS 1 AND GTID MODE IS OFF; SQLSTATE: HY000

Message: Detected misconfiguration: replication channel '%s' was configured with

AUTO_POSITION = 1, but the server was started with --gtid-mode=off. Either reconfigure

replication using CHANGE MASTER TO MASTER_AUTO_POSITION = 0 FOR CHANNEL '%s',

or change GTID MODE to some value other than OFF, before starting the slave receiver thread.

Error number: MY-010531; Symbol:

ER RPL SLAVE CANT START SLAVE FOR CHANNEL; SQLSTATE: HY000

Message: Slave: Could not start slave for channel '%s'. operation discontinued

Error number: MY-010532; Symbol: ER RPL SLAVE CANT STOP SLAVE FOR CHANNEL;

SQLSTATE: HY000

Message: Slave: Could not stop slave for channel '%s' operation discontinued

Error number: MY-010533; Symbol:

ER_RPL_RECOVERY_NO_ROTATE_EVENT_FROM_MASTER; SQLSTATE: HY000 Message: Error during --relay-log-recovery: Could not locate rotate event from the master.

Error number: MY-010534; Symbol: ER RPL RECOVERY ERROR READ RELAY LOG;

SQLSTATE: HY000

Message: Error during --relay-log-recovery: Error reading events from relay log: %d

Error number: MY-010535; Symbol: ER RPL RECOVERY ERROR FREEING IO CACHE;

SQLSTATE: HY000

Message: Error during --relay-log-recovery: Error while freeing IO CACHE object

Error number: MY-010536; Symbol:

ER RPL RECOVERY SKIPPED GROUP REPLICATION CHANNEL; SQLSTATE: HY000

Message: Relay log recovery skipped for group replication channel.

Error number: MY-010537; Symbol: ER RPL RECOVERY ERROR; SQLSTATE: HY000

Message: Error during --relay-log-recovery: %s

Error number: MY-010538; Symbol:

ER_RPL_RECOVERY_IO_ERROR_READING_RELAY_LOG_INDEX; SQLSTATE: HY000

Message: Error during --relay-log-recovery: Could not read relay log index file due to an IO error.

Error number: MY-010539; Symbol: ER RPL RECOVERY FILE MASTER POS INFO;

SQLSTATE: HY000

Message: Recovery from master pos %ld and file %s%s. Previous relay log pos and relay log file had

been set to %lld, %s respectively.

Error number: MY-010540; Symbol:

ER RPL RECOVERY REPLICATE SAME SERVER ID REQUIRES POSITION;

SQLSTATE: HY000

Message: Error during --relay-log-recovery: replicate same server id is in use and sql thread's

positions are not initialized, hence relay log recovery cannot happen.

Error number: MY-010541; Symbol: ER RPL MTS RECOVERY STARTING COORDINATOR;

SQLSTATE: HY000

Message: MTS recovery: starting coordinator thread to fill MTS gaps.

Error number: MY-010542; Symbol:

ER RPL MTS RECOVERY FAILED TO START COORDINATOR; SQLSTATE: HY000

Message: MTS recovery: failed to start the coordinator thread. Check the error log for additional details.

Error number: MY-010543; Symbol: ER_RPL_MTS_AUTOMATIC_RECOVERY_FAILED; SOLSTATE: HY000

Message: MTS recovery: automatic recovery failed. Either the slave server had stopped due to an error during an earlier session or relay logs are corrupted. Fix the cause of the slave side error and restart the slave server or consider using RESET SLAVE.

Error number: MY-010544; Symbol: ER_RPL_MTS_RECOVERY_CANT_OPEN_RELAY_LOG; SQLSTATE: HY000

Message: Failed to open the relay log '%s' (relay_log_pos %s).

Error number: MY-010545; Symbol: ER_RPL_MTS_RECOVERY_SUCCESSFUL; SQLSTATE: HY000

Message: MTS recovery: completed successfully.

Error number: MY-010546; Symbol: ER_RPL_SERVER_ID_MISSING; SQLSTATE: HY000 Message: Server id not set, will not start slave%s

Error number: MY-010547; Symbol: ER_RPL_CANT_CREATE_SLAVE_THREAD; SQLSTATE: HY000

Message: Can't create slave thread%s.

Error number: MY-010548; Symbol: ER_RPL_SLAVE_IO_THREAD_WAS_KILLED;

SQLSTATE: HY000

Message: The slave IO thread%s was killed while executing initialization query '%s'

Error number: MY-010549; Symbol: ER_RPL_SLAVE_MASTER_UUID_HAS_CHANGED;

SQLSTATE: HY000

Message: The master's UUID has changed, although this should not happen unless you have changed it manually. The old UUID was %s.

Error number: MY-010550; Symbol:

ER RPL SLAVE USES CHECKSUM AND MASTER PRE 50; SQLSTATE: HY000

Message: Found a master with MySQL server version older than 5.0. With checksums enabled on the slave, replication might not work correctly. To ensure correct replication, restart the slave server with --replica_sql_verify_checksum=0.

Error number: MY-010551; Symbol:

ER RPL SLAVE SECONDS BEHIND MASTER DUBIOUS; SQLSTATE: HY000

Message: "SELECT UNIX_TIMESTAMP()" failed on master, do not trust column Seconds Behind Master of SHOW SLAVE STATUS. Error: %s (%d)

Error number: MY-010552; Symbol: ER RPL SLAVE CANT FLUSH MASTER INFO FILE;

SQLSTATE: HY000

Message: Failed to flush master info file.

Error number: MY-010553; Symbol: ER RPL SLAVE REPORT HOST TOO LONG;

SQLSTATE: HY000

Message: The length of report_host is %zu. It is larger than the max length(%d), so this slave cannot

be registered to the master%s.

Error number: MY-010554; Symbol: ER RPL SLAVE REPORT USER TOO LONG;

SQLSTATE: HY000

Message: The length of report_user is %zu. It is larger than the max length(%d), so this slave cannot

be registered to the master%s.

Error number: MY-010555; Symbol: ER RPL SLAVE REPORT PASSWORD TOO LONG;

SQLSTATE: HY000

Message: The length of report password is %zu. It is larger than the max length(%d), so this slave

cannot be registered to the master%s.

Error number: MY-010556; Symbol: ER RPL SLAVE ERROR RETRYING; SQLSTATE:

HY000

Message: Error on %s: %d %s, will retry in %d secs

Error number: MY-010557; Symbol: ER_RPL_SLAVE_ERROR_READING_FROM_SERVER;

SOLSTATE: HY000

Message: Error reading packet from server%s: %s (server errno=%d)

Error number: MY-010558; Symbol:

ER RPL SLAVE DUMP THREAD KILLED BY MASTER; SQLSTATE: HY000

Message: Slave%s: received end packet from server due to dump thread being killed on master.

Dump threads are killed for example during master shutdown, explicitly by a user, or when the

master receives a binlog send request from a duplicate server UUID <%s>: Error %s

Error number: MY-010559; Symbol: ER RPL MTS STATISTICS; SQLSTATE: HY000

Message: Multi-threaded slave statistics%s: seconds elapsed = %lu; events assigned = %llu; worker queues filled over overrun level = %lu; waited due a Worker queue full = %lu; waited due the total size = %lu; waited at clock conflicts = %llu waited (count) when Workers occupied = %lu waited when Workers occupied = %llu

Error number: MY-010560; Symbol: ER_RPL_MTS_RECOVERY_COMPLETE; SQLSTATE: HY000

Message: Slave%s: MTS Recovery has completed at relay log %s, position %llu master log %s, position %llu.

 $Error\ number:\ MY-010561;\ Symbol:\ ER_RPL_SLAVE_CANT_INIT_RELAY_LOG_POSITION;$

SQLSTATE: HY000

Message: Error initializing relay log position%s: %s

Error number: MY-010562; Symbol:

ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION_STARTED; SQLSTATE: HY000

Message: Slave I/O thread%s: connected to master '%s@%s:%d',replication started in log '%s' at position %s

Error number: MY-010563; Symbol: ER_RPL_SLAVE_IO_THREAD_KILLED; SQLSTATE:

HY000

Message: Slave I/O thread%s killed while connecting to master

Error number: MY-010564; Symbol:

ER RPL SLAVE IO THREAD CANT REGISTER ON MASTER; SQLSTATE: HY000

Message: Slave I/O thread couldn't register on master

Error number: MY-010565; Symbol:

ER RPL SLAVE FORCING TO RECONNECT IO THREAD; SQLSTATE: HY000

Message: Forcing to reconnect slave I/O thread%s

Error number: MY-010566; Symbol:

ER RPL SLAVE ERROR REQUESTING BINLOG DUMP; SQLSTATE: HY000

Message: Failed on request dump()%s

Error number: MY-010567; Symbol:

ER_RPL_LOG_ENTRY_EXCEEDS_SLAVE_MAX_ALLOWED_PACKET; SQLSTATE: HY000 Message: Log entry on master is longer than slave_max_allowed_packet (%lu) on slave. If the entry is correct, restart the server with a higher value of slave max_allowed_packet

Error number: MY-010567; Symbol:

ER_RPL_LOG_ENTRY_EXCEEDS_REPLICA_MAX_ALLOWED_PACKET; SQLSTATE: HY000

Message: Log entry on master is longer than replica_max_allowed_packet (%lu) on slave. If the entry is correct, restart the server with a higher value of replica_max_allowed_packet

Error number: MY-010568; Symbol: ER RPL SLAVE STOPPING AS MASTER OOM;

SOLSTATE: HY000

Message: Stopping slave I/O thread due to out-of-memory error from master

Error number: MY-010569; Symbol:

ER RPL SLAVE IO THREAD ABORTED WAITING FOR RELAY LOG SPACE;

SQLSTATE: HY000

Message: Slave I/O thread aborted while waiting for relay log space

Error number: MY-010570; Symbol: ER RPL SLAVE IO THREAD EXITING; SQLSTATE:

HY000

Message: Slave I/O thread exiting%s, read up to log '%s', position %s

Error number: MY-010571; Symbol: ER RPL SLAVE CANT INITIALIZE SLAVE WORKER;

SQLSTATE: HY000

Message: Failed during slave worker initialization%s

Error number: MY-010572; Symbol:

ER RPL MTS GROUP RECOVERY RELAY LOG INFO FOR WORKER; SQLSTATE:

HY000

Message: Slave: MTS group recovery relay log info based on Worker-Id %lu,

group relay log name %s, group relay log pos %llu group master log name %s,

group master log pos %llu

Error number: MY-010573; Symbol: ER RPL ERROR LOOKING FOR LOG; SQLSTATE:

HY000

Message: Error looking for %s.

Error number: MY-010574; Symbol: ER RPL MTS GROUP RECOVERY RELAY LOG INFO;

SQLSTATE: HY000

Message: Slave: MTS group recovery relay log info group master log name %s,

event master log pos %llu.

Error number: MY-010575; Symbol: ER RPL CANT FIND FOLLOWUP FILE; SQLSTATE:

HY000

Message: Error looking for file after %s.

Error number: MY-010576; Symbol:

ER RPL MTS CHECKPOINT PERIOD DIFFERS FROM CNT; SQLSTATE: HY000

Message: This an error cnt != mta_checkpoint_period

Error number: MY-010577; Symbol:

ER RPL SLAVE WORKER THREAD CREATION FAILED; SQLSTATE: HY000

Message: Failed during slave worker thread creation%s

Error number: MY-010578; Symbol:

ER RPL SLAVE WORKER THREAD CREATION FAILED WITH ERRNO; SQLSTATE:

HY000

Message: Failed during slave worker thread creation%s (errno= %d)

Error number: MY-010579; Symbol: ER RPL SLAVE FAILED TO INIT PARTITIONS HASH;

SQLSTATE: HY000

Message: Failed to init partitions hash

Error number: MY-010581; Symbol: ER_RPL_SLAVE_SQL_THREAD_STARTING; SQLSTATE:

HY000

Message: Slave SQL thread%s initialized, starting replication in log '%s' at position %s, relay log

'%s' position: %s

Error number: MY-010582; Symbol: ER RPL SLAVE SKIP COUNTER EXECUTED;

SQLSTATE: HY000

Message: 'SQL REPLICA SKIP COUNTER=%ld' executed at relay log file='%s',

relay_log_pos='%ld', master_log_name='%s', master_log_pos='%ld' and new position at

relay log file='%s', relay log pos='%ld', master log name='%s', master log pos='%ld'

Error number: MY-010583; Symbol:

ER RPL SLAVE ADDITIONAL ERROR INFO FROM DA; SQLSTATE: HY000

Message: Slave (additional info): %s Error_code: MY-%06d

Error number: MY-010584; Symbol: ER RPL SLAVE ERROR INFO FROM DA; SQLSTATE:

HY000

Message: Slave: %s Error code: MY-%06d

Error number: MY-010585; Symbol:

ER RPL SLAVE ERROR LOADING USER DEFINED LIBRARY; SQLSTATE: HY000

Message: Error loading user-defined library, slave SQL thread aborted. Install the missing library,

and restart the slave SQL thread with "SLAVE START". We stopped at log '%s' position %s

Error number: MY-010586; Symbol: ER RPL SLAVE ERROR RUNNING QUERY;

SQLSTATE: HY000

Message: Error running query, slave SQL thread aborted. Fix the problem, and restart the slave SQL

thread with "SLAVE START". We stopped at log '%s' position %s

Error number: MY-010587; Symbol: ER_RPL_SLAVE_SQL_THREAD_EXITING; SQLSTATE:

HY000

Message: Slave SQL thread%s exiting, replication stopped in log '%s' at position %s

Error number: MY-010588; Symbol:

ER RPL SLAVE READ_INVALID_EVENT_FROM_MASTER; SQLSTATE: HY000

Message: Read invalid event from master: '%s', master could be corrupt but a more likely cause of

this is a bug

Error number: MY-010589; Symbol:

ER RPL SLAVE QUEUE EVENT FAILED INVALID CONFIGURATION; SQLSTATE:

HY000

Message: The queue event failed for channel '%s' as its configuration is invalid.

Error number: MY-010590; Symbol:

ER RPL SLAVE IO THREAD DETECTED UNEXPECTED EVENT SEQUENCE;

SQLSTATE: HY000

Message: An unexpected event sequence was detected by the IO thread while queuing the event

received from master '%s' binary log file, at position %llu.

Error number: MY-010591; Symbol: ER_RPL_SLAVE_CANT_USE_CHARSET; SQLSTATE:

HY000

Message: '%s' can not be used as client character set. '%s' will be used as default client character set

while connecting to master.

Error number: MY-010592; Symbol:

ER_RPL_SLAVE_CONNECTED_TO_MASTER_REPLICATION_RESUMED; SQLSTATE:

HY000

Message: Slave%s: connected to master '%s@%s:%d',replication resumed in log '%s' at position %s

Error number: MY-010593; Symbol: ER RPL SLAVE NEXT LOG IS ACTIVE; SQLSTATE:

HY000

Message: next log '%s' is active

Error number: MY-010594; Symbol: ER RPL SLAVE NEXT LOG IS INACTIVE; SQLSTATE:

HY000

Message: next log '%s' is not active

Error number: MY-010595; Symbol:

ER RPL SLAVE SQL THREAD IO ERROR READING EVENT; SQLSTATE: HY000

Message: Slave SQL thread%s: I/O error reading event (errno: %d cur log->error: %d)

Error number: MY-010596; Symbol:

ER RPL SLAVE ERROR READING RELAY LOG EVENTS; SQLSTATE: HY000

Message: Error reading relay log event%s: %s

Error number: MY-010597; Symbol: ER SLAVE CHANGE MASTER TO EXECUTED;

SQLSTATE: HY000

Message: 'CHANGE MASTER TO%s executed'. Previous state master_host='%s', master_port= %u,

master log file='%s', master log pos= %ld, master bind='%s'. New state master host='%s',

master port= %u, master log file='%s', master log pos= %ld, master bind='%s'.

Error number: MY-010598; Symbol:

ER RPL SLAVE NEW MASTER INFO NEEDS REPOS TYPE OTHER THAN FILE;

SQLSTATE: HY000

Message: Slave: Cannot create new master info structure when repositories are of type FILE.

Convert slave repositories to TABLE to replicate from multiple sources.

Error number: MY-010599; Symbol: ER RPL FAILED TO STAT LOG IN INDEX;

SQLSTATE: HY000

Message: log %s listed in the index, but failed to stat.

Error number: MY-010600; Symbol:

ER RPL LOG NOT FOUND WHILE COUNTING RELAY LOG SPACE; SQLSTATE:

HY000

Message: Could not find first log while counting relay log space.

Error number: MY-010601; Symbol: ER_SLAVE_CANT_USE_TEMPDIR; SQLSTATE: HY000

Message: Unable to use slave's temporary directory '%s'.

Error number: MY-010602; Symbol: ER RPL RELAY LOG NEEDS FILE NOT DIRECTORY;

SQLSTATE: HY000

Message: Path '%s' is a directory name, please specify a file name for --relay-log option.

Error number: MY-010603; Symbol:

ER RPL RELAY LOG INDEX NEEDS FILE NOT DIRECTORY; SQLSTATE: HY000

Message: Path '%s' is a directory name, please specify a file name for --relay-log-index option.

Error number: MY-010604; Symbol: ER RPL PLEASE USE OPTION RELAY LOG;

SQLSTATE: HY000

Message: Neither --relay-log nor --relay-log-index were used; so replication may break when this MySQL server acts as a slave and has his hostname changed!! Please use '--relay-log=%s' to avoid

this problem.

Error number: MY-010605; Symbol: ER_RPL_OPEN_INDEX_FILE_FAILED; SQLSTATE:

HY000

Message: Failed in open index file() called from Relay log info::rli init info().

Error number: MY-010606; Symbol:

ER RPL CANT INITIALIZE GTID SETS IN RLI INIT INFO; SQLSTATE: HY000

Message: Failed in init gtid sets() called from Relay log info::rli init info().

Error number: MY-010607; Symbol: ER RPL CANT OPEN LOG IN RLI INIT INFO;

SQLSTATE: HY000

Message: Failed in open_log() called from Relay_log_info::rli_init_info().

Error number: MY-010608; Symbol:

ER RPL ERROR WRITING RELAY LOG CONFIGURATION; SQLSTATE: HY000

Message: Error writing relay log configuration.

Error number: MY-010709; Symbol:

ER TREE CORRUPT PARENT SHOULD POINT AT PARENT; SQLSTATE: HY000

Message: Wrong tree: Parent doesn't point at parent

Error number: MY-010710; Symbol: ER_TREE_CORRUPT_ROOT_SHOULD_BE_BLACK;

SOLSTATE: HY000

Message: Wrong tree: Root should be black

Error number: MY-010711; Symbol: ER TREE CORRUPT 2 CONSECUTIVE REDS;

SQLSTATE: HY000

Message: Wrong tree: Found two red in a row

Error number: MY-010712; Symbol: ER TREE CORRUPT RIGHT IS LEFT; SQLSTATE:

HY000

Message: Wrong tree: Found right == left

Error number: MY-010713; Symbol: ER TREE CORRUPT INCORRECT BLACK COUNT;

SQLSTATE: HY000

Message: Wrong tree: Incorrect black-count: %d - %d

Error number: MY-010714; Symbol: ER WRONG COUNT FOR ORIGIN; SQLSTATE: HY000

Message: Use count: Wrong count %lu for origin %p

Error number: MY-010715; Symbol: ER WRONG COUNT FOR KEY; SQLSTATE: HY000

Message: Use count: Wrong count for key at %p, %lu should be %lu

Error number: MY-010716; Symbol: ER_WRONG_COUNT_OF_ELEMENTS; SQLSTATE:

HY000

Message: Wrong number of elements: %u (should be %u) for tree at %p

Error number: MY-010717; Symbol:

ER RPL ERROR_READING_SLAVE_WORKER_CONFIGURATION; SQLSTATE: HY000

Message: Error reading slave worker configuration

Error number: MY-010718; Symbol:

ER RPL ERROR WRITING SLAVE WORKER CONFIGURATION; SQLSTATE: HY000

Message: Error writing slave worker configuration

Error number: MY-010719; Symbol: ER RPL FAILED TO OPEN RELAY LOG; SQLSTATE:

HY000

Message: Failed to open relay log %s, error: %s

Error number: MY-010720; Symbol: ER RPL WORKER CANT READ RELAY LOG;

SQLSTATE: HY000

Message: Error when worker read relay log events, relay log name %s, position %llu

Error number: MY-010721; Symbol: ER RPL WORKER CANT FIND NEXT RELAY LOG;

SOLSTATE: HY000

Message: Failed to find next relay log when retrying the transaction, current relay log is %s

Error number: MY-010722; Symbol: ER RPL MTS SLAVE COORDINATOR HAS WAITED;

SQLSTATE: HY000

Message: Multi-threaded slave: Coordinator has waited %lu times hitting

replica pending jobs size max; current event size = %zu.

Error number: MY-010723; Symbol:

ER BINLOG FAILED TO WRITE DROP FOR TEMP TABLES; SQLSTATE: HY000

Message: Failed to write the DROP statement for temporary tables to binary log

Error number: MY-010724; Symbol:

ER BINLOG OOM WRITING DELETE WHILE OPENING HEAP TABLE; SQLSTATE:

HY000

Message: When opening HEAP table, could not allocate memory to write 'DELETE FROM

'%s'.'%s'' to the binary log

Error number: MY-010725; Symbol: ER FAILED TO REPAIR TABLE; SQLSTATE: HY000

Message: Couldn't repair table: %s.%s

Error number: MY-010726; Symbol: ER_FAILED_TO_REMOVE_TEMP_TABLE; SQLSTATE:

HY000

Message: Could not remove temporary table: '%s', error: %d

Error number: MY-010727; Symbol: ER SYSTEM TABLE NOT TRANSACTIONAL;

SQLSTATE: HY000

Message: System table '%.*s' is expected to be transactional.

Error number: MY-010728; Symbol:

ER RPL ERROR WRITING MASTER CONFIGURATION; SQLSTATE: HY000

Message: Error writing master configuration.

Error number: MY-010729; Symbol:

ER RPL ERROR READING MASTER CONFIGURATION; SQLSTATE: HY000

Message: Error reading master configuration.

Error number: MY-010730; Symbol: ER RPL SSL INFO IN MASTER INFO IGNORED;

SQLSTATE: HY000

Message: SSL information in the master info file are ignored because this MySQL slave was

compiled without SSL support.

Error number: MY-010731; Symbol: ER PLUGIN FAILED DEINITIALIZATION; SQLSTATE:

HY000

Message: Plugin '%s' of type %s failed deinitialization

Error number: MY-010732; Symbol:

ER PLUGIN HAS NONZERO REFCOUNT AFTER DEINITIALIZATION; SQLSTATE:

HY000

Message: Plugin '%s' has ref count=%d after deinitialization.

Error number: MY-010733; Symbol: ER PLUGIN SHUTTING DOWN PLUGIN; SQLSTATE:

HY000

Message: Shutting down plugin '%s'

Error number: MY-010734; Symbol: ER PLUGIN REGISTRATION FAILED; SQLSTATE:

HY000

Message: Plugin '%s' registration as a %s failed.

Error number: MY-010735; Symbol: ER PLUGIN CANT OPEN PLUGIN TABLE; SQLSTATE:

HY000

Message: Could not open the mysql.plugin table. Please perform the MySQL upgrade procedure.

Error number: MY-010736; Symbol: ER_PLUGIN_CANT_LOAD; SQLSTATE: HY000

Message: Couldn't load plugin named '%s' with soname '%s'.

Error number: MY-010737; Symbol: ER PLUGIN LOAD PARAMETER TOO LONG;

SQLSTATE: HY000

Message: plugin-load parameter too long

Error number: MY-010738; Symbol: ER PLUGIN FORCING SHUTDOWN; SQLSTATE: HY000

Message: Plugin '%s' will be forced to shutdown

Error number: MY-010739; Symbol:

ER PLUGIN HAS NONZERO REFCOUNT_AFTER_SHUTDOWN; SQLSTATE: HY000

Message: Plugin '%s' has ref_count=%d after shutdown.

Error number: MY-010740; Symbol: ER PLUGIN UNKNOWN VARIABLE TYPE;

SQLSTATE: HY000

Message: Unknown variable type code 0x%x in plugin '%s'.

Error number: MY-010741; Symbol: ER PLUGIN VARIABLE SET READ ONLY;

SQLSTATE: HY000

Message: Server variable %s of plugin %s was forced to be read-only: string variable without

update func and PLUGIN VAR MEMALLOC flag

Error number: MY-010742; Symbol: ER PLUGIN VARIABLE MISSING NAME; SQLSTATE:

HY000

Message: Missing variable name in plugin '%s'.

Error number: MY-010743; Symbol:

ER PLUGIN VARIABLE NOT ALLOCATED THREAD LOCAL; SQLSTATE: HY000

Message: Thread local variable '%s' not allocated in plugin '%s'.

Error number: MY-010744; Symbol: ER_PLUGIN_OOM; SQLSTATE: HY000

Message: Out of memory for plugin '%s'.

Error number: MY-010745; Symbol: ER PLUGIN BAD OPTIONS; SQLSTATE: HY000

Message: Bad options for plugin '%s'.

Error number: MY-010746; Symbol: ER PLUGIN PARSING_OPTIONS_FAILED; SQLSTATE:

HY000

Message: Parsing options for plugin '%s' failed.

Error number: MY-010747; Symbol: ER PLUGIN DISABLED; SQLSTATE: HY000

Message: Plugin '%s' is disabled.

Error number: MY-010748; Symbol:

ER PLUGIN HAS CONFLICTING SYSTEM VARIABLES; SQLSTATE: HY000

Message: Plugin '%s' has conflicting system variables

Error number: MY-010749; Symbol: ER PLUGIN CANT SET PERSISTENT OPTIONS;

SQLSTATE: HY000

Message: Setting persistent options for plugin '%s' failed.

Error number: MY-010750; Symbol:

ER MY NET WRITE FAILED FALLING BACK ON STDERR; SQLSTATE: HY000

Message: Failed on my net write, writing to stderr instead: %s

Error number: MY-010751; Symbol: ER RETRYING REPAIR WITHOUT QUICK; SQLSTATE:

HY000

Message: Retrying repair of: '%s' without quick

Error number: MY-010752; Symbol: ER RETRYING REPAIR WITH KEYCACHE;

SQLSTATE: HY000

Message: Retrying repair of: '%s' with keycache

Error number: MY-010753; Symbol: ER_FOUND_ROWS_WHILE_REPAIRING; SQLSTATE:

HY000

Message: Found %s of %s rows when repairing '%s'

Error number: MY-010754; Symbol: ER ERROR DURING OPTIMIZE TABLE; SQLSTATE:

HY000

Message: Warning: Optimize table got errno %d on %s.%s, retrying

Error number: MY-010755; Symbol: ER ERROR ENABLING KEYS; SQLSTATE: HY000

Message: Warning: Enabling keys got errno %d on %s.%s, retrying

Error number: MY-010756; Symbol: ER CHECKING TABLE; SQLSTATE: HY000

Message: Checking table: '%s'

Error number: MY-010757; Symbol: ER RECOVERING TABLE; SQLSTATE: HY000

Message: Recovering table: '%s'

Error number: MY-010758; Symbol: ER CANT CREATE TABLE SHARE FROM FRM;

SQLSTATE: HY000

Message: Error in creating TABLE SHARE from %s.frm file.

Error number: MY-010759; Symbol: ER CANT LOCK TABLE; SQLSTATE: HY000

Message: Unable to acquire lock on %s.%s

Error number: MY-010760; Symbol: ER CANT ALLOC TABLE OBJECT; SQLSTATE: HY000

Message: Error in allocation memory for TABLE object.

Error number: MY-010761; Symbol: ER CANT CREATE HANDLER OBJECT FOR TABLE;

SQLSTATE: HY000

Message: Error in creating handler object for table %s.%s

Error number: MY-010762; Symbol: ER CANT SET HANDLER REFERENCE FOR TABLE;

SQLSTATE: HY000

Message: Error in setting handler reference for table %s.%s

Error number: MY-010763; Symbol: ER CANT LOCK TABLESPACE; SQLSTATE: HY000

Message: Unable to acquire lock on tablespace name %s

Error number: MY-010764; Symbol:

ER CANT UPGRADE GENERATED COLUMNS TO DD; SQLSTATE: HY000

Message: Error in processing generated columns for table %s.%s

Error number: MY-010765; Symbol: ER DD ERROR CREATING ENTRY; SQLSTATE: HY000

Message: Error in Creating DD entry for %s.%s

Error number: MY-010766; Symbol: ER DD CANT FETCH TABLE DATA; SQLSTATE:

HY000

Message: Error in fetching %s.%s table data from dictionary

Error number: MY-010767; Symbol: ER DD CANT FIX SE DATA; SQLSTATE: HY000

Message: Error in fixing SE data for %s.%s

Error number: MY-010768; Symbol: ER DD CANT CREATE SP; SQLSTATE: HY000

Message: Error in creating stored program '%s.%s'

Error number: MY-010769; Symbol:

ER_CANT_OPEN_DB_OPT_USING_DEFAULT_CHARSET; SQLSTATE: HY000

Message: Unable to open db.opt file %s. Using default Character set.

Error number: MY-010770; Symbol: ER CANT CREATE CACHE FOR DB OPT; SQLSTATE:

HY000

Message: Unable to intialize IO cache to open db.opt file %s.

Error number: MY-010771; Symbol: ER CANT IDENTIFY CHARSET USING DEFAULT;

SQLSTATE: HY000

Message: Unable to identify the charset in %s. Using default character set.

Error number: MY-010772; Symbol:

ER DB OPT NOT FOUND USING DEFAULT CHARSET; SQLSTATE: HY000

Message: db.opt file not found for %s database. Using default Character set.

Error number: MY-010773; Symbol: ER_EVENT_CANT_GET_TIMEZONE_FROM_FIELD;

SQLSTATE: HY000

Message: Event '%s'.'%s': invalid value in column mysql.event.time zone.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the mysql.event system table and migrates its contents to the internal data dictionary.

Error number: MY-010774; Symbol: ER_EVENT_CANT_FIND_TIMEZONE; SQLSTATE:

HY000

Message: Event '%s'.'%s': has invalid time zone value

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the mysql event system table and migrates its contents to the internal data dictionary.

Error number: MY-010775; Symbol: ER_EVENT_CANT_GET_CHARSET; SQLSTATE: HY000 Message: Event '%s'.'%s': invalid value in column mysql.event.character_set_client.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the mysql.event system table and migrates its contents to the internal data dictionary.

Error number: MY-010776; Symbol: ER_EVENT_CANT_GET_COLLATION; SQLSTATE: HY000

Message: Event '%s'.'%s': invalid value in column mysql.event.collation_connection.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the mysql event system table and migrates its contents to the internal data dictionary.

Error number: MY-010777; Symbol: ER EVENT CANT OPEN TABLE MYSQL EVENT;

SQLSTATE: HY000

Message: Failed to open mysql.event Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the mysql event system table and migrates its contents to the internal data dictionary.

Error number: MY-010778; Symbol: ER CANT PARSE STORED ROUTINE BODY;

SQLSTATE: HY000

Message: Parsing '%s.%s' routine body failed.%s

Error number: MY-010779; Symbol: ER_CANT_OPEN_TABLE_MYSQL_PROC; SQLSTATE:

HY000

Message: Failed to open mysql.proc Table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the mysql.proc system table and migrates its contents to the internal data dictionary.

Error number: MY-010780; Symbol: ER_CANT_READ_TABLE_MYSQL_PROC; SQLSTATE: HY000

Message: Failed to read mysql.proc table.

This error can occur for upgrades to MySQL 8.0 from previous versions. During the upgrade process, the server reads the mysql.proc system table and migrates its contents to the internal data dictionary.

Error number: MY-010781; Symbol: ER_FILE_EXISTS_DURING_UPGRADE; SQLSTATE: HY000

Message: Found %s file in mysql schema. DD will create .ibd file with same name. Please rename table and start upgrade process again.

Error number: MY-010782; Symbol:

ER_CANT_OPEN_DATADIR_AFTER_UPGRADE_FAILURE; SQLSTATE: HY000 Message: Unable to open the data directory %s during clean up after upgrade failed

Error number: MY-010783; Symbol: ER CANT SET PATH FOR; SQLSTATE: HY000

Message: Failed to set path %s

Error number: MY-010784; Symbol: ER CANT OPEN DIR; SQLSTATE: HY000

Message: Failed to open dir %s

Error number: MY-010801; Symbol:

ER_EVENT_ERROR_CREATING_QUERY_TO_WRITE_TO_BINLOG; SQLSTATE: HY000 Message: Event Error: An error occurred while creating query string, before writing it into binary log.

Error number: MY-010802; Symbol:

ER EVENT SCHEDULER ERROR LOADING_FROM_DB; SQLSTATE: HY000

Message: Event Scheduler: Error while loading from disk.

Error number: MY-010803; Symbol:

ER EVENT SCHEDULER ERROR GETTING EVENT OBJECT; SQLSTATE: HY000

Message: Event Scheduler: Error getting event object.

Error number: MY-010804; Symbol:

ER EVENT SCHEDULER GOT BAD DATA FROM TABLE; SQLSTATE: HY000

Message: Event Scheduler: Error while loading events from mysql.events. The table probably

contains bad data or is corrupted

Error number: MY-010805; Symbol:

ER_EVENT_CANT_GET_LOCK_FOR_DROPPING_EVENT; SQLSTATE: HY000

Message: Unable to obtain lock for dropping event %s from schema %s

Error number: MY-010806; Symbol: ER_EVENT_UNABLE_TO_DROP_EVENT; SQLSTATE:

HY000

Message: Unable to drop event %s from schema %s

Error number: MY-010807; Symbol:

ER BINLOG ATTACHING THREAD MEMORY FINALLY AVAILABLE; SQLSTATE:

HY000

Message: Server overcomes the temporary 'out of memory' in '%d' tries while attaching to session

thread during the group commit phase.

Error number: MY-010808; Symbol: ER BINLOG CANT RESIZE CACHE; SQLSTATE: HY000

Message: Unable to resize binlog IOCACHE auxiliary file

Error number: MY-010809; Symbol: ER BINLOG FILE BEING READ NOT PURGED;

SQLSTATE: HY000

Message: file %s was not purged because it was being read by thread number %u

Error number: MY-010810; Symbol: ER BINLOG IO ERROR READING HEADER;

SQLSTATE: HY000

Message: I/O error reading the header from the binary log, errno=%d, io cache code=%d

Error number: MY-010811; Symbol: ER BINLOG CANT OPEN LOG; SQLSTATE: HY000

Message: Failed to open log (file '%s', errno %d)

Error number: MY-010812; Symbol: ER BINLOG CANT CREATE CACHE FOR LOG;

SQLSTATE: HY000

Message: Failed to create a cache on log (file '%s')

Error number: MY-010813; Symbol:

ER BINLOG FILE EXTENSION NUMBER EXHAUSTED; SQLSTATE: HY000

Message: Log filename extension number exhausted: %06lu. Please fix this by archiving old logs

and updating the index files.

Error number: MY-010814; Symbol: ER_BINLOG_FILE_NAME_TOO_LONG; SQLSTATE:

HY000

Message: Log filename too large: %s%s (%zu). Please fix this by archiving old logs and updating the

index files.

Error number: MY-010815; Symbol:

ER BINLOG FILE EXTENSION NUMBER RUNNING LOW; SQLSTATE: HY000

Message: Next log extension: %lu. Remaining log filename extensions: %lu. Please consider

archiving some logs.

Error number: MY-010816; Symbol: ER_BINLOG_CANT_OPEN_FOR_LOGGING; SQLSTATE:

HY000

restart it.

Message: Could not open %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and

Error number: MY-010817; Symbol: ER BINLOG FAILED TO SYNC INDEX FILE;

SQLSTATE: HY000

Message: MYSQL BIN LOG::open index file failed to sync the index file.

Error number: MY-010818; Symbol:

ER BINLOG ERROR READING GTIDS FROM RELAY LOG; SQLSTATE: HY000

Message: Error reading GTIDs from relaylog: %d

Error number: MY-010819; Symbol:

ER BINLOG EVENTS READ FROM RELAY LOG INFO; SQLSTATE: HY000

Message: %lu events read in relaylog file '%s' for updating Retrieved Gtid Set and/or IO thread

transaction parser state.

Error number: MY-010820; Symbol:

ER BINLOG ERROR READING GTIDS FROM BINARY LOG; SQLSTATE: HY000

Message: Error reading GTIDs from binary log: %d

Error number: MY-010821; Symbol: ER_BINLOG_EVENTS_READ_FROM_BINLOG_INFO;

SQLSTATE: HY000

Message: Read %lu events from binary log file '%s' to determine the GTIDs purged from binary logs.

Error number: MY-010822; Symbol: ER BINLOG CANT GENERATE NEW FILE NAME;

SQLSTATE: HY000

Message: MYSQL BIN LOG::open failed to generate new file name.

Error number: MY-010823; Symbol:

ER BINLOG FAILED TO SYNC INDEX FILE IN OPEN; SQLSTATE: HY000

Message: MYSQL BIN LOG::open failed to sync the index file.

Error number: MY-010824; Symbol: ER_BINLOG_CANT_USE_FOR_LOGGING; SQLSTATE:

HY000

Message: Could not use %s for logging (error %d). Turning logging off for the whole duration of the MySQL server process. To turn it on again: fix the cause, shutdown the MySQL server and restart it.

Error number: MY-010825; Symbol:

ER BINLOG FAILED TO CLOSE INDEX FILE WHILE REBUILDING; SQLSTATE:

HY000

Message: While rebuilding index file %s: Failed to close the index file.

Error number: MY-010826; Symbol:

ER_BINLOG_FAILED_TO_DELETE_INDEX_FILE_WHILE_REBUILDING; SQLSTATE:

HY000

Message: While rebuilding index file %s: Failed to delete the existing index file. It could be that file is being used by some other process.

Error number: MY-010827; Symbol:

 $ER_BINLOG_FAILED_TO_RENAME_INDEX_FILE_WHILE_REBUILDING; SQLSTATE:$

HY000

Message: While rebuilding index file %s: Failed to rename the new index file to the existing index

file.

Error number: MY-010828; Symbol:

 $ER_BINLOG_FAILED_TO_OPEN_INDEX_FILE_AFTER_REBUILDING; SQLSTATE: HY000$

Message: After rebuilding the index file %s: Failed to open the index file.

Error number: MY-010829; Symbol: ER BINLOG CANT APPEND LOG TO TMP INDEX;

SQLSTATE: HY000

Message: MYSQL_BIN_LOG::add_log_to_index failed to append log file name: %s, to crash safe index file.

Error number: MY-010830; Symbol:

ER BINLOG CANT LOCATE OLD BINLOG OR RELAY LOG FILES; SQLSTATE: HY000

Message: Failed to locate old binlog or relay log files

Error number: MY-010831; Symbol: ER_BINLOG_CANT_DELETE_FILE; SQLSTATE: HY000

Message: Failed to delete file '%s'

Error number: MY-010832; Symbol: ER BINLOG CANT SET TMP INDEX NAME;

SQLSTATE: HY000

Message: MYSQL BIN LOG::set crash safe index file name failed to set file name.

Error number: MY-010833; Symbol:

ER BINLOG FAILED TO OPEN TEMPORARY INDEX FILE; SQLSTATE: HY000

Message: MYSQL BIN LOG::open crash safe index file failed to open temporary index file.

Error number: MY-010834; Symbol:

ER BINLOG ERROR GETTING NEXT LOG FROM INDEX; SQLSTATE: HY000

Message: next log error: %d offset: %s log: %s included: %d

Error number: MY-010835; Symbol: ER BINLOG CANT OPEN TMP INDEX; SQLSTATE:

HY000

Message: %s failed to open the crash safe index file.

Error number: MY-010836; Symbol: ER BINLOG CANT COPY INDEX TO TMP;

SOLSTATE: HY000

Message: %s failed to copy index file to crash safe index file.

Error number: MY-010837; Symbol: ER BINLOG CANT CLOSE TMP INDEX; SQLSTATE:

HY000

Message: %s failed to close the crash safe index file.

Error number: MY-010838; Symbol: ER BINLOG CANT MOVE TMP TO INDEX;

SQLSTATE: HY000

Message: %s failed to move crash safe index file to index file.

Error number: MY-010839; Symbol:

ER_BINLOG_PURGE_LOGS_CALLED_WITH_FILE_NOT_IN_INDEX; SQLSTATE: HY000

Message: MYSQL BIN LOG::purge logs was called with file %s not listed in the index.

Error number: MY-010840; Symbol: ER BINLOG PURGE LOGS CANT SYNC INDEX FILE;

SOLSTATE: HY000

Message: MYSQL BIN LOG::purge logs failed to sync the index file.

Error number: MY-010841; Symbol:

ER BINLOG PURGE LOGS CANT COPY TO REGISTER FILE; SQLSTATE: HY000

Message: MYSQL BIN LOG::purge logs failed to copy %s to register file.

Error number: MY-010842; Symbol:

ER BINLOG PURGE LOGS CANT FLUSH REGISTER FILE; SQLSTATE: HY000

Message: MYSQL BIN LOG::purge logs failed to flush register file.

Error number: MY-010843; Symbol:

ER BINLOG PURGE LOGS CANT UPDATE INDEX FILE; SQLSTATE: HY000

Message: MYSQL BIN LOG::purge logs failed to update the index file

Error number: MY-010844; Symbol: ER BINLOG PURGE LOGS FAILED TO PURGE LOG;

SQLSTATE: HY000

Message: MYSQL BIN LOG::purge logs failed to process registered files that would be purged.

Error number: MY-010845; Symbol:

ER BINLOG FAILED TO SET PURGE INDEX FILE NAME; SQLSTATE: HY000

Message: MYSQL BIN LOG::set purge index file name failed to set file name.

Error number: MY-010846; Symbol: ER BINLOG FAILED TO OPEN REGISTER FILE;

SQLSTATE: HY000

Message: MYSQL BIN LOG::open purge index file failed to open register file.

Error number: MY-010847; Symbol: ER BINLOG FAILED TO REINIT REGISTER FILE;

SQLSTATE: HY000

Message: MYSQL BIN LOG::purge index entry failed to reinit register file for read

Error number: MY-010848; Symbol: ER_BINLOG_FAILED_TO_READ_REGISTER_FILE;

SOLSTATE: HY000

Message: MYSQL BIN LOG::purge index entry error %d reading from register file.

Error number: MY-010849; Symbol: ER CANT STAT FILE; SQLSTATE: HY000

Message: Failed to execute mysql file stat on file '%s'

Error number: MY-010850; Symbol:

ER BINLOG CANT DELETE LOG FILE DOES INDEX MATCH FILES; SQLSTATE:

HY000

Message: Failed to delete log file '%s'; consider examining correspondence of your binlog index file to the actual binlog files

Error number: MY-010851; Symbol:

ER BINLOG CANT DELETE FILE AND READ BINLOG INDEX; SQLSTATE: HY000

Message: Failed to delete file '%s' and read the binlog index file

Error number: MY-010852; Symbol: ER BINLOG FAILED TO DELETE LOG FILE;

SQLSTATE: HY000

Message: Failed to delete log file '%s'

Error number: MY-010853; Symbol: ER BINLOG LOGGING INCIDENT TO STOP SLAVES;

SQLSTATE: HY000

Message: %s An incident event has been written to the binary log which will stop the slaves.

Error number: MY-010854; Symbol: ER BINLOG CANT FIND LOG IN INDEX; SQLSTATE:

HY000

Message: find log pos() failed (error: %d)

Error number: MY-010855; Symbol: ER BINLOG RECOVERING AFTER CRASH USING;

SQLSTATE: HY000

Message: Recovering after a crash using %s

Error number: MY-010856; Symbol: ER BINLOG CANT OPEN CRASHED BINLOG;

SQLSTATE: HY000

Message: Failed to open the crashed binlog file when master server is recovering it.

Error number: MY-010857; Symbol: ER_BINLOG_CANT_TRIM_CRASHED_BINLOG;

SQLSTATE: HY000

Message: Failed to trim the crashed binlog file when master server is recovering it.

Error number: MY-010858; Symbol: ER BINLOG CRASHED BINLOG TRIMMED;

SQLSTATE: HY000

Message: Crashed binlog file %s size is %llu, but recovered up to %llu. Binlog trimmed to %llu

bytes.

Error number: MY-010859; Symbol:

ER BINLOG CANT CLEAR IN USE FLAG FOR CRASHED BINLOG; SQLSTATE: HY000

Message: Failed to clear LOG_EVENT_BINLOG_IN_USE_F for the crashed binlog file when

master server is recovering it.

Error number: MY-010860; Symbol: ER BINLOG FAILED TO RUN AFTER SYNC HOOK;

SOLSTATE: HY000

Message: Failed to run 'after sync' hooks

Error number: MY-010861; Symbol: ER TURNING LOGGING OFF FOR THE DURATION;

SQLSTATE: HY000

Message: %s Hence turning logging off for the whole duration of the MySQL server process. To turn

it on again: fix the cause, shutdown the MySQL server and restart it.

Error number: MY-010862; Symbol: ER BINLOG FAILED TO RUN AFTER FLUSH HOOK;

SQLSTATE: HY000

Message: Failed to run 'after_flush' hooks

Error number: MY-010863; Symbol: ER_BINLOG_CRASH_RECOVERY_FAILED; SQLSTATE:

HY000

Message: Crash recovery failed. Either correct the problem (if it's, for example, out of memory error)

and restart, or delete (or rename) binary log and start mysqld with --tc-heuristic-

recover={commit|rollback}

Error number: MY-010864; Symbol: ER_BINLOG_WARNING_SUPPRESSED; SQLSTATE:

HY000

Message: The following warning was suppressed %d times during the last %d seconds in the error

log

Error number: MY-010868; Symbol: ER INNODB UNKNOWN COLLATION; SQLSTATE:

HY000

Message: Unknown collation #%lu.

Error number: MY-010869; Symbol: ER INNODB INVALID LOG GROUP HOME DIR;

SQLSTATE: HY000

Message: syntax error in innodb log group home dir

Error number: MY-010870; Symbol: ER INNODB INVALID INNODB UNDO DIRECTORY;

SOLSTATE: HY000

Message: syntax error in innodb undo directory

Error number: MY-010871; Symbol: ER INNODB ILLEGAL COLON IN POOL; SQLSTATE:

HY000

Message: InnoDB: innodb buffer pool filename cannot have colon (:) in the file name.

Error number: MY-010872; Symbol: ER INNODB INVALID PAGE SIZE; SQLSTATE: HY000

Message: InnoDB: Invalid page size=%lu.

Error number: MY-010873; Symbol: ER INNODB DIRTY WATER MARK NOT LOW;

SQLSTATE: HY000

Message: InnoDB: innodb_max_dirty_pages_pct_lwm cannot be set higher than innodb max dirty pages pct. Setting innodb max dirty pages pct lwm to %lf

Error number: MY-010874; Symbol: ER INNODB IO CAPACITY EXCEEDS MAX;

SQLSTATE: HY000

Message: InnoDB: innodb io capacity cannot be set higher than innodb io capacity max. Setting

innodb io capacity to %lu

Error number: MY-010875; Symbol: ER_INNODB_FILES_SAME; SQLSTATE: HY000

Message: %s and %s file names seem to be the same.

Error number: MY-010876; Symbol: ER_INNODB_UNREGISTERED_TRX_ACTIVE;

SQLSTATE: HY000

Message: Transaction not registered for MySQL 2PC, but transaction is active

Error number: MY-010877; Symbol: ER INNODB CLOSING CONNECTION ROLLS BACK;

SQLSTATE: HY000

Message: MySQL is closing a connection that has an active InnoDB transaction. %llu row

modifications will roll back.

Error number: MY-010878; Symbol: ER INNODB TRX XLATION TABLE OOM; SQLSTATE:

HY000

Message: InnoDB: fail to allocate memory for index translation table. Number of Index:%lu, array

size:%lu

Error number: MY-010879; Symbol: ER INNODB CANT FIND INDEX IN INNODB DD;

SQLSTATE: HY000

Message: Cannot find index %s in InnoDB index dictionary.

Error number: MY-010880; Symbol:

ER_INNODB_INDEX_COLUMN_INFO_UNLIKE_MYSQLS; SQLSTATE: HY000

Message: Found index %s whose column info does not match that of MySQL.

Error number: MY-010881; Symbol: ER INNODB CANT OPEN TABLE; SQLSTATE: HY000

Message: Failed to open table %s.

Error number: MY-010882; Symbol:

ER INNODB CANT BUILD INDEX XLATION TABLE FOR; SQLSTATE: HY000

Message: Build InnoDB index translation table for Table %s failed

Error number: MY-010883; Symbol: ER_INNODB_PK_NOT_IN_MYSQL; SQLSTATE: HY000 Message: Table %s has a primary key in InnoDB data dictionary, but not in MySQL!

Error number: MY-010884; Symbol: ER_INNODB_PK_ONLY_IN_MYSQL; SQLSTATE: HY000 Message: Table %s has no primary key in InnoDB data dictionary, but has one in MySQL! If you created the table with a MySQL version < 3.23.54 and did not define a primary key, but defined a unique key with all non-NULL columns, then MySQL internally treats that key as the primary key. You can fix this error by dump + DROP + CREATE + reimport of the table.

Error number: MY-010885; Symbol: ER_INNODB_CLUSTERED_INDEX_PRIVATE;

SQLSTATE: HY000

Message: Table %s key used on scan is %lu even though there is no primary key inside InnoDB.

Error number: MY-010886; Symbol: ER_INNODB_PARTITION_TABLE_LOWERCASED; SQLSTATE: HY000

Message: Partition table %s opened after converting to lower case. The table may have been moved from a case-insensitive file system. Please recreate the table in the current file system.

Error number: MY-010887; Symbol: ER_ERRMSG_REPLACEMENT_DODGY; SQLSTATE: HY000

Message: Cannot replace error Message (%s,%s,%s) "%s" with "%s"; wrong number or type of %% substitutions.

Error number: MY-010888; Symbol: ER_ERRMSG_REPLACEMENTS_FAILED; SQLSTATE: HY000

Message: Table for error Message replacements could not be found or read, or one or more replacements could not be applied.

Error number: MY-010889; Symbol: ER_NPIPE_CANT_CREATE; SQLSTATE: HY000 Message: %s: %s

Error number: MY-010890; Symbol:

ER_PARTITION_MOVE_CREATED_DUPLICATE_ROW_PLEASE_FIX; SQLSTATE: HY000 Message: Table '%s': Delete from part %d failed with error %d. But it was already inserted into part %d, when moving the misplaced row! Please manually fix the duplicate row: %s

Error number: MY-010891; Symbol: ER_AUDIT_CANT_ABORT_COMMAND; SQLSTATE: HY000

Message: Command '%s' cannot be aborted. The trigger error was (%d) [%s]: %s

Error number: MY-010892; Symbol: ER AUDIT CANT ABORT EVENT; SQLSTATE: HY000

Message: Event '%s' cannot be aborted. The trigger error was (%d) [%s]: %s

Error number: MY-010893; Symbol: ER AUDIT WARNING; SQLSTATE: HY000

Message: %s. The trigger error was (%d) [%s]: %s

Error number: MY-010897; Symbol: ER_RPL_SLAVE_INSECURE_CHANGE_MASTER; SQLSTATE: HY000

Message: Storing MySQL user name or password information in the master info repository is not secure and is therefore not recommended. Please consider using the USER and PASSWORD connection options for START SLAVE; see the 'START SLAVE Syntax' in the MySQL Manual for more information.

Error number: MY-010898; Symbol:

ER RPL SLAVE FLUSH RELAY LOGS NOT ALLOWED; SQLSTATE: HY000

Message: FLUSH RELAY LOGS cannot be performed on channel '%s'.

Error number: MY-010899; Symbol: ER_RPL_SLAVE_INCORRECT_CHANNEL; SQLSTATE: HY000

Message: Slave channel '%s' does not exist.

Error number: MY-010900; Symbol: ER_FAILED_TO_FIND_DL_ENTRY; SQLSTATE: HY000 Message: Can't find symbol '%s' in library.

Error number: MY-010901; Symbol: ER_FAILED_TO_OPEN_SHARED_LIBRARY; SQLSTATE: HY000

Message: Can't open shared library '%s' (errno: %d %s).

Error number: MY-010902; Symbol: ER_THREAD_PRIORITY_IGNORED; SQLSTATE: HY000 Message: Thread priority attribute setting in Resource Group SQL shall be ignored due to unsupported platform or insufficient privilege.

Error number: MY-010903; Symbol: ER_BINLOG_CACHE_SIZE_TOO_LARGE; SQLSTATE: HY000

Message: Option binlog_cache_size (%lu) is greater than max_binlog_cache_size (%lu); setting binlog_cache_size equal to max_binlog_cache_size.

Error number: MY-010904; Symbol: ER_BINLOG_STMT_CACHE_SIZE_TOO_LARGE;

SQLSTATE: HY000

Message: Option binlog_stmt_cache_size (%lu) is greater than max_binlog_stmt_cache_size (%lu); setting binlog_stmt_cache_size equal to max_binlog_stmt_cache_size.

Error number: MY-010905; Symbol: ER FAILED TO GENERATE UNIQUE LOGFILE;

SOLSTATE: HY000

Message: Can't generate a unique log-filename %s.(1-999).

Error number: MY-010906; Symbol: ER FAILED TO READ FILE; SQLSTATE: HY000

Message: Error reading file '%s' (errno: %d - %s)

Error number: MY-010907; Symbol: ER FAILED TO WRITE TO FILE; SQLSTATE: HY000

Message: Error writing file '%s' (errno: %d - %s)

Error number: MY-010908; Symbol: ER BINLOG UNSAFE MESSAGE AND STATEMENT;

SQLSTATE: HY000

Message: %s Statement: %s

Error number: MY-010909; Symbol: ER FORCE CLOSE THREAD; SQLSTATE: HY000

Message: %s: Forcing close of thread %ld user: '%s'.

Error number: MY-010910; Symbol: ER SERVER SHUTDOWN COMPLETE; SQLSTATE:

HY000

Message: %s: Shutdown complete (mysqld %s) %s.

Error number: MY-010911; Symbol: ER_RPL_CANT_HAVE_SAME_BASENAME; SQLSTATE: HY000

Message: Cannot have same base name '%s' for both binary and relay logs. Please check %s (default '%s' if --log-bin option is not used, default '%s' if --log-bin option is used without argument) and %s (default '%s') options to ensure they do not conflict.

Error number: MY-010912; Symbol:

 $ER_RPL_GTID_MODE_REQUIRES_ENFORCE_GTID_CONSISTENCY_ON; SQLSTATE:$

HY000

Message: GTID MODE = ON requires ENFORCE GTID CONSISTENCY = ON.

Error number: MY-010913; Symbol: ER_WARN_NO_SERVERID_SPECIFIED; SQLSTATE: HY000

Message: You have not provided a mandatory server-id. Servers in a replication topology must have unique server-ids. Please refer to the proper server start-up parameters documentation.

Error number: MY-010914; Symbol: ER_ABORTING_USER_CONNECTION; SQLSTATE:

HY000

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).

 $Error\ number:\ MY-010915;\ Symbol:\ ER_SQL_MODE_MERGED_WITH_STRICT_MODE;$

SQLSTATE: HY000

Message: 'NO_ZERO_DATE', 'NO_ZERO_IN_DATE' and 'ERROR_FOR_DIVISION_BY_ZERO' sql modes should be used with strict mode. They will be merged with strict mode in a future release.

Error number: MY-010916; Symbol: ER_GTID_PURGED_WAS_UPDATED; SQLSTATE: HY000 Message: @@GLOBAL.GTID PURGED was changed from '%s' to '%s'.

Error number: MY-010917; Symbol: ER_GTID_EXECUTED_WAS_UPDATED; SQLSTATE:

HY000

Message: @@GLOBAL.GTID EXECUTED was changed from '%s' to '%s'.

Error number: MY-010918; Symbol: ER DEPRECATE MSG WITH REPLACEMENT;

SQLSTATE: HY000

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead.

Error number: MY-010919; Symbol: ER TRG CREATION CTX NOT SET; SQLSTATE:

HY000

Message: Triggers for table '%s'.'%s' have no creation context

Error number: MY-010920; Symbol: ER FILE HAS OLD FORMAT; SQLSTATE: HY000

Message: '%s' has an old format, you should re-create the '%s' object(s)

Error number: MY-010921; Symbol: ER VIEW CREATION CTX NOT SET; SQLSTATE:

HY000

Message: View '%s'.'%s' has no creation context

Error number: MY-010923; Symbol: ER TABLE UPGRADE REQUIRED; SQLSTATE: HY000

Message: Table upgrade required. Please do "REPAIR TABLE `%s`" or dump/reload to fix it!

Error number: MY-010924; Symbol: ER GET ERRNO FROM STORAGE ENGINE;

SQLSTATE: HY000

Message: Got error %d - '%s' from storage engine.

Error number: MY-010925; Symbol: ER ACCESS DENIED ERROR WITHOUT PASSWORD;

SQLSTATE: HY000

Message: Access denied for user '%s'@'%s'

Error number: MY-010926; Symbol: ER ACCESS DENIED_ERROR_WITH_PASSWORD;

SQLSTATE: HY000

Message: Access denied for user '%s'@'%s' (using password: %s)

Error number: MY-010927; Symbol: ER ACCESS DENIED FOR USER ACCOUNT LOCKED;

SQLSTATE: HY000

Message: Access denied for user '%s'@'%s'. Account is locked.

Error number: MY-010928; Symbol: ER MUST CHANGE EXPIRED PASSWORD;

SQLSTATE: HY000

Message: Your password has expired. To log in you must change it using a client that supports

expired passwords.

Error number: MY-010929; Symbol:

ER SYSTEM TABLES NOT SUPPORTED BY STORAGE ENGINE; SQLSTATE: HY000

Message: Storage engine '%s' does not support system tables. [%s.%s].

Error number: MY-010930; Symbol: ER FILESORT TERMINATED; SQLSTATE: HY000

Message: Sort aborted

Error number: MY-010931; Symbol: ER SERVER STARTUP MSG; SQLSTATE: HY000

Message: %s: ready for connections. Version: '%s' socket: '%s' port: %d %s.

Error number: MY-010932; Symbol: ER FAILED TO FIND LOCALE NAME; SQLSTATE:

HY000

Message: Unknown locale: '%s'.

Error number: MY-010933; Symbol: ER_FAILED_TO_FIND_COLLATION_NAME; SQLSTATE:

HY000

Message: Unknown collation: '%s'.

Error number: MY-010934; Symbol: ER_SERVER_OUT_OF_RESOURCES; SQLSTATE: HY000 Message: Out of memory; check if mysqld or some other process uses all available memory; if not,

you may have to use 'ulimit' to allow mysqld to use more memory or you can add more swap space

Error number: MY-010935; Symbol: ER SERVER OUTOFMEMORY; SQLSTATE: HY000

Message: Out of memory; restart server and try again (needed %d bytes)

Error number: MY-010936; Symbol: ER INVALID COLLATION FOR CHARSET; SQLSTATE:

HY000

Message: COLLATION '%s' is not valid for CHARACTER SET '%s'

Error number: MY-010937; Symbol: ER_CANT_START_ERROR_LOG_SERVICE; SQLSTATE:

HY000

Message: Failed to set %s at or around "%s" -- service is valid, but can not be initialized; please

check its configuration and make sure it can read its input(s) and write to its output(s).

Error number: MY-010938; Symbol: ER_CREATING_NEW_UUID_FIRST_START; SQLSTATE:

HY000

Message: Generating a new UUID: %s.

Error number: MY-010939; Symbol: ER FAILED TO GET ABSOLUTE PATH; SQLSTATE:

HY000

Message: Failed to get absolute path of program executable %s

Error number: MY-010940; Symbol:

ER PERFSCHEMA COMPONENTS INFRASTRUCTURE BOOTSTRAP; SQLSTATE: HY000

Message: Failed to bootstrap performance schema components infrastructure.

Error number: MY-010941; Symbol:

ER PERFSCHEMA COMPONENTS INFRASTRUCTURE SHUTDOWN; SQLSTATE: HY000

Message: Failed to deinit performance schema components infrastructure.

Error number: MY-010942; Symbol: ER_DUP_FD_OPEN_FAILED; SQLSTATE: HY000

Message: Could not open duplicate fd for %s: %s.

Error number: MY-010943; Symbol: ER SYSTEM VIEW INIT FAILED; SQLSTATE: HY000

Message: System views initialization failed.

Error number: MY-010944; Symbol: ER RESOURCE GROUP POST INIT FAILED;

SQLSTATE: HY000

Message: Resource group post initialization failed.

Error number: MY-010945; Symbol: ER_RESOURCE_GROUP_SUBSYSTEM_INIT_FAILED;

SQLSTATE: HY000

Message: Resource Group subsystem initialization failed.

Error number: MY-010946; Symbol: ER FAILED START MYSQLD DAEMON; SQLSTATE:

HY000

Message: Failed to start mysqld daemon. Check mysqld error log.

Error number: MY-010947; Symbol: ER CANNOT CHANGE TO ROOT DIR; SQLSTATE:

HY000

Message: Cannot change to root directory: %s.

Error number: MY-010948; Symbol: ER PERSISTENT PRIVILEGES BOOTSTRAP;

SOLSTATE: HY000

Message: Failed to bootstrap persistent privileges.

Error number: MY-010949; Symbol: ER BASEDIR SET TO; SQLSTATE: HY000

Message: Basedir set to %s.

Error number: MY-010950; Symbol: ER RPL FILTER ADD WILD DO TABLE FAILED;

SQLSTATE: HY000

Message: Could not add wild do table rule '%s'!

Error number: MY-010951; Symbol:

ER RPL FILTER ADD WILD IGNORE TABLE FAILED; SQLSTATE: HY000

Message: Could not add wild ignore table rule '%s'!

Error number: MY-010952; Symbol: ER_PRIVILEGE_SYSTEM_INIT_FAILED; SQLSTATE: HY000

Message: The privilege system failed to initialize correctly. For complete instructions on how to upgrade MySQL to a new version please see the 'Upgrading MySQL' section from the MySQL manual.

Error number: MY-010953; Symbol: ER CANNOT SET LOG ERROR SERVICES;

SQLSTATE: HY000

Message: Cannot set services "%s" requested in --log-error-services, using defaults.

Error number: MY-010954; Symbol: ER PERFSCHEMA TABLES INIT FAILED; SQLSTATE:

HY000

Message: Performance schema tables initialization failed.

Error number: MY-010955; Symbol:

ER TX EXTRACTION ALGORITHM FOR BINLOG TX DEPEDENCY TRACKING;

SQLSTATE: HY000

Message: The transaction write set extraction must be set to %s when

binlog_transaction_dependency_tracking is %s.

Error number: MY-010956; Symbol: ER_INVALID_REPLICATION_TIMESTAMPS;

SOLSTATE: HY000

Message: Invalid replication timestamps: original commit timestamp is more recent than the immediate commit timestamp. This may be an issue if delayed replication is active. Make sure that servers have their clocks set to the correct time. No further Message will be emitted until after timestamps become valid again.

Error number: MY-010957; Symbol: ER RPL TIMESTAMPS RETURNED TO NORMAL;

SOLSTATE: HY000

Message: The replication timestamps have returned to normal values.

Error number: MY-010958; Symbol: ER_BINLOG_FILE_OPEN_FAILED; SQLSTATE: HY000 Message: %s.

Error number: MY-010959; Symbol:

ER BINLOG EVENT WRITE TO STMT CACHE FAILED; SQLSTATE: HY000

Message: Failed to write an incident event into stmt cache.

Error number: MY-010960; Symbol: ER SLAVE RELAY LOG TRUNCATE INFO;

SQLSTATE: HY000

Message: Relaylog file %s size was %llu, but was truncated at %llu.

Error number: MY-010961; Symbol: ER_SLAVE_RELAY_LOG_PURGE_FAILED; SQLSTATE:

HY000

Message: Unable to purge relay log files. %s:%s.

 $Error\ number:\ MY-010962;\ Symbol:\ ER_RPL_SLAVE_FILTER_CREATE_FAILED;\ SQLSTATE:$

HY000

Message: Slave: failed in creating filter for channel '%s'.

Error number: MY-010963; Symbol: ER_RPL_SLAVE_GLOBAL_FILTERS_COPY_FAILED;

SQLSTATE: HY000

Message: Slave: failed in copying the global filters to its own per-channel filters on configuration for

channel '%s'.

Error number: MY-010964; Symbol: ER_RPL_SLAVE_RESET_FILTER_OPTIONS; SQLSTATE:

HY000

Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist.

The filter(s) have been discarded.

Error number: MY-010965; Symbol: ER MISSING GRANT SYSTEM TABLE; SQLSTATE:

HY000

Message: The system table mysql.global grants is missing. Please perform the MySQL upgrade

procedure.

Error number: MY-010966; Symbol: ER MISSING ACL SYSTEM TABLE; SQLSTATE: HY000

Message: ACL table mysql.%.*s missing. Some operations may fail.

Error number: MY-010967; Symbol:

ER ANONYMOUS AUTH ID NOT ALLOWED IN MANDATORY ROLES; SQLSTATE:

HY000

Message: Can't set mandatory role %s@%s: Anonymous authorization IDs are not allowed as roles.

Error number: MY-010968; Symbol: ER UNKNOWN AUTH ID IN MANDATORY ROLE;

SQLSTATE: HY000

Message: Can't set mandatory role: There's no such authorization ID %s@%s.

Error number: MY-010969; Symbol: ER WRITE ROW TO PARTITION FAILED; SQLSTATE:

HY000

Message: Table '%s' failed to move/insert a row from part %d into part %d: %s.

Error number: MY-010970; Symbol:

ER RESOURCE GROUP METADATA UPDATE SKIPPED; SQLSTATE: HY000

Message: Skipped updating resource group metadata in InnoDB read only mode.

Error number: MY-010971; Symbol:

ER FAILED TO PERSIST RESOURCE GROUP METADATA; SQLSTATE: HY000

Message: Failed to persist resource group %s to Data Dictionary.

Error number: MY-010972; Symbol: ER FAILED TO DESERIALIZE RESOURCE GROUP;

SQLSTATE: HY000

Message: Failed to deserialize resource group %s.

Error number: MY-010973; Symbol: ER FAILED TO UPDATE RESOURCE GROUP;

SOLSTATE: HY000

Message: Update of resource group %s failed.

Error number: MY-010974; Symbol: ER RESOURCE GROUP VALIDATION FAILED;

SQLSTATE: HY000

Message: Validation of resource group %s failed. Resource group is disabled.

Error number: MY-010975; Symbol:

ER FAILED TO ALLOCATE MEMORY FOR RESOURCE GROUP; SQLSTATE: HY000

Message: Unable to allocate memory for Resource Group %s.

Error number: MY-010976; Symbol:

ER FAILED TO ALLOCATE MEMORY FOR RESOURCE GROUP HASH; SQLSTATE:

HY000

Message: Failed to allocate memory for resource group hash.

Error number: MY-010977; Symbol: ER FAILED TO ADD RESOURCE GROUP TO MAP;

SQLSTATE: HY000

Message: Failed to add resource group %s to resource group map.

Error number: MY-010978; Symbol: ER RESOURCE GROUP IS DISABLED; SQLSTATE:

HY000

Message: Resource group feature is disabled. (Server is compiled with DISABLE PSI THREAD).

Error number: MY-010979; Symbol:

ER FAILED TO APPLY RESOURCE GROUP CONTROLLER; SQLSTATE: HY000

Message: Unable to apply resource group controller %s.

2.8 错误码及错误信息汇总 08

Error number: MY-010980; Symbol:

ER FAILED TO ACQUIRE LOCK ON RESOURCE GROUP; SQLSTATE: HY000

Message: Unable to acquire lock on the resource group %s. Hint to switch resource group shall be

ignored.

Error number: MY-010981; Symbol:

ER PFS NOTIFICATION FUNCTION REGISTER FAILED; SQLSTATE: HY000

Message: PFS %s notification function registration failed.

Error number: MY-010982; Symbol: ER RES GRP SET THR AFFINITY FAILED;

SOLSTATE: HY000

Message: Unable to bind thread id %llu to cpu id %u (error code %d - %s).

Error number: MY-010983; Symbol: ER_RES_GRP_SET_THR_AFFINITY_TO_CPUS_FAILED;

SQLSTATE: HY000

Message: Unable to bind thread id %llu to cpu ids (error code %d - %s).

Error number: MY-010984; Symbol: ER RES GRP THD UNBIND FROM CPU FAILED;

SQLSTATE: HY000

Message: Unbind thread id %llu failed. (error code %d - %s).

Error number: MY-010985; Symbol: ER RES GRP SET THREAD PRIORITY FAILED;

SQLSTATE: HY000

Message: Setting thread priority %d to thread id %llu failed. (error code %d - %s).

Error number: MY-010986; Symbol:

ER RES GRP FAILED TO DETERMINE NICE CAPABILITY; SQLSTATE: HY000

Message: Unable to determine CAP SYS NICE capability.

Error number: MY-010987; Symbol: ER RES GRP FAILED TO GET THREAD HANDLE;

SQLSTATE: HY000

Message: %s failed: Failed to get handle for thread %llu.

Error number: MY-010988; Symbol: ER RES GRP GET THREAD PRIO NOT SUPPORTED;

SQLSTATE: HY000

Message: Retrieval of thread priority unsupported on %s.

Error number: MY-010989; Symbol: ER RES GRP FAILED DETERMINE CPU COUNT;

SQLSTATE: HY000

Message: Unable to determine the number of CPUs.

Error number: MY-010990; Symbol: ER RES GRP FEATURE NOT AVAILABLE;

SQLSTATE: HY000

Message: Resource group feature shall not be available. Incompatible thread handling option.

Error number: MY-010991; Symbol: ER RES GRP INVALID THREAD PRIORITY;

SQLSTATE: HY000

Message: Invalid thread priority %d for a %s resource group. Allowed range is [%d, %d].

Error number: MY-010992; Symbol:

ER RES GRP SOLARIS PROCESSOR BIND TO CPUID FAILED; SQLSTATE: HY000

Message: bind to cpu failed: processor bind for cpuid %u failed (error code %d - %s).

Error number: MY-010993; Symbol:

ER_RES_GRP_SOLARIS_PROCESSOR_BIND_TO_THREAD_FAILED; SQLSTATE: HY000 Message: bind to cpu failed: processor bind for thread %%llx with cpu id %u (error code %d - %s).

Error number: MY-010994; Symbol:

ER RES GRP SOLARIS PROCESSOR AFFINITY FAILED; SQLSTATE: HY000

Message: %s failed: processor affinity failed (error code %d - %s).

Error number: MY-010995; Symbol:

ER DD UPGRADE RENAME IDX STATS FILE FAILED; SQLSTATE: HY000

Message: Error in renaming mysql index stats.ibd.

Error number: MY-010996; Symbol: ER DD UPGRADE DD OPEN FAILED; SQLSTATE:

HY000

Message: Error in opening data directory %s.

Error number: MY-010997; Symbol:

ER DD UPGRADE FAILED TO FETCH TABLESPACES; SQLSTATE: HY000

Message: Error in fetching list of tablespaces.

Error number: MY-010998; Symbol:

ER DD UPGRADE FAILED TO ACQUIRE TABLESPACE; SQLSTATE: HY000

Message: Error in acquiring Tablespace for SDI insertion %s.

Error number: MY-010999; Symbol:

ER DD UPGRADE FAILED TO RESOLVE TABLESPACE ENGINE; SQLSTATE: HY000

Message: Error in resolving Engine name for tablespace %s with engine %s.

Error number: MY-011000; Symbol: ER FAILED TO CREATE SDI FOR TABLESPACE;

SQLSTATE: HY000

Message: Error in creating SDI for %s tablespace.

Error number: MY-011001; Symbol: ER_FAILED_TO_STORE_SDI_FOR_TABLESPACE;

SQLSTATE: HY000

Message: Error in storing SDI for %s tablespace.

Error number: MY-011002; Symbol: ER DD UPGRADE FAILED TO FETCH TABLES;

SQLSTATE: HY000

Message: Error in fetching list of tables.

Error number: MY-011003; Symbol: ER DD UPGRADE DD POPULATED; SQLSTATE:

HY000

Message: Finished populating Data Dictionary tables with data.

Error number: MY-011004; Symbol: ER DD UPGRADE INFO FILE OPEN FAILED;

SOLSTATE: HY000

Message: Could not open the upgrade info file '%s' in the MySQL servers datadir, errno: %d.

Error number: MY-011005; Symbol: ER DD UPGRADE INFO FILE CLOSE FAILED;

SQLSTATE: HY000

Message: Could not close the upgrade info file '%s' in the MySQL servers datadir, errno: %d.

Error number: MY-011006; Symbol:

ER DD UPGRADE TABLESPACE MIGRATION FAILED; SQLSTATE: HY000

Message: Got error %d from SE while migrating tablespaces.

Error number: MY-011007; Symbol:

ER DD UPGRADE FAILED TO CREATE TABLE STATS; SQLSTATE: HY000

Message: Error in creating TABLE statistics entry. Fix statistics data by using ANALYZE command.

Error number: MY-011008; Symbol:

ER DD UPGRADE TABLE STATS MIGRATE COMPLETED; SQLSTATE: HY000

Message: Finished migrating TABLE statistics data.

Error number: MY-011009; Symbol:

ER DD UPGRADE FAILED TO CREATE INDEX STATS; SQLSTATE: HY000

Message: Error in creating Index statistics entry. Fix statistics data by using ANALYZE command.

Error number: MY-011010; Symbol:

ER DD UPGRADE INDEX STATS MIGRATE COMPLETED; SQLSTATE: HY000

Message: Finished migrating INDEX statistics data.

Error number: MY-011011; Symbol: ER DD UPGRADE FAILED FIND VALID DATA DIR;

SQLSTATE: HY000

Message: Failed to find valid data directory.

Error number: MY-011012; Symbol: ER DD UPGRADE START; SQLSTATE: HY000

Message: Starting upgrade of data directory.

Error number: MY-011013; Symbol: ER DD UPGRADE FAILED INIT DD SE; SQLSTATE:

HY000

Message: Failed to initialize DD Storage Engine.

Error number: MY-011014; Symbol:

ER DD UPGRADE FOUND PARTIALLY UPGRADED DD ABORT; SQLSTATE: HY000

Message: Found partially upgraded DD. Aborting upgrade and deleting all DD tables. Start the

upgrade process again.

Error number: MY-011015; Symbol:

ER DD UPGRADE FOUND PARTIALLY UPGRADED DD CONTINUE; SQLSTATE:

HY000

Message: Found partially upgraded DD. Upgrade will continue and start the server.

Error number: MY-011016; Symbol: ER DD UPGRADE SE LOGS FAILED; SQLSTATE:

HY000

Message: Error in upgrading engine logs.

Error number: MY-011017; Symbol: ER DD UPGRADE SDI INFO UPDATE FAILED;

SQLSTATE: HY000

Message: Error in updating SDI information.

Error number: MY-011018; Symbol: ER SKIP UPDATING METADATA IN SE RO MODE;

SOLSTATE: HY000

Message: Skip updating %s metadata in InnoDB read-only mode.

Error number: MY-011019; Symbol: ER CREATED SYSTEM WITH VERSION; SQLSTATE:

HY000

Message: Created system views with I S version %d.

Error number: MY-011020; Symbol: ER UNKNOWN ERROR DETECTED IN SE;

SQLSTATE: HY000

Message: Unknown error detected %d in handler.

Error number: MY-011021; Symbol: ER READ LOG EVENT FAILED; SQLSTATE: HY000

Message: Error in Log event::read log event(): '%s', data len: %lu, event type: %d.

Error number: MY-011022; Symbol: ER ROW DATA TOO BIG TO WRITE IN BINLOG;

SQLSTATE: HY000

Message: The row data is greater than 4GB, which is too big to write to the binary log.

Error number: MY-011023; Symbol: ER FAILED TO CONSTRUCT DROP EVENT QUERY;

SQLSTATE: HY000

Message: Unable to construct DROP EVENT SQL query string.

Error number: MY-011024; Symbol: ER FAILED TO BINLOG DROP EVENT; SQLSTATE:

HY000

Message: Unable to binlog drop event %s.%s.

Error number: MY-011025; Symbol: ER FAILED TO START SLAVE THREAD; SQLSTATE:

HY000

Message: Failed to start slave threads for channel '%s'.

Error number: MY-011026; Symbol: ER RPL IO THREAD KILLED; SQLSTATE: HY000

Message: %s%s.

Error number: MY-011027; Symbol: ER SLAVE RECONNECT FAILED; SQLSTATE: HY000

Message: Failed registering on master, reconnecting to try again, log '%s' at position %s. %s.

Error number: MY-011028; Symbol: ER SLAVE KILLED AFTER RECONNECT; SQLSTATE:

HY000

Message: Slave I/O thread killed during or after reconnect.

Error number: MY-011029; Symbol: ER_SLAVE_NOT_STARTED_ON_SOME_CHANNELS; SOLSTATE: HY000

Message: Some of the channels are not created/initialized properly. Check for additional Messages above. You will not be able to start replication on those channels until the issue is resolved and the server restarted.

Error number: MY-011030; Symbol: ER_FAILED_TO_ADD_RPL_FILTER; SQLSTATE: HY000 Message: Failed to add a replication filter into filter map for channel '%s'.

Error number: MY-011031; Symbol:

ER_PER_CHANNEL_RPL_FILTER_CONF_FOR_GRP_RPL; SQLSTATE: HY000

Message: There are per-channel replication filter(s) configured for group replication channel '%s' which is disallowed. The filter(s) have been discarded.

Error number: MY-011032; Symbol: ER_RPL_FILTERS_NOT_ATTACHED_TO_CHANNEL; SQLSTATE: HY000

Message: There are per-channel replication filter(s) configured for channel '%s' which does not exist. The filter(s) have been discarded.

Error number: MY-011033; Symbol:

 $ER_FAILED_TO_BUILD_DO_AND_IGNORE_TABLE_HASHES; SQLSTATE: HY000$

Message: An error occurred while building do_table and ignore_table rules to hashes for per-channel filter.

Error number: MY-011034; Symbol: ER_CLONE_PLUGIN_NOT_LOADED; SQLSTATE: HY000 Message: Clone plugin not loaded.

Error number: MY-011034; Symbol: ER_CLONE_PLUGIN_NOT_LOADED_TRACE;

SQLSTATE: HY000

Message: Clone plugin cannot be loaded.

Error number: MY-011035; Symbol: ER_CLONE_HANDLER_EXISTS; SQLSTATE: HY000 Message: Clone Handler exists.

Error number: MY-011035; Symbol: ER_CLONE_HANDLER_EXIST_TRACE; SQLSTATE: HY000

Message: Clone Handler exists.

Error number: MY-011036; Symbol: ER FAILED TO CREATE CLONE HANDLER;

SOLSTATE: HY000

Message: Could not create Clone Handler.

Error number: MY-011036; Symbol: ER CLONE CREATE HANDLER FAIL TRACE;

SQLSTATE: HY000

Message: Could not create Clone Handler.

Error number: MY-011037; Symbol: ER CYCLE TIMER IS NOT AVAILABLE; SQLSTATE:

HY000

Message: The CYCLE timer is not available. WAIT events in the performance schema will not be

timed.

Error number: MY-011038; Symbol: ER NANOSECOND TIMER IS NOT AVAILABLE;

SQLSTATE: HY000

Message: The NANOSECOND timer is not available.

 $IDLE/STAGE/STATEMENT/TRANSACTION\ events\ in\ the\ performance_schema\ will\ not\ be$

timed.

Error number: MY-011039; Symbol: ER_MICROSECOND_TIMER_IS_NOT_AVAILABLE;

SQLSTATE: HY000

Message: The MICROSECOND timer is not available.

IDLE/STAGE/STATEMENT/TRANSACTION events in the performance schema will not be

timed.

Error number: MY-011040; Symbol: ER_PFS_MALLOC_ARRAY_OVERFLOW; SQLSTATE:

HY000

Message: Failed to allocate memory for %zu chunks each of size %zu for buffer '%s' due to

overflow.

Error number: MY-011041; Symbol: ER PFS MALLOC ARRAY OOM; SQLSTATE: HY000

Message: Failed to allocate %zu bytes for buffer '%s' due to out-of-memory.

Error number: MY-011042; Symbol: ER INNODB FAILED TO FIND IDX WITH KEY NO;

SQLSTATE: HY000

Message: InnoDB could not find index %s key no %u for table %s through its index translation table.

Error number: MY-011043; Symbol: ER INNODB FAILED TO FIND IDX; SQLSTATE:

HY000

Message: Cannot find index %s in InnoDB index translation table.

Error number: MY-011044; Symbol:

ER INNODB FAILED TO FIND IDX FROM DICT CACHE; SQLSTATE: HY000

Message: InnoDB could not find key no %u with name %s from dict cache for table %s.

Error number: MY-011045; Symbol: ER INNODB ACTIVE INDEX CHANGE FAILED;

SOLSTATE: HY000

Message: InnoDB: change active index(%u) failed.

Error number: MY-011046; Symbol: ER_INNODB_DIFF_IN_REF_LEN; SQLSTATE: HY000

Message: Stored ref len is %lu, but table ref len is %lu.

Error number: MY-011047; Symbol: ER_WRONG_TYPE_FOR_COLUMN_PREFIX_IDX_FLD;

SQLSTATE: HY000

Message: MySQL is trying to create a column prefix index field, on an inappropriate data type. Table

name %s, column name %s.

Error number: MY-011048; Symbol: ER INNODB CANNOT CREATE TABLE; SQLSTATE:

HY000

Message: Cannot create table %s.

Error number: MY-011049; Symbol: ER INNODB INTERNAL INDEX; SQLSTATE: HY000

Message: Found index %s in InnoDB index list but not its MySQL index number. It could be an

InnoDB internal index.

Error number: MY-011050; Symbol:

ER INNODB IDX CNT MORE THAN DEFINED IN MYSQL; SQLSTATE: HY000

Message: InnoDB: Table %s contains %lu indexes inside InnoDB, which is different from the

number of indexes %u defined in MySQL.

Error number: MY-011051; Symbol:

ER_INNODB_IDX_CNT_FEWER_THAN_DEFINED_IN_MYSQL; SQLSTATE: HY000

Message: Table %s contains fewer indexes inside InnoDB than are defined in the MySQL. Have you

mixed up with data dictionary from different installation?

Error number: MY-011052; Symbol: ER INNODB IDX COLUMN CNT DIFF; SQLSTATE:

HY000

Message: Index %s of %s has %lu columns unique inside InnoDB, but MySQL is asking statistics

for %lu columns. Have you mixed data dictionary from different installation?

Error number: MY-011053; Symbol: ER INNODB USE MONITOR GROUP NAME;

SQLSTATE: HY000

Message: Monitor counter '%s' cannot be turned on/off individually. Please use its module name to

turn on/off the counters in the module as a group.

Error number: MY-011054; Symbol:

ER INNODB_MONITOR_DEFAULT_VALUE_NOT_DEFINED; SQLSTATE: HY000

Message: Default value is not defined for this set option. Please specify correct counter or module name.

Error number: MY-011055; Symbol: ER_INNODB_MONITOR_IS_ENABLED; SQLSTATE:

HY000

Message: InnoDB: Monitor %s is already enabled.

Error number: MY-011056; Symbol: ER INNODB INVALID MONITOR COUNTER NAME;

SQLSTATE: HY000

Message: Invalid monitor counter: %s.

Error number: MY-011057; Symbol: ER WIN LOAD LIBRARY FAILED; SQLSTATE: HY000

Message: LoadLibrary("%s") failed: GetLastError returns %lu.

Error number: MY-011058; Symbol: ER PARTITION HANDLER ADMIN MSG; SQLSTATE:

HY000

Message: %s.

Error number: MY-011059; Symbol: ER RPL RLI INIT INFO MSG; SQLSTATE: HY000

Message: %s.

Error number: MY-011060; Symbol: ER_DD_UPGRADE_TABLE_INTACT_ERROR;

SOLSTATE: HY000

Message: %s.

Error number: MY-011061; Symbol: ER SERVER INIT COMPILED IN COMMANDS;

SQLSTATE: HY000

Message: %s.

Error number: MY-011062; Symbol: ER MYISAM CHECK_METHOD_ERROR; SQLSTATE:

HY000

Message: %s.

Error number: MY-011063; Symbol: ER MYISAM CRASHED ERROR; SQLSTATE: HY000

Message: %s.

Error number: MY-011064; Symbol: ER WAITPID FAILED; SQLSTATE: HY000

Message: Unable to wait for process %lld.

Error number: MY-011065; Symbol: ER FAILED TO FIND MYSQLD STATUS; SQLSTATE:

HY000

Message: Unable to determine if daemon is running: %s (rc=%d).

Error number: MY-011066; Symbol: ER INNODB ERROR LOGGER MSG; SQLSTATE:

HY000

Message: %s

Error number: MY-011067; Symbol: ER INNODB ERROR LOGGER FATAL MSG;

SQLSTATE: HY000

Message: [FATAL] InnoDB: %s

Error number: MY-011068; Symbol: ER DEPRECATED SYNTAX WITH REPLACEMENT;

SQLSTATE: HY000

Message: The syntax '%s' is deprecated and will be removed in a future release. Please use %s

instead.

Error number: MY-011069; Symbol: ER_DEPRECATED_SYNTAX_NO_REPLACEMENT;

SQLSTATE: HY000

Message: The syntax '%s' is deprecated and will be removed in a future release.

Error number: MY-011070; Symbol: ER DEPRECATE MSG NO REPLACEMENT;

SQLSTATE: HY000

Message: '%s' is deprecated and will be removed in a future release.

Error number: MY-011071; Symbol: ER LOG PRINTF MSG; SQLSTATE: HY000

Message: %s

Error number: MY-011072; Symbol: ER BINLOG LOGGING NOT POSSIBLE; SQLSTATE:

HY000

Message: Binary logging not possible. Message: %s.

Error number: MY-011073; Symbol: ER FAILED TO SET PERSISTED OPTIONS;

SQLSTATE: HY000

Message: Failed to set persisted options.

Error number: MY-011074; Symbol:

ER COMPONENTS FAILED TO ACQUIRE SERVICE IMPLEMENTATION; SQLSTATE:

HY000

Message: Cannot acquire specified service implementation: '%s'.

Error number: MY-011075; Symbol: ER RES GRP INVALID VCPU RANGE; SQLSTATE:

HY000

Message: Invalid VCPU range %u-%u.

Error number: MY-011076; Symbol: ER_RES_GRP_INVALID_VCPU_ID; SQLSTATE: HY000 Message: Invalid cpu id %u.

Error number: MY-011077; Symbol: ER ERROR DURING FLUSH LOG COMMIT PHASE;

SQLSTATE: HY000

Message: Got error %d during FLUSH LOGS.

Error number: MY-011078; Symbol: ER_DROP_DATABASE_FAILED_RMDIR_MANUALLY; SQLSTATE: HY000

Message: Problem while dropping database. Can't remove database directory (%s). Please remove it manually.

Error number: MY-011079; Symbol:

ER_BINLOG_EXPIRAY_LOG_DAYS_AND_SECS_USED_TOGETHER; SQLSTATE: HY000

Message: The option expire_logs_days cannot be used together with option binlog_expire_logs_seconds. Therefore, value of expire_logs_days is ignored.

Error number: MY-011079; Symbol: ER_EXPIRE_LOGS_DAYS_IGNORED; SQLSTATE: HY000

Message: The option expire_logs_days cannot be used together with option binlog_expire_logs_seconds. Therefore, value of expire_logs_days is ignored.

Error number: MY-011080; Symbol: ER_BINLOG_MALFORMED_OR_OLD_RELAY_LOG; SQLSTATE: HY000

Message: malformed or very old relay log which does not have FormatDescriptor.

Error number: MY-011081; Symbol:

ER DD UPGRADE VIEW COLUMN NAME TOO LONG; SQLSTATE: HY000

Message: Upgrade of view '%s.%s' failed. Re-create the view with the explicit column name lesser

than 64 characters.

Error number: MY-011082; Symbol: ER_TABLE_NEEDS_DUMP_UPGRADE; SQLSTATE: HY000

Message: Table upgrade required for `%s`.`%s`. Please dump/reload table to fix it!

Error number: MY-011083; Symbol:

ER_DD_UPGRADE_FAILED_TO_UPDATE_VER_NO_IN_TABLESPACE; SQLSTATE: HY000 Message: Error in updating version number in %s tablespace.

Error number: MY-011084; Symbol: ER_KEYRING_MIGRATION_FAILED; SQLSTATE: HY000 Message: Keyring migration failed.

Error number: MY-011085; Symbol: ER KEYRING MIGRATION SUCCESSFUL; SQLSTATE:

HY000

Message: Keyring migration successful.

Error number: MY-011086; Symbol: ER RESTART RECEIVED INFO; SQLSTATE: HY000

Message: Received RESTART from user %s. Restarting mysqld (Version: %s).

Error number: MY-011087; Symbol: ER LCTN CHANGED; SQLSTATE: HY000

Message: Different lower case table names settings for server ('%u') and data dictionary ('%u').

Error number: MY-011088; Symbol: ER DD INITIALIZE; SQLSTATE: HY000

Message: Data dictionary initializing version '%u'.

Error number: MY-011089; Symbol: ER DD RESTART; SQLSTATE: HY000

Message: Data dictionary restarting version '%u'.

Error number: MY-011090; Symbol: ER DD UPGRADE; SQLSTATE: HY000

Message: Data dictionary upgrading from version '%u' to '%u'.

Error number: MY-011091; Symbol: ER DD UPGRADE OFF; SQLSTATE: HY000

Message: Data dictionary upgrade prohibited by the command line option '--no dd upgrade'.

Error number: MY-011092; Symbol: ER DD UPGRADE VERSION NOT SUPPORTED;

SQLSTATE: HY000

Message: Upgrading the data dictionary from dictionary version '%u' is not supported.

Error number: MY-011093; Symbol: ER DD UPGRADE SCHEMA UNAVAILABLE;

SOLSTATE: HY000

Message: Upgrading the data dictionary failed, temporary schema name '%s' not available.

Error number: MY-011094; Symbol: ER DD MINOR DOWNGRADE; SQLSTATE: HY000

Message: Data dictionary minor downgrade from version '%u' to '%u'.

Error number: MY-011095; Symbol:

ER DD MINOR DOWNGRADE VERSION NOT SUPPORTED; SQLSTATE: HY000

Message: Minor downgrade of the Data dictionary from dictionary version '%u' is not supported.

Error number: MY-011096; Symbol: ER DD NO VERSION FOUND; SQLSTATE: HY000

Message: No data dictionary version number found.

Error number: MY-011097; Symbol:

ER THREAD POOL NOT SUPPORTED ON PLATFORM; SQLSTATE: HY000

Message: Thread pool not supported, requires a minimum of %s.

Error number: MY-011098; Symbol: ER_THREAD_POOL_SIZE_TOO_LOW; SQLSTATE:

HY000

Message: thread_pool_size=0 means thread pool disabled, Allowed range of thread_pool_size is %d-%d

Error number: MY-011099; Symbol: ER_THREAD_POOL_SIZE_TOO_HIGH; SQLSTATE: HY000

Message: thread_pool_size=%lu is too high, %d is maximum, thread pool is disabled. Allowed range of thread_pool_size is %d-%d.

Error number: MY-011100; Symbol: ER THREAD POOL ALGORITHM INVALID;

SQLSTATE: HY000

Message: thread_pool_algorithm can be set to 0 and 1, 0 indicates the default low concurrency algorithm, 1 means a high concurrency algorithm.

Error number: MY-011101; Symbol: ER_THREAD_POOL_INVALID_STALL_LIMIT;

SQLSTATE: HY000

Message: thread_pool_stall_limit can be %d at minimum and %d at maximum, smaller values would render the thread pool fairly useless and higher values could make it possible to have undetected deadlock issues in the MySQL Server.

Error number: MY-011102; Symbol: ER THREAD POOL INVALID PRIO KICKUP TIMER;

SQLSTATE: HY000

Message: Invalid value of thread pool prio kickup timer specified. Value of

thread pool prio kickup timer should be in range 0-4294967294.

Error number: MY-011103; Symbol:

ER THREAD POOL MAX UNUSED THREADS INVALID; SQLSTATE: HY000

Message: thread pool max unused threads cannot be set higher than %d.

Error number: MY-011104; Symbol: ER_THREAD_POOL_CON_HANDLER_INIT_FAILED;

SOLSTATE: HY000

Message: Failed to instantiate the connection handler object.

Error number: MY-011105; Symbol: ER THREAD POOL INIT FAILED; SQLSTATE: HY000

Message: Failed to initialize thread pool plugin.

Error number: MY-011107; Symbol:

ER THREAD POOL CANNOT SET THREAD SPECIFIC DATA; SQLSTATE: HY000

Message: Can't setup connection teardown thread-specific data.

Error number: MY-011108; Symbol:

ER THREAD POOL FAILED TO CREATE CONNECT HANDLER THD; SQLSTATE:

HY000

Message: Creation of connect handler thread failed.

Error number: MY-011109; Symbol:

ER THREAD POOL FAILED TO CREATE THD AND AUTH CONN; SQLSTATE: HY000

Message: Failed to create thd and authenticate connection.

Error number: MY-011110; Symbol:

ER THREAD POOL FAILED PROCESS CONNECT EVENT; SQLSTATE: HY000

Message: Failed to process connection event.

Error number: MY-011111; Symbol: ER_THREAD_POOL_FAILED_TO_CREATE_POOL;

SQLSTATE: HY000

Message: Can't create pool thread (error %d, errno: %d).

Error number: MY-011112; Symbol: ER_THREAD POOL RATE LIMITED ERROR MSGS;

SQLSTATE: HY000

Message: %.*s.

Error number: MY-011113; Symbol: ER TRHEAD POOL LOW LEVEL INIT FAILED;

SQLSTATE: HY000

Message: tp group_low_level_init() failed.

Error number: MY-011114; Symbol: ER THREAD POOL LOW LEVEL REARM FAILED;

SOLSTATE: HY000

Message: Rearm failed even after 30 seconds, can't continue without notify socket.

Error number: MY-011115; Symbol: ER THREAD POOL BUFFER TOO SMALL; SQLSTATE:

HY000

Message: %s: %s buffer is too small

Error number: MY-011116; Symbol: ER MECAB NOT SUPPORTED; SQLSTATE: HY000

Message: Mecab v%s is not supported, the lowest version supported is v%s.

Error number: MY-011117; Symbol: ER MECAB NOT VERIFIED; SQLSTATE: HY000

Message: Mecab v%s is not verified, the highest version supported is v%s.

Error number: MY-011118; Symbol: ER MECAB CREATING MODEL; SQLSTATE: HY000

Message: Mecab: Trying createModel(%s).

Error number: MY-011119; Symbol: ER_MECAB_FAILED_TO_CREATE_MODEL; SQLSTATE:

HY000

Message: Mecab: createModel() failed: %s.

Error number: MY-011120; Symbol: ER MECAB FAILED TO CREATE TRIGGER;

SQLSTATE: HY000

Message: Mecab: createTagger() failed: %s.

Error number: MY-011121; Symbol: ER MECAB UNSUPPORTED CHARSET; SQLSTATE:

HY000

Message: Mecab: Unsupported dictionary charset %s.

Error number: MY-011122; Symbol: ER MECAB CHARSET LOADED; SQLSTATE: HY000

Message: Mecab: Loaded dictionary charset is %s.

Error number: MY-011123; Symbol: ER_MECAB_PARSE_FAILED; SQLSTATE: HY000

Message: Mecab: parse() failed: %s.

Error number: MY-011124; Symbol: ER MECAB OOM WHILE PARSING TEXT; SQLSTATE:

HY000

Message: Mecab: parse() failed: out of memory.

Error number: MY-011125; Symbol: ER MECAB CREATE LATTICE FAILED; SQLSTATE:

HY000

Message: Mecab: createLattice() failed: %s.

Error number: MY-011126; Symbol: ER SEMISYNC TRACE ENTER FUNC; SQLSTATE:

HY000

Message: ---> %s enter.

Error number: MY-011127; Symbol: ER SEMISYNC TRACE EXIT WITH INT EXIT CODE;

SQLSTATE: HY000

Message: <--- %s exit (%d).

Error number: MY-011128; Symbol:

ER SEMISYNC TRACE EXIT WITH BOOL EXIT CODE; SQLSTATE: HY000

Message: <--- %s exit (%s).

Error number: MY-011129; Symbol: ER SEMISYNC TRACE EXIT; SQLSTATE: HY000

Message: <--- %s exit.

Error number: MY-011130; Symbol: ER SEMISYNC RPL INIT FOR TRX; SQLSTATE:

HY000

Message: Semi-sync replication initialized for transactions.

Error number: MY-011131; Symbol: ER SEMISYNC FAILED TO ALLOCATE TRX NODE;

SQLSTATE: HY000

Message: %s: transaction node allocation failed for: (%s, %lu).

Error number: MY-011132; Symbol: ER SEMISYNC BINLOG WRITE OUT OF ORDER;

SQLSTATE: HY000

Message: %s: binlog write out-of-order, tail (%s, %lu), new node (%s, %lu).

Error number: MY-011133; Symbol: ER SEMISYNC INSERT LOG INFO IN ENTRY;

SQLSTATE: HY000

Message: %s: insert (%s, %lu) in entry(%u).

Error number: MY-011134; Symbol: ER SEMISYNC PROBE LOG INFO IN ENTRY;

SQLSTATE: HY000

Message: %s: probe (%s, %lu) in entry(%u).

Error number: MY-011135; Symbol:

ER SEMISYNC CLEARED ALL ACTIVE TRANSACTION NODES; SQLSTATE: HY000

Message: %s: cleared all nodes.

Error number: MY-011136; Symbol:

ER SEMISYNC CLEARED ACTIVE TRANSACTION TILL POS; SQLSTATE: HY000

Message: %s: cleared %d nodes back until pos (%s, %lu).

Error number: MY-011137; Symbol: ER SEMISYNC REPLY MAGIC NO ERROR;

SQLSTATE: HY000

Message: Read semi-sync reply magic number error.

Error number: MY-011138; Symbol: ER_SEMISYNC_REPLY_PKT_LENGTH_TOO_SMALL;

SOLSTATE: HY000

Message: Read semi-sync reply length error: packet is too small.

Error number: MY-011139; Symbol: ER SEMISYNC REPLY BINLOG FILE TOO LARGE;

SQLSTATE: HY000

Message: Read semi-sync reply binlog file length too large.

Error number: MY-011140; Symbol: ER SEMISYNC SERVER REPLY; SQLSTATE: HY000

Message: %s: Got reply(%s, %lu) from server %u.

Error number: MY-011141; Symbol: ER SEMISYNC FUNCTION CALLED TWICE;

SQLSTATE: HY000 Message: %s called twice.

Error number: MY-011142; Symbol: ER SEMISYNC RPL ENABLED ON MASTER;

SQLSTATE: HY000

Message: Semi-sync replication enabled on the master.

Error number: MY-011143; Symbol: ER SEMISYNC MASTER OOM; SQLSTATE: HY000

Message: Cannot allocate memory to enable semi-sync on the master.

Error number: MY-011144; Symbol: ER SEMISYNC DISABLED ON MASTER; SQLSTATE:

HY000

Message: Semi-sync replication disabled on the master.

Error number: MY-011145; Symbol: ER SEMISYNC FORCED SHUTDOWN; SQLSTATE:

HY000

Message: SEMISYNC: Forced shutdown. Some updates might not be replicated.

Error number: MY-011146; Symbol: ER SEMISYNC MASTER GOT REPLY AT POS;

SQLSTATE: HY000

Message: %s: Got reply at (%s, %lu).

Error number: MY-011147; Symbol:

ER SEMISYNC MASTER SIGNAL ALL WAITING THREADS; SQLSTATE: HY000

Message: %s: signal all waiting threads.

Error number: MY-011148; Symbol: ER SEMISYNC MASTER TRX WAIT POS; SQLSTATE:

HY000

Message: %s: wait pos (%s, %lu), repl(%d).

Error number: MY-011149; Symbol: ER_SEMISYNC_BINLOG_REPLY_IS_AHEAD;

SQLSTATE: HY000

Message: %s: Binlog reply is ahead (%s, %lu).

Error number: MY-011150; Symbol: ER SEMISYNC MOVE BACK WAIT POS; SQLSTATE:

HY000

Message: %s: move back wait position (%s, %lu).

Error number: MY-011151; Symbol: ER SEMISYNC INIT WAIT POS; SQLSTATE: HY000

Message: %s: init wait position (%s, %lu).

Error number: MY-011152; Symbol: ER SEMISYNC WAIT TIME FOR BINLOG SENT;

SQLSTATE: HY000

Message: %s: wait %lu ms for binlog sent (%s, %lu).

Error number: MY-011153; Symbol: ER SEMISYNC WAIT FOR BINLOG TIMEDOUT;

SQLSTATE: HY000

Message: Timeout waiting for reply of binlog (file: %s, pos: %lu), semi-sync up to file %s,

position %lu.

Error number: MY-011154; Symbol:

ER SEMISYNC WAIT TIME ASSESSMENT FOR COMMIT TRX FAILED; SQLSTATE:

HY000

Message: Assessment of waiting time for commitTrx failed at wait position (%s, %lu).

Error number: MY-011155; Symbol: ER_SEMISYNC_RPL_SWITCHED_OFF; SQLSTATE:

HY000

Message: Semi-sync replication switched OFF.

Error number: MY-011156; Symbol: ER SEMISYNC RPL SWITCHED ON; SQLSTATE:

HY000

Message: Semi-sync replication switched ON at (%s, %lu).

Error number: MY-011157; Symbol: ER SEMISYNC NO SPACE IN THE PKT; SQLSTATE:

HY000

Message: No enough space in the packet for semi-sync extra header, semi-sync replication disabled.

Error number: MY-011158; Symbol: ER SEMISYNC SYNC HEADER UPDATE INFO;

SQLSTATE: HY000

Message: %s: server(%d), (%s, %lu) sync(%d), repl(%d).

Error number: MY-011159; Symbol: ER SEMISYNC FAILED TO INSERT TRX NODE;

SQLSTATE: HY000

Message: Semi-sync failed to insert tranx node for binlog file: %s, position: %lu.

Error number: MY-011160; Symbol: ER SEMISYNC TRX SKIPPED AT POS; SQLSTATE:

HY000

Message: %s: Transaction skipped at (%s, %lu).

Error number: MY-011161; Symbol: ER SEMISYNC MASTER FAILED ON NET FLUSH;

SOLSTATE: HY000

Message: Semi-sync master failed on net flush() before waiting for replica reply.

Error number: MY-011162; Symbol: ER SEMISYNC RECEIVED ACK IS SMALLER;

SQLSTATE: HY000

Message: The received ack is smaller than m greatest ack.

Error number: MY-011163; Symbol: ER SEMISYNC ADD ACK TO SLOT; SQLSTATE:

HY000

Message: Add the ack into slot %u.

Error number: MY-011164; Symbol: ER SEMISYNC UPDATE EXISTING SLAVE ACK;

SQLSTATE: HY000

Message: Update an exsiting ack in slot %u.

Error number: MY-011165; Symbol:

ER_SEMISYNC_FAILED_TO_START_ACK_RECEIVER_THD; SQLSTATE: HY000 Message: Failed to start semi-sync ACK receiver thread, could not create thread(errno:%d).

Error number: MY-011166; Symbol: ER SEMISYNC STARTING ACK RECEIVER THD;

SQLSTATE: HY000

Message: Starting ack receiver thread.

Error number: MY-011167; Symbol:

ER SEMISYNC FAILED TO WAIT ON DUMP SOCKET; SQLSTATE: HY000

Message: Failed to wait on semi-sync dump sockets, error: errno=%d.

Error number: MY-011168; Symbol: ER SEMISYNC STOPPING ACK RECEIVER THREAD;

SQLSTATE: HY000

Message: Stopping ack receiver thread.

Error number: MY-011169; Symbol:

ER SEMISYNC FAILED REGISTER SLAVE TO RECEIVER; SQLSTATE: HY000

Message: Failed to register slave to semi-sync ACK receiver thread.

Error number: MY-011170; Symbol: ER_SEMISYNC_START_BINLOG_DUMP_TO_SLAVE;

SQLSTATE: HY000

Message: Start %s binlog dump to slave (server id: %d), pos(%s, %lu).

Error number: MY-011171; Symbol: ER SEMISYNC STOP BINLOG DUMP TO SLAVE;

SQLSTATE: HY000

Message: Stop %s binlog_dump to slave (server_id: %d).

Error number: MY-011172; Symbol:

ER SEMISYNC UNREGISTER TRX OBSERVER FAILED; SQLSTATE: HY000

Message: unregister trans observer failed.

Error number: MY-011173; Symbol:

ER SEMISYNC UNREGISTER BINLOG STORAGE OBSERVER FAILED; SQLSTATE:

HY000

Message: unregister_binlog_storage_observer failed.

Error number: MY-011174; Symbol:

ER SEMISYNC UNREGISTER BINLOG_TRANSMIT_OBSERVER_FAILED; SQLSTATE:

HY000

Message: unregister binlog transmit observer failed.

Error number: MY-011175; Symbol: ER_SEMISYNC_UNREGISTERED_REPLICATOR;

SQLSTATE: HY000

Message: unregister replicator OK.

Error number: MY-011176; Symbol: ER_SEMISYNC_SOCKET_FD_TOO_LARGE; SQLSTATE:

HY000

Message: Semisync slave socket fd is %u. select() cannot handle if the socket fd is bigger than %u

(FD_SETSIZE).

Error number: MY-011177; Symbol: ER SEMISYNC SLAVE REPLY; SQLSTATE: HY000

Message: %s: reply - %d.

Error number: MY-011178; Symbol:

ER SEMISYNC MISSING MAGIC NO FOR SEMISYNC PKT; SQLSTATE: HY000

Message: Missing magic number for semi-sync packet, packet len: %lu.

Error number: MY-011179; Symbol: ER SEMISYNC SLAVE START; SQLSTATE: HY000

Message: Slave I/O thread: Start %s replication to master '%s@%s:%d' in log '%s' at position %lu.

Error number: MY-011180; Symbol: ER SEMISYNC SLAVE REPLY WITH BINLOG INFO;

SQLSTATE: HY000

Message: %s: reply (%s, %lu).

Error number: MY-011181; Symbol: ER SEMISYNC SLAVE NET FLUSH REPLY FAILED;

SQLSTATE: HY000

Message: Semi-sync slave net_flush() reply failed.

Error number: MY-011182; Symbol: ER SEMISYNC SLAVE SEND REPLY FAILED;

SOLSTATE: HY000

Message: Semi-sync slave send reply failed: %s (%d).

Error number: MY-011183; Symbol: ER SEMISYNC EXECUTION FAILED ON MASTER;

SQLSTATE: HY000

Message: Execution failed on master: %s; error %d

Error number: MY-011184; Symbol: ER SEMISYNC NOT SUPPORTED BY MASTER;

SQLSTATE: HY000

Message: Master server does not support semi-sync, fallback to asynchronous replication

Error number: MY-011185; Symbol: ER SEMISYNC SLAVE SET FAILED; SQLSTATE:

HY000

Message: Set 'rpl semi sync replica=1' on master failed

Error number: MY-011186; Symbol:

ER SEMISYNC FAILED TO STOP ACK RECEIVER THD; SQLSTATE: HY000

Message: Failed to stop ack receiver thread on my thread join, errno(%d).

Error number: MY-011187; Symbol:

ER FIREWALL FAILED TO READ FIREWALL TABLES; SQLSTATE: HY000

Message: Failed to read the firewall tables

Error number: MY-011188; Symbol:

ER FIREWALL FAILED TO REG DYNAMIC PRIVILEGES; SQLSTATE: HY000

Message: Failed to register dynamic privileges

Error number: MY-011189; Symbol:

ER FIREWALL RECORDING STMT WAS TRUNCATED; SQLSTATE: HY000

Message: Statement was truncated and not recorded: %s

Error number: MY-011190; Symbol: ER_FIREWALL_RECORDING_STMT_WITHOUT_TEXT;

SOLSTATE: HY000

Message: Statement with no text was not recorded

Error number: MY-011191; Symbol: ER FIREWALL SUSPICIOUS STMT; SQLSTATE: HY000

Message: SUSPICIOUS STATEMENT from '%s'. Reason: %s Statement: %s

Error number: MY-011192; Symbol: ER FIREWALL ACCESS DENIED; SQLSTATE: HY000

Message: ACCESS DENIED for '%s'. Reason: %s Statement: %s

Error number: MY-011193; Symbol: ER FIREWALL SKIPPED UNKNOWN USER MODE;

SOLSTATE: HY000

Message: Skipped unknown user mode '%s'

Error number: MY-011194; Symbol: ER FIREWALL RELOADING CACHE; SQLSTATE:

HY000

Message: Reloading cache from disk

Error number: MY-011195; Symbol: ER_FIREWALL_RESET_FOR_USER; SQLSTATE: HY000

Message: FIREWALL RESET for '%s'

Error number: MY-011196; Symbol: ER FIREWALL STATUS FLUSHED; SQLSTATE: HY000

Message: Counters are reset to zero

Error number: MY-011197; Symbol: ER KEYRING LOGGER ERROR MSG; SQLSTATE:

HY000

Message: %s

Error number: MY-011198; Symbol: ER AUDIT LOG FILTER IS NOT INSTALLED;

SQLSTATE: HY000

Message: Audit Log plugin supports a filtering, which has not been installed yet. Audit Log plugin

will run in the legacy mode, which will be disabled in the next release.

Error number: MY-011199; Symbol: ER AUDIT LOG SWITCHING TO INCLUDE LIST;

SQLSTATE: HY000

Message: Previously exclude list is used, now we start using include list, exclude list is set to NULL.

Error number: MY-011200; Symbol:

ER_AUDIT_LOG_CANNOT_SET_LOG_POLICY_WITH_OTHER_POLICIES; SQLSTATE:

HY000

Message: Cannot set audit_log_policy simultaneously with either audit_log_connection_policy or audit_log_statement_policy, setting audit_log_connection_policy and audit_log_statement_policy

based on audit_log_policy.

Error number: MY-011201; Symbol: ER AUDIT LOG ONLY INCLUDE LIST USED;

SQLSTATE: HY000

Message: Both include and exclude lists provided, include list is preferred, exclude list is set to

NULL.

Error number: MY-011202; Symbol: ER AUDIT LOG INDEX MAP CANNOT ACCESS DIR;

SQLSTATE: HY000

Message: Could not access '%s' directory.

Error number: MY-011203; Symbol: ER AUDIT LOG WRITER RENAME FILE FAILED;

SQLSTATE: HY000

Message: Could not rename file from '%s' to '%s'.

Error number: MY-011204; Symbol:

ER AUDIT LOG WRITER DEST FILE ALREADY EXISTS; SQLSTATE: HY000

Message: File '%s' should not exist. It may be incomplete. The server crashed.

Error number: MY-011205; Symbol:

ER AUDIT LOG WRITER RENAME FILE FAILED REMOVE FILE MANUALLY;

SQLSTATE: HY000

Message: Could not rename file from '%s' to '%s'. Remove the file manually.

Error number: MY-011206; Symbol:

ER AUDIT LOG WRITER INCOMPLETE FILE RENAMED; SQLSTATE: HY000

Message: Incomplete file renamed from '%s' to '%s'.

Error number: MY-011207; Symbol:

ER AUDIT LOG WRITER FAILED TO WRITE TO FILE; SQLSTATE: HY000

Message: Error writing file \'%s\' (errno: %d - %s).

Error number: MY-011208; Symbol:

ER AUDIT LOG EC WRITER FAILED TO INIT ENCRYPTION; SQLSTATE: HY000

Message: Could not initialize audit log file encryption.

Error number: MY-011209; Symbol:

ER AUDIT LOG EC WRITER FAILED TO INIT COMPRESSION; SQLSTATE: HY000

Message: Could not initialize audit log file compression.

Error number: MY-011210; Symbol:

ER AUDIT LOG EC WRITER FAILED TO CREATE FILE; SQLSTATE: HY000

Message: Could not create '%s' file for audit logging.

Error number: MY-011211; Symbol:

ER AUDIT LOG RENAME LOG FILE BEFORE FLUSH; SQLSTATE: HY000

Message: Audit log file (%s) must be manually renamed before audit log flush is set to true.

Error number: MY-011212; Symbol: ER AUDIT LOG FILTER RESULT MSG; SQLSTATE:

HY000

Message: %s

Error number: MY-011213; Symbol: ER AUDIT LOG JSON READER FAILED TO PARSE;

SOLSTATE: HY000

Message: Error parsing JSON event. Event not accessible.

Error number: MY-011214; Symbol: ER AUDIT LOG JSON READER BUF TOO SMALL;

SQLSTATE: HY000

Message: Buffer is too small to hold JSON event. Number of events skipped: %zu.

Error number: MY-011215; Symbol:

ER AUDIT LOG JSON READER_FAILED_TO_OPEN_FILE; SQLSTATE: HY000

Message: Could not open JSON file for reading. Reading next file if exists.

Error number: MY-011216; Symbol:

ER AUDIT LOG JSON READER FILE PARSING ERROR; SQLSTATE: HY000

Message: JSON file parsing error. Reading next file if exists

Error number: MY-011217; Symbol: ER AUDIT LOG FILTER INVALID COLUMN COUNT;

SQLSTATE: HY000

Message: Invalid column count in the '%s.%s' table.

Error number: MY-011218; Symbol:

ER AUDIT LOG FILTER INVALID COLUMN DEFINITION; SQLSTATE: HY000

Message: Invalid column definition of the '%s.%s' table.

Error number: MY-011219; Symbol:

ER AUDIT LOG FILTER FAILED TO STORE TABLE FLDS; SQLSTATE: HY000

Message: Could not store field of the %s table.

Error number: MY-011220; Symbol:

ER AUDIT LOG FILTER FAILED TO UPDATE TABLE; SQLSTATE: HY000

Message: Could not update %s table.

Error number: MY-011221; Symbol:

ER AUDIT LOG FILTER FAILED TO INSERT INTO TABLE; SQLSTATE: HY000

Message: Could not insert into %s table.

Error number: MY-011222; Symbol:

ER AUDIT LOG FILTER FAILED TO DELETE FROM TABLE; SQLSTATE: HY000

Message: Could not delete from %s table.

Error number: MY-011223; Symbol:

ER AUDIT_LOG_FILTER_FAILED_TO_INIT_TABLE_FOR_READ; SQLSTATE: HY000

Message: Could not initialize %s table for reading.

Error number: MY-011224; Symbol: ER AUDIT LOG FILTER FAILED TO READ TABLE;

SQLSTATE: HY000

Message: Could not read %s table.

Error number: MY-011225; Symbol:

ER AUDIT LOG FILTER FAILED TO CLOSE TABLE AFTER READING; SQLSTATE:

HY000

Message: Could not close %s table reading.

Error number: MY-011226; Symbol:

ER_AUDIT_LOG_FILTER_USER_AND_HOST_CANNOT_BE_EMPTY; SQLSTATE: HY000

Message: Both user and host columns of %s table cannot be empty.

Error number: MY-011227; Symbol:

ER AUDIT LOG FILTER FLD FILTERNAME CANNOT BE EMPTY; SQLSTATE: HY000

Message: Filtername column of %s table cannot be empty.

Error number: MY-011228; Symbol: ER_VALIDATE_PWD_DICT_FILE_NOT_SPECIFIED;

SQLSTATE: HY000

Message: Dictionary file not specified

Error number: MY-011229; Symbol: ER VALIDATE PWD DICT FILE NOT LOADED;

SQLSTATE: HY000

Message: Dictionary file not loaded

Error number: MY-011230; Symbol: ER VALIDATE PWD DICT FILE TOO BIG;

SQLSTATE: HY000

Message: Dictionary file size exceeded MAX DICTIONARY_FILE_LENGTH, not loaded

Error number: MY-011231; Symbol: ER VALIDATE PWD FAILED TO READ DICT FILE;

SQLSTATE: HY000

Message: Exception while reading the dictionary file

Error number: MY-011232; Symbol:

ER VALIDATE PWD FAILED TO GET FLD FROM SECURITY CTX; SQLSTATE: HY000

Message: Can't retrieve the %s from the security context

Error number: MY-011233; Symbol:

ER VALIDATE PWD FAILED TO GET SECURITY CTX; SQLSTATE: HY000

Message: Can't retrieve the security context

Error number: MY-011234; Symbol: ER_VALIDATE_PWD_LENGTH_CHANGED; SQLSTATE:

HY000

Message: Effective value of validate password length is changed. New value is %d

Error number: MY-011235; Symbol: ER REWRITER QUERY ERROR MSG; SQLSTATE:

HY000

Message: %s

Error number: MY-011236; Symbol: ER REWRITER QUERY FAILED; SQLSTATE: HY000

Message: Rewritten query failed to parse:%s

Error number: MY-011237; Symbol: ER XPLUGIN STARTUP FAILED; SQLSTATE: HY000

Message: Startup failed with error "%s"

Error number: MY-011238; Symbol: ER XPLUGIN SERVER EXITING; SQLSTATE: HY000

Message: Exiting

Error number: MY-011239; Symbol: ER XPLUGIN SERVER EXITED; SQLSTATE: HY000

Message: Exit done

Error number: MY-011240; Symbol: ER XPLUGIN USING SSL CONF FROM SERVER;

SOLSTATE: HY000

Message: Using SSL configuration from MySQL Server

Error number: MY-011241; Symbol: ER XPLUGIN USING SSL CONF FROM MYSQLX;

SQLSTATE: HY000

Message: Using SSL configuration from Mysqlx Plugin

Error number: MY-011242; Symbol: ER XPLUGIN FAILED TO USE SSL CONF;

SQLSTATE: HY000

Message: Neither MySQL Server nor Mysqlx Plugin has valid SSL configuration

Error number: MY-011243; Symbol: ER XPLUGIN USING SSL FOR TLS CONNECTION;

SQLSTATE: HY000

Message: Using %s for TLS connections

Error number: MY-011244; Symbol:

ER_XPLUGIN_REFERENCE_TO_SECURE_CONN_WITH_XPLUGIN; SQLSTATE: HY000

Message: For more information, please see the Using Secure Connections with X Plugin section in

the MySQL documentation

Error number: MY-011245; Symbol: ER XPLUGIN ERROR MSG; SQLSTATE: HY000

Message: %s

Error number: MY-011246; Symbol: ER SHA PWD FAILED TO PARSE AUTH STRING;

SQLSTATE: HY000

Message: Failed to parse stored authentication string for %s. Please check if mysql.user table not

corrupted

Error number: MY-011247; Symbol:

ER_SHA_PWD_FAILED_TO_GENERATE_MULTI_ROUND_HASH; SQLSTATE: HY000

Message: Error in generating multi-round hash for %s. Plugin can not perform authentication without

it. This may be a transient problem

Error number: MY-011248; Symbol: ER SHA PWD AUTH REQUIRES RSA OR SSL;

SQLSTATE: HY000

Message: Authentication requires either RSA keys or SSL encryption

Error number: MY-011249; Symbol: ER SHA PWD RSA KEY TOO LONG; SQLSTATE:

HY000

Message: RSA key cipher length of %u is too long. Max value is %u

Error number: MY-011250; Symbol:

ER PLUGIN COMMON FAILED TO OPEN FILTER TABLES; SQLSTATE: HY000

Message: Failed to open the %s filter tables

Error number: MY-011251; Symbol: ER PLUGIN COMMON FAILED TO OPEN TABLE;

SQLSTATE: HY000

Message: Failed to open '%s.%s' %s table

Error number: MY-011252; Symbol: ER AUTH LDAP ERROR_LOGGER_ERROR_MSG;

SQLSTATE: HY000

Message: %s

Error number: MY-011253; Symbol: ER CONN CONTROL ERROR MSG; SQLSTATE: HY000

Message: %s

Error number: MY-011254; Symbol: ER GRP RPL ERROR MSG; SQLSTATE: HY000

Message: %s

Error number: MY-011255; Symbol: ER SHA PWD SALT FOR USER CORRUPT;

SQLSTATE: HY000

Message: Password salt for user '%s' is corrupt

Error number: MY-011256; Symbol: ER_SYS_VAR_COMPONENT_OOM; SQLSTATE: HY000 Message: Out of memory for component system variable '%s'.

Error number: MY-011257; Symbol:

ER_SYS_VAR_COMPONENT_VARIABLE_SET_READ_ONLY; SQLSTATE: HY000 Message: variable %s of component %s was forced to be read-only: string variable without update func and PLUGIN VAR MEMALLOC flag.

Error number: MY-011258; Symbol:

ER_SYS_VAR_COMPONENT_UNKNOWN_VARIABLE_TYPE; SQLSTATE: HY000 Message: Unknown variable type code 0x%x in component '%s'.

Error number: MY-011259; Symbol:

 $\label{lem:component_failed_to_parse_variable_options; sqlstate: $HY000$$

Message: Parsing options for variable '%s' failed.

Error number: MY-011260; Symbol:

ER_SYS_VAR_COMPONENT_FAILED_TO_MAKE_VARIABLE_PERSISTENT; SQLSTATE: HY000

Message: Setting persistent options for component variable '%s' failed.

Error number: MY-011261; Symbol: ER_COMPONENT_FILTER_CONFUSED; SQLSTATE: HY000

Message: The log-filter component "%s" got confused at "%s" (state: %s) ...

Error number: MY-011262; Symbol: ER_STOP_SLAVE_IO_THREAD_DISK_SPACE; SQLSTATE: HY000

Message: Waiting until I/O thread for channel '%s' finish writing to disk before stopping. Free some disk space or use 'KILL' to abort I/O thread operation. Notice that aborting the I/O thread while rotating the relay log might corrupt the relay logs, requiring a server restart to fix it.

Error number: MY-011263; Symbol: ER_LOG_FILE_CANNOT_OPEN; SQLSTATE: HY000 Message: Could not use %s for logging (error %d - %s). Turning logging off for the server process. To turn it on again: fix the cause, then%s restart the MySQL server.

Error number: MY-011268; Symbol: ER_PERSIST_OPTION_STATUS; SQLSTATE: HY000 Message: Configuring persisted options failed: "%s".

Error number: MY-011269; Symbol:

ER NOT IMPLEMENTED GET TABLESPACE STATISTICS; SQLSTATE: HY000

Message: The storage engine '%s' does not provide dynamic table statistics

Error number: MY-011272; Symbol: ER SSL FIPS MODE ERROR; SQLSTATE: HY000

Message: SSL fips mode error: %s

Error number: MY-011273; Symbol: ER CONN INIT CONNECT IGNORED; SQLSTATE:

HY000

Message: init connect variable is ignored for user: %s host: %s due to expired password.

Error number: MY-011275; Symbol: ER REWRITER OOM; SQLSTATE: HY000

Message: Out of memory.

Error number: MY-011276; Symbol: ER REWRITER TABLE MALFORMED ERROR;

SQLSTATE: HY000

Message: Wrong column count or names when loading rules.

Error number: MY-011277; Symbol: ER REWRITER LOAD FAILED; SQLSTATE: HY000

Message: Some rules failed to load.

Error number: MY-011278; Symbol: ER REWRITER READ FAILED; SQLSTATE: HY000

Message: Got error from storage engine while refreshing rewrite rules.

Error number: MY-011279; Symbol:

ER CONN CONTROL EVENT COORDINATOR INIT FAILED; SQLSTATE: HY000

Message: Failed to initialize Connection event coordinator

Error number: MY-011280; Symbol:

ER CONN CONTROL STAT CONN DELAY TRIGGERED UPDATE FAILED; SQLSTATE:

HY000

Message: Failed to update connection delay triggered stats

Error number: MY-011281; Symbol:

ER_CONN_CONTROL_STAT_CONN_DELAY_TRIGGERED_RESET_FAILED; SQLSTATE:

HY000

Message: Failed to reset connection delay triggered stats

Error number: MY-011282; Symbol: ER CONN CONTROL INVALID CONN DELAY TYPE;

SQLSTATE: HY000

Message: Unexpected option type for connection delay.

Error number: MY-011283; Symbol: ER CONN CONTROL DELAY ACTION INIT FAILED;

SQLSTATE: HY000

Message: Failed to initialize Connection delay action

Error number: MY-011284; Symbol: ER CONN CONTROL FAILED TO SET CONN DELAY;

SQLSTATE: HY000

Message: Could not set %s delay for connection delay.

Error number: MY-011285; Symbol:

ER CONN CONTROL FAILED TO UPDATE CONN DELAY HASH; SQLSTATE: HY000

Message: Failed to update connection delay hash for account: %s

Error number: MY-011286; Symbol: ER XPLUGIN FORCE STOP CLIENT; SQLSTATE:

HY000

Message: %s: Force stopping client because exception occurred: %s

Error number: MY-011287; Symbol: ER_XPLUGIN_MAX_AUTH_ATTEMPTS_REACHED;

SQLSTATE: HY000

Message: %s.%u: Maximum number of authentication attempts reached, login failed.

Error number: MY-011288; Symbol: ER XPLUGIN BUFFER PAGE ALLOC FAILED;

SQLSTATE: HY000

Message: Error allocating Buffer page: %s

Error number: MY-011289; Symbol: ER XPLUGIN DETECTED HANGING CLIENTS;

SQLSTATE: HY000

Message: Detected %u hanging client(s)

Error number: MY-011290; Symbol: ER XPLUGIN FAILED TO ACCEPT CLIENT;

SOLSTATE: HY000

Message: Error accepting client

Error number: MY-011291; Symbol: ER XPLUGIN FAILED TO SCHEDULE CLIENT;

SQLSTATE: HY000

Message: Internal error scheduling client for execution

Error number: MY-011292; Symbol: ER XPLUGIN FAILED TO PREPARE IO INTERFACES;

SQLSTATE: HY000

Message: Preparation of I/O interfaces failed, X Protocol won't be accessible

Error number: MY-011293; Symbol: ER XPLUGIN SRV SESSION INIT THREAD FAILED;

SQLSTATE: HY000

Message: srv session init thread returned error

Error number: MY-011294; Symbol:

ER XPLUGIN UNABLE TO USE USER SESSION ACCOUNT; SQLSTATE: HY000

Message: Unable to use user mysql.session account when connecting the server for internal plugin

requests.

Error number: MY-011295; Symbol:

ER XPLUGIN REFERENCE TO USER ACCOUNT DOC SECTION; SQLSTATE: HY000

Message: For more information, please see the X Plugin User Account section in the MySQL

documentation

Error number: MY-011296; Symbol:

ER XPLUGIN UNEXPECTED EXCEPTION DISPATCHING CMD; SQLSTATE: HY000

Message: %s: Unexpected exception dispatching command: %s

Error number: MY-011297; Symbol: ER_XPLUGIN_EXCEPTION_IN_TASK_SCHEDULER;

SQLSTATE: HY000

Message: Exception in post: %s

Error number: MY-011298; Symbol: ER XPLUGIN TASK SCHEDULING FAILED;

SQLSTATE: HY000

Message: Internal error scheduling task

Error number: MY-011299; Symbol: ER XPLUGIN EXCEPTION IN EVENT LOOP;

SQLSTATE: HY000

Message: Exception in event loop: "%s": %s

Error number: MY-011300; Symbol: ER_XPLUGIN_LISTENER_SETUP_FAILED; SQLSTATE:

HY000

Message: Setup of %s failed, %s

Error number: MY-011301; Symbol: ER XPLUING NET STARTUP FAILED; SQLSTATE:

HY000

Message: %s

Error number: MY-011302; Symbol: ER XPLUGIN FAILED AT SSL CONF; SQLSTATE:

HY000

Message: Failed at SSL configuration: "%s"

Error number: MY-011303; Symbol: ER XPLUGIN CLIENT SSL HANDSHAKE FAILED;

SQLSTATE: HY000

Message: Error during SSL handshake for client connection (%i)

Error number: MY-011304; Symbol:

ER XPLUGIN SSL HANDSHAKE_WITH_SERVER_FAILED; SQLSTATE: HY000

Message: %s: Error during SSL handshake

Error number: MY-011305; Symbol:

ER XPLUGIN FAILED TO CREATE SESSION FOR CONN; SQLSTATE: HY000

Message: %s: Error creating session for connection from %s

Error number: MY-011306; Symbol: ER XPLUGIN FAILED TO INITIALIZE SESSION;

SQLSTATE: HY000

Message: %s: Error initializing session for connection: %s

Error number: MY-011307; Symbol: ER XPLUGIN MESSAGE TOO LONG; SQLSTATE:

HY000

Message: %s: Message of size %u received, exceeding the limit of %i

Error number: MY-011308; Symbol: ER XPLUGIN UNINITIALIZED MESSAGE; SQLSTATE:

HY000

Message: Message is not properly initialized: %s

Error number: MY-011309; Symbol:

ER XPLUGIN FAILED TO SET MIN NUMBER OF WORKERS; SQLSTATE: HY000

Message: Unable to set minimal number of workers to %u; actual value is %i

Error number: MY-011310; Symbol: ER XPLUGIN UNABLE TO ACCEPT CONNECTION;

SQLSTATE: HY000

Message: Unable to accept connection, disconnecting client

Error number: MY-011311; Symbol: ER XPLUGIN ALL IO INTERFACES DISABLED;

SOLSTATE: HY000

Message: All I/O interfaces are disabled, X Protocol won't be accessible

Error number: MY-011312; Symbol: ER_XPLUGIN_INVALID_MSG_DURING_CLIENT_INIT;

SOLSTATE: HY000

Message: %s: Invalid Message %i received during client initialization

Error number: MY-011313; Symbol: ER XPLUGIN CLOSING CLIENTS ON SHUTDOWN;

SQLSTATE: HY000

Message: %s: closing client because of shutdown (state: %i)

Error number: MY-011314; Symbol: ER XPLUGIN ERROR READING SOCKET; SQLSTATE:

HY000

Message: %s: Error reading from socket %s (%i)

Error number: MY-011315; Symbol:

ER XPLUGIN PEER DISCONNECTED WHILE READING MSG BODY; SQLSTATE:

HY000

Message: %s: peer disconnected while reading Message body

Error number: MY-011316; Symbol: ER XPLUGIN READ FAILED CLOSING CONNECTION;

SQLSTATE: HY000

Message: client id:%s - %s while reading from socket, closing connection

Error number: MY-011317; Symbol: ER_XPLUGIN_INVALID_AUTH_METHOD; SQLSTATE:

HY000

Message: %s.%u: Invalid authentication method %s

Error number: MY-011318; Symbol:

ER XPLUGIN UNEXPECTED MSG DURING AUTHENTICATION; SQLSTATE: HY000

Message: %s: Unexpected Message of type %i received during authentication

Error number: MY-011319; Symbol: ER XPLUGIN ERROR WRITING TO CLIENT;

SQLSTATE: HY000

Message: Error writing to client: %s (%i)

Error number: MY-011320; Symbol: ER XPLUGIN SCHEDULER STARTED; SQLSTATE:

HY000

Message: Scheduler "%s" started.

Error number: MY-011321; Symbol: ER XPLUGIN SCHEDULER STOPPED; SQLSTATE:

HY000

Message: Scheduler "%s" stopped.

Error number: MY-011322; Symbol: ER XPLUGIN LISTENER SYS VARIABLE ERROR;

SQLSTATE: HY000

Message: Please see the MySQL documentation for '%s' system variables to fix the error

Error number: MY-011323; Symbol: ER XPLUGIN LISTENER STATUS MSG; SQLSTATE:

HY000

Message: X Plugin ready for connections. %s

Error number: MY-011324; Symbol: ER XPLUGIN RETRYING BIND ON PORT; SQLSTATE:

HY000

Message: Retrying 'bind()' on TCP/IP port %i

Error number: MY-011325; Symbol: ER XPLUGIN SHUTDOWN TRIGGERED; SQLSTATE:

HY000

Message: Shutdown triggered by mysqld abort flag

Error number: MY-011326; Symbol:

ER XPLUGIN USER ACCOUNT WITH ALL PERMISSIONS; SQLSTATE: HY000

Message: Using %s account for authentication which has all required permissions

Error number: MY-011327; Symbol:

ER XPLUGIN EXISTING USER ACCOUNT WITH INCOMPLETE GRANTS; SQLSTATE:

HY000

Message: Using existing %s account for authentication. Incomplete grants will be fixed

Error number: MY-011328; Symbol:

ER XPLUGIN SERVER STARTS HANDLING CONNECTIONS; SQLSTATE: HY000

Message: Server starts handling incoming connections

Error number: MY-011329; Symbol:

ER XPLUGIN SERVER STOPPED HANDLING CONNECTIONS; SQLSTATE: HY000

Message: Stopped handling incoming connections

Error number: MY-011330; Symbol: ER XPLUGIN FAILED TO INTERRUPT SESSION;

SQLSTATE: HY000

Message: %s: Could not interrupt client session

Error number: MY-011331; Symbol: ER XPLUGIN CLIENT RELEASE TRIGGERED;

SOLSTATE: HY000

Message: %s: release triggered by timeout in state:%i

Error number: MY-011332; Symbol: ER XPLUGIN IPv6 AVAILABLE; SQLSTATE: HY000

Message: IPv6 is available

Error number: MY-011333; Symbol: ER_XPLUGIN_UNIX_SOCKET_NOT_CONFIGURED;

SQLSTATE: HY000

Message: UNIX socket not configured

Error number: MY-011334; Symbol: ER XPLUGIN CLIENT KILL MSG; SQLSTATE: HY000

Message: Kill client: %i %s

Error number: MY-011335; Symbol: ER XPLUGIN FAILED TO GET SECURITY CTX;

SQLSTATE: HY000

Message: Could not get security context for session

Error number: MY-011336; Symbol:

ER XPLUGIN FAILED TO SWITCH SECURITY CTX TO ROOT; SQLSTATE: HY000

Message: Unable to switch security context to root

Error number: MY-011337; Symbol: ER XPLUGIN FAILED TO CLOSE SQL SESSION;

SQLSTATE: HY000

Message: Error closing SQL session

Error number: MY-011338; Symbol: ER XPLUGIN FAILED TO EXECUTE ADMIN CMD;

SQLSTATE: HY000

Message: Error executing admin command %s: %s

Error number: MY-011339; Symbol: ER XPLUGIN EMPTY ADMIN CMD; SQLSTATE:

HY000

Message: Error executing empty admin command

Error number: MY-011340; Symbol: ER XPLUGIN FAILED TO GET SYS VAR; SQLSTATE:

HY000

Message: Unable to retrieve system variable \"%s\"

Error number: MY-011341; Symbol: ER XPLUGIN FAILED TO GET CREATION STMT;

SQLSTATE: HY000

Message: Unable to get creation stmt for collection \'%s\'; query result size: %lu

Error number: MY-011342; Symbol: ER XPLUGIN FAILED TO GET ENGINE INFO;

SOLSTATE: HY000

Message: Unable to get engine info for collection \'%s\'; creation stmt: %s

Error number: MY-011343; Symbol: ER XPLUGIN FAIL TO GET RESULT DATA;

SQLSTATE: HY000

Message: Error getting result data: %s

Error number: MY-011344; Symbol: ER XPLUGIN CAPABILITY EXPIRED PASSWORD;

SQLSTATE: HY000

Message: Capability expired password failed with error: %s

Error number: MY-011345; Symbol:

ER_XPLUGIN_FAILED_TO_SET_SO_REUSEADDR_FLAG; SQLSTATE: HY000

Message: Failed to set SO REUSEADDR flag (error: %d).

Error number: MY-011346; Symbol: ER XPLUGIN FAILED TO OPEN INTERNAL SESSION;

SOLSTATE: HY000

Message: Could not open internal MySQL session

Error number: MY-011347; Symbol: ER XPLUGIN FAILED TO SWITCH CONTEXT;

SQLSTATE: HY000

Message: Unable to switch context to user %s

Error number: MY-011348; Symbol: ER XPLUGIN FAILED TO UNREGISTER UDF;

SQLSTATE: HY000

Message: Can\'t unregister \'%s\' user defined function

Error number: MY-011349; Symbol: ER XPLUGIN GET PEER ADDRESS FAILED;

SQLSTATE: HY000

Message: %s: get peer address failed, can't resolve IP to hostname

Error number: MY-011350; Symbol:

ER XPLUGIN CAPABILITY CLIENT INTERACTIVE FAILED; SQLSTATE: HY000

Message: Capability client interactive failed with error: %s

2.9 错误码及错误信息汇总 09

Error number: MY-011351; Symbol:

ER XPLUGIN FAILED TO RESET IPV6 V6ONLY FLAG; SQLSTATE: HY000

Message: Failed to reset IPV6 V6ONLY flag (error: %d). The server will listen to IPv6 addresses

only.

Error number: MY-011352; Symbol: ER KEYRING INVALID KEY TYPE; SQLSTATE: HY000

Message: Invalid key type

Error number: MY-011353; Symbol: ER KEYRING INVALID KEY LENGTH; SQLSTATE:

HY000

Message: Invalid key length for given block cipher

Error number: MY-011354; Symbol: ER KEYRING FAILED TO CREATE KEYRING DIR;

SQLSTATE: HY000

Message: Could not create keyring directory. The keyring_file will stay unusable until correct path to

the keyring directory gets provided

Error number: MY-011355; Symbol: ER KEYRING FILE INIT FAILED; SQLSTATE: HY000

Message: keyring_file initialization failure. Please check if the keyring_file_data points to readable keyring file or keyring file can be created in the specified location. The keyring_file will stay unusable until correct path to the keyring file gets provided

Error number: MY-011356; Symbol:

ER_KEYRING_INTERNAL_EXCEPTION_FAILED_FILE_INIT; SQLSTATE: HY000 Message: keyring file initialization failure due to internal exception inside the plugin.

Error number: MY-011357; Symbol: ER KEYRING FAILED TO GENERATE KEY;

SQLSTATE: HY000

Message: Failed to generate a key due to internal exception inside keyring file plugin

Error number: MY-011358; Symbol:

ER_KEYRING_CHECK_KEY_FAILED_DUE_TO_INVALID_KEY; SQLSTATE: HY000

Message: Error while %s key: invalid key_type

Error number: MY-011359; Symbol:

ER KEYRING CHECK KEY FAILED DUE TO EMPTY KEY ID; SQLSTATE: HY000

Message: Error while %s key: key id cannot be empty

Error number: MY-011360; Symbol:

ER KEYRING OPERATION FAILED DUE TO INTERNAL ERROR; SQLSTATE: HY000

Message: Failed to %s due to internal exception inside %s plugin

Error number: MY-011361; Symbol: ER KEYRING INCORRECT FILE; SQLSTATE: HY000

Message: Incorrect Keyring file

Error number: MY-011362; Symbol: ER KEYRING FOUND MALFORMED BACKUP FILE;

SQLSTATE: HY000

Message: Found malformed keyring backup file - removing it

Error number: MY-011363; Symbol:

ER_KEYRING_FAILED_TO_RESTORE_FROM_BACKUP_FILE; SQLSTATE: HY000

Message: Error while restoring keyring from backup file cannot overwrite keyring with backup

Error number: MY-011364; Symbol: ER KEYRING FAILED TO FLUSH KEYRING TO FILE;

SQLSTATE: HY000

Message: Error while flushing in-memory keyring into keyring file

Error number: MY-011365; Symbol: ER KEYRING FAILED TO GET FILE STAT;

SQLSTATE: HY000

Message: Error while reading stat for %s.Please check if file %s was not removed. OS returned this error: %s

Error number: MY-011366; Symbol: ER_KEYRING_FAILED_TO_REMOVE_FILE; SQLSTATE:

HY000

Message: Could not remove file %s OS retuned this error: %s

Error number: MY-011367; Symbol: ER KEYRING FAILED TO TRUNCATE FILE;

SQLSTATE: HY000

Message: Could not truncate file %s. OS retuned this error: %s

Error number: MY-011368; Symbol: ER KEYRING UNKNOWN ERROR; SQLSTATE: HY000

Message: Unknown error %d

Error number: MY-011369; Symbol:

ER KEYRING FAILED TO SET KEYRING FILE DATA; SQLSTATE: HY000

Message: keyring file data cannot be set to new value as the keyring file cannot be created/accessed

in the provided path

Error number: MY-011370; Symbol: ER KEYRING FILE IO ERROR; SQLSTATE: HY000

Message: %s

Error number: MY-011371; Symbol:

ER KEYRING FAILED TO LOAD KEYRING CONTENT; SQLSTATE: HY000

Message: Error while loading keyring content. The keyring might be malformed

Error number: MY-011372; Symbol:

ER KEYRING FAILED TO FLUSH KEYS TO KEYRING; SQLSTATE: HY000

Message: Could not flush keys to keyring

Error number: MY-011373; Symbol:

ER KEYRING FAILED TO FLUSH KEYS TO KEYRING BACKUP; SQLSTATE: HY000

Message: Could not flush keys to keyring's backup

Error number: MY-011374; Symbol:

ER KEYRING KEY FETCH FAILED DUE TO EMPTY KEY ID; SQLSTATE: HY000

Message: Error while fetching key: key id cannot be empty

Error number: MY-011375; Symbol:

ER_KEYRING_FAILED_TO_REMOVE_KEY_DUE_TO_EMPTY_ID; SQLSTATE: HY000

Message: Error while removing key: key id cannot be empty

Error number: MY-011376; Symbol:

ER_KEYRING_OKV_INCORRECT_KEY_VAULT_CONFIGURED; SQLSTATE: HY000 Message: For keyring_okv to be initialized, please point keyring_okv_conf_dir variable to a

directory with Oracle Key Vault configuration file and ssl materials

Error number: MY-011377; Symbol:

ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INCORRECT_CONF; SQLSTATE: HY000 Message: keyring_okv initialization failure. Please check that the keyring_okv_conf_dir points to a readable directory and that the directory contains Oracle Key Vault configuration file and ssl materials. Please also check that Oracle Key Vault is up and running.

Error number: MY-011378; Symbol:

 $ER_KEYRING_OKV_INIT_FAILED_DUE_TO_INTERNAL_ERROR; SQLSTATE: HY000$

Message: keyring_okv initialization failure due to internal exception inside the plugin

Error number: MY-011379; Symbol: ER KEYRING OKV INVALID KEY TYPE; SQLSTATE:

HY000

Message: Invalid key type

Error number: MY-011380; Symbol:

ER KEYRING OKV INVALID KEY LENGTH FOR CIPHER; SQLSTATE: HY000

Message: Invalid key length for given block cipher

Error number: MY-011381; Symbol:

ER KEYRING OKV FAILED TO GENERATE KEY DUE TO INTERNAL ERROR;

SQLSTATE: HY000

Message: Failed to generate a key due to internal exception inside keyring okv plugin

Error number: MY-011382; Symbol:

ER KEYRING OKV FAILED TO FIND SERVER ENTRY; SQLSTATE: HY000

Message: Could not find entry for server in configuration file %s

Error number: MY-011383; Symbol:

ER KEYRING OKV FAILED TO FIND STANDBY SERVER ENTRY; SQLSTATE: HY000

Message: Could not find entry for standby server in configuration file %s

Error number: MY-011384; Symbol: ER KEYRING OKV FAILED TO PARSE CONF FILE;

SQLSTATE: HY000

Message: Could not parse the %s file provided

Error number: MY-011385; Symbol: ER KEYRING OKV FAILED TO LOAD KEY UID;

SQLSTATE: HY000

Message: Could not load keys' uids from the OKV server

Error number: MY-011386; Symbol: ER KEYRING OKV FAILED TO INIT SSL LAYER;

SQLSTATE: HY000

Message: Could not initialize ssl layer

Error number: MY-011387; Symbol: ER KEYRING OKV FAILED TO INIT CLIENT;

SQLSTATE: HY000

Message: Could not initialize OKV client

Error number: MY-011388; Symbol:

ER KEYRING OKV CONNECTION TO SERVER FAILED; SQLSTATE: HY000

Message: Could not connect to the OKV server

Error number: MY-011389; Symbol: ER_KEYRING_OKV_FAILED_TO_REMOVE_KEY;

SQLSTATE: HY000

Message: Could not remove the key

Error number: MY-011390; Symbol: ER KEYRING OKV FAILED TO ADD ATTRIBUTE;

SQLSTATE: HY000

Message: Could not add attribute, attribute name=%s attribute value=%s

Error number: MY-011391; Symbol: ER KEYRING OKV FAILED TO GENERATE KEY;

SQLSTATE: HY000

Message: Could not generate the key.

Error number: MY-011392; Symbol: ER KEYRING OKV FAILED TO STORE KEY;

SQLSTATE: HY000

Message: Could not store the key.

Error number: MY-011393; Symbol: ER_KEYRING_OKV_FAILED_TO_ACTIVATE_KEYS;

SQLSTATE: HY000

Message: Could not activate the key.

Error number: MY-011394; Symbol: ER KEYRING OKV FAILED TO FETCH KEY;

SQLSTATE: HY000

Message: Could not fetch generated key

Error number: MY-011395; Symbol:

ER KEYRING OKV FAILED TO STORE OR GENERATE KEY; SQLSTATE: HY000

Message: Could not store/generate the key - failed to set key attribute x-key-ready

Error number: MY-011396; Symbol:

ER KEYRING OKV FAILED TO_RETRIEVE_KEY_SIGNATURE; SQLSTATE: HY000

Message: Could not retrieve key signature from custom attributes

Error number: MY-011397; Symbol: ER KEYRING OKV FAILED TO RETRIEVE KEY;

SQLSTATE: HY000

Message: Could not retrieve key from OKV

Error number: MY-011398; Symbol:

ER KEYRING OKV FAILED TO LOAD SSL TRUST STORE; SQLSTATE: HY000

Message: Error loading trust store

Error number: MY-011399; Symbol:

ER KEYRING OKV FAILED TO SET CERTIFICATE FILE; SQLSTATE: HY000

Message: Error setting the certificate file.

Error number: MY-011400; Symbol: ER KEYRING OKV FAILED TO SET KEY FILE;

SQLSTATE: HY000

Message: Error setting the key file.

Error number: MY-011401; Symbol: ER KEYRING OKV KEY MISMATCH; SQLSTATE:

HY000

Message: Private key does not match the certificate public key

Error number: MY-011402; Symbol:

ER KEYRING ENCRYPTED FILE INCORRECT KEYRING FILE; SQLSTATE: HY000

Message: Incorrect Keyring file

Error number: MY-011403; Symbol:

ER KEYRING ENCRYPTED FILE DECRYPTION FAILED; SQLSTATE: HY000

Message: Keyring_encrypted_file decryption failed. Please verify --keyring-encrypted-file-password

option value.

Error number: MY-011404; Symbol:

ER KEYRING ENCRYPTED FILE FOUND MALFORMED BACKUP FILE; SQLSTATE:

HY000

Message: Found malformed keyring backup file - removing it

Error number: MY-011405; Symbol:

ER KEYRING ENCRYPTED FILE FAILED TO RESTORE KEYRING; SQLSTATE: HY000

Message: Error while restoring keyring from backup file cannot overwrite keyring with backup

Error number: MY-011406; Symbol:

ER KEYRING ENCRYPTED FILE FAILED TO FLUSH KEYRING; SQLSTATE: HY000

Message: Error while flushing in-memory keyring into keyring file

Error number: MY-011407; Symbol:

ER KEYRING ENCRYPTED FILE ENCRYPTION FAILED; SQLSTATE: HY000

Message: Keyring_encrypted_file encryption failed. Please verify --keyring-encrypted-file-password

option value.

Error number: MY-011408; Symbol:

ER KEYRING ENCRYPTED FILE INVALID KEYRING DIR; SQLSTATE: HY000

Message: keyring encrypted file data cannot be set to new value as the keyring file cannot be

created/accessed in the provided path

Error number: MY-011409; Symbol:

ER KEYRING ENCRYPTED FILE FAILED TO CREATE KEYRING DIR; SQLSTATE:

HY000

Message: Could not create keyring directory The keyring encrypted file will stay unusable until

correct path to the keyring directory gets provided

Error number: MY-011410; Symbol:

ER KEYRING ENCRYPTED FILE PASSWORD IS INVALID; SQLSTATE: HY000

Message: The keyring encrypted file password must be set to a valid value.

Error number: MY-011411; Symbol:

ER KEYRING ENCRYPTED FILE PASSWORD IS TOO LONG; SQLSTATE: HY000

Message: Too long keyring encrypted file password value.

Error number: MY-011412; Symbol: ER KEYRING ENCRYPTED FILE INIT FAILURE;

SQLSTATE: HY000

Message: keyring encrypted file initialization failure. Please check if the

keyring encrypted file data points to readable keyring file or keyring file can be created in the

specified location or password to decrypt keyring file is correct.

Error number: MY-011413; Symbol:

ER KEYRING ENCRYPTED FILE INIT FAILED DUE TO INTERNAL ERROR;

SQLSTATE: HY000

Message: keyring encrypted file initialization failure due to internal exception inside the plugin

Error number: MY-011414; Symbol:

ER KEYRING ENCRYPTED FILE GEN KEY FAILED DUE TO INTERNAL ERROR;

SQLSTATE: HY000

Message: Failed to generate a key due to internal exception inside keyring encrypted file plugin

Error number: MY-011415; Symbol: ER KEYRING AWS FAILED TO SET CMK ID;

SQLSTATE: HY000

Message: keyring aws cmk id cannot be set to the new value as AWS KMS seems to not

understand the id provided. Please check that CMK id provided is correct.

Error number: MY-011416; Symbol: ER KEYRING AWS FAILED TO SET REGION;

SQLSTATE: HY000

Message: keyring_aws_region cannot be set to the new value as AWS KMS seems to not understand

the region provided. Please check that region provided is correct.

Error number: MY-011417; Symbol: ER KEYRING AWS FAILED TO OPEN CONF FILE;

SQLSTATE: HY000

Message: Could not open keyring aws configuration file: %s. OS returned this error: %s

Error number: MY-011418; Symbol:

ER_KEYRING_AWS_FAILED_TO_ACCESS_KEY_ID_FROM_CONF_FILE; SQLSTATE:

HY000

Message: Could not read AWS access key id from keyring aws configuration file: %s. OS returned

this error: %s

Error number: MY-011419; Symbol:

ER KEYRING AWS FAILED TO ACCESS KEY FROM CONF FILE; SQLSTATE: HY000

Message: Could not read AWS access key from keyring aws configuration file: %s. OS returned this

error: %s

Error number: MY-011420; Symbol: ER_KEYRING_AWS_INVALID_CONF_FILE_PATH;

SQLSTATE: HY000

Message: Path to keyring aws configuration file cannot be empty

Error number: MY-011421; Symbol: ER KEYRING AWS INVALID DATA FILE PATH;

SQLSTATE: HY000

Message: Path to keyring aws storage file cannot be empty.

Error number: MY-011422; Symbol:

ER KEYRING AWS FAILED TO ACCESS OR CREATE KEYRING DIR; SQLSTATE:

HY000

Message: Unable to create/access keyring directory.

Error number: MY-011423; Symbol:

ER KEYRING AWS FAILED TO_ACCESS_OR_CREATE_KEYRING_DATA_FILE;

SQLSTATE: HY000

Message: Unable to create/access keyring_aws storage file. Please check if keyring_aws_data_file points to location where keyring file can be created/accessed. Please also make sure that MySQL server's user has high enough privileges to access this location.

Error number: MY-011424; Symbol:

ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_INTERNAL_ERROR; SQLSTATE: HY000 Message: keyring_aws initialization failed due to internal error when initializing synchronization primitive - %s. OS returned this error: %s:

Error number: MY-011425; Symbol: ER_KEYRING_AWS_FAILED_TO_ACCESS_DATA_FILE; SQLSTATE: HY000

Message: Could not access keyring_aws storage file in the path provided. Please check if the keyring aws directory can be accessed by MySQL Server

Error number: MY-011426; Symbol: ER_KEYRING_AWS_CMK_ID_NOT_SET; SQLSTATE: HY000

Message: keyring aws cmk id has to be set

Error number: MY-011427; Symbol:

ER KEYRING AWS FAILED TO GET KMS CREDENTIAL FROM CONF FILE;

SQLSTATE: HY000

Message: Could not get AWS KMS credentials from the configuration file

Error number: MY-011428; Symbol: ER_KEYRING_AWS_INIT_FAILURE; SQLSTATE: HY000 Message: keyring_aws initialization failure.

Error number: MY-011429; Symbol:

ER_KEYRING_AWS_FAILED_TO_INIT_DUE_TO_PLUGIN_INTERNAL_ERROR;

SQLSTATE: HY000

Message: keyring_aws initialization failure due to internal exception inside the plugin

Error number: MY-011430; Symbol:

ER KEYRING AWS INVALID KEY LENGTH FOR CIPHER; SQLSTATE: HY000

Message: Invalid key length for given block cipher

Error number: MY-011431; Symbol:

ER KEYRING AWS FAILED TO GENERATE KEY DUE TO INTERNAL ERROR;

SOLSTATE: HY000

Message: Failed to generate a key due to internal exception inside keyring file plugin

Error number: MY-011432; Symbol: ER_KEYRING_AWS_INCORRECT_FILE; SQLSTATE:

HY000

Message: Incorrect Keyring file

Error number: MY-011433; Symbol:

ER KEYRING AWS FOUND MALFORMED_BACKUP_FILE; SQLSTATE: HY000

Message: Found malformed keyring backup file - removing it

Error number: MY-011434; Symbol:

ER_KEYRING_AWS_FAILED_TO_RESTORE_FROM_BACKUP_FILE; SQLSTATE: HY000 Message: Error while restoring keyring from backup file cannot overwrite keyring with backup

Error number: MY-011435; Symbol:

ER KEYRING AWS FAILED TO FLUSH KEYRING TO FILE; SQLSTATE: HY000

Message: Error while flushing in-memory keyring into keyring file

Error number: MY-011436; Symbol: ER KEYRING AWS INCORRECT REGION; SQLSTATE:

HY000

Message: Wrong region

Error number: MY-011437; Symbol: ER KEYRING AWS FAILED TO CONNECT KMS;

SOLSTATE: HY000

Message: Could not connect to AWS KMS with the credentials provided. Please make sure they are

correct. AWS KMS returned this error: %s

Error number: MY-011438; Symbol:

ER KEYRING AWS FAILED TO GENERATE NEW KEY; SQLSTATE: HY000

Message: Could not generate a new key. AWS KMS returned this error: %s

Error number: MY-011439; Symbol: ER KEYRING AWS FAILED TO ENCRYPT KEY;

SQLSTATE: HY000

Message: Could not encrypt key. AWS KMS returned this error: %s

Error number: MY-011440; Symbol: ER_KEYRING_AWS_FAILED_TO_RE_ENCRYPT_KEY;

SQLSTATE: HY000

Message: Could not re-encrypt key. AWS KMS returned this error: %s

Error number: MY-011441; Symbol: ER KEYRING AWS FAILED TO DECRYPT KEY;

SOLSTATE: HY000

Message: Could not decrypt key. AWS KMS returned this error: %s

Error number: MY-011442; Symbol: ER KEYRING AWS FAILED TO ROTATE CMK;

SOLSTATE: HY000

Message: Could not rotate the CMK. AWS KMS returned this error: %s

Error number: MY-011443; Symbol: ER GRP RPL GTID ALREADY USED; SQLSTATE:

HY000

Message: The requested GTID '%s:%lld' was already used, the transaction will rollback.

Error number: MY-011444; Symbol: ER GRP RPL APPLIER THD KILLED; SQLSTATE:

HY000

Message: The group replication applier thread was killed.

Error number: MY-011445; Symbol: ER_GRP_RPL_EVENT_HANDLING_ERROR; SQLSTATE:

HY000

Message: Error at event handling! Got error: %d.

Error number: MY-011446; Symbol: ER GRP RPL ERROR GTID EXECUTION INFO;

SQLSTATE: HY000

Message: Error when extracting group GTID execution information, some recovery operations may

face future issues.

Error number: MY-011447; Symbol: ER_GRP_RPL_CERTIFICATE_SIZE_ERROR; SQLSTATE:

HY000

Message: An error occurred when trying to reduce the Certification information size for

transmission.

Error number: MY-011448; Symbol: ER GRP RPL CREATE APPLIER CACHE ERROR;

SOLSTATE: HY000

Message: Failed to create group replication pipeline applier cache!

Error number: MY-011449; Symbol: ER GRP RPL UNBLOCK WAITING THD; SQLSTATE:

HY000

Message: Unblocking the group replication thread waiting for applier to start, as the start group

replication was killed.

Error number: MY-011450; Symbol: ER GRP RPL APPLIER PIPELINE NOT DISPOSED;

SQLSTATE: HY000

Message: The group replication applier pipeline was not properly disposed. Check the error log for

further info.

Error number: MY-011451; Symbol: ER GRP RPL APPLIER THD EXECUTION ABORTED;

SQLSTATE: HY000

Message: The applier thread execution was aborted. Unable to process more transactions, this member will now leave the group.

Error number: MY-011452; Symbol: ER_GRP_RPL_APPLIER_EXECUTION_FATAL_ERROR; SOLSTATE: HY000

Message: Fatal error during execution on the Applier process of Group Replication. The server will now leave the group.

Error number: MY-011453; Symbol: ER_GRP_RPL_ERROR_STOPPING_CHANNELS;

SQLSTATE: HY000

Message: Error stopping all replication channels while server was leaving the group. %s

Error number: MY-011454; Symbol:

ER_GRP_RPL_ERROR_SENDING_SINGLE_PRIMARY_MSSG; SQLSTATE: HY000 Message: Error sending single primary Message informing that primary did apply relay logs.

Error number: MY-011455; Symbol:

ER_GRP_RPL_UPDATE_TRANS_SNAPSHOT_VER_ERROR; SQLSTATE: HY000 Message: Error updating transaction snapshot version after transaction being positively certified.

Error number: MY-011456; Symbol: ER_GRP_RPL_SIDNO_FETCH_ERROR; SQLSTATE: HY000

Message: Error fetching transaction sidno after transaction being positively certified.

Error number: MY-011457; Symbol:

ER_GRP_RPL_BROADCAST_COMMIT_TRANS_MSSG_FAILED; SQLSTATE: HY000 Message: Broadcast of committed transactions Message failed.

Error number: MY-011458; Symbol: ER_GRP_RPL_GROUP_NAME_PARSE_ERROR; SQLSTATE: HY000

Message: Unable to parse the group_replication_group_name during the Certification module initialization.

Error number: MY-011459; Symbol:

ER_GRP_RPL_ADD_GRPSID_TO_GRPGTIDSID_MAP_ERROR; SQLSTATE: HY000 Message: Unable to add the group_sid in the group_gtid_sid_map during the Certification module initialization.

Error number: MY-011460; Symbol: ER_GRP_RPL_UPDATE_GRPGTID_EXECUTED_ERROR; SQLSTATE: HY000

Message: Error updating group_gtid_executed GITD set during the Certification module initialization.

Error number: MY-011461; Symbol: ER GRP RPL DONOR TRANS INFO ERROR;

SQLSTATE: HY000

Message: Unable to handle the donor's transaction information when initializing the conflict detection component. Possible out of memory error.

detection component. Possible out of memory error.

Error number: MY-011462; Symbol: ER_GRP_RPL_SERVER_CONN_ERROR; SQLSTATE:

HY000

Message: Error when establishing a server connection during the Certification module initialization.

Error number: MY-011463; Symbol:

ER_GRP_RPL_ERROR_FETCHING_GTID_EXECUTED_SET; SQLSTATE: HY000

Message: Error when extracting this member GTID executed set. Certification module can't be properly initialized.

Error number: MY-011464; Symbol:

ER_GRP_RPL_ADD_GTID_TO_GRPGTID_EXECUTED_ERROR; SQLSTATE: HY000

Message: Error while adding the server GTID EXECUTED set to the group_gtid_execute during the

Certification module initialization.

Error number: MY-011465; Symbol: ER GRP RPL ERROR FETCHING GTID SET;

SQLSTATE: HY000

Message: Error when extracting this member retrieved set for its applier. Certification module can't

be properly initialized.

Error number: MY-011466; Symbol:

ER_GRP_RPL_ADD_RETRIEVED_SET_TO_GRP_GTID_EXECUTED_ERROR; SQLSTATE:

HY000

Message: Error while adding the member retrieved set to the group gtid executed during the

Certification module initialization.

Error number: MY-011467; Symbol:

ER_GRP_RPL_CERTIFICATION_INITIALIZATION_FAILURE; SQLSTATE: HY000

Message: Error during Certification module initialization.

Error number: MY-011468; Symbol:

ER GRP RPL UPDATE LAST CONFLICT FREE TRANS ERROR; SQLSTATE: HY000

Message: Unable to update last conflict free transaction, this transaction will not be tracked on

performance_schema.replication_group_member_stats.last_conflict_free_transaction.

Error number: MY-011469; Symbol:

ER GRP RPL UPDATE_TRANS_SNAPSHOT_REF_VER_ERROR; SQLSTATE: HY000

Message: Error updating transaction snapshot version reference for internal storage.

Error number: MY-011470; Symbol: ER GRP RPL FETCH TRANS SIDNO ERROR;

SQLSTATE: HY000

Message: Error fetching transaction sidno while adding to the group gtid executed set.

Error number: MY-011471; Symbol: ER GRP RPL ERROR VERIFYING SIDNO; SQLSTATE:

HY000

Message: Error while ensuring the sidno be present in the group gtid executed.

Error number: MY-011472; Symbol: ER_GRP_RPL_CANT_GENERATE_GTID; SQLSTATE:

HY000

Message: Impossible to generate Global Transaction Identifier: the integer component reached the maximal value. Restart the group with a new group replication group name.

Error number: MY-011473; Symbol: ER_GRP_RPL_INVALID_GTID_SET; SQLSTATE: HY000

Message: Invalid stable transactions set.

Error number: MY-011474; Symbol: ER GRP RPL UPDATE GTID SET ERROR; SQLSTATE:

HY000

Message: Error updating stable transactions set.

Error number: MY-011475; Symbol: ER GRP RPL RECEIVED SET MISSING GTIDS;

SQLSTATE: HY000

Message: There was an error when filling the missing GTIDs on the applier channel received set.

Despite not critical, on the long run this may cause performance issues.

Error number: MY-011476; Symbol:

ER GRP RPL SKIP COMPUTATION TRANS COMMITTED; SQLSTATE: HY000

Message: Skipping the computation of the Transactions_committed_all_members field as an older

instance of this computation is still ongoing.

Error number: MY-011477; Symbol: ER GRP RPL NULL PACKET; SQLSTATE: HY000

Message: Null packet on certifier's queue.

Error number: MY-011478; Symbol: ER GRP RPL CANT READ GTID; SQLSTATE: HY000

Message: Error reading GTIDs from the Message.

Error number: MY-011479; Symbol: ER GRP RPL PROCESS GTID SET ERROR;

SQLSTATE: HY000

Message: Error processing stable transactions set.

Error number: MY-011480; Symbol:

ER GRP RPL PROCESS INTERSECTION GTID SET ERROR; SQLSTATE: HY000

Message: Error processing intersection of stable transactions set.

Error number: MY-011481; Symbol: ER GRP RPL SET STABLE TRANS ERROR;

SQLSTATE: HY000

Message: Error setting stable transactions set.

Error number: MY-011482; Symbol: ER GRP RPL CANT READ GRP GTID EXTRACTED;

SQLSTATE: HY000

Message: Error reading group gtid extracted from the View change log event.

Error number: MY-011483; Symbol: ER GRP RPL CANT READ WRITE SET ITEM;

SQLSTATE: HY000

Message: Error reading the write set item '%s' from the View change log event.

Error number: MY-011484; Symbol: ER GRP RPL INIT CERTIFICATION INFO FAILURE;

SQLSTATE: HY000

Message: Error during certification info initialization.

Error number: MY-011485; Symbol: ER GRP RPL CONFLICT DETECTION DISABLED;

SQLSTATE: HY000

Message: Primary had applied all relay logs, disabled conflict detection.

Error number: MY-011486; Symbol: ER GRP RPL MSG DISCARDED; SQLSTATE: HY000

Message: Message received while the plugin is not ready, Message discarded.

Error number: MY-011487; Symbol: ER GRP RPL MISSING GRP RPL APPLIER;

SQLSTATE: HY000

Message: Message received without a proper group replication applier.

Error number: MY-011488; Symbol: ER GRP RPL CERTIFIER MSSG PROCESS ERROR;

SQLSTATE: HY000

Message: Error processing Message in Certifier.

Error number: MY-011489; Symbol: ER GRP RPL SRV NOT ONLINE; SQLSTATE: HY000

Message: This server was not declared online since it is on status %s.

Error number: MY-011490; Symbol: ER GRP RPL SRV ONLINE; SQLSTATE: HY000

Message: This server was declared online within the replication group.

Error number: MY-011491; Symbol:

ER_GRP_RPL_DISABLE_SRV_READ_MODE_RESTRICTED; SQLSTATE: HY000 Message: When declaring the plugin online it was not possible to disable the server read mode

settings. Try to disable it manually.

Error number: MY-011492; Symbol: ER_GRP_RPL_MEM_ONLINE; SQLSTATE: HY000 Message: The member with address %s:%u was declared online within the replication group.

Error number: MY-011493; Symbol: ER_GRP_RPL_MEM_UNREACHABLE; SQLSTATE: HY000

Message: Member with address %s:%u has become unreachable.

Error number: MY-011494; Symbol: ER_GRP_RPL_MEM_REACHABLE; SQLSTATE: HY000 Message: Member with address %s:%u is reachable again.

Error number: MY-011495; Symbol: ER_GRP_RPL_SRV_BLOCKED; SQLSTATE: HY000 Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked until contact with the majority is restored. It is possible to use group_replication_force_members to force a new group membership.

Error number: MY-011496; Symbol: ER_GRP_RPL_SRV_BLOCKED_FOR_SECS; SQLSTATE: HY000

Message: This server is not able to reach a majority of members in the group. This server will now block all updates. The server will remain blocked for the next %lu seconds. Unless contact with the majority is restored, after this time the member will error out and leave the group. It is possible to use group_replication_force_members to force a new group membership.

Error number: MY-011497; Symbol: ER_GRP_RPL_CHANGE_GRP_MEM_NOT_PROCESSED; SQLSTATE: HY000

Message: A group membership change was received but the plugin is already leaving due to the configured timeout on group replication unreachable majority timeout option.

Error number: MY-011498; Symbol: ER_GRP_RPL_MEMBER_CONTACT_RESTORED; SQLSTATE: HY000

Message: The member has resumed contact with a majority of the members in the group. Regular operation is restored and transactions are unblocked.

Error number: MY-011499; Symbol: ER_GRP_RPL_MEMBER_REMOVED; SQLSTATE: HY000 Message: Members removed from the group: %s

Error number: MY-011500; Symbol: ER_GRP_RPL_PRIMARY_MEMBER_LEFT_GRP; SQLSTATE: HY000

Message: Primary server with address %s left the group. Electing new Primary.

Error number: MY-011501; Symbol: ER_GRP_RPL_MEMBER_ADDED; SQLSTATE: HY000

Message: Members joined the group: %s

Error number: MY-011502; Symbol: ER GRP RPL MEMBER EXIT PLUGIN ERROR;

SQLSTATE: HY000

Message: There was a previous plugin error while the member joined the group. The member will

now exit the group.

Error number: MY-011503; Symbol: ER GRP RPL MEMBER CHANGE; SQLSTATE: HY000

Message: Group membership changed to %s on view %s.

Error number: MY-011504; Symbol: ER_GRP_RPL_MEMBER_LEFT_GRP; SQLSTATE: HY000

Message: Group membership changed: This member has left the group.

Error number: MY-011505; Symbol: ER GRP RPL MEMBER EXPELLED; SQLSTATE: HY000

Message: Member was expelled from the group due to network failures, changing member status to

ERROR.

Error number: MY-011506; Symbol: ER GRP RPL SESSION OPEN FAILED; SQLSTATE:

HY000

Message: Unable to open session to (re)set read only mode. Skipping.

Error number: MY-011507; Symbol: ER GRP RPL NEW PRIMARY ELECTED; SQLSTATE:

HY000

Message: A new primary with address %s:%u was elected. %s

Error number: MY-011508; Symbol: ER GRP RPL DISABLE READ ONLY FAILED;

SQLSTATE: HY000

Message: Unable to disable super read only flag. Try to disable it manually

Error number: MY-011509; Symbol: ER_GRP_RPL_ENABLE_READ_ONLY_FAILED;

SOLSTATE: HY000

Message: Unable to set super read only flag. Try to set it manually.

Error number: MY-011510; Symbol: ER GRP RPL SRV PRIMARY MEM; SQLSTATE: HY000

Message: This server is working as primary member.

Error number: MY-011511; Symbol: ER GRP RPL SRV SECONDARY MEM; SQLSTATE:

HY000

Message: This server is working as secondary member with primary member address %s:%u.

Error number: MY-011512; Symbol: ER GRP RPL NO SUITABLE PRIMARY MEM;

SQLSTATE: HY000

Message: Unable to set any member as primary. No suitable candidate.

Error number: MY-011513; Symbol:

ER GRP RPL SUPER READ ONLY ACTIVATE ERROR; SQLSTATE: HY000

Message: Error when activating super read only mode on start. The member will now exit the

group.

Error number: MY-011514; Symbol: ER GRP RPL EXCEEDS AUTO INC VALUE;

SQLSTATE: HY000

Message: Group contains %lu members which is greater than

group_replication_auto_increment_increment value of %lu. This can lead to a higher transactional

abort rate.

Error number: MY-011515; Symbol: ER_GRP_RPL_DATA_NOT_PROVIDED_BY_MEM;

SQLSTATE: HY000

Message: Member with address '%s:%u' didn't provide any data during the last group change. Group

information can be outdated and lead to errors on recovery.

Error number: MY-011516; Symbol: ER_GRP_RPL_MEMBER_ALREADY_EXISTS;

SOLSTATE: HY000

Message: There is already a member with server uuid %s. The member will now exit the group.

Error number: MY-011517; Symbol: ER GRP RPL GRP CHANGE INFO EXTRACT ERROR;

SQLSTATE: HY000

Message: Error when extracting information for group change. Operations and checks made to group

joiners may be incomplete.

Error number: MY-011518; Symbol: ER GRP RPL GTID EXECUTED EXTRACT ERROR;

SQLSTATE: HY000

Message: Error when extracting this member GTID executed set. Operations and checks made to

group joiners may be incomplete.

Error number: MY-011519; Symbol: ER GRP RPL GTID SET EXTRACT ERROR;

SQLSTATE: HY000

Message: Error when extracting this member retrieved set for its applier. Operations and checks

made to group joiners may be incomplete.

Error number: MY-011520; Symbol: ER GRP RPL START FAILED; SQLSTATE: HY000

Message: The START GROUP_REPLICATION command failed since the group already has 9 members.

Error number: MY-011521; Symbol: ER_GRP_RPL_MEMBER_VER_INCOMPATIBLE;

SQLSTATE: HY000

Message: Member version is incompatible with the group.

Error number: MY-011522; Symbol: ER GRP RPL TRANS NOT PRESENT IN GRP;

SQLSTATE: HY000

Message: The member contains transactions not present in the group. The member will now exit the

group.

Error number: MY-011523; Symbol: ER GRP RPL TRANS GREATER THAN GRP;

SQLSTATE: HY000

Message: It was not possible to assess if the member has more transactions than the group. The

member will now exit the group.

Error number: MY-011524; Symbol:

ER GRP RPL MEMBER VERSION LOWER THAN GRP; SQLSTATE: HY000

Message: Member version is lower than some group member, but since option

'group_replication_allow_local_lower_version_join is enabled, member will be allowed to join.

Error number: MY-011525; Symbol: ER_GRP_RPL_LOCAL_GTID_SETS_PROCESS_ERROR;

SQLSTATE: HY000

Message: Error processing local GTID sets when comparing this member transactions against the

group.

Error number: MY-011526; Symbol:

ER GRP RPL MEMBER TRANS GREATER THAN GRP; SQLSTATE: HY000

Message: This member has more executed transactions than those present in the group. Local

transactions: %s > Group transactions: %s

Error number: MY-011527; Symbol: ER_GRP_RPL_BLOCK_SIZE_DIFF_FROM_GRP;

SOLSTATE: HY000

Message: The member is configured with a group replication gtid assignment block size option

value '%llu' different from the group '%llu'. The member will now exit the group.

Error number: MY-011528; Symbol:

ER GRP RPL TRANS WRITE SET EXTRACT DIFF FROM GRP; SQLSTATE: HY000

Message: The member is configured with a transaction-write-set-extraction option value '%s'

different from the group '%s'. The member will now exit the group.

Error number: MY-011529; Symbol:

ER GRP RPL MEMBER CFG INCOMPATIBLE WITH GRP CFG; SQLSTATE: HY000

Message: The member configuration is not compatible with the group configuration. Variables such as group replication single primary mode or

group_replication_enforce_update_everywhere_checks must have the same value on every server in the group. (member configuration option: [%s], group configuration option: [%s]).

Error number: MY-011530; Symbol:

ER_GRP_RPL_MEMBER_STOP_RPL_CHANNELS_ERROR; SQLSTATE: HY000 Message: Error stopping all replication channels while server was leaving the group. %s

Error number: MY-011531; Symbol: ER_GRP_RPL_PURGE_APPLIER_LOGS; SQLSTATE: HY000

Message: Detected previous RESET MASTER invocation or an issue exists in the group replication applier relay log. Purging existing applier logs.

Error number: MY-011532; Symbol:

ER GRP RPL RESET APPLIER MODULE LOGS ERROR; SQLSTATE: HY000

Message: Unknown error occurred while resetting applier's module logs.

Error number: MY-011533; Symbol: ER GRP RPL APPLIER THD SETUP ERROR;

SQLSTATE: HY000

Message: Failed to setup the group replication applier thread.

Error number: MY-011534; Symbol: ER GRP RPL APPLIER THD START ERROR;

SQLSTATE: HY000

Message: Error while starting the group replication applier thread

Error number: MY-011535; Symbol: ER GRP RPL APPLIER THD STOP ERROR;

SQLSTATE: HY000

Message: Failed to stop the group replication applier thread.

Error number: MY-011536; Symbol: ER_GRP_RPL_FETCH_TRANS_DATA_FAILED;

SOLSTATE: HY000

Message: Failed to fetch transaction data containing required transaction info for applier

Error number: MY-011537; Symbol: ER GRP RPL SLAVE IO THD PRIMARY UNKNOWN;

SQLSTATE: HY000

Message: Can't start slave IO THREAD of channel '%s' when group replication is running with

single-primary mode and the primary member is not known.

Error number: MY-011538; Symbol:

ER_GRP_RPL_SALVE_IO_THD_ON_SECONDARY_MEMBER; SQLSTATE: HY000 Message: Can't start slave IO THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

Error number: MY-011539; Symbol:

ER GRP RPL SLAVE SQL THD PRIMARY UNKNOWN; SQLSTATE: HY000

Message: Can't start slave SQL THREAD of channel '%s' when group replication is running with single-primary mode and the primary member is not known.

Error number: MY-011540; Symbol:

ER_GRP_RPL_SLAVE_SQL_THD_ON_SECONDARY_MEMBER; SQLSTATE: HY000 Message: Can't start slave SQL THREAD of channel '%s' when group replication is running with single-primary mode on a secondary member.

Error number: MY-011541; Symbol: ER_GRP_RPL_NEEDS_INNODB_TABLE; SQLSTATE: HY000

Message: Table %s does not use the InnoDB storage engine. This is not compatible with Group Replication.

Error number: MY-011542; Symbol: ER_GRP_RPL_PRIMARY_KEY_NOT_DEFINED; SQLSTATE: HY000

Message: Table %s does not have any PRIMARY KEY. This is not compatible with Group Replication.

Error number: MY-011543; Symbol: ER_GRP_RPL_FK_WITH_CASCADE_UNSUPPORTED; SQLSTATE: HY000

Message: Table %s has a foreign key with 'CASCADE', 'SET NULL' or 'SET DEFAULT' clause. This is not compatible with Group Replication.

Error number: MY-011544; Symbol: ER_GRP_RPL_AUTO_INC_RESET; SQLSTATE: HY000 Message: group replication auto increment increment is reset to %lu

Error number: MY-011545; Symbol: ER_GRP_RPL_AUTO_INC_OFFSET_RESET; SQLSTATE: HY000

Message: auto_increment_offset is reset to %lu

Error number: MY-011546; Symbol: ER_GRP_RPL_AUTO_INC_SET; SQLSTATE: HY000 Message: group_replication_auto_increment_increment is set to %lu

Error number: MY-011547; Symbol: ER_GRP_RPL_AUTO_INC_OFFSET_SET; SQLSTATE: HY000

Message: auto increment offset is set to %lu

Error number: MY-011548; Symbol: ER GRP RPL FETCH TRANS CONTEXT FAILED;

SQLSTATE: HY000

Message: Failed to fetch transaction context containing required transaction info for certification

Error number: MY-011549; Symbol:

ER GRP RPL FETCH FORMAT DESC LOG EVENT FAILED; SQLSTATE: HY000

Message: Failed to fetch Format description log event containing required server info for applier

Error number: MY-011550; Symbol:

 $ER_GRP_RPL_FETCH_TRANS_CONTEXT_LOG_EVENT_FAILED; SQLSTATE: HY000$

Message: Failed to fetch Transaction_context_log_event containing required transaction info for

certification

Error number: MY-011551; Symbol: ER_GRP_RPL_FETCH_SNAPSHOT_VERSION_FAILED;

SQLSTATE: HY000

Message: Failed to read snapshot version from transaction context event required for certification

Error number: MY-011552; Symbol: ER GRP RPL FETCH GTID LOG EVENT FAILED;

SOLSTATE: HY000

Message: Failed to fetch Gtid log event containing required transaction info for certification

Error number: MY-011553; Symbol: ER GRP RPL UPDATE SERV CERTIFICATE FAILED;

SQLSTATE: HY000

Message: Unable to update certification result on server side, thread id: %lu

Error number: MY-011554; Symbol:

ER GRP RPL ADD GTID INFO WITH LOCAL GTID FAILED; SQLSTATE: HY000

Message: Unable to add gtid information to the group gtid executed set when gtid was provided for

local transactions

Error number: MY-011555; Symbol:

ER GRP RPL ADD GTID INFO WITHOUT LOCAL GTID FAILED; SQLSTATE: HY000

Message: Unable to add gtid information to the group gtid executed set when no gtid was provided

for local transactions

Error number: MY-011556; Symbol:

ER GRP RPL NOTIFY CERTIFICATION OUTCOME FAILED; SQLSTATE: HY000

Message: Failed to notify certification outcome

Error number: MY-011557; Symbol:

ER_GRP_RPL_ADD_GTID_INFO_WITH_REMOTE_GTID_FAILED; SQLSTATE: HY000 Message: Unable to add gtid information to the group_gtid_executed set when gtid was provided for

remote transactions

Error number: MY-011558; Symbol:

ER_GRP_RPL_ADD_GTID_INFO_WITHOUT_REMOTE_GTID_FAILED; SQLSTATE: HY000 Message: Unable to add gtid information to the group_gtid_executed set when gtid was not provided for remote transactions

Error number: MY-011559; Symbol:

ER_GRP_RPL_FETCH_VIEW_CHANGE_LOG_EVENT_FAILED; SQLSTATE: HY000 Message: Failed to fetch View change log event containing required info for certification

Error number: MY-011560; Symbol: ER_GRP_RPL_CONTACT_WITH_SRV_FAILED;

SQLSTATE: HY000

Message: Error when contacting the server to ensure the proper logging of a group change in the binlog

Error number: MY-011561; Symbol: ER_GRP_RPL_SRV_WAIT_TIME_OUT; SQLSTATE: HY000

Message: Timeout when waiting for the server to execute local transactions in order assure the group change proper logging

Error number: MY-011562; Symbol: ER GRP RPL FETCH LOG EVENT FAILED;

SQLSTATE: HY000

Message: Failed to fetch Log event containing required server info for applier

Error number: MY-011563; Symbol: ER_GRP_RPL_START_GRP_RPL_FAILED; SQLSTATE: HY000

Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with --initialize, --initialize-insecure or --upgrade=MINIMAL on a server upgrade.

Error number: MY-011564; Symbol: ER GRP RPL CONN INTERNAL PLUGIN FAIL;

SQLSTATE: HY000

Message: Failed to establish an internal server connection to execute plugin operations

Error number: MY-011565; Symbol: ER_GRP_RPL_SUPER_READ_ON; SQLSTATE: HY000 Message: Setting super read only=ON.

Error number: MY-011566; Symbol: ER_GRP_RPL_SUPER_READ_OFF; SQLSTATE: HY000

Message: Setting super read only=OFF.

Error number: MY-011567; Symbol: ER GRP RPL KILLED SESSION ID; SQLSTATE: HY000

Message: killed session id: %d status: %d

Error number: MY-011568; Symbol: ER GRP RPL KILLED FAILED ID; SQLSTATE: HY000

Message: killed failed id: %d failed: %d

Error number: MY-011569; Symbol: ER GRP RPL INTERNAL QUERY; SQLSTATE: HY000

Message: Internal query: %s result in error. Error number: %ld

Error number: MY-011570; Symbol: ER GRP RPL COPY FROM EMPTY STRING;

SQLSTATE: HY000

Message: Error copying from empty string

Error number: MY-011571; Symbol: ER GRP RPL QUERY FAIL; SQLSTATE: HY000

Message: Query execution resulted in failure. errno: %d

Error number: MY-011572; Symbol: ER GRP RPL CREATE SESSION UNABLE; SQLSTATE:

HY000

Message: Unable to create a session for executing the queries on the server

Error number: MY-011573; Symbol: ER GRP RPL MEMBER NOT FOUND; SQLSTATE:

HY000

Message: The member with address %s:%u has unexpectedly disappeared, killing the current group

replication recovery connection

Error number: MY-011574; Symbol:

ER GRP RPL MAXIMUM CONNECTION RETRIES REACHED; SQLSTATE: HY000

Message: Maximum number of retries when trying to connect to a donor reached. Aborting group

replication incremental recovery.

Error number: MY-011575; Symbol:

ER GRP RPL ALL DONORS LEFT ABORT RECOVERY; SOLSTATE: HY000

Message: All donors left. Aborting group replication incremental recovery.

Error number: MY-011576; Symbol: ER GRP RPL ESTABLISH RECOVERY WITH DONOR;

SQLSTATE: HY000

Message: Establishing group recovery connection with a possible donor. Attempt %d/%d

Error number: MY-011577; Symbol:

ER_GRP_RPL_ESTABLISH_RECOVERY_WITH_ANOTHER_DONOR; SQLSTATE: HY000

Message: Retrying group recovery connection with another donor. Attempt %d/%d

Error number: MY-011578; Symbol: ER_GRP_RPL_NO_VALID_DONOR; SQLSTATE: HY000 Message: No valid donors exist in the group, retrying

Error number: MY-011579; Symbol: ER_GRP_RPL_CONFIG_RECOVERY; SQLSTATE: HY000 Message: Error when configuring the asynchronous recovery channel connection to the donor.

Error number: MY-011580; Symbol:

ER_GRP_RPL_ESTABLISHING_CONN_GRP_REC_DONOR; SQLSTATE: HY000 Message: Establishing connection to a group replication recovery donor %s at %s port: %d.

Error number: MY-011581; Symbol: ER_GRP_RPL_CREATE_GRP_RPL_REC_CHANNEL; SQLSTATE: HY000

Message: Error while creating the group replication recovery channel with donor %s at %s port: %d.

Error number: MY-011582; Symbol: ER_GRP_RPL_DONOR_SERVER_CONN; SQLSTATE: HY000

Message: There was an error when connecting to the donor server. Please check that group_replication_recovery channel credentials and all MEMBER_HOST column values of performance schema.replication group members table are correct and DNS resolvable.

Error number: MY-011583; Symbol: ER_GRP_RPL_CHECK_STATUS_TABLE; SQLSTATE: HY000

Message: For details please check performance_schema.replication_connection_status table and error log Messages of Slave I/O for channel group_replication_recovery.

Error number: MY-011584; Symbol: ER_GRP_RPL_STARTING_GRP_REC; SQLSTATE: HY000 Message: Error while starting the group replication incremental recovery receiver/applier threads

Error number: MY-011585; Symbol: ER_GRP_RPL_DONOR_CONN_TERMINATION; SQLSTATE: HY000

Message: Terminating existing group replication donor connection and purging the corresponding logs.

Error number: MY-011586; Symbol: ER_GRP_RPL_STOPPING_GRP_REC; SQLSTATE: HY000 Message: Error when stopping the group replication incremental recovery's donor connection

Error number: MY-011587; Symbol: ER_GRP_RPL_PURGE_REC; SQLSTATE: HY000 Message: Error when purging the group replication recovery's relay logs

Error number: MY-011588; Symbol:

ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_APPLIER; SQLSTATE: HY000 Message: Unable to kill the current group replication recovery donor connection after an applier error. Incremental recovery will shutdown.

Error number: MY-011589; Symbol:

ER_GRP_RPL_UNABLE_TO_KILL_CONN_REC_DONOR_FAILOVER; SQLSTATE: HY000 Message: Unable to kill the current group replication recovery donor connection during failover. Incremental recovery will shutdown.

Error number: MY-011590; Symbol:

ER_GRP_RPL_FAILED_TO_NOTIFY_GRP_MEMBERSHIP_EVENT; SQLSTATE: HY000 Message: Unexpected error when notifying an internal component named %s regarding a group membership event.

Error number: MY-011591; Symbol:

ER_GRP_RPL_FAILED_TO_BROADCAST_GRP_MEMBERSHIP_NOTIFICATION;

SQLSTATE: HY000

Message: An undefined error was found while broadcasting an internal group membership notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!

Error number: MY-011592; Symbol:

ER GRP RPL FAILED TO BROADCAST MEMBER STATUS NOTIFICATION;

SQLSTATE: HY000

Message: An undefined error was found while broadcasting an internal group member status notification! This is likely to happen if your components or plugins are not properly loaded or are malfunctioning!

Error number: MY-011593; Symbol:

 $ER_GRP_RPL_OOM_FAILED_TO_GENERATE_IDENTIFICATION_HASH; SQLSTATE:$

HY000

Message: No memory to generate write identification hash

Error number: MY-011594; Symbol:

ER_GRP_RPL_WRITE_IDENT_HASH_BASE64_ENCODING_FAILED; SQLSTATE: HY000

Message: Base 64 encoding of the write identification hash failed

Error number: MY-011595; Symbol: ER_GRP_RPL_INVALID_BINLOG_FORMAT; SQLSTATE:

HY000

Message: Binlog format should be ROW for Group Replication

Error number: MY-011596; Symbol: ER GRP RPL BINLOG CHECKSUM SET; SQLSTATE:

HY000

Message: binlog checksum should be NONE for Group Replication

Error number: MY-011597; Symbol:

ER_GRP_RPL_TRANS_WRITE_SET_EXTRACTION_NOT_SET; SQLSTATE: HY000

Message: A transaction write set extraction algorithm should be selected when running Group

Replication

Error number: MY-011598; Symbol: ER GRP RPL UNSUPPORTED TRANS ISOLATION;

SQLSTATE: HY000

Message: Transaction isolation level (tx isolation) is set to SERIALIZABLE, which is not

compatible with Group Replication

Error number: MY-011599; Symbol:

ER GRP RPL CANNOT EXECUTE TRANS WHILE STOPPING; SQLSTATE: HY000

Message: Transaction cannot be executed while Group Replication is stopping.

Error number: MY-011600; Symbol:

ER GRP RPL CANNOT EXECUTE TRANS WHILE RECOVERING; SQLSTATE: HY000

Message: Transaction cannot be executed while Group Replication is recovering. Try again when the

server is ONLINE.

Error number: MY-011601; Symbol:

ER GRP RPL CANNOT EXECUTE TRANS IN ERROR STATE; SQLSTATE: HY000

Message: Transaction cannot be executed while Group Replication is on ERROR state. Check for

errors and restart the plugin

Error number: MY-011602; Symbol:

ER GRP RPL CANNOT EXECUTE TRANS IN OFFLINE MODE; SQLSTATE: HY000

Message: Transaction cannot be executed while Group Replication is OFFLINE. Check for errors

and restart the plugin

Error number: MY-011603; Symbol:

ER GRP RPL MULTIPLE CACHE TYPE NOT SUPPORTED FOR SESSION; SQLSTATE:

HY000

Message: We can only use one cache type at a time on session %u

Error number: MY-011604; Symbol:

ER GRP RPL FAILED TO REINIT BINLOG CACHE FOR READ; SQLSTATE: HY000

Message: Failed to reinit binlog cache log for read on session %u

Error number: MY-011605; Symbol: ER GRP RPL FAILED TO CREATE TRANS CONTEXT;

SOLSTATE: HY000

Message: Failed to create the context of the current transaction on session %u

Error number: MY-011606; Symbol:

ER GRP RPL FAILED TO EXTRACT TRANS WRITE SET; SQLSTATE: HY000

Message: Failed to extract the set of items written during the execution of the current transaction on

session %u

Error number: MY-011607; Symbol:

ER GRP RPL FAILED TO GATHER TRANS WRITE SET; SQLSTATE: HY000

Message: Failed to gather the set of items written during the execution of the current transaction on

session %u

Error number: MY-011608; Symbol: ER GRP RPL TRANS SIZE EXCEEDS LIMIT;

SQLSTATE: HY000

Message: Error on session %u. Transaction of size %llu exceeds specified limit %lu. To increase the

limit please adjust group_replication_transaction_size_limit option.

Error number: MY-011609; Symbol:

ER GRP RPL REINIT OF INTERNAL CACHE FOR READ FAILED; SQLSTATE: HY000

Message: Error while re-initializing an internal cache, for read operations, on session %u

Error number: MY-011610; Symbol:

ER GRP RPL APPENDING DATA TO INTERNAL CACHE FAILED; SQLSTATE: HY000

Message: Error while appending data to an internal cache on session %u

Error number: MY-011611; Symbol: ER_GRP_RPL_WRITE_TO_BINLOG_CACHE_FAILED;

SQLSTATE: HY000

Message: Error while writing binary log cache on session %u

Error number: MY-011611; Symbol:

ER GRP RPL WRITE TO TRANSACTION MESSAGE FAILED; SQLSTATE: HY000

Message: Error while writing to transaction Message on session %u

Error number: MY-011612; Symbol:

ER GRP RPL FAILED TO REGISTER TRANS OUTCOME NOTIFICTION; SQLSTATE:

HY000

Message: Unable to register for getting notifications regarding the outcome of the transaction on

session %u

Error number: MY-011613; Symbol:

ER GRP RPL MSG TOO LONG BROADCASTING TRANS FAILED; SQLSTATE: HY000

Message: Error broadcasting transaction to the group on session %u. Message is too big.

Error number: MY-011614; Symbol:

ER GRP RPL BROADCASTING TRANS TO GRP FAILED; SQLSTATE: HY000

Message: Error while broadcasting the transaction to the group on session %u

Error number: MY-011615; Symbol:

ER GRP RPL ERROR WHILE WAITING FOR CONFLICT DETECTION; SQLSTATE:

HY000

Message: Error while waiting for conflict detection procedure to finish on session %u

Error number: MY-011616; Symbol:

ER GRP RPL REINIT OF INTERNAL CACHE FOR WRITE FAILED; SQLSTATE: HY000

Message: Error while re-initializing an internal cache, for write operations, on session %u

Error number: MY-011617; Symbol: ER_GRP_RPL_FAILED_TO_CREATE_COMMIT_CACHE;

SQLSTATE: HY000

Message: Failed to create group replication commit cache on session %u

Error number: MY-011618; Symbol:

ER GRP RPL REINIT OF COMMIT CACHE FOR WRITE FAILED; SQLSTATE: HY000

Message: Failed to reinit group replication commit cache for write on session %u

Error number: MY-011619; Symbol: ER GRP RPL PREV REC SESSION RUNNING;

SQLSTATE: HY000

Message: A previous recovery session is still running. Please stop the group replication plugin and

wait for it to stop

Error number: MY-011620; Symbol: ER GRP RPL FATAL REC PROCESS; SQLSTATE:

HY000

Message: Fatal error during the incremental recovery process of Group Replication. The server will

leave the group.

Error number: MY-011621; Symbol: ER GRP RPL WHILE STOPPING REP CHANNEL;

SQLSTATE: HY000

Message: Error stopping all replication channels while server was leaving the group. %s

Error number: MY-011622; Symbol:

ER GRP RPL UNABLE TO EVALUATE APPLIER STATUS; SQLSTATE: HY000

Message: Unable to evaluate the group replication applier execution status. Group replication recovery will shutdown to avoid data corruption.

Error number: MY-011623; Symbol: ER_GRP_RPL_ONLY_ONE_SERVER_ALIVE; SQLSTATE: HY000

Message: Only one server alive. Declaring this server as online within the replication group

Error number: MY-011624; Symbol: ER_GRP_RPL_CERTIFICATION_REC_PROCESS; SQLSTATE: HY000

Message: Error when processing certification information in the incremental recovery process

Error number: MY-011625; Symbol:

ER_GRP_RPL_UNABLE_TO_ENSURE_EXECUTION_REC; SQLSTATE: HY000 Message: Unable to ensure the execution of group transactions received during recovery.

 $Error\ number:\ MY-011626;\ Symbol:\ ER_GRP_RPL_WHILE_SENDING_MSG_REC;$

SQLSTATE: HY000

Message: Error while sending Message in the group replication incremental recovery process.

Error number: MY-011627; Symbol:

ER GRP RPL READ UNABLE FOR SUPER READ ONLY; SQLSTATE: HY000

Message: Unable to read the server value for the super read only variable.

Error number: MY-011628; Symbol:

 $\label{eq:control} ER_GRP_RPL_READ_UNABLE_FOR_READ_ONLY_SUPER_READ_ONLY; SQLSTATE: \\ HY000$

Message: Unable to read the server values for the read only and super read only variables.

Error number: MY-011629; Symbol:

ER_GRP_RPL_UNABLE_TO_RESET_SERVER_READ_MODE; SQLSTATE: HY000

Message: Unable to reset the server read mode settings. Try to reset them manually.

Error number: MY-011630; Symbol: ER_GRP_RPL_UNABLE_TO_CERTIFY_PLUGIN_TRANS;

SOLSTATE: HY000

Message: Due to a plugin error, some transactions were unable to be certified and will now rollback.

Error number: MY-011631; Symbol: ER GRP RPL UNBLOCK CERTIFIED TRANS;

SQLSTATE: HY000

Message: Error when trying to unblock non certified or consistent transactions. Check for

consistency errors when restarting the service

Error number: MY-011632; Symbol: ER_GRP_RPL_SERVER_WORKING_AS_SECONDARY;

SOLSTATE: HY000

Message: This server is working as secondary member with primary member address %s:%u.

Error number: MY-011633; Symbol:

ER_GRP_RPL_FAILED_TO_START_WITH_INVALID_SERVER_ID; SQLSTATE: HY000 Message: Unable to start Group Replication. Replication applier infrastructure is not initialized since the server was started with server_id=0. Please, restart the server with server_id larger than 0.

Error number: MY-011634; Symbol: ER_GRP_RPL_FORCE_MEMBERS_MUST_BE_EMPTY;

SQLSTATE: HY000

Message: group_replication_force_members must be empty on group start. Current value: '%s'

Error number: MY-011635; Symbol:

 $\label{eq:con_server_start} ER_GRP_RPL_PLUGIN_STRUCT_INIT_NOT_POSSIBLE_ON_SERVER_START; SQLSTATE: \\ HY0000$

Message: It was not possible to guarantee the initialization of plugin structures on server start

Error number: MY-011636; Symbol:

ER_GRP_RPL_FAILED_TO_ENABLE_SUPER_READ_ONLY_MODE; SQLSTATE: HY000 Message: Could not enable the server read only mode and guarantee a safe recovery execution

Error number: MY-011637; Symbol:

ER_GRP_RPL_FAILED_TO_INIT_COMMUNICATION_ENGINE; SQLSTATE: HY000 Message: Error on group communication engine initialization

Error number: MY-011638; Symbol:

ER_GRP_RPL_FAILED_TO_START_ON_SECONDARY_WITH_ASYNC_CHANNELS; SQLSTATE: HY000

Message: Can't start group replication on secondary member with single-primary mode while asynchronous replication channels are running.

Error number: MY-011639; Symbol:

 $ER_GRP_RPL_FAILED_TO_START_COMMUNICATION_ENGINE; SQLSTATE: HY000$

Message: Error on group communication engine start

Error number: MY-011640; Symbol:

ER GRP RPL TIMEOUT ON VIEW AFTER JOINING GRP; SQLSTATE: HY000

Message: Timeout on wait for view after joining group

Error number: MY-011641; Symbol:

ER_GRP_RPL_FAILED_TO_CALL_GRP_COMMUNICATION_INTERFACE; SQLSTATE:

HY000

Message: Error calling group communication interfaces

Error number: MY-011642; Symbol:

 $ER_GRP_RPL_MEMBER_SERVER_UUID_IS_INCOMPATIBLE_WITH_GRP; SQLSTATE:$

HY000

Message: Member server uuid is incompatible with the group. Server uuid %s matches

group replication group name %s.

Error number: MY-011643; Symbol: ER_GRP_RPL_MEMBER_CONF_INFO; SQLSTATE:

HY000

Message: Member configuration: member id: %lu; member uuid: "%s"; single-primary mode:

"%s"; group_replication_auto_increment_increment: %lu; group_replication_view_change_uuid: "%s";

Error number: MY-011644; Symbol:

ER GRP RPL FAILED TO CONFIRM IF SERVER LEFT GRP; SQLSTATE: HY000

Message: Unable to confirm whether the server has left the group or not. Check

performance schema.replication group members to check group membership information.

Error number: MY-011645; Symbol: ER GRP RPL SERVER IS ALREADY LEAVING;

SQLSTATE: HY000

Message: Skipping leave operation: concurrent attempt to leave the group is on-going.

Error number: MY-011646; Symbol: ER GRP RPL SERVER ALREADY LEFT; SQLSTATE:

HY000

Message: Skipping leave operation: member already left the group.

Error number: MY-011647; Symbol: ER GRP RPL WAITING FOR VIEW UPDATE;

SQLSTATE: HY000

Message: Going to wait for view modification

Error number: MY-011648; Symbol:

ER GRP RPL TIMEOUT RECEIVING VIEW CHANGE ON SHUTDOWN; SQLSTATE:

HY000

Message: While leaving the group due to a stop, shutdown or failure there was a timeout receiving a

view change. This can lead to a possible inconsistent state. Check the log for more details

Error number: MY-011649; Symbol:

ER GRP RPL REQUESTING NON MEMBER SERVER TO LEAVE; SQLSTATE: HY000

Message: Requesting to leave the group despite of not being a member

Error number: MY-011650; Symbol: ER GRP RPL IS STOPPING; SQLSTATE: HY000

Message: Plugin 'group replication' is stopping.

Error number: MY-011651; Symbol: ER GRP RPL IS STOPPED; SQLSTATE: HY000

Message: Plugin 'group replication' has been stopped.

Error number: MY-011652; Symbol:

ER_GRP_RPL_FAILED_TO_ENABLE_READ_ONLY_MODE_ON_SHUTDOWN; SQLSTATE:

HY000

Message: On plugin shutdown it was not possible to enable the server read only mode. Local

transactions will be accepted and committed.

Error number: MY-011653; Symbol:

ER_GRP_RPL_RECOVERY_MODULE_TERMINATION_TIMED_OUT_ON_SHUTDOWN;

SQLSTATE: HY000

Message: On shutdown there was a timeout on the Group Replication recovery module termination.

Check the log for more details

Error number: MY-011654; Symbol:

ER GRP RPL APPLIER TERMINATION TIMED OUT ON SHUTDOWN; SQLSTATE:

HY000

Message: On shutdown there was a timeout on the Group Replication applier termination.

Error number: MY-011655; Symbol:

ER GRP RPL FAILED TO SHUTDOWN REGISTRY MODULE; SQLSTATE: HY000

Message: Unexpected failure while shutting down registry module!

Error number: MY-011656; Symbol: ER GRP RPL FAILED TO INIT HANDLER; SQLSTATE:

HY000

Message: Failure during Group Replication handler initialization

Error number: MY-011657; Symbol:

ER GRP RPL FAILED TO REGISTER SERVER STATE OBSERVER; SQLSTATE: HY000

Message: Failure when registering the server state observers

Error number: MY-011658; Symbol:

ER GRP RPL FAILED TO REGISTER TRANS STATE OBSERVER; SQLSTATE: HY000

Message: Failure when registering the transactions state observers

Error number: MY-011659; Symbol:

ER GRP RPL FAILED TO REGISTER BINLOG STATE OBSERVER; SQLSTATE: HY000

Message: Failure when registering the binlog state observers

Error number: MY-011660; Symbol: ER GRP RPL FAILED TO START ON BOOT;

SQLSTATE: HY000

Message: Unable to start Group Replication on boot

Error number: MY-011661; Symbol:

ER GRP RPL FAILED TO STOP ON PLUGIN UNINSTALL; SQLSTATE: HY000

Message: Failure when stopping Group Replication on plugin uninstall

Error number: MY-011662; Symbol:

ER_GRP_RPL_FAILED_TO_UNREGISTER_SERVER_STATE_OBSERVER; SQLSTATE:

HY000

Message: Failure when unregistering the server state observers

Error number: MY-011663; Symbol:

ER GRP RPL FAILED TO UNREGISTER TRANS STATE OBSERVER; SQLSTATE:

HY000

Message: Failure when unregistering the transactions state observers

Error number: MY-011664; Symbol:

ER GRP RPL FAILED TO UNREGISTER BINLOG STATE OBSERVER; SQLSTATE:

HY000

Message: Failure when unregistering the binlog state observers

Error number: MY-011665; Symbol: ER_GRP_RPL_ALL_OBSERVERS_UNREGISTERED;

SQLSTATE: HY000

Message: All Group Replication server observers have been successfully unregistered

Error number: MY-011666; Symbol: ER GRP RPL FAILED TO PARSE THE GRP NAME;

SQLSTATE: HY000

Message: Unable to parse the group replication group name.

Error number: MY-011667; Symbol:

ER GRP RPL FAILED TO GENERATE SIDNO FOR GRP; SQLSTATE: HY000

Message: Unable to parse the group replication group name.

Error number: MY-011668; Symbol:

ER GRP RPL APPLIER NOT STARTED DUE TO RUNNING PREV SHUTDOWN;

SQLSTATE: HY000

Message: Cannot start the Group Replication applier as a previous shutdown is still running: The thread will stop once its task is complete.

Error number: MY-011669; Symbol: ER_GRP_RPL_FAILED_TO_INIT_APPLIER_MODULE;

SQLSTATE: HY000

Message: Unable to initialize the Group Replication applier module.

Error number: MY-011670; Symbol: ER GRP RPL APPLIER INITIALIZED; SQLSTATE:

HY000

Message: Group Replication applier module successfully initialized!

Error number: MY-011671; Symbol: ER_GRP_RPL_COMMUNICATION_SSL_CONF_INFO;

SQLSTATE: HY000

Message: Group communication SSL configuration: group_replication_ssl_mode: "%s"; server_key_file: "%s"; server_cert_file: "%s"; client_key_file: "%s"; client_cert_file: "%s"; ca_file: "%s"; ca_path: "%s"; cipher: "%s"; tls_version: "%s"; tls_ciphersuites: "%s"; crl_file: "%s"; crl_path: "%s"; ssl_fips_mode: "%s"

2.10 错误码及错误信息汇总 10

Error number: MY-011672; Symbol:

ER_GRP_RPL_ABORTS_AS_SSL_NOT_SUPPORTED_BY_MYSQLD; SQLSTATE: HY000 Message: MySQL server does not have SSL support and group_replication_ssl_mode is "%s", START GROUP_REPLICATION will abort

Error number: MY-011673; Symbol: ER_GRP_RPL_SSL_DISABLED; SQLSTATE: HY000 Message: Group communication SSL configuration: group_replication_ssl_mode: "%s"

Error number: MY-011674; Symbol:

ER_GRP_RPL_UNABLE_TO_INIT_COMMUNICATION_ENGINE; SQLSTATE: HY000 Message: Unable to initialize the group communication engine

Error number: MY-011675; Symbol: ER_GRP_RPL_BINLOG_DISABLED; SQLSTATE: HY000 Message: Binlog must be enabled for Group Replication

Error number: MY-011676; Symbol: ER_GRP_RPL_GTID_MODE_OFF; SQLSTATE: HY000 Message: Gtid mode should be ON for Group Replication

Error number: MY-011677; Symbol: ER_GRP_RPL_LOG_SLAVE_UPDATES_NOT_SET; SQLSTATE: HY000

Message: LOG SLAVE UPDATES should be ON for Group Replication

Error number: MY-011677; Symbol: ER GRP RPL LOG REPLICA UPDATES NOT SET;

SQLSTATE: HY000

Message: LOG REPLICA UPDATES should be ON for Group Replication

Error number: MY-011678; Symbol:

ER GRP RPL INVALID TRANS WRITE SET EXTRACTION VALUE; SQLSTATE: HY000

Message: Extraction of transaction write sets requires an hash algorithm configuration. Please, double check that the parameter transaction-write-set-extraction is set to a valid algorithm.

Error number: MY-011679; Symbol:

ER GRP RPL RELAY LOG INFO REPO MUST BE TABLE; SQLSTATE: HY000

Message: Relay log info repository must be set to TABLE

Error number: MY-011680; Symbol: ER GRP RPL MASTER INFO REPO MUST BE TABLE;

SQLSTATE: HY000

Message: Master info repository must be set to TABLE.

Error number: MY-011681; Symbol:

ER_GRP_RPL_INCORRECT_TYPE_SET_FOR_PARALLEL_APPLIER; SQLSTATE: HY000 Message: In order to use parallel applier on Group Replication, parameter replica-parallel-type must be set to 'LOGICAL CLOCK'.

Error number: MY-011682; Symbol:

ER_GRP_RPL_SLAVE_PRESERVE_COMMIT_ORDER_NOT_SET; SQLSTATE: HY000 Message: Group Replication requires slave-preserve-commit-order to be set to ON when using more than 1 applier threads.

Error number: MY-011682; Symbol:

ER_GRP_RPL_REPLICA_PRESERVE_COMMIT_ORDER_NOT_SET; SQLSTATE: HY000 Message: Group Replication requires replica-preserve-commit-order to be set to ON when using more than 1 applier threads.

Error number: MY-011683; Symbol:

ER GRP RPL SINGLE PRIM MODE NOT ALLOWED WITH UPDATE EVERYWHERE;

SQLSTATE: HY000

Message: It is not allowed to run single primary mode with

'group replication enforce update everywhere checks' enabled.

Error number: MY-011684; Symbol: ER GRP RPL MODULE TERMINATE ERROR;

SQLSTATE: HY000

Message: error Message: %s

Error number: MY-011685; Symbol: ER GRP RPL GRP NAME OPTION MANDATORY;

SQLSTATE: HY000

Message: The group_replication_group_name option is mandatory

Error number: MY-011686; Symbol: ER GRP RPL GRP NAME IS TOO LONG; SQLSTATE:

HY000

Message: The group replication group name '%s' is not a valid UUID, its length is too big

Error number: MY-011687; Symbol: ER GRP RPL GRP NAME IS NOT VALID UUID;

SQLSTATE: HY000

Message: The group replication group name '%s' is not a valid UUID

Error number: MY-011688; Symbol:

ER_GRP_RPL_FLOW_CTRL_MIN_QUOTA_GREATER_THAN_MAX_QUOTA; SQLSTATE:

HY000

Message: group replication flow control min quota cannot be larger than

group replication flow control max quota

Error number: MY-011689; Symbol:

ER GRP RPL FLOW CTRL MIN RECOVERY QUOTA GREATER THAN MAX QUOTA;

SOLSTATE: HY000

Message: group replication flow control min recovery quota cannot be larger than

group replication flow control max quota

Error number: MY-011690; Symbol:

ER_GRP_RPL_FLOW_CTRL_MAX_QUOTA_SMALLER_THAN_MIN_QUOTAS; SQLSTATE:

HY000

Message: group replication flow control max quota cannot be smaller than

group replication flow control min quota or group replication flow control min recovery quota

Error number: MY-011691; Symbol: ER GRP RPL INVALID SSL RECOVERY STRING;

SOLSTATE: HY000

Message: The given value for recovery ssl option 'group replication %s' is invalid as its length is

beyond the limit

Error number: MY-011692; Symbol:

ER GRP RPL SUPPORTS ONLY ONE FORCE MEMBERS SET; SQLSTATE: HY000

Message: There is one group_replication_force_members operation already ongoing

Error number: MY-011693; Symbol:

ER_GRP_RPL_FORCE_MEMBERS_SET_UPDATE_NOT_ALLOWED; SQLSTATE: HY000 Message: group_replication_force_members can only be updated when Group Replication is running and a majority of the members are unreachable

Error number: MY-011694; Symbol:

ER GRP RPL GRP COMMUNICATION_INIT_WITH_CONF; SQLSTATE: HY000

Message: Initialized group communication with configuration: group_replication_group_name: '%s';

group_replication_local_address: '%s'; group_replication_group_seeds: '%s';

 $group_replication_bootstrap_group: \ '\%s'; \ group_replication_poll_spin_loops: \ \%lu;$

group_replication_compression_threshold: %lu; group_replication_ip_allowlist: '%s';

 $group_replication_communication_debug_options: \ '\%s'; \ group_replication_member_expel_timeout:$

'%lu'; group_replication_communication_max_Message_size: %lu;

group_replication_Message_cache_size: '%luu; group_replication_communication_stack: '%lu'

Error number: MY-011695; Symbol:

ER GRP RPL UNKNOWN GRP RPL APPLIER PIPELINE REQUESTED; SQLSTATE:

HY000

Message: Unknown group replication applier pipeline requested

Error number: MY-011696; Symbol:

ER GRP RPL FAILED TO BOOTSTRAP EVENT HANDLING INFRASTRUCTURE;

SOLSTATE: HY000

Message: Unable to bootstrap group replication event handling infrastructure. Unknown handler

type: %d

Error number: MY-011697; Symbol: ER_GRP_RPL_APPLIER_HANDLER_NOT_INITIALIZED;

SOLSTATE: HY000

Message: One of the group replication applier handlers is null due to an initialization error

Error number: MY-011698; Symbol: ER GRP RPL APPLIER HANDLER IS IN USE;

SQLSTATE: HY000

Message: A group replication applier handler, marked as unique, is already in use.

Error number: MY-011699; Symbol: ER GRP RPL APPLIER HANDLER ROLE IS IN USE;

SQLSTATE: HY000

Message: A group replication applier handler role, that was marked as unique, is already in use.

Error number: MY-011700; Symbol: ER GRP RPL FAILED TO INIT APPLIER HANDLER;

SQLSTATE: HY000

Message: Error on group replication applier handler initialization

Error number: MY-011701; Symbol:

 $ER_GRP_RPL_SQL_SERVICE_FAILED_TO_INIT_SESSION_THREAD; SQLSTATE: HY000$

Message: Error when initializing a session thread for internal server connection.

Error number: MY-011702; Symbol:

ER GRP RPL SQL SERVICE COMM SESSION NOT INITIALIZED; SQLSTATE: HY000

Message: Error running internal SQL query: %s. The internal server communication session is not

initialized

Error number: MY-011703; Symbol:

ER GRP RPL SQL SERVICE SERVER SESSION KILLED; SQLSTATE: HY000

Message: Error running internal SQL query: %s. The internal server session was killed or server is

shutting down.

Error number: MY-011704; Symbol:

ER GRP RPL SQL SERVICE FAILED TO RUN SQL QUERY; SQLSTATE: HY000

Message: Error running internal SQL query: %s. Got internal SQL error: %s(%d)

Error number: MY-011705; Symbol:

ER GRP RPL SQL SERVICE SERVER INTERNAL FAILURE; SQLSTATE: HY000

Message: Error running internal SQL query: %s. Internal failure.

Error number: MY-011706; Symbol:

ER GRP RPL SQL SERVICE RETRIES EXCEEDED ON SESSION STATE; SQLSTATE:

HY000

Message: Error, maximum number of retries exceeded when waiting for the internal server session

state to be operating

Error number: MY-011707; Symbol:

ER GRP RPL SQL SERVICE FAILED TO FETCH SECURITY CTX; SQLSTATE: HY000

Message: Error when trying to fetch security context when contacting the server for internal plugin

requests.

Error number: MY-011708; Symbol:

ER GRP RPL SQL SERVICE SERVER ACCESS DENIED FOR USER; SQLSTATE: HY000

Message: There was an error when trying to access the server with user: %s. Make sure the user is

present in the server and that the MySQL upgrade procedure was run correctly.

Error number: MY-011709; Symbol:

ER GRP RPL SQL SERVICE MAX CONN ERROR FROM SERVER; SQLSTATE: HY000

Message: Failed to establish an internal server connection to execute plugin operations since the server does not have available connections, please increase @@GLOBAL.MAX_CONNECTIONS. Server error: %i.

Error number: MY-011710; Symbol:

ER_GRP_RPL_SQL_SERVICE_SERVER_ERROR_ON_CONN; SQLSTATE: HY000 Message: Failed to establish an internal server connection to execute plugin operations. Server error: %i. Server error Message: %s

Error number: MY-011711; Symbol:

ER_GRP_RPL_UNREACHABLE_MAJORITY_TIMEOUT_FOR_MEMBER; SQLSTATE: HY000

Message: This member could not reach a majority of the members for more than %ld seconds. The member will now leave the group as instructed by the group replication unreachable majority timeout option.

Error number: MY-011712; Symbol:

ER_GRP_RPL_SERVER_SET_TO_READ_ONLY_DUE_TO_ERRORS; SQLSTATE: HY000 Message: The server was automatically set into read only mode after an error was detected.

Error number: MY-011713; Symbol:

ER_GRP_RPL_GMS_LISTENER_FAILED_TO_LOG_NOTIFICATION; SQLSTATE: HY000 Message: Unable to log notification to table (errno: %lu) (res: %d)! Message: %s

Error number: MY-011714; Symbol:

ER_GRP_RPL_GRP_COMMUNICATION_ENG_INIT_FAILED; SQLSTATE: HY000 Message: Failure in group communication engine '%s' initialization

Error number: MY-011715; Symbol:

ER_GRP_RPL_SET_GRP_COMMUNICATION_ENG_LOGGER_FAILED; SQLSTATE: HY000 Message: Unable to set the group communication engine logger

Error number: MY-011716; Symbol: ER_GRP_RPL_DEBUG_OPTIONS; SQLSTATE: HY000 Message: Current debug options are: '%s'.

Error number: MY-011717; Symbol: ER_GRP_RPL_INVALID_DEBUG_OPTIONS; SQLSTATE: HY000

Message: Some debug options in '%s' are not valid.

Error number: MY-011718; Symbol: ER_GRP_RPL_EXIT_GRP_GCS_ERROR; SQLSTATE: HY000

Message: Error calling group communication interfaces while trying to leave the group

Error number: MY-011719; Symbol: ER_GRP_RPL_GRP_MEMBER_OFFLINE; SQLSTATE: HY000

Message: Member is not ONLINE, it is not possible to force a new group membership

Error number: MY-011720; Symbol: ER_GRP_RPL_GCS_INTERFACE_ERROR; SQLSTATE: HY000

Message: Error calling group communication interfaces

Error number: MY-011721; Symbol: ER_GRP_RPL_FORCE_MEMBER_VALUE_SET_ERROR; SQLSTATE: HY000

Message: Error setting group_replication_force_members value '%s' on group communication interfaces

Error number: MY-011722; Symbol: ER_GRP_RPL_FORCE_MEMBER_VALUE_SET;

SQLSTATE: HY000

Message: The group_replication_force_members value '%s' was set in the group communication interfaces

Error number: MY-011723; Symbol: ER_GRP_RPL_FORCE_MEMBER_VALUE_TIME_OUT; SOLSTATE: HY000

Message: Timeout on wait for view after setting group_replication_force_members value '%s' into group communication interfaces

Error number: MY-011724; Symbol: ER_GRP_RPL_BROADCAST_COMMIT_MSSG_TOO_BIG; SOLSTATE: HY000

Message: Broadcast of committed transactions Message failed. Message is too big.

Error number: MY-011725; Symbol: ER_GRP_RPL_SEND_STATS_ERROR; SQLSTATE: HY000 Message: Error while sending stats Message

Error number: MY-011726; Symbol: ER_GRP_RPL_MEMBER_STATS_INFO; SQLSTATE: HY000

Message: Flow control - update member stats: %s stats certifier_queue %d, applier_queue %d certified %ld (%ld), applied %ld (%ld), local %ld (%ld), quota %ld (%ld) mode=%d

Error number: MY-011727; Symbol: ER_GRP_RPL_FLOW_CONTROL_STATS; SQLSTATE: HY000

Message: Flow control: throttling to %ld commits per %ld sec, with %d writing and %d non-recovering members, min capacity %lld, lim throttle %lld

Error number: MY-011728; Symbol:

ER GRP RPL UNABLE TO CONVERT PACKET TO EVENT; SQLSTATE: HY000

Message: Unable to convert a packet into an event on the applier. Error: %s

Error number: MY-011729; Symbol: ER GRP RPL PIPELINE CREATE FAILED; SQLSTATE:

HY000

Message: Failed to create group replication pipeline cache.

Error number: MY-011730; Symbol: ER GRP RPL PIPELINE REINIT FAILED WRITE;

SQLSTATE: HY000

Message: Failed to reinit group replication pipeline cache for write.

Error number: MY-011731; Symbol:

ER_GRP_RPL_UNABLE_TO_CONVERT_EVENT_TO_PACKET; SQLSTATE: HY000

Message: Unable to convert the event into a packet on the applier. Error: %s

Error number: MY-011732; Symbol: ER GRP RPL PIPELINE FLUSH FAIL; SQLSTATE:

HY000

Message: Failed to flush group replication pipeline cache.

Error number: MY-011733; Symbol: ER GRP RPL PIPELINE REINIT FAILED READ;

SQLSTATE: HY000

Message: Failed to reinit group replication pipeline cache for read.

Error number: MY-011734; Symbol: ER GRP RPL STOP REP CHANNEL; SQLSTATE:

HY000

Message: Error stopping all replication channels while server was leaving the group. Got error: %d.

Please check the error log for more details.

Error number: MY-011735; Symbol: ER GRP RPL GCS GR ERROR MSG; SQLSTATE:

HY000

Message: %s

Error number: MY-011736; Symbol: ER GRP RPL SLAVE IO THREAD UNBLOCKED;

SQLSTATE: HY000

Message: The slave IO thread of channel '%s' is unblocked as the member is declared ONLINE now.

Error number: MY-011737; Symbol: ER GRP RPL SLAVE IO THREAD ERROR OUT;

SQLSTATE: HY000

Message: The slave IO thread of channel '%s' will error out as the member failed to come ONLINE.

Error number: MY-011738; Symbol:

ER GRP RPL SLAVE APPLIER THREAD UNBLOCKED; SQLSTATE: HY000

Message: The slave applier thread of channel '%s' is unblocked as the member is declared ONLINE

now.

Error number: MY-011739; Symbol: ER_GRP_RPL_SLAVE_APPLIER_THREAD_ERROR_OUT;

SQLSTATE: HY000

Message: The slave applier thread of channel '%s' will error out as the member failed to come

ONLINE.

Error number: MY-011740; Symbol:

ER LDAP AUTH FAILED TO CREATE OR GET CONNECTION; SQLSTATE: HY000

Message: LDAP authentication initialize: failed to create/ get connection from the pool.

Error number: MY-011741; Symbol: ER LDAP AUTH DEINIT FAILED; SQLSTATE: HY000

Message: LDAP authentication de initialize Failed

Error number: MY-011742; Symbol: ER LDAP AUTH SKIPPING USER GROUP SEARCH;

SQLSTATE: HY000

Message: Skipping group search, No group attribute mentioned

Error number: MY-011743; Symbol: ER_LDAP_AUTH_POOL_DISABLE_MAX_SIZE_ZERO;

SOLSTATE: HY000

Message: Pool max size is 0, connection pool is disabled

Error number: MY-011744; Symbol:

ER LDAP AUTH FAILED TO CREATE LDAP OBJECT CREATOR; SQLSTATE: HY000

Message: Connection pool initialization, failed to create LDAP object creator

Error number: MY-011745; Symbol: ER LDAP AUTH FAILED TO CREATE LDAP OBJECT;

SQLSTATE: HY000

Message: Connection pool initialization, failed to create LDAP object

Error number: MY-011746; Symbol: ER LDAP AUTH TLS CONF; SQLSTATE: HY000

Message: LDAP TLS configuration

Error number: MY-011747; Symbol: ER LDAP AUTH TLS CONNECTION; SQLSTATE:

HY000

Message: LDAP TLS connection

Error number: MY-011748; Symbol: ER LDAP AUTH CONN POOL NOT CREATED;

SQLSTATE: HY000

Message: LDAP pool is not created.

Error number: MY-011749; Symbol: ER LDAP AUTH CONN POOL INITIALIZING;

SQLSTATE: HY000

Message: LDAP pool is initializing

Error number: MY-011750; Symbol: ER LDAP AUTH CONN POOL DEINITIALIZING;

SQLSTATE: HY000

Message: LDAP pool is de-initializing

Error number: MY-011751; Symbol:

ER LDAP AUTH ZERO MAX POOL SIZE UNCHANGED; SQLSTATE: HY000

Message: Pool max size old and new values are 0

Error number: MY-011752; Symbol: ER LDAP AUTH POOL REINITIALIZING; SQLSTATE:

HY000

Message: LDAP pool is re-initializing

Error number: MY-011753; Symbol: ER LDAP AUTH FAILED TO WRITE PACKET;

SQLSTATE: HY000

Message: Plug-in has failed to write the packet.

Error number: MY-011754; Symbol: ER LDAP AUTH SETTING USERNAME; SQLSTATE:

HY000

Message: Setting LDAP user name as: %s

Error number: MY-011755; Symbol: ER LDAP AUTH USER AUTH DATA; SQLSTATE:

HY000

Message: User authentication data: %s size: %lu

Error number: MY-011756; Symbol: ER LDAP AUTH INFO FOR USER; SQLSTATE: HY000

Message: User is authenticated as: %s external user: %s

Error number: MY-011757; Symbol: ER LDAP AUTH USER GROUP SEARCH INFO;

SQLSTATE: HY000

Message: Group search information base DN: %s scope: %d filter: %s attribute: %s

Error number: MY-011758; Symbol: ER LDAP AUTH GRP SEARCH SPECIAL HDL;

SQLSTATE: HY000

Message: Special handling for group search, {GA} found

Error number: MY-011759; Symbol: ER LDAP AUTH GRP IS FULL DN; SQLSTATE: HY000

Message: Group search special handling, group full DN found.

Error number: MY-011760; Symbol: ER LDAP AUTH USER NOT FOUND IN ANY GRP;

SQLSTATE: HY000

Message: User %s is not member of any group.

Error number: MY-011761; Symbol: ER LDAP AUTH USER FOUND IN MANY GRPS;

SQLSTATE: HY000

Message: User %s is member of more than one group

Error number: MY-011762; Symbol: ER LDAP AUTH USER HAS MULTIPLE GRP NAMES;

SQLSTATE: HY000

Message: For user %s has multiple user group names. Please check if group attribute name is correct

Error number: MY-011763; Symbol: ER LDAP AUTH SEARCHED USER GRP NAME;

SQLSTATE: HY000

Message: Searched group name: %s

Error number: MY-011764; Symbol: ER LDAP AUTH OBJECT CREATE TIMESTAMP;

SQLSTATE: HY000

Message: LDAP authentication object creation time stamp: %s dn: %s

Error number: MY-011765; Symbol: ER LDAP AUTH CERTIFICATE NAME; SQLSTATE:

HY000

Message: Certificate name: %s

Error number: MY-011766; Symbol: ER LDAP AUTH FAILED TO POOL DEINIT;

SOLSTATE: HY000

Message: Failed to pool de-initialized: pool is already reconstructing

Error number: MY-011767; Symbol:

ER LDAP AUTH FAILED TO INITIALIZE POOL IN RECONSTRUCTING; SQLSTATE:

HY000

Message: Pool initialization failed: pool is already initialized

Error number: MY-011768; Symbol:

ER LDAP AUTH FAILED TO INITIALIZE POOL IN INIT STATE; SQLSTATE: HY000

Message: Pool initialization failed: pool is initializing

Error number: MY-011769; Symbol:

ER LDAP AUTH FAILED TO INITIALIZE POOL IN DEINIT STATE; SQLSTATE: HY000

Message: Pool initialization failed: pool is de-initializing

Error number: MY-011770; Symbol:

ER LDAP AUTH FAILED TO DEINITIALIZE POOL IN RECONSTRUCT STATE;

SQLSTATE: HY000

Message: Failed to pool deinitialized: pool is already reconstructing

Error number: MY-011771; Symbol:

ER LDAP AUTH FAILED TO DEINITIALIZE NOT READY POOL; SQLSTATE: HY000

Message: Failed to pool deinitialized: pool is not ready

Error number: MY-011772; Symbol:

ER LDAP AUTH FAILED TO GET CONNECTION AS PLUGIN NOT READY;

SQLSTATE: HY000

Message: Ldap connection pool::get: Failed to return connection as plug-in is not

ready/initializing/de-initializing

Error number: MY-011773; Symbol: ER LDAP AUTH CONNECTION POOL INIT FAILED;

SQLSTATE: HY000

Message: Connection pool has failed to initialized

Error number: MY-011774; Symbol:

ER_LDAP_AUTH_MAX_ALLOWED_CONNECTION_LIMIT_HIT; SQLSTATE: HY000

Message: Ldap connetion pool::get LDAP maximum connection allowed size is reached. Increase

the maximum limit.

Error number: MY-011775; Symbol: ER LDAP AUTH MAX POOL SIZE SET FAILED;

SQLSTATE: HY000

Message: Set max pool size failed.

Error number: MY-011776; Symbol:

ER LDAP AUTH PLUGIN FAILED TO READ PACKET; SQLSTATE: HY000

Message: Plug-in has failed to read the packet from client

Error number: MY-011777; Symbol: ER LDAP AUTH CREATING LDAP CONNECTION;

SQLSTATE: HY000

Message: Ldap authentication::initialize: creating new LDAP connection.

Error number: MY-011778; Symbol:

ER LDAP AUTH GETTING CONNECTION FROM POOL; SQLSTATE: HY000

Message: Ldap_authentication::initialize: getting connection from pool.

Error number: MY-011779; Symbol:

ER LDAP AUTH RETURNING CONNECTION TO POOL; SQLSTATE: HY000

Message: Ldap authentication::de initialize putting back connection in the pool

Error number: MY-011780; Symbol:

ER LDAP AUTH SEARCH USER GROUP ATTR NOT FOUND; SQLSTATE: HY000

Message: Ldap authentication::search user group no group attribute found

Error number: MY-011781; Symbol: ER LDAP AUTH LDAP INFO NULL; SQLSTATE:

HY000

Message: Ldap connetion pool::put ldap info null

Error number: MY-011782; Symbol: ER LDAP AUTH FREEING CONNECTION; SQLSTATE:

HY000

Message: Ldap connection pool::put connection is freeing.

Error number: MY-011783; Symbol: ER LDAP AUTH CONNECTION PUSHED TO POOL;

SQLSTATE: HY000

Message: Ldap connection pool::put connection in pushed in the pool

Error number: MY-011784; Symbol: ER LDAP AUTH CONNECTION CREATOR ENTER;

SQLSTATE: HY000

Message: Ldap connection creator::Ldap connection creator

Error number: MY-011785; Symbol: ER LDAP AUTH STARTING TLS; SQLSTATE: HY000

Message: starting TLS

Error number: MY-011786; Symbol:

ER LDAP AUTH CONNECTION GET LDAP INFO NULL; SQLSTATE: HY000

Message: Ldap connection pool::get: (ldap info == NULL)|| (*ldap info)

Error number: MY-011787; Symbol: ER LDAP AUTH DELETING CONNECTION KEY;

SQLSTATE: HY000

Message: Ldap connection pool::deinit: deleting connection key %s

Error number: MY-011788; Symbol: ER LDAP AUTH POOLED CONNECTION KEY;

SQLSTATE: HY000

Message: Ldap connection pool::get pooled connection key: %s

Error number: MY-011789; Symbol: ER LDAP AUTH CREATE CONNECTION KEY;

SOLSTATE: HY000

Message: Ldap connection pool::get create connection key: %s

Error number: MY-011790; Symbol: ER LDAP AUTH COMMUNICATION HOST INFO;

SQLSTATE: HY000

Message: LDAP communication host %s port %u

Error number: MY-011791; Symbol: ER LDAP AUTH METHOD TO CLIENT; SQLSTATE:

HY000

Message: Sending authentication method to client: %s

Error number: MY-011792; Symbol: ER LDAP AUTH SASL REQUEST FROM CLIENT;

SQLSTATE: HY000

Message: SASL request received from mysql client: %s

Error number: MY-011793; Symbol: ER LDAP AUTH SASL PROCESS SASL; SQLSTATE:

HY000

Message: Ldap sasl authentication::process sasl rc: %s

Error number: MY-011794; Symbol: ER_LDAP_AUTH_SASL_BIND_SUCCESS_INFO;

SQLSTATE: HY000

Message: Ldap sasl authentication::process sasl sasl bind succeed. dn: %s method: %s server

credential: %s

Error number: MY-011795; Symbol: ER LDAP AUTH STARTED FOR USER; SQLSTATE:

HY000

Message: LDAP authentication started for user name: %s

Error number: MY-011796; Symbol: ER LDAP AUTH DISTINGUISHED NAME; SQLSTATE:

HY000

Message: %s

Error number: MY-011797; Symbol: ER LDAP AUTH INIT FAILED; SQLSTATE: HY000

Message: LDAP authentication initialize is failed with: %s

Error number: MY-011798; Symbol: ER LDAP AUTH OR GROUP RETRIEVAL FAILED;

SQLSTATE: HY000

Message: LDAP authentication failed or group retrieval failed: %s

Error number: MY-011799; Symbol: ER LDAP AUTH USER GROUP SEARCH FAILED;

SQLSTATE: HY000

Message: Search user group has failed: %s

Error number: MY-011800; Symbol: ER LDAP AUTH USER BIND FAILED; SQLSTATE:

HY000

Message: LDAP user bind has failed: %s

Error number: MY-011801; Symbol:

ER LDAP AUTH POOL GET FAILED TO CREATE CONNECTION; SQLSTATE: HY000

Message: Connection pool get: Failed to create LDAP connection. %s

Error number: MY-011802; Symbol:

ER LDAP AUTH FAILED TO CREATE LDAP CONNECTION; SQLSTATE: HY000

Message: Failed to create new LDAP connection: %s

Error number: MY-011803; Symbol:

ER_LDAP_AUTH_FAILED_TO_ESTABLISH_TLS_CONNECTION; SQLSTATE: HY000

Message: Failed to establish TLS connection: %s

Error number: MY-011804; Symbol: ER LDAP AUTH FAILED TO SEARCH DN;

SQLSTATE: HY000

Message: Failed to search user full dn: %s

Error number: MY-011805; Symbol: ER LDAP AUTH CONNECTION POOL REINIT ENTER;

SQLSTATE: HY000

Message: Ldap connection pool::reinit

Error number: MY-011806; Symbol: ER SYSTEMD NOTIFY PATH TOO LONG; SQLSTATE:

HY000

Message: The path '%s', from the NOTIFY_SOCKET environment variable, is too long. At %u bytes

it exceeds the limit of %u bytes for an AF_UNIX socket.

Error number: MY-011807; Symbol: ER SYSTEMD NOTIFY CONNECT FAILED;

SQLSTATE: HY000

Message: Failed to connect to systemd notification socket named %s. Error: '%s'

Error number: MY-011808; Symbol: ER SYSTEMD NOTIFY WRITE FAILED; SQLSTATE:

HY000

Message: Failed to write '%s' to systemd notification. Error: '%s'

Error number: MY-011809; Symbol: ER_FOUND_MISSING_GTIDS; SQLSTATE: HY000 Message: Cannot replicate to server with server_uuid='%s' because the present server has purged required binary logs. The connecting server needs to replicate the missing transactions from elsewhere, or be replaced by a new server created from a more recent backup. To prevent this error in the future, consider increasing the binary log expiration period on the present server. %s.

Error number: MY-011810; Symbol: ER PID FILE PRIV DIRECTORY INSECURE;

SQLSTATE: HY000

Message: Insecure configuration for --pid-file: Location '%s' in the path is accessible to all OS users.

Consider choosing a different directory.

Error number: MY-011811; Symbol: ER CANT CHECK PID PATH; SQLSTATE: HY000

Message: Can't start server: can't check PID filepath: %s

Error number: MY-011812; Symbol:

ER VALIDATE PWD STATUS VAR REGISTRATION FAILED; SQLSTATE: HY000

Message: validate password status variables registration failed.

Error number: MY-011813; Symbol:

ER VALIDATE PWD STATUS VAR UNREGISTRATION FAILED; SQLSTATE: HY000

Message: validate password status variables unregistration failed.

Error number: MY-011814; Symbol: ER VALIDATE PWD DICT FILE OPEN FAILED;

SQLSTATE: HY000

Message: Dictionary file open failed

Error number: MY-011815; Symbol: ER VALIDATE PWD COULD BE NULL; SQLSTATE:

HY000

Message: given password string could be null

Error number: MY-011816; Symbol:

ER VALIDATE PWD STRING CONV TO LOWERCASE FAILED; SQLSTATE: HY000

Message: failed to convert the password string to lower case

Error number: MY-011817; Symbol:

ER VALIDATE_PWD_STRING_CONV_TO_BUFFER_FAILED; SQLSTATE: HY000

Message: failed to convert the password string into a buffer

Error number: MY-011818; Symbol:

ER VALIDATE PWD STRING HANDLER MEM ALLOCATION FAILED; SQLSTATE:

HY000

Message: memory allocation failed for string handler

Error number: MY-011819; Symbol:

ER VALIDATE PWD STRONG POLICY DICT FILE UNSPECIFIED; SQLSTATE: HY000

Message: Since the validate password policy is mentioned as Strong, dictionary file must be

specified

Error number: MY-011820; Symbol: ER VALIDATE PWD CONVERT TO BUFFER FAILED;

SQLSTATE: HY000

Message: convert to buffer service failed

Error number: MY-011821; Symbol:

ER VALIDATE PWD VARIABLE REGISTRATION FAILED; SQLSTATE: HY000

Message: %s variable registration failed.

Error number: MY-011822; Symbol:

ER VALIDATE PWD VARIABLE UNREGISTRATION FAILED; SQLSTATE: HY000

Message: %s variable unregistration failed.

Error number: MY-011823; Symbol: ER KEYRING MIGRATION EXTRA OPTIONS;

SQLSTATE: HY000

Message: Please specify options specific to keyring migration. Any additional options can be ignored. NOTE: Although some options are valid, migration tool can still report error example:

plugin variables for which plugin is not loaded yet.

Error number: MY-011879; Symbol: ER_IB_MSG_54; SQLSTATE: HY000

Message: Failed to set NUMA memory policy of buffer pool page frames with

mbind(%p,%zu,%s,...,..%s) failed with %s

Error number: MY-011974; Symbol: ER IB CLONE INTERNAL; SQLSTATE: HY000

Message: %s

Error number: MY-011975; Symbol: ER IB CLONE TIMEOUT; SQLSTATE: HY000

Message: %s

Error number: MY-011976; Symbol: ER IB CLONE STATUS FILE; SQLSTATE: HY000

Message: %s

Error number: MY-011977; Symbol: ER IB CLONE SQL; SQLSTATE: HY000

Message: %s

Error number: MY-011978; Symbol: ER IB CLONE VALIDATE; SQLSTATE: HY000

Message: %s

Error number: MY-011979; Symbol: ER IB CLONE PUNCH HOLE; SQLSTATE: HY000

Message: %s

Error number: MY-011980; Symbol: ER IB CLONE GTID PERSIST; SQLSTATE: HY000

Message: %s

Error number: MY-012097; Symbol: ER IB MSG 272; SQLSTATE: HY000

Message: Table flags are 0x%lx in the data dictionary but the flags in file %s are 0x%llx!

Error number: MY-012098; Symbol: ER_IB_MSG_273; SQLSTATE: HY000

Message: Can't read encryption key from file %s!

Error number: MY-012099; Symbol: ER IB MSG 274; SQLSTATE: HY000

Message: Cannot close file %s, because n_pending_flushes %zu

Error number: MY-012100; Symbol: ER IB MSG 275; SQLSTATE: HY000

Message: Cannot close file %s, because modification count %lld != flush count %lld

Error number: MY-012101; Symbol: ER IB MSG 276; SQLSTATE: HY000

Message: Cannot close file %s, because it is in use

Error number: MY-012102; Symbol: ER IB MSG 277; SQLSTATE: HY000

Message: Open file list len in shard %zu is %llu

Error number: MY-012103; Symbol: ER IB MSG 278; SQLSTATE: HY000

Message: Tablespace %s, waiting for IO to stop for %lld seconds

Error number: MY-012109; Symbol: ER IB MSG 284; SQLSTATE: HY000

Message: You must raise the value of innodb_open_files in my.cnf! Remember that InnoDB keeps all redo log files and all system tablespace files open for the whole time mysqld is running, and needs to open also some .ibd files if the file-per-table storage model is used. Current open files %zu, max allowed open files %zu.

Error number: MY-012110; Symbol: ER IB MSG 285; SQLSTATE: HY000

Message: Max tablespace id is too high, %lu

Error number: MY-012111; Symbol: ER_IB_MSG_286; SQLSTATE: HY000

Message: Trying to access missing tablespace %lu

Error number: MY-012111; Symbol: ER IB WARN ACCESSING NONEXISTINC SPACE;

SQLSTATE: HY000

Message: Trying to access missing tablespace %lu

Error number: MY-012112; Symbol: ER IB MSG 287; SQLSTATE: HY000

Message: Trying to close/delete tablespace '%s' but there are %lu pending operations on it.

Error number: MY-012113; Symbol: ER IB MSG 288; SQLSTATE: HY000

Message: Trying to delete/close tablespace '%s' but there are %lu flushes and %zu pending I/O's on it.

Error number: MY-012115; Symbol: ER IB MSG 290; SQLSTATE: HY000

Message: Cannot delete tablespace %lu because it is not found in the tablespace memory cache.

Error number: MY-012116; Symbol: ER IB MSG 291; SQLSTATE: HY000

Message: While deleting tablespace %lu in DISCARD TABLESPACE. File rename/delete

failed: %s

Error number: MY-012117; Symbol: ER_IB_MSG_292; SQLSTATE: HY000 Message: Cannot delete tablespace %lu in DISCARD TABLESPACE: %s

Error number: MY-012118; Symbol: ER IB MSG 293; SQLSTATE: HY000

Message: Cannot rename '%s' to '%s' for space ID %lu because the source file does not exist.

Error number: MY-012119; Symbol: ER_IB_MSG_294; SQLSTATE: HY000

Message: Cannot rename '%s' to '%s' for space ID %lu because the target file exists. Remove the target file and try again.

Error number: MY-012120; Symbol: ER IB MSG 295; SQLSTATE: HY000

Message: Cannot rename file '%s' (space id %lu) retried %llu times. There are either pending IOs or

flushes or the file is being extended.

Error number: MY-012121; Symbol: ER IB MSG 296; SQLSTATE: HY000

Message: Cannot find space id %lu in the tablespace memory cache, though the file '%s' in a rename

operation should have that ID.

Error number: MY-012122; Symbol: ER IB MSG 297; SQLSTATE: HY000

Message: Rename waiting for IO to resume

Error number: MY-012123; Symbol: ER IB MSG 298; SQLSTATE: HY000

Message: Cannot find tablespace for '%s' in the tablespace memory cache

Error number: MY-012124; Symbol: ER IB MSG 299; SQLSTATE: HY000

Message: Cannot find tablespace for '%s' in the tablespace memory cache

Error number: MY-012125; Symbol: ER IB MSG 300; SQLSTATE: HY000

Message: Tablespace '%s' is already in the tablespace memory cache

Error number: MY-012126; Symbol: ER IB MSG 301; SQLSTATE: HY000

Message: Cannot create file '%s'

Error number: MY-012127; Symbol: ER IB MSG 302; SQLSTATE: HY000

Message: The file '%s' already exists though the corresponding table did not exist. Have you moved InnoDB .ibd files around without using the SQL commands DISCARD TABLESPACE and IMPORT TABLESPACE, or did mysqld crash in the middle of CREATE TABLE? You can resolve the problem by removing the file '%s' under the 'datadir' of MySQL.

Error number: MY-012127; Symbol: ER_IB_MSG_UNEXPECTED_FILE_EXISTS; SQLSTATE: HY000

Message: The file '%s' already exists though the corresponding table did not exist. Have you moved InnoDB .ibd files around without using the SQL commands DISCARD TABLESPACE and IMPORT TABLESPACE, or did mysqld crash in the middle of CREATE TABLE? You can resolve the problem by removing the file '%s' under the 'datadir' of MySQL.

Error number: MY-012128; Symbol: ER IB MSG 303; SQLSTATE: HY000

Message: posix_fallocate(): Failed to preallocate data for file %s, desired size %llu Operating system Error number %d - %s. Check that the disk is not full or a disk quota exceeded. Make sure the file system supports this function. Refer to your operating system documentation for operating system error code information.

Error number: MY-012129; Symbol: ER IB MSG 304; SQLSTATE: HY000

Message: Could not write the first page to tablespace '%s'

Error number: MY-012130; Symbol: ER IB MSG 305; SQLSTATE: HY000

Message: File flush of tablespace '%s' failed

Error number: MY-012131; Symbol: ER_IB_MSG_306; SQLSTATE: HY000

Message: Could not find a valid tablespace file for '%s'. %s

Error number: MY-012132; Symbol: ER IB MSG 307; SQLSTATE: HY000

Message: Ignoring data file '%s' with space ID %lu. Another data file called '%s' exists with the same

space ID

Error number: MY-012137; Symbol: ER_IB_MSG 312; SQLSTATE: HY000

Message: Can't set encryption information for tablespace %s!

Error number: MY-012177; Symbol: ER IB MSG UNPROTECTED LOCATION ALLOWED;

SQLSTATE: HY000

Message: The datafile '%s' for tablespace %s is in an unprotected location. This file cannot be

recovered after a crash until this location is added to innodb directories.

Error number: MY-012191; Symbol: ER_IB_MSG_IGNORE_SCAN_PATH; SQLSTATE: HY000 Message: Scan path '%s' is ignored because %s

Error number: MY-012213; Symbol: ER IB MSG GENERAL TABLESPACE UNDER DATADIR; SQLSTATE: HY000

Message: A general tablespace cannot be located under the datadir. Cannot open file '%s'.

Error number: MY-012214; Symbol: ER IB MSG IMPLICIT TABLESPACE IN DATADIR;

SQLSTATE: HY000

Message: A file-per-table tablespace cannot be located in the datadir. Cannot open file '%s'.

Error number: MY-012390; Symbol: ER IB MSG INVALID LOCATION FOR TABLE;

SQLSTATE: HY000

Message: Cannot create a tablespace for table %s because the directory is not a valid location. %s

Error number: MY-012489; Symbol: ER IB MSG 664; SQLSTATE: HY000

Message: The transaction log size is too large for innodb_log_buffer_size (%lu >= %lu / 2). Trying

to extend it.

Error number: MY-012490; Symbol: ER_IB_MSG_665; SQLSTATE: HY000

Message: innodb_log_buffer_size was extended to %lu bytes.

Error number: MY-012491; Symbol: ER IB MSG 666; SQLSTATE: HY000

Message: The transaction log files are too small for the single transaction log (size=%lu). So, the last

checkpoint age might exceed the log group capacity %llu.

Error number: MY-012492; Symbol: ER IB MSG 667; SQLSTATE: HY000

Message: The age of the last checkpoint is %llu, which exceeds the log group capacity %llu.

Error number: MY-012493; Symbol: ER IB MSG 668; SQLSTATE: HY000

Message: Cannot continue operation. ib_logfiles are too small for innodb_thread_concurrency %lu.

The combined size of ib_logfiles should be bigger than 200 kB * innodb_thread_concurrency. To get mysqld to start up, set innodb thread concurrency in my.cnf to a lower value, for example, to 8.

After an ERROR-FREE shutdown of mysqld you can adjust the size of ib logfiles. %s

Error number: MY-012494; Symbol: ER IB MSG 669; SQLSTATE: HY000

Message: Redo log was encrypted, but keyring plugin is not loaded.

Error number: MY-012495; Symbol: ER IB MSG 670; SQLSTATE: HY000

Message: Read redo log encryption metadata successful.

Error number: MY-012496; Symbol: ER IB MSG 671; SQLSTATE: HY000

Message: Can't set redo log tablespace encryption metadata.

Error number: MY-012497; Symbol: ER_IB_MSG_672; SQLSTATE: HY000

Message: Cannot read the encryption information in log file header, please check if keyring plugin loaded and the key file exists.

Error number: MY-012498; Symbol: ER_IB_MSG_673; SQLSTATE: HY000 Message: Can't set redo log tablespace to be encrypted in read-only mode.

Error number: MY-012499; Symbol: ER_IB_MSG_674; SQLSTATE: HY000 Message: Can't set redo log tablespace to be encrypted.

Error number: MY-012500; Symbol: ER_IB_MSG_675; SQLSTATE: HY000 Message: Can't set redo log tablespace to be encrypted.

Error number: MY-012501; Symbol: ER_IB_MSG_676; SQLSTATE: HY000 Message: Redo log encryption is enabled.

Error number: MY-012502; Symbol: ER_IB_MSG_677; SQLSTATE: HY000 Message: Flush Waiting for archiver to to catch up lag LSN: %llu

Error number: MY-012503; Symbol: ER_IB_MSG_678; SQLSTATE: HY000 Message: Flush overwriting data to archive - wait too long (1 minute) lag LSN: %llu

Error number: MY-012505; Symbol: ER_IB_MSG_680; SQLSTATE: HY000 Message: Starting shutdown...

Error number: MY-012506; Symbol: ER_IB_MSG_681; SQLSTATE: HY000 Message: Waiting for %s to exit

Error number: MY-012507; Symbol: ER_IB_MSG_682; SQLSTATE: HY000 Message: Waiting for %lu active transactions to finish

Error number: MY-012508; Symbol: ER_IB_MSG_683; SQLSTATE: HY000 Message: Waiting for master thread to be suspended

Error number: MY-012509; Symbol: ER_IB_MSG_684; SQLSTATE: HY000 Message: Waiting for page cleaner to finish flushing of buffer pool

Error number: MY-012510; Symbol: ER_IB_MSG_685; SQLSTATE: HY000 Message: Pending checkpoint_writes: %lu. Pending log flush writes: %lu.

Error number: MY-012511; Symbol: ER IB MSG 686; SQLSTATE: HY000

Message: Waiting for %lu buffer page I/Os to complete

Error number: MY-012512; Symbol: ER IB MSG 687; SQLSTATE: HY000

Message: MySQL has requested a very fast shutdown without flushing the InnoDB buffer pool to

data files. At the next mysqld startup InnoDB will do a crash recovery!

Error number: MY-012513; Symbol: ER IB MSG 688; SQLSTATE: HY000

Message: Background thread %s woke up during shutdown

Error number: MY-012514; Symbol: ER IB MSG 689; SQLSTATE: HY000

Message: Waiting for archiver to finish archiving page and log

Error number: MY-012515; Symbol: ER_IB_MSG_690; SQLSTATE: HY000

Message: Background thread %s woke up during shutdown

Error number: MY-012516; Symbol: ER_IB_MSG_691; SQLSTATE: HY000

Message: Waiting for dirty buffer pages to be flushed

Error number: MY-012517; Symbol: ER_IB_MSG_692; SQLSTATE: HY000 Message: Log sequence number at shutdown %llu is lower than at startup %llu!

Error number: MY-012518; Symbol: ER_IB_MSG_693; SQLSTATE: HY000

Message: Waiting for archiver to finish archiving page and log

Error number: MY-012519; Symbol: ER IB MSG 694; SQLSTATE: HY000

Error number: MY-012520; Symbol: ER IB MSG 695; SQLSTATE: HY000

Message: Log record type %d, page %lu:%lu. Log parsing proceeded successfully up to %llu.

Previous log record type %d, is multi %llu Recv offset %zd, prev %llu

Error number: MY-012521; Symbol: ER IB MSG 696; SQLSTATE: HY000

Message: Hex dump starting %llu bytes before and ending %llu bytes after the corrupted record:

Error number: MY-012522; Symbol: ER IB MSG 697; SQLSTATE: HY000

Message: Set innodb force recovery to ignore this error.

Error number: MY-012523; Symbol: ER IB MSG 698; SQLSTATE: HY000

Message: The log file may have been corrupt and it is possible that the log scan did not proceed far enough in recovery! Please run CHECK TABLE on your InnoDB tables to check that they are ok! If mysqld crashes after this recovery; %s

Error number: MY-012523; Symbol: ER_IB_MSG_LOG_CORRUPT; SQLSTATE: HY000 Message: The redo log file may have been corrupt and it is possible that the log scan did not proceed far enough in recovery! Please run CHECK TABLE on your InnoDB tables to check that they are ok! If mysqld crashes after this recovery; %s

Error number: MY-012524; Symbol: ER IB MSG 699; SQLSTATE: HY000

Message: %llu pages with log records were left unprocessed!

Error number: MY-012525; Symbol:

ER IB MSG LOG FORMAT OLD AND LOG CORRUPTED; SQLSTATE: HY000

Message: Upgrade after a crash is not supported. This redo log was created with %s, and it appears

corrupted. Please follow the instructions at %s

Error number: MY-012526; Symbol:

ER_IB_MSG_LOG_FORMAT_OLD_AND_NO_CLEAN_SHUTDOWN; SQLSTATE: HY000 Message: Upgrade is not supported after a crash or shutdown with innodb_fast_shutdown = 2. This redo log was created with %s, and it appears logically non empty. Please follow the instructions at %s

Error number: MY-012527; Symbol: ER IB MSG 702; SQLSTATE: HY000

Message: Invalid redo log header checksum.

Error number: MY-012528; Symbol: ER IB MSG 703; SQLSTATE: HY000

Message: Unsupported redo log format (%lu). The redo log was created before MySQL 5.7.9

Error number: MY-012529; Symbol: ER_IB_MSG_704; SQLSTATE: HY000 Message: Redo log format is v%lu. The redo log was created before MySQL 8.0.3.

Error number: MY-012529; Symbol: ER IB MSG LOG FORMAT BEFORE 8 0 30;

SQLSTATE: HY000

Message: Redo log format is v%lu. The redo log was created before MySQL 8.0.30.

Error number: MY-012530; Symbol: ER IB MSG 705; SQLSTATE: HY000

Message: Unknown redo log format (%lu). Please follow the instructions at %s upgrading-

downgrading.html.

Error number: MY-012530; Symbol: ER IB MSG LOG FILE FORMAT UNKNOWN;

SQLSTATE: HY000

Message: Unknown redo log format (v%lu) in file %s. Please follow the instructions at %s

Error number: MY-012531; Symbol: ER IB MSG 706; SQLSTATE: HY000

Message: No valid checkpoint found (corrupted redo log). You can try --innodb-force-recovery=6 as a last resort.

Error number: MY-012531; Symbol: ER IB MSG RECOVERY CHECKPOINT NOT FOUND;

SQLSTATE: HY000

Message: No valid checkpoint found (corrupted redo log). You can try --innodb-force-recovery=6 as

a last resort.

Error number: MY-012532; Symbol: ER IB MSG 707; SQLSTATE: HY000

Message: Applying a batch of %llu redo log records ...

Error number: MY-012535; Symbol: ER IB MSG 710; SQLSTATE: HY000

Message: Apply batch completed!

Error number: MY-012542; Symbol: ER IB MSG 717; SQLSTATE: HY000

Message: An optimized(without redo logging) DDL operation has been performed. All modified

pages may not have been flushed to the disk yet. This offline backup may not be consistent

Error number: MY-012543; Symbol: ER_IB_MSG_718; SQLSTATE: HY000

Message: Extending tablespace: %lu space name: %s to new size: %lu pages during recovery.

Error number: MY-012544; Symbol: ER IB MSG 719; SQLSTATE: HY000

Message: Could not extend tablespace: %lu space name: %s to new size: %lu pages during recovery.

Error number: MY-012545; Symbol: ER IB MSG 720; SQLSTATE: HY000

Message: Log block %lu at lsn %llu has valid header, but checksum field contains %lu, should

be %lu.

Error number: MY-012546; Symbol: ER IB MSG 721; SQLSTATE: HY000

Message: Recovery skipped, --innodb-read-only set!

Error number: MY-012546; Symbol:

ER IB MSG RECOVERY SKIPPED IN READ ONLY MODE; SQLSTATE: HY000

Message: Recovery skipped, --innodb-read-only set!

Error number: MY-012547; Symbol: ER IB MSG 722; SQLSTATE: HY000

Message: Log scan progressed past the checkpoint LSN %llu.

Error number: MY-012548; Symbol: ER IB MSG 723; SQLSTATE: HY000

Message: Log parsing buffer overflow. Recovery may have failed! Please set log_buffer_size to a

value higher than %lu.

Error number: MY-012549; Symbol: ER IB MSG 724; SQLSTATE: HY000

Message: Set innodb force recovery to ignore this error.

Error number: MY-012550; Symbol: ER IB MSG 725; SQLSTATE: HY000

Message: Doing recovery: scanned up to log sequence number %llu

Error number: MY-012551; Symbol: ER IB MSG 726; SQLSTATE: HY000

Message: Database was not shutdown normally!

Error number: MY-012552; Symbol: ER IB MSG 727; SQLSTATE: HY000

Message: Starting crash recovery.

Error number: MY-012553; Symbol: ER_IB_MSG_728; SQLSTATE: HY000 Message: The user has set SRV FORCE NO LOG REDO on, skipping log redo

Error number: MY-012554; Symbol: ER_IB_MSG_729; SQLSTATE: HY000 Message: Cannot restore from mysqlbackup, InnoDB running in read-only mode!

Error number: MY-012554; Symbol:

ER IB MSG LOG FILES CREATED BY MEB AND READ ONLY MODE; SQLSTATE:

HY000

Message: Cannot restore from mysqlbackup, InnoDB running in read-only mode!

Error number: MY-012555; Symbol: ER IB MSG 730; SQLSTATE: HY000

Message: The log file was created by mysqlbackup --apply-log at %s. The following crash recovery is part of a normal restore.

Error number: MY-012555; Symbol: ER IB MSG LOG FILES CREATED BY MEB;

SOLSTATE: HY000

Message: The redo log file was created by mysqlbackup --apply-log at %s. The following crash

recovery is part of a normal restore.

Error number: MY-012556; Symbol: ER_IB_MSG_731; SQLSTATE: HY000

Message: Opening cloned database

Error number: MY-012556; Symbol: ER IB MSG LOG FILES CREATED BY CLONE;

SQLSTATE: HY000

Message: Opening cloned database

Error number: MY-012557; Symbol: ER IB MSG 732; SQLSTATE: HY000

Message: Redo log is from an earlier version, v%lu.

Error number: MY-012557; Symbol: ER_IB_MSG_LOG_FORMAT_OLD; SQLSTATE: HY000 Message: Redo log is from an earlier version, v%lu.

Error number: MY-012558; Symbol: ER_IB_MSG_733; SQLSTATE: HY000 Message: Redo log format v%lu not supported. Current supported format is v%lu.

Error number: MY-012558; Symbol: ER IB MSG LOG FORMAT NOT SUPPORTED;

SQLSTATE: HY000

Message: Redo log format v%lu not supported. Current supported format is v%lu.

Error number: MY-012559; Symbol: ER IB MSG 734; SQLSTATE: HY000

Message: Are you sure you are using the right ib_logfiles to start up the database? Log sequence number in the ib_logfiles is %llu, less than the log sequence number in the first system tablespace file header, %llu.

Error number: MY-012559; Symbol:

ER IB MSG RECOVERY CHECKPOINT FROM BEFORE CLEAN SHUTDOWN;

SQLSTATE: HY000

Message: Are you sure you are using the right redo log files to start up the database? Log sequence number in the redo log files is %llu, less than the log sequence number in the first system tablespace file header, %llu.

Error number: MY-012560; Symbol: ER IB MSG 735; SQLSTATE: HY000

Message: The log sequence number %llu in the system tablespace does not match the log sequence number %llu in the ib logfiles!

Error number: MY-012560; Symbol: ER_IB_MSG_RECOVERY_IS_NEEDED; SQLSTATE: HY000

Message: The log sequence number %llu in the system tablespace does not match the log sequence number %llu in the redo log files!

Error number: MY-012561; Symbol: ER IB MSG 736; SQLSTATE: HY000

Message: Can't initiate database recovery, running in read-only-mode.

Error number: MY-012561; Symbol: ER_IB_MSG_RECOVERY_IN_READ_ONLY; SQLSTATE: HY000

Message: Can't initiate database recovery, running in read-only-mode.

Error number: MY-012562; Symbol: ER IB MSG 737; SQLSTATE: HY000

Message: We scanned the log up to %llu. A checkpoint was at %llu and the maximum LSN on a database page was %llu. It is possible that the database is now corrupt!

Error number: MY-012563; Symbol: ER IB MSG 738; SQLSTATE: HY000

Message: Waiting for recv_writer to finish flushing of buffer pool

Error number: MY-012564; Symbol: ER IB MSG 739; SQLSTATE: HY000

Message: Recovery parsing buffer extended to %zu.

Error number: MY-012565; Symbol: ER IB MSG 740; SQLSTATE: HY000

Message: Out of memory while resizing recovery parsing buffer.

Error number: MY-012871; Symbol: ER IB MSG 1046; SQLSTATE: HY000

Message: Old log sequence number %llu was greater than the new log sequence number %llu. Please

submit a bug report to http://bugs.mysql.com

Error number: MY-012872; Symbol: ER_IB_MSG_1047; SQLSTATE: HY000

Message: Semaphore wait has lasted > %llu seconds. We intentionally crash the server because it

appears to be hung.

Error number: MY-012873; Symbol: ER IB MSG 1048; SQLSTATE: HY000

Message: Waiting for %llu table(s) to be dropped

Error number: MY-012874; Symbol: ER IB MSG 1049; SQLSTATE: HY000

Message: Waiting for change buffer merge to complete number of bytes of change buffer just

merged: %llu

Error number: MY-012875; Symbol: ER IB MSG 1050; SQLSTATE: HY000

Message: Can't set undo tablespace(s) to be encrypted since --innodb undo tablespaces=0.

Error number: MY-012876; Symbol: ER IB MSG 1051; SQLSTATE: HY000

Message: Can't set undo tablespace(s) to be encrypted in read-only-mode.

Error number: MY-012877; Symbol: ER IB MSG 1052; SQLSTATE: HY000

Message: Can't set undo tablespace '%s' to be encrypted.

Error number: MY-012878; Symbol: ER IB MSG 1053; SQLSTATE: HY000

Message: Can't set undo tablespace '%s' to be encrypted. Failed to write header page.

Error number: MY-012879; Symbol: ER IB MSG 1054; SQLSTATE: HY000

Message: Can't set undo tablespace '%s' to be encrypted. Error %d - %s

Error number: MY-012880; Symbol: ER IB MSG 1055; SQLSTATE: HY000

Message: Encryption is enabled for undo tablespace '%s'.

Error number: MY-012881; Symbol: ER IB MSG 1056; SQLSTATE: HY000

Message: Can't rotate encryption on undo tablespace '%s'.

Error number: MY-012882; Symbol: ER IB MSG 1057; SQLSTATE: HY000

Message: Encryption is enabled for undo tablespace '%s'.

Error number: MY-012883; Symbol: ER_IB_MSG_1058; SQLSTATE: HY000 Message: os file get status() failed on '%s'. Can't determine file permissions.

Error number: MY-012884; Symbol: ER_IB_MSG_1059; SQLSTATE: HY000

Message: %s can't be opened in %s mode.

Error number: MY-012885; Symbol: ER_IB_MSG_1060; SQLSTATE: HY000

Message: '%s' not a regular file.

Error number: MY-012886; Symbol: ER IB MSG 1061; SQLSTATE: HY000

Message: Cannot create %s

Error number: MY-012886; Symbol: ER IB MSG LOG FILE OS CREATE FAILED;

SQLSTATE: HY000

Message: Cannot create %s

Error number: MY-012887; Symbol: ER IB MSG 1062; SQLSTATE: HY000

Message: Setting log file %s size to %llu MB. Progress: %u%%

Error number: MY-012887; Symbol: ER IB MSG FILE RESIZE; SQLSTATE: HY000

Message: Setting file %s size to %llu MB. Progress: %u%%

Error number: MY-012888; Symbol: ER IB MSG 1063; SQLSTATE: HY000

Message: Cannot set log file %s to size %llu MB

Error number: MY-012888; Symbol: ER_IB_MSG_LOG_FILE_RESIZE_FAILED; SQLSTATE:

HY000

Message: Cannot resize redo log file %s to %llu MB (%s)

Error number: MY-012889; Symbol: ER_IB_MSG_1064; SQLSTATE: HY000

Message: Cannot create log files in read-only mode

Error number: MY-012889; Symbol:

ER IB MSG LOG FILES CREATE AND READ ONLY MODE; SQLSTATE: HY000

Message: Cannot create redo log files in read-only mode (--innodb-read-only).

Error number: MY-012890; Symbol: ER_IB_MSG_1065; SQLSTATE: HY000

Message: Redo log encryption is enabled, but the keyring is not loaded.

Error number: MY-012891; Symbol: ER IB MSG 1066; SQLSTATE: HY000

Message: Cannot create file for log file %s.

Error number: MY-012891; Symbol:

ER IB MSG LOG FILE PREPARE ON CREATE FAILED; SQLSTATE: HY000

Message: Failed to create redo log file %s (error: %d) for start LSN %llu

Error number: MY-012892; Symbol: ER IB MSG 1067; SQLSTATE: HY000

Message: Renaming log file %s to %s

Error number: MY-012893; Symbol: ER IB MSG 1068; SQLSTATE: HY000

Message: New log files created, LSN=%llu

Error number: MY-012893; Symbol: ER IB MSG LOG FILES INITIALIZED; SQLSTATE:

HY000

Message: New redo log files created, LSN=%llu

Error number: MY-012894; Symbol: ER IB MSG 1069; SQLSTATE: HY000

Message: Unable to open '%s'.

Error number: MY-012894; Symbol: ER IB MSG LOG FILE OPEN FAILED; SQLSTATE:

HY000

Message: Unable to open '%s' (error: %d).

Error number: MY-012895; Symbol: ER IB MSG 1070; SQLSTATE: HY000

Message: Cannot create construction log file '%s' for undo tablespace '%s'.

Error number: MY-012896; Symbol: ER IB MSG 1071; SQLSTATE: HY000

Message: Creating UNDO Tablespace %s

Error number: MY-012897; Symbol: ER_IB_MSG_1072; SQLSTATE: HY000

Message: Setting file %s size to %llu MB

Error number: MY-012898; Symbol: ER IB MSG 1073; SQLSTATE: HY000

Message: Physically writing the file full

Error number: MY-012899; Symbol: ER IB MSG 1074; SQLSTATE: HY000

Message: Error in creating %s: probably out of disk space

Error number: MY-012900; Symbol: ER IB MSG 1075; SQLSTATE: HY000

Message: Can't set encryption metadata for space %s

Error number: MY-012901; Symbol: ER IB MSG 1076; SQLSTATE: HY000

Message: Cannot read first page of '%s' - %s

Error number: MY-012902; Symbol: ER_IB_MSG_1077; SQLSTATE: HY000 Message: Undo tablespace number %lu was being truncated when mysqld quit.

Error number: MY-012903; Symbol: ER IB MSG 1078; SQLSTATE: HY000

Message: Cannot recover a truncated undo tablespace in read-only mode

Error number: MY-012904; Symbol: ER IB MSG 1079; SQLSTATE: HY000

Message: Reconstructing undo tablespace number %lu.

Error number: MY-012905; Symbol: ER IB MSG 1080; SQLSTATE: HY000

Message: Cannot create %s because %s already uses Space ID=%lu! Did you change

innodb undo directory?

Error number: MY-012906; Symbol: ER IB MSG 1081; SQLSTATE: HY000

Message: UNDO tablespace %s must be %s

Error number: MY-012907; Symbol: ER IB MSG 1082; SQLSTATE: HY000

Message: Error creating file for %s

Error number: MY-012908; Symbol: ER IB MSG 1083; SQLSTATE: HY000

Message: Error reading encryption for %s

Error number: MY-012909; Symbol: ER IB MSG 1084; SQLSTATE: HY000

Message: Unable to open undo tablespace number %lu

Error number: MY-012909; Symbol: ER_IB_MSG_CANNOT_OPEN_57_UNDO; SQLSTATE:

HY000

Message: Unable to open undo tablespace number %lu

Error number: MY-012910; Symbol: ER IB MSG 1085; SQLSTATE: HY000

Message: Opened %llu existing undo tablespaces.

Error number: MY-012911; Symbol: ER IB MSG 1086; SQLSTATE: HY000

Message: Cannot create undo tablespaces since innodb_%s has been set. Using %llu existing undo

tablespaces.

Error number: MY-012912; Symbol: ER IB MSG 1087; SQLSTATE: HY000

Message: Cannot continue InnoDB startup in %s mode because there are no existing undo

tablespaces found.

Error number: MY-012913; Symbol: ER IB MSG 1088; SQLSTATE: HY000

Message: Could not create undo tablespace '%s'.

Error number: MY-012914; Symbol: ER IB MSG 1089; SQLSTATE: HY000

Message: Error %d - %s - opening newly created undo tablespace '%s'.

Error number: MY-012915; Symbol: ER IB MSG 1090; SQLSTATE: HY000

Message: Created %llu undo tablespaces.

Error number: MY-012916; Symbol: ER IB MSG 1091; SQLSTATE: HY000

Message: Unable to create encrypted undo tablespace number %lu. please check if the keyring is

initialized correctly

Error number: MY-012917; Symbol: ER IB MSG 1092; SQLSTATE: HY000

Message: Encryption is enabled for undo tablespace number %lu.

Error number: MY-012918; Symbol: ER_IB_MSG_1093; SQLSTATE: HY000

Message: Unable to initialize the header page in undo tablespace number %lu.

Error number: MY-012919; Symbol: ER IB MSG 1094; SQLSTATE: HY000

Message: Cannot delete old undo tablespaces because they contain undo logs for XA PREPARED

transactions.

Error number: MY-012920; Symbol: ER IB MSG 1095; SQLSTATE: HY000

Message: Upgrading %zu existing undo tablespaces that were tracked in the system tablespace

to %lu new independent undo tablespaces.

Error number: MY-012921; Symbol: ER IB MSG 1096; SQLSTATE: HY000

Message: Deleting %llu new independent undo tablespaces that we just created.

Error number: MY-012922; Symbol: ER IB MSG 1097; SQLSTATE: HY000

Message: Waiting for purge to start

Error number: MY-012923; Symbol: ER IB MSG 1098; SQLSTATE: HY000

Message: Creating shared tablespace for temporary tables

Error number: MY-012924; Symbol: ER IB MSG 1099; SQLSTATE: HY000

Message: The %s data file must be writable!

Error number: MY-012925; Symbol: ER IB MSG 1100; SQLSTATE: HY000

Message: Could not create the shared %s.

Error number: MY-012926; Symbol: ER IB MSG 1101; SQLSTATE: HY000

Message: Unable to create the shared %s.

2.11 错误码及错误信息汇总 11

Error number: MY-012927; Symbol: ER_IB_MSG_1102; SQLSTATE: HY000 Message: The %s data file cannot be re-opened after check file spec() succeeded!

Error number: MY-012928; Symbol: ER_IB_MSG_1103; SQLSTATE: HY000

Message: %d threads created by InnoDB had not exited at shutdown!

Error number: MY-012929; Symbol: ER IB MSG 1104; SQLSTATE: HY000

Message: InnoDB Database creation was aborted %swith error %s. You may need to delete the

ibdata1 file before trying to start up again.

Error number: MY-012930; Symbol: ER IB MSG 1105; SQLSTATE: HY000

Message: Plugin initialization aborted %swith error %s.

Error number: MY-012931; Symbol: ER IB MSG 1106; SQLSTATE: HY000

Message: Waiting for %llu buffer page I/Os to complete

Error number: MY-012931; Symbol: ER IB MSG BUF PENDING IO; SQLSTATE: HY000

Message: Waiting for %zu buffer page I/Os to complete.

Error number: MY-012932; Symbol: ER IB MSG 1107; SQLSTATE: HY000

Message: PUNCH HOLE support available

Error number: MY-012933; Symbol: ER IB MSG 1108; SQLSTATE: HY000

Message: PUNCH HOLE support not available

Error number: MY-012934; Symbol: ER IB MSG 1109; SQLSTATE: HY000

Message: Size of InnoDB's ulint is %zu but size of void* is %zu. The sizes should be the same so

that on a 64-bit platforms you can allocate more than 4 GB of memory.

Error number: MY-012935; Symbol: ER IB MSG 1110; SQLSTATE: HY000

Message: Database upgrade cannot be accomplished in read-only mode.

Error number: MY-012936; Symbol: ER_IB_MSG_1111; SQLSTATE: HY000 Message: Database upgrade cannot be accomplished with innodb force recovery > 0

Error number: MY-012947; Symbol: ER_IB_MSG_1122; SQLSTATE: HY000

Message: MySQL was built without a memory barrier capability on this architecture, which might

allow a mutex/rw lock violation under high thread concurrency. This may cause a hang.

Error number: MY-012948; Symbol: ER_IB_MSG_1123; SQLSTATE: HY000

Message: Compressed tables use zlib %s

Error number: MY-012950; Symbol: ER_IB_MSG_1125; SQLSTATE: HY000

Message: Startup called second time during the process lifetime. In the MySQL Embedded Server

Library you cannot call server init() more than once during the process lifetime.

Error number: MY-012952; Symbol: ER_IB_MSG_1127; SQLSTATE: HY000

Message: Unable to create monitor file %s: %s

Error number: MY-012953; Symbol: ER IB MSG 1128; SQLSTATE: HY000

Message: Disabling background log and ibuf IO write threads.

Error number: MY-012954; Symbol: ER IB MSG 1129; SQLSTATE: HY000

Message: Cannot initialize AIO sub-system

Error number: MY-012955; Symbol: ER IB MSG 1130; SQLSTATE: HY000

Message: Initializing buffer pool, total size = %lf%c, instances = %lu, chunk size = %lf%c

Error number: MY-012956; Symbol: ER IB MSG 1131; SQLSTATE: HY000

Message: Cannot allocate memory for the buffer pool

Error number: MY-012957; Symbol: ER IB MSG 1132; SQLSTATE: HY000

Message: Completed initialization of buffer pool

Error number: MY-012958; Symbol: ER_IB_MSG_1133; SQLSTATE: HY000

Message: Small buffer pool size (%lluM), the flst_validate() debug function can cause a deadlock if

the buffer pool fills up.

Error number: MY-012959; Symbol: ER IB MSG 1134; SQLSTATE: HY000

Message: Could not open or create the system tablespace. If you tried to add new data files to the system tablespace, and it failed here, you should now edit innodb_data_file_path in my.cnf back to what it was, and remove the new ibdata files InnoDB created in this failed attempt. InnoDB only wrote those files full of zeros, but did not yet use them in any way. But be careful: do not remove old data files which contain your precious data!

Error number: MY-012960; Symbol: ER IB MSG 1135; SQLSTATE: HY000

Message: Cannot create log files because data files are corrupt or the database was not shut down cleanly after creating the data files.

Error number: MY-012960; Symbol:

 $\label{eq:corrupted} ER_IB_MSG_DATA_DIRECTORY_NOT_INITIALIZED_OR_CORRUPTED; SQLSTATE: \\ HY0000$

Message: Cannot create redo log files because data files are corrupt or the database was not shut down cleanly after creating the data files.

Error number: MY-012961; Symbol: ER IB MSG 1136; SQLSTATE: HY000

Message: Only one log file found

Error number: MY-012961; Symbol: ER IB MSG LOG FILES INVALID SET; SQLSTATE:

HY000

Message: Only one redo log file found

Error number: MY-012962; Symbol: ER IB MSG 1137; SQLSTATE: HY000

Message: Log file %s size %llu is not a multiple of innodb page size

Error number: MY-012962; Symbol: ER_IB_MSG_LOG_FILE_SIZE_INVALID; SQLSTATE:

HY000

Message: The redo log file %s size %llu is not a multiple of innodb page size

Error number: MY-012963; Symbol: ER_IB_MSG_1138; SQLSTATE: HY000 Message: Log file %s is of different size %llu bytes than other log files %llu bytes!

Error number: MY-012963; Symbol: ER IB MSG LOG FILES DIFFERENT SIZES;

SQLSTATE: HY000

Message: The redo log file %s is of different size %llu bytes than other log files %llu bytes!

Error number: MY-012964; Symbol: ER_IB_MSG_1139; SQLSTATE: HY000

Message: Use --innodb-directories to find the tablespace files. If that fails then use --innodb-force-

recovery=1 to ignore this and to permanently lose all changes to the missing tablespace(s)

Error number: MY-012965; Symbol: ER IB MSG 1140; SQLSTATE: HY000

Message: The log file may have been corrupt and it is possible that the log scan or parsing did not proceed far enough in recovery. Please run CHECK TABLE on your InnoDB tables to check that they are ok! It may be safest to recover your InnoDB database from a backup!

Error number: MY-012965; Symbol: ER IB MSG RECOVERY CORRUPT; SQLSTATE: HY000

Message: The redo log file may have been corrupt and it is possible that the log scan or parsing did not proceed far enough in recovery. Please run CHECK TABLE on your InnoDB tables to check that they are ok! It may be safest to recover your InnoDB database from a backup!

Error number: MY-012966; Symbol: ER IB MSG 1141; SQLSTATE: HY000

Message: Cannot resize log files in read-only mode.

Error number: MY-012966; Symbol:

ER IB MSG LOG FILES RESIZE ON START IN READ ONLY MODE; SQLSTATE:

HY000

Message: Cannot resize redo log files in read-only mode. Provide --

innodb redo log capacity >= %lluMB or start without --innodb-read-only.

Error number: MY-012967; Symbol: ER_IB_MSG_1142; SQLSTATE: HY000

Message: Cannot open DD tablespace.

Error number: MY-012968; Symbol: ER_IB_MSG_1143; SQLSTATE: HY000

Message: Starting to delete and rewrite log files.

Error number: MY-012968; Symbol: ER IB MSG LOG FILES REWRITING; SQLSTATE:

HY000

Message: Starting to delete and rewrite redo log files.

Error number: MY-012969; Symbol: ER IB MSG 1144; SQLSTATE: HY000

Message: Undo from 5.7 found. It will be purged

Error number: MY-012970; Symbol: ER IB MSG 1145; SQLSTATE: HY000

Message: %s

Error number: MY-012971; Symbol: ER IB MSG 1146; SQLSTATE: HY000

Message: %s

Error number: MY-012972; Symbol: ER IB MSG 1147; SQLSTATE: HY000

Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is %lu pages

Error number: MY-012973; Symbol: ER IB MSG 1148; SQLSTATE: HY000

Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited innodb_data_file_path in my.cnf in an inappropriate way, removing ibdata files from there? You can set innodb_force_recovery=1 in my.cnf to force a startup if you are trying to recover a badly corrupt database.

Error number: MY-012974; Symbol: ER IB MSG 1149; SQLSTATE: HY000

Message: Tablespace size stored in header is %lu pages, but the sum of data file sizes is only %lu pages

Error number: MY-012975; Symbol: ER_IB_MSG_1150; SQLSTATE: HY000 Message: Cannot start InnoDB. The tail of the system tablespace is missing. Have you edited innodb_data_file_path in my.cnf in an InnoDB: inappropriate way, removing ibdata files from there? You can set innodb_force_recovery=1 in my.cnf to force InnoDB: a startup if you are trying to recover a badly corrupt database.

Error number: MY-012976; Symbol: ER_IB_MSG_1151; SQLSTATE: HY000 Message: %s started; log sequence number %llu

Error number: MY-012977; Symbol: ER_IB_MSG_1152; SQLSTATE: HY000 Message: Waiting for purge to complete

Error number: MY-012978; Symbol: ER_IB_MSG_1153; SQLSTATE: HY000 Message: Waiting for dict stats thread to exit

Error number: MY-012979; Symbol: ER_IB_MSG_1154; SQLSTATE: HY000 Message: Query counter shows %lld queries still inside InnoDB at shutdown

Error number: MY-012980; Symbol: ER_IB_MSG_1155; SQLSTATE: HY000 Message: Shutdown completed; log sequence number %llu

Error number: MY-012981; Symbol: ER_IB_MSG_1156; SQLSTATE: HY000 Message: Cannot continue operation.

Error number: MY-012991; Symbol:

ER_IB_MSG_UNDO_TRUNCATE_FAIL_TO_READ_LOG_FILE; SQLSTATE: HY000 Message: Unable to read the existing undo truncate log file '%s'. The error is %s

Error number: MY-012992; Symbol: ER IB MSG UNDO MARKED FOR TRUNCATE;

SQLSTATE: HY000

Message: Undo tablespace %s is marked for truncate

Error number: MY-012994; Symbol: ER IB MSG UNDO TRUNCATE START; SQLSTATE:

HY000

Message: Truncating UNDO tablespace %s

Error number: MY-012996; Symbol: ER_IB_MSG_1171; SQLSTATE: HY000

Message: Cannot create truncate log for undo tablespace '%s'.

Error number: MY-012996; Symbol:

ER IB MSG UNDO TRUNCATE DELAY BY LOG CREATE; SQLSTATE: HY000

Message: Cannot create truncate log for undo tablespace '%s'.

Error number: MY-012998; Symbol: ER IB MSG 1173; SQLSTATE: HY000

Message: Failed to truncate undo tablespace '%s'.

Error number: MY-012998; Symbol: ER IB MSG UNDO TRUNCATE DELAY BY FAILURE;

SQLSTATE: HY000

Message: Failed to truncate undo tablespace '%s'.

Error number: MY-013000; Symbol: ER IB MSG UNDO TRUNCATE COMPLETE;

SQLSTATE: HY000

Message: Completed truncate of undo tablespace %s.

Error number: MY-013015; Symbol:

ER IB MSG TRX RECOVERY ROLLBACK COMPLETED; SQLSTATE: HY000

Message: Rollback of non-prepared transactions completed

Error number: MY-013038; Symbol: ER IB MSG 1213; SQLSTATE: HY000

Message: gettimeofday() failed: %s

Error number: MY-013039; Symbol: ER IB MSG 1214; SQLSTATE: HY000

Message: Can't create UNDO tablespace %s %s

Error number: MY-013041; Symbol: ER IB MSG LOG FILES RESIZE ON START;

SQLSTATE: HY000

Message: Resizing redo log from %lluM to %lluM (LSN=%llu) synchronously. If this takes too long, consider starting the server with large --innodb_redo_log_capacity, and resizing the redo log online using SET.

Error number: MY-013059; Symbol: ER IB MSG LOG WRITER OUT OF SPACE;

SQLSTATE: HY000

Message: Out of space in the redo log. Checkpoint LSN: %llu. Consider increasing

innodb redo log capacity.

Error number: MY-013061; Symbol: ER IB MSG LOG WRITER ABORTS LOG ARCHIVER;

SQLSTATE: HY000

Message: Log writer waited too long for redo-archiver to advance (1 second). There are unarchived: %llu bytes. Archiver LSN: %llu. Aborted the redo-archiver. Consider increasing innodb redo log capacity.

Error number: MY-013062; Symbol: ER_IB_MSG_LOG_WRITER_WAITING_FOR_ARCHIVER; SOLSTATE: HY000

Message: Log writer is waiting for redo-archiver to catch up unarchived: %llu bytes. Archiver

LSN: %llu. Consider increasing innodb redo log capacity.

Error number: MY-013067; Symbol: ER IB MSG 1242; SQLSTATE: HY000

Message: Can't set redo log tablespace to be encrypted in read-only mode.

Error number: MY-013067; Symbol:

ER IB MSG LOG FILES CANNOT ENCRYPT IN READ ONLY; SQLSTATE: HY000

Message: Can't set redo log files to be encrypted in read-only mode.

Error number: MY-013068; Symbol: ER IB MSG 1243; SQLSTATE: HY000

Message: Can't set redo log tablespace to be encrypted.

Error number: MY-013068; Symbol: ER IB MSG LOG FILES ENCRYPTION INIT FAILED;

SQLSTATE: HY000

Message: Can't set redo log files to be encrypted.

Error number: MY-013069; Symbol: ER IB MSG 1244; SQLSTATE: HY000

Message: Can't set redo log tablespace to be encrypted.

Error number: MY-013070; Symbol: ER_IB_MSG_1245; SQLSTATE: HY000

Message: Redo log encryption is enabled.

Error number: MY-013071; Symbol: ER IB MSG 1246; SQLSTATE: HY000

Message: Waiting for archiver to finish archiving page and log

Error number: MY-013072; Symbol: ER IB MSG 1247; SQLSTATE: HY000

Message: Starting shutdown...

Error number: MY-013073; Symbol: ER IB MSG 1248; SQLSTATE: HY000

Message: Waiting for %s to exit.

Error number: MY-013074; Symbol: ER IB MSG 1249; SQLSTATE: HY000

Message: Waiting for rollback of %zu recovered transactions, before shutdown.

Error number: MY-013075; Symbol: ER IB MSG 1250; SQLSTATE: HY000

Message: Waiting for master thread to be suspended.

Error number: MY-013076; Symbol: ER IB MSG 1251; SQLSTATE: HY000

Message: Waiting for page_cleaner to finish flushing of buffer pool.

Error number: MY-013077; Symbol: ER IB MSG 1252; SQLSTATE: HY000

Message: Waiting for %lu buffer page I/Os to complete.

Error number: MY-013077; Symbol: ER IB MSG BUF PENDING IO ON SHUTDOWN;

SQLSTATE: HY000

Message: Shutdown is waiting for %zu buffer page I/Os to complete.

Error number: MY-013078; Symbol: ER IB MSG 1253; SQLSTATE: HY000

Message: MySQL has requested a very fast shutdown without flushing the InnoDB buffer pool to

data files. At the next mysqld startup InnoDB will do a crash recovery!

Error number: MY-013089; Symbol:

ER_IB_MSG_LOG_FILE_HEADER_INVALID_CHECKSUM; SQLSTATE: HY000

Message: Invalid redo log header checksum.

Error number: MY-013090; Symbol: ER IB MSG LOG FORMAT BEFORE 5 7 9;

SQLSTATE: HY000

Message: Unsupported redo log format (v%lu). The redo log was created before MySQL 5.7.9

Error number: MY-013092; Symbol:

ER_IB_MSG_LOG_PARAMS_CONCURRENCY_MARGIN_UNSAFE; SQLSTATE: HY000 Message: Cannot continue operation. The innodb_redo_log_capacity=%lluM is too small for the innodb_thread_concurrency=%lu. The capacity of redo should be >= %lluM. To get mysqld running, set innodb_thread_concurrency to a smaller value or increase innodb_redo_log_capacity. %s

Error number: MY-013095; Symbol: ER IB MSG THREAD CONCURRENCY CHANGED;

SOLSTATE: HY000

Message: User has set innodb thread concurrency to %lu.

Error number: MY-013096; Symbol:

ER_RPL_SLAVE_SQL_THREAD_STOP_CMD_EXEC_TIMEOUT; SQLSTATE: HY000

Message: STOP SLAVE command execution is incomplete: Slave SQL thread got the stop signal,

thread is busy, SQL thread will stop once the current task is complete.

Error number: MY-013097; Symbol:

ER RPL SLAVE IO THREAD STOP CMD EXEC TIMEOUT; SQLSTATE: HY000

Message: STOP SLAVE command execution is incomplete: Slave IO thread got the stop signal,

thread is busy, IO thread will stop once the current task is complete.

Error number: MY-013098; Symbol:

ER RPL GTID UNSAFE STMT ON NON TRANS TABLE; SQLSTATE: HY000

Message: Statement violates GTID consistency: Updates to non-transactional tables can only be done in either autocommitted statements or single-statement transactions, and never in the same statement as updates to transactional tables.

Error number: MY-013099; Symbol: ER RPL GTID UNSAFE STMT CREATE SELECT;

SQLSTATE: HY000

Message: Statement violates GTID consistency: CREATE TABLE ... SELECT.

Error number: MY-013100; Symbol:

ER_RPL_GTID_UNSAFE_STMT_ON_TEMPORARY_TABLE; SQLSTATE: HY000 Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE can only be executed outside transactional context. These statements are also not allowed in a function or trigger because functions and triggers are also considered to be multi-statement transactions.

Error number: MY-013101; Symbol: ER BINLOG ROW VALUE OPTION IGNORED;

SQLSTATE: HY000

Message: When %s, the option binlog_row_value_options=%s will be ignored and updates will be written in full format to binary log.

Error number: MY-013102; Symbol: ER_BINLOG_USE_V1_ROW_EVENTS_IGNORED; SQLSTATE: HY000

Message: When %s, the option log_bin_use_v1_row_events=1 will be ignored and row events will be written in new format to binary log.

Error number: MY-013103; Symbol:

ER_BINLOG_ROW_VALUE_OPTION_USED_ONLY_FOR_AFTER_IMAGES; SQLSTATE: HY000

Message: When %s, the option binlog_row_value_options=%s will be used only for the after-image. Full values will be written in the before-image, so the saving in disk space due to binlog row value options is limited to less than 50%%.

Error number: MY-013104; Symbol: ER_CONNECTION_ABORTED; SQLSTATE: HY000 Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s).

Error number: MY-013105; Symbol: ER_NORMAL_SERVER_SHUTDOWN; SQLSTATE: HY000

Message: %s: Normal shutdown.

Error number: MY-013106; Symbol: ER_KEYRING_MIGRATE_FAILED; SQLSTATE: HY000 Message: Can not perform keyring migration : %s.

Error number: MY-013107; Symbol:

ER_GRP_RPL_LOWER_CASE_TABLE_NAMES_DIFF_FROM_GRP; SQLSTATE: HY000 Message: The member is configured with a lower_case_table_names option value '%u' different from the group '%u'. The member will now exit the group. If there is existing data on member, it may be incompatible with group if it was created with a lower_case_table_names value different from the group.

Error number: MY-013108; Symbol: ER_OOM_SAVE_GTIDS; SQLSTATE: HY000 Message: An out-of-memory error occurred while saving the set of GTIDs from the last binary log into the mysql.gtid executed table

Error number: MY-013109; Symbol: ER_LCTN_NOT_FOUND; SQLSTATE: HY000 Message: The lower_case_table_names setting for the data dictionary was not found. Starting the server using lower case table names = '%u'.

Error number: MY-013111; Symbol: ER COMPONENT FILTER WRONG VALUE;

SQLSTATE: HY000

Message: Variable '%s' can't be set to the value of '%s'

Error number: MY-013112; Symbol: ER XPLUGIN FAILED TO STOP SERVICES;

SQLSTATE: HY000

Message: Stopping services failed with error "%s"

Error number: MY-013113; Symbol: ER_INCONSISTENT_ERROR; SQLSTATE: HY000 Message: Query caused different errors on master and slave. Error on master: Message (format)='%s' error code=%d; Error on slave:actual Message='%s', error code=%d. Default database:'%s'. Query:'%s'

Error number: MY-013114; Symbol:

ER SERVER MASTER FATAL ERROR READING BINLOG; SQLSTATE: HY000

Message: Got fatal error %d from master when reading data from binary log: '%s'

Error number: MY-013115; Symbol: ER_NETWORK_READ_EVENT_CHECKSUM_FAILURE;

SQLSTATE: HY000

Message: Replication event checksum verification failed while reading from network.

Error number: MY-013116; Symbol: ER SLAVE CREATE EVENT FAILURE; SQLSTATE:

HY000

Message: Failed to create %s

Error number: MY-013118; Symbol: ER_SLAVE_HEARTBEAT_FAILURE; SQLSTATE: HY000 Message: Unexpected master's heartbeat data: %s

Error number: MY-013119; Symbol: ER SLAVE INCIDENT; SQLSTATE: HY000

Message: The incident %s occurred on the master. Message: %s

Error number: MY-013120; Symbol: ER SLAVE MASTER COM FAILURE; SQLSTATE:

HY000

Message: Master command %s failed: %s

Error number: MY-013121; Symbol: ER SLAVE RELAY LOG READ FAILURE; SQLSTATE:

HY000

Message: Relay log read failure: %s

Error number: MY-013122; Symbol: ER SLAVE RELAY LOG WRITE FAILURE;

SQLSTATE: HY000

Message: Relay log write failure: %s

Error number: MY-013123; Symbol: ER SERVER SLAVE MI INIT REPOSITORY;

SQLSTATE: HY000

Message: Slave failed to initialize master info structure from the repository

Error number: MY-013124; Symbol: ER SERVER SLAVE RLI INIT REPOSITORY;

SQLSTATE: HY000

Message: Slave failed to initialize relay log info structure from the repository

Error number: MY-013125; Symbol: ER SERVER NET PACKET TOO LARGE; SQLSTATE:

HY000

Message: Got a packet bigger than 'max allowed packet' bytes

Error number: MY-013126; Symbol: ER SERVER NO SYSTEM TABLE ACCESS;

SOLSTATE: HY000

Message: Access to %s '%s.%s' is rejected.

Error number: MY-013127; Symbol: ER_SERVER_UNKNOWN_ERROR; SQLSTATE: HY000

Message: Unknown error

Error number: MY-013128; Symbol: ER SERVER UNKNOWN SYSTEM VARIABLE;

SQLSTATE: HY000

Message: Unknown system variable '%s'

Error number: MY-013129; Symbol: ER SERVER NO SESSION TO SEND TO; SQLSTATE:

HY000

Message: A Message intended for a client cannot be sent there as no client-session is attached. Therefore, we're sending the information to the error-log instead: MY-%06d - %s

Error number: MY-013130; Symbol: ER_SERVER_NEW_ABORTING_CONNECTION; SQLSTATE: 08S01

Message: Aborted connection %u to db: '%s' user: '%s' host: '%s' (%s; diagnostics area: MY-%06d - %s)

Error number: MY-013131; Symbol: ER_SERVER_OUT_OF_SORTMEMORY; SQLSTATE: HY000

Message: Out of sort memory, consider increasing server sort buffer size!

Error number: MY-013132; Symbol: ER_SERVER_RECORD_FILE_FULL; SQLSTATE: HY000 Message: The table '%s' is full!

Error number: MY-013133; Symbol: ER_SERVER_DISK_FULL_NOWAIT; SQLSTATE: HY000 Message: Create table/tablespace '%s' failed, as disk is full.

Error number: MY-013134; Symbol: ER_SERVER_HANDLER_ERROR; SQLSTATE: HY000 Message: Handler reported error %d - %s

Error number: MY-013135; Symbol: ER_SERVER_NOT_FORM_FILE; SQLSTATE: HY000 Message: Incorrect information in file: '%s'

Error number: MY-013136; Symbol: ER_SERVER_CANT_OPEN_FILE; SQLSTATE: HY000 Message: Can't open file: '%s' (OS errno: %d - %s)

Error number: MY-013137; Symbol: ER_SERVER_FILE_NOT_FOUND; SQLSTATE: HY000 Message: Can't find file: '%s' (OS errno: %d - %s)

Error number: MY-013138; Symbol: ER_SERVER_FILE_USED; SQLSTATE: HY000 Message: '%s' is locked against change (OS errno: %d - %s)

Error number: MY-013139; Symbol: ER_SERVER_CANNOT_LOAD_FROM_TABLE_V2; SQLSTATE: HY000

Message: Cannot load from %s.%s. The table is probably corrupted!

Error number: MY-013140; Symbol: ER_ERROR_INFO_FROM_DA; SQLSTATE: HY000 Message: Error in diagnostics area: MY-%06d - %s

Error number: MY-013141; Symbol: ER_SERVER_TABLE_CHECK_FAILED; SQLSTATE: HY000

Message: Incorrect definition of table %s.%s: expected column '%s' at position %d, found '%s'.

Error number: MY-013142; Symbol:

ER_SERVER_COL_COUNT_DOESNT_MATCH_PLEASE_UPDATE_V2; SQLSTATE: HY000 Message: The column count of %s.%s is wrong. Expected %d, found %d. Created with MySQL %d, now running %d. Please perform the MySQL upgrade procedure.

Error number: MY-013143; Symbol:

ER_SERVER_COL_COUNT_DOESNT_MATCH_CORRUPTED_V2; SQLSTATE: HY000 Message: Column count of %s.%s is wrong. Expected %d, found %d. The table is probably corrupted

Error number: MY-013144; Symbol: ER_SERVER_ACL_TABLE_ERROR; SQLSTATE: HY000 Message:

Error number: MY-013145; Symbol: ER SERVER SLAVE INIT QUERY FAILED;

SQLSTATE: HY000

Message: Slave SQL thread aborted. Can't execute init replica query, MY-%06d - '%s'

Error number: MY-013146; Symbol: ER SERVER SLAVE CONVERSION FAILED;

SQLSTATE: HY000

Message: Column %d of table '%s.%s' cannot be converted from type '%s' to type '%s'

Error number: MY-013147; Symbol: ER_SERVER_SLAVE_IGNORED_TABLE; SQLSTATE: HY000

Message: Slave SQL thread ignored the query because of replicate-*-table rules

Error number: MY-013148; Symbol:

ER_CANT_REPLICATE_ANONYMOUS_WITH_AUTO_POSITION; SQLSTATE: HY000 Message: Cannot replicate anonymous transaction when AUTO_POSITION = 1, at file %s, position %lld.

Error number: MY-013149; Symbol:

ER_CANT_REPLICATE_ANONYMOUS_WITH_GTID_MODE_ON; SQLSTATE: HY000 Message: Cannot replicate anonymous transaction when @@GLOBAL.GTID_MODE = ON, at file %s, position %lld.

Error number: MY-013150; Symbol: ER_CANT_REPLICATE_GTID_WITH_GTID_MODE_OFF; SQLSTATE: HY000

Message: Cannot replicate GTID-transaction when @@GLOBAL.GTID_MODE = OFF, at file %s, position %lld.

Error number: MY-013151; Symbol: ER SERVER TEST MESSAGE; SQLSTATE: HY000

Message: Simulated error

Error number: MY-013152; Symbol: ER AUDIT LOG JSON FILTER PARSING ERROR;

SQLSTATE: HY000

Message: %s

Error number: MY-013153; Symbol: ER AUDIT LOG JSON FILTERING NOT ENABLED;

SQLSTATE: HY000

Message: Audit Log filtering has not been installed.

Error number: MY-013154; Symbol: ER PLUGIN FAILED TO OPEN TABLES; SQLSTATE:

HY000

Message: Failed to open the %s filter tables.

Error number: MY-013155; Symbol: ER PLUGIN FAILED TO OPEN TABLE; SQLSTATE:

HY000

Message: Failed to open '%s.%s' %s table.

Error number: MY-013156; Symbol:

ER AUDIT LOG JSON FILTER NAME CANNOT BE EMPTY; SQLSTATE: HY000

Message: Filter name cannot be empty.

Error number: MY-013157; Symbol: ER_AUDIT_LOG_USER_NAME_INVALID_CHARACTER;

SQLSTATE: HY000

Message: Invalid character in the user name.

Error number: MY-013158; Symbol: ER_AUDIT_LOG_UDF_INSUFFICIENT_PRIVILEGE;

SQLSTATE: HY000

Message: Request ignored for '%s'@'%s'. SUPER or AUDIT ADMIN needed to perform operation

Error number: MY-013159; Symbol: ER AUDIT LOG NO KEYRING PLUGIN INSTALLED;

SQLSTATE: HY000

Message: No keyring installed.

Error number: MY-013160; Symbol: ER AUDIT LOG HOST NAME INVALID CHARACTER;

SQLSTATE: HY000

Message: Invalid character in the host name.

Error number: MY-013161; Symbol:

ER AUDIT LOG ENCRYPTION PASSWORD HAS NOT BEEN SET; SQLSTATE: HY000

Message: Audit log encryption password has not been set; it will be generated automatically. Use audit_log_encryption_password_get to obtain the password or audit_log_encryption_password_set to set a new one.

Error number: MY-013162; Symbol: ER AUDIT LOG COULD NOT CREATE AES KEY;

SQLSTATE: HY000

Message: Could not create AES key. OpenSSL's EVP BytesToKey function failed.

Error number: MY-013163; Symbol:

ER AUDIT LOG ENCRYPTION_PASSWORD_CANNOT_BE_FETCHED; SQLSTATE:

HY000

Message: Audit log encryption password cannot be fetched from the keyring. Password used so far is used for encryption.

Error number: MY-013164; Symbol:

ER COULD NOT REINITIALIZE AUDIT LOG FILTERS; SQLSTATE: HY000

Message: Could not reinitialize audit log filters.

Error number: MY-013165; Symbol:

ER AUDIT LOG JSON USER NAME CANNOT BE EMPTY; SQLSTATE: HY000

Message: User cannot be empty.

Error number: MY-013166; Symbol:

ER AUDIT LOG USER FIRST CHARACTER MUST BE ALPHANUMERIC; SQLSTATE:

HY000

Message: First character of the user name must be alphanumeric.

Error number: MY-013167; Symbol: ER AUDIT LOG JSON FILTER DOES NOT EXIST;

SQLSTATE: HY000

Message: Specified filter has not been found.

Error number: MY-013168; Symbol: ER IB MSG 1271; SQLSTATE: HY000

Message: Cannot upgrade server earlier than 5.7 to 8.0

Error number: MY-013169; Symbol: ER STARTING INIT; SQLSTATE: HY000

Message: %s (mysqld %s) initializing of server in progress as process %lu

Error number: MY-013170; Symbol: ER ENDING INIT; SQLSTATE: HY000

Message: %s (mysqld %s) initializing of server has completed

Error number: MY-013171; Symbol: ER IB MSG 1272; SQLSTATE: HY000

Message: Cannot boot server version %lu on data directory built by version %llu. Downgrade is not supported

Error number: MY-013172; Symbol: ER_SERVER_SHUTDOWN_INFO; SQLSTATE: HY000 Message: Received SHUTDOWN from user %s. Shutting down mysqld (Version: %s).

Error number: MY-013173; Symbol: ER_GRP_RPL_PLUGIN_ABORT; SQLSTATE: HY000 Message: The plugin encountered a critical error and will abort: %s

Error number: MY-013177; Symbol: ER_AUDIT_LOG_TABLE_DEFINITION_NOT_UPDATED; SQLSTATE: HY000

Message: '%s.%s' table definition has not been upgraded; Please perform the MySQL upgrade procedure.

Error number: MY-013178; Symbol: ER_DD_INITIALIZE_SQL_ERROR; SQLSTATE: HY000 Message: Execution of server-side SQL statement '%s' failed with error code = %d, error Message = '%s'.

Error number: MY-013179; Symbol: ER_NO_PATH_FOR_SHARED_LIBRARY; SQLSTATE: HY000

Message: No paths allowed for shared library.

Error number: MY-013180; Symbol: ER_UDF_ALREADY_EXISTS; SQLSTATE: HY000 Message: Function '%s' already exists.

Error number: MY-013181; Symbol: ER_SET_EVENT_FAILED; SQLSTATE: HY000 Message: Got Error: %ld from SetEvent.

Error number: MY-013182; Symbol: ER_FAILED_TO_ALLOCATE_SSL_BIO; SQLSTATE: HY000

Message: Error allocating SSL BIO.

Error number: MY-013184; Symbol: ER_PID_FILEPATH_LOCATIONS_INACCESSIBLE; SOLSTATE: HY000

Message: One or several locations were inaccessible while checking PID filepath.

Error number: MY-013185; Symbol:

ER_UNKNOWN_VARIABLE_IN_PERSISTED_CONFIG_FILE; SQLSTATE: HY000 Message: Currently unknown variable '%s' was read from the persisted config file.

Error number: MY-013186; Symbol: ER_FAILED_TO_HANDLE_DEFAULTS_FILE; SQLSTATE: HY000

Message: Fatal error in defaults handling. Program aborted!

Error number: MY-013187; Symbol: ER DUPLICATE SYS VAR; SQLSTATE: HY000

Message: Duplicate variable name '%s'.

Error number: MY-013188; Symbol: ER FAILED TO INIT SYS VAR; SQLSTATE: HY000

Message: Failed to initialize system variables.

Error number: MY-013189; Symbol: ER SYS VAR NOT FOUND; SQLSTATE: HY000

Message: Variable name '%s' not found.

Error number: MY-013190; Symbol: ER IB MSG 1274; SQLSTATE: HY000

Message: Some (%d) threads are still active

Error number: MY-013192; Symbol: ER_TARGET_TS_UNENCRYPTED; SQLSTATE: HY000

Message: Source tablespace is encrypted but target tablespace is not.

Error number: MY-013193; Symbol: ER_IB_MSG_WAIT_FOR_ENCRYPT_THREAD;

SQLSTATE: HY000

Message: Waiting for tablespace alter encrypt thread to exit

Error number: MY-013195; Symbol: ER IB MSG NO ENCRYPT PROGRESS FOUND;

SOLSTATE: HY000

Message: %s

Error number: MY-013196; Symbol: ER IB MSG RESUME OP FOR SPACE; SQLSTATE:

HY000

Message: %s

Error number: MY-013202; Symbol:

ER CANT SET ERROR SUPPRESSION LIST FROM COMMAND LINE; SQLSTATE:

HY000

Message: %s: Could not add suppression rule for code "%s". Rule-set may be full, or code may not

correspond to an error-log Message.

Error number: MY-013203; Symbol: ER INVALID VALUE OF BIND ADDRESSES;

SQLSTATE: HY000

Message: Invalid value for command line option bind-addresses: '%s'

Error number: MY-013204; Symbol: ER RELAY LOG SPACE LIMIT DISABLED;

SQLSTATE: HY000

Message: Ignoring the @@global.relay_log_space_limit option because @@global.relay_log_purge is disabled.

Error number: MY-013205; Symbol: ER GRP RPL ERROR GTID SET EXTRACTION;

SQLSTATE: HY000

Message: Error when extracting GTID execution information: %s

Error number: MY-013206; Symbol:

ER GRP RPL MISSING GRP RPL ACTION COORDINATOR; SQLSTATE: HY000

Message: Message received without a proper group coordinator module.

Error number: MY-013207; Symbol:

ER GRP RPL JOIN WHEN GROUP ACTION RUNNING; SQLSTATE: HY000

Message: A member cannot join the group while a group configuration operation is running.

Error number: MY-013208; Symbol:

ER_GRP_RPL_JOINER_EXIT_WHEN_GROUP_ACTION_RUNNING; SQLSTATE: HY000 Message: A member is joining the group while a group configuration operation is occurring. The

member will now leave the group

Error number: MY-013209; Symbol:

ER GRP RPL CHANNEL THREAD WHEN GROUP ACTION RUNNING; SQLSTATE:

HY000

Message: Can't start slave %s when group replication is running a group configuration operation.

Error number: MY-013210; Symbol: ER GRP RPL APPOINTED PRIMARY NOT PRESENT;

SQLSTATE: HY000

Message: A primary election was invoked but the requested primary member is not in the group.

Request ignored.

Error number: MY-013211; Symbol: ER GRP RPL ERROR ON MESSAGE SENDING;

SQLSTATE: HY000

Message: Error while sending Message. Context: %s

Error number: MY-013212; Symbol: ER GRP RPL CONFIGURATION ACTION ERROR;

SQLSTATE: HY000

Message: Error while executing a group configuration operation: %s

Error number: MY-013213; Symbol:

ER GRP RPL CONFIGURATION ACTION LOCAL TERMINATION; SQLSTATE: HY000

Message: Configuration operation '%s' terminated. %s

Error number: MY-013214; Symbol: ER GRP RPL CONFIGURATION ACTION START;

SQLSTATE: HY000

Message: Starting group operation local execution: %s

Error number: MY-013215; Symbol: ER GRP RPL CONFIGURATION ACTION END;

SQLSTATE: HY000

Message: Termination of group operation local execution: %s

Error number: MY-013216; Symbol:

ER GRP RPL CONFIGURATION ACTION KILLED ERROR; SQLSTATE: HY000

Message: A configuration change was killed in this member. The member will now leave the group as its configuration may have diverged.

Error number: MY-013217; Symbol: ER_GRP_RPL_PRIMARY_ELECTION_PROCESS_ERROR;

SQLSTATE: HY000

Message: There was an issue on the primary election process: %s The member will now leave the

group.

Error number: MY-013218; Symbol: ER GRP RPL PRIMARY ELECTION STOP ERROR;

SQLSTATE: HY000

Message: There was an issue when stopping a previous election process: %s

Error number: MY-013219; Symbol: ER GRP RPL NO STAGE SERVICE; SQLSTATE: HY000

Message: It was not possible to initialize stage logging for this task. The operation will still run

without stage tracking.

Error number: MY-013220; Symbol: ER_GRP_RPL_UDF_REGISTER_ERROR; SQLSTATE:

HY000

Message: Could not execute the installation of Group Replication UDF function: %s. Check if the

function is already present, if so, try to remove it

Error number: MY-013221; Symbol: ER GRP RPL UDF UNREGISTER ERROR; SQLSTATE:

HY000

Message: Could not uninstall Group Replication UDF functions. Try to remove them manually if

present.

Error number: MY-013222; Symbol: ER GRP RPL UDF REGISTER SERVICE ERROR;

SQLSTATE: HY000

Message: Could not execute the installation of Group Replication UDF functions. Check for other

errors in the log and try to reinstall the plugin

Error number: MY-013223; Symbol: ER GRP RPL SERVER UDF ERROR; SQLSTATE:

HY000

Message: The function '%s' failed. %s

Error number: MY-013227; Symbol: ER SERVER WRONG VALUE FOR VAR; SQLSTATE:

HY000

Message: Variable '%s' can't be set to the value of '%s'

Error number: MY-013228; Symbol:

ER_COULD_NOT_CREATE_WINDOWS_REGISTRY_KEY; SQLSTATE: HY000

Message: %s was unable to create a new Windows registry key %s for %s; continuing to use the

previous ident.

Error number: MY-013229; Symbol:

ER SERVER GTID UNSAFE CREATE DROP TEMP TABLE IN TRX IN SBR;

SQLSTATE: HY000

Message: Statement violates GTID consistency: CREATE TEMPORARY TABLE and DROP TEMPORARY TABLE are not allowed inside a transaction or inside a procedure in a transactional

context when @@session.binlog format=STATEMENT.

Error number: MY-013233; Symbol: ER XPLUGIN FAILED TO SWITCH SECURITY CTX;

SQLSTATE: HY000

Message: Unable to switch security context to user: %s

Error number: MY-013234; Symbol:

 $ER_RPL_GTID_UNSAFE_ALTER_ADD_COL_WITH_DEFAULT_EXPRESSION; SQLSTATE:$

HY000

Message: Statement violates GTID consistency: ALTER TABLE ... ADD COLUMN .. with

expression as DEFAULT.

Error number: MY-013235; Symbol: ER UPGRADE PARSE ERROR; SQLSTATE: HY000

Message: Error in parsing %s '%s'.'%s' during upgrade. %s

Error number: MY-013236; Symbol: ER DATA DIRECTORY UNUSABLE; SQLSTATE:

HY000

Message: The designated data directory %s is unusable. You can remove all files that the server

added to it.

Error number: MY-013237; Symbol: ER LDAP AUTH USER GROUP SEARCH ROOT BIND;

SQLSTATE: HY000

Message: Group search rebinding via root DN: %s

Error number: MY-013238; Symbol: ER_PLUGIN_INSTALL_ERROR; SQLSTATE: HY000 Message: Error installing plugin '%s': %s

Error number: MY-013239; Symbol: ER_PLUGIN_UNINSTALL_ERROR; SQLSTATE: HY000 Message: Error uninstalling plugin '%s': %s

Error number: MY-013240; Symbol:

ER_SHARED_TABLESPACE_USED_BY_PARTITIONED_TABLE; SQLSTATE: HY000 Message: Partitioned table '%s' is not allowed to use shared tablespace '%s'. Please move all partitions to file-per-table tablespaces before upgrade.

Error number: MY-013241; Symbol: ER_UNKNOWN_TABLESPACE_TYPE; SQLSTATE: HY000

Message: Cannot determine the type of the tablespace named '%s'.

Error number: MY-013242; Symbol: ER_WARN_DEPRECATED_UTF8_ALIAS_OPTION; SQLSTATE: HY000

Message: %s: 'utf8' is currently an alias for the character set UTF8MB3, but will be an alias for UTF8MB4 in a future release. Please consider using UTF8MB4 in order to be unambiguous.

Error number: MY-013243; Symbol:

ER WARN DEPRECATED UTF8MB3 CHARSET OPTION; SQLSTATE: HY000

Message: %s: The character set UTF8MB3 is deprecated and will be removed in a future release. Please consider using UTF8MB4 instead.

Error number: MY-013244; Symbol:

ER_WARN_DEPRECATED_UTF8MB3_COLLATION_OPTION; SQLSTATE: HY000 Message: %s: '%s' is a collation of the deprecated character set UTF8MB3. Please consider using UTF8MB4 with an appropriate collation instead.

Error number: MY-013245; Symbol: ER_SSL_MEMORY_INSTRUMENTATION_INIT_FAILED; SQLSTATE: HY000

Message: The SSL library function %s failed. This is typically caused by the SSL library already being used. As a result the SSL memory allocation will not be instrumented.

Error number: MY-013246; Symbol: ER_IB_MSG_MADV_DONTDUMP_UNSUPPORTED; SQLSTATE: HY000

Message: Disabling @@core_file because @@innodb_buffer_pool_in_core_file is disabled, yet MADV_DONTDUMP is not supported on this platform

Error number: MY-013247; Symbol: ER_IB_MSG_MADVISE_FAILED; SQLSTATE: HY000

Message: Disabling @@core_file because @@innodb_buffer_pool_in_core_file is disabled, yet madvise(%p,%zu,%s) failed with %s

Error number: MY-013249; Symbol: ER_WARN_REMOVED_SQL_MODE; SQLSTATE: HY000 Message: sql mode=0x%08x has been removed and will be ignored

Error number: MY-013250; Symbol: ER IB MSG FAILED TO ALLOCATE WAIT;

SQLSTATE: HY000

Message: Failed to allocate memory for a pool of size %zu bytes. Will wait for %zu seconds for a

thread to free a resource.

Error number: MY-013251; Symbol: ER IB MSG NUM POOLS; SQLSTATE: HY000

Message: Number of pools: %zu

Error number: MY-013252; Symbol: ER_IB_MSG_USING_UNDO_SPACE; SQLSTATE: HY000

Message: Using undo tablespace '%s'.

Error number: MY-013253; Symbol: ER IB MSG FAIL TO SAVE SPACE STATE;

SQLSTATE: HY000

Message: %s Unable to save the current state of tablespace '%s' to the data dictionary

Error number: MY-013254; Symbol: ER_IB_MSG_MAX_UNDO_SPACES_REACHED;

SOLSTATE: HY000

Message: Cannot create undo tablespace %s at %s because %d undo tablespaces already exist.

Error number: MY-013255; Symbol: ER IB MSG ERROR OPENING NEW UNDO SPACE;

SQLSTATE: HY000

Message: Error %d opening newly created undo tablespace %s.

Error number: MY-013256; Symbol: ER IB MSG FAILED SDI Z BUF ERROR; SQLSTATE:

HY000

Message: SDI Compression failed, Z BUF ERROR

Error number: MY-013257; Symbol: ER IB MSG FAILED SDI Z MEM ERROR; SQLSTATE:

HY000

Message: SDI Compression failed, Z MEM ERROR

Error number: MY-013258; Symbol: ER IB MSG SDI Z STREAM ERROR; SQLSTATE:

HY000

Message: SDI Compression failed, Z STREAM ERROR

Error number: MY-013259; Symbol: ER IB MSG SDI Z UNKNOWN ERROR; SQLSTATE:

HY000 Message: %s

Error number: MY-013260; Symbol: ER IB MSG FOUND WRONG UNDO SPACE;

SQLSTATE: HY000

Message: Expected to find undo tablespace '%s' for Space ID=%lu, but found '%s' instead! Did you

change innodb undo directory?

Error number: MY-013261; Symbol: ER IB MSG NOT END WITH IBU; SQLSTATE: HY000

Message: Cannot use %s as an undo tablespace because it does not end with '.ibu'.

Error number: MY-013262; Symbol: ER IB MSG UNDO TRUNC EMPTY FILE; SQLSTATE:

HY000

Message: ib undo trunc empty file

Error number: MY-013263; Symbol: ER IB MSG UNDO TRUNC BEFOR DD UPDATE;

SQLSTATE: HY000

Message: ib undo trunc before dd update

Error number: MY-013264; Symbol:

ER IB MSG UNDO TRUNC BEFORE UNDO LOGGING; SQLSTATE: HY000

Message: ib undo trunc before done logging

Error number: MY-013265; Symbol: ER IB MSG UNDO TRUNK BEFORE RSEG;

SQLSTATE: HY000

Message: ib undo trunc before rsegs

Error number: MY-013266; Symbol: ER IB MSG FAILED TO FINISH TRUNCATE;

SQLSTATE: HY000

Message: %s Failed to finish truncating Undo Tablespace '%s'

Error number: MY-013267; Symbol:

ER IB MSG DEPRECATED INNODB UNDO TABLESPACES; SQLSTATE: HY000

Message: The setting INNODB UNDO TABLESPACES is deprecated and is no longer used. InnoDB always creates 2 undo tablespaces to start with. If you need more, please use CREATE

UNDO TABLESPACE.

Error number: MY-013268; Symbol: ER IB MSG DIR DOES NOT EXIST; SQLSTATE:

HY000

Message: The directory '%s' does not exist.

Error number: MY-013268; Symbol: ER IB MSG WRONG TABLESPACE DIR; SQLSTATE:

HY000

Message: The directory for tablespace %s does not exist or is incorrect.

Error number: MY-013269; Symbol: ER IB MSG LOCK FREE HASH USAGE STATS;

SQLSTATE: HY000

Message: %s

Error number: MY-013270; Symbol: ER CLONE REMOTE ERROR; SQLSTATE: HY000

Message: Clone Remote Error: %s.

Error number: MY-013270; Symbol: ER CLONE DONOR TRACE; SQLSTATE: HY000

Message: Clone donor reported: %s.

Error number: MY-013271; Symbol: ER CLONE PROTOCOL ERROR; SQLSTATE: HY000

Message: Clone Protocol Error: %s.

Error number: MY-013271; Symbol: ER CLONE PROTOCOL TRACE; SQLSTATE: HY000

Message: Clone received unexpected response from donor: %s.

Error number: MY-013272; Symbol: ER CLONE INFO CLIENT; SQLSTATE: HY000

Message: Client: %s.

Error number: MY-013272; Symbol: ER CLONE CLIENT TRACE; SQLSTATE: HY000

Message: Client: %s.

Error number: MY-013273; Symbol: ER CLONE INFO SERVER; SQLSTATE: HY000

Message: Server: %s.

Error number: MY-013273; Symbol: ER CLONE SERVER TRACE; SQLSTATE: HY000

Message: Server: %s.

Error number: MY-013274; Symbol: ER_THREAD_POOL_PFS_TABLES_INIT_FAILED;

SOLSTATE: HY000

Message: Failed to initialize the performance schema tables service.

Error number: MY-013275; Symbol: ER THREAD POOL PFS TABLES ADD FAILED;

SQLSTATE: HY000

Message: Failed to add thread pool performance schema tables.

Error number: MY-013276; Symbol: ER CANT SET DATA DIR; SQLSTATE: HY000

Message: Failed to set datadir to \'%s\' (OS errno: %d - %s)

Error number: MY-013277; Symbol:

ER INNODB INVALID INNODB UNDO DIRECTORY LOCATION; SQLSTATE: HY000

Message: The innodb undo directory is not allowed to be an ancestor of the datadir.

Error number: MY-013278; Symbol:

ER SERVER RPL ENCRYPTION FAILED TO FETCH KEY; SQLSTATE: HY000

Message: Failed to fetch key from keyring, please check if keyring is loaded.

Error number: MY-013279; Symbol: ER SERVER RPL ENCRYPTION KEY NOT FOUND;

SQLSTATE: HY000

Message: Can't find key from keyring, please check in the server log if a keyring is loaded and

initialized successfully.

Error number: MY-013280; Symbol:

ER SERVER RPL ENCRYPTION KEYRING INVALID KEY; SQLSTATE: HY000

Message: Fetched an invalid key from keyring.

Error number: MY-013281; Symbol: ER SERVER RPL ENCRYPTION HEADER ERROR;

SQLSTATE: HY000

Message: Error reading a replication log encryption header: %s.

Error number: MY-013282; Symbol:

ER SERVER RPL ENCRYPTION FAILED TO ROTATE LOGS; SQLSTATE: HY000

Message: Failed to rotate some logs after changing binlog encryption settings. Please fix the problem

and rotate the logs manually.

Error number: MY-013283; Symbol:

ER SERVER RPL ENCRYPTION KEY EXISTS UNEXPECTED; SQLSTATE: HY000

Message: Key %s exists unexpected.

Error number: MY-013284; Symbol:

ER_SERVER_RPL_ENCRYPTION_FAILED_TO_GENERATE_KEY; SQLSTATE: HY000

Message: Failed to generate key, please check if keyring is loaded.

Error number: MY-013285; Symbol:

ER SERVER RPL ENCRYPTION FAILED TO STORE KEY; SQLSTATE: HY000

Message: Failed to store key, please check if keyring is loaded.

Error number: MY-013286; Symbol:

ER SERVER RPL ENCRYPTION FAILED TO REMOVE KEY; SQLSTATE: HY000

Message: Failed to remove key, please check if keyring is loaded.

Error number: MY-013287; Symbol:

ER SERVER RPL ENCRYPTION MASTER KEY RECOVERY FAILED; SQLSTATE:

HY000

Message: Unable to recover binlog encryption master key, please check if keyring is loaded.

Error number: MY-013288; Symbol:

ER SERVER RPL ENCRYPTION UNABLE TO INITIALIZE; SQLSTATE: HY000

Message: Failed to initialize binlog encryption, please check if keyring is loaded.

Error number: MY-013289; Symbol:

ER SERVER RPL ENCRYPTION UNABLE TO ROTATE MASTER KEY AT STARTUP;

SQLSTATE: HY000

Message: Failed to rotate binlog encryption master key at startup, please check if keyring is loaded.

Error number: MY-013290; Symbol:

ER SERVER RPL ENCRYPTION IGNORE ROTATE MASTER KEY AT STARTUP;

SQLSTATE: HY000

Message: Ignoring binlog_rotate_encryption_master_key_at_startup because binlog_encryption

option is disabled.

Error number: MY-013291; Symbol: ER_INVALID_ADMIN_ADDRESS; SQLSTATE: HY000

Message: Invalid value for command line option admin-address: '%s'

Error number: MY-013292; Symbol: ER SERVER STARTUP_ADMIN_INTERFACE;

SQLSTATE: HY000

Message: Admin interface ready for connections, address: '%s' port: %d

Error number: MY-013293; Symbol: ER CANT CREATE ADMIN THREAD; SQLSTATE:

HY000

Message: Can't create thread to handle admin connections (errno= %d)

Error number: MY-013294; Symbol:

ER WARNING RETAIN CURRENT PASSWORD CLAUSE VOID; SQLSTATE: HY000

Message: RETAIN CURRENT PASSWORD ignored for user '%s'@'%s' as its authentication

plugin %s does not support multiple passwords.

Error number: MY-013295; Symbol:

ER WARNING DISCARD OLD PASSWORD CLAUSE VOID; SQLSTATE: HY000

Message: DISCARD OLD PASSWORD ignored for user '%s'@'%s' as its authentication plugin %s

does not support multiple passwords.

Error number: MY-013299; Symbol:

ER WARNING AUTHCACHE INVALID USER ATTRIBUTES; SQLSTATE: HY000

Message: Can not read and process value of User attributes column from mysql.user table for user:

'%s@%s'; Ignoring user.

Error number: MY-013300; Symbol:

ER MYSQL NATIVE PASSWORD SECOND PASSWORD USED INFORMATION;

SQLSTATE: HY000

Message: Second password was used for login by user: '%s'@'%s'.

Error number: MY-013301; Symbol:

ER SHA256 PASSWORD SECOND PASSWORD USED INFORMATION; SQLSTATE:

HY000

Message: Second password was used for login by user: '%s'@'%s'.

Error number: MY-013302; Symbol:

ER CACHING SHA2 PASSWORD SECOND PASSWORD USED INFORMATION;

SQLSTATE: HY000

Message: Second password was used for login by user: '%s'@'%s'.

Error number: MY-013303; Symbol:

ER GRP RPL SEND TRX PREPARED MESSAGE FAILED; SQLSTATE: HY000

Message: Error sending transaction '%d:%lld' prepared Message from session '%u'.

Error number: MY-013304; Symbol:

 $ER_GRP_RPL_RELEASE_COMMIT_AFTER_GROUP_PREPARE_FAILED; SQLSTATE:$

HY000

Message: Error releasing transaction '%d:%lld' for commit on session '%u' after being prepared on all

group members.

Error number: MY-013305; Symbol:

ER GRP RPL TRX ALREADY EXISTS ON TCM ON AFTER CERTIFICATION;

SQLSTATE: HY000

Message: Transaction '%d:%lld' already exists on Group Replication consistency manager while

being registered after conflict detection.

Error number: MY-013306; Symbol:

ER GRP RPL FAILED TO INSERT TRX ON TCM ON AFTER CERTIFICATION;

SQLSTATE: HY000

Message: Error registering transaction '%d:%lld' on Group Replication consistency manager after

conflict detection.

Error number: MY-013307; Symbol:

ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_GROUP_PREPARE_FAILED; SQLSTATE: HY000

Message: Error registering transaction '%d:%lld' from session '%u' to wait for being prepared on all group members.

Error number: MY-013308; Symbol:

ER GRP RPL TRX WAIT FOR GROUP PREPARE FAILED; SQLSTATE: HY000

Message: Error on transaction '%d:%lld' from session '%u' while waiting for being prepared on all group members.

Error number: MY-013309; Symbol:

ER_GRP_RPL_TRX_DOES_NOT_EXIST_ON_TCM_ON_HANDLE_REMOTE_PREPARE;

SQLSTATE: HY000

Message: Transaction '%d:%lld' does not exist on Group Replication consistency manager while receiving remote transaction prepare.

Error number: MY-013310; Symbol:

ER_GRP_RPL_RELEASE_BEGIN_TRX_AFTER_DEPENDENCIES_COMMIT_FAILED;

SQLSTATE: HY000

Message: Error releasing transaction '%d:%lld' for execution on session '%u' after its dependencies did complete commit.

Error number: MY-013311; Symbol:

ER_GRP_RPL_REGISTER_TRX_TO_WAIT_FOR_DEPENDENCIES_FAILED; SQLSTATE: HY000

Message: Error registering transaction from session '%u' to wait for its dependencies to complete commit.

Error number: MY-013312; Symbol: ER_GRP_RPL_WAIT_FOR_DEPENDENCIES_FAILED; SQLSTATE: HY000

Message: Error on session '%u' while waiting for its dependencies to complete commit.

Error number: MY-013313; Symbol:

ER GRP RPL REGISTER TRX TO WAIT FOR SYNC BEFORE EXECUTION FAILED;

SQLSTATE: HY000

Message: Error registering transaction from session '%u' to wait for sync before execution.

Error number: MY-013314; Symbol:

ER GRP RPL SEND TRX SYNC BEFORE EXECUTION FAILED; SQLSTATE: HY000

Message: Error sending sync before execution Message from session '%u'.

Error number: MY-013315; Symbol:

ER GRP RPL TRX WAIT FOR SYNC BEFORE EXECUTION FAILED; SQLSTATE:

HY000

Message: Error on transaction from session '%u' while waiting for sync before execution.

Error number: MY-013316; Symbol:

ER GRP RPL RELEASE BEGIN TRX AFTER WAIT FOR SYNC BEFORE EXEC;

SQLSTATE: HY000

Message: Error releasing transaction for execution on session '%u' after wait for sync before

execution.

Error number: MY-013317; Symbol:

ER GRP RPL_TRX_WAIT_FOR_GROUP_GTID_EXECUTED; SQLSTATE: HY000

Message: Error waiting for group executed transactions commit on session '%u'.

Error number: MY-013320; Symbol: ER WARN PROPERTY STRING PARSE FAILED;

SQLSTATE: HY000

Message: Could not parse key-value pairs in property string '%s'

Error number: MY-013321; Symbol: ER INVALID PROPERTY KEY; SQLSTATE: HY000

Message: Property key '%s' is invalid.

Error number: MY-013322; Symbol:

ER GRP RPL GTID SET EXTRACT ERROR DURING RECOVERY; SQLSTATE: HY000

Message: Error when extracting the group replication applier channel received transactions set.

Unable to ensure the execution of group transactions received during recovery.

Error number: MY-013323; Symbol:

ER SERVER RPL ENCRYPTION FAILED TO ENCRYPT; SQLSTATE: HY000

Message: Failed to encrypt content to write into binlog file: %s.

Error number: MY-013324; Symbol:

ER_CANNOT_GET_SERVER_VERSION_FROM_TABLESPACE_HEADER; SQLSTATE:

HY000

Message: Cannot get the server version number from the dictionary tablespace header.

Error number: MY-013325; Symbol:

ER CANNOT SET SERVER VERSION IN TABLESPACE HEADER; SQLSTATE: HY000

Message: Cannot set the server version number in the dictionary tablespace header.

Error number: MY-013326; Symbol: ER SERVER UPGRADE VERSION NOT SUPPORTED;

SQLSTATE: HY000

Message: Upgrading the server from server version '%u' is not supported.

Error number: MY-013327; Symbol: ER SERVER UPGRADE FROM VERSION; SQLSTATE:

HY000

Message: MySQL server upgrading from version '%u' to '%u'.

Error number: MY-013328; Symbol: ER GRP RPL ERROR ON CERT DB INSTALL;

SQLSTATE: HY000

Message: The certification information could not be set in this server: '%s'

Error number: MY-013329; Symbol: ER GRP RPL FORCE MEMBERS WHEN LEAVING;

SQLSTATE: HY000

Message: A request to force a new group membership was issued when the member is leaving the

group.

Error number: MY-013330; Symbol: ER TRG WRONG ORDER; SQLSTATE: HY000

Message: Trigger %s.%s for table %s.%s is listed in wrong order. Please drop and recreate all

triggers for the table.

Error number: MY-013332; Symbol: ER LDAP AUTH GRP SEARCH NOT SPECIAL HDL;

SQLSTATE: HY000

Message: Special handling for group search, {GA} not found

Error number: MY-013333; Symbol:

ER LDAP AUTH GRP USER OBJECT HAS GROUP INFO; SQLSTATE: HY000

Message: User group retrieval: User object has group information

Error number: MY-013334; Symbol:

ER LDAP AUTH GRP INFO FOUND IN MANY OBJECTS; SQLSTATE: HY000

Message: Group information found in multiple user objects. Search filter configuration is incorrect.

Error number: MY-013335; Symbol: ER LDAP AUTH GRP INCORRECT ATTRIBUTE;

SQLSTATE: HY000

Message: User group retrieval: no group attribute found. Incorrect group search attribute.

Error number: MY-013336; Symbol: ER LDAP AUTH GRP NULL ATTRIBUTE VALUE;

SQLSTATE: HY000

Message: User group retrieval: Group attribute values is NULL.

Error number: MY-013337; Symbol: ER LDAP AUTH GRP DN PARSING FAILED;

SOLSTATE: HY000

Message: User group retrieval: parsing DN failed.

Error number: MY-013338; Symbol: ER LDAP AUTH GRP OBJECT HAS USER INFO;

SQLSTATE: HY000

Message: User group retrieval: Group object has user information

Error number: MY-013339; Symbol: ER LDAP AUTH LDAPS; SQLSTATE: HY000

Message: Reserved port for ldaps using ldaps

Error number: MY-013340; Symbol: ER LDAP MAPPING GET USER PROXY; SQLSTATE:

HY000

Message: Get user proxy

Error number: MY-013341; Symbol: ER LDAP MAPPING USER DONT BELONG GROUP;

SQLSTATE: HY000

Message: Get user proxy: User doesn't belongs to any group, user name will be treated as

authenticated user.

Error number: MY-013342; Symbol: ER LDAP MAPPING INFO; SQLSTATE: HY000

Message: Get user proxy: configured mapping info: %s

Error number: MY-013343; Symbol: ER_LDAP_MAPPING_EMPTY_MAPPING; SQLSTATE:

HY000

Message: Get user proxy: User doesn't have group mapping information, First LDAP group will be

treated as authenticated user.

Error number: MY-013344; Symbol: ER LDAP MAPPING PROCESS MAPPING; SQLSTATE:

HY000

Message: Process group proxy mapping

Error number: MY-013345; Symbol: ER LDAP MAPPING CHECK DELIMI QUOTE;

SQLSTATE: HY000

Message: Check delimiter after quote

Error number: MY-013346; Symbol: ER LDAP MAPPING PROCESS DELIMITER;

SQLSTATE: HY000

Message: Processing delimiter

Error number: MY-013347; Symbol:

ER LDAP MAPPING PROCESS DELIMITER EQUAL NOT FOUND; SQLSTATE: HY000

Message: Processing delimiter, separator = not found, resetting position

Error number: MY-013348; Symbol:

ER LDAP MAPPING PROCESS DELIMITER TRY COMMA; SQLSTATE: HY000

Message: "Processing delimiter, failed to get data for = separator try for separator,."

Error number: MY-013349; Symbol:

ER LDAP MAPPING PROCESS DELIMITER COMMA NOT FOUND; SQLSTATE: HY000

Message: Processing delimiter, separator, not found, resetting position

Error number: MY-013350; Symbol:

ER_LDAP_MAPPING_NO_SEPEARATOR_END_OF_GROUP; SQLSTATE: HY000

Message: Processing delimiter: No mapping separator is found, end of group information

Error number: MY-013351; Symbol: ER LDAP MAPPING GETTING NEXT MAPPING;

SQLSTATE: HY000

Message: Getting next mapping information

Error number: MY-013352; Symbol: ER LDAP MAPPING PARSING CURRENT STATE;

SQLSTATE: HY000

Message: Parsing mapping, current state: %d delimiter char: %c

Error number: MY-013353; Symbol: ER LDAP MAPPING PARSING MAPPING INFO;

SQLSTATE: HY000

Message: Parsing mapping info, LDAP group: %s MySQL proxy: %s

Error number: MY-013354; Symbol: ER LDAP MAPPING PARSING ERROR; SQLSTATE:

HY000

Message: Mapping parsing error

Error number: MY-013355; Symbol: ER LDAP MAPPING TRIMMING SPACES; SQLSTATE:

HY000

Message: Trimming left spaces

Error number: MY-013356; Symbol: ER LDAP MAPPING IS QUOTE; SQLSTATE: HY000

Message: Checking if current characters is quote

Error number: MY-013357; Symbol: ER LDAP MAPPING NON DESIRED STATE;

SQLSTATE: HY000

Message: Not desired state or un-defined states.

Error number: MY-013358; Symbol: ER INVALID NAMED PIPE FULL ACCESS GROUP;

SQLSTATE: HY000

Message: Invalid value for named pipe full access group.

Error number: MY-013359; Symbol: ER_PREPARE_FOR_SECONDARY_ENGINE; SQLSTATE:

HY000

Message: Retry the statement using a secondary storage engine.

Error number: MY-013360; Symbol: ER SERVER WARN DEPRECATED; SQLSTATE: HY000

Message: '%s' is deprecated and will be removed in a future release. Please use %s instead

Error number: MY-013361; Symbol:

ER AUTH ID WITH SYSTEM USER PRIV IN MANDATORY ROLES; SQLSTATE:

HY000

Message: Cannot set mandatory_roles: AuthId `%s`@`%s` has '%s' privilege.

Error number: MY-013362; Symbol:

ER SERVER BINLOG MASTER KEY RECOVERY OUT OF COMBINATION;

SQLSTATE: HY000

Message: Unable to recover binary log master key, the combination of new_master_key_seqno=%u,

master_key_seqno=%u and old_master_key_seqno=%u are wrong.

Error number: MY-013363; Symbol:

ER SERVER BINLOG MASTER KEY ROTATION FAIL TO CLEANUP AUX KEY;

SQLSTATE: HY000

Message: Failed to remove auxiliary binary log encryption key from keyring, please check if keyring is loaded. The cleanup of the binary log master key rotation process did not finish as expected and the cleanup will take place upon server restart or next 'ALTER INSTANCE ROTATE BINLOG MASTER KEY' execution.

Error number: MY-013368; Symbol: ER_TURNING_ON_PARTIAL_REVOKES; SQLSTATE: HY000

Message: At least one partial revoke exists on a database. Turning ON the system variable '@@partial revokes'.

 $Error\ number:\ MY-013369;\ Symbol:\ ER_WARN_PARTIAL_REVOKE_AND_DB_GRANT;$

SOLSTATE: HY000

Message: For user '%s'@'%s', one or more privileges granted through mysql.db for database '%s', conflict with partial revoke. It could mean 'mysql' schema is corrupted.

Error number: MY-013370; Symbol:

ER_WARN_INCORRECT_PRIVILEGE_FOR_DB_RESTRICTIONS; SQLSTATE: HY000 Message: For user %s, ignored restrictions for privilege(s) '%s' for database '%s' as these are not valid database privileges.

Error number: MY-013371; Symbol: ER_WARN_INVALID_DB_RESTRICTIONS; SQLSTATE: HY000

Message: For user %s, ignored restrictions for privilege(s) '%s' for database '%s' as corresponding global privilege(s) are not granted.

Error number: MY-013372; Symbol:

ER_GRP_RPL_INVALID_COMMUNICATION_PROTOCOL; SQLSTATE: HY000

Message: '%s' is an invalid value for group_replication_communication_protocol_join, please use a MySQL version between 5.7.14 and this server's version

Error number: MY-013373; Symbol: ER_GRP_RPL_STARTED_AUTO_REJOIN; SQLSTATE: HY000

Message: Started auto-rejoin procedure attempt %lu of %lu

Error number: MY-013374; Symbol: ER_GRP_RPL_TIMEOUT_RECEIVED_VC_ON_REJOIN; SQLSTATE: HY000

Message: Timeout while waiting for a view change event during the auto-rejoin procedure

Error number: MY-013375; Symbol: ER_GRP_RPL_FINISHED_AUTO_REJOIN; SQLSTATE: HY000

Message: Auto-rejoin procedure attempt %lu of %lu finished. Member was%s able to join the group.

Error number: MY-013376; Symbol:

ER_GRP_RPL_DEFAULT_TABLE_ENCRYPTION_DIFF_FROM_GRP; SQLSTATE: HY000 Message: The member is configured with a default_table_encryption option value '%d' different from the group '%d'. The member will now exit the group.

Error number: MY-013377; Symbol: ER_SERVER_UPGRADE_OFF; SQLSTATE: HY000 Message: Server shutting down because upgrade is required, yet prohibited by the command line option '--upgrade=NONE'.

Error number: MY-013378; Symbol: ER_SERVER_UPGRADE_SKIP; SQLSTATE: HY000 Message: Server upgrade is required, but skipped by command line option '--upgrade=MINIMAL'.

Error number: MY-013379; Symbol: ER_SERVER_UPGRADE_PENDING; SQLSTATE: HY000 Message: Server upgrade started with version %d, but server upgrade of version %d is still pending.

Error number: MY-013380; Symbol: ER_SERVER_UPGRADE_FAILED; SQLSTATE: HY000 Message: Failed to upgrade server.

Error number: MY-013381; Symbol: ER_SERVER_UPGRADE_STATUS; SQLSTATE: HY000 Message: Server upgrade from '%d' to '%d' %s.

Error number: MY-013382; Symbol: ER SERVER UPGRADE REPAIR REQUIRED;

SQLSTATE: HY000

Message: Table '%s' requires repair.

Error number: MY-013383; Symbol: ER SERVER UPGRADE REPAIR STATUS; SQLSTATE:

HY000

Message: Table '%s' repair %s.

Error number: MY-013384; Symbol: ER_SERVER_UPGRADE_INFO_FILE; SQLSTATE: HY000 Message: Could not open server upgrade info file '%s' for writing. Please make sure the file is

writable.

2.12 错误码及错误信息汇总 12

Error number: MY-013385; Symbol: ER SERVER UPGRADE SYS SCHEMA; SQLSTATE:

HY000

Message: Upgrading the sys schema.

Error number: MY-013386; Symbol: ER SERVER UPGRADE MYSQL TABLES; SQLSTATE:

HY000

Message: Running queries to upgrade MySQL server.

Error number: MY-013387; Symbol: ER SERVER UPGRADE SYSTEM TABLES; SQLSTATE:

HY000

Message: Upgrading system table data.

Error number: MY-013388; Symbol: ER SERVER UPGRADE EMPTY SYS; SQLSTATE:

HY000

Message: Found empty sys database. Installing the sys schema.

Error number: MY-013389; Symbol: ER SERVER UPGRADE NO SYS VERSION;

SOLSTATE: HY000

Message: A sys schema exists with no sys.version view. If you have a user created sys schema, this

must be renamed for the upgrade to succeed.

Error number: MY-013390; Symbol: ER SERVER UPGRADE SYS VERSION EMPTY;

SQLSTATE: HY000

Message: A sys schema exists with a sys.version view, but it returns no results.

Error number: MY-013391; Symbol: ER SERVER UPGRADE SYS SCHEMA OUTDATED;

SQLSTATE: HY000

Message: Found outdated sys schema version %s.

Error number: MY-013392; Symbol: ER SERVER UPGRADE SYS SCHEMA UP TO DATE;

SQLSTATE: HY000

Message: The sys schema is already up to date (version %s).

Error number: MY-013393; Symbol:

ER SERVER UPGRADE SYS SCHEMA OBJECT COUNT; SQLSTATE: HY000

Message: Found %d sys %s, but expected %d. Re-installing the sys schema.

Error number: MY-013394; Symbol: ER_SERVER_UPGRADE_CHECKING_DB; SQLSTATE:

HY000

Message: Checking '%s' schema.

Error number: MY-013395; Symbol: ER IB MSG DDL LOG DELETE BY ID TMCT;

SQLSTATE: HY000

Message: Too many concurrent transactions while clearing the DDL Log. Please increase the number

of Rollback Segments.

Error number: MY-013396; Symbol: ER IB MSG POST RECOVER DDL LOG RECOVER;

SQLSTATE: HY000

Message: Error in DDL Log recovery during Post-Recovery processing.

Error number: MY-013397; Symbol: ER_IB_MSG_POST_RECOVER_POST_TS_ENCRYPT;

SQLSTATE: HY000

Message: Error in Post-Tablespace-Encryption during Post-Recovery processing.

Error number: MY-013398; Symbol: ER IB MSG DDL LOG FAIL POST DDL; SQLSTATE:

HY000

Message: Error in DLL Log cleanup during Post-DDL processing.

Error number: MY-013399; Symbol: ER SERVER BINLOG UNSAFE SYSTEM FUNCTION;

SQLSTATE: HY000

Message: '%s' statement is unsafe because it uses a system function that may return a different value

on the slave.

Error number: MY-013400; Symbol: ER SERVER UPGRADE HELP TABLE STATUS;

SQLSTATE: HY000

Message: Upgrade of help tables %s.

 $Error\ number:\ MY-013401;\ Symbol:\ ER_GRP_RPL_SRV_GTID_WAIT_ERROR;\ SQLSTATE:$

HY000

Message: Error when waiting for the server to execute local transactions in order assure the group

change proper logging

Error number: MY-013402; Symbol: ER_GRP_DELAYED_VCLE_LOGGING; SQLSTATE:

HY000

Message: Unable to log the group change View log event in its exaction position in the log. This will

not however affect the group replication recovery process or the overall plugin process.

Error number: MY-013404; Symbol:

ER_BINLOG_UNABLE_TO_ROTATE_GTID_TABLE_READONLY; SQLSTATE: HY000

Message: Unable to create a new binlog file: Table 'mysql.gtid executed' couldn't be opened. %s

Error number: MY-013405; Symbol: ER NETWORK NAMESPACES NOT SUPPORTED;

SQLSTATE: HY000

Message: Network Namespaces is not supported on this platform

Error number: MY-013406; Symbol: ER UNKNOWN NETWORK NAMESPACE; SQLSTATE:

HY000

Message: Unknown network namespace '%s'

Error number: MY-013407; Symbol:

ER NETWORK NAMESPACE NOT ALLOWED FOR WILDCARD ADDRESS; SQLSTATE:

HY000

Message: Network namespace not allowed for wildcard interface address

Error number: MY-013408; Symbol: ER SETNS FAILED; SQLSTATE: HY000

Message: setns() failed with error '%s'

Error number: MY-013409; Symbol:

ER WILDCARD NOT ALLOWED FOR MULTIADDRESS BIND; SQLSTATE: HY000

Message: Wildcard address value not allowed for multivalued bind address

Error number: MY-013410; Symbol: ER NETWORK NAMESPACE FILE PATH TOO LONG;

SQLSTATE: HY000

Message: The path to a special network namespace file is too long. (got %u > max %u)

Error number: MY-013411; Symbol: ER IB MSG TOO LONG PATH; SQLSTATE: HY000

Message: Cannot create tablespace '%s'. The filepath is too long for this OS.

Error number: MY-013412; Symbol: ER IB RECV FIRST REC GROUP INVALID;

SOLSTATE: HY000

Message: The last block of redo had corrupted first rec group and became fixed (%u -> %u).

Error number: MY-013413; Symbol: ER_DD_UPGRADE_COMPLETED; SQLSTATE: HY000

Message: Data dictionary upgrade from version '%u' to '%u' completed.

Error number: MY-013414; Symbol: ER SSL SERVER CERT VERIFY FAILED; SQLSTATE:

HY000

Message: Server SSL certificate doesn't verify: %s

Error number: MY-013415; Symbol: ER_PERSIST_OPTION_USER_TRUNCATED; SQLSTATE:

HY000

Message: Truncated a user name for %s that was too long while reading the persisted variables file

Error number: MY-013416; Symbol: ER_PERSIST_OPTION_HOST_TRUNCATED; SQLSTATE:

HY000

Message: Truncated a host name for %s that was too long while reading the persisted variables file

Error number: MY-013417; Symbol: ER NET WAIT ERROR; SQLSTATE: HY000

Message: The wait timeout period was exceeded, the idle time since last command was too long.

Error number: MY-013418; Symbol: ER IB MSG 1285; SQLSTATE: HY000

Message: '%s' found not encrypted while '%s' is ON. Trying to encrypt it now.

Error number: MY-013419; Symbol: ER IB MSG CLOCK MONOTONIC UNSUPPORTED;

SOLSTATE: HY000

Message: CLOCK MONOTONIC is unsupported, so do not change the system time when MySQL

is running!

Error number: MY-013420; Symbol: ER IB MSG CLOCK GETTIME FAILED; SQLSTATE:

HY000

Message: clock gettime() failed: %s

Error number: MY-013421; Symbol: ER PLUGIN NOT EARLY DUP; SQLSTATE: HY000

Message: Plugin '%s' is not to be used as an "early" plugin. Don't add it to --early-plugin-load,

keyring migration etc.

Error number: MY-013422; Symbol: ER PLUGIN NO INSTALL DUP; SQLSTATE: HY000

Message: Plugin '%s' is marked as not dynamically installable. You have to stop the server to install

it.

Error number: MY-013425; Symbol:

ER_BINLOG_UNSAFE_DEFAULT_EXPRESSION_IN_SUBSTATEMENT; SQLSTATE: HY000 Message: The statement is unsafe because it invokes a trigger or a stored function that modifies a table that has a column with a DEFAULT expression that may return a different value on the slave.

Error number: MY-013426; Symbol: ER GRP RPL MEMBER VER READ COMPATIBLE;

SQLSTATE: HY000

Message: Member version is read compatible with the group.

Error number: MY-013427; Symbol: ER_LOCK_ORDER_INIT_FAILED; SQLSTATE: HY000 Message: Lock order disabled (reason: init failed).

Error number: MY-013428; Symbol:

ER AUDIT LOG KEYRING ID TIMESTAMP VALUE IS INVALID; SQLSTATE: HY000

Message: Keyring ID timestamp value is invalid: '%s'

Error number: MY-013429; Symbol:

ER AUDIT LOG FILE NAME TIMESTAMP VALUE IS MISSING OR INVALID;

SQLSTATE: HY000

Message: Cannot process audit log file. File name timestamp value is missing or invalid: '%s'

Error number: MY-013430; Symbol:

 $ER_AUDIT_LOG_FILE_NAME_DOES_NOT_HAVE_REQUIRED_FORMAT; SQLSTATE:$

HY000

Message: Cannot process audit log file. File name does not have required format: '%s'

Error number: MY-013431; Symbol:

ER AUDIT LOG FILE NAME KEYRING ID VALUE IS MISSING; SQLSTATE: HY000

Message: Cannot process audit log file. File name keyring ID value is missing: '%s'

Error number: MY-013432; Symbol:

ER AUDIT LOG FILE HAS BEEN SUCCESSFULLY PROCESSED; SQLSTATE: HY000

Message: Audit log file has been successfully processed: '%s'

Error number: MY-013433; Symbol:

ER AUDIT LOG COULD NOT OPEN FILE FOR READING; SQLSTATE: HY000

Message: Could not open audit log file for reading: '%s'

Error number: MY-013434; Symbol: ER AUDIT LOG INVALID FILE CONTENT;

SQLSTATE: HY000

Message: Invalid audit log file content: '%s'

Error number: MY-013435; Symbol: ER_AUDIT_LOG_CANNOT_READ_PASSWORD;

SQLSTATE: HY000

Message: Cannot read password: '%s'.

Error number: MY-013436; Symbol: ER AUDIT LOG CANNOT STORE PASSWORD;

SQLSTATE: HY000

Message: Cannot store password: '%s'.

Error number: MY-013437; Symbol: ER AUDIT LOG CANNOT REMOVE PASSWORD;

SQLSTATE: HY000

Message: Cannot remove password: '%s'.

Error number: MY-013438; Symbol: ER_AUDIT_LOG_PASSWORD_HAS_BEEN_COPIED;

SQLSTATE: HY000

Message: 'audit_log' password has been copied into '%s' and will be removed with first purged

password.

Error number: MY-013447; Symbol: ER_LDAP_EMPTY_USERDN_PASSWORD; SQLSTATE:

HY000

Message: Empty user dn or password is not allowed, not attempting LDAP bind.

Error number: MY-013449; Symbol: ER ACL WRONG OR MISSING ACL TABLES LOG;

SQLSTATE: HY000

Message: The current layout of the ACL tables does not conform to the server's expected layout. They're either altered, missing or not upgraded from a previous version. However a best effort

attempt to read data from these tables will still be made.

Error number: MY-013450; Symbol: ER_LOCK_ORDER_FAILED_WRITE_FILE; SQLSTATE:

HY000

Message: LOCK ORDER: Failed to write to file <%s>.

Error number: MY-013451; Symbol: ER LOCK ORDER FAILED READ FILE; SQLSTATE:

HY000

Message: LOCK ORDER: Failed to read from file <%s>.

Error number: MY-013452; Symbol: ER LOCK ORDER MESSAGE; SQLSTATE: HY000

Message: LOCK ORDER Message: %s

Error number: MY-013453; Symbol: ER LOCK ORDER DEPENDENCIES SYNTAX;

SOLSTATE: HY000

Message: Lock order dependencies file <%s> (%d:%d) - (%d:%d) : %s

Error number: MY-013454; Symbol: ER_LOCK_ORDER_SCANNER_SYNTAX; SQLSTATE:

HY000

Message: Lock order scanner: (%d:%d) - (%d:%d) : %s

Error number: MY-013455; Symbol: ER_DATA_DIRECTORY_UNUSABLE_DELETABLE;

SQLSTATE: HY000

Message: The newly created data directory %s by --initialize is unusable. You can remove it.

Error number: MY-013456; Symbol: ER_IB_MSG_BTREE_LEVEL_LIMIT_EXCEEDED; SQLSTATE: HY000

Message: No. of B-tree level created for index %s has crossed the permissible limit. If debug option innodb_limit_optimistic_insert_debug is being used try tweaking it to include more records in a page.

Error number: MY-013457; Symbol: ER_IB_CLONE_START_STOP; SQLSTATE: HY000 Message: %s

Error number: MY-013458; Symbol: ER_IB_CLONE_OPERATION; SQLSTATE: HY000 Message: %s

Error number: MY-013459; Symbol: ER_IB_CLONE_RESTART; SQLSTATE: HY000 Message: %s

Error number: MY-013460; Symbol: ER_IB_CLONE_USER_DATA; SQLSTATE: HY000 Message: Clone removing all user data for provisioning: %s

Error number: MY-013461; Symbol: ER_IB_CLONE_NON_INNODB_TABLE; SQLSTATE: HY000

Message: Non innodb table: %s.%s is not cloned and is empty.

Error number: MY-013462; Symbol: ER_CLONE_SHUTDOWN_TRACE; SQLSTATE: HY000 Message: Clone shutting down server as RESTART failed. Please start server to complete clone operation.

Error number: MY-013463; Symbol: ER_GRP_RPL_GTID_PURGED_EXTRACT_ERROR; SQLSTATE: HY000

Message: Error when extracting this member GTID purged set. Operations and checks made to group joiners may be incomplete.

Error number: MY-013464; Symbol: ER_GRP_RPL_CLONE_PROCESS_PREPARE_ERROR; SQLSTATE: HY000

Message: There was an issue when configuring the remote cloning process: %s

Error number: MY-013465; Symbol: ER GRP RPL CLONE PROCESS EXEC ERROR;

SQLSTATE: HY000

Message: There was an issue when cloning from another server: %s

Error number: MY-013466; Symbol: ER GRP RPL RECOVERY EVAL ERROR; SQLSTATE:

HY000

Message: There was an issue when trying to evaluate the best distributed recovery strategy while

joining.%s

Error number: MY-013467; Symbol: ER GRP RPL NO POSSIBLE RECOVERY; SQLSTATE:

HY000

Message: No valid or ONLINE members exist to get the missing data from the group. For cloning check if donors of the same version and with clone plugin installed exist. For incremental recovery check if you have donors where the required data was not purged from the binary logs.

Error number: MY-013468; Symbol: ER GRP RPL CANT KILL THREAD; SQLSTATE: HY000

Message: The group replication plugin could not kill the plugin routine for %s. %s

Error number: MY-013469; Symbol:

ER GRP RPL RECOVERY STRAT CLONE THRESHOLD; SQLSTATE: HY000

Message: This member will start distributed recovery using clone. It is due to the number of missing

transactions being higher than the configured threshold of %llu.

Error number: MY-013470; Symbol: ER GRP RPL RECOVERY STRAT CLONE PURGED;

SOLSTATE: HY000

Message: This member will start distributed recovery using clone. It is due to no ONLINE member

has the missing data for recovering in its binary logs.

Error number: MY-013471; Symbol: ER GRP RPL RECOVERY STRAT CHOICE;

SQLSTATE: HY000

Message: Distributed recovery will transfer data using: %s

Error number: MY-013472; Symbol: ER GRP RPL RECOVERY STRAT FALLBACK;

SQLSTATE: HY000

Message: Due to some issue on the previous step distributed recovery is now executing: %s

Error number: MY-013473; Symbol: ER GRP RPL RECOVERY STRAT NO FALLBACK;

SQLSTATE: HY000

Message: Due to a critical cloning error or lack of donors, distributed recovery cannot be executed. The member will now leave the group.

Error number: MY-013474; Symbol: ER_GRP_RPL_SLAVE_THREAD_ERROR_ON_CLONE; SOLSTATE: HY000

Message: The '%s' thread of channel '%s' will error out as the server will attempt to clone another

server

Error number: MY-013475; Symbol: ER_UNKNOWN_TABLE_IN_UPGRADE; SQLSTATE:

HY000

Message: Unknown table '%s'

Error number: MY-013476; Symbol: ER_IDENT_CAUSES_TOO_LONG_PATH_IN_UPGRADE;

SQLSTATE: HY000

Message: Long database name and identifier for object resulted in path length exceeding %d

characters. Path: '%s'.

Error number: MY-013477; Symbol: ER XA CANT CREATE MDL BACKUP; SQLSTATE:

HY000

Message: XA: Failed to take MDL Lock backup of PREPARED XA transaction during client

disconnect.

Error number: MY-013478; Symbol: ER AUDIT LOG SUPER PRIVILEGE REQUIRED;

SQLSTATE: HY000

Message: SUPER privilege or AUDIT ADMIN role required for '%s'@'%s' user.

Error number: MY-013479; Symbol: ER AUDIT LOG UDF INVALID ARGUMENT TYPE;

SOLSTATE: HY000

Message: Invalid argument type

Error number: MY-013480; Symbol: ER AUDIT LOG UDF INVALID ARGUMENT COUNT;

SQLSTATE: HY000

Message: Invalid argument count

Error number: MY-013481; Symbol: ER AUDIT LOG HAS NOT BEEN INSTALLED;

SQLSTATE: HY000

Message: audit log plugin has not been installed using INSTALL PLUGIN syntax.

Error number: MY-013482; Symbol:

ER AUDIT LOG UDF READ INVALID MAX ARRAY LENGTH ARG TYPE; SQLSTATE:

HY000

Message: Invalid "max array length" argument type.

Error number: MY-013483; Symbol: ER LOG CANNOT WRITE EXTENDED; SQLSTATE:

HY000

Message: Failed to write to %s: %s (%s)

Error number: MY-013484; Symbol:

ER UPGRADE WITH PARTITIONED TABLES REJECTED; SQLSTATE: HY000

Message: Upgrading from server version %d with partitioned tables and lower_case_table_names == 1 on a case sensitive file system may cause issues, and is therefore prohibited. To upgrade anyway, restart the new server version with the command line option 'upgrade=FORCE'. When upgrade is completed, please execute 'RENAME TABLE <part_table_name> TO <new_table_name>; RENAME TABLE <new_table_name> TO <part_table_name>;' for each of the partitioned tables. Please see the documentation for further information.

Error number: MY-013485; Symbol: ER_KEYRING_AWS_INCORRECT_PROXY; SQLSTATE:

HY000

Message: Incorrect environment variable %s, invalid port: %s

Error number: MY-013486; Symbol:

ER_GRP_RPL_SERVER_SET_TO_OFFLINE_MODE_DUE_TO_ERRORS; SQLSTATE: HY000

Message: The server was automatically set into offline mode after an error was detected.

 $Error\ number:\ MY-013487;\ Symbol:\ ER_GRP_RPL_MESSAGE_SERVICE_FATAL_ERROR;$

SQLSTATE: HY000

Message: A Message sent through the Group Replication Message deliver service was not delivered successfully. The server will now leave the group. Try to add the server back to the group and check if the problem persists, or check previous Messages in the log for hints of what could be the problem.

Error number: MY-013488; Symbol:

ER WARN WRONG COMPRESSION ALGORITHM LOG; SQLSTATE: HY000

Message: Invalid MASTER_COMPRESSION_ALGORITHMS '%s' found in repository for channel

'%s'. Resetting to 'uncompressed' (no compression).

Error number: MY-013489; Symbol: ER WARN WRONG COMPRESSION LEVEL LOG;

SQLSTATE: HY000

Message: Invalid MASTER ZSTD COMPRESSION LEVEL found in repository for channel '%s'.

Resetting to %u.

Error number: MY-013490; Symbol: ER PROTOCOL COMPRESSION RESET LOG;

SQLSTATE: HY000

Message: Option --protocol-compression-algorithms is reset to default value.

Error number: MY-013491; Symbol: ER XPLUGIN COMPRESSION ERROR; SQLSTATE:

HY000

Message: Fatal error while compressing outgoing data - %s

Error number: MY-013492; Symbol: ER MYSOLBACKUP MSG; SOLSTATE: HY000

Message: %s

Error number: MY-013493; Symbol: ER WARN UNKNOWN KEYRING AWS REGION;

SQLSTATE: HY000

Message: Unknown keyring aws region '%s'. Connection to AWS KMS may fail.

Error number: MY-013494; Symbol:

ER_WARN_LOG_PRIVILEGE_CHECKS_USER_DOES_NOT_EXIST; SQLSTATE: HY000 Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to `%s`@`%s`, but this is not an existing user. Correct this before starting replication threads.

Error number: MY-013495; Symbol:

ER_WARN_LOG_PRIVILEGE_CHECKS_USER_CORRUPT; SQLSTATE: HY000

Message: Invalid, corrupted PRIVILEGE_CHECKS_USER was found in the replication

configuration repository for channel '%s'. Use CHANGE MASTER TO

PRIVILEGE CHECKS USER to correct the configuration.

Error number: MY-013496; Symbol:

ER_WARN_LOG_PRIVILEGE_CHECKS_USER_NEEDS_RPL_APPLIER_PRIV; SQLSTATE: HY000

Message: PRIVILEGE_CHECKS_USER for replication channel '%s' was set to `%s`@`%s`, but this user does not have REPLICATION_APPLIER privilege. Correct this before starting the replication threads.

Error number: MY-013497; Symbol: ER_FILE_PRIVILEGE_FOR_REPLICATION_CHECKS; SOLSTATE: HV000

SQLSTATE: HY000

Message: The PRIVILEGE_CHECKS_USER for channel '%s' would need FILE privilege to execute a LOAD DATA INFILE statement replicated in statement format. Consider using

binlog_format=ROW on master. If the replicated events are trusted, recover from the failure by temporarily granting FILE to the PRIVILEGE CHECKS USER.

Error number: MY-013498; Symbol:

Message: Slave SQL thread%s initialized, starting replication in log '%s' at position %s, relay log '%s' position: %s, user: '%s'@'%s', roles: %s

Error number: MY-013499; Symbol: ER AUDIT LOG CANNOT GENERATE PASSWORD;

SOLSTATE: HY000

Message: Cannot generate password: '%s'

Error number: MY-013500; Symbol: ER INIT FAILED TO GENERATE ROOT PASSWORD;

SQLSTATE: HY000

Message: Failed to generate a random password for root. Probabably not enough enthropy.

Error number: MY-013501; Symbol: ER_PLUGIN_LOAD_OPTIONS_IGNORED; SQLSTATE:

HY000

Message: Ignoring --plugin-load[add] list as the server is running with --initialize(-insecure).

Error number: MY-013502; Symbol:

ER WARN AUTH ID WITH SYSTEM USER PRIV IN MANDATORY ROLES;

SQLSTATE: HY000

Message: Cannot set mandatory roles: AuthId '%s'@'%s' has '%s' privilege. AuthId(s) set in the

mandatory roles are ignored.

Error number: MY-013503; Symbol: ER IB MSG SKIP HIDDEN DIR; SQLSTATE: HY000

Message: Directory '%s' will not be scanned because it is a hidden directory.

Error number: MY-013504; Symbol:

ER WARN RPL RECOVERY NO ROTATE EVENT FROM MASTER EOF; SQLSTATE:

HY000

Message: Server was not able to find a rotate event from master server to initialize relay log recovery

for channel '%s'. Skipping relay log recovery for the channel.

Error number: MY-013505; Symbol: ER_IB_LOB_ROLLBACK_INDEX_LEN; SQLSTATE:

HY000

Message: Rolling back LOB for transaction %llu undo number %llu: current index length %llu.

(iteration %llu)

Error number: MY-013506; Symbol:

ER CANT PROCESS EXPRESSION FOR GENERATED COLUMN TO DD; SQLSTATE:

HY000

Message: Error in processing (possibly deprecated) expression or function '%s' for generated

column %s.%s.%s

Error number: MY-013507; Symbol:

ER RPL SLAVE QUEUE EVENT FAILED INVALID NON ROW FORMAT; SQLSTATE:

HY000

Message: The queue event failed for channel '%s' as an invalid event according to REQUIRE ROW FORMAT was found.

Error number: MY-013508; Symbol:

ER RPL SLAVE APPLY LOG EVENT FAILED INVALID NON ROW FORMAT;

SQLSTATE: HY000

Message: The application of relay events failed for channel '%s' as an invalid event according to

REQUIRE ROW FORMAT was found.

Error number: MY-013509; Symbol:

ER_LOG_PRIV_CHECKS_REQUIRE_ROW_FORMAT_NOT_SET; SQLSTATE: HY000 Message: PRIVILEGE_CHECKS_USER for replication channel '%s' can't be set to `%s`@`%s` unless REQUIRE_ROW_FORMAT is also set to %d.

Error number: MY-013510; Symbol:

ER RPL SLAVE SQL THREAD DETECTED UNEXPECTED EVENT SEQUENCE;

SQLSTATE: HY000

Message: An unexpected event sequence was detected by the SQL thread while applying an event.

Error number: MY-013511; Symbol: ER_IB_MSG_UPGRADE_PARTITION_FILE; SQLSTATE: HY000

Message: Updating partition file name '%s' to '%s' and all other partition files during upgrade

Error number: MY-013512; Symbol: ER IB MSG DOWNGRADE PARTITION FILE;

SOLSTATE: HY000

Message: Updating partition file name '%s' to '%s' and all other partition files during downgrade

Error number: MY-013513; Symbol: ER_IB_MSG_UPGRADE_PARTITION_FILE_IMPORT;

SQLSTATE: HY000

Message: Updating partition file name '%s' to '%s' for import

Error number: MY-013514; Symbol: ER_IB_WARN_OPEN_PARTITION_FILE; SQLSTATE:

HY000

Message: Unable to open partition file with new name '%s'. Please check if innodb_directories is set

to include all external file paths

Error number: MY-013515; Symbol: ER IB MSG FIL STATE MOVED CORRECTED;

SQLSTATE: HY000

Message: %s DD ID: %llu - Partition tablespace %u, name '%s' is corrected to '%s'

Error number: MY-013516; Symbol: ER IB MSG FIL STATE MOVED CHANGED PATH;

SQLSTATE: HY000

Message: %s DD ID: %llu - Tablespace %u, name '%s', '%s' is moved to '%s'

Error number: MY-013517; Symbol: ER IB MSG FIL STATE MOVED CHANGED NAME;

SQLSTATE: HY000

Message: %s DD ID: %llu - Partition tablespace %u, name '%s', '%s' is updated to '%s'

Error number: MY-013518; Symbol: ER IB MSG FIL STATE MOVED TOO MANY;

SQLSTATE: HY000

Message: %s Too many files have been moved, disabling logging of detailed Messages

Error number: MY-013519; Symbol: ER GR ELECTED PRIMARY GTID INFORMATION;

SQLSTATE: HY000

Message: Elected primary member %s: %s

Error number: MY-013520; Symbol:

ER SCHEMA NAME IN UPPER CASE NOT ALLOWED; SQLSTATE: HY000

Message: Schema name '%s' containing upper case characters is not allowed with

lower case table names = 1.

Error number: MY-013521; Symbol: ER TABLE NAME IN UPPER CASE NOT ALLOWED;

SQLSTATE: HY000

Message: Table name '%s.%s' containing upper case characters is not allowed with

lower case table names = 1.

Error number: MY-013522; Symbol:

 $ER_SCHEMA_NAME_IN_UPPER_CASE_NOT_ALLOWED_FOR_FK; SQLSTATE: HY000$

Message: Schema name '%s' containing upper case characters, used by foreign key '%s' in table

'%s.%s', is not allowed with lower case table names = 1.

Error number: MY-013523; Symbol:

ER TABLE NAME IN UPPER CASE NOT ALLOWED FOR FK; SQLSTATE: HY000

Message: Table name '%s.%s' containing upper case characters, used by foreign key '%s' in table

'%s.%s', is not allowed with lower case table names = 1.

Error number: MY-013524; Symbol: ER IB MSG DICT PARTITION NOT FOUND;

SQLSTATE: HY000

Message: Table Partition: %s is not found in InnoDB dictionary

Error number: MY-013525; Symbol:

ER ACCESS DENIED FOR USER ACCOUNT BLOCKED BY PASSWORD LOCK;

SQLSTATE: HY000

Message: Access denied for user '%s'@'%s'. Account is blocked for %s day(s) (%s day(s) remaining) due to %u consecutive failed logins. Use FLUSH PRIVILEGES or ALTER USER to reset.

Error number: MY-013526; Symbol: ER_INNODB_OUT_OF_RESOURCES; SQLSTATE: HY000 Message: %s

Error number: MY-013527; Symbol:

ER DD UPGRADE FOUND PREPARED XA TRANSACTION; SQLSTATE: HY000

Message: Upgrade cannot proceed due to an existing prepared XA transaction.

Error number: MY-013528; Symbol: ER_MIGRATE_TABLE_TO_DD_OOM; SQLSTATE: HY000

Message: Could not allocate memory for key info when migrating table %s.%s

Error number: MY-013529; Symbol:

ER_RPL_RELAY_LOG_RECOVERY_INFO_AFTER_CLONE; SQLSTATE: HY000 Message: Relay log information for channel '%s' was found after a clone operation. Relay log recovery will be executed to adjust positions and file information for this new server. Should that automatic procedure fail please adjust the positions through 'CHANGE MASTER TO'

Error number: MY-013530; Symbol: ER_IB_MSG_57_UNDO_SPACE_DELETE_FAIL; SQLSTATE: HY000

Message: Failed to delete 5.7 undo tablespace: %s during upgrade

Error number: MY-013531; Symbol: ER_IB_MSG_DBLWR_1285; SQLSTATE: HY000 Message: Empty doublewrite file: %s

Error number: MY-013532; Symbol: ER_IB_MSG_DBLWR_1286; SQLSTATE: HY000 Message: Using '%s' for doublewrite

Error number: MY-013533; Symbol: ER_IB_MSG_DBLWR_1287; SQLSTATE: HY000 Message: Error reading doublewrite buffer from the system tablespace

Error number: MY-013534; Symbol: ER_IB_MSG_DBLWR_1288; SQLSTATE: HY000 Message: Cannot create doublewrite buffer: you must increase your buffer pool size. Cannot continue operation.

Error number: MY-013535; Symbol: ER_IB_MSG_DBLWR_1290; SQLSTATE: HY000 Message: The page in the doublewrite file is corrupt. Cannot continue operation. You can try to recover the database with innodb force recovery=6

Error number: MY-013536; Symbol: ER IB MSG BAD DBLWR FILE NAME; SQLSTATE:

HY000

Message: The doublewrite filename '%s' is incorrect.

Error number: MY-013538; Symbol: ER IB MSG DBLWR 1293; SQLSTATE: HY000

Message: Doublewrite file create failed: %s

Error number: MY-013539; Symbol: ER IB MSG DBLWR 1294; SQLSTATE: HY000

Message: DBLWRThread: pthread setaffinity() failed!

Error number: MY-013542; Symbol: ER IB MSG DBLWR 1297; SQLSTATE: HY000

Message: Doublewrite file read failed: %s

Error number: MY-013543; Symbol: ER IB MSG DBLWR 1298; SQLSTATE: HY000

Message: Dump of the data file page:

Error number: MY-013561; Symbol: ER IB MSG DBLWR 1319; SQLSTATE: HY000

Message: Doublewrite load file %s size %lu is not a multiple of the configured page size %lu"

Error number: MY-013562; Symbol: ER IB MSG DBLWR 1320; SQLSTATE: HY000

Message: Doublewrite file %s truncate failed

Error number: MY-013563; Symbol: ER IB MSG DBLWR 1321; SQLSTATE: HY000

Message: Doublewrite file %s failed to writ zeros

Error number: MY-013564; Symbol: ER IB MSG DBLWR 1322; SQLSTATE: HY000

Message: Doublewrite create file %s size %lu is not a multiple of the configured page size %lu"

Error number: MY-013570; Symbol: ER IB MSG GTID FLUSH AT SHUTDOWN;

SQLSTATE: HY000

Message: Could not flush all GTIDs during slow shutdown. Will recover GTIDs when server

restarts.

Error number: MY-013571; Symbol: ER IB MSG 57 STAT SPACE DELETE FAIL;

SQLSTATE: HY000

Message: Failed to delete 5.7 stat tablespace: %s during upgrade

Error number: MY-013575; Symbol: ER IB MSG CREATE LOG FILE; SQLSTATE: HY000

Message: Creating log file %s

Error number: MY-013576; Symbol: ER IB MSG INNODB START INITIALIZE; SQLSTATE:

HY000

Message: InnoDB initialization has started.

Error number: MY-013577; Symbol: ER_IB_MSG_INNODB_END_INITIALIZE; SQLSTATE:

HY000

Message: InnoDB initialization has ended.

Error number: MY-013578; Symbol: ER IB MSG PAGE ARCH NO RESET POINTS;

SQLSTATE: HY000

Message: Could not find appropriate reset points.

Error number: MY-013579; Symbol: ER IB WRN PAGE ARCH FLUSH DATA; SQLSTATE:

HY000

Message: Unable to flush. Page archiving data may be corrupt in case of a crash.

Error number: MY-013580; Symbol:

ER IB ERR PAGE ARCH INVALID DOUBLE WRITE BUF; SQLSTATE: HY000

Message: Page archiver's doublewrite buffer for %ld is not valid.

Error number: MY-013581; Symbol: ER IB ERR PAGE ARCH RECOVERY FAILED;

SQLSTATE: HY000

Message: Page archiver system's recovery failed.

Error number: MY-013582; Symbol: ER IB ERR PAGE ARCH INVALID FORMAT;

SQLSTATE: HY000

Message: Invalid archived file name format. The archived file is supposed to have the format %s +

[0-9]*.

Error number: MY-013583; Symbol: ER_INVALID_XPLUGIN_SOCKET_SAME_AS_SERVER;

SQLSTATE: HY000

Message: X Plugins UNIX socket must use different file than MySQL server. X Plugin won't be

accessible through UNIX socket

Error number: MY-013584; Symbol: ER_INNODB_UNABLE_TO_ACQUIRE_DD_OBJECT;

SOLSTATE: HY000

Message: %s

Error number: MY-013585; Symbol:

ER WARN LOG DEPRECATED PARTITION PREFIX KEY; SQLSTATE: HY000

Message: Column '%s.%s.%s' having prefix key part '%s(%u)' is ignored by the partitioning

function. Use of prefixed columns in the PARTITION BY KEY() clause is deprecated and will be

removed in a future release.

Error number: MY-013586; Symbol: ER IB MSG UNDO TRUNCATE TOO OFTEN;

SOLSTATE: HY000

Message: Undo Truncation is occurring too often. Consider increasing --innodb-max-undo-log-size.

Error number: MY-013587; Symbol: ER GRP RPL IS STARTING; SQLSTATE: HY000

Message: Plugin 'group replication' is starting.

Error number: MY-013588; Symbol: ER_IB_MSG_INVALID_LOCATION_FOR_TABLESPACE;

SQLSTATE: HY000

Message: Cannot create tablespace %s because the directory is not a valid location. %s

Error number: MY-013589; Symbol: ER IB MSG INVALID LOCATION WRONG DB;

SQLSTATE: HY000

Message: Scanned file '%s' for tablespace %s cannot be opened because it is not in a sub-directory

named for the schema.

Error number: MY-013590; Symbol: ER IB MSG CANNOT FIND DD UNDO SPACE;

SQLSTATE: HY000

Message: Cannot find undo tablespace %s with filename '%s' as indicated by the Data Dictionary.

Did you move or delete this tablespace? Any undo logs in it cannot be used.

Error number: MY-013591; Symbol: ER_GRP_RPL_RECOVERY_ENDPOINT_FORMAT;

SOLSTATE: HY000

Message: Invalid input value for recovery socket endpoints '%s'. Please, provide a valid, comma

separated, list of endpoints (IP:port)

Error number: MY-013592; Symbol: ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID;

SOLSTATE: HY000

Message: The server is not listening on endpoint '%s'. Only endpoints that the server is listening on

are valid recovery endpoints.

Error number: MY-013593; Symbol:

ER_GRP_RPL_RECOVERY_ENDPOINT_INVALID_DONOR_ENDPOINT; SQLSTATE:

HY000

Message: Received invalid recovery endpoints configuration from donor. This member is not a valid

donor for recovery, so it will be skipped.

Error number: MY-013594; Symbol:

ER GRP RPL RECOVERY ENDPOINT INTERFACES IPS; SQLSTATE: HY000

Message: Failed to retrieve IP addresses from enabled host network interfaces.

Error number: MY-013595; Symbol: ER WARN TLS CHANNEL INITIALIZATION ERROR;

SQLSTATE: HY000

Message: Failed to initialize TLS for channel: %s. See below for the description of exact issue.

Error number: MY-013596; Symbol: ER XPLUGIN FAILED TO VALIDATE ADDRESS;

SQLSTATE: HY000

Message: Validation of value '%s' set to 'Mysqlx bind address' failed: %s. Skipping this value.

Error number: MY-013597; Symbol:

ER_XPLUGIN_FAILED_TO_BIND_INTERFACE_ADDRESS; SQLSTATE: HY000

Message: Value '%s' set to `Mysqlx_bind_address`, X Plugin can't bind to it. Skipping this value.

Error number: MY-013598; Symbol: ER IB ERR RECOVERY REDO DISABLED;

SQLSTATE: HY000

Message: Server was killed when InnoDB redo logging was disabled. Data files could be corrupt.

You can try to restart the database with innodb force recovery=6

Error number: MY-013599; Symbol: ER_IB_WRN_FAST_SHUTDOWN_REDO_DISABLED;

SQLSTATE: HY000

Message: InnoDB cannot do cold shutdown 'innodb fast shutdown = 2' and is forcing

'innodb_fast_shutdown = 1' as redo logging is disabled. InnoDB would flush all dirty pages to ensure

physical data consistency.

Error number: MY-013600; Symbol: ER_IB_WRN_REDO_DISABLED; SQLSTATE: HY000

Message: InnoDB redo logging is disabled. All data could be lost in case of a server crash.

Error number: MY-013601; Symbol: ER IB WRN REDO ENABLED; SQLSTATE: HY000

Message: InnoDB redo logging is enabled. Data is now safe and can be recovered in case of a server

crash.

Error number: MY-013602; Symbol: ER TLS CONFIGURED FOR CHANNEL; SQLSTATE:

HY000

Message: Channel %s configured to support TLS. Encrypted connections are now supported for this

channel.

Error number: MY-013603; Symbol: ER TLS CONFIGURATION REUSED; SQLSTATE:

HY000

Message: No TLS configuration was given for channel %s; re-using TLS configuration of

channel %s.

Error number: MY-013604; Symbol: ER IB TABLESPACE PATH VALIDATION SKIPPED;

SQLSTATE: HY000

Message: Skipping InnoDB tablespace path validation. Manually moved tablespace files will not be detected!

Error number: MY-013605; Symbol:

ER_IB_CANNOT_UPGRADE_WITH_DISCARDED_TABLESPACES; SQLSTATE: HY000

Message: Upgrade failed because database contains discarded tablespaces.

Error number: MY-013606; Symbol: ER_USERNAME_TRUNKATED; SQLSTATE: HY000 Message: The user name '%s' exceeds the maximum number of allowed characters %d and is trunkated.

Error number: MY-013607; Symbol: ER_HOSTNAME_TRUNKATED; SQLSTATE: HY000 Message: The host name '%s' exceeds the maximum number of allowed characters %d and is trunkated.

Error number: MY-013608; Symbol:

ER_IB_MSG_TRX_RECOVERY_ROLLBACK_NOT_COMPLETED; SQLSTATE: HY000

Message: Rollback of non-prepared transactions not completed, due to fast shutdown

Error number: MY-013609; Symbol:

ER_AUTHCACHE_ROLE_EDGES_IGNORED_EMPTY_NAME; SQLSTATE: HY000 Message: Found an entry in the 'role edges' table with empty authorization ID; Skipped

Error number: MY-013610; Symbol:

ER_AUTHCACHE_ROLE_EDGES_UNKNOWN_AUTHORIZATION_ID; SQLSTATE: HY000 Message: Found an entry in the 'role edges' table with unknown authorization ID '%s'; Skipped

Error number: MY-013611; Symbol:

ER_AUTHCACHE_DEFAULT_ROLES_IGNORED_EMPTY_NAME; SQLSTATE: HY000 Message: Found an entry in the 'default_roles' table with empty authorization ID; Skipped

Error number: MY-013612; Symbol:

ER_AUTHCACHE_DEFAULT_ROLES_UNKNOWN_AUTHORIZATION_ID; SQLSTATE: HY000

Message: Found an entry in the 'default roles' table with unknown authorization ID '%s'; Skipped

Error number: MY-013613; Symbol: ER_IB_ERR_DDL_LOG_INSERT_FAILURE; SQLSTATE: HY000

Message: Couldn't insert entry in ddl log for ddl.

Error number: MY-013614; Symbol: ER_IB_LOCK_VALIDATE_LATCH_ORDER_VIOLATION; SQLSTATE: HY000

Message: %s

Error number: MY-013615; Symbol: ER IB RELOCK LATCH ORDER VIOLATION;

SQLSTATE: HY000

Message: %s

Error number: MY-013624; Symbol: ER IB FAILED TO DELETE TABLESPACE FILE;

SQLSTATE: HY000

Message: %s

Error number: MY-013625; Symbol:

ER IB UNABLE TO EXPAND TEMPORARY TABLESPACE POOL; SQLSTATE: HY000

Message: %s

Error number: MY-013626; Symbol:

ER IB TMP TABLESPACE CANNOT CREATE DIRECTORY; SQLSTATE: HY000

Message: %s

Error number: MY-013627; Symbol: ER IB MSG SCANNING TEMP TABLESPACE DIR;

SQLSTATE: HY000

Message: %s

Error number: MY-013628; Symbol: ER IB ERR TEMP TABLESPACE DIR DOESNT EXIST;

SQLSTATE: HY000

Message: %s

Error number: MY-013629; Symbol: ER IB ERR TEMP TABLESPACE DIR EMPTY;

SOLSTATE: HY000

Message: %s

Error number: MY-013630; Symbol:

ER IB ERR TEMP TABLESPACE DIR CONTAINS SEMICOLON; SQLSTATE: HY000

Message: %s

Error number: MY-013631; Symbol:

ER IB ERR TEMP TABLESPACE DIR SUBDIR OF DATADIR; SQLSTATE: HY000

Message: %s

Error number: MY-013632; Symbol: ER IB ERR SCHED_SETAFFNINITY_FAILED;

SQLSTATE: HY000

Message: %s

Error number: MY-013633; Symbol: ER IB ERR UNKNOWN PAGE FETCH MODE;

SQLSTATE: HY000

Message: %s

Error number: MY-013634; Symbol: ER IB ERR LOG PARSING BUFFER OVERFLOW;

SQLSTATE: HY000

Message: %s

Error number: MY-013635; Symbol:

ER IB ERR NOT ENOUGH MEMORY FOR PARSE BUFFER; SQLSTATE: HY000

Message: %s

Error number: MY-013640; Symbol: ER IB ERR ZLIB UNCOMPRESS FAILED; SQLSTATE:

HY000

Message: %s

Error number: MY-013641; Symbol: ER IB ERR ZLIB BUF ERROR; SQLSTATE: HY000

Message: %s

Error number: MY-013642; Symbol: ER IB ERR ZLIB MEM ERROR; SQLSTATE: HY000

Message: %s

Error number: MY-013643; Symbol: ER IB ERR ZLIB DATA ERROR; SQLSTATE: HY000

Message: %s

Error number: MY-013644; Symbol: ER IB ERR ZLIB UNKNOWN ERROR; SQLSTATE:

HY000

Message: %s

Error number: MY-013646; Symbol: ER IB ERR INDEX RECORDS WRONG ORDER;

SQLSTATE: HY000

Message: %s

Error number: MY-013647; Symbol: ER IB ERR INDEX DUPLICATE KEY; SQLSTATE:

HY000

Message: %s

Error number: MY-013648; Symbol: ER IB ERR FOUND N DUPLICATE KEYS; SQLSTATE:

HY000

Message: %s

Error number: MY-013649; Symbol: ER IB ERR FOUND N RECORDS WRONG ORDER;

SQLSTATE: HY000

Message: %s

Error number: MY-013650; Symbol: ER IB ERR PARALLEL READ OOM; SQLSTATE:

HY000

Message: %s

Error number: MY-013651; Symbol: ER IB MSG UNDO MARKED ACTIVE; SQLSTATE:

HY000

Message: The state of undo tablespace %s is set to active implicitly.

Error number: MY-013652; Symbol: ER_IB_MSG_UNDO_ALTERED_ACTIVE; SQLSTATE:

HY000

Message: The state of undo tablespace %s is set to 'active' by ALTER TABLESPACE.

Error number: MY-013653; Symbol: ER IB MSG UNDO ALTERED INACTIVE; SQLSTATE:

HY000

Message: The state of undo tablespace %s is set to 'inactive' by ALTER TABLESPACE.

Error number: MY-013654; Symbol: ER IB MSG UNDO MARKED EMPTY; SQLSTATE:

HY000

Message: The state of undo tablespace %s is set to 'empty'.

Error number: MY-013655; Symbol: ER IB MSG UNDO TRUNCATE DELAY BY CLONE;

SQLSTATE: HY000

Message: Delaying truncate of undo tablespace %s due to clone activity.

Error number: MY-013656; Symbol: ER IB MSG UNDO TRUNCATE DELAY BY MDL;

SQLSTATE: HY000

Message: Delaying truncate of undo tablespace %s due to a metadata lock.

Error number: MY-013657; Symbol: ER IB MSG UNDO INJECT CRASH; SQLSTATE: HY000

Message: Injected debug crash point: %s

Error number: MY-013657; Symbol: ER IB MSG INJECT CRASH; SQLSTATE: HY000

Message: Injected debug crash point: %s

Error number: MY-013658; Symbol: ER IB MSG UNDO_INJECT_FAILURE; SQLSTATE:

HY000

Message: Injected debug failure point: %s

Error number: MY-013658; Symbol: ER_IB_MSG_INJECT_FAILURE; SQLSTATE: HY000 Message: Injected debug failure point: %s

Error number: MY-013659; Symbol:

ER_GRP_RPL_TIMEOUT_RECEIVED_VC_LEAVE_ON_REJOIN; SQLSTATE: HY000 Message: Timeout while waiting for a view change event during the leave step before a auto-rejoin attempt.

Error number: MY-013660; Symbol: ER_RPL_ASYNC_RECONNECT_FAIL_NO_SOURCE; SOLSTATE: HY000

Message: Failed to automatically re-connect to a different source, for channel '%s', because %s. To fix this %s.

Error number: MY-013661; Symbol: ER_UDF_REGISTER_SERVICE_ERROR; SQLSTATE: HY000

Message: Could not execute the installation of UDF functions. Check for other errors in the log

Error number: MY-013662; Symbol: ER_UDF_REGISTER_ERROR; SQLSTATE: HY000 Message: Could not execute the installation of UDF function: %s. Check if the function is already present, if so, try to remove it.

Error number: MY-013663; Symbol: ER_UDF_UNREGISTER_ERROR; SQLSTATE: HY000 Message: Could not uninstall UDF functions. Try to remove them manually if present.

Error number: MY-013664; Symbol: ER_EMPTY_PRIVILEGE_NAME_IGNORED; SQLSTATE: HY000

Message: An empty or illegal privilege identifier was ignored when global privileges were read from disk.

Error number: MY-013665; Symbol: ER_IB_MSG_INCORRECT_SIZE; SQLSTATE: HY000 Message: %s

Error number: MY-013666; Symbol: ER_TMPDIR_PATH_TOO_LONG; SQLSTATE: HY000 Message: A tmpdir temporary path "%s" is too long (> %zu) for this OS. This would not leave enough space for a temporary filename of length %zu within it.

Error number: MY-013667; Symbol: ER_ERROR_LOG_DESTINATION_NOT_A_FILE; SQLSTATE: HY000

Message: Error-log destination "%s" is not a file. Can not restore error log Messages from previous run.

Error number: MY-013668; Symbol: ER_NO_ERROR_LOG_PARSER_CONFIGURED; SQLSTATE: HY000

Message: None of the log-sinks selected with --log-error-services=... provides a log-parser. The server will not be able to make the previous runs' error-logs available in performance schema.error log.

Error number: MY-013669; Symbol: ER_UPGRADE_NONEXISTENT_SCHEMA; SQLSTATE: HY000

Message: The schema "%s" referenced by %s "%s" does not exist. Please clean up any orphan %s before upgrading.

Error number: MY-013670; Symbol: ER_IB_MSG_CREATED_UNDO_SPACE; SQLSTATE: HY000

Message: Created undo tablespace '%s'.

Error number: MY-013671; Symbol: ER_IB_MSG_DROPPED_UNDO_SPACE; SQLSTATE: HY000

Message: Dropped undo tablespace '%s'.

Error number: MY-013672; Symbol: ER_IB_MSG_MASTER_KEY_ROTATED; SQLSTATE: HY000

Message: The InnoDB Encryption Master Key has been rotated in %d tablespaces.

Error number: MY-013673; Symbol: ER_IB_DBLWR_DECOMPRESS_FAILED; SQLSTATE: HY000

Message: Failed to decompress a DBLWR page (err=%d). The original size is %d. Reporting the dblwr page as corrupted.

Error number: MY-013674; Symbol: ER_IB_DBLWR_DECRYPT_FAILED; SQLSTATE: HY000 Message: Decrypting a page in doublewrite file failed: %s.

Error number: MY-013675; Symbol: ER_IB_DBLWR_KEY_MISSING; SQLSTATE: HY000 Message: Encryption key missing: %s.

Error number: MY-013676; Symbol: ER_INNODB_IO_WRITE_ERROR_RETRYING;

SQLSTATE: HY000

Message: I/O error while writing to file: %s. Retrying ...

Error number: MY-013677; Symbol: ER_INNODB_IO_WRITE_FAILED; SQLSTATE: HY000 Message: Failed to write data to file: %s

Error number: MY-013678; Symbol: ER LOG COMPONENT CANNOT INIT; SQLSTATE:

HY000

Message: Log component %s failed to initialize.

Error number: MY-013679; Symbol: ER RPL ASYNC CHANNEL CANT CONNECT;

SQLSTATE: HY000

Message: The Monitor IO thread failed to connect to the source (host:%s port:%u

network namespace:%s) for channel '%s', thence it will try to connect to another source.

Error number: MY-013680; Symbol: ER_RPL_ASYNC_SENDER_ADDED; SQLSTATE: HY000 Message: The source (host:%s port:%u network_namespace:%s) for channel '%s' has joined the group (group_name: %s), and so added its entry into replication_asynchronous_connection_failover table.

Error number: MY-013681; Symbol: ER_RPL_ASYNC_SENDER_REMOVED; SQLSTATE: HY000

Message: The source (host:%s port:%u network_namespace:%s) for channel '%s' has left the group (group_name: %s), and so removed its entry from replication_asynchronous_connection_failover table.

Error number: MY-013682; Symbol:

ER RPL ASYNC CHANNEL STOPPED QUORUM LOST; SQLSTATE: HY000

Message: The Monitor IO thread detected that the source (host:%s port:%u network_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.

Error number: MY-013683; Symbol:

ER_RPL_ASYNC_CHANNEL_CANT_CONNECT_NO_QUORUM; SQLSTATE: HY000

Message: The IO thread detected that the source (host:%s port:%u network_namespace:%s) does not belong to the group majority, thence the channel '%s' will try to connect to another source.

Error number: MY-013684; Symbol: ER_RPL_ASYNC_EXECUTING_QUERY; SQLSTATE:

HY000

Message: %s on the source (host:%s port:%u network_namespace:%s) for channel '%s'.

Error number: MY-013685; Symbol: ER RPL REPLICA MONITOR IO THREAD EXITING;

SQLSTATE: HY000

Message: Replica Monitor IO thread exiting.

Error number: MY-013686; Symbol: ER RPL ASYNC MANAGED_NAME_REMOVED;

SQLSTATE: HY000

Message: The group (group_name: %s) for the channel '%s' has been removed, and so removed its entry from replication_asynchronous_connection_failover_managed and all the group members from replication asynchronous connection failover table.

Error number: MY-013687; Symbol: ER RPL ASYNC MANAGED NAME ADDED;

SQLSTATE: HY000

Message: The group (group_name: %s) for the channel '%s' has been added, and so added its entry in replication_asynchronous_connection_failover_managed and source to replication asynchronous connection failover table.

Error number: MY-013688; Symbol: ER RPL ASYNC READ FAILOVER TABLE;

SQLSTATE: HY000

Message: Error reading failover sources for channel '%s' from

replication asynchronous connection failover table.

Error number: MY-013689; Symbol:

ER RPL REPLICA MONITOR IO THREAD RECONNECT CHANNEL; SQLSTATE: HY000

Message: Error %s the channel '%s', the operation will be automatically retried.

Error number: MY-013690; Symbol:

ER_SLAVE_ANONYMOUS_TO_GTID_IS_LOCAL_OR_UUID_AND_GTID_MODE_NOT_ON;

SQLSTATE: HY000

Message: Replication channel '%s' is configured with

ASSIGN GTIDS TO ANONYMOUS TRANSACTIONS='%s', which is invalid when

GTID MODE <> ON. If you intend to use GTID MODE = ON everywhere, change to

ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = OFF and use the procedure for

enabling GTIDs online (see the documentation). If you intend to use GTIDs on this replica and cannot enable GTIDs on the source, enable GTID MODE = ON and leave

cannot enable G11Ds on the source, enable G11D_MODE = ON and leave

ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS = LOCAL|<UUID>. If you intend to not use CTIDs at all in the realisation tanalogy, shange to

use GTIDs at all in the replication topology, change to

ASSIGN GTIDS TO ANONYMOUS TRANSACTIONS=OFF and leave GTID MODE = '%s'.

Error number: MY-013691; Symbol:

 $ER_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_GROUP_NAME; SQLSTATE:$

HY000

Message: Replication channel '%s' is configured with

ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS='%s' which is equal to group_replication_group_name. To fix this issue, either change the group_replication_group_name or use a different value for ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS.

Error number: MY-013692; Symbol:

ER_GRP_RPL_GRP_NAME_IS_SAME_AS_ANONYMOUS_TO_GTID_UUID; SQLSTATE: HY000

Message: The group_replication_group_name '%s' is the same as the UUID value for ASSIGN_GTIDS_TO_ANONYMOUS_TRANSACTIONS in a server channel

Error number: MY-013693; Symbol: ER_WARN_GTID_THRESHOLD_BREACH; SQLSTATE: HY000

Message: The integer component of the GTID number is high. Suggest restarting the server with a new server_uuid to prevent it from reaching the maximum number 2^63-1, which will make it impossible to write the binary log and invoke the behavior specified by binlog error action.

Error number: MY-013694; Symbol: ER_HEALTH_INFO; SQLSTATE: HY000 Message: %s

Error number: MY-013695; Symbol: ER_HEALTH_WARNING; SQLSTATE: HY000 Message: %s

Error number: MY-013696; Symbol: ER_HEALTH_ERROR; SQLSTATE: HY000 Message: %s

Error number: MY-013697; Symbol: ER_HEALTH_WARNING_DISK_USAGE_LEVEL_1; SOLSTATE: HY000

Message: %s: Warning Level 1 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB

Error number: MY-013698; Symbol: ER_HEALTH_WARNING_DISK_USAGE_LEVEL_2; SQLSTATE: HY000

Message: %s: Warning Level 2 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB

Error number: MY-013699; Symbol: ER_HEALTH_WARNING_DISK_USAGE_LEVEL_3; SQLSTATE: HY000

Message: %s: Warning Level 3 (%llu MiB): mount point = '%s', available = %llu MiB, total = %llu MiB, used = %.2f%%, low limit = %llu MiB, critical level = %llu MiB

Error number: MY-013700; Symbol: ER_IB_INNODB_TBSP_OUT_OF_SPACE; SQLSTATE: HY000

Message: InnoDB: Size of tablespace %s is more than the maximum size allowed.

Error number: MY-013701; Symbol: ER_GRP_RPL_APPLIER_CHANNEL_STILL_RUNNING; SQLSTATE: HY000

Message: The group_replication_applier channel is still running, most likely it is waiting for a database/table lock, which is preventing the channel from stopping. Please check database/table locks, including the ones created by backup tools.

Error number: MY-013702; Symbol:

ER RPL ASYNC RECONNECT GTID MODE OFF CHANNEL; SQLSTATE: HY000

Message: Detected misconfiguration: replication channel \'%s\' was configured with

SOURCE CONNECTION AUTO FAILOVER = 1, but the server was started with a value other

then --gtid-mode = ON. Either reconfigure replication using CHANGE MASTER TO

SOURCE CONNECTION AUTO FAILOVER = 0 FOR CHANNEL \'%s\', or change

GTID MODE to value ON, before starting the replica receiver thread.

Error number: MY-013703; Symbol: ER FIREWALL SERVICES NOT ACQUIRED;

SQLSTATE: HY000

Message: Could not acquire required component services.

Error number: MY-013704; Symbol: ER FIREWALL UDF REGISTER FAILED; SQLSTATE:

HY000

Message: Automatic registration of function(s) failed.

Error number: MY-013705; Symbol: ER FIREWALL PFS TABLE REGISTER FAILED;

SQLSTATE: HY000

Message: Automatic registration of Performance schema table(s) failed.

Error number: MY-013706; Symbol: ER IB MSG STATS SAMPLING TOO LARGE;

SQLSTATE: HY000

Message: %s

Error number: MY-013707; Symbol: ER AUDIT LOG FILE PRUNE FAILED; SQLSTATE:

HY000

Message: Failed to auto-prune file '%s', Error (%d): %s

Error number: MY-013708; Symbol: ER AUDIT LOG FILE AUTO PRUNED; SQLSTATE:

HY000

Message: File '%s' auto-pruned

Error number: MY-013709; Symbol:

ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_INIT; SQLSTATE: HY000

Message: Received an error while processing components from manifest file: %s

Error number: MY-013710; Symbol:

ER_COMPONENTS_INFRASTRUCTURE_MANIFEST_DEINIT; SQLSTATE: HY000

Message: Received an error while unloading components read from manifest file: %s

Error number: MY-013711; Symbol:

ER_WARN_COMPONENTS_INFRASTRUCTURE_MANIFEST_NOT_RO; SQLSTATE: HY000 Message: Manifest file '%s' is not read-only. For better security, please make sure that the file is read-only.

Error number: MY-013712; Symbol:

ER WARN NO KEYRING COMPONENT SERVICE FOUND; SQLSTATE: HY000

Message: No suitable '%s' service implementation found to fulfill the request.

Error number: MY-013713; Symbol: ER NOTE KEYRING COMPONENT INITIALIZED;

SQLSTATE: HY000

Message: Keyring component initialized successfully.

Error number: MY-013714; Symbol: ER KEYRING COMPONENT NOT INITIALIZED;

SQLSTATE: HY000

Message: The component is not initialized properly. Make sure that configuration is proper and use

ALTER INSTANCE RELOAD KEYRING to reinitialize the component.

Error number: MY-013715; Symbol: ER_KEYRING_COMPONENT_EXCEPTION; SQLSTATE:

HY000

Message: Keyring component encountered an exception while executing: '%s' API of service: '%s'

Error number: MY-013716; Symbol:

ER KEYRING COMPONENT MEMORY ALLOCATION ERROR; SQLSTATE: HY000

Message: Failed to allocated memory for '%s' while executing: '%s' API of service: '%s'

Error number: MY-013717; Symbol:

ER NOTE KEYRING COMPONENT AES INVALID MODE BLOCK SIZE; SQLSTATE:

HY000

Message: Empty or 0 values for AES encryption mode and/or block size are not permitted.

Error number: MY-013718; Symbol:

ER NOTE KEYRING COMPONENT AES DATA IDENTIFIER EMPTY; SQLSTATE:

HY000

Message: A valid data identifier is required in order to fetch the key required for the AES operation.

Error number: MY-013719; Symbol:

ER NOTE KEYRING COMPONENT AES INVALID KEY; SQLSTATE: HY000

Message: Key identified by Data ID: '%s' and Auth ID: '%s' is not of type AES.

Error number: MY-013720; Symbol:

ER_NOTE_KEYRING_COMPONENT_AES_OPERATION_ERROR; SQLSTATE: HY000 Message: Encountered error: '%s' while executing '%s' API of keyring_aes service. Key details are

Data ID: '%s' and Auth ID: '%s'.

Error number: MY-013721; Symbol:

ER NOTE KEYRING COMPONENT READ DATA NOT FOUND; SQLSTATE: HY000

Message: Could not find the data corresponding to Data ID: '%s', Auth ID: '%s'.

Error number: MY-013722; Symbol:

ER_NOTE_KEYRING_COMPONENT_WRITE_MAXIMUM_DATA_LENGTH; SQLSTATE:

HY000

Message: Maximum permissible size of data is '%zu' bits

Error number: MY-013723; Symbol: ER_NOTE_KEYRING_COMPONENT_STORE_FAILED;

SQLSTATE: HY000

Message: Error writing data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same

identifier or keyring backend encountered an error.

Error number: MY-013724; Symbol: ER_NOTE_KEYRING_COMPONENT_REMOVE_FAILED;

SQLSTATE: HY000

Message: Error removing data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same

identifier or keyring backend encountered an error.

Error number: MY-013725; Symbol:

ER NOTE KEYRING COMPONENT GENERATE FAILED; SQLSTATE: HY000

Message: Error generating data for Data ID: '%s', Auth ID: '%s'. Either data already exists with same

identifier or keyring backend encountered an error.

Error number: MY-013726; Symbol:

ER_NOTE_KEYRING_COMPONENT_KEYS_METADATA_ITERATOR_FETCH_FAILED;

SQLSTATE: HY000

Message: Failed to get metadata from current keys metadata iterator position.

Error number: MY-013727; Symbol:

ER NOTE KEYRING COMPONENT METADATA ITERATOR INVALID OUT PARAM;

SQLSTATE: HY000

Message: Key and value length parameters must not be null.

Error number: MY-013728; Symbol: ER IB WRN FAILED TO ACQUIRE SERVICE;

SQLSTATE: HY000

Message: Innodb could not acquire service: %s

Error number: MY-013729; Symbol: ER_IB_WRN_OLD_GEOMETRY_TYPE; SQLSTATE: HY000

Message: Column %s of type GEOMETRY is in old (5.6) format which could be deprecated in the future. To change the format to latest, please consider rebuilding the table after the upgrade.

Error number: MY-013730; Symbol: ER_NET_WAIT_ERROR2; SQLSTATE: HY000 Message: 'wait_timeout' period of %s seconds was exceeded for %s. The idle time since last command was too long.

Error number: MY-013731; Symbol: ER_GRP_RPL_MEMBER_ACTION_TRIGGERED;

SQLSTATE: HY000

Message: The member action "%s" for event "%s" with priority "%u" will be run.

Error number: MY-013732; Symbol: ER_GRP_RPL_MEMBER_ACTION_FAILURE_IGNORE; SQLSTATE: HY000

Message: The member action "%s" for event "%s" with priority "%u" failed, this error is ignored as instructed. Please check previous Messages in the error log for hints about what could have caused this failure

Error number: MY-013733; Symbol: ER_GRP_RPL_MEMBER_ACTION_FAILURE; SQLSTATE: HY000

Message: The member action "%s" for event "%s" with priority "%u" failed. Please check previous Messages in the error log for hints about what could have caused this failure.

Error number: MY-013734; Symbol:

ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_RECEIVE; SQLSTATE: HY000 Message: Unable to parse the member actions configuration sent by the primary.

Error number: MY-013735; Symbol: ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS; SQLSTATE: HY000

Message: Unable to update the member actions configuration with the one sent by the primary. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication group configuration version'.

Error number: MY-013736; Symbol:

ER_GRP_RPL_MEMBER_ACTION_GET_EXCHANGEABLE_DATA; SQLSTATE: HY000 Message: Unable to read the member actions configuration during group membership change. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication group configuration version'.

Error number: MY-013737; Symbol:

ER GRP RPL MEMBER ACTION DEFAULT CONFIGURATION; SQLSTATE: HY000

Message: This member joined a group on which all members do not support member actions, as such it did reset its member configuration to the default one.

Error number: MY-013738; Symbol:

ER GRP RPL MEMBER ACTION UNABLE TO SET DEFAULT CONFIGURATION;

SQLSTATE: HY000

Message: Unable to reset to member actions default configuration on member join. Please check the tables 'mysql.replication_group_member_actions' and

'mysql.replication group configuration version'.

Error number: MY-013739; Symbol:

ER_GRP_RPL_MEMBER_ACTION_PARSE_ON_MEMBER_JOIN; SQLSTATE: HY000 Message: Unable to parse the member actions configuration sent by the group on member join.

Error number: MY-013740; Symbol:

ER_GRP_RPL_MEMBER_ACTION_UPDATE_ACTIONS_ON_MEMBER_JOIN; SQLSTATE: HY000

Message: Unable to update the member actions configuration on member join. Please check the tables 'mysql.replication_group_member_actions' and 'mysql.replication group configuration version'.

Error number: MY-013741; Symbol:

ER_GRP_RPL_MEMBER_ACTION_INVALID_ACTIONS_ON_MEMBER_JOIN; SQLSTATE: HY000

Message: The group members were unable to send their member actions configuration. Please check the tables 'mysql.replication_group_member_actions' and

'mysql.replication group configuration version' on all members.

Error number: MY-013742; Symbol: ER GRP RPL MEMBER ACTION ENABLED;

SQLSTATE: HY000

Message: Member action enabled: "%s", type: "%s", event: "%s", priority: "%u", error_handling: "%s".

Error number: MY-013743; Symbol: ER_GRP_RPL_MEMBER_ACTION_DISABLED;

SQLSTATE: HY000

Message: Member action disabled: "%s", type: "%s", event: "%s", priority: "%u", error_handling: "%s".

Error number: MY-013744; Symbol: ER_GRP_RPL_MEMBER_ACTIONS_RESET; SQLSTATE: HY000

Message: Member actions configuration was reset.

Error number: MY-013745; Symbol: ER DEPRECATED TLS VERSION SESSION;

SQLSTATE: HY000

Message: Accepted a connection with deprecated protocol '%s' for account `%s`@`%s` from host

'%s'. Client supplied username '%s'

Error number: MY-013746; Symbol:

ER WARN DEPRECATED TLS VERSION FOR CHANNEL; SQLSTATE: HY000

Message: A deprecated TLS version %s is enabled for channel %s

Error number: MY-013747; Symbol: ER FIREWALL DEPRECATED USER PROFILE;

SQLSTATE: HY000

Message: User profile \'%s\' loaded. Firewall user profiles are deprecated, consider migrating to

group profiles.

Error number: MY-013748; Symbol: ER GRP RPL VIEW CHANGE UUID INVALID;

SQLSTATE: HY000

Message: Invalid input value for group_replication_view_change_uuid '%s'. Please, provide a valid

UUID.

Error number: MY-013749; Symbol:

 $ER_GRP_RPL_VIEW_CHANGE_UUID_SAME_AS_GROUP_NAME; SQLSTATE: HY000$

Message: Variable 'group_replication_view_change_uuid' cannot be set to the value of '%s'. If you want to use the UUID of 'group replication group name' for the UUID of View change log events,

please set 'group replication view change uuid' to AUTOMATIC.

Error number: MY-013750; Symbol:

ER GRP RPL GROUP NAME SAME AS VIEW CHANGE UUID; SQLSTATE: HY000

Message: group replication group name '%s', which is the same as

group replication view change uuid. Please change group replication view change uuid to

AUTOMATIC

Error number: MY-013751; Symbol:

ER GRP RPL VIEW CHANGE UUID IS SAME AS ANONYMOUS TO GTID UUID;

SQLSTATE: HY000

Message: The group replication view change uuid '%s' is the same as the UUID value for

ASSIGN GTIDS TO ANONYMOUS TRANSACTIONS in a server channel

Error number: MY-013752; Symbol:

ER GRP RPL GRP VIEW CHANGE UUID IS INCOMPATIBLE WITH SERVER UUID;

SQLSTATE: HY000

Message: group_replication_view_change_uuid is incompatible with group. group replication view change uuid %s matches server uuid %s.

Error number: MY-013753; Symbol: ER_GRP_RPL_VIEW_CHANGE_UUID_DIFF_FROM_GRP; SOLSTATE: HY000

Message: The member is configured with a group_replication_view_change_uuid option value '%s' different from the group '%s'. The member will now exit the group.

Error number: MY-013754; Symbol:

ER_WARN_REPLICA_ANONYMOUS_TO_GTID_UUID_SAME_AS_VIEW_CHANGE_UUID; SQLSTATE: HY000

Message: Replication channel '%s' is configured with

ASSIGN GTIDS TO ANONYMOUS TRANSACTIONS='%s' which is equal to

group replication view change uuid. To fix this issue, either change the

group_replication_view_change_uuid or use a different value for

ASSIGN GTIDS TO ANONYMOUS TRANSACTIONS.

Error number: MY-013755; Symbol:

ER_GRP_RPL_FAILED_TO_PARSE_THE_VIEW_CHANGE_UUID; SQLSTATE: HY000 Message: Unable to parse the group replication view change uuid.

Error number: MY-013756; Symbol:

ER_GRP_RPL_FAILED_TO_GENERATE_SIDNO_FOR_VIEW_CHANGE_UUID; SQLSTATE: HY000

Message: Unable to generate sidno for group replication view change uuid.

Error number: MY-013757; Symbol: ER_GRP_RPL_VIEW_CHANGE_UUID_PARSE_ERROR; SQLSTATE: HY000

Message: Unable to parse the group_replication_view_change_uuid during the Certification module initialization

Error number: MY-013758; Symbol:

ER GRP RPL UPDATE GRPGTID VIEW CHANGE UUID EXECUTED ERROR;

SOLSTATE: HY000

Message: Error updating group_gtid_executed GTID set with view change uuid during the Certification module initialization.

Error number: MY-013759; Symbol:

ER_GRP_RPL_ADD_VIEW_CHANGE_UUID_TO_GRP_SID_MAP_ERROR; SQLSTATE: HY000

Message: Unable to add the group_replication_view_change_uuid sidno in the group_gtid_sid_map during the Certification module initialization.

Error number: MY-013760; Symbol:

ER_GRP_RPL_DONOR_VIEW_CHANGE_UUID_TRANS_INFO_ERROR; SQLSTATE: HY000 Message: Unable to handle the donor's view change unid transaction information when initializing the conflict detection component. Possible out of memory error.

Error number: MY-013761; Symbol:

ER_WARN_GRP_RPL_VIEW_CHANGE_UUID_FAIL_GET_VARIABLE; SQLSTATE: HY000 Message: Unable to retrieve group_replication_view_change_uuid during server checks on replication operations.

Error number: MY-013762; Symbol:

ER_WARN_ADUIT_LOG_MAX_SIZE_AND_PRUNE_SECONDS_LOG; SQLSTATE: HY000 Message: Both audit_log_max_size and audit_log_prune_seconds are set to non-zero. audit_log_max_size takes precedence and audit_log_prune_seconds is ignored

Error number: MY-013763; Symbol:

ER_WARN_ADUIT_LOG_MAX_SIZE_CLOSE_TO_ROTATE_ON_SIZE_LOG; SQLSTATE: HY000

Message: audit_log_rotate_on_size is not granular enough for the value of audit_log_max_size supplied. Should be at least %d times smaller.

Error number: MY-013764; Symbol: ER PLUGIN INVALID TABLE DEFINITION;

SQLSTATE: HY000

Message: Invalid table definition for '%s.%s'.

Error number: MY-013765; Symbol: ER AUTH KERBEROS LOGGER GENERIC MSG;

SOLSTATE: HY000

Message: %s

Error number: MY-013766; Symbol: ER_INSTALL_PLUGIN_CONFLICT_LOG; SQLSTATE:

HY000

Message: Cannot install the %s plugin when the %s plugin is installed.

Error number: MY-013767; Symbol:

ER DEPRECATED PERSISTED VARIABLE WITH ALIAS; SQLSTATE: HY000

Message: The variable %s has been renamed to %s, and the old name deprecated. Only the old name was found in the persisted variable file. Next time the file is saved, both names will be stored. Issue any SET PERSIST command to save the file, get rid of this warning, and prepare the persisted configuration for when the variable is removed in a future version.

Error number: MY-013768; Symbol: ER_LOG_COMPONENT_FLUSH_FAILED; SQLSTATE: HY000

Message: %d error logging component(s) failed to flush. For file-based logs this can happen when the path or permissions of the log-file have changed. Failure to flush filed-based logs may affect log-rotation.

 $Error\ number:\ MY-013769;\ Symbol:\ ER_IB_MSG_REENCRYPTED_TABLESPACE_KEY;$

SQLSTATE: HY000

Message: Tablespace key for %s has been re-encrypted using the latest InnoDB master key.

However, we recommend that you rebuild the table for better security.

Error number: MY-013770; Symbol:

ER_IB_MSG_REENCRYPTED_GENERAL_TABLESPACE_KEY; SQLSTATE: HY000 Message: Tablespace key for %s has been re-encrypted using the latest InnoDB master key. However, we recommend that you reencrypt the tablespace for better security.

Error number: MY-013771; Symbol: ER_IB_ERR_PAGE_ARCH_DBLWR_INIT_FAILED; SQLSTATE: HY000

Message: Page Archiver's doublewrite buffer initialisation failed. Page tracking is at risk of losing tracked information.

Error number: MY-013772; Symbol:

ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__SKIP_IBUF_MERGES; SQLSTATE: HY000

Message: There is not enough free space in the redo log during recovery to perform pending ibuf merges. Please retry starting MySQL with --innodb-force-recovery=4.

Error number: MY-013773; Symbol:

ER_IB_MSG_RECOVERY_NO_SPACE_IN_REDO_LOG__UNEXPECTED; SQLSTATE: HY000

Message: There is not enough free space in the redo log during recovery, restore from backup (or retry with --innodb-force-recovery=6).

Error number: MY-013774; Symbol:

ER WARN AUDIT LOG FORMAT UNIX TIMESTAMP ONLY WHEN JSON LOG;

SQLSTATE: HY000

Message: audit log format unix timestamp is applicable only when audit log format = JSON.

Error number: MY-013775; Symbol: ER_PREPARE_FOR_PRIMARY_ENGINE; SQLSTATE: HY000

Message: Retry the statement using the primary storage engine.

Error number: MY-013776; Symbol: ER IB MSG PAR RSEG INIT COMPLETE MSG;

SQLSTATE: HY000

Message: Parallel initialization of rseg complete

Error number: MY-013777; Symbol: ER IB MSG PAR RSEG INIT TIME MSG; SQLSTATE:

HY000

Message: Time taken to initialize rseg using %u thread: %u ms.

Error number: MY-013778; Symbol: ER_DDL_MSG_1; SQLSTATE: HY000 Message: DDL failed to create a thread to load an index, fall back to single thread

Error number: MY-013779; Symbol: ER MTR MSG 1; SQLSTATE: HY000

Message: Debug check no latching failed, slot->type=%d

Error number: MY-013780; Symbol:

ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_CONN_ERR; SQLSTATE: HY000

Message: Failed to establish MySQL client connection in Group Replication. Error establishing connection. Please refer to the manual to make sure that you configured Group Replication properly to work with MySQL Protocol connections.

Error number: MY-013781; Symbol:

ER_GRP_RPL_MYSQL_NETWORK_PROVIDER_CLIENT_ERROR_COMMAND_ERR; SQLSTATE: HY000

Message: Failed to establish MySQL client connection in Group Replication. Error sending connection delegation command. Please refer to the manual to make sure that you configured Group Replication properly to work with MySQL Protocol connections.

Error number: MY-013782; Symbol:

ER_GRP_RPL_FAILOVER_CONF_GET_EXCHANGEABLE_DATA; SQLSTATE: HY000 Message: Unable to read the replication failover channels configuration during group membership change. Please check the tables 'mysql.replication_asynchronous_connection_failover', 'mysql.replication_asynchronous_connection_failover_managed' and 'mysql.replication_group_configuration_version'.

Error number: MY-013783; Symbol:

ER_GRP_RPL_FAILOVER_CONF_DEFAULT_CONFIGURATION; SQLSTATE: HY000 Message: This member joined a group on which all members do not support replication failover channels integration on Group Replication, as such it did reset its replication failover channels configuration to the default one.

Error number: MY-013784; Symbol:

ER GRP RPL FAILOVER CONF UNABLE TO SET DEFAULT CONFIGURATION;

SQLSTATE: HY000

Message: Unable to reset to replication failover channels default configuration on member join.

Please check the tables 'mysql.replication asynchronous connection failover',

'mysql.replication asynchronous connection failover managed' and

'mysql.replication group configuration version'.

Error number: MY-013785; Symbol:

ER_GRP_RPL_FAILOVER_CONF_PARSE_ON_MEMBER_JOIN; SQLSTATE: HY000 Message: Unable to parse the replication failover channels configuration sent by the group on member join.

Error number: MY-013786; Symbol:

ER_GRP_RPL_FAILOVER_CONF_CHANNEL_DOES_NOT_EXIST; SQLSTATE: HY000 Message: Unable to set SOURCE_CONNECTION_AUTO_FAILOVER on a non-existent or misconfigured replication channel '%s', please create the channel and rejoin the server to the group.

Error number: MY-013787; Symbol:

ER_GRP_RPL_FAILOVER_REGISTER_MESSAGE_LISTENER_SERVICE; SQLSTATE:

HY000

Message: Unable to register the listener

'replication asynchronous connection failover configuration' to the service

'group replication Message service recv'.

Error number: MY-013788; Symbol:

ER GRP RPL FAILOVER PRIMARY WITHOUT MAJORITY; SQLSTATE: HY000

Message: This server is not able to reach a majority of members in the group. This server will skip the replication failover channels handling until this server is back to the group majority.

Error number: MY-013789; Symbol:

ER_GRP_RPL_FAILOVER_PRIMARY_BACK_TO_MAJORITY; SQLSTATE: HY000 Message: This server is back to the group majority. Replication failover channels handling is resumed.

Error number: MY-013790; Symbol:

ER_RPL_INCREMENTING_MEMBER_ACTION_VERSION; SQLSTATE: HY000 Message: Error incrementing member action configuration version for %s.%s table.

2.13 错误码及错误信息汇总 13

Error number: MY-013791; Symbol:

ER GRP RPL SLAVE THREAD ERROR ON SECONDARY MEMBER; SQLSTATE: HY000

Message: The '%s' thread of channel '%s' will error out as this server is a group secondary.

Error number: MY-013792; Symbol: ER IB MSG CLONE DDL NTFN; SQLSTATE: HY000

Message: Clone DDL Notification: %s

Error number: MY-013793; Symbol: ER IB MSG CLONE DDL APPLY; SQLSTATE: HY000

Message: Clone DDL APPLY: %s

Error number: MY-013794; Symbol: ER IB MSG CLONE DDL INVALIDATE; SQLSTATE:

HY000

Message: Clone DDL Invalidate: %s

Error number: MY-013795; Symbol: ER IB MSG UNDO ENCRYPTION INFO LOADED;

SQLSTATE: HY000

Message: Encryption key is loaded for undo tablespace '%s'.

Error number: MY-013796; Symbol: ER IB WRN ENCRYPTION INFO SIZE MISMATCH;

SQLSTATE: HY000

Message: Ignoring encryption INFO size in redo log: %zu, expected: %zu

Error number: MY-013797; Symbol: ER_INVALID_AUTHENTICATION_POLICY; SQLSTATE:

HY000

Message: Option --authentication-policy is set to an invalid value. Please check if the specified

authentication plugins are valid.

Error number: MY-013798; Symbol:

ER AUTHENTICATION PLUGIN REGISTRATION FAILED; SQLSTATE: HY000

Message: Signature verification failed during registration.

Error number: MY-013799; Symbol:

ER AUTHENTICATION PLUGIN REGISTRATION INSUFFICIENT BUFFER; SQLSTATE:

HY000

Message: Buffer too small to hold registration challenge response.

Error number: MY-013800; Symbol:

ER AUTHENTICATION PLUGIN AUTH DATA CORRUPT; SQLSTATE: HY000

Message: FIDO device authenticator data corrupt.

Error number: MY-013801; Symbol:

ER AUTHENTICATION PLUGIN SIGNATURE CORRUPT; SQLSTATE: HY000

Message: FIDO device signature corrupt.

Error number: MY-013802; Symbol:

ER AUTHENTICATION PLUGIN VERIFY SIGNATURE FAILED; SQLSTATE: HY000

Message: Signature verification failed during authentication.

Error number: MY-013803; Symbol: ER AUTHENTICATION PLUGIN OOM; SQLSTATE:

HY000

Message: Out of memory.

Error number: MY-013804; Symbol: ER AUTHENTICATION PLUGIN LOG; SQLSTATE:

HY000

Message: Can't initialize logging service

Error number: MY-013805; Symbol:

ER_WARN_REPLICA_GTID_ONLY_AND_GTID_MODE_NOT_ON; SQLSTATE: HY000 Message: Replication channel '%s' is configured with GTID_ONLY=1, which is invalid when GTID_MODE <> ON. If you intend to disable GTIDs in the replication topology, change GTID_ONLY to 0.

Error number: MY-013806; Symbol:

ER WARN L DISABLE GTID ONLY WITH SOURCE AUTO POS INVALID POS;

SQLSTATE: HY000

Message: The replication positions relative to the source may be out-of-date on channel '%s', due to the use of GTID_ONLY=1. The out-of-date positions can still be used in some cases so, in order to update them, we suggest that you start the replication to receive and apply at least one transaction, which will set the positions to valid values.

Error number: MY-013807; Symbol: ER RPL CANNOT OPEN RELAY LOG; SQLSTATE:

HY000

Message: Could not open relay log: %s

Error number: MY-013808; Symbol:

ER AUTHENTICATION OCI PLUGIN NOT INITIALIZED; SQLSTATE: HY000

Message: Authentication plugin not initialized.

Error number: MY-013809; Symbol: ER AUTHENTICATION OCI PRIVATE KEY ERROR;

SQLSTATE: HY000

Message: Cannot use the generated private key file.

Error number: MY-013810; Symbol:

ER AUTHENTICATION OCI DOWNLOAD PUBLIC KEY; SQLSTATE: HY000

Message: Unavailable public key with fingerprint %s for user %s in tenancy %s.

Error number: MY-013811; Symbol: ER_AUTHENTICATION_OCI_IMDS; SQLSTATE: HY000 Message: Cannot obtain the OCI configuration from the IMDS service.

Error number: MY-013812; Symbol: ER_AUTHENTICATION_OCI_IAM; SQLSTATE: HY000 Message: Cannot initialize the IAM service.

Error number: MY-013813; Symbol:

ER_AUTHENTICATION_OCI_INVALID_AUTHENTICATION_STRING; SQLSTATE: HY000 Message: Invalid authentication string details for user: '%s'@'%s'.

Error number: MY-013814; Symbol: ER_AUTHENTICATION_OCI_NO_MATCHING_GROUPS; SQLSTATE: HY000

Message: None of the groups returned by IAM matches any of the entries from authentication string.

Error number: MY-013815; Symbol: ER_AUTHENTICATION_OCI_NO_GROUPS_FOUND; SQLSTATE: HY000

Message: User is not part of any groups. However, account is configured to use group mapping.

Error number: MY-013816; Symbol: ER_AUTHENTICATION_OCI_NONCE; SQLSTATE: HY000

Message: Public/private key mismatch (fingerprint %s) while authenticating user %s in tenancy %s.

Error number: MY-013817; Symbol: ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_1; SOLSTATE: HY000

Message: %s: Warning Level 1 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqld=%llu MiB

Error number: MY-013818; Symbol: ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_2; SQLSTATE: HY000

Message: %s: Warning Level 2 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqld=%llu MiB

Error number: MY-013819; Symbol: ER_HEALTH_WARNING_MEMORY_USAGE_LEVEL_3; SQLSTATE: HY000

Message: %s: Warning Level 3 (%llu MiB): available=%llu MiB, total=%llu MiB, used=%.2f%%, mysqld=%llu MiB

Error number: MY-013820; Symbol: ER_GRP_RPL_SET_SINGLE_CONSENSUS_LEADER; SOLSTATE: HY000

Message: The member %s:%u, with UUID: %s, was set as the single preferred consensus leader.

Error number: MY-013821; Symbol:

ER GRP RPL ERROR SET SINGLE CONSENSUS LEADER; SQLSTATE: HY000

Message: Something went wrong trying to set the member %s:%u, with UUID: %s, as the single preferred consensus leader. Please query the

performance_schema.replication_group_communication_information table to see whether the operation took effect, i.e. whether the preferred consensus leader matches the current primary. If not, consider electing a different primary to try again. Please check the error log and GCS_DEBUG_TRACE for more information that may help understanding what went wrong.

Error number: MY-013822; Symbol: ER_GRP_RPL_SET_MULTI_CONSENSUS_LEADER;

SQLSTATE: HY000

Message: All members were set as consensus leaders.

Error number: MY-013823; Symbol:

ER_GRP_RPL_ERROR_SET_MULTI_CONSENSUS_LEADER; SQLSTATE: HY000 Message: Something went wrong trying to set all members as consensus leaders. Please query the performance_schema.replication_group_communication_information table to see whether the operation took effect, i.e. whether the consensus leaders match all members. If not, consider resetting the group communication protocol to a version < 8.0.22, or switch to single-primary mode and back again to multi-primary mode, to try again. Please check the error log and GCS_DEBUG_TRACE for more information that may help understanding what went wrong.

Error number: MY-013824; Symbol:

ER_GRP_RPL_PAXOS_SINGLE_LEADER_DIFF_FROM_GRP; SQLSTATE: HY000 Message: This member is configured with a group_replication_paxos_single_leader option value of '%d' that is different from the group's value ('%d'). This member will now exit the group.

Error number: MY-013825; Symbol: ER_MFA_USER_ATTRIBUTES_CORRUPT; SQLSTATE: HY000

Message: Invalid and/or corrupted multi factor authentication methods in User_attributes column in mysql.user table. "%s".

Error number: MY-013826; Symbol: ER_MFA_PLUGIN_NOT_LOADED; SQLSTATE: HY000 Message: Plugin \'%s\' is not loaded; Ignoring user

Error number: MY-013827; Symbol: ER_WARN_DEPRECATED_CHARSET_OPTION;

SQLSTATE: HY000

Message: %s: The character set %s is deprecated and will be removed in a future release. Please consider using %s instead.

Error number: MY-013828; Symbol: ER_WARN_DEPRECATED_COLLATION_OPTION;

SQLSTATE: HY000

Message: %s: '%s' is a collation of the deprecated character set %s. Please consider using %s with an

appropriate collation instead.

Error number: MY-013829; Symbol: ER REGEXP MISSING ICU DATADIR; SQLSTATE:

HY000

Message: Missing data directory for ICU regular expressions: %s.

Error number: MY-013830; Symbol: ER_IB_WARN_MANY_NON_LRU_FILES_OPENED;

SQLSTATE: HY000

Message: More than 90%% of files opened out of the innodb_open_files limit are files that are not easy to close. The performance of system may degrade. Consider increasing value of the innodb_open_files system variable. There are %zu such files opened out of the total limit for all files opened of %zu.

Error number: MY-013831; Symbol:

ER IB MSG TRYING TO OPEN FILE FOR LONG TIME; SQLSTATE: HY000

Message: Trying to open a file for %lld seconds. Configuration only allows for %zu open files.

Consider setting innobase open files higher.

Error number: MY-013832; Symbol: ER_GLOBAL_CONN_LIMIT; SQLSTATE: HY000

Message: Connection closed. Global connection memory limit %llu bytes exceeded. Consumed %llu

bytes.

Error number: MY-013833; Symbol: ER CONN LIMIT; SQLSTATE: HY000

Message: Connection closed. Connection memory limit %llu bytes exceeded. Consumed %llu bytes.

Error number: MY-013834; Symbol: ER_WARN_AUDIT_LOG_DISABLED; SQLSTATE: HY000

Message: Audit Log is disabled. Enable it with audit log disable = false.

Error number: MY-013835; Symbol: ER INVALID TLS VERSION; SQLSTATE: HY000

Message: Option --tls-version or --admin-tls-version is set to an invalid value %s.

Error number: MY-013836; Symbol: ER RPL RELAY LOG RECOVERY GTID ONLY;

SQLSTATE: HY000

Message: Relay log recovery on channel with GTID_ONLY=1. The channel will switch to a new

relay log and the GTID protocol will be used to replicate unapplied transactions.

Error number: MY-013837; Symbol:

ER KEYRING OKV STANDBY SERVER COUNT EXCEEDED; SQLSTATE: HY000

Message: Number of STANDBY_SERVER values exceeded maximum limit of 64.

Error number: MY-013838; Symbol: ER WARN MIGRATION EMPTY SOURCE KEYRING;

SQLSTATE: HY000

Message: Source keyring does not have any keys to migrate.

Error number: MY-013839; Symbol:

ER WARN CANNOT_PERSIST_SENSITIVE_VARIABLES; SQLSTATE: HY000

Message: Cannot persist SENSITIVE system variables because keyring component support is unavailable and persist_sensitive_variables_in_plaintext is set to OFF. Please make sure that keyring services are active and required keys are available.

Error number: MY-013840; Symbol:

ER_CANNOT_INTERPRET_PERSISTED_SENSITIVE_VARIABLES; SQLSTATE: HY000 Message: Cannot interpret persisted SENSITIVE system variables. Please make sure that keyring services are active and required keys are available.

Error number: MY-013841; Symbol:

ER_PERSISTED_VARIABLES_KEYRING_SUPPORT_REQUIRED; SQLSTATE: HY000 Message: Keyring has to be loaded through manifest file in order to support secure storage for persisted variables

Error number: MY-013842; Symbol:

ER PERSISTED VARIABLES MASTER KEY NOT FOUND; SQLSTATE: HY000

Message: Could not find master key %s in keyring

Error number: MY-013843; Symbol:

ER PERSISTED VARIABLES MASTER KEY CANNOT BE GENERATED; SQLSTATE:

HY000

Message: A new master key %s could not be generated

Error number: MY-013844; Symbol: ER_PERSISTED_VARIABLES_ENCRYPTION_FAILED;

SQLSTATE: HY000

Message: Failed to encrypt %s using %s

Error number: MY-013845; Symbol: ER PERSISTED VARIABLES DECRYPTION FAILED;

SQLSTATE: HY000

Message: Failed to decrypt %s using %s

Error number: MY-013846; Symbol:

ER_PERSISTED_VARIABLES_LACK_KEYRING_SUPPORT; SQLSTATE: HY000

Message: Persisting SENSITIVE variables in encrypted form requires keyring component loaded

through manifest file.

Error number: MY-013847; Symbol: ER_MY_MALLOC_USING_JEMALLOC; SQLSTATE:

HY000

Message: Using jemalloc.dll for my malloc and ut::malloc etc.

Error number: MY-013848; Symbol: ER MY MALLOC USING STD MALLOC; SQLSTATE:

HY000

Message: %s.

Error number: MY-013849; Symbol: ER MY MALLOC LOADLIBRARY FAILED;

SQLSTATE: HY000

Message: %s.

Error number: MY-013850; Symbol: ER MY MALLOC GETPROCADDRESS FAILED;

SQLSTATE: HY000

Message: %s.

Error number: MY-013851; Symbol: ER ACCOUNT WITH EXPIRED PASSWORD;

SQLSTATE: HY000

Message: Password for the account '%s'@'%s' has expired. To log in, either change it using a client

that supports expired passwords or send the change request to an administrator.

Error number: MY-013852; Symbol: ER THREAD POOL PLUGIN STARTED; SQLSTATE:

HY000

Message: Thread pool plugin started successfully with parameters: %s

Error number: MY-013853; Symbol:

ER THREAD POOL DEDICATED LISTENERS INVALID; SQLSTATE: HY000

Message: thread pool dedicated listeners cannot be set unless

thread pool max transactions limit > 0

Error number: MY-013854; Symbol: ER IB DBLWR BYTES INFO; SQLSTATE: HY000

Message: %s

Error number: MY-013855; Symbol: ER IB RDBLWR BYTES INFO; SQLSTATE: HY000

Message: %s

Error number: MY-013856; Symbol: ER_IB_MSG_LOG_FILE_IS_EMPTY; SQLSTATE: HY000 Message: The redo log file %s is empty, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file or try recovering without the redo files, in read-only mode, by providing --innodb-force-recovery=6.

Error number: MY-013857; Symbol: ER_IB_MSG_LOG_FILE_TOO_SMALL; SQLSTATE: HY000

Message: The redo log file %s is smaller than %llu bytes, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file.

Error number: MY-013858; Symbol: ER_IB_MSG_LOG_FILE_TOO_BIG; SQLSTATE: HY000 Message: The redo log file %s is larger than %llu bytes, which indicates it was not generated by InnoDB or become corrupted. Please restore the correct file.

Error number: MY-013859; Symbol: ER_IB_MSG_LOG_FILE_HEADER_READ_FAILED;

SQLSTATE: HY000

Message: Failed to read header of the redo log file %s

Error number: MY-013860; Symbol:

ER_IB_MSG_LOG_INIT_DIR_NOT_EMPTY_WONT_INITIALIZE; SQLSTATE: HY000 Message: --initialize specified but the redo log directory %s has redo log files inside. Aborting.

Error number: MY-013861; Symbol: ER_IB_MSG_LOG_INIT_DIR_LIST_FAILED; SQLSTATE:

HY000

Message: Failed to list redo log files in the redo log directory %s

Error number: MY-013862; Symbol: ER IB MSG LOG INIT DIR MISSING SUBDIR;

SOLSTATE: HY000

Message: Neither found %s subdirectory, nor %s* files in %s

Error number: MY-013863; Symbol:

 $ER_IB_MSG_LOG_FILES_CREATED_BY_CLONE_AND_READ_ONLY_MODE; SQLSTATE:$

HY000

Message: Cannot restore cloned data directory, InnoDB running in read-only mode!

Error number: MY-013864; Symbol: ER IB MSG LOG WRITER WRITE FAILED;

SQLSTATE: HY000

Message: Error %d encountered when writing to the redo log file: %s.

Error number: MY-013865; Symbol:

ER IB MSG LOG WRITER WAIT ON NEW LOG FILE; SQLSTATE: HY000

Message: Redo log writer is waiting for a new redo log file. Consider increasing

innodb redo log capacity.

Error number: MY-013866; Symbol:

ER IB MSG RECOVERY CHECKPOINT OUTSIDE LOG FILE; SQLSTATE: HY000

Message: Found checkpoint LSN %llu in a redo log file %s, but the file represents range of LSN values [%llu, %llu), so the file is corrupted.

Error number: MY-013867; Symbol:

ER IB MSG LOG WRITER ENTERED EXTRA MARGIN; SQLSTATE: HY000

Message: Redo log is running out of free space, pausing user threads... Consider increasing

innodb redo log capacity.

Error number: MY-013868; Symbol: ER IB MSG LOG WRITER EXITED EXTRA MARGIN;

SQLSTATE: HY000

Message: Redo log reclaimed some free space, resuming user threads.

Error number: MY-013869; Symbol: ER IB MSG LOG PARAMS FILE SIZE UNUSED;

SQLSTATE: HY000

Message: Ignored deprecated configuration parameter innodb log file size. Used

innodb redo log capacity instead.

Error number: MY-013870; Symbol: ER IB MSG LOG PARAMS N FILES UNUSED;

SQLSTATE: HY000

Message: Ignored deprecated configuration parameter innodb log files in group. Used

innodb redo log capacity instead.

Error number: MY-013871; Symbol: ER IB MSG LOG UPGRADE FORCED RECV;

SQLSTATE: HY000

Message: Cannot upgrade format (v%lu) of redo log files when innodb-force-recovery > 0.

Error number: MY-013872; Symbol: ER IB MSG LOG UPGRADE IN READ ONLY MODE;

SOLSTATE: HY000

Message: Cannot upgrade format (v%lu) of redo log files in read-only mode (--innodb-read-only).

Error number: MY-013873; Symbol: ER IB MSG LOG UPGRADE CLONED DB; SQLSTATE:

HY000

Message: Cannot upgrade format (v%lu) of redo log files on cloned data directory. Please use an

older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

Error number: MY-013874; Symbol: ER IB MSG LOG UPGRADE UNINITIALIZED FILES;

SQLSTATE: HY000

Message: Cannot upgrade format (v%lu) of redo log files because they are marked as uninitialized.

Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

Error number: MY-013875; Symbol:

ER IB MSG LOG UPGRADE CORRUPTION UNEXPECTED; SQLSTATE: HY000

Message: Cannot upgrade format (v%lu) of redo log files when the redo log is corrupted. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown \leq 2).

Error number: MY-013876; Symbol:

ER IB MSG LOG UPGRADE NON PERSISTED DD METADATA UNEXPECTED;

SQLSTATE: HY000

Message: Cannot upgrade format (v%lu) of redo log files when there is non-persisted DD metadata in redo. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

Error number: MY-013877; Symbol:

ER_IB_MSG_LOG_UPGRADE_FLUSH_FAILED__UNEXPECTED; SQLSTATE: HY000 Message: Cannot upgrade format (v%lu) of redo log files, because InnoDB failed to reach state in which redo log is logically empty. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

Error number: MY-013878; Symbol:

ER_IB_MSG_LOG_FILES_RESIZE_ON_START_FAILED__UNEXPECTED; SQLSTATE: HY000

Message: Failed to resize the redo log synchronously, because InnoDB failed to reach state in which redo log is logically empty. Please use an older version of MySQL - recover and shutdown (with innodb-fast-shutdown < 2).

Error number: MY-013879; Symbol: ER_IB_MSG_LOG_FILE_FOREIGN_UUID; SQLSTATE: HY000

Message: The redo log file %s comes from other data directory than redo log file %s.

Error number: MY-013880; Symbol: ER IB MSG LOG FILE INVALID START LSN;

SQLSTATE: HY000

Message: The redo log file %s has invalid start lsn %llu.

Error number: MY-013881; Symbol: ER_IB_MSG_LOG_FILE_INVALID_LSN_RANGES; SQLSTATE: HY000

Message: The redo log file %s has start_lsn %llu but expected %llu (end_lsn of the previous redo log file).

Error number: MY-013882; Symbol: ER_IB_MSG_LOG_FILE_MISSING_FOR_ID; SQLSTATE: HY000

Message: Missing redo log file %s (with start lsn = %llu).

Error number: MY-013883; Symbol: ER_IB_MSG_LOG_CHECKPOINT_FOUND; SQLSTATE: HY000

Message: The latest found checkpoint is at lsn = %llu in redo log file %s.

Error number: MY-013884; Symbol: ER IB MSG LOG FILES CAPACITY CHANGED;

SQLSTATE: HY000

Message: User has set innodb redo log capacity to %lluM.

Error number: MY-013885; Symbol: ER IB MSG LOG FILES RESIZE REQUESTED;

SQLSTATE: HY000

Message: Redo log has been requested to resize from %lluM to %lluM.

Error number: MY-013886; Symbol: ER IB MSG LOG FILES RESIZE CANCELLED;

SQLSTATE: HY000

Message: Redo log resize has been cancelled.

Error number: MY-013887; Symbol: ER IB MSG LOG FILES RESIZE FINISHED;

SQLSTATE: HY000

Message: Redo log has been resized to %lluM.

Error number: MY-013888; Symbol: ER_IB_MSG_LOG_FILES_UPGRADE; SQLSTATE: HY000

Message: Upgrading redo log: %lluM, LSN=%llu.

Error number: MY-013889; Symbol:

ER IB MSG LOG FILE MARK CURRENT AS INCOMPLETE; SQLSTATE: HY000

Message: Marked the current redo log file %s as incomplete.

Error number: MY-013890; Symbol: ER IB MSG LOG FILE REMOVE FAILED; SQLSTATE:

HY000

Message: Failed to remove redo log file %s.

Error number: MY-013891; Symbol:

ER IB MSG LOG FILE RENAME ON CREATE FAILED; SQLSTATE: HY000

Message: Failed to rename %s when creating redo log file %s (error: %d)

Error number: MY-013892; Symbol:

ER IB MSG LOG FILES CREATED BY UNKNOWN CREATOR; SQLSTATE: HY000

Message: Redo log files created by unknown creator %s.

Error number: MY-013893; Symbol: ER_IB_MSG_LOG_FILES_FOUND_MISSING; SQLSTATE:

HY000

Message: Found existing redo log files, but at least one is missing. It is unknown if recovery could reach physically consistent state. Please consider restoring from backup or providing --innodb-force-recovery > 0.

Error number: MY-013894; Symbol: ER IB MSG LOG FILE FORMAT TOO NEW;

SOLSTATE: HY000

Message: Found redo log file %s which has format (v%lu) and is stored outside #innodb redo.

Error number: MY-013895; Symbol: ER IB MSG LOG FILE FORMAT TOO OLD;

SQLSTATE: HY000

Message: Found redo log file %s which has format (v%lu) and is stored inside #innodb redo.

Error number: MY-013896; Symbol: ER IB MSG LOG FILE DIFFERENT FORMATS;

SQLSTATE: HY000

Message: Found redo log files with different formats: %s has format v%lu, %s has format v%lu.

Error number: MY-013897; Symbol: ER IB MSG LOG PRE 8 0 30 MISSING FILEO;

SQLSTATE: HY000

Message: Missing ib logfile0 in the directory %s.

Error number: MY-013898; Symbol: ER IB MSG LOG PFS ACQUIRE SERVICES FAILED;

SQLSTATE: HY000

Message: Failed to initialize services required to handle redo log PFS tables.

Error number: MY-013899; Symbol: ER IB MSG LOG PFS CREATE TABLES FAILED;

SOLSTATE: HY000

Message: Failed to create redo log PFS tables.

Error number: MY-013900; Symbol: ER IB MSG LOG FILE TRUNCATE; SQLSTATE: HY000

Message: Truncating redo log file %s...

Error number: MY-013901; Symbol: ER IB MSG LOG FILE UNUSED RESIZE FAILED;

SQLSTATE: HY000

Message: Failed to resize unused redo log file %s to %llu MB (%s).

Error number: MY-013902; Symbol: ER_IB_MSG_LOG_FILE_UNUSED_REMOVE_FAILED;

SOLSTATE: HY000

Message: Failed to remove unused redo log file %s.

Error number: MY-013903; Symbol: ER IB MSG LOG FILE UNUSED RENAME FAILED;

SQLSTATE: HY000

Message: Failed to rename unused redo log file %s to %s.

Error number: MY-013904; Symbol:

ER IB MSG LOG FILE UNUSED MARK AS IN USE FAILED; SQLSTATE: HY000

Message: Failed to mark unused redo log file %s as in use (by renaming to %s).

Error number: MY-013905; Symbol: ER_IB_MSG_LOG_FILE_MARK_AS_UNUSED_FAILED;

SQLSTATE: HY000

Message: Failed to mark redo log file %s as unused (by renaming to %s).

Error number: MY-013906; Symbol:

ER_IB_MSG_LOG_PARAMS_DEDICATED_SERVER_IGNORED; SQLSTATE: HY000 Message: Option innodb_dedicated_server is ignored for innodb_redo_log_capacity, because innodb_redo_log_capacity, innodb_log_file_size or innodb_log_files_in_group is specified explicitly. Redo log capacity: %lluM.

Error number: MY-013907; Symbol: ER IB MSG LOG PARAMS LEGACY USAGE;

SQLSTATE: HY000

Message: Deprecated configuration parameters innodb log file size and/or

innodb_log_files_in_group have been used to compute innodb_redo_log_capacity=%llu. Please use innodb_redo_log_capacity instead.

Error number: MY-013908; Symbol: ER_GRP_RPL_FAILED_TO_LOG_VIEW_CHANGE; SQLSTATE: HY000

Message: This member was unable to log the View_change_log_event into the binary log, hence it will leave the group. Please check that there is available disk space and add the member back to the group.

Error number: MY-013909; Symbol: ER_BINLOG_CRASH_RECOVERY_MALFORMED_LOG; SQLSTATE: HY000

Message: Found invalid event sequence while recovering from binary log file '%s', between positions %llu and %llu: %s. The recovery process was stopped early and no transaction was recovered. Side effects may be transactions in an inconsistent state between the binary log and the storage engines, or transactions kept by storage engines in a prepared state (possibly holding locks). Either fix the issues with the binary log or, to release possibly acquired locks, disable the binary log during server recovery. Note that disabling the binary log may lead to loss of transactions that were already acknowledged as successful to client connections and may have been replicated to other servers in the topology.

Error number: MY-013910; Symbol:

ER BINLOG CRASH RECOVERY ERROR RETURNED SE; SQLSTATE: HY000

Message: Storage engines failed to recover one or more transactions. The recovery process was stopped early, check previous Messages for the details on failed transactions. Side effects may be transactions in an inconsistent state between the binary log and the storage engines, or transactions kept by storage engines in a prepared state (possibly holding locks). Either fix the issues with the storage engine (out-of-memory, no disk space, etc) or, to release possibly acquired locks held by XA transactions, disable the binary log during server recovery and check consistency between storage engines and binary log files.

Error number: MY-013911; Symbol: ER BINLOG CRASH RECOVERY ENGINE RESULTS;

SQLSTATE: HY000

Message: Crash recovery finished in %s engine. %s

Error number: MY-013912; Symbol: ER BINLOG CRASH RECOVERY COMMIT FAILED;

SQLSTATE: HY000

Message: Failed to commit %s in %s, with failure code %s.

Error number: MY-013913; Symbol: ER BINLOG CRASH RECOVERY ROLLBACK FAILED;

SQLSTATE: HY000

Message: Failed to rollback %s in %s, with failure code %s.

Error number: MY-013914; Symbol: ER BINLOG CRASH RECOVERY PREPARE FAILED;

SQLSTATE: HY000

Message: Failed to prepare %s in %s, with failure code %s.

Error number: MY-013915; Symbol:

ER_COMPONENT_EE_SYS_VAR_REGISTRATION_FAILURE; SQLSTATE: HY000 Message: Cannot register variable '%s'. Please check if it is not already registered by another

component.

Error number: MY-013916; Symbol:

ER COMPONENT EE SYS VAR DEREGISTRATION FAILURE; SQLSTATE: HY000

Message: Cannot unregister variable '%s'. Please check if it was registered properly in the first place.

Error number: MY-013917; Symbol:

ER COMPONENT EE FUNCTION REGISTRATION FAILURE; SQLSTATE: HY000

Message: Cannot register function '%s'. Please check if it is not already registered.

Error number: MY-013918; Symbol:

ER COMPONENT EE FUNCTION DEREGISTRATION FAILURE; SQLSTATE: HY000

Message: Cannot unregister function '%s'. Please check if it was registered properly in the first place.

Error number: MY-013919; Symbol:

ER COMPONENT EE FUNCTION INVALID ARGUMENTS; SQLSTATE: HY000

Message: Invalid arguments to function '%s'. Expected values: %s.

Error number: MY-013920; Symbol:

ER COMPONENT EE FUNCTION INVALID ALGORITHM; SQLSTATE: HY000

Message: Invalid algorithm value '%s' in function %s.

Error number: MY-013921; Symbol:

ER COMPONENT EE FUNCTION KEY LENGTH OUT OF RANGE; SQLSTATE: HY000

Message: Invalid key length '%d' for function '%s' with algorithm '%s'. Please provide a value

between [%d, %d].

Error number: MY-013922; Symbol:

ER_COMPONENT_EE_FUNCTION_PRIVATE_KEY_GENERATION_FAILURE; SQLSTATE:

HY000

Message: Failed to generate private key of length '%d' with algorithm '%s' in function '%s'. More

details about the error would have been logged before this Message.

Error number: MY-013923; Symbol:

ER_COMPONENT_EE_FUNCTION_PUBLIC_KEY_GENERATION_FAILURE; SQLSTATE:

HY000

Message: Failed to generate public key with algorithm '%s' for given private key in function '%s'.

More details about the error would have been logged before this Message.

Error number: MY-013924; Symbol: ER COMPONENT EE DATA LENGTH OUT OF RAGE;

SQLSTATE: HY000

Message: Invalid data length '%d' (in bytes) for function '%s' with algorithm '%s'. The maximum

support data length for given private key is %d (in bytes).

Error number: MY-013925; Symbol: ER COMPONENT EE DATA ENCRYPTION ERROR;

SQLSTATE: HY000

Message: Could not encrypt data in function '%s' using algorithm '%s'. Data length was '%d' bytes.

More details about the error would have been logged before this Message.

Error number: MY-013926; Symbol: ER COMPONENT EE DATA DECRYPTION ERROR;

SQLSTATE: HY000

Message: Could not decrypt data in function '%s' using algorithm '%s'. Data length was '%d' bytes.

More details about the error would have been logged before this Message.

Error number: MY-013927; Symbol: ER COMPONENT EE DATA SIGN ERROR; SQLSTATE:

HY000

Message: Could not sign data in function '%s' using algorithm '%s' and digest type '%s'. More details about the error would have logged before this Message.

Error number: MY-013928; Symbol: ER_COMPONENT_EE_OPENSSL_ERROR; SQLSTATE: HY000

Message: Received OpenSSL error in function '%s' for algorithm '%s': '%s'

Error number: MY-013929; Symbol: ER_COMPONENT_EE_INSUFFICIENT_LENGTH; SQLSTATE: HY000

Message: In function '%s' with algorithm '%s': insufficient output buffer length '%zu'. Required length '%zu'.

Error number: MY-013930; Symbol: ER_SYSTEMD_NOTIFY_DEBUG; SQLSTATE: HY000 Message: %s%s

Error number: MY-013931; Symbol: ER_TMP_SESSION_FOR_VAR; SQLSTATE: HY000 Message: Setting session values for system variables only makes sense in a user session (failed to set '0%s').

Error number: MY-013932; Symbol: ER_BUILD_ID; SQLSTATE: HY000

Message: BuildID[sha1]=%s

Error number: MY-013933; Symbol:

ER THREAD POOL CANNOT REGISTER DYNAMIC PRIVILEGE; SQLSTATE: HY000

Message: Failed to register dynamic privilege %s.

3 赤兔管理系统错误信息参考

间 说明:

某些分支版本的错误码可能与本文略有差异,您也可以直接运营管理系统赤兔安装机中查看到类似错误信息:

/data/website/tdsqlpcloud/www/config/oss error code.php

0: ok。 10000: OSS 系统错误。 11000: OSS 输入参数错误。 11001: OSS setid 输入错误。 11002: OSS groupid 输入错误。 11003: OSS taskid 输入错误。 11004: 空返回值。 11005: 节点名错误。11006:数据库连接错误。11007:配置文件错误。11008:不支持的变量。 11009: 不合法变量值。 11010: 时间值错误。 11011: set 状态错误。 11012: groupid 或者 setid 填写错误。 11013: 创建修改 setrun job 失败。 11014: 获取 zk 的 taskid 节点失败。 11015: 获取 setinfo 信息失败。 11016: 没有锁定资源。 11017: 获取 zk 上默认的配置节点失 败。 11018: 重启时不能标识 json 对象。 11019: 字符串转 json 失败。 11020: SOL 参数错 误。 11021: SQL 执行失败。 11022: 连接 Mysql 失败。 11023: 扩容任务没有设定手动切换 路由,不支持手动切换。11024:在手动切换路由的任务中,扩容任务已经完成。11025:在 手动切换路由的任务中,扩容任务还没有完成,没有到可以切换路由的状态。11026:变量 在当前的 db 版本中不支持。 11027: 修改的 proxy 的配置中,包含重复的配置项目。 11028: 修改的 PROXY 的配置中,没有当前的这个配置。 11029: 修改 PROXY 的配置,回 写到 zk 重试多次失败。11030:输入的配置项目,和原有的配置相比没有变化。11031:网 关的配置在 zk 上有错误,某些字段 key 或者 value 为空。 11032: 回档获取 vipinfo 的时候, 回档得到的新 setid 和新 groupid 均为 empty。 11033: 从获取到的 setrun 中取信息错误。 11034: groupid 或者 setid 只支持填写一个。 11035: 获取 vipinfo 过程中的异常。 11036: 扩 容任务失败。 11037: swich 时 groupid 或 setid 不可设置。 11038: 时间错误。 11039: 当前 的 ddl 任务已经结束。 11040: 当前的 ddl 任务失败。 11041: 当前的 ddl 任务还不能切换。 11042: 当前的 dll 任务不存在。 11043: 扩容后的源 set 禁止解除隔离。 11044: 隔离实例失 败。 11045: 解除隔离失败。 11046: 从 zk 上获取节点,转换为 int 失败,多为获取 taskid 错 误。 11047: 从 zk 获取多源同步任务失败。 11048: db 不存在。 11049: 这个 set 的扩容任已 经完成或者失败。 11050: 这个 set 正在扩容任务中, 但是还没有的到切换路由的状态。 11051: 修改 noshard 和 groupshard 垂直扩容完成后手动切换路由中某个 set 设置失败。 11052: Binlog 日志分片接口返回的 code 显示失败,具体的查看 code 字段。 11053: 这个扩容 任务没有设置手动切换。 11054: 获取 group 或者 id 的 hostport 失败。 11055: 用户没有 grant 权限。 11056: 用户已经有啦 withgrantoption。 11057: 用户不包含 withgrantoption。 11058: 这个任务没有设置时间,不能修改时间。11059:任务不可重复。11060:禁止修改 proxy 配 置。 11061: proxy 的配置修改时间错误。 11062: proxy 的 start time 字段错误。 11063: setrun 中的 status 不为 0。 11064: setrun 中缺少 status 字段。 11065: taskids 这个参数错误。 11066: 这个输入的 group 和 task 任务中对应的 group 不一致。 11067: 多源同步任务中的 setid 为空。 11068: SetAutoSyncTaskByTaskIDS 中一些子任务成功一些子任务失败。 11069: group 中没有 set。 11070: 设置备机权重时,写 zk 多次重试失败。 11071: 获取 set 的 all config 节点失败。 11072: 修改配置失败,恢复原来的配置失败。 11073: 这个实例已 经有 tag 了。 11074: 实例没有 tag, 禁止添加 tag。 11075: 不需要重试扩容。 11076: 配置 不存在。 **11077**: 从 routezknode 获取第一个 set 失败。 **11078**: 创建用户失败。 **11079**: group 中 set 的数量异常。 **11080**: 获取 idc 和 idcweight 错误。 **11081**: 初始化 vip 信息失败。 11082: 初始化 vip 参数失败。 11083: 返回 VIP 信息错误。 11084: 加载库失败。 11085: 加 载库失败。 11086: 获取 vip 信息失败。 11087: 修改设备资源属性失败。 11088: 获取

setinfo 失败。 11089: oss 子任务错误。 11090: set 自动同步失败。 11091: 扩容任务类型异 常。 11092: 资源节点大小错误。 11093: 操作超时。 11094: 内部错误。 11095: 未知的类 型。 11096: setid 错误。 12001: oss 服务不存在该接口。 12100: ZKapi 错误。 12101: zk 节 点不存在。 12102: zk 权限验证失败。 12103: zkversion 冲突。 12104: zk 临时节点不存在子 节点。 12105: zk 节点已存在。 12106: zk 存在子节点。 12107: zk 节点可能过期。 12108: zk 不合法回调。 12109: zk 不合法 acl。 12110: zk 客户端权限校验失败。 12111: zk 关闭。 12112: zk 服务端无响应。12113: zk 会话转移, 操作被忽略。12114: zk 数据不合法。 14000: fence 的 type 字段内容为空。 14002: 多源同步已启动。 15001: 这个参数需要重启。 15002: 这个版本的 proxy 不支持 ssl。 15003: proxy 的配置参数中类型错误。 15004: 涉及 proxy 版本的错误。 15005: setrun 缺失 proxy 的配置, proxy 的数组为空。 15006: oss 缺失 enabled_ssl_proxy_min_version 这个配置项目。 15007: oss 缺失 enabled ssl proxy min version 这个配置项目的值错误,小于 0,或者异常。15008:获取 proxv配置时,gateway字段的格式错误。 15009: zk 上没有 defaultproxy 的配置节点。 15010: zk 上 defaultproxyconfig 节点异常。 15011: oss 执行命令失败。 15012: 获取 secretid 和 secretkey 失败。 15013: 获取 datakey 失败,调用获取 datakey 的脚本失败。 15014: 获取 KMS 失败, 调用 createCMK.py 失败。 15015: 开启 KMS 失败。 15016: 执行开启 CMK 脚本 失败。15017: 获取或者写加密 zk 节点失败。15018: 主密钥产生了, 需要生成数据密钥。 15019: 主密钥和数据密钥都产生了。 15020: KMS 服务已经开启。 15021: KMS 的 SDK 错 误。 15022: KMS 的位置错误。 15023: KMS 获取 CMK 的错误。 15024: listKMS 错误。 15025: KMS 的任务执行脚本失败。 15026: 禁止开始 KMS。 15027: agent@global 这和节点 下面的一下值错误。 15028: defaultservice 这节点中某些值错误。 15029: 调用 KMS 的接口 参数错误。 15030: 所有 set 的 size 错误。 15031: 所有的配置项都没有改动。 15032: proxy 注册节点缺少时间字段。 15033: proxy 重启还没有成功。 15034: KMS 获取 dbversion 错 误。15035: KMS 脚本执行返回的结果错误,无法解析。15036: 没有开启 KMS 服务。 15037: zk上 kms encryptionnode 信息错误。 15038: 当前的时间没有的到轮换的时间,不需 要轮换。 15039: 没有开启 KMS 服务。 15040: KMSbaseinfo 信息错误。 15041: 机器故障, 重新安装 db 上的实例,安装失败。15042: manager 资源节点错误。15043: 同步任务信息失 败。 15044: 无效操作。 15045: 创建任务失败。 19999: 未知错误。 20001: 输入机型没有 找到对应配置信息。 20002: 输入购买资源信息有误。 20003: 指定购买强同步信息有误, 仅 支持 0, 1, 2 或者-1 (不指定)。 20005: 指定机器资源池中不存在。 20006: 根据 ip 获取 manager 配置信息失败。 20012: 申请不到可使用 mysql 端口。 20013: 机器资源处于 busy 状 态。 20016: 指定 slavezone, 但没有指定 masterzone。 20017: 指定 zone 个数大于购买节点 数。 20018: 指定 idc 购买信息有误。 20019: 指定 idc 购买节点数与输入节点数不一致。 20020: 找不到符合条件的资源。20021: 要执行任务已经超时未处理。20023: 获取初始化 任务节点失败。 20024: 初始化的 group 正在水平扩容中。 20025: 获取删除 set 的 proxyport 失败。 20026: 机器不存活。 20027: 获取 setrunzk 节点失败。 20028: 获取购买实例任务节 点失败。 20029: set 处于删除隔离中,不能发起初始化。 20030: 获取 setinfozk 节点失败。 **20031**: 获取 sethostdirzk 节点失败。 **20032**: 连接 db 失败。 **20033**: 创建系统账号失败。

20034: 删除任务正在进行中,不需要重新发起。20035: 初始化的 group 正在删除。

20036: 初始化任务正在执行中,不需要重新发起。 20037: 获取 setconfigzk 节点失败。

20038: 获取初始化任务应答节点失败。 20039: 获取 setsparkconfigzk 节点失败。 20040: 获 取购买实例任务应答节点失败。 20041: 获取删除隔离任务节点失败。 20042: 删除隔离任务 正在执行中,不需要重新发起。 20043: 判断 set 冷备节点是否存在失败。 20044: 判断 set 网 关查询节点失败。 20045: 解除删除隔离 set 不在删除隔离中。 20046: 初始化的 group 正在 授权流程中。 20047: set 正在扩容中,不需要重新发起。 20048: set 未初始化。 20049: 获 取 setrsinfozk 节点失败。 20050: 获取 rsinfo 节点中磁盘目录失败。 20051: 缩容的目标磁盘 小于当前使用量的 1.25 倍。 20052: 扩容 set 的 db 版本不支持。 20054: 扩容源 set 的主机不 存活。 20055: 扩容源 set 的备机不存活。 20056: 获取 host 的心跳节点失败。 20058: 扩容 手动切换参数错误, 仅支持0或者1。20059: 获取扩容任务节点失败。20064: 获取回档任 务节点失败。 20066: 初始化的 group 正在执行 xa 任务。 20067: 独享集群购买实例必须输 入机型信息。 20068: 备份源 setzk 配置信息到 set 失败。 20069: 获取 group 任务节点失败。 20070: 获取 zkrootdir 配置信息失败。 20071: 输入分片数为 0 或者大于系统配置值。 20072: 输入允许 shard 二级分区表个数小于等于 0。 20073: 指定退化参数有误, 仅支持 0 或 1。 20074: 开启退化,但退化时间为负值。 20075: 获取 group 任务应答节点失败。 20076: group 正在建立 dcn 中。 20077: group 正在删除中,不需要再发起。 20079: group 执行授权 任务中。 **20080**: 获取 grouppriv 节点失败。 **20081**: 输入的 fenceid 与 groupfenceid 不一致。 20082: 要回档的 group 正在删除中。 20083: 获取 groupzone 节点失败。 20084: 指定分区段 非法。 20086: 获取 groupinitzk 节点失败。 20088: 找不到可分的分区段。 20090: 获取水平 扩容任务节点失败。 20091: group 正在执行 xa 任务中。 20096: group 处于隔离状态。 **20098**: group 正在删除中。 **20099**: 输入任务类型不支持。 **20100**: 垂直扩容 group 任务正在 执行中。 20104: 获取水平扩容任务应答节点失败。 20107: 获取 noshard 快速回档任务节点 失败。 20108: 获取备份节点失败。 20109: 获取备份 initspec 节点失败。 20110: 获取快速 回档全局配置节点失败。 20114: 获取回档任务节点失败。 20115: 获取回档任务应答节点失 败。 20116: 要删除的 group 存在 dcn 关系。 20117: group 正在回档中,不需要重新发起。 20118: 获取要回档点备份 zone 信息失败。 20119: 获取 groupencrypt 节点失败。 20120: 设 置新 groupgroupencrypt 节点失败。 20123: 获取回档购买 set 记录节点失败。 20124: 获取回 档购买成 set 记录节点失败。 20125: 要删除的 group 正在执行设置只读任务。 20126: 要删 除的 group 正在执行授权操作。 20127: 要删除的 group 正在执行删除扩容后的 set 任务。 20128: 要删除的 group 正在执行 xa 任务。 20129: 要删除的 group 正在回档中。 20130: 要

20128: 要删除的 group 止在执行 xa 任务。 20129: 要删除的 group 止在回档中。 20130: 要删除的 group 正在垂直扩容中。 20131: 要删除的 group 正在激活任务中。 20132: 要删除的 group 正在初始化中。 20133: 要删除的 group 正在水平扩容中。 20134: 要重装 set 正在重启中。 20135: 要重装 set 正在回档中。 20140: 获取资源 specinfozk 节点失败。 20141: 获取重启任务节点失败。 20143: set 正在重启中,不需要重新发起。 20144: 获取重启任务应答节点失败。 20146: set 主备切换失败。 20150: 执行安装命令失败。 20152: 发送安装命令后zk 上没有生成 instanceinit 节点。 20154: 获取整机替换任务节点失败。 20156: 整机替换任务正在执行中。 20176: 要删除的 set 在路由表中。

20199: 获取重装任务节点失败。 **20200**: 要重装 set 正在扩容中。 **20201**: set 主节点不允许 重装。20202: 要重装的端口不在 setrun 中。20203: 要重装的端口已经在重装中,不需要重 新发起。 20204: 该 set 只有一个强同步备机,不允许重装。 20206: 执行重装命令失败。 20207: 输入参数非法。 20208: 获取授权账号失败。 20209: 授权不支持 db 版本。 20212: 添加 ip 输入参数非法。 20213: group 正在水平扩容中,不能授权。 20214: 删除 ip 输入参数 非法。 20215: 从 db 权限中获取库表名失败。 20216: 重置密码输入参数非法。 20217: 账 号 db 不存在。 20218: 替换 host 操作的 set 正在删除中。 20219: 删除用户输入参数非法。 20220: 拷贝权限的源和目标账号密码不一致。 20221: 替换 host 操作的 set 正在初始化。 **20222**: 添加权限输入参数非法。 **20223**: 重装任务重试超时失败。 **20224**: user 或者 host 为 空。 20225: 删除权限输入参数非法。 20226: 获取 free 机器无法满足申请独享集群需求。 **20227**: 目标账号 db 不存在。 **20228**: 拷贝账号权限输入参数非法。 **20229**: 获取 usercheck 节点失败。 20230: free 机器 idc 个数小于申请独享集群模式。 20231: 拷贝权限源和目标同 一个。20232: 获取密码失败。20233: 授权并拷贝权限输入参数非法。20234: 二级分区表 zk 节点不存在。 20235: group 正在删除中,不能授权。 20236: group 正在初始化中,不能 授权。 20237: 没有 groupid 信息。 20238: 拷贝二级分区权限输入参数非法。 20240: 获取 申请独享集群任务节点失败。 20241: 删除独享集群没有获取相关机器。 20242: 自动生成的 fenceid 重复。 20243: 申请独享集群指定 fenceid 已存在。 20244: 申请独享集群输入参数非 法。20245: 独享集群机器个数不是独享集群模式整数倍。20246: 指定要独享集群中删除的 机器与 zk 上独享集群节点记录不一致。 20247: 获取给独享集群添加机器任务节点失败。 20248: 给独享集群机器任务的模式与 zk 上独享集群里面模式不一致。 20250: free 机器个数 小于申请机器数。 20251: 打包目录磁盘空间太小。 20252: 获取 zk 独享集群节点失败。 20255: 从独享集群中要删除的机型没有找到。 20256: 执行获取打包目录磁盘空间失败。 20274: 授权的密码和 zk 配置文件不一致。 20275: 创建 usercheck 到 zk 失败。 20279: 获取 group 快速回档任务节点失败。 20280: 获取 group 备份节点失败。 20281: 获取 group 快速回 档任务应答节点失败。 20282: 删除独享集群的机器不是 free 状态。 20283: 获取 setvipzk 节 点失败。 20284: 逻辑扩容当前 db 版本不支持。 20287: 连接 zk 失败。 20288: 输入 dcn 参 数非法。 20289: 获取 dcn 关系节点失败。 20290: 建立的 set 为备,并且存在 dcn 关系。 **20291**: 建立 dcn 关系的 setdb 版本不一致。 **20293**: 建立 dcn 的备机存在非默认的库。 20295: 获取建立 dcn 主 set 的系统账号失败。 20296: 创建 dcn 关系节点失败。 20297: 建立 dcn 主 set 上 dcnslave 节点失败。 **20298**: 获取 dcn 主 set 上 dcnslave 节点失败。 **20299**: group 快速回档任务正在执行中。 20300: 要回档的时间点没有对应备份数据。 20301: 建立 dcn 关 系的 set 初始化参数不一致。 **20302**: 建立 groupden 拷贝 shardkey 节点失败。 **20303**: 建立 groupden 拷贝 sequenceid 节点失败。 20304: 建立 groupden 路由分区段不一致。 20306: 执行 sql 失败。 20312: 获取扩容 noshardset 标签节点失败。 20313: set 设置标签,不能被删除。 **20314**: set 有特殊标签,不允许删除隔离该 set。 **20315**: 获取 group 标签节点失败。 **20316**: group 存在特殊标签不允许删除。 20321: 独享集群删除机器找到符合要求机器个数与请求个 数不一致。 **20322**: 指定机器的 fenceid 和购买输入 fenceid 不一致。 **20324**: 建立 dcn 的 set 加密 key 不一致。 20325: proxy 打包目标目录权限不对。 20332: 扩容源 set 存在标签,不允 许扩容。 **20334**: noshard 建立 dcn 任务执行中。 **20336**: groupdcn 切换任务正在执行中。 **20338**: 执行远程命令失败。 **20339**: proxy 打包脚本不存在。 **20340**: 打包 proxy 安装包失 败。 20342: 推 proxy 安装包到目标机器失败。 20344: db 打包脚本不存在。 20345: 打包 db 安装包失败。 20346: 推 db 安装包到目标机器失败。 20348: 在进行扩容中不允许 dcn 切 换。 20349: 在建立 dcn 关系时不允许 dcn 切换。 20350: 要切换 dcn 主 set 也是其他 dcn 关 系的备。 20351: 获取 groupden 切换任务应答节点失败。 20352: 替换 host 任务正在执行 中。 20353: 要删除的 host 不在 setrun 节点中。 20354: 要删除的 set 正在回档中。 20355: 指定 ip 存在同 IDC, 默认不允许。 20356: 资源固定模式下备机个数与指定机器不一致。 20357: 机器处于隔离状态。 20358: 机器资源不满足购买需求。 20359: 机器处于锁定状 态。 20360: 找不到符合 masterzone 的机器。 20361: 找不到符合 slavezone 的机器。 20362: zone 模式下找到机器个数不满足购买节点数。 20363: idc 模式下找到机器个数不满 足购买节点数。20364: 云平独享集群购买没有找到机器资源。20365: 获取机型配置信息失 败。 20366: 要删除的 set 正在扩容中。 20368: 要删除的 set 为 masterdon。 20369: 要删除 的 set 为 slavedcn。 20370: 要删除的 set 正在 replaceip。 20371: 要删除的 set 正在 replacehost。 20372: 要删除的 set 正在购买流程中。 20373: 要删除的 set 正在初始化中。 20374: 要删除的 set 在设置只读任务中。 20375: 要删除的 set 在重启 set 流程中。 20376: 要初始化 set 正在购买流程中。 20377: 要初始化 set 正在 reinstall 流程中。 20378: 要初始化 set 正在重启流程中。 20379: 要初始化 set 正在 replacehost 中。 20380: 要初始化 set 正在 replaceip 流程中。 20381: 获取 setproxyconfigzk 节点失败。 20382: 要重启的 set 正在主备切 换中。 20383: 要重启的 set 正在删除流程中。 20384: 要重启的 set 正在扩容流程中。 **20385**: 要重启的 set 正在回档中。 **20386**: 要重启的 set 正在重装流程中。 **20387**: 扩容源 set 正在主备切换中。 20388: 扩容源 set 正在删除中。 20389: 扩容源 set 正在重启中。 20390: 扩容源 set 正在重装中。 20391: 扩容源 set 正在执行 dcn 任务。 20392: 扩容源 set 正在进行 dcn 切换任务。 20393: 回档 set 正在主备切换中。 20394: 回档 set 正在删除中。 20395: 回 档 set 正在重启中。 20396: 回档 set 正在重装中。 20397: 要重装 set 正在主备切换中。 **20398**: 要重装 set 正在删除中。 **20399**: 垂直扩容的 group 正在删除中。 **20400**: 垂直扩容的 group 正在水平扩容中。 20401: 垂直扩容的 group 正在授权中。 20402: 垂直扩容的 group 正 在执行 XA 任务中。 20403: 垂直扩容的 group 正在建立 dcn 关系中。 20405: 要回档的 group 正执行 XA 任务。 **20406**: 当前正在删除 group 中。 **20407**: 要删除的 set 正在初始化。 **20408**: 当前 group 正在回档中。 **20409**: 要删除的 set 正在水平扩容。 **20410**: 建立 dcn 的 set 正在扩容中。 20411: 建立 dcn 的 set 正在 dcn 切换中。 20412: 建立 dcn 的 set 正在删除中。 **20413**: 建立 groupden 正在垂直扩容。 **20414**: 建立 groupden 正在水平扩容。 **20415**: 建立 groupden 正在删除 group 中。 20416: group 正在垂直扩容中,不允许 den 切换。 20417: group 正在水平扩容中,不允许 dcn 切换。 20418: 备份 usercheck 到 db 失败。 20419: 获取 db 中权限内容格式有问题。 20420: 没有找到目标用户权限添加 withgrantoption。 20431: 分 离版本获取购买实例任务失败。 20432: 获取上报 proxy 机器任务节点失败。 20433: 上报的 proxy 机器已经存在。 20434: 购买实例输入的 gwgroup 不存在。 20435: 购买实例没有可用 的 gwgroup。 20436: 校验输入 vip 状态失败。 20437: 输入网关组和端口都为空。 20438:

没有可用的网关组。 20439: 网关组状态不是 free 和 release 状态。 20440: 分离版本 vip 操作 失败。20441:通过网页获取密码失败。20442:分离版本删除实例检测是否存在网关失败。 20443: 获取申请网关组任务失败。 20444: 申请网关组指定 ip 为空。 20445: 申请网关组指 定 ip 不是 ipv6 机器。 20446: 申请网关组指定 ip 不是 free 机器。 20447: 申请网关组输入参 数有误。 20448: 申请网关组资源不足。 20449: 获取网关端口 zk 节点失败。 20450: 获取 机器网关组端口不足。20451: 删除网关回收端口失败。20452: 删除网关组输入参数有误。 **20453**: 删除网关组的 groupid 不存在。 **20454**: 要删除的网关组有端口在使用。 **20455**: 网关 组有端口在安装中。 20456: 网关组有 leave 标识。 20457: 获取网关组安装配置节点失败。 20458: 合并网关组源和目标 group 相同。 20459: 合并网关组源网关组不存在。 20460: 合 并网关组源网关组状态异常。20461:合并网关组源网关组存在指定安装端口。20462:合并 网关组源网关组没有使用端口。 20463: 合并网关组目标网关组不存在。 20464: 合并网关组 目标网关组存在指定安装端口。20465: 合并网关组目标网关组状态异常。20466: 安装网关 端口失败。 20467: 获取扩容网关任务节点失败。 20468: 扩容网关输入参数有误。 20469: 要缩容的网关组中没有指定 ip。 20470: 要缩容的网关组只有一台机器了。 20471: 获取移除 网关组失败。 20472: 要移除网关组状态不对。 20473: 获取 proxysupervisor 节点失败。 20474: 获取 ressetinfo 节点失败。 20475: 获取使用网关资源失败。 20476: 获取 proxy 监控 节点失败。 20477: 需要屏蔽端口不在网关组中。 20478: 获取 pro setzk 节点失败。 20479: 删除分离版本 group 未指定 groupid。 20480: 指定 ip 不在该实例备机中。 20481: 设置延迟 备机输入参数有误。 20482: 要设置延迟备机为 set 的唯一强同步备机。 20483: 上报 lvs 机 器输入参数有误。 20484: 上报 lvs 机器已经存在。 20485: 上报 lvs 机器的子网掩码有误。 20486: 删除 lvs 机器不存在。 20487: lvs 上报任务参数有误。 20488: 创建 lvsgroup 已经存 在。 **20489**: 添加 ip 到 lvsgroup 已经存在。 **20490**: ip 要添加/删除到 lvsgroup 不存在。 **20491**: 获取 iplvs 状态节点失败。 **20492**: iplvs 状态不是 free。 **20493**: 要删除 lvsgroup 中只 有一个 ip。 **20494**: 要从 lvsgroup 删除的 ip 不存在。 **20495**: iplvs 状态不是 used。 **20496**: lvsjob 输入参数有误。 **20497**: lvs 机器 zk 节点不存在。 **20498**: lvs 机器状态非 free。 **20499**: lvs 机器与 vip 不是同一网段。 **20500**: lvs 机器 idc 不同。 **20501**: assignvip 输入参数 有误。 20502: assignvip 不支持多 vip 同时操作。 20503: assignvip 的 vip 没有关联实例。 **20504**: assignvip 的 viptype 不存在。 **20505**: proxyassign 输入参数有误。 **20506**: 网关组状态 不是 portmanual。 20507: 网关组增加指定端口输入参数有误。 20508: 网关组增加指定端口 在使用中。 **20509**: 获取 pro_groupzk 节点失败。 **20510**: 网关组状态不是 portauto。 **20511**: 获取 globalportzk 节点失败。 20512: globalport 不足。 20513: groupshard 并行多实例购买任 务参数有误。 20514: proxy 上报监控节点不存在。 20515: groupmultijob 正在执行中。 **20516**: 获取 groupmultijobzk 应答节点失败。 **20517**: 将 group 添加独享集群未找到 groupid。 **20518**: 要切换路由的 set 不是回档的原 set。 **20519**: 将 group 添加到独享集群 fenceid 为 none。 20520: 将 group 添加独享集群该 group 下 set 在多个 fenceid 中。 20521: 获取 setconfig all 节点失败。 20522: 获取符合要求资源节点个数为 0。 20523: 从 specinfo 节点获 取机型配置信息失败。 20524: 从 specinfo 获取 proxy 机型安装参数失败。 20525: 该机型数 据盘和日志盘个数不一致。 20526: 模式 3 情况下 zone 个数小于机器节点数。 20527: 获取

迁移网关组失败。 20528: 迁移的目标网关组不支持 ipv6。 20529: 要迁移的端口为源网关组 disable 端口。 20530: 要迁移的端口为目标网关组 used 端口。 20531: 在同版本下要迁移的 端口为目标网关组 free 端口。 20532: 要迁移的端口不是源网关组 used 端口。 20533: groupshard 回档获取 set 指定 ip 失败。 20534: 添加备机机器上端口已经使用。 20535: 获取 重做 dcn 备 set 任务节点失败。 20536: 要重做的 set 不是 dcnslave。 20537: 要重做的 set 正 在主备切换。 20538: 获取修改 dcn 配置任务节点失败。 20539: 配置 dcn 数据同步暂停恢复 参数错误。 20540: 配置 dcn 备 set 是否只读参数错误。 20541: noshardsetdcn conf 节点不存 在。 20542: 获取 noshardsetdcn conf 节点失败。 20543: groupshardgroup dcn 节点不存在。 20544: 配置 dcn 选举逻辑主参数错误。 20545: 通过 zone 添加备机获取机器失败。 20546: 获取批量重做 dcn 备 set 任务节点失败。 20547: 任务被手动终止执行。 20548: 指定具体网 关组端口购买失败,端口不可用。 20549:解析 tcp 上 proxy 授权任务失败。 20550: dcn 数据 同步停止状态,不允许重做 dcn 备机。 20551: 删除 group 重试 5 次失败。 20552: 获取 group 下 jobrelation 节点失败。 20553: group 正在回档中, 删除失败。 20554: 设置提升同 IDC 模式类型错误。 20555: 同时设置提升同 IDC 模式和可退化。 20556: 获取跨集群 noshard 回档任务节点失败。 20557: 获取冷备类型失败。 20558: 获取 set 冷备元数据失败。 20559: 下载 set 冷备元数据失败。 20560: 获取跨集群回档任务 answer 节点失败。 20561: 获取跨集群 groupshard 回档任务失败。 20562: 获取跨集群 groupshard 回档任务 answer 节点 失败。 20563: 跨集群 groupshard 回档任务正在进行中。 20564: 获取 group 冷备元数据失 败。 20565: 下载 group 冷备元数据失败。 20566: 设置 dcnstop sql 输入参数有误。 20567: groupsharddcn 水平扩容任务已经存在。 30001: 购买 set 任务状态错误。 30002: 购买 set 任 务类型错误。 30003: 购买 set 端口已经被使用。 30004: 购买 set 任务使用 setname 已经存 在。 30005: 购买 set 获取解密 key 失败。 30007: 购买 set 解密密文密码失败。 30008: 获取 setconfig 节点失败。 30009: 解析 setconfig 节点内容失败。 30010: 获取扩容任务 gjid 失败。 **30011**: 获取扩容 setconnection 节点失败。 **30012**: 获取扩容 job 节点失败。 **30013**: 获取扩 容源 set 失败。 30014: 扩容任务目标 set 不一致。 30015: 扩容任务状态错误。 30016: 扩容 设置只读失败。 30017: 获取水平扩容 setconnection 节点失败。 30018: 获取水平扩容 job 节 点失败。 30019: 获取水平扩容目标 set 失败。 30020: 水平扩容任务目标 set 不一致。 30021: 水平扩容任务状态错误。30022: 水平扩容设置只读失败。30023: 获取水平扩容源 set 失败。 30024: 水平扩容手动输入路由分段错误。 30026: 主备切换去掉 master 节点失 败。30027: 主备切换主节点恢复。30028: 主备切换任务正在进行中,不需要重复触发。 **30029**: 获取心跳节点失败。 **30030**: 主备切换 sqldelay 校验失败。 **30031**: 主备切换 iodelay 校验失败。 30032: 主备切换中选举备机不存活。 30033: 主备切换中上报 binlog 格式错误。 30034: 主备切换中上报 binlog 位置错误。 30035: 主备切换上报 binlog 失败。 30036: 主备 切换获取 applyhost 失败。 30037: 主备切换 applybinlog 失败。 30038: 替换实例主节点。 **30039**: 主备切换任务超时。 **30040**: dcn 切换任务参数错误。 **30041**: 获取 setrun 节点失败。 30042: 获取 hb 心跳节点失败。 30043: dcn 切换备 dcn 实例延迟过大。 40001: 获取 ZK 参 数节点异常。 40002: 解析 zkjson 参数失败。 40003: oc 密码字段不能同时指定明文及秘 文。 40004: oc 密码未指定。 40005: oc 密码解密失败。 40006: 端口获取为空。 40007: db

版本号格式错误。40008: db 版本号不支持。40009: 安装目录已存在。40010: 创建目录tdsql_run 失败。40011: 创建实例端口目录失败。40012: 同版本安装 db 解压失败。40013: 拷贝 db 文件失败。40014: db 安装失败。40015: 加密 agent 配置文件秘文失败。40016: 拷贝 agent 文件失败。40017: 启动 agent 失败。40018: 同版本安装网关解压失败。40019: 拷贝网关文件失败。40020: 启动网关失败。40021: 启动 dcagent 失败。40022: 删除网关解压目录失败。40023: 启动生产者失败。41013: 无法获取可用的镜像。42001: 安装网关的获取端口参数为空。42002: 网关的端口安装目录已存在。42003: 创建目录tdsql_run 失败。42004: 创建网关端口目录失败。42005: 磁盘空间不足。42006: 同版本安装网关解压失败。42007: 拷贝网关 gateway 包失败。42008: 网关启动命令执行失败。42009: 网关由于端口被其他进程占用,启动失败。42010: 网关进程不断重启,无法正常工作。42011: 启动 dcagent 失败。42012: 删除网关解压目录失败。50001: onlineddl 操作错误。50002: onlineddl 操作已经运行。50003: 停止安全检查任务失败。