


Recursion and Fibonacci Sequence



The Recursion Pattern

- ❑ **Recursion:** when a method calls itself
- ❑ Classic example--the factorial function:
 - $n! = 1 \cdot 2 \cdot 3 \cdot \dots \cdot (n-1) \cdot n$
- ❑ Recursive definition:

$$f(n) = \begin{cases} 1 & \text{if } n = 0 \\ n \cdot f(n-1) & \text{else} \end{cases}$$

- ❑ As a C++ method:

```
// recursive factorial function
int recursiveFactorial(int n) {
    if (n == 0) return 1;    // basis case
    else return n * recursiveFactorial(n-1); // recursive case
}
```

Linear Recursion

- Test for base cases

- Begin by testing for a set of base cases (there should be at least one).
- Every possible chain of recursive calls **must** eventually reach a base case, and the handling of each base case should not use recursion.

- Recur once

- Perform a single recursive call
- This step may have a test that decides which of several possible recursive calls to make, but it should ultimately make just one of these calls
- Define each possible recursive call so that it makes progress towards a base case.

Example of Linear Recursion

Algorithm LinearSum(A, n):

Input:

A integer array A and an integer $n = 1$, such that A has at least n elements

Output:

The sum of the first n integers in A


if $n = 1$ **then**

return $A[0]$

else

return LinearSum($A, n - 1$) + $A[n - 1]$

Example recursion trace:



Reversing an Array

Algorithm ReverseArray(A, i, j):

Input: An array A and nonnegative integer indices i and j

Output: The reversal of the elements in A starting at index i and ending at j

if $i < j$ **then**

 Swap $A[i]$ and $A[j]$

 ReverseArray($A, i + 1, j - 1$)

return

Defining Arguments for Recursion

- ❑ In creating recursive methods, it is important to define the methods in ways that facilitate recursion.
- ❑ This sometimes requires we define additional parameters that are passed to the method.
- ❑ For example, we defined the array reversal method as `ReverseArray(A , i , j)`, not `ReverseArray(A)`.

Computing Powers

- The power function, $p(x,n)=x^n$, can be defined recursively:

$$p(x,n) = \begin{cases} 1 & \text{if } n = 0 \\ x \cdot p(x,n-1) & \text{else} \end{cases}$$

- This leads to a power function that runs in $O(n)$ time (for we make n recursive calls).
- We can do better than this, however.

Recursive Squaring

- We can derive a more efficient linearly recursive algorithm by using repeated squaring:

$$p(x, n) = \begin{cases} 1 & \text{if } x = 0 \\ x \cdot p(x, (n-1)/2)^2 & \text{if } x > 0 \text{ is odd} \\ p(x, n/2)^2 & \text{if } x > 0 \text{ is even} \end{cases}$$

- For example,

$$2^4 = 2^{(4/2)^2} = (2^{4/2})^2 = (2^2)^2 = 4^2 = 16$$

$$2^5 = 2^{1+(4/2)^2} = 2(2^{4/2})^2 = 2(2^2)^2 = 2(4^2) = 32$$

$$2^6 = 2^{(6/2)^2} = (2^{6/2})^2 = (2^3)^2 = 8^2 = 64$$

$$2^7 = 2^{1+(6/2)^2} = 2(2^{6/2})^2 = 2(2^3)^2 = 2(8^2) = 128.$$

Recursive Squaring Method

Algorithm **Power**(x, n):

Input: A number x and integer $n = 0$

Output: The value x^n

if $n = 0$ **then**

return 1

if n is odd **then**

$y = \text{Power}(x, (n - 1)/2)$

return $x \cdot y \cdot y$

else

$y = \text{Power}(x, n/2)$

return $y \cdot y$

Analysis

Algorithm **Power**(x, n):

Input: A number x and integer $n = 0$

Output: The value x^n

if $n = 0$ **then**

return 1

if n is odd **then**

$y = \text{Power}(x, (n - 1)/2)$

return $x \cdot y \cdot y$

else

$y = \text{Power}(x, n/2)$

return $y \cdot y$

Each time we make a recursive call we halve the value of n ; hence, we make $\log n$ recursive calls. That is, this method runs in $O(\log n)$ time.

It is important that we use a variable twice here rather than calling the method twice.

Tail Recursion

- ❑ Tail recursion occurs when a linearly recursive method makes its recursive call as its last step.
- ❑ The array reversal method is an example.
- ❑ Such methods can be easily converted to non-recursive methods (which saves on some resources).

Reversing an Array

Algorithm ReverseArray(A, i, j):

Input: An array A and nonnegative integer indices i and j

Output: The reversal of the elements in A starting at index i and ending at j

if $i < j$ **then**

 Swap $A[i]$ and $A[j]$

 ReverseArray($A, i + 1, j - 1$)

return

Tail Recursion

- ❑ Tail recursion occurs when a linearly recursive method makes its recursive call as its last step.
- ❑ The array reversal method is an example.
- ❑ Such methods can be easily converted to non-recursive methods (which saves on some resources).
- ❑ Example:

Algorithm IterativeReverseArray(A, i, j):

Input: An array A and nonnegative integer indices i and j

Output: The reversal of the elements in A starting at index i and ending at j

while $i < j$ **do**

 Swap $A[i]$ and $A[j]$


$i = i + 1$

$j = j - 1$

return

Binary Recursion

- ❑ Binary recursion occurs whenever there are **two** recursive calls for each non-base case.
- ❑ Example: the DrawTicks method for drawing ticks on an English ruler.



A Binary Recursive Method for Drawing Ticks

```
// draw a tick with no label
public static void drawOneTick(int tickLength) { drawOneTick(tickLength, - 1); }
// draw one tick
public static void drawOneTick(int tickLength, int tickLabel) {
    for (int i = 0; i < tickLength; i++)
        System.out.print("-");
    if (tickLabel >= 0) System.out.print(" " + tickLabel);
    System.out.print("\n");
}
public static void drawTicks(int tickLength) { // draw ticks of given length
    if (tickLength > 0) { // stop when length drops to 0
        drawTicks(tickLength- 1); // recursively draw left ticks
        drawOneTick(tickLength); // draw center tick
        drawTicks(tickLength- 1); // recursively draw right ticks
    }
}
public static void drawRuler(int nInches, int majorLength) { // draw ruler
    drawOneTick(majorLength, 0); // draw tick 0 and its label
    for (int i = 1; i <= nInches; i++) {
        drawTicks(majorLength- 1); // draw ticks for this inch
        drawOneTick(majorLength, i); // draw tick i and its label
    }
}
```

Note the two recursive calls

Fibonacci Numbers

- Useful for
 - Stock market
 - **Search**
 - And more...

Fibonacci Search (Kiefer et al. 1953)

- Similar to binary search, but
 - Instead of dividing an array by the midpoint during search,
 - You use the largest $F_N \leq \text{midpoint}$
 - Since



A	B	B / A
2	3	1.5
3	5	1.666666666...
5	8	1.6
8	13	1.625
13	21	1.615384615...
...
144	233	1.618055556...
233	377	1.618025751...
...

Fibonacci Search (Kiefer et al. 1953)

- Similar to binary search, but
 - Instead of dividing an array by the midpoint during search,
 - You use the largest $F_n \leq \text{midpoint}$
 - This results in dividing the area roughly by the Golden Ratio (e.g., 62% and 38%)
 - In practice has slightly better average time performance (still $O(\log n)$)

Golden Ratio

□ 1.61803398875



Computing Fibonacci Numbers

- Fibonacci numbers are defined recursively:

$$F_0 = 0$$

$$F_1 = 1$$

$$F_i = F_{i-1} + F_{i-2} \quad \text{for } i > 1.$$

- Recursive algorithm (first attempt):

Algorithm BinaryFib(k):

Input: Nonnegative integer k

Output: The k th Fibonacci number F_k

if $k = 1$ **then**

return k

else

return BinaryFib($k - 1$) + BinaryFib($k - 2$)

Analysis

- Let n_k be the number of recursive calls by **BinaryFib**(k)
 - $n_0 = 1$
 - $n_1 = 1$
 - $n_2 = n_1 + n_0 + 1 = 1 + 1 + 1 = 3$
 - $n_3 = n_2 + n_1 + 1 = 3 + 1 + 1 = 5$
 - $n_4 = n_3 + n_2 + 1 = 5 + 3 + 1 = 9$
 - $n_5 = n_4 + n_3 + 1 = 9 + 5 + 1 = 15$
 - $n_6 = n_5 + n_4 + 1 = 15 + 9 + 1 = 25$
 - $n_7 = n_6 + n_5 + 1 = 25 + 15 + 1 = 41$
 - $n_8 = n_7 + n_6 + 1 = 41 + 25 + 1 = 67.$
- Note that n_k at least doubles every other time
- That is, $n_k > 2^{k/2}$. It is exponential!

A Better Fibonacci Algorithm

- Use linear recursion in this case

Algorithm **LinearFibonacci**(k):

Input: A nonnegative integer k

Output: Pair of Fibonacci numbers (F_k , F_{k-1})

if $k = 1$ **then**

return (k, 0)

else

(i, j) = **LinearFibonacci**(k - 1)

return (i + j, i)

- **LinearFibonacci** makes k-1 recursive calls
- This is also a form of “dynamic programming”

Even Better Fibonacci Algorithm

□ Binet's Fibonacci number formula:

$$u_n = u_{n-1} + u_{n-2} \text{ for } n > 1$$

where

$$u_0 = 0,$$

$$u_1 = 1,$$

$$u_n = \frac{(1 + \sqrt{5})^n - (1 - \sqrt{5})^n}{2^n \sqrt{5}}$$