

Simplicial surfaces

Markus Baumeister




(j/w Alice Niemeyer, Wilhelm Plesken, Ansgar Strzelczyk)

Lehrstuhl B für Mathematik
RWTH Aachen University




27.09.2017

Simplicial surfaces

Simplicial surfaces






Simplicial surfaces






↔ structures build from triangles

Simplicial surfaces



↔ structures build from triangles (or arbitrary polygons)

Simplicial surfaces



↔ structures build from triangles (or arbitrary polygons)
→ focus on the combinatorial/incidence structure (without embedding)

Classification

Classification

Goal: Classify all closed simplicial surfaces.

Classification

Goal: Classify all closed simplicial surfaces.

Already classified the basic surfaces (building blocks) up to 20 triangles.

Classification

Goal: Classify all closed simplicial surfaces.

Already classified the basic surfaces (building blocks) up to 20 triangles.

- e. g. exactly 87 non-isomorphic basic surfaces with 20 triangles

Classification

Goal: Classify all closed simplicial surfaces.

Already classified the basic surfaces (building blocks) up to 20 triangles.


- e. g. exactly 87 non-isomorphic basic surfaces with 20 triangles
- e. g. only one basic surface with 10 triangles:

Classification

Goal: Classify all closed simplicial surfaces.

Already classified the basic surfaces (building blocks) up to 20 triangles.

- e. g. exactly 87 non-isomorphic basic surfaces with 20 triangles
- e. g. only one basic surface with 10 triangles:



One type of triangle

One type of triangle

For embedding purposes:

One type of triangle


For embedding purposes:

We are interested in surfaces that are built from one type of triangle.

One type of triangle

For embedding purposes:


We are interested in surfaces that are built from one type of triangle.



One type of triangle

For embedding purposes:

We are interested in surfaces that are built from one type of triangle.




~> edge-colouring encodes lengths

One type of triangle

For embedding purposes:

We are interested in surfaces that are built from one type of triangle.




- ~~ edge-colouring encodes lengths
- ~~ analyse edge-coloured surfaces

Colouring as permutation


Colouring as permutation

Consider a tetrahedron




Colouring as permutation

Consider a tetrahedron with an edge colouring



Colouring as permutation


Consider a tetrahedron with an edge colouring



simplicial surface \Rightarrow

Colouring as permutation


Consider a tetrahedron with an edge colouring



simplicial surface $\Rightarrow \leq 2$ faces at each edge

Colouring as permutation

Consider a tetrahedron with an edge colouring




simplicial surface $\Rightarrow \leq 2$ faces at each edge

\rightsquigarrow every edge defines a transposition of incident faces

Colouring as permutation

Consider a tetrahedron with an edge colouring




simplicial surface $\Rightarrow \leq 2$ faces at each edge

\rightsquigarrow every edge defines a transposition of incident faces

- (1,2)

Colouring as permutation

Consider a tetrahedron with an edge colouring




simplicial surface $\Rightarrow \leq 2$ faces at each edge

\rightsquigarrow every edge defines a transposition of incident faces

- $(1,2)(3,4)$

Colouring as permutation

Consider a tetrahedron with an edge colouring




simplicial surface $\Rightarrow \leq 2$ faces at each edge

- ~~ every edge defines a transposition of incident faces
- ~~ every colour class defines a permutation of the faces
- $(1,2)(3,4)$

Colouring as permutation

Consider a tetrahedron with an edge colouring




simplicial surface $\Rightarrow \leq 2$ faces at each edge

- ~~ every edge defines a transposition of incident faces
- ~~ every colour class defines a permutation of the faces
- $(1,2)(3,4)$, $(1,3)(2,4)$

Colouring as permutation

Consider a tetrahedron with an edge colouring




simplicial surface $\Rightarrow \leq 2$ faces at each edge

- ~~ every edge defines a transposition of incident faces
- ~~ every colour class defines a permutation of the faces
- $(1,2)(3,4)$, $(1,3)(2,4)$, $(1,4)(2,3)$

Colouring as permutation

Consider a tetrahedron with an edge colouring



simplicial surface $\Rightarrow \leq 2$ faces at each edge

- ~ every edge defines a transposition of incident faces
- ~ every colour class defines a permutation of the faces
- $(1,2)(3,4)$, $(1,3)(2,4)$, $(1,4)(2,3)$
- ~ group theoretic considerations

Implementation in GAP

Implementation in GAP

Implemented in GAP (package SimplicialSurfaces, unpublished)

Implementation in GAP

Implemented in GAP (package SimplicialSurfaces, unpublished)

Example: define a coloured icosahedron:

Implementation in GAP

Implemented in GAP (package SimplicialSurfaces, unpublished)

Example: define a coloured icosahedron:

```
gap> iko := ColouredSimplicialSurface(
```

Implementation in GAP

Implemented in GAP (package SimplicialSurfaces, unpublished)

Example: define a coloured icosahedron:

```
gap> iko := ColouredSimplicialSurface(  
[[ 1, 2 ], [ 1, 3 ], [ 1, 4 ], [ 1, 5 ], [ 1, 6 ], [ 2, 3 ], [ 2, 4 ], [ 2, 7 ],  
[ 2, 8 ], [ 3, 6 ], [ 3, 7 ], [ 3, 11 ], [ 4, 5 ], [ 4, 8 ], [ 4, 9 ], [ 5, 6 ],  
[ 5, 9 ], [ 5, 10 ], [ 6, 10 ], [ 6, 11 ], [ 7, 8 ], [ 7, 11 ], [ 7, 12 ], [ 8, 9 ],  
[ 8, 12 ], [ 9, 10 ], [ 9, 12 ], [ 10, 11 ], [ 10, 12 ], [ 11, 12 ] ],  
  
[[ [ 1, 2, 6 ], [ 1, 3, 7 ], [ 3, 4, 13 ], [ 4, 5, 16 ], [ 2, 5, 10 ], [ 6, 8, 11 ],  
[ 7, 9, 14 ], [ 13, 15, 17 ], [ 16, 18, 19 ], [ 10, 12, 20 ], [ 8, 9, 21 ],  
[ 14, 15, 24 ], [ 17, 18, 26 ], [ 19, 20, 28 ], [ 11, 12, 22 ], [ 21, 23, 25 ],  
[ 24, 25, 27 ], [ 26, 27, 29 ], [ 28, 29, 30 ], [ 22, 23, 30 ] ],  
  
[ 1, 2, 3, 1, 3, 3, 2, 1, 3, 1, 2, 3, 2, 1, 3, 2, 1, 3, 1, 2, 2, 1, 3, 2, 1, 2, 3, 3,  
1, 2 ] );;
```


Net of an icosahedron

Net of an icosahedron



```
gap> DrawSurfaceToTikZ(iko,"NetIko.tex");
```

Net of an icosahedron

```
gap> DrawSurfaceToTikZ(iko,"NetIko.tex");
```



Embedded icosahedron



Further research

Further research

- Structural properties of coloured surfaces (coverings/ramifications)

Further research

- Structural properties of coloured surfaces (coverings/ramifications)
- Immersion/Embedding of surfaces into \mathbb{R}^3

Further research

- Structural properties of coloured surfaces (coverings/ramifications)
- Immersion/Embedding of surfaces into \mathbb{R}^3
- Folding of surfaces (description and classification)

Further research

- Structural properties of coloured surfaces (coverings/ramifications)
- Immersion/Embedding of surfaces into \mathbb{R}^3
- Folding of surfaces (description and classification)
- GAP-implementation of this theory (package SimplicialSurfaces)

Further research

- Structural properties of coloured surfaces (coverings/ramifications)
- Immersion/Embedding of surfaces into \mathbb{R}^3
- Folding of surfaces (description and classification)
- GAP-implementation of this theory (package SimplicialSurfaces)

Thanks for your attention

Alice Niemeyer
Wilhelm Plesken

Markus Baumeister
Ansgar Strzelczyk