

numericalsgps– a package for numerical semigroups

Version 1.0.1

Manuel Delgado
Pedro A. García-Sánchez
José João Morais

Manuel Delgado Email: mdelgado@fc.up.pt
Homepage: <http://www.fc.up.pt/cmup/mdelgado>

Pedro A. García-Sánchez Email: pedro@ugr.es
Homepage: <http://www.ugr.es/~pedro>

Copyright

© 2005–2015 Centro de Matemática da Universidade do Porto, Portugal and Universidad de Granada, Spain
Numericalsgps is free software; you can redistribute it and/or modify it under the terms of the [GNU General Public License](#) as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

Acknowledgements

The first author's work was (partially) supported by the *Centro de Matemática da Universidade do Porto* (CMUP), financed by FCT (Portugal) through the programs POCTI (Programa Operacional "Ciência, Tecnologia, Inovação") and POSI (Programa Operacional Sociedade da Informação), with national and European Community structural funds and a sabbatical grant of FCT.

The second author was supported by the projects MTM2004-01446, FQM-343, and FEDER funds.

The third author acknowledges financial support of FCT and the POCTI program through a scholarship given by *Centro de Matemática da Universidade do Porto*.

The authors wish to thank J. I. García-García and Alfredo Sánchez-R. Navarro for many helpful discussions and for helping in the programming of preliminary versions of some functions, and also to C. O'Neill, A. Sammartano and K. Stokes for their contributions (see Contributions Chapter). We are also in debt with S. Gutsche, M. Horn, H. Schönemann, C. Söeger and M. Barakat for their fruitful advices concerning 4ti2Interface, SingularInterface, Singular, Normaliz, NormalizInterface and GradedModules.

The first and second authors warmly thank María Burgos for her support and help.

CONCERNING THE MAINTAINMENT:

The first author was (partially) supported by the FCT project PTDC/MAT/65481/2006 and also by the *Centro de Matemática da Universidade do Porto* (CMUP), funded by the European Regional Development Fund through the programme COMPETE and by the Portuguese Government through the FCT - Fundação para a Ciência e a Tecnologia under the project PEst-C/MAT/UI0144/2011.

The second author was/is supported by the projects MTM2007-62346 and MTM2010-15595.

Both authors want to acknowledge partial support by CMUP (UID/MAT/00144/2013), which is funded by FCT (Portugal) with national (MEC) and European structural funds through the programs FEDER, under the partnership agreement PT2020.

The maintainers want to thank the organizers of GAPDays in their several editions.

The authors also thank the Centro de Servicios de Informática y Redes de Comunicaciones (CSIRC), Universidad de Granada, for providing the computing time, specially Rafael Arco Arredondo for installing everything this package and the extra software needed in alhambra.ugr.es.

Colophon

This work started when (in 2004) the first author visited the University of Granada in part of a sabbatical year. Since Version 0.96 (released in 2008), the package is maintained by the first two authors. Bug reports, suggestions and comments are, of course, welcome. Please use our email addresses to this effect.

If you have benefited from the use of the numericalsgps GAP package in your research, please cite it in addition to GAP itself, following the scheme proposed in <http://www.gap-system.org/Contacts/cite.html>.

If you have predominantly used the functions in the Appendix, contributed by other authors, please cite in addition these authors, referring "software implementations available in the GAP package NumericalSgps".

Contents

1	Introduction	6
2	Numerical Semigroups	9
2.1	Generating Numerical Semigroups	9
2.2	Some basic tests	14
3	Basic operations with numerical semigroups	18
3.1	Invariants	18
3.2	Wilf's conjecture	25
4	Presentations of Numerical Semigroups	27
4.1	Presentations of Numerical Semigroups	27
4.2	Uniquely Presented Numerical Semigroups	28
5	Constructing numerical semigroups from others	30
5.1	Adding and removing elements of a numerical semigroup	30
5.2	Intersections, and quotients and multiples by integers	31
5.3	Constructing the set of all numerical semigroups containing a given numerical semi-group	32
5.4	Constructing the set of numerical semigroup with given Frobenius number	33
5.5	Constructing the set of numerical semigroups with genus g , that is, numerical semi-groups with exactly g gaps	33
5.6	Constructing the set of numerical semigroups with a given set of pseudo-Frobenius numbers	34
6	Irreducible numerical semigroups	37
6.1	Irreducible numerical semigroups	37
6.2	Complete intersection numerical semigroups	39
6.3	Almost-symmetric numerical semigroups	41
7	Ideals of numerical semigroups	43
7.1	Definitions and basic operations	43
7.2	Other functions for ideals	49
8	Numerical semigroups with maximal embedding dimension	53
8.1	Numerical semigroups with maximal embedding dimension	53
8.2	Numerical semigroups with the Arf property and Arf closures	54

8.3	Saturated numerical semigroups	55
9	Nonunique invariants for factorizations in numerical semigroups	57
9.1	Factorizations in Numerical Semigroups	57
9.2	Invariants based on lengths	59
9.3	Invariants based on distances	62
9.4	Primality	66
9.5	Homogenization of Numerical Semigroups	66
9.6	Divisors, posets	68
10	Polynomials and numerical semigroups	69
10.1	Generating functions or Hilbert series	69
10.2	Semigroup of values of algebraic curves	71
11	Affine semigroups	75
11.1	Defining affine semigroups	75
11.2	Gluing of affine semigroups	79
11.3	Presentations of affine semigroups	79
11.4	Factorizations in affine semigroups	81
12	Good semigroups	84
12.1	Defining good semigroups	84
12.2	Notable elements	86
12.3	Symmetric semigroups	89
12.4	Good ideals	90
13	External packages	93
13.1	Using external packages	93
A	Generalities	95
A.1	Bézout sequences	95
A.2	Periodic subadditive functions	96
B	"Random" functions	97
B.1	Random functions	97
C	Contributions	100
C.1	Functions implemented by A. Sammartano	100
C.2	Functions implemented by C. O'Neill	103
C.3	Functions implemented by K. Stokes	105
C.4	Functions implemented by I. Ojeda and C. J. Moreno Ávila	108
	References	113
	Index	114

Chapter 1

Introduction

A *numerical semigroup* is a subset of the set \mathbb{N} of nonnegative integers that is closed under addition, contains 0 and whose complement in \mathbb{N} is finite. The smallest positive integer belonging to a numerical semigroup is its *multiplicity*.

Let S be a numerical semigroup and A be a subset of S . We say that A is a *system of generators* of S if $S = \{k_1 a_1 + \cdots + k_n a_n \mid n, k_1, \dots, k_n \in \mathbb{N}, a_1, \dots, a_n \in A\}$. The set A is a *minimal system of generators* of S if no proper subset of A is a system of generators of S .

Every numerical semigroup has a unique minimal system of generators. This is a data that can be used in order to uniquely define a numerical semigroup. Observe that since the complement of a numerical semigroup in the set of nonnegative integers is finite, this implies that the greatest common divisor of the elements of a numerical semigroup is 1, and the same condition must be fulfilled by its minimal system of generators (or by any of its systems of generators).

Given a numerical semigroup S and a nonzero element s in it, one can consider for every integer i ranging from 0 to $s - 1$, the smallest element in S congruent with i modulo s , say $w(i)$ (this element exists since the complement of S in \mathbb{N} is finite). Clearly $w(0) = 0$. The set $\text{Ap}(S, s) = \{w(0), w(1), \dots, w(s - 1)\}$ is called the *Apéry set* of S with respect to s . Note that a nonnegative integer x congruent with i modulo s belongs to S if and only if $w(i) \leq x$. Thus the pair $(s, \text{Ap}(S, s))$ fully determines the numerical semigroup S (and can be used to easily solve the membership problem to S). This set is in fact one of the most powerful tools known for numerical semigroups, and it is used almost everywhere in the computation of components and invariants associated to a numerical semigroup. Usually the element s is taken to be the multiplicity, since in this way the resulting Apéry set is the smallest possible.

A *gap* of a numerical semigroup S is a nonnegative integer not belonging to S . The set of gaps of S is usually denoted by $H(S)$, and clearly determines uniquely S . Note that if x is a gap of S , then so are all the nonnegative integers dividing it. Thus in order to describe S we do not need to know all its gaps, but only those that are maximal with respect to the partial order induced by division in \mathbb{N} . These gaps are called *fundamental gaps*.

The largest nonnegative integer not belonging to a numerical semigroup S is the *Frobenius number* of S . If S is the set of nonnegative integers, then clearly its Frobenius number is -1 , otherwise its Frobenius number coincides with the maximum of the gaps (or fundamental gaps) of S . The Frobenius number plus one is known as the *conductor* of the semigroup. In this package we refer to the elements in the semigroup that are less than or equal to the conductor as *small elements* of the semigroup. Observe that from the definition, if S is a numerical semigroup with Frobenius number f , then $f + \mathbb{N} \setminus \{0\} \subseteq S$. An integer z is a *pseudo-Frobenius number* of S if $z + S \setminus \{0\} \subseteq S$. Thus the

Frobenius number of S is one of its pseudo-Frobenius numbers. The *type* of a numerical semigroup is the cardinality of the set of its pseudo-Frobenius numbers.

The number of numerical semigroups having a given Frobenius number is finite. The elements in this set of numerical semigroups that are maximal with respect to set inclusion are precisely those numerical semigroups that cannot be expressed as intersection of two other numerical semigroups containing them properly, and thus they are known as *irreducible* numerical semigroups. Clearly, every numerical semigroup is the intersection of (finitely many) irreducible numerical semigroups.

A numerical semigroup S with Frobenius number f is *symmetric* if for every integer x , either $x \in S$ or $f - x \in S$. The set of irreducible numerical semigroups with odd Frobenius number coincides with the set of symmetric numerical semigroups. The numerical semigroup S is *pseudo-symmetric* if f is even and for every integer x not equal to $f/2$ either $x \in S$ or $f - x \in S$. The set of irreducible numerical semigroups with even Frobenius number is precisely the set of pseudo-symmetric numerical semigroups. These two classes of numerical semigroups have been widely studied in the literature due to their nice applications in Algebraic Geometry. This is probably one of the main reasons that made people turn their attention on numerical semigroups again in the last decades. Symmetric numerical semigroups can be also characterized as those with type one, and pseudo-symmetric numerical semigroups are those numerical semigroups with type two and such that its pseudo-Frobenius numbers are its Frobenius number and its Frobenius number divided by two.

Another class of numerical semigroups that caught the attention of researchers working on Algebraic Geometry and Commutative Ring Theory is the class of numerical semigroups with maximal embedding dimension. The *embedding dimension* of a numerical semigroup is the cardinality of its minimal system of generators. It can be shown that the embedding dimension is at most the multiplicity of the numerical semigroup. Thus *maximal embedding dimension* numerical semigroups are those numerical semigroups for which their embedding dimension and multiplicity coincide. These numerical semigroups have nice maximal properties, not only (of course) related to their embedding dimension, but also by means of their presentations. Among maximal embedding dimension there are two classes of numerical semigroups that have been studied due to the connections with the equivalence of algebroid branches. A numerical semigroup S is *Arf* if for every $x \geq y \geq z \in S$, then $x + y - z \in S$; and it is *saturated* if the following condition holds: if $s, s_1, \dots, s_r \in S$ are such that $s_i \leq s$ for all $i \in \{1, \dots, r\}$ and $z_1, \dots, z_r \in \mathbb{Z}$ are such that $z_1 s_1 + \dots + z_r s_r \geq 0$, then $s + z_1 s_1 + \dots + z_r s_r \in S$.

If we look carefully inside the set of fundamental gaps of a numerical semigroup, we see that there are some fulfilling the condition that if they are added to the given numerical semigroup, then the resulting set is again a numerical semigroup. These elements are called *special gaps* of the numerical semigroup. A numerical semigroup other than the set of nonnegative integers is irreducible if and only if it has only a special gap.

The inverse operation to the one described in the above paragraph is that of removing an element of a numerical semigroup. If we want the resulting set to be a numerical semigroup, then the only thing we can remove is a minimal generator.

Let a, b, c, d be positive integers such that $a/b < c/d$, and let $I = [a/b, c/d]$. Then the set $S(I) = \mathbb{N} \cap \bigcup_{n \geq 0} nI$ is a numerical semigroup. This class of numerical semigroups coincides with that of sets of solutions to equations of the form $Ax \bmod B \leq Cx$ with A, B, C positive integers. A numerical semigroup in this class is said to be *proportionally modular*.

A sequence of positive rational numbers $a_1/b_1 < \dots < a_n/b_n$ with a_i, b_i positive integers is a *Bézout sequence* if $a_{i+1}b_i - a_i b_{i+1} = 1$ for all $i \in \{1, \dots, n-1\}$. If $a/b = a_1/b_1 < \dots < a_n/b_n = c/d$, then $S([a/b, c/d]) = \langle a_1, \dots, a_n \rangle$. Bézout sequences are not only interesting for this fact, they have shown to be a major tool in the study of proportionally modular numerical semigroups.

If S is a numerical semigroup and k is a positive integer, then the set $S/k = \{x \in \mathbb{N} \mid kx \in S\}$ is a

numerical semigroup, known as the *quotient* S by k .

Let m be a positive integer. A *subadditive* function with period m is a map $f : \mathbb{N} \rightarrow \mathbb{N}$ such that $f(0) = 0$, $f(x+y) \leq f(x) + f(y)$ and $f(x+m) = f(x)$. If f is a subadditive function with period m , then the set $M_f = \{x \in \mathbb{N} \mid f(x) \leq x\}$ is a numerical semigroup. Moreover, every numerical semigroup is of this form. Thus a numerical semigroup can be given by a subadditive function with a given period. If S is a numerical semigroup and $s \in S, s \neq 0$, and $\text{Ap}(S, s) = \{w(0), w(1), \dots, w(s-1)\}$, then $f(x) = w(x \bmod s)$ is a subadditive function with period s such that $M_f = S$.

Let S be a numerical semigroup generated by $\{n_1, \dots, n_k\}$. Then we can define the following morphism (called sometimes the factorization morphism) by $\varphi : \mathbb{N}^k \rightarrow S$, $\varphi(a_1, \dots, a_k) = a_1 n_1 + \dots + a_k n_k$. If σ is the kernel congruence of φ (that is, $a \sigma b$ if $\varphi(a) = \varphi(b)$), then S is isomorphic to \mathbb{N}^k / σ . A *presentation* for S is a system of generators (as a congruence) of σ . If $\{n_1, \dots, n_p\}$ is a minimal system of generators, then a *minimal presentation* is a presentation such that none of its proper subsets is a presentation. Minimal presentations of numerical semigroups coincide with presentations with minimal cardinality, though in general these two concepts are not the same for an arbitrary commutative semigroup.

A set I of integers is an *ideal relative to a numerical semigroup* S provided that $I + S \subseteq I$ and that there exists $d \in S$ such that $d + I \subseteq S$. If $I \subseteq S$, we simply say that I is an *ideal* of S . If I and J are relative ideals of S , then so is $I - J = \{z \in \mathbb{Z} \mid z + J \subseteq I\}$, and it is tightly related to the operation ":" of ideals in a commutative ring.

In this package we have implemented the functions needed to deal with the elements exposed in this introduction.

Many of the algorithms, and the necessary background to understand them, can be found in the monograph [RGS09]. Some examples in this book have been illustrated with the help of this package. So the reader can also find there more examples on the usage of the functions implemented here.

This package was presented in [DGSM06]. For a survey of the features of this package, see [DGS16].

Chapter 2

Numerical Semigroups

This chapter describes how to create numerical semigroups in GAP and perform some basic tests.

2.1 Generating Numerical Semigroups

We recall some definitions from Chapter 1.

A numerical semigroup is a subset of the set \mathbb{N} of nonnegative integers that is closed under addition, contains 0 and whose complement in \mathbb{N} is finite.

We refer to the elements in a numerical semigroup that are less than or equal to the conductor as *small elements* of the semigroup.

A *gap* of a numerical semigroup S is a nonnegative integer not belonging to S . The *fundamental gaps* of S are those gaps that are maximal with respect to the partial order induced by division in \mathbb{N} .

Given a numerical semigroup S and a nonzero element s in it, one can consider for every integer i ranging from 0 to $s - 1$, the smallest element in S congruent with i modulo s , say $w(i)$ (this element exists since the complement of S in \mathbb{N} is finite). Clearly $w(0) = 0$. The set $\text{Ap}(S, s) = \{w(0), w(1), \dots, w(s - 1)\}$ is called the *Apéry set* of S with respect to s .

Let a, b, c, d be positive integers such that $a/b < c/d$, and let $I = [a/b, c/d]$. Then the set $S(I) = \mathbb{N} \cap \bigcup_{n \geq 0} nI$ is a numerical semigroup. This class of numerical semigroups coincides with that of sets of solutions to equations of the form $Ax \bmod B \leq Cx$ with A, B, C positive integers. A numerical semigroup in this class is said to be *proportionally modular*. If $C = 1$, then it is said to be *modular*.

There are different ways to specify a numerical semigroup S , namely, by its generators; by its gaps, its fundamental or special gaps by its Apéry set, just to name some. In this section we describe functions that may be used to specify, in one of these ways, a numerical semigroup in GAP.

2.1.1 NumericalSemigroupByGenerators

- ▷ `NumericalSemigroupByGenerators(List)` (function)
- ▷ `NumericalSemigroup(String, List)` (function)

`List` is a list of nonnegative integers with greatest common divisor equal to one. These integers may be given as a list or by a sequence of individual elements. The output is the numerical semigroup spanned by `List`.

`String` does not need to be present. When it is present, it must be "generators".

Example

```
gap> s1 := NumericalSemigroupByGenerators(3,5,7);
<Numerical semigroup with 3 generators>
gap> s2 := NumericalSemigroupByGenerators([3,5,7]);
<Numerical semigroup with 3 generators>
gap> s3 := NumericalSemigroup("generators",3,5,7);
<Numerical semigroup with 3 generators>
gap> s4 := NumericalSemigroup("generators",[3,5,7]);
<Numerical semigroup with 3 generators>
gap> s5 := NumericalSemigroup(3,5,7);
<Numerical semigroup with 3 generators>
gap> s6 := NumericalSemigroup([3,5,7]);
<Numerical semigroup with 3 generators>
gap> s1=s2;s2=s3;s3=s4;s4=s5;s5=s6;
true
true
true
true
true
```

2.1.2 NumericalSemigroupBySubAdditiveFunction

- ▷ NumericalSemigroupBySubAdditiveFunction(List) (function)
- ▷ NumericalSemigroup(String, List) (function)

A periodic subadditive function with period m is given through the list of images of the integers from 1 to m . The image of m has to be 0. The output is the numerical semigroup determined by this subadditive function.

In the second form, String must be "subadditive".

Example

```
gap> s := NumericalSemigroupBySubAdditiveFunction([5,4,2,0]);
<Numerical semigroup>
gap> t := NumericalSemigroup("subadditive",[5,4,2,0]);
gap> s=t;
true
```

2.1.3 NumericalSemigroupByApéryList

- ▷ NumericalSemigroupByApéryList(List) (function)
- ▷ NumericalSemigroup(String, List) (function)

List is an Apéry list. The output is the numerical semigroup whose Apéry set with respect to the length of given list is List.

In the second form, String must be "apery".

Example

```
gap> s:=NumericalSemigroup(3,11);;
gap> ap := ApéryListOfNumericalSemigroupWRTElement(s,20);
[ 0, 21, 22, 3, 24, 25, 6, 27, 28, 9, 30, 11, 12, 33, 14, 15, 36, 17, 18, 39 ]
gap> t:=NumericalSemigroupByApéryList(ap);;
gap> r := NumericalSemigroup("apery",ap);;
```

```
gap> s=t;t=r;
true
true
```

2.1.4 NumericalSemigroupBySmallElements

- ▷ NumericalSemigroupBySmallElements(List) (function)
- ▷ NumericalSemigroup(String, List) (function)

List is the set of small elements of a numerical semigroup, that is, the set of all elements not greater than the conductor. The output is the numerical semigroup with this set of small elements. When no such semigroup exists, an error is returned.

In the second form, String must be "elements".

Example

```
gap> s:=NumericalSemigroup(3,11);;
gap> se := SmallElements(s);
[ 0, 3, 6, 9, 11, 12, 14, 15, 17, 18, 20 ]
gap> t := NumericalSemigroupBySmallElements(se);;
gap> r := NumericalSemigroup("elements",se);;
gap> s=t;t=r;
true
true
gap> e := [ 0, 3, 6, 9, 11, 14, 15, 17, 18, 20 ];
[ 0, 3, 6, 9, 11, 14, 15, 17, 18, 20 ]
gap> NumericalSemigroupBySmallElements(e);
Error, The argument does not represent a numerical semigroup called from
<function "NumericalSemigroupBySmallElements">( <arguments> )
called from read-eval loop at line 35 of *stdin*
you can 'quit;' to quit to outer loop, or
you can 'return;' to continue
brk>
```

2.1.5 NumericalSemigroupByGaps

- ▷ NumericalSemigroupByGaps(List) (function)
- ▷ NumericalSemigroup(String, List) (function)

List is the set of gaps of a numerical semigroup. The output is the numerical semigroup with this set of gaps. When no semigroup exists with the given set as set of gaps, an error is returned.

In the second form, String must be "gaps".

Example

```
gap> g := [ 1, 2, 4, 5, 7, 8, 10, 13, 16 ];;
gap> s := NumericalSemigroupByGaps(g);;
gap> t := NumericalSemigroup("gaps",g);;
gap> s=t;
true
gap> h := [ 1, 2, 5, 7, 8, 10, 13, 16 ];;
gap> NumericalSemigroupByGaps(h);
Error, The argument does not represent the gaps of a numerical semigroup called
from
```

```
<function "NumericalSemigroupByGaps">( <arguments> )
  called from read-eval loop at line 34 of *stdin*
you can 'quit;' to quit to outer loop, or
you can 'return;' to continue
brk>
```

2.1.6 NumericalSemigroupByFundamentalGaps

- ▷ NumericalSemigroupByFundamentalGaps(List) (function)
- ▷ NumericalSemigroup(String, List) (function)

List is the set of fundamental gaps of a numerical semigroup. The output is the numerical semigroup determined by these gaps. When the given set contains elements (which will be gaps) that are not fundamental gaps, they are silently removed.

In the second form, String must be "fundamentalgaps".

Example

```
gap> fg := [ 11, 14, 17, 20, 23, 26, 29, 32, 35 ];;
gap> NumericalSemigroupByFundamentalGaps(fg);
<Numerical semigroup>
gap> NumericalSemigroup("fundamentalgaps",fg);
<Numerical semigroup>
gap> last=last2;
true
gap> gg := [ 11, 17, 20, 22, 23, 26, 29, 32, 35 ];; #22 is not fundamental
gap> NumericalSemigroup("fundamentalgaps",fg);
<Numerical semigroup>
```

2.1.7 NumericalSemigroupByAffineMap

- ▷ NumericalSemigroupByAffineMap(a, b, c) (function)
- ▷ NumericalSemigroup(String, a, b) (function)

Given three nonnegative integers a , b and c , with $a, c > 0$ and $\gcd(b, c) = 1$, this function returns the least (with respect to set order inclusion) numerical semigroup containing c and closed under the map $x \mapsto ax + b$. The procedure is explained in [Ugo16].

In the second form, String must be "affinemap".

Example

```
gap> s:=NumericalSemigroupByAffineMap(3,1,3);
<Numerical semigroup with 3 generators>
gap> SmallElements(s);
[ 0, 3, 6, 9, 10, 12, 13, 15, 16, 18 ]
gap> t:=NumericalSemigroup("affinemap",3,1,3);
gap> s=t;
true
```

2.1.8 ModularNumericalSemigroup

- ▷ ModularNumericalSemigroup(a, b) (function)
- ▷ NumericalSemigroup(String, a, b) (function)

Given two positive integers a and b , this function returns a modular numerical semigroup satisfying $ax \bmod b \leq x$.

In the second form, `String` must be "modular".

Example

```
gap> ModularNumericalSemigroup(3,7);
<Modular numerical semigroup satisfying 3x mod 7 <= x >
gap> NumericalSemigroup("modular",3,7);
<Modular numerical semigroup satisfying 3x mod 7 <= x >
```

2.1.9 ProportionallyModularNumericalSemigroup

▷ `ProportionallyModularNumericalSemigroup(a, b, c)` (function)

▷ `NumericalSemigroup(String, a, b)` (function)

Given three positive integers a , b and c , this function returns a proportionally modular numerical semigroup satisfying $ax \bmod b \leq cx$.

In the second form, `String` must be "propmodular".

Example

```
gap> ProportionallyModularNumericalSemigroup(3,7,12);
<Proportionally modular numerical semigroup satisfying 3x mod 7 <= 12x >
gap> NumericalSemigroup("propmodular",3,7,12);
<Proportionally modular numerical semigroup satisfying 3x mod 7 <= 12x >
```

When $c = 1$, the semigroup is seen as a modular numerical semigroup.

Example

```
gap> NumericalSemigroup("propmodular",67,98,1);
<Modular numerical semigroup satisfying 67x mod 98 <= x >
```

Numerical semigroups generated by an interval of positive integers are known to be proportionally modular, and thus they are treated as such, since membership and other problems can be solved efficiently for these semigroups.

2.1.10 NumericalSemigroupByInterval

▷ `NumericalSemigroupByInterval(List)` (function)

▷ `NumericalSemigroup(String, List)` (function)

The input is a list of rational numbers defining a closed interval. The output is the semigroup of numerators of all rational numbers in this interval.

`String` does not need to be present. When it is present, it must be "interval".

Example

```
gap> NumericalSemigroupByInterval(7/5,5/3);
<Proportionally modular numerical semigroup satisfying 25x mod 35 <= 4x >
gap> NumericalSemigroup("interval",[7/5,5/3]);
<Proportionally modular numerical semigroup satisfying 25x mod 35 <= 4x >
gap> SmallElements(last);
[ 0, 3, 5 ]
```

2.1.11 NumericalSemigroupByOpenInterval

- ▷ `NumericalSemigroupByOpenInterval(List)` (function)
- ▷ `NumericalSemigroup(String, List)` (function)

The input is a list of rational numbers defining a open interval. The output is the semigroup of numerators of all rational numbers in this interval.

String does not need to be present. When it is present, it must be "openinterval".

Example

```
gap> NumericalSemigroupByOpenInterval(7/5,5/3);
<Numerical semigroup>
gap> NumericalSemigroup("openinterval",[7/5,5/3]);
<Numerical semigroup>
gap> SmallElements(last);
[ 0, 3, 6, 8 ]
gap>
```

2.2 Some basic tests

This section describes some basic tests on numerical semigroups. The first described tests refer to what the semigroup is currently known to be (not necessarily the way it was created). Then are presented functions to test if a given list represents the small elements, gaps or the Apéry set (see 1) of a numerical semigroup; to test if an integer belongs to a numerical semigroup and if a numerical semigroup is a subsemigroup of another one.

2.2.1 IsNumericalSemigroup

- ▷ `IsNumericalSemigroup(NS)` (attribute)
- ▷ `IsNumericalSemigroupByGenerators(NS)` (attribute)
- ▷ `IsNumericalSemigroupByMinimalGenerators(NS)` (attribute)
- ▷ `IsNumericalSemigroupByInterval(NS)` (attribute)
- ▷ `IsNumericalSemigroupByOpenInterval(NS)` (attribute)
- ▷ `IsNumericalSemigroupBySubAdditiveFunction(NS)` (attribute)
- ▷ `IsNumericalSemigroupByAperyList(NS)` (attribute)
- ▷ `IsNumericalSemigroupBySmallElements(NS)` (attribute)
- ▷ `IsNumericalSemigroupByGaps(NS)` (attribute)
- ▷ `IsNumericalSemigroupByFundamentalGaps(NS)` (attribute)
- ▷ `IsProportionallyModularNumericalSemigroup(NS)` (attribute)
- ▷ `IsModularNumericalSemigroup(NS)` (attribute)

NS is a numerical semigroup and these attributes are available (their names should be self explanatory).

Example

```
gap> s:=NumericalSemigroup(3,7);
<Numerical semigroup with 2 generators>
gap> AperyListOfNumericalSemigroupWRTElement(s,30);;
gap> t:=NumericalSemigroupByAperyList(last);
<Numerical semigroup>
```

```
gap> IsNumericalSemigroupByGenerators(s);
true
gap> IsNumericalSemigroupByGenerators(t);
false
gap> IsNumericalSemigroupByApéryList(s);
false
gap> IsNumericalSemigroupByApéryList(t);
true
```

2.2.2 RepresentsSmallElementsOfNumericalSemigroup

▷ RepresentsSmallElementsOfNumericalSemigroup(*L*) (attribute)

Tests if the list *L* (which has to be a set) may represent the “small” elements of a numerical semigroup.

Example

```
gap> L:= [ 0, 3, 6, 9, 11, 12, 14, 15, 17, 18, 20 ];
[ 0, 3, 6, 9, 11, 12, 14, 15, 17, 18, 20 ]
gap> RepresentsSmallElementsOfNumericalSemigroup(L);
true
gap> L:= [ 6, 9, 11, 12, 14, 15, 17, 18, 20 ];
[ 6, 9, 11, 12, 14, 15, 17, 18, 20 ]
gap> RepresentsSmallElementsOfNumericalSemigroup(L);
false
```

2.2.3 RepresentsGapsOfNumericalSemigroup

▷ RepresentsGapsOfNumericalSemigroup(*L*) (attribute)

Tests if the list *L* may represent the gaps (see 1) of a numerical semigroup.

Example

```
gap> s:=NumericalSemigroup(3,7);
<Numerical semigroup with 2 generators>
gap> L:=GapsOfNumericalSemigroup(s);
[ 1, 2, 4, 5, 8, 11 ]
gap> RepresentsGapsOfNumericalSemigroup(L);
true
gap> L:=Set(List([1..21], i->RandomList([1..50])));
[ 2, 6, 7, 8, 10, 12, 14, 19, 24, 28, 31, 35, 42, 50 ]
gap> RepresentsGapsOfNumericalSemigroup(L);
false
```

2.2.4 IsApéryListOfNumericalSemigroup

▷ IsApéryListOfNumericalSemigroup(*L*) (function)

Tests whether a list *L* of integers may represent the Apéry list of a numerical semigroup. It returns true when the periodic function represented by *L* is subadditive (see RepresentsPeriodicSubAdditiveFunction (A.2.1)) and the remainder of the division of *L*[*i*] by the length of *L* is *i* and returns false otherwise (the criterium used is the one explained in [Ros96b]).

Example

```
gap> IsAperyListOfNumericalSemigroup([0,21,7,28,14]);
true
```

2.2.5 IsSubsemigroupOfNumericalSemigroup

▷ `IsSubsemigroupOfNumericalSemigroup(S , T)` (function)

S and T are numerical semigroups. Tests whether T is contained in S .

Example

```
gap> S := NumericalSemigroup("modular", 5,53);
<Modular numerical semigroup satisfying 5x mod 53 <= x >
gap> T:=NumericalSemigroup(2,3);
<Numerical semigroup with 2 generators>
gap> IsSubsemigroupOfNumericalSemigroup(T,S);
true
gap> IsSubsemigroupOfNumericalSemigroup(S,T);
false
```

2.2.6 IsSubset

▷ `IsSubset(S , T)` (attribute)

S is a numerical semigroup. T can be a numerical semigroup, in which case the function is just a synonym of `IsSubsemigroupOfNumericalSemigroup` (2.2.5), or a list of integers, in which case tests whether all elements of the list belong to S .

Example

```
gap> ns1 := NumericalSemigroup(5,7);;
gap> ns2 := NumericalSemigroup(5,7,11);;
gap> IsSubset(ns1,ns2);
false
gap> IsSubset(ns2,[5,15]);
true
gap> IsSubset(ns1,[5,11]);
false
gap> IsSubset(ns2,ns1);
true
```

2.2.7 BelongsToNumericalSemigroup

▷ `BelongsToNumericalSemigroup(n , S)` (operation)

▷ `\in(n , S)` (operation)

n is an integer and S is a numerical semigroup. Tests whether n belongs to S . `\in(n , S)` calls the infix variant `n in S`, and both can be seen as a short for `BelongsToNumericalSemigroup(n , S)`.

Example

```
gap> S := NumericalSemigroup("modular", 5,53);
<Modular numerical semigroup satisfying 5x mod 53 <= x >
gap> BelongsToNumericalSemigroup(15,S);
```



```
false
gap> 15 in S;
false
gap> SmallElementsOfNumericalSemigroup(S);
[ 0, 11, 12, 13, 22, 23, 24, 25, 26, 32, 33, 34, 35, 36, 37, 38, 39, 43 ]
gap> BelongsToNumericalSemigroup(13,S);
true
gap> 13 in S;
true
```

Chapter 3

Basic operations with numerical semigroups

3.1 Invariants

3.1.1 Multiplicity (for numerical semigroup)

- ▷ `Multiplicity(NS)` (attribute)
- ▷ `MultiplicityOfNumericalSemigroup(NS)` (attribute)

`NS` is a numerical semigroup. Returns the multiplicity of `NS`, which is the smallest positive integer belonging to `NS`.

Example

```
gap> S := NumericalSemigroup("modular", 7,53);
<Modular numerical semigroup satisfying 7x mod 53 <= x >
gap> MultiplicityOfNumericalSemigroup(S);
8
gap> NumericalSemigroup(3,5);
<Numerical semigroup with 2 generators>
gap> Multiplicity(last);
3
```

3.1.2 GeneratorsOfNumericalSemigroup

- ▷ `GeneratorsOfNumericalSemigroup(S)` (attribute)
- ▷ `Generators(S)` (attribute)
- ▷ `MinimalGeneratingSystemOfNumericalSemigroup(S)` (attribute)
- ▷ `MinimalGeneratingSystem(S)` (attribute)
- ▷ `MinimalGenerators(S)` (attribute)

`S` is a numerical semigroup. `GeneratorsOfNumericalSemigroup` returns a set of generators of `S`, which may not be minimal. `MinimalGeneratingSystemOfNumericalSemigroup` returns the minimal set of generators of `S`.

From Version 0.980, `ReducedSetOfGeneratorsOfNumericalSemigroup` is a synonym of `MinimalGeneratingSystemOfNumericalSemigroup`; `GeneratorsOfNumericalSemigroupNC` is

a synonym of `GeneratorsOfNumericalSemigroup`. The names are kept for compatibility with code produced for previous versions, but will be removed in the future.

Example

```
gap> S := NumericalSemigroup("modular", 5, 53);
<Modular numerical semigroup satisfying 5x mod 53 <= x >
gap> GeneratorsOfNumericalSemigroup(S);
[ 11, 12, 13, 32, 53 ]
gap> S := NumericalSemigroup(3, 5, 53);
<Numerical semigroup with 3 generators>
gap> GeneratorsOfNumericalSemigroup(S);
[ 3, 5, 53 ]
gap> MinimalGeneratingSystemOfNumericalSemigroup(S);
[ 3, 5 ]
gap> MinimalGeneratingSystem(S)=MinimalGeneratingSystemOfNumericalSemigroup(S);
true
gap> s := NumericalSemigroup(3, 5, 7, 15);
<Numerical semigroup with 4 generators>
gap> HasGenerators(s);
true
gap> HasMinimalGenerators(s);
false
gap> MinimalGenerators(s);
[ 3, 5, 7 ]
gap> Generators(s);
[ 3, 5, 7, 15 ]
```

3.1.3 EmbeddingDimension (for numerical semigroup)

- ▷ `EmbeddingDimension(NS)` (attribute)
- ▷ `EmbeddingDimensionOfNumericalSemigroup(NS)` (attribute)

`NS` is a numerical semigroup. It returns the cardinality of its minimal generating system.

Example

```
gap> s := NumericalSemigroup(3, 5, 7, 15);
<Numerical semigroup with 4 generators>
gap> EmbeddingDimension(s);
3
gap> EmbeddingDimensionOfNumericalSemigroup(s);
3
```

3.1.4 SmallElements (for numerical semigroup)

- ▷ `SmallElements(NS)` (attribute)
- ▷ `SmallElementsOfNumericalSemigroup(NS)` (attribute)

`NS` is a numerical semigroup. It returns the list of small elements of `NS`. Of course, the time consumed to return a result may depend on the way the semigroup is given.

Example

```
gap> SmallElementsOfNumericalSemigroup(NumericalSemigroup(3, 5, 7));
[ 0, 3, 5 ]
```

```
gap> SmallElements(NumericalSemigroup(3,5,7));
[ 0, 3, 5 ]
```

3.1.5 FirstElementsOfNumericalSemigroup

▷ `FirstElementsOfNumericalSemigroup(n , NS)` (function)

NS is a numerical semigroup. It returns the list with the first n elements of NS .

Example

```
gap> FirstElementsOfNumericalSemigroup(2,NumericalSemigroup(3,5,7));
[ 0, 3 ]
gap> FirstElementsOfNumericalSemigroup(10,NumericalSemigroup(3,5,7));
[ 0, 3, 5, 6, 7, 8, 9, 10, 11, 12 ]
```

3.1.6 ApéryListOfNumericalSemigroupWRTElement

▷ `ApéryListOfNumericalSemigroupWRTElement(S , m)` (operation)

S is a numerical semigroup and m is a positive element of S . Computes the Apéry list of S with respect to m . It contains for every $i \in \{0, \dots, m-1\}$, in the $i+1$ th position, the smallest element in the semigroup congruent with i modulo m .

Example

```
gap> S := NumericalSemigroup("modular", 5,53);
<Modular numerical semigroup satisfying 5x mod 53 <= x >
gap> ApéryListOfNumericalSemigroupWRTElement(S,12);
[ 0, 13, 26, 39, 52, 53, 54, 43, 32, 33, 22, 11 ]
```

3.1.7 ApéryList (for numerical semigroup with respect to multiplicity)

▷ `ApéryList(S)` (attribute)

▷ `ApéryListOfNumericalSemigroup(S)` (attribute)

S is a numerical semigroup. It computes the Apéry list of S with respect to the multiplicity of S .

Example

```
gap> S := NumericalSemigroup("modular", 5,53);
<Modular numerical semigroup satisfying 5x mod 53 <= x >
gap> ApéryListOfNumericalSemigroup(S);
[ 0, 12, 13, 25, 26, 38, 39, 51, 52, 53, 32 ]
gap> ApéryList(NumericalSemigroup(5,7,11));
[ 0, 11, 7, 18, 14 ]
```

3.1.8 ApéryListOfNumericalSemigroupWRTInteger

▷ `ApéryListOfNumericalSemigroupWRTInteger(S , m)` (function)

S is a numerical semigroup and m is an integer. Computes the Apéry list of S with respect to m , that is, the set of elements x in S such that $x-m$ is not in S . If m is an element in S , then the output, as sets, is the same as `ApéryListOfNumericalSemigroupWRTInteger`, though without side effects, in the sense that this information is no longer used by the package.

Example

```

gap> s:=NumericalSemigroup(10,13,19,27);
<Numerical semigroup with 4 generators>
gap> ApéryListOfNumericalSemigroupWRTInteger(s,11);
[ 0, 10, 13, 19, 20, 23, 26, 27, 29, 32, 33, 36, 39, 42, 45, 46, 52, 55 ]
gap> Length(last);
18
gap> ApéryListOfNumericalSemigroupWRTInteger(s,10);
[ 0, 13, 19, 26, 27, 32, 38, 45, 51, 54 ]
gap> ApéryListOfNumericalSemigroupWRTElement(s,10);
[ 0, 51, 32, 13, 54, 45, 26, 27, 38, 19 ]
gap> Length(last);
10

```

3.1.9 ApéryListOfNumericalSemigroupAsGraph

▷ ApéryListOfNumericalSemigroupAsGraph(*ap*)

(function)

ap is the Apéry list of a numerical semigroup. This function returns the adjacency list of the graph (ap, E) where the edge $u \rightarrow v$ is in E iff $v - u$ is in ap . The 0 is ignored.

Example

```

gap> s:=NumericalSemigroup(3,7);
gap> ApéryListOfNumericalSemigroupWRTElement(s,10);
[ 0, 21, 12, 3, 14, 15, 6, 7, 18, 9 ]
gap> ApéryListOfNumericalSemigroupAsGraph(last);
[ ., [ 3, 6, 9, 12, 15, 18, 21 ], ., [ 6, 9, 12, 15, 18, 21 ],
[ 7, 14, 21 ], ., [ 9, 12, 15, 18, 21 ], ., [ 12, 15, 18, 21 ],
[ 14, 21 ], [ 15, 18, 21 ], ., [ 18, 21 ], ., [ 21 ] ]

```

3.1.10 KunzCoordinatesOfNumericalSemigroup

▷ KunzCoordinatesOfNumericalSemigroup(*S*, *m*)

(function)

S is a numerical semigroup, and *m* is a nonzero element of *S*. The second argument is optional, and if missing it is assumed to be the multiplicity of *S*.

Then the Apéry set of *m* in *S* has the form $[0, k_1m + 1, \dots, k_{m-1}m + m - 1]$, and the output is the $(m - 1)$ -uple $[k_1, k_2, \dots, k_{m-1}]$

Example

```

gap> s:=NumericalSemigroup(3,5,7);
<Numerical semigroup with 3 generators>
gap> KunzCoordinatesOfNumericalSemigroup(s);
[ 2, 1 ]
gap> KunzCoordinatesOfNumericalSemigroup(s,5);
[ 1, 1, 0, 1 ]

```

3.1.11 KunzPolytope

▷ KunzPolytope(*m*)

(function)

m is a positive integer.

The Kunz coordinates of the semigroups with multiplicity m are solutions of a system of inequalities $Ax \geq b$ (see [RGSB02]). The output is the matrix $(A \mid -b)$.

Example

```
gap> KunzPolytope(3);
[ [ 1, 0, -1 ], [ 0, 1, -1 ], [ 2, -1, 0 ], [ -1, 2, 1 ] ]
```

3.1.12 FrobeniusNumber (for numerical semigroup)

▷ `FrobeniusNumber(NS)` (attribute)

▷ `FrobeniusNumberOfNumericalSemigroup(NS)` (attribute)

The largest nonnegative integer not belonging to a numerical semigroup S is the *Frobenius number* of S . If S is the set of nonnegative integers, then clearly its Frobenius number is -1 , otherwise its Frobenius number coincides with the maximum of the gaps (or fundamental gaps) of S .

`NS` is a numerical semigroup. It returns the Frobenius number of `NS`. Of course, the time consumed to return a result may depend on the way the semigroup is given or on the knowledge already produced on the semigroup.

Example

```
gap> FrobeniusNumberOfNumericalSemigroup(NumericalSemigroup(3,5,7));
4
gap> FrobeniusNumber(NumericalSemigroup(3,5,7));
4
```

3.1.13 Conductor (for numerical Semigroup)

▷ `Conductor(NS)` (attribute)

▷ `ConductorOfNumericalSemigroup(NS)` (attribute)

This is just a synonym of `FrobeniusNumberOfNumericalSemigroup(NS)+1`.

Example

```
gap> ConductorOfNumericalSemigroup(NumericalSemigroup(3,5,7));
5
gap> Conductor(NumericalSemigroup(3,5,7));
5
```

3.1.14 PseudoFrobeniusOfNumericalSemigroup

▷ `PseudoFrobeniusOfNumericalSemigroup(S)` (attribute)

An integer z is a *pseudo-Frobenius number* of S if $z + S \setminus \{0\} \subseteq S$.

S is a numerical semigroup. It returns set of pseudo-Frobenius numbers of S .

Example

```
gap> S := NumericalSemigroup("modular", 5,53);
<Modular numerical semigroup satisfying 5x mod 53 <= x >
gap> PseudoFrobeniusOfNumericalSemigroup(S);
[ 21, 40, 41, 42 ]
```

3.1.15 TypeOfNumericalSemigroup

▷ `TypeOfNumericalSemigroup(NS)`

(attribute)

Stands for `Length(PseudoFrobeniusOfNumericalSemigroup (NS))`.

Example

```
gap> S := NumericalSemigroup("modular", 5,53);
<Modular numerical semigroup satisfying 5x mod 53 <= x >
gap> Type(S);
4
gap> TypeOfNumericalSemigroup(S);
4
```

3.1.16 Gaps (for numerical semigroup)

▷ `Gaps(NS)`

(attribute)

▷ `GapsOfNumericalSemigroup(NS)`

(attribute)

A *gap* of a numerical semigroup S is a nonnegative integer not belonging to S . `NS` is a numerical semigroup. Both return the set of gaps of NS .

Example

```
gap> GapsOfNumericalSemigroup(NumericalSemigroup(3,5,7));
[ 1, 2, 4 ]
gap> Gaps(NumericalSemigroup(5,7,11));
[ 1, 2, 3, 4, 6, 8, 9, 13 ]
```

3.1.17 Holes (for numerical semigroup)

▷ `Holes(NS)`

(attribute)

▷ `HolesOfNumericalSemigroup(S)`

(attribute)

S is a numerical semigroup. Returns the set of gaps x of S such that $F(S) - x$ is also a gap, where $F(S)$ stands for the Frobenius number of S .

Example

```
gap> s:=NumericalSemigroup(3,5);;
gap> Holes(s);
[ ]
gap> s:=NumericalSemigroup(3,5,7);;
gap> HolesOfNumericalSemigroup(s);
[ 2 ]
```

3.1.18 LatticePathAssociatedToNumericalSemigroup

▷ `LatticePathAssociatedToNumericalSemigroup(S, p, q)`

(attribute)

S is a numerical semigroup and p, q are two elements in S .

In this setting S is an oversemigroup of $\langle p, q \rangle$, and consequently every gap of S is a gap of $\langle p, q \rangle$. If c is the conductor of $\langle p, q \rangle$, then every gap g of $\langle p, q \rangle$ can be written uniquely as $g = c - 1 - (ap + bq)$ for some nonnegative integers a, b . We say that (a, b) are the coordinates associated to g .

The output is a path in \mathbb{N}^2 such that coordinates of the gaps of S correspond exactly with the points in \mathbb{N}^2 that are between the path in the line $ax + by = c - 1$. See [KW14].

Example

```
gap> s:=NumericalSemigroup(16,17,71,72);;
gap> LatticePathAssociatedToNumericalSemigroup(s,16,17);
[ [ 0, 14 ], [ 1, 13 ], [ 2, 12 ], [ 3, 11 ], [ 4, 10 ], [ 5, 9 ], [ 6, 8 ],
  [ 7, 7 ], [ 8, 6 ], [ 9, 5 ], [ 10, 4 ], [ 11, 3 ], [ 12, 2 ], [ 13, 1 ],
  [ 14, 0 ] ]
```

3.1.19 Genus (for numerical semigroup)

- ▷ Genus(NS) (attribute)
- ▷ GenusOfNumericalSemigroup(NS) (attribute)

NS is a numerical semigroup. It returns the number of gaps of NS.

Example

```
gap> s:=NumericalSemigroup(16,17,71,72);;
gap> GenusOfNumericalSemigroup(s);
80
gap> S := NumericalSemigroup("modular", 5,53);
<Modular numerical semigroup satisfying 5x mod 53 <= x >
gap> Genus(S);
26
```

3.1.20 FundamentalGaps (for numerical semigroup)

- ▷ FundamentalGaps(S) (attribute)
- ▷ FundamentalGapsOfNumericalSemigroup(S) (attribute)

S The *fundamental gaps* of S are those gaps that are maximal with respect to the partial order induced by division in \mathbb{N} . is a numerical semigroup. It returns the set of fundamental gaps of S .

Example

```
gap> S := NumericalSemigroup("modular", 5,53);
<Modular numerical semigroup satisfying 5x mod 53 <= x >
gap> FundamentalGapsOfNumericalSemigroup(S);
[ 16, 17, 18, 19, 27, 28, 29, 30, 31, 40, 41, 42 ]
gap> GapsOfNumericalSemigroup(S);
[ 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 14, 15, 16, 17, 18, 19, 20, 21, 27, 28, 29,
  30, 31, 40, 41, 42 ]
gap> Gaps(NumericalSemigroup(5,7,11));
[ 1, 2, 3, 4, 6, 8, 9, 13 ]
gap> FundamentalGaps(NumericalSemigroup(5,7,11));
[ 6, 8, 9, 13 ]
```

3.1.21 SpecialGaps (for numerical semigroup)

- ▷ SpecialGaps(S) (attribute)
- ▷ SpecialGapsOfNumericalSemigroup(S) (attribute)

The *special gaps* of a numerical semigroup S , are those fundamental gaps such that if they are added to the given numerical semigroup, then the resulting set is again a numerical semigroup. S is a numerical semigroup. It returns the special gaps of S .

Example

```
gap> S := NumericalSemigroup("modular", 5,53);
<Modular numerical semigroup satisfying 5x mod 53 <= x >
gap> SpecialGaps(S);
[ 40, 41, 42 ]
gap> SpecialGapsOfNumericalSemigroup(S);
[ 40, 41, 42 ]
```

3.2 Wilf's conjecture

Let S be a numerical semigroup, with conductor c and embedding dimension e . Denote by l the cardinality of the set of elements in S smaller than c . Wilf in [Wil78] asked whether or not $l/c \geq 1/e$ for all numerical semigroups. In this section we give some functions to experiment with this conjecture, as defined in [Eli15].

3.2.1 WilfNumber (for numerical semigroup)

▷ WilfNumber(S) (attribute)
 ▷ WilfNumberOfNumericalSemigroup(S) (attribute)

S is a numerical semigroup. Let c , e and l be the conductor, embedding dimension and number of elements smaller than c in S . Returns $el - c$, which was conjectured by Wilf to be nonnegative.

Example

```
gap> l:=NumericalSemigroupsWithGenus(21);;
gap> Filtered(l, s->WilfNumberOfNumericalSemigroup(s)<0);
[ ]
gap> Maximum(Set(l, s->WilfNumberOfNumericalSemigroup(s)));
378
gap> s := NumericalSemigroup(13,25,37);;
gap> WilfNumber(s);
96
```

3.2.2 EliahouNumber (for numerical semigroup)

▷ EliahouNumber(S) (attribute)
 ▷ TruncatedWilfNumberOfNumericalSemigroup(S) (attribute)

S is a numerical semigroup. Let c , m , s and l be the conductor, multiplicity, number of generators smaller than c , and number of elements smaller than c in S , respectively. Let q and r be the quotient and negative remainder of the division of c by m , that is, $c = qm - r$. Returns $sl - qd_q + r$, where d_q corresponds with the number of integers in $[c, c+m[$ that are not minimal generators of S .

Example

```
gap> s:=NumericalSemigroup(5,7,9);;
gap> TruncatedWilfNumberOfNumericalSemigroup(s);
4
gap> s:=NumericalSemigroupWithGivenElementsAndFrobenius([14,22,23],55);;
```

```
gap> EliahouNumber(s);
-1
```

3.2.3 ProfileOfNumericalSemigroup

▷ ProfileOfNumericalSemigroup(S)

(attribute)

S is a numerical semigroup. Let c and m be the conductor and multiplicity of S , respectively. Let q and r be the quotient and nonpositive remainder of the division of c by m , that is, $c = qm - r$. Returns a list of lists of integers, each list is the cardinality of $S \cap [jm - r, (j+1)m - r[$ with j in $[1..q-1]$.

Example

```
gap> s:=NumericalSemigroup(5,7,9);;
gap> ProfileOfNumericalSemigroup(s);
[ 2, 1 ]
gap> s:=NumericalSemigroupWithGivenElementsAndFrobenius([14,22,23],55);;
gap> ProfileOfNumericalSemigroup(s);
[ 3, 0, 0 ]
```

3.2.4 EliahouSlicesOfNumericalSemigroup

▷ EliahouSlicesOfNumericalSemigroup(S)

(attribute)

S is a numerical semigroup. Let c and m be the conductor and multiplicity of S , respectively. Let q and r be the quotient and negative remainder of the division of c by m , that is, $c = qm - r$. Returns a list of lists of integers, each list is the set $S \cap [jm - r, (j+1)m - r[$ with j in $[1..q]$. So this is a partition of the set of small elements of S (without 0).

Example

```
gap> s:=NumericalSemigroup(5,7,9);;
gap> EliahouSlicesOfNumericalSemigroup(s);
[ [ 5, 7 ], [ 9, 10, 12 ] ]
gap> SmallElements(s);
[ 0, 5, 7, 9, 10, 12, 14 ]
```

Chapter 4

Presentations of Numerical Semigroups

In this chapter we explain how to compute a minimal presentation of a numerical semigroup. There are three functions involved in this process.

4.1 Presentations of Numerical Semigroups

4.1.1 MinimalPresentationOfNumericalSemigroup

▷ `MinimalPresentationOfNumericalSemigroup(S)` (function)

S is a numerical semigroup. The output is a list of lists with two elements. Each list of two elements represents a relation between the minimal generators of the numerical semigroup. If $\{\{x_1, y_1\}, \dots, \{x_k, y_k\}\}$ is the output and $\{m_1, \dots, m_n\}$ is the minimal system of generators of the numerical semigroup, then $\{x_i, y_i\} = \{\{a_{i_1}, \dots, a_{i_n}\}, \{b_{i_1}, \dots, b_{i_n}\}\}$ and $a_{i_1}m_1 + \dots + a_{i_n}m_n = b_{i_1}m_1 + \dots + b_{i_n}m_n$.

Any other relation among the minimal generators of the semigroup can be deduced from the ones given in the output.

The algorithm implemented is described in [Ros96a] (see also [RGS99a]).

Example

```
gap> s:=NumericalSemigroup(3,5,7);
<Numerical semigroup with 3 generators>
gap> MinimalPresentationOfNumericalSemigroup(s);
[ [ [ 0, 2, 0 ], [ 1, 0, 1 ] ], [ [ 3, 1, 0 ], [ 0, 0, 2 ] ],
  [ [ 4, 0, 0 ], [ 0, 1, 1 ] ] ]
```

The first element in the list means that $1 \times 3 + 1 \times 7 = 2 \times 5$, and the others have similar meanings.

4.1.2 GraphAssociatedToElementInNumericalSemigroup

▷ `GraphAssociatedToElementInNumericalSemigroup(n, S)` (function)

S is a numerical semigroup and n is an element in S .

The output is a pair. If $\{m_1, \dots, m_n\}$ is the set of minimal generators of S , then the first component is the set of vertices of the graph associated to n in S , that is, the set $\{m_i \mid n - m_i \in S\}$, and the second component is the set of edges of this graph, that is, $\{\{m_i, m_j\} \mid n - (m_i + m_j) \in S\}$.

This function is used to compute a minimal presentation of the numerical semigroup S , as explained in [Ros96a].

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> GraphAssociatedToElementInNumericalSemigroup(10,s);
[ [ 3, 5, 7 ], [ [ 3, 7 ] ] ]
```

4.1.3 BettiElementsOfNumericalSemigroup

▷ BettiElementsOfNumericalSemigroup(S)

(function)

S is a numerical semigroup.

The output is the set of elements in S whose associated graph is nonconnected [GSO10].

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> BettiElementsOfNumericalSemigroup(s);
[ 10, 12, 14 ]
```

4.1.4 PrimitiveElementsOfNumericalSemigroup

▷ PrimitiveElementsOfNumericalSemigroup(S)

(function)

S is a numerical semigroup.

The output is the set of elements s in S such that there exists a minimal solution to $msg \cdot x - msg \cdot y = 0$, such that x, y are factorizations of s , and msg is the minimal generating system of S . Betti elements are primitive, but not the way around in general.

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> PrimitiveElementsOfNumericalSemigroup(s);
[ 3, 5, 7, 10, 12, 14, 15, 21, 28, 35 ]
```

4.1.5 ShadedSetOfElementInNumericalSemigroup

▷ ShadedSetOfElementInNumericalSemigroup(n, S)

(function)

S is a numerical semigroup and n is an element in S .

The output is a simplicial complex C . If $\{m_1, \dots, m_n\}$ is the set of minimal generators of S , then $L \in C$ if $n - \sum_{i \in L} m_i \in S$ ([SW86]).

This function is a generalization of the graph associated to n .

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> ShadedSetOfElementInNumericalSemigroup(10,s);
[ [ ], [ 3 ], [ 3, 7 ], [ 5 ], [ 7 ] ]
```

4.2 Uniquely Presented Numerical Semigroups

A numerical semigroup S is uniquely presented if for any two minimal presentations σ and τ and any $(a, b) \in \sigma$, either $(a, b) \in \tau$ or $(b, a) \in \tau$, that is, there is essentially a unique minimal presentation (up to arrangement of the components of the pairs in it).

4.2.1 IsUniquelyPresentedNumericalSemigroup

▷ `IsUniquelyPresentedNumericalSemigroup(S)` (function)

S is a numerical semigroup.

The output is true if S has uniquely presented. The implementation is based on (see [GSO10]).

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> IsUniquelyPresentedNumericalSemigroup(s);
true
```

4.2.2 IsGenericNumericalSemigroup

▷ `IsGenericNumericalSemigroup(S)` (function)

S is a numerical semigroup.

The output is true if S has a generic presentation, that is, in every minimal relation all generators occur. These semigroups are uniquely presented (see [BGS11]).

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> IsGenericNumericalSemigroup(s);
true
```

Chapter 5

Constructing numerical semigroups from others

5.1 Adding and removing elements of a numerical semigroup

In this section we show how to construct new numerical semigroups from a given numerical semigroup. Two dual operations are presented. The first one removes a minimal generator from a numerical semigroup. The second adds a special gap to a semigroup (see [RSGGJM03]).

5.1.1 RemoveMinimalGeneratorFromNumericalSemigroup

▷ RemoveMinimalGeneratorFromNumericalSemigroup(n , S) (function)

S is a numerical semigroup and n is one of its minimal generators.

The output is the numerical semigroup $S \setminus \{n\}$ (see [RSGGJM03]; $S \setminus \{n\}$ is a numerical semigroup if and only if n is a minimal generator of S).

Example

```
gap> s:=NumericalSemigroup(3,5,7);  
<Numerical semigroup with 3 generators>  
gap> RemoveMinimalGeneratorFromNumericalSemigroup(7,s);  
<Numerical semigroup with 3 generators>  
gap> MinimalGeneratingSystemOfNumericalSemigroup(last);  
[ 3, 5 ]
```

5.1.2 AddSpecialGapOfNumericalSemigroup

▷ AddSpecialGapOfNumericalSemigroup(g , S) (function)

S is a numerical semigroup and g is a special gap of S

The output is the numerical semigroup $S \cup \{g\}$ (see [RSGGJM03], where it is explained why this set is a numerical semigroup).

Example

```
gap> s:=NumericalSemigroup(3,5,7);  
gap> s2:=RemoveMinimalGeneratorFromNumericalSemigroup(5,s);  
<Numerical semigroup with 3 generators>  
gap> s3:=AddSpecialGapOfNumericalSemigroup(5,s2);
```

```

<Numerical semigroup>
gap> SmallElementsOfNumericalSemigroup(s) =
> SmallElementsOfNumericalSemigroup(s3);
true
gap> s=s3;
true

```

5.2 Intersections, and quotients and multiples by integers

5.2.1 IntersectionOfNumericalSemigroups

▷ `IntersectionOfNumericalSemigroups(S, T)` (function)

S and T are numerical semigroups. Computes the intersection of S and T (which is a numerical semigroup).

Example

```

gap> S := NumericalSemigroup("modular", 5,53);
<Modular numerical semigroup satisfying 5x mod 53 <= x >
gap> T := NumericalSemigroup(2,17);
<Numerical semigroup with 2 generators>
gap> SmallElements(S);
[ 0, 11, 12, 13, 22, 23, 24, 25, 26, 32, 33, 34, 35, 36, 37, 38, 39, 43 ]
gap> SmallElements(T);
[ 0, 2, 4, 6, 8, 10, 12, 14, 16 ]
gap> IntersectionOfNumericalSemigroups(S,T);
<Numerical semigroup>
gap> SmallElements(last);
[ 0, 12, 22, 23, 24, 25, 26, 32, 33, 34, 35, 36, 37, 38, 39, 43 ]

```

5.2.2 QuotientOfNumericalSemigroup

▷ `QuotientOfNumericalSemigroup(S, n)` (function)

S is a numerical semigroup and n is an integer. Computes the quotient of S by n , that is, the set $\{x \in \mathbb{N} \mid nx \in S\}$, which is again a numerical semigroup. S / n may be used as a short for `QuotientOfNumericalSemigroup(S, n)`.

Example

```

gap> s:=NumericalSemigroup(3,29);
<Numerical semigroup with 2 generators>
gap> SmallElements(s);
[ 0, 3, 6, 9, 12, 15, 18, 21, 24, 27, 29, 30, 32, 33, 35, 36, 38,
39, 41, 42, 44, 45, 47, 48, 50, 51, 53, 54, 56 ]
gap> t:=QuotientOfNumericalSemigroup(s,7);
<Numerical semigroup>
gap> SmallElements(t);
[ 0, 3, 5, 6, 8 ]
gap> u := s / 7;
<Numerical semigroup>
gap> SmallElements(u);
[ 0, 3, 5, 6, 8 ]

```

5.2.3 MultipleOfNumericalSemigroup

▷ `MultipleOfNumericalSemigroup(S , a , b)` (function)

S is a numerical semigroup, and a and b are positive integers. Computes $aS \cup \{b, b+1, \rightarrow\}$. If b is smaller than ac , with c the conductor of S , then a warning is displayed.

Example

```
gap> N:=NumericalSemigroup(1);;
gap> s:=MultipleOfNumericalSemigroup(N,4,20);;
gap> SmallElements(s);
[ 0, 4, 8, 12, 16, 20 ]
```

5.2.4 NumericalDuplication

▷ `NumericalDuplication(S , E , b)` (function)

S is a numerical semigroup, and E and ideal of S with $E \subseteq S$, and b are positive odd integer in S . Computes $2S \cup (2E + b)$.

Example

```
gap> s:=NumericalSemigroup(3,5,7);
<Numerical semigroup with 3 generators>
gap> e:=6+s;
<Ideal of numerical semigroup>
gap> ndup:=NumericalDuplication(s,e,3);
<Numerical semigroup>
gap> SmallElements(ndup);
[ 0, 6, 10, 12, 14, 15, 16, 18, 20, 21, 22, 24 ]
```

5.2.5 InductiveNumericalSemigroup

▷ `InductiveNumericalSemigroup(S , a , b)` (function)

S is a numerical semigroup, and a and b are lists of positive integers, such that $b[i+1] \geq a[i]b[i]$. Computes inductively $S_0 = \mathbb{N}$ and $S_{i+1} = a[i]S_i \cup \{a[i]b[i], a[i]b[i] + 1, \rightarrow\}$, and returns S_k , with k the length of a and b .

Example

```
gap> s:=InductiveNumericalSemigroup([4,2],[5,23]);;
gap> SmallElements(s);
[ 0, 8, 16, 24, 32, 40, 42, 44, 46 ]
```

5.3 Constructing the set of all numerical semigroups containing a given numerical semigroup

In order to construct the set of numerical semigroups containing a fixed numerical semigroup S , one first constructs its unitary extensions, that is to say, the sets $S \cup \{g\}$ that are numerical semigroups with g a positive integer. This is achieved by constructing the special gaps of the semigroup, and then adding each of them to the numerical semigroup. Then we repeat the process for each of this new numerical semigroups until we reach \mathbb{N} .

These procedures are described in [\[RSGGJM03\]](#).

5.3.1 OverSemigroupsNumericalSemigroup

▷ OverSemigroupsNumericalSemigroup(s) (function)

s is a numerical semigroup. The output is the set of numerical semigroups containing it.

Example

```
gap> OverSemigroupsNumericalSemigroup(NumericalSemigroup(3,5,7));
[ <The numerical semigroup N>, <Numerical semigroup with 2 generators>,
  <Numerical semigroup with 3 generators>,
  <Numerical semigroup with 3 generators> ]
gap> List(last,s->MinimalGenerators(s));
[ [ 1 ], [ 2, 3 ], [ 3 .. 5 ], [ 3, 5, 7 ] ]
```

5.4 Constructing the set of numerical semigroup with given Frobenius number

5.4.1 NumericalSemigroupsWithFrobeniusNumber

▷ NumericalSemigroupsWithFrobeniusNumber(f) (function)

f is a non zero integer greater than or equal to -1. The output is the set of numerical semigroups with Frobenius number f . The algorithm implemented is given in [RSGGJM04].

Example

```
gap> Length(NumericalSemigroupsWithFrobeniusNumber(20));
900
```

5.5 Constructing the set of numerical semigroups with genus g , that is, numerical semigroups with exactly g gaps

Given a numerical semigroup of genus g , removing minimal generators, one obtains numerical semigroups of genus $g+1$. In order to avoid repetitions, we only remove minimal generators greater than the Frobenius number of the numerical semigroup (this is accomplished with the local function sons).

These procedures are described in [RSGGB03] and [BA08].

5.5.1 NumericalSemigroupsWithGenus

▷ NumericalSemigroupsWithGenus(g) (function)

g is a nonnegative integer. The output is the set of numerical semigroups with genus g .

Example

```
gap> NumericalSemigroupsWithGenus(5);
[ <Numerical semigroup with 6 generators>,
  <Numerical semigroup with 5 generators>,
  <Numerical semigroup with 5 generators>,
  <Numerical semigroup with 5 generators>,
  <Numerical semigroup with 5 generators>,
  <Numerical semigroup with 4 generators>,
  <Numerical semigroup with 4 generators>]
```

```

<Numerical semigroup with 4 generators>,
<Numerical semigroup with 4 generators>,
<Numerical semigroup with 3 generators>,
<Numerical semigroup with 3 generators>,
<Numerical semigroup with 2 generators> ]
gap> List(last, MinimalGenerators);
[ [ 6 .. 11 ], [ 5, 7, 8, 9, 11 ], [ 5, 6, 8, 9 ], [ 5, 6, 7, 9 ],
  [ 5, 6, 7, 8 ], [ 4, 6, 7 ], [ 4, 7, 9, 10 ], [ 4, 6, 9, 11 ],
  [ 4, 5, 11 ], [ 3, 8, 10 ], [ 3, 7, 11 ], [ 2, 11 ] ]

```

5.6 Constructing the set of numerical semigroups with a given set of pseudo-Frobenius numbers

Refer to `PseudoFrobeniusOfNumericalSemigroup` (3.1.14).

These procedures are described in [DGSRP15].

5.6.1 ForcedIntegersForPseudoFrobenius

▷ `ForcedIntegersForPseudoFrobenius(PF)`

(function)

PF is a list of positive integers (given as a list or individual elements). The output is:

- in case there exists a numerical semigroup S such that $PF(S) = PF$:
 - a list $[forced_gaps, forced_elts]$ such that:
 - * $forced_gaps$ is contained in $\mathbb{N} - S$ for any numerical semigroup S such that $PF(S) = \{g_1, \dots, g_n\}$
 - * $forced_elts$ is contained in S for any numerical semigroup S such that $PF(S) = \{g_1, \dots, g_n\}$
- "fail" in case it is found some condition that fails.

Example

```

gap> pf := [ 58, 64, 75 ];
[ 58, 64, 75 ]
gap> ForcedIntegersForPseudoFrobenius(pf);
[ [ 1, 2, 3, 4, 5, 6, 7, 8, 11, 15, 16, 17, 25, 29, 32, 58, 64, 75 ],
  [ 0, 59, 60, 67, 68, 69, 70, 71, 72, 73, 74, 76 ] ]

```

5.6.2 SimpleForcedIntegersForPseudoFrobenius

▷ `SimpleForcedIntegersForPseudoFrobenius(fg, fe, PF)`

(function)

Is just a quicker version of `ForcedIntegersForPseudoFrobenius` (5.6.1)

fg is a list of integers that we require to be gaps of the semigroup; fe is a list of integers that we require to be elements of the semigroup; PF is a list of positive integers. The output is:

- in case there exists a numerical semigroup S such that $PF(S) = PF$:
 - a list $[forced_gaps, forced_elts]$ such that:

- * *forced_gaps* is contained in $\mathbb{N} - S$ for any numerical semigroup S such that $PF(S) = \{g_1, \dots, g_n\}$
- * *forced_elts* is contained in S for any numerical semigroup S such that $PF(S) = \{g_1, \dots, g_n\}$

- "fail" in case it is found some condition that fails.

Example

```
gap> pf := [ 15, 20, 27, 35 ];;
gap> fint := ForcedIntegersForPseudoFrobenius(pf);
[ [ 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 15, 16, 20, 27, 35 ],
  [ 0, 19, 23, 25, 26, 28, 29, 30, 31, 32, 33, 34, 36 ] ]
gap> free := Difference([1..Maximum(pf)], Union(fint));
[ 11, 13, 14, 17, 18, 21, 22, 24 ]
gap> SimpleForcedIntegersForPseudoFrobenius(fint[1], Union(fint[2], [free[1]]), pf);
[ [ 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 13, 15, 16, 20, 24, 27, 35 ],
  [ 0, 11, 19, 22, 23, 25, 26, 28, 29, 30, 31, 32, 33, 34, 36 ] ]
```

5.6.3 NumericalSemigroupsWithPseudoFrobeniusNumbers

▷ NumericalSemigroupsWithPseudoFrobeniusNumbers(*g*)

(function)

PF is a list of positive integers (given as a list or individual elements). The output is: a list of numerical semigroups S such that $PF(S)=PF$. When $\text{Length}(PF)=1$, it makes use of the function NumericalSemigroupsWithFrobeniusNumber (5.4.1)

Example

```
gap> pf := [ 58, 64, 75 ];;
[ 58, 64, 75 ]
gap> Length(NumericalSemigroupsWithPseudoFrobeniusNumbers(pf));
561
gap> pf := [11,19,22];;
gap> NumericalSemigroupsWithPseudoFrobeniusNumbers(pf);
[ <Numerical semigroup>, <Numerical semigroup>, <Numerical semigroup>,
  <Numerical semigroup>, <Numerical semigroup> ]
gap> List(last, MinimalGenerators);
[ [ 7, 9, 17, 20 ], [ 7, 10, 13, 16, 18 ], [ 9, 12, 14, 15, 16, 17, 20 ],
  [ 10, 13, 14, 15, 16, 17, 18, 21 ],
  [ 12, 13, 14, 15, 16, 17, 18, 20, 21, 23 ] ]
```

5.6.4 ANumericalSemigroupWithPseudoFrobeniusNumbers

▷ ANumericalSemigroupWithPseudoFrobeniusNumbers(*g*)

(function)

PF is a list of positive integers (given as a list or individual elements). Alternatively, a record with fields "pseudo_frobenius" and "max_attempts" option The output is: A numerical semigroup S such that $PF(S)=PF$. Returns fail if it concludes that it exists and suggests to use NumericalSemigroupsWithPseudoFrobeniusNumbers if it is not able to conclude...

It makes use of the function AnIrreducibleNumericalSemigroupWithFrobeniusNumber (6.1.4), when $\text{Length}(PF)=1$ or $\text{Length}(PF)=2$ and $2*PF[1] = PF[2]$.

Example

```
gap> pf := [ 83, 169, 173, 214, 259 ];;
gap> ANumericalSemigroupWithPseudoFrobeniusNumbers(pf);
<Numerical semigroup>
gap> gen := MinimalGeneratingSystem(last);
[ 38, 57, 64, 72, 79, 98, 99, 106, 118, 120, 124, 132, 134, 146, 147, 154,
  165, 168, 179 ]
gap> ns := NumericalSemigroup(gen);
<Numerical semigroup with 19 generators>
gap> PseudoFrobeniusOfNumericalSemigroup(ns);
[ 83, 169, 173, 214, 259 ]
```

Chapter 6

Irreducible numerical semigroups

6.1 Irreducible numerical semigroups

An irreducible numerical semigroup is a semigroup that cannot be expressed as the intersection of numerical semigroups properly containing it.

It is not difficult to prove that a semigroup is irreducible if and only if it is maximal (with respect to set inclusion) in the set of all numerical semigroups having its same Frobenius number (see [RB03]). Hence, according to [FGR87] (respectively [BDF97]), symmetric (respectively pseudo-symmetric) numerical semigroups are those irreducible numerical semigroups with odd (respectively even) Frobenius number.

In [RGSGGJM03] it is shown that a nontrivial numerical semigroup is irreducible if and only if it has only one special gap. We use this characterization.

In this section we show how to construct the set of all numerical semigroups with a given Frobenius number. In old versions of the package, we first constructed an irreducible numerical semigroup with the given Frobenius number (as explained in [RGS04]), and then we constructed the rest from it. That is why we separated both functions. The present version uses a faster procedure presented in [BR13].

Every numerical semigroup can be expressed as an intersection of irreducible numerical semigroups. If S can be expressed as $S = S_1 \cap \dots \cap S_n$, with S_i irreducible numerical semigroups, and no factor can be removed, then we say that this decomposition is minimal. Minimal decompositions can be computed by using Algorithm 26 in [RGSGGJM03].

6.1.1 IsIrreducibleNumericalSemigroup

▷ IsIrreducibleNumericalSemigroup(s) (function)

s is a numerical semigroup. The output is true if s is irreducible, false otherwise.

Example

```
gap> IsIrreducibleNumericalSemigroup(NumericalSemigroup(4,6,9));
true
gap> IsIrreducibleNumericalSemigroup(NumericalSemigroup(4,6,7,9));
false
```

6.1.2 IsSymmetricNumericalSemigroup

▷ IsSymmetricNumericalSemigroup(s) (function)

s is a numerical semigroup. The output is true if s is symmetric, false otherwise.

Example

```
gap> IsSymmetricNumericalSemigroup(NumericalSemigroup(10,23));
true
gap> IsSymmetricNumericalSemigroup(NumericalSemigroup(10,11,23));
false
```

6.1.3 IsPseudoSymmetricNumericalSemigroup

▷ IsPseudoSymmetricNumericalSemigroup(s) (function)

s is a numerical semigroup. The output is true if s is pseudo-symmetric, false otherwise.

Example

```
gap> IsPseudoSymmetricNumericalSemigroup(NumericalSemigroup(6,7,8,9,11));
true
gap> IsPseudoSymmetricNumericalSemigroup(NumericalSemigroup(4,6,9));
false
```

6.1.4 AnIrreducibleNumericalSemigroupWithFrobeniusNumber

▷ AnIrreducibleNumericalSemigroupWithFrobeniusNumber(f) (function)

f is an integer greater than or equal to -1. The output is an irreducible numerical semigroup with Frobenius number f . From the way the procedure is implemented, the resulting semigroup has at most four generators (see [RGS04]).

Example

```
gap> s := AnIrreducibleNumericalSemigroupWithFrobeniusNumber(28);
<Numerical semigroup with 3 generators>
gap> MinimalGenerators(s);
[ 3, 17, 31 ]
gap> FrobeniusNumber(s);
28
```

6.1.5 IrreducibleNumericalSemigroupsWithFrobeniusNumber

▷ IrreducibleNumericalSemigroupsWithFrobeniusNumber(f) (function)

f is an integer greater than or equal to -1. The output is the set of all irreducible numerical semigroups with Frobenius number f .

Example

```
gap> Length(IrreducibleNumericalSemigroupsWithFrobeniusNumber(39));
227
```

6.1.6 DecomposeIntoIrreducibles (for numerical semigroup)

▷ `DecomposeIntoIrreducibles(s)`

(function)

s is a numerical semigroup. The output is a set of irreducible numerical semigroups containing it. These elements appear in a minimal decomposition of s as intersection into irreducibles.

Example

```
gap> DecomposeIntoIrreducibles(NumericalSemigroup(5,6,8));
[ <Numerical semigroup with 3 generators>,
  <Numerical semigroup with 4 generators> ]
```

6.2 Complete intersection numerical semigroups

The cardinality of a minimal presentation of a numerical semigroup is always greater than or equal to its embedding dimension minus one. Complete intersection numerical semigroups are numerical semigroups reaching this bound, and they are irreducible. It can be shown that every complete intersection (other than \mathbb{N}) is a complete intersection if and only if it is the gluing of two complete intersections. When in this gluing, one of the copies is isomorphic to \mathbb{N} , then we obtain a free semigroup in the sense of [BC77]. Two special kinds of free semigroups are telescopic semigroups ([KP95]) and those associated to an irreducible planar curve ([Zar86]). We use the algorithms presented in [AGS13] to find the set of all complete intersections (also free, telescopic and associated to irreducible planar curves) numerical semigroups with given Frobenius number.

6.2.1 AsGluingOfNumericalSemigroups

▷ `AsGluingOfNumericalSemigroups(s)`

(function)

s is a numerical semigroup. Returns all partitions $\{A_1, A_2\}$ of the minimal generating set of s such that s is a gluing of $\langle A_1 \rangle$ and $\langle A_2 \rangle$ by $\gcd(A_1)\gcd(A_2)$

Example

```
gap> s := NumericalSemigroup( 10, 15, 16 );
<Numerical semigroup with 3 generators>
gap> AsGluingOfNumericalSemigroups(s);
[ [ [ 10, 15 ], [ 16 ] ], [ [ 10, 16 ], [ 15 ] ] ]
gap> s := NumericalSemigroup( 18, 24, 34, 46, 51, 61, 74, 8 );
<Numerical semigroup with 8 generators>
gap> AsGluingOfNumericalSemigroups(s);
[ ]
```

6.2.2 IsACompleteIntersectionNumericalSemigroup

▷ `IsACompleteIntersectionNumericalSemigroup(s)`

(function)

s is a numerical semigroup. The output is true if the numerical semigroup is a complete intersection, that is, the cardinality of a (any) minimal presentation equals its embedding dimension minus one.

Example

```
gap> s := NumericalSemigroup( 10, 15, 16 );
<Numerical semigroup with 3 generators>
gap> IsACompleteIntersectionNumericalSemigroup(s);
true
gap> s := NumericalSemigroup( 18, 24, 34, 46, 51, 61, 74, 8 );
<Numerical semigroup with 8 generators>
gap> IsACompleteIntersectionNumericalSemigroup(s);
false
```

6.2.3 CompleteIntersectionNumericalSemigroupsWithFrobeniusNumber

▷ CompleteIntersectionNumericalSemigroupsWithFrobeniusNumber(f) (function)

f is an integer greater than or equal to -1 . The output is the set of all complete intersection numerical semigroups with frobenius number f .

Example

```
gap> Length(CompleteIntersectionNumericalSemigroupsWithFrobeniusNumber(57));
34
```

6.2.4 IsFreeNumericalSemigroup

▷ IsFreeNumericalSemigroup(s) (function)

s is a numerical semigroup. The output is true if the numerical semigroup is free in the sense of [BC77]: it is either \mathbb{N} or the gluing of a copy of \mathbb{N} with a free numerical semigroup.

Example

```
gap> IsFreeNumericalSemigroup(NumericalSemigroup(10,15,16));
true
gap> IsFreeNumericalSemigroup(NumericalSemigroup(3,5,7));
false
```

6.2.5 FreeNumericalSemigroupsWithFrobeniusNumber

▷ FreeNumericalSemigroupsWithFrobeniusNumber(f) (function)

f is an integer greater than or equal to -1 . The output is the set of all free numerical semigroups with frobenius number f .

Example

```
gap> Length(FreeNumericalSemigroupsWithFrobeniusNumber(57));
33
```

6.2.6 IsTelescopicNumericalSemigroup

▷ IsTelescopicNumericalSemigroup(s) (function)

s is a numerical semigroup. The output is true if the numerical semigroup is telescopic in the sense of [KP95]: it is either \mathbb{N} or the gluing of $\langle n_e \rangle$ and $s' = \langle n_1/d, \dots, n_{e-1}/d \rangle$, and s' is again a telescopic numerical semigroup, where $n_1 < \dots < n_e$ are the minimal generators of s .

Example

```
gap> IsTelescopicNumericalSemigroup(NumericalSemigroup(4,11,14));
false
gap> IsFreeNumericalSemigroup(NumericalSemigroup(4,11,14));
true
```

6.2.7 TelescopicNumericalSemigroupsWithFrobeniusNumber

▷ `TelescopicNumericalSemigroupsWithFrobeniusNumber(f)` (function)

f is an integer greater than or equal to -1 . The output is the set of all telescopic numerical semigroups with frobenius number f .

Example

```
gap> Length(TelescopicNumericalSemigroupsWithFrobeniusNumber(57));
20
```

6.2.8 IsNumericalSemigroupAssociatedIrreduciblePlanarCurveSingularity

▷ `IsNumericalSemigroupAssociatedIrreduciblePlanarCurveSingularity(s)` (function)

s is a numerical semigroup. The output is true if the numerical semigroup is associated to an irreducible planar curve singularity ([Zar86]). These semigroups are telescopic.

Example

```
gap> ns := NumericalSemigroup(4,11,14);
gap> IsNumericalSemigroupAssociatedIrreduciblePlanarCurveSingularity(ns);
false
gap> ns := NumericalSemigroup(4,11,19);
gap> IsNumericalSemigroupAssociatedIrreduciblePlanarCurveSingularity(ns);
true
```

6.2.9 NumericalSemigroupsAssociatedIrreduciblePlanarCurveSingularityWithFrobeniusNumber

▷ `NumericalSemigroupsAssociatedIrreduciblePlanarCurveSingularityWithFrobeniusNumber(f)` (function)

f is an integer greater than or equal to -1 . The output is the set of all numerical semigroups associated to irreducible planar curves singularities with frobenius number f .

Example

```
gap> Length(
> NumericalSemigroupsAssociatedIrreduciblePlanarCurveSingularityWithFrobeniusNumber
> (57));
7
```

6.3 Almost-symmetric numerical semigroups

A numerical semigroup is almost-symmetric ([BR97]) if its genus is the arithmetic mean of its Frobenius number and type. We use a procedure presented in [RGS14] to determine the set of all almost-symmetric numerical semigroups with given Frobenius number. In order to do this, we first calculate

the set of all almost-symmetric numerical semigroups that can be constructed from an irreducible numerical semigroup.

6.3.1 AlmostSymmetricNumericalSemigroupsFromIrreducible

▷ `AlmostSymmetricNumericalSemigroupsFromIrreducible(s)` (function)

s is an irreducible numerical semigroup. The output is the set of almost-symmetric numerical semigroups that can be constructed from s by removing some of its generators as explained in [RGS14]).

Example

```
gap> ns := NumericalSemigroup(5,8,9,11);;
gap> AlmostSymmetricNumericalSemigroupsFromIrreducible(ns);
[ <Numerical semigroup with 4 generators>,
  <Numerical semigroup with 5 generators>,
  <Numerical semigroup with 5 generators> ]
gap> List(last, MinimalGeneratingSystemOfNumericalSemigroup);
[ [ 5, 8, 9, 11 ], [ 5, 8, 11, 14, 17 ], [ 5, 9, 11, 13, 17 ] ]
```

6.3.2 IsAlmostSymmetricNumericalSemigroup

▷ `IsAlmostSymmetricNumericalSemigroup(s)` (function)

s is a numerical semigroup. The output is true if the numerical semigroup is almost symmetric.

Example

```
gap> IsAlmostSymmetricNumericalSemigroup(NumericalSemigroup(5,8,11,14,17));
true
```

6.3.3 AlmostSymmetricNumericalSemigroupsWithFrobeniusNumber

▷ `AlmostSymmetricNumericalSemigroupsWithFrobeniusNumber(f)` (function)

f is an integer greater than or equal to -1 . The output is the set of all almost symmetric numerical semigroups with Frobenius number f .

Example

```
gap> Length(AlmostSymmetricNumericalSemigroupsWithFrobeniusNumber(12));
15
gap> Length(IrreducibleNumericalSemigroupsWithFrobeniusNumber(12));
2
```

Chapter 7

Ideals of numerical semigroups

Let S be a numerical semigroup. A set I of integers is an *ideal relative* to a numerical semigroup S provided that $I + S \subseteq I$ and that there exists $d \in S$ such that $d + I \subseteq S$.

If $\{i_1, \dots, i_k\}$ is a subset of \mathbb{Z} , then the set $I = \{i_1, \dots, i_k\} + S = \bigcup_{n=1}^k i_n + S$ is an ideal relative to S , and $\{i_1, \dots, i_k\}$ is a system of generators of I . A system of generators M is minimal if no proper subset of M generates the same ideal. Usually, ideals are specified by means of its generators and the ambient numerical semigroup to which they are ideals (for more information see for instance [BDF97]).

7.1 Definitions and basic operations

7.1.1 IdealOfNumericalSemigroup

- ▷ `IdealOfNumericalSemigroup(l, S)` (function)
- ▷ `+(l, S)` (function)

S is a numerical semigroup and l a list of integers. The output is the ideal of S generated by l . There are several shortcuts for this function, as shown in the example.

Example

```
gap> IdealOfNumericalSemigroup([3,5], NumericalSemigroup(9,11));
<Ideal of numerical semigroup>
gap> [3,5]+NumericalSemigroup(9,11);
<Ideal of numerical semigroup>
gap> last=last2;
true
gap> 3+NumericalSemigroup(5,9);
<Ideal of numerical semigroup>
```

7.1.2 IsIdealOfNumericalSemigroup

- ▷ `IsIdealOfNumericalSemigroup(Obj)` (function)

Tests if the object *Obj* is an ideal of a numerical semigroup.

Example

```
gap> I:=[1..7]+NumericalSemigroup(7,19);;
gap> IsIdealOfNumericalSemigroup(I);
true
```

```
gap> IsIdealOfNumericalSemigroup(2);
false
```

7.1.3 MinimalGenerators (for ideal of numerical semigroup)

- ▷ MinimalGenerators(I) (attribute)
- ▷ MinimalGeneratingSystem(I) (attribute)
- ▷ MinimalGeneratingSystemOfIdealOfNumericalSemigroup(I) (attribute)

I is an ideal of a numerical semigroup. The output is the minimal system of generators of I .

Example

```
gap> I := [3,5,9] + NumericalSemigroup(2,11);
gap> MinimalGeneratingSystemOfIdealOfNumericalSemigroup(I);
[ 3 ]
gap> MinimalGeneratingSystem(I);
[ 3 ]
gap> MinimalGenerators([3,5] + NumericalSemigroup(2,11));
[ 3 ]
```

7.1.4 Generators (for ideal of numerical semigroup)

- ▷ Generators(I) (attribute)
- ▷ GeneratorsOfIdealOfNumericalSemigroup(I) (attribute)

I is an ideal of a numerical semigroup. The output is a system of generators of the ideal.

Remark: from Version 1.0.1 on, this value does not change even when a set of minimal generators is computed.

Example

```
gap> I := [3,5,9] + NumericalSemigroup(2,11);
gap> GeneratorsOfIdealOfNumericalSemigroup(I);
[ 3, 5, 9 ]
gap> Generators(I);
[ 3, 5, 9 ]
```

7.1.5 AmbientNumericalSemigroupOfIdeal

- ▷ AmbientNumericalSemigroupOfIdeal(I) (function)

I is an ideal of a numerical semigroup, say S . The output is S .

Example

```
gap> I := [3,5,9] + NumericalSemigroup(2,11);
gap> AmbientNumericalSemigroupOfIdeal(I);
<Numerical semigroup with 2 generators>
```

7.1.6 IsIntegralIdealOfNumericalSemigroup

- ▷ IsIntegralIdealOfNumericalSemigroup(I) (function)

I is an ideal of a numerical semigroup, say S . Detects if $I \subseteq S$.

Example

```
gap> s:=NumericalSemigroup(3,7,5);;
gap> IsIntegralIdealOfNumericalSemigroup(4+s);
false
gap> IsIntegralIdealOfNumericalSemigroup(10+s);
true
```

7.1.7 SmallElements (for ideal of numerical semigroup)

- ▷ SmallElements(I) (function)
- ▷ SmallElementsOfIdealOfNumericalSemigroup(I) (function)

I is an ideal of a numerical semigroup. The output is a list with the elements in I that are less than or equal to the greatest integer not belonging to the ideal plus one.

Example

```
gap> I:=[3,5,9]+NumericalSemigroup(2,11);;
gap> SmallElementsOfIdealOfNumericalSemigroup(I);
[ 3, 5, 7, 9, 11, 13 ]
gap> SmallElements(I) = SmallElementsOfIdealOfNumericalSemigroup(I);
true
gap> J:=[2,11]+NumericalSemigroup(2,11);;
gap> SmallElementsOfIdealOfNumericalSemigroup(J);
[ 2, 4, 6, 8, 10 ]
```

7.1.8 Conductor (for ideal of numerical semigroup)

- ▷ Conductor(NS) (attribute)
- ▷ ConductorOfIdealOfNumericalSemigroup(I) (function)

I is an ideal of a numerical semigroup. The output is the largest element in *SmallElements*(I).

Example

```
gap> s:=NumericalSemigroup(3,7,5);;
gap> ConductorOfIdealOfNumericalSemigroup(10+s);
15
gap> Conductor(10+s);
15
```

7.1.9 BelongsToIdealOfNumericalSemigroup

- ▷ BelongsToIdealOfNumericalSemigroup(n , I) (function)
- ▷ \backslash in(n , I) (operation)

I is an ideal of a numerical semigroup, n is an integer. The output is true if n belongs to I . n in I can be used for short.

Example

```
gap> J:=[2,11]+NumericalSemigroup(2,11);;
gap> BelongsToIdealOfNumericalSemigroup(9,J);
false
gap> 9 in J;
```

```

false
gap> BelongsToIdealOfNumericalSemigroup(10,J);
true
gap> 10 in J;
true

```

7.1.10 SumIdealsOfNumericalSemigroup

▷ SumIdealsOfNumericalSemigroup(I, J) (function)
 ▷ $+(I, J)$ (function)

I, J are ideals of a numerical semigroup. The output is the sum of both ideals $\{i+j \mid i \in I, j \in J\}$.

Example

```

gap> I:=[3,5,9]+NumericalSemigroup(2,11);;
gap> J:=[2,11]+NumericalSemigroup(2,11);;
gap> I+J;
<Ideal of numerical semigroup>
gap> MinimalGeneratingSystemOfIdealOfNumericalSemigroup(last);
[ 5, 14 ]
gap> SumIdealsOfNumericalSemigroup(I,J);
<Ideal of numerical semigroup>
gap> MinimalGeneratingSystemOfIdealOfNumericalSemigroup(last);
[ 5, 14 ]

```

7.1.11 MultipleOfIdealOfNumericalSemigroup

▷ MultipleOfIdealOfNumericalSemigroup(n, I) (function)
 ▷ $*(n, I)$ (function)

I is an ideal of a numerical semigroup, n is a non negative integer. The output is the ideal $I + \dots + I$ (n times).

$n * I$ can be used for short.

Example

```

gap> I:=[0,1]+NumericalSemigroup(3,5,7);;
gap> MinimalGeneratingSystemOfIdealOfNumericalSemigroup(2*I);
[ 0, 1, 2 ]

```

7.1.12 SubtractIdealsOfNumericalSemigroup

▷ SubtractIdealsOfNumericalSemigroup(I, J) (function)
 ▷ $-(I, J)$ (function)

I, J are ideals of a numerical semigroup. The output is the ideal $\{z \in \mathbb{Z} \mid z+J \subseteq I\}$.

$I-J$ is a synonym of SubtractIdealsOfNumericalSemigroup.

$S-J$ is a synonym of $(0+S)-J$, if S is the ambient semigroup of I and J . The following example appears in [HS04].

Example

```
gap> S:=NumericalSemigroup(14, 15, 20, 21, 25);;
gap> I:=[0,1]+S;;
gap> II:=S-I;;
gap> MinimalGeneratingSystemOfIdealOfNumericalSemigroup(I);
[ 0, 1 ]
gap> MinimalGeneratingSystemOfIdealOfNumericalSemigroup(II);
[ 14, 20 ]
gap> MinimalGeneratingSystemOfIdealOfNumericalSemigroup(I+II);
[ 14, 15, 20, 21 ]
```

7.1.13 DifferenceOfIdealsOfNumericalSemigroup

▷ `DifferenceOfIdealsOfNumericalSemigroup(I, J)` (function)

I, J are ideals of a numerical semigroup. J must be contained in I . The output is the set $I \setminus J$.

Example

```
gap> S:=NumericalSemigroup(14, 15, 20, 21, 25);;
gap> I:=[0,1]+S;
<Ideal of numerical semigroup>
gap> 2*I-2*I;
<Ideal of numerical semigroup>
gap> I-I;
<Ideal of numerical semigroup>
gap> DifferenceOfIdealsOfNumericalSemigroup(last2,last);
[ 26, 27, 37, 38 ]
```

7.1.14 TranslationOfIdealOfNumericalSemigroup

▷ `TranslationOfIdealOfNumericalSemigroup(k, I)` (function)

Given an ideal I of a numerical semigroup S and an integer k returns an ideal of the numerical semigroup S generated by $\{i_1 + k, \dots, i_n + k\}$ where $\{i_1, \dots, i_n\}$ is the system of generators of I .

As a synonym to `TranslationOfIdealOfNumericalSemigroup(k, I)` the expression $k + I$ may be used.

Example

```
gap> s:=NumericalSemigroup(13,23);;
gap> l:=List([1..6], _ -> Random([8..34]));
[ 22, 29, 34, 25, 10, 12 ]
gap> I:=IdealOfNumericalSemigroup(l, s);;
gap> It:=TranslationOfIdealOfNumericalSemigroup(7,I);
<Ideal of numerical semigroup>
gap> It2:=7+I;
<Ideal of numerical semigroup>
gap> It2=It;
true
```

7.1.15 IntersectionIdealsOfNumericalSemigroup

▷ IntersectionIdealsOfNumericalSemigroup(I, J) (function)

Given two ideals I and J of a numerical semigroup S returns the ideal of the numerical semigroup S which is the intersection of the ideals I and J .

Example

```
gap> i:=IdealOfNumericalSemigroup([75,89],s);
gap> j:=IdealOfNumericalSemigroup([115,289],s);
gap> IntersectionIdealsOfNumericalSemigroup(i,j);
<Ideal of numerical semigroup>
```

7.1.16 MaximalIdealOfNumericalSemigroup

▷ MaximalIdealOfNumericalSemigroup(S) (function)

Returns the maximal ideal of the numerical semigroup S .

Example

```
gap> MaximalIdealOfNumericalSemigroup(NumericalSemigroup(3,7));
<Ideal of numerical semigroup>
```

7.1.17 CanonicalIdealOfNumericalSemigroup

▷ CanonicalIdealOfNumericalSemigroup(S) (function)

S is a numerical semigroup. Computes a canonical ideal of S ([BF06]): $\{x \in \mathbb{Z} \mid g - x \notin S\}$.

Example

```
gap> s:=NumericalSemigroup(4,6,11);
gap> m:=MaximalIdealOfNumericalSemigroup(s);
gap> c:=CanonicalIdealOfNumericalSemigroup(s);
<Ideal of numerical semigroup>
gap> c-(c-m)=m;
true
gap> id:=3+s;
<Ideal of numerical semigroup>
gap> c-(c-id)=id;
true
```

7.1.18 IsCanonicalIdealOfNumericalSemigroup

▷ IsCanonicalIdealOfNumericalSemigroup(E) (function)

E is an ideal of a numerical semigroup, say S . Determines if E is a translation of the canonical ideal of S , or equivalently, for every ideal J , $E - (E - J) = J$.

Example

```
gap> s:=NumericalSemigroup(3,5,7);
gap> c:=3+CanonicalIdealOfNumericalSemigroup(s);
gap> c-(c-(3+s))=3+s;
true
gap> IsCanonicalIdealOfNumericalSemigroup(c);
true
```


7.2 Other functions for ideals

7.2.1 HilbertFunctionOfIdealOfNumericalSemigroup

▷ `HilbertFunctionOfIdealOfNumericalSemigroup(n , I)` (function)

I is an ideal of a numerical semigroup, n is a non negative integer. I must be contained in its ambient semigroup. The output is the cardinality of the set $nI \setminus (n+1)I$.

Example

```
gap> I:=[6,9,11]+NumericalSemigroup(6,9,11);;
gap> List([1..7],n->HilbertFunctionOfIdealOfNumericalSemigroup(n,I));
[ 3, 5, 6, 6, 6, 6, 6 ]
```

7.2.2 BlowUpIdealOfNumericalSemigroup

▷ `BlowUpIdealOfNumericalSemigroup(I)` (function)

I is an ideal of a numerical semigroup. The output is the ideal $\bigcup_{n \geq 0} nI - nI$.

Example

```
gap> I:=[0,2]+NumericalSemigroup(6,9,11);;
gap> BlowUpIdealOfNumericalSemigroup(I);;
gap> SmallElementsOfIdealOfNumericalSemigroup(last);
[ 0, 2, 4, 6, 8 ]
```

7.2.3 ReductionNumberIdealNumericalSemigroup

▷ `ReductionNumberIdealNumericalSemigroup(I)` (function)

I is an ideal of a numerical semigroup. The output is the least integer such that $nI + i = (n+1)I$, where $i = \min(I)$.

Example

```
gap> I:=[0,2]+NumericalSemigroup(6,9,11);;
gap> ReductionNumberIdealNumericalSemigroup(I);
2
```

7.2.4 BlowUpOfNumericalSemigroup

▷ `BlowUpOfNumericalSemigroup(S)` (function)

S is a numerical semigroup. If M is the maximal ideal of the numerical semigroup, then the output is the numerical semigroup $\bigcup_{n \geq 0} nM - nM$.

Example

```
gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> BlowUpOfNumericalSemigroup(s);
<Numerical semigroup with 10 generators>
gap> SmallElementsOfNumericalSemigroup(last);
[ 0, 5, 10, 12, 15, 17, 20, 22, 24, 25, 27, 29, 30, 32, 34, 35, 36, 37, 39,
  40, 41, 42, 44 ]
gap> m:=MaximalIdealOfNumericalSemigroup(s);
```

```

<Ideal of numerical semigroup>
gap> BlowUpIdealOfNumericalSemigroup(m);
<Ideal of numerical semigroup>
gap> SmallElementsOfIdealOfNumericalSemigroup(last);
[ 0, 5, 10, 12, 15, 17, 20, 22, 24, 25, 27, 29, 30, 32, 34, 35, 36, 37, 39,
  40, 41, 42, 44 ]

```

7.2.5 LipmanSemigroup

▷ LipmanSemigroup(S) (attribute)

This is just a synonym of BlowUpOfNumericalSemigroup (7.2.4)(S).

Example

```

gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> LipmanSemigroup(s);
<Numerical semigroup with 10 generators>
gap> SmallElementsOfNumericalSemigroup(last);
[ 0, 5, 10, 12, 15, 17, 20, 22, 24, 25, 27, 29, 30, 32, 34, 35, 36, 37, 39,
  40, 41, 42, 44 ]

```

7.2.6 MultiplicitySequenceOfNumericalSemigroup

▷ MultiplicitySequenceOfNumericalSemigroup(S) (attribute)

S is a numerical semigroup. The output is a list with the multiplicities of the sequence $S \subseteq L(S) \subseteq \dots \subseteq \mathbb{N}$, where $L(\cdot)$ means LipmanSemigroup (7.2.5).

Example

```

gap> s:=NumericalSemigroup(3,5);
<Numerical semigroup with 2 generators>
gap> MultiplicitySequenceOfNumericalSemigroup(s);
[ 3, 2, 1 ]

```

7.2.7 MicroInvariantsOfNumericalSemigroup

▷ MicroInvariantsOfNumericalSemigroup(S) (function)

Returns the microinvariants of the numerical semigroup S defined in [Eli01]. For their computation we have used the formula given in [BF06]. The Apéry set of S and its blow up are involved in this computation.

Example

```

gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> bu:=BlowUpOfNumericalSemigroup(s);;
gap> ap:=AperyListOfNumericalSemigroupWRTElement(s,30);;
gap> apbu:=AperyListOfNumericalSemigroupWRTElement(bu,30);;
gap> (ap-apbu)/30;
[ 0, 4, 4, 3, 2, 1, 3, 4, 4, 3, 2, 3, 1, 4, 4, 3, 3, 1, 4, 4, 4, 3, 2, 4, 2,
  5, 4, 3, 3, 2 ]
gap> MicroInvariantsOfNumericalSemigroup(s)=last;
true

```

7.2.8 IsGradedAssociatedRingNumericalSemigroupCM

▷ IsGradedAssociatedRingNumericalSemigroupCM(S) (function)

S is a numerical semigroup. Returns true if the graded ring associated to $K[[S]]$ is Cohen-Macaulay, and false otherwise. This test is the implementation of the algorithm given in [BF06].

Example

```
gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> IsGradedAssociatedRingNumericalSemigroupCM(s);
false
gap> MicroInvariantsOfNumericalSemigroup(s);
[ 0, 4, 4, 3, 2, 1, 3, 4, 4, 3, 2, 3, 1, 4, 4, 3, 3, 1, 4, 4, 4, 3, 2, 4, 2,
  5, 4, 3, 3, 2 ]
gap> List(AperyListOfNumericalSemigroupWRTElement(s,30),
> w->MaximumDegreeOfElementWRTNumericalSemigroup (w,s));
[ 0, 1, 4, 1, 2, 1, 3, 1, 4, 3, 2, 3, 1, 1, 4, 3, 3, 1, 4, 1, 4, 3, 2, 4, 2,
  5, 4, 3, 1, 2 ]
gap> last=last2;
false
gap> s:=NumericalSemigroup(4,6,11);;
gap> IsGradedAssociatedRingNumericalSemigroupCM(s);
true
gap> MicroInvariantsOfNumericalSemigroup(s);
[ 0, 2, 1, 1 ]
gap> List(AperyListOfNumericalSemigroupWRTElement(s,4),
> w->MaximumDegreeOfElementWRTNumericalSemigroup (w,s));
[ 0, 2, 1, 1 ]
```

7.2.9 IsMonomialNumericalSemigroup

▷ IsMonomialNumericalSemigroup(S) (function)

S is a numerical semigroup. Tests whether S is a monomial numerical semigroup.

Let R be a Noetherian ring such that $K \subseteq R \subseteq K[[t]]$, K is a field of characteristic zero, the algebraic closure of R is $K[[t]]$, and the conductor $(R : K[[t]])$ is not zero. If $v : K((t)) \rightarrow \mathbb{Z}$ is the natural valuation for $K((t))$, then $v(R)$ is a numerical semigroup.

Let S be a numerical semigroup minimally generated by $\{n_1, \dots, n_e\}$. The semigroup ring associated to S is $K[[S]] = K[[t^{n_1}, \dots, t^{n_e}]]$. A ring is called a semigroup ring if it is of the form $K[[S]]$, for some numerical semigroup S . We say that S is a monomial numerical semigroup if for any R as above with $v(R) = S$, R is a semigroup ring. See [Mic02] for details.

Example

```
gap> IsMonomialNumericalSemigroup(NumericalSemigroup(4,6,7));
true
gap> IsMonomialNumericalSemigroup(NumericalSemigroup(4,6,11));
false
```

7.2.10 AperyListOfIdealOfNumericalSemigroupWRTElement

▷ AperyListOfIdealOfNumericalSemigroupWRTElement(I, n) (function)

I is an ideal and n is an integer. Computes the set of elements x of I such that $x - n$ is not in the ideal I , where n is supposed to be in the ambient semigroup of I . The element in the i th position of the output list (starting in 0) is congruent with i modulo n .

Example

```
gap> s:=NumericalSemigroup(10,11,13);;
gap> i:=[12,14]+s;;
gap> ApéryListOfIdealOfNumericalSemigroupWRTElement(i,10);
[ 40, 51, 12, 23, 14, 25, 36, 27, 38, 49 ]
```

7.2.11 ApéryTableOfNumericalSemigroup

▷ ApéryTableOfNumericalSemigroup(s)

(function)

Computes the Apéry table associated to the numerical semigroup s as explained in [CBJZA13], that is, a list containing the Apéry list of s with respect to its multiplicity and the Apéry lists of kM (with M the maximal ideal of s) with respect to the multiplicity of s , for $k \in \{1, \dots, r\}$, where r is the reduction number of M (see ReductionNumberIdealNumericalSemigroup).

Example

```
gap> s:=NumericalSemigroup(10,11,13);;
gap> ApéryTableOfNumericalSemigroup(s);
[ [ 0, 11, 22, 13, 24, 35, 26, 37, 48, 39 ],
  [ 10, 11, 22, 13, 24, 35, 26, 37, 48, 39 ],
  [ 20, 21, 22, 23, 24, 35, 26, 37, 48, 39 ],
  [ 30, 31, 32, 33, 34, 35, 36, 37, 48, 39 ],
  [ 40, 41, 42, 43, 44, 45, 46, 47, 48, 49 ] ]
```

7.2.12 StarClosureOfIdealOfNumericalSemigroup

▷ StarClosureOfIdealOfNumericalSemigroup(i , is)

(function)

i is an ideal and is is a set of ideals (all from the same numerical semigroups). The output is $i^{*_{is}}$, where $*_{is}$ is the star operation generated by is : $(s - (s - i)) \cap_{k \in is} (k - (k - i))$. The implementation uses Section 3 of [Spi15].

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> StarClosureOfIdealOfNumericalSemigroup([0,2]+s,[[0,4]+s]);;
gap> MinimalGeneratingSystemOfIdealOfNumericalSemigroup(last);
[ 0, 2, 4 ]
```

Chapter 8

Numerical semigroups with maximal embedding dimension

8.1 Numerical semigroups with maximal embedding dimension

If S is a numerical semigroup and m is its multiplicity (the least positive integer belonging to it), then the embedding dimension e of S (the cardinality of the minimal system of generators of S) is less than or equal to m . We say that S has maximal embedding dimension (MED for short) when $e = m$. The intersection of two numerical semigroups with the same multiplicity and maximal embedding dimension is again of maximal embedding dimension. Thus we define the MED closure of a non-empty subset of positive integers $M = \{m < m_1 < \dots < m_n < \dots\}$ with $\gcd(M) = 1$ as the intersection of all MED numerical semigroups with multiplicity m .

Given a MED numerical semigroup S , we say that $M = \{m_1 < \dots < m_k\}$ is a MED system of generators if the MED closure of M is S . Moreover, M is a minimal MED generating system for S provided that every proper subset of M is not a MED system of generators of S . Minimal MED generating systems are unique, and in general are smaller than the classical minimal generating systems (see [RGSGB03]).

8.1.1 IsMEDNumericalSemigroup

▷ `IsMEDNumericalSemigroup(S)` (function)

S is a numerical semigroup.

Returns true if S is a MED numerical semigroup and false otherwise.

Example

```
gap> IsMEDNumericalSemigroup(NumericalSemigroup(3,5,7));
true
gap> IsMEDNumericalSemigroup(NumericalSemigroup(3,5));
false
```

8.1.2 MEDNumericalSemigroupClosure

▷ `MEDNumericalSemigroupClosure(S)` (function)

S is a numerical semigroup.

Returns the MED closure of S .

Example

```
gap> MEDNumericalSemigroupClosure(NumericalSemigroup(3,5));
<Numerical semigroup>
gap> MinimalGenerators(last);
[ 3, 5, 7 ]
```

8.1.3 MinimalMEDGeneratingSystemOfMEDNumericalSemigroup

▷ MinimalMEDGeneratingSystemOfMEDNumericalSemigroup(S)

(function)

S is a MED numerical semigroup.

Returns the minimal MED generating system of S .

Example

```
gap> MinimalMEDGeneratingSystemOfMEDNumericalSemigroup(
> NumericalSemigroup(3,5,7));
[ 3, 5 ]
```

8.2 Numerical semigroups with the Arf property and Arf closures

Numerical semigroups with the Arf property are a special kind of numerical semigroups with maximal embedding dimension. A numerical semigroup S is Arf if for every x, y, z in S with $x \geq y \geq z$, one has that $x + y - z \in S$.

The intersection of two Arf numerical semigroups is again Arf, and thus we can consider the Arf closure of a set of nonnegative integers with greatest common divisor equal to one. Analogously as with MED numerical semigroups, we define Arf systems of generators and minimal Arf generating system for an Arf numerical semigroup. These are also unique (see [RSGGB04]).

8.2.1 IsArfNumericalSemigroup

▷ IsArfNumericalSemigroup(S)

(function)

S is a numerical semigroup.

Returns true if S is an Arf numerical semigroup and false otherwise.

Example

```
gap> IsArfNumericalSemigroup(NumericalSemigroup(3,5,7));
true
gap> IsArfNumericalSemigroup(NumericalSemigroup(3,7,11));
false
gap> IsMEDNumericalSemigroup(NumericalSemigroup(3,7,11));
true
```

8.2.2 ArfNumericalSemigroupClosure

▷ ArfNumericalSemigroupClosure(S)

(function)

S is a numerical semigroup.

Returns the Arf closure of S .

Example

```
gap> ArfNumericalSemigroupClosure(NumericalSemigroup(3,7,11));
<Numerical semigroup>
gap> MinimalGenerators(last);
[ 3, 7, 8 ]
```

8.2.3 MinimalArfGeneratingSystemOfArfNumericalSemigroup

▷ MinimalArfGeneratingSystemOfArfNumericalSemigroup(S)

(function)

S is an Arf numerical semigroup.

Returns the minimal Arf generating system of S .

Example

```
gap> MinimalArfGeneratingSystemOfArfNumericalSemigroup(
> NumericalSemigroup(3,7,8));
[ 3, 7 ]
```

8.2.4 ArfNumericalSemigroupsWithFrobeniusNumber

▷ ArfNumericalSemigroupsWithFrobeniusNumber(f)

(function)

f is an integer greater than or equal to -1. The output is the set of all Arf numerical semigroups with Frobenius number f .

Example

```
gap> ArfNumericalSemigroupsWithFrobeniusNumber(10);
[ <Numerical semigroup>, <Numerical semigroup>, <Numerical semigroup>,
  <Numerical semigroup>, <Numerical semigroup>, <Numerical semigroup>,
  <Numerical semigroup>, <Numerical semigroup>, <Numerical semigroup> ]
gap> List(last, MinimalGenerators);
[ [ 7, 9, 11, 12, 13, 15, 17 ], [ 3, 11, 13 ], [ 6, 9, 11, 13, 14, 16 ],
  [ 9, 11, 12, 13, 14, 15, 16, 17, 19 ], [ 4, 11, 13, 14 ],
  [ 8, 11, 12, 13, 14, 15, 17, 18 ], [ 7, 11, 12, 13, 15, 16, 17 ],
  [ 6, 11, 13, 14, 15, 16 ], [ 11 .. 21 ] ]
```

8.3 Saturated numerical semigroups

Saturated numerical semigroups with the Arf property are a special kind of numerical semigroups with maximal embedding dimension. A numerical semigroup S is saturated if the following condition holds: s, s_1, \dots, s_r in S are such that $s_i \leq s$ for all i in $\{1, \dots, r\}$ and z_1, \dots, z_r in \mathbb{Z} are such that $z_1 s_1 + \dots + z_r s_r \geq 0$, then $s + z_1 s_1 + \dots + z_r s_r$ in S .

The intersection of two saturated numerical semigroups is again saturated, and thus we can consider the saturated closure of a set of nonnegative integers with greatest common divisor equal to one (see [RGS09]).

8.3.1 IsSaturatedNumericalSemigroup

▷ IsSaturatedNumericalSemigroup(S)

(function)

S is a numerical semigroup.

Returns true if S is a saturated numerical semigroup and false otherwise.

Example

```
gap> IsSaturatedNumericalSemigroup(NumericalSemigroup(4,6,9,11));
true
gap> IsSaturatedNumericalSemigroup(NumericalSemigroup(8, 9, 12, 13, 15, 19 ));
false
```

8.3.2 SaturatedNumericalSemigroupClosure

▷ SaturatedNumericalSemigroupClosure(S)

(function)

S is a numerical semigroup.

Returns the saturated closure of S .

Example

```
gap> SaturatedNumericalSemigroupClosure(NumericalSemigroup(8, 9, 12, 13, 15));
<Numerical semigroup>
gap> MinimalGenerators(last);
[ 8 .. 15 ]
```

8.3.3 SaturatedNumericalSemigroupsWithFrobeniusNumber

▷ SaturatedNumericalSemigroupsWithFrobeniusNumber(f)

(function)

f is an integer greater than or equal to -1. The output is the set of all Saturated numerical semigroups with Frobenius number f .

Example

```
gap> SaturatedNumericalSemigroupsWithFrobeniusNumber(10);
[ <Numerical semigroup with 3 generators>,
  <Numerical semigroup with 4 generators>,
  <Numerical semigroup with 6 generators>,
  <Numerical semigroup with 6 generators>,
  <Numerical semigroup with 7 generators>,
  <Numerical semigroup with 8 generators>,
  <Numerical semigroup with 9 generators>,
  <Numerical semigroup with 11 generators> ]
gap> List(last,MinimalGenerators);
[ [ 3, 11, 13 ], [ 4, 11, 13, 14 ], [ 6, 9, 11, 13, 14, 16 ],
  [ 6, 11, 13, 14, 15, 16 ], [ 7, 11, 12, 13, 15, 16, 17 ],
  [ 8, 11, 12, 13, 14, 15, 17, 18 ], [ 9, 11, 12, 13, 14, 15, 16, 17, 19 ],
  [ 11 .. 21 ] ]
```


Chapter 9

Nonunique invariants for factorizations in numerical semigroups

9.1 Factorizations in Numerical Semigroups

Let S be a numerical semigroup minimally generated by $\{m_1, \dots, m_n\}$. A factorization of an element $s \in S$ is an n -tuple $a = (a_1, \dots, a_n)$ of nonnegative integers such that $s = a_1 m_1 + \dots + a_n m_n$. The length of a is $|a| = a_1 + \dots + a_n$. Given two factorizations a and b of s , the distance between a and b is $d(a, b) = \max\{|a - \gcd(a, b)|, |b - \gcd(a, b)|\}$, where $\gcd((a_1, \dots, a_n), (b_1, \dots, b_n)) = (\min(a_1, b_1), \dots, \min(a_n, b_n))$.

If $l_1 > \dots > l_k$ are the lengths of all the factorizations of $s \in S$, the Delta set associated to s is $\Delta(s) = \{l_1 - l_2, \dots, l_k - l_{k-1}\}$.

The catenary degree of an element in S is the least positive integer c such that for any two of its factorizations a and b , there exists a chain of factorizations starting in a and ending in b and so that the distance between two consecutive links is at most c . The catenary degree of S is the supremum of the catenary degrees of the elements in S .

The tame degree of S is the least positive integer t such that for any factorization a of an element s in S , and any i such that $s - m_i \in S$, there exists another factorization b of s so that the distance to a is at most t and $b_i \neq 0$.

The ω -primality of an element s in S is the least positive integer k such that if $(\sum_{i \in I} s_i) - s \in S, s_i \in S$, then there exists $\Omega \subseteq I$ with cardinality k such that $(\sum_{i \in \Omega} s_i) - s \in S$. The ω -primality of S is the maximum of the ω -primality of its minimal generators.

The basic properties of these constants can be found in [GHK06]. The algorithm used to compute the catenary and tame degree is an adaptation of the algorithms appearing in [CGSL⁺06] for numerical semigroups (see [CGSD07]). The computation of the elasticity of a numerical semigroup reduces to m/n with m the multiplicity of the semigroup and n its largest minimal generator (see [CHM06] or [GHK06]).

9.1.1 FactorizationsIntegerWRTList

▷ FactorizationsIntegerWRTList(n , ls) (function)

ls is a list of integers and n an integer. The output is the set of factorizations of n in terms of the elements in the list ls . This function uses RestrictedPartitions.

Example

```
gap> FactorizationsIntegerWRTList(100,[11,13,15,19]);
[[ 2, 6, 0, 0 ], [ 3, 4, 1, 0 ], [ 4, 2, 2, 0 ], [ 5, 0, 3, 0 ],
 [ 5, 2, 0, 1 ], [ 6, 0, 1, 1 ], [ 0, 1, 2, 3 ], [ 1, 1, 0, 4 ]]
```

9.1.2 FactorizationsElementWRTNumericalSemigroup

▷ `FactorizationsElementWRTNumericalSemigroup(n , S)` (function)

S is a numerical semigroup and n a nonnegative integer. The output is the set of factorizations of n in terms of the minimal generating set of S .

Example

```
gap> s:=NumericalSemigroup(101,113,196,272,278,286);
<Numerical semigroup with 6 generators>
gap> FactorizationsElementWRTNumericalSemigroup(1100,s);
[[ 0, 8, 1, 0, 0, 0 ], [ 0, 0, 0, 2, 2, 0 ], [ 5, 1, 1, 0, 0, 1 ],
 [ 0, 2, 3, 0, 0, 1 ]]
```

9.1.3 RClassesOfSetOfFactorizations

▷ `RClassesOfSetOfFactorizations(ls)` (function)

ls is a set of factorizations (a list of lists of nonnegative integers with the same length). The output is the set of \mathcal{R} -classes of this set of factorizations as defined in Chapter 7 of [RGS09].

Example

```
gap> s:=NumericalSemigroup(10,11,19,23);;
gap> BettiElementsOfNumericalSemigroup(s);
[ 30, 33, 42, 57, 69 ]
gap> FactorizationsElementWRTNumericalSemigroup(69,s);
[[ 5, 0, 1, 0 ], [ 2, 1, 2, 0 ], [ 0, 0, 0, 3 ] ]
gap> RClassesOfSetOfFactorizations(last);
[[ [ 2, 1, 2, 0 ], [ 5, 0, 1, 0 ] ], [ [ 0, 0, 0, 3 ] ] ]
```

9.1.4 LShapesOfNumericalSemigroup

▷ `LShapesOfNumericalSemigroup(S)` (function)

S is a numerical semigroup. The output is the number of LShapes associated to S . These are ways of arranging the set of factorizations of the elements in the Apéry set of the largest generator, so that if one factorization x is chosen for w and $w - w' \in S$, then only the factorization of x' of w' with $x' \leq x$ can be in the LShape (and if there is no such a factorization, then we have no LShape with x in it), see [AGGS10].

Example

```
gap> s:=NumericalSemigroup(4,6,9);;
gap> LShapesOfNumericalSemigroup(s);
[[ [ 0, 0 ], [ 1, 0 ], [ 0, 1 ], [ 2, 0 ], [ 1, 1 ], [ 0, 2 ], [ 2, 1 ],
 [ 1, 2 ], [ 2, 2 ] ],
 [ [ 0, 0 ], [ 1, 0 ], [ 0, 1 ], [ 2, 0 ], [ 1, 1 ], [ 3, 0 ], [ 2, 1 ],
 [ 4, 0 ], [ 5, 0 ] ] ]
```

9.1.5 DenumerantOfElementInNumericalSemigroup

▷ `DenumerantOfElementInNumericalSemigroup(n , S)` (function)

S is a numerical semigroup and n a positive integer. The output is the number of factorizations of n in terms of the minimal generating set of S .

Example

```
gap> s:=NumericalSemigroup(101,113,195,272,278,286);
gap> DenumerantOfElementInNumericalSemigroup(1311,s);
6
```

9.2 Invariants based on lengths

9.2.1 LengthsOfFactorizationsIntegerWRTList

▷ `LengthsOfFactorizationsIntegerWRTList(n , ls)` (function)

ls is a list of integers and n an integer. The output is the set of lengths of the factorizations of n in terms of the elements in ls .

Example

```
gap> LengthsOfFactorizationsIntegerWRTList(100,[11,13,15,19]);
[ 6, 8 ]
```

9.2.2 LengthsOfFactorizationsElementWRTNumericalSemigroup

▷ `LengthsOfFactorizationsElementWRTNumericalSemigroup(n , S)` (function)

S is a numerical semigroup and n a nonnegative integer. The output is the set of lengths of the factorizations of n in terms of the minimal generating set of S .

Example

```
gap> s:=NumericalSemigroup(101,113,196,272,278,286);
<Numerical semigroup with 6 generators>
gap> LengthsOfFactorizationsElementWRTNumericalSemigroup(1100,s);
[ 4, 6, 8, 9 ]
```

9.2.3 ElasticityOfFactorizationsElementWRTNumericalSemigroup

▷ `ElasticityOfFactorizationsElementWRTNumericalSemigroup(n , S)` (function)

S is a numerical semigroup and n a positive integer. The output is the maximum length divided by the minimum length of the factorizations of n in terms of the minimal generating set of S .

Example

```
gap> s:=NumericalSemigroup(101,113,196,272,278,286);
<Numerical semigroup with 6 generators>
gap> ElasticityOfFactorizationsElementWRTNumericalSemigroup(1100,s);
9/4
```

9.2.4 ElasticityOfNumericalSemigroup

▷ ElasticityOfNumericalSemigroup(S) (function)

S is a numerical semigroup. The output is the elasticity of S .

Example

```
gap> s:=NumericalSemigroup(101,113,196,272,278,286);
<Numerical semigroup with 6 generators>
gap> ElasticityOfNumericalSemigroup(s);
286/101
```

9.2.5 DeltaSetOfSetOfIntegers

▷ DeltaSetOfSetOfIntegers(ls) (function)

ls is list of integers. The output is the Delta set of the elements in ls , that is, the set of differences of consecutive elements in the list.

Example

```
gap> LengthsOfFactorizationsIntegerWRTList(100,[11,13,15,19]);
[ 6, 8 ]
gap> DeltaSetOfSetOfIntegers(last);
[ 2 ]
```

9.2.6 DeltaSetOfFactorizationsElementWRTNumericalSemigroup

▷ DeltaSetOfFactorizationsElementWRTNumericalSemigroup(n , S) (function)

S is a numerical semigroup and n a nonnegative integer. The output is the Delta set of the factorizations of n in terms of the minimal generating set of S .

Example

```
gap> s:=NumericalSemigroup(101,113,196,272,278,286);
<Numerical semigroup with 6 generators>
gap> DeltaSetOfFactorizationsElementWRTNumericalSemigroup(1100,s);
[ 1, 2 ]
```

9.2.7 MaximumDegreeOfElementWRTNumericalSemigroup

▷ MaximumDegreeOfElementWRTNumericalSemigroup(n , S) (function)

S is a numerical semigroup and n a nonnegative integer. The output is the maximum length of the factorizations of n in terms of the minimal generating set of S .

Example

```
gap> s:=NumericalSemigroup(101,113,196,272,278,286);
<Numerical semigroup with 6 generators>
gap> MaximumDegreeOfElementWRTNumericalSemigroup(1100,s);
9
```

9.2.8 MaximalDenumerantOfElementInNumericalSemigroup

▷ `MaximalDenumerantOfElementInNumericalSemigroup(n , S)` (function)

S is a numerical semigroup and n a positive integer. The output is the number of factorizations of n in terms of the minimal generating set of S with maximal length.

Example

```
gap> s:=NumericalSemigroup(101,113,196,272,278,286);;
gap> MaximalDenumerantOfElementInNumericalSemigroup(1100,s);
1
gap> MaximalDenumerantOfElementInNumericalSemigroup(1311,s);
2
```

9.2.9 MaximalDenumerantOfSetOfFactorizations

▷ `MaximalDenumerantOfSetOfFactorizations(ls)` (function)

ls is list of factorizations (a list of lists of nonnegative integers with the same length). The output is number of elements in ls with maximal length.

Example

```
gap> FactorizationsIntegerWRTList(100,[11,13,15,19]);
[ [ 2, 6, 0, 0 ], [ 3, 4, 1, 0 ], [ 4, 2, 2, 0 ], [ 5, 0, 3, 0 ], [ 5, 2, 0, 1 ],
  [ 6, 0, 1, 1 ], [ 0, 1, 2, 3 ], [ 1, 1, 0, 4 ] ]
gap> MaximalDenumerantOfSetOfFactorizations(last);
6
```

9.2.10 MaximalDenumerantOfNumericalSemigroup

▷ `MaximalDenumerantOfNumericalSemigroup(S)` (function)

S is a numerical semigroup. The output is the maximal denumerant of S , that is, the maximum of the maximal denumerant of the elements in S (see [BH13]).

Example

```
gap> s:=NumericalSemigroup(101,113,196,272,278,286);;
gap> MaximalDenumerantOfNumericalSemigroup(s);
4
```

9.2.11 AdjustmentOfNumericalSemigroup

▷ `AdjustmentOfNumericalSemigroup(S)` (function)

S is a numerical semigroup. The output is the adjustment of S as defined in [BH13].

Example

```
gap> s:=NumericalSemigroup(101,113,196,272,278,286);;
gap> AdjustmentOfNumericalSemigroup(s);
[ 0, 12, 24, 36, 48, 60, 72, 84, 95, 96, 107, 108, 119, 120, 131, 132, 143,
  144, 155, 156, 167, 168, 171, 177, 179, 180, 183, 185, 189, 190, 191, 192,
  195, 197, 201, 203, 204, 207, 209, 213, 215, 216, 219, 221, 225, 227, 228,
  231, 233, 237, 239, 240, 243, 245, 249, 251, 252, 255, 257, 261, 263, 264,
  266, 267, 269, 273, 275, 276, 279, 280, 281, 285, 287, 288, 292, 293, 299,
```

```

300, 304, 305, 311, 312, 316, 317, 323, 324, 328, 329, 335, 336, 340, 341,
342, 347, 348, 352, 353, 354, 356, 359, 360, 361, 362, 364, 365, 366, 368,
370, 371, 372, 374, 376, 377, 378, 380, 382, 383, 384, 388, 389, 390, 394,
395, 396, 400, 401, 402, 406, 407, 408, 412, 413, 414, 418, 419, 420, 424,
425, 426, 430, 431, 432, 436, 437, 438, 442, 444, 448, 450, 451, 454, 456,
460, 465, 466, 472, 477, 478, 484, 489, 490, 496, 501, 502, 508, 513, 514,
519, 520, 525, 526, 527, 531, 532, 533, 537, 539, 543, 545, 549, 551, 555,
561, 567, 573, 579, 585, 591, 597, 603, 609, 615, 621, 622, 627, 698, 704,
710, 716, 722 ]

```

9.2.12 IsAdditiveNumericalSemigroup

▷ IsAdditiveNumericalSemigroup(S) (function)

S is a numerical semigroup. Detects if S is additive, that is, $\text{ord}(m+x) = \text{ord}(x) + 1$ for all x in S , where m is the multiplicity of S and ord stands for MaximumDegreeOfElementWRTNumericalSemigroup. For these semigroups $gr_m(K[[S]])$ is Cohen-Macaulay (see [BH13]).

Example

```

gap> l:=IrreducibleNumericalSemigroupsWithFrobeniusNumber(31);;
gap> Length(l);
109
gap> Length(Filtered(l,IsAdditiveNumericalSemigroup));
20

```

9.2.13 IsSuperSymmetricNumericalSemigroup

▷ IsSuperSymmetricNumericalSemigroup(S) (function)

S is a numerical semigroup. Detects if S is supersymmetric, that is, it is symmetric, additive and whenever $w+w' = f+m$ (with m the multiplicity and f the Frobenius number) we have $\text{ord}(w+w') = \text{ord}(w) + \text{ord}(w')$, where ord stands for MaximumDegreeOfElementWRTNumericalSemigroup.

Example

```

gap> l:=IrreducibleNumericalSemigroupsWithFrobeniusNumber(31);;
gap> Length(l);
109
gap> Length(Filtered(l,IsSuperSymmetricNumericalSemigroup));
7

```

9.3 Invariants based on distances

9.3.1 CatenaryDegreeOfSetOfFactorizations

▷ CatenaryDegreeOfSetOfFactorizations(ls) (function)

ls is a set of factorizations (a list of lists of nonnegative integers with the same length). The output is the catenary degree of this set of factorizations.

Example

```

gap> FactorizationsIntegerWRTList(100,[11,13,15,19]);
[ [ 2, 6, 0, 0 ], [ 3, 4, 1, 0 ], [ 4, 2, 2, 0 ], [ 5, 0, 3, 0 ],

```

```
[ 5, 2, 0, 1 ], [ 6, 0, 1, 1 ], [ 0, 1, 2, 3 ], [ 1, 1, 0, 4 ] ]
gap> CatenaryDegreeOfSetOfFactorizations(last);
5
```

9.3.2 AdjacentCatenaryDegreeOfSetOfFactorizations

▷ AdjacentCatenaryDegreeOfSetOfFactorizations(*ls*) (function)

ls is a set of factorizations. The output is the adjacent catenary degree of this set of factorizations, that is, the supremum of the distance between to sets of factorizations with adjacent lengths. More precisely, if l_1, \dots, l_t are the lengths of the factorizations of the elements in *ls*, and Z_{l_i} is the set of factorizations in *ls* with length l_i , then the adjacent catenary degree is the maximum of the distances $d(Z_{l_i}, Z_{l_{i+1}})$.

Example

```
gap> FactorizationsIntegerWRTList(100, [11,13,15,19]);
[ [ 2, 6, 0, 0 ], [ 3, 4, 1, 0 ], [ 4, 2, 2, 0 ], [ 5, 0, 3, 0 ], [ 5, 2, 0, 1 ],
  [ 6, 0, 1, 1 ], [ 0, 1, 2, 3 ], [ 1, 1, 0, 4 ] ]
gap> AdjacentCatenaryDegreeOfSetOfFactorizations(last);
5
```

9.3.3 EqualCatenaryDegreeOfSetOfFactorizations

▷ EqualCatenaryDegreeOfSetOfFactorizations(*ls*) (function)

ls is a set of factorizations. The same as CatenaryDegreeOfSetOfFactorizations, but now the factorizations joined by the chain must have the same length, and the elements in the chain also. Equivalently, if l_1, \dots, l_t are the lengths of the factorizations of the elements in *ls*, and Z_{l_i} is the set of factorizations in *ls* with length l_i , then the equal catenary degree is the maximum of the CatenaryDegreeOfSetOfFactorizations of $d(Z_{l_i}, Z_{l_{i+1}})$.

Example

```
gap> FactorizationsIntegerWRTList(100, [11,13,15,19]);
[ [ 2, 6, 0, 0 ], [ 3, 4, 1, 0 ], [ 4, 2, 2, 0 ], [ 5, 0, 3, 0 ], [ 5, 2, 0, 1 ],
  [ 6, 0, 1, 1 ], [ 0, 1, 2, 3 ], [ 1, 1, 0, 4 ] ]
gap> EqualCatenaryDegreeOfSetOfFactorizations(last);
2
```

9.3.4 MonotoneCatenaryDegreeOfSetOfFactorizations

▷ MonotoneCatenaryDegreeOfSetOfFactorizations(*ls*) (function)

ls is a set of factorizations. The same as CatenaryDegreeOfSetOfFactorizations, but now the factorizations are joined by a chain with nondecreasing lengths. Equivalently, it is the maximum of the AdjacentCatenaryDegreeOfSetOfFactorizations and the EqualCatenaryDegreeOfSetOfFactorizations.

Example

```
gap> FactorizationsIntegerWRTList(100, [11,13,15,19]);
[ [ 2, 6, 0, 0 ], [ 3, 4, 1, 0 ], [ 4, 2, 2, 0 ], [ 5, 0, 3, 0 ], [ 5, 2, 0, 1 ],
  [ 6, 0, 1, 1 ], [ 0, 1, 2, 3 ], [ 1, 1, 0, 4 ] ]
```

```
gap> MonotoneCatenaryDegreeOfSetOfFactorizations(last);
5
```

9.3.5 CatenaryDegreeOfElementInNumericalSemigroup

▷ `CatenaryDegreeOfElementInNumericalSemigroup(n , S)` (function)

n is a nonnegative integer and S is a numerical semigroup. The output is the catenary degree of n relative to S .

Example

```
gap> CatenaryDegreeOfElementInNumericalSemigroup(157, NumericalSemigroup(13, 18));
0
gap> CatenaryDegreeOfElementInNumericalSemigroup(1157, NumericalSemigroup(13, 18));
18
```

9.3.6 TameDegreeOfSetOfFactorizations

▷ `TameDegreeOfSetOfFactorizations(ls)` (function)

ls is a set of factorizations (a list of lists of nonnegative integers with the same length). The output is the tame degree of this set of factorizations.

Example

```
gap> FactorizationsIntegerWRTList(100, [11, 13, 15, 19]);
[ [ 2, 6, 0, 0 ], [ 3, 4, 1, 0 ], [ 4, 2, 2, 0 ], [ 5, 0, 3, 0 ],
  [ 5, 2, 0, 1 ], [ 6, 0, 1, 1 ], [ 0, 1, 2, 3 ], [ 1, 1, 0, 4 ] ]
gap> TameDegreeOfSetOfFactorizations(last);
4
```

9.3.7 CatenaryDegreeOfNumericalSemigroup

▷ `CatenaryDegreeOfNumericalSemigroup(S)` (function)

S is a numerical semigroup. The output is the catenary degree of S .

Example

```
gap> s:=NumericalSemigroup(101, 113, 196, 272, 278, 286);
<Numerical semigroup with 6 generators>
gap> CatenaryDegreeOfNumericalSemigroup(s);
8
```

9.3.8 EqualPrimitiveElementsOfNumericalSemigroup

▷ `EqualPrimitiveElementsOfNumericalSemigroup(S)` (function)

S is a numerical semigroup.

The output is the set of elements s in S such that there exists a minimal solution to $msg \cdot x - msg \cdot y = 0$, such that x, y are factorizations with the same length of s , and msg is the minimal generating system of S . These elements are used to compute the equal catenary degree of S .

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> BettiElementsOfNumericalSemigroup(s);
[ 10, 12, 14 ]
```

9.3.9 EqualCatenaryDegreeOfNumericalSemigroup

▷ EqualCatenaryDegreeOfNumericalSemigroup(S) (function)

S is a numerical semigroup. The output is the equal catenary degree of S .

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> EqualPrimitiveElementsOfNumericalSemigroup(s);
[ 3, 5, 7, 10 ]
```

9.3.10 MonotonePrimitiveElementsOfNumericalSemigroup

▷ MonotonePrimitiveElementsOfNumericalSemigroup(S) (function)

S is a numerical semigroup.

The output is the set of elements s in S such that there exists a minimal solution to $msg \cdot x - msg \cdot y = 0$, such that x, y are factorizations of s , with $|x| \leq |y|$; msg stands the minimal generating system of S . These elements are used to compute the monotone catenary degree of S .

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> MonotonePrimitiveElementsOfNumericalSemigroup(s);
[ 3, 5, 7, 10, 12, 14, 15, 21, 28, 35 ]
```

9.3.11 MonotoneCatenaryDegreeOfNumericalSemigroup

▷ MonotoneCatenaryDegreeOfNumericalSemigroup(S) (function)

S is a numerical semigroup. The output is the monotone catenary degree of S .

Example

```
gap> s:=NumericalSemigroup(10,23,31,44);;
gap> CatenaryDegreeOfNumericalSemigroup(s);
9
gap> MonotoneCatenaryDegreeOfNumericalSemigroup(s);
21
```

9.3.12 TameDegreeOfNumericalSemigroup

▷ TameDegreeOfNumericalSemigroup(S) (function)

S is a numerical semigroup. The output is the tame degree of S .

Example

```
gap> s:=NumericalSemigroup(101,113,196,272,278,286);
<Numerical semigroup with 6 generators>
gap> TameDegreeOfNumericalSemigroup(s);
14
```

9.3.13 TameDegreeOfElementInNumericalSemigroup

▷ TameDegreeOfElementInNumericalSemigroup(n , S) (function)

n is an element of the numerical semigroup S . The output is the tame degree of n in S .

Example

```
gap> s:=NumericalSemigroup(10,11,13);
<Numerical semigroup with 3 generators>
gap> TameDegreeOfElementInNumericalSemigroup(100,s);
5
```

9.4 Primality

9.4.1 OmegaPrimalityOfElementInNumericalSemigroup

▷ OmegaPrimalityOfElementInNumericalSemigroup(n , S) (function)

n is an element of the numerical semigroup S . The output is the ω -primality of n in S as explained in [BGS11]. The current implementation is due to Chris O’Neill based on a work in progress with Pelayo and Thomas.

Example

```
gap> s:=NumericalSemigroup(10,11,13);
<Numerical semigroup with 3 generators>
gap> OmegaPrimalityOfElementInNumericalSemigroup(100,s);
13
```

9.4.2 OmegaPrimalityOfNumericalSemigroup

▷ OmegaPrimalityOfNumericalSemigroup(n , S) (function)

S is a numerical semigroup. The output is the maximum of the ω -primalitys of the minimal generators of S .

Example

```
gap> s:=NumericalSemigroup(10,11,13);
<Numerical semigroup with 3 generators>
gap> OmegaPrimalityOfNumericalSemigroup(s);
5
```

9.5 Homogenization of Numerical Semigroups

Let S be a numerical semigroup minimally generated by $\{m_1, \dots, m_n\}$. The homogenization of S , S^{hom} is the semigroup generated by $\{(1,0), (1,m_1), \dots, (1,m_n)\}$. The catenary degree of S^{hom} coincides

with the homogeneous catenary degree of S , and it is between the catenary and the monotone catenary degree of S . The advantage of this catenary degree is that is less costly to compute than the monotone catenary degree, and has some nice interpretations ([GSOSRN13]). This section contains the auxiliary functions needed to compute the homogeneous catenary degree.

9.5.1 BelongsToHomogenizationOfNumericalSemigroup

▷ `BelongsToHomogenizationOfNumericalSemigroup(n , S)` (function)

S is a numerical semigroup and n a list with two entries (a pair). The output is true if the n belongs to the homogenization of S .

Example

```
gap> s:=NumericalSemigroup(10,11,13);;
gap> BelongsToHomogenizationOfNumericalSemigroup([10,23],s);
true
gap> BelongsToHomogenizationOfNumericalSemigroup([1,23],s);
false
```

9.5.2 FactorizationsInHomogenizationOfNumericalSemigroup

▷ `FactorizationsInHomogenizationOfNumericalSemigroup(n , S)` (function)

S is a numerical semigroup and n a list with two entries (a pair). The output is the set of factorizations n in terms of the minimal generating system of the homogenization of S .

Example

```
gap> s:=NumericalSemigroup(10,11,13);;
gap> FactorizationsInHomogenizationOfNumericalSemigroup([20,230],s);
[[ 0, 0, 15, 5 ], [ 0, 2, 12, 6 ], [ 0, 4, 9, 7 ],
 [ 0, 6, 6, 8 ], [ 0, 8, 3, 9 ], [ 0, 10, 0, 10 ],
 [ 1, 1, 7, 11 ], [ 1, 3, 4, 12 ], [ 1, 5, 1, 13 ],
 [ 2, 0, 2, 16 ] ]
gap> FactorizationsElementWRTNumericalSemigroup(230,s);
[[ 23, 0, 0 ], [ 12, 10, 0 ], [ 1, 20, 0 ], [ 14, 7, 1 ],
 [ 3, 17, 1 ], [ 16, 4, 2 ], [ 5, 14, 2 ], [ 18, 1, 3 ],
 [ 7, 11, 3 ], [ 9, 8, 4 ], [ 11, 5, 5 ], [ 0, 15, 5 ],
 [ 13, 2, 6 ], [ 2, 12, 6 ], [ 4, 9, 7 ], [ 6, 6, 8 ],
 [ 8, 3, 9 ], [ 10, 0, 10 ], [ 1, 7, 11 ], [ 3, 4, 12 ],
 [ 5, 1, 13 ], [ 0, 2, 16 ] ]
```

9.5.3 HomogeneousBettiElementsOfNumericalSemigroup

▷ `HomogeneousBettiElementsOfNumericalSemigroup(n , S)` (function)

S is a numerical semigroup. The output is the set of Betti elements of the homogenization of S .

Example

```
gap> s:=NumericalSemigroup(10,17,19);;
gap> BettiElementsOfNumericalSemigroup(s);
[ 57, 68, 70 ]
gap> HomogeneousBettiElementsOfNumericalSemigroup(s);
[[ 5, 57 ], [ 5, 68 ], [ 6, 95 ], [ 7, 70 ], [ 9, 153 ] ]
```

9.5.4 HomogeneousCatenaryDegreeOfNumericalSemigroup

▷ HomogeneousCatenaryDegreeOfNumericalSemigroup(S) (function)

S is a numerical semigroup. The output is the homogeneous catenary degree of S . Observe that for a single element in the homogenization of S , its catenary degree can be computed with CatenaryDegreeOfSetOfFactorizations and FactorizationsInHomogenizationOfNumericalSemigroup.

Example

```
gap> s:=NumericalSemigroup(10,17,19);;
gap> CatenaryDegreeOfNumericalSemigroup(s);
7
gap> HomogeneousCatenaryDegreeOfNumericalSemigroup(s);
9
```

9.6 Divisors, posets

Given a numerical semigroup S and two integers a, b , we write $a \leq_S b$ if $b - a \in S$. We also say that a divides b (with respect to S). The semigroup S with this binary relation is a poset.

9.6.1 MoebiusFunctionAssociatedToNumericalSemigroup

▷ MoebiusFunctionAssociatedToNumericalSemigroup(S, n) (function)

S is a numerical semigroup and n is an integer. As (S, \leq_S) is a poset, we can define the Möbius function associated to it as in [CRA13]. The output is the value of the Möbius function in the integer n , that is, the alternate sum of the number of chains from 0 to n .

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> MoebiusFunctionAssociatedToNumericalSemigroup(s,10);
2
gap> MoebiusFunctionAssociatedToNumericalSemigroup(s,34);
25
```

Chapter 10

Polynomials and numerical semigroups

10.1 Generating functions or Hilbert series

Let S be a numerical semigroup. The Hilbert series or generating function associated to S is $H_S(x) = \sum_{s \in S} x^s$ (actually it is the Hilbert function of the ring $K[S]$ with K a field). See for instance [Mor14].

10.1.1 NumericalSemigroupPolynomial

▷ `NumericalSemigroupPolynomial(s, x)` (function)

s is a numerical semigroups and x a variable (or a value to evaluate in). The output is the polynomial $1 + (x - 1) \sum_{s \in \mathbb{N} \setminus S} x^s$, which equals $(1 - x)H_S(x)$.

Example

```
gap> x:=X(Rationals,"x");;
gap> s:=NumericalSemigroup(5,7,9);;
gap> NumericalSemigroupPolynomial(s,x);
x^14-x^13+x^12-x^11+x^9-x^8+x^7-x^6+x^5-x+1
```

10.1.2 IsNumericalSemigroupPolynomial

▷ `IsNumericalSemigroupPolynomial(f)` (function)

f is polynomial in one variable. The output is true if there exists a numerical semigroup S such that f equals $(1 - x)H_S(x)$, that is, the polynomial associated to S (false otherwise).

Example

```
gap> x:=X(Rationals,"x");;
gap> s:=NumericalSemigroup(5,6,7,8);;
gap> f:=NumericalSemigroupPolynomial(s,x);
x^10-x^9+x^5-x+1
gap> IsNumericalSemigroupPolynomial(f);
true
```

10.1.3 NumericalSemigroupFromNumericalSemigroupPolynomial

▷ `NumericalSemigroupFromNumericalSemigroupPolynomial(f)` (function)

f is a polynomial associated to a numerical semigroup (otherwise yields error). The output is the numerical semigroup S such that f equals $(1-x)H_S(x)$.

Example

```
gap> x:=X(Rationals,"x");;
gap> s:=NumericalSemigroup(5,6,7,8);;
gap> f:=NumericalSemigroupPolynomial(s,x);
x^10-x^9+x^5-x+1
gap> NumericalSemigroupFromNumericalSemigroupPolynomial(f)=s;
true
```

10.1.4 HilbertSeriesOfNumericalSemigroup

▷ `HilbertSeriesOfNumericalSemigroup(s, x)` (function)

s is a numerical semigroup and x a variable (or a value to evaluate in). The output is the series $\sum_{s \in S} x^s$. The series is given as a rational function.

Example

```
gap> x:=X(Rationals,"x");;
gap> s:=NumericalSemigroup(5,7,9);;
gap> HilbertSeriesOfNumericalSemigroup(s,x);
(x^14-x^13+x^12-x^11+x^9-x^8+x^7-x^6+x^5-x+1)/(-x+1)
```

10.1.5 GraeffePolynomial

▷ `GraeffePolynomial(p)` (function)

p is a polynomial. Computes the Graeffe polynomial of p . Needed to test if p is a cyclotomic polynomial (see [BD89]).

Example

```
gap> x:=X(Rationals,"x");;
gap> GraeffePolynomial(x^2-1);
x^2-2*x+1
```

10.1.6 IsCyclotomicPolynomial

▷ `IsCyclotomicPolynomial(p)` (function)

p is a polynomial. Detects if p is a cyclotomic polynomial using the procedure given in [BD89].

Example

```
gap> CyclotomicPolynomial(Rationals,3);
x^2+x+1
gap> IsCyclotomicPolynomial(last);
true
```

10.1.7 IsKroneckerPolynomial

▷ `IsKroneckerPolynomial(p)` (function)

p is a polynomial. Detects if p is a Kronecker polynomial, that is, a monic polynomial with integer coefficients having all its roots in the unit circumference, or equivalently, a product of cyclotomic polynomials.

Example

```
gap> x:=X(Rationals,"x");;
gap> s:=NumericalSemigroup(3,5,7);;
gap> t:=NumericalSemigroup(4,6,9);;
gap> p:=NumericalSemigroupPolynomial(s,x);
x^5-x^4+x^3-x+1
gap> q:=NumericalSemigroupPolynomial(t,x);
x^12-x^11+x^8-x^7+x^6-x^5+x^4-x+1
gap> IsKroneckerPolynomial(p);
false
gap> IsKroneckerPolynomial(q);
true
```

10.1.8 IsCyclotomicNumericalSemigroup

▷ IsCyclotomicNumericalSemigroup(s) (function)

s is a numerical semigroup. Detects if the polynomial associated to s is a Kronecker polynomial.

Example

```
gap> l:=CompleteIntersectionNumericalSemigroupsWithFrobeniusNumber(21);;
gap> ForAll(l, IsCyclotomicNumericalSemigroup);
true
```

10.1.9 IsSelfReciprocalUnivariatePolynomial

▷ IsSelfReciprocalUnivariatePolynomial(p) (function)

p is a univariate polynomial. Detects if p is selfreciprocal. A numerical semigroup is symmetric if and only if it is selfreciprocal, [Mor14].

Example

```
gap> l:=IrreducibleNumericalSemigroupsWithFrobeniusNumber(13);;
gap> x:=X(Rationals,"x");;
gap> ForAll(l, s->
> IsSelfReciprocalUnivariatePolynomial(NumericalSemigroupPolynomial(s,x)));
true
```

10.2 Semigroup of values of algebraic curves

Let $f(x, y) \in \mathbb{K}[x, y]$, with \mathbb{K} an algebraically closed field of characteristic zero. Let $f(x, y) = y^n + a_1(x)y^{n-1} + \dots + a_n(x)$ be a nonzero polynomial of $\mathbb{K}[x][y]$. After possibly a change of variables, we may assume that, that $\deg_x(a_i(x)) \leq i - 1$ for all $i \in \{1, \dots, n\}$. For $g \in \mathbb{K}[x, y]$ that is not a multiple of f , define $\text{int}(f, g) = \dim_{\mathbb{K}} \frac{\mathbb{K}[x, y]}{(f, g)}$. If f has one place at infinity, then the set $\{\text{int}(f, g) \mid g \in \mathbb{K}[x, y] \setminus (f)\}$ is a free numerical semigroup (and thus a complete intersection).

10.2.1 SemigroupOfValuesOfPlaneCurveWithSinglePlaceAtInfinity

▷ `SemigroupOfValuesOfPlaneCurveWithSinglePlaceAtInfinity(f)` (function)

f is a polynomial in the variables $X(\text{Rationals},1)$ and $X(\text{Rationals},2)$. Computes the semigroup $\{\text{int}(f,g) \mid g \in \mathbb{K}[x,y] \setminus (f)\}$, where $\text{int}(f,g) = \dim_{\mathbb{K}}(\mathbb{K}[x,y]/(f,g))$. The algorithm checks if f has one place at infinity. If the extra argument "all" is given, then the output is the δ -sequence and approximate roots of f . The method is explained in [AGS14].

Example

```
gap> x:=X(Rationals,"x");; y:=X(Rationals,"y");;
gap> f:=((y^3-x^2)^2-x*y^2)^4-(y^3-x^2);;
gap> SemigroupOfValuesOfPlaneCurveWithSinglePlaceAtInfinity(f,"all");
[ [ 24, 16, 28, 7 ], [ y, y^3-x^2, y^6-2*x^2*y^3+x^4-x*y^2 ] ]
```

10.2.2 IsDeltaSequence

▷ `IsDeltaSequence(l)` (function)

l is a list of positive integers. Assume that l equals a_0, a_1, \dots, a_h . Then l is a δ -sequence if $\gcd(a_0, \dots, a_h) = 1$, $\langle a_0, \dots, a_s \rangle$ is free, $a_k D_k > a_{k+1} D_{k+1}$ and $a_0 > a_1 > D_2 > D_3 > \dots > D_{h+1}$, where $D_1 = a_0$, $D_k = \gcd(D_{k-1}, a_{k-1})$.

Every δ -sequence generates a numerical semigroup that is the semigroup of values of a plane curve with one place at infinity.

Example

```
gap> IsDeltaSequence([24,16,28,7]);
true
```

10.2.3 DeltaSequencesWithFrobeniusNumber

▷ `DeltaSequencesWithFrobeniusNumber(f)` (function)

f is a positive integer. Computes the set of all δ -sequences generating numerical semigroups with Frobenius number f .

Example

```
gap> DeltaSequencesWithFrobeniusNumber(21);
[ [ 8, 6, 11 ], [ 10, 4, 15 ], [ 12, 8, 6, 11 ], [ 14, 4, 11 ],
  [ 15, 10, 4 ], [ 23, 2 ] ]
```

10.2.4 CurveAssociatedToDeltaSequence

▷ `CurveAssociatedToDeltaSequence(l)` (function)

l is a δ -sequence. Computes a curve in the variables $X(\text{Rationals},1)$ and $X(\text{Rationals},2)$ whose semigroup of values is generated by the l .

Example

```
gap> CurveAssociatedToDeltaSequence([24,16,28,7]);
x_2^24-8*x_2^21+28*x_2^18-56*x_2^15-4*x_2^20+70*x_2^12+24*x_2^3-
3*x_2^17-56*x_2^10*x_2^9-60*x_2^5*x_2^14+28*x_2^12*x_2^6+80*x_2^7*x_2^11+6*x_2^2*x_2^16-
8*x_2^14*x_2^3-60*x_2^9*x_2^8-24*x_2^4*x_2^13+x_2^16+24*x_2^11*x_2^5+36*x_2^6*x_2^10-4*x_2^1
```



```

3*x_2^2-24*x^8*x_2^7-4*x^3*x_2^12+6*x^10*x_2^4+8*x^5*x_2^9-4*x^7*x_2^6+x^4*x_2\
^8-x_2^3*x^2
gap> SemigroupOfValuesOfPlaneCurveWithSinglePlaceAtInfinity(last,"all");
[ [ 24, 16, 28, 7 ], [ x_2, x_2^3-x_1^2, x_2^6-2*x_1^2*x_2^3+x_1^4-x_1*x_2^2 ] ]

```

10.2.5 SemigroupOfValuesOfPlaneCurve

▷ `SemigroupOfValuesOfPlaneCurve(f)` (function)

f is a polynomial in the variables $X(\text{Rationals},1)$ and $X(\text{Rationals},2)$. The singular package is mandatory. Either by loading it prior to numerical semigroups or by using `NumSgpsUseSingular()`. If f is irreducible, computes the semigroup $\{\text{int}(f,g) \mid g \in \mathbb{K}[x,y] \setminus (f)\}$, where $\text{int}(f,g) = \dim_{\mathbb{K}}(\mathbb{K}[[x,y]]/(f,g))$. If it has two components, the output is the value semigroup in two variables, and thus a good semigroup. If there are more components, then the output is that of *semigroup* in the alexpoly singular library.

Example

```

gap> x:=X(Rationals,"x");; y:=X(Rationals,"y");;
gap> f:= y^4-2*x^3*y^2-4*x^5*y+x^6-x^7;
      -x^7+x^6-4*x^5*y-2*x^3*y^2+y^4
gap> SemigroupOfValuesOfPlaneCurve(f);
<Numerical semigroup with 3 generators>
gap> MinimalGenerators(last);
[ 4, 6, 13 ]
gap> f:=(y^4-2*x^3*y^2-4*x^5*y+x^6-x^7)*(y^2-x^3);;
gap> SemigroupOfValuesOfPlaneCurve(f);
<Good semigroup>
gap> MinimalGenerators(last);
[ [ 4, 2 ], [ 6, 3 ], [ 13, 15 ], [ 29, 13 ] ]

```

10.2.6 SemigroupOfValuesOfCurve_Local

▷ `SemigroupOfValuesOfCurve_Local(arg)` (function)

The function admits one or two parameters. In any case, the first is a list of polynomials *pol*s. And the second can be the string "*basis*" or an integer *val*.

If only one argument is given, the output is the semigroup of all possible orders of $K[[\text{pol}s]]$ provided that $K[[x]]/K[[\text{pol}s]]$ has finite length. If the second argument "*basis*" is given, then the output is a (reduced) basis of the algebra $K[[\text{pol}s]]$ such that the orders of the basis elements generate minimally the semigroup of orders of $K[[\text{pol}s]]$. If an integer *val* is the second argument, then the output is a polynomial in $K[[\text{pol}s]]$ with order *val* (fail if there is no such polynomial, that is, *val* is not in the semigroup of values).

The method is explained in [AGSM14].

Example

```

gap> x:=Indeterminate(Rationals,"x");;
gap> SemigroupOfValuesOfCurve_Local([x^4,x^6+x^7,x^13]);
<Numerical semigroup with 4 generators>
gap> MinimalGeneratingSystem(last);
[ 4, 6, 13, 15 ]
gap> SemigroupOfValuesOfCurve_Local([x^4,x^6+x^7,x^13], "basis");

```

```
[ x^4, x^7+x^6, x^13, x^15 ]
gap> SemigroupOfValuesOfCurve_Local([x^4,x^6+x^7,x^13], 20);
x^20
```

10.2.7 SemigroupOfValuesOfCurve_Global

▷ `SemigroupOfValuesOfCurve_Global(arg)` (function)

The function admits one or two parameters. In any case, the first is a list of polynomials *pols*. And the second can be the string *"basis"* or an integer *val*.

If only one argument is given, the output is the semigroup of all possible degrees of $K[pols]$ provided that $K[x]/K[pols]$ has finite length. If the second argument *"basis"* is given, then the output is a (reduced) basis of the algebra $K[pols]$ such that the degrees of the basis elements generate minimally the semigroup of degrees of $K[pols]$. If an integer *val* is the second argument, then the output is a polynomial in $K[pols]$ with degree *val* (fail if there is no such polynomial, that is, *val* is not in the semigroup of values).

The method is explained in [AGSM14].

Example

```
gap> x:=Indeterminate(Rationals,"x");;
gap> SemigroupOfValuesOfCurve_Global([x^4,x^6+x^7,x^13]);
<Numerical semigroup with 3 generators>
gap> MinimalGeneratingSystem(last);
[ 4, 7, 13 ]
gap> SemigroupOfValuesOfCurve_Global([x^4,x^6+x^7,x^13],"basis");
[ x^4, x^7+x^6, x^13 ]
gap> SemigroupOfValuesOfCurve_Global([x^4,x^6+x^7,x^13],12);
x^12
gap> SemigroupOfValuesOfCurve_Global([x^4,x^6+x^7,x^13],6);
fail
```

Chapter 11

Affine semigroups

11.1 Defining affine semigroups

An affine semigroup S is a finitely generated cancellative monoid that is reduced (no units other than 0) and is torsion-free ($as = bs$ implies $a = b$, with $a, b \in \mathbb{N}$ and $s \in S$). Up to isomorphisms any affine semigroup can be viewed as a finitely generated submonoid of \mathbb{N}^k for some positive integer k . Thus affine semigroups are a natural generalization of numerical semigroups. The most common way to give an affine semigroup is by any of its systems of generators. As for numerical semigroups, any affine semigroup admits a unique minimal system of generators. A system of generators can be represented as a list of lists of nonnegative integers; all lists in the list having the same length (a matrix actually). If G is a subgroup of \mathbb{Z}^k , then $S = G \cap \mathbb{N}^k$ is an affine semigroup (these semigroups are called full affine semigroups). As G can be represented by its defining equations (homogeneous and some of them possibly in congruences), we can represent S by the defining equations of G ; indeed S is just the set of nonnegative solutions of this system of equations. We can represent the equations as a list of lists of integers, all with the same length. Every list is a row of the matrix of coefficients of the system of equations. For the equations in congruences, if we arrange them so that they are the first ones in the list, we provide the corresponding moduli in a list. So for instance, the equations $x + y \equiv 0 \pmod{2}$, $x - 2y = 0$ will be represented as $[[1,1],[1,-2]]$ and the moduli $[2]$.

To create an affine semigroup in GAP the function `AffineSemigroup` is used.

11.1.1 AffineSemigroup

▷ `AffineSemigroup(Representation, List)` (function)

`Representation` may be "generators", "equations" or "inequalities" according to whether the semigroup is to be given by means of a system of generators, a system of homogeneous linear Diophantine equations or a system of homogeneous linear Diophantine inequalities.

When no string is given as first argument it is assumed that the numerical semigroup will be given by means of a set of generators.

Example

```
gap> AffineSemigroup([1,3],[7,2],[1,5]);  
<Affine semigroup in 2 dimensional space, with 3 generators>  
gap> a2 := AffineSemigroup("equations",[[[-2,1],[3]]]);  
<Affine semigroup>
```

11.1.2 GeneratorsOfAffineSemigroup

- ▷ `GeneratorsOfAffineSemigroup(S)` (function)
- ▷ `Generators(S)` (function)

S is an affine semigroup, the output is a system of generators.

Example

```
gap> a:=AffineSemigroup([[1,0],[0,1],[1,1]]);
<Affine semigroup in 2 dimensional space, with 3 generators>
gap> Generators(a);
[ [ 0, 1 ], [ 1, 0 ], [ 1, 1 ] ]
```

11.1.3 MinimalGeneratingSystem (for affine semigroup)

- ▷ `MinimalGeneratingSystem(S)` (function)
- ▷ `MinimalGenerators(S)` (function)

S is an affine semigroup, the output is its system of minimal generators.

Example

```
gap> a:=AffineSemigroup([[1,0],[0,1],[1,1]]);
<Affine semigroup in 2 dimensional space, with 3 generators>
gap> MinimalGenerators(a);
[ [ 0, 1 ], [ 1, 0 ] ]
```

11.1.4 AsAffineSemigroup

- ▷ `AsAffineSemigroup(S)` (function)

S is a numerical semigroup, the output is S regarded as an affine semigroup.

Example

```
gap> s:=NumericalSemigroup(1310,1411,1546,1601);
<Numerical semigroup with 4 generators>
gap> MinimalPresentationOfNumericalSemigroup(s);;time;
2960
gap> a:=AsAffineSemigroup(s);
<Affine semigroup in 1 dimensional space, with 4 generators>
gap> GeneratorsOfAffineSemigroup(a);
[ [ 1310 ], [ 1411 ], [ 1546 ], [ 1601 ] ]
gap> MinimalPresentationOfAffineSemigroup(a);;time;
237972
```

If we use the package `SingularInterface`, the speed up is considerable.

Example

```
gap> NumSgpsUseSingularInterface();
...
gap> MinimalPresentationOfAffineSemigroup(a);;time;
32
```

11.1.5 IsAffineSemigroup

- ▷ IsAffineSemigroup(AS) (attribute)
- ▷ IsAffineSemigroupByGenerators(AS) (attribute)
- ▷ IsAffineSemigroupByMinimalGenerators(AS) (attribute)
- ▷ IsAffineSemigroupByEquations(AS) (attribute)
- ▷ IsAffineSemigroupByInequalities(AS) (attribute)

AS is an affine semigroup and these attributes are available (their names should be self explanatory). They reflect what is currently known about the semigroup.

Example

```
gap> a1:=AffineSemigroup([[3,0],[2,1],[1,2],[0,3]]);
<Affine semigroup in 2 dimensional space, with 4 generators>
gap> IsAffineSemigroupByEquations(a1);
false
gap> IsAffineSemigroupByGenerators(a1);
true
```

11.1.6 BelongsToAffineSemigroup

- ▷ BelongsToAffineSemigroup(v, a) (function)

v is a list of nonnegative integers and a an affine semigroup. Returns true if the vector is in the semigroup, and false otherwise.

If the semigroup is full and its equations are known (either because the semigroup was defined by equations, or because the user has called IsFullAffineSemigroup(a) and the output was true), then membership is performed by evaluating v in the equations. The same holds for normal semigroups and its defining inequalities.

Example

```
gap> a:=AffineSemigroup([[2,0],[0,2],[1,1]]);
gap> BelongsToAffineSemigroup([5,5],a);
true
gap> BelongsToAffineSemigroup([1,2],a);
false
gap> [5,5] in a;
true
gap> [1,2] in a;
false
```

11.1.7 IsFullAffineSemigroup

- ▷ IsFullAffineSemigroup(S) (function)

s is an affine semigroup.

Returns true if the semigroup is full, false otherwise. The semigroup is full if whenever $a, b \in S$ and $b - a \in \mathbb{N}^k$, then $a - b \in S$, where k is the dimension of S .

If the semigroup is full, then its equations are stored in the semigroup for further use.

Example

```
gap> a:=AffineSemigroup("equations",[[[1,1,1],[0,0,2]],[2,2]]);
gap> IsFullAffineSemigroup(a);
true
```

11.1.8 HilbertBasisOfSystemOfHomogeneousEquations

▷ `HilbertBasisOfSystemOfHomogeneousEquations(ls, m)` (function)

ls is a list of lists of integers and *m* a list of integers. The elements of *ls* represent the rows of a matrix *A*. The output is a minimal generating system (Hilbert basis) of the set of nonnegative integer solutions of the system $Ax = 0$ where the *k* first equations are in the congruences modulo $m[i]$, with *k* the length of *m*.

If the package `NormalizInterface` has not been loaded, then Contejean-Devie algorithm is used [CD94] instead (if this is the case, congruences are treated as in [RGS98]).

Example

```
gap> HilbertBasisOfSystemOfHomogeneousEquations([[1,0,1],[0,1,-1]],[2]);
[[ 0, 2, 2 ], [ 1, 1, 1 ], [ 2, 0, 0 ]]
```

If *C* is a pointed cone (a cone in \mathbb{Q}^k not containing lines and $0 \in C$), then $S = C \cap \mathbb{N}^k$ is an affine semigroup (known as normal affine semigroup). So another way to give an affine semigroup is by a set of homogeneous inequalities, and we can represent these inequalities by its coefficients. If we put them in a matrix *S* can be defined as the set of nonnegative integer solutions to $Ax \geq 0$.

11.1.9 HilbertBasisOfSystemOfHomogeneousInequalities

▷ `HilbertBasisOfSystemOfHomogeneousInequalities(ls)` (function)

ls is a list of lists of integers. The elements of *ls* represent the rows of a matrix *A*. The output is a minimal generating system (Hilbert basis) of the set of nonnegative integer solutions to $Ax \geq 0$.

If the package `NormalizInterface` has not been loaded, then Contejean-Devie algorithm is used [CD94] instead (the use of slack variables is described in [RGSB02]).

Example

```
gap> HilbertBasisOfSystemOfHomogeneousInequalities([[2,-3],[0,1]]);
[[ 1, 0 ], [ 2, 1 ], [ 3, 2 ]]
```

11.1.10 EquationsOfGroupGeneratedBy

▷ `EquationsOfGroupGeneratedBy(M)` (function)

M is a matrix of integers. The output is a pair $[A, m]$ that represents the set of defining equations of the group spanned by the rows of *M*: $Ax = 0 \in \mathbb{Z}_{n_1} \times \cdots \times \mathbb{Z}_{n_t} \times \mathbb{Z}^k$, with $m = [n_1, \dots, n_t]$.

Example

```
gap> EquationsOfGroupGeneratedBy([[1,2,0],[2,-2,2]]);
[[ [ 0, 0, -1 ], [ -2, 1, 3 ] ], [ 2 ]]
```

11.1.11 BasisOfGroupGivenByEquations

▷ `BasisOfGroupGivenByEquations(A, m)` (function)

A is a matrix of integers and m is a list of positive integers. The output is a basis for the group with defining equations $Ax = 0 \in \mathbb{Z}_{n_1} \times \cdots \times \mathbb{Z}_{n_t} \times \mathbb{Z}^k$, with $m = [n_1, \dots, n_t]$.

Example

```
gap> BasisOfGroupGivenByEquations([[0,0,1],[2,-1,-3]],[2]);
[ [-1, -2, 0 ], [ -2, 2, -2 ] ]
```

11.2 Gluings of affine semigroups

Let S_1 and S_2 be two affine semigroups with the same dimension generated by A_1 and A_2 , respectively. We say that the affine semigroup S generated by the union of A_1 and A_2 is a gluing of S_1 and S_2 if $G(S_1) \cap G(S_2) = d\mathbb{Z}$ ($G(\cdot)$ stands for group spanned by) for some $d \in S_1 \cap S_2$.

The algorithm used is explained in [RGS99b].

11.2.1 GluingOfAffineSemigroups

▷ `GluingOfAffineSemigroups(a1, a2)` (function)

$a1$, $a2$ are affine semigroups. Determines if they can be glued, and if so, returns the gluing. Otherwise it returns fail.

Example

```
gap> a1:=AffineSemigroup([[2,0],[0,2]]);
<Affine semigroup in 2 dimensional space, with 2 generators>
gap> a2:=AffineSemigroup([[1,1]]);
<Affine semigroup in 2 dimensional space, with 1 generators>
gap> GluingOfAffineSemigroups(a1,a2);
<Affine semigroup in 2 dimensional space, with 3 generators>
gap> Generators(last);
[ [ 0, 2 ], [ 1, 1 ], [ 2, 0 ] ]
```

11.3 Presentations of affine semigroups

A minimal presentation of an affine semigroup is defined analogously as for numerical semigroups. The user might take into account that generators are stored in a set, and thus might be arranged in a different way to the initial input.

11.3.1 GeneratorsOfKernelCongruence

▷ `GeneratorsOfKernelCongruence(M)` (function)

M is matrix with nonnegative integer coefficients. The output is a system of generators of the congruence $\{(x,y) \mid xM = yM\}$.

The main difference with `MinimalPresentationOfAffineSemigroup` is that the matrix M can have repeated columns and these are not treated as a set.

11.3.2 MinimalPresentationOfAffineSemigroup

▷ `MinimalPresentationOfAffineSemigroup(a)` (function)

`a` is an affine semigroup. The output is a minimal presentation for `a`.

There are four methods implemented for this function, depending on the packages loaded. All of them use elimination, and Herzog's correspondence, computing the kernel of a ring homomorphism ([Her70]). The fastest procedure is achieved when `SingularInterface` is loaded, followed by `Singular`. The procedure that does not use external packages uses internal GAP Gröbner basis computations and thus it is slower. Also in this case, from the Gröbner basis, a minimal set of generating binomials must be refined, and for this `Rclasses` are used (if `NormalizInterface` is loaded, then the factorizations are faster). The `4ti2` implementation uses `4ti2` internal Gröbner bases and factorizations are done via `zsolve`.

Example

```
gap> a:=AffineSemigroup([2,0],[0,2],[1,1]);;
gap> MinimalPresentationOfAffineSemigroup(a);
[ [ [ 1, 0, 1 ], [ 0, 2, 0 ] ] ]
gap> GeneratorsOfAffineSemigroup(a);
[ [ 0, 2 ], [ 1, 1 ], [ 2, 0 ] ]
```

11.3.3 BettiElementsOfAffineSemigroup

▷ `BettiElementsOfAffineSemigroup(a)` (function)

`a` is an affine semigroup. The output is the set of Betti elements of `a` (defined as for numerical semigroups).

This function relies on the computation of a minimal presentation.

Example

```
gap> a:=AffineSemigroup([2,0],[0,2],[1,1]);;
gap> BettiElementsOfAffineSemigroup(a);
[ [ 2, 2 ] ]
```

11.3.4 ShadedSetOfElementInAffineSemigroup

▷ `ShadedSetOfElementInAffineSemigroup(v, a)` (function)

`a` is an affine semigroup and `v` is an element in `a`. This is a translation to affine semigroups of `ShadedSetOfElementInNumericalSemigroup` (4.1.5).

11.3.5 IsGenericAffineSemigroup

▷ `IsGenericAffineSemigroup(a)` (function)

`a` is an affine semigroup.

The same as `IsGenericNumericalSemigroup` (4.2.2) but for affine semigroups.

11.3.6 IsUniquelyPresentedAffineSemigroup

▷ IsUniquelyPresentedAffineSemigroup(a) (function)

a is an affine semigroup.

The same as IsUniquelyPresentedNumericalSemigroup (4.2.1) but for affine semigroups.

11.3.7 PrimitiveElementsOfAffineSemigroup

▷ PrimitiveElementsOfAffineSemigroup(a) (function)

a is an affine semigroup. The output is the set of primitive elements of a (defined as for numerical semigroups).

This function has three implementations (methods), one using Graver basis via the Lawrence lifting of a and the other (much faster) using NormalizInterface. Also a 4ti2 version using its Graver basis computation is provided.

Example

```
gap> a:=AffineSemigroup([2,0],[0,2],[1,1]);
gap> PrimitiveElementsOfAffineSemigroup(a);
[ [ 0, 2 ], [ 1, 1 ], [ 2, 0 ], [ 2, 2 ] ]
```

11.4 Factorizations in affine semigroups

The invariants presented here are defined as for numerical semigroups.

As with presentations, the user should take into account that generators are stored in a set, and thus might be arranged in a different way to the initial input.

11.4.1 FactorizationsVectorWRTList

▷ FactorizationsVectorWRTList(v, ls) (function)

v is a list of nonnegative integers and ls is a list of lists of nonnegative integers. The output is set of factorizations of v in terms of the elements of ls.

If no extra package is loaded, then factorizations are computed recursively; and thus slowly. If NormalizInterface is loaded, then a system of equations is solved with Normaliz, and the performance is much better. If 4ti2Interface is loaded instead, then factorizations are calculated using zsolve command of 4ti2.

Example

```
gap> FactorizationsVectorWRTList([5,5],[[2,0],[0,2],[1,1]]);
[ [ 2, 2, 1 ], [ 1, 1, 3 ], [ 0, 0, 5 ] ]
```

11.4.2 ElasticityOfAffineSemigroup

▷ ElasticityOfAffineSemigroup(a) (function)

a is an affine semigroup. The output is the elasticity of a (defined as for numerical semigroups).

The procedure used is based on [Phi10], where it is shown that the elasticity can be computed by using circuits. The set of circuits is calculated using [ES96].

Example

```
gap> a:=AffineSemigroup([2,0],[0,2],[1,1]);
gap> ElasticityOfAffineSemigroup(a);
1
```

11.4.3 CatenaryDegreeOfAffineSemigroup

▷ CatenaryDegreeOfAffineSemigroup(a) (function)

a is an affine semigroup. The output is the catenary degree of a (defined as for numerical semigroups).

Example

```
gap> a:=AffineSemigroup([2,0],[0,2],[1,1]);
gap> CatenaryDegreeOfAffineSemigroup(a);
2
```

11.4.4 EqualCatenaryDegreeOfAffineSemigroup

▷ EqualCatenaryDegreeOfAffineSemigroup(a) (function)

a is an affine semigroup. The output is the equal catenary degree of a (defined as for numerical semigroups).

This function relies on the results presented in [GSOSRN13].

11.4.5 HomogeneousCatenaryDegreeOfAffineSemigroup

▷ HomogeneousCatenaryDegreeOfAffineSemigroup(a) (function)

a is an affine semigroup. The output is the homogeneous catenary degree of a (defined as for numerical semigroups).

This function is based on [GSOSRN13].

11.4.6 MonotoneCatenaryDegreeOfAffineSemigroup

▷ MonotoneCatenaryDegreeOfAffineSemigroup(a) (function)

a is an affine semigroup. The output is the monotone catenary degree of a (defined as for numerical semigroups), computed as explained in [Phi10].

Example

```
gap> a:=AffineSemigroup("inequalities",[2,-1],[-1,3]);
<Affine semigroup>
gap> GeneratorsOfAffineSemigroup(a);
[ [ 1, 1 ], [ 1, 2 ], [ 2, 1 ], [ 3, 1 ] ]
gap> CatenaryDegreeOfAffineSemigroup(a);
3
gap> EqualCatenaryDegreeOfAffineSemigroup(a);
2
gap> HomogeneousCatenaryDegreeOfAffineSemigroup(a);
3
```

```
gap> MonotoneCatenaryDegreeOfAffineSemigroup(a);
3
```

11.4.7 TameDegreeOfAffineSemigroup

▷ TameDegreeOfAffineSemigroup(a) (function)

a is an affine semigroup. The output is the tame degree of a (defined as for numerical semigroups). If a is given by equations (or its equations are known), then the procedure explained in [GS14] is used.

Example

```
gap> a:=AffineSemigroup([2,0],[0,2],[1,1]);;
gap> TameDegreeOfAffineSemigroup(a);
2
```

11.4.8 OmegaPrimalityOfElementInAffineSemigroup

▷ OmegaPrimalityOfElementInAffineSemigroup(v, a) (function)

v is a list of nonnegative integers and a is an affine semigroup. The output is the omega primality of a (defined as for numerical semigroups). Returns 0 if the element is not in the semigroup.

The implementation of this procedure is performed as explained in [BGS11] (also, if the semigroup has defining equations, then it takes advantage of this fact as explained in this reference).

Example

```
gap> a:=AffineSemigroup([2,0],[0,2],[1,1]);;
gap> OmegaPrimalityOfElementInAffineSemigroup([5,5],a);
6
```

11.4.9 OmegaPrimalityOfAffineSemigroup

▷ OmegaPrimalityOfAffineSemigroup(a) (function)

a is an affine semigroup. The output is the omega primality of a (defined as for numerical semigroups).

Example

```
gap> a:=AffineSemigroup([2,0],[0,2],[1,1]);;
gap> OmegaPrimalityOfAffineSemigroup(a);
2
```

Chapter 12

Good semigroups

We will only cover here good semigroups of \mathbb{N}^2 .

A good semigroup S is a submonoid of \mathbb{N}^2 , with the following properties.

(G1) It is closed under infimums (minimum componentwise).

(G2) if $a, b \in M$ and $a_i = b_i$ for some $i \in \{1, 2\}$, then there exists $c \in M$ such that $c_i > a_i = b_i$ and $c_j = \min\{a_j, b_j\}$, with $j \in \{1, 2\} \setminus \{i\}$.

(G3) there exists $C \in \mathbb{N}^n$ such that $C + \mathbb{N}^n \subseteq S$.

Value semigroups of algebroid branches are good semigroups, but there are good semigroups that are not of this form. Since good semigroups are closed under infimums, if C_1 and C_2 fulfill $C_i + \mathbb{N}^n \subseteq S$, then $C_1 \wedge C_2 + \mathbb{N}^n \subseteq S$. So there is a minimum C fulfilling $C + \mathbb{N}^n \subseteq S$, which is called the conductor of S .

The contents of this chapter are described in [DGSM16].

12.1 Defining good semigroups

12.1.1 IsGoodSemigroup

▷ IsGoodSemigroup(S) (function)

Detects if S is a an object type good semigroup.

12.1.2 NumericalSemigroupDuplication

▷ NumericalSemigroupDuplication(S, E) (function)

S is a numerical semigroup and E is an ideal of S with $E \subseteq S$. The output is $S \bowtie E = D \cup (E \times E) \cup \{a \wedge b \mid a \in D, b \in E \times E\}$, where $D = \{(s, s) \mid s \in S\}$.

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> e:=6+s;;
gap> dup:=NumericalSemigroupDuplication(s,e);
<Good semigroup>
gap> l:=Cartesian([1..11],[1..11]);;
gap> Intersection(dup,l);
[ [ 3, 3 ], [ 5, 5 ], [ 6, 6 ], [ 6, 7 ], [ 6, 8 ], [ 6, 9 ], [ 6, 10 ],
  [ 6, 11 ], [ 7, 6 ], [ 7, 7 ], [ 8, 6 ], [ 8, 8 ], [ 9, 6 ], [ 9, 9 ],
```

```

[ 9, 10 ], [ 9, 11 ], [ 10, 6 ], [ 10, 9 ], [ 10, 10 ], [ 11, 6 ],
[ 11, 9 ], [ 11, 11 ] ]
gap> [384938749837,349823749827] in dup;
true

```

12.1.3 AmalgamationOfNumericalSemigroups

▷ AmalgamationOfNumericalSemigroups(S , E , b) (function)

S is a numerical semigroup, E is an ideal of a numerical semigroup T with $E \subseteq T$, and b is an integer such that multiplication by b is a morphism from S to T , say g . The output is $S \bowtie^g E = D \cup (g^{-1}(E) \times E) \cup \{a \wedge b \mid a \in D, b \in g^{-1}(E) \times E\}$, where $D = \{(s, bs) \mid s \in S\}$.

Example

```

gap> s:=NumericalSemigroup(2,3);;
gap> t:=NumericalSemigroup(3,4);;
gap> e:=3+t;;
gap> dup:=AmalgamationOfNumericalSemigroups(s,e,2);;
gap> [2,3] in dup;
true

```

12.1.4 CartesianProductOfNumericalSemigroups

▷ CartesianProductOfNumericalSemigroups(S , T) (function)

S and T are numerical semigroups. The output is $S \times T$, which is a good semigroup.

Example

```

gap> s:=NumericalSemigroup(2,3);;
gap> t:=NumericalSemigroup(3,4);;
gap> IsGoodSemigroup(CartesianProductOfNumericalSemigroups(s,t));
true

```

12.1.5 GoodSemigroup

▷ GoodSemigroup(X , C) (function)

X is a list of points with nonnegative integer coordinates and C is a pair of nonnegative integer (a list with two elements). If M is the affine and infimum closure of X , decides if it is a good semigroup, and if so, outputs it.

Example

```

gap> G:=[[4,3],[7,13],[11,17],[14,27],[15,27],[16,20],[25,12],[25,16]];
gap> C:=[25,27];
gap> GoodSemigroup(G,C);
<Good semigroup>

```

12.2 Notable elements

12.2.1 BelongsToGoodSemigroup

- ▷ `BelongsToGoodSemigroup(v, S)` (operation)
- ▷ `\in(v, S)` (operation)

S is a good semigroup and v is a pair of integers. The output is true if v is in S , and false otherwise. Other ways to use this operation are `\in(v, S)` and `v in S`.

Example

```
gap> s:=NumericalSemigroup(2,3);;
gap> e:=6+s;;
gap> dup:=NumericalSemigroupDuplication(s,e);;
gap> BelongsToGoodSemigroup([2,2],dup);
true
gap> [2,2] in dup;
true
gap> [3,2] in dup;
false
```

12.2.2 Conductor (for good semigroup)

- ▷ `Conductor(S)` (function)
- ▷ `ConductorOfGoodSemigroup(S)` (function)

S is a good semigroup. The output is its conductor.

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> e:=6+s;;
gap> dup:=NumericalSemigroupDuplication(s,e);
<Good semigroup>
gap> Conductor(dup);
[ 11, 11 ]
gap> ConductorOfGoodSemigroup(dup);
[ 11, 11 ]
```

12.2.3 SmallElements (for good semigroup)

- ▷ `SmallElements(S)` (function)
- ▷ `SmallElementsOfGoodSemigroup(S)` (function)

S is a good semigroup. The output is its set of small elements, that is, the elements smaller than its conductor with respect to the usual partial ordering.

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> e:=6+s;;
gap> dup:=NumericalSemigroupDuplication(s,e);
<Good semigroup>
gap> SmallElementsOfGoodSemigroup(dup);
[ [ 0, 0 ], [ 3, 3 ], [ 5, 5 ], [ 6, 6 ], [ 6, 7 ], [ 6, 8 ], [ 6, 9 ],
```

```
[ 6, 10 ], [ 6, 11 ], [ 7, 6 ], [ 7, 7 ], [ 8, 6 ], [ 8, 8 ], [ 9, 6 ],
[ 9, 9 ], [ 9, 10 ], [ 9, 11 ], [ 10, 6 ], [ 10, 9 ], [ 10, 10 ],
[ 11, 6 ], [ 11, 9 ], [ 11, 11 ] ]
```

12.2.4 RepresentsSmallElementsOfGoodSemigroup

▷ RepresentsSmallElementsOfGoodSemigroup(X)

(function)

X is a list of points in the nonnegative orthant of the plane with integer coordinates. Determines if it represents the set of small elements of a good semigroup.

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> e:=6+s;;
gap> dup:=NumericalSemigroupDuplication(s,e);
<Good semigroup>
gap> SmallElementsOfGoodSemigroup(dup);
[ [ 0, 0 ], [ 3, 3 ], [ 5, 5 ], [ 6, 6 ], [ 6, 7 ], [ 6, 8 ], [ 6, 9 ], [ 6, 10 ],
  [ 6, 11 ], [ 7, 6 ], [ 7, 7 ], [ 8, 6 ], [ 8, 8 ], [ 9, 6 ], [ 9, 9 ], [ 9, 10 ],
  [ 9, 11 ], [ 10, 6 ], [ 10, 9 ], [ 10, 10 ], [ 11, 6 ], [ 11, 9 ], [ 11, 11 ] ]
gap> RepresentsSmallElementsOfGoodSemigroup(last);
true
```

12.2.5 GoodSemigroupBySmallElements

▷ GoodSemigroupBySmallElements(X)

(function)

X is a list of points in the nonnegative orthant of the plane with integer coordinates. Determines if it represents the set of small elements of a good semigroup, and then outputs the good semigroup having X as set of small elements.

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> e:=6+s;;
gap> dup:=NumericalSemigroupDuplication(s,e);
<Good semigroup>
gap> SmallElementsOfGoodSemigroup(dup);
[ [ 0, 0 ], [ 3, 3 ], [ 5, 5 ], [ 6, 6 ], [ 6, 7 ], [ 6, 8 ], [ 6, 9 ], [ 6, 10 ],
  [ 6, 11 ], [ 7, 6 ], [ 7, 7 ], [ 8, 6 ], [ 8, 8 ], [ 9, 6 ], [ 9, 9 ], [ 9, 10 ],
  [ 9, 11 ], [ 10, 6 ], [ 10, 9 ], [ 10, 10 ], [ 11, 6 ], [ 11, 9 ], [ 11, 11 ] ]
gap> G:=GoodSemigroupBySmallElements(last);
<Good semigroup>
gap> dup=G;
true
```

12.2.6 MaximalElementsOfGoodSemigroup

▷ MaximalElementsOfGoodSemigroup(S)

(attribute)

S is a good semigroup. The output is the set of elements (x, y) of S with the following property: there is no other element (x', y') in S with $(x, y) \leq (x', y')$ sharing a coordinate with (x, y) .

Example

```
gap> G:=[[4,3],[7,13],[11,17]];;
gap> g:=GoodSemigroup(G,[11,17]];;
gap> mx:=MaximalElementsOfGoodSemigroup(g);
[ [ 0, 0 ], [ 4, 3 ], [ 7, 13 ], [ 8, 6 ] ]
```

12.2.7 IrreducibleMaximalElementsOfGoodSemigroup

▷ IrreducibleMaximalElementsOfGoodSemigroup(S)

(attribute)

S is a good semigroup. The output is the set of elements nonzero maximal elements that cannot be expressed as a sum of two nonzero maximal elements of the good semigroup.

Example

```
gap> G:=[[4,3],[7,13],[11,17]];;
gap> g:=GoodSemigroup(G,[11,17]];;
gap> IrreducibleMaximalElementsOfGoodSemigroup(g);
[ [ 4, 3 ], [ 7, 13 ] ]
```

12.2.8 GoodSemigroupByMaximalElements

▷ GoodSemigroupByMaximalElements(S , T , M , C)

(function)

S and T are numerical semigroups, M is a list of pairs in $S \times T$. C is the conductor, and thus a pair of nonnegative integers. The output is the set of elements of $S \times T$ that are not above an element in M , that is, if they share a coordinate with an element in M , then they must be smaller or equal to that element with respect to the usual partial ordering. The output is a good semigroup, if M is an correct set of maximal elements.

Example

```
gap> G:=[[4,3],[7,13],[11,17]];;
gap> g:=GoodSemigroup(G,[11,17]];;
gap> sm:=SmallElements(g);;
gap> mx:=MaximalElementsOfGoodSemigroup(g);;
gap> s:=NumericalSemigroupBySmallElements(Set(sm,x->x[1]));;
gap> t:=NumericalSemigroupBySmallElements(Set(sm,x->x[2]));;
gap> Conductor(g);
[ 11, 15 ]
gap> gg:=GoodSemigroupByMaximalElements(s,t,mx,[11,15]);
<Good semigroup>
gap> gg=g;
true
```

12.2.9 MinimalGoodGeneratingSystemOfGoodSemigroup

▷ MinimalGoodGeneratingSystemOfGoodSemigroup(S)

(function)

S is a good semigroup. The output is its minimal good generating system (which is unique in the local case).

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> e:=6+s;;
```



```
gap> dup:=NumericalSemigroupDuplication(s,e);
<Good semigroup>
gap> MinimalGoodGeneratingSystemOfGoodSemigroup(dup);
[ [ 3, 3 ], [ 5, 5 ], [ 6, 11 ], [ 7, 7 ], [ 11, 6 ] ]
```

12.2.10 MinimalGenerators

▷ MinimalGenerators(S) (attribute)

This is just a synonym of MinimalGoodGeneratingSystemOfGoodSemigroup(S).

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> e:=6*s;;
gap> dup:=NumericalSemigroupDuplication(s,e);
<Good semigroup>
gap> MinimalGenerators(dup);
[ [ 3, 3 ], [ 5, 5 ], [ 6, 11 ], [ 7, 7 ], [ 11, 6 ] ]
```

12.3 Symmetric semigroups

12.3.1 IsSymmetricGoodSemigroup

▷ IsSymmetricGoodSemigroup(S) (function)

S is a good semigroup. Determines if S is a symmetric good semigroup.

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> e:=CanonicalIdealOfNumericalSemigroup(s);;
gap> e:=15*e;;
gap> dup:=NumericalSemigroupDuplication(s,e);;
gap> IsSymmetricGoodSemigroup(dup);
true
```

12.3.2 ArfGoodSemigroupClosure

▷ ArfGoodSemigroupClosure(S) (function)

S is a good semigroup. Determines the Arf good semigroup closure of S .

Example

```
gap> G:=[[3,3],[4,4],[5,4],[4,6]];
[ [ 3, 3 ], [ 4, 4 ], [ 5, 4 ], [ 4, 6 ] ]
gap> C:=[6,6];
[ 6, 6 ]
gap> S:=GoodSemigroup(G,C);
<Good semigroup>
gap> SmallElements(S);
[ [ 0, 0 ], [ 3, 3 ], [ 4, 4 ], [ 4, 6 ], [ 5, 4 ], [ 6, 6 ] ]
gap> A:=ArfGoodSemigroupClosure(S);
<Good semigroup>
```

```
gap> SmallElements(A);
[ [ 0, 0 ], [ 3, 3 ], [ 4, 4 ] ]
```

12.4 Good ideals

A relative ideal I of a relative good semigroup M is a relative good ideal if I fulfills conditions (G1) and (G2) of the definition of good semigroup.

12.4.1 GoodIdeal

▷ `GoodIdeal(X, S)` (function)

X is a list of points with nonnegative integer coordinates and S is good semigroup. Decides if the closure of $X + S$ under infimums is a relative good ideal of S , and if so, outputs it.

Example

```
gap> G:=[[4,3],[7,13],[11,17],[14,27],[15,27],[16,20],[25,12],[25,16]];
[ [ 4, 3 ], [ 7, 13 ], [ 11, 17 ], [ 14, 27 ], [ 15, 27 ], [ 16, 20 ],
[ 25, 12 ], [ 25, 16 ] ]
gap> C:=[25,27];
[ 25, 27 ]
gap> GoodSemigroup(G,C);
<Good semigroup>
gap> i:=GoodIdeal([[2,3]],g);
<Good ideal of good semigroup>
```

12.4.2 GoodGeneratingSystemOfGoodIdeal

▷ `GoodGeneratingSystemOfGoodIdeal(I)` (function)

I is a good ideal of a good semigroup. The output is a good generating system of I .

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> e:=10+s;;
gap> d:=NumericalSemigroupDuplication(s,e);;
gap> e:=GoodIdeal([[2,3],[3,2],[2,2]],d);;
gap> GoodGeneratingSystemOfGoodIdeal(e);
[ [ 2, 2 ], [ 2, 3 ], [ 3, 2 ] ]
```

12.4.3 AmbientGoodSemigroupOfGoodIdeal

▷ `AmbientGoodSemigroupOfGoodIdeal(I)` (function)

If I is a good ideal of a good semigroup M , then the output is M . The output is a good generating system of I .

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> e:=10+s;;
gap> a:=AmalgamationOfNumericalSemigroups(s,e,5);;
```

```
gap> e:=GoodIdeal([[2,3],[3,2],[2,2]],a);;
gap> a=AmbientGoodSemigroupOfGoodIdeal(e);
true
```

12.4.4 MinimalGoodGeneratingSystemOfGoodIdeal

▷ `MinimalGoodGeneratingSystemOfGoodIdeal(I)` (function)

I is a good ideal of a good semigroup. The output is the minimal good generating system of I .

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> e:=10+s;;
gap> d:=NumericalSemigroupDuplication(s,e);;
gap> e:=GoodIdeal([[2,3],[3,2],[2,2]],d);;
gap> MinimalGoodGeneratingSystemOfGoodIdeal(e);
[[ 2, 3 ], [ 3, 2 ]]
```

12.4.5 BelongsToGoodIdeal

▷ `BelongsToGoodIdeal(v, I)` (operation)

▷ `\in(v, I)` (operation)

I is a good ideal of a good semigroup and v is a pair of integers. The output is true if v is in I , and false otherwise. Other ways to use this operation are `\in(v, I)` and `v in I`.

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> e:=10+s;;
gap> d:=NumericalSemigroupDuplication(s,e);;
gap> e:=GoodIdeal([[2,3],[3,2]],d);;
gap> [1,1] in e;
false
gap> [2,2] in e;
true
```

12.4.6 SmallElementsOfGoodIdeal

▷ `SmallElementsOfGoodIdeal(I)` (function)

▷ `SmallElements(I)` (function)

I is a good ideal. The output is its set of small elements, that is, the elements smaller than its conductor and larger than its minimum element (with respect to the usual partial ordering).

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> e:=10+s;;
gap> d:=NumericalSemigroupDuplication(s,e);;
gap> e:=GoodIdeal([[2,3],[3,2]],d);;
gap> SmallElements(e);
[[ 2, 2 ], [ 2, 3 ], [ 3, 2 ], [ 5, 5 ], [ 5, 6 ], [ 6, 5 ], [ 7, 7 ]]
```

12.4.7 CanonicalIdealOfGoodSemigroup

▷ CanonicalIdealOfGoodSemigroup(S)

(function)

S is a good semigroup. The output is the canonical ideal of S .

Example

```
gap> s:=NumericalSemigroup(3,5,7);;
gap> e:=10+s;;
gap> d:=NumericalSemigroupDuplication(s,e);;
gap> c:=CanonicalIdealOfGoodSemigroup(d);;
gap> MinimalGoodGeneratingSystemOfGoodIdeal(c);
[ [ 0, 0 ], [ 2, 2 ] ]
```

Chapter 13

External packages

The use of the packages `NormalizInterface` [GHS14] (an interface to `Normalize` [BIRC14]; or in its absence `4ti2Interface` [Gut], and interface to `4ti2` [tt]), `SingularInterface` (an interface to `Singular` [DGPS12]; or in its absence `Singular` [CdG12]); or in its absence `GradedModules` [BGJ⁺14] is highly recommended for many of the functions presented in this chapter. However, whenever possible a method not depending on these packages is also provided (though slower). The package tests if the user has downloaded any of the above packages, and if so puts `NumSgpsCanUsePackage` to true, where `Package` is any of the above.

13.1 Using external packages

As mentioned above some methods are specifically implemented to take advantage of several external packages. The following functions can be used in case these packages have not been loaded prior to `numericalsgps`.

13.1.1 NumSgpsUse4ti2

▷ `NumSgpsUse4ti2()` (function)

Tries to load the package `4ti2Interface`. If the package is available, then it also loads methods implemented using functions in this package.

13.1.2 NumSgpsUse4ti2gap

▷ `NumSgpsUse4ti2gap()` (function)

Tries to load the package `4ti2gap`. If the package is available, then it also loads methods implemented using functions in this package.

13.1.3 NumSgpsUseNormalize

▷ `NumSgpsUseNormalize()` (function)

Tries to load the package `NormalizInterface`. If the package is available, then it also loads methods implemented using functions in this package.

13.1.4 NumSgpsUseSingular

▷ NumSgpsUseSingular() (function)

Tries to load the package `singular`. If the package is available, then it also loads methods implemented using functions in this package.

To prevent incompatibilities, the package will not load if `SingularInterface` has been already loaded.

13.1.5 NumSgpsUseSingularInterface

▷ NumSgpsUseSingularInterface() (function)

Tries to load the package `SingularInterface`. If the package is available, then it also loads methods implemented using functions in this package.

To prevent incompatibilities, the package will not load if `singular` has been already loaded.

13.1.6 NumSgpsUseSingularGradedModules

▷ NumSgpsUseSingularGradedModules() (function)

Tries to load the package `GradedModules`. If the package is available, then it also loads methods implemented using functions in this package.

It also creates a ring of rationals `NumSgpsRationals`.

Appendix A

Generalities

Here we describe some functions which are not specific for numerical semigroups but are used to do computations with them. As they may have interest by themselves, we describe them here.

A.1 Bézout sequences

A sequence of positive rational numbers $a_1/b_1 < \dots < a_n/b_n$ with a_i, b_i positive integers is a *Bézout sequence* if $a_{i+1}b_i - a_ib_{i+1} = 1$ for all $i \in \{1, \dots, n-1\}$.

The following function uses an algorithm presented in [BR09].

A.1.1 BezoutSequence

▷ `BezoutSequence(arg)` (function)

`arg` consists of two rational numbers or a list of two rational numbers. The output is a Bézout sequence with ends the two rational numbers given. (Warning: rational numbers are silently transformed into irreducible fractions.)

Example

```
gap> BezoutSequence(4/5, 53/27);  
[ 4/5, 1, 3/2, 5/3, 7/4, 9/5, 11/6, 13/7, 15/8, 17/9, 19/10, 21/11, 23/12,  
 25/13, 27/14, 29/15, 31/16, 33/17, 35/18, 37/19, 39/20, 41/21, 43/22,  
 45/23, 47/24, 49/25, 51/26, 53/27 ]
```

A.1.2 IsBezoutSequence

▷ `IsBezoutSequence(L)` (function)

`L` is a list of rational numbers. `IsBezoutSequence` returns true or false according to whether `L` is a Bézout sequence or not.

Example

```
gap> IsBezoutSequence([ 4/5, 1, 3/2, 5/3, 7/4, 9/5, 11/6]);  
true  
gap> IsBezoutSequence([ 4/5, 1, 3/2, 5/3, 7/4, 9/5, 11/3]);  
Take the 6 and the 7 elements of the sequence  
false
```

A.1.3 CeilingOfRational

▷ CeilingOfRational(r) (function)

Returns the smallest integer greater than or equal to the rational r .

Example

```
gap> CeilingOfRational(3/5);
1
```

A.2 Periodic subadditive functions

A periodic function f of period m from the set \mathbb{N} of natural numbers into itself may be specified through a list of m natural numbers. The function f is said to be *subadditive* if $f(i+j) \leq f(i) + f(j)$ and $f(0) = 0$.

A.2.1 RepresentsPeriodicSubAdditiveFunction

▷ RepresentsPeriodicSubAdditiveFunction(L) (function)

L is a list of integers. RepresentsPeriodicSubAdditiveFunction returns true or false according to whether L represents a periodic subadditive function f periodic of period m or not. To avoid defining $f(0)$ (which we assume to be 0) we define $f(m) = 0$ and so the last element of the list must be 0. This technical need is due to the fact that positions in a list must be positive (not a 0).

Example

```
gap> RepresentsPeriodicSubAdditiveFunction([1,2,3,4,0]);
true
```

A.2.2 IsListOfIntegersNS

▷ IsListOfIntegersNS(L) (function)

Detects whether L is a nonempty list of integers.

Example

```
gap> IsListOfIntegersNS([1,-1,0]);
true
gap> IsListOfIntegersNS(2);
false
gap> IsListOfIntegersNS([2],3);
false
gap> IsListOfIntegersNS([]);
false
```


Appendix B

"Random" functions

Here we describe some functions which allow to create several "random" objects. We make use of the function `RandomList`.

B.1 Random functions

B.1.1 `RandomNumericalSemigroup`

▷ `RandomNumericalSemigroup(n, a[], b)` (function)

Returns a "random" numerical semigroup with no more than n generators in $[1..a]$ (or in $[a..b]$, if b is present).

Example

```
gap> RandomNumericalSemigroup(3,9);
<Numerical semigroup with 3 generators>
gap> RandomNumericalSemigroup(3,9,55);
<Numerical semigroup with 3 generators>
```

B.1.2 `RandomListForNS`

▷ `RandomListForNS(n, a, b)` (function)

Returns a set of length not greater than n of random integers in $[a..b]$ whose GCD is 1. It is used to create "random" numerical semigroups.

Example

```
gap> RandomListForNS(13,1,79);
[ 22, 26, 29, 31, 34, 46, 53, 61, 62, 73, 76 ]
```

B.1.3 `RandomModularNumericalSemigroup`

▷ `RandomModularNumericalSemigroup(k[], m)` (function)

Returns a "random" modular numerical semigroup $S(a,b)$ with $a \leq k$ (see 1) and multiplicity at least m , were m is the second argument, which may not be present..

Example

```
gap> RandomModularNumericalSemigroup(9);
<Modular numerical semigroup satisfying 5x mod 6 <= x >
gap> RandomModularNumericalSemigroup(10,25);
<Modular numerical semigroup satisfying 4x mod 157 <= x >
```

B.1.4 RandomProportionallyModularNumericalSemigroup

▷ RandomProportionallyModularNumericalSemigroup(k , m) (function)

Returns a “random” proportionally modular numerical semigroup $S(a, b, c)$ with $a \leq k$ (see 1) and multiplicity at least m , where m is the second argument, which may not be present.

Example

```
gap> RandomProportionallyModularNumericalSemigroup(9);
<Proportionally modular numerical semigroup satisfying 2x mod 3 <= 2x >
gap> RandomProportionallyModularNumericalSemigroup(10,25);
<Proportionally modular numerical semigroup satisfying 6x mod 681 <= 2x >
```

B.1.5 RandomListRepresentingSubAdditiveFunction

▷ RandomListRepresentingSubAdditiveFunction(m , a) (function)

Produces a “random” list representing a subadditive function (see 1) which is periodic with period m (or less). When possible, the images are in $[a..20*a]$. (Otherwise, the list of possible images is enlarged.)

Example

```
gap> RandomListRepresentingSubAdditiveFunction(7,9);
[ 173, 114, 67, 0 ]
gap> RepresentsPeriodicSubAdditiveFunction(last);
true
```

B.1.6 NumericalSemigroupWithRandomElementsAndFrobenius

▷ NumericalSemigroupWithRandomElementsAndFrobenius(n , $mult$, $frob$) (function)

Produces a “random” semigroup containing (at least) n elements greater than or equal to $mult$ and less than $frob$, chosen at random. The semigroup returned has multiplicity chosen at random but no smaller than $mult$ and having Frobenius number chosen at random but not greater than $frob$. Returns *fail* if $frob$ is greater than $mult$.

Example

```
gap> ns := NumericalSemigroupWithRandomElementsAndFrobenius(5,10,50);
<Numerical semigroup with 17 generators>
gap> MinimalGeneratingSystem(ns);
[ 12, 13, 19, 27, 47 ]
gap> SmallElements(ns);
[ 0, 12, 13, 19, 24, 25, 26, 27, 31, 32, 36, 37, 38, 39, 40, 43 ]
gap> ns2 := NumericalSemigroupWithRandomElementsAndFrobenius(5,10,9);
#I The third argument must not be smaller than the second
fail
```

```
gap> ns3 := NumericalSemigroupWithRandomElementsAndFrobenius(5,10,10);  
<Proportionally modular numerical semigroup satisfying  $20x \bmod 200 \leq 10x$  >  
gap> MinimalGeneratingSystem(ns3);  
[ 10 .. 19 ]  
gap> SmallElements(ns3);  
[ 0, 10 ]
```

Appendix C

Contributions

C.1 Functions implemented by A. Sammartano

C.1.1 IsGradedAssociatedRingNumericalSemigroupBuchsbaum

▷ IsGradedAssociatedRingNumericalSemigroupBuchsbaum(S) (function)

S is a numerical semigroup.

Returns true if the graded ring associated to $K[[S]]$ is Buchsbaum, and false otherwise. This test is the implementation of the algorithm given in [DMV09].

Example

```
gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> IsGradedAssociatedRingNumericalSemigroupBuchsbaum(s);
true
```

C.1.2 TorsionOfAssociatedGradedRingNumericalSemigroup

▷ TorsionOfAssociatedGradedRingNumericalSemigroup(S) (function)

S is a numerical semigroup.

This function returns the set of elements in the numerical semigroup S corresponding to a \mathbb{K} -basis of the torsion submodule of the associated graded ring of the numerical semigroup ring $\mathbb{K}[[S]]$. It uses the Apéry table as explained in [CBJZA13].

Example

```
gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> TorsionOfAssociatedGradedRingNumericalSemigroup(s);
[ 181, 153, 157, 193, 169, 148 ]
```

C.1.3 BuchsbaumNumberOfAssociatedGradedRingNumericalSemigroup

▷ BuchsbaumNumberOfAssociatedGradedRingNumericalSemigroup(S) (function)

S is a numerical semigroup.

This function returns the smallest non-negative integer k for which the associated graded ring G of a given numerical semigroup ring is k -Buchsbaum, that is, the least k for which the torsion submodule of G is annihilated by the k -th power of the homogeneous maximal ideal of G .

Example

```
gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> BuchsbaumNumberOfAssociatedGradedRingNumericalSemigroup(s);
1
gap> IsGradedAssociatedRingNumericalSemigroupBuchsbaum(s);
true
```

C.1.4 IsMpureNumericalSemigroup▷ IsMpureNumericalSemigroup(S)

(function)

 S is a numerical semigroup.Test for the M-Purity of the numerical semigroup S . This test is based on [Bry10].

Example

```
gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> IsMpureNumericalSemigroup(s);
false
gap> s:=NumericalSemigroup(4,6,11);;
gap> IsMpureNumericalSemigroup(s);
true
```

C.1.5 IsPureNumericalSemigroup▷ IsPureNumericalSemigroup(S)

(function)

 S is a numerical semigroup.Test for the purity of the numerical semigroup S . This test is based on [Bry10].

Example

```
gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> IsPureNumericalSemigroup(s);
false
gap> s:=NumericalSemigroup(4,6,11);;
gap> IsPureNumericalSemigroup(s);
true
```

C.1.6 IsGradedAssociatedRingNumericalSemigroupGorenstein▷ IsGradedAssociatedRingNumericalSemigroupGorenstein(S)

(function)

 S is a numerical semigroup.Returns true if the graded ring associated to $K[[S]]$ is Gorenstein, and false otherwise. This test is the implementation of the algorithm given in [DMS11].

Example

```
gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> IsGradedAssociatedRingNumericalSemigroupGorenstein(s);
false
gap> s:=NumericalSemigroup(4,6,11);;
gap> IsGradedAssociatedRingNumericalSemigroupGorenstein(s);
true
```

C.1.7 IsGradedAssociatedRingNumericalSemigroupCI

▷ IsGradedAssociatedRingNumericalSemigroupCI(S) (function)

S is a numerical semigroup.

Returns true if the Complete Intersection property of the associated graded ring of a numerical semigroup ring associated to $K[[S]]$, and false otherwise. This test is the implementation of the algorithm given in [DMS13].

Example

```
gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> IsGradedAssociatedRingNumericalSemigroupCI(s);
false
gap> s:=NumericalSemigroup(4,6,11);;
gap> IsGradedAssociatedRingNumericalSemigroupCI(s);
true
```

C.1.8 IsAperySetGammaRectangular

▷ IsAperySetGammaRectangular(S) (function)

S is a numerical semigroup.

Test for the Gamma-Rectangularity of the Apéry Set of a numerical semigroup. This test is the implementation of the algorithm given in [DMS14].

Example

```
gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> IsAperySetGammaRectangular(s);
false
gap> s:=NumericalSemigroup(4,6,11);;
gap> IsAperySetGammaRectangular(s);
true
```

C.1.9 IsAperySetBetaRectangular

▷ IsAperySetBetaRectangular(S) (function)

S is a numerical semigroup.

Test for the Beta-Rectangularity of the Apéry Set of a numerical semigroup. This test is the implementation of the algorithm given in [DMS14].

Example

```
gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> IsAperySetBetaRectangular(s);
false
gap> s:=NumericalSemigroup(4,6,11);;
gap> IsAperySetBetaRectangular(s);
true
```

C.1.10 IsAperySetAlphaRectangular

▷ IsAperySetAlphaRectangular(S) (function)

S is a numerical semigroup.

Test for the Alpha-Rectangularity of the Apéry Set of a numerical semigroup. This test is the implementation of the algorithm given in [DMS14].

Example

```
gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> IsAperySetAlphaRectangular(s);
false
gap> s:=NumericalSemigroup(4,6,11);;
gap> IsAperySetAlphaRectangular(s);
true
```

C.1.11 TypeSequenceOfNumericalSemigroup

▷ TypeSequenceOfNumericalSemigroup(S)

(function)

S is a numerical semigroup.

Computes the type sequence of a numerical semigroup. This test is the implementation of the algorithm given in [BDF97].

Example

```
gap> s:=NumericalSemigroup(30, 35, 42, 47, 148, 153, 157, 169, 181, 193);;
gap> TypeSequenceOfNumericalSemigroup(s);
[ 13, 3, 4, 4, 7, 3, 3, 3, 2, 2, 2, 3, 3, 2, 4, 3, 2, 1, 3, 2, 1, 1, 2, 2, 1,
  1, 1, 2, 2, 1, 3, 1, 1, 1, 1, 2, 2, 1, 1, 1, 1, 1, 1, 1, 2, 1, 1, 1, 1, 1,
  1, 1, 1 ]
gap> s:=NumericalSemigroup(4,6,11);;
gap> TypeSequenceOfNumericalSemigroup(s);
[ 1, 1, 1, 1, 1, 1, 1, 1 ]
```

C.2 Functions implemented by C. O'Neill

This section includes the implementations of some procedures described in [BOP14].

C.2.1 OmegaPrimalityOfElementListInNumericalSemigroup

▷ OmegaPrimalityOfElementListInNumericalSemigroup(l , S)

(function)

S is a numerical semigroup and l a list of elements of S .

Computes the omega-values of all the elements in l .

Example

```
gap> s:=NumericalSemigroup(10,11,13);;
gap> l:=FirstElementsOfNumericalSemigroup(100,s);;
gap> List(l,x->OmegaPrimalityOfElementInNumericalSemigroup(x,s)); time;
[ 0, 4, 5, 5, 4, 6, 7, 6, 6, 6, 6, 7, 8, 7, 7, 7, 7, 7, 8, 7, 8, 9, 8, 8, 8,
  8, 8, 8, 8, 9, 9, 10, 9, 9, 9, 9, 9, 9, 9, 10, 11, 10, 10, 10, 10, 10,
  10, 10, 10, 11, 12, 11, 11, 11, 11, 11, 11, 11, 11, 12, 13, 12, 12, 12, 12,
  12, 12, 12, 12, 13, 14, 13, 13, 13, 13, 13, 13, 13, 13, 14, 15, 14, 14, 14,
  14, 14, 14, 14, 14, 15, 16, 15, 15, 15, 15, 15, 15, 15, 15 ]
218
gap> OmegaPrimalityOfElementListInNumericalSemigroup(l,s);time;
```

```
[ 0, 4, 5, 5, 4, 6, 7, 6, 6, 6, 6, 7, 8, 7, 7, 7, 7, 7, 8, 7, 8, 9, 8, 8, 8,
  8, 8, 8, 8, 9, 9, 10, 9, 9, 9, 9, 9, 9, 9, 10, 11, 10, 10, 10, 10, 10,
  10, 10, 10, 11, 12, 11, 11, 11, 11, 11, 11, 11, 12, 13, 12, 12, 12, 12,
  12, 12, 12, 12, 13, 14, 13, 13, 13, 13, 13, 13, 13, 13, 14, 15, 14, 14, 14,
  14, 14, 14, 14, 14, 15, 16, 15, 15, 15, 15, 15, 15, 15, 15 ]
10
```

C.2.2 FactorizationsElementListWRTNumericalSemigroup

▷ FactorizationsElementListWRTNumericalSemigroup(l , S) (function)

S is a numerical semigroup and l a list of elements of S .
Computes the factorizations of all the elements in l .

Example

```
gap> s:=NumericalSemigroup(10,11,13);
<Numerical semigroup with 3 generators>
gap> FactorizationsElementListWRTNumericalSemigroup([100,101,103],s);
[ [ [ 0, 2, 6 ], [ 1, 7, 1 ], [ 3, 4, 2 ], [ 5, 1, 3 ], [ 10, 0, 0 ] ],
  [ [ 0, 8, 1 ], [ 1, 0, 7 ], [ 2, 5, 2 ], [ 4, 2, 3 ], [ 9, 1, 0 ] ],
  [ [ 0, 7, 2 ], [ 2, 4, 3 ], [ 4, 1, 4 ], [ 7, 3, 0 ], [ 9, 0, 1 ] ] ]
```

C.2.3 DeltaSetPeriodicityBoundForNumericalSemigroup

▷ DeltaSetPeriodicityBoundForNumericalSemigroup(S) (function)

S is a numerical semigroup.

Computes the bound were the periodicity starts for Delta sets of the elements in S ; see [GGMFVT14].

Example

```
gap> s:=NumericalSemigroup(5,7,11);;
gap> DeltaSetPeriodicityBoundForNumericalSemigroup(s);
60
```

C.2.4 DeltaSetPeriodicityStartForNumericalSemigroup

▷ DeltaSetPeriodicityStartForNumericalSemigroup(S) (function)

S is a numerical semigroup.

Computes the element were the periodicity starts for Delta sets of the elements in S .

Example

```
gap> s:=NumericalSemigroup(5,7,11);;
gap> DeltaSetPeriodicityStartForNumericalSemigroup(s);
21
```


C.2.5 DeltaSetListUpToElementWRTNumericalSemigroup

▷ `DeltaSetListUpToElementWRTNumericalSemigroup(n , S)` (function)

S is a numerical semigroup, n a nonnegative integer.

Computes the Delta sets of the integers up to (and including) n , if an integer is not in S , the corresponding Delta set is empty.

Example

```
gap> s:=NumericalSemigroup(5,7,11);;
gap> DeltaSetListUpToElementWRTNumericalSemigroup(31,s);
[[ ], [ ], [ ], [ ], [ ], [ ], [ ], [ ], [ ], [ ], [ ], [ ], [ ],
 [ ], [ ], [ ], [ ], [ ], [ ], [ ], [ ], [2 ], [ ], [2 ], [ ],
 [2 ], [ ], [2 ], [2 ], [ ]]
```

C.2.6 DeltaSetUnionUpToElementWRTNumericalSemigroup

▷ `DeltaSetUnionUpToElementWRTNumericalSemigroup(n , S)` (function)

S is a numerical semigroup, n a nonnegative integer.

Computes the union of the delta sets of the elements of S up to and including n , using a ring buffer to conserve memory.

Example

```
gap> s:=NumericalSemigroup(5,7,11);;
gap> DeltaSetUnionUpToElementWRTNumericalSemigroup(60,s);
[ 2 ]
```

C.2.7 DeltaSetOfNumericalSemigroup

▷ `DeltaSetOfNumericalSemigroup(S)` (function)

S is a numerical semigroup.

Computes the Delta set of S .

Example

```
gap> s:=NumericalSemigroup(5,7,11);;
gap> DeltaSetOfNumericalSemigroup(s);
[ 2 ]
```

C.3 Functions implemented by K. Stokes

In this section we document the functions implemented by K. Stokes related to patterns of ideals in numerical semigroups. The correctness of the algorithms can be found in [Sto15].

C.3.1 IsAdmissiblePattern

▷ `IsAdmissiblePattern(p)` (function)

p is the list of integers that are the coefficients of a pattern.

Returns true or false depending if the pattern is admissible or not (see [BAGS06]).

Example

```
gap> IsAdmissiblePattern([1,1,-1]);
true
gap> IsAdmissiblePattern([1,-2]);
false
```

C.3.2 IsStronglyAdmissiblePattern

▷ IsStronglyAdmissiblePattern(p) (function)

p is the list of integers that are the coefficients of a pattern.
Returns true or false depending if the pattern is strongly admissible or not (see [BAGS06]).

Example

```
gap> IsAdmissiblePattern([1,-1]);
true
gap> IsStronglyAdmissiblePattern([1,-1]);
false
gap> IsStronglyAdmissiblePattern([1,1,-1]);
true
```

C.3.3 AsIdealOfNumericalSemigroup

▷ AsIdealOfNumericalSemigroup(I , T) (function)

I is an ideal of a numerical semigroup S , and T is a numerical semigroup. Detects if I is an ideal of T and contained in T (integral ideal), and if so, returns I as an ideal of T . It returns fail if I is an ideal of some semigroup but not an integral ideal of t .

Example

```
gap> s:=NumericalSemigroup(3,7,5);;
gap> t:=NumericalSemigroup(10,11,14);;
gap> AsIdealOfNumericalSemigroup(10+s,t);
fail
gap> AsIdealOfNumericalSemigroup(100+s,t);
<Ideal of numerical semigroup>
```

C.3.4 BoundForConductorOfImageOfPattern

▷ BoundForConductorOfImageOfPattern(p , C) (function)

p is the list of integers that are the coefficients of an admissible pattern. C is a positive integer. Calculates an upper bound of the smallest element K in $p(I)$ such that all integers larger than K are contained in $p(I)$, where I is an ideal of a numerical semigroup. Instead of taking I as parameter, the function takes C , which is assumed to be the conductor of I .

Example

```
gap> BoundForConductorOfImageOfPattern([1,1,-1],10);
10
```

C.3.5 ApplyPatternToIdeal

▷ `ApplyPatternToIdeal(p , I)` (function)

p is the list of integers that are the coefficients of a strongly admissible pattern. I is an ideal of a numerical semigroup.

Calculates $p(I)$. Outputs $p(I)$, represented as $[d, p(I)/d]$, where d is the gcd of the coefficients of p . All elements of $p(I)$ are divisible by d , and $p(I)/d$ is an ideal of some numerical semigroup. It is returned as the maximal ideal of the numerical semigroup $p(I)/d \cup \{0\}$. The parent numerical semigroup can later be changed with the function `AsIdealOfNumericalSemigroup`.

Example

```
gap> s:=NumericalSemigroup(3,7,5);;
gap> i:=10+s;;
gap> ApplyPatternToIdeal([1,1,-1],i);
[ 1, <Ideal of numerical semigroup> ]
```

C.3.6 ApplyPatternToNumericalSemigroup

▷ `ApplyPatternToNumericalSemigroup(p , S)` (function)

p is the list of integers that are the coefficients of a strongly admissible pattern. S is a numerical semigroup.

Outputs `ApplyPatternToIdeal(p , 0+S)`.

Example

```
gap> s:=NumericalSemigroup(3,7,5);;
gap> ApplyPatternToNumericalSemigroup([1,1,-1],s);
[ 1, <Ideal of numerical semigroup> ]
gap> SmallElements(last[2]);
[ 0, 3, 5 ]
```

C.3.7 IsAdmittedPatternByIdeal

▷ `IsAdmittedPatternByIdeal(p , I , J)` (function)

p is the list of integers that are the coefficients of a strongly admissible pattern. I and J are ideals of certain numerical semigroups.

Tests whether or not $p(I)$ is contained in J .

Example

```
gap> s:=NumericalSemigroup(3,7,5);;
gap> i:=[3,5]+s;;
gap> IsAdmittedPatternByIdeal([1,1,-1],i,i);
false
gap> IsAdmittedPatternByIdeal([1,1,-1],i,0+s);
true
```

C.3.8 IsAdmittedPatternByNumericalSemigroup

▷ `IsAdmittedPatternByNumericalSemigroup(p , S , T)` (function)

p is the list of integers that are the coefficients of a strongly admissible pattern. S and T are numerical semigroups.

Tests whether or not $p(S)$ is contained in T .

Example

```
gap> IsAdmittedPatternByNumericalSemigroup([1,1,-1],s,s);  
true  
gap> IsArfNumericalSemigroup(s);  
true
```

C.4 Functions implemented by I. Ojeda and C. J. Moreno Ávila

Ignacio and Carlos Jesús implemented the algorithms given in [Rou08] and [MCOT15] for the calculation of the Frobenius number and Apéry set of a numerical semigroup using Gröbner basis calculations. These methods will be used if 4ti2 is loaded (either 4ti2Interface or 4ti2gap). A faster algorithm is employed provided that singular is loaded.

References

- [AGGS10] F. Aguiló-Gost and P. A. García-Sánchez. Factoring in embedding dimension three numerical semigroups. *Electron. J. Combin.*, 17(1):Research Paper 138, 21, 2010. [58](#)
- [AGS13] A. Assi and P. A. García-Sánchez. Constructing the set of complete intersection numerical semigroups with a given frobenius number. *Applicable Algebra in Engineering, Communication and Computing*, 2013. [39](#)
- [AGS14] A. Assi and P. A. García-Sánchez. On curves with one place at infinity. *arXiv*, 1407.0490, 2014. [72](#)
- [AGSM14] A. Assi, P. A. García-Sánchez, and V. Micalé. Bases of subalgebras of $k[[x]]$ and $k[x]$. *arXiv*, 1412.4089, 2014. [73](#), [74](#)
- [BA08] M. Bras-Amorós. Fibonacci-like behavior of the number of numerical semigroups of a given genus. *Semigroup Forum*, 76:379–384, 2008. [33](#)
- [BAGS06] Maria Bras-Amorós and Pedro A. García-Sánchez. Patterns on numerical semigroups. *Linear Algebra Appl.*, 414(2-3):652–669, 2006. [105](#), [106](#)
- [BC77] J. Bertin and P. Carbonne. Semi-groupes d’entiers et application aux branches. *J. Algebra*, 49(1):81–95, 1977. [39](#), [40](#)
- [BD89] R. J. Bradford and J. H. Davenport. Effective tests for cyclotomic polynomials. In *Symbolic and algebraic computation (Rome, 1988)*, volume 358 of *Lecture Notes in Comput. Sci.*, pages 244–251. Springer, Berlin, 1989. [70](#)
- [BDF97] V. Barucci, D. D. Dobbs, and M. Fontana. *Maximality properties in numerical semigroups and applications to one-dimensional analytically irreducible local domains*. Number 598 in *Memoirs of the American Mathematical Society*. American Mathematical Society, 1997. [37](#), [43](#), [103](#)
- [BF06] V. Barucci and R. Fröberg. Associated graded rings of one-dimensional analytically irreducible rings. *J. Algebra*, 304:349–358, 2006. [48](#), [50](#), [51](#)
- [BGJ⁺14] M. Barakat, S. Gutsche, S. Jambor, M. Lange-Hegermann, A. Lorenz, and O. Motsak. GradedModules, a homalg based package for the abelian category of finitely presented graded modules over computable graded rings, Version 2014.09.17. <http://homalg.math.rwth-aachen.de/~barakat/homalg-project/GradedModules/>, Sep 2014. GAP package. [93](#)

- [BGS11] V. Blanco, P. A. García-Sánchez, and A. Geroldinger. Semigroup-theoretical characterizations of arithmetical invariants with applications to numerical monoids and krull monoids. *Illinois J. Math.*, 55:1385–1414, 2011. 29, 66, 83
- [BH13] Lance Bryant and James Hamblin. The maximal denominator of a numerical semigroup. *Semigroup Forum*, 86(3):571–582, 2013. 61, 62
- [BIRC14] W. Bruns, B. Ichim, T. Römer, and Söger C. Normaliz. algorithms for rational cones and affine monoids. <http://www.math.uos.de/normaliz>, 2014. 93
- [BOP14] T. Barron, C. O’Neill, and R. Pelayo. On the computation of delta sets and ω -primality in numerical monoids. *preprint*, 2014. 103
- [BR97] V. Barucci and Fröberg R. One-dimensional almost gorenstein rings. *J. Algebra*, 188:418–442, 1997. 41
- [BR09] M. Bullejos and J. C. Rosales. Proportionally modular Diophantine inequalities and the Stern-Brocot tree. *Math. Comp.*, 78(266):1211–1226, 2009. 95
- [BR13] Victor Blanco and José Carlos Rosales. The tree of irreducible numerical semigroups with fixed Frobenius number. *Forum Math.*, 25(6):1249–1261, 2013. 37
- [Bry10] L. Bryant. Goto numbers of a numerical semigroup ring and the Gorensteiness of associated graded rings. *Comm. Algebra*, 38(6):2092–2128, 2010. 101
- [CBJZA13] T. Cortadellas Benítez, R. Jafari, and S. Zarzuela Armengou. On the apéry sets of monomial curves. *Semigroup Forum*, 86:289–320, 2013. 52, 100
- [CD94] E. Contejean and H. Devie. An efficient incremental algorithm for solving systems of linear Diophantine equations. *Inform. and Comput.*, 113(1):143–172, 1994. 78
- [CdG12] M. Costantini and W. de Graaf. Gap package singular; the gap interface to singular. <http://gap-system.org/Packages/singular.html>, 2012. 93
- [CGSD07] S. T. Chapman, P. A. García-Sánchez, and Llena D. The catenary and tame degree of numerical semigroups. *Forum Math.*, pages 1–13, 2007. 57
- [CGSL⁺06] S. T. Chapman, P. A. García-Sánchez, D. Llena, V. Ponomarenko, and J. C. Rosales. The catenary and tame degree in finitely generated commutative cancellative monoids. *Manuscripta Math.*, 120(3):253–264, 2006. 57
- [CHM06] S. T. Chapman, M. T. Holden, and T. A. Moore. Full elasticity in atomic monoids and integral domains. *Rocky Mountain J. Math.*, 36(5):1437–1455, 2006. 57
- [CRA13] Jonathan Chappelon and Jorge Luis Ramírez Alfonsín. On the Möbius function of the locally finite poset associated with a numerical semigroup. *Semigroup Forum*, 87(2):313–330, 2013. 68
- [DGPS12] Wolfram Decker, Gert-Martin Greuel, Gerhard Pfister, and Hans Schönemann. SINGULAR 3-1-6 — A computer algebra system for polynomial computations. <http://www.singular.uni-kl.de>, 2012. 93

- [DGS16] M. Delgado and P. A. García-Sánchez. numericalsgps, a GAP package for numerical semigroups. *ACM Commun. Comput. Algebra*, 50(1):12–24, 2016. 8
- [DGSM06] M. Delgado, P. A. García-Sánchez, and J. Morais. On the GAP package numericalsgps. In *Fifth Conference on Discrete Mathematics and Computer Science (Spanish)*, volume 23 of *Ciencias (Valladolid)*, pages 271–278. Univ. Valladolid, Secr. Publ. Intercamb. Ed., Valladolid, 2006. 8
- [DGSM16] M. D’Anna, P. A. García-Sánchez, and E. Micale. Good semigroups. *preprint*, 2016. 84
- [DGSRP15] M. Delgado, P. A. García-Sánchez, and A. M. Robles-Pérez. Numerical semigroups with a given set of pseudo-frobenius numbers. *ArXiv e-prints*, May 2015. 34
- [DMS11] M. D’Anna, V. Micale, and A. Sammartano. On the associated graded ring of a semigroup ring. *J. Commut. Algebra*, 3(2):147–168, 2011. 101
- [DMS13] M. D’Anna, V. Micale, and A. Sammartano. When the associated graded ring of a semigroup ring is complete intersection. *J. Pure Appl. Algebra*, 217(6):1007–1017, 2013. 102
- [DMS14] Marco D’Anna, Vincenzo Micale, and Alessio Sammartano. Classes of complete intersection numerical semigroups. *Semigroup Forum*, 88(2):453–467, 2014. 102, 103
- [DMV09] M. D’Anna, M. Mezzasalma, and Micale V. On the buchsbaumness of the associated graded ring of a one-dimensional local ring. *Comm. Algebra*, 37:1594–1603, 2009. 100
- [Eli01] J. Elias. On the deep structure of the blowing-up of curve singularities. *Math. Proc. Camb. Phil. Soc.*, 131:227–240, 2001. 50
- [Eli15] S. Eliahou. Wilf’s conjecture and Macaulay’s theorem. *preprint*, 2015. 25
- [ES96] David Eisenbud and Bernd Sturmfels. Binomial ideals. *Duke Math. J.*, 84(1):1–45, 1996. 81
- [FGR87] R. Fröberg, C. Gottlieb, and Haggkvist R. On numerical semigroups. *Semigroup Forum*, 35(1):63–83, 1987. 37
- [GGMFVT14] J. I. García-García, M. A. Moreno-Frías, and A. Vigneron-Tenorio. Computation of delta sets of numerical monoids. *arxiv:1406.0280*, 2014. 104
- [GHK06] A. Geroldinger and F. Halter-Koch. *Non-unique Factorizations: Algebraic, Combinatorial and Analytic Theory*. Chapman & Hall/CRC, 2006. 57
- [GHS14] S Gutsche, M. Horn, and C. Söger. Normalizinterface for gap. <https://github.com/fingolfin/NormalizInterface>, 2014. 93
- [GS14] P. A. García-Sánchez. A new approach for the computation of the tame degree. *arxiv:1504.02998*, 2014. 83

- [GSO10] P. A. García-Sánchez and I. Ojeda. Uniquely presented finitely generated commutative monoids. *Pacific J. Math.*, 249:91–105, 2010. 28, 29
- [GSOSRN13] P. A. García Sánchez, I. Ojeda, and A. Sánchez-R.-Navarro. Factorization invariants in half-factorial affine semigroups. *Internat. J. Algebra Comput.*, 23(1):111–122, 2013. 67, 82
- [Gut] S. Gutsche. 4ti2interface, a link to 4ti2. <http://www.gap-system.org/Packages/4ti2interface.html>. 93
- [Her70] Jürgen Herzog. Generators and relations of abelian semigroups and semigroup rings. *Manuscripta Math.*, 3:175–193, 1970. 80
- [HS04] K. Herzinger and R. Sanford. Minimal generating sets for relative ideals in numerical semigroups of multiplicity eight. *Communications in Algebra*, 32(12):4713–4731, 2004. 46
- [KP95] Christoph Kirfel and Ruud Pellikaan. The minimum distance of codes in an array coming from telescopic semigroups. *IEEE Trans. Inform. Theory*, 41(6, part 1):1720–1732, 1995. Special issue on algebraic geometry codes. 39, 40
- [KW14] E. Kunz and R. Waldi. Geometrical illustration of numerical semigroups and of some of their invariants. *Semigroup Forum*, 89(3):664–691, 2014. 24
- [MCOT15] Guadalupe Márquez-Campos, Ignacio Ojeda, and José M. Tornero. On the computation of the Apéry set of numerical monoids and affine semigroups. *Semigroup Forum*, 91(1):139–158, 2015. 108
- [Mic02] V. Micale. On monomial semigroups. *Communications in Algebra*, 30:4687 – 4698, 2002. 51
- [Mor14] Pieter Moree. Numerical semigroups, cyclotomic polynomials, and Bernoulli numbers. *Amer. Math. Monthly*, 121(10):890–902, 2014. 69, 71
- [Phi10] A. Philipp. A characterization of arithmetical invariants by the monoid of relations. *Semigroup Forum*, 81:424–434, 2010. 81, 82
- [RB03] J. C. Rosales and M. B. Branco. Irreducible numerical semigroups. *Pacific J. Math.*, 209(1):131–143, 2003. 37
- [RGS98] J.C. Rosales and Pedro A. García-Sánchez. Nonnegative elements of subgroups of \mathbb{Z}^n . *Linear Algebra and its Applications*, 270(1-3):351–357, 1998. 78
- [RGS99a] J. C. Rosales and P. A. García-Sánchez. *Finitely generated commutative monoids*. Nova Science Publishers, New York, 1999. 27
- [RGS99b] J. C. Rosales and P. A. García-Sánchez. On free affine semigroups. *Semigroup Forum*, 58(3):367–385, 1999. 79
- [RGS04] J. C. Rosales and P. A. García-Sánchez. Every positive integer is the frobenius number of an irreducible numerical semigroup with at most four generators. *Ark. Mat.*, 42:301–306, 2004. 37, 38

- [RGS09] J. C. Rosales and P. A. García-Sánchez. *Numerical Semigroups*. Springer, 2009. [8](#), [55](#), [58](#)
- [RGS14] J. C. Rosales and P. A. García-Sánchez. Constructing almost symmetric numerical semigroups from irreducible numerical semigroups. *Comm. Algebra*, 42(3):1362–1367, 2014. [41](#), [42](#)
- [RGSB02] J. C. Rosales, García-García J. I. García-Sánchez, P. A. and, and M. B. Branco. Systems of inequalities and numerical semigroups. *Journal of the London Mathematical Society*, 65:611–623, 6 2002. [22](#), [78](#)
- [RSGGB03] J. C. Rosales, P. A. García-Sánchez, J. I. García-García, and M. B. Branco. Numerical semigroups with maximal embedding dimension. *J. Algebra*, 2:47–53, 2003. [33](#), [53](#)
- [RSGGB04] J. C. Rosales, P. A. García-Sánchez, J. I. García-García, and M. B. Branco. Arf numerical semigroups. *J. Algebra*, 276:3–12, 2004. [54](#)
- [RSGGJM03] J. C. Rosales, P. A. García-Sánchez, J. I. García-García, and J. A. Jiménez-Madrid. The oversemigroups of a numerical semigroup. *Semigroup Forum*, 67:145–158, 2003. [30](#), [32](#), [37](#)
- [RSGGJM04] J. C. Rosales, P. A. García-Sánchez, J. I. García-García, and J. A. Jiménez Madrid. Fundamental gaps in numerical semigroups. *J. Pure Appl. Algebra*, 189(1-3):301–313, 2004. [33](#)
- [Ros96a] J. C. Rosales. An algorithmic method to compute a minimal relation for any numerical semigroup. *Internat. J. Algebra Comput.*, 6:441–455, 1996. [27](#), [28](#)
- [Ros96b] J. C. Rosales. On numerical semigroups. *Semigroup Forum*, 52:307–318, 1996. [15](#)
- [Rou08] Bjarke Hammersholt Roune. Solving thousand-digit Frobenius problems using Gröbner bases. *J. Symbolic Comput.*, 43(1):1–7, 2008. [108](#)
- [Spi15] Dario Spirito. Star operations on numerical semigroups. *Comm. Algebra*, 43(7):2943–2963, 2015. [52](#)
- [Sto15] K. Stokes. Patterns of ideals of numerical semigroups. *preprint*, 2015. [105](#)
- [SW86] L. A. Székely and N. C. Wormald. Generating functions for the Frobenius problem with 2 and 3 generators. *Math. Chronicle*, 15:49–57, 1986. [28](#)
- [tt] 4ti2 team. 4ti2—a software package for algebraic, geometric and combinatorial problems on linear spaces. Available at www.4ti2.de. [93](#)
- [Ugo16] Simone Ugolini. On numerical semigroups closed with respect to the action of affine maps. *arXiv*, 1505.06580, 2016. [12](#)
- [Wil78] Herbert S. Wilf. A circle-of-lights algorithm for the “money-changing problem”. *Amer. Math. Monthly*, 85(7):562–565, 1978. [25](#)
- [Zar86] O. Zariski. *Le problème des modules pour les courbes planes*. Hermann, 1986. [39](#), [41](#)

Index

- *
 - for multiple of ideal of numerical semigroup, [46](#)
- +
 - for defining ideal of numerical semigroup, [43](#)
 - for ideals of numerical semigroup, [46](#)
- - for ideals of numerical semigroup, [46](#)
- AddSpecialGapOfNumericalSemigroup, [30](#)
- AdjacentCatenaryDegreeOfSetOfFactorizations, [63](#)
- AdjustmentOfNumericalSemigroup, [61](#)
- AffineSemigroup, [75](#)
- AlmostSymmetricNumericalSemigroupsFromIrreducible, [42](#)
- AlmostSymmetricNumericalSemigroupsWithFrobeniusNumber, [42](#)
- AmalgamationOfNumericalSemigroups, [85](#)
- AmbientGoodSemigroupOfGoodIdeal, [90](#)
- AmbientNumericalSemigroupOfIdeal, [44](#)
- AnIrreducibleNumericalSemigroupWithFrobeniusNumber, [38](#)
- ANumericalSemigroupWithPseudoFrobeniusNumbers, [35](#)
- AperyList
 - for numerical semigroup with respect to multiplicity, [20](#)
- AperyListOfIdealOfNumericalSemigroupWRTElement, [51](#)
- AperyListOfNumericalSemigroup, [20](#)
- AperyListOfNumericalSemigroupAsGraph, [21](#)
- AperyListOfNumericalSemigroupWRTElement, [20](#)
- AperyListOfNumericalSemigroupWRTInteger, [20](#)
- AperyTableOfNumericalSemigroup, [52](#)
- ApplyPatternToIdeal, [107](#)
- ApplyPatternToNumericalSemigroup, [107](#)
- ArfGoodSemigroupClosure, [89](#)
- ArfNumericalSemigroupClosure, [54](#)
- ArfNumericalSemigroupsWithFrobeniusNumber, [55](#)
- AsAffineSemigroup, [76](#)
- AsGluingOfNumericalSemigroups, [39](#)
- AsIdealOfNumericalSemigroup, [106](#)
- BasisOfGroupGivenByEquations, [79](#)
- BelongsToAffineSemigroup, [77](#)
- BelongsToGoodIdeal, [91](#)
- BelongsToGoodSemigroup, [86](#)
- BelongsToHomogenizationOfNumericalSemigroup, [67](#)
- BelongsToIdealOfNumericalSemigroup, [45](#)
- BelongsToNumericalSemigroup, [16](#)
- BettiElementsOfAffineSemigroup, [80](#)
- BettiElementsOfNumericalSemigroup, [28](#)
- BezoutSequence, [95](#)
- BlowUpIdealOfNumericalSemigroup, [49](#)
- BlowUpOfNumericalSemigroup, [49](#)
- BoundForConductorOfImageOfPattern, [106](#)
- BuchsbaumNumberOfAssociatedGradedRingNumericalSemigroup, [100](#)
- CanonicalIdealOfGoodSemigroup, [92](#)
- CanonicalIdealOfNumericalSemigroup, [48](#)
- CartesianProductOfNumericalSemigroups, [85](#)
- CatenaryDegreeOfAffineSemigroup, [82](#)
- CatenaryDegreeOfElementInNumericalSemigroup, [64](#)
- CatenaryDegreeOfNumericalSemigroup, [64](#)
- CatenaryDegreeOfSetOfFactorizations, [62](#)
- CeilingOfRational, [96](#)
- CompleteIntersectionNumericalSemigroupsWithFrobeniusNumber, [40](#)

- Conductor
 - for good semigroup, [86](#)
 - for ideal of numerical semigroup, [45](#)
 - for numerical Semigroup, [22](#)
- ConductorOfGoodSemigroup, [86](#)
- ConductorOfIdealOfNumericalSemigroup, [45](#)
- ConductorOfNumericalSemigroup, [22](#)
- CurveAssociatedToDeltaSequence, [72](#)
- DecomposeIntoIrreducibles
 - for numerical semigroup, [39](#)
- DeltaSequencesWithFrobeniusNumber, [72](#)
- DeltaSetListUpToElementWRTNumericalSemigroup, [105](#)
- DeltaSetOfFactorizationsElementWRTNumericalSemigroup, [60](#)
- DeltaSetOfNumericalSemigroup, [105](#)
- DeltaSetOfSetOfIntegers, [60](#)
- DeltaSetPeriodicityBoundForNumericalSemigroup, [104](#)
- DeltaSetPeriodicityStartForNumericalSemigroup, [104](#)
- DeltaSetUnionUpToElementWRTNumericalSemigroup, [105](#)
- DenumerantOfElementInNumericalSemigroup, [59](#)
- DifferenceOfIdealsOfNumericalSemigroup, [47](#)
- ElasticityOfAffineSemigroup, [81](#)
- ElasticityOfFactorizationsElementWRTNumericalSemigroup, [59](#)
- ElasticityOfNumericalSemigroup, [60](#)
- EliahouNumber
 - for numerical semigroup, [25](#)
- EliahouSlicesOfNumericalSemigroup, [26](#)
- EmbeddingDimension
 - for numerical semigroup, [19](#)
- EmbeddingDimensionOfNumericalSemigroup, [19](#)
- EqualCatenaryDegreeOfAffineSemigroup, [82](#)
- EqualCatenaryDegreeOfNumericalSemigroup, [65](#)
- EqualCatenaryDegreeOfSetOfFactorizations, [63](#)
- EqualPrimitiveElementsOfNumericalSemigroup, [64](#)
- EquationsOfGroupGeneratedBy, [78](#)
- FactorizationsElementListWRTNumericalSemigroup, [104](#)
- FactorizationsElementWRTNumericalSemigroup, [58](#)
- FactorizationsInHomogenizationOfNumericalSemigroup, [67](#)
- FactorizationsIntegerWRTList, [57](#)
- FactorizationsVectorWRTList, [81](#)
- FirstElementsOfNumericalSemigroup, [20](#)
- ForcedIntegersForPseudoFrobenius, [34](#)
- FreeNumericalSemigroupsWithFrobeniusNumber, [40](#)
- FrobeniusNumber
 - for numerical semigroup, [22](#)
- FrobeniusNumberOfNumericalSemigroup, [22](#)
- FundamentalGaps
 - for numerical semigroup, [24](#)
- FundamentalGapsOfNumericalSemigroup, [24](#)
- Gaps
 - for numerical semigroup, [23](#)
- GapsOfNumericalSemigroup, [23](#)
- Generators
 - for affine semigroup, [76](#)
 - for ideal of numerical semigroup, [44](#)
 - for numerical semigroup, [18](#)
- GeneratorsOfAffineSemigroup, [76](#)
- GeneratorsOfIdealOfNumericalSemigroup, [44](#)
- GeneratorsOfKernelCongruence, [79](#)
- GeneratorsOfNumericalSemigroup, [18](#)
- Genus
 - for numerical semigroup, [24](#)
- GenusOfNumericalSemigroup, [24](#)
- GluingOfAffineSemigroups, [79](#)
- GoodGeneratingSystemOfGoodIdeal, [90](#)
- GoodIdeal, [90](#)
- GoodSemigroup, [85](#)
- GoodSemigroupByMaximalElements, [88](#)
- GoodSemigroupBySmallElements, [87](#)
- GraeffePolynomial, [70](#)
- GraphAssociatedToElementInNumericalSemigroup, [27](#)

- HilbertBasisOfSystemOfHomogeneous-
Equations, 78
- HilbertBasisOfSystemOfHomogeneous-
Inequalities, 78
- HilbertFunctionOfIdealOfNumerical-
Semigroup, 49
- HilbertSeriesOfNumericalSemigroup, 70
- Holes
 - for numerical semigroup, 23
- HolesOfNumericalSemigroup, 23
- HomogeneousBettiElementsOfNumerical-
Semigroup, 67
- HomogeneousCatenaryDegreeOfAffine-
Semigroup, 82
- HomogeneousCatenaryDegreeOfNumerical-
Semigroup, 68
- IdealOfNumericalSemigroup, 43
- \in
 - membership for good ideal, 91
 - membership for good semigroup, 86
 - membership test for numerical semigroup,
16
 - membership test ideal of numerical semi-
group, 45
- InductiveNumericalSemigroup, 32
- IntersectionIdealsOfNumerical-
Semigroup, 48
- IntersectionOfNumericalSemigroups, 31
- IrreducibleMaximalElementsOfGood-
Semigroup, 88
- IrreducibleNumericalSemigroupsWith-
FrobeniusNumber, 38
- IsACompleteIntersectionNumerical-
Semigroup, 39
- IsAdditiveNumericalSemigroup, 62
- IsAdmissiblePattern, 105
- IsAdmittedPatternByIdeal, 107
- IsAdmittedPatternByNumericalSemigroup,
107
- IsAffineSemigroup, 77
- IsAffineSemigroupByEquations, 77
- IsAffineSemigroupByGenerators, 77
- IsAffineSemigroupByInequalities, 77
- IsAffineSemigroupByMinimalGenerators,
77
- IsAlmostSymmetricNumericalSemigroup, 42
- IsAperyListOfNumericalSemigroup, 15
- IsAperySetAlphaRectangular, 102
- IsAperySetBetaRectangular, 102
- IsAperySetGammaRectangular, 102
- IsArfNumericalSemigroup, 54
- IsBezoutSequence, 95
- IsCanonicalIdealOfNumericalSemigroup,
48
- IsCyclotomicNumericalSemigroup, 71
- IsCyclotomicPolynomial, 70
- IsDeltaSequence, 72
- IsFreeNumericalSemigroup, 40
- IsFullAffineSemigroup, 77
- IsGenericAffineSemigroup, 80
- IsGenericNumericalSemigroup, 29
- IsGoodSemigroup, 84
- IsGradedAssociatedRingNumerical-
SemigroupBuchsbaum, 100
- IsGradedAssociatedRingNumerical-
SemigroupCI, 102
- IsGradedAssociatedRingNumerical-
SemigroupCM, 51
- IsGradedAssociatedRingNumerical-
SemigroupGorenstein, 101
- IsIdealOfNumericalSemigroup, 43
- IsIntegralIdealOfNumericalSemigroup, 44
- IsIrreducibleNumericalSemigroup, 37
- IsKroneckerPolynomial, 70
- IsListOfIntegersNS, 96
- IsMEDNumericalSemigroup, 53
- IsModularNumericalSemigroup, 14
- IsMonomialNumericalSemigroup, 51
- IsMpureNumericalSemigroup, 101
- IsNumericalSemigroup, 14
- IsNumericalSemigroupAssociated-
IrreduciblePlanarCurve-
Singularity, 41
- IsNumericalSemigroupByAperyList, 14
- IsNumericalSemigroupByFundamentalGaps,
14
- IsNumericalSemigroupByGaps, 14
- IsNumericalSemigroupByGenerators, 14
- IsNumericalSemigroupByInterval, 14
- IsNumericalSemigroupByMinimal-
Generators, 14
- IsNumericalSemigroupByOpenInterval, 14
- IsNumericalSemigroupBySmallElements, 14

- IsNumericalSemigroupBySubAdditive-Function, 14
- IsNumericalSemigroupPolynomial, 69
- IsProportionallyModularNumericalSemigroup, 14
- IsPseudoSymmetricNumericalSemigroup, 38
- IsPureNumericalSemigroup, 101
- IsSaturatedNumericalSemigroup, 55
- IsSelfReciprocalUnivariatePolynomial, 71
- IsStronglyAdmissiblePattern, 106
- IsSubsemigroupOfNumericalSemigroup, 16
- IsSubset, 16
- IsSuperSymmetricNumericalSemigroup, 62
- IsSymmetricGoodSemigroup, 89
- IsSymmetricNumericalSemigroup, 38
- IsTelescopicNumericalSemigroup, 40
- IsUniquelyPresentedAffineSemigroup, 81
- IsUniquelyPresentedNumericalSemigroup, 29
- KunzCoordinatesOfNumericalSemigroup, 21
- KunzPolytope, 21
- LatticePathAssociatedToNumericalSemigroup, 23
- LengthsOfFactorizationsElementWRTNumericalSemigroup, 59
- LengthsOfFactorizationsIntegerWRTList, 59
- LipmanSemigroup, 50
- LShapesOfNumericalSemigroup, 58
- MaximalDenumerantOfElementInNumericalSemigroup, 61
- MaximalDenumerantOfNumericalSemigroup, 61
- MaximalDenumerantOfSetOfFactorizations, 61
- MaximalElementsOfGoodSemigroup, 87
- MaximalIdealOfNumericalSemigroup, 48
- MaximumDegreeOfElementWRTNumericalSemigroup, 60
- MEDNumericalSemigroupClosure, 53
- MicroInvariantsOfNumericalSemigroup, 50
- MinimalArfGeneratingSystemOfArfNumericalSemigroup, 55
- MinimalGeneratingSystem
 - for affine semigroup, 76
 - for ideal of numerical semigroup, 44
 - for numerical semigroup, 18
- MinimalGeneratingSystemOfIdealOfNumericalSemigroup, 44
- MinimalGeneratingSystemOfNumericalSemigroup, 18
- MinimalGenerators, 89
 - for affine semigroup, 76
 - for ideal of numerical semigroup, 44
 - for numerical semigroup, 18
- MinimalGoodGeneratingSystemOfGoodIdeal, 91
- MinimalGoodGeneratingSystemOfGoodSemigroup, 88
- MinimalMEDGeneratingSystemOfMEDNumericalSemigroup, 54
- MinimalPresentationOfAffineSemigroup, 80
- MinimalPresentationOfNumericalSemigroup, 27
- ModularNumericalSemigroup, 12
- MoebiusFunctionAssociatedToNumericalSemigroup, 68
- MonotoneCatenaryDegreeOfAffineSemigroup, 82
- MonotoneCatenaryDegreeOfNumericalSemigroup, 65
- MonotoneCatenaryDegreeOfSetOfFactorizations, 63
- MonotonePrimitiveElementsOfNumericalSemigroup, 65
- MultipleOfIdealOfNumericalSemigroup, 46
- MultipleOfNumericalSemigroup, 32
- Multiplicity
 - for numerical semigroup, 18
- MultiplicityOfNumericalSemigroup, 18
- MultiplicitySequenceOfNumericalSemigroup, 50
- NumericalDuplication, 32
- NumericalSemigroup
 - by (closed) interval, 13
 - by affine map, 12
 - by Apéry list, 10
 - by fundamental gaps, 12
 - by gaps, 11

- by generators, 9
- by modular condition, 12
- by open interval, 14
- by proportionally modular condition, 13
- by small elements, 11
- by subadditive function, 10
- NumericalSemigroupByAffineMap, 12
- NumericalSemigroupByApéryList, 10
- NumericalSemigroupByFundamentalGaps, 12
- NumericalSemigroupByGaps, 11
- NumericalSemigroupByGenerators, 9
- NumericalSemigroupByInterval, 13
- NumericalSemigroupByOpenInterval, 14
- NumericalSemigroupBySmallElements, 11
- NumericalSemigroupBySubAdditive-
Function, 10
- NumericalSemigroupDuplication, 84
- NumericalSemigroupFromNumerical-
SemigroupPolynomial, 69
- NumericalSemigroupPolynomial, 69
- NumericalSemigroupsAssociated-
IrreduciblePlanarCurve-
SingularityWithFrobeniusNumber, 41
- NumericalSemigroupsWithFrobenius-
Number, 33
- NumericalSemigroupsWithGenus, 33
- NumericalSemigroupsWithPseudo-
FrobeniusNumbers, 35
- NumericalSemigroupWithRandomElements-
AndFrobenius, 98
- NumSgpsUse4ti2, 93
- NumSgpsUse4ti2gap, 93
- NumSgpsUseNormalize, 93
- NumSgpsUseSingular, 94
- NumSgpsUseSingularGradedModules, 94
- NumSgpsUseSingularInterface, 94
- OmegaPrimalityOfAffineSemigroup, 83
- OmegaPrimalityOfElementInAffine-
Semigroup, 83
- OmegaPrimalityOfElementInNumerical-
Semigroup, 66
- OmegaPrimalityOfElementListIn-
NumericalSemigroup, 103
- OmegaPrimalityOfNumericalSemigroup, 66
- OverSemigroupsNumericalSemigroup, 33
- PrimitiveElementsOfAffineSemigroup, 81
- PrimitiveElementsOfNumericalSemigroup, 28
- ProfileOfNumericalSemigroup, 26
- ProportionallyModularNumerical-
Semigroup, 13
- PseudoFrobeniusOfNumericalSemigroup, 22
- QuotientOfNumericalSemigroup, 31
- RandomListForNS, 97
- RandomListRepresentingSubAdditive-
Function, 98
- RandomModularNumericalSemigroup, 97
- RandomNumericalSemigroup, 97
- RandomProportionallyModularNumerical-
Semigroup, 98
- RClassesOfSetOfFactorizations, 58
- ReductionNumberIdealNumerical-
Semigroup, 49
- RemoveMinimalGeneratorFromNumerical-
Semigroup, 30
- RepresentsGapsOfNumericalSemigroup, 15
- RepresentsPeriodicSubAdditiveFunction, 96
- RepresentsSmallElementsOfGood-
Semigroup, 87
- RepresentsSmallElementsOfNumerical-
Semigroup, 15
- SaturatedNumericalSemigroupClosure, 56
- SaturatedNumericalSemigroupsWith-
FrobeniusNumber, 56
- SemigroupOfValuesOfCurve_Global, 74
- SemigroupOfValuesOfCurve_Local, 73
- SemigroupOfValuesOfPlaneCurve, 73
- SemigroupOfValuesOfPlaneCurveWith-
SinglePlaceAtInfinity, 72
- ShadedSetOfElementInAffineSemigroup, 80
- ShadedSetOfElementInNumerical-
Semigroup, 28
- SimpleForcedIntegersForPseudo-
Frobenius, 34
- SmallElements
 - for good ideal, 91
 - for good semigroup, 86
 - for ideal of numerical semigroup, 45
 - for numerical semigroup, 19

[SmallElementsOfGoodIdeal](#), 91
[SmallElementsOfGoodSemigroup](#), 86
[SmallElementsOfIdealOfNumerical-](#)
 [Semigroup](#), 45
[SmallElementsOfNumericalSemigroup](#), 19
[SpecialGaps](#)
 for numerical semigroup, 24
[SpecialGapsOfNumericalSemigroup](#), 24
[StarClosureOfIdealOfNumerical-](#)
 [Semigroup](#), 52
[SubtractIdealsOfNumericalSemigroup](#), 46
[SumIdealsOfNumericalSemigroup](#), 46

[TameDegreeOfAffineSemigroup](#), 83
[TameDegreeOfElementInNumerical-](#)
 [Semigroup](#), 66
[TameDegreeOfNumericalSemigroup](#), 65
[TameDegreeOfSetOfFactorizations](#), 64
[TelescopicNumericalSemigroupsWith-](#)
 [FrobeniusNumber](#), 41
[TorsionOfAssociatedGradedRing-](#)
 [NumericalSemigroup](#), 100
[TranslationOfIdealOfNumerical-](#)
 [Semigroup](#), 47
[TruncatedWilfNumberOfNumerical-](#)
 [Semigroup](#), 25
[TypeOfNumericalSemigroup](#), 23
[TypeSequenceOfNumericalSemigroup](#), 103

[WilfNumber](#)
 for numerical semigroup, 25
[WilfNumberOfNumericalSemigroup](#), 25