

Multimodal Visual Understanding + Robotic Arm Grasping

Multimodal Visual Understanding + Robotic Arm Grasping

1. Course Content
2. Starting the Agent
3. Running the Examples
 - 3.1 Starting the Program
 - 3.2 Test Cases
 - 3.2.1 Case 1: "Find the red cube in front of you and grasp it"
 - 3.2.2 Case 2: "Put the red block in front of you to the right of the blue block"
 - 3.2.3 Case 3: "Please help me remove the machine code in front of you that is taller than 5 centimeters"
4. Source Code Analysis
 - 4.1 Case 1
 - 4.2 Case Study 2
 - 4.3 Case Study 3

1. Course Content

Run the example program, using the robot's visual understanding combined with robotic arm grasping for a comprehensive task.

[!NOTE]

- The only difference between the text version and the voice version is the method of command input; the text version does not include speech recognition and speech synthesis playback.

2. Starting the Agent

Note: If already started, there is no need to start again.

Enter the following command in the vehicle terminal:

```
sh start_agent.sh
```

The terminal will print the following information, indicating a successful connection:

```
Jetson@yahboom: ~
Jetson@yahboom: ~ 177x26
Jetson@yahboom:~$ ./open_agent.sh
[1749538760.063253] Info | TermiosAgentLinux.cpp | Init | running... | fd: 3
[1749538760.064012] Info | Root.cpp | set_verbose_level | logger setup | verbose_level: 4
[1749538760.941420] Info | Root.cpp | create_client | create | client_key: 0x0DA64EFC, session_id: 0x81
[1749538760.941537] Info | SessionManager.hpp | establish_session | session established | client_key: 0x0DA64EFC, address: 0
[1749538760.979971] Info | ProxyClient.cpp | create_participant | participant created | client_key: 0x0DA64EFC, participant_id: 0x000(1)
[1749538760.983835] Info | ProxyClient.cpp | create_topic | topic created | client_key: 0x0DA64EFC, topic_id: 0x000(2), participant_id: 0x000(1)
[1749538760.988244] Info | ProxyClient.cpp | create_publisher | publisher created | client_key: 0x0DA64EFC, publisher_id: 0x000(3), participant_id: 0x000(1)
[1749538760.993117] Info | ProxyClient.cpp | create_datawriter | datawriter created | client_key: 0x0DA64EFC, datawriter_id: 0x000(5), publisher_id: 0x000(3)
[1749538760.997675] Info | ProxyClient.cpp | create_topic | topic created | client_key: 0x0DA64EFC, topic_id: 0x001(2), participant_id: 0x000(1)
[1749538761.001121] Info | ProxyClient.cpp | create_publisher | publisher created | client_key: 0x0DA64EFC, publisher_id: 0x001(3), participant_id: 0x000(1)
[1749538761.007277] Info | ProxyClient.cpp | create_datawriter | datawriter created | client_key: 0x0DA64EFC, datawriter_id: 0x001(5), publisher_id: 0x001(3)
[1749538761.010634] Info | ProxyClient.cpp | create_topic | topic created | client_key: 0x0DA64EFC, topic_id: 0x002(2), participant_id: 0x000(1)
[1749538761.014296] Info | ProxyClient.cpp | create_publisher | publisher created | client_key: 0x0DA64EFC, publisher_id: 0x002(3), participant_id: 0x000(1)
[1749538761.020171] Info | ProxyClient.cpp | create_datawriter | datawriter created | client_key: 0x0DA64EFC, datawriter_id: 0x002(5), publisher_id: 0x002(3)
[1749538761.023939] Info | ProxyClient.cpp | create_topic | topic created | client_key: 0x0DA64EFC, topic_id: 0x003(2), participant_id: 0x000(1)
[1749538761.029173] Info | ProxyClient.cpp | create_publisher | publisher created | client_key: 0x0DA64EFC, publisher_id: 0x003(3), participant_id: 0x000(1)
[1749538761.034377] Info | ProxyClient.cpp | create_datawriter | datawriter created | client_key: 0x0DA64EFC, datawriter_id: 0x003(5), publisher_id: 0x003(3)
[1749538761.038946] Info | ProxyClient.cpp | create_topic | topic created | client_key: 0x0DA64EFC, topic_id: 0x004(2), participant_id: 0x000(1)
[1749538761.042215] Info | ProxyClient.cpp | create_publisher | publisher created | client_key: 0x0DA64EFC, publisher_id: 0x004(3), participant_id: 0x000(1)
[1749538761.048422] Info | ProxyClient.cpp | create_datawriter | datawriter created | client_key: 0x0DA64EFC, datawriter_id: 0x004(5), publisher_id: 0x004(3)
[1749538761.051660] Info | ProxyClient.cpp | create_topic | topic created | client_key: 0x0DA64EFC, topic_id: 0x005(2), participant_id: 0x000(1)
[1749538761.057494] Info | ProxyClient.cpp | create_publisher | publisher created | client_key: 0x0DA64EFC, publisher_id: 0x005(3), participant_id: 0x000(1)
[1749538761.062183] Info | ProxyClient.cpp | create_datawriter | datawriter created | client_key: 0x0DA64EFC, datawriter_id: 0x005(5), publisher_id: 0x005(3)
[1749538761.066842] Info | ProxyClient.cpp | create_topic | topic created | client_key: 0x0DA64EFC, topic_id: 0x006(2), participant_id: 0x000(1)
[1749538761.071217] Info | ProxyClient.cpp | create_subscriber | subscriber created | client_key: 0x0DA64EFC, subscriber_id: 0x000(4), participant_id: 0x000(1)
```

3. Running the Examples

3.1 Starting the Program

Connect to the vehicle's screen via VNC and start the AI agent function:

```
ros2 launch multi_brains llm_agent_control.launch.py text_chat_mode:=True
```

- Start text interaction in any terminal:

```
ros2 run text_chat text_chat
```

3.2 Test Cases

Here are four reference test cases; users can create their own dialogue commands.


- Find the red cube in front of you and grasp it.
- Place the red cube in front of you to the right of the blue cube.
- Please remove the machine code in front of you that is taller than 5 centimeters.
- Track machine code number three.

3.2.1 Case 1: "Find the red cube in front of you and grasp it"

Enter "Find the red cube in front of you and grasp it" in the virtual machine terminal. The terminal will print the following information:

```
yahboom@yahboom-virtual-machine: ~  
yahboom@yahboom-virtual-machine: ~ 85x17  
yahboom@yahboom-virtual-machine:~$ ros2 run text_chat text_chat  
user input: 找出你面前的红色方块并夹取它  
okay😊, let me think for a moment... |[INFO] [1749528991.282079958] [text_chat_node]  
: robot response: "action": ['seewhat()'], "response": 好的, 我先用我的眼睛看看面前有什么。  
user input: [INFO] [1749528995.404830295] [text_chat_node]: robot response: "action":  
['grasp_obj(334,241,389,296)'], "response": 我已经找到了红色方块, 现在准备用我的机械臂去夹取它。
```

After the `grasp_obj()` function is called, a window titled **rgb_img** will open in the VNC screen, displaying the image from the robot's perspective. The robot will automatically adjust the distance to the target object. After the distance adjustment is complete, the robot will use the robotic arm to grasp the target object.



After the robot picks up an object, the robotic arm will remain in its current position. If you need the robotic arm to return to its initial state, you can use the following methods:

- Method 1: Enter the command: "Put down the block you just picked up" to make the robot put down the red block it just picked up.
- Method 2: Enter the command: "End the current task" to make the robot end the current task. After the task cycle ends, the robotic arm will reset to its initial posture.

Here, we use Method 2 as an example to make the robot end the task and reset the task cycle.

```
yahboom@yahboom-virtual-machine: ~
yahboom@yahboom-virtual-machine: ~ 80x18
yahboom@yahboom-virtual-machine:~$ ros2 run text_chat text_chat
user input: 找出你面前的红色方块并夹取它
okay😊, let me think for a moment... \[INFO] [1749529120.909372361] [text_chat_
node]: robot response: "action": ['seewhat()'], "response": 好的，我先用我的眼睛
看看面前有什么。
user input: [INFO] [1749529123.638094620] [text_chat_node]: robot response: "act
ion": ['grasp_obj(318,260,377,325)'], "response": 我已经找到了红色方块，现在准备
用我的机械臂去夹取它。
[INFO] [1749529147.326151707] [text_chat_node]: robot response: "action": ['fini
shtask()'], "response": 我已经成功夹取了红色方块，任务完成啦！
结束当前任务
okay😊, let me think for a moment... \[INFO] [1749529175.189809286] [text_chat_
node]: robot response: "action": ['finish_dialogue()'], "response": 好的，任务已
经结束了，有需要再叫我哦！
user input:
```


3.2.2 Case 2: "Put the red block in front of you to the right of the blue block"

- Enter "Put the red block in front of you to the right of the blue block" in the terminal. The terminal will print the following information:

```
yahboom@yahboom-virtual-machine: ~
yahboom@yahboom-virtual-machine: ~ 80x18
yahboom@yahboom-virtual-machine:~$ ros2 run text_chat text_chat
user input: 把你面前的红色方块放到蓝色方块的右边
okay😊, let me think for a moment... /[INFO] [1749535692.677677595] [text_chat_
node]: robot response: "action": ['seewhat()'], "response": 好的，我先看看面前都
有些什么。
user input: [INFO] [1749535696.731774075] [text_chat_node]: robot response: "act
ion": ['grasp_obj(260,300,315,355)'], "response": 我已经看到了红色方块，现在准备
夹取它。

```

A window titled **rgb_img** will open in the VNC screen, displaying the image from the robot's perspective. The robot will automatically adjust the distance between itself and the target object. After the distance adjustment is complete, the robot will use its robotic arm to pick up the target object.



Then the robot will translate to the right for a certain distance, and then use its robotic arm to put down the red block it just picked up, and indicate that the task is complete.



When commands such as "End current task" or "You can rest now," which indicate that the robot is no longer needed, are entered, the robot will end the current task.


```
yahboom@yahboom-virtual-machine: ~  
yahboom@yahboom-virtual-machine: ~ 80x18  
node]: robot response: "action": ['seewhat()'], "response": 好的，我先看看面前都  
有什么。  
user input: [INFO] [1749535696.731774075] [text_chat_node]: robot response: "act  
ion": ['grasp_obj(260,300,315,355)'], "response": 我已经看到了红色方块，现在准备  
夹取它。  
[INFO] [1749535719.755869876] [text_chat_node]: robot response: "action": ['set_  
cmdvel(0, -0.3, 0, 1.2)'], "response": 红色方块已经夹取成功，现在我将向右平移一  
段距离。  
[INFO] [1749535724.391909140] [text_chat_node]: robot response: "action": ['putd  
own()'], "response": 我已经向右平移了，现在准备放下红色方块。  
[INFO] [1749535734.350047207] [text_chat_node]: robot response: "action": ['fini  
shetask()'], "response": 红色方块已经成功放到蓝色方块的右边啦！任务完成，还有其他  
需要帮忙的吗？  
结束当前任务  
okay😊, let me think for a moment... -[INFO] [1749535799.069898864] [text_chat_  
node]: robot response: "action": ['finish_dialogue()'], "response": 好的，任务已  
经结束了。有需要再叫我哦！  
user input: 
```

3.2.3 Case 3: "Please help me remove the machine code in front of you that is taller than 5 centimeters"

Entering "Please help me remove the machine code in front of you that is taller than 5 centimeters" in the virtual machine terminal will print the following information:

```
yahboom@yahboom-virtual-machine: ~  
yahboom@yahboom-virtual-machine: ~ 80x24  
yahboom@yahboom-virtual-machine:~$ ros2 run text_chat text_chat  
user input: 请帮我移除你面前高度高于5厘米的机器码  
okay😊, let me think for a moment... \[INFO] [1749537101.728560811] [text_chat_  
node]: robot response: "action": ['apriltag_remove_higher(5)'], "response": 好的  
，我这就帮你移除高度高于5厘米的机器码。稍等一下哦！  
user input:
```

A window titled **result_image** will open in the VNC screen, displaying the image from the robot's perspective. The height of each machine code can be seen. After the distance measurement stabilizes, the robot will automatically adjust its distance from the target, and then use its robotic arm to pick up the machine code of the target height and move it to the right side of the robot.



```
yahboom@yahboom-virtual-machine: ~
yahboom@yahboom-virtual-machine: ~ 80x24
yahboom@yahboom-virtual-machine:~$ ros2 run text_chat text_chat
user input: 请帮我移除你面前高度高于5厘米的机器码
okay😊, let me think for a moment... \[INFO] [1749537101.728560811] [text_chat_
node]: robot response: "action": ['apriltag_remove_higher(5)'], "response": 好的
, 我这就帮你移除高度高于5厘米的机器码。稍等一下哦!
user input: [INFO] [1749537145.735233387] [text_chat_node]: robot response: "act
ion": ['finishtask()'], "response": 已经成功移除高度高于5厘米的机器码啦! 还有什
么我能帮你的吗?
█
```

When you enter commands in the terminal such as "end current task" or "you can rest now," which no longer require the robot's action, the robot will end the current task.

4. Source Code Analysis

- Robot action source code path:


```
~/M3Pro_ws/src/multi_brains/multi_brains/action_service.py
```

4.1 Case 1

action_service.py program:

Case 1 uses the **seewhat** and **grasp_obj** methods in the **ActionController** class. The **seewhat** function mainly obtains the color image from the depth camera, which has been explained in the **Multimodal Visual Understanding** section. Here, we will explain the **grasp_obj** function.

The coordinate rules for objects in the robotic arm's grasping view are shown in the following figure:



The **grasp_obj(x1, y1, x2, y2)** function is used to call the robotic arm to grasp the target object. The parameters are the coordinates of the top-left and bottom-right vertices of the bounding box of the object to be grasped (the top-left corner of the image is the pixel coordinate origin). For example, in Case 1, the bounding box coordinates of the red square to be grasped can be obtained from the large model's response: the top-left corner coordinates are (365, 200), and the bottom-right corner coordinates are (408, 261).

- `grasp_obj` starts three subprocesses: **grasp_desktop**, **KCF_follow**, and **ALM_KCF_Tracker_Node3**, and passes the parameters given by the AI large model to the **ALM_KCF_Tracker_Node** node via topics.

```
def grasp_obj(self, x1, y1, x2, y2) -> None:
    """grasp_obj: Grasping object x1, y1, x2, y2: Coordinates of the
    object's bounding box """
    def __reset_grasp_obj():
        kill_process_tree(self.grasp_obj_process_1.pid)
        kill_process_tree(self.grasp_obj_process_2.pid)
        kill_process_tree(self.grasp_obj_process_3.pid)
        self.grasp_obj_future = Future()

    cmd_1=['ros2', 'run', 'largemodel_arm', 'grasp_desktop']
    cmd_2=['ros2', 'run', 'largemodel_arm', 'KCF_follow']
    cmd_3=['ros2', 'run', 'M3Pro_KCF', 'ALM_KCF_Tracker_Node']

    self.grasp_obj_process_1=subprocess.Popen(cmd_1)
    time.sleep(5.0) #Waiting for grasp_desktop to finish starting up
    self.grasp_obj_process_2=subprocess.Popen(cmd_2)
    self.grasp_obj_process_3=subprocess.Popen(cmd_3)
    time.sleep(1.0)

    x1 = int(x1)
    y1 = int(y1)
    x2 = int(x2)
    y2 = int(y2)
    self.object_position_pub.publish(Int16MultiArray(data=[x1, y1, x2, y2]))

    while not self.grasp_obj_future.done():
        if self.interrupt_event.is_set():
            __reset_grasp_obj()
            self.pubSix_Arm(self.init_joints)
            return None
        time.sleep(0.1)

    result = self.grasp_obj_future.result()
    if not self.interrupt_event.is_set():
        if result.data == "grasp_obj_done":
            res = True
        else:
            res = False

    __reset_grasp_obj()
    if self.interrupt_event.is_set():
        time.sleep(0.5)
        self.pubSix_Arm(self.init_joints) # Robotic arm retracted
    return res
```

After the grasping is complete, the **KCF_follow** node will publish a signal on the **largemodel_arm_done** topic with the content "**grasp_obj_done**", which sets the **grasp_obj_future** object in the **largemodel_arm_done_callback** callback function.

```
def action_feedback_callback(self, msg:String):
    ''' 外部动作反馈回调函数 / External action feedback callback function '''
    if msg.data == "follow_line_finish":
        if not self.follow_line_clear_future.done():
            self.follow_line_clear_future.set_result(msg)
    elif msg.data == "road_net_nav_succeeded":
        if not self.road_net_nav_future.done():
            self.road_net_nav_future.set_result(msg)
    elif msg.data == "road_net_nav_failed":
        if not self.road_net_nav_future.done():
            self.road_net_nav_future.set_result(msg)
    if msg.data in ["apriltag_sort_done", "apriltag_sort_failed"]:
        if not self.apriltag_sort_future.done():
            self.apriltag_sort_future.set_result(msg)
    elif msg.data in
["apriltag_remove_higher_done", "apriltag_remove_higher_failed"]:
        if not self.apriltag_remove_higher_future.done():
            self.apriltag_remove_higher_future.set_result(msg)
    elif msg.data == "grasp_obj_done":
        if not self.grasp_obj_future.done():
            self.grasp_obj_future.set_result(msg)
    elif msg.data == "color_remove_higher_done":
        if not self.color_remove_higher_future.done():
            self.color_remove_higher_future.set_result(msg)
    elif msg.data == "follow_line_clear_future_done":
        if not self.follow_line_clear_future.done():
            self.follow_line_clear_future.set_result(msg)
```

4.2 Case Study 2

- The `set_cmdvel` function controls the robot's base movement by publishing the `cmd_vel` velocity topic.

```
def set_cmdvel(self, linear_x:str, linear_y:str, angular_z:str,
duration:str)->None:
    ''' 发布cmd_vel速度指令 / Publish cmd_vel velocity command '''
    linear_x = float(linear_x)
    linear_y = float(linear_y)
    angular_z = float(angular_z)
    duration = float(duration)
    twist = Twist()
    twist.linear.x = linear_x
    twist.linear.y = linear_y
    twist.angular.z = angular_z
    self._execute_action(twist, durationtime=duration)
    self.stop()
    return True
```

The `putdown` method is used to make the robotic arm put down the object it is holding.

```
def putdown(self):
    self.pubSix_Arm(self.putdown_joints) # Deployment of robotic arm
    time.sleep(4)
    self.pubSingle_Arm(6, 30, 1000) #The robotic arm opens its gripper and
    releases the object.
    time.sleep(3)
    self.pubSix_Arm(self.init_joints) # Robotic arm retracted
    return True
```

4.3 Case Study 3

- The `apriltag_remove_higher` method starts the external `grasp_desktop_remove` and `apriltag_remove_higher` nodes via a subprocess. This is an example from the robotic arm chapter demonstrating the removal of machine code at a specified height.

```
def apriltag_remove_higher(self, target_high):
    '''Remove machine code at the specified height.'''
    def __reset_apriltag_remove_higher():
        kill_process_tree(self.apriltag_remove_higher_process_1.pid)
        kill_process_tree(self.apriltag_remove_higher_process_2.pid)
        self.apriltag_remove_higher_future = Future()
    target_highf = float(target_high) / 100
    cmd_1=['ros2', 'run', 'largemodel_arm', 'grasp_desktop_remove']
    cmd_2=['ros2', 'run', 'largemodel_arm', 'apriltag_remove_higher', '--ros-
    args', '-p', f'target_high:={target_highf:.2f}']
    self.apriltag_remove_higher_process_1=subprocess.Popen(cmd_1)
    self.apriltag_remove_higher_process_2=subprocess.Popen(cmd_2)

    while not self.apriltag_remove_higher_future.done():
        if self.interrupt_event.is_set():
            __reset_apriltag_remove_higher()
            self.stop()
            self.pubSix_Arm(self.init_joints)
            return None
        time.sleep(0.1)

    result = self.apriltag_remove_higher_future.result()
    if not self.interrupt_event.is_set():
        if result.data == "apriltag_remove_higher_done":
            res=True
        elif result.data == "apriltag_remove_higher_failed":
            res= False

    __reset_apriltag_remove_higher()
    self.pubSix_Arm(self.init_joints)
    return res
```

