3-Step ML Auxiliary Variable Integration Using MplusAutomation

Adding Covariate and Distal Outcome Variables to Mixture Models

Adam Garber

September, 13, 2021

This R tutorial automates the 3-step ML axiliary variable procedure (Vermunt, 2010) using the MplusAutomation package (Hallquist & Wiley, 2018) to estimate models and extract relevant parameters. To learn more about auxiliary variable integration methods and why multi-step methods are necessary for producing un-biased estimates see Asparouhov & Muthén (2014). For an accessible description of the 3-step ML method applied in the context latent transition analysis see Nylund-Gibson et al. (2014). The BCH method (Bolck et al., 2004) can also be implemented with MplusAutomation (see tutorial; https://psyarxiv.com/wmfcj). Although the BCH outperforms the 3-step approach, in many applied contexts it cannot be implemented due to the estimation of negative weights.

The motivation for writing this tutorial is that conducting the 3-step manually is highly error prone as it requires pulling logit values estimated in the step-1 model and adding them in the model statement of the step-2 model (i.e., lots of copying & pasting). In contrast, this approach is fully replicable and provides clear documentation which translates to more reliable research.

If using this tutorial to automate the 3-step approach it would be greatly appreciated if you cite this resource:

Garber, A. C. (2021). 3-Step ML Auxiliary Variable Integration Using MplusAutomation. Retrieved from psyarxiv.com/phtxa

Associated Github repository here:

https://github.com/garberadamc/3step-ML-Method

Load packages

```
library(MplusAutomation) # Conduit between R & Mplus
library(glue) # Pasting R code into strings
library(here) # Location, location
```

"Manual 3-Step" ML Auxiliary Variable Integration Method

Step 1 - Estimate the unconditional model with all covariate & distal outcome variables mentioned in the auxiliary statement.

NOTE: In this example, Mplus input and output files are directed to the sub-folder 3step_mplus. Due to the fact that adding auxiliary variables is conducted after enumeration, generally other sub-folders will exist in the top-most Rproject folder such as enum_mplus, data, and figures.

```
m_step1 <- mplusObject(</pre>
 TITLE = "Step1 (MANUAL 3-STEP ML APPROACH)",
  VARIABLE =
   "categorical = X1 X2 X3 X5 X6;
    usevar = X1 X2 X3 X5 X6;
    classes = c(3);
    !!! All auxiliary variables to be considered in the final model should be listed here !!!
    auxiliary =
    COVAR1 DISTAL1 DISTAL2; ",
  ANALYSIS =
   "estimator = mlr;
   type = mixture;
    starts = 500 100;",
  SAVEDATA =
   "!!! This saved dataset will contain class probabilities and modal assignment columns !!!
    File=3step_savedata_012020.dat;
    Save=cprob;
    Missflag= 999;",
  MODEL = "",
  OUTPUT = "",
 PLOT =
    "type = plot3;
    series = X1 X2 X3 X5 X6(*);",
  usevariables = colnames(example_data),
  rdata = example_data)
m_step1_fit <- mplusModeler(m_step1,</pre>
                 dataout=here("3step_mplus", "Step1_3step.dat"),
                 modelout=here("3step_mplus", "Step1_3step.inp") ,
                 check=TRUE, run = TRUE, hashfilename = FALSE)
```

Step 2 - Extract logits & saved data from the step 1 unconditional model.

Extract logits for the classification probabilities for the most likely latent class

Extract saved data from the step 1 model mplusObject named "m step1 fit"

Rename the column in savedata for "C" and change to "N"

```
colnames(savedata)[colnames(savedata)=="C"] <- "N"
```

Step 3 (part 1) - Estimate the unconditional model with logits from step 2.

NOTE: This syntax is specific for a three-class model. For models with different numbers of classes the syntax will need to be adapted within the MODEL section. This model is estimated without auxiliary variables added for the purpose of checking the class proportions for shifting or coding errors. Users should check the output file and compare with the Step 1 model to check whether the class proportions are approximately the same.

```
m_step2 <- mplusObject(</pre>
  TITLE = "Step2 (MANUAL 3-STEP ML APPROACH)",
  VARIABLE =
 "nominal=N;
 USEVAR = n;
  missing are all (999);
  classes = c(3); ",
  ANALYSIS =
 "estimator = mlr;
 type = mixture;
  starts = 0;",
  MODEL =
    glue(
 "%C#1%
  [n#10{logit_cprobs[1,1]}];
  [n#20{logit_cprobs[1,2]}];
  %C#2%
  [n#10{logit_cprobs[2,1]}];
  [n#20{logit_cprobs[2,2]}];
 %C#3%
```

Step 3 (part 2) - Add covariates & distal outcomes to the model.

Estimate the final SEM Model - Moderation Example

Specification details:

- This example contains two distal outcomes (DISTAL1 & DISTAL2) and one binary covariate (COVAR1).
- Under each class-specific statement (e.g., %C#1%) the distal outcomes are mentioned to estimate the intercept parameters.
- Moderation is specified by mentioning the "outcome ON covariate;" syntax under each of the class-specific statements.
- Note that the binary covariate is centered so that reported distal means (intercepts) are estimated at the weighted average of COVAR1.

```
m_step3 <- mplusObject(
   TITLE = "Step3 (MANUAL 3-STEP ML APPROACH)",

VARIABLE =
   "nominal = N;
   usevar = n;
   missing are all (999);

usevar = COVAR1 DISTAL1 DISTAL2;
   classes = c(3); ",

DEFINE =
   "Center COVAR1 (Grandmean);",

ANALYSIS =</pre>
```

```
"estimator = mlr;
type = mixture;
starts = 0;",
MODEL =
glue(
"!!! OUTCOMES = DISTAL1 DISTAL2 !!!
!!! MODERATOR = COVAR1 !!!
%OVERALL%
DISTAL1 on COVAR1;
DISTAL1;
DISTAL2 on COVAR1;
DISTAL2;
%C#1%
[n#1@{logit_cprobs[1,1]}];
[n#20{logit_cprobs[1,2]}];
[DISTAL1] (m01);
DISTAL1;
                            !!! estimate conditional intercept !!!
DISTAL1 on COVAR1 (s01); !!! estimate conditional regression !!!
[DISTAL2] (m1);
DISTAL2;
DISTAL2 on COVAR1 (s1);
%C#2%
[n#1@{logit_cprobs[2,1]}];
[n#2@{logit_cprobs[2,2]}];
[DISTAL1] (m02);
DISTAL1;
DISTAL1 on COVAR1 (s02);
[DISTAL2] (m2);
DISTAL2;
DISTAL2 on COVAR1 (s2);
%C#3%
[n#10{logit_cprobs[3,1]}];
[n#2@{logit_cprobs[3,2]}];
[DISTAL1] (m03);
DISTAL1;
DISTAL1 on COVAR1 (s03);
[DISTAL2] (m3);
DISTAL2;
DISTAL2 on COVAR1 (s3);"),
MODELCONSTRAINT =
```

```
"New (diff12 diff13
  diff23 slope12 slope13
  slope23 ndiff12 ndiff13
  ndiff23 nslope12 nslope13
  nslope23);
  diff12 = m1-m2; ndiff12 = m01-m02;
  diff13 = m1-m3; ndiff13 = m01-m03;
  diff23 = m2-m3; ndiff23 = m02-m03;
  slope12 = s1-s2; nslope12 = s01-s02;
  slope13 = s1-s3; nslope13 = s01-s03;
  slope23 = s2-s3; nslope23 = s02-s03;",
  MODELTEST =
  ## NOTE: Only a single Wald test can be conducted per model run. Therefore,
  ## this example requires running separate models for each omnibus test (e.g.,
  ## 4 models; 2 outcomes and 2 slope coefficients). This can be done by
  ## commenting out all but one test and then estimating multiple versions of the model.
              !!! Distal outcome omnibus Wald test for `DISTAL2` !!!
 "m1=m2;
  m2=m3;
  !s1=s2;
              !!! Slope difference omnibus Wald test `DISTAL2 on COVAR1` !!!
  !s2=s3;
  !m01=m02;
              !!! Distal outcome omnibus Wald test for `DISTAL1` !!!
  !m02=m03;
              !!! Slope difference omnibus Wald test for `DISTAL2 on COVAR1` !!!
  !s01=s02;
  !s02=s03;",
  usevariables = colnames(savedata),
  rdata = savedata)
m_step3_fit <- mplusModeler(m_step3,</pre>
                 dataout=here("3step_mplus", "Step3_3step.dat"),
                 modelout=here("3step_mplus", "Step3_3step.inp"),
                 check=TRUE, run = TRUE, hashfilename = FALSE)
```

End of 3-Step Procedure

References:

Asparouhov, T., & Muthén, B. O. (2014). Auxiliary variables in mixture modeling: Three-step approaches using Mplus. Structural Equation Mod- eling, 21, 329-341. http://dx.doi.org/10.1080/ 10705511.2014.915181

Bolck, A., Croon, M., & Hagenaars, J. (2004). Estimating latent structure models with categorical variables: One-step versus three-step estimators. Political analysis, 12(1), 3-27.

Hallquist, Michael N., and Joshua F. Wiley. 2018. "MplusAutomation: An R Package for FacilitatingLarge-Scale Latent Variable Analyses in Mplus." Structural Equation Modeling, 1–18. https://doi.org/10.1080/

10705511.2017.1402334.

Müller, Kirill. 2017.Here: A Simpler Way to Find Your Files. https://CRAN.R-project.org/package=here.

Muthen L.K., & Muthen B.O. (1998-2017) Mplus User's Guide. Eight Edition. Los Angelos, CA: Muthen & Muthen.

Nylund-Gibson, K., Grimm, R., Quirk, M., & Furlong, M. (2014). A latent transition mixture model using the three-step specification. Structural Equation Modeling: A Multidisciplinary Journal, 21(3), 439-454.

R Core Team. 2019.R: A Language and Environment for Statistical Computing. Vienna, Austria: R Foundation for Statistical Computing. https://www.R-project.org/.

Vermunt, J. K. (2010). Latent class modeling with covariates: Two improved three-step approaches. Political analysis, 18(4), 450-469.

For more examples using MplusAutomation:

https://garberadamc.github.io/project-site/