

Moderation

Adam Garber

Norwegian University of Science and Technology - A Course in MplusAutomation

May 31, 2021

Lab preparation

Data source for example 1:

The first example utilizes the *Vocabulary and Education* dataset from the National Opinion Research Center General Social Survey. GSS Cumulative Datafile 1972-2016 (Fox, 2008) [See documentation here](#)

This dataset is available via the R-package `{carData}` and can be directly loaded into the R environment.

Note: All models specified in the following exercise are for demonstration only and are **not** theoretically justified or valid.

```
# equatiomatic is not yet on CRAN. Install the development version from GitHub with  
remotes::install_github("datalogorax/equatiomatic", force = TRUE)
```

```
library(tidyverse)  
library(MplusAutomation)  
library(rhdf5)  
library(here)  
library(gt)  
library(gtsummary)  
library(carData)  
library(Ecdat)
```

Change starting location to folder 14-moderation

```
source("rep_functions.R")  
  
change_here(glue("{project_location}/14-moderation"))  
  
here()
```

```
## [1] "/Users/agarber/github/NTNU-workshop/14-moderation"
```

Begin lab 2 exercise

Read the dataframe into your R-environment from package `{carData}`

```
data(Vocab)

vocab <- as.data.frame(Vocab)
```

Take a look at focal variables, make a `tribble` table

Name	Labels
year	Year of the survey
sex	Sex of the respondent (Female or Male)
education	Education, in years
vocabulary	Vocabulary test score: number correct on a 10-word test

check some basic descriptives with the `{gtsummary}` package


```
table1 <- tbl_summary(vocab,
  statistic = list(all_continuous() ~ "{mean} ({sd})"),
  missing = "no" ) %>%
  bold_labels()

table1
```

Characteristic	N = 30351
year	1995 (13)
sex	
Female	17148 (56%)
Male	13203 (44%)
education	13.0 (3.0)
vocabulary	6.00 (2.12)

Estimate moderation example 1

1. covariate: Years of education (**education**)
2. moderator: Year of the survey with 2-levels 1974 and 2016 (**year**)
3. outcome: Vocabulary test score - number correct on a 10-word test (**vocabulary**)



```
m1_model <- mplusObject(
  TITLE = "m1 model moderation",
  VARIABLE =
    "usevar =
      year          ! covariate/moderator
      education     ! covariate
      vocabulary    ! outcome
      int_yred;     ! interaction of year and education",
  DEFINE =
    "center education (grandmean);
     int_yred = year*education; ! create interaction term ",
  ANALYSIS =
    "estimator = MLR" ,
```

```

MODEL =
  "[vocabulary](b0);
  vocabulary on
  year(b1)
  education(b2)
  int_yred(b3); " ,

MODELCONSTRAINT =
  "LOOP(x,-1,1,0.01);
  PLOT(y1974 y2016);
  new(hi_y1974 lo_y1974 hi_y2016 lo_y2016 diff_hi);
  y1974 = b0 + b2*x;
  y2016 = b0 + b1 + (b2+b3)*x;

  hi_y1974 = b0 + b2*(6.28);  !!! education 2SD = 2*sqrt(9.85) = 6.28 !!!
  lo_y1974 = b0 + b2*(-6.28);
  hi_y2016 = b0 + b1 + (b2 + b3)*(6.28);
  lo_y2016 = b0 + b1 + (b2 + b3)*(-6.28);
  diff_hi = hi_y2016 - hi_y1974; ",

OUTPUT = "sampstat standardized modindices (3.84)",

PLOT = "type=plot3;",

usevariables = colnames(vocab2),
rdata = vocab2)

m1_model_fit <- mplusModeler(m1_model,
  dataout=here("mplus_files", "vocab.dat"),
  modelout=here("mplus_files", "model1_vocab.inp"),
  check=TRUE, run = TRUE, hashfilename = FALSE)

```

Create the simple slope plot from Mplus model output

Extract the output parameters generated using the `model constraint`

```

simp_slope <- data.frame(m1_model_fit[["results"]][["parameters"]][["unstandardized"]]) %>%
  filter(paramHeader == "New.Additional.Parameters") %>%
  filter(param != "DIFF_HI") %>%
  select(param, est, se) %>%
  mutate(year = case_when(
    param %in% c("HI_Y1974", "LO_Y1974") ~ "1974",
    param %in% c("HI_Y2016", "LO_Y2016") ~ "2016")) %>%
  mutate(education = case_when(
    param %in% c("HI_Y1974", "HI_Y2016") ~ 6.28,
    param %in% c("LO_Y1974", "LO_Y2016") ~ -6.28))


```

Plot the interaction effect with `ggplot` using theme from `{hrbrthemes}` package

```
# un-center 'education' so values on x-axis are on the original scale
plot_data <- simp_slope %>% mutate(education = education + 12.9)

ggplot(plot_data, aes(x=education, y=est, color=year, group=year)) +
  geom_point(size=0) +
  geom_line() +
  geom_errorbar(aes(ymin=est-se, ymax=est+se),
               width=.2) +
  scale_x_continuous(breaks = c(seq(6,20,2))) +
  labs(title = "Simple Slopes Graph",
       subtitle = "Vocabulary test score predicted by years of education in 1974 & 2016",
       x = "Education (years)",
       y = "Vocabulary test score") +
  theme_minimal()
```

```
ggsave(here("figures", "m1_simple_slope.png"), height = 6, width = 8)
```



Data source for example 2:

The next example utilizes the **Effects on Learning of Small Class Sizes (Star)** dataset from the *Introduction to Econometrics* textbook. (Stock et al., 2003) [See documentation here](#)

This dataset is available via the R-package {Ecdat} and can be directly loaded into the R environment.

Read the dataframe into your R-environment from package {Ecdat}

```
data(Star)


star_data <- as.data.frame(Star)
```

Take a look at the variables in the `Star` dataset

Name	Labels
tmathssk	total math scaled score
treadssk	total reading scaled score
classk	type of class (small, regular, regular with aide)
totexpk	years of total teaching experience

Subset and recode variables to use in moderation model with `select`, `mutate`, and `case_when`

```
mod_data <- star_data %>%
  select(totexpk, # years of total teaching experience
         classk, # type of class, a factor with levels (regular, small.class, regular.with.aide)
         tmathssk, treadssk) %>%
  mutate(classk = case_when(
    classk == "small.class" ~ "small.class",
    classk %in% c("regular.with.aide", "regular") ~ "regular")) %>%
  mutate(classk = fct_rev(classk))
```



Estimate moderation example 2

1. covariate: Years of education (`totexpk`)

2. moderator: type of class (small, regular) (`classk`)
 3. outcome 1: total math scaled score (`tmathssk`)
 4. outcome 2: total reading scaled score (`treadssk`)
-

```
m2_model <- mplusObject(
  TITLE = "m2 model indirect - Lab 3",
  VARIABLE =
    "usevar =
      totexpk classk
      tmathssk, treadssk
      tchXclas;  ",

  DEFINE =
    "center totexpk (grandmean);
      tchXclas = totexpk*classk;  ! create interaction term" ,

  ANALYSIS =
    "estimator = mlr; ",

  MODEL =
    "treadssk on classk totexpk tchXclas;

      [tmathssk] (b0);

      tmathssk on
      classk (b1)
      totexpk (b2)
      tchXclas (b3); ",

  MODELCONSTRAINT =
    "LOOP(x,-1,1,0.01);
      PLOT(small regular);
      new(hi_small lo_small hi_regular lo_regular diff_hi);
      small = b0 + b2*x;
      regular = b0 + b1 + (b2+b3)*x;

      hi_small = b0 + b2*(9.3);
      lo_small = b0 + b2*(-9.3);
      hi_regular = b0 + b1 + (b2 + b3)*(9.3);
      lo_regular = b0 + b1 + (b2 + b3)*(-9.3);
      diff_hi = hi_small - hi_regular; ",

  OUTPUT = "sampstat standardized modindices (3.84)",

  PLOT = "type=plot3;",

  usevariables = colnames(mod_data),
  rdata = mod_data)

m2_model_fit <- mplusModeler(m2_model,
  dataout=here("mplus_files", "caschools.dat"),
```

```
modelout=here("mplus_files", "model2_caschools.inp"),
check=TRUE, run = TRUE, hashfilename = FALSE)
```

Create the simple slope plot from Mplus model output

```
simp_slope2 <- data.frame(m2_model_fit[["results"]][["parameters"]][["unstandardized"]]) %>%
  filter(paramHeader == "New.Additional.Parameters") %>%
  filter(param!= "DIFF_HI") %>%
  select(param, est, se) %>%
  mutate(size = case_when(
    param %in% c("HI_SMALL", "LO_SMALL") ~ "Small",
    param %in% c("HI_REGUL", "LO_REGUL") ~ "Regular")) %>%
  mutate(experience = case_when(
    param %in% c("HI_SMALL", "HI_REGUL") ~ 9.3,
    param %in% c("LO_SMALL", "LO_REGUL") ~ -9.3))


# un-center 'experience' so values on x-axis are on the original scale
mean_exp <- mean(mod_data$totexpk)
plot_data2 <- simp_slope2 %>% mutate(experience = experience + mean_exp)

ggplot(plot_data2, aes(x=experience, y=est, color=size, group=size)) +
  geom_point(size=0) +
  geom_line() +
  geom_errorbar(aes(ymin=est-se, ymax=est+se), width=.25) +
  scale_x_continuous( breaks = c(seq(0,18,2))) +
  labs(title = "Simple Slopes Graph",
       subtitle = "Math test score predicted by years of teaching experience in small & regular classrooms",
       x = "Teaching Experience (years)",
       y = "Math test score") +
  theme_minimal()

ggsave(here("figures", "m2_simple_slope.png"), height = 6, width = 8)
```


Simple Slopes Graph

Math test score predicted by years of teaching experience in small & regular classrooms



End

References

- Hallquist, M. N., & Wiley, J. F. (2018). MplusAutomation: An R Package for Facilitating Large-Scale Latent Variable Analyses in Mplus. *Structural equation modeling: a multidisciplinary journal*, 25(4), 621-638.
- Horst, A. (2020). Course & Workshop Materials. GitHub Repositories, <https://allisonhorst.github.io/>
- Muthén, L.K. and Muthén, B.O. (1998-2017). *Mplus User's Guide*. Eighth Edition. Los Angeles, CA: Muthén & Muthén
- R Core Team (2017). R: A language and environment for statistical computing. R Foundation for Statistical Computing, Vienna, Austria. URL <http://www.R-project.org/>
- Wickham et al., (2019). Welcome to the tidyverse. *Journal of Open Source Software*, 4(43), 1686, <https://doi.org/10.21105/joss.01686>