

Introduction to Latent Profile Analysis (LPA)

A Course in `MplusAutomation`

Adam Garber




Figure. Gaussian mixture models. Data simulated from a 2-class model.

Preparation

Data source:

1. The first example closely follows the vignette used to demonstrate the `tidyLPA` package (Rosenberg, 2019): [See detailed documentation of this model here](#)

- This model utilizes the PISA data collected in the U.S. in 2015. To learn more about this data [see here](#).
- To access the 2015 US PISA data & documentation in R use the following code:

```
devtools::install_github("jrosen48/pisaUSA15"); library(pisaUSA15); open_codebook()
```

2. The second examples utilizes 4 test score measures from the public-use dataset, *The Longitudinal Survey of American Youth* (**LSAY**): [See documentation here](#)

Load packages

```
library(naniar)
library(tidyverse)
library(haven)
library(glue)
library(MplusAutomation)
library(here)
library(janitor)
library(gt)
library(tidyLPA)
```

Load data

```
pisa <- pisaUSA15
```

Latent Profile Analysis

Variance/covariance specification decisions in LPA modeling

$$\begin{bmatrix} \sigma_1^2 & \sigma_{21} & \sigma_{31} & \sigma_{41} \\ \sigma_{12} & \sigma_2^2 & \sigma_{23} & \sigma_{24} \\ \sigma_{13} & \sigma_{12} & \sigma_3^2 & \sigma_{33} \\ \sigma_{14} & \sigma_{12} & \sigma_{12} & \sigma_4^2 \end{bmatrix}$$

Figure. Picture of variance/covariance matrix adapted from tutorial by Rosenberg (2019).

- **model 1** Class-invariant / Diagonal: Equal variances, and covariances fixed to 0
- **model 2** Class-varying / Diagonal: Free variances and covariances fixed to 0
- **model 3** Class-invariant / Non-Diagonal: Equal variances and equal covariances
- **model 4** Free variances, and equal covariances
- **model 5** Equal variances, and free covariances
- **model 6** Class Varying / Non-Diagonal: Free variances and free covariances

Example 1: PISA dataset from the `tidyLPA` package

Enumerate using `estimate_profiles()`:

- Estimate models with classes $K = 1 : 3$
- Model has 4 continuous indicators
- Default variance-covariance specifications (model 1)
- Add line `scale() %>%` to center indicator means

```
lpa_models <- pisa[1:500,] %>%  
  select(broad_interest, enjoyment, instrumental_mot, self_efficacy) %>%  
  estimate_profiles(1:3,  
    package = "MplusAutomation",
```

```

ANALYSIS = "starts = 100, 20;",
variances = c("equal", "varying"),
covariances = c("zero", "varying"))

get_fit(lpa_models)

```


Plot 3-class model

Note: single imputation is used in this example as `plot_profiles()` requires complete cases

```


pisa[1:200,] %>%
  select(broad_interest, enjoyment, instrumental_mot, self_efficacy) %>%
  single_imputation() %>%
  estimate_profiles(3, package = "MplusAutomation") %>%
  plot_profiles(sd=FALSE)

```



Plot densities for classes $k = 1:4$

```
pisa[1:500, c("broad_interest", "enjoyment")] %>%
  single_imputation() %>%
  estimate_profiles(1:4, package = "MplusAutomation") %>%
  plot_density()
```



Example 2: Math, Science, Physics, and Biology measures (LSAY).

Read in data

```
lsay_data <- read_csv("https://garberadamc.github.io/project-site/data/lsay_lab10.2_lpa.csv")
```

Run a quick enumeration

```
lpa_k14 <- lapply(1:4, function(k) {
```

```

lpa_enum <- mplusObject(

  TITLE = glue("Class {k}"),

  VARIABLE = glue(
    "usevar = mth_scor-bio_scor;
    classes = c({k}); "),

  ANALYSIS =
    "estimator = mlr;
    type = mixture;
    starts = 200 50;
    processors = 10;",

  OUTPUT = "sampstat residual tech11 tech14;",

  PLOT =
    "type = plot3;
    series = mth_scor-bio_scor(*);",

  usevariables = colnames(lsay_data),
  rdata = lsay_data)

lpa_enum_fit <- mplusModeler(lpa_enum,
  dataout=here("15-LPA", "enum_lpa", "lpa_lsay.dat"),
  modelout=glue(here("15-LPA", "enum_lpa", "c{k}_lpa_lsay.inp")) ,
  check=TRUE, run = TRUE, hashfilename = FALSE)
})

```

Plot 3-class profile

```

lsay_data[1:500,5:8] %>%
  single_imputation() %>%
  estimate_profiles(1:4, package = "MplusAutomation") %>%
  plot_profiles(sd=FALSE)

```




Figure. Here we see ordered solutions.

Compare model fit.

```
all_output <- readModels(here("15-LPA", "enum_lpa"), quiet = TRUE)

enum_extract <- LatexSummaryTable(all_output,
  keepCols=c("Title", "Parameters", "LL", "BIC",
    "aBIC", "BLRT_PValue", "T11_VLMR_PValue"),
  sortBy = "Title")

enum_extract %>% gt()
```

Title	Parameters	LL	BIC	aBIC	BLRT_PValue	T11_VLMR_PValue
Class 1	8	-46288.29	92640.89	92615.47	NA	NA
Class 2	13	-43352.36	86809.23	86767.93	0	0
Class 3	18	-42126.11	84396.93	84339.74	0	0
Class 4	23	-41433.72	83052.37	82979.29	0	0

References

- Hallquist, M. N., & Wiley, J. F. (2018). MplusAutomation: An R Package for Facilitating Large-Scale Latent Variable Analyses in Mplus. *Structural equation modeling: a multidisciplinary journal*, 25(4), 621-638.
- Miller, J. D., Hoffer, T., Suchner, R., Brown, K., & Nelson, C. (1992). LSAY codebook. Northern Illinois University.
- Muthén, B. O., Muthén, L. K., & Asparouhov, T. (2017). *Regression and mediation analysis using Mplus*. Los Angeles, CA: Muthén & Muthén.
- Muthén, L.K. and Muthén, B.O. (1998-2017). *Mplus User's Guide*. Eighth Edition. Los Angeles, CA: Muthén & Muthén
- Rosenberg, J. M., van Lissa, C. J., Beymer, P. N., Anderson, D. J., Schell, M. J. & Schmidt, J. A. (2019). tidyLPA: Easily carry out Latent Profile Analysis (LPA) using open-source or commercial software [R package]. <https://data-edu.github.io/tidyLPA/>
- R Core Team (2017). *R: A language and environment for statistical computing*. R Foundation for Statistical Computing, Vienna, Austria. URL <http://www.R-project.org/>
- Wickham et al., (2019). Welcome to the tidyverse. *Journal of Open Source Software*, 4(43), 1686, <https://doi.org/10.21105/joss.01686>
-

Further resources & examples here:

<https://garberadamc.github.io/project-site/>
<https://www.adam-garber.com/>
