



Mega65Modular Low current DC/DC v0.1
gardners
License: CERN-OHL-S v2
Year: 2025

Page
CoverPage 1



VFB = 0.5V
R2 <= 100K. 91K recommended

$$\begin{aligned} R1 &= R2 \times (VOUT / VFB - 1) \\ 1.8V : \quad R1 &= R2 * (1.8 / 0.5 - 1) = R2 * 2.6 = 234K \\ 3.3V : \quad R1 &= R2 * (3.3 / 0.5 - 1) = R2 * 5.6 = 511K \end{aligned}$$

So SEL1V8 should tie FB to VOUT with a resistor that is parallel to 511K yields 234K.

$$\begin{aligned} 1/R_P &= 1/R + 1/R \\ 1/260K &= 1/R + 1/511K \\ 1/R &= 1/234K - 1/511K \\ 1/R &= -1/436K \\ R &= -436K \end{aligned}$$

Actual values = 90.9K, 510K, so VFB = 0.5V at junction means
VOUT = $(1 + 510K/90.9K) * 0.5V = 3.305V$
And with SEL1V8 tied to VOUT:
 $1/R = 1/510K + 1/432K = 233.8K$
 $VOUT = (1 + 233.8K/90.9K) * 0.5V = 1.79V$
Close enough...

3D top side

CERN-OHL-S v2
gardners
Sheet: /
File: megaphone-low-current-dc-dc-converter.kicad_sch
Title: Mega65Modular Low current DC/DC
Size: A4 Date: 2025-11-10
KiCad E.D.A. 9.0.1 Rev: v0.1
Id: 1/1