Testing Like A Boss

Arkady Galyash

TosChart

May 1, 2014

Agenda

1. How regular JUnit test looks like (in time)?
2. Links

Intro

- John Doe The Programmer
- Java developer @ Moon Ms
- Since 2000
- Binary search algorithm

June 2000



Just graduated, "tests are for chicken"

May 2001



JUnit discovered

July 2006

User tries to search non-existant element

December 2007

User tries to search in array with duplicates

October 2009

Integer overflow

Long way



2000 2001 2006 2007 2009

simpleTest

missingTest

sameTest

hugeArrayTest

xUnit

- Design tests example by example
- Test suites give us confidence that code works for the examples we thought of
- If we discover a test case, this test is useless right now, it may be useful only in future
- "Don't ask, don't tell"

QuickCheck

- Another approach
- You specify actions and post-conditions
- Let computer generate input data
  (he will not forget about corner cases)

QuickCheck History

- Initially written for Haskell in 1999
- By Koen Claessen and John Hughes
- BSD-style License

QuickCheck implementations



QuickCheck implementations



junit-quickcheck

- Based on `org.junit.contrib.theories.*`
- Annotation-based
- MIT License

JUnit Theory

- Experimental JUnit feature
- `@RunWith(Theories.class)`
- `@Theory`, `@DataPoint`, `@DataPoints`

Demo


We Can Check It!
POST FEB. 15 TO FEB. 28
WAR PRODUCTION CO-ORDINATING COMMITTEE

Links

- Introduction to QuickCheck2

Thank you!


DONE WITH MY PRESENTATION
NOW I HAVE TO ANSWER QUESTIONS
Troll.me