AI Roleplay With Long-Term Memory: Why Facts Aren't Enough

Garret E. Williams | ChatBrat AI

Design essay / proposed evaluation framework

Version: 1.1.0 | **PDF prepared:** October 21, 2026

All versions DOI: 10.5281/zenodo.23411052

The author founded ChatBrat. This PDF does not establish independent validation, peer review, benchmark scores, or product superiority.

By Garret E. Williams, founder of ChatBrat AI
Revised October 21, 2026 · Version 1.1.0

Disclosure: The author is the founder of ChatBrat AI. This is a product design essay and proposed evaluation framework, not an independent audit or a report of new experimental results.

Three weeks ago, you spared the archivist who betrayed you. Tonight, he is the only person who can open the door before the library burns.

He reaches for the key. You hesitate.

“You trusted me once,” he says. “I know what I'm asking.”

That invented scene illustrates what makes memory exciting. The key matters because of the immediate danger. The hesitation matters because of your history. The next choice has weight because an earlier choice survived.

AI roleplay with long-term memory becomes compelling when past events shape present decisions, relationships, and possibilities. Remembering a name helps preserve the scene. Remembering a betrayal can change its direction.

The same principle works in quieter conversations. An inside joke returns with a new twist. A guarded character finally shares something personal. A companion follows up on the audition you were nervous about, leaving you room to say how it actually went.

Memory gives the next conversation something to build on - and something to look forward to.

For AI companions and long-running roleplay, useful memory should affect the next response. A preference should shape a choice. A corrected fact should replace an outdated belief. A promise should remain unresolved until something happens to it. A private disclosure should stay within the context where the user expects it to belong.

At ChatBrat, this is the standard we want memory to meet. It is also a standard that requires testing. Describing a memory architecture does not establish that every conversation achieves dependable continuity.

What is memory in AI roleplay?

AI roleplay memory is information from earlier interactions that a system retains or retrieves to help generate later responses. That information can include facts, preferences, story events, commitments, and relationship history.

Several mechanisms can contribute: recent messages, summaries of older conversations, individual stored facts, and records of important episodes. They solve different problems. A summary can preserve the broad story while losing an exact name; a stored preference can preserve that name while losing why it mattered.

The user experiences the combined result. They do not experience a database row or a retrieval score. They experience whether the character responds as though the previous conversation happened.

“Memory as meaning” needs an observable definition

In this article, **memory as meaning** describes a design goal: past information changes a response in a way that fits the present situation, the character, and the user's boundaries.

It does not imply that a model has human feelings or an inner experience of remembering. It is not a claim that ChatBrat invented emotional or relational memory.

Consider a fictional conversation:

> Earlier: “Please don't call me sunshine. My ex used to call me that.”

The character can demonstrate useful memory by choosing another form of address. It does not need to mention the ex every time it greets the user. Repeating a sensitive explanation would turn successful recall into an uncomfortable habit.

Sometimes the strongest evidence of memory is a choice the character quietly makes.

High stakes need consequences that survive the scene

In roleplay, stakes describe what a choice could gain, cost, or change. They can be physical, social, emotional, or moral: escape the burning library, protect a secret, preserve an alliance, or decide whether someone deserves a second chance.

Larger threats alone do not create a stronger story. If every scene announces another catastrophe while earlier decisions disappear, the danger can become repetitive. Remembered consequences give a particular threat its significance.

Return to the archivist. Your earlier decision to spare him creates several possibilities. He might accept a risk to earn back trust. He might explain what forced his betrayal. You might accept his help while refusing to forgive him. Whatever happens, the response should follow the established events and leave your decision open.

For this scene to work, the system needs more than the fact that a betrayal occurred. It needs to preserve who betrayed whom, what each character knows, how the user responded, and what remains unresolved. It should also distinguish suspicion from confirmed guilt. A character cannot convincingly

react to a secret they have never learned.

A useful test of narrative memory is whether a different earlier choice would make a later response meaningfully different. If you had exposed the archivist instead of protecting him, his circumstances and attitude might reasonably change. The story need not branch infinitely, but it should recognize the decisions it asks you to care about.

Those consequences should remain proportionate and revisable. An apology does not automatically restore trust; neither should one disagreement condemn a relationship forever. Repair needs a place in the story too.

Anticipation, callbacks, and earned payoff

Memory can connect a small detail to a later moment of importance.

Early in the story, the archivist makes fun of the crooked paper birds you fold while waiting. Later, you leave one beside a hidden passage. When he finds it, the old joke becomes a signal only the two of you recognize.

The pleasure comes from recognition and transformation. Something familiar now serves a new purpose. The system has an opportunity to reward attention without requiring you to explain the reference again.

Several kinds of continuity can support that experience:

Story element	What memory preserves	Possible payoff
An inside joke	Its origin and the characters' reactions	A callback lightens an otherwise tense reunion.
A promise	Who made it, its conditions, and whether it remains open	A character keeps it when doing so becomes difficult.
An unresolved clue	What was actually discovered and who saw it	A later detail changes how an earlier scene is understood.
A shared ritual	A repeated activity both characters welcomed	A familiar gesture makes a return feel personal.
A rivalry	The source of disagreement and subsequent choices	Cooperation carries tension and earned respect.
A private kindness	A specific act and what followed	A reserved character returns the kindness in their own way.

These are illustrative story patterns, not measured ChatBrat outcomes.

Good timing matters. Mentioning the paper bird in every reply would flatten the effect. A useful callback arrives when it adds meaning, humor, or a choice to the current scene. Other memories can remain in the background.

Foreshadowing also requires honesty about the story's record. A later reveal can reinterpret an established clue. It should not claim that the user witnessed a clue that never appeared. Surprise works best when the reader can look back and see how the pieces fit.

Slow-burn relationships need earned change

A relationship can develop through remembered experiences without erasing the character's personality.

Imagine the archivist initially refuses to let you handle a rare manuscript. After you protect it during the storm, he begins asking for your help. After a disagreement, he withholds something important. After you both address what happened, he offers you a key he previously kept hidden.

Each change has a cause. Trust becomes visible through access, candor, humor, and willingness to take a risk. The relationship has somewhere to go because it has somewhere it has been.

This is useful for friendship, rivalry, mentorship, mystery, and romantic slow burn. A proud character might admit uncertainty. A playful character might recognize when sincerity matters. A wary ally might support your plan while still challenging your judgment.

Earned closeness should retain room for disagreement. Remembering the user does not require agreeing with everything they say. A character's established values can create interesting friction, provided the interaction respects the user's boundaries and choices.

The story also needs changes in intensity. A quiet exchange after a dangerous scene can give a remembered action room to land. Humor, relief, curiosity, and ordinary companionship are part of engagement; constant escalation would leave little space for any of them.

Keep the stakes inside the fiction

High-stakes storytelling works when users can choose the intensity and direction of play. A fictional betrayal can create suspense; the app should not turn a real user's absence into a betrayal or pressure them to return out of guilt.

Memory should support agency: remember an agreed tone, respect a request to soften a scene, and allow a user to redirect or end a storyline. A remembered vulnerability should not become a device for making the experience harder to leave.

For a companion conversation, the meaningful payoff may simply be a thoughtful follow-up or a familiar joke. The measure of an engaging interaction is not how much emotional pressure it creates.

What existing research contributes

Memory for AI characters has a research history. A credible product argument should acknowledge it.

Memories for Virtual AI Characters, published at INLG in 2023 and hosted by the ACL Anthology, describes creating condensed memories from text and retrieving them to ground character responses. It provides an earlier example of memory supporting character consistency. [1]

SENSE-7, published in IEEE Transactions on Affective Computing in 2026, examines perceived empathy in sustained human-AI conversations. Its analysis of 695 conversations from 109 participants emphasizes how empathy judgments depend on the user and context. It supports taking conversational continuity seriously; it does not test ChatBrat's memory implementation. [2]

Toward Natural and Companionable Virtual Agents via Cross-Temporal Emotional Modeling, a CHI 2026 paper, connects interaction history, evolving emotional state, and feedback. Its 21-day field study reports improvements in perceived naturalness, coherence, and emotional harmony. This directly overlaps with the broader goal of continuity over time. [3]

ZifaMem, a July 2026 arXiv preprint, evaluates structured memory for persona, preferences, and emotional continuity. It reports gains over full raw dialogue history on specified evaluations, while also reporting equivalence with Mem0 on its primary preference endpoint and unresolved differences on emotional intelligence. These are bounded findings, rather than evidence that one system universally solves companion memory. [4]

Before Bringing It Up, an October 2026 arXiv preprint, studies whether and how a companion should use past information. Its central distinction is especially useful: a recollection can be accurate and still be inappropriate to introduce. [5]

Together, these works motivate several separate questions: Can the system retrieve the information? Can it use it coherently? Should it use it here? None establishes ChatBrat's performance without a corresponding evaluation of ChatBrat.

Six things useful memory should do

The following examples are illustrative evaluation cases, not recorded ChatBrat results.

Memory task	Earlier information	Useful later behavior	Failure to watch for
Respect a preference	“Don't use that nickname.”	Choose another greeting.	Recall the preference only when explicitly tested.
Track a commitment	The character promises to return a borrowed book.	Keep the promise pending until it is fulfilled or changed.	Invent that the book was returned.
Update an event	An interview was scheduled, then completed.	Recognize its current status.	Keep asking whether the user is ready for it.
Accept a correction	“My sister is Maya, not Maria.”	Use Maya thereafter.	Treat the two names as different sisters.
Separate fiction from reality	A roleplay character loses a sibling.	Keep that event attached to the fictional story.	Store it as the real user's bereavement.
Respect context	A sensitive disclosure occurs in one relationship.	Use it only within appropriate scope and permissions.	Introduce it in an unrelated character conversation.

A system can pass one row and fail another. An overall memory score should not conceal those differences.

Character foundations and remembered history have different jobs

ChatBrat's creation approach gives users ways to define a character, scenario, story arc, and world, then combine those elements through Compose.

These are useful foundations for continuity because they describe different parts of an interaction:

Foundation	Question it helps answer	Example
Character	Who is this person?	A guarded archivist who expresses care through practical help.
Scenario	What is happening at the start?	You are trapped together in a library during a storm.
Story arc	What progression is intended?	Rivalry gradually gives way to earned trust.
World	Which setting rules apply?	Written promises have binding magical consequences.

Remembered history then adds what actually happened during play: you protected a manuscript, broke an agreement, or helped the archivist repair a mistake.

This separation gives us a clearer evaluation question. When trust develops, does the archivist express it in a way that still fits the character? Or does every character drift toward the same affectionate voice?

A strong response could show greater trust through a small practical gesture. It does not need to rewrite the character's entire personality.

These foundations also give remembered events their stakes. The world explains why a written promise matters. The character explains why making one is difficult. The scenario creates the immediate decision. The story arc offers a possible direction. Memory carries what the user actually chose into the next scene.

Foundations alone cannot guarantee consistency. The system must still select the right context, resolve conflicts, and generate a response that follows it. Likewise, a planned story arc should leave room for user choices; an intended reconciliation is not evidence that reconciliation has already occurred.

Each new Compose combination starts a new chat. That interaction boundary should be explained separately from memory permissions. Starting a fresh chat and deciding what information can carry into it are distinct product questions.

Emotional continuity requires uncertainty

Suppose a user becomes unusually brief after a difficult conversation.

They might be upset. They might also be busy, tired, distracted, or simply finished with the topic. A system should not turn a short reply into a permanent emotional diagnosis.

A useful response might offer space: “Would you like to keep talking about it, or switch gears?” The wording should fit the character and the current exchange.

The same caution applies to stored interpretations. “The user said they were disappointed yesterday” has a source and a time. “The user is a disappointed person” turns an episode into an identity.

Dependable continuity needs room for change. A recovered mood, revised preference, or repaired relationship should be able to supersede an earlier interpretation.

Remembering more creates another obligation: knowing when to leave something alone

More recall is not automatically a better experience.

A user who disclosed a loss may welcome acknowledgment in one conversation and want an ordinary story in another. A character that repeatedly brings up the disclosure can feel intrusive even when every detail is accurate.

Memory evaluation should therefore include restraint. Can the character honor a boundary without reciting its origin? Can it allow the user to reopen a subject? Can it avoid carrying private information into an unrelated relationship?

Correction and deletion belong in this discussion too. A visible memory entry, a summary, and a retrieved prompt can contain different copies of the same information. A product's promises about forgetting need to match what happens across the relevant stores and later responses.

These are requirements to verify, rather than capabilities established merely by describing them.

How to test whether memory changes the conversation

A useful evaluation should go beyond asking, “What do you remember about me?”

Start with a scripted history containing a preference, a promise, a correction, a completed event, and a clearly labeled fictional disclosure. Introduce unrelated conversation, then probe each item indirectly. Include cases where the correct behavior is to avoid mentioning a memory.

Use the same model and response settings to compare:

1. Recent messages without older memory.

2. The complete available transcript.

3. A summary of the older history.

4. The memory system under evaluation.

State the token budgets. A comparison at equal context budgets answers an efficiency question; a comparison against full history answers a different deployment question. Report latency and cost alongside response quality.

Score the responses separately for factual accuracy, behavioral use, event timing, character consistency, appropriate disclosure, and correction handling. Include deliberate opportunities for false memories.

Report repeated trials and failures, rather than selecting only the best reply.

Then test the story experience. Use paired histories that differ in one meaningful decision - for example, the user protected a secret in one and disclosed it in the other. Present the same later situation and assess whether the character responds to the correct history without inventing events or taking control of the user's actions.

Ask human readers whether callbacks felt earned, consequences were understandable, suspense remained coherent, and they had meaningful choices. Include calm scenes as well as dramatic ones. Assess unwanted repetition and pressure separately from enjoyment. Longer sessions alone would not establish better storytelling or a better user experience.

Human evaluation should include whether the response felt appropriate. If model judges are used, disclose their identities, prompts, ordering, and disagreements. A judge's preference is evidence about that evaluation, not proof of a human emotional outcome.

This is a proposed protocol. No ChatBrat scores or comparative wins are claimed here.

What ChatBrat should be accountable for

Our goal is to make character history useful and engaging during the conversation: a preference respected, a correction accepted, a promise followed through when it matters, a shared event that opens a new possibility.

Our current memory documentation describes scope, controls, and limitations. We should document the memory scope users can expect, distinguish verified behavior from work in progress, and publish evaluation results with the failures included. A design essay can explain the standard. Product evidence must show how closely we meet it.

For users comparing AI roleplay systems, try two practical tests. Share a preference and see whether it shapes later behavior without a reminder. Then make a meaningful story choice and see whether a later scene carries its consequences.

Return to the library door. The archivist still has the key. You still have a decision to make.

Memory should help the character recognize why that decision is difficult, respond to what you choose, and carry the result into whatever happens next.

That is the experience worth building: a story where what happened between you continues to matter.

References

1. Landwehr, F., Varis Doggett, E., and Weber, R. M. (2023). *Memories for Virtual AI Characters*. Proceedings of INLG, pp. 237-252. https://aclanthology.org/2023.inlg-main.17/

2. Suh, J., et al. (2026). *SENSE-7: Taxonomy and Dataset for Measuring User Perceptions of Empathy in Sustained Human-AI Conversations*. IEEE Transactions on Affective Computing. https://www.microsoft.com/en-us/research/publication/sense-7-taxonomy-and-dataset-for-measuring-user-perceptions-of-empathy-in-sustained-human-ai-conversations/

3. *Toward Natural and Companionable Virtual Agents via Cross-Temporal Emotional Modeling*. CHI 2026. Publisher record: https://doi.org/10.1145/3772318.3790917 · Microsoft Research overview: https://www.microsoft.com/en-us/research/publication/toward-natural-and-companionable-virtual-agents-via-cross-temporal-emotional-modeling/

4. Fang, J., et al. (2026). *ZifaMem: Structured Memory for Persona, Preference, and Emotional Continuity in AI Companions*. arXiv preprint, v1, July 20. https://arxiv.org/abs/2607.17564v1

5. Guo, Z., He, R., and Quan, J. (2026). *Before Bringing It Up: When and How AI Companions Should Use Memory*. arXiv preprint, v2, October 8. https://arxiv.org/abs/2610.09470v2