

Fitter Resource Usage Summary

 <<Filter>>

	Resource	Usage
1	▼ Total logic elements	428 / 114,480 (< 1 %)
1	-- Combinational with no register	53
2	-- Register only	172
3	-- Combinational with a register	203
2		
3	▼ Logic element usage by number of LUT inputs	
1	-- 4 input functions	197
2	-- 3 input functions	40
3	-- <=2 input functions	19
4	-- Register only	172
4		
5	▼ Logic elements by mode	
1	-- normal mode	219
2	-- arithmetic mode	37
6		
7	▼ Total registers*	375 / 117,053 (< 1 %)
1	-- Dedicated logic registers	375 / 114,480 (< 1 %)
2	-- I/O registers	0 / 2,573 (0 %)
8		
9	Total LABs: partially or completely used	48 / 7,155 (< 1 %)
10	Virtual pins	0

	Resource	Usage
11	▼ I/O pins	38 / 529 (7 %)
1	-- Clock pins	1 / 7 (14 %)
2	-- Dedicated input pins	0 / 9 (0 %)
12		
13	M9Ks	0 / 432 (0 %)
14	Total block memory bits	0 / 3,981,312 (0 %)
15	Total block memory implementation bits	0 / 3,981,312 (0 %)
16	Embedded Multiplier 9-bit elements	2 / 532 (< 1 %)
17	PLLs	0 / 4 (0 %)
18	▼ Global signals	1
1	-- Global clocks	1 / 20 (5 %)
19	JTAGs	0 / 1 (0 %)
20	CRC blocks	0 / 1 (0 %)
21	ASMI blocks	0 / 1 (0 %)
22	Oscillator blocks	0 / 1 (0 %)
23	Impedance control blocks	0 / 4 (0 %)
24	Average interconnect usage (total/H/V)	0.1% / 0.1% / 0.1%
25	Peak interconnect usage (total/H/V)	3.4% / 3.5% / 3.3%
26	Maximum fan-out	377
27	Highest non-global fan-out	273
28	Total fan-out	2296

* Register count does not include registers inside RAM blocks or DSP blocks.