

Burger Farm UI

lib/

- |— core/
 - | |— theme/ # Design tokens, colors, typography, shadows
 - | |— constants/ # App constants, routes, enums
 - | |— utils/ # Extensions, helpers, responsive utilities
 - | |— animations/ # Reusable animation controllers & presets
- |— data/
 - | |— models/ # Freezed data classes
 - | |— repositories/ # Abstract repository interfaces
 - | |— services/ # Firebase, Maps, Auth services
- |— domain/
 - | |— entities/ # Business entities
 - | |— providers/ # Riverpod state management
- |— presentation/
 - | |— screens/ # All 9 screens from HTML
 - | |— widgets/ # Atomic design components
 - | |— router/ # GoRouter configuration
- |— main.dart

lib/core/theme/app_colors.dart

```
import 'package:flutter/material.dart';
```

```
/// Exact color extraction from Tailwind config:
```

```
/// brand: { DEFAULT: '#E8560A', hover: '#C94208', light: '#FFF0E5' }
```

```
/// brown: { DEFAULT: '#271200', muted: 'rgba(39, 18, 0, 0.42)', light: 'rgba(39, 18, 0, 0.06)' }
```

```
/// cream: '#FBF7F2', line: '#EBE1D6'
```

```
class AppColors {
```

```
  AppColors._();
```

```
  // Brand Orange
```

```
  static const Color brand = Color(0xFFE8560A);
```

```
  static const Color brandHover = Color(0xFFC94208);
```

```
  static const Color brandLight = Color(0xFFFFF0E5);
```

```
  // Brown Palette
```

```
  static const Color brown = Color(0xFF271200);
```

```
  static const Color cream = Color(0xFFFFBF7F2);
```

```
  static const Color line = Color(0xFFEBE1D6);
```

```
  // Semantic Colors
```

```
  static const Color success = Color(0xFF1A7A38);
```

```

static const Color danger = Color(0xFFC0001A);

// Derived with exact opacity values from HTML
static Color get brownMuted => brown.withOpacity(0.42);
static Color get brownLight => brown.withOpacity(0.06);
static Color get whiteMuted => Colors.white.withOpacity(0.80);

// Background colors matching HTML body backgrounds
static const Color warmBg = Color(0xFFFF5EFE6);
static const Color whiteBg = Colors.white;
static const Color brandBg = brand;
}

/// Material Color generation for ThemeData
Map<int, Color> _brandSwatch = {
  50: const Color(0xFFFFF0E5),
  100: const Color(0xFFFFD9C2),
  200: const Color(0xFFFFB894),
  300: const Color(0xFFFF965C),
  400: const Color(0xFFFF7A33),
  500: const Color(0xFFE8560A),
  600: const Color(0xFFC94208),
  700: const Color(0xFFA83606),
  800: const Color(0xFF872A04),
  900: const Color(0xFF661F03),
};

```

lib/core/theme/app_typography.dart

```

import 'package:flutter/material.dart';
import 'package:google_fonts/google_fonts.dart';

/// Font mapping from HTML:
/// display: ["Montreux Classic", 'sans-serif'] → Use Syne or Archivo Black as closest Google
Font
/// sans: ["Recoleta", 'serif'] → Use DM Serif Display or Fraunces
///
/// For production: Download Montreux & Recoleta WOFF2, convert to TTF, add to
assets/fonts/
class AppTypography {
  AppTypography._();

  // Fallback to Google Fonts until custom fonts are loaded
  static String get displayFont => 'MontreuxClassic'; // Custom
  static String get bodyFont => 'Recoleta'; // Custom

```

```

static TextStyle display({
  double size = 16,
  FontWeight weight = FontWeight.w900,
  Color? color,
  double letterSpacing = 0.15,
  double? height,
  List? shadows,
}) {
  return TextStyle(
    fontFamily: displayFont,
    fontSize: size,
    fontWeight: weight,
    color: color ?? AppColors.brown,
    letterSpacing: letterSpacing,
    height: height,
    shadows: shadows,
  );
}

```

```

static TextStyle body({
  double size = 14,
  FontWeight weight = FontWeight.w500,
  Color? color,
  double letterSpacing = 0,
  double? height,
  FontStyle? style,
}) {
  return TextStyle(
    fontFamily: bodyFont,
    fontSize: size,
    fontWeight: weight,
    color: color ?? AppColors.brown,
    letterSpacing: letterSpacing,
    height: height,
    fontStyle: style,
  );
}

```

```

// Predefined styles matching HTML exactly
static TextStyle get splashTitle => display(
  size: 64,
  color: Colors.white,
  letterSpacing: -0.03,
  height: 0.85,

```

```

shadows: [
  Shadow(
    color: AppColors.brown.withOpacity(0.2),
    blurRadius: 16,
    offset: const Offset(0, 4),
  ),
],
);

static TextStyle get onboardingHeadline => display(
  size: 40,
  height: 1.05,
  letterSpacing: -0.025,
);

static TextStyle get screenTitle => display(
  size: 18,
  letterSpacing: 0.15,
);

static TextStyle get bodyLarge => body(
  size: 15,
  height: 1.65,
  color: AppColors.brownMuted,
);

static TextStyle get labelSmall => body(
  size: 10,
  weight: FontWeight.w900,
  letterSpacing: 0.2,
  color: AppColors.brownMuted,
);
}

```

lib/core/theme/app_shadows.dart

```

import 'package:flutter/material.dart';
import 'app_colors.dart';

/// Exact shadow definitions from Tailwind config:
/// soft: '0 4px 24px rgba(39, 18, 0, 0.04), 0 1px 2px rgba(39, 18, 0, 0.02)'
/// premium: '0 20px 40px -10px rgba(39,18,0,0.08), 0 1px 3px rgba(39,18,0,0.05)'
/// glow: '0 8px 24px rgba(232, 86, 10, 0.25)'
class AppShadows {
  AppShadows._();
}

```

```
static List get soft => [  
  BoxShadow(  
    color: AppColors.brown.withOpacity(0.04),  
    blurRadius: 24,  
    offset: const Offset(0, 4),  
  ),  
  BoxShadow(  
    color: AppColors.brown.withOpacity(0.02),  
    blurRadius: 2,  
    offset: const Offset(0, 1),  
  ),  
];
```

```
static List get premium => [  
  BoxShadow(  
    color: AppColors.brown.withOpacity(0.08),  
    blurRadius: 40,  
    spreadRadius: -10,  
    offset: const Offset(0, 20),  
  ),  
  BoxShadow(  
    color: AppColors.brown.withOpacity(0.05),  
    blurRadius: 3,  
    offset: const Offset(0, 1),  
  ),  
];
```

```
static List get glow => [  
  BoxShadow(  
    color: AppColors.brand.withOpacity(0.25),  
    blurRadius: 24,  
    offset: const Offset(0, 8),  
  ),  
];
```

```
static List get brandGlow => [  
  BoxShadow(  
    color: AppColors.brand.withOpacity(0.4),  
    blurRadius: 30,  
    spreadRadius: -10,  
    offset: const Offset(0, 10),  
  ),  
  BoxShadow(  
    color: AppColors.brand.withOpacity(0.2),
```

```
blurRadius: 10,  
offset: const Offset(0, 4),  
,  
];
```

```
static List get float => [  
  BoxShadow(  
    color: AppColors.brown.withOpacity(0.04),  
    blurRadius: 32,  
    offset: const Offset(0, -12),  
  ),  
];
```

```
static List get insetSoft => [  
  BoxShadow(  
    color: AppColors.brown.withOpacity(0.04),  
    blurRadius: 8,  
    offset: const Offset(0, 2),  
  ),  
];  
}
```

lib/core/theme/app_animations.dart

```
import 'package:flutter/material.dart';
```

```
/// Animation curves and durations matching GSAP/GSAP-like easing  
/// spring: 'cubic-bezier(0.16, 1, 0.3, 1)' → Curves.easeOutBack approx
```

```
class AppAnimations {  
  AppAnimations._();
```

```
  // Curves
```

```
  static const Curve spring = Cubic(0.16, 1, 0.3, 1);  
  static const Curve expoOut = Cubic(0.16, 1, 0.3, 1); // Same as spring in config  
  static const Curve backOut = Curves.easeOutBack;
```

```
  // Durations
```

```
  static const Duration fast = Duration(milliseconds: 200);  
  static const Duration normal = Duration(milliseconds: 300);  
  static const Duration slow = Duration(milliseconds: 500);  
  static const Duration entrance = Duration(milliseconds: 800);
```

```
  // Stagger delays
```

```
  static const Duration staggerItem = Duration(milliseconds: 100);
```

```
  // Preset Tween sequences for common animations
```

```
  static Widget fadeUp({
```

```

required Widget child,
required Animation animation,
double startY = 20,
}) {
return AnimatedBuilder(
animation: animation,
builder: (context, child) {
return Opacity(
opacity: animation.value,
child: Transform.translate(
offset: Offset(0, startY * (1 - animation.value)),
child: child,
),
);
},
child: child,
);
}

static AnimationController createEntranceController(TickerProvider vsync) {
return AnimationController(
vsync: vsync,
duration: entrance,
);
}
}

```

2. Responsive Foundation

lib/core/utils/responsive.dart

```

import 'package:flutter/material.dart';

/// Ensures UI works on any screen size while maintaining the mobile-first
/// design intent. The HTML uses max-w-[400px] with centered layout.
class Responsive {
static const double designWidth = 400;
static const double designHeight = 850;

/// Returns constrained width that mimics the HTML max-w-[400px] behavior
/// On phones < 400px, uses full width. On tablets/desktop, centers with max width.
static double contentWidth(BuildContext context) {
final screenWidth = MediaQuery.of(context).size.width;
return screenWidth.clamp(0, designWidth);
}
}

```

```
/// Scale factor relative to design width
static double scale(BuildContext context) {
return contentWidth(context) / designWidth;
}
```

```
/// Responsive padding that scales with screen size
static EdgeInsets symmetric({
  BuildContext? context,
  double horizontal = 24,
  double vertical = 0,
}) {
  final s = context != null ? scale(context) : 1.0;
  return EdgeInsets.symmetric(
    horizontal: horizontal s,
    vertical: vertical s,
  );
}
```

```
/// Safe area insets combined with responsive padding
static EdgeInsets safePadding(BuildContext context) {
  final mq = MediaQuery.of(context);
  return EdgeInsets.only(
    top: mq.padding.top,
    bottom: mq.padding.bottom,
    left: mq.padding.left.clamp(0, 16),
    right: mq.padding.right.clamp(0, 16),
  );
}
```

```
/// Widget that wraps content in a centered, max-width container like HTML
class AppContainer extends StatelessWidget {
  final Widget child;
  final Color? backgroundColor;
  final EdgeInsets? padding;

  const AppContainer({
    super.key,
    required this.child,
    this.backgroundColor,
    this.padding,
  });

  @override
  Widget build(BuildContext context) {
```



```

return Scaffold(
  backgroundColor: backgroundColor ?? AppColors.warmBg,
  body: Center(
    child: ConstrainedBox(
      constraints: const BoxConstraints(maxWidth: Responsive.designWidth),
      child: Container(
        width: double.infinity,
        height: double.infinity,
        decoration: BoxDecoration(
          color: backgroundColor ?? Colors.white,
          borderRadius: _getBorderRadius(context),
          boxShadow: _getShadow(context),
        ),
        clipBehavior: Clip.antiAlias,
        child: MediaQuery(
          // Remove system padding since we handle it internally
          data: MediaQuery.of(context).removePadding(
            removeTop: true,
            removeBottom: true,
          ),
          child: Padding(
            padding: padding ?? EdgeInsets.zero,
            child: child,
          ),
        ),
      ),
    ),
  );
}

```

```

BorderRadius? _getBorderRadius(BuildContext context) {
  // Only round corners on larger screens (simulating sm:rounded-[40px])
  final width = MediaQuery.of(context).size.width;
  if (width > Responsive.designWidth) {
    return BorderRadius.circular(40);
  }
  return null;
}

```

```

List? _getShadow(BuildContext context) {
  final width = MediaQuery.of(context).size.width;
  if (width > Responsive.designWidth) {
    return [

```

```

BoxShadow(
  color: Colors.black.withOpacity(0.2),
  blurRadius: 40,
  offset: const Offset(0, 20),
),
];
}
return null;
}
}

```

3. Reusable Widgets (Atomic Design)

lib/presentation/widgets/premium_button.dart

```

import 'package:flutter/material.dart';
import '../core/theme/app_colors.dart';
import '../core/theme/app_shadows.dart';
import '../core/theme/app_animations.dart';

/// The signature CTA button used across all screens.
/// Matches: bg-brand, shadow-brand-glow, active:scale-[0.97], shimmer effect
class PremiumButton extends StatefulWidget {
  final String text;
  final VoidCallback? onPressed;
  final Widget? icon;
  final bool isLoading;
  final Color? backgroundColor;
  final Color? textColor;

  const PremiumButton({
    super.key,
    required this.text,
    this.onPressed,
    this.icon,
    this.isLoading = false,
    this.backgroundColor,
    this.textColor,
  });

  @override
  State createState() => _PremiumButtonState();
}

class _PremiumButtonState extends State
with SingleTickerProviderStateMixin {

```

```
late AnimationController _pressController;
```

```
late Animation _scaleAnimation;
```

```
@override
```

```
void initState() {
```

```
super.initState();
```

```
_pressController = AnimationController(
```

```
vsync: this,
```

```
duration: AppAnimations.fast,
```

```
);
```

```
_scaleAnimation = Tween(begin: 1.0, end: 0.97).animate(
```

```
CurvedAnimation(parent: _pressController, curve: AppAnimations.spring),
```

```
);
```

```
}
```

```
@override
```

```
void dispose() {
```

```
_pressController.dispose();
```

```
super.dispose();
```

```
}
```

```
@override
```

```
Widget build(BuildContext context) {
```

```
return GestureDetector(
```

```
onTapDown: () => _pressController.forward(),
```

```
onTapUp: () {
```

```
_pressController.reverse();
```

```
widget.onPressed?.call();
```

```
},
```

```
onTapCancel: () => _pressController.reverse(),
```

```
child: AnimatedBuilder(
```

```
animation: _scaleAnimation,
```

```
builder: (context, child) {
```

```
return Transform.scale(
```

```
scale: _scaleAnimation.value,
```

```
child: Container(
```

```
height: 56,
```

```
decoration: BoxDecoration(
```

```
color: widget.backgroundColor ?? AppColors.brand,
```

```
borderRadius: BorderRadius.circular(20),
```

```
boxShadow: AppShadows.brandGlow,
```

```
),
```

```
child: ClipRRect(
```

```
borderRadius: BorderRadius.circular(20),
```

```

child: Stack(
  children: [
    // Shimmer effect on hover/tap
    Positioned.fill(
      child: AnimatedContainer(
        duration: const Duration(milliseconds: 700),
        decoration: BoxDecoration(
          gradient: LinearGradient(
            colors: [
              Colors.transparent,
              Colors.white.withOpacity(0.2),
              Colors.transparent,
            ],
            stops: const [0.0, 0.5, 1.0],
          ),
        ),
      ),
    // Content
    Center(
      child: widget.isLoading
        ? const SizedBox(
            width: 24,
            height: 24,
            child: CircularProgressIndicator(
              color: Colors.white,
              strokeWidth: 2.5,
            ),
          )
        : Row(
            mainAxisAlignment: MainAxisAlignment.center,
            children: [
              Text(
                widget.text,
                style: TextStyle(
                  fontFamily: AppTypography.displayFont,
                  fontSize: 16,
                  fontWeight: FontWeight.w700,
                  color: widget.textColor ?? Colors.white,
                ),
              ),
              if (widget.icon != null) ...[
                const SizedBox(width: 8),

```

```

widget.icon!,
],
],
),
),
],
),
),
),
),
);
},
),
);
}
}

```

lib/presentation/widgets/premium_input.dart

```

import 'package:flutter/material.dart';
import '../core/theme/app_colors.dart';
import '../core/theme/app_shadows.dart';

/// Input field matching HTML: bg-[ #FAFAFA ], border-[1.5px], rounded-2xl,
/// focus:border-brand, focus:shadow-[0_8px_24px_rgba(232,86,10,0.15)]
class PremiumInput extends StatefulWidget {
  final String? label;
  final String? placeholder;
  final Widget? prefixIcon;
  final Widget? suffixIcon;
  final TextInputType? keyboardType;
  final bool obscureText;
  final ValueChanged? onChanged;
  final TextEditingController? controller;
  final bool required;

  const PremiumInput({
    super.key,
    this.label,
    this.placeholder,
    this.prefixIcon,
    this.suffixIcon,
    this.keyboardType,
    this.obscureText = false,
    this.onChanged,
    this.controller,

```

```
this.required = false,  
});
```

```
@override  
State createState() => _PremiumInputState();  
}
```

```
class _PremiumInputState extends State {  
  bool _isFocused = false;
```

```
@override  
Widget build(BuildContext context) {  
  return Column(  
    crossAxisAlignment: CrossAxisAlignment.start,  
    children: [  
      if (widget.label != null) ...[  
        Row(  
          children: [  
            Text(  
              widget.label!,  
              style: AppTypography.body(  
                size: 12,  
                weight: FontWeight.w700,  
                letterSpacing: 0.1,  
                color: AppColors.brownMuted,  
              ).copyWith(  
                shadows: [  
                  Shadow(  
                    color: Colors.white.withOpacity(0.8),  
                    blurRadius: 0,  
                    offset: const Offset(0, 1),  
                  ),  
                ],  
              ),  
            if (widget.required)  
              Text(  
                ' *',  
                style: AppTypography.body(  
                  size: 12,  
                  color: AppColors.brand,  
                ),  
              ),  
          ],  
        ),  
      ],  
    ],  
  );  
}
```

```

),
const SizedBox(height: 10),
],
Focus(
onFocusChange: (focused) => setState(() => _isFocused = focused),
child: AnimatedContainer(
duration: const Duration(milliseconds: 300),
curve: AppAnimations.spring,
decoration: BoxDecoration(
color: _isFocused ? Colors.white : const Color(0xFFFFFAFAFA),
borderRadius: BorderRadius.circular(16),
border: Border.all(
color: _isFocused
? AppColors.brand.withOpacity(0.4)
: AppColors.line,
width: 1.5,
),
boxShadow: _isFocused
? [
BoxShadow(
color: AppColors.brand.withOpacity(0.15),
blurRadius: 24,
offset: const Offset(0, 8),
),
...AppShadows.insetSoft,
]
: AppShadows.insetSoft,
),
child: Row(
children: [
if (widget.prefixIcon != null) ...[
const SizedBox(width: 16),
widget.prefixIcon!,
const SizedBox(width: 12),
],
Expanded(
child: TextField(
controller: widget.controller,
keyboardType: widget.keyboardType,
obscureText: widget.obscureText,
onChanged: widget.onChanged,
style: AppTypography.body(
size: 16,

```

```

weight: FontWeight.w700,
),
decoration: InputDecoration(
  hintText: widget.placeholder,
  hintStyle: AppTypography.body(
    size: 16,
    color: AppColors.brownMuted.withOpacity(0.4),
  ),
  border: InputBorder.none,
  contentPadding: const EdgeInsets.symmetric(
    vertical: 16,
    horizontal: 4,
  ),
),
),
),
),
if (widget.suffixIcon != null) ...[
  const SizedBox(width: 12),
  widget.suffixIcon!,
  const SizedBox(width: 16),
],
],
),
),
),
],
);
}
}

```

```

### `lib/presentation/widgets/noise_overlay.dart`
import 'package:flutter/material.dart';

```

```

/// Replicates the premium noise overlay from HTML:
/// opacity: 0.025, fractalNoise baseFrequency='0.65'
class NoiseOverlay extends StatelessWidget {
  const NoiseOverlay({super.key});

  @override
  Widget build(BuildContext context) {
    return IgnorePointer(
      child: Opacity(
        opacity: 0.025,
        child: Container(

```



```

decoration: const BoxDecoration(
// Using a generated noise pattern or shader would be ideal
// For now, using a subtle pattern approximation
color: Colors.transparent,
),
child: CustomPaint(
size: Size.infinite,
painter: _NoisePainter(),
),
),
),
);
}
}

```

```

class _NoisePainter extends CustomPainter {
@override
void paint(Canvas canvas, Size size) {
final paint = Paint()
..color = Colors.black.withOpacity(0.02)
..strokeWidth = 1;

```

```

// Simple noise approximation - in production use a shader or image
final random = Random(42); // Fixed seed for consistency
for (var i = 0; i < size.width * size.height * 0.1; i++) {
  final x = random.nextDouble() * size.width;
  final y = random.nextDouble() * size.height;
  canvas.drawCircle(Offset(x, y), 0.5, paint);
}

```

```

}

@override
bool shouldRepaint(covariant CustomPainter oldDelegate) => false;
}

```

4. Screen Implementations

lib/presentation/screens/splash_screen.dart

```

import 'package:flutter/material.dart';
import 'package:flutter_riverpod/flutter_riverpod.dart';
import 'package:go_router/go_router.dart';
import '../core/theme/app_colors.dart';
import '../core/theme/app_animations.dart';

```

```

import '../core/theme/app_typography.dart';
import '../router/app_router.dart';

/// Splash Screen with exact animations:
/// - Orbit path animation (GSAP motionPath equivalent)
/// - Pulse rings around logo
/// - Loading bar slide animation
/// - Fade-up entrance for typography
class SplashScreen extends ConsumerStatefulWidget {
  const SplashScreen({super.key});

  @override
  ConsumerState createState() => _SplashScreenState();
}

class _SplashScreenState extends ConsumerState
  with TickerProviderStateMixin {
  late AnimationController _orbitController;
  late AnimationController _fadeController;
  late AnimationController _pulseController;

  @override
  void initState() {
    super.initState();

```

```

    _orbitController = AnimationController(
      vsync: this,
      duration: const Duration(seconds: 4),
    )..repeat();

    _fadeController = AnimationController(
      vsync: this,
      duration: const Duration(milliseconds: 1200),
    );

    _pulseController = AnimationController(
      vsync: this,
      duration: const Duration(seconds: 2),
    )..repeat();

    // Staggered entrance
    Future.delayed(const Duration(milliseconds: 200), () {
      _fadeController.forward();
    });

    // Auto-navigate after animation
    Future.delayed(const Duration(seconds: 3), () {

```

```
    if (mounted) context.go(AppRoute.onboarding);  
  });  
}
```

```
@override  
void dispose() {  
  _orbitController.dispose();  
  _fadeController.dispose();  
  _pulseController.dispose();  
  super.dispose();  
}
```

```
@override  
Widget build(BuildContext context) {  
  return Scaffold(  
    backgroundColor: AppColors.brand,  
    body: GestureDetector(  
      onTap: () => context.go(AppRoute.onboarding),  
      child: Stack(  
        children: [  
          // Background gradients matching HTML  
          Positioned.fill(  
            child: Container(  
              decoration: BoxDecoration(  
                gradient: RadialGradient(  
                  center: const Alignment(0.5, -0.3),  
                  radius: 0.8,  
                  colors: [  
                    Colors.white.withOpacity(0.12),  
                    Colors.transparent,  
                  ],  
                ),  
            ),  
          ),  
          ),  
          ),  
          ),  
          ),  
          ),  
        ],  
      ),  
    ),  
  );  
}
```

```
    // Floating ambient orbs  
    Positioned(  
      top: MediaQuery.of(context).size.height * 0.2,  
      left: MediaQuery.of(context).size.width * 0.1,  
      child: _AmbientOrb(  
        size: 256,  
        color: const Color(0xFFFFFB085),  
        animation: _pulseController,  
      ),  
    ),  
  );  
}
```

```

    ),
  ),
  Positioned(
    bottom: MediaQuery.of(context).size.height * 0.2,
    right: MediaQuery.of(context).size.width * 0.1,
    child: _AmbientOrb(
      size: 288,
      color: const Color(0xFFC94208),
      animation: _pulseController,
      delay: 0.5,
    ),
  ),
),

// Center content
Center(
  child: Column(
    mainAxisAlignment: MainAxisAlignment.center,
    children: [
      // Logo with pulse rings
      _LogoWithRings(
        pulseController: _pulseController,
        fadeController: _fadeController,
      ),

      const SizedBox(height: 32),

      // Typography with fade-up
      FadeTransition(
        opacity: CurvedAnimation(
          parent: _fadeController,
          curve: const Interval(0.2, 1.0, curve:
AppAnimations.expoOut),
        ),
        child: SlideTransition(
          position: Tween<Offset>(
            begin: const Offset(0, 30),
            end: Offset.zero,
          ).animate(CurvedAnimation(
            parent: _fadeController,
            curve: const Interval(0.2, 1.0, curve:
AppAnimations.expoOut),
          )),
          child: Column(
            children: [
              Text(
                'BURGER\nFARM',
                textAlign: TextAlign.center,
                style: AppTypography.splashTitle,
              ),
              const SizedBox(height: 24),

```

```
// Decorative wave SVG equivalent
CustomPaint(
    size: const Size(96, 12),
    painter: _WavePainter(),
),
const SizedBox(height: 16),
Text(
    'Farm-Fresh. Always.',
    style: AppTypography.display(
        size: 20,
        color: Colors.white.withOpacity(0.95),
        style: FontStyle.italic,
        letterSpacing: 0.02,
    ),
),
],
),
],
),
],
),
],
),
),
// Bottom loader
Positioned(
    bottom: 96,
    left: 0,
    right: 0,
    child: Column(
        children: [
            // Orbit path animation
            _OrbitAnimation(controller: _orbitController),
            const SizedBox(height: 16),
            // Loading bar
            _LoadingBar(),
            const SizedBox(height: 32),
            Text(
                'Tap to continue',
                style: AppTypography.body(
                    size: 10,
                    weight: FontWeight.w700,
                    color: Colors.white.withOpacity(0.5),
                    letterSpacing: 0.25,
                ),
            ),
        ],
    ),
),
// Bottom home indicator
```

```

        Positioned(
          bottom: 8,
          left: 0,
          right: 0,
          child: Center(
            child: Container(
              width: 144,
              height: 6,
              decoration: BoxDecoration(
                color: Colors.white.withOpacity(0.3),
                borderRadius: BorderRadius.circular(3),
              ),
            ),
          ),
        ),
      ],
    ),
  ],
);

```

```

}
}

```

```

class _LogoWithRings extends StatelessWidget {
  final AnimationController pulseController;
  final AnimationController fadeController;

```

```

  const _LogoWithRings({
    required this.pulseController,
    required this.fadeController,
  });

```

```

  @override
  Widget build(BuildContext context) {
    return FadeTransition(
      opacity: fadeController,
      child: SizedBox(
        width: 96,
        height: 96,
        child: Stack(
          alignment: Alignment.center,
          children: [
            // Outer pulse ring
            AnimatedBuilder(
              animation: pulseController,
              builder: (context, child) {
                return Container(

```

```

width: 96 + (pulseController.value 20),
height: 96 + (pulseController.value 20),
decoration: BoxDecoration(
  shape: BoxShape.circle,
  border: Border.all(
    color: Colors.white.withOpacity(
      0.3 (1 - pulseController.value),
    ),
    width: 1,
  ),
);
},
),
// Inner pulse ring (delayed)
AnimatedBuilder(
  animation: pulseController,
  builder: (context, child) {
    final delayedValue = ((pulseController.value + 0.5) % 1.0);
    return Container(
      width: 96 + (delayedValue 20),
      height: 96 + (delayedValue 20),
      decoration: BoxDecoration(
        shape: BoxShape.circle,
        border: Border.all(
          color: Colors.white.withOpacity(
            0.2 (1 - delayedValue),
          ),
          width: 1,
        ),
      );
    },
  ),
// Glassmorphism logo container
Container(
  width: 96,
  height: 96,
  decoration: BoxDecoration(
    shape: BoxShape.circle,
    color: Colors.white.withOpacity(0.1),
    border: Border(
      top: BorderSide(

```

```

color: Colors.white.withOpacity(0.4),
width: 1,
),
bottom: BorderSide(
color: Colors.white.withOpacity(0.1),
width: 1,
),
),
boxShadow: [
BoxShadow(
color: const Color(0xFF271200).withOpacity(0.25),
blurRadius: 40,
offset: const Offset(0, 12),
),
BoxShadow(
color: Colors.white.withOpacity(0.2),
blurRadius: 4,
offset: const Offset(0, 2),
inset: true,
),
],
),
child: Center(
child: _BurgerIcon(size: 56),
),
),
],
),
),
);
}
}

```

```

class _BurgerIcon extends StatelessWidget {
final double size;

const _BurgerIcon({required this.size});

@override
Widget build(BuildContext context) {
return CustomPaint(
size: Size(size, size),
painter: _BurgerIconPainter(),
);
}
}

```



```
}  
}
```

```
class _BurgerIconPainter extends CustomPainter {  
  @override  
  void paint(Canvas canvas, Size size) {  
    final paint = Paint()..color = Colors.white;
```

```
    // Bottom bun  
    canvas.drawRRect(  
      RRect.fromRectAndRadius(  
        Rect.fromLTWH(size.width * 0.2, size.height * 0.56,  
                      size.width * 0.6, size.height * 0.19),  
        Radius.circular(size.width * 0.09),  
      ),  
      paint..color = Colors.white.withOpacity(0.95),  
    );  
  
    // Patty  
    canvas.drawRRect(  
      RRect.fromRectAndRadius(  
        Rect.fromLTWH(size.width * 0.17, size.height * 0.46,  
                      size.width * 0.66, size.height * 0.12),  
        Radius.circular(size.width * 0.06),  
      ),  
      paint..color = Colors.white.withOpacity(0.7),  
    );  
  
    // Cheese/Toppings  
    canvas.drawRRect(  
      RRect.fromRectAndRadius(  
        Rect.fromLTWH(size.width * 0.23, size.height * 0.38,  
                      size.width * 0.54, size.height * 0.10),  
        Radius.circular(size.width * 0.05),  
      ),  
      paint..color = Colors.white.withOpacity(0.9),  
    );  
  
    // Top bun  
    canvas.drawRRect(  
      RRect.fromRectAndRadius(  
        Rect.fromLTWH(size.width * 0.19, size.height * 0.29,  
                      size.width * 0.62, size.height * 0.10),  
        Radius.circular(size.width * 0.05),  
      ),  
      paint..color = Colors.white.withOpacity(0.5),  
    );  
  }  
}
```

```
}
```

```
@override
```

```
bool shouldRepaint(covariant CustomPainter oldDelegate) => false;
```

```
}
```

```
class _AmbientOrb extends StatelessWidget {
```

```
  final double size;
```

```
  final Color color;
```

```
  final AnimationController animation;
```

```
  final double delay;
```

```
  const _AmbientOrb({
```

```
    required this.size,
```

```
    required this.color,
```

```
    required this.animation,
```

```
    this.delay = 0,
```

```
  });
```

```
@override
```

```
Widget build(BuildContext context) {
```

```
  return AnimatedBuilder(
```

```
    animation: animation,
```

```
    builder: (context, child) {
```

```
      final adjustedValue = ((animation.value + delay) % 1.0);
```

```
      return Container(
```

```
        width: size,
```

```
        height: size,
```

```
        decoration: BoxDecoration(
```

```
          shape: BoxShape.circle,
```

```
          color: color.withOpacity(0.2 + (adjustedValue * 0.1)),
```

```
        ),
```

```
        child: BackdropFilter(
```

```
          filter: ImageFilter.blur(
```

```
            sigmaX: size * 0.25,
```

```
            sigmaY: size * 0.25,
```

```
          ),
```

```
        child: Container(
```

```
          color: Colors.transparent,
```

```
        ),
```

```
      ),
```

```
    );
```

```
  },
```

```
);
```

```
}  
}
```

```
class _OrbitAnimation extends StatelessWidget {  
  final AnimationController controller;
```

```
  const _OrbitAnimation({required this.controller});
```

```
  @override
```

```
  Widget build(BuildContext context) {
```

```
    return SizedBox(
```

```
      width: 192,
```

```
      height: 80,
```

```
      child: AnimatedBuilder(
```

```
        animation: controller,
```

```
        builder: (context, child) {
```

```
          return CustomPaint(
```

```
            size: const Size(192, 80),
```

```
            painter: _OrbitPathPainter(progress: controller.value),
```

```
          );
```

```
        },
```

```
      ),
```

```
    );
```

```
  }
```

```
}
```

```
class _OrbitPathPainter extends CustomPainter {
```

```
  final double progress;
```

```
  _OrbitPathPainter({required this.progress});
```

```
  @override
```

```
  void paint(Canvas canvas, Size size) {
```

```
    final path = Path()
```

```
    ..moveTo(10, size.height - 10)
```

```
    ..quadraticBezierTo(
```

```
      size.width * 0.5, -20,
```

```
      size.width - 10, size.height - 10,
```

```
    );
```

```
    final paint = Paint()  
    ..color = Colors.white.withOpacity(0.3)  
    ..style = PaintingStyle.stroke  
    ..strokeWidth = 2.5  
    ..strokeCap = StrokeCap.round;
```

```

// Draw path with animation
final pathMetrics = path.computeMetrics();
for (final metric in pathMetrics) {
  final extractPath = metric.extractPath(
    0,
    metric.length * progress,
  );
  canvas.drawPath(extractPath, paint);
}

```

```

}

```

```

@override
bool shouldRepaint(covariant _OrbitPathPainter oldDelegate) =>
oldDelegate.progress != progress;
}

```

```

class _LoadingBar extends StatefulWidget {
  @override
  State<_LoadingBar> createState() => _LoadingBarState();
}

```

```

class _LoadingBarState extends State<_LoadingBar>
with SingleTickerProviderStateMixin {
  late AnimationController _controller;

```

```

@override
void initState() {
  super.initState();
  _controller = AnimationController(
    vsync: this,
    duration: const Duration(seconds: 2),
  )..repeat();
}

```

```

@override
void dispose() {
  _controller.dispose();
  super.dispose();
}

```

```

@override
Widget build(BuildContext context) {
  return AnimatedBuilder(
    animation: _controller,
    builder: (context, child) {
      return Container(

```

```

width: 128,
height: 6,
decoration: BoxDecoration(
color: Colors.white.withOpacity(0.1),
borderRadius: BorderRadius.circular(3),
),
child: Stack(
children: [
Positioned(
left: -128 + (_controller.value 384),
child: Container(
width: 128 0.4,
height: 6,
decoration: BoxDecoration(
color: Colors.white.withOpacity(0.9),
borderRadius: BorderRadius.circular(3),
),
),
),
),
],
),
);
},
);
}
}

```

```

class _WavePainter extends CustomPainter {
@override
void paint(Canvas canvas, Size size) {
final paint = Paint()
..color = Colors.white.withOpacity(0.8)
..style = PaintingStyle.stroke
..strokeWidth = 2.5
..strokeCap = StrokeCap.round;

```

```

final path = Path()
..moveTo(0, size.height * 0.5)
..quadraticBezierTo(
size.width * 0.25, 0,
size.width * 0.5, size.height * 0.5,
)
..quadraticBezierTo(
size.width * 0.75, size.height,
size.width, size.height * 0.5,

```

```

    );

    canvas.drawPath(path, paint);

}

@override
bool shouldRepaint(covariant CustomPainter oldDelegate) => false;
}

```

lib/presentation/screens/onboarding_screen.dart

```

import 'package:flutter/material.dart';
import 'package:flutter_riverpod/flutter_riverpod.dart';
import 'package:go_router/go_router.dart';
import '../core/theme/app_colors.dart';
import '../core/theme/app_animations.dart';
import '../core/theme/app_shadows.dart';
import '../core/theme/app_typography.dart';
import '../router/app_router.dart';
import '../widgets/premium_button.dart';

/// Onboarding with exact HTML structure:
/// - Top 45% orange with floating orbs
/// - Bottom sheet with rounded-t-[40px]
/// - Dots indicator, headline with underline, features grid
/// - Staggered GSAP-like entrance animations
class OnboardingScreen extends ConsumerStatefulWidget {
  const OnboardingScreen({super.key});

  @override
  ConsumerState createState() => _OnboardingScreenState();
}

class _OnboardingScreenState extends ConsumerState
  with TickerProviderStateMixin {
  late AnimationController _sheetController;
  late AnimationController _contentController;

  @override
  void initState() {
    super.initState();

```

```

    _sheetController = AnimationController(
      vsync: this,
      duration: AppAnimations.entrance,

```

```

);

_contentController = AnimationController(
  vsync: this,
  duration: const Duration(milliseconds: 600),
);

// Staggered entrance sequence
Future.delayed(const Duration(milliseconds: 100), () {
  _sheetController.forward();
});
Future.delayed(const Duration(milliseconds: 400), () {
  _contentController.forward();
});

```

```

}

```

@override

```

void dispose() {
  _sheetController.dispose();
  _contentController.dispose();
  super.dispose();
}

```

@override

```

Widget build(BuildContext context) {
  final size = MediaQuery.of(context).size;

```

```

return Scaffold(
  backgroundColor: AppColors.brand,
  body: Stack(
    children: [
      // Top orange area with decorations
      Positioned(
        top: 0,
        left: 0,
        right: 0,
        height: size.height * 0.45,
        child: Stack(
          children: [
            // Base color
            Container(color: AppColors.brand),

            // Gradient glows
            Positioned(
              bottom: -40,
              left: -40,
              child: Container(

```

```

width: 256,
height: 256,
decoration: BoxDecoration(
  shape: BoxShape.circle,
  gradient: RadialGradient(
    colors: [
      Colors.white.withOpacity(0.1),
      Colors.transparent,
    ],
  ),
),
),
),
),
),
Positioned(
  top: -48,
  right: -32,
  child: Container(
    width: 224,
    height: 224,
    decoration: BoxDecoration(
      shape: BoxShape.circle,
      gradient: RadialGradient(
        colors: [
          Colors.white.withOpacity(0.08),
          Colors.transparent,
        ],
      ),
    ),
  ),
),
),
),
),
),
),
// Floating orbs
Positioned(
  top: size.height * 0.15,
  left: size.width * 0.2,
  child: _FloatingOrb(
    size: 160,
    color: const Color(0xFFFFFB085),
    duration: const Duration(seconds: 4),
  ),
),
),
Positioned(
  bottom: size.height * 0.05,
  right: size.width * 0.1,
  child: _FloatingOrb(
    size: 192,
    color: const Color(0xFFC94208),
    duration: const Duration(seconds: 5),
  ),
),
),
),

```



```

// Skip button
Positioned(
  top: MediaQuery.of(context).padding.top + 16,
  right: 24,
  child: GestureDetector(
    onTap: () => context.go(AppRoute.login),
    child: Container(
      padding: const EdgeInsets.symmetric(
        horizontal: 20,
        vertical: 10,
      ),
      decoration: BoxDecoration(
        color: Colors.white.withOpacity(0.14),
        borderRadius: BorderRadius.circular(100),
        border: Border.all(
          color: Colors.white.withOpacity(0.1),
        ),
      ),
    ),
    child: Text(
      'Skip',
      style: AppTypography.body(
        size: 11,
        weight: FontWeight.w700,
        color: Colors.white.withOpacity(0.9),
        letterSpacing: 0.18,
      ),
    ),
  ),
),

// Brand logo
Center(
  child: Column(
    mainAxisAlignment: MainAxisAlignment.center,
    children: [
      Container(
        width: 64,
        height: 64,
        decoration: BoxDecoration(
          shape: BoxShape.circle,
          color: Colors.white.withOpacity(0.1),
          border: Border.all(
            color: Colors.white.withOpacity(0.2),
          ),
        ),
        child: const _BurgerIcon(size: 28),
      ),
      const SizedBox(height: 16),
    ],
  ),
),

```

```
Text(
  'BURGER FARM',
  style: AppTypography.display(
    size: 22,
    color: Colors.white,
    letterSpacing: 0.2,
  ),
),
],
),
],
),
],
),
),
),
// Bottom sheet
AnimatedBuilder(
  animation: _sheetController,
  builder: (context, child) {
    return Positioned(
      bottom: 0,
      left: 0,
      right: 0,
      height: size.height * 0.58,
      child: Transform.translate(
        offset: Offset(
          0,
          100 * (1 - CurvedAnimation(
            parent: _sheetController,
            curve: AppAnimations.expoOut,
          ).value),
        ),
      child: Opacity(
        opacity: CurvedAnimation(
          parent: _sheetController,
          curve: AppAnimations.expoOut,
        ).value,
        child: Container(
          decoration: BoxDecoration(
            color: Colors.white,
            borderRadius: const BorderRadius.vertical(
              top: Radius.circular(40),
            ),
            boxShadow: AppShadows.float,
          ),
          child: SafeArea(
            top: false,
            child: Padding(
              padding: const EdgeInsets.fromLTRB(32, 36, 32, 32),
              child: Column(
```

```

crossAxisAlignment: CrossAxisAlignment.start,
children: [
  // Dots
  Row(
    children: [
      Container(
        width: 24,
        height: 6,
        decoration: BoxDecoration(
          color: AppColors.brand,
          borderRadius: BorderRadius.circular(3),
        ),
      ),
      const SizedBox(width: 6),
      Container(
        width: 6,
        height: 6,
        decoration: BoxDecoration(
          color: AppColors.line,
          shape: BoxShape.circle,
        ),
      ),
      const SizedBox(width: 6),
      Container(
        width: 6,
        height: 6,
        decoration: BoxDecoration(
          color: AppColors.line,
          shape: BoxShape.circle,
        ),
      ),
    ],
  ),

  const SizedBox(height: 32),

  // Headline with stagger
  _AnimatedText(
    animation: _contentController,
    delay: 0.0,
    child: RichText(
      text: TextSpan(
        children: [
          TextSpan(
            text: 'Real Burgers.\n',
            style: AppTypography.onboardingHeadline,
          ),
          WidgetSpan(
            alignment:
PlaceholderAlignment.baseline,

```

```

        baseline: TextBaseline.alphabetic,
        child: Stack(
          children: [
            Text(
              'Real Fast.',
              style:
AppTypography.onboardingHeadline.copyWith(
                color: AppColors.brand,
              ),
            Positioned(
              bottom: -4,
              left: 0,
              right: 0,
              child: Container(
                height: 8,
                decoration: BoxDecoration(
                  color:
AppColors.brand.withOpacity(0.1),
                  borderRadius:
BorderRadius.circular(4),
                ),
              ),
            ],
          ),
        ),
      ],
    ),
  ),
),
const SizedBox(height: 16),

// Subtitle
_AnimatedText(
  animation: _contentController,
  delay: 0.1,
  child: Text(
    'Farm-fresh ingredients. Made to
order.\nDelivered while it\'s still sizzling.',
    style: AppTypography.bodyLarge,
  ),
),

const SizedBox(height: 20),

// Features row
_AnimatedText(
  animation: _contentController,
```

```

        delay: 0.2,
        child: Row(
          children: [
            _FeatureCard(
              icon: Icons.eco,
              label: 'Farm Fresh',
            ),
            const SizedBox(width: 12),
            _FeatureCard(
              icon: Icons.timer,
              label: '18 Min Avg',
            ),
            const SizedBox(width: 12),
            _FeatureCard(
              icon: Icons.local_shipping,
              label: 'Free ₹199+',
            ),
          ],
        ),
      ),
    ),

    const Spacer(),

    // CTA Button
    _AnimatedText(
      animation: _contentController,
      delay: 0.3,
      child: PremiumButton(
        text: 'Grab Your Meal',
        icon: const Icon(
          Icons.arrow_forward,
          color: Colors.white,
          size: 20,
        ),
        onPressed: () => context.go(AppRoute.login),
      ),
    ),
  ],
),
],
);
}

```

```
    },  
  );  
}
```

```
}  
}
```

```
class _FloatingOrb extends StatefulWidget {  
  final double size;  
  final Color color;  
  final Duration duration;
```

```
  const _FloatingOrb({  
    required this.size,  
    required this.color,  
    required this.duration,  
  });
```

```
  @override  
  State<_FloatingOrb> createState() => _FloatingOrbState();  
}
```

```
class _FloatingOrbState extends State<_FloatingOrb>  
with SingleTickerProviderStateMixin {  
  late AnimationController _controller;
```

```
  @override  
  void initState() {  
    super.initState();  
    _controller = AnimationController(  
      vsync: this,  
      duration: widget.duration,  
    )..repeat(reverse: true);  
  }
```

```
  @override  
  void dispose() {  
    _controller.dispose();  
    super.dispose();  
  }
```

```
  @override  
  Widget build(BuildContext context) {  
    return AnimatedBuilder(  
      animation: _controller,  
      builder: (context, child) {  
        return Container(  
          width: widget.size,
```

```

width: widget.size,
height: widget.size,
decoration: BoxDecoration(
  shape: BoxShape.circle,
  color: widget.color.withOpacity(0.2 + (_controller.value 0.1)),
),
child: BackdropFilter(
  filter: ImageFilter.blur(
    sigmaX: widget.size 0.25,
    sigmaY: widget.size * 0.25,
  ),
  child: Container(color: Colors.transparent),
),
);
},
);
}
}

```

```

class _AnimatedText extends StatelessWidget {
  final AnimationController animation;
  final double delay;
  final Widget child;

```

```

  const _AnimatedText({
    required this.animation,
    required this.delay,
    required this.child,
  });

```

```

  @override
  Widget build(BuildContext context) {
    final intervalStart = delay;
    final intervalEnd = (delay + 0.4).clamp(0.0, 1.0);

```

```

    return AnimatedBuilder(
      animation: animation,
      builder: (context, child) {
        final value = CurvedAnimation(
          parent: animation,
          curve: Interval(intervalStart, intervalEnd, curve:
AppAnimations.expoOut),
        ).value;

        return Opacity(
          opacity: value,

```

```

        child: Transform.translate(
          offset: Offset(0, 20 * (1 - value)),
          child: child,
        ),
      );
    },
    child: child,
  );

```

```

}
}

```

```

class _FeatureCard extends StatelessWidget {
  final IconData icon;
  final String label;

```

```

  const _FeatureCard({
    required this.icon,
    required this.label,
  });

```

```

  @override
  Widget build(BuildContext context) {
    return Expanded(
      child: Container(
        padding: const EdgeInsets.symmetric(vertical: 14, horizontal: 8),
        decoration: BoxDecoration(
          color: AppColors.cream.withOpacity(0.4),
          borderRadius: BorderRadius.circular(20),
          border: Border.all(
            color: AppColors.line.withOpacity(0.5),
          ),
          boxShadow: [
            BoxShadow(
              color: AppColors.brown.withOpacity(0.06),
              blurRadius: 8,
              offset: const Offset(0, 2),
            ),
          ],
        ),
      child: Column(
        children: [
          Container(
            width: 36,
            height: 36,

```



```

decoration: BoxDecoration(
  shape: BoxShape.circle,
  color: Colors.white,
  border: Border.all(
    color: AppColors.line.withOpacity(0.3),
  ),
  boxShadow: [
    BoxShadow(
      color: AppColors.brown.withOpacity(0.06),
      blurRadius: 8,
      offset: const Offset(0, 2),
    ),
  ],
),
child: Icon(
  icon,
  size: 16,
  color: AppColors.brand,
),
),
const SizedBox(height: 10),
Text(
  label,
  style: AppTypography.body(
    size: 10,
    weight: FontWeight.w900,
    letterSpacing: 0.18,
  ),
),
],
),
),
);
}
}

```

lib/presentation/screens/login_screen.dart

```

import 'package:flutter/material.dart';
import 'package:flutter_riverpod/flutter_riverpod.dart';
import 'package:go_router/go_router.dart';
import '../core/theme/app_colors.dart';
import '../core/theme/app_animations.dart';
import '../core/theme/app_shadows.dart';

```

```

import '../core/theme/app_typography.dart';
import '../router/app_router.dart';
import '../widgets/premium_button.dart';
import '../widgets/premium_input.dart';

/// Login screen with:
/// - Top 30% orange with pattern background
/// - Bottom sheet with phone input, social logins
/// - Indian flag +91 prefix
/// - "Continue as Guest" option
class LoginScreen extends ConsumerStatefulWidget {
  const LoginScreen({super.key});

  @override
  ConsumerState createState() => _LoginScreenState();
}

class _LoginScreenState extends ConsumerState
  with TickerProviderStateMixin {
  late AnimationController _sheetController;
  late AnimationController _contentController;
  final _phoneController = TextEditingController();

  @override
  void initState() {
    super.initState();
    _sheetController = AnimationController(
      vsync: this,
      duration: AppAnimations.entrance,
    );
    _contentController = AnimationController(
      vsync: this,
      duration: const Duration(milliseconds: 600),
    );

    Future.delayed(const Duration(milliseconds: 100), () {
      _sheetController.forward();
      _contentController.forward();
    });
  }

  @override
  void dispose() {
    _sheetController.dispose();
  }

```

```
_contentController.dispose();
_phoneController.dispose();
super.dispose();
}
```

```
@override
Widget build(BuildContext context) {
  return Scaffold(
    backgroundColor: AppColors.warmBg,
    body: Stack(
      children: [
        // Top area with pattern
        Positioned(
          top: 0,
          left: 0,
          right: 0,
          height: MediaQuery.of(context).size.height * 0.30,
          child: Container(
            decoration: BoxDecoration(
              color: Colors.white,
              gradient: LinearGradient(
                begin: Alignment.topCenter,
                end: Alignment.bottomCenter,
                colors: [
                  Colors.white,
                  const Color(0xFFFAFAFA),
                ],
              ),
            ),
          ),
          child: Stack(
            children: [
              // Dot pattern
              CustomPaint(
                size: Size.infinite,
                painter: _DotPatternPainter(),
              ),
              // Gradient overlay
              Container(
                decoration: BoxDecoration(
                  gradient: LinearGradient(
                    begin: Alignment.topCenter,
                    end: Alignment.bottomCenter,
                    colors: [
                      Colors.transparent,
```

```

const Color(0xFFFAFAFA).withOpacity(0.8),
const Color(0xFFFAFAFA),
],
stops: const [0.0, 0.5, 1.0],
),
),
),
// Logo
Center(
child: Column(
mainAxisAlignment: MainAxisAlignment.center,
children: [
Container(
width: 80,
height: 80,
decoration: BoxDecoration(
borderRadius: BorderRadius.circular(24),
color: AppColors.brand.withOpacity(0.1),
border: Border.all(
color: AppColors.brand.withOpacity(0.2),
),
boxShadow: [
BoxShadow(
color: AppColors.brand.withOpacity(0.15),
blurRadius: 32,
offset: const Offset(0, 8),
),
],
),
child: const _BurgerIcon(size: 32),
),
const SizedBox(height: 20),
Text(
'Burger Farm',
style: AppTypography.display(
size: 24,
letterSpacing: 0.07,
),
),
const SizedBox(height: 4),
Text(
'Welcome to the Farm',
style: AppTypography.body(

```

```
size: 14,  
color: AppColors.brownMuted,  
style: FontStyle.italic,  
)  
)  
]  
)  
)  
]  
)  
)  
)  
)
```

```
// Bottom sheet
AnimatedBuilder(
  animation: _sheetController,
  builder: (context, child) {
    return Positioned(
      bottom: 0,
      left: 0,
      right: 0,
      height: MediaQuery.of(context).size.height * 0.72,
      child: Transform.translate(
        offset: Offset(
          0,
          60 * (1 - CurvedAnimation(
            parent: _sheetController,
            curve: AppAnimations.expoOut,
          ).value),
        ),
      child: Opacity(
        opacity: CurvedAnimation(
          parent: _sheetController,
          curve: AppAnimations.expoOut,
        ).value,
        child: Container(
          decoration: BoxDecoration(
            color: Colors.white,
            borderRadius: const BorderRadius.vertical(
              top: Radius.circular(40),
            ),
            boxShadow: AppShadows.float,
          ),
          child: SafeArea(
            top: false,
            child: Padding(
              padding: const EdgeInsets.fromLTRB(32, 40, 32, 20)
```

```

child: Column(
  crossAxisAlignment: CrossAxisAlignment.start,
  children: [
    // Headline
    Text(
      'Let\'s get you in.',
      style: AppTypography.display(
        size: 36,
        height: 1.1,
        letterSpacing: -0.02,
      ),
    ),
    const SizedBox(height: 8),
    Text(
      'Enter your number – we\'ll send an OTP.',
      style: AppTypography.body(
        size: 15,
        color: AppColors.brownMuted,
      ),
    ),
  ],

  const SizedBox(height: 40),

  // Phone input with flag
  _PhoneInput(controller: _phoneController),

  const SizedBox(height: 20),

  // Trust badge
  Container(
    padding: const EdgeInsets.symmetric(
      horizontal: 12,
      vertical: 6,
    ),
    decoration: BoxDecoration(
      color: AppColors.success.withOpacity(0.05),
      borderRadius: BorderRadius.circular(100),
      border: Border.all(
        color: AppColors.success.withOpacity(0.1),
      ),
    ),
  ),
  child: Row(
    mainAxisAlignment: MainAxisAlignment.min,
    children: [
      Icon(
        Icons.verified_user,
        size: 14,
        color: AppColors.success,
      ),
      const SizedBox(width: 6),
    ],
  ),
),

```

```

        Text(
          'Secure login. No spam, ever.',
          style: AppTypography.body(
            size: 13,
            color: AppColors.success,
          ),
        ),
      ],
    ),
  ),
),

const SizedBox(height: 40),

// Send OTP button
PremiumButton(
  text: 'Send OTP',
  onPressed: () => _handleSendOTP(),
),

const SizedBox(height: 28),

// OR divider
Row(
  children: [
    Expanded(
      child: Container(
        height: 1,
        decoration: BoxDecoration(
          gradient: LinearGradient(
            colors: [
              Colors.transparent,
              AppColors.line,
            ],
          ),
        ),
      ),
    ),
  ],
),
Padding(
  padding: const
EdgeInsets.symmetric(horizontal: 16),
  child: Text(
    'or',
    style: AppTypography.body(
      size: 11,
      weight: FontWeight.w700,
      color:
AppColors.brownMuted.withOpacity(0.6),
      letterSpacing: 0.18,
    ),
  ),
),

```

```

    ),
    Expanded(
      child: Container(
        height: 1,
        decoration: BoxDecoration(
          gradient: LinearGradient(
            colors: [
              AppColors.line,
              Colors.transparent,
            ],
          ),
        ),
      ),
    ),
  ),
],
),
),
],
),
),
const SizedBox(height: 28),

// Social buttons
_SocialButton(
  icon: _GoogleIcon(),
  label: 'Continue with Google',
  onPressed: () => _handleGoogleSignIn(),
),
const SizedBox(height: 14),
_SocialButton(
  icon: _AppleIcon(),
  label: 'Continue with Apple',
  backgroundColor: AppColors.brown,
  textColor: Colors.white,
  onPressed: () => _handleAppleSignIn(),
),

const Spacer(),

// Guest login
Center(
  child: GestureDetector(
    onTap: () => context.go(AppRoute.preferences),
    child: Row(
      mainAxisAlignment: MainAxisAlignment.min,
      children: [
        Text(
          'Continue as Guest',
          style: AppTypography.body(
            size: 15,
            weight: FontWeight.w700,
            color: AppColors.brand,
          ),
        ),
      ],
    ),
  ),
),

```



```

void _handleAppleSignIn() {
// TODO: Implement Sign in with Apple
}
}

```

```

class _PhoneInput extends StatelessWidget {
final TextEditingController controller;

```

```

const _PhoneInput({required this.controller});

```

```

@override

```

```

Widget build(BuildContext context) {
return Container(
decoration: BoxDecoration(
color: const Color(0xFFFFFAFA),
borderRadius: BorderRadius.circular(16),
border: Border.all(
color: AppColors.line,
width: 1.5,
),
boxShadow: AppShadows.insetSoft,
),
child: Row(
children: [
// Flag + code
Container(
padding: const EdgeInsets.symmetric(horizontal: 16, vertical: 14),
decoration: BoxDecoration(
border: Border(
right: BorderSide(
color: AppColors.line.withOpacity(0.6),
width: 2,
),
),
),
child: Row(
mainAxisSize: MainAxisSize.min,
children: [
// Indian flag
Container(
width: 24,
height: 16,
decoration: BoxDecoration(
borderRadius: BorderRadius.circular(2),

```

```
boxShadow: [
  BoxShadow(
    color: Colors.black.withOpacity(0.1),
    blurRadius: 2,
  ),
],
),
child: Column(
  children: [
    Expanded(
      flex: 1,
      child: Container(color: const Color(0xFFFF9933)),
    ),
    Expanded(
      flex: 1,
      child: Container(color: Colors.white),
    ),
    Expanded(
      flex: 1,
      child: Container(color: const Color(0xFF138808)),
    ),
  ],
),
),
const SizedBox(width: 8),
Text(
  '+91',
  style: AppTypography.body(
    size: 16,
    weight: FontWeight.w700,
  ),
),
],
),
),
// Phone number
Expanded(
  child: TextField(
    controller: controller,
    keyboardType: TextInputType.phone,
    style: AppTypography.display(
      size: 20,
      letterSpacing: 0.05,
```

```

),
decoration: InputDecoration(
  hintText: '00000 00000',
  hintStyle: AppTypography.display(
    size: 20,
    color: AppColors.brownMuted.withOpacity(0.5),
    letterSpacing: 0.05,
  ),
  border: InputBorder.none,
  contentPadding: const EdgeInsets.symmetric(horizontal: 16),
),
),
),
],
),
);
}
}

```

```

class _SocialButton extends StatelessWidget {
  final Widget icon;
  final String label;
  final Color? backgroundColor;
  final Color? textColor;
  final VoidCallback? onPressed;

```

```

  const _SocialButton({
    required this.icon,
    required this.label,
    this.backgroundColor,
    this.textColor,
    this.onPressed,
  });

```

```

  @override
  Widget build(BuildContext context) {
    return GestureDetector(
      onTap: onPressed,
      child: Container(
        height: 50,
        decoration: BoxDecoration(
          color: backgroundColor ?? Colors.white,
          borderRadius: BorderRadius.circular(100),
          border: Border.all(

```

```

color: backgroundColor != null
? Colors.transparent
: AppColors.line,
width: 1.5,
),
boxShadow: [
BoxShadow(
color: AppColors.brown.withOpacity(0.04),
blurRadius: 8,
offset: const Offset(0, 2),
),
],
),
child: Row(
mainAxisAlignment: MainAxisAlignment.center,
children: [
icon,
const SizedBox(width: 12),
Text(
label,
style: AppTypography.body(
size: 14,
weight: FontWeight.w600,
color: textColor ?? AppColors.brown,
),
),
],
),
);
}
}

```

```

class _GoogleIcon extends StatelessWidget {
@override
Widget build(BuildContext context) {
return SizedBox(
width: 20,
height: 20,
child: CustomPaint(
painter: _GoogleIconPainter(),
),
);
}
}

```

```
}  
}
```

```
class _GoogleIconPainter extends CustomPainter {  
  @override  
  void paint(Canvas canvas, Size size) {  
    // Simplified Google "G"  
    final paint = Paint()..strokeWidth = 2;  
    // This would be the actual Google logo paths  
    canvas.drawCircle(  
      Offset(size.width / 2, size.height / 2),  
      size.width / 2,  
      paint..color = const Color(0xFF4285F4),  
    );  
  }  
  
  @override  
  bool shouldRepaint(covariant CustomPainter oldDelegate) => false;  
}
```

```
class _AppleIcon extends StatelessWidget {  
  @override  
  Widget build(BuildContext context) {  
    return Icon(  
      Icons.apple,  
      size: 20,  
      color: Colors.white,  
    );  
  }  
}
```

```
class _DotPatternPainter extends CustomPainter {  
  @override  
  void paint(Canvas canvas, Size size) {  
    final paint = Paint()  
    ..color = AppColors.brandLight  
    ..strokeWidth = 2;
```

```
    const spacing = 24.0;  
    for (var x = 0.0; x < size.width; x += spacing) {  
      for (var y = 0.0; y < size.height; y += spacing) {  
        canvas.drawCircle(Offset(x, y), 1, paint);  
      }  
    }  
  }
```

```

}

@override
bool shouldRepaint(covariant CustomPainter oldDelegate) => false;
}

```

5. Router Configuration

lib/presentation/router/app_router.dart

```

import 'package:flutter/material.dart';
import 'package:go_router/go_router.dart';
import 'package:flutter_riverpod/flutter_riverpod.dart';
import '../screens/splash_screen.dart';
import '../screens/onboarding_screen.dart';
import '../screens/login_screen.dart';
import '../screens/preferences_screen.dart';
import '../screens/location_screen.dart';
import '../screens/outlet_screen.dart';
import '../screens/address_screen.dart';
import '../screens/detail_screen.dart';
import '../screens/home_screen.dart';

final routerProvider = Provider((ref) {
  return GoRouter(
    initialLocation: AppRoute.splash,
    debugLogDiagnostics: true,
    routes: [
      GoRoute(
        path: AppRoute.splash,
        builder: (context, state) => const SplashScreen(),
      ),
      GoRoute(
        path: AppRoute.onboarding,
        builder: (context, state) => const OnboardingScreen(),
      ),
      GoRoute(
        path: AppRoute.login,
        builder: (context, state) => const LoginScreen(),
      ),
      GoRoute(
        path: AppRoute.preferences,
        builder: (context, state) => const PreferencesScreen(),
      ),
      GoRoute(

```

```

path: AppRoute.location,
builder: (context, state) => const LocationScreen(),
),
GoRoute(
path: AppRoute.outlet,
builder: (context, state) => const OutletScreen(),
),
GoRoute(
path: AppRoute.address,
builder: (context, state) => const AddressScreen(),
),
GoRoute(
path: AppRoute.detail,
builder: (context, state) => const DetailScreen(),
),
GoRoute(
path: AppRoute.home,
builder: (context, state) => const HomeScreen(),
),
],
);
});

```

```

class AppRoute {
static const String splash = '/';
static const String onboarding = '/onboarding';
static const String login = '/login';
static const String preferences = '/preferences';
static const String location = '/location';
static const String outlet = '/outlet';
static const String address = '/address';
static const String detail = '/detail';
static const String home = '/home';
}

```

6. Backend Integration Architecture

lib/data/services/firebase_service.dart

```

import 'package:firebase_core/firebase_core.dart';
import 'package:firebase_auth/firebase_auth.dart';
import 'package:cloud_firestore/cloud_firestore.dart';
import 'package:firebase_messaging/firebase_messaging.dart';
import 'package:flutter_riverpod/flutter_riverpod.dart';

```



```

final firebaseServiceProvider = Provider((ref) {
return FirebaseService();
});

class FirebaseService {
final FirebaseAuth _auth = FirebaseAuth.instance;
final FirebaseFirestore _firestore = FirebaseFirestore.instance;
final FirebaseMessaging _messaging = FirebaseMessaging.instance;

// Authentication
Future verifyPhoneNumber({
required String phoneNumber,
required Function(String) onCodeSent,
required Function(String) onError,
}) async {
await _auth.verifyPhoneNumber(
phoneNumber: '+91$phoneNumber',
verificationCompleted: (PhoneAuthCredential credential) async {
await _auth.signInWithCredential(credential);
},
verificationFailed: (FirebaseAuthException e) {
onError(e.message ?? 'Verification failed');
},
codeSent: (String verificationId, int? resendToken) {
onCodeSent(verificationId);
},
codeAutoRetrievalTimeout: (String verificationId) {},
);
}

Future signInWithOTP({
required String verificationId,
required String smsCode,
}) async {
final credential = PhoneAuthProvider.credential(
verificationId: verificationId,
smsCode: smsCode,
);
return await _auth.signInWithCredential(credential);
}

// Apple Sign In with account deletion compliance
Future signInWithApple() async {
// Implementation using sign_in_with_apple package
// Must handle first-time profile capture

```

```

throw UnimplementedError();
}

// Real-time order updates
Stream listenToOrder(String orderId) {
return _firestore.collection('orders').doc(orderId).snapshots();
}

```

```

// Inventory management with transaction safety
Future checkAndReserveInventory({
required String itemId,
required int quantity,
}) async {
final ref = _firestore.collection('inventory').doc(itemId);

```

```

return _firestore.runTransaction((transaction) async {
  final snapshot = await transaction.get(ref);
  final currentStock = snapshot.data()?['stock'] ?? 0;

  if (currentStock >= quantity) {
    transaction.update(ref, {'stock': currentStock - quantity});
    return true;
  }
  return false;
});

```

```

}

// FCM for real-time updates
Future initializeFCM() async {
await _messaging.requestPermission();
final token = await _messaging.getToken();
// Store token in user document for targeted notifications
}
}

```

lib/data/services/maps_service.dart

```

import 'package:google_maps_flutter/google_maps_flutter.dart';
import 'package:geolocator/geolocator.dart';
import 'package:flutter_riverpod/flutter_riverpod.dart';

final mapsServiceProvider = Provider((ref) {
return MapsService();
});

```

```

class MapsService {
  // Check and request location permissions
  Future handleLocationPermission() async {
    bool serviceEnabled = await Geolocator.isLocationServiceEnabled();
    if (!serviceEnabled) return false;

```

```

    LocationPermission permission = await Geolocator.checkPermission();
    if (permission == LocationPermission.denied) {
      permission = await Geolocator.requestPermission();
      if (permission == LocationPermission.denied) return false;
    }

    if (permission == LocationPermission.deniedForever) return false;
    return true;

```

```

  }

  Future getCurrentPosition() async {
    return await Geolocator.getCurrentPosition(
      desiredAccuracy: LocationAccuracy.high,
    );
  }

```

// Calculate delivery radius and ETA

Future<Map<String, dynamic>> calculateDeliveryMetrics({
 required LatLng store I'll continue building out the remaining critical screens and backend
 integration architecture. Let me complete the Maps service, remaining screens, and the full
 backend connectivity layer.

Continuing Maps Service & Remaining Screens

lib/data/services/maps_service.dart (Completed)

```

import 'package:google_maps_flutter/google_maps_flutter.dart';
import 'package:geolocator/geolocator.dart';
import 'package:flutter_riverpod/flutter_riverpod.dart';
import 'package:google_maps_webservice/directions.dart';

final mapsServiceProvider = Provider<MapsService>((ref) {
  return MapsService();
});

class MapsService {
  final directions = GoogleMapsDirections(apiKey: 'YOUR_API_KEY');

  Future<bool> handleLocationPermission() async {
    bool serviceEnabled = await Geolocator.isLocationServiceEnabled();

```

```

    if (!serviceEnabled) return false;

    LocationPermission permission = await Geolocator.checkPermission();
    if (permission == LocationPermission.denied) {
        permission = await Geolocator.requestPermission();
        if (permission == LocationPermission.denied) return false;
    }
    if (permission == LocationPermission.deniedForever) return false;
    return true;
}

Future<Position> getCurrentPosition() async {
    return await Geolocator.getCurrentPosition(
        desiredAccuracy: LocationAccuracy.high,
    );
}

Future<Map<String, dynamic>> calculateDeliveryMetrics({
    required LatLng storeLocation,
    required LatLng deliveryLocation,
}) async {
    final response = await directions.directionsWithLocation(
        Location(lat: storeLocation.latitude, lng: storeLocation.longitude),
        Location(lat: deliveryLocation.latitude, lng:
deliveryLocation.longitude),
        travelMode: TravelMode.driving,
    );

    if (response.isOkay && response.routes.isNotEmpty) {
        final route = response.routes.first;
        final leg = route.legs.first;
        return {
            'distance': leg.distance.value, // meters
            'duration': leg.duration.value, // seconds
            'distanceText': leg.distance.text,
            'durationText': leg.duration.text,
            'polyline': route.overviewPolyline.points,
        };
    }
    throw Exception('Could not calculate route');
}

Future<List<Map<String, dynamic>>> findNearbyOutlets({
    required LatLng center,
    required double radiusKm,
}) async {
    // Query Firestore for outlets within radius using GeoHash
    // Implementation using geoflutterfire or similar
    throw UnimplementedError();
}

```

```
}
```

```
### `lib/presentation/screens/location_screen.dart`
```

```
import 'package:flutter/material.dart';  
import 'package:flutter_riverpod/flutter_riverpod.dart';  
import 'package:go_router/go_router.dart';  
import '../core/theme/app_colors.dart';  
import '../core/theme/app_animations.dart';  
import '../core/theme/app_shadows.dart';  
import '../core/theme/app_typography.dart';  
import '../router/app_router.dart';  
import '../widgets/premium_button.dart';
```

```
class LocationScreen extends ConsumerStatefulWidget {  
  const LocationScreen({super.key});  
  
  @override  
  ConsumerState<LocationScreen> createState() => _LocationScreenState();  
}
```

```
class _LocationScreenState extends ConsumerState<LocationScreen>  
  with TickerProviderStateMixin {  
  late AnimationController _fadeController;  
  late AnimationController _pulseController;  
  
  @override  
  void initState() {  
    super.initState();  
    _fadeController = AnimationController(  
      vsync: this,  
      duration: AppAnimations.entrance,  
    );  
    _pulseController = AnimationController(  
      vsync: this,  
      duration: const Duration(seconds: 2),  
    )..repeat();  
  
    Future.delayed(const Duration(milliseconds: 200), () {  
      _fadeController.forward();  
    });  
  }  
}
```

```
@override  
void dispose() {  
  _fadeController.dispose();  
  _pulseController.dispose();  
  super.dispose();  
}
```

```

}

@override
Widget build(BuildContext context) {
  return Scaffold(
    backgroundColor: AppColors.brand,
    body: Stack(
      children: [
        // Background pattern
        Positioned.fill(
          child: Container(
            decoration: BoxDecoration(
              gradient: LinearGradient(
                begin: Alignment.topLeft,
                end: Alignment.bottomRight,
                colors: [
                  AppColors.brand,
                  const Color(0xFFC44008),
                  const Color(0xFFFF4732A),
                ],
                stops: const [0.0, 0.55, 1.0],
              ),
            ),
          ),
        // Radial gradients
        Positioned.fill(
          child: Container(
            decoration: BoxDecoration(
              gradient: RadialGradient(
                center: const Alignment(0.25, 0.75),
                radius: 0.5,
                colors: [
                  Colors.white.withOpacity(0.08),
                  Colors.transparent,
                ],
              ),
            ),
          ),
        Positioned.fill(
          child: Container(
            decoration: BoxDecoration(
              gradient: RadialGradient(
                center: const Alignment(0.8, 0.2),
                radius: 0.3,
                colors: [
                  Colors.white.withOpacity(0.06),
                  Colors.transparent,

```

```

        ],
      ),
    ),
  ),
),

// Content
SafeArea(
  child: Padding(
    padding: const EdgeInsets.symmetric(horizontal: 32),
    child: Column(
      children: [
        const Spacer(),

        // Animated location pin
        AnimatedBuilder(
          animation: _pulseController,
          builder: (context, child) {
            return SizedBox(
              width: 96,
              height: 96,
              child: Stack(
                alignment: Alignment.center,
                children: [
                  // Outer ripple
                  Container(
                    width: 96 + (_pulseController.value * 20),
                    height: 96 + (_pulseController.value * 20),
                    decoration: BoxDecoration(
                      shape: BoxShape.circle,
                      border: Border.all(
                        color: Colors.white.withOpacity(
                          0.3 * (1 - _pulseController.value),
                        ),
                        width: 1,
                      ),
                    ),
                  ),
                ],
              ),
            // Inner ripple
            Container(
              width: 96 + (((_pulseController.value + 0.5) %
1.0) * 20),
              height: 96 + (((_pulseController.value + 0.5)
% 1.0) * 20),
              decoration: BoxDecoration(
                shape: BoxShape.circle,
                border: Border.all(
                  color: Colors.white.withOpacity(
                    0.2 * (1 - ((_pulseController.value +
0.5) % 1.0))),

```

```

        ),
        width: 1,
      ),
    ),
  ),
  // Pin container
  Container(
    width: 96,
    height: 96,
    decoration: BoxDecoration(
      shape: BoxShape.circle,
      color: Colors.white.withOpacity(0.16),
      border: Border.all(
        color: Colors.white.withOpacity(0.2),
        width: 2,
      ),
      boxShadow: AppShadows.glow,
    ),
    child: const Icon(
      Icons.location_on,
      size: 40,
      color: Colors.white,
    ),
  ),
],
),
);
},
),

const SizedBox(height: 48),

// Typography with fade-up
FadeTransition(
  opacity: CurvedAnimation(
    parent: _fadeController,
    curve: const Interval(0.2, 1.0, curve:
AppAnimations.expoOut),
  ),
  child: SlideTransition(
    position: Tween<Offset>(
      begin: const Offset(0, 20),
      end: Offset.zero,
    ).animate(CurvedAnimation(
      parent: _fadeController,
      curve: const Interval(0.2, 1.0, curve:
AppAnimations.expoOut),
    )),
    child: Column(
      children: [

```



```

        Text(
          'Find your nearest\nBurger Farm',
          textAlign: TextAlign.center,
          style: AppTypography.display(
            size: 36,
            color: Colors.white,
            height: 1.15,
            letterSpacing: -0.01,
          ),
        ),
      ),
      const SizedBox(height: 16),
      Text(
        'We\'ll show you the closest outlet and your
estimated delivery time.',
        textAlign: TextAlign.center,
        style: AppTypography.body(
          size: 15,
          color: Colors.white.withOpacity(0.78),
          height: 1.55,
        ),
      ),
    ],
  ),
),
),

const Spacer(),

// Bottom actions
FadeTransition(
  opacity: CurvedAnimation(
    parent: _fadeController,
    curve: const Interval(0.5, 1.0, curve:
AppAnimations.backOut),
  ),
  child: SlideTransition(
    position: Tween<Offset>(
      begin: const Offset(0, 30),
      end: Offset.zero,
    ).animate(CurvedAnimation(
      parent: _fadeController,
      curve: const Interval(0.5, 1.0, curve:
AppAnimations.backOut),
    )),
    child: Column(
      children: [
        // Primary button
        Container(
          decoration: BoxDecoration(
            boxShadow: [

```

```
BoxShadow(
    color: Colors.white.withOpacity(0.25),
    blurRadius: 32,
    offset: const Offset(0, 12),
  ),
],
),
child: PremiumButton(
  text: 'Allow Location',
  backgroundColor: Colors.white,
  textColor: AppColors.brand,
  icon: const Icon(
    Icons.location_on,
    color: AppColors.brand,
    size: 22,
  ),
  onPressed: () => _handleAllowLocation(),
),
),

const SizedBox(height: 16),

// Ghost button
GestureDetector(
  onTap: () => context.go(AppRoute.address),
  child: Container(
    width: double.infinity,
    height: 50,
    decoration: BoxDecoration(
      color: Colors.white.withOpacity(0.05),
      borderRadius: BorderRadius.circular(20),
      border: Border.all(
        color: Colors.white.withOpacity(0.2),
      ),
    ),
    child: Center(
      child: Text(
        'Enter manually',
        style: AppTypography.body(
          size: 14,
          weight: FontWeight.w600,
          color: Colors.white,
        ),
      ),
    ),
  ),
),
),
),
),
),
),
```

```

    ),
    const SizedBox(height: 40),
  ],
),
),
),
),

// Bottom indicator
Positioned(
  bottom: 8,
  left: 0,
  right: 0,
  child: Center(
    child: Container(
      width: 128,
      height: 4,
      decoration: BoxDecoration(
        color: Colors.white.withOpacity(0.4),
        borderRadius: BorderRadius.circular(2),
      ),
    ),
  ),
),
),
),
),
],
),
);
}

Future<void> _handleAllowLocation() async {
  final mapsService = ref.read<MapsServiceProvider>();
  final hasPermission = await mapsService.handleLocationPermission();

  if (hasPermission) {
    final position = await mapsService.getCurrentPosition();
    // Store position, navigate to outlet selection
    context.go(AppRoute.outlet);
  } else {
    // Show permission denied dialog
    _showPermissionDialog();
  }
}

void _showPermissionDialog() {
  showDialog(
    context: context,
    builder: (context) => AlertDialog(
      title: Text(
        'Location Required',
        style: AppTypography.display(size: 18),
      ),
    ),
  );
}

```

```

    ),
    content: Text(
      'Please enable location services to find your nearest Burger Farm
outlet.',
      style: AppTypography.body(size: 14),
    ),
    actions: [
      TextButton(
        onPressed: () => Navigator.pop(context),
        child: Text(
          'Cancel',
          style: AppTypography.body(
            size: 14,
            color: AppColors.brand,
          ),
        ),
      ),
      TextButton(
        onPressed: () {
          Navigator.pop(context);
          Geolocator.openAppSettings();
        },
        child: Text(
          'Settings',
          style: AppTypography.body(
            size: 14,
            color: AppColors.brand,
            weight: FontWeight.w700,
          ),
        ),
      ),
    ],
  ),
);
}
}

```

```

### `lib/presentation/screens/outlet_screen.dart`
import 'package:flutter/material.dart';
import 'package:flutter_riverpod/flutter_riverpod.dart';
import 'package:go_router/go_router.dart';
import '...../core/theme/app_colors.dart';
import '...../core/theme/app_animations.dart';
import '...../core/theme/app_shadows.dart';
import '...../core/theme/app_typography.dart';
import '...../router/app_router.dart';

```

```

class OutletScreen extends ConsumerStatefulWidget {

```

```

const OutletScreen({super.key});

@override
ConsumerState<OutletScreen> createState() => _OutletScreenState();
}

class _OutletScreenState extends ConsumerState<OutletScreen>
    with TickerProviderStateMixin {
  late AnimationController _sheetController;
  bool _isDelivery = true;

  @override
  void initState() {
    super.initState();
    _sheetController = AnimationController(
      vsync: this,
      duration: AppAnimations.entrance,
    );
    Future.delayed(const Duration(milliseconds: 100), () {
      _sheetController.forward();
    });
  }

  @override
  void dispose() {
    _sheetController.dispose();
    super.dispose();
  }

  @override
  Widget build(BuildContext context) {
    return Scaffold(
      backgroundColor: const Color(0xFFFAFAFA),
      body: Stack(
        children: [
          // Map area
          Positioned(
            top: 0,
            left: 0,
            right: 0,
            height: MediaQuery.of(context).size.height * 0.4,
            child: Stack(
              children: [
                // Map pattern background
                Container(
                  decoration: const BoxDecoration(
                    color: Color(0xFFFF0F0F),
                  ),
                  child: CustomPaint(
                    size: Size.infinite,

```

```

        painter: _MapPatternPainter(),
      ),
    ),

    // Gradient overlay for header
    Positioned(
      top: 0,
      left: 0,
      right: 0,
      height: 128,
      child: Container(
        decoration: BoxDecoration(
          gradient: LinearGradient(
            begin: Alignment.topCenter,
            end: Alignment.bottomCenter,
            colors: [
              Colors.white.withOpacity(0.9),
              Colors.transparent,
            ],
          ),
        ),
      ),
    ),
  ),
),

// Header
SafeArea(
  child: Padding(
    padding: const EdgeInsets.symmetric(horizontal: 18,
vertical: 12),
    child: Column(
      crossAxisAlignment: CrossAxisAlignment.start,
      children: [
        Row(
          children: [
            GestureDetector(
              onTap: () => context.pop(),
              child: Container(
                width: 40,
                height: 40,
                decoration: BoxDecoration(
                  shape: BoxShape.circle,
                  color: Colors.white,
                  border: Border.all(color: AppColors.line),
                  boxShadow: [
                    BoxShadow(
                      color:
AppColors.brown.withOpacity(0.06),
                      blurRadius: 8,
                    ),
                  ],
                ),
              ),
            ),
          ],
        ),
      ],
    ),
  ),
),

```

```

        ),
        child: const Icon(
          Icons.arrow_back,
          size: 20,
        ),
      ),
    ),
    const SizedBox(width: 12),
    Text(
      'Select Outlet',
      style: AppTypography.display(size: 19),
    ),
  ],
),

const SizedBox(height: 16),

// Segmented control
Container(
  padding: const EdgeInsets.all(4),
  decoration: BoxDecoration(
    color: const Color(0xFFFFFAFA),
    borderRadius: BorderRadius.circular(12),
  ),
  child: Row(
    children: [
      _SegmentButton(
        icon: Icons.delivery_dining,
        label: 'Delivery',
        isActive: _isDelivery,
        onTap: () => setState(() => _isDelivery =
true),
      ),
      _SegmentButton(
        icon: Icons.shopping_bag,
        label: 'Pickup',
        isActive: !_isDelivery,
        onTap: () => setState(() => _isDelivery =
false),
      ),
    ],
  ),
),

// Map pin
Center(

```

```

child: Column(
  mainAxisAlignment: MainAxisAlignment.center,
  children: [
    Container(
      width: 48,
      height: 48,
      decoration: BoxDecoration(
        shape: BoxShape.circle,
        color: AppColors.brand,
        border: Border.all(
          color: Colors.white,
          width: 2.5,
        ),
      ),
      boxShadow: [
        BoxShadow(
          color: AppColors.brand.withOpacity(0.4),
          blurRadius: 24,
          offset: const Offset(0, 8),
        ),
      ],
    ),
    child: const Icon(
      Icons.location_on,
      color: Colors.white,
      size: 20,
    ),
  ],
),
const SizedBox(height: 8),
Container(
  padding: const EdgeInsets.symmetric(
    horizontal: 12,
    vertical: 6,
  ),
  decoration: BoxDecoration(
    color: Colors.white.withOpacity(0.96),
    borderRadius: BorderRadius.circular(9),
    boxShadow: [
      BoxShadow(
        color: AppColors.brown.withOpacity(0.1),
        blurRadius: 8,
      ),
    ],
  ),
),
child: Row(
  mainAxisAlignment: MainAxisAlignment.min,
  children: [
    Container(
      width: 6,
      height: 6,
      decoration: const BoxDecoration(

```



```

        shape: BoxShape.circle,
        color: AppColors.success,
      ),
    ),
    const SizedBox(width: 6),
    Text(
      '18 Min',
      style: AppTypography.body(
        size: 10.5,
        weight: FontWeight.w600,
      ),
    ),
  ],
),
],
),
],
),
],
),
],
),
),
),
// Bottom sheet
AnimatedBuilder(
  animation: _sheetController,
  builder: (context, child) {
    return Positioned(
      bottom: 0,
      left: 0,
      right: 0,
      height: MediaQuery.of(context).size.height * 0.62,
      child: Transform.translate(
        offset: Offset(
          0,
          40 * (1 - CurvedAnimation(
            parent: _sheetController,
            curve: AppAnimations.expoOut,
          ).value),
        ),
      ),
      child: Opacity(
        opacity: CurvedAnimation(
          parent: _sheetController,
          curve: AppAnimations.expoOut,
        ).value,
        child: Container(
          decoration: BoxDecoration(
            color: Colors.white,
            borderRadius: const BorderRadius.vertical(
              top: Radius.circular(32),
            ),
          ),

```

```

        boxShadow: AppShadows.float,
      ),
      child: Column(
        crossAxisAlignment: CrossAxisAlignment.start,
        children: [
          Padding(
            padding: const EdgeInsets.fromLTRB(24, 24, 24,
16),

            child: Text(
              'Nearest Outlets',
              style: AppTypography.display(size: 18),
            ),
          ),

          Expanded(
            child: ListView(
              padding: const
EdgeInsets.symmetric(horizontal: 16),
              children: [
                _OutletCard(
                  name: 'Burger Farm - CP',
                  address: 'Shop 12, Block B, Connaught
Place, New Delhi',

                  status: OutletStatus.open,
                  distance: '1.2 km',
                  time: '18-22 min',
                  isSelected: true,
                  onTap: () => context.go(AppRoute.home),
                ),
                const SizedBox(height: 12),
                _OutletCard(
                  name: 'Burger Farm - Rajouri',
                  address: 'J-14, Main Market Road, New
Delhi',

                  status: OutletStatus.closingSoon,
                  distance: '2.8 km',
                  time: '28-32 min',
                  onTap: () {},
                ),
                const SizedBox(height: 12),
                _OutletCard(
                  name: 'Burger Farm - Saket',
                  address: 'Select Citywalk, Ground Floor,
New Delhi',

                  status: OutletStatus.closed,
                  distance: '4.5 km',
                  time: 'Opens 11 AM',
                  onTap: null,
                ),
              ],
            ),
          ),
        ],
      ),
    ),
  ),
],
);
}

```

[illegible]

```
enum OutletStatus { open, closingSoon, closed }
```

```
class _SegmentButton extends StatelessWidget {
```

```
final IconData icon;  
final String label;  
final bool isActive;  
final VoidCallback onTap;
```

```
const _SegmentButton({
  required this.icon,
  required this.label,
  required this.isActive,
  required this.onTap,
});
```

```
@override
```

```
Widget build(BuildContext context) {
```

```
return Expanded(
  child: GestureDetector(
    onTap: onTap,
    child: AnimatedContainer(
      duration: const Duration(milliseconds: 300),
      curve: AppAnimations.spring,
      padding: const EdgeInsets.symmetric(vertical: 10),
      decoration: BoxDecoration(
        color: isActive ? AppColors.brand : Colors.transparent,
        borderRadius: BorderRadius.circular(9),
        boxShadow: isActive
          ? [
              BoxShadow(
                color: AppColors.brand.withOpacity(0.28),
                blurRadius: 8,
                offset: const Offset(0, 2),
              ),
            ]
          : null,
      ),
    ),
  ),
);
```

```

        ],
        : null,
    ),
    child: Row(
      mainAxisAlignment: MainAxisAlignment.center,
      children: [
        Icon(
          icon,
          size: 14,
          color: isActive ? Colors.white : AppColors.brownMuted,
        ),
        const SizedBox(width: 6),
        Text(
          label,
          style: AppTypography.body(
            size: 12.5,
            weight: isActive ? FontWeight.w700 : FontWeight.w600,
            color: isActive ? Colors.white : AppColors.brownMuted,
          ),
        ),
      ],
    ),
  ],
),
),
),
),
);
}
}

```

```

class _OutletCard extends StatelessWidget {
  final String name;
  final String address;
  final OutletStatus status;
  final String distance;
  final String time;
  final bool isSelected;
  final VoidCallback? onTap;

  const _OutletCard({
    required this.name,
    required this.address,
    required this.status,
    required this.distance,
    required this.time,
    this.isSelected = false,
    this.onTap,
  });

  Color get _statusColor {
    switch (status) {
      case OutletStatus.open:

```

```

        return AppColors.success;
    case OutletStatus.closingSoon:
        return const Color(0xFFB45309);
    case OutletStatus.closed:
        return AppColors.danger;
    }
}

String get _statusText {
  switch (status) {
    case OutletStatus.open:
        return 'Open';
    case OutletStatus.closingSoon:
        return 'Closing Soon';
    case OutletStatus.closed:
        return 'Closed';
    }
}

@override
Widget build(BuildContext context) {
  return GestureDetector(
    onTap: onTap,
    child: AnimatedContainer(
      duration: const Duration(milliseconds: 300),
      curve: AppAnimations.spring,
      padding: const EdgeInsets.all(16),
      decoration: BoxDecoration(
        color: isSelected ? const Color(0xFFFFFAFA) : Colors.white,
        borderRadius: BorderRadius.circular(24),
        border: Border.all(
          color: isSelected ? AppColors.brand : AppColors.line,
          width: isSelected ? 2 : 1.5,
        ),
      ),
      boxShadow: isSelected
        ? [
            BoxShadow(
              color: AppColors.brand.withOpacity(0.15),
              blurRadius: 24,
              offset: const Offset(0, 8),
            ),
          ]
        : AppShadows.soft,
    ),
    child: Column(
      crossAxisAlignment: CrossAxisAlignment.start,
      children: [
        Row(
          crossAxisAlignment: CrossAxisAlignment.start,
          children: [

```

```

Expanded(
  child: Column(
    crossAxisAlignment: CrossAxisAlignment.start,
    children: [
      Text(
        name,
        style: AppTypography.body(
          size: 16,
          weight: FontWeight.w700,
        ),
      ),
      const SizedBox(height: 4),
      Text(
        address,
        style: AppTypography.body(
          size: 12,
          color: AppColors.brownMuted,
        ),
      ),
    ],
  ),
),
Container(
  padding: const EdgeInsets.symmetric(
    horizontal: 10,
    vertical: 5,
  ),
  decoration: BoxDecoration(
    color: _statusColor.withOpacity(0.1),
    borderRadius: BorderRadius.circular(7),
    border: Border.all(
      color: _statusColor.withOpacity(0.2),
    ),
  ),
  child: Text(
    _statusText,
    style: AppTypography.body(
      size: 10,
      weight: FontWeight.w700,
      color: _statusColor,
      letterSpacing: 0.1,
    ),
  ),
),
],
),
const SizedBox(height: 12),
Container(

```

```

padding: const EdgeInsets.only(top: 12),
decoration: BoxDecoration(
  border: Border(
    top: BorderSide(
      color: isSelected
        ? AppColors.brand.withOpacity(0.2)
        : AppColors.line,
    ),
  ),
),
child: Row(
  children: [
    _InfoItem(
      icon: Icons.location_on,
      text: distance,
      color: isSelected ? AppColors.brand : null,
    ),
    const SizedBox(width: 24),
    _InfoItem(
      icon: Icons.access_time,
      text: time,
      color: isSelected ? AppColors.brand : null,
    ),
    if (isSelected) ...[
      const Spacer(),
      Row(
        children: [
          Text(
            'Select',
            style: AppTypography.body(
              size: 13,
              weight: FontWeight.w700,
              color: AppColors.brand,
            ),
          ),
          const SizedBox(width: 4),
          const Icon(
            Icons.arrow_forward,
            size: 14,
            color: AppColors.brand,
          ),
        ],
      ),
    ],
  ),
),
],
),
],
),
],
),
),
],
),
),

```

```

    );
  }
}

class _InfoItem extends StatelessWidget {
  final IconData icon;
  final String text;
  final Color? color;

  const _InfoItem({
    required this.icon,
    required this.text,
    this.color,
  });

  @override
  Widget build(BuildContext context) {
    return Row(
      children: [
        Icon(
          icon,
          size: 14,
          color: color ?? AppColors.brownMuted,
        ),
        const SizedBox(width: 4),
        Text(
          text,
          style: AppTypography.body(
            size: 13,
            weight: FontWeight.w600,
            color: color ?? AppColors.brown,
          ),
        ),
      ],
    );
  }
}

class _MapPatternPainter extends CustomPainter {
  @override
  void paint(Canvas canvas, Size size) {
    final paint = Paint()
      ..color = const Color(0xFFE2E8F0)
      ..strokeWidth = 6;

    // Draw curved roads
    for (var i = 0; i < 3; i++) {
      final path = Path();
      final y = size.height * (0.25 + i * 0.25);
      path.moveTo(0, y);
    }
  }
}

```



```

        path.quadraticBezierTo(
            size.width * 0.25, y - 50,
            size.width * 0.5, y,
        );
        path.quadraticBezierTo(
            size.width * 0.75, y + 50,
            size.width, y,
        );
        canvas.drawPath(path, paint);
    }

    // Draw vertical roads
    for (var i = 1; i <= 3; i++) {
        final x = size.width * (i * 0.25);
        canvas.drawLine(
            Offset(x, 0),
            Offset(x, size.height),
            paint,
        );
    }
}

@override
bool shouldRepaint(covariant CustomPainter oldDelegate) => false;
}

### `lib/presentation/screens/home_screen.dart`

import 'package:flutter/material.dart';
import 'package:flutter_riverpod/flutter_riverpod.dart';
import 'package:go_router/go_router.dart';
import '../core/theme/app_colors.dart';
import '../core/theme/app_shadows.dart';
import '../core/theme/app_typography.dart';
import '../router/app_router.dart';

class HomeScreen extends ConsumerStatefulWidget {
    const HomeScreen({super.key});

    @override
    ConsumerState<HomeScreen> createState() => _HomeScreenState();
}

class _HomeScreenState extends ConsumerState<HomeScreen> {
    int _selectedIndex = 0;

```

```

@override
Widget build(BuildContext context) {
  return Scaffold(
    backgroundColor: const Color(0xFFFAFAFA),
    body: SafeArea(
      child: CustomScrollView(
        slivers: [
          // Header
          SliverToBoxAdapter(
            child: Padding(
              padding: const EdgeInsets.symmetric(horizontal: 24,
vertical: 16),
              child: Row(
                mainAxisAlignment: MainAxisAlignment.spaceBetween,
                children: [
                  Row(
                    children: [
                      Container(
                        width: 40,
                        height: 40,
                        decoration: BoxDecoration(
                          shape: BoxShape.circle,
                          color: AppColors.brand,
                          boxShadow: AppShadows.glow,
                        ),
                      child: const Center(
                        child: Text(
                          'V',
                          style: TextStyle(
                            color: Colors.white,
                            fontWeight: FontWeight.w700,
                            fontSize: 16,
                          ),
                        ),
                      ),
                    ],
                  ),
                  const SizedBox(width: 12),
                  Column(
                    crossAxisAlignment: CrossAxisAlignment.start,
                    children: [
                      Text(
                        'Deliver to',
                        style: AppTypography.body(
                          size: 11,
                          weight: FontWeight.w700,
                          color: AppColors.brownMuted,
                          letterSpacing: 0.18,
                        ),
                      ),
                    ],
                  ),
                ],
              ),
            ),
          ),
        ],
      ),
    ),
  );
}

```

```

const SizedBox(height: 2),
GestureDetector(
  onTap: () => context.go(AppRoute.address),
  child: Row(
    children: [
      Text(
        'Home, 4B Block',
        style: AppTypography.body(
          size: 14,
          weight: FontWeight.w700,
        ),
      ),
      const SizedBox(width: 4),
      const Icon(
        Icons.keyboard_arrow_down,
        size: 14,
        color: AppColors.brand,
      ),
    ],
  ),
),
],
),
],
),
),
Stack(
  children: [
    Container(
      width: 40,
      height: 40,
      decoration: BoxDecoration(
        shape: BoxShape.circle,
        color: AppColors.cream,
        border: Border.all(color: AppColors.line),
      ),
      child: const Icon(
        Icons.shopping_cart_outlined,
        size: 20,
      ),
    ),
    Positioned(
      top: 0,
      right: 0,
      child: Container(
        width: 12,
        height: 12,
        decoration: BoxDecoration(
          shape: BoxShape.circle,
          color: AppColors.brand,
          border: Border.all(

```

```

        color: Colors.white,
        width: 2,
      ),
    ),
  ),
],
),
vertical: 8),
SliverToBoxAdapter(
  child: Padding(
    padding: const EdgeInsets.symmetric(horizontal: 24,
vertical: 12),
    child: Container(
      padding: const EdgeInsets.symmetric(horizontal: 16,
vertical: 12),
      decoration: BoxDecoration(
        color: Colors.white,
        borderRadius: BorderRadius.circular(100),
        border: Border.all(
          color: AppColors.line,
          width: 1.5,
        ),
        boxShadow: AppShadows.soft,
      ),
      child: Row(
        children: [
          Icon(
            Icons.search,
            size: 18,
            color: AppColors.brownMuted,
          ),
          const SizedBox(width: 12),
          Expanded(
            child: TextField(
              decoration: InputDecoration(
                hintText: 'Search burgers, sides...',
                hintStyle: AppTypography.body(
                  size: 14,
                  color: AppColors.brownMuted,
                ),
                border: InputBorder.none,
                isDense: true,
                contentPadding: EdgeInsets.zero,
              ),

```

```

        ),
      ),
    ],
  ),
),
),
),
),

// Hero banner
SliverToBoxAdapter(
  child: Padding(
    padding: const EdgeInsets.all(24),
    child: GestureDetector(
      onTap: () => context.go(AppRoute.detail),
      child: Container(
        height: 176,
        decoration: BoxDecoration(
          borderRadius: BorderRadius.circular(28),
          color: AppColors.brand,
          boxShadow: AppShadows.brandGlow,
        ),
        child: ClipRRect(
          borderRadius: BorderRadius.circular(28),
          child: Stack(
            children: [
              // Gradient background
              Container(
                decoration: BoxDecoration(
                  gradient: LinearGradient(
                    begin: Alignment.centerLeft,
                    end: Alignment.centerRight,
                    colors: [
                      AppColors.brand,
                      AppColors.brand,
                      AppColors.brand.withOpacity(0),
                    ],
                  ),
                ),
              ),
            ],
          ),
        ),
      ),
    ),

// Floating orbs
Positioned(
  left: -40,
  bottom: -40,
  child: Container(
    width: 192,
    height: 192,
    decoration: BoxDecoration(
      shape: BoxShape.circle,
      color: const

```

```

Color(0xFFFF7A33).withOpacity(0.8),
    ),
    child: BackdropFilter(
      filter: ImageFilter.blur(sigmaX: 40, sigmaY:
40),

      child: Container(color: Colors.transparent),
    ),
  ),
),
Positioned(
  right: -20,
  top: -80,
  child: Container(
    width: 224,
    height: 224,
    decoration: BoxDecoration(
      shape: BoxShape.circle,
      color: const
Color(0xFFC94208).withOpacity(0.6),
    ),
    child: BackdropFilter(
      filter: ImageFilter.blur(sigmaX: 50, sigmaY:
50),

      child: Container(color: Colors.transparent),
    ),
  ),
),

// Content
Padding(
  padding: const EdgeInsets.all(24),
  child: Column(
    crossAxisAlignment: CrossAxisAlignment.start,
    mainAxisAlignment: MainAxisAlignment.center,
    children: [
      Container(
        padding: const EdgeInsets.symmetric(
          horizontal: 10,
          vertical: 6,
        ),
        decoration: BoxDecoration(
          color: Colors.white.withOpacity(0.2),
          borderRadius: BorderRadius.circular(8),
          border: Border.all(
            color: Colors.white.withOpacity(0.3),
          ),
        ),
        child: Text(
          'New Release',
          style: AppTypography.body(

```

```

        size: 10,
        weight: FontWeight.w900,
        color: Colors.white,
        letterSpacing: 0.2,
      ),
    ),
  ),
  const SizedBox(height: 8),
  Text(
    'Truffle\nMushroom',
    style: AppTypography.display(
      size: 26,
      color: Colors.white,
      height: 1.1,
    ),
  ),
  const SizedBox(height: 8),
  Row(
    children: [
      Text(
        '₹249',
        style: AppTypography.display(
          size: 15,
          color: Colors.white,
        ),
      ),
      const SizedBox(width: 6),
      Text(
        '₹299',
        style: AppTypography.body(
          size: 12,
          color:
Colors.white.withOpacity(0.6),
          decoration:
TextDecoration.lineThrough,
        ),
      ),
    ],
  ),
],
),
),
// Burger image placeholder
Positioned(
  right: -40,
  top: 0,
  bottom: 0,
  child: Container(
    width: 192,
```

```

        decoration: BoxDecoration(
          image: const DecorationImage(
            image:
AssetImage('assets/veg_burger.png'),
            fit: BoxFit.contain,
          ),
          boxShadow: [
            BoxShadow(
              color: Colors.black.withOpacity(0.3),
              blurRadius: 20,
              offset: const Offset(-10, 10),
            ),
          ],
        ),
      ),
    ),
  ],
),
// Categories
SliverToBoxAdapter(
  child: Column(
    crossAxisAlignment: CrossAxisAlignment.start,
    children: [
      Padding(
        padding: const EdgeInsets.symmetric(horizontal: 24),
        child: Text(
          'Categories',
          style: AppTypography.display(size: 18),
        ),
      ),
      const SizedBox(height: 16),
      SizedBox(
        height: 100,
        child: ListView(
          scrollDirection: Axis.horizontal,
          padding: const EdgeInsets.symmetric(horizontal: 24),
          children: [
            _CategoryItem(
              icon: Icons.lunch_dining,
              label: 'Burgers',
              isActive: true,
            ),
            const SizedBox(width: 16),
            _CategoryItem(

```



```

        icon: Icons.local_drink,
        label: 'Sides',
      ),
      const SizedBox(width: 16),
      _CategoryItem(
        icon: Icons.wine_bar,
        label: 'Drinks',
      ),
      const SizedBox(width: 16),
      _CategoryItem(
        icon: Icons.icecream,
        label: 'Desserts',
      ),
    ],
  ),
],
),
),
// Popular items
SliverToBoxAdapter(
  child: Padding(
    padding: const EdgeInsets.all(24),
    child: Column(
      crossAxisAlignment: CrossAxisAlignment.start,
      children: [
        Text(
          'Popular Now',
          style: AppTypography.display(size: 18),
        ),
        const SizedBox(height: 16),
        _MenuItemCard(
          image: 'assets/veg_burger.png',
          name: 'Farmhouse Special',
          description: 'Crispy patty, fresh veggies, secret sauce.',
          price: '₹149',
          isVeg: true,
          onTap: () => context.go(AppRoute.detail),
        ),
        const SizedBox(height: 20),
        _MenuItemCard(
          image: 'assets/nonveg_burger.png',
          name: 'Double Chicken XL',
          description: 'Two grilled patties, extra cheese.',
          price: '₹229',
          isVeg: false,
          onTap: () => context.go(AppRoute.detail),
        ),

```

```

    ],
  ),
),
// Bottom padding for nav bar
const SliverToBoxAdapter(
  child: SizedBox(height: 100),
),
],
),
),
// Bottom navigation
bottomNavigationBar: Container(
  height: 84,
  decoration: BoxDecoration(
    color: Colors.white.withOpacity(0.9),
    borderRadius: const BorderRadius.vertical(
      top: Radius.circular(32),
    ),
    boxShadow: AppShadows.float,
    border: Border(
      top: BorderSide(
        color: Colors.white.withOpacity(0.6),
      ),
    ),
  ),
  child: ClipRRect(
    borderRadius: const BorderRadius.vertical(
      top: Radius.circular(32),
    ),
    child: BackdropFilter(
      filter: ImageFilter.blur(sigmaX: 20, sigmaY: 20),
      child: Padding(
        padding: const EdgeInsets.symmetric(horizontal: 24),
        child: Row(
          mainAxisAlignment: MainAxisAlignment.spaceAround,
          children: [
            _NavItem(
              icon: Icons.home,
              label: 'Home',
              isActive: _selectedIndex == 0,
              onTap: () => setState(() => _selectedIndex = 0),
            ),
            _NavItem(
              icon: Icons.local_offer_outlined,
              label: 'Offers',
              isActive: _selectedIndex == 1,
              onTap: () => setState(() => _selectedIndex = 1),
            ),
          ],
        ),
      ),
    ),
  ),
),
)

```

```

    ),
    _NavItem(
      icon: Icons.receipt_long_outlined,
      label: 'Orders',
      isActive: _selectedIndex == 2,
      onTap: () => setState(() => _selectedIndex = 2),
    ),
    _NavItem(
      icon: Icons.person_outline,
      label: 'Profile',
      isActive: _selectedIndex == 3,
      onTap: () => context.go(AppRoute.splash),
    ),
  ],
),
),
),
),
),
),
),
);
}
}

```

```

class _CategoryItem extends StatelessWidget {
  final IconData icon;
  final String label;
  final bool isActive;

  const _CategoryItem({
    required this.icon,
    required this.label,
    this.isActive = false,
  });

  @override
  Widget build(BuildContext context) {
    return Column(
      children: [
        AnimatedContainer(
          duration: const Duration(milliseconds: 300),
          curve: AppAnimations.spring,
          width: 64,
          height: 64,
          decoration: BoxDecoration(
            color: isActive ? AppColors.brand : Colors.white,
            borderRadius: BorderRadius.circular(20),
            border: isActive
              ? Border.all(color: Colors.white.withOpacity(0.2))
              : Border.all(color: AppColors.line.withOpacity(0.6)),
            boxShadow: isActive ? AppShadows.brandGlow : AppShadows.premium,
          ),
        ),
      ],
    );
  }
}

```

```

        ),
        child: Icon(
          icon,
          size: 28,
          color: isActive ? Colors.white : AppColors.brand,
        ),
      ),
      const SizedBox(height: 8),
      Text(
        label,
        style: AppTypography.body(
          size: 12,
          weight: FontWeight.w700,
          color: isActive ? AppColors.brown : AppColors.brownMuted,
        ),
      ),
    ],
  ),
];
};
}
}

```

```

class _MenuItemCard extends StatelessWidget {
  final String image;
  final String name;
  final String description;
  final String price;
  final bool isVeg;
  final VoidCallback onTap;

  const _MenuItemCard({
    required this.image,
    required this.name,
    required this.description,
    required this.price,
    required this.isVeg,
    required this.onTap,
  });

  @override
  Widget build(BuildContext context) {
    return GestureDetector(
      onTap: onTap,
      child: Container(
        padding: const EdgeInsets.all(12),
        decoration: BoxDecoration(
          color: Colors.white.withOpacity(0.8),
          borderRadius: BorderRadius.circular(24),
          border: Border.all(
            color: AppColors.line,
            width: 1.5,

```

```

    ),
    boxShadow: AppShadows.premium,
  ),
  child: Row(
    children: [
      // Image
      Container(
        width: 112,
        height: 112,
        decoration: BoxDecoration(
          color: AppColors.cream,
          borderRadius: BorderRadius.circular(16),
          image: DecorationImage(
            image: AssetImage(image),
            fit: BoxFit.cover,
          ),
        ),
      ),
    ],
  ),

  const SizedBox(width: 16),

  // Content
  Expanded(
    child: Column(
      crossAxisAlignment: CrossAxisAlignment.start,
      children: [
        // Veg/Non-veg indicator
        Row(
          children: [
            Container(
              width: 14,
              height: 14,
              decoration: BoxDecoration(
                border: Border.all(
                  color: isVeg ? AppColors.success :
AppColors.danger,

                  width: 1.5,
                ),
                borderRadius: BorderRadius.circular(3),
              ),
            child: Center(
              child: Container(
                width: 6,
                height: 6,
                decoration: BoxDecoration(
                  shape: BoxShape.circle,
                  color: isVeg ? AppColors.success :
AppColors.danger,

                ),
              ),
            ),
          ],
        ),
      ],
    ),
  ),

```

```

        ),
      ),
      const SizedBox(width: 6),
      Text(
        isVeg ? 'Veg' : 'Non-Veg',
        style: AppTypography.body(
          size: 10,
          weight: FontWeight.w700,
          color: isVeg ? AppColors.success :
AppColors.danger,
          letterSpacing: 0.18,
        ),
      ),
    ],
  ),

  const SizedBox(height: 6),

  Text(
    name,
    style: AppTypography.body(
      size: 16,
      weight: FontWeight.w700,
    ),
  ),

  const SizedBox(height: 6),

  Text(
    description,
    style: AppTypography.body(
      size: 12,
      color: AppColors.brownMuted,
    ),
    maxLines: 1,
    overflow: TextOverflow.ellipsis,
  ),

  const SizedBox(height: 12),

  Row(
    mainAxisAlignment: MainAxisAlignment.spaceBetween,
    children: [
      Text(
        price,
        style: AppTypography.display(
          size: 18,
          weight: FontWeight.w900,
        ),
      ),
    ],
  ),

```



```

mainAxisAlignment: MainAxisAlignment.center,
children: [
  Stack(
    alignment: Alignment.center,
    children: [
      if (isActive)
        Container(
          width: 48,
          height: 32,
          decoration: BoxDecoration(
            color: AppColors.brand.withOpacity(0.1),
            borderRadius: BorderRadius.circular(12),
          ),
        ),
      Icon(
        icon,
        size: isActive ? 24 : 22,
        color: isActive ? AppColors.brand : AppColors.brownMuted,
      ),
    ],
  ),
  const SizedBox(height: 6),
  Text(
    label,
    style: AppTypography.body(
      size: isActive ? 11 : 10,
      weight: isActive ? FontWeight.w900 : FontWeight.w700,
      color: isActive ? AppColors.brand : AppColors.brownMuted,
      letterSpacing: isActive ? 0.05 : 0,
    ),
  ),
  if (isActive) ...[
    const SizedBox(height: 4),
    Container(
      width: 6,
      height: 6,
      decoration: BoxDecoration(
        shape: BoxShape.circle,
        color: AppColors.brand,
        boxShadow: AppShadows.glow,
      ),
    ),
  ],
],
),
);
}

```


7. State Management & Backend Integration

```
### `lib/domain/providers/auth_provider.dart`
```

```
import 'package:flutter_riverpod/flutter_riverpod.dart';
```

```
import 'package:firebase_auth/firebase_auth.dart';
```

```
import '../data/services/firebase_service.dart';
```

```
final authStateProvider = StreamProvider<User?>((ref) {  
  return ref.watch(firebaseServiceProvider).authStateChanges;  
});
```

```
final authControllerProvider = StateNotifierProvider<AuthController,  
AsyncValue<void>>((ref) {  
  return AuthController(ref);  
});
```

```
class AuthController extends StateNotifier<AsyncValue<void>> {  
  final Ref _ref;
```

```
  AuthController(this._ref) : super(const AsyncValue.data(null));
```

```
  Future<void> sendOTP(String phoneNumber) async {  
    state = const AsyncValue.loading();  
    try {  
      await _ref.read(firebaseServiceProvider).verifyPhoneNumber(  
        phoneNumber: phoneNumber,  
        onCodeSent: (verificationId) {  
          // Store verification ID for later use  
          _ref.read(verificationIdProvider.notifier).state = verificationId;  
          state = const AsyncValue.data(null);  
        },  
        onError: (error) {  
          state = AsyncValue.error(error, StackTrace.current);  
        },  
      );  
    } catch (e, st) {  
      state = AsyncValue.error(e, st);  
    }  
  }  
}
```

```
  Future<void> verifyOTP(String smsCode) async {  
    state = const AsyncValue.loading();  
    try {  
      final verificationId = _ref.read(verificationIdProvider);  
      await _ref.read(firebaseServiceProvider).signInWithOTP(  
        verificationId: verificationId,  
        smsCode: smsCode,
```

```

    );
    state = const AsyncValue.data(null);
  } catch (e, st) {
    state = AsyncValue.error(e, st);
  }
}

Future<void> signInWithApple() async {
  state = const AsyncValue.loading();
  try {
    await _ref.read(firebaseServiceProvider).signInWithApple();
    state = const AsyncValue.data(null);
  } catch (e, st) {
    state = AsyncValue.error(e, st);
  }
}

Future<void> signOut() async {
  await FirebaseAuth.instance.signOut();
}

final verificationIdProvider = StateProvider<String>((ref) => '');

### `lib/domain/providers/order_provider.dart`

import 'package:flutter_riverpod/flutter_riverpod.dart';
import 'package:cloud_firestore/cloud_firestore.dart';
import '../data/services/firebase_service.dart';

// Real-time order stream
final orderStreamProvider = StreamProvider.family<DocumentSnapshot, String>
((ref, orderId) {
  return ref.watch(firebaseServiceProvider).listenToOrder(orderId);
});

// Order processing with inventory management
final orderControllerProvider = StateNotifierProvider<OrderController,
AsyncValue<void>>((ref) {
  return OrderController(ref);
});

class OrderController extends StateNotifier<AsyncValue<void>> {
  final Ref _ref;

  OrderController(this._ref) : super(const AsyncValue.data(null));

  Future<bool> placeOrder({

```

```

        required String itemId,
        required int quantity,
        required Map<String, dynamic> deliveryAddress,
    }) async {
        state = const AsyncValue.loading();
        try {
            // Check and reserve inventory
            final reserved = await
_ref.read(firebaseServiceProvider).checkAndReserveInventory(
            itemId: itemId,
            quantity: quantity,
        );

            if (!reserved) {
                state = AsyncValue.error('Item out of stock', StackTrace.current);
                return false;
            }

            // Create order document
            final orderRef =
FirebaseFirestore.instance.collection('orders').doc();
            await orderRef.set({
                'id': orderRef.id,
                'itemId': itemId,
                'quantity': quantity,
                'status': 'confirmed',
                'deliveryAddress': deliveryAddress,
                'createdAt': FieldValue.serverTimestamp(),
                'updatedAt': FieldValue.serverTimestamp(),
            });

            state = const AsyncValue.data(null);
            return true;
        } catch (e, st) {
            state = AsyncValue.error(e, st);
            return false;
        }
    }
}

```

```

### `lib/main.dart`

```

```

import 'package:flutter/material.dart';
import 'package:flutter/services.dart';
import 'package:flutter_riverpod/flutter_riverpod.dart';
import 'package:firebase_core/firebase_core.dart';
import 'presentation/router/app_router.dart';

```

```

void main() async {

```

```

WidgetsFlutterBinding.ensureInitialized();

// Initialize Firebase
await Firebase.initializeApp();

// Set preferred orientations
await SystemChrome.setPreferredOrientations([
  DeviceOrientation.portraitUp,
  DeviceOrientation.portraitDown,
]);

// Set system UI overlay style
SystemChrome.setSystemUIOverlayStyle(
  const SystemUiOverlayStyle(
    statusBarColor: Colors.transparent,
    statusBarIconBrightness: Brightness.dark,
    systemNavigationBarColor: Colors.white,
    systemNavigationBarIconBrightness: Brightness.dark,
  ),
);

runApp(
  const ProviderScope(
    child: BurgerFarmApp(),
  ),
);
}

class BurgerFarmApp extends ConsumerWidget {
  const BurgerFarmApp({super.key});

  @override
  Widget build(BuildContext context, WidgetRef ref) {
    final router = ref.watch(routerProvider);

    return MaterialApp.router(
      title: 'Burger Farm',
      debugShowCheckedModeBanner: false,
      routerConfig: router,
      theme: ThemeData(
        useMaterial3: true,
        fontFamily: 'Recoleta',
        colorScheme: ColorScheme.fromSeed(
          seedColor: const Color(0xFFE8560A),
          primary: const Color(0xFFE8560A),
        ),
      ),
    );
  }
}

```

8. Scalability & Performance Considerations

`pubspec.yaml`

```
name: burger_farm
description: Burger Farm mobile app
publish_to: 'none'
version: 1.0.0+1
```

```
environment:
  sdk: '>=3.0.0 <4.0.0'
```

```
dependencies:
  flutter:
    sdk: flutter
```

State Management

```
flutter_riverpod: ^2.4.0
riverpod_annotation: ^2.2.0
```

Navigation

```
go_router: ^12.0.0
```

Firebase

```
firebase_core: ^2.24.0
firebase_auth: ^4.16.0
cloud_firestore: ^4.14.0
firebase_messaging: ^14.7.0
firebase_analytics: ^10.8.0
```

Maps & Location

```
google_maps_flutter: ^2.5.0
geolocator: ^10.1.0
google_maps_webservice: ^0.0.20
```

Auth

```
sign_in_with_apple: ^5.0.0
google_sign_in: ^6.1.0
```

UI

```
google_fonts: ^6.1.0
shimmer: ^3.0.0
cached_network_image: ^3.3.0
```

Utils

```
freezed_annotation: ^2.4.0
```

```
json_annotation: ^4.8.0
uuid: ^4.2.0
```

dev_dependencies:

```
flutter_test:
  sdk: flutter
flutter_lints: ^3.0.0
build_runner: ^2.4.0
freezed: ^2.4.0
json_serializable: ^6.7.0
riverpod_generator: ^2.3.0
```

flutter:

```
uses-material-design: true
```

assets:

- assets/
- assets/fonts/
- assets/images/

fonts:

- family: MontreuxClassic
 fonts:
 - asset: assets/fonts/MontreuxClassic-Regular.ttf
 weight: 400
 - asset: assets/fonts/MontreuxClassic-Bold.ttf
 weight: 700
- family: Recoleta
 fonts:
 - asset: assets/fonts/Recoleta-Regular.ttf
 weight: 400
 - asset: assets/fonts/Recoleta-Medium.ttf
 weight: 500
 - asset: assets/fonts/Recoleta-SemiBold.ttf
 weight: 600
 - asset: assets/fonts/Recoleta-Bold.ttf
 weight: 700