

組員: 1063054、1071551、1073808

Cisco Packet Tracer

File Edit Options View Tools Extensions Help

Logical Physical x 786 y 257

```
graph LR
    PC0[PC-PT PC0] --- S0[2960-24TT Switch0]
    PC1[PC-PT PC1] --- S0
    PC2[PC-PT PC2] --- S1[2960-24TT Switch1]
    PC3[PC-PT PC3] --- S1
    S0 --- R0[1941 Router0]
    S1 --- R0
```

PC0

Physical Config Desktop Programming Attributes

Command Prompt

```
Packet Tracer PC Command Line 1.0
C:\>ping 200.200.200.130

Pinging 200.200.200.130 with 32 bytes of data:

Reply from 200.200.200.130: bytes=32 time<1ms TTL=127
Reply from 200.200.200.130: bytes=32 time<1ms TTL=127
Reply from 200.200.200.130: bytes=32 time<1ms TTL=127
Reply from 200.200.200.130: bytes=32 time<1ms TTL=127

Ping statistics for 200.200.200.130:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>
```

Time: 02:29:07

Realtime Simulation

Copper Straight-Through

Windows taskbar: 下午 12:45 2021/11/4