

Metainfo Page

Gary B. Genett

2024-12-03

#WORK # metainfo page description text

#WORK metainfo file description text

Lorem Ipsum #0 in 2022

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #1 in 2022

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #2 in 2022

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #3 in 2022

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #4 in 2022

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #5 in 2022

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #6 in 2022

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #7 in 2022

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #8 in 2022

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #9 in 2022

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #0 in 2023

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #1 in 2023

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #2 in 2023

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #3 in 2023

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #4 in 2023

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #5 in 2023

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #6 in 2023

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #7 in 2023

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #8 in 2023

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #9 in 2023

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd ../documents
make -f ../.Composer/Makefile init
make -f ../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd ../tld
ln -rs ../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #0 in 2024

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #1 in 2024

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #2 in 2024

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #3 in 2024

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #4 in 2024

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #5 in 2024

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #6 in 2024

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #7 in 2024

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #8 in 2024

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

Lorem Ipsum #9 in 2024

Directory Tree

The ideal workflow is to put [Composer] in a top-level .Composer for each directory tree you want to manage, creating a structure similar to this:

```
.../.Composer
.../
.../tld/
.../tld/sub/
```

To save on disk space using a central [Composer] install for multiple directory trees, the [init] target can be used to create a linked .Composer directory, and then the entire directory tree can be converted to a [Composer] documentation archive ([Quick Start] example):

```
cd .../documents
make -f .../.Composer/Makefile init
make -f .../.Composer/Makefile install-all
make all-all
```

Customization

If specific settings need to be used, either globally or per-directory, .composer.mk and .composer.yml files can be created (see [Configuration Settings], [Quick Start] example):

```
make template >.composer.mk && $EDITOR .composer.mk
make template.yml >.composer.yml && $EDITOR .composer.yml
```

Custom targets can also be defined, using standard [GNU Make] syntax (see [Custom Targets]).

Important Notes

[GNU Make] does not support file and directory names with spaces in them, and neither does [Composer]. Documentation archives which have such files or directories will produce unexpected results.

It is fully supported for input files to be symbolic links to files that reside outside the documentation archive:

```
cd .../tld
ln -rs .../README.md ./
make README.html
```

Similarly to source code, [GNU Make] is meant to only run one instance within the directory at a time, and [Composer] shares this requirement. It should be run as a single user, to avoid duplication and conflicts. Concurrent runs will produce unexpected results. It is highly recommended to set [MAKEJOBS] to a value greater than the default, to speed up processing.

It is best practice to [install-force] after every [Composer] upgrade, in case there are any changes to the Makefile template (see [Templates]). Everything in [Composer] sources from the main Makefile, so that is the only file which requires review to see what changes have been made between versions.

Next Steps

The archive is ready, and each directory is both a part of the collective and its own individual instance. Targets can be run per-file, per-directory, or recursively through an entire directory tree. The most commonly used targets are in [Primary Targets].

Welcome to [Composer]. *Happy Making!*

#WORK # metainfo page description text