

# Paths

The path is a critical aspect of your environment, and is encapsulated in the **PATH** environment variable. On an RHEL 7 system for a user named **student**, we get:

```
1 $ echo $PATH
2 /usr/lib64/qt-3.3/bin:/usr/lib64/ccache:/usr/local/bin:/usr/bin:\
3 /usr/local/sbin:/usr/sbin:/home/student/.local/bin:/home/student/bin
```

(Note we have had to split the path across across two lines in the output.)

When a user tries to run a program, the path is searched (from left to right) until an executable program or script is found with that name. You can see what would be found with the **which** command, as in:

```
1 $ which --skip-alias emacs
2 /usr/bin/emacs
```

Note that if there was a **/usr/local/bin/emacs**, it would be executed instead, since it is earlier in the path.

It is easy to add directories to your path, as in:

```
1 $ MY_BIN_DIR=$HOME/my_bin_dir
2 $ export PATH=$MY_BIN_DIR:$PATH
3 $ export PATH=$PATH:$MY_BIN_DIR
```

with the first form prepending your new directory and the second appending it to the path.

Note that the current directory is noted by **./** and the directory up one level by **../**.

The current directory is never placed in the path by default. Thus, if you want to run **foobar** in the current directory, you must say:

```
1 $ ./foobar
```

for it to work.

You can save changes to your path by putting them in your shell initialization file, **.bashrc** in your home directory.

```
student@ubuntu: ~  
student@ubuntu:~$ echo $PATH  
/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/games:/usr/local/games:/snap/bin  
student@ubuntu:~$ OLDPATH=$PATH  
student@ubuntu:~$ PATH=$PATH:/opt/some_application  
student@ubuntu:~$ echo $PATH  
/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/games:/usr/local/games:/snap/bin:/opt/some_application  
student@ubuntu:~$ PATH=$OLDPATH  
student@ubuntu:~$ echo $PATH  
/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/games:/usr/local/games:/snap/bin  
student@ubuntu:~$
```

Another useful path variable is **CDPATH** which is searched when you change directories. For example:

```
1 $ cd bin  
2 -bash: cd: usr: No such file or directory  
3 $ export CDPATH=/usr:$CDPATH  
4 $ cd bin  
5 /usr/bin
```

Any path which begins with */* is considered absolute because it specifies the exact filesystem location. Otherwise, it is considered relative and it is implicitly assumed your current directory is prepended.