WHITEPAPER

Gaskiyya: verifiable bank communications

A registry that lets a bank customer confirm, in seconds, whether a message, link or call really came from their bank, without exposing message content or phone numbers.

Version	Date	Audience
1.0	October 2026	Bank technology, security, fraud and data protection teams

Contents

1	Executive summary
2	The problem: impersonation of banks
3	Design principles
4	System architecture
5	How verification works
6	Customer channels
7	The AI layer and its guardrails
8	Security and privacy
9	Bank integration
10	Deployment and operations
11	Limitations, risks and trade-offs
12	Implementation status and roadmap
A	Appendix A: API reference
B	Appendix B: Configuration reference
C	Appendix C: Glossary

Gaskiyya means "truth" in Hausa. Values quoted in this paper (time limits, rate limits, retention periods) are the defaults of the current release and are configurable where stated. Identifiers that appear in code, such as the token audience `gaskiya`, are written exactly as the software expects them.

1 Executive summary

Fraudsters copy a bank's wording, sender name and tone, then add a link, a phone number or a request for a code. A customer has no reliable way to tell the copy from the original. Gaskiyya gives the customer that way, and it does so with a lookup, not a guess.

When a bank sends a message, it also registers a fingerprint of that message with Gaskiyya: a SHA-256 digest of the canonical text, together with the recipient's number. When a customer doubts a message, their phone computes the same fingerprint and asks whether the bank registered it for their number. The answer is one of three fixed verdicts.

Verdict	When	What the customer sees
Confirmed	An exact, unexpired record exists for this number and this fingerprint	"Sent by your bank", with channel, date and time
Not confirmed	No such record	"Not confirmed", with advice not to click, call or share codes, and a summary of what the bank really sent recently
Cannot check	The registry is unavailable or the bank is not enrolled	"Cannot check right now", never "genuine"

The same registry verifies outbound calls. Before an agent dials, the contact centre announces the call. The customer's app shows "your bank is calling you" with a four-digit code that the agent reads aloud from their own screen. Caller ID, which can be spoofed, plays no part.

What makes the design suitable for a bank

- **No content is stored.** The registry holds keyed hashes and a few descriptive fields. A breach reveals no message text and no phone numbers.
- **Nothing changes for the customer.** Messages keep their wording, sender ID and length. Integration is one extra call at the point of sending.
- **No access to core banking.** Gaskiyya never reads balances, accounts or transactions, and needs no open banking API.
- **AI never decides.** Language models explain a "not confirmed" result and group reported fakes into campaigns. They run after the verdict and cannot change it.
- **It fails closed.** Any error produces "cannot check right now". There is no code path from an error to "confirmed".

> **For the fraud desk:** customer reports of fakes are grouped into campaigns by shared link domain, shared callback number or similar wording. Each campaign arrives with a drafted advisory that an analyst must approve. Gaskiyya never sends anything to customers on its own.

2 The problem: impersonation of banks

Impersonation scams succeed because the customer cannot verify the sender. An SMS sender ID can be spoofed or imitated. A caller ID can be spoofed. A link can differ from the bank's own by one hyphen, one dot or one look-alike character. The fraudster's message is often a near-perfect copy of a genuine one.

Banks respond with education: "we will never ask for your PIN". Education helps, but it asks the customer to judge content, which is exactly what a skilled copy defeats. The customer needs a yes-or-no answer from a source they can trust, at the moment of doubt.

Why existing signals fall short

Signal	Weakness
Sender ID on SMS	Can be imitated or spoofed on some routes; customers cannot tell a genuine sender ID from a copied one
Caller ID	Can be spoofed; a call that shows the bank's number proves nothing
Spotting fake links	Look-alike domains differ by a single character; punycode can render as familiar letters
Spam filters and AI classifiers	Produce a probability, not a fact; a good copy of a real message scores as genuine

Gaskiyya replaces judgement with a fact: either the bank recorded sending exactly this message to this number, or it did not.

3 Design principles

Six rules are fixed. Code that breaks one of them is wrong even if its tests pass. Changing any of them requires a written decision record and explicit approval.

1. **Only the registry confirms.** A message is confirmed only by an exact match against a record the bank registered. No AI model, heuristic or similarity score may produce a confirmation.
2. **Fail closed.** If the registry is unreachable or a check errors, the answer is "cannot check right now". It is never "genuine".

3. **Verification is bound to the recipient.** A record matches only for the phone number the bank sent it to. A genuine message replayed to another person does not verify.
4. **No message content is stored.** The registry holds keyed hashes and a few descriptive fields, such as channel, category and whether the message contained a link.
5. **The bank changes nothing the customer sees.** Messages keep their wording, sender ID and length. Integration is one extra call at the point of sending.
6. **Gaskiyya never asks for secrets.** No screen or bot message requests a PIN, password, card number or one-time code.

Each principle is enforced in code and covered by automated acceptance tests. The verdict itself is decided in one pure function with no network, model or clock access, which makes its behaviour exhaustively testable.

4 System architecture

Gaskiyya sits beside the bank's existing systems, not in their path (Figure 1). Bank systems call a bank-facing API to register messages and announce calls. Customer channels call a customer-facing API to check what they received. The bank delivers its messages exactly as before.

Components

Component	Responsibility
Bank-facing API	Accepts message registrations and call announcements. Authenticated with OAuth 2.0 client credentials; mutual TLS and an IP allowlist are enforced at the bank's or operator's gateway in front of it
Customer API	Answers checks of messages, links, screenshots and calls. Authenticated with a short-lived token signed by the bank. Rate limited per customer
Key service	Holds one HMAC-SHA-256 key per bank, apart from the data. Turns numbers and digests into keyed hashes
Registry store	Holds keyed hashes, descriptive fields and call sessions, each with an expiry. Behind a repository interface so a bank can use its own standard database
Verdict engine	A single pure function that turns a lookup into one of three verdicts and fails closed
Call sessions	Open, answer and end announced calls; generate the four-digit code
Notice delivery	Sends "your bank is calling" notices by Firebase Cloud Messaging and a live event stream to an open app
Verification log	Records verdict counts without content, for coverage and usage metrics
AI service	Explains "not confirmed" results, reads screenshots, embeds reports. Gemini by default, OpenAI as an option, both behind one interface
Campaign agent	Groups reported fakes into campaigns and drafts advisories for analyst approval

Technology

The registry is a TypeScript service on Node.js and Fastify. Requests are validated against strict schemas before any logic runs. Production storage is Google Cloud Firestore with time-to-live policies; an in-memory store exists for tests and demonstrations and is refused in production. Push notices use Firebase Cloud Messaging HTTP v1. Email uses Resend. The customer app is built with Flutter. The canonicalisation library exists in TypeScript and Dart, and both are checked against the same shared test vectors.

Every external service sits behind an interface: store, key service, model provider, push provider and messaging. Tests run against in-memory implementations of each, and a bank can substitute its own.




Figure 1. System architecture. The message gateway delivers to the customer directly; Gaskiyya is never in the delivery path.

5 How verification works

5.1 The fingerprint

Before hashing, text is canonicalised so that harmless differences, such as extra spaces or invisible characters, do not change the result, while every meaningful character does. The steps run in this exact order:

1. Remove zero-width characters: U+200B, U+200C, U+200D, U+2060 and U+FEFF.
2. Apply Unicode NFKC normalisation.
3. Collapse every run of whitespace, including line breaks, to one space. The whitespace set is listed explicitly so that every language implementation agrees: tab, line feed, vertical tab, form feed, carriage return, space, U+0085, U+00A0, U+1680, U+2000 to U+200A, U+2028, U+2029, U+202F, U+205F and U+3000.
4. Trim spaces from both ends.

The digest is the SHA-256 of the canonical text's UTF-8 bytes, written as 64 lowercase hexadecimal characters. Letter case and punctuation are deliberately kept: a single hyphen or dot is the difference between the bank's link and a fake one. Figure 2 shows the full path from message to stored record.

The TypeScript and Dart libraries are verified against 36 shared test vectors, including multi-line SMS, the naira sign, Nigerian Pidgin text, zero-width characters, compatibility forms and tampered links. A bank that writes its own implementation in another language passes the same vectors before going live.

5.2 Registering a message

The bank's connector computes the digest and sends it, with the recipient's E.164 number, the channel, the message category, whether it contains a link, the link domains, whether it asks the customer to call back, and the send time. The registry immediately converts the number and the digest into keyed hashes:

```
recipientKey = HMAC-SHA-256(bankKey, "recipient:" + E.164 number)
contentKey   = HMAC-SHA-256(bankKey, "content:"   + contentDigest)
```

It stores the record with an expiry and discards the plain number and the digest. Records expire 30 days after the send time by default; the period is configurable per bank. A registration that repeats an idempotency key returns the original record instead of creating a second one. Figure 3 shows registration and verification end to end.

5.3 Verifying a message

The customer is identified by a token their bank signed. In the app, the text is canonicalised and digested on the device, so the text never leaves the phone. The registry keys the number and digest with the bank's key and performs one exact lookup. Reads time out after three seconds, and a timeout

is treated as an error. Figure 4 shows every gate a check passes.

Every "not confirmed" result also shows what the bank did send to this number in the last 24 hours, built only from descriptive fields. For example: "In the last 24 hours DemoBank sent you two transaction alerts by SMS. Neither contained a link." An expired record and a record that never existed give the same answer, because the registry cannot tell them apart.

The wording the customer reads for each verdict comes from one shared file of fixed text. Screens and bot replies cannot invent their own verdict wording.

5.4 Verifying a link

A link is checked against the domains the bank registered. A host that equals a registered domain, or is a subdomain of one, "belongs to the bank". Everything else is "not confirmed". The registry also records why a link failed, and these reasons feed the explanation, never the verdict:

Reason	Meaning
`lookalike`	The bank's name, or a registered domain's first label, appears inside another domain after mapping common substitutions (0 for o, 1 for l, rn for m, vv for w and others)
`punycode`	A label begins with `xn--`, which is how look-alike Unicode domains appear
`shortened`	The host is a known link shortener. Shortened links are never confirmed
`ip_address`	The host is a bare IP address
`not_http`	The scheme is not http or https
`not_registered`	The host is not on any registered domain

5.5 Verifying a call

A call cannot be hashed, so it is registered as a session. Before dialling, the contact centre announces the call with the customer's number, a purpose and an agent reference. The registry opens a session with a random four-digit code and sends the customer's app a notice. The agent reads the code from their own screen; the customer compares it with the code in the app (Figure 5).

If no session is open for the customer's number, the app states that the bank is not calling them, and advises them to hang up on anyone who claims otherwise. Call purposes are a fixed list: card activation, fraud check, loan follow-up, account update and service follow-up.




Figure 2. From message to stored record. The bank and the phone compute the same digest; the registry keys it with the bank's secret and stores neither the digest nor the number.




Figure 3. Registration at send time, and verification when the customer doubts the message.




Figure 4. The gates a check passes. Only an exact, unexpired record for the checking number produces "confirmed".




Figure 5. Call verification. The session lasts 180 seconds unanswered; once answered it is kept for up to two hours, and ending the call closes it at once.

6 Customer channels

Customers reach Gaskiyya through channels they already use. The route inside the bank's own app is the primary one, because it carries the bank's identity and keeps message text on the device.

Channel	What the customer can do	How it connects and its limits
Bank app	Check text, a screenshot or a link; see whether the bank is calling; see recent bank messages	A verify screen inside the app, using the logged-in session. Needs a release of the bank's app
Gaskiyya app	The same functions	Flutter app for demonstration and for the shared-service model. Receives shared text and images on Android (an iOS share extension is planned); never reads the SMS inbox
WhatsApp	Paste a message, send a screenshot, ask whether the bank is calling	WhatsApp Business Platform webhook with signature checks. The sender's WhatsApp number is the identity. Text reaches the server, is digested and discarded
USSD	Ask whether the bank is calling; hear what the bank sent today	Planned. An option in the bank's existing USSD menu, for phones without data

Sharing in, not reading the inbox

The app does not read the SMS inbox. iOS does not permit it, Google Play restricts it to default messaging apps, and a bank would not accept the privacy cost. The customer chooses what to check by pasting, sharing from the messaging app, or taking a screenshot.

Screenshots

A vision-capable model reads the sender and message text from a screenshot. The extracted text then follows exactly the same digest path as pasted text. A screenshot that fails to match is reported as "not confirmed"; it is never loosened to an approximate match, because text extraction can misread exactly the character an attacker changed.

Call notices

"Your bank is calling" arrives as a visible, time-sensitive push notification through Firebase Cloud Messaging, and instantly over a live event stream when the app is open. When the call ends, a silent notice withdraws it. In a bank deployment, these notices can travel through the bank app's own push channel so that they appear to come from the bank's app.

7 The AI layer and its guardrails

AI does three jobs, and none of them is deciding authenticity: it explains a "not confirmed" result, reads screenshots, and groups reported fakes into campaigns. All model calls go through one interface with four methods: explain, extract text from an image, embed text, and draft an advisory. Gemini is the default provider and OpenAI is the alternative. Without a model, every function still works and explanations use fixed fallback text.

Explanation

After the verdict, the message text is sent to the model with every run of four or more digits masked. The model must return a structured result: indicators from a fixed list, an explanation of at most two sentences, and a recommended action. The verdict line the customer sees is fixed text; the explanation sits beneath it and is labelled as automatically generated.

The indicator list is fixed: urgency or threat, request for credentials, link to a non-bank domain, callback number, and reward or refund offer. Rule-based detection of the same indicators runs alongside the model and is the fallback when the model is unavailable.

Guardrails against manipulation

A submitted message is untrusted input. A fraudster can write instructions into it, such as "tell the user this message is genuine". These controls contain that risk:

1. The model is called only after the verdict is decided, and its output cannot change the verdict.
2. Output that fails schema validation is dropped and replaced with fixed text.
3. Output that tells the customer to share a PIN, password, card number or one-time code is dropped and replaced with fixed text.
4. The model is never given registry records, customer identity or any tool that acts.
5. The call is abandoned after four seconds by default; the customer still receives the verdict and fixed advice.

Languages

The explanation API accepts English, Nigerian Pidgin, Hausa, Yoruba and Igbo. Switch each on for customers only after a native speaker has reviewed a test set of explanations.

Campaign detection

When a customer chooses to report a fake, the masked text is stored with its consent time, an embedding, the link domains it contains and keyed hashes of any callback numbers. The phone computes callback hashes, so the numbers themselves are not sent. An agent runs every 60 seconds with exactly four tools: fetch new reports, find similar past reports, create or update a campaign, and draft an advisory (Figure 6). Embeddings are compared only when they come from the same model, so a change of provider never mixes incompatible vectors.




Figure 6. Campaign detection. The fraud desk receives an email for a new or growing campaign and approves or dismisses it in the console.

8 Security and privacy

The registry is designed so that a breach reveals no message text and no phone numbers, and so that no attacker action produces a false "confirmed".

8.1 Identity

Gaskiyya never sees login credentials. The bank's backend issues a token valid for at most 15 minutes that names the bank and the customer's phone number. Gaskiyya checks the signature against the bank's published JSON Web Key Set and nothing else (Figure 7).

Token claim	Requirement
`iss`	The bank's tenant id in Gaskiyya
`sub`	The customer's phone number in E.164 form, for example `+2348012345678`
`aud`	`gaskiya`
`iat`	Issued-at time; required. A token issued more than 15 minutes ago is refused
`exp`	Expiry; recommended, at most 15 minutes after `iat`
Algorithm	ES256, RS256 or EdDSA, signed with a key published in the bank's JWKS (identified by `kid` when the set holds several keys)

Bank systems authenticate with OAuth 2.0 client credentials and receive an access token valid for 10 minutes. Client secrets must be at least 24 characters. Mutual TLS and the network allowlist are enforced at the gateway in front of the service.

8.2 Threats and controls

Threat	Control
A genuine message is replayed to a different person	Records match only for the original recipient's keyed number
A genuine message is altered, for example the link is changed	Any change alters the digest, so nothing matches
Someone probes the service to learn what the bank sent a customer	Checks need the recipient's own bank-signed token or WhatsApp number, and are limited to 30 per minute per customer by default
A stolen bank credential registers fake messages as genuine	Mutual TLS, network allowlist, 10-minute access tokens, per-system clients; alert on unusual volume or new link domains; audit at the gateway
Instructions hidden in a message manipulate the AI	Verdict fixed before the model runs, schema validation, secret-request filter, no tools

A fraudster calls at the same moment as the bank	Only the genuine agent can read the session code from their screen
A fraudster impersonates the Gaskiyya WhatsApp number	Number published inside the bank app, verified business profile, in-app route primary, secrets never requested
The registry is breached, or its operator is curious	Only keyed hashes and descriptive fields are stored; keys are held apart from the data

8.3 Data handling and retention

Stored

Keyed hashes of numbers and digests, descriptive fields (channel, category, link flag and domains, callback flag, times), call sessions, verdict logs without content, push tokens of registered devices, and masked reports the customer chose to submit.

Never stored

Message text, plain phone numbers, contentDigest values, login credentials, PINs, account or transaction data.

Data	Retention (default)
Message records	30 days after the send time; configurable per bank
Call sessions	Open for 180 seconds unanswered or up to 2 hours once answered; deleted 24 hours after expiry
Verification logs	90 days
Idempotency keys	24 hours
Device push tokens	Until the device stops being valid; invalid tokens are removed automatically
Consented reports	No automatic expiry in the current release; the period should be set in the data processing agreement

Logging. Request bodies, query strings and authorisation headers are never logged. An automated test plants marker strings in request bodies and fails if any appear in the logs.

Consent. Verification stores no content. Reporting a fake is opt-in every time.

Known limitation. A digest of a short, predictable message such as a one-time code could be brute-forced by whoever handles it before keying. One-time codes expire within minutes, which limits the value, and a bank-hosted deployment removes the exposure. Customers are advised to check one-time code messages in the app, where the text stays on the device.

Regulatory review. The bank's data protection officer should review the design under the Nigeria Data Protection Act 2023. A shared-service deployment also needs a data processing agreement with each bank. Any transfer of masked text to a model provider outside Nigeria needs the same review.




Figure 7. Customer identity. The bank remains the only party that authenticates its customers.

9 Bank integration

Gaskiyya connects only where the bank sends communications. It needs no access to core banking, account data or transaction data. There are four touchpoints, and Figure 8 shows the workflow from agreement to production.

Bank system	What it does	Interface
Notification service (or gateway, or queue)	Registers each outbound message before or alongside hand-off	`POST /v1/messages`, `POST /v1/messages/batch`
Contact centre	Announces each outbound call before dialling and shows the code on the agent's screen	`POST /v1/calls`, `PATCH /v1/calls/{id}`
Mobile banking backend	Signs short-lived customer tokens and publishes the public keys	JWT plus a JWKS URL
Fraud desk	Reviews campaigns, approves or dismisses advisories, watches coverage	Console, `GET /v1/campaigns`, `GET /v1/metrics`, email alerts

9.1 Registering messages

A bank can register messages in three ways (Figure 9). Choose by what the bank can change most easily.

Rules for the registration path:

- **Never block sending.** Register asynchronously from a local retry queue; the message goes out regardless.
- **Register before the customer could check.** The target is under two seconds from send to searchable record.
- **Make retries safe.** Send an `Idempotency-Key` header of up to 128 characters. A repeat returns `200` with the original record; a new record returns `202`. In a batch, the key is suffixed with each message's position.
- **Hash exactly what is sent.** Compute the digest from the final text handed to the gateway, after any templating.

```
POST /v1/messages
Authorization: Bearer <bank access token>
Idempotency-Key: alert-7f3c9a
Content-Type: application/json

{
  "recipient": "+2348012345678",
  "channel": "sms",
  "contentDigest": "<64 lowercase hex characters>",
  "category": "transaction_alert",
  "hasLink": false,
  "linkDomains": [],
  "asksCallback": false,
  "sentAt": "2026-10-20T13:02:11Z"
}

202 Accepted
{ "recordId": "rec_...", "expiresAt": "2026-11-19T13:02:11.000Z" }
```

Categories are a fixed list: `otp`, `transaction_alert`, `security_notice`, `service_update`, `marketing` and `call_follow_up`. Channels are `sms`, `whatsapp`, `email` and `push`. A batch carries up to 500 messages.

9.2 Announcing calls

```
POST /v1/calls
{ "recipient": "+2348012345678", "purpose": "card_activation", "agentRef": "agent-017" }

201 Created
{ "id": "call_...", "code": "4821", "status": "open", "expiresAt": "..." }

PATCH /v1/calls/call_...
{ "status": "answered" }   then later   { "status": "ended" }
```

The agent's screen must display the returned code. A small panel in the agent desktop is enough. Calls placed by staff on personal phones have no announcement and therefore no session; they are outside the first release.

9.3 Customer tokens

The bank's backend signs a token as described in section 8.1 whenever the app opens the verify screen, and publishes its public keys at a stable HTTPS URL registered as the tenant's `tokenKeysUrl`. Gaskiyya caches the key set for up to ten minutes, so keys can be rotated by publishing the new key

before signing with it.

Three ways to bring the verify screen into the bank's app:

1. **API only.** The bank's app team builds the screen against the customer API. Least risk to the app, most effort for the bank. Recommended for a pilot.
2. **Native libraries.** Thin Android and iOS libraries supply the screen, canonicalisation and API client. Planned.
3. **Embedded Flutter module.** Fastest from the existing codebase; adds app size and a second UI framework.

9.4 Onboarding checklist

#	Item	Owner
1	Data protection review and data processing terms	Bank DPO and legal
2	Choose bank-hosted or shared deployment	Bank architecture
3	Tenant record: id, name, official domains, sender IDs, JWKS URL, record retention, fraud desk emails	Bank and operator
4	Per-bank hashing key of at least 32 bytes, held in a key management service	Bank security
5	One OAuth client per calling system, mutual TLS certificates, IP allowlist	Bank security and operator
6	Canonicalisation passes all 36 shared vectors in the bank's language	Bank engineering
7	Registration connector live for the first message type	Notification team
8	Call announcement in the dialler and code panel for agents	Contact centre
9	Customer token signing and JWKS publication	Mobile backend team
10	Fraud desk trained on the console; test alert email received	Fraud team

9.5 Coverage, the key metric

A genuine message that was never registered shows as "not confirmed", which damages trust in both the bank and the tool. A pilot should enrol one message type at a time and expand only when nearly every sent message of that type is registered. The bank measures coverage by comparing its own sent counts per category with the registration counts that `GET /v1/metrics` returns. The app should state which message types are covered.




Figure 8. The integration workflow from agreement to production.




Figure 9. Three ways to register messages. Choose by what the bank can change most easily.

10 Deployment and operations

Gaskiyya can run inside one bank or as a shared service (Figure 10).

Bank-hosted

Gaskiyya runs in the bank's own cloud or data centre, with the bank's database, key management service and gateway. This is the simpler route through security review and data residency, and the likelier pilot.

Shared service

One deployment serves several banks, each a separate tenant with its own key, records and clients. Customers can verify messages from any enrolled bank in one place.

Operations

- **Start-up checks.** All configuration is validated before the service starts and every problem is reported at once. The store is pinged before the service accepts traffic.
- **Health.** `GET /health` answers when the process is up.
- **Metrics.** `GET /v1/metrics` returns registrations by category, verifications by verdict and channel, link and call checks, open calls and report counts.
- **Fraud desk email.** New and growing campaigns, approved advisories, an on-demand activity summary and a welcome message go to the bank's alert addresses through Resend.
- **Live checks.** A server check command tests the store, token keys, AI provider, push and email with the live credentials.
- **Expiry.** Firestore time-to-live policies delete expired records; reads also enforce expiry, so an expired record never matches even before deletion.




Figure 10. Deployment options. Both keep a separate key and separate data for every bank.

11 Limitations, risks and trade-offs

Risk or trade-off	Consequence	Position taken
Incomplete registration coverage	Genuine messages show as not confirmed	Enrol one message type at a time, measure coverage, state covered types in the app
Exact matching only	Partial copies, edited text and misread screenshots do not match	Accepted. A looser match would create false confirmations, which are worse. The activity summary softens the miss
Customers learn to submit bank messages for checking	Fraudsters may set up fake verification channels	In-app route primary, WhatsApp number published in the app, secrets never requested
Integration effort	Changes to notification and contact centre systems may be slow	Three registration patterns; start with one message type
Bank app release cycle	The verify screen arrives only when the bank ships it	WhatsApp, and later USSD, need no app release
Explanation quality in local languages	Wrong or awkward advice	Enable a language only after native-speaker review; fixed fallback text
Hosted AI model	Customer-submitted text leaves the bank's environment	Digits masked, one provider interface, a self-hosted option, data protection review
SIM swap	An attacker holding the number could see activity summaries on WhatsApp, never text	Accepted in the first release
Calls from personal phones	No session exists	Out of scope; needs a staff tool that opens a session

12 Implementation status and roadmap

The current release is a complete working system with an automated acceptance suite in which every test is named after the requirement it proves. It has not yet been piloted with a bank.

Capability	Status	Notes
Registry: registration, batch, idempotency, expiry	**Built**	Firestore in production, memory for tests
Message, link and screenshot verification	**Built**	Screenshots need an AI provider key
Call sessions with push and live notices	**Built**	Firebase Cloud Messaging HTTP v1
Customer app (Android, iOS)	**Built**	Flutter, on-device digest; share target on Android
iOS share extension	**Planned**	iOS customers paste text or pick a screenshot today
WhatsApp bot	**Built**	Webhook with signature checks
Explanations and campaign agent	**Built**	Gemini default, OpenAI option
Fraud desk console and email alerts	**Built**	Email through Resend
Canonicalisation libraries	**Built**	TypeScript and Dart, 36 shared vectors
Bank simulator	**Built**	Reference for every bank touchpoint
Key service backed by a KMS	**Planned**	Keys are supplied by environment variable in this release, behind the key service interface
Connectors in Java, Kotlin and C#	**Planned**	Must pass the shared vectors
Native Android and iOS libraries	**Planned**	For banks that prefer them to API only
USSD menu	**Planned**	Calls and today's activity
Self-service bank onboarding	**Planned**	Tenants are configured by the operator today
Email and push message registration in production	**After pilot**	The API already accepts these channels

Phases

Pilot with one bank: one message type and outbound calls, a limited customer group, bank-hosted, API-only embedding. It is done when nearly every sent message of the enrolled type is registered and the bank's security review is passed. **Production:** all message types, email, USSD, native libraries and the shared service for further banks, on terms agreed with the bank after the pilot.

A Appendix A: API reference

Bodies are JSON. Times are ISO 8601. Phone numbers are E.164. Every body is validated against a strict schema before any logic runs; unknown fields are rejected. Errors share one shape: `{ "code": "...", "message": "..." }`.

Bank-facing (bank access token)

Method and path	Purpose	Success
`POST /v1/oauth/token`	Exchange client credentials for a 10-minute access token	200
`POST /v1/messages`	Register one outbound message	202 new, 200 repeat
`POST /v1/messages/batch`	Register up to 500 messages	202
`POST /v1/calls`	Open a call session; returns id and code	201
`PATCH /v1/calls/{id}`	Mark a session answered or ended	200
`GET /v1/campaigns`	List campaigns with indicators and advisories	200
`POST /v1/campaigns/{id}/approve`	Approve a campaign's advisory	200
`POST /v1/campaigns/{id}/dismiss`	Dismiss a campaign	200
`POST /v1/agent/run`	Run the campaign agent now for this bank	200
`GET /v1/metrics`	Registration and verification counts	200
`POST /v1/notifications/test`	Send a test push, a test email, or both	200
`POST /v1/notifications/welcome`	Send the welcome email to the fraud desk	200
`POST /v1/notifications/summary`	Email the activity summary now	200

Customer-facing (bank-signed customer token)

Method and path	Purpose	Success
`GET /v1/me`	The bank, its domains and the last four digits of the number	200
`POST /v1/verify/message`	Check a digest; returns the verdict	200
`POST /v1/verify/link`	Check a URL against the bank's domains	200

`POST /v1/verify/screenshot`	Read a screenshot, then check its text	200, or 422 unreadable
`GET /v1/calls/open`	The customer's open call session, if any	200
`GET /v1/activity`	What the bank sent in the last 24 hours	200
`POST /v1/explain`	Explain a not-confirmed message from masked text	200
`POST /v1/reports`	Report a fake, with consent	201
`POST /v1/devices`	Register a push token	204
`GET /v1/events`	Live call notices (server-sent events)	200 stream

Webhooks

Method and path	Purpose
`GET /webhooks/whatsapp`	WhatsApp subscription handshake
`POST /webhooks/whatsapp`	Inbound WhatsApp messages; the `X-Hub-Signature-256` header must be valid

Error codes

Status	Code	Meaning
400	`invalid_request`	The body failed schema validation; the message names the fields, never their values
400	`invalid_json`	The body is not valid JSON
401	`unauthorized`	Missing or invalid bank or customer token
401	`invalid_client`	Unknown client or wrong secret at the token endpoint
401	`invalid_signature`	WhatsApp webhook signature check failed
404	`not_found`	No such call session, campaign or route
413	`too_large`	The body exceeds 12 MB
422	`unreadable`	No message text could be read from the screenshot
429	`rate_limited`	Too many checks for this customer in the last minute

B Appendix B: Configuration reference

All configuration comes from environment variables. Nothing secret is stored in the code repository.

Variable	Meaning	Default
`GASKIYA_TENANTS`	JSON list of banks: id, name, domains, senderIds, tokenKeysUrl, optional recordTtlDays and alertEmails	Required
`GASKIYA_TENANT_KEYS`	JSON map of tenant id to a base64 hashing key of at least 32 bytes	Required
`GASKIYA_BANK_CLIENTS`	JSON list of OAuth clients: clientId, clientSecret (24+ characters), tenantId	Required
`GASKIYA_TOKEN_SECRET`	Secret of at least 32 characters for signing bank access tokens	Required
`STORE`, `FIRESTORE_PROJECT_ID`	Storage backend and Firestore project	Firestore when a project is set
`RECORD_TTL_DAYS`	Message record lifetime	30
`CALL_RING_SECONDS`	How long an unanswered call session stays open	180
`VERIFY_RATE_LIMIT_PER_MINUTE`	Checks allowed per customer per minute	30
`AI_PROVIDER`	`gemini`, `openai` or `none`	gemini
`AI_TIMEOUT_MS`	Time allowed for an explanation	4000
`AGENT_INTERVAL_SECONDS`	How often the campaign agent runs	60
`FCM_SERVICE_ACCOUNT_JSON`	Firebase service account for push notices	Push off
`RESEND_API_KEY`, `EMAIL_FROM`	Email for fraud desk alerts	Email off
`WHATSAPP_*`	Verify token, app secret, access token and phone number id	WhatsApp off

C Appendix C: Glossary

Term	Meaning
Canonical text	Message text after the four canonicalisation steps, so harmless differences disappear
contentDigest	SHA-256 of the canonical text as 64 lowercase hex characters, computed by the bank and by the phone
contentKey, recipientKey	HMAC-SHA-256 of the digest or the number under the bank's key; the only forms the registry stores
Tenant	One enrolled bank, with its own key, domains, clients and data
JWKS	JSON Web Key Set: the public keys a bank publishes so its customer tokens can be checked
Call session	The record of an announced call, holding the four-digit code and its expiry
Coverage	The share of a bank's sent messages of a type that were registered
Campaign	A group of reported fakes that share a link domain, a callback number or similar wording
Advisory	A drafted customer warning for a campaign; it needs analyst approval and Gaskiyya never sends it
NDPA	Nigeria Data Protection Act 2023