


TOP (along -Z)



ISO (iso, not to scale)






ENG-FS-09   MV cam (r 6.0 -> 8.8 over 45 deg, 15 deg dwell, width 5; closed 25 deg before the rise) + shaft 5 in 2x MR85-2
Material: 17-4PH (1.4542) condition H900: pintle crankshaft, crank/link pins, MV-P poppet   Process: wire EDM + lathe + broach
Mass: 8.1 g (CAD volume x density)   Units: mm   Frame: modelling frame (+Z forward)   Bounding box: 21.80 x 14.77 x 12.00
Datum: seat plane A, module axis B   Finish: clear anodise (6061) / passivate (316L, 17-4PH); oxygen-clean wetted parts   Heat treatment: n/a
Fits / features: piston bore 11.9 H8 Ra 0.4; rod bore 4.05 +0.02/0; seat counterbore 16 H7; 1/4-18 NPT, 1/8-27 NPT
Notes: module frame: axis r 10 / az 219.5, seat plane z 279.5 (lead Option A, zone top); dry side
ARGOS engine CAD v3.5 - DESIGN-MODEL DRAWING generated from the solid; dimensions from the model; general tolerances ISO 2768-m unless a fit is listed; NOT released for fabrication (Mechanical, 2026-10-13)