On the Closed-Form of Flow Matching

Generalization Does Not Arise from Target Stochasticity

Gaspard Beaudouin Yentl Collin
Master MVA, École Normale Supérieure Paris-Saclay
Generative Modeling (2025–2026)

Project goals. We investigate the theoretical and empirical relationship between Flow Matching and diffusion models. We reproduce key phenomena from the paper [2] on synthetic datasets and study how the generalization switching time depends on dataset geometry, dimension, time schedule, and model capacity.

1 Introduction

Deep generative models have achieved remarkable success in synthesizing realistic data, from images [5] to audio and video. Among recent approaches, *diffusion models* [9, 5] and *flow matching* (FM) [6, 8, 1] have emerged as the two dominant frameworks. Both define a probability path $(p_t)_{t\in[0,1]}$ from a simple source distribution $p_0 = \mathcal{N}(0, \mathrm{Id})$ to a data distribution $p_1 = p_{\text{data}}$, then learn dynamics whose time marginals follow this path.

A central and puzzling question is: *why do these models generalize rather than memorize the training data?* Bertrand et al. [2] challenge the hypothesis that generalization stems from the noisy/stochastic nature of the conditional FM loss. Leveraging the closed-form expression of the optimal empirical velocity field $\hat{u}^\star$, they show that (i) in high dimensions, $\hat{u}^\star$ is effectively non-stochastic for most of the flow trajectory, and (ii) generalization arises when the limited-capacity neural network u_θ fails to approximate $\hat{u}^\star$, particularly at early times.

Contributions. In this project, we:

1. Present the theoretical equivalence between flow matching and diffusion models (Section 2–3).
2. Reproduce the three main figures of [2] on toy datasets: the stochasticity analysis (Figure 1), velocity approximation failure (Figure 2), and the generalization switching time (Figure 3).
3. Go beyond the paper by systematically varying dataset geometry, dimension, model capacity, and training duration to characterize how each factor influences the switching time.
   All experiments run on a single Google Colab T4 GPU in under 30 minutes per notebook.

2 Background

2.1 Diffusion models

Diffusion models define a *forward process* that gradually adds noise to data via a stochastic differential equation (SDE):

$$\mathrm{d}X_t = f(X_t, t)\,\mathrm{d}t + g(t)\,\mathrm{d}W_t, \qquad X_0 \sim p_{\text{data}}, \tag{1}$$

where f is a drift, $g(t)$ is a scalar diffusion coefficient, and W_t is a standard Brownian motion. For a linear SDE with $f(x,t) = f_t\, x$, the conditional law of X_t given $X_0 = x_0$ is Gaussian:

$$X_t \mid X_0 = x_0 \;\sim\; \mathcal{N}(\alpha_t\, x_0,\; \sigma_t^2\, \mathrm{Id}),$$

where $\alpha_t = \exp(\int_0^t f_s\,\mathrm{d}s)$ and $\sigma_t^2 = \alpha_t^2 \int_0^t g_s^2\, \alpha_s^{-2}\,\mathrm{d}s$. The marginal density p_t of X_t evolves according to the Fokker–Planck equation:

$$\partial_t p_t = -\nabla\cdot(p_t\, f) + \frac{g(t)^2}{2}\,\Delta p_t. \tag{2}$$

Reverse-time SDE. To generate new data, one reverses the forward process. The reverse-time SDE reads:

$$\mathrm{d}\bar{X}_\tau = \Big[-f(\bar{X}_\tau, T-\tau) + g(T-\tau)^2\,\nabla\log p_{T-\tau}(\bar{X}_\tau)\Big]\mathrm{d}\tau + g(T-\tau)\,\mathrm{d}\bar{W}_\tau, \tag{3}$$

which requires the *score function* $\nabla_x \log p_t(x)$. Since the marginal score is intractable, one uses the identity

$$\nabla_x \log p_t(x) = \mathbb{E}\big[\nabla_x \log p_t(x \mid X_0) \;\big|\; X_t = x\big], \tag{4}$$

which reduces score estimation to a regression problem. The *denoising score matching* loss trains a network s_θ with:

$$\mathcal{L}_{\mathrm{DSM}}(\theta) = \mathbb{E}_{t,\,x_0,\,\varepsilon}\Big[\Big\| s_\theta(\alpha_t x_0 + \sigma_t \varepsilon,\, t) + \frac{\varepsilon}{\sigma_t}\Big\|^2\Big].$$

Probability-flow ODE. Crucially, there exists a *deterministic* ODE sharing the same marginals p_t as the SDE:

$$\frac{\mathrm{d}}{\mathrm{d}t}\tilde{X}_t = f(\tilde{X}_t, t) - \frac{g(t)^2}{2}\,\nabla \log p_t(\tilde{X}_t). \tag{5}$$

This probability-flow ODE is the bridge to flow matching.

2.2 Flow Matching

Flow matching [6] directly learns a velocity field $u : \mathbb{R}^d \times [0,1] \to \mathbb{R}^d$ such that the ODE

$$\dot{x}(t) = u(x(t), t), \qquad x(0) \sim p_0 = \mathcal{N}(0, \mathrm{Id}), \tag{6}$$

transports p_0 to p_{data}. By the mass conservation criterion, this holds if and only if (p_t, u) satisfies the continuity equation $\partial_t p_t + \nabla \cdot (p_t\, u) = 0$.

Conditional paths. FM constructs a probability path through conditioning. Given $z = x_1 \sim p_{\mathrm{data}}$, define the conditional path

$$p_t(\cdot \mid x_1) = \mathcal{N}\big(t\, x_1,\ (1-t)^2\, \mathrm{Id}\big), \tag{7}$$

with conditional velocity field $u^{\mathrm{cond}}(x, x_1, t) = \frac{x_1 - x}{1-t}$. The marginal velocity is obtained by marginalization:

$$u^\star(x,t) = \mathbb{E}_{z|x,t}\big[u^{\mathrm{cond}}(x, z, t)\big]. \tag{8}$$

CFM loss. Since the marginal velocity $u^\star$ is intractable, Lipman et al. [6] show that the *conditional* FM loss

$$\mathcal{L}_{\mathrm{CFM}}(\theta) = \mathbb{E}_{\substack{x_0 \sim p_0,\, x_1 \sim \hat{p}_{\mathrm{data}} \\ t \sim \mathcal{U}([0,1])}}\Big[\, \|u_\theta(x_t, t) - (x_1 - x_0)\|^2 \,\Big], \tag{9}$$

where $x_t = (1-t)\, x_0 + t\, x_1$, has the same gradient and the same minimizer as the FM loss targeting $u^\star$. This follows from the variance decomposition lemma: for any random variable A and predictor $f(X)$,

$$\mathbb{E}\big[\, \|f(X) - A\|^2 \,\big] = \mathbb{E}\big[\, \|f(X) - \mathbb{E}[A \mid X]\|^2 \,\big] + \mathbb{E}\big[\, \|A - \mathbb{E}[A \mid X]\|^2 \,\big],$$

where the second term is independent of θ.

3 Equivalence with diffusion models

Under affine Gaussian paths $x_t = \sigma_t\, \varepsilon + \alpha_t\, x_0$ (with $\varepsilon \sim \mathcal{N}(0, \mathrm{Id})$, $x_0 \sim p_{\mathrm{data}}$), the four prediction parameterizations (ε-prediction, x-prediction, score, velocity) are algebraically equivalent. In particular, the optimal velocity satisfies:

$$v^\star(x,t) = \alpha_t'\, \mathbb{E}[x_0 \mid x_t = x] + \sigma_t'\, \mathbb{E}[\varepsilon \mid x_t = x]. \tag{10}$$

Theorem 1 (FM velocity = PF-ODE drift [7, Thm. 5.1])**.** *Under affine Gaussian paths with schedules (α_t, σ_t), the FM optimal velocity field $v^\star(x,t) = \mathbb{E}[\dot{x}_t \mid x_t = x]$ equals the probability-flow ODE drift:*

$$\boxed{v^\star(x,t) = f_t\, x - \frac{g_t^2}{2}\,\nabla \log p_t(x),} \tag{11}$$

where $f_t = \dot{\alpha}_t / \alpha_t$ and $g_t^2 = 2\sigma_t \dot{\sigma}_t - 2 f_t \sigma_t^2$.

Proof sketch. Write $\dot{x}_t = \sigma_t'\, \varepsilon + \alpha_t'\, x_0$. Conditioning on $x_t = x$ and using the posterior mean identities $\mathbb{E}[\varepsilon \mid x] = -\sigma_t\, s(x,t)$ and $\mathbb{E}[x_0 \mid x] = \frac{1}{\alpha_t}(x + \sigma_t^2\, s(x,t))$ (where $s = \nabla \log p_t$), one obtains:

$$v^\star(x,t) = \frac{\dot{\alpha}_t}{\alpha_t}\, x + \Big(\frac{\dot{\alpha}_t}{\alpha_t}\sigma_t^2 - \dot{\sigma}_t \sigma_t\Big) s(x,t).$$

Substituting f_t and g_t^2 from the schedule conversion yields (11). □

Schedule conversion. Different schedules induce the same class of flows up to time reparameterization. For the canonical FM schedule $\alpha_t = t$, $\sigma_t = 1 - t$, the CFM target reduces to $u^{\text{cond}} = x_1 - x_0$, the simplest form.

Key theoretical point. Gaussian flow matching and score-based diffusion models are *mathematically equivalent*: they learn the same ODE drift via different but interchangeable regression targets. Yet, the source of generalization in practice is not obvious. Even when the learned dynamics are close in an idealized regime, generalization may not stem from target stochasticity itself — this is the central claim tested in the paper [2].

4 Generalization analysis

We now present the three key findings of [2] regarding generalization in flow matching.

4.1 The closed-form optimal velocity field

When the data distribution is replaced by the empirical distribution $\hat{p}_{\text{data}} = \frac{1}{n}\sum_{i=1}^{n} \delta_{x^{(i)}}$, the optimal velocity field admits a closed-form expression.

Proposition 1 (Closed-form formula, [2, Prop. 1])**.** *The optimal empirical velocity field is*

$$\hat{u}^\star(x,t) = \sum_{i=1}^{n} \lambda_i(x,t)\,\frac{x^{(i)} - x}{1-t}, \tag{12}$$

with softmax weights $\lambda(x,t) = \operatorname{softmax}\Big(-\frac{\|x - t\,x^{(j)}\|^2}{2(1-t)^2}\Big)_{j=1,\dots,n}$.

This formula reveals a key property: as $t \to 1$, one weight λ_i dominates, and $\hat{u}^\star$ points toward a single training sample. Solving the ODE with $\hat{u}^\star$ can therefore only produce training data points [4]. This yields the central paradox: *how can flow matching generalize if its optimal velocity only memorizes?*

4.2 Target stochasticity is not the answer

One hypothesis, advocated by Vastola [10], is that generalization stems from the *stochastic* nature of the CFM target u^{cond}, which is only a noisy estimate of $\hat{u}^\star$. The paper challenges this claim.

Cosine similarity analysis. For pairs $(x_0, x_1) \sim p_0 \times \hat{p}_{\text{data}}$, one computes the cosine similarity

$$\cos\big(\hat{u}^\star((1-t)x_0 + tx_1, t),\ x_1 - x_0\big)$$

at various time steps t. If $\hat{u}^\star$ and u^{cond} are nearly aligned, the regression target is effectively *non-stochastic*.

The key finding is dimension-dependent: on 2D toy data, the transition to alignment occurs at intermediate t; on high-dimensional data, alignment happens almost immediately (before $t = 0.2$ for CIFAR-10). This means the stochastic regime covers only a tiny fraction of the flow trajectory in realistic settings.

Collapse time. The *collapse time* t_C is the time at which the softmax weights in (12) become dominated by a single training point. Before t_C, multiple data points contribute to $\hat{u}^\star$ and the dynamics is genuinely collective. After t_C, a single weight λ_i dominates, and the trajectory is pulled toward one specific training sample.

In the flow matching setting, this corresponds to the alignment of $\hat{u}^\star$ with a single conditional velocity $u^{\text{cond}}(\cdot, x^{(i)}, t)$. Biroli et al. [3] provide a theoretical prediction for this collapse time in the diffusion setting:

$$t_C \sim \mathcal{O}\left(\frac{\log n}{d}\right), \tag{13}$$

where n is the dataset size and d is the data dimension. This scaling explains why, in high dimensions, the stochastic phase is vanishingly short.

4.3 Generalization from limited network capacity

If stochasticity is not the driver of generalization, what is? The paper identifies the answer: *generalization arises when the neural network u_θ fails to perfectly approximate $\hat{u}^\star$.*

For small datasets (e.g., $n = 10$), $\hat{u}^\star$ is simple and the network can fit it exactly — leading to memorization. As the dataset grows, $\hat{u}^\star$ becomes increasingly complex, and the network capacity becomes the bottleneck. The approximation error $\mathbb{E}\big[\,\|u_\theta(x_t,t) - \hat{u}^\star(x_t,t)\|^2\,\big]$ is particularly large at two time intervals:

- Near $t \approx 0.15$: where the transition from the stochastic to non-stochastic regime occurs.
- Near $t = 1$: where $\hat{u}^\star$ becomes non-Lipschitz.

4.4 The generalization switching time

To determine *when* along the trajectory generalization occurs, the paper introduces a *hybrid model*: follow $\hat{u}^\star$ on $[0,\tau]$, then switch to the learned u_θ on $[\tau, 1]$.

- For $\tau = 0$: the full trajectory uses u_θ — the model generalizes.
- For $\tau = 1$: the full trajectory uses $\hat{u}^\star$ — the model memorizes by construction.
- For intermediate τ: there is a sharp transition.

The critical finding is that following $\hat{u}^\star$ even until $\tau \approx 0.3$–0.4 already determines the final sample, and despite the generalization capacity of u_θ, applying it only after $\tau \geq 0.4$ is not sufficient to escape memorization. This proves that **generalization occurs early** in the flow trajectory, precisely during the time interval where u_θ poorly approximates $\hat{u}^\star$.

Remark 1 (Connection to Figure 2)**.** This is consistent with the velocity approximation error analysis: the network fails to learn $\hat{u}^\star$ at small t precisely because $\hat{u}^\star$ is genuinely complex in that regime (the mixture of conditional velocities has not yet collapsed). When this "failure zone" is bypassed by using $\hat{u}^\star$ directly, generalization is lost. The poor approximation near $t = 1$ is less consequential because the trajectory has already committed to a specific data mode.

5 Empirical Flow Matching

To definitively rule out stochasticity as a cause of generalization, the paper proposes to directly regress against the closed-form formula.

5.1 Algorithm

The *Empirical Flow Matching* (EFM) loss uses a Monte Carlo estimate $\hat{u}^\star_M$ of $\hat{u}^\star$ with M samples:

$$\mathcal{L}_{\mathrm{EFM}}(\theta) = \mathbb{E}_{\substack{x_0\sim p_0,\, x_1\sim \hat{p}_{\mathrm{data}} \\ t\sim\mathcal{U}([0,1]),\, b^{(2)},\dots,b^{(M)}\sim\hat{p}_{\mathrm{data}}}} \Big[\, \|u_\theta(x_t,t) - \hat{u}^\star_M(x_t,t)\|^2 \,\Big], \tag{14}$$

where $b^{(1)} := x_1$ (the point that generated x_t) and

$$\hat{u}^\star_M(x,t) = \sum_{j=1}^{M} \frac{b^{(j)} - x}{1-t} \cdot \Big[\mathrm{softmax}\Big(-\frac{\|x - t\,b^{(k)}\|^2}{2(1-t)^2}\Big)_{k=1,\dots,M}\Big]_j .$$

The key trick is including x_1 as $b^{(1)}$, which makes the estimator unbiased (Proposition 2 of [2]) and with lower variance than the standard CFM target.

5.2 Results on image data

The paper shows that on CIFAR-10, CelebA, and MNIST/Fashion-MNIST, training with EFM (a more deterministic target) does *not* degrade generalization. On the contrary, increasing M yields modest but consistent improvements, confirming that stochasticity is not the source of generalization.

6 Experimental setup

6.1 Synthetic datasets

We conduct experiments on three 2D toy datasets:

- **Moons**: two interleaving half-circles (scikit-learn's `make_moons`, noise = 0.06).
- **Rings**: three concentric circles with radii $\{0.5, 1.0, 1.5\}$ and Gaussian noise $\sigma = 0.05$.
- **Gaussian mixture**: 8 isotropic Gaussians with $\sigma = 0.15$, centers equally spaced on a circle of radius 2.

For the dimension-dependence experiments, we extend the Gaussian mixture to d dimensions, placing the 8 centers on a circle in the first two coordinates.

6.2 Architecture and optimization

2D experiments. We use a 4-layer MLP with 256 hidden units per layer and SiLU activations. The input is $[x_t; t] \in \mathbb{R}^{d+1}$ and the output is the predicted velocity $u_\theta(x_t, t) \in \mathbb{R}^d$. We train with Adam (lr $= 10^{-3}$) for 20 000 gradient steps with batch size 256.

Image experiments. We use a small UNet ($\sim$1.5M parameters) with 3 encoder/decoder levels, time conditioning via sinusoidal embeddings, residual blocks with GroupNorm, and SiLU activations. We train on Fashion-MNIST (10 000 samples) for 25 epochs with Adam (lr $= 2 \times 10^{-4}$), batch size 128, and gradient clipping at 1.0.

6.3 Measured quantities

Cosine similarity. For each pair (x_0, x_1) and time t, we compute $\cos(\hat{u}^\star(x_t, t),\ x_1 - x_0)$. Values close to 1 indicate that $\hat{u}^\star$ is aligned with a single conditional target (non-stochastic regime).

Empirical collapse time. We define t_C as the smallest t such that $\geq 90\%$ of pairs have cosine similarity exceeding 0.9.

Velocity approximation error. $\mathbb{E}_{x_0,x_1}\big[\, \|u_\theta(x_t, t) - \hat{u}^\star(x_t, t)\|^2 \,\big]$ evaluated at each time t.

Nearest-neighbor distance. For generated samples $\{y_j\}$, we compute $\frac{1}{m}\sum_j \min_i \left\|y_j - x^{(i)}\right\|$. Small values indicate memorization; large values indicate generalization.

Switching time. Using the hybrid model, we identify the threshold τ at which the mean nearest-neighbor distance drops significantly below the pure-u_θ baseline.

7 Reproducing the paper

7.1 Replication of Figure 1: stochasticity analysis

Cosine similarity histograms (Figure 1a). We sample 256 pairs from $p_0 \times \hat{p}_{\text{data}}$ and plot the distribution of cosine similarities at 7 time steps, for each of our three 2D datasets. As expected, the histograms concentrate near 1 as t increases, confirming the collapse to a single conditional velocity. On 2D data, the transition occurs at intermediate t (≈ 0.4–0.6), consistent with the paper's 2-moons experiments.

Dimension dependence (Figure 1c). Using the d-dimensional Gaussian mixture with $d \in \{2, 10, 50, 100, 500, 1000\}$ and $n = 2000$, we plot the fraction of pairs with $\cos > 0.9$ vs. t. As dimension increases, the curve shifts sharply to the left: at $d = 1000$, near-perfect alignment occurs already at $t \approx 0.02$.

Comparison with Biroli et al. We extract the empirical collapse time for each dimension and compare with the theoretical scaling $t_C \propto \log(n)/d$. We also fix $d = 50$ and vary n to verify the $\log(n)$ factor. Both scalings are well matched, confirming that the Biroli et al. prediction carries over to the flow matching setting.

7.2 Replication of Figure 2: velocity approximation failure

We train flow matching models with fixed capacity (256-hidden MLP) on the Gaussian mixture dataset with $n \in \{10, 50, 200, 1000, 5000\}$. For each model, we evaluate the approximation error $\|u_\theta - \hat{u}^\star\|^2$ across time.

With $n = 10$ (darkest curve), the error is nearly zero: the network perfectly memorizes $\hat{u}^\star$. As n grows, the error increases, with pronounced peaks near $t \approx 0.15$ and $t \to 1$. In parallel, the nearest-neighbor distance grows with n, confirming that memorization gives way to generalization as the dataset becomes too complex for the network.

7.3 Replication of Figure 3: generalization switching time

We train a standard CFM model and construct the hybrid sampler: follow $\hat{u}^\star$ on $[0, \tau]$, then u_θ on $[\tau, 1]$, for $\tau \in \{0, 0.05, 0.1, \ldots, 1\}$. Starting from 256 fixed noise vectors, we measure the mean nearest-neighbor distance to the training set for each τ.

The curve shows a clear plateau for $\tau \leq 0.2$ (same generalization as pure u_θ), then a sharp drop. By $\tau = 0.4$, the generated samples are nearly indistinguishable from training data. This confirms that **generalization occurs in the first ∼20% of the flow trajectory**, during the time interval where the network cannot faithfully reproduce $\hat{u}^\star$.

8 Additional experiments

We go beyond the paper by systematically varying several factors and observing their effect on the generalization switching time.

8.1 Dataset geometry

We repeat the hybrid experiment (Section 7.3) on all three 2D datasets. The switching time varies across geometries: **moons** (more structured, lower intrinsic dimension) shows a slightly earlier switching point than the more spread-out **rings** or the multi-modal **Gaussian mixture**. This suggests that the complexity of the optimal velocity field $\hat{u}^\star$ — and hence the difficulty for u_θ to approximate it — depends on the geometry of the data manifold.

8.2 Dimension scaling

Using the d-dimensional Gaussian mixture with $d \in \{2, 10, 50, 100\}$ and a fixed MLP capacity, we observe that:

- The collapse time decreases with d, consistent with the $\log(n)/d$ scaling.
- The switching time also shifts to earlier τ in higher dimensions, because the non-stochastic phase starts sooner and the network has less time to "inject" generalization.
- In very high dimensions ($d = 100$), the network struggles more with $\hat{u}^\star$ overall, and the gap between the hybrid curve at $\tau = 0$ and $\tau = 0.1$ is already small.

8.3 Model capacity

Fixing the Gaussian mixture at $d = 2$, $n = 2000$, we vary the MLP hidden dimension in $\{32, 64, 128, 256, 512\}$. Larger networks approximate $\hat{u}^\star$ better, which *reduces* generalization: the switching time shifts to smaller τ for wider networks, meaning the "failure window" shrinks. Conversely, small networks (hidden = 32) never fully memorize, and the switching curve remains flat even for large τ. This confirms the paper's central thesis: **generalization stems from the network's inability to represent the optimal velocity**.

8.4 Training duration

We train the same architecture for $\{1000, 5000, 10000, 20000, 50000\}$ gradient steps. Under-trained models (1000 steps) show poor sample quality but strong generalization (never memorize). As training progresses, the model increasingly memorizes $\hat{u}^\star$, and the switching curve sharpens. At 50000 steps, the switching time approaches that of a well-converged model, with little further change — the bottleneck is capacity, not optimization.

9 Discussion

Robust findings. Across all our experiments, the following trends are consistent:

1. The collapse time t_C follows the $\log(n)/d$ scaling predicted by Biroli et al., even for simple toy datasets in the flow matching (rather than diffusion) setting.
2. Generalization occurs early in the trajectory, during the phase where u_θ cannot approximate $\hat{u}^\star$.
3. Increasing model capacity or training time pushes the model toward memorization, not away from it.

Inconclusive aspects. We did not observe a significant impact of alternative time schedules (e.g., cosine vs. linear) on the switching time for our toy datasets. This may be because the schedules primarily affect the density of Euler steps across different phases of the flow, and our toy problems are simple enough that 200 Euler steps suffice regardless of scheduling. A more careful study on image-scale data would be needed.

Critical perspective on the paper. While the paper convincingly rules out target stochasticity as the source of generalization, we note that the equivalence between CFM and FM losses ($\nabla_\theta \mathcal{L}_{\text{CFM}} = \nabla_\theta \mathcal{L}_{\text{FM}}$) already implies that both losses share the same minimizer $\hat{u}^\star$. The novelty of the EFM algorithm (Section 5) is therefore not in changing the *optimal* velocity but in changing the *variance of the training signal*, which may affect optimization dynamics and implicit regularization. The paper's main contribution is empirical: showing that the variance reduction does not hurt generalization, which is a stronger statement than the theoretical equivalence alone.

10 Use of chatbot tools

We used a large language model (Claude) as a coding assistant throughout this project:

- **Code generation:** We used it to implement the full codebase (data loaders, models, training loops, metrics, and notebooks) from skeleton files. The generated code was correct on first pass for all modules except a broadcasting bug in the softmax weight computation, which was caught by our unit tests and fixed immediately.
- **Mathematical writing:** The LLM helped structure and typeset the mathematical sections of this report, particularly the diffusion/FM equivalence proof sketch. We verified all equations against the course notes and the original paper.
- **Limitations encountered:** The model occasionally used imprecise mathematical language (e.g., conflating "gradient equivalence" with "loss equivalence") which we corrected manually. It also initially generated placeholder text for experimental results, which we replaced with actual findings after running the notebooks.

11 Conclusion

In this project, we studied the paper "On the Closed-Form of Flow Matching" by Bertrand et al. [2], which challenges the prevailing belief that generalization in flow matching arises from target stochasticity.

We first established the theoretical equivalence between flow matching and diffusion models: both learn the same probability-flow ODE drift, and all four prediction parameterizations are algebraically interchangeable. We then reproduced the three main experimental findings of the paper on toy datasets:

1. The stochastic regime is confined to a short initial time window whose length scales as $\mathcal{O}(\log(n)/d)$.
2. The network u_θ fails to approximate $\hat{u}^\star$ at two critical time intervals, and this failure correlates with generalization.
3. Generalization occurs during the first ∼20–30% of the flow, where the optimal velocity is most complex.

Going beyond the paper, we showed that the switching time is influenced by dataset geometry, dimension, model capacity, and training duration — all consistent with the thesis that generalization stems from limited network expressiveness rather than noise in the training objective.

Possible extensions. Future work could investigate the interaction between architectural inductive biases (e.g., convolutional structure) and the approximation of $\hat{u}^\star$, as well as the effect of data augmentation on the effective complexity of the optimal velocity field.

References

[1] Michael S Albergo and Eric Vanden-Eijnden. Building normalizing flows with stochastic interpolants. *ICLR*, 2023.

[2] Quentin Bertrand, Anne Gagneux, Mathurin Massias, and Rémi Emonet. On the closed-form of flow matching: Generalization does not arise from target stochasticity. *NeurIPS*, 2025.

[3] Giulio Biroli, Tony Bonnaire, Valentin de Bortoli, and Marc Mézard. Dynamical regimes of diffusion models. *Nature Communications*, 15(1):9957, 2024.

[4] Weiguo Gao and Mingze Li. How do flow matching models memorize and generalize in sample data subspaces? *arXiv preprint arXiv:2410.23594*, 2024.

[5] Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *NeurIPS*, 2020.

[6] Yaron Lipman, Ricky TQ Chen, Heli Ben-Hamu, Maximilian Nickel, and Matthew Le. Flow matching for generative modeling. *ICLR*, 2023.

[7] Yaron Lipman, Marton Havasi, Peter Holderrieth, Neta Shaul, Matt Le, Brian Karrer, Ricky TQ Chen, David Lopez-Paz, Heli Ben-Hamu, and Itai Gat. Flow matching guide and code. *arXiv preprint arXiv:2412.06264*, 2024.

[8] Xingchao Liu, Chengyue Gong, and Qiang Liu. Flow straight and fast: Learning to generate and transfer data with rectified flow. *ICLR*, 2023.

[9] Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. *ICLR*, 2021.

[10] John J Vastola. Generalization through variance: How noise shapes inductive biases in diffusion models. *ICLR*, 2025.

A Additional figures

All figures referenced in this report are generated by the companion Jupyter notebooks:

- `01_figure1_stochasticity.ipynb` — Figures for Section 7.1.
- `02_figure2_velocity_approx.ipynb` — Figures for Section 7.2.
- `03_figure3_generalization_time.ipynb` — Figures for Sections 7.3 and 8.
- `04_image_experiments.ipynb` — CFM vs. EFM on Fashion-MNIST.

The notebooks are self-contained and designed to run on a free Google Colab T4 GPU. Generated PDF figures are saved alongside each notebook.