

Midterm Module B

Due Oct 20 at 11:59pm

Points 20

Questions 20

Time Limit 30 Minutes

Instructions

There are 20 questions in this module and you have 30 minutes to complete the quiz.

In all 3 module put together (A, B, and C), the question distribution is **roughly** as follows

- HTML/CSS/Flex (~15%)
- Networking/HTTP (~10%)
- Project structure (Client/Server/Setup/etc) (~10%)
- Database/DAO (~15%)
- Vue-related (~35%)
- REST/fetch/router/terms (~15%)

Attempt History

	Attempt	Time	Score
LATEST	<u>Attempt 1</u>	30 minutes	19 out of 20

Score for this quiz: **19** out of 20

Submitted Oct 16 at 5:50pm

This attempt took 30 minutes.

Correct!

Question 1

1 / 1 pts

Which of the following is **false** about the UDP protocol?

☐ UDP is faster than TCP

☒ UDP is useful for documents

☐ UDP is a connectionless protocol

- ☐ UDP is useful for live media

Question 2**1 / 1 pts**

In an HTML <form> element, which of the following is NOT a good reason to use method="post"?

Correct!

- ☐ you have an input type "password" in your form
- ☒ you want your data to be visible in the page address field
- ☐ you are sending large amounts of data
- ☐ you are sending sensitive information

Question 3**1 / 1 pts**

A foreign key in a table does NOT have to be unique.

Correct!

- ☒ True
- ☐ False

Question 4**1 / 1 pts**

What is the default port for internet web server software?

Correct!

- ☒ 80

☐ 8080☐ 127.0.0.1☐ 3306**Question 5****1 / 1 pts**

Suppose I have three flexbox items: A, B, and C arranged in a row. I want A to be all the way on the left edge of the container, C to be all the way on the right edge of the container, and the three items to be evenly spaced. What CSS command will do this?

Correct!☒ justify-content: space-between☐ align-items: center☐ align-items: distribute-horizontally☐ justify-content: space-around**Question 6****1 / 1 pts**

When is the following CSS rule applied?

```
ul.buttons a:hover{  
  color: #ff00ff;  
}
```

☐ When you are hovering over any link inside an unordered list with class *or* id buttons

Correct!

When you are hovering over a link in an unordered list with class buttons that is directly under the tag (*not* inside an element)



When you are hovering over any link inside an unordered list with class buttons



When you are hovering over a link in an unordered list with class buttons that is also inside an element

Question 7**1 / 1 pts**

What is the difference between the data property in a Vue instance and the data property in a Vue component?



no difference - they are both objects



data in a Vue instance is a function; data in a Vue component is an object



no difference - they are both functions

Correct!

data in a Vue instance is an object; data in a Vue component is a function

Question 8**1 / 1 pts**

Vue is reactive. What is an example of this?



Vue applications can be created using a single HTML page and multiple components



Data in Vue components can be passed to a child component using props



The same Vue application can be viewed on different devices (browsers, phones, etc.)

Correct!



When data in a Vue instance changes, the HTML content linked to that data is updated

Question 9

1 / 1 pts

Suppose you want an image to update whenever the image data in a Vue instance changes. What would your HTML img tag look like?

☐

☒

☐

☐

Correct!

Question 10

1 / 1 pts

Assuming our Vue data contains a "messages" array of strings, how would we print out the list of messages in HTML?

- ☐ `<ul v-for="message in messages">
 {{ message }}
`
- ☐ `<ul v-for="message" v-in="messages">
 {{ message }}
`
- ☐ `<ul v-for="messages">
 <li v-item="message">{{ message }}
`
- ☒ `
 <li v-for="message in messages">{{ message }}
`

Correct!

Question 11

1 / 1 pts

In general, when using the v-for attribute, you should also use the :key attribute

Correct!

- ☒ True
- ☐ False

Question 12

1 / 1 pts

What is another way of writing `<button v-on:click="cart += 1"/>`?

Correct!

- ☐ <button :click="cart += 1"/>
- ☐ <button click={{cart += 1}}/>
- ☒ <button @click="cart += 1"/>
- ☐ <button \$click="cart += 1"/>

Question 13**1 / 1 pts**

In Vue, a child component automatically has access to the data from its parent component

Correct!

- ☐ True
- ☒ False

Question 14**1 / 1 pts**

Consider the following template code in a Vue single-file component. Suppose that product-list-item is the child component of the component with this element.

```
<product-list-item :product="product" @add-to-cart="addToCart"></product-list-item>
```

What can we say about :product="product"?

- ☐ the child component has an emit event named product, and an object named product is being passed to the event

Correct!

the child component has a prop named product, and an object named product is being passed to it



the child component has a prop named product, and the result of a method named product is being passed to it



the child component has an emit event named product, and a method named product is being executed when the event is received

Question 15**1 / 1 pts**

JSON stands for "Java Standard Object Notation"

☐ True☒ False**Correct!****Question 16****1 / 1 pts**

If we have a Vue router path of "/user/:id" and /user/bob is entered into the address bar, how can we access the value "bob" in HTML?

☒ {{ \$route.params.id }}☐ {{ /user/id }}☐ {{ \$route/user/id }}**Correct!**

☐ {{ \$route.user.id }}

Question 17

0 / 1 pts

Suppose we have a Vue router path of `"/category/:name"` with a name of `"category"`. One way of creating a router link is through the path, as in:

```
<router-link to="category/Mystery"></router-link>
```

Which of the following is another way of achieving the same thing?

You Answered



```
<router-link :to="{path: 'category', params: {category: 'Mystery'}}"></router-link>
```



```
<router-link to="{path: 'category', params: {name: 'Mystery'}}"></router-link>
```



```
<router-link to="{name: 'category', params.name: 'Mystery'}"></router-link>
```

Correct Answer



```
<router-link :to="{name: 'category', params: {name: 'Mystery'}}"></router-link>
```

Question 18

1 / 1 pts

In our project, suppose we wanted to be able to access all the orders associated with a customer's name through a REST API. Given our naming conventions, which of the following path's should we use?

Correct!

- ☒ `api/customers/name/{customer-name}/orders`
- ☐ `api/customers/{customer-name}/orders`
- ☐ `api/customer/{customer-name}/orders`
- ☐ `api/customer/name/{customer-name}/all-orders`

Question 19**1 / 1 pts**

The fetch method is specific to Vue. Other frameworks such as Angular and React have their own methods for fetching server resources

☐ True

Correct!

☒ False

Question 20**1 / 1 pts**

A RESTful API is a service that runs on the web over HTTP to facilitate access to web resources

☒ True

Correct!

☐ False

Quiz Score: 19 out of 20