Permisos en la Base de Datos

#PERMISOS_ROOT

GRANT ALL PRIVILEGES ON quickcarryDB.all TO 'root'@'localhost';

#PERMISOS_ADMIN_BD

GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.trabajador TO 'admin_bd'@'localhost';

GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.almacen TO 'admin_bd'@'localhost';

GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.camion TO 'admin_bd'@'localhost';

GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.producto TO 'admin_bd'@'localhost';

GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.destino TO 'admin_bd'@'localhost';

GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.lote TO 'admin_bd'@'localhost';

GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.camionero TO 'admin_bd'@'localhost';

GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.operario TO 'admin_bd'@'localhost';

GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.conduce TO 'admin_bd'@'localhost';

GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.gestiona TO 'admin_bd'@'localhost';

GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.almacena TO 'admin_bd'@'localhost';

```
GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.integra TO
'admin_bd'@'localhost';

GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.llevan TO
'admin_bd'@'localhost';

GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.transporta TO
'admin_bd'@'localhost';

GRANT SELECT, INSERT, DELETE, UPDATE ON quickcarryDB.recorrido TO
'admin_bd'@'localhost';

#PERMISOS_CAMIONERO

GRANT SELECT, UPDATE ON quickcarryDB.transporta TO 'camionero'@'localhost';

GRANT SELECT, UPDATE ON quickcarryDB.recorrido TO 'camionero'@'localhost';

GRANT SELECT ON quickcarryDB.destino TO 'camionero'@'localhost';

GRANT SELECT ON quickcarryDB.conduce TO 'camionero'@'localhost';

GRANT SELECT ON quickcarryDB.llevan TO 'camionero'@'localhost';

#PERMISOS_OPERARIO

GRANT SELECT, UPDATE ON quickcarryDB.almacena TO 'operario'@'localhost';

GRANT SELECT, UPDATE ON quickcarryDB.integra TO 'operario'@'localhost';

GRANT SELECT, UPDATE ON quickcarryDB.llevan TO 'operario'@'localhost';

GRANT SELECT, UPDATE ON quickcarryDB.lote TO 'operario'@'localhost';

GRANT SELECT ON quickcarryDB.almacen TO 'operario'@'localhost';

GRANT SELECT ON quickcarryDB.producto TO 'operario'@'localhost';

GRANT SELECT ON quickcarryDB.gestiona TO 'operario'@'localhost';

GRANT SELECT ON quickcarryDB.camion TO 'operario'@'localhost';
```

```sql
GRANT SELECT ON quickcarryDB.destino TO 'operario'@'localhost';
```