

Internal Back-Office API — Integration Guide (QA) · Phase 1



Internal Back-Office API — Phase 1 (QA)

CONTENTS

1. Endpoint & transport
2. Authentication
3. Member bio-data by national ID
4. Errors
5. Integration checklist

This document describes the HTTP contract for the NSSF Integration Gateway's **internal back-office** member lookup: **member bio-data by national ID**. It is everything an integrator needs to authenticate and call the endpoint end to end. It documents the **contract only** — field names, meanings and status codes — not internals.

All example identifiers below are **illustrative**. NSSF supplies real QA test identifiers separately.

1. Endpoint & transport

QA base URL	<code>https://api-v2-qa.k8s.nssf.ke</code>
Transport	HTTPS only (valid public TLS certificate; no client certificate required)
Content type	<code>application/json</code>

Every `/api/**` call must carry a **Bearer JWT** (see §2). There is no IP allowlist — authentication and per-endpoint authorization are the access control.

2. Authentication

Authentication is two steps: mint a short-lived JWT with your HTTP Basic credential, then send that JWT as a **Bearer** token on every subsequent call.

Step 1 — mint a token. `POST /token` with your HTTP Basic credential:



CONFIDENTIAL

NSSF KENYA · GROWING YOU. FOR GOOD

```
POST /token HTTP/1.1
Host: api-v2-qa.k8s.nssf.ke
Authorization: Basic <base64(username:password)>
```

Response (200):

```
{
  "token": "eyJhbGciOiJSUzI1NiJ9...",
  "tokenType": "Bearer",
  "expiresInSeconds": 3600
}
```

A missing or invalid Basic credential returns 401 .

Step 2 — call the API. Send the token in the `Authorization` header (no Basic credential on this call):

```
GET /api/v1/internal/biodata/12345678 HTTP/1.1
Host: api-v2-qa.k8s.nssf.ke
Authorization: Bearer eyJhbGciOiJSUzI1NiJ9...
```

When the token expires (`expiresInSeconds`), mint a new one. Your credential is granted the `INTERNAL_BACKOFFICE` role, which authorizes the endpoint below; NSSF issues the credential.

3. Member bio-data by national ID

```
GET /api/v1/internal/biodata/{idNumber}
```

`{idNumber}` — the member's national ID number.

Response (200):



CONFIDENTIAL

NSSF KENYA · GROWING YOU. FOR GOOD

```
{
  "memberNumber": "1002003",
  "nationalId": "12345678",
  "fullName": "OTIENO JAMES OCHIENG",
  "gender": "Male",
  "dateOfBirth": "1985-04-12",
  "motherName": "ATIENO MARY ADHIAMBO",
  "nationality": "Kenyan",
  "registrationDate": "2008-09-01",
  "passport": null,
  "phone": "254712345678",
  "email": "james.otieno@example.com",
  "employerCode": "9000123",
  "employerName": "ACME LIMITED",
  "employmentDate": "2015-02-16",
  "district": "Kisumu",
  "town": "Kisumu",
  "location": "Kondele",
  "subLocation": "Migosi",
  "village": "Nyalenda",
  "estateName": "Lumumba Estate",
  "marketName": "Kibuye Market",
  "streetName": "Oginga Odinga Street",
  "allAddress": "P.O. Box 1234, Kisumu",
  "creationDate": "2008-09-01",
  "lastUpdatedDate": "2023-11-20"
}
```

Field	Type	Meaning
memberNumber	string	NSSF member number.
nationalId	string	National ID the member is registered under.
fullName	string	Member's full name.
gender	string	Gender (e.g. Male / Female).
dateOfBirth	string (YYYY-MM-DD)	Date of birth.
motherName	string null	Mother's name.
nationality	string	Nationality.
registrationDate	string (YYYY-MM-DD) null	Date the member was registered with NSSF.
passport	string null	Passport number, when held.
phone	string null	Registered mobile number.
email	string null	Registered email address.
employerCode	string null	Current employer number.
employerName	string null	Current employer name.
employmentDate	string (YYYY-MM-DD) null	Date employment commenced with the current employer.
district	string null	District of residence.
town	string null	Town of residence.
location	string null	Location (administrative area) of residence.
subLocation	string null	Sub-location of residence.
village	string null	Village of residence.
estateName	string null	Estate name.
marketName	string null	Market name.
streetName	string null	Street name.
allAddress	string null	Full postal/physical address as held on record.
creationDate	string (YYYY-MM-DD) null	Date the record was created.
lastUpdatedDate	string (YYYY-MM-DD) null	Date the record was last updated.

Outcomes: 200 exactly one match · 404 none · 409 the national ID is held by more than one member (needs manual resolution at an NSSF office).



CONFIDENTIAL

NSSF KENYA · GROWING YOU. FOR GOOD

4. Errors

Handled failures return a consistent JSON body:

```
{ "code": "NOT_FOUND", "message": "No member found for national ID 12345678" }
```

HTTP status	code	When
401	—	No token, or an expired/invalid token. Mint a fresh one via <code>POST /token</code> .
403	FORBIDDEN	Authenticated, but your credential lacks the required role.
404	NOT_FOUND	No member matches the national ID.
409	MULTIPLE_MEMBERS	The national ID is shared by more than one member.

`code` is stable and machine-readable; `message` is for humans and may change.

5. Integration checklist

1. Obtain your **HTTP Basic credential** from NSSF (granted the `INTERNAL_BACKOFFICE` role).
2. Mint a token: `POST /token` with the Basic credential → store the `token` and its `expiresInSeconds` .
3. Call the endpoint with `Authorization: Bearer <token>` ; re-mint when the token expires.
4. Handle the documented status codes — in particular `404` (no match) and `409` (the national ID is shared by more than one member).

QA only. Production is served separately; this endpoint is for integration testing.



CONFIDENTIAL