	MANUAL ON UNIFORM TRAFFIC CONTROL DEVIC
	FOR STREETS AND HIGHWAYS (MUTCD)
	INTRODUCTION
(I 1	Il text in the Introduction has been moved to and combined with Part 1, except Paragraph 6 nistorical development of the MUTCD), which has been deleted as it is unneeded, and Paragraphs 3, 0, 12, 13, and 14 which are either duplicative of text in existing Part 1 or pertain to the use of metric nits no longer used.
	PART 1
	GENERAL
11	The text in Part 1 has been reorganized and separated into four Chapters, and text from the existing
	ntroduction has been inserted into and combined with existing Part 1 text.
	CHAPTER 1A. GENERAL
S	ection 1A.01 Purpose of thUTCD
	<u>upport</u> :
	The purpose of the MUTCD is to establish national criteria for the use of traffic control devices that meet needs and expectancy of road users on all streets, highways, bikeways, and site roadways open to public
1	ravel. This purpose is achieved through the following objectives:
	A. Promote national uniformity in the meaning and appearance of traffic control devices. B. Promote national consistency in the use, installation, and operation of traffic control devices.
	C. Provide basic principles for traffic engineers to use in making decisions regarding the use, installation,
	operation, maintenance, and removal of traffic control devices.
	D. Promote safety and efficiency through appropriate use of traffic control devices.
ι	Applicability of the MUTCD to facilities open to public travel is independent of the type of ownership or urisdiction (public or private) and the source of funding (Federal, State, local, or private).
	This Manual presumes sufficient working knowledge, professional training and experience, and education the principles of engineering. Other resources can be consulted to understand the basis for decisions that
<u>a</u> :	re made in which engineering study or judgment will be applied.
S	ection 1A.01 1A.02 Purpose of Traffic Control Devices – Definition
	Support:
_	The purpose of traffic control devices, as well as the principles for their use, is to promote highway safety and efficiency by providing for the orderly movement of all road users on streets, highways, bikeways, and
	rivate roads open to public travel throughout the Nation. This paragraph moved to new Section 1D.01
P	Traffic control devices notify road users of regulations and provide warning and guidance needed for the
u	niform and efficient operation of all elements of the traffic stream in a manner intended to minimize the
	ccurrences of crashes. This paragraph deleted since it is redundant with the definition provided in ection 1C.02
	Standard:
	As defined in Section 1C.02, Traffic control devices shall be defined as include all signs, signals,
	narkings, channelizing devices, and or other devices that use color, shapes, symbols, words, sounds, and/or
	actile information for the primary purpose of communicating a used to regulatorye, warning, or guidance
_	nessage to road users one traffic, placed on, over, or adjacent to a street, highway, pedestrian facility, ikeway, pathway or private roadsite roadway open to public travel (see definition in Section 1A.13) by
	uthority of a public agency or official having jurisdiction, or, in the case of a private road, by authority of the
	rivate owner or private official having jurisdiction. This paragraph moved from the existing Introduction

Certain types of signs and other devices that do not have any traffic control purpose are sometimes placed within the highway right-of-way by or with the permission of the public agency or the official having jurisdiction over the street or highway. Most of these signs and other devices are not intended for use by roadusers in general, and their message is only important to individuals who have been instructed in their meanings. These signs and other devices are not considered to be traffic control devices and provisions regarding their design and use are not included in this Manual. Among these signs and other devices are the following:

- A. Devices whose purpose is to assist highway maintenance personnel. Examples include markers to guide snowplow operators, devices that identify culvert and drop inlet locations, and devices that precisely identify highway locations for maintenance or mowing purposes.
- B. Devices whose purpose is to assist fire or law enforcement personnel. Examples include markers that identify fire hydrant locations, signs that identify fire or water district boundaries, speed measurement pavement markings, small indicator lights to assist in enforcement of red light violations, and photo enforcement systems.
- C. Devices whose purpose is to assist utility company personnel and highway contractors, such as markers that identify underground utility locations.
- D. Signs posting local non-traffic ordinances.
- E. Signs giving civic organization meeting information.
- F. Messages displayed on changeable message signs for America's Missing: Broadcast Emergency
 Response (AMBER) alerts and homeland security information during declared states of emergency
 (see Chapter 2L of this Manual for specific provisions and limitations).

This paragraph moved from existing Section 1A.08, except for the second sentence, which has been deleted as it is unnecessary

Infrastructure elements that restrict the road user's travel paths or vehicle speeds, such as curbs, speed bumps or humps, and other raised roadway surfaces, are not traffic control devices. Certain operational devices associated with the application of traffic control strategies, such as in-vehicle electronics, fencing, roadway lighting, barriers, and attenuators are shown in this Manual for context but their design, application, and usage are not specified since they are not traffic control devices.

Standard:

Traffic control devices or their supports shall not bear any advertising message or any other message that is not related to traffic control. This paragraph has been moved to new Section 1D.09

Tourist-oriented directional signs and Specific Service signs are not considered advertising; rather, they are classified as motorist service signs. This paragraph has been moved to new Section 1D.09

Section 1A.03 Target Road Users

36 Support:

There are two groups of targe ad users for traffic control devices:

- A. Operators of vehicles, including bicyclists -- This target user is a reasonable and prudent individual who is alert and attentive, has demonstrated a basic proficiency in operating a vehicle on a specific facility, has demonstrated a basic understanding of traffic control devices and traffic laws, and is operating in a lawful manner that is appropriate for the facility and conditions, while demonstrating due care for the current conditions on the roadway.

 B. Pedestrians—This target user is an alert and attentive individual who is functioning in a lawful
- B. Pedestrians This target user is an alert and attentive individual who is functioning in a lawful manner that is appropriate for the facility and conditions, while demonstrating due care for the current conditions on the roadway. Pedestrians with disabilities might be blind or vision-impaired, have mobility limitations, or other impairments.

Because of the connectivity of the transportation network, familiarity of the target road users with a particular location cannot be presumed for the purpose of selecting and installing traffic control devices.

49 Section 1A.04 Use of the MUTCD

Standard:

1 Traffic control device principles in the MUTCD shall be developed for and used by individuals who are duly authorized and qualified to conduct traffic control device activities.

Where MUTCD content requires a decision for implementation, such decisions shall be made by individuals who have the appropriate levels of experience and expertise to make traffic control device decisions.

6 Support:

 See Section 1C.02 for definitions of "engineering study" and "engineering judgment."

8 Guidance:

In making traffic control device decisions, individuals chould consider the impacts of the decision on the following: safety and operational efficiency (mobility) of vusers at that location; the effective utilization of agency resources; cost-effectiveness; and enforcement and education aspects of traffic control devices.

Support:

Throughout this Manual the headings Standard, Guidance, Option, and Support, the meanings of which are defined in Section 1C.01, are used to classify the nature of the text that follows. Figures and tables, including the notes contained therein, supplement the text and might constitute a Standard, Guidance, Option, or Support. The user needs to refer to the appropriate text to classify the nature of the figure, table, or note contained therein. This paragraph moved from the existing Introduction

Standard:

When used in this Manual, the text headings of Standard, Guidance, Option, and Support shall be as defined in Paragraph 1 of Section 1A.13. This paragraph deleted; redundant

Support:

Throughout this Manual all dimensions and distances are provided in English units. Appendix A2 contains tables for converting each of the English unit numerical values that are used in this Manual to the equivalent Metric (International System of Units) values. This paragraph deleted; metric units are no longer referenced in the MUTCD

Guidance:

If Metric units are to be used in laying out distances or determining sizes of devices, such units should be specified on plan drawings and made known to those responsible for designing, installing, or maintaining traffic control devices. This paragraph deleted; metric units are no longer referenced in the MUTCD Guidance:

Except when a specific numeral is required or recommended by the text of a Section of this Manual, numerals displayed on the images of devices in the figures that specify quantities such as times, distances, speed limits, and weights should be regarded as examples only. When installing any of these devices, the numerals should be appropriately altered to fit the specific situation. This paragraph moved from the existing Introduction

Similarly, destination names, route numbers, and State route shields that are displayed on the images of devices in the figures should be regarded as examples only. When installing any of these devices, the destination names, route numbers, and State route shields should be appropriately altered to fit the specific situation.

Support: The following Support paragraphs moved from the existing Introduction

The following information will be useful when reference is being made to a specific portion of text in this Manual.

There are nine Parts in this Manual and each Part is comprised of one or more Chapters. Each Chapter is comprised of one or more Sections. Parts are given a single-digit numerical identification, such as Part 2 – Signs. Chapters are identified by the Part number and a letter, such as Chapter 2B – Regulatory Signs, Barricades, and Gates. Sections are identified by the Chapter number and letter followed by a decimal point and a 2-digit number, such as Section 2B.03 – Size of Regulatory Signs. In some Chapters the Sections are grouped together by subject into un-numbered sub-chapters with a heading, such as "Signing for Right-of-Way at Intersections" (Sections 2B.06 through 2B.22).

- Each Section is comprised of one or more paragraphs. The paragraphs are indented and are identified by a number. Paragraphs are counted from the beginning of each Section without regard to the
- identified by a number. Paragraphs are counted from the beginning of each Section without regard to the intervening text headings (Standard, Guidance, Option, or Support) or any intervening text in embedded
- 4 Figures or Tables. Some paragraphs have lettered or numbered items. As an example of how to cite this
- Manual, the phrase "Not less than 40 feet beyond the stop line" that appears in Section 4D. 14-07 of this
- 6 Manual would be referenced in writing a "Section 4D.1407, Par.1, A.1," and would be verbally referenced as
- 7 "Item A.1 of Paragraph 1 of Section 4D.1407."

8 Section 1A.11 1A.05 Relation ther Pub tions

Standard:

1

9

10

11

12

13

1415

16

17

18

19

20

21

22

23

24 25

26

27

28

29

30

31

32

33

34

35

36

37

38 39

40

41

42

43 44

45

46 47

48

To the extent that they are incorporated by specific reference, the latest editions of the following publications, or those editions specifically noted, shall be a part of this Manual: "Standard Highway Signs and Markings" book publication (FHWA); and "Color Specifications for Retroreflective Sign and Pavement Marking Materials" (appendix to subpart F of Part 655 of Title 23 of the Code of Federal Regulations).

Support:

The "Standard Highway Signs-and Markings" book publication includes standard alphabets and symbols and arrows for signs and pavement markings.

For information about the publications mentioned in Paragraph 1, visit the Federal Highway Administration's MUTCD website at http://mutcd.fhwa.dot.gov, or write to the FHWA, 1200 New Jersey Avenue, SE, HOTO, Washington, DC 20590.

Other publications that <u>are not regulatory in nature</u>, and <u>are not independently legally enforceable</u>, <u>but are might be</u> useful sources of information with respect to the use of this Manual <u>are listed in this paragraph.include</u>: <u>See Page i of this Manual for ordering information for the following publications (latereditions might also be available as useful sources of information): The following list has been reorganized by title</u>

- "AAA School Safety Patrol Operations Manual," 2006 Edition (American Automobile Association— AAA)
- 2. "Accessible Pedestrian Signals—A Guide to Best Practices (NCHRP Web-Only Document 117A)," 2008 Edition (Transportation Research Board—TRB)
- 3. "American National Standard for High-Visibility Public Safety Vests," (ANSI/ISEA 207-20062011), 20062011 Edition (International Safety Equipment Association—ISEA)
- 4. "American National Standard for High-Visibility Safety Apparel and Headwear," (ANSI/ISEA 107-20042010), 20042010 Edition (ISEA)
- 5. "A Policy on Geometric Design of Highways and Streets," 20042011 Edition (American Association of State Highway and Transportation Officials—AASHTO)
- 6. "Changeable Message Sign Operation and Messaging Handbook (FHWA-OP-03-070)," 2004 Edition (Federal Highway Administration—FHWA)
- 7. "Designing Sidewalks and Trails for Access—Part 2—Best Practices Design Guide (FHWA-EP-01-027)," 2001 Edition (FHWA)
- 8. "Equipment and Materials Standards of the Institute of Transportation Engineers," 1988 Edition
 (available at http://www.ite.org/standards/led/signals.asp); which includes "Chapter 1 Traffic Signal
 Lamps," 1980 Edition; "Chapter 2 Vehicle Traffic Control Signal Heads," 1985 Edition; "Chapter 3
 Pedestrian Traffic Control Signal Indications," 1985 Edition; and "Chapter 13 Purchase
 Specification for Flashing and Steady Burn Warning Lights," 2001 Edition (ITE)
- 9. "Federal-Aid Highway Program Guidance on High Occupancy Vehicle (HOV) Lanes," 2001/2012 (FHWA)
- 10. "Guide for the Development of Bicycle Facilities," 19992012 Edition (AASHTO)
- 11. "Guide for the Planning, Design, and Operation of Pedestrian Facilities," 2004 Edition (AASHTO)
- 49 12. "Guide to Metric Conversion," 1993 Edition (AASHTO)
- 50 13. "Guidelines for Accessible Pedestrian Signals (NCHRP Web-Only Document 117B)," 2008 Edition (TRB)

- 14. "Guidelines for Deter ing Traffic Signal Change and Clearance Intervals: A Recommended 1 Practice of Institute of Institute of Transportation Engineers – ITE) 3
 - 15. "Guidelines for the Selection of Supplemental Guide Signs for Traffic Generators Adjacent to Freeways," 4th-5th Edition/Guide Signs, Part II: Guidelines for Airport Guide Signing/Guide Signs, Part III: List of Control Cities for Use in Guide Signs on Interstate Highways," Item Code: GSGLC-4GSLC, 2001-2016 Edition (AASHTO)
 - 16. "Highway Capacity Manual," 20002010 Edition (TRB)

4

5

6

7 8

9

10

11 12

13

14 15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31 32

33

34

35

36 37

38

39

40 41

42

43

44

47

48

49

50

- 17. "LRFD Standard Specifications for Movable Highway Bridges Design Specifications," 1988/2007 Edition (AASHTO)
- 18. "Maintaining Traffic Sign Retroreflectivity," 20072013 Edition (FHWA)
- 19. "Manual for Assessing Safety Hardware," 2009 Edition (AASHTO)
- 20. "Manual of Traffic Signal Design," 1998 Edition (Institute of Transportation Engineers—ITE)
- 21. "Manual of Transportation Engineering Studies, 2nd Edition," 19942010 Edition (ITE
- 22. "NEMA Standards Publication TS 4-20052010 Hardware Standards for Dynamic Message Signs (DMS) With NTCIP Requirements," 20052010 Edition (National Electrical Manufacturers Association—NEMA)
- 23. "Occupational Safety and Health Administration Regulations (Standards 29 CFR), General Safety and Health Provisions - 1926.20," amended June 30, 1993 December 12, 2008 (Occupational Safety and Health Administration—OSHA)
- 24. "Pedestrian Traffic Control Signal Indications-," Part 1 1985 Edition; Part 2 Light Emitting Diode (LED) Pede n Traffic Signal Modules,") 20042010 Edition (ITE)
- 25. "Practice for roadway Lighting," RP-8, 2001 (Illuminating Engineering Society—IES)
- 26. "Preemption of Traffic Signals Near Railroad Crossings," 2006 Edition (ITE)
- 27. "Purchase Specification for Flashing and Steady Burn Warning Lights," 1981 Edition (ITE)
- 28. "Railroad-Highway Grade Crossing Handbook—Revised Second Edition (FHWA-SA-07-010)," 2007 Edition (FHWA)
- 29. "Ramp Management and Control Handbook (FHWA-HOP-06-001)," 2006 Edition (FHWA)
- 30. "Recommended Procedures for the Safety Performance Evaluation of Highway Features," (NCHRP Report 350), 1993 Edition (TRB)
- 31. "Roadside Design Guide," 20062011 Edition (AASHTO)
- 32. "Roundabouts-An Informational Guide. 2nd Edition (FHWA RD 00 067) (NCHRP Report 672)," 20002010 Edition (FHWATRB)
- 33. "Safety Guide for the Prevention of Radio Frequency Radiation Hazards in the Use of Commercial Electric Detonators (Blasting Caps)," Safety Library Publication No. 20, July 20012011 Edition (Institute of Makers of Explosives)
- 34. "Signal Timing Manual (FHWA-HOP-08-024)," 2008 Edition (FHWA)
- 35. "Signalized Intersections: an Informational Guide (FHWA-HRT-04-091SA-13-027)," 20042013 Edition (FHWA)
- 36. "The Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)," July 1998 Edition (The U.S. Access Board)
- 37. "Traffic Control Devices Handbook," 20012013 Edition (ITE)
- 38. "Traffic Detector Handbook, Third Edition (FHWA-HRT-06-018 & 139)" 1991 2006 Edition (ITEFHWA)
- 39. "Traffic Engineering Handbook," 2009 Edition (ITE)
- 40. "Traffic Engineering Metric Conversion Folders—Addendum to the Guide to Metric Conversion," 45 46 1993 Edition (AASHTO)
 - 41. "Traffic Signal Lamps," 1980 Edition (ITE)
 - 42. "Travel Better, Travel Longer: A Pocket Guide to Improving Traffic Control and Mobility for Our Older Population (FHWA-OP-03-098)," 2003 Edition (FHWA)
 - 43. "20092014 AREMA Communications & Signals Manual," (American Railway Engineering & Maintenance-of-Way Association—AREMA)
- 52 44. "Uniform Vehicle Code (UVC) and Model Traffic Ordinance," 2000 Edition" and subsequent updates 53 to "Rules of the Road" through 2014 (National Committee on Uniform Traffic Laws and Ordinances 54 Control Devices NCUTLONCUTCD)

- 45. . "Vehicle Traffic Control Signal Heads:," Part 1—1985 Edition; Part 2 Light Emitting Diode (LED) Circular Signal Supplement,")—2005 Edition (ITE); Part 3 (LED Vehicular Arrow Traffic Signal Supplement)—2004 Edition (ITE)
 - 46. "Vehicle Traffic Control Signal Heads: Light Emitting Diode (LED) Vehicle Arrow Traffic Signal Supplement," 2007 Edition (ITE)

Contact information for the organizations that publish the references in the preceding list is contained in Appendix A3 of this Manual.

The provisions of this Manual have been developed based on the content included in the specific editions of the resources listed in Paragraph 3 of this Section. Newer editions of those resources are typically reflected in subsequent editions of or revisions to this Manual, which might result in one or more changes in the provisions to which the resources apply.

Standard:

 To the extent that they are referenced in this Manual, the resources listed in this Section shall reference only to the specific edition cited. Subsequent editions of those resources shall not be applied to the provisions of this Manual until such time as it is officially revised.

Section 1A.06 Uniform Vehicle Code - Rules of the Road

Support:

The "Uniform Vehicle Code" (UVC)" is one of the publications referenced in the MUTCD. The UVC contains a model set of motor vehicle codes and traffic laws for use throughout the United States, the intent of which is to promote national uniformity in these laws. The Rules of the Road contained in the UVC are intended to be recommendations for States to adopt in their State statutes and are not independently legally enforceable.

Guidance:

The actions required of road users to obey regulatory devices should be specified by State statute, or in cases not covered by State statute, byin local ordinances or resolutions. Such statutes, ordinances, and resolutions should be consistent with the "Uniform Vehicle Code" (see Section 1A.4405). This paragraph moved from the existing Introduction and existing Section 1A.02 and revised

CHAPTER 1B. LEGAL REQUIREMENTS FOR TRAFFIC CONTROL DEVICES

2 Section 1B.01 National Standard

Standard: The following Standard paragraphs moved from the existing Introduction

The Manual on Uniform Traffic Control Devices <u>for Streets and Highways</u> (MUTCD) is incorporated by reference in 23 Code of Federal Regulations (CFR), Part 655, Subpart F and shall be recognized as the national standard for all traffic control devices installed on any street, highway, bikeway, or <u>private road site roadways</u> open to public travel (see definition in Section <u>1A.13-1C.02</u>) in accordance with 23 U.S.C. 109(d) and 402(a). <u>In accordance with 23 CFR 655.603(a)</u>, for the <u>purposes of applicability of the MUTCD:</u>

- A. Toll roads under the jurisdiction of public agencies or authorities or public-private partnerships shall be considered to be public highways;
 - B. Private roads open to public travel shall be as defined in Section 1A.13; and
 - C. Parking areas, including the driving aisles within those parking areas, that are either publicly or privately owned shall not be considered to be "open to public travel" for purposes of MUTCD applicability.

<u>In accordance with 23 CFR 655.603(a), the MUTCD shall apply to all of the following types of facilities:</u>

- A. Any street, roadway, or bikeway open to public travel, either publicly or privately owned;
- B. Streets and roadways on sites that are off the public right-of-way that are open to public travel without full-time access restrictions. Examples include roadways within shopping centers, office parks, airports, sports arenas, other similar business and/or recreation facilities, governmental office complexes, schools, universities, airports recreational parks, and other similar publicly owned complexes and/or recreation facilities. The above-described examples of streets and roadways are referred to in this Manual as Site Roadways Open to Public Travel;
- C. Publicly-owned toll roads, including those under the jurisdiction of a public agency, public authority, or public-private partnership;
- D. Privately-owned toll roads where the public is allowed to travel without access restriction. This includes gated toll roads or roadways where the general public is able to pay to access the facility and
- E. Grade crossings of publicly-owned roadways with railroads or light rail transit.

The MUTCD shall not apply to the following types of facilities:

- A. Roadways within private gated properties where access to the general public is restricted at all times;
- B. Grade crossings of privately-owned roadways with railroads;
- C. Parking areas, including the driving aisles within those parking areas, that are either publicly or privately owned and
- D. Pedestrian ways internal to buildings.

Support:

The policies and procedures of the Federal Highway Administration (FHWA) to obtain basic uniformity of traffic control devices shall be are as described in 23 CFR 655, Subpart F. This paragraph moved from the existing Introduction

Section 15-116 of the UVC states, "No person shall install or maintain in any area of private property used by the public any sign, signal, marking, or other device intended to regulate, warn, or guide traffic unless it conforms with the State manual and specifications adopted under Section 15-104." Adoption by agencies of such a provision through statute or ordinance can help maintain the integrity of official traffic control devices and provide continuity of uniformity at locations that are not subject to the provisions of this Manual.

Section 1B.02 State Adoption and Conformance

49 Support:

All States have officially adopted the National MUTCD either in its entirety, with supplemental provisions, or as a separate published document. The National MUTCD has also been adopted by the

- 1 National Park Service, the U.S. Forest Service, the U.S. Military Command, the Bureau of Indian Affairs, the
- 2 Bureau of Land Management, and the U.S. Fish and Wildlife Service. This paragraph moved from existing
- 3 Section 1A.07
- 4 Guidance:

These individual State <u>or agency</u> manuals or supplements should be reviewed for specific provisions relating to that State <u>or agency</u>. This paragraph moved from existing Section 1A.07

Standard:

In accordance with 23 CFR 655.603(b)(3), States or other Federal agencies that have their own MUTCDs or Supplements shall revise these MUTCDs or Supplements to be in substantial conformance with changes to the National MUTCD within 2 years of the effective date of the Final Rule for the changes [23 CFR 655.603(b)(3)]. Substantial conformance of such State or other Federal agency MUTCDs or Supplements shall be as defined in 23 CFR 655.603(b)(1). This paragraph moved from the existing Introduction

For purposes of Paragraph 3 of this Section, policies, directives, specifications, standard drawings, or similar documents related to traffic control devices that are issued by an agency shall be considered as supplements to the MUTCD and shall be in substantial conformance with the National MUTCD.

Guidance:

18 <u>Traffic control devices that have been granted Interim Approval in accordance with Section 1B.07, but</u>
19 <u>which have not yet been adopted into the National MUTCD, should not be included in State MUTCDs or</u>
20 <u>Supplements.</u>

Section 1B.03 Compliance of Devices

22 Standard:

The U.S. Secretary of Transportation, under authority granted by the Highway Safety Act of 1966, decreed that traffic control devices on all streets and highways open to public travel in accordance with 23 U.S.C. 109(d) and 402(a) in each State shall be in substantial conformance with the Standards issued or endorsed by the FHWA. This paragraph moved from the existing Introduction.

StandardSupport:

23 CFR 655.603 also states that requires traffic control devices on all streets, highways, bikeways, and site roadways private roads open to public travel in each State shall be in substantial conformance with standards issued or endorsed by the Federal Highway Administrator. This paragraph moved from existing Section 1A.07.

Standard:

After the effective date of a new edition of the MUTCD or a revision thereto, or after the adoption thereof by the State, whichever occurs later, new or reconstructed devices installed shall be incompliance comply with the new edition or revision. This paragraph moved from the existing Introduction

In cases involving Federal-aid projects for new highway or bikeway construction of a facility to which this Manual applies, the traffic control devices installed (temporary or permanent) shall be in conformance comply with the most recent edition of the National MUTCD before that highway is opened or re-opened to the public for unrestricted travel [23 CFR 655.603(d)(2) and (d)(3)]. This paragraph moved from the existing Introduction

Unless a particular device is no longer serviceable (see Section 1C.02 for definition), non-compliant devices on existing highways and bikeways shall be brought into compliance with the current edition of the National MUTCD as part of the systematic upgrading of substandard traffic control devices (and installation of new required traffic control devices) required pursuant to the Highway Safety Program, 23 U.S.C. §402(a). This paragraph moved from the existing Introduction

Support:

The FHWA has the authority to establish other target compliance dates for implementation of particular changes to the MUTCD [23 CFR 655.603(d)(1)]. This paragraph moved from the existing Introduction

Standard:

1 2	These target compliance dates established by the FHWA shall be as shown in Table 1-2-1B-1. This paragraph moved from the existing Introduction
3	Table 1B-1. Target Compliance Dates Established by FHWA
4 5 6	Design, application, and placement of traffic control devices other than those adopted in this Manual shall be prohibited unless the provisions of this Sections 1B.04 through 1B.07 are followed regarding official interpretations, experiments, changes to the MUTCD, and interim approvals granted
7	by the FHWA. This paragraph moved from existing Section 1A.10
8	Support:
9 10 11 12 13 14 15 16	Many of the provisions in this Manual that are explicitly prohibitive have been included to address practices that have come to be known as counterintuitive, ineffective, or inconsistent with uniformity. A provision of mandatory or recommended practice represents the accepted and established practice that promotes uniformity and consistency. The absence of a provision in this Manual that explicitly prohibits a particular practice, use, design, application, operation, or other aspect of a traffic control device does not, in itself, constitute acceptability or permission to use the device. The FHWA can issue an official interpretation (see Section 1B.05) in a case where an agency is considering employing a practice or application that is not explicitly addressed in this Manual.
17	Standard: This paragraph has been moved from the existing Introduction
18 19 20 21 22 23 24 25 26 27 28	Except as provided in Paragraph 24, when a A non-compliant traffic control device that is being replaced or refurbished because it is damaged, missing, or no longer serviceable (see Section 1C.02 for definition) for any reason, it shall be replaced with a compliant device, except when engineering judgment indicates that replacement in kind is more appropriate because: Option: A damaged, missing, or otherwise non-serviceable device that is non-compliant may be replaced in kind if engineering judgment indicates that: A. One compliant device in the midst of a series of adjacent non-compliant devices would be confusing to road users; and/or B. The schedule for replacement of the whole series of non-compliant devices will result in achieving timely compliance with the MUTCD.
29 30	Section 1A.10 Interpretations, Experimentation, Changes, and Interim Approvals This section removed and divided into Sections 1B.03 through 1B.09
31	Section 1B.04 Issuance of Official Rulings Related to this Manual
32 33 34 35	Option: The FHWA, in response to requests for interpretation, experimentation, or change, may issue an Official Ruling in response to such requests. Support:
36 37 38 39	Official Rulings are issued by the FHWA. Official Rulings include responses to requests for interpretation of the provisions of this Manual, experimentation with novel traffic control devices or application, and changes to the provisions of this Manual. Each Official Ruling is assigned a unique number and title for recordkeeping purposes.
40 41 42	Official Rulings issued under previous editions of the MUTCD are typically addressed, either in whole or part, in the next rulemaking to amend the MUTCD. Official Rulings issued under previous editions of the MUTCD are considered to be superseded by the new edition of the MUTCD.
43	The MUTCD Web site contains a searchable database of current and past Official Rulings.
44 45 46 47	Section 1B.05 Official Interpretations Paragraphs in this section moved from existing Section 1A.10 Support: In addition, Uunique situations often arise for device applications that might require interpretation or clarification of this Manual. This paragraph moved from existing Section 1A.10

An interpretation includes a consideration of the application and operation of standard traffic control devices, official meanings of standard traffic control devices, or the variations from standard device designs.

Guidance:

Requests for an interpretation of this Manual should contain the following information:

- A. A concise statement of the interpretation being sought;
 - *B.* A description of the condition that provoked the need for an interpretation;
 - C. Any illustration that would be helpful to understand the request; and
- D. Any supporting research data that is pertinent to the item to be interpreted.

Section 1B.06 Experimentation

Support:

Requests to for experimentation include consideration of field deployment for the purpose of testing or evaluating a new traffic control device, its application or manner of use, or a provision not specifically described in this Manual. This paragraph moved from existing Section 1A.10

Standard:

A traffic control ce or application that does not comply with the provisions of this Manual shall not be used on any street, highway, bikeway, or site roadway open to public travel (see definition in Section 1A.13) without first receiving official approval to experiment from the FHWA's Office of Transportation Operations.

Support:

A request for permission to experiment will be considered only when submitted by the public agency or toll facility operator authority responsible for the operation of the road or street on which the experiment is to take place. For a private road site roadway open to public travel, the request will be considered only if it is submitted by the private owner or private official having jurisdiction. This paragraph has been moved from existing Section 1A.10.

Manufacturers or inventors of novel devices are encouraged to engage the services of a qualified traffic engineer or other professional who is versed in traffic control devices. Early engagement during the concept and development processes will help ensure the efficacy of the device with regard to human factors, operational, safety, and other considerations prior to an agency requesting experimentation.

In some cases, an off-roadway closed-course or laboratory study might be required before a request for experimentation can be considered. The purpose of such a study is to determine whether testing the experimental device or application in an open-road setting could result in an undue safety risk.

Guidance:

Before requesting permission to experiment with a new device or application, an owner of a site roadway open to public travel should first check for any laws, regulations, and/or directives covering the application of the MUTCD that might apply.

Support:

A diagram indicating the process for experimenting with traffic control devices is shown in Figure 14-11B-1. This paragraph moved from existing Section 1A.10

Figure 1B-1. Process for Requesting and Conducting Experimentations for New Traffic Control

Devices

Standard: This paragraph moved from existing Section 1A.10 and revised

The request for permission to experiment should shall contain the following:

- A. A statement indicating the nature of the problem and a hypothesis establishing the premise of the experiment.
- B. A description of the proposed change to the traffic control device or application of the traffic control device, how it was developed, including the manner in which it deviates from the standard, and how it is expected to be an improvement over existing standards.
- C. <u>Any illustration <u>Illustrations</u> that would <u>be helpful</u> to <u>understand explain</u> the traffic control device or use of the traffic control device.</u>

- D. Any supporting data explaining how the traffic control device was developed, <u>including</u> if it has been <u>tried-tested</u>, in what ways it was found to be adequate or inadequate, and how this choice of device or application was derived.
- E. Comparison of the proposed device to other compliant devices or treatments, either individually or in combination, that address the same condition, if applicable.
- F. A legally binding statement that the experimental device or application is in the public domain, in accordance with Paragraph 11 of this Section.
- **G**. The time period and location(s) of the experiment.
- H. Control sites for comparison purposes.

- I. A detailed research or and evaluation plan that must provides for close monitoring of the experimentation, especially in the early throughout all stages of its field implementation. The evaluation plan should shall include before and after studies as well as quantitative data describing the performance of the experimental device.
- J. An agreement to restore the site of the experiment to a condition that complies with the provisions of this Manual within 3 months following the end of the time period of the experiment. This agreement must-shall also provide that the agency sponsoring the experimentation will terminate the experimentation at any time that it determines significant-that safety concerns are directly or indirectly attributable to the experimentation Transportation Operations. The FHWA's Office of Transportation Operations not-operational-concerns, <a href="mailto:or-or-or-or-of-the-approval-are-not-being-adhered-to-being-adhered-
- K. An agreement to provide semi-annual progress reports for the duration of the experimentation, in accordance with the schedule provided in Paragraph 8 of this Section, and an agreement to provide a copy-report of the final results of the experimentation to the FHWA's Office of Transportation Operations within 3 months following completion of the experimentation (see Paragraph 10 of this Section). The FHWA's Office of Transportation Operations has shall have the right to terminate approval of an agency's experiment if reports are not provided received in accordance with this schedule.

The required semi-annual progress reports shall be submitted throughout the course of an approved experiment in accordance with the following schedule:

- A. August 1, for the preceding period of January through June; and
- B. February 1, for the preceding period of July through December.

The experimenting agency shall submit a semi-annual progress report for any approved experiment even if no work was performed during the previous reporting period. Failure to submit two consecutive progress reports shall result in termination of the experiment and shall constitute rescission of the FHWA's approval to the experimenting agency, requiring restoration of the site(s) to a condition that complies with the provisions of this Manual within 3 months.

The experimenting agency shall submit a final report within 3 months of the conclusion of an approved experiment. If a final report is not received by the FHWA's Office of Transportation Operations, and the experimenting agency fails to notify the FHWA of any mitigating circumstances within 6 months of the end of the approved experimentation period, then the experiment shall be considered terminated and shall constitute rescission of the FHWA's approval to the experimenting agency, requiring restoration of the site(s) to a condition that complies with the provisions of this Manual within 3 months.

A request for experimentation that involves a new traffic control device or a new application of an existing traffic control device shall include from the agency conducting the experiment, the manufacturer and/or developer of the device, and the supplier of the device, a legally binding statement

- certifying that the traffic control device is not protected by a patent, trademark, or copyright, and that the traffic control device is in the public domain and may be used freely in traffic control device design and application without infringement or claim of trade secret misappropriation. The legally binding statement shall also state that the agency conducting the experiment, the manufacturer and/or developer of the device, and the supplier of the device are aware that if patent, trademark, or copyright protection is established in the future for the device or application, such action will result in its removal from the MUTCD, cancellation of its interim approval, or cancellation of the authorization for
 - Support:

experimentation.

For the purpose of the Standard in the Paragraph 7 of this Section, traffic control device means those aspects of a sign, signal, marking or other device which regulates, warns, or guides traffic. The limitation on patent, trademark, or copyright protection does not include the legal protection of individual elements of such devices. For example, manufacturing methods, assembly methods, or individual components of such devices can be protected, whereas the traffic control device cannot be subject to protection so long as it remains in this Manual. As further example, an internal circuit board for an electronic traffic control device can be legally protected, but the electronic traffic control device itself or its operational function cannot be legally protected.by any of the above forms of intellectual property.

Section 1B.07 Changes to the MUTCD

Support:

Continuing advances in technology will produce changes in the highway, vehicle, and road user proficiency; therefore, portions of the system of traffic control devices in this Manual will require updating. In addition, unique situations often arise for device applications that might require interpretation or clarification of this Manual. This sentence moved to new Section 1B.05 It is important to have a procedure for recognizing these developments and for introducing new ideas and modifications into the system. This paragraph moved from existing Section 1A.10

A change includes consideration of a new device to replace a present standard device, an additional device to be added to the list of standard devices, or a revision to a traffic control device application or placement criteria.

Guidance:

Requests for a change to this Manual should contain the following information:

- A. A statement indicating what change is proposed;
- B. Any illustration that would be helpful to understand the request; and
- C. Any supporting research data that is pertinent to the item to be reviewed. This paragraph moved from existing Section 1A.10

35 Support:

Requests for a change to this Manual will be evaluated for consideration in the next rulemaking to issue a <u>new edition of the Manual.</u> A diagram indicating the process for incorporating new traffic control devices into this Manual is shown in Figure 1A-21B-2. This paragraph moved from existing Section 1A.10

Figure 1B-2. Process for Incorporating New Traffic Control Devices into the MUTCD

Section 1B.08 Interim Approvals Paragraphs in this section moved from existing Section 1A.10 Support:

Interim approval allows <u>interim for provisional</u> use, pending official rulemaking, of a new traffic control device, a revision to the application or manner of use of an existing traffic control device, or a provision not specifically described in this Manual.

The FHWA issues an Linterim Aapproval by official memorandum signed by the Associate Administrator for Operations and posts this memorandum on the MUTCD website.

Interim approval allows for optional use of a traffic control device or application and does not create a new mandate or recommendation for use. Interim approval includes conditions that jurisdictions, toll facility

<u>authorities</u>, <u>or owners of site roadways open to public travel</u> agree to comply with in order to use the traffic control device or application until an official rulemaking action has occurred.

The issuance by FHWA of an interim approval will typically may might result in the traffic control device or application being proposed for adoption in placed into the next scheduled rulemaking process for revisions to to issue a new edition of this Manual. If the device or application under interim approval is not proposed in the next rulemaking for a new edition, then a statement of the status of the interim approval, whether it is to be rescinded or remain in effect, will be included in the Federal Register notice for the rulemaking.

Interim approval is considered based on the results of successful experimentation, results of analytical or laboratory studies, and/or review of <u>documented</u> non-U.S. experience with a traffic control device or application. Interim approval considerations include an assessment of relative risks, benefits, costs, impacts, and other factors.

Interim approval is ordinarily considered only after published authoritative research demonstrates that the device or application provides a safety or operational improvement or meets other objectives established by FHWA. Individual experiments by various jurisdictions, without a research report on the overall findings of the experimental device or application, will not ordinarily qualify for issuance of an interim approval.

Standard:

A jurisdiction, toll facility operator authority, or owner of a private road site roadway open to public travel that desires to use a traffic control device for which FHWA has issued an interim approval shall request permission from FHWA in writing prior to applying the device.

Guidance: Changed from Guidance to Standard and revised

The request *for permission*-to place a traffic control device under an <u>existing</u> interim approval <u>should</u> <u>shall</u> contain the following:

- A. A description of where the device will be used, such as a list of specific locations or highway segments or types of situations, or a statement of the intent to use the device jurisdiction-wide;
- B. An agreement to abide by the specific conditions for use of the device as contained in the FHWA's interim approval document memorandum;
- C. An agreement to maintain and continually update a list of locations where the device has been installed; and
- D. An agreement to:
 - 1. Restore the site(s) of the interim approval to a condition that complies with the provisions in this Manual within 3 months following the issuance of a Final Rule on this traffic control device; and
 - 2. Terminate use of the device or application installed under the interim approval at any time that it determines significant that safety concerns are directly or indirectly attributable to the device or application. The FHWA's Office of Transportation Operations has shall have the right to terminate the interim approval at any time if there is an indication of safety, operational, or other concerns.

Option:

A State may submit a request for the permission to use of a device under an existing interim approval for all jurisdictions in that State, as long as the request contains the information listed required in Paragraph 188 of this Section.

Guidance: Standard: Changed from Guidance to Standard and revised

If a A jurisdiction, toll facility authority, or owner of a site roadway open to public travel that elects to use a device or application under a statewide interim approval state requests and receives approval from FHWA of a statewide interim approval, the State

maintain a list of jurisdictions, toll facility authorities, and owners of site roadways open to public travel that are using the statewide interim approval. The jurisdictions, toll facility authorities, an owners of site roadways open to public travel-shall inform the State of their its use of a the device or application under the statewide interim approval.

The respective jurisdictions, toll facility authorities, and owners of site roadways open to public travel shall keep maintain and continually update a record of all locations on their roads where the

device or application is implemented (see Item C of Paragraph 8 of this Section) under any interimapproval, statewide or otherwiseshall furnish this information to the State.

Option:

 Except in a case in which an interim approval is rescinded and such rescission explicitly requires removal of the device or application installed under that interim approval, Aa device or application installed under an interim approval may remain in place, under the conditions established in the interim approval, until an official rulemaking action has occurred.

Section 1B.09 Requesting Official Interpretations, Experiments, Changes to the MUTCD, or Interim

Approvals Paragraphs in this section moved from existing Section 1A.10

10 Guidance:

A local jurisdiction, toll facility operator-authority, or owner of a private road-site roadway open to public travel that is requesting permission to experiment or permission to use a device or application under an existing interim approval should first check for any State laws, regulations, and/or directives covering the application of the MUTCD provisions that might exist apply. in their State.

Standard:

Except as provided in Paragraph 43 of this Section, requests for any interpretation, permission to experiment, a change to the MUTCD, granting of an interim approval, or change or permission to use an existing interim approval shall be submitted electronically to the Federal Highway Administration (FHWA), Office of Transportation Operations, MUTCD team, at the following e-mail address: MUTCDofficialrequest@dot.gov.

Option:

If electronic submittal is not possible, requests for <u>an interpretations</u>, permission to experiment, <u>a change to the MUTCD</u>, <u>or granting of</u> an interim approvals, <u>or changes</u> may instead be mailed to the Office of Transportation Operations, HOTO-1, Federal Highway Administration, 1200 New Jersey Avenue, SE, Washington, DC 20590.

Support:

Communications regarding other MUTCD matters that are not related to official requests will receive quicker attention if they are submitted electronically to the MUTCD Team Leader or to the appropriate individual MUTCD technical lead team member. Their e-mail addresses are available through the links contained on the "Who's WhoMUTCD Team" page on the MUTCD website at http://mutcd.fhwa.dot.gov/team.htm.

For additional information concerning interpretations, experimentation, changes, or interim approvals, visit the MUTCD website web site at http://mutcd.fhwa.dot.gov.

Each official ruling (response to a request for interpretation, experimentation, or change) issued by the FHWA is assigned a unique alphanumeric designation that corresponds to the relevant Part and edition of the MUTCD under which it was issued. Beginning with the 11th edition, the designation includes the consecutive edition number, in parentheses, following the MUTCD Part number. The number that follows the Part and edition numbers is the sequential number of the official ruling for that Part and edition. The type of official ruling is denoted in parentheses by the letter I, E, or C for interpretation, experimentation, or change, respectively. For example, Official Ruling "4(11)-20 (I)" denotes the twentieth official ruling for Part 4 of the 11th edition of the MUTCD, which is an official interpretation.

The 10th edition of the MUTCD, issued in 2009, included the edition reference as "(09)" denoting the 2009 edition of the MUTCD rather than the 10th edition of the MUTCD. The reference to the year of the edition is discontinued and replaced with the consecutive number of the edition beginning with the 11th edition of the MUTCD.

Section 1C.01 Definitions of Headings, Words, and Phrases Used in this Manual

Standard:

When used in this Manual, the text headings of Standard, Guidance, Option, and Support shall be as defined in Paragraph 1 in Section 1A.13 as follows:

- A. Standard—a statement of required, mandatory, or specifically prohibitive practice regarding a traffic control device. In limited, location-specific cases, the results of a documented engineering study (see Section 1D.05) might indicate a deviation from one or more requirements of a Standard provision to be appropriate. Based on Official Ruling No. 1(09)-1(1) All Standard statements are labeled, and the text appears in bold type. The verb "shall" is typically used. The verbs "should" and "may" are not used in Standard statements. Standard statements are sometimes modified by Options statements.
- B. Guidance—a statement of recommended, but not mandatory, practice in typical situations, with deviations allowed if engineering judgment or engineering study (see Section 1D.05) indicates the deviation to be appropriate. All Guidance statements are labeled, and the text appears in unbold type. The verb "should" is typically used. The verbs "shall" and "may" are not used in Guidance statements. Guidance statements are sometimes modified by Options statements.
- C. Option—a statement of practice that is a permissive condition and carries no requirement or recommendation. Option statements sometimes contain allowable modifications to a Standard or Guidance statement. All Option statements are labeled, and the text appears in unbold type. The verb "may" is typically used. The verbs "shall" and "should" are not used in Option statements.
- D. Support—an informational statement that does not convey any degree of mandate, recommendation, authorization, prohibition, or enforceable condition. Support statements are labeled, and the text appears in unbold type. The verbs "shall," "should," and "may" are not used in Support statements.

<u>Section 1C.02</u> <u>Definitions of Words and Phrases Used in this Manual</u> Standard:

Unless otherwise defined in this Section, or in other Parts of this Manual, words or phrases shall have the meaning(s) as defined in the most recent editions of the "Uniform Vehicle Code," "AASHTO Transportation Glossary (Highway Definitions)," and other publications mentioned referenced in Section 1A.111A.05.

The following words and phrases, when used in this Manual, shall have the following meanings:

- 1. Accessible Pedestrian Signal—a device that communicates information about pedestrian signal timing in non-visual format such as audible tones, speech messages, and/or vibrating surfaces.
- 2. Accessible Pedestrian Signal Detector—a device designated to assist the pedestrian who has visual or physical disabilities in activating the pedestrian phase.
- 3. Active Grade Crossing---a grade crossing equipped with automatic traffic control devices, such as flashing-light signals, gates, and/or traffic control signals, that are activated upon the detection of approaching rail traffic.
- 4. Actuated Operation—a type of traffic control signal operation in which some or all signal phases are operated on the basis of actuation.
- 5. Actuation—initiation of, a change in, or <u>an</u> extension of a traffic signal phase <u>or a sign legend</u> through the operation of any type of detector.
- 6. Advance Preemption—the notification of approaching rail traffic that is forwarded to the highway traffic signal controller unit or assembly by the railroad or light rail transit equipment in advance of the activation of the railroad or light rail transit warning devices.
- 7. Advance Preemption Time—the period of time that is the difference between the required maximum highway traffic signal preemption time and the activation of the railroad or light rail transit warning devices.

- 6. Advisory Speed—a recommended speed for all vehicles operating on a section of highway and based on the highway design, operating characteristics, and conditions.
 - 7. Agency---an organization with the responsibility for providing, maintaining, and/or operating a public or private road system.
 - 8. Alley—a street or highway intended to provide access to the rear or side of lots or buildings in urban areas and not intended for the purpose of through vehicular traffic.
 - **9.** Altered Speed Zone—a speed limit, other than a statutory speed limit, that is based upon an engineering study.
 - 10. Application---in regard to a traffic control device, the act of deciding to use a device, generally or at a particular location for a particular condition.
 - 11. Approach—all lanes of traffic moving toward an intersection or a midblock location from one direction, including any adjacent parking lane(s).
 - 12. Arterial Highway (Street)—a general term denoting a highway primarily used by through traffic, usually on a continuous route or a highway designated as part of an arterial system.
 - 13. Attended Lane (Manual Lane)—a toll lane adjacent to a toll booth occupied by a human toll collector who makes change, issues receipts, and perform other toll-related functions. Attended lanes at toll plazas typically require vehicles to stop to pay the toll.
 - 14. Automatic Lane—see Exact Change Lane.

- 15. Average Annual Daily Traffic (AADT)—the total volume of traffic passing a point or segment of a highway facility in both directions for one year divided by the number of days in the year. Normally, periodic daily traffic volumes are adjusted for hours of the day counted, days of the week, and seasons of the year to arrive at average annual daily traffic.
- 16. Average Daily Traffic (ADT)—the average 24 hour volume, being the total volume during a stated period divided by the number of days in that period. Normally, this would be periodic daily traffic volumes over several days, not adjusted for days of the week or seasons of the year.
- 17. Average Day—a day representing traffic volumes normally and repeatedly found at a location, typically a weekday when volumes are influenced by employment or a weekend day when volumes are influenced by entertainment or recreation.
- 17. Backplate—see Signal Backplate.
- 18. Barrier-Separated Lane—a preferential lane or other special purpose lane that is separated from the adjacent general-purpose lane(s) by a physical barrier.
- 19. Beacon—a highway traffic signal with one or more signal sections that operates in a flashing mode.
- 20. Bicycle—a pedal-powered vehicle upon which the human operator sits.
- 21. Bicycle Facilities—a general term denoting improvements and provisions that accommodate or encourage bicycling, including parking and storage facilities, and shared roadways not specifically defined for bicycle use.
- 22. Bicycle Lane—a portion of a roadway that has been designated for preferential or exclusive use by bicyclists by pavement markings and, if used, signs.
- 23. Bicycle Signal Face—a signal face that displays only bicycle symbol signal indications, that exclusively controls a bicycle movement from a designated bicycle lane or from a separate facility such as a shared use path, and that displays signal indications that are applicable only to the bicycle movement.
- 24. <u>Bicycle Symbol Signal Indication—a red, yellow, or green signal indication that displays a bicycle symbol rather than a circular or arrow indication.</u>
- 25. Bikeway—a generic term for any road, street, path, or way that in some manner is specifically designated for bicycle travel, regardless of whether such facilities are designated for the exclusive use of bicycles or are to be shared with other transportation modes.
- 26. Blank-Out Sign—a sign that displays a single predetermined message only when activated. When not activated, the sign legend is not visible.
- 27. Buffer-Separated Lane—a preferential lane or other special purpose lane that is separated from the adjacent general-purpose lane(s) by a pattern of standard longitudinal pavement markings that is wider than a normal or wide lane line marking. The buffer area might include rumble strips, textured pavement, or channelizing devices such as tubular markers or traversable curbs, but does not include a physical barrier.

28. Busway – traveled way that is used exclusively by buses.

- 26. Cantilevered Signal Structure—a structure, also referred to as a mast arm, that is rigidly attached to a vertical pole and is used to provide overhead support of highway traffic signal faces or grade crossing signal units.
- 29. Center Line Markings—the yellow pavement marking line(s) that delineates the separation of traffic lanes that have opposite directions of travel on a roadway. These markings need not be at the geometrical center of the pavement.
- 30. Changeable Message Sign—a sign that is capable of displaying more than one message (one of which might be a "blank" display), changeable manually, by remote control, or by automatic control. Electronic-display changeable message signs are referred to as Dynamic Message Signs in the National Intelligent Transportation Systems (ITS) Architecture and are referred to as Variable Message Signs in the National Electrical Manufacturers Association (NEMA) standards publication.
- 31. Channelizing Line Markings—a solid wide or double white line marking used to form islands where traffic in the same direction of travel is permitted on both sides of the island.
- 32. Circular Intersection—an intersection that has an island, generally circular in design, located in the center of the intersection where traffic passes to the right of the island. Circular intersections include roundabouts, rotaries, and traffic circles.
- 33. Circulatory Roadway—the roadway within a circular intersection on which traffic travels in a counterclockwise direction around an island in the center of the circular intersection.
- 34. Clear Storage Distance—when used in Part 8, the distance available for vehicle storage measured between 6 feet from the rail nearest the intersection to the intersection stop line or the normal stopping point on the highway. At skewed grade crossings and intersections, the 6-foot distance shall be measured perpendicular to the nearest rail either along the center line or edge line of the highway, as appropriate, to obtain the shorter distance. Where exit gates are used, the distance available for vehicle storage is measured from the point where the rear of the vehicle would be clear of the exit gate arm. In cases where the exit gate arm is parallel to the track(s) and is not perpendicular to the highway, the distance is measured either along the center line or edge line of the highway, as appropriate, to obtain the shorter distance.
- 35. Clear Zone—the total roadside border area, starting at the edge of the traveled way, that is available for an errant driver to stop or regain control of a vehicle. This area might consist of a shoulder, a recoverable slope, and/or a non-recoverable, traversable slope with a clear run-out area at its toe.
- <u>36</u>. Collector Highway—a term denoting a highway that in rural areas connects small towns and local highways to arterial highways, and in urban areas provides land access and traffic circulation within residential, commercial, and business areas and connects local highways to the arterial highways.
- 35. Concurrent Flow Preferential Lane—a preferential lane that is operated in the same direction as the adjacent mixed flow lanes, separated from the adjacent general-purpose freeway lanes by a standard lane stripe, painted buffer, or barrier.
- 37. Conflict Monitor—a device used to detect and respond to improper or conflicting signal indications and improper operating voltages in a traffic controller assembly.
- 38. Constant Warning Time <u>Train</u> Detection—a means of detecting rail traffic that provides relatively uniform warning time for the approach of <u>through</u> trains or light rail transit traffic that are not accelerating or decelerating after being detected.
- 39. Contiguous Lane—a lane, preferential or otherwise, that is separated from the adjacent lane(s) only by a normal or wide lane line marking.
- <u>40</u>. Controller Assembly—a complete electrical device mounted in a cabinet for controlling the operation of a highway traffic signal.
- 41. Controller Unit—that part of a controller assembly that is devoted to the selection and timing of the display of signal indications.
- 42. Conventional Road—a street or highway other than an low-volume road (as defined in Section 5A.01), expressway; or freeway.
- 43. Counter-Flow Lane—a lane operating in a direction opposite to the normal flow of traffic designated for peak direction of travel during at least a portion of the day. Counter-flow lanes

- are usually separated from the off-peak direction lanes by tubular markers or other flexible channelizing devices, temporary lane separators, or movable or permanent barrier.
- 44. Crashworthy—a characteristic the ability of a roadside safety hardware device or appurtenance that has been successfully crash tested is intended to minimize risks to design vehicle occupants by allowing a vehicle impacting the appurtenance to be slowed, slowed before stopping, redirected, or to continue without significant resistance, in accordance with a national standard such as the National Cooperative Highway Research Program Report 350, "Recommended Procedures for the Safety Performance Evaluation of Highway Features." Acceptable performance of a crashworthy device is determined by a nationally established standard. Roadside appurtenances include permanent and portable sign supports, other permanent or temporary traffic control devices, and other roadside fixtures that are not traffic control devices, such as longitudinal barriers, bridge railings, barricades, crash cushions, within the clear zone. Information on the FHWA's policy on crashworthiness of devices on the National Highway System and other roadways is available at the FHWA Office of Safety Web site at https://safety.fhwa.dot.gov/roadway_dept/countermeasures/reduce_crash_severity/policy_memo_guidance.cfm.
- 45. Crosswalk—(a) that part of a roadway at an intersection included within the connections of the lateral lines of the sidewalks on opposite sides of the highway measured from the curbs or in the absence of curbs, from the edges of the traversable roadway, and in the absence of a sidewalk on one side of the roadway, the part of a roadway included within the extension of the lateral lines of the sidewalk at right angles to the center line; (b) any portion of a roadway at an intersection or elsewhere distinctly indicated as a pedestrian crossing by pavement marking lines on the surface, which might be supplemented by contrasting pavement texture, style, or color.
- 46. Crosswalk Lines—white pavement marking lines that identify a crosswalk.
- 47. Cycle Length—the time required for one complete sequence of signal indications.
- 48. Dark Mode—the lack of all signal indications at a signalized location. (The dark mode is most commonly associated with power failures, ramp meters, hybrid beacons, beacons, and some movable bridge signals.)
- <u>49.</u> Delineator—a retroreflective device mounted <u>on the roadway surface or</u> at the side of the roadway in a series to indicate the alignment of the roadway, especially at night or in adverse weather.
- <u>50</u>. Design Vehicle—the longest vehicle permitted by statute of the road authority (State or other) on that roadway.
- <u>51</u>. Designated Bicycle Route—a system of bikeways designated by the jurisdiction having authority with appropriate directional and informational route signs, with or without specific bicycle route numbers.
- 52. Detectable—having a continuous edge within 6 inches of the surface so that pedestrians who have visual disabilities can sense its presence and receive usable guidance information.
- 53. Detector—a device used for determining the presence or passage of vehicles or pedestrians.
- 54. Diagnostic Team a group of knowledgeable representatives of the parties of interest in a grade crossing or group of grade crossings (see 23 CFR Section 109, Part 646.204).
- 55. Downstream—a term that refers to a location that is encountered by traffic subsequent to an upstream location as it flows in an "upstream to downstream" direction. For example, "the downstream end of a lane line separating the turn lane from a through lane on the approach to an intersection" is the end of the lane line that is closest to the intersection.
- 56. Driveway an access from a roadway to a building, site, or abutting property.
- 57. <u>Driving Aisle circulation area for motor vehicles within a parking area, typically between rows of parking spaces. Driving aisle provide a one-way or two-way travel. Driving aisles are exempted from compliance with MUTCD provisions.</u>
- 58. Dropped Lane—a through lane that becomes a mandatory turn lane on a conventional roadway, or a through lane that becomes a mandatory exit lane on a freeway or expressway. The end of an acceleration lane and reductions in the number of through lanes that do not involve a mandatory turn or exit are not considered dropped lanes.
- 59. Dual-Arrow Signal Section—a type of signal section designed to include both a yellow arrow and a green arrow.

- <u>60</u>. Dynamic Envelope—the clearance required for light rail transit traffic or a train and its cargo overhang due to any combination of loading, lateral motion, or suspension failure (see Figure 8B-8).
 - <u>61</u>. Dynamic Exit Gate Operating Mode—a mode of operation where the exit gate operation is based on the presence of vehicles within the minimum track clearance distance.
 - 62. Dynamic Message Sign—see Changeable Message Sign.

- 63. Edge Line Markings—white or yellow pavement marking lines that delineate the right or left edge(s) of a traveled way.
- 64. Electronic Toll Collection (ETC)—a system for automated collection of tolls from moving or stopped vehicles through wireless technologies such as radio-frequency communication or optical scanning. ETC systems are classified as one of the following: (1) systems that require users to have registered toll accounts, with the use of equipment inside or on the exterior of vehicles, such as a transponder or barcode decal, that communicates with or is detected by roadside or overhead receiving equipment, or with the use of license plate optical scanning, to automatically deduct the toll from the registered user account, or (2) systems that do not require users to have registered toll accounts because vehicle license plates are optically scanned and invoices for the toll amount are sent through postal mail to the address of the vehicle owner.
- 65. Electronic Toll Collection (ETC) Account Only Lane—a non-attended toll lane that is restricted to use only by vehicles with a registered toll payment account.
- <u>66</u>. Emergency-Vehicle Hybrid Beacon—a special type of hybrid beacon used to warn and control traffic at an unsignalized location to assist authorized emergency vehicles in entering or crossing a street or highway.
- <u>67</u>. Emergency-Vehicle Traffic Control Signal—a special traffic control signal that <u>assigns the</u> <u>right-of-way</u> <u>directs all conflicting traffic to stop in order to permit the driver of to an authorized emergency vehicle to proceed into the roadway or intersection.</u>
- 63. End-of-Roadway Marker—a device used to warn and alert road users of the end of a roadway in other than temporary traffic control zones.
- 68. Engineer—see Professional Engineer.
- 69. Engineering Judgment—the evaluation of available pertinent information, and the application of appropriate principles, provisions, and practices as contained in this Manual and other sources, for the purpose of deciding upon the appearance, use, installation, or applicability, design, operation, or installation of a traffic control device. Engineering judgment shall be exercised by an professional engineer (see Definition 169) with appropriate traffic engineering expertise, or by an individual working under the supervision of such an engineer, through the application of procedures and criteria established by the engineer. Documentation of engineering judgment is not required.
- 70. Engineering Study—the comprehensive analysis and evaluation of available pertinent information, and the application of appropriate principles, provisions, and practices as contained in this Manual and other sources, for the purpose of deciding upon the appearance, use, installation, or applicability, design, operation, or installation of a traffic control device. An engineering study shall be performed by an professional engineer (see Definition 169) with appropriate traffic engineering expertise, or by an individual working under the supervision of such an engineer, through the application of procedures and criteria established by the engineer. An engineering study shall be documented in writing.
- 71. Entrance Gate—an automatic gate that can be lowered across the lanes approaching a grade crossing to block road users from entering the grade crossing.
- 72. Exact Change Lane (Automatic Lane)—a non-attended toll lane that has a receptacle into which road users deposit coins totaling the exact amount of the toll. Exact Change lanes at toll plazas typically require vehicles to stop to pay the toll.
- 73. Exclusive Alignment---a light rail transit track(s) or a bus rapid transit busway that is grade-separated or protected by a fence or traffic barrier. No grade crossings exist along the track(s) or busway. Motor vehicles, bicycles, and pedestrians are prohibited within the right-of-way. Subways and elevated structures are included within this definition.
- 74. Exit Gate—an automatic gate that can be lowered across the lanes departing a grade crossing to block road users from entering the grade crossing by driving in the opposing traffic lanes.

- Exit Gate Clearance Time—for Four-Quadrant Gate systems at grade crossings, the amount of time provided to delay the descent of the exit gate arm(s) after entrance gate arm(s) begin to descend.
 - 76. Exit Gate Operating Mode—for Four-Quadrant Gate systems at grade crossings, the mode of control used to govern the operation of the exit gate arms.
 - 77. Expressway—a divided highway with partial control of access.

- 78. Fail-Safe—when used in Part 8, a railroad signal design philosophy applied to a system or device such that the result of a hardware failure or the effect of a software error shall either prohibit the system or device from assuming or maintaining an unsafe state or shall cause the system or device to assume a state that is known to be safe.
- 79. Flagger—a person who actively controls the flow of vehicular traffic into and/or through a temporary traffic control zone using hand-signaling devices or an Automated Flagger Assistance Device (AFAD).
- <u>80</u>. Flasher—a device used to turn highway traffic signal indications on and off at a repetitive rate of approximately once per second.
- 81. Flashing—an operation in which a light source, such as a traffic signal indication or LEDs in a sign, is turned on and off repetitively.
- 82. Flashing-Light Signals—a warning device consisting of two red signal indications arranged horizontally that are activated to flash alternately when rail traffic is approaching or present at a grade crossing.
- 83. Flashing Mode—a mode of operation in which at least one traffic signal indication in each vehicular signal face of a highway traffic signal is turned on and off repetitively.
- 84. Four-Quadrant Gate System an exit gate system that includes entrance and exit gates that control and block road users on all lanes entering and exiting the grade crossing.
- 85. Freeway—a divided highway with full control of access.
- **86.** Full-Actuated Operation—a type of traffic control signal operation in which all signal phases function on the basis of actuation.
- <u>87</u>. Gate—an automatically-operated or manually-operated traffic control device that is used to physically obstruct road users such that they are discouraged from proceeding past a particular point on a roadway or pathway, or such that they are discouraged from entering a particular grade crossing, ramp, lane, roadway, or facility.
- 88. General-Purpose Lane— a highway lane or set of lanes, other than a preferential lane (see

 Definition No. 169), on which all or most traffic that is allowed on that highway is also allowed
 use. Certain classes of vehicles, such as commercial vehicles or vehicles exceeding a certain
 weight, might be prohibited from using one or more of the general-purpose lanes. A
 general-purpose lane might also be restricted to certain uses, such as passing or turning.
- 89. Gore Area—see Physical Gore, Theoretical Gore.
- <u>90</u>. Grade Crossing—the general area where a highway and a railroad and/or light rail transit route cross at the same level, within which are included the tracks, highway, and traffic control devices for traffic traversing that area.
- 91. Active Grade Crossing Warning System—the flashing-light signals, with or without warning automatic gates, together with the necessary control equipment used to inform road users of the approach or presence of rail traffic at grade crossings. Name changed; moved in alphabetical order
- 92. Guide Sign—a sign that shows route designations, <u>highway names</u>, destinations, directions, distances, services, points of interest, or other geographical, recreational, or cultural information.
- 93. High-Occupancy Vehicle (HOV)—a motor vehicle carrying at least two or more persons, including carpools, vanpools, and buses.
- 94. Highway—a general term for denoting a public way for purposes of vehicular travel, including the entire area within the right-of-way.
- 95. Highway-Light Rail Transit Grade Crossing—the general area where a highway and a light rail transit route cross at the same level, within which are included the light rail transit tracks, highway, and traffic control devices for traffic traversing that area.

- 96. Highway-Rail Grade Crossing—the general area where a highway and a railroad cross at the same level, within which are included the railroad tracks, highway, and traffic control devices for highway traffic traversing that area.
 - <u>97</u>. Highway Traffic Signal—a power-operated traffic control device by which traffic is warned or directed to take some specific action. These devices do not include power-operated signs, steadily-illuminated pavement markers, <u>gates</u>, <u>flashing light signals</u> (see Section 8D.03), warning lights (see Section 6F.836L.07), or <u>steady-steady-burning</u> electric lamps.
 - 98. HOV Lane—any preferential lane designated for exclusive use by high-occupancy vehicles for all or part of a day—including a designated lane on a freeway, other highway, street, or independent roadway on a separate right-of-way.
 - 99. Hybrid Beacon—a special type of beacon that is intentionally placed in a dark mode (no indications displayed) between periods of operation and, when operated, displays both steady and flashing traffic control signal indications.
 - 100. Identification Marker--a shape, color, and/or pictograph that is used as a visual identifier for a destination guide signing system of a community wayfinding system or a shared-use path system for an area.
 - 101. Inherently Low Emission Vehicle (ILEV)—any kind of vehicle that, because of inherent properties of the fuel system design, will not have significant evaporative emissions, even if its evaporative emission control system has failed.
 - 102. In-Roadway Lights—a special type of highway traffic signal installed in the roadway surface to warn road users that they are approaching a condition on or adjacent to the roadway that might not be readily apparent and might require the road users to slow downreduce speed and/or come to a stop.
 - <u>103</u>. Interchange—a system of interconnecting roadways providing for traffic movement between two or more highways that do not intersect at grade.
 - 104. Interconnection—when used in Part 8, the electrical connection between the railroad or light rail transit active warning system and the highway traffic signal controller assembly for the purpose of preemption.
 - <u>105</u>. Intermediate Interchange—an interchange with an urban or rural route that is not a major or minor interchange as defined in this Section.
 - 106. Intersection—intersection is defined as follows:

- (a) The area embraced within the prolongation or connection of the lateral curb lines, or if none, the lateral boundary lines of the roadways of two highways that join one another at, or approximately at, right angles, or the area within which vehicles traveling on different highways that join at any other angle might come into conflict.
- (b) The junction of an alley, or driveway, or side roadway with a <u>public</u> roadway or highway shall not constitute an intersection, unless the <u>public</u> roadway or highway at said junction is controlled by a traffic control device.
- (c) If a highway includes two roadways separated by a median, then every crossing of each roadway of such divided highway by an intersecting highway shall be a separate intersection if the opposing left-turn paths cross and there is sufficient interior storage for the design vehicle. (see Figure 2A-XX)If a highway includes two roadways that are 30 feet or more apart (see definition of Median), then every crossing of each roadway of such divided highway by an intersecting highway shall be a separate intersection.
- (d) If both intersecting highways include two roadways that are 30 feet or more apart, then every crossing of any two roadways of such highways shall be a separate intersection.
- (ed) At a location controlled by a traffic control signal, regardless of the distance between the separate intersections as defined in (c) and (d) above:
 - (1) If a stop line, yield line, or crosswalk has not been designated on the roadway (within the median) between the separate intersections, the two intersections and the roadway (median) between them shall be considered as one intersection;
 - (2) Where a stop line, yield line, or crosswalk is designated on the roadway on the intersection approach, the area within the crosswalk and/or beyond the designated stop line or yield line shall be part of the intersection; and

- (3) Where a crosswalk is designated on a roadway on the departure from the intersection, the intersection shall include the area extending to the far side of such crosswalk.
- <u>107</u>. Intersection Control Beacon—a beacon used only at an intersection to control two or more directions of travel.
- 108. Interval—the part of a signal cycle during which signal indications do not change.
- 97. Interval Sequence—the order of appearance of signal indications during successive intervals of a signal cycle.
- 109. Island—a defined area between traffic lanes for control of vehicular movements, for toll collection, or for pedestrian refuge. It includes all end protection and approach treatments. Within an intersection area, a median or an outer separation is considered to be an island.
- 110. Jughandle Turn--- a left-turn or U-turn that, in conjunction with special geometry, is made by initially making a right-turn or diverging to the right. With other special geometry, a right-turn or U-turn makes a jughandle turn by initially making a left-turn or diverging to the left.
- **111.** Lane Drop—see Dropped Lane.
- 112. Lane Line Markings—white pavement marking lines that delineate the separation of traffic lanes that have the same direction of travel on a roadway.
- 113. Lane-Use Control Signal—a signal face displaying indications to permit or prohibit the use of specific lanes of a roadway or to indicate the impending prohibition of such use.
- 114. Legend—see Sign Legend.
- 115. Lens—see Signal Lens.

- 116. Light Rail Transit Traffic (Light Rail Transit Equipment)—every device in, upon, or by which any person or property can be transported on light rail transit tracks, including single-unit light rail transit cars (such as streetcars and trolleys) and assemblies of multiple light rail transit cars coupled together.
- 117. Loading Zone a specially marked, signed or designated area for the loading or unloading of vehicles (passenger or freight)
- 118. Locomotive Horn—an air horn, steam whistle, or similar audible warning device (see 49 CFR Part 229.129) mounted on a locomotive or control cab car. The terms "locomotive horn," "train whistle," "locomotive whistle," and "train horn" are used interchangeably in the railroad industry.
- 119. Logo—a distinctive emblem or trademark that identifies a commercial and/or non-commercial business, program, or organization, and/or the product or service offered by the business.
- 120. Longitudinal Markings—pavement markings that are generally placed parallel and adjacent to the flow of traffic such as lane lines, center lines, edge lines, channelizing lines, and others.
- **121.** Louver—see Signal Louver.
- 122. Low-Volume Rural Road A category of paved or unpaved conventional or special-purpose roadways having an AADT of less than 400 vehicles and lying outside of built-up or urbanized areas of cities, towns, and communities.
- 123. Major Interchange—an interchange with another freeway or expressway, or an interchange with a high-volume multi-lane highway, principal urban arterial, or major rural route where the interchanging traffic is heavy or includes many road users unfamiliar with the area.
- 124. Major Street—the street normally carrying the higher volume of vehicular traffic.
- 125. Malfunction Management Unit—same as Conflict Monitor.
- 126. Managed Lane—a highway lane or set of lanes, or a highway facility, for which variable operational strategies such as direction of travel, tolling, pricing, and/or vehicle type or occupancy requirements are implemented and managed in real-time in response to changing conditions. Managed lanes are typically buffer- or barrier-separated lanes parallel to the general-purpose lanes of a highway in which access is restricted to designated locations. There are also some highways on which all lanes are managed.
- 127. Manual Lane—see Attended Lane.
- 114. Maximum Highway Traffic Signal Preemption Time—the maximum amount of time needed following initiation of the preemption sequence for the highway traffic signals to complete the timing of the right-of-way transfer time, queue clearance time, and separation time.
- 128. Median—the portion of a highway separating opposing directions of the traveled way. the area between two roadways of a divided highway measured from edge of traveled way to edge of

- traveled way. The median excludes turn lanes. The median width might be different between intersections, interchanges, and at opposite approaches of the same intersection.
- 129. Minimum Track Clearance Distance— for standard two quadrant warning devices, the minimum track clearance distance is the length along a highway over the track(s) where a vehicle could be struck by rail traffic. at one or more railroad or light rail transit tracks, measured from the highway stop line, warning device, or 12 feet perpendicular to the track center line, to 6 feet beyond the track(2) measured perpendicular to the far rail, along the center line or edge line of the highway, as appropriate, to obtain the longer distance. The minimum track clearance distance is measured from a point upstream from the track(s) on the approach to the grade crossing to a point downstream from the track(s) on the departure from the grade crossing. The length along the highway between the two points is the minimum track clearance distance. For Four-Quadrant Gate systems, the minimum track clearance distance is the length along a highway at one or more railroad or light rail transit tracks, measured either from the highway stop line or entrance warning device, to the point where the rear of the vehicle would be clear of the exit gate arm. In cases where the exit gate arm is parallel to the track(s) and is not perpendicular to the highway, the distance is measured either along the center line or edge line of the highway, as appropriate, to obtain the longer distance.
- 117. Minimum Warning Time—when used in Part 8, the least amount of time active warning devices shall operate prior to the arrival of rail traffic at a grade crossing.
- 130. Minor Interchange—an interchange where traffic is local and very light, such as interchanges with land service access roads. Where the sum of the exit volumes is estimated to be lower than 100 vehicles per day in the design year, the interchange is classified as local.
- 131. Minor Street—the street normally carrying the lower volume of vehicular traffic.
- 132. Mixed-Use Alignment—a light rail transit track(s), a busway, or a bus only lane(s) where the LRT or BRT vehicles operate in mixed traffic with all types of road users. This includes streets, transit malls and pedestrian malls where the right-of-way is shared. In a mixed-use alignment, the light rail transit or the bus rapid transit traffic does not have the right-or-way over other road users at grade crossings and intersections. If the LRT traffic or buses are controlled by traffic control signals or LRT signal faces at an intersection with a roadway, the alignment is considered to be mixed-use even if some of the approaches to the intersection are used exclusively by LRT traffic or buses.
- 133. Movable Bridge Resistance Gate—a type of traffic gate, which is located downstream of the movable bridge warning gate, that provides a physical deterrent to vehicle and/or pedestrian traffic when placed in the appropriate position.
- 134. Movable Bridge Signal—a highway traffic signal installed at a movable bridge to notify traffic to stop during periods when the roadway is closed to allow the bridge to open.
- 135. Movable Bridge Warning Gate—a type of traffic gate designed to warn, but not primarily to block, vehicle and/or pedestrian traffic when placed in the appropriate position.
- 136. Multi-Lane—more than one lane moving in the same direction. A multi-lane street, highway, or roadway has a basic cross-section comprised of two or more through lanes in one or both directions. A multi-lane approach has two or more lanes moving toward the intersection, including turning lanes.
- 137. Neutral Area—the paved area between the channelizing lines separating an entrance or exit ramp or a channelized turn lane or channelized entering lane from the adjacent through lane(s).
- 138. Object Marker—a device used to mark obstructions within or adjacent to the roadway.
- 139. Occupancy Requirement—any restriction that regulates the use of a facility or one or more lanes of a facility for any period of the day based on a specified number of persons in a vehicle.
- 140. Occupant—a person driving or riding in a car, truck, bus, or other vehicle.
- 141. On-Street Parking parking within or along, and accessed directly from, a public roadway or a site roadway open to public travel.
- 142. Open-Road ETC Lane—a non-attended lane that is designed to allow toll payments to be electronically collected from vehicles traveling at normal highway speeds. Open-Road ETC lanes are typically physically separated from the toll plaza, often following the alignment of the mainline lanes, with toll plaza lanes for cash toll payments being on a different alignment after diverging from the mainline lanes or a subset thereof.

- 143. Open-Road Tolling—a system designed to allow electronic toll collection (ETC) from vehicles traveling at normal highway speeds. Open-Road Tolling might be used on toll roads or toll facilities in conjunction with toll plazas. Open-Road Tolling is also typically used on managed lanes and on toll facilities that only accept payment by ETC.
 - 144. Open-Road Tolling Point—the location along an Open-Road ETC lane at which roadside or overhead detection and receiving equipment are placed and vehicles are electronically assessed a toll.
 - 145. Opposing Traffic—vehicles that are traveling in the opposite direction. At an intersection, vehicles entering from an approach that is approximately straight ahead would be considered to be opposing traffic, but vehicles entering from approaches on the left or right would not be considered to be opposing traffic.
 - 146. Option Lane A lane that widens on the approach to, then splits into two lanes at, the theoretical gore of a decision point or bifurcation to allow traffic within the lane the option to continue on either route without changing lanes.
 - 147. Overhead Sign—a sign that is placed such that a portion or the entirety of the sign or its support is directly above the roadway or shoulder such that vehicles travel below it. Typical installations include signs placed on cantilever arms that extend over the roadway or shoulder, on sign support structures that span the entire width of the pavement, on mast arms or span wires either independently or that also support traffic control signals, and on highway bridges that cross over the roadway.
 - 148. Parking Area—a parking lot or parking garage that is separated from a roadway. Parallel, perpendicular, or angle parking spaces along a roadway are not considered a parking area.
 - <u>149.</u> Parking Space an area marked or designated for storage of a vehicle while the driver is not present.
 - 150. Passive Grade Crossing—a grade crossing where none of the automatic traffic control devices associated with an Active Grade Crossing Warning System are present and at which the traffic control devices consist entirely of signs and/or markings.
 - 151. Pathway—a general term denoting a public way for purposes of travel by authorized users outside the traveled way and physically separated from the roadway by an open space or barrier and either within the highway right-of-way or within an independent alignment. Pathways include shared-use paths, but do not include sidewalks.
 - 152. Pathway Grade Crossing—the general area where a pathway and railroad or light rail transit tracks cross at the same level, within which are included the tracks, pathway, and traffic control devices for pathway traffic traversing that area.
 - 153. Paved—having a roadway surface that has both a structural (weight bearing) and a sealing purpose for the roadway, such as a bituminous surface treatment, mixed bituminous concrete, or Portland cement concrete-roadway surface that has both a structural (weight bearing) and a sealing purpose for the roadway.
 - 154. Pedestrian—a person on foot, in a wheelchair, on skates, or on a skateboard.
 - 155. Pedestrian Change Interval—an interval during which the flashing UPRAISED HAND (symbolizing DONT WALK) signal indication is displayed.
 - <u>156</u>. Pedestrian Clearance Time—the time provided for a pedestrian crossing in a crosswalk, after leaving the curb or <u>shoulderedge of traveled way</u>, to travel to the far side of the traveled way or to a median.
 - 157. Pedestrian Facility—a general term denoting <u>a location where</u> improvements and provisions made to accommodate or encourage walking.
 - 158. Pedestrian Hybrid Beacon— a special type of hybrid beacon used to warn and control traffic at an unsignalized location to assist pedestrians in crossing a street or highway at a marked crosswalk.
 - 159. Pedestrian Signal Head—a signal head, which contains the symbols WALKING PERSON (symbolizing WALK) and UPRAISED HAND (symbolizing DONT WALK), that is installed to direct pedestrian traffic at a traffic control signal.
 - 160. Permissive Mode—a mode of traffic control signal operation in which left or right turns are permitted to be made after yielding to pedestrians, if any, and/or opposing traffic, if any. When a CIRCULAR GREEN signal indication is displayed, both left and right turns are permitted

- unless otherwise prohibited by another traffic control device. When a flashing YELLOW ARROW or flashing RED ARROW signal indication is displayed, the turn indicated by the arrow is permitted.
 - <u>161</u>. Physical Gore—a longitudinal point where a physical barrier or the lack of a paved surface inhibits road users from crossing from a ramp or channelized turn lane or channelized entering lane to the adjacent through lane(s) or vice versa.
 - <u>162</u>. Pictograph—a pictorial representation used to identify a governmental jurisdiction, an area of jurisdiction, a governmental <u>or other public transportation</u> agency <u>or provider</u>, a <u>military base or branch of service</u>, a governmental-approved university or college, <u>or</u> a toll payment system, <u>or a government-approved institution</u>.
 - 163. Plaque—a traffic control device intended to communicate specific information to road users through a word, symbol, or arrow legend that is placed immediately adjacent to a sign to supplement the message on the sign. The difference between a plaque and a sign is that a plaque cannot be used alone. The designation for a plaque includes a "P" suffix.
 - <u>164</u>. Platoon—a group of vehicles or pedestrians traveling together as a group, either voluntarily or involuntarily, because of traffic signal controls, geometrics, or other factors.
 - <u>165</u>. Portable Traffic Control Signal—a temporary traffic control signal that is designed so that it can be easily transported and reused at different locations.
 - <u>166</u>. Post-Mounted Sign—a sign that is placed to the side of the roadway such that no portion of the sign or its support is directly above the roadway or shoulder.
 - <u>167</u>. Posted Speed Limit—a speed limit determined by law or regulation and displayed on Speed Limit signs.
 - <u>168</u>. Preemption—the transfer of normal operation of a traffic control signal <u>or a hybrid beacon</u> to a special control mode of operation.
 - 169. Preferential Lane—a highway lane or set of lanes, or a highway facility, reserved for the exclusive use of one or more specific types of vehicles or vehicles with at least a specific number of occupants.
 - 170. Pre-Signal—traffic control signal faces that are located upstream from a signalized intersection control traffic approaching a grade crossing and are operated in conjunction with the traffic control signal faces that control traffic approaching a highway-highway intersection beyond the tracks at the downstream signalized intersection in a manner that is designed to keep the area between the stop line for the upstream traffic control signal faces and the stop line for the downstream signalized intersection clear of queued vehicles. Supplemental near-side traffic control signal faces for the highway-highwaydownstream signalized intersection are not considered to be pre-signals. Pre-signals are typically used where the clear storage distance is insufficient to store one or more design vehicles.
 - <u>171</u>. Pretimed Operation—a type of traffic control signal operation in which none of the signal phases function on the basis of actuation.
 - <u>172</u>. Primary Signal Face—one of the required or recommended minimum number of signal faces for a given approach or separate turning movement, but not including near-side signal faces required as a result of the far-side signal faces exceeding the maximum distance from the stop line.
 - 173. Principal Legend—place names, street names, and route numbers placed on guide signs.
 - 174. Priority Control—a means by which the assignment of right-of-way is obtained or modified.
 - 175. Private Road Open to Public Travel—see Site Roadways Open to Public Travel.private toll-roads and roads (including any adjacent sidewalks that generally run parallel to the road) within shopping centers, airports, sports arenas, and other similar business and/or recreation facilities that are privately owned, but where the public is allowed to travel without access restrictions. Roads within private gated properties (except for gated toll roads) where access is restricted at all times, parking areas, driving aisles within parking areas, and private grade crossings shall not be included in this definition.
 - 176. Professional Engineer (P.E.) —An individual who has fulfilled education and experience requirements and passed examinations that, under State licensure laws, permit the individual to offer engineering services within areas of expertise directly to the public.

- 177. Protected Mode—a mode of traffic control signal operation in which left or right turns are permitted to be made when a left or right GREEN ARROW signal indication is displayed.
- <u>178</u>. Public Road—any road, street, or similar facility under the jurisdiction of and maintained by a public agency and open to public travel.
- 179. Pushbutton—a button to activate a device or signal timing for pedestrians, bicyclists, or other road users.
- 180. Pushbutton Information Message—a recorded message that can be actuated by pressing a pushbutton when the walk interval is not timing and that provides the name of the street that the crosswalk associated with that particular pushbutton crosses and can also provide other information about the intersection signalization or geometry.
- 181. Pushbutton Locator Tone—a repeating sound that informs approaching pedestrians that a pushbutton exists to actuate pedestrian timing or receive additional information and that enables pedestrians who have visual disabilities to locate the pushbutton.
- 182. Queue Clearance Time—when used in Part 8, the time required for the design vehicle of maximum length stopped just inside the minimum track clearance distance to start up and move through and clear the entire minimum track clearance distance. If pre-signals are present, this time shall be long enough to allow the vehicle to move through the intersection, or to clear the tracks if there is sufficient clear storage distance. If a Four-Quadrant Gate system is present, this time shall be long enough to permit the exit gate arm to lower after the design vehicle is clear of the minimum track clearance distance.
- 183. Queue Cutter Signal—an independently-controlled traffic control signal (not operated in conjunction with the traffic control signal faces at a downstream signalized intersection) located at a grade crossing that controls traffic in one direction only on the roadway for the purpose of minimizing vehicular queuing across the tracks. The display of red signal indications is activated from a downstream queue detection system, by time of day, by approaching rail traffic, by an approaching bus on a busway, or by a combination of any of these methods.
- 184. Quiet Zone—a segment of a rail line, with in which is situated one or a number of consecutive public highway-rail grade crossings at which locomotive horns are not routinely sounded per 49 CFR Part 222.
- 185. Rail Traffic—every device in, upon, or by which any person or property can be transported on rails or tracks and to which all other traffic must yield the right-of-way by law at grade crossings, including trains, one or more locomotives coupled (with or without cars), other railroad equipment, and light rail transit operating in exclusive or semi-exclusive alignments. Light rail transit operating in a mixed-use alignment, to which other traffic is not required to yield the right-of-way by law, is a vehicle and is not considered to be rail traffic.
- 186. Raised Pavement Marker—a device mounted on or in a road surface that has a height generally not exceeding approximately 1 inch above the road surface for a permanent marker, or not exceeding approximately 2 inches above the road surface for a temporary flexible marker, and that is intended to be used as a positioning guide and/or to supplement or substitute for pavement markings. Raised pavement markers might also be recessed into or flush with the pavement surface.
- 187. Ramp Control Signal—a highway traffic signal installed to control the flow of traffic onto a freeway at an entrance ramp or at a freeway-to-freeway ramp connection.
- 188. Ramp Meter—see Ramp Control Signal.
- 189. Reconstructed---a term used to describe a roadway or a traffic control device. When used to describe a roadway, it describes a roadway that has been rebuilt or restored to its former use or that has been improved through major renovation of its structural elements. When used to describe a traffic control device, it describes a device that has been rebuilt or improved through major renovation of its structural or control elements.
- 190. Rectangular Rapid-Flashing Beacon—a pedestrian-activated device comprising two horizontally arranged, rapidly flashed, rectangular-shaped yellow indications that is used to provide supplemental emphasis for a pedestrian, school, or trail crossing warning sign at a marked crosswalk across an uncontrolled approach.
- 191. Red Clearance Interval—an interval that follows a yellow change interval and precedes the next conflicting green interval.

- 192. Regulatory Sign—a sign that gives notice to road users of traffic laws or regulations.
- 193. Retroreflectivity—a property of a surface that allows a large portion of the light coming from a point source to be returned directly back to a point near its origin.
- 194. Right-of-Way [Assignment]—the permitting of vehicles and/or pedestrians to proceed in a lawful manner in preference to other vehicles or pedestrians by the display of a sign or signal indications.
- 195. Right-of-Way, Public Highway—the limits of real property, including the traveled way, shoulders, median, and the land alongside, that are owned by the public highway agency having jurisdiction. The land within these limits is dedicated to highway uses, including roadside areas such as rest areas, scenic overlooks, and weigh stations.
- 175. Right-of-Way Transfer Time—when used in Part 8, the maximum amount of time needed for the worst case condition, prior to display of the track clearance green interval. This includes any railroad or light rail transit or highway traffic signal control equipment time to react to a preemption call, and any traffic control signal green, pedestrian walk and clearance, yellow-change, and red clearance intervals for conflicting traffic.
- 196. Road—see Roadway.

- 197. Road User—a vehicle operator, bicyclist, or pedestrian, including persons with disabilities, within the highway or on a private roadsite roadway open to public travel.
- 198. Roadway—that portion of a highway improved, designed, or ordinarily used for vehicular travel and parking lanes, but exclusive of the sidewalk, berm, or shoulder even though such sidewalk, berm, or shoulder is used by persons riding bicycles or other human-powered vehicles. In the event a highway includes two or more separate roadways, the term roadway as used in this Manual shall refer to any such roadway separately, but not to all such roadways collectively.
- 199. Roadway Network—a geographical arrangement of intersecting roadways.
- 200. Roundabout—a circular intersection with yield control at entry, which permits a vehicle on the circulatory roadway to proceed, and with deflection of the approaching vehicle counterclockwise around a central island.
- 201. Rumble Strip—a series of intermittent, narrow, transverse areas of rough-textured, slightly raised, or depressed road surface that extend across the travel lane to alert road users to unusual traffic conditions or are located along the shoulder, along the roadway center line, or within islands formed by pavement markings to alert road users that they are leaving the travel lanes.
- <u>202</u>. Rural Highway—a type of roadway normally characterized by lower volumes, higher speeds, fewer turning conflicts, and less conflict with pedestrians.
- 183. Safe-Positioned—the positioning of emergency vehicles at an incident in a manner that attempts to protect both the responders performing their duties and road users traveling through the incident scene, while minimizing, to the extent practical, disruption of the adjacent traffic flow. Relocated to Part 6.
- **203.** School—a public or private educational institution recognized by the State education authority for one or more grades K through 12 or as otherwise defined by the State.
- 204. School Zone—a designated roadway segment approaching, adjacent to, and beyond school buildings or grounds, or along which school related activities occur.
- **205.** Semi-Actuated Operation—a type of traffic control signal operation in which at least one, but not all, signal phases function on the basis of actuation.
- 206. Semi-Exclusive Alignment—a light rail transit track(s) or a bus rapid transit busway that is in a separate right-of-way or that is along a street or railroad right-of-way where motor vehicles, bicycles, and pedestrians have limited access and cross only at designated locations, such as at grade crossings where road users must yield the right-of-way to the light rail transit or the bus rapid transit traffic.
- **207.** Separate Turn Signal Face—a signal face that exclusively controls a turn movement and that displays signal indications that are applicable only to the turn movement.
- 188. Separation Time—the component of maximum highway traffic signal preemption time during which the minimum track clearance distance is clear of vehicular traffic prior to the arrival of rail traffic.

- 208. Serviceable—the condition of a traffic control device in which it appears and operates as intended, until it requires replacement due to damage or wear. Whether a device is serviceable will depend on the type of device under consideration. In general, if the device is capable of being serviced with minimal effort or replacement parts so that it continues to appear and operate as intended, and the device is otherwise substantially intact, then it can be considered to be in serviceable condition. If the device is damaged or not operational beyond reasonable repair, then it is likely no longer serviceable.
 - 209. Shared Roadway—a roadway that is officially designated and marked as a bicycle route, but which is open to motor vehicle travel and upon which no bicycle lane is designated.
 - 210. Shared Turn Signal Face—a signal face, for controlling both a turn movement and the adjacent through movement, that always displays the same color of circular signal indication that the adjacent through signal face or faces display.
- 211. Shared-Use Path—a bikeway outside the traveled way and physically separated from motorized vehicular traffic by an open space or barrier and either within the highway right-of-way or within an independent alignment. Shared-use paths are also used by pedestrians (including skaters, users of manual and motorized wheelchairs, and joggers) and other authorized motorized and non-motorized users.
- 212. Shoulder---a longitudinal area contiguous with the traveled way that is primarily for accommodation of stopped vehicles for emergency use and for lateral support of base and surface courses, and that is graded for emergency stopping. A shoulder might be paved or unpaved. A paved shoulder might be opened to part-time travel by some or all vehicles.
- **213**. Sidewalk—that portion of a street between the curb line, or the lateral line of a roadway, and the adjacent property line or on easements of private property that is paved or improved and intended for use by pedestrians.
- 214. Sidewalk Grade Crossing the portion of a highway-rail grade crossing or of a highway-light rail transit grade crossing where a sidewalk and railroad tracks or a sidewalk and light rail transit tracks cross at the same level, within which are included the tracks, sidewalk, and traffic control devices for sidewalk users traversing that area.
- 215. Sign—with regard to controlling traffic, any traffic control device that is intended to communicate specific information to road users through a word, symbol, and/or arrow legend. Signs do not include highway traffic signals, pavement markings, delineators, or channelization devices. Signs whose purpose is unrelated to traffic control are addressed in Section 1D.04.
- **216.** Sign Assembly—a group of signs, located on the same support(s), that supplement one another in conveying information to road users.
- 217. Sign Illumination—either internal or external lighting that shows similar color by day or night. Street or highway lighting shall not be considered as meeting this definition.
- 218. Sign Legend—all word messages, logos, pictographs, and symbol and arrow designs that are intended to convey specific meanings. The border, if any, on a sign is not considered to be a part of the legend.
- 219. Sign Panel—a separate panel or piece of material containing a word, <u>logo</u>, <u>pictograph</u>, symbol, and/or arrow legend that is affixed to the face of a sign.
- 220. Signal Backplate—a thin strip of material that extends outward from and parallel to a signal face on all sides of a signal housing to provide a background for improved visibility of the signal indications.
- **221.** Signal Coordination—the establishment of timed relationships between adjacent traffic control signals.
- 222. Signal Dimming---a reduction of the light output from a signal indication, hybrid beacon, or rectangular rapid-flashing beacon indication, typically for nighttime conditions, to a value that is below the minimum specified intensity for daytime conditions. If a variety of intensity levels are used during daytime conditions and all of the various levels (including the lowest of the intensities) are above the minimum specified intensity for daytime conditions, this would not be considered to be signal dimming.
- **223.** Signal Face—an assembly of one or more signal sections that is provided for controlling one or more traffic movements on a single approach.

- **224.** Signal Head—an assembly of one or more signal faces that is provided for controlling traffic movements on one or more approaches.
- **225.** Signal Housing—that part of a signal section that protects the light source and other required components.
- 226. Signal Indication—the illumination of a signal lens or equivalent device.

- 227. Signal Lens—that part of the signal section that redirects the light coming directly from the light source and its reflector, if any.
- 228. Signal Louver—a device that can be mounted inside a signal visor to restrict visibility of a signal indication from the side or to limit the visibility of the signal indication to a certain lane or lanes, or to a certain distance from the stop line.
- 229. Signal Phase—the right-of-way, yellow change, and red clearance intervals in a cycle that are assigned to an independent traffic movement or combination of movements.
- 230. Signal Section—the assembly of a signal housing, signal lens, if any, and light source with necessary components to be used for displaying one signal indication.
- 231. Interval Signal Sequence (Sequence of Indications)—the order of appearance of signal indications during successive intervals of a signal cycle.
- 232. Signal System—two or more traffic control signals operating in signal coordination.
- 233. Signal Timing—the amount of time allocated for the display of a signal indication.
- 234. Signal Visor—that part of a signal section that directs the signal indication specifically to approaching traffic and reduces the effect of direct external light entering the signal lens.
- 235. Signing—individual signs or a group of signs, not necessarily on the same support(s), that supplement one another in conveying information to road users.
- 212. Simultaneous Preemption—notification of approaching rail traffic is forwarded to the highway traffic signal controller unit or assembly and railroad or light rail transit active warning devices at the same time.
- 236. Site Roadways Open to Public Travel –Roadways and bikeways on sites of shopping centers, office parks, airports, schools, universities, sports arenas, recreational parks, and other similar business, governmental, and/or recreation facilities that are publicly or privately owned but where the public is allowed to travel without full-time access restrictions. Two types of roadways are not included in this definition: (1) roadways where access is restricted at all times by gates and/or guards to residents, employees or other specifically authorized persons; and (2) private highway-rail grade crossings. Site roadways open to public travel do not include parking areas, including the driving aisles (see Definition 148) within those parking areas.
- 237. Special-Purpose Road—a low-volume, low-speed road that serves recreational areas or resource development activities.
- 238. Speed—speed is defined based on the following classifications:
 - (a) Average Speed—the summation of the instantaneous or spot-measured speeds at a specific location of vehicles divided by the number of vehicles observed.
 - (b) Design Speed—a selected speed used to determine the various geometric design features of a roadway.
 - (c) 85th-Percenture Speed—the speed at or below which 85 percent of the motor vehicles travel.
 - (d) Operating Speed—a speed at which a typical vehicle or the overall traffic operates. Operating speed might be defined with speed values such as the average, pace, or 85^{th} -percentile speeds.
 - (e) Pace—the 10 mph speed range representing the speeds of the largest percentage of vehicles in the traffic stream.
- 239. Speed Limit—the maximum (or minimum) speed applicable to a section of highway as established by law or regulation.
- 240. Speed Limit Sign Beacon—a beacon used to supplement a SPEED LIMIT sign.
- **241.** Speed Measurement Markings—a white transverse pavement marking placed on the roadway to assist the enforcement of speed regulations.
- 242. Speed Zone—a section of highway with a speed limit that is established by law or regulation, but which might be different from a legislatively specified statutory speed limit.

- **<u>243.</u>** Splitter Island—a median island used to separate opposing directions of traffic entering and exiting a roundabout.
- **244.** Station Crossing—a pathway grade crossing that is associated with a station platform.
- 245. Statutory Speed Limit—a speed limit established by legislative action (e.g., Federal or State law) that typically is applicable for a particular class of highways with specified design, functional, jurisdictional and/or location characteristics and that is not necessarily displayed on Speed Limit signs.
- **246.** Steady (Steady Mode)—the continuous display of a signal indication for the duration of an interval, signal phase, or consecutive signal phases.
- 247. Stop Beacon—a beacon used to supplement a STOP sign, a DO NOT ENTER sign, or a WRONG WAY sign.
- **248.** Stop Line—a solid white pavement marking line extending across approach lanes to indicate the point at which a stop is intended or required to be made.
- **249.** Street—see Highway.

- 250. Supplemental Signal Face—a signal face that is not a primary signal face but which is provided for a given approach or separate turning movement to enhance visibility or conspicuity.
- 251. Swing Gate— a self-closing fence-type gate designated to swing open away from the track area and return to the closed position upon release.
- <u>252.</u> Symbol—the approved design of a pictorial <u>or graphical</u> representation of a specific traffic control message for signs, pavement markings, traffic control signals, or other traffic control devices, as shown in the MUTCD.
- **<u>253.</u>** Temporary Traffic Control Signal—a traffic control signal that is installed for a limited time period.
- <u>254.</u> Temporary Traffic Control Zone—an area of a highway where road user conditions are changed because of a work zone or incident by the use of temporary traffic control devices, flaggers, uniformed law enforcement officers, or other authorized personnel.
- 255. Theoretical Gore—a longitudinal point at the upstream end of a neutral area at an exit ramp or channelized turn lane where the channelizing lines that separate the ramp or channelized turn lane from the adjacent through lane(s) begin to diverge, or a longitudinal point at the downstream end of a neutral area at an entrance ramp or channelized entering lane where the channelizing lines that separate the ramp or channelized entering lane from the adjacent through lane(s) intersect each other.
- 256. Through Train—a train movement that continues without stopping or reversing direction throughout the entire length of the rail traffic detection circuit length approaching a highway-rail grade crossing.
- 257. Timed Exit Gate Operating Mode—a mode of operation where the exit gate descent at a grade crossing is based on a predetermined time interval.
- 258. Toll Booth—a shelter where a toll attendant is stationed to collect tolls or issue toll tickets. A toll booth is located adjacent to a toll lane and is typically set on a toll island.
- **259.** Toll Island—a raised island on which a toll booth or other toll collection and related equipment are located.
- <u>260</u>. Toll Lane—an individual lane located within a toll plaza in which a toll payment is collected or, for toll-ticket systems, a toll ticket is issued.
- <u>261</u>. Toll Plaza—the location at which tolls are collected consisting of a grouping of toll booths, toll islands, toll lanes, and, typically, a canopy. Toll plazas might be located on highway mainlines or on interchange ramps. A mainline toll plaza is sometimes referred to as a barrier toll plaza because it interrupts the traffic flow.
- 262. Toll Road (facility)---a road or facility that is open to traffic only by payment of a user toll or fee.
- 263. Toll-Ticket System—a system in which the user of a toll road receives a ticket from a machine or toll booth attendant upon entering a toll system. The ticket denotes the user's point of entry and, upon exiting the toll system, the user surrenders the ticket and is charged a toll based on the distance traveled between the points of entry and exit.

- 264. Traffic—pedestrians, bicyclists, ridden or herded animals, vehicles, streetcars, and other conveyances either singularly or together while using for purposes of travel any highway or private roadsite roadway open to public travel.
- 265. Traffic Control Device—all signs, signals, markings, channelization devices, or other devices that use colors, shapes, symbols, words, sounds, and/or tactile information for the primary purpose of communicating used to a regulateory, warning, or guideance message to road users on traffic, placed on, over, or adjacent to a street, highway, private road open to public travel, pedestrian facility, bikeway, pathway, or privatesite roadway open to public travelshared-use path by authority of a public agency or official having jurisdiction, or, in the case of a private road open to public travel, by authority of the private owner or private official having jurisdiction. Infrastructure elements that restrict the road user's travel paths or vehicle speeds, such as curbs, speed humps, and other raised roadway surfaces, are not traffic control devices.

 Transverse or longitudinal rumble strips are also not traffic control devices. Operational devices associated with the application of traffic control strategies such as in-vehicle electronics, fencing, roadway lighting, barriers, and attenuators are shown in the Manual for context but their design, application, and usage are not specified since they are not traffic control devices.
- <u>266.</u> Traffic Control Signal (Traffic Signal)—any highway traffic signal by which traffic is alternately directed to stop and permitted to proceed. <u>These devices do not include pedestrian hybrid beacons</u> (see Chapter 4J) or emergency-vehicle hybrid beacons (see Chapter 4N).
- 267. Train—one or more locomotives coupled, with or without cars, that operates on rails or tracks and to which all other traffic must yield the right-of-way by law at highway-rail grade crossings.
- 268. Transverse Markings—pavement markings that are generally placed perpendicular and across the flow of traffic such as shoulder markings; word, symbol, and arrow markings; stop lines; crosswalk lines; speed measurement markings; parking space markings; and others.
- **269.** Traveled Way—the portion of the roadway for the movement of vehicles, exclusive of the shoulders, berms, sidewalks, and parking lanes.
- 270. Turn Bay—a lane for the exclusive use of turning vehicles that is formed on the approach to the location where the turn is to be made. In most cases where turn bays are provided, drivers who desire to turn must move out of a through lane into the newly formed turn bay in order to turn. A through lane that becomes a turn lane is considered to be a dropped lane rather than a turn bay.
- 271. Uncontrolled Approach---an approach on which vehicles are not controlled by a traffic control signal, hybrid beacon, STOP sign, or YIELD sign.
- 272. Upstream—a term that refers to a location that is encountered by traffic prior to a downstream location as it flows in an "upstream to downstream" direction. For example, "the upstream end of a lane line separating the turn lane from a through lane on the approach to an intersection" is the end of the line that is furthest from the intersection.
- 273. Urban Street—a type of street normally characterized by relatively low speeds, wide ranges of traffic volumes, narrower lanes, frequent intersections and driveways, significant pedestrian traffic, and more businesses and houses.
- 274. Variable Message Sign—see Changeable Message Sign.
- 275. Vehicle—every device in, upon, or by which any person or property can be transported or drawn upon a highway, except trains and light rail transit operating in exclusive or semi-exclusive alignments. Light rail transit equipment operating in a mixed-use alignment, to which other traffic is not required to yield the right-of-way by law, is a vehicle.
- <u>276</u>. Vibrotactile Pedestrian Device—an accessible pedestrian signal feature that communicates, by touch, information about pedestrian timing using a vibrating surface.
- 277. Visibility-Limited Signal Face or Visibility-Limited Signal Section—a type of signal face or signal section designed (or shielded, hooded, or louvered) to restrict the visibility of a signal indication from the side, to a certain lane or lanes, or to a certain distance from the stop line.
- 278. Walk Interval—an interval during which the WALKING PERSON (symbolizing WALK) signal indication is displayed.
- 279. Warning Beacon—a beacon used only to supplement an appropriate warning or regulatory sign or marker.

- **280.** Warning Light—a portable, powered, yellow, lens-directed, enclosed light that is used in a temporary traffic control zone in either a steady burn or a flashing mode.
- **281.** Warning Sign—a sign that gives notice to road users of a situation that might not be readily apparent.
- 282. Warrant—a warrant describes a threshold condition based upon average or normal conditions that, if found to be satisfied as part of an engineering study, shall result in analysis of other traffic conditions or factors to determine whether a traffic control device or other improvement is justified. Warrants are not a substitute for engineering judgment. The fact that a warrant for a particular traffic control device is met is not conclusive justification for the installation of the device.
- 254. Wayside Equipment—the signals, switches, and/or control devices for railroad or light rail transit operations housed within one or more enclosures located along the railroad or light rail transit right-of-way and/or on railroad or light rail transit property.
- 283. Wayside Horn System—a stationary horn (or series of horns) located at a grade crossing that is used in conjunction with train-activated or light rail transit-activated warning systems to provide audible warning of approaching rail traffic to road users on the highway or pathway approaches to a grade crossing, either as a supplement or alternative to the sounding of a locomotive horn.
- 284. Worker—a person on foot whose duties place him or her within the right-of-way of a street, highway, or pathway construction and maintenance forces; survey crews; utility crews; responders to incidents within the street, highway, or pathway right-of-way; and law enforcement personnel when directing traffic, investigating crashes, and handling lane closures, obstructed roadways, and disasters within the right-of-way-of a street, highway, or pathway.
- 285. Wrong-Way Arrow—a slender, elongated, white pavement marking arrow placed upstream from the ramp terminus to indicate the correct direction of traffic flow. Wrong-way arrows are intended primarily to warn wrong-way road users that they are going in the wrong direction.
- 286. Yellow Change Interval—the first interval following the green or flashing arrow interval during which the steady yellow signal indication is displayed.
- 287. Yield Line—a row of solid white isosceles triangles pointing toward approaching vehicles extending across approach lanes to indicate the point at which the yield is intended or required to be made.

Section <u>1A.141C.03</u> <u>Meanings of Acronyms and Abbreviations <u>Used in this Manual</u></u>

Standard:

The following acronyms and abbreviations, when used in this Manual, shall have the following meanings:

- 1. AADT—annual average daily traffic
- 2. AASHTO—American Association of State Highway and Transportation Officials
- 3. ADA—Americans with Disabilities Act
- 4. ADAAG—Americans with Disabilities Accessibility Guidelines
- 5. ADT—average daily traffic
- 6. AFAD—Automated Flagger Assistance Device
- 7. ANSI—American National Standards Institute
- 8. cd/lx/m2---candelas per lux per square meter
- 9. CFR—Code of Federal Regulations
 - 10. CMS—changeable message sign
 - 11. dBA—A-weighted decibels
 - 11. EPA—Environmental Protection Agency
 - 12. ETC—electronic toll collection
 - 13. EV—electric vehicle
 - 14. FHWA—Federal Highway Administration
 - 15. FRA—Federal Railroad Administration
- 53 <u>16. ft --- foot or feet</u> **17. FTA—Federal T**
 - 17. FTA—Federal Transit Administration

1 17. HOT—high occupancy tolls 2 18. HOTM—FHWA's Office of Transportation Management 3 19. HOTO—FHWA's Office of Transportation Operations 4 18. HOV—high-occupancy vehicle 5 19. ILEV—inherently low-low-emission vehicle 6 **20.** in---inch(es) 7 21. ISEA—International Safety Equipment Association 8 22. ITE—Institute of Transportation Engineers 9 23. ITS—intelligent transportation systems 10 24. LED—light-light-emitting diode 25. LP—liquid petroleum 11 **26.** LRT—light rail transit 12 13 27. mi --- mile(s) 14 28. MPH or mph—miles per hour 15 29. MUTCD—Manual on Uniform Traffic Control Devices for Streets and Highways 16 30. NCHRP—National Cooperative Highway Research Program 17 31. ORT—open-road tolling 32. PCMS portable changeable message sign 18 19 32. PRT—perception-response time 20 33. RPM—raised pavement marker 21 35. RRPM raised retroreflective pavement marker 22 34. RV—recreational vehicle 23 37. TDD—telecommunication devices for the deaf 24 35. TRB—Transportation Research Board 25 36. TTC—temporary traffic control 26 **37.** U.S.—United States 27 38. U.S.C.—United States Code 28 39. USDOT—United States Department of Transportation

40. UVC—Uniform Vehicle Code

41. VPH or vph—vehicles per hour

29

30

CHAPTER 1D. PROVISIONS APPLICABLE TO TRAFFIC CONTROL DEVICES IN GENERAL

Section 1A.02 1D.01 Purpose and Principles of Traffic Control Devices

Support:

1

2

3

4

5

6

7

8

9

10

11

12

13

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31 32

33

34

35

36

37

38

39

40

41

42

43

The purpose of traffic control devices, as well as the principles for their use, is to promote highway safety and efficiency by providing for the orderly movement of all <u>reasonable and prudent</u> road users on streets, highways, bikeways, and <u>private roads site roadways</u> open to public travel throughout the Nation. <u>See Section 1A.03</u> for additional information on target road users. This paragraph moved from existing Section 1A.01

This Manual contains the basic principles that govern the design and use of traffic control devices for all streets, highways, bikeways, and private roadssite roadways open to public travel (see definition in Section 1A.131C.02) regardless of type or class or the public agency, official, or owner having jurisdiction. This Manual's text specifies the restriction on the use of a device if it is intended for limited application or for a specific system. It is important that these principles be given primary consideration in the selection and application of each device.

14 Guidance:

To be effective, a traffic control device should meet five basic requirements:

- A. Fulfill a need;
- B. Command attention;
- C. Convey a clear, simple meaning;
- D. Command respect from road users; and
- E. Give adequate time for proper response.

Design, placement, operation, maintenance, and uniformity are aspects that should be carefully considered in order to maximize the ability of a traffic control device to meet the five requirements be consistent with the five principles listed in the previous preceding paragraph. Vehicle speed should be carefully considered as an element that governs the design, operation, placement, and location of various traffic control devices.

The proper use of traffic control devices should provide the reasonable and prudent road user with the information necessary to efficiently and lawfully use the streets, highways, pedestrian facilities, and bikeways.

This paragraph relocated from later in this Section

Standard:

All traffic control devices used on site roadways open to public travel shall have the same shape, color, and meaning as those required by the MUTCD for use on public highways, except as provided in Paragraph 5 of Section 1A.03. Sign size exceptions are noted in each Chapter as applicable.

Support:

The definition of the word "speed" varies depending on its use. The definitions of specific speed terms are contained in Section 1A.13.

Guidance:

The actions required of road users to obey regulatory devices should be specified by State statute, or in cases not covered by State statute, by local ordinance or resolution. Such statutes, ordinances, and resolutions should be consistent with the "Uniform Vehicle Code" (see Section 1A.11). This paragraph moved to new Section 1A.06

The proper use of traffic control devices should provide the reasonable and prudent road user with the information necessary to efficiently and lawfully use the streets, highways, pedestrian facilities, and bikeways.

This paragraph moved up from earlier in this Section

44 Support:

- Uniformity of the meaning of traffic control devices is vital to their effectiveness. The meanings ascribed to devices in this Manual are in general accord with the publications mentioned in Section 1A.05. The first
- sentence of this paragraph moved to new Section 1D.03, while the second sentence has been deleted.
- 48 Section 1D.02 Traffic Control Device Characteristics and Activities
- 49 Support:

- The characteristics and activities associated with traffic control devices are:
- A. Meaning—The message the device is intended to convey and the expected road user response to the device.
- B. Appearance—The general physical characteristics of a specific device as it appears to the road user.

 These characteristics include color, shape, legend, acoustical and tactile features, and the relative position and layout of individual elements.
- C. Use (Application) —The process of making a decision to use a specific device at a specific location and the manner and criteria by which such a decision is made given the specific circumstances at that location.
- D. Installation—The process of determining the proper position for a device and providing appropriate visibility for the device. Considerations related to installation include height, lateral distance (offset), longitudinal distance from a reference point, and distance from other devices. Installation also includes addressing the visibility/detection of a device. In addition to height, lateral distance, and longitudinal distance, visibility/detection incorporates size, conspicuity, and contrast with the environmental background. The physical activity of installing a device is not an activity for MUTCD content purposes.
- E. Operation—The process of establishing how the physical characteristics of a device changes over a relatively short period of time to impact the movement of traffic. Most traffic control devices are static and do not have an operational aspect. However, some devices do operate (such as traffic control signals and changeable message signs). Operation does not include gradual deterioration over an extended period of time of physical characteristics due to aging, weathering, or other factors.
- F. Maintenance—The process of monitoring the visibility, crashworthiness, operational, acoustical and tactile features of a device and its performance and taking appropriate actions so that that it will function in the intended manner throughout the life of the device and be replaced at the end of its useful life.
- G. Removal—The process of determining when to remove a specific device from service.

Section 1A.06 1D.03 Uniformity of Traffic Control Devices

Support:

Uniformity of the meaning of traffic control devices is vital to their effectiveness. The meanings ascribed to devices in this Manual are in general accord with the publications mentioned in Section 1A.11. Uniformity means treating similar situations in a similar way. The first sentence of this paragraph moved from existing Section 1A.02; third sentence moved from later in existing Section 1A.06

Uniformity of devices simplifies the task of the road user because it aids in recognition and understanding, thereby reducing perception/reaction time. Uniformity assists road users, law enforcement officers, and traffic courts by giving everyone the same interpretation. Uniformity assists public highway officials through efficiency in manufacture, installation, maintenance, and administration. Uniformity means treating similar situations in a similar way. This sentence moved to earlier in this section

The use of uniform traffic control devices does not, in itself, constitute uniformity. A standard device used where it is not appropriate is as objectionable as a non-standard device; in fact, this might be worse, because such misuse might result in disrespect at those locations where the device is needed and appropriate.

Section 1A.07 1D.04 Responsibility and Authority for Traffic Control Devices

42 Standard:

The responsibility for the design, placement, operation, maintenance, and uniformity of traffic control devices in compliance with the provisions of this Manual shall rest with the public agency or the official having jurisdiction, or, in the case of private roads ite roadways or private toll roads open to public travel, with the private owner or private official having jurisdiction. 23 CFR 655.603 adopts the MUTCD as the national standard for all traffic control devices installed on any street, highway, bikeway, or private road open to public travel (see definition in Section 1A.13). When a State or other Federal agency manual or supplement is required, that manual or supplement shall be in substantial conformance with the National MUTCD.

23 CFR 655.603 also states that traffic control devices on all streets, highways, bikeways, and private roads open to public travel in each State shall be in substantial conformance with standards issued or endorsed by the Federal Highway Administrator.

This paragraph moved to new Section 1B.03

Support:

The Introduction of this Manual contains information regarding the meaning of substantial conformance and the applicability of the MUTCD to private roads open to public travel.

The "Uniform Vehicle Code" (see Section 1A.11) has the following provision in Section 15-104 for the adoption of a uniform manual:

"(a) The [State Highway Agency] shall adopt a manual and specification for a uniform system of traffic control devices consistent with the provisions of this code for use upon highways within this State. Such uniform system shall correlate with and so far as possible conform to the system set forthin the most recent edition of the Manual on Uniform Traffic Control Devices for Streets and Highways, and other standards issued or endorsed by the Federal Highway Administrator."

"(b) The Manual adopted pursuant to subsection (a) shall have the force and effect of law."

Paragraph deleted; all States have a law on adoption and have adopted the MUTCD; this is covered in new Section 1B.02

All States have officially adopted the National MUTCD either in its entirety, with supplemental provisions, or as a separate published document. This paragraph moved to new Section 1B.02 *Guidance:*

These individual State manuals or supplements should be reviewed for specific provisions relating to that State. This paragraph moved to new Section 1B.02

Support:

The National MUTCD has also been adopted by the National Park Service, the U.S. Forest Service, the U.S. Military Command, the Bureau of Indian Affairs, the Bureau of Land Management, and the U.S. Fish and Wildlife Service. This paragraph moved to new Section 1B.02

Guidance:

States should adopt Section 15-116 of the "Uniform Vehicle Code," which states that, "No person shall install or maintain in any area of private property used by the public any sign, signal, marking, or other device intended to regulate, warn, or guide traffic unless it conforms with the State manual and specifications adopted under Section 15-104." This paragraph deleted; duplicative of text in new Section 1B.01

Section 1A.08 Authority for Placement of Traffic Control Devices

Standard:

All regulatory traffic control devices shall be supported by laws, ordinances, or regulations.

Traffic control devices, advertisements, <u>public</u> announcements <u>or notices</u>, and other signs or messages within the highway right-of-way shall be placed only as authorized by a public authority or the official having jurisdiction, or, in the case of <u>private roads</u>site <u>roadways or private toll roads</u> open to public travel, by the private owner or private official having jurisdiction, for the purpose of regulating, warning, or guiding traffic.

When the public agency or the official having jurisdiction over a street or highway or, in the case of private roads open to public travel, the private owner or private official having jurisdiction, has granted proper authority, others such as contractors and public utility companies shall be permitted to install temporary traffic control devices in temporary traffic control zones. Such traffic control devices shall eonform comply with the Standards provisions of this Manual.

Support:

Provisions of this Manual are based upon the concept that effective traffic control depends upon both appropriate application of the devices and reasonable enforcement of the regulations.

Although some highway design features, such as curbs, median barriers, guardrails, speed humps or tables, and textured pavement, have a significant impact on traffic operations and safety, they are not considered to be traffic control devices and provisions regarding their design and use are generally not included in this Manual.

Certain types of signs and other devices that do not have any traffic control purpose are sometimes placed within the highway right of way by or with the permission of the public agency or the official having jurisdiction over the street or highway. Most of these signs and other devices are not intended for use by road users in general, and their message is only important to individuals who have been instructed in their meanings. These signs and other devices are not considered to be traffic control devices and provisions regarding their design and use are not included in this Manual. Among these signs and other devices are the following:

- A. Devices whose purpose is to assist highway maintenance personnel. Examples include markers to guide snowplow operators, devices that identify culvert and drop inlet locations, and devices that precisely identify highway locations for maintenance or mowing purposes.
- B. Devices whose purpose is to assist fire or law enforcement personnel. Examples include markers that identify fire hydrant locations, signs that identify fire or water district boundaries, speed measurement pavement markings, small indicator lights to assist in enforcement of red light violations, and photoenforcement systems.
- C. Devices whose purpose is to assist utility company personnel and highway contractors, such as markers that identify underground utility locations.
- D. Signs posting local non-traffic ordinances.
- E. Signs giving civic organization meeting information. This paragraph moved to new Section 1A.02

Standard:

Signs and other devices that do not have any traffic control purpose that are placed within the highway right-of-way shall not be located where they will interfere with, or detract from, traffic control devices.

Guidance:

Any unauthorized traffic control device or other sign or message placed on the highway right of way by a private organization or individual constitutes a public nuisance and should be removed. All unofficial or non-essential traffic control devices, signs, or messages should be removed.

Support:

23 CFR 1.23(b) requires that the highway right-of-way be used exclusively for highway purposes.

States are encouraged to adopt, through policy or legislation, the provisions of 23 CFR 750.108 that restrict outdoor advertising from resembling traffic control devices.

Section 1A.09 1D.05 Engineering Study and Engineering Judgment

Support:

Definitions of an professional engineer, engineering study, and engineering judgment are contained in Section 1A.131C.02.

The application of engineering study and engineering judgment is a fundamental tenet of the application of traffic control devices. It is for this reason that, in most cases, the selection of a particular device is not required by a Standard provision, but is determined by engineering study or engineering judgment. Many Standard provisions in this Manual specifically require, by explicit language in the individual provisions or by implication, the application of engineering study or engineering judgment in applying those Standards. Sitespecific conditions might result in the determination that it is impossible or impracticable to comply with a Standard. In such a case, a deviation from the requirement of a particular Standard at that location might be the only possibility. In such limited, specific cases, the deviation is allowed, provided that the agency or official having jurisdiction fully document, through engineering study, the engineering basis for the deviation.

Standard:

This Manual describes the application of traffic control devices, but shall not be a legal requirement for their installation.

Guidance:

The decision to use a particular device at a particular location should be made on the basis of either an engineering study or the application of engineering judgment. Thus, while this Manual provides Standards, Guidance, and Options for design and applications of traffic control devices, this Manual should not be considered a substitute for engineering judgment. Engineering judgment should be exercised in the selection

and application of traffic control devices, as well as in the location and design of roads and streets that the devices complement.

Early in the processes of location and design of roads and streets, engineers should coordinate such location and design with the design and placement of the traffic control devices to be used with such roads and streets.

Jurisdictions, or owners of private roadssite roadways or private toll roads open to public travel, with responsibility for traffic control that do not have engineers on their staffs who are trained and/or experienced in traffic control devices should seek engineering assistance from others, such as the State transportation agency, their county, a nearby large city, or a traffic engineering consultant.

Support: Revisions to the following Support paragraphs are based on Official Ruling No. 1(09)-1(I)

The provisions of this Manual are intended to be interpreted and applied by engineers or those under the supervision of an engineer. The construction of the provisions of this Manual, therefore, are informed by bases referenced in Paragraphs 8 and 9 of this Section.

The National Council of Examiners for Engineering and Surveying (NCEES) has defined the practice of engineering as "any service or creative work requiring engineering education, training, and experience in the application of engineering principles and the interpretation of engineering data to engineering activities that potentially impact the health, safety, and welfare of the public." The practice of engineering is, therefore, subject to regulation in the public interest and is regulated by the State licensing boards in order to safeguard the health, safety, and welfare of the public. The NCEES has defined an engineer as "an individual who is qualified to practice engineering by reason of engineering education, training, and experience in the application of engineering principles and the interpretation of engineering data."

The U. S. Office of Personnel Management (OPM) has defined the professional knowledge of engineering as "the comprehensive, in-depth knowledge of mathematical, physical, and engineering sciences applicable to a specialty field of engineering that characterizes a full 4-year engineering program leading to a bachelor's degree, or the equivalent." The OPM has defined professional ability to apply engineering knowledge as "the ability to (a) apply fundamental and diversified professional engineering concepts, theories, and practices to achieve engineering objectives with versatility, judgment, and perception; (b) adapt and apply methods and techniques of related scientific disciplines; and (c) organize, analyze, interpret, and evaluate scientific data in the solution of engineering problems."

As part of the Federal aid Program, each State is required to have a Local Technical Assistance Program (LTAP) and to provide technical assistance to local highway agencies. Requisite technical training in the application of the principles of the MUTCD is available from the State's Local Technical Assistance Program (LTAP) for needed engineering guidance and assistance. First sentence deleted; not needed

Section 1A.03 1D.06 Design of Traffic Control Devices

Guidance:

Devices should be designed so that features such as size, shape, color, composition, lighting or retroreflection, and contrast are combined to draw attention to the devices; that size, shape, color, and simplicity of message combine to produce a clear meaning; that legibility and size combine with placement to permit adequate time for response; and that uniformity, size, legibility, and reasonableness of the message combine to command respect.

Option:

With the eException of for symbols and colors, minor modifications in the specific design elements of a device may be made based on an engineering study or engineering judgment, in accordance with Paragraph 3 of this Section, provided the essential appearance characteristics are preserved. This paragraph moved from later in this Section

Guidance:

Aspects of a <u>traffic control</u> device's standard design should <u>not</u> be modified only ifunless there is a demonstrated need <u>in unusual circumstances</u>, <u>based on an engineering study or engineering judgment</u>.

49 Support:

An example of modifying a device's design would be to modify the Combination Horizontal
Alignment/Intersection (W1-10) sign to show intersecting side roads on both sides rather than on just one side
of the major road within the curve.

Standard:

4

5

6

7

8

9 10

16

17

18

23

24

25

26

27 28

34

35

36

37

38

39 40

41

42

43

44

46

47

48

Shapes that are exclusive to a particular sign (e.g., octagon for Stop, pennant for No Passing Zone, or circle for Railroad Advance) shall not be obscured by another sign mounted on the back of the same assembly.

<u>Colors (see Section 1D.07) shall be consistent across the face of a sign or a sign panel. Color gradients (smooth or defined gradual transitions either within a color or transition to another color) shall not be allowed.</u>

11 Section 1A.12 1D.07 Color Code

12 Support:

The following color code establishes general meanings for 11 colors of a total of 13 colors that have been identified as being appropriate for use in conveying traffic control information.

15 Standard:

The general meaning of the 13 colors shall be as follows:

- A. Black—regulation
 - B. Blue—road-user services guidance, tourist information, and evacuation route
- 19 C. Brown—recreational and cultural interest area guidance
- 20 **D.** Coral—unassigned (reserved for future designation)
- 21 E. Fluorescent Pink—incident management 22 F. Fluorescent Yellow-Green—pedestrian w
 - F. Fluorescent Yellow-Green—pedestrian warning, bicycle warning, playground warning, school bus and school warning
 - G. Green—indicated movements or actions permitted, direction guidance
 - H. Light Blue—unassigned (reserved for future designation)
 - I. Orange—temporary traffic control
 - J. Purple—lanes restricted to use only by vehicles with registered electronic toll collection (ETC) accounts
- 29 K. Red—stop or prohibition
- 30 L. White—regulation
- 31 M. Yellow—warning

These colors shall be used only as prescribed for the specific devices or applications throughout this Manual.

Support:

The two colors for which general meanings have not yet been assigned are being reserved for future applications that will be determined only by FHWA after consultation with the States, the engineering community, and the general public. The meanings described in this Section are of a general nature. More specific assignments of colors are given in the individual Parts of this Manual relating to each class of devices.

This paragraph moved from earlier in the Section

Tolerance limits for each color are contained in 23 CFR Part 655, Appendix to Subpart F and are available at the Federal Highway Administration's MUTCD webWeb site at http://mutcd.fhwa.dot.gov or by writing to the FHWA, Office of Safety Research and Development (HRD-T-301), 6300 Georgetown Pike, McLean, VA 22101. This paragraph moved from earlier in this Section

Section 1D.08 Public Domain, Copyrights, and Patents

45 **Standard:**

Any traffic Traffic control device design or application provisions contained in this Manual shall be considered to be in the public domain. Traffic control devices contained in this Manual shall not be protected by a patent, trademark, or copyright, except for the Interstate Shield, 511 Travel

49 <u>Information pictograph</u>, and any items owned by FHWA. This paragraph moved from the existing

50 Introduction.

A traffic control device design or application shall not be eligible for official experimentation (see Section 1B.05) or interim approval (see Section 1B.07) unless it is in the public domain. Express abandonment of any and all forms of proprietary protection, such as patents, trademarks, or copyrights, related to the design and application of the traffic control device shall satisfy the requirement for the traffic control device to be in the public domain.

The requirement for the traffic control device to be in the public domain shall not apply to individual components used in the assembly or manufacture of the traffic control device.

Support:

The limitation on patented, trademarked, or copyrighted traffic control devices applies to the message that the device conveys to the road user. If a patent or other protection covers the device's communication to the road user by virtue of its appearance, audible message, or other aspects of the message conveyed (e.g., the order in which traffic control signal indications change from green to yellow and red), then the device is considered to be protected and not in the public domain. Such a device is precluded from inclusion in this Manual. The purpose of this limitation is to ensure uniformity of the messaging of individually approved traffic control devices. This limitation does not apply to other aspects of a device (e.g., internal controls, circuitry, electronics, mechanics, housing, etc.) so long as the appearance, audible message, or other aspects of the message conveyed, including the manner of conveyance, remain freely reproducible by all without infringing on any proprietary rights or interests. This Manual does not prohibit such other aspects of a traffic control device that meet the legal requirements from being protected through patent, trademark, or copyright; and does not restrict components, parts, manufacturing processes, or similar aspects of traffic control devices from being patented or otherwise protected.

Pictographs, as defined in Section <u>1A.131C.02</u>, are embedded in traffic control devices but the pictographs themselves are not considered traffic control devices for the purposes of Paragraph 4 <u>of this Section</u>.

Business identification logos, as defined in Section 1C.02, are embedded in traffic control devices but the pictographs themselves are not considered traffic control devices for the purposes of Paragraph 4 of this Section.

Section 1D.09 Advertising

Standard:

Traffic control devices or their supports shall not bear any advertising message or any other message that is not related to traffic control. This paragraph moved from existing Section 1A.01 Support:

Tourist-oriented dDirectional signs, and Specific Service signs, and Acknowledgment signs are not considered advertising; rather, they are classified as motorist service signs. This paragraph moved from existing Section 1A.01

Section 1A.15 1D.10 Abbreviations Used on Traffic Control Devices

Standard:

When the word messages shown in Table <u>1A-11D-1</u> need to be abbreviated in connection with traffic control devices, the abbreviations shown in Table <u>1A-11D-1</u> shall be used.

Table 1D-1. Acceptable Abbreviations

When the word messages shown in Table <u>1A-21D-2</u> need to be abbreviated on a portable changeable message sign, the abbreviations shown in Table <u>1A-21D-2</u> shall be used. Unless indicated by an asterisk, these abbreviations shall only be used on portable changeable message signs.

Table 1D-2. Abbreviations That Shall be Used Only on Portable Changeable Message Signs

45 Guidance:

The abbreviations for the words listed in Table $\frac{1A-2}{1D-2}$ that also show a prompt word should not be used on a portable changeable message sign (or a static sign if indicated in Table 1D-2 by an asterisk) unless the prompt word shown in Table $\frac{1A-2}{1D-2}$ either precedes or follows the abbreviation, as applicable.

Standard:

The abbreviations shown in Table <u>1A-31D-3</u> shall not be used in connection with traffic control devices because of their potential to be misinterpreted by road users.

Table 1D-3. Unacceptable Abbreviations

Guidance:

1

2

3

4

5

6 7

8

9

10

11

12

13

14

15 16

17

18

19

20

21

22

23

24

25

26

27

28

29

31

32

33

34

36

If multiple abbreviations are permitted in Table 1A-11D-1 or 1A-21D-2 indicates that more than one abbreviation is permitted for a given word or phrase, the same abbreviation should be used throughout a single jurisdiction.

Except as otherwise provided in Table <u>1A-1D-1</u> or <u>1A-21D-2</u> or unless necessary to avoid confusion, periods, commas, apostrophes, question marks, ampersands, and other punctuation marks or characters that are not letters or numerals should not be used in any abbreviation.

Section 1A.04 1D.11 Placement and Operation of Traffic Control Devices

Standard:

Before any new highway, private roadsite roadway open to public travel (see definition in Section 1A.131C.02), paved detour, or temporary route is opened to public travel, all necessary markingstraffic control devices should shall be in place. Relocated from existing Sections 3A.01 and 6B.01 and changed from Guidance to Standard

Guidance:

Placement of a traffic control device should be within the road user's view so that adequate visibility is provided. To aid in conveying the proper meaning, the traffic control device should be appropriately positioned with respect to the location, object, or situation to which it applies. The location and legibility of the traffic control device should be such that a road user has adequate time to make the proper response in both day and night conditions.

Traffic control devices should be placed and operated in a uniform and consistent manner.

Unnecessary traffic control devices should be removed. The fact that a device is in good physical condition should not be a basis for deferring needed removal or change.

Support:

Section 2A.02 contains information on excessive use of signs and other considerations that can reduce their effectiveness and the effectiveness of other traffic control devices.

Section 1A.05 1D.12 Maintenance of Traffic Control Devices

30 Guidance:

Functional maintenance of traffic control devices should be used to determine if certain devices need to be changed to meet current traffic conditions.

Physical maintenance of traffic control devices should be performed to retain the legibility and visibility of the device, and to retain the proper functioning of the device.

35 Support:

Clean, legible, properly mounted devices in good working condition command the respect of road users.

2

4

5

6

7

8

22

23

24

25

26

27

28

29

30

31

32

33

34

35 36

37

38

41

42

43

44

45

46

47

48 49

Section 2A.01 Function and Purpose of Signs

3 Support

This Manual contains Standards, Guidance, and Options for the signing of all types of highways, and private roads open to public travel. The functions of signs are to provide regulations, warnings, and guidance information for road users. Words, symbols, and arrows are used to convey the messages. Signs are not typically used to confirm rules of the road (see Paragraph 4 of this Section).

Detailed sign requirements are located in the following Chapters of Part 2:

- 9 Chapter 2B—Regulatory Signs, Barricades, and Gates
- 10 Chapter 2C—Warning Signs and Object Markers
- 11 Chapter 2D—Guide Signs for Conventional Roads
- 12 Chapter 2E—Guide Signs for Freeways and Expressways
- 13 Chapter 2F—Toll Road Signs
- 14 Chapter 2G—Preferential and Managed Lane Signs
- 15 Chapter 2H—General Information Signs
- 16 Chapter 2I—General Service Signs
- 17 Chapter 2J—Specific Service (Logo) Signs
- 18 Chapter 2K—Tourist-Oriented Directional Signs
- 19 Chapter 2L—Changeable Message Signs
- 20 Chapter 2M—Recreational and Cultural Interest Area Signs
- 21 Chapter 2N—Emergency Management Signs

Definitions and acronyms that are applicable to signs are given in Sections 1A.13 and 1A.14 Chapter 1C.

Moved from Section 2A.02

Standard:

Because the requirements and standards for signs depend on the particular type of highway uponwhich they are to be used, the definitions for freeway, expressway, conventional road, and specialpurpose road given in Section 1A.13 shall apply in Part 2. Deleted, repetitive and not necessary

Guidance:

Signs should not be used on a frequent basis to confirm rules of the road or statutes. Instead, when determined necessary to advise of new regulations as part of an educational campaign, temporary signs or messages should be used instead of permanent signs. These temporary signs or messages should be used sparingly and only at strategic locations, and should be considered only as a supporting element of a larger educational campaign rather than as the primary source of notification. If engineering judgment determines a need for a permanent sign to distinguish between differing requirements of similar statutes in different States or jurisdictions, then a sign should be located in the vicinity of the State or jurisdictional boundary, removed from warning, directional, and higher priority regulatory signs, so as not to contribute to sign clutter (see Section 2A.19).

Section 2A.02 Definitions Moved to Section 2A.01

39 Section 2A.03 2A.02 Standardization of Application

40 Support:

It is recognized that urban traffic conditions differ from those in rural environments, and in many instances signs are applied and located differently. Where pertinent and practical, this Manual sets forth separate recommendations for urban and rural conditions.

Low-volume <u>rural</u> roads typically include <u>access to rural residences</u>, agricultural, recreational, resource management and development such as mining, <u>and</u> logging, and grazing, and local roads in rural areas. <u>Atsome locations on On</u> low-volume <u>rural</u> roads, the use of traffic control devices <u>might be needed to provide the road user limited</u>, <u>but essential</u>, information regarding regulation, guidance, and <u>warning is limited to essential information regarding regulation</u>, guidance and <u>warning</u>. On low-volume rural roads, it is important to consider the needs of unfamiliar road users for occasional, recreational, and commercial transportation

- 50 purposes. Moved from existing Section 5A.01 and edited
- 51 Guidance:

Signs should be used only where justified by engineering judgment or studies, as provided in Section 1A.09.

Results from traffic engineering studies of physical and traffic factors should indicate the locations where signs are deemed necessary or desirable.

Roadway geometric design and sign application should be coordinated so that signing can be effectively placed to give the road user any necessary regulatory, warning, guidance, and other information.

Standard:

1

2

3

4

5

6

7 8

9

10 11

12

13

15

17

18

19

20

21

27

28

29

30

31

32

33 34

35

36

37

38

39

40

41 42

43

44

45

46

47

48 49

50

Each standard sign shall be displayed only for the specific purpose as prescribed in this Manual.

Determination of the particular signs to be applied to a specific condition shall be made in accordance with the provisions set forth in Part 2. Deleted, redundant and implied Before any new highway, private road open to public travel (see definition in Section 1A.13), detour, or temporary route is opened to public travel, all necessary signs shall be in place. Signs required by road conditions or restrictions shall be removed when those conditions cease to exist or the restrictions are withdrawn.

14 Section 2A.04 Excessive Use of Signs Moved to Section 2A.19

Section 2A.05 2A.03 Classification of Signs

16 **Standard:**

Signs shall be defined by their function as follows:

- A. Regulatory signs give notice of traffic laws or regulations.
- B. Warning signs give notice of a situation that might not be readily apparent.
 - C. Guide signs show route designations, destinations, directions, distances, services, points of interest, and other geographical, recreational, or cultural information.
- 22 Support:
- Barricades are defined in Section 2B.76.
- 24 Gates are defined in Section 2B.77.
- Object markers are defined in Section 2C.693.

26 Section 2A.062A.04 Design of Signs

Support:

This Manual shows many typical standard signs and object markers approved for use on streets, highways, bikeways, and pedestrian crossings.

In the specifications for individual signs and object markers, the general appearance of the legend, color, and size are shown in the accompanying tables and illustrations, and are not always detailed in the text.

Detailed drawings of standard signs, object markers, alphabets, symbols, and arrows (see Figure 2D-42) are shown in the "Standard Highway Signs-and Markings" bookpublication. Section 1A.0511 contains information regarding how to obtain this publication.

The basic requirements of a sign are that it be legible to those for whom it is intended and that it be understandable in time to permit a proper response. Desirable attributes include:

- A. High visibility by day and night; and
- B. High legibility (adequately sized letters, symbols, or arrows, and a short legend for quick comprehension by a road user approaching a sign).

Standardized colors and shapes are specified so that the several classes of traffic signs can be promptly recognized. Simplicity and uniformity in design, position, and application are important essential for a sign to be effective.

Standard:

The term legend shall include all word messages and symbol and arrow designs that are intended to convey specific meanings.

Uniformity in design shall include shape, color, dimensions, legends, <u>letter style</u>, borders, and illumination or retroreflectivity.

Standardization of these designs does not preclude further improvement by minor changes immodifications toof the proportion or orientation of symbols (see Section 2A.09), width of borders, or layout of word messages, but all shapes and colors shall be as indicated.

All symbols (see Section 2A.09) shall be unmistakably similar to, or mirror images of, the adopted symbol signs, all of which are shown in the "Standard Highway Signs and Markings" book publication (see Section 1A.0511). Symbols and colors shall not be modified unless otherwise provided in this Manual. All symbols, and colors, or other design features for signs not shown in the "Standard Highway Signs and Markings" book publication shall follow the procedures for experimentation and change described in Section 1A.10 Chapter 1B.

Option:

Although the standard design of symbol signs cannot be modified, the orientation of the symbol may be changed to better reflect the direction of travel, if appropriate. Modification of the orientation of symbols is provided in Section 2A.09

Standard:

Where a standard word message is applicable, the wording shall be as provided in this Manual.

In situations where word messages are required other than those provided in this Manual, the signs shall be of the same shape and color as standard signs of the same functional type.

Where a standard sign is a symbol legend, an alternative word legend shall not be allowed in place of the symbol, except as otherwise provided in this Manual.

Where a standard sign provided in this Manual or the "Standard Highway Signs" publication is applicable, an alternative legend sign or alternative sign design shall not be allowed in place of the standardized legend or design except as provided in this Manual.

Where a standard sign provided in this Manual or the "Standard Highway Signs" publication is applicable, but the legend is variable, such as for destination names, an alternative sign design or dimensions shall not be allowed in place of the standardized design for the non-variable elements except as provided in this Manual.

Option:

State and local highway agencies may develop special word message legend signs in situations where roadway conditions make it necessary to provide road users with additional regulatory, warning, or guidance information, such as when road users need to be notified of special regulations or warned about a situation that might not be readily apparent. Unlike colors that have not been assigned or symbols that have not been approved for signs, new word message legend signs may be used without the need for experimentation. Support:

The message conveyed by some special word legend signs might be unclear to the road user. Although experimentation is not required for such word legends, they might still warrant an evaluation to determine comprehension or possible misinterpretation of the intended message by the road user.

Standard:

Except as Unless otherwise provided in Paragraph 16 and except for the Carpool Information (D12-2) sign (see Section 2I.11)this Manual for a specific sign, and as provided in Option statement that follows, telephone numbers; Internet addresses; and e-mail addresses, including; domain names and; uniform resource locators (URL); metadata tags ("hash-tags"); quick-response (QR) codes; bar codes or other graphics for optical scanning for the purpose of obtaining information; shall not be displayed on any sign, supplemental plaque, sign panel (including logo sign panels on Specific Service signs), or changeable message sign.

Guidance:

Unless otherwise provided in this Manual for a specific sign, and except as provided in Paragraph 16, telephone numbers of more than four characters should not be displayed on any sign, supplemental plaque, sign panel (including logo sign panels on Specific Service signs), or changeable message sign.

Option:

Internet addresses, e-mail addresses, or telephone numbers, quick-response (QR) codes, bar codes or other graphics for the purpose of obtaining information (other than those for maintenance or inventory purposes, see Paragraphs 20 and 21 of this Section) with more than four characters may be displayed on the face of signs, supplemental plaques, sign panels, and changeable message signs that are intended for viewing only by pedestrians, bicyclists, occupants of parked vehicles, or drivers of vehicles on low speed roadways where engineering judgment indicates that an area is available for drivers to stop out of the traffic flow to read the message, and are oriented away from and not visible to operators of motor vehicles.

Standard:

Pictographs (see definition in Section <u>1C.02</u>1A.13) shall not be displayed on signs except as specifically provided in this Manual. Pictographs shall be simple, dignified, and devoid of any advertising <u>and not contain any quick-response (QR) codes, bar codes, or other graphics designed for optical scanning for the purpose of obtaining information. When used to represent a political jurisdiction (such as a State, county, or municipal corporation) the pictograph shall be the official designation adopted by the jurisdiction. When used to represent a college or university, the pictograph shall be the official seal adopted by the institution. Pictorial representations of university or college programs shall not be permitted to be displayed on a sign.</u>

Business Identification sign panels (see definition in Section 1A.13) shall not be displayed on signs except as specifically provided in this Manual. Business Identification sign panels, including any logo displayed thereupon, shall not contain any quick-response (QR) codes, bar codes, or other graphics designed for optical scanning for the purpose of obtaining information.

No items other than official traffic control signs, inventory stickers or decals, sign installation dates, sign sizes, sign designations, anti-vandalism stickers, and bar codes inventory or maintenance codes shall be mounted on the back of STOP or YIELD signs a sign. Moved from Section 2B.10 and edited Option:

Date of fabrication, sign designation, sign size, and manufacturer name may be displayed on the front of a sign face in accordance with the provisions of Paragraph 22 of this Section.

Standard:

If displayed on the sign face, the date of fabrication, sign designation, sign size, and manufacturer name shall be completely within the border or inset along the bottom edge of the sign. The letter height shall not exceed ¾ of the width of the border or inset or, if no border is used, shall not exceed 1¾ inches and shall be within 2 inches of the edge of the sign. The color of the lettering within the border shall be the same as the color of the sign background. The color of the lettering within the inset shall be the same as the color of the sign border. For changeable message signs or blank-out signs, such information, if displayed, shall be embossed in a non-contrasting color in the housing of the sign.

- 28 Section 2A.07 Retroreflectivity and Illumination Moved to Section 2A.20
- 29 Section 2A.08 Maintaining Minimum Retroreflectivity Moved to Section 2A.21
- **Section** 2A.092A.05 **Shapes**
- 31 Standard:

Particular shapes, as shown in Table 2A-42A-1, shall be used exclusively for specific signs or series of signs, unless otherwise provided in the text discussion in this Manual for a particular sign or class of signs.

Table 2A-1. Use of Sign Shapes

Guidance:

Where the lateral space available in which to install a diamond-shaped warning sign is constrained, such as mounting on a narrow median barrier or adjacent to a retaining wall, the following methods should be considered to maintain the diamond-shaped sign:

- A. Angle the sign toward the roadway while still maintaining adequate legibility.
- B. Install the sign at a different location that still provides adequate advance warning, supplementing the sign with a Distance plaque (see Section 2C.61), if appropriate.
- C. Reduce the size of the sign at the advance warning location, but supplement it with a duplicate sign on the opposite side of the roadway (see Section 2A.11).
- D. In addition to either angling or reducing the size of the sign at the advance warning location, supplement with a duplicate warning sign and Distance plaque at an upstream location.
- E. Mount the sign asymmetrically on the sign support, such as when the support is mounted on a bridge parapet or railing, such that the edge of the sign does not overhang the roadway.
- F. Increase the mounting height of the sign to above the statutory maximum vehicle height for the tallest vehicle allowed on that roadway.

Option:

Where the methods described in Paragraph 2 of this Section are impracticable, the legend of the warning sign may be displayed in a vertically oriented rectangle.

Standard:

Other modifications to sign shapes, such as cutting off the left and right points of a diamond, shall not be allowed.

Section 2A.102A.06 Sign-Colors

Standard:

The colors to be used on standard signs and their specific use on these signs shall be as provided in the applicable Sections of this Manual. The color coordinates and values shall be as described in 23 CFR, Part 655, Subpart F, Appendix.

Support:

As a quick reference, cCommon uses of sign colors are shown in Table 2A-52A-2. Color schemes on specific signs are shown in the illustrations located in each appropriate applicable Chapter.

Whenever white is specified in this Manual or in the "Standard Highway Signs and Markings" book publication (see Section 1A.0511) as a color, it is understood to include silver-colored retroreflective coatings or elements that reflect white light.

The colors coral and light blue are being reserved for uses that will be determined in the future by the Federal Highway Administration.

Information regarding color coding of destinations on guide signs, including community wayfinding signs, is contained in Chapter 2D.

Option:

The approved fluorescent version of the standard red, yellow, green, or orange color may be used as an alternative to the corresponding standard color.

Table 2A-2. Common Uses of Sign Colors

Section 2A.112A.07 Dimensions

Support:

The "Standard Highway Signs-and Markings" book publication (see Section 1A.0511) prescribes design details for up to five different sizes of each sign or plaque depending on the type of traffic facility, including bikeways. Smaller sizes are designed to be used on bikeways and some other off-road applications. Larger sizes are designed for use on freeways and expressways, and can also be used in oversized applications to enhance road user safety and convenience on other facilities, especially on multi-lane divided highways and on undivided highways having five or more lanes of traffic and/or high speeds. The intermediate sizes are designed to be used on other highway types. Minimum sizes of signs and plaques for specific applications are prescribed in the various sign size tables in each Chapter of this Manual.

Standard:

The sign dimensions prescribed in the sign size tables in the various Parts and Chapters in this Manual and in the "Standard Highway Signs and Markings" book publication (see Section 1A.0511) shall be used unless engineering judgment determines that other sizes are appropriate in accordance with the following. Except as provided in Paragraph 3 of this Section, where engineering judgment determines that sizes smaller than the prescribed dimensions are appropriate for use, the sign dimensions shall not be less than the minimum dimensions specified in this Manual. The sizes shown in the Minimum columns that are smaller than the sizes shown in the Conventional Road columns in the various sign size tables in this Manual shall only be used on low-speed roadways, alleys, and private roadssite roadways open to public travel, and on low-volume rural roads with operating speeds of 30 mph or less; and only where the reduced legend size would be adequate for the regulation or warning or where physical conditions preclude the use of larger sizes.

Option:

For alleys with restrictive physical conditions and vehicle <u>usage use</u> that limits installation of the Minimum size sign (or the Conventional Road size sign if no Minimum size is shown), both the sign height and the sign width may be decreased by up to 6 inches.

Guidance:

The sizes shown in the Freeway and Expressway columns in the various sign size tables in this Manual should <u>also</u> be used <u>on freeways and expressways</u>, <u>and</u> for other higher-speed applications <u>on conventional roads</u> based upon engineering judgment, to provide larger signs for increased visibility and recognition.

The sizes shown in the Oversized columns in the various sign size tables in this Manual size should be used for those special applications where speed, volume, or other factors result in conditions where increased emphasis, improved recognition, or increased legibility is needed, as determined by engineering judgment or study.

Except as provided in first paragraph of Standard that followsParagraph 7 of this Section, and where specifically prohibited in this Manual, Increases above the minimum prescribed sizes should be used where greater legibility or emphasis is needed. If signs larger than the prescribed sizes are used, the overall sign dimensions should be increased in 6-inch increments.

Standard:

Where a maximum allowable sign size is prescribed, increases in sign size shall not be allowed.

Where engineering judgment determines that sizes that are different than from the minimum prescribed dimensions are appropriate for use, standard shapes and colors shall be used. and standard proportions shall be retained as much as practical practicable.

Guidance:

Except where specifically prohibited in this Manual, When supplemental plaques are installed with larger sized signs, a corresponding increase in the size of the plaque and its legend should also be made. The resulting plaque size should be approximately in the same relative proportion to the larger sized sign as the conventional sized plaque is to the conventional sized sign.

Section 2A.132A.08 Word Messages

Standard:

Except as provided otherwise in this Manual, all word messages shall be aligned horizontally across a sign, reading left to right.

Except as provided in Section 2A<u>.04</u>, all word messages shall use standard wording and letters as shown in this Manual and in the "Standard Highway Signs and Markings" book publication (see Section 1A.0511).

All sign lettering, <u>numerals</u>, <u>and other characters</u> shall be <u>in upper-case letters of the Standard Alphabets</u> as provided in the "Standard Highway Signs and Markings" <u>bookpublication</u> (see Section 1A.11), unless <u>provided</u> otherwise <u>provided</u> in this Manual <u>for a particular sign or type of message</u>.

The sign lettering for names of places, streets, and highways shall be composed of a combination of lower-case letters with initial upper-case letters. The sign lettering for other legends shall be composed of upper-case letters, unless otherwise provided in this Manual for a particular sign or type of message.

Except as provided in Chapter 2E of this Manual, Wwhen a mixed-case legend is used, the nominal loop height of the lower-case letters shall be 3/4 of the height of the initial upper-case letter.

The unique letter forms for each of the Standard Alphabet series shall not be stretched, compressed, warped, or otherwise manipulated. Moved from later in this section and edited

Support:

Section 2D.07 contains information regarding the acceptable methods of modifying the length of a word for a given letter height and series.

Guidance:

Word messages should be as brief as possible practical to convey a clear, simple meaning, and the lettering should be large enough to provide the necessary legibility distance. A minimum specific ratio of 1 inch of letter height per 30 feet of legibility distance should be used.

Abbreviations (see Section <u>1A.15</u><u>1D.10</u>) should be kept to a minimum, <u>except as otherwise prescribed in</u> this Manual.

Word messages should not contain periods, apostrophes, question marks, ampersands, or other punctuation or characters that are not letters, numerals, or hyphens unless necessary to avoid confusion.

50 Support:

<u>Diacritical marks on words or names that are adapted to English are not normally needed on signs for comprehension or navigational purposes.</u>

Guidance:

The solidus (slanted line or forward slash) is intended to be used for fractions only and should not be used to separate words on the same line of legend. Instead, a hyphen should be used for this purpose, such as "TRUCKS - BUSES."

Standard:

Fractions shall be displayed with the numerator and denominator diagonally arranged about the solidus (slanted line or forward slash). The overall height of the fraction is measured from the top of the numerator to the bottom of the denominator, each of which is vertically aligned with the upper and lower ends of the solidus. The overall height of the fraction shall be determined by the height of the numerals within the fraction, and shall be 1.5 times the height of an individual numeral within the fraction.

Except as otherwise provided in this Manual, distances shall be displayed on signs using fractions of a mile rather than decimals.

Support:

The "Standard Highway Signs—and Markings" book publication (see Section 1A.0511) contains details regarding the layouts of fractions on signs.

Guidance:

When initials are used to represent an abbreviation for separate words (such as "US" for a United States route), the initials should be separated by a space of between 1/2 and 3/4 of the letter height of the initials.

When an Interstate route is displayed in text form instead of using the route shield, a hyphen should be used for clarity, such as "I-50."

Standard:

All sign lettering shall be in upper-case letters as provided in the "Standard Highway Signs and Markings" book (see Section 1A.11), unless otherwise provided in this Manual for a particular sign or type of message.

The sign lettering for names of places, streets, and highways shall be composed of a combination of lower-case letters with initial upper-case letters. Moved earlier in this section

Support:

Letter height is expressed in terms of the height of an upper-case letter. For mixed-case legends (those composed of an initial upper-case letter followed by lower-case letters), the height of the lower-case letters is derived from the specified height of the initial upper-case letter based on a prescribed ratio. Letter heights for mixed-case legends might be expressed in terms of both the upper- and lower-case letters, or in terms of the initial upper-case letter alone. When the height of a lower-case letter is specified or determined from the prescribed ratio, the reference is to the nominal loop height of the letter. The term loop height refers to the portion of a lower-case letter that excludes any ascending or descending stems or tails of the letter, such as with the letters "d" or "q." The nominal loop height is equal to the actual height of a non-rounded lower-case letter whose form does not include ascending or descending stems or tails, such as the letter "x." The rounded portions of a lower-case letter extend slightly above and below the baselines projected from the top and bottom of such a non-rounded letter so that the appearance of a uniform letter height within a word is achieved. The actual loop height of a rounded lower-case letter is slightly greater than the nominal loop height and this additional height is excluded from the expression of the lower-case letter height.

Standard:

When a mixed-case legend is used, the height of the lower-case letters shall be 3/4 of the height of the initial upper-case letter.

The unique letter forms for each of the Standard Alphabet series shall not be stretched, compressed, warped, or otherwise manipulated.

Support:

Section 2D.04 contains information regarding the acceptable methods of modifying the length of a word for a given letter height and series. Moved earlier in this section

Section 2A.122A.09 Symbols

51 Standard:

Symbol designs shall in all cases be unmistakably similar to those shown in this Manual and in the "Standard Highway Signs and Markings" book publication (see Section 1A.0511).

Support:

New symbol designs are adopted by the Federal Highway Administration based on research evaluations to determine road user comprehension, sign conspicuity, and sign legibility.

Sometimes a change from word messages to symbols requires significant time for public education and transition. Therefore, this Manual sometimes includes the practice of using educational plaques to accompany new symbol signs.

Guidance:

New <u>standardized</u> warning or regulatory symbol signs not readily recognizable by the public should be accompanied by an educational plaque <u>where engineering judgment determines that the plaque will improve</u> road user comprehension during the transition from word message to symbol signs.

Option:

Educational plaques may be left in place as long as they are in serviceable condition.

State and/or local highway agencies may conduct research studies to determine road user comprehension, sign conspicuity, and sign legibility in compliance with the provisions for official experimentation when a new symbol design is under consideration (see Section 1A.10).

Guidance:

Although most standard symbols are oriented facing left, mirror images of these symbols should may be used where the reverse orientation might better convey to road users a direction of movement. Changed from Guidance to Option

Standard:

A symbol used for a given category of signs (regulatory, warning, or guide) shall not be used for a different category of signs, except as specifically authorized in this Manual.

Except as provided in Paragraph 11, a A recreational and cultural interest area symbol (see Chapter 2M) shall not be used on streets or highways outside of recreational and cultural interest areas.

A recreational and cultural interest area guide sign symbol (see Chapter 2M) shall not be used on any regulatory or warning sign on any street, road, or highway.

Option:

A recreational and cultural interest area guide sign symbol (see Section 2M.04) may be used on a highway guide sign outside of a recreational and cultural interest area to supplement a comparable word message for which there is no approved symbol for that message in Chapters 2B through 2I or 2N.

33 Support:

Section 2M.07 contains provisions for the use of recreational and cultural interest area symbols to indicate prohibited activities or items in non-road applications.

Section 2A.13 Word Messages Moved to Section 2A.08

Section 2A.142A.10 Sign Borders

Standard:

Unless otherwise provided, each sign illustrated in this Manual signs shall have a border of the same color as the legend in order to outline their distinctive shape and thereby give them easy recognition and a finished appearance, at or just inside the edge.

The corners of all sign borders shall be rounded, except for STOP signs.

43 Guidance:

A dark border on a light background should be set in from the edge, while a light border on a dark background should extend to the edge of the sign. A border for 30-inch signs with a light background should be from 1/2 to 3/4 inch in width, 1/2 inch from the edge. For similar signs with a light border, a width of 1 inch should be used. For other sizes, the border width should be of similar proportions, but should not exceed the stroke-width of the major lettering of the sign. On signs exceeding 72 x 120 inches in size, the border should be 2 inches wide. On unusually large signs with oversized letter heights, route shields, or other legend elements, the border should be 2-½ inches wide and should not exceed, or on larger signs, 3 inches

Support:

See Section 2A.20 regarding the use of light-emitting diode (LED) units within the border of a sign.

Section 2A.152A.11 Enhanced Conspicuity for Standard Signs

Option:

Based upon engineering judgment, where the improvement of the conspicuity of a standard regulatory, warning, or guide sign is desired, any of the following methods may be used, as appropriate, to enhance the sign's conspicuity (see Figure 2A-1):

- A. Increasing the size of a standard regulatory, warning, or guide sign.
- B. Doubling up Dual signing of a standard regulatory, warning, or guide sign by adding a second identical sign on the left-hand side of the roadway at the same location.
- C. Adding a solid yellow or fluorescent yellow rectangular "header panel" above a standard regulatory sign, with the width of the panel corresponding to the width of the standard regulatory sign. A legend of "NOTICE," "STATE LAW," or other appropriate text may be added in black letters within the header panel for a period of time determined by engineering judgment.
- D. Adding a NEW plaque (see Section 2C.602) above a new standard regulatory or warning sign, for a period of time determined by engineering judgment, but not to exceed six months, to call attention to the new sign.
- E. Adding one or more red or orange flags (cloth or retroreflective sheeting) above a standard regulatory or warning sign, with the flags oriented so as to be at 45 degrees to the vertical.
- F. Adding a solid yellow, a solid fluorescent yellow, or a diagonally striped black and yellow (or black and fluorescent yellow) strip of retroreflective sheeting at least 3 inches wide around the perimeter of a standard warning sign. This may be accomplished by affixing the standard warning sign on a background that is 6 inches larger than the size of the standard warning sign.
- G. Adding a warning beacon (see Section 4L.034S.03) to a standard regulatory (other than a STOP, DO NOT ENTER, WRONG WAY, or a Speed Limit sign), warning, or guide sign.
- H. Adding a speed limit sign beacon (see Section 4L.044S.04) to a standard Speed Limit sign.
- I. Adding a stop beacon (see Section 4L.054S.05) to a STOP sign.
- J. Adding a rectangular rapid-flashing beacon (see Chapter 4L) to a Pedestrian or School warning sign at an uncontrolled, midblock crosswalk.
- JK. Adding light-light-emitting diode (LED) units within the symbol-or, legend, or border of a sign or border of a standard regulatory, warning, or guide sign, as provided in Section 2A.2007.
- <u>KL</u>. Adding a strip of retroreflective material to the sign support in <u>compliance accordance</u> with the provisions of <u>Section 2A.21 pParagraph 4 of this Section</u>.
- LM. Using other methods that are specifically allowed for certain signs as described elsewhere in this Manual.

Support:

Sign conspicuity improvements can also be achieved by removing non-essential and illegal signs from the right-of-way (see Section <u>1D.04</u><u>1A.08</u>), and by relocating signs to provide better spacing. <u>Section 2A.19</u> contains information on excessive use of signs.

Standard:

The NEW plaque (see Section 2C.62) shall not be used alone. Deleted; plaques by definition may not be used alone

Strobe lights shall not be used to enhance the conspicuity of highway signs.

If a strip of retroreflective material is used on the sign support, it shall be at least 2 inches in width, it shall be placed for the full length of the support from the sign to within 2 feet above the edge of the roadway, and its color shall match the background color of the sign, except that the color of the strip for the YIELD and DO NOT ENTER signs shall be red. The retroreflective strip shall not display any legend or other information. Relocated from existing Section 2A.21

For a post-mounted sign installation, placing a duplicate sign in the same assembly facing the same direction of traffic shall not be considered an acceptable method of enhancing conspicuity.

Section 2A.162A.12 Standardization of Location

Support:

Standardization of position cannot always be attained in practice. Examples of heights and lateral locations of signs for typical installations are illustrated in Figure 2A-2, and examples of locations for some typical signs at intersections are illustrated in Figures 2A-3—and, 2A-4—and 2-5A and B.

Examples of advance signing on an-intersection approaches are illustrated in Figures 2A-4 and 2A-5A and B. Chapters 2B, 2C, and 2D contain provisions regarding the application of regulatory, warning, and guide signs, respectively.

Standard:

Signs requiring separate decisions by the road user shall be spaced sufficiently far apart for the appropriate decisions to be made. One of the factors considered when determining the appropriate spacing shall be the posted or 85th-percentile speed. Changed to Guidance below *Guidance*:

of the factors considered when determining the appropriate spacing of signs should be the posted or 85th Changed from Standard above

<u>Except as provided in Paragraph 8 of this Section, Signs signs</u> should be located on the right-hand side of the roadway where they are easily recognized and understood by road users. Signs in other locations should be considered only as supplementary to signs in the normal locations, except as otherwise provided in this Manual.

Signs should be individually installed on separate posts or mountings except where:

- A. One sign supplements another;
- B. Route or directional signs are grouped to clarify information to motorists;
- C. Regulatory signs that do not conflict with each other are grouped, such as Turn Prohibition signs posted with ONE WAY signs or a parking regulation sign posted with a Speed Limit sign; or
- D. Street Name signs are posted with a STOP or YIELD sign.

Signs should be located so that they:

- A. Are outside the clear zone unless placed on a breakaway or yieldingcrashworthy support (see Section 2A.1519),
- B. Optimize nighttime visibility,
- C. Minimize the effects of mud splatter and debris,
- D. Do not obscure each other,
 - E. Do not obscure the sight distance to approaching vehicles on the major street for drivers who are stopped on minor-street approaches, and
 - F. Are not hidden from view.

Except for Stop, Yield, Do Not Enter, and Wrong Way signs, or as otherwise provided in this Manual, where a sign indicates an action by a road user in the left lane or at the left-hand side of a one-way road, such as Lane Ends Merge Right, the sign should be located on the left-hand side of the roadway. In the case of a divided road, the sign should be located in median if adequate width is available.

Support:

Signs located on the left-hand side of a one-way road or in the median of a divided road, in accordance with the Guidance above, may be supplemented by an identical sign located on the right-hand side of the road.

The clear zone is the total roadside border area, starting at the edge of the traveled way, available for use by errant vehicles. The width of the clear zone is dependent upon traffic volumes, speeds, and roadside geometry. Additional information can be found in AASHTO's "Roadside Design Guide" (see Section 1A.0511).

Guidance:

With the increase in traffic volumes and the <u>desire need</u> to provide road users regulatory, warning, and guidance information, an order of priority for sign installation should be established.

Support:

An order of priority is especially critical where space is limited for sign installation and there is a demand for several different types of signs. Overloading road users with too much information is not desirable._

Primacy according type of sign will depend on the specific situation and conditions of the site at which the

signs are to be installed. For example, in the vicinity of an exit ramp, guide signs and warning signs for the

exit ramp might take precedence over regulatory signs that confirm rules of the road, such as for passing or for the mainline speed limit where there is no change in the speed zone.

Guidance:

1

2

3

4

5

6

7

8

9

10

11

12 13

14

15

16

17

18

19

20

21 22

23

25

26

27

28

29

30

31

32

33

34

35

36

37 38

40

41

42

43

44

Because regulatory and warning information is <u>typically</u> more critical to the road user than guidance information, regulatory and warning signing whose locations <u>is are</u> critical should be displayed rather than guide signing in cases where conflicts occur. <u>In such cases, the guide sign should be relocated to another appropriate location where it will still be effective. In other cases, such as at a decision point, the guide sign should take precedence over other signs whose locations are not as critical to an immediate decision or action necessary by the road user. In all cases, careful attention should be given to minimizing sign clutter.

Community wayfinding and acknowledgment guide signs should have a lower priority as to placement than other guide signs. Information of a less critical nature should be moved to less critical locations or omitted.</u>

Option:

Under some circumstances, such as on curves to the right, signs may be placed on median islands or on the left-hand side of the road. A supplementary sign located on the left-hand side of the roadway may be used on a multi-lane road where traffic in a lane to the right might obstruct the view to the right.

Guidance:

In urban areas where crosswalks exist, signs should not be placed within 4 feet in advance of the crosswalk (see Drawing D in Figure 2A-3).

Figure 2A-2. Examples of Heights and Lateral Locations of Sign Installations

Figure 2A-3. Examples of Locations for Some Typical Signs at Intersections

Figure 2A-4. Relative Locations of Regulatory, Warning, and Guide Signs on an Intersection
Approach

Section 2A.172A.13 Overhead Sign Installations

24 Guidance:

Overhead signs should be used on freeways and expressways, at locations where some degree of lane-use control is desirable, and at locations where space is not available at the roadside.

Support:

The operational requirements of the present highway system are such that overhead signs have value at many locations. The factors to be considered for the installation of overhead sign displays are not definable in specific numerical terms. In some cases, overhead mounting of a sign might be required by other provisions of this Manual.

Option:

The following conditions (not in priority order) may be considered in an engineering study to determine if overhead signs would be beneficial:

- A. Traffic volume at or near capacity,
- B. Complex interchange design,
- C. Three or more lanes in each direction,
 - D. Restricted sight distance,
- 39 E. Closely-spaced interchanges,
 - F. Multi-lane exits,
 - G. Large percentage of trucks,
 - H. Street lighting background,
 - I. High-speed traffic,
 - J. Consistency of sign message location through a series of interchanges,
- 45 K. Insufficient space for post-mounted signs,
- 46 L. Junction of two freeways, and
- 47 M. Left-side exit ramps.
- 48 Over-crossing structures may be used to support overhead signs.
- 49 Support:

Under some circumstances, the use of over-crossing structures as sign supports might be the only practical solution that will provide adequate viewing distance. The use of such structures as sign supports might eliminate the need for the foundations and sign supports along the roadside.

Section 2A.182A.14 Mounting Height

Standard:

The provisions of this Section shall apply unless specifically stated otherwise for a particular sign or object marker elsewhere in this Manual.

The minimum mounting heights prescribed in this Section or as provided otherwise in this Manual shall not supersede those necessary for crash performance of sign installations that are required to be crashworthy (see Paragraph 2 of Section 2A.15).

Support:

The mounting height requirements for object markers are provided in Chapter 2C.

In addition to the provisions of this Section, information affecting the minimum mounting height of signs as a function of crash performance can be found in AASHTO's "Roadside Design Guide" (see Section 1A.0511).

Standard:

The minimum height, measured vertically from the bottom of the sign to the elevation of the near edge of the pavement, of signs installed at the side of the road in rural areas shall be 5 feet (see Figure 2A-2).

The minimum height, measured vertically from the bottom of the sign to the top of the curb, or in the absence of curb, measured vertically from the bottom of the sign to the elevation of the near edge of the traveled way, of signs installed at the side of the road in business, commercial, or residential areas where parking or pedestrian movements are likely to occur, or where the view of the sign might be obstructed, shall be 7 feet (see Figure 2A-2).

Option:

The height to the bottom of a secondary sign mounted below another sign may be 1 foot less than the height specified in Paragraphs 4 and 5 of this Section.

Standard:

The minimum height, measured vertically from the bottom of the sign to the sidewalk, of signs installed above sidewalks shall be 7 feet.

If the bottom of a secondary sign that is mounted below another sign is mounted lower than 7 feet above a pedestrian sidewalk or pathway (see Section 6D.026C.03), the secondary sign shall not project more than 4 inches into the pedestrian facility.

Option:

Except as required in Paragraph 10 of this Section, Ssigns that are placed 30 feet or more from the edge of the traveled way may be installed with a minimum height of 5 feet, measured vertically from the bottom of the sign to the elevation of the near edge of the pavement.

Standard:

Directional signs on freeways and expressways shall be installed with a minimum height of 7 feet, measured vertically from the bottom of the sign to the elevation of the near edge of the pavement. All route signs, warning signs, and regulatory signs on freeways and expressways shall be installed with a minimum height of 7 feet, measured vertically from the bottom of the sign to the elevation of the near edge of the pavement. If a secondary sign is mounted below another sign on a freeway or expressway, the major sign shall be installed with a minimum height of 8 feet and the secondary sign shall be installed with a minimum height of 5 feet, measured vertically from the bottom of the sign to the elevation of the near edge of the pavement.

Where large signs having an area exceeding 50 square feet are installed on multiple breakaway posts, the clearance from the ground to the bottom of the sign shall be at least 7 feet.

Option:

A route sign assembly consisting of a route sign and auxiliary signs (see Section 2D.31) may be treated as a single sign for the purposes of this Section.

The mounting height may be adjusted when supports are located near the edge of the right-of-way on a steep backslope in order to avoid the sometimes less desirable alternative of placing the sign closer to the roadway.

Standard:

Overhead signs shall provide a vertical clearance of not less than 17 feet to the sign, light fixture, or sign bridge over the entire width of the pavement and shoulders except where the structure on which the overhead signs are to be mounted or other structures along the roadway near the sign structure have a lesser vertical clearance.

Option:

If the vertical clearance of other structures along the roadway near the sign structure is less than 16 feet, the vertical clearance to an overhead sign structure or support may be as low as 1 foot higher than the vertical clearance of the other structures in order to improve the visibility of the overhead signs.

In special cases it may be necessary to reduce the clearance to overhead signs may be reduced if necessary because of substandard dimensions in tunnels and other major structures such as double-deck bridges.

Reworded to be consistent with Option language

Guidance:

While a maximum mounting height for signs is generally not prescribed in this Manual, agencies should ensure that signs are not mounted at such a height as to be out of the road user's normal field of vision (see Paragraph 2 of Section 1D.11), especially in urban settings where signs are mounted on traffic signal or light poles.

21 Support:

Figure 2A-2 illustrates some examples of the mounting height requirements contained in this Section.

Section 2A.192A.15 Lateral Offset

Standard:

For overhead sign supports, the minimum lateral offset from the edge of the shoulder (or if no shoulder exists, from the edge of the pavement) to the near edge of overhead sign supports (cantilever or sign bridges) shall be 6 feet. Overhead sign supports shall have a barrier or crash cushion to shield them if they are within the clear zone.

Post-mounted sign and object marker supports shall be crashworthy (breakaway, yielding, or shielded with a longitudinal barrier or crash cushion) if within the clear zone.

Support:

Information on the FHWA's policy on crashworthiness of devices on the National Highway System and other roadways is available at the FHWA Office of Departure Web site at https://safety.fhwa.dot.gov/roadway_dept/countermeasures/reduce_crash_severity/policy_memo_guidance.cfm.

Guidance:

For post-mounted signs, the minimum lateral offset should be 12 feet from the edge of the traveled way. If a shoulder wider than 6 feet exists, the minimum lateral offset for post-mounted signs should be 6 feet from the edge of the shoulder.

Support:

The minimum lateral offset requirements for object markers are provided in Chapter 2C.

The minimum lateral offset is intended to keep trucks and cars that use the shoulders from striking the signs or supports. The minimum lateral offset requirements do not supersede the requirement for crashworthiness (see Paragraph 2 of this Section) if the sign is located within the clear zone. Added to further clarify the intent of minimum lateral offsets

Guidance:

All supports should be located as far as practical from the edge of the shoulder. Advantage should be taken to place signs behind existing roadside barriers, on over-crossing structures, or other locations that minimize the exposure of the traffic to sign supports.

Option:

Where permitted, signs may be placed on existing supports used for other purposes, such as highway traffic signal supports, highway lighting supports, and utility poles. Moved to Section 2A.17

Standard:

1

2

3

4

5

6

7

8

9

10

11

13

14

16

17

18

19

20

21

22

23

24

25

27

28

31

323334

35

36

37

38

39

40

43

45

46

48

49

If signs are placed on existing supports, they shall meet other placement criteria contained in this-Manual. Deleted, repetitive and not necessary

Option:

Lesser lateral offsets may be used on connecting roadways or ramps at interchanges, but not less than 6 feet from the edge of the traveled way.

On conventional, <u>low-volume rural</u>, <u>and special-purpose</u> roads in areas where it is impractical to locate a sign with the lateral offset prescribed by this Section <u>because of roadside features such as terrain or vegetation</u>, a lateral offset of at least 2 feet may be used.

A lateral offset of at least 1 foot from the face of the curb may be used in business, commercial or residential areas where sidewalk width is limited or where existing poles are close to the curb.

12 Guidance:

Overhead sign supports and post-mounted sign and object marker supports should not intrude into the usable width of a sidewalk or other pedestrian facility.

15 Support:

Figures 2A-2 and 2A-3 illustrate some examples of the lateral offset requirements contained in this Section.

Section 2A.202A.16 Orientation

Guidance:

Unless otherwise provided in this Manual, signs should be vertically mounted at right angles to the direction of, and facing, the traffic that they are intended to serve.

Where mirror reflection from the sign face is encountered to such a degree as to reduce legibility, the sign should be turned slightly away from the road. Signs that are placed 30 feet or more from the pavement edge should be turned toward the road. On curved alignments, the angle of placement should be determined by the direction of approaching traffic rather than by the roadway edge at the point where the sign is located.

26 Option:

On grades, sign faces may be tilted forward or back from the vertical position to improve the viewing angle.

29 Section 2A.212A.17 Posts and Mountings

30 Standard:

Sign posts, foundations, and mountings shall be so constructed as to hold signs in a proper and permanent position, and to resist swaying in the wind or displacement by vandalism.

Support:

The latest edition of AASHTO's "Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals" contains additional information regarding posts and mounting (see Page i for AASHTO's address).

Option:

Where permitted, signs may be placed on existing supports used for other purposes, such as highway traffic signal supports, highway lighting supports, and utility poles. Relocated from existing Section 2A.19

41 <u>Support:</u> 42 See 5

See Section 2A.11 for criteria for enhanced conspicuity of standard signs.

See Section 2A.15 for lateral and height placement criteria for signs placed on existing supports.

44 Option:

Where engineering judgment indicates a need to draw attention to the sign during nighttime conditions, a strip of retroreflective material may be used on regulatory and warning sign supports.

47 Standard:

If a strip of retroreflective material is used on the sign support, it shall be at least 2 inches in width, it shall be placed for the full length of the support from the sign to within 2 feet above the edge of the

roadway, and its color shall match the background color of the sign, except that the color of the stripfor the YIELD and DO NOT ENTER signs shall be red. Relocated to new Section 2A.11

Standard:

If mounted to the sign support, equipment for powering electronic components of a sign, including solar panels, shall be mounted so as not to compromise the crashworthy performance of the sign installation (see Section 2A.15). Such equipment shall be mounted either below or behind the sign so as not to detract from or obscure the face of the sign, either directly or by casting shadows onto the sign, and so as not to obscure the shape of the sign.

Section 2A.222A.18 Maintenance

Guidance:

Maintenance activities should consider proper position, cleanliness, legibility, and daytime and nighttime visibility (see Section 2A.0821). Damaged or deteriorated signs, gates, or object markers should be replaced.

To assure adequate maintenance, a schedule for inspecting (both day and night), cleaning, and replacing signs, gates, and object markers should be established. Employees of highway, law enforcement, and other public agencies whose duties require that they travel on the roadways should be encouraged to report any damaged, deteriorated, or obscured signs, gates, or object markers at the first opportunity.

Steps should be taken to see that weeds, trees, shrubbery, and construction, maintenance, and utility materials and equipment do not obscure the face of any sign or object marker.

A regular schedule of replacement of lighting elements for illuminated signs should be maintained.

Section 2A.04 2A.19 Excessive Use of Signs

Guidance:

Signs should be used and located judiciously, minimizing their proliferation in order to maintain their effectiveness. Regulatory and warning signs should be used conservatively because these signs, if used to excess, tend to lose their effectiveness. If used, rRoute signs and directional guide signs for primary routes and destinations should be used frequently at strategic locations because their use promotes efficient operations by keeping road users informed of their location. In all cases, however, sign clutter (see Paragraph 2 of this Section) should be avoided and minimized as much as practicable.

Sign clutter is the proliferation of sign installations or assemblies along the roadway or roadside, either separately or grouped, to such an extent that adequate spacing between installations necessary for orderly processing of the sign messages by the driver cannot be achieved. Sign clutter can reduce the effectiveness of one or more signs in a sequence of signs.

Vanity signs display information that is of little value or interest to the majority or significant number of road users. Vanity signs often take the form of General Information signs, but provide no navigational guidance or orientation to the road user. Vanity signs are usually of importance only to the entity requesting the sign. Vanity signs can result in sign clutter and undermine the basic role of official traffic control devices in providing only as much information to the road user as necessary to promote the safe and efficient operation of streets and highways.

Guidance:

Signs and other traffic control devices should be installed and maintained from a systematic standpoint rather than individually. When a new sign is installed, the existing signs in the vicinity should be considered for replacement, relocation, or removal as a result of the new sign that is installed. Existing systems of signs should be reviewed periodically for evidence of sign clutter and adjustments should be made accordingly.

Section 2A.072A.20 Retroreflectivity Retroreflection and Illumination

Support:

There are many materials currently available for retroreflection and various methods currently available for the illumination of signs and object markers. New materials and methods continue to emerge. New materials and methods can be used as long as the signs and object markers meet the standard requirements for color, both by day and by night.

<u>Paragraphs 3 through 7 of this Section regarding illumination apply to nighttime visibility of signs whose</u> legends are otherwise visible under daytime viewing conditions without illumination. Paragraphs 8 through

20 of this Section regarding illumination apply to the use of illuminated elements that supplement a sign legend to enhance conspicuity of the sign. Changeable message or blank-out signs whose legends change or extinguish by means of illuminated elements are addressed elsewhere in this Manual.

Standard:

Regulatory, warning, and guide signs, and object markers, shall be retroreflective (see Section 2A.08) or illuminated to show the same shape and similar color by both day and night, unless otherwise provided in the text discussion in this Manual for a particular sign or group of signs.

Where the color black is specified for the legend or background of a sign, an opaque or non-retroreflective material shall be used.

The requirements for sign illumination shall not be considered to be satisfied by street or highway lighting.

Option:

Sign elements may be illuminated by the means shown in Table $\frac{2A-1}{2A-3}$.

Retroreflection of sign elements may be accomplished by the means shown in Table 2A-22A-4.

Light-Emitting <u>emitting Diode diode</u> (LED) units may be used individually within the <u>border</u>, <u>or</u> legend <u>or symbol</u> of a sign <u>to enhance the sign conspicuity and legibility</u> (see Section 2A.11) and in the border of a sign, except for changeable message signs, to improve the conspicuity, increase the legibility of sign legends and borders, or provide a changeable message.

Except as provided in Paragraph 17 of this Section, LED units may either operate continuously or be actuated.

Support:

The application of LED units in compliance with Paragraph 14 of this Section does not create a changeable message sign because the legend of the sign is always displayed when the LED units are not illuminated.

LED units that are used to illuminate the full sign display, background, and legend, are changeable message signs (CMS), which are covered in Chapters 2B, 2C, and 2L, and Part 7.

Standard:

Where LED units are used to enhance conspicuity of a sign (see Paragraph 8 of this Section), the sign shall otherwise comply with the requirements for retroreflection and illumination for nighttime viewing.

Except as provided in Paragraphs <u>1120</u> and <u>1221 of this Section</u>, <u>and for changeable message signs</u>, neither individual LEDs nor groups of LEDs shall be placed within the background area of a sign.

The application of LEDs to display sign legends or symbols shall use a maximum pitch of 20 mm to cover the stroke width of the letter or symbol.

If used, the LEDs shall have a maximum diameter of 1/4 inch and shall be the following colors based on the type of sign:

- A. White or red, if used with STOP or YIELD with STOP, YIELD, DO NOT ENTER, or WRONG WAY signs.
- B. White, if used with other regulatory signs other than STOP or YIELD signs.
- C. White or yellow, if used with warning signs.
- D. White or green, if used with guide signs.
- E. White, yellow, or orange, if used with temporary traffic control signs.
- F. White or yellow, if used with school area or pedestrian or bicycle warning signs.

If flashed, all LED units shall flash simultaneously at <u>any steady rate between 50 and 60 times per minute</u>. All the LED units in a sign legend or border shall be illuminated <u>simultaneously with no sequential (chasing) or variable flash rates</u>. A cluster of LEDs shall not be used within the border of a sign.

Where used in STOP or YIELD signs, flashing LED units shall operate continuously. Actuation of the LED units shall not be allowed.

Where LED units are used along the edge of a sign, at least one LED unit shall be placed along each edge of the sign, in addition to one LED unit at each corner of the sign, so that the distinct outline of the sign shape is recognized under nighttime viewing conditions. The LED units along each side of the sign

1 shall be spaced approximately equidistantly. For a circular sign shape, the number of LED units shall 2 clearly form the appearance of a circle and not be perceived as some other shape. 3 The uniformity of the sign design shall be maintained without any decrease in visibility, legibility, or driver comprehension during either daytime or nighttime conditions. The LED units shall have the 4 5 capability to be dimmed automatically by a timing mechanism or a device sensitive to ambient light (photoelectric cell) such that the LEDs do not reduce the visibility of the sign legend. 6 7 Option: 8 For STOP-and, YIELD, DO NOT ENTER, and WRONG WAY signs, LEDs may be placed within the 9 border or within one border width within the background of the sign. 10 For STOP/SLOW paddles (see Section 6E.03) used by flaggers and the STOP paddles (see Section-11 7D.05) used by adult crossing guards, individual LEDs or groups of LEDs may be used. Revised and

changed to Support below

Support:

13

14

1516

17

18

19

20

21

23

24

25

26

27

28 29

30

31

32

33

34

35

36

37

38 39

40

41 42

43

44

45 46

47

48 49

50

For STOP/SLOW paddles used by flaggers, see Section 6D.02. For STOP paddles used by adult crossing guards, see Section 7D.02. Revised and changed from Option above

Other methods of enhancing the conspicuity of standard signs are described in Section 2A.1115.

Information regarding the use of retroreflective material on the sign support is contained in Section 2A.2111.

Table 2A-3. Illumination of Sign Elements

Table 2A-4. Retroreflection of Sign Elements

Section 2A.082A.21 Maintaining Minimum Retroreflectivity

22 Support

Retroreflectivity is one of several factors associated with maintaining nighttime sign visibility (see Section 2A.22).

Standard:

Public agencies or officials having jurisdiction shall use an assessment or management method that is designed to maintain sign retroreflectivity at or above the minimum levels in Table $\frac{2A-3}{2A-5}$.

Support:

Compliance with the Standard in Paragraph 2 of this Section is achieved by having a method in place and using the method to maintain the minimum levels established in Table 2A-32A-5. Provided that an assessment or management method is being used, an agency or official having jurisdiction would be in compliance with the Standard in Paragraph 2 of this Section even if there are some individual signs that do not meet the minimum retroreflectivity levels at a particular point in time.

Guidance:

Except for those signs specifically identified in Paragraph 6-5 of this Section, one or more of the following assessment or management methods described in "Maintaining Traffic Sign Retroreflectivity" (see Section 14.05) or a method developed based on an engineering study should be used to maintain sign retroreflectivity at or above the minimum levels in Table 2A-5. Signs that are below the minimum levels should be replaced:

- A. Visual Nighttime Inspection—The retroreflectivity of an existing sign is assessed by a trained sign inspector conducting a visual inspection from a moving vehicle during nighttime conditions. Signs that are visually identified by the inspector to have retroreflectivity below the minimum levels should be replaced.
- B. Measured Sign Retroreflectivity Sign retroreflectivity is measured using a retroreflectometer. Signs with retroreflectivity below the minimum levels should be replaced.
- C. Expected Sign Life—When signs are installed, the installation date is labeled or recorded so that the age of a sign is known. The age of the sign is compared to the expected sign life. The expected sign life is based on the experience of sign retroreflectivity degradation in a geographic area compared to the minimum levels. Signs older than the expected life should be replaced.
- D. Blanket Replacement All signs in an area/corridor, or of a given type, should be replaced at specified intervals. This eliminates the need to assess retroreflectivity or track the life of individual

1 signs. The replacement interval is based on the expected sign life, compared to the minimum levels, 2 for the shortest-life material used on the affected signs. 3 E. Control Signs Replacement of signs in the field is based on the performance of a sample of control 4 signs. The control signs might be a small sample located in a maintenance vard or a sample of signs 5 in the field. The control signs are monitored to determine the end of retroreflective life for the 6 associated signs. All field signs represented by the control sample should be replaced before the 7 retroreflectivity levels of the control sample reach the minimum levels. 8 F. Other Methods Other methods developed based on engineering studies can be used. 9 10 Additional information about these methods is contained in the 2007 Edition of FHWA's "Maintaining Traffic Sign Retroreflectivity" (see Section 1A.11). Incorporated into preceding Guidance 11 12 13 Highway agencies may exclude the following signs from the retroreflectivity maintenance guidelines 14 described in this Section: 15 A. Parking, Standing, and Stopping signs (R7 and R8 series) B. Walking/Hitchhiking/Crossing signs (R9 series, R10-1 through R10-4b) 16 17 C. Acknowledgment signs 18 D. All signs with blue or brown backgrounds 19 **ED**. Bikeway signs that are intended for exclusive use by bicyclists or pedestrians 20 Table 2A-5. Minimum Maintained Retroreflectivity Levels 21 Section 2A.232A.22 Median Opening Treatments for Divided Highways with Wide Medians 22 Guidance: 23 Where divided highways are separated by median widths at the median opening itself of 30 feet or more, 24 median openings should be signed as two separate intersections. 25 A divided highway crossing should be signed and marked as separate intersections when both of the 26 *following conditions are present:* 27 A. The paths of opposing left turns from the divided highway cross each other (see Figure 2A-5) and 28 B. There is adequate storage in the interior approaches for the design vehicles expected to cross the 29 divided highway. 30 If either one or both of the conditions in Paragraph 1 of this Section do not exist, the divided highway 31 crossing should be signed and marked as a single intersection. 32 At the crossing of two divided highways, engineering judgment should be used to determine the number of 33 separate intersections. 34 Support: 35 Divided highway crossings with median widths between 30 feet and 85 feet might function as either one 36 or two intersections depending upon the interaction of the opposing left-turn vehicle paths and the available 37 interior storage in the median for a crossing vehicle. Other factors that could determine whether a divided 38 highway crossing is operating as one or two intersections include: 39 A. the geometric design of the divided highway crossing, 40 B. the use of positive offset mainline left turn lanes, 41 C. the length of the median opening (as measured parallel to the centerline of the divided highway), 42 D. the geometric design of the median noses, 43 E. other roadway geometric considerations such as a skewed side street approach or a variable median 44 width, 45 F. intersection sight distance, 46 G. the physical characteristics of the design vehicle, and

47

48

H. the observed prevailing driver behavior with regard to opposing left turn path interaction.

		CHAPTER 2B. REGULATORY SIGNS, BARRICADES, AND GATES
<u>Ch</u>	apter 2B S	Subchapter and Section Organization
Ger	<u>neral</u>	
	2B.01	Application of Regulatory Signs
	2B.02	Design of Regulatory Signs
	2B.03	Size of Regulatory Signs
	2B.04	STOP Sign (R1-1) and ALL-WAY Plaque (R1-3P)
	2B.05	YIELD Sign (R1-2)
Sig	ning for R	ight-Of-Way at Intersections
	2B.06	General Considerations
	2B.07	Determining the Minor Road for Unsignalized Intersections
	2B.08	Right-of-Way Intersection Control Considerations
	2B.09	No Intersection Control
	2B.10	Yield Control
	2B.11	Minor Road Stop Control
	2B.12	All-Way Stop Control
	2B.13	All-Way Stop Control Warrant A: Crash Experience
	2B.14	All-Way Stop Control Warrant B: Sight Distance
	2B.15	All-Way Stop Control Warrant C: Transition to Signal Control or YIELD Control at a
		Roundabout
	2B.16	All-Way Stop Control Warrant D: 8-Hour Volume (Vehicle, Pedestrians, Bicycles)
	2B.17	All-Way Stop Control Warrant E: Other Factors
	2B.18	STOP Sign or YIELD Sign Placement
	2B.19	Yield Here to Pedestrians Signs and Stop Here for Pedestrians Signs (R1-5 Series)
	2B.20	In-Street and Overhead Pedestrian and Trail Crossing Signs (R1-6 and R1-9 Series)
Sne	ed Limit S	Signs and Plaques
<u> 5</u>	2B.21	Speed Limit Sign (R2-1)
	2B.22	Vehicle Speed Limit Plaques (R2-2P Series)
	2B.23	Night Speed Limit Plaque (R2-3P)
	2B.24	Minimum Speed Limit Plaque (R2-4P) and Combined Maximum and Minimum Speed Limits
	<u>ZD.Z4</u>	(R2-4a) Sign
	2B.25	Higher Fines Signs and Plaque (R2-6P, R2-10, and R2-11)
Mo		d Lane Control Signs
1110	2B.26	Movement Prohibition Signs (R3-1 through R3-4, R3-18, and R3-27)
	2B.27	Intersection Lane Control Signs (R3-5 through R3-8)
	2B.28	Mandatory Movement Lane Control Signs (R3-5, R3-5a, R3-7, R3-19 Series, and R3-20)
	2B.29	Optional Movement Lane Control Sign (R3-6 Series)
	2B.30	Advance Intersection Lane Control Signs (R3-8 Series)
	2B.31	RIGHT (LEFT) LANE MUST EXIT Signs (R3-33, R3-33a)
	2B.32	Two-Way Left Turn Only Signs (R3-9a, R3-9b)
	2B.33	BEGIN and END Plaques (R3-9cP, R3-9dP)
	2B.34	Reversible Lane Control Signs (R3-9e through R3-9i)
	2B.35	Jughandle Signs (R3-23, R3-24, R3-25, and R3-26 Series)
Pac	sing Keer	o Right and Slow Traffic Signs
<u>1 as</u>	2B.36	DO NOT PASS Sign (R4-1)
	2B.37	PASS WITH CARE Sign (R4-2)
	2B.37 2B.38	KEEP RIGHT EXCEPT TO PASS Sign (R4-16) and SLOWER TRAFFIC KEEP RIGHT
	<u>20.00</u>	Sign (R4-3)
	2B.39	TRUCKS USE RIGHT LANE Sign (R4-5)
	2B.40	Keep Right and Keep Left Signs (R4-7 Series, R4-8 Series)
	2B.40 2B.41	STAY IN LANE Sign (R4-9)
	2B.41 2B.42	RUNAWAY VEHICLES ONLY Sign (R4-10))
	4D.42	KUNAWAI VEHICLES ONLI SIM (K4-10))

1	2B.43	Slow Vehicle Turn-Out Signs (R4-12, R4-13, and R4-14)
2	<u>2B.44</u>	DO NOT DRIVE ON SHOULDER Sign (R4-17) and DO NOT PASS ON SHOULDER Sign
3		<u>(R4-18)</u>
4	<u>2B.45</u>	ALL TRAFFIC Sign (R4-20) and RIGHT (LEFT) TURN ONLY Sign (R4-21)
5	Selective Exc	
6	2B.46	Selective Exclusion Signs
7	DO NOT EN	TER, WRONG WAY, ONE-WAY and Related Signs and Plaques
3	2B.47	DO NOT ENTER Sign (R5-1)
)	<u>2B.48</u>	WRONG WAY Sign (R5-1a)
)	2B.49	Wrong-Way Traffic Control at Interchange Ramps
	2B.50	ONE WAY Signs (R6-1, R6-2)
2	<u>2B.51</u>	<u>Divided Highway Crossing Signs (R6-3, R6-3a)</u>
;	2B.52	Roundabout Circulation Plaque (R6-5P)
	Parking, Stan	ding, Stopping and Emergency Signs
	2B.53	Parking, Standing, and Stopping Signs (R7 and R8 Series)
	2B.54	Design of Parking, Standing, and Stopping Signs
	2B.55	Placement of Parking, Stopping, and Standing Signs
	2B.56	Emergency Restriction Signs (R8-4, R8-7, R8-8)
	Pedestrian Si	gns
	2B.57	WALK ON LEFT FACING TRAFFIC and No Hitchhiking Signs (R9-1, R9-4, R9-4a)
	2B.58	Pedestrian Crossing Signs (R9-2, R9-3)
	2B.59	Traffic Signal Pedestrian and Bicycle Actuation Signs (R10-1 through R10-4, and R10-24
		through R10-26)
	Traffic Signa	1 Signs
	2B.60	Traffic Signal Signs (R10-5 through R10-30)
	2B.61	No Turn on Red Signs (R10-11 Series, R10-17a, and R10-30)
	2B.62	Photo Enforced Signs and Plaques (R10-18, R10-19P, R10-19aP, R10-18a)
	2B.63	Ramp Metering Signs (R10-28 and R10-29)
	ROAD CLOS	SED and Weight Limit Signs
	2B.64	KEEP OFF MEDIAN Sign (R11-1)
	2B.65	ROAD CLOSED Sign (R11-2) and LOCAL TRAFFIC ONLY Signs (R11-3 Series, R11-4)
	2B.66	Weight Limit Signs (R12-1 through R12-7)
	2B.67	Vehicle Inspection Area Signs (R13-1 Series)
	2B.68	TRUCK ROUTE Sign (R14-1)
	2B.69	Hazardous Material Signs (R14-2, R14-3)
	2B.70	National Network Signs (R14-4, R14-5)
	Other Regula	tory Signs
	2B.71	MINOR CRASES MOVE VEHICLES FROM TRAVEL LANES (R16-4) Sign
	2B.71 2B.72	Minor Crases Move Vehicles from Travel Lanes (R10-4) Sign Move Over or Reduce Speed Sign
	2B.72 2B.73	No Hand-Held Phones by Driver Signs (R16-15, R16-15a)
	2B.73 2B.74	Headlight Use Signs (R16-5 through R16-11)
	2B.75	Seat Belt Symbol
	Barricades an	
	2B.76 2B.77	Barricades Gates
5	∠ D . / /	Gates

46

1 <u>GENERAL</u>

Section 2B.01 Application of Regulatory Signs

Standard:

2

3

4

5 6

7

8

9

10

11 12

13 14

15

16 17

18

19

20

21

22

23

24

25

2627

28 29

30

31

32

33

34

35

36

37

39

40 41

42

43

44

45

46

Regulatory signs shall be used to inform road users of selected traffic laws or regulations and indicate the applicability of the legal requirements.

Regulatory signs shall be installed at or near where the regulations apply. The signs shall clearly indicate the requirements imposed by the regulations and shall be designed and installed to provide adequate visibility and legibility in order to obtain compliance.

Regulatory signs shall be retroreflective or illuminated (see Section 2A.0720), to show the same shape and similar color by both day and night, unless specifically stated otherwise in the text discussion in this Manual for a particular sign or group of signs.

The requirements for sign illumination shall not be considered to be satisfied by street or highway lighting. Not needed because this is already covered in new Section 2A.20

Support:

Section 1A.09 contains information regarding the assistance that is available to jurisdictions that do not have engineers on their staffs who are trained and/or experienced in traffic control devices. Not needed because this is covered in new Section 1D.05

Section 2B.02 <u>Design of Regulatory Signs</u>

Standard:

Regulatory signs shall be rectangular unless specifically designated otherwise. Regulatory signs shall be designed in accordance with the sizes, shapes, colors, and legends contained in the "Standard Highway Signs and Markings" book publication (see Section 1A.1105).

Option:

Regulatory word message signs other than those classified and specified in this Manual and the "Standard-Highways Signs and Markings" book (see Section 1A.11) may be developed to aid the enforcement of other laws or regulations.

Except for symbols on regulatory signs, minor modifications may be made to the design provided that the essential appearance characteristics are met. Not needed because this is covered in new Section 2A.04 and is redundant

Support:

The use of educational plaques to supplement symbol signs is described in Section 2A.1219.

Guidance Standard:

Changeable message LED signs displaying a part-time regulatory message incorporating a prohibitory message that includes a red circle and slash diagonal on of a static sign should shall display a red symbol that approximates the same red circle and slash diagonal as closely as possible. The prohibited movement symbol shall be a white LED symbol on a black background or a black symbol on a full-matrix white LED background.

38 Option:

The LEDs in the border of regulatory signs may be static or flash at rates per Section 2A. 20.

Standard

A regulatory sign displayed entirely with LEDs and incorporated within the border of a larger full-matrix changeable message sign shall display the regulatory sign legend in the size, shape, color and legend of the standard regulatory sign.

A blank-out or changeable display shall not be used for a STOP (R1-1) sign or a YIELD (R1-2) sign.

Section 2B.03 Size of Regulatory Signs

Notice of Proposed Amendments – Part 2

Standard:

Except as provided in Section 2A.<u>1107</u>, the sizes for regulatory signs shall be as shown in Table 2B-48 1. Support:

Section 2A. 1107 contains information regarding the applicability of the various columns in Table 2B-1.

Standard:

Except as provided in Paragraphs 45 and 56, the minimum sizes for regulatory signs facing traffic on multi-lane conventional roads shall be as shown in the Multi-Lane column of Table 2B-1.

The typical size of regulatory signs applied on low-volume rural roads with operating speeds of 30 mph or less shall be as shown in the Minimum column of Table 2B-1. Content relocated from Part 5.

Option:

Where the posted speed limit is 35 mph or less on a multi-lane highway or street, other than for a STOP sign, the minimum size shown in the Single Lane column in Table 2B-1 may be used.

Where a regulatory sign, other than a STOP sign, is placed on the left-hand side of a multi-lane roadway in addition to the installation of the same regulatory sign on the right-hand side or the roadway, the size shown in the Single Lane column in Table 2B-1 may be used for both the sign on the right-hand side and the sign on the left-hand side of the roadway.

Standard:

A minimum size of 36 x 36 inches shall be used for STOP signs that face multi-lane approaches.

Where side roads intersect a multi-lane street or highway that has a speed limit of 45 mph or higher, the minimum size of the STOP signs facing the side road approaches, even if the side road only has one approach lane, shall be 36 x 36 inches.

Where side roads intersect a multi-lane street or highway that has a speed limit of 40 MPH or lower, the minimum size of the STOP signs facing the side road approaches shall be as shown in the Single Lane or Multi-Lane columns of Table 2B-1 based on the number of approach lanes on the side street approach.

Table 2B-1. Regulatory Sign and Plaque Sizes

Guidance:

The minimum sizes for regulatory signs facing traffic on exit and entrance ramps at major interchanges connecting an Expressway or Freeway with an Expressway or Freeway (see Section 2E.11) should be as shown in the column of Table 2B-1 that corresponds to the mainline roadway classification (Expressway or Freeway). If a minimum size is not provided in the Freeway column, the minimum size in the Expressway column should be used. If a minimum size is not provided in the Freeway or Expressway Column, the size in the Oversized column should be used.

The minimum size for all regulatory signs facing traffic on exit and entrance ramps at all other interchanges (see Section 2E.11) should be the regulatory sign size shown in Table 2B-1 Conventional Road Single Lane column for single-lane ramps and Multi-lane column for multi-lane ramps.

35 Option:

The size shown in the Single-Lane column of Table 2B-1 may be used on a multi-lane approach for the following signs:

- A. The NO TURN ON RED (R10-11, R10-11a, and R10-11b) signs.
- B. The RIGHT (LEFT) ON RED ARROW AFTER STOP (R10-17a) sign.

Standard:

If a single-lane R10-11, R10-11a, R10-11b, or R10-17a sign size as shown in Table 2B-1 is used on an approach on the far side of the intersection, and the distance between the stop line and the sign is more than 120 feet, then a duplicate sign shall be required on the near side of the intersection to supplement the sign on the far side of the intersection.

- 45 Section 2B.04 Right-of-Way at Intersections Incorporated into new Subchapter: Signing for
- 46 Right-of-Way at Intersections
- 47 Section 2B.052B.04 STOP Sign (R1-1) and ALL-ALL-WAY Plaque (R1-3P)
- **Standard:**

1 When it is determined that a full stop is always required on an approach to an intersection, a STOP 2 (R1-1) sign (see Figure 2B-1) shall be used. 3 The STOP sign shall be an octagon with a white legend and border on a red background. Secondary legends shall not be used on STOP sign faces. 4 5 At intersections where all approaches are controlled by STOP signs (see Section 2B.0713), an ALL-WAY supplemental plaque (R1-3P) shall be mounted below each STOP sign. The ALL-WAY plaque 6 7 (see Figure 2B-1)-shall have a white legend and border on a red background. 8 The ALL WAY plaque shall only be used if all intersection approaches are controlled by STOP 9 signs. 10 Supplemental plaques with legends such as 2-WAY, 3-WAY, 4-WAY, or other numbers of ways shall not be used with STOP signs. 11 12 Support: 13 The use of the CROSS TRAFFIC DOES NOT STOP (W4-4P) plaque (and other plaques with variations 14 of this word message) is described in Section 2C.5965. 15 Guidance: Plaques with the appropriate alternative messages of TRAFFIC FROM LEFT (RIGHT) DOES NOT 16 STOP (W4-4aP) or ONCOMING TRAFFIC DOES NOT STOP (W4-4bP) should be used at intersections 17 18 where STOP signs control all but one approach to the intersection, unless the only non-stopped approach is 19 from a one-way street. 20 Option: 21 An EXCEPT RIGHT TURN (R1-10P) plaque (see Figure 2B-1) may be mounted below the STOP sign if 22 an engineering study determines that a special combination of geometry and traffic volumes is present that 23 makes it possible for right-turning traffic on the approach to be permitted to enter the intersection without 24 stopping. 25 Support: 26 The design and application of Stop Beacons are described in Section 4L4S.05. 27 Figure 2B-1. STOP and YIELD Signs and Plaques Section 2B.06 STOP Sign Applications Incorporated into new Subchapter: Signing for Right-28 of-Way at Intersections 29 Section 2B.07 Multi-Way Stop Applications Incorporated into new Subchapter: Signing for 30 Right-of-Way at Intersections 31 32 Section **2B.08 2B.05 YIELD Sign** (R1-2) 33 **Standard:** 34 The YIELD (R1-2) sign (see Figure 2B-1) shall be a downward-pointing equilateral triangle with a 35 wide red border and the legend YIELD in red on a white background. 36 37 The YIELD sign requires road users to yield the right-of-way to other traffic assigns right-of-way to 38 traffic on certain approaches to an intersection. Vehicles controlled by a YIELD sign need to slow down to a 39 speed that is reasonable for the existing conditions or stop when necessary to avoid interfering with 40 conflicting traffic. 41 Section 2B.09 YIELD Sign Applications Incorporated into new Subchapter: Signing for Right-

of-Way at Intersections

42 43

SIGNING FOR RIGHT-OF-WAY AT INTERSECTIONS

2 <u>Section 2B.06 General Considerations</u> Contains material relocated from existing Section 2B.04

3 Support:

1

4

5

6

7

8

9

10

11

12

13

14

1516

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

38

39

40

41

42

43

44

45

46

47

48

49

<u>Unsignalized intersections represent the most common form of intersection right-of-way control.</u>
Selection of control type might be impacted by specific requirements of state law or local ordinances.

Roundabouts and traffic circles are intersection designs and are not traffic control devices. The decision to convert an intersection from a conventional intersection to a circular intersection is an engineering design decision and not a traffic control device decision. As such, criteria for conversion from a conventional intersection to a circular intersection are not included in the MUTCD.

Guidance:

The type of traffic control used at an unsignalized intersection should be the least restrictive that provides appropriate levels of safety and efficiency.

Support:

Some types of right-of-way control that can exist at an unsignalized intersection are listed below in order from the least restrictive to the most restrictive.

- A. No intersection control: There are no right-of-way traffic control devices on any of the approaches to the intersection (See Section 2B.04c for guidance).
- B. Yield Control: YIELD signs are placed on all approaches (for a roundabout), on opposing approaches for a 4-leg intersection, on a single approach for a 2-leg intersection, or in the median of a divided highway. The YIELD signs are placed on the minor road. (See Section 2B.04b for guidance)
- C. Minor road stop control: STOP signs are typically placed on opposing approaches (for a 4-leg intersection) or on a single approach (for a 3-leg intersection). The STOP signs are normally placed on the minor road. (See Section 2B.04a for guidance on selecting the minor road.)
- D. All-way stop control: STOP signs are placed on all approaches to the intersection. (See Section 2B.04f for guidance.)

Guidance:

Engineering judgment should be used to establish intersection control. When selecting a form of intersection control, Fthe following factors should be considered:

- A. Vehicular, bicycle, and pedestrian traffic volumes on all approaches. Where the term units/day or units/hour is indicated, it should be the total of vehicular, bicycle, and pedestrian volume.
- B. Driver yielding behavior with regard to bicyclists and pedestrians;
- B. Number and angle of approaches;
- C. Approach speeds;
 - D. Sight distance available on each approach; and
- F. Reported crash experience.
- 36 <u>G. The presence of a grade crossing near the intersection.</u>
- 37 *YIELD or STOP signs should be used at an intersection if one or more of the following conditions exist:*
 - A. An intersection of a less important road with a main road where application of the normal right of way rule would not be expected to provide reasonable compliance with the law;
 - B. A street entering a designated through highway or street; and/or
 - C. An unsignalized intersection in a signalized area.

In addition, the use of YIELD or STOP signs should be considered at the intersection of two minor streets or local roads where the intersection has more than three approaches and where one or more of the following conditions exist:

- A. The combined vehicular, bicycle, and pedestrian volume entering the intersection from all approaches averages more than 2,000 units per day;
- B. The ability to see conflicting traffic on an approach is not sufficient to allow a road user to stop or yield in compliance with the normal right of way rule if such stopping or yielding is necessary; and/or

C. Crash records indicate that five or more crashes that involve the failure to yield the right-of-way at the intersection under the normal right-of way rule have been reported within a 3-year period, or that three or more such crashes have been reported within a 2-year period.

Support:

Appropriate traffic calming or other speed-control measures are available to control vehicle speeds, such as those that do not have the potential to diminish the effectiveness of traffic control devices when used for their specified purpose.

Guidance: Standard: Existing Section 2B.04 paragraph 5 changed to Standard

Yield or Stop signs should shall not be used for speed control.

Standard:

Because the potential for conflicting commands could create driver confusion, Yield or Stop signs shall not be used in conjunction with any traffic control signal operation, except in the following cases:

- A. If the signal indication for an approach is a flashing red at all times;
- B. If a minor street or driveway is located within or adjacent to the area controlled by the traffic control signal, but does not require separate traffic signal control because an extremely low potential for conflict exists; or
- C. If a channelized turn lane is separated from the adjacent travel lanes by an island and the channelized turn lane is not controlled by a traffic control signal.

Except as provided in Section 2B. 911, STOP signs and YIELD signs shall not be installed on different approaches to the same unsignalized intersection if those approaches conflict with or oppose each other.

Portable or part-time STOP or YIELD signs shall not be used except for emergency and temporary traffic control zone purposes.

A portable or part-time (folding) STOP sign that is manually placed into view and manually removed from view shall not be used during a power outage to control a signalized approach unless the maintaining agency establishes that the signal indication that will first be displayed to that approach upon restoration of power is a flashing red signal indication and that the portable STOP sign will be manually removed from view prior to stop-and-go operation of the traffic control signal.

Option:

A portable or part-time (folding) Stop sign that is electrically or mechanically operated such that it only displays the Stop message during a power outage and ceases to display the Stop message upon restoration of power may be used during a power outage to control a signalized approach.

Support:

The use of STOP signs at grade crossings is described in Sections 8B.04 and 8B.05. Relocated from existing Section 2B.06 paragraph 3

Section 9B.0301 contains provisions regarding the assignment of priority at a shared-use path/roadway intersection.

Section 2B.07 contains provisions regarding the application of multi-way STOP control at an intersection.

Deleted, replaced by other text

Section 2B.07 Determining the Minor Road for Unsignalized Intersections Contains material relocated from existing Section 2B.04

Guidance:

Once the decision has been made to control an intersection, the decision regarding the appropriate roadway to control should be based on engineering judgment. In most cases, the roadway carrying the lowest volume of traffic should be controlled. Deleted, replaced by other text

A YIELD or STOP sign should not be installed on the higher volume roadway unless justified by an engineering study. Deleted, replaced by other text

The selection of the minor road to be controlled by YIELD or STOP signs should be based on one or more of the following criteria:

A. A roadway intersecting a designated through or numbered highway.

- 1 B. A roadway with the lower functional classification.
 2 C. A roadway with the lower traffic volume.
 3 D. A roadway with the lower speed limit
 - E. A roadway that intersects with a roadway that has a higher priority for one of more modes of travel. - Support:

The following are considerations that might influence the decision regarding the appropriate roadway upon which to install a YIELD or STOP sign where When two roadways with that have relatively equal volumes, speeds, and/or characteristics intersect, the following factors should be considered in selecting the minor road for installation of YIELD or STOP signs:

- A. Controlling the direction that conflicts the most with established pedestrian crossing activity or school walking routes;
- B. Controlling the direction that has obscured vision, dips, or bumps that already require drivers to use lower operating speeds; and
- C. Controlling the direction that has the best sight distance from a controlled position to observe conflicting traffic.

Section 2B.08 Right-of-Way Intersection Control Considerations

Guidance:

4

5

6

7

8 9

10

11

12

13

14

15

16 17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42 43

44

45

46 47

48

49

50

51

52

53

Before converting to a more restrictive form of right-of-way control at an unsignalized intersection, consideration should be given, but not limited, to the following alternative treatments to address safety, operational, or other concerns.

Option: Relocated from existing Section 4B.04 and changed from Option to Guidance

Alternatives that should be considered include, but are not limited to, the following:

- A. Where Yield or Stop controlled, installing Stop Ahead or Yield Ahead signs on the appropriate approaches to the intersection.
- B. Removing parking on one or more approaches.
- C. Removing sight distance restrictions.
- A.D. Installing signs along the major street to warn road users approaching the intersection;
- **B.**<u>E.</u> Relocating the stop line(s) and making other changes to improve the sight distance at ——the intersection;
- <u>C.F.</u> Installing measures designed to reduce speeds on the approaches;
- <u>D.G.</u>Installing <u>a flashing</u> <u>an intersection control</u> beacon (<u>see Section 4S.02</u>) or stop beacon (<u>see Section 4S.05</u>) at the intersection to supplement STOP sign control;
- E.H. Installing flashing warning beacons (see Section 4S.03) on warning signs in advance of a STOP sign controlled intersection on major- and/or minor-street approaches;
- F.I. Adding one or more lanes on a minor-street approach to reduce the number of vehicles per lane on the approach;
- G.J. Revising the geometrics at the intersection to channelize vehicular movements and reduce the time required for a vehicle to complete a movement, which could also assist pedestrians;
- <u>H.K.</u> Revising the geometrics at the intersection to add pedestrian median refuge islands and/or curb extensions;
- <u>H.L.</u> Installing roadway lighters if a disproportionate number of crashes occur at night;
- J.M. Restricting one or more turning movements, perhaps on a time of day on a full-or part-time basis if alternate routes are available;
- K. If the warrant is satisfied, installing multi-way STOP sign control;
- L.N. Installing on the major street a pedestrian-actuated device: pedestrian hybrid warning beacon (see Chapter 4F Section 4S.03), rectangular rapid-flashing beacon (see Section 4L.01), or In-Roadway Warning Lights (see Chapter 4NU), if pedestrian safety is the major concern;
- M.O. If the warrant is satisfied, installing multi-way STOP sign control;
- N.P. Installing on the major street a pedestrian hybrid beacon (see Chapter 4J) if pedestrian safety is the major concern;
- O.O. Installing a roundabout; and
- P.R. Employing other alternatives, depending on conditions at the intersection.

Section 2B.09 No Intersection Control

Support:

State or local laws written in accordance with the "Uniform Vehicle Code" (see Section 1A.11) establish-the right of way rule at intersections having no regulatory traffic control signs such that the driver of a vehicle approaching an intersection must yield the right of way to any vehicle or pedestrian already in the intersection. When two vehicles approach an intersection from different streets or highways at approximately the same time, the right of way rule requires the driver of the vehicle on the left to yield the right of way to the vehicle on the right. The right of way can be modified at through streets or highways by placing YIELD (R1-2) signs (see Sections 2B.08 and 2B.09) or STOP (R1-1) signs (see Sections 2B.05 through 2B.07) on one or more approaches.

Paragraph 1 of 2009 MUTCD Section 2B.04 deleted, as it is unneeded Guidance:

The decision not to use intersection control should be based on engineering judgment.

Option:

The following factors may be considered:

- A. Intersection sight distance is adequate on all approaches.
- B. All approaches to the intersection are a single lane and there are no separate turn lanes.
- C. The combined vehicular, bicycle, and pedestrian volume (existing or projected) entering the intersection from all approaches averages less than 1,000 units per day or 80 units in the peak hour.
- D. There are no marked crosswalks or bicycle lanes on any approach.
- E. None of the approaches to the intersection are for a through highway, main road, or higher functional classification.
- F. The angle of intersection is between 90 and 75 degrees.
- G. The functional classification of the intersecting streets is either the intersection of two local streets or the intersection of a local street with a collector street.

Section 2B.10 Yield Control

Guidance:

At intersections where a full stop is not necessary at all times, consideration should first be given to using less restrictive measures such as YIELD signs. From existing Section 2B.06, Paragraph 01

<u>Yield control should be considered when engineering judgment indicates that all of the following conditions exist:</u>

- A. Intersection sight distance is adequate on the approaches to be controlled by YIELD signs.
- B. All approaches to the intersection are a single lane and there are no separate turn lanes.
- C. One of the following crash-related criteria applies:
 - 1. For changing from no intersection control to yield control, there have been two or more reported crashes that are susceptible to correction by installation of a YIELD sign in the previous 12 months.
 - 2. For changing from minor road stop control to yield control, there have been two or fewer reported crashes in the previous 12 months.
- D. Entering intersection volume of less than 1800 units per day or 140 units in the peak hour.
- *E.* The angle of intersection is between 90 and 75 degrees.
- F. The functional classification of the intersecting streets is either the intersection of two local streets or the intersection of a local street with a collector street.

Option:

YIELD signs may be installed at an intersection when any of the following conditions apply: From existing Section 2B.09, Paragraph 1

- A. On the approaches to a through street or highway where conditions are such that a full stop is not always required.
- B.A. At the second erossroad-intersection of a divided highway, highway crossing or median break functioning as two separate intersections (see Figures 2B-12 and 2B-15), where the median width at the intersection is 30 feet or greater. In this case, a YIELD sign may be installed at the entrance to the second roadwayintersection.
- C.B. For a channelized turn lane that is separated from the adjacent travel lanes by an island, even if the adjacent lanes at the intersection are controlled by a highway traffic control signal or by a Stop sign.

- D.C. At an intersection where a special problem exists and where engineering judgment indicates the problem to be susceptible to correction by the use of the YIELD sign.
 - ED. Facing the entering roadway for a merge-type movement if engineering judgment indicates that control is needed because acceleration geometry and/or sight distance is not adequate for merging traffic operation.
 - E. On low-volume rural roads if engineering judgment indicates that the YIELD would provide adequate control. Moved from 2009 MUTCD Part 5
 - F. On an approach to an intersection where the only permissible movement is a right turn movement with an intersection geometry similar to a channelized right turn lane or an approach to a roundabout.

Guidance:

The YIELD signs should be installed on opposing minor street approaches (for a 4-leg intersection) or on the minor approach (for a 3-leg intersection). (See Section 2B-X3) for information to identify the minor road). When two intersection roadways have relatively equal volumes, speeds and other characteristics, y¥ield control should be installed on the approach that conflicts the most with established pedestrian crossing activity or school walking routes or bicycle crossing activity.

Standard:

A YIELD sign shall be used to <u>require road users to yield the right-of-way to other traffic assign-right-of-way</u> at the entrance to a roundabout. Yield signs at roundabouts shall be used to control the approach roadways and shall not be used to control the circulatory roadway. From existing Section 2B.09, Paragraph 2

Other than for all of the approaches to a roundabout, YIELD signs shall not be placed on all of the approaches to an intersection, except at roundabouts. From existing Section 2B.09, Paragraph 3

Section 2B.11 Minor Road Stop Control

Guidance:

The use of STOP signs on Stop control on the minor-street road approach or approaches to an intersection should be considered if when engineering judgment indicates that a stop is always required because of one or more of the following conditions exist: From existing Section 2B.06 Paragraph 2

- A. The vehicular traffic volumes on the through street or highway exceed 6,000 vehicles perday;
- B. A. A restricted view exists that requires road users to stop in order to adequately observe conflicting traffic on the through street or highway; and/or
- *€B. Crash records indicate that:*
 - 1. For a four-leg intersection, there are three or more reported crashes in a 12-month period or six or more reported crashes in a 36-month period. The crashes should be susceptible to correction by installation of two-way stop control.
 - 2. For a three-leg intersection, there are three or more reported crashes in a 12-month period or five or more reported crashes in a 36-month period. The crashes should be susceptible to correction by installation of two-way stop control.
- <u>C. The intersection is of a lower functional classification road with a higher functional classification road</u>
- D. Conditions that previously supported installation of an all-way stop control under all-way stop control criteria no longer exist.

On low-volume rural roads, a STOP sign should be considered at an intersection where engineering judgment indicates that Item C above is applicable or where the intersection has inadequate sight distance for the operating vehicle speeds. Moved from existing MUTCD Part 5

- Section 2B.12 All-Way Stop Control Changing the term to all-way rather than multi-way
- 48 Support: From existing Section 2B.07 Paragraphs 1 and 2 deleted as unneeded
 - Multi-way stop control can be useful as a safety measure at intersections if certain traffic conditions exist. Safety concerns associated with multi-way stops include pedestrians, bicyclists, and all road users expecting

other road users to stop. Multi-way stop control is used where the volume of traffic on the intersecting roads is approximately equal.

The restrictions on the use of STOP signs described in Section 2B.04 also apply to multi-way stop-applications.

Guidance:

The decision to <u>install-establish</u> all-way stop control at an unsignalized intersection should be based on an engineering study. From existing Section 2B.07 Paragraph 3

The engineering study for all-way stop control should include an analysis of factors related to the existing operation and safety at the intersection, the potential to improve these conditions, and the applicable factors contained in the following all-way stop control warrants:

- A. All-Way Stop Control Warrant A: Crash Experience (Section 2B.13)
- B. All-Way Stop Control Warrant B: Sight Distance (Section 2B.14)
- C. All-Way Stop Control Warrant C: Transition to Signal Control or YIELD Control at a Roundabout (Section 2B.15)

D. All-Way Stop Control Warrant D: Peak Hour Volume (Vehicle, Pedestrians, Bicycles) (Section 2B.16) E. All-Way Stop Control Warrant E: Other Factors (Section 2B.17)

Standard:

The satisfaction of an all-way stop control warrant or warrants shall not in itself require the installation of all-way stop control at an unsignalized intersection.

Guidance: Existing Section 2B.07 Paragraph 4 deleted and replaced with new text in new Sections

The following criteria should be considered in the engineering study for a multi-way STOP signinstallation:

- A. Where traffic control signals are justified, the multi-way stop is an interim measure that can be installed quickly to control traffic while arrangements are being made for the installation of the traffic control signal.
- B. Five or more reported crashes in a 12 month period that are susceptible to correction by a multi-way stop installation. Such crashes include right-turn and left-turn collisions as well as right-angle collisions.
- C. Minimum volumes:
 - 1. The vehicular volume entering the intersection from the major street approaches (total of both approaches) averages at least 300 vehicles per hour for any 8 hours of an average day; and
 - 2. The combined vehicular, pedestrian, and bicycle volume entering the intersection from the minor street approaches (total of both approaches) averages at least 200 units per hour for the same 8 hours, with an average delay to minor street vehicular traffic of at least 30 seconds per vehicle during the highest hour; but
 - 3. If the 85th-percentile approach speed of the major street traffic exceeds 40 mph, the minimum vehicular volume warrants are 70 percent of the values provided in Items 1 and 2.
- D. Where no single criterion is satisfied, but where Criteria B, C.1, and C.2 are all satisfied to 80 percent of the minimum values. Criterion C.3 is excluded from this condition.

Section 2B.13 All-Way Stop Control Warrant A: Crash Experience

Option:

All-way stop control may be installed at an intersection where an engineering study indicates that:

- A. For a four-leg intersection, there are five or more reported crashes in a 12-month period or six or more reported crashes in a 36-month period that were of a type susceptible to correction by the installation of all-way stop control.
- B. For a three-leg intersection, there are four or more reported crashes in a 12-month period or five or more reported crashes in a 36-month period that were of a type susceptible to correction by the installation of all-way stop control.
- C. The sight distance on the minor road approaches controlled by a Stop sign is not adequate for a vehicle to turn onto or cross the major (uncontrolled) road.

2B.14 All-Way Stop Control Warrant B: Sight Distance

Option:

All-way stop control may be installed at an intersection where an engineering study indicates that sight distance on the minor road approaches controlled by a Stop sign is not adequate for a vehicle to turn onto or cross the major (uncontrolled) road.

5 Support:

At such a location, a road user, after stopping, cannot see conflicting traffic and is not able to negotiate the intersection unless conflicting cross traffic is also required to stop. Existing Section 2B.07 Paragraph 5C

Section 2B.15 All-Way Stop Control Warrant C: Transition to Signal Control or YIELD Control at a Roundabout

Option:

All-way stop control may be installed at locations where all-way stop control is an interim measure that can be installed to control traffic while arrangements are being made for the installation of the traffic control signals at the intersection or YIELD control at a roundabout. Similar to Existing Section 2B.07 Paragraph

Section 2B.16 All-Way Stop Control Warrant D: 8-Hour Volume (Vehicle, Pedestrians, Bicycles)

Option: Similar to existing Section 2B.07 Paragraph 4C

All-way stop control may be installed at an intersection where an engineering study indicates:

- A. The volume entering the intersection from the major street approaches (total of both approaches) averages at least 300 units per hour for each of any 8 hours of an average day; and
- B. The volume entering the intersection from the minor street approaches (total of both approaches) averages at the street 200 units per hour for each of any of the same 8 hours; and
- C. If the 85th ventile approach speed of the major-street traffic exceeds 40mph, the minimum vehicular volume warrants are 70 percent of the values in Items A and B.

Section 2B.17 All-Way Stop Control Warrant E: Other Factors

Option:

All-way stop control may be installed at an intersection where an engineering study indicates that all-way stop control is needed due to other factors not addressed in the other all-way stop control warrants. Such other factors may include, but are not limited to, the following:

- A. The need to control left-turn conflicts; From existing Section 2B.07 Paragraph 5
- B. An intersection of two residential neighborhood collector (through) streets of similar design and operating characteristics where all-way stop control would improve traffic operational characteristics of the intersection; or From exiting Section 2B.07 Paragraph 5D
- C. Where pedestrian and/or bicycle movements justify the installation of all-way stop control. Similar to existing Section 2B.07 Paragraph 5B

Section 2B.102B.18 STOP Sign or YIELD Sign Placement

Standard:

The STOP or YIELD sign shall be installed on the near side of the intersection on the right-hand side of the approach to which it applies. When the STOP or YIELD sign is installed at this required location and the sign visibility is restricted, a Stop Ahead sign (see Section 2C.3637) shall be installed in advance of the STOP sign or a Yield Ahead sign (see Section 2C.3637) shall be installed in advance of the YIELD sign.

The STOP or YIELD sign shall be located as close as practical to the intersection it regulates, while optimizing its visibility to the road user it is intended to regulate.

STOP signs and YIELD signs shall not be mounted on the same post.

No items other than inventory stickers, sign installation dates, and bar codes shall be affixed to the fronts of STOP or YIELD signs, and the placement of these items shall be in the border of the sign.

No items other than official traffic control signs, inventory stickers, sign installation dates, antivandalism stickers, and bar codes shall be mounted on the backs of STOP or YIELD signs. No items other than retroreflective strips (see Section 2A.21) or official traffic control signs shall be mounted on the fronts or backs of STOP or YIELD signs supports.

Guidance:

 STOP or YIELD signs should not be placed farther than 50 feet from the edge of the pavement of the intersected roadway (see Drawing F in Figure 2A-3).

A sign that is mounted back-to-back with a STOP or YIELD sign should stay within the edges of the STOP or YIELD sign. If necessary, the size of the STOP or YIELD sign should be increased so that any other sign installed back-to-back with a STOP or YIELD sign remains within the edges of the STOP or YIELD sign

<u>Supplemental plaques used in conjunction with a STOP or YIELD sign should be limited to those specified</u> for such use in this Manual.

Option:

Where drivers proceeding straight ahead must yield to traffic approaching from the opposite direction, such as at a one-lane bridge, a TO ONCOMING TRAFFIC (R1-2aP) plaque may be mounted below the YIELD sign.

Where drivers must yield to traffic in a multi-lane roundabout, a TO TRAFFIC IN CIRCLE (R1-2bP) or TO ALL LANES (R1-2cP) plaque may be mounted below the YIELD sign.

17 Support:

Figure 2A-3 shows examples of some typical placements of STOP signs and YIELD signs.

Section 2A.<u>1612</u> contains additional information about separate and combined mounting of other signs with STOP or YIELD signs.

Guidance:

Stop lines that are used to supplement a STOP sign should be located as described in Section 3B.<u>1619</u>. Yield lines that are used to supplement a YIELD sign should be located as described in Section 3B.<u>1619</u>.

Where there is a marked crosswalk at the intersection, the STOP sign should be installed in advance of the crosswalk line nearest to the approaching traffic.

Except at roundabouts, where there is a marked crosswalk at the intersection, the YIELD sign should be installed in advance of the crosswalk line nearest to the approaching traffic.

Where two roads intersect at an acute angle, the STOP or YIELD sign should be positioned at an angle, or shielded, so that the legend is out of view of traffic to which it does not apply.

If a raised splitter island is available on the left-hand side of a multi-lane roundabout approach, an additional YIELD sign should be placed on the left-hand side of the approach.

Option:

If a raised splitter island is available on the left-hand side of a single lane roundabout approach, an additional YIELD sign may be placed on the left-hand side of the approach.

At wide-throat intersections or where two or more approach lanes of traffic exist on the signed approach, observance of the right-of-way control may be improved by the installation of an additional STOP or YIELD sign on the left-hand side of the road and/or the use of a stop or yield line. At channelized intersections or at divided roadways separated by a median, the additional STOP or YIELD sign may be placed on a channelizing island or in the median. An additional STOP or YIELD sign may also be placed overhead facing the approach at the intersection to improve observance of the right-of-way control.

Standard:

More than one STOP sign or more than one YIELD sign shall not be placed on the same support facing in the same direction.

Option:

For a yield-controlled channelized right-turn movement onto a roadway without an acceleration lane and for an entrance ramp onto a freeway or expressway without an acceleration lane, a NO MERGE AREA (W4-5P) supplemental plaque (see Section 2C.4047) may be mounted below a Yield Ahead (W3-2) sign and/or below a YIELD (R1-2) sign when engineering judgment indicates that road users would expect an acceleration lane to be present.

Section 2B.112B.19 Yield Here To Pedestrians Signs and Stop Here For Pedestrians Signs (R1-5 Series)

Support:

The R1-5 series signs are intended to mitigate the scenario that can place pedestrians at risk by blocking other drivers' view of pedestrians and by blocking the pedestrians' view of the vehicles approaching in the adjacent lanes.

Standard:

Yield Here To (Stop Here For) Pedestrians (R1-5, R1-5a, R1-5b, or R1-5c) signs (see Figure 2B-2) shall only be used if yield (stop) lines are used in advance of a marked crosswalk that crosses an uncontrolled multi-lane approach. The Stop Here for Pedestrians signs shall only be used where the law specifically requires that a driver must stop for a pedestrian in a crosswalk. The legend STATE LAW may shall not be displayed at the top of on the R1-5, R1-5a, R1-5b, and R1-5e series signs, if applicable.

If yield (stop) lines and Yield Here To (Stop Here For) Pedestrians signs are used in advance of a crosswalk that crosses an uncontrolled multi-lane approach, the signs shall be placed 20 to 50 feet in advance of the nearest crosswalk line (see Section 3B.19 and Figure 3B-16).

Option:

The R1-5a and R1-5c signs may be used in place of the R1-5 and R1-5b signs provided that the signs are only used in advance of a marked crosswalk that crosses an uncontrolled multi-lane approach within school zones (see Part 7). Added to reflect Official Interpretation 2(09)-40

Guidance:

If yield (stop) lines and Yield Here To (Stop Here For) Pedestrians signs are used in advance of a crosswalk that crosses an uncontrolled multi-lane approach, they should be placed 20 to 50 feet in advance of the nearest crosswalk line (see Section 3B.16 and Figure 3B-17), and Changed to Standard above

When Yield Here To (Stop Here For) Pedestrians signs are provided in advance of a crosswalk across an multi-lane approach, parking should be prohibited in the area between the yield (stop) line and the crosswalk.

Yield (stop) lines and Yield Here To (Stop Here For) Pedestrians signs should not be used in advance of crosswalks that cross an approach to or departure from a roundabout.

Option:

Yield Here To (Stop Here For) Pedestrians signs may be used in <u>accordance with Paragraphs 2 through 4 of this Section advance of a crosswalk that crosses an uncontrolled multi-lane approach to indicate to roadusers where to yield (stop) even if yield (stop) lines are not used.</u>

A Pedestrian Crossing (W11-2) warning sign may be placed overhead or may be post-mounted with a diagonal downward pointing arrow (W16-7P) plaque at the crosswalk location where Yield Here To (Stop Here For) Pedestrians signs have been installed in advance of the crosswalk.

Standard:

If a W11-2 sign has been post-mounted at the crosswalk location where a Yield Here To (Stop Here For) Pedestrians sign is used on the approach, the Yield Here To (Stop Here For) Pedestrians sign shall not be placed on the same post as or block the road user's view of the W11-2 sign.

Option:

An advance Pedestrian Crossing (W11-2) warning sign with an AHEAD or a distance supplemental plaque may be used in conjunction with a Stop Here For (Yield Here To) Pedestrians sign on the approach to the same crosswalk.

In-Street Pedestrian Crossing signs and Stop Here For (Yield Here To) Pedestrians signs may be used together at the same crosswalk.

47 Section 2B.122B.20 In-Street and Overhead Pedestrian and Trail Crossing Signs (R1-6 and R1-9 Series, R1-6a, R1-9, and R1-9a)

Option:

The In-Street Pedestrian Crossing (R1-6 or R1-6a) sign (see Figure 2B-2), In-Street Trail Crossing (R1-6b or R1-6c) sign (see Figure 2B-2), or the Overhead Pedestrian Crossing (R1-9 or R1-9a) sign (see Figure 2B-2), or the Overhead Trail Crossing (R1-9d or R1-9e) may be used to remind road users of laws regarding right-of-way at an unsignalized pedestrian crosswalk. The legend STATE LAW may be displayed at the top of the R1-6 and R1-9 series signs, R1-6a, R1-9, and R1-9a signs, if applicable. On the R1-6 and R1-6a series signs, the legends STOP or YIELD may be used instead of the appropriate STOP sign or YIELD sign symbol.

Highway agencies may develop and apply criteria for determining the applicability of In-Street Pedestrian Crossing signs.

Standard:

 If used, the In-Street Pedestrian <u>or Trail</u> Crossing sign shall be placed <u>-at one of the following</u> locations:

A: in the roadway at the crosswalk location on the center line;

B: on a median island;

<u>C:</u> or, in the case of a one-way roadway application, on a lane line, or on a median island. Moved above

The In-Street Pedestrian or Trail Crossing sign shall not be post-mounted on the left-hand or right-hand side of the roadway.

If used, the Overhead Pedestrian <u>or Trail</u> Crossing sign shall be placed over the roadway at the crosswalk location.

If used, the In-Street or Overhead Pedestrian Crossing sign shall be used only as a supplement to a Pedestrian Crossing (W11-2) warning sign with a diagonal downward-pointing arrow (W16-7P) plaque at the crosswalk location. Changed from an Option below and revised

If used, the In-Street or Overhead Trail Crossing sign shall be used only as a supplement to a Trail Crossing (W11-15) warning sign with a diagonal downward-pointing arrow (W16-7P) plaque at the crosswalk location.

An In-Street or Overhead Pedestrian <u>or Trail</u> Crossing sign shall not be placed in advance of the crosswalk to educate road users about the State law prior to reaching the crosswalk, nor shall it be installed as an educational display that is not near any crosswalk.

Guidance:

If an island (see Chapter 31) is available, the In-Street Pedestrian or Trail Crossing sign, if used, should be placed on the island.

Option:

If a Pedestrian Crossing (W11-2) warning sign is used in combination with an In Street or an Overhead Pedestrian Crossing sign, the W11-2 sign with a diagonal downward pointing arrow (W16-7P) plaque may be post-mounted on the right-hand side of the roadway at the crosswalk location. Changed to a Standard above and revised

<u>In-Street Pedestrian or Trail Crossing signs may be mounted back to back in the median or on the centerline of an undivided roadway.</u>

Standard:

The In-Street Pedestrian or Trail Crossing sign and the Overhead Pedestrian Crossing or Trail sign shall not be used at signalized locations crosswalks on approaches controlled by a traffic control signal, pedestrian hybrid beacon, or an emergency vehicle hybrid beacon.

The STOP FOR legend shall only be used in States where the State law specifically requires that a driver must stop for a pedestrian or bicycle in a crosswalk.

The In-Street Pedestrian Crossing sign shall have a black legend (except for the red STOP or YIELD sign symbols) and border on a white background, surrounded by an outer yellow or fluorescent yellow-green background area (see Figure 2B-2). The Overhead Pedestrian Crossing sign shall have a black legend and border on a yellow or fluorescent yellow-green background at the top of the sign and a black legend and border on a white background at the bottom of the sign (see Figure 2B-2).

<u>Unless Except where</u> the In-Street <u>Pedestrian</u> Crossing sign is placed on a physical island, the sign support shall be designed to bend over and then bounce back to its normal vertical position when struck by a vehicle.

1	Option:
2	The In-Street and Overhead Pedestrian and Trail Crossing sign may be used at intersections or midblock
3	pedestrian crossings with flashing beacons.
4	Support:
5 6	The provisions of Section 2A. <u>1814</u> concerning mounting height are not applicable for the In-Street Pedestrian Crossing sign. See Section 2A.21 for sign mounting methods.
7	Standard:
8 9	The top of an In-Street Pedestrian <u>or Trail</u> Crossing sign shall be a maximum of 4 feet above the pavement surface. The top of an In-Street Pedestrian <u>or Trail</u> Crossing sign placed in an island shall be
10	a maximum of 4 feet above the island surface.
11	Option:
12 13 14	The In-Street Pedestrian Crossing or <u>Trail Crossing</u> signs may be used seasonally to prevent damage in winter because of plowing operations, and may be removed at night if the pedestrian activity at night is minimal.
15 16	Both sign mounting types, In-Street -Crossing (R1-6 series) signs and Overhead Crossing (R1-9 series) signs may be used together at the same crosswalk.
17 18	In Street Pedestrian Crossing signs, Overhead Pedestrian Crossing signs, and Yield Here To (Stop Here For) Pedestrians signs may be used together at the same crosswalk.

Figure 2B-2. Unsignalized Pedestrian Crosswalk Signs

19

20

Section 2B.132B.21 Speed Limit Sign (R2-1)

Standard:

Speed zones (other than statutory speed limits <u>e.g., established by Federal or state law</u>) shall only be established on the basis of an engineering study that has been performed in accordance with traffic engineering practices. The engineering study shall include an analysis of the current speed distribution of free-flowing vehicles.

Guidance:

Among the factors that should be considered when establishing or reevaluating speed limits within speed zones are the following: Changed from Option to Guidance and relocated and edited from later in this section

- A. Speed distribution of free-flowing vehicles (such as current 85th centile; the pace; review of past speed studies)
- B. Reported crash experience for at least a 12-month period
- <u>C.</u> Road characteristics (<u>such as lane widths</u>; shoulder condition; grade; alignment; <u>median type</u>; sight distance)
- <u>D. Road context (such as Roadside roadside development and environment (number of driveways land use)</u>; functional classification; parking practices; pedestrian activity; bicycle activity).

When a speed limit thin a speed zone is posted <u>on freeways or expressways</u>, it should be within 5 mph of the 85th-percentil peed of free-flowing traffic <u>vehicles</u>.

Except in urbanized locations within rural regions, when a speed limit within a speed zone is posted on a rural highway, it should be within 5 mph of the 85th reentile speed of free-flowing traffic vehicles.

State and local agencies should conduct engineering studies to reevaluate non-statutory speed limits on segments of their roadways that have undergone significant changes since the last review, (such as the addition or elimination of parking or driveways, changes in the number of travel lanes, changes in the configuration of bicycle lanes, changes to road geometrics, changes to road context, changes in traffic control signal coordination, or significant changes in traffic volumes).

Speed studies for signalized intersection approaches should be taken outside the influence area of the traffic control signal, which is generally considered to be approximately 1/2 mile, to avoid obtaining skewed results for the 85th centile speed. If the signal spacing is less than 1 mile, the speed study should be at approximately the middle of the segment.

Support:

In addition to the factors in Paragraph 2, there are other available resources for practitioners that can assist when establishing or reevaluating speed limits within speed zones. The FHWA's Engineering Speed Limits (https://safety.fhwa.dot.gov/speedmgt/eng_spd_lmts/) Web page provides information on resources and tools that can be used to help practitioners set speed limits for specific segments of roads.

Standard:

The Speed Limit (R2-1) sign (see Figure 2B-3) shall display the limit established by law, ordinance, regulation, or as adopted by the authorized agency based on the engineering study. The speed limits displayed shall be in multiples of 5 mph.

Speed Limit (R2-1) signs, indicating speed limits for which posting is required by law, shall be located at the points of change from one speed limit to another.

At the downstream end of the section to which a speed limit applies, a Speed Limit sign showing the next speed limit shall be installed. Additional Speed Limit signs shall be installed beyond major-intersections and at other locations where it is necessary to remind road users of the speed limit that is applicable. Last sentence changed to Guidance

Speed Limit signs indicating the statutory speed limits shall be installed at entrances to the State and, where appropriate, at jurisdictional boundaries in urban areas.

Guidance:

Additional Speed Limit signs should be installed beyond major intersections and at other locations where it is necessary to remind road users of the speed limit that is applicable. Relocated and changed to

Guidance

Support:

In general, the maximum speed limits applicable to rural and urban roads are established:

- A. Statutorily a maximum speed limit applicable to a particular class of road, such as freeways or city streets, that is established by State law; or
- B. As altered speed zones based on engineering studies.

State statutory limits might restrict the maximum speed limit that can be established on a particular road, notwithstanding what an engineering study might indicate.

<u>The "Traffic Control Devices Handbook" contains suggested criteria on the spacing of speed limit signs.</u>
Option:

If a jurisdiction has a policy of installing Speed Limit signs in accordance with statutory requirements only on the streets that enter a city, neighborhood, or residential area to indicate the speed limit that is applicable to the entire city, neighborhood, or residential area unless otherwise posted, a CITYWIDE (R2-5aP), NEIGHBORHOOD (R2-5bP), or RESIDENTIAL (R2-5cP) plaque may be mounted above the Speed Limit sign and an UNLESS OTHERWISE POSTED (R2-5P) plaque may be mounted below the Speed Limit sign (see Figure 2B-3).

Guidance:

A Reduced Speed Limit (W3-5 or W3-5a), Variable Speed Zone (W3-5b), or Truck Speed Zone (W3-5c) Ahead (W3-5 or W3-5a) sign (see Section 2C.3841) should be used to inform road users of a reduced speed zone where the speed limit is being reduced by more than 10 mph, or where engineering judgment indicates the need for advance notice to comply with the posted speed limit ahead.

Option:

If a W3-5b sign is posted to provide notice of a variable speed zone, an END VARIABLE SPEED LIMIT (R2-13) sign (see Figure 2B-3) may be installed at the downstream end of the zone to provide notice to road users of the termination of the speed zone.

Standard:

If a W3-5c sign is posted to provide notice of a truck speed zone, an END TRUCK SPEED LIMIT (R2-14) sign (see Figure 2B-3) shall be installed at the downstream end of the zone to provide notice to road users of the termination of the speed zone.

States and local agencies should conduct engineering studies to reevaluate non-statutory speed limits on segments of their roadways that have undergone significant changes since the last review, such as the addition or elimination of parking or driveways, changes in the number of travel lanes, changes in the configuration of bicycle lanes, changes in traffic control signal coordination, or significant changes in traffic volumes. Moved to earlier in this section.

No more than three speed limits should be displayed on any one Speed Limit sign or assembly. Moved to later in this section

When a speed limit within a speed zone is posted, it should be within 5 mph of the 85th percentile speed of free flowing traffic. Moved to earlier in this section

Speed studies for signalized intersection approaches should be taken outside the influence area of the traffic control signal, which is generally considered to be approximately 1/2 mile, to avoid obtaining skewed results for the 85th percentile speed. Moved to earlier in this section Support:

Advance warning signs and other traffic control devices to attract the motorist's attention to a signalized intersection are usually more effective than a reduced speed limit zone. Moved to later in this section

Guidance:

An advisory speed plaque (see Section 2C.0859) mounted below a warning sign should be used to warn road users of an advisory speed for a roadway condition. A Speed Limit sign should not be used for this situation.

1 Advance traffic control warning signs (see Section 2C.36), advance intersection warning signs (see 2 Section 2C.46), and/or other traffic control devices to attract motorists' attention are appropriate warning prior to a signalized intersection are usually more effective than a reduced speed zone. A speed limit should 3 not be used for this purpose. Changed from Support to Guidance and moved and revised from earlier in 4 5 this Section 6 Option: 7 Other factors that may be considered when establishing or reevaluating speed limits are the following: 8 A. Road characteristics, shoulder condition, grade, alignment, and sight distance; Moved to earlier in 9 this section 10 B. The pace; 11 C. Roadside development and environment; 12 D. Parking practices and pedestrian activity; and E. Reported crash experience for at least a 12-month period. 13 14 Two types of Speed Limit signs may be used: one to designate passenger car speeds, including any 15 nighttime information or minimum speed limit that might apply; and the other to show any special speed limits for trucks and other vehicles. 16 17 Guidance: 18 No more than three speed limits should be displayed on any one Speed Limit sign or assembly. Moved 19 from earlier in this section 20 Option: 21 A changeable message sign variable speed limit sign that changes the speed limit for traffic and ambient conditions may be installed provided that the appropriate speed limit is displayed at the proper times and 22 23 locations in accordance with paragraphs 3, 4, and 6 of this section. 24 **Standard:** 25 The variable speed limit sign legend "SPEED LIMIT" shall be a black legend on a white retroreflective background. 26 The variable speed limit legend shall be displayed in white LEDs on an opaque black 27 28 background. 29 Option: 30 A changeable message sign that displays to approaching drivers the speed at which they are traveling 31 may be installed in conjunction with a Speed Limit sign. 32 Guidance: 33 If a changeable message sign displaying approach speeds is installed, the legend YOUR SPEED XX MPH or such similar legend should be displayed. The color of the changeable message legend should be a yellow 34 35 legend on a black background or the reverse of these colors. 36 Support: 37 See Section 2C.14 for the provisions for the use of a Vehicle Speed Feedback plaque mounted below a Speed Limit Sign that displays to approaching drivers the speed at which they are traveling. 38 39 Advisory Speed signs and plaques are discussed in Sections 2C.0859 and 2C.1412. Temporary Traffic 40 Control Zone Speed signs are discussed in Part 6. The WORK ZONE (G20-5aP) plaque intended for installation above a Speed Limit sign is discussed in Section 6F.126G.08. School Speed Limit signs are 41 discussed in Section 7B.1505. 42 43 Figure 2B-3. Speed Limit and Photo Enforcement 44 Section 2B.142B.22 Truck Vehicle Speed Limit Plaques (R2-2P Series) 45 Standard:

Where a special speed limit applies to trucks or other certain classes of vehicles, the legend TRUCKS XX (R2-2P) plaque, BUSES XX (R2-2aP) plaque, TRUCKS BUSES XX (R2-2bP) plaque, or VEHICLES OVER X TONS XX (R2-2cP) plaque or such similar legend shall be displayed below the legend Speed Limit (R2-1)SPEED LIMIT XX on the same sign or on a separate R2-2P plaque (see Figure 2B-3) below the standard legend, except as provided in Paragraph 2 of this Section.

46

47

48

49

50

1 Option:

The legend of a Vehicle Speed Limit (R2-2P series) plaque may be combined in a single sign and displayed below the SPEED LIMIT XX legend, similar to the Combined Maximum and Minimum Speed Limits (R2-4a) sign (see Section 2B.25).

A different vehicle class legend may be substituted on the R2-2P series plaque -for other classes of vehicles not included in Paragraph 1 of this Section.

Section 2B.152B.23 Night Speed Limit Plaque (R2-3P)

Standard:

Where different speed limits are prescribed for day and night, both limits shall be posted.

10 Guidance:

A Night Speed Limit (R2-3P) plaque (see Figure 2B-3) should be reversed using a white retroreflectorized retroreflective legend and border on a black background.

13 Option:

A Night Speed Limit plaque may be combined with or installed below the standard Speed Limit (R2-1) sign.

Section 2B.162B.24 Minimum Speed Limit Plaque (R2-4P) and Combined Maximum and Minimum Speed Limits (R2-4a) Sign

Standard:

A Minimum Speed Limit (R2-4P) plaque (see Figure 2B-3) shall be displayed only in combination with a Speed Limit sign. Where used, the R2-4P plaque shall be mounted below a Speed Limit (R2-1) sign.

22 Option:

Where engineering judgment determines that slow speeds on a highway might impede the normal and reasonable movement of traffic, the Minimum Speed Limit plaque may be installed below a Speed Limit (R2-1) sign to indicate the minimum legal speed. If desired In lieu of a sign assembly with the R2-1 sign and R2-4P plaque, the Combined Maximum and Minimum Speed Limits (R2-4a) sign may be used and the Minimum Speed Limit plaque may be combined on the R2-4a sign (see Figure 2B-3).

Section 2B.172B.25 Higher Fines Signs and Plaque (R2-6P, R2-10, and R2-11)

Standard Guidance:

If increased fines are imposed for traffic violations within a designated zone of a roadway, a BEGIN HIGHER FINES ZONE (R2-10) sign (see Figure 2B-3) or a FINES HIGHER (R2-6P) plaque (see Figure 2B-3) shall-should be used to provide notice to road users. If used, the FINES HIGHER plaque shall be mounted below an applicable regulatory or warning sign in a temporary traffic control zone, a school zone, or other applicable designated zone.

Last sentence retained as Standard and moved to later in this section

If an R2-10 sign or an R2-6P plaque is posted to provide notice of increased fines for traffic violations, an END HIGHER FINES ZONE (R2-11) sign (see Figure 2B-3) shall should be installed at the downstream end of the zone to provide notice to road users of the termination of the increased fines zone.

Guidance:

If used, tThe BEGIN HIGHER FINES ZONE sign or FINES HIGHER plaque should be located at the beginning of the temporary traffic control zone, school zone, or other applicable designated zone and just beyond any interchanges, major intersections, or other major traffic generators.

Agencies should limit the use of the Higher Fines signs and plaque to locations where work is actually underway, or to locations where the roadway, shoulder, or other conditions, including the presence of a school zone and/or a reduced school speed limit zone, require a speed reduction or extra caution on the part of the road user. This paragraph was moved up from later in the section in order to group all Guidance

47 paragraphs together

Standard:

The Higher Fines signs and plaque shall have a black legend and border on a white rectangular background. All supplemental plaques mounted below the Higher Fines signs and plaque shall have a black legend and border on a white rectangular background.

If used, tThe FINES HIGHER plaque shall be mounted below an applicable regulatory or warning sign in a temporary traffic control zone, a school zone, or other applicable designated zone. Moved from earlier in this section

Option:

1

2

3

4

5 6

7

8

9

10

11

12

13

14

15

16 17

18

19

20

21

Alternate legends such as BEGIN (or END) DOUBLE FINES ZONE may also be used for the R2-10 and R2-11 signs.

The legend FINES HIGHER on the R2-6P plaque may be replaced by FINES DOUBLE (R2-6aP), \$XX FINE (R2-6bP), or another legend appropriate to the specific regulation (see Figure 2B-3).

The following may be mounted below an R2-10 sign or R2-6P plaque:

- A. A supplemental plaque specifying the times that the higher fines are in effect (similar to the S4-1P plaque shown in Figure 7B-1), or
- B. A supplemental plaque WHEN CHILDREN (WORKERS) ARE PRESENT, or
- C. A supplemental plaque WHEN FLASHING (similar to the S4-4P plaque shown in Figure 7B-1) if used in conjunction with a yellow flashing beacon.

Support:

Section 6F.126G.08 contains information regarding other signs and plaques associated with increased fines for traffic violations in temporary traffic control zones. Section 7B.10 contains information regarding other signs and plaques associated with increased fines for traffic violations in designated school zones.

 Section 2B.182B.26 Movement Prohibition Signs (R3-1 through R3-4, R3-18, and R3-27)

Standard:

Except as provided in Paragraphs 11 and 13, where specific movements are prohibited, Movement Prohibition signs shall be installed. Movement Prohibition signs shall be installed where specific movements are prohibited at an intersection approach except as provided in Paragraphs 13 and 17 of this Section.

Guidance:

Movement Prohibition signs should only be used to prohibit a turn or through movement from an entire approach and should not be used to designate movements that are required or permitted from a specific lane or lanes on a multi-lane approach.

Movement Prohibition signs should be placed where they will be most easily seen by road users who might be intending to make the movement.

If No Right Turn (R3-1) signs (see Figure 2B-4) are used, at least one should be placed either over the roadway or at a right-hand corner of the intersection.

If No Left Turn (R3-2) signs (see Figure 2B-4) are used, at least one should be placed over the roadway, at the far left-hand corner of the intersection, on a median, or in conjunction with the STOP sign or YIELD sign located on the near right-hand corner.

Except as provided in Item C of Paragraph 9 for signalized locations, if NO TURNS (R3-3) signs (see Figure 2B-4) are used, two signs should be used, one at a location specified for a No Right Turn sign and one at a location specified for a No Left Turn sign.

If No U-Turn (R3-4) signs (see Figure 2B-4) or combination No U-Turn/No Left Turn (R3-18) signs (see Figure 2B-4) are used, at least one should be used at a location specified for No Left Turn signs.

Option:

If both left turns and U-turns are prohibited, the combination No U-Turn/No Left Turn (R3-18) sign (see Figure 2B-4) may be used instead of separate R3-2 and R3-4 signs.

Support:

Sections 2B.19, 2B.20, 2B.21 and 2B.22 contain information regarding lane control signs that indicate the required or permitted movements from individual lanes.

Guidance:

If No Straight Through (R3-27) signs (see Figure 2B-4) are used, at least one should be placed either over the roadway or at a location where it can be seen by road users who might be intending to travel straight through the intersection.

If turn prohibition signs are installed in conjunction with traffic control signals:

- A. The No Right Turn sign should be installed adjacent to a signal face viewed by road users in the right-hand lane.
- B. The No Left Turn (or No U-Turn or combination No U-Turn/No Left Turn) sign should be installed adjacent to a signal face viewed by road users in the left-hand lane.
- C. A NO TURNS sign should be placed adjacent to a signal face viewed by all road users on that approach, or two signs should be used.

Option:

If turn prohibition signs are installed in conjunction with traffic control signals, an additional Movement Prohibition sign may be post-mounted to supplement the sign mounted overhead.

Where ONE WAY signs are used (see Section 2B.4051), No Left Turn and No Right Turn signs may be omitted.

When the movement restriction applies during certain time periods only, the following Movement Prohibition signing alternatives may be used and are listed in order of preference:

A. Changeable message signs A blank-out part-time display regulatory sign that displays the prohibited movement only during the time that the movement prohibition is applicable, especially at signalized intersections.

- B. Permanently mounted signs incorporating a supplementary legend showing the hours and days during which the prohibition is applicable. (See Figure 2B-4)
- C. Portable signs, installed by proper authority, located off the roadway at each corner of the intersection. The portable signs are only to be used during the time that the movement prohibition is applicable.

Where the movement restriction applies to certain vehicle classes, permanently mounted signs incorporating a supplementary legend showing the vehicle class restriction (R3-1b through R3-1d) or exception (R3-1e and R3-1f) may be used (See Figure 2B-4).

Standard:

The blank-out part-time electronic-display Movement Prohibition sign shall consist of a red circle and diagonal with a white prohibited movement on an opaque black background.

Option:

Movement Prohibition signs may be omitted at a ramp entrance to an expressway or a channelized intersection where the design is such as to indicate clearly the one-way traffic movement on the ramp or turning lane.

Standard:

The No Left Turn (R3-2) sign, the No U-Turn (R3-4) sign, and the combination No U-Turn/No Left Turn (R3-18) sign shall not be used at approaches to roundabouts to prohibit drivers from turning left onto the circulatory roadway of a roundabout.

Support:

At roundabouts, the use of R3-2, R3-4, or R3-18 signs to prohibit left turns onto the circulatory roadway might confuse drivers about the possible legal turning movements around the roundabout. Roundabout

Directional Arrow (R6-4 series) signs (see Section 2B.4354) and/or ONE WAY (R6-1R or R6-2R) and/or

One-Direction Large Arrow (See Section 2C.10) signs are the appropriate signs to indicate the travel direction within a roundabout.

Figure 2B-4. Movement Prohibition and Lane Control Signs and Plaques

Section 2B.192B.27 <u>Intersection Lane Control Signs (R3-5 through R3-8)</u>

Standard:

Intersection Lane Control signs, if used, shall require road users in certain lanes to turn, shall permit turns from a lane where such turns would otherwise not be permitted, shall require a road user to stay in the same lane and proceed straight through an intersection, or shall indicate permitted movements from a lane.

Support: Changed from Standard to Support

Intersection Lane Control signs (see Figure 2B-4) shall have three applications:

- A. Mandatory Movement Lane Control (R3-5, R3-5a, and R3-7) signs,
- B. Optional Movement Lane Control (R3-6) sign, and
- C. Advance Intersection Lane Control (R3-8 series) signs.

Guidance:

When Intersection Lane Control signs are mounted overhead, each sign <u>used</u> should be placed over the lane or a projection of the lane to which it applies. Modified to correspond with change in Standard below to a Guidance

On signalized approaches where through lanes that become mandatory turn lanes, multiple-lane turns that include shared lanes for through and turning movements, or other lane-use regulations are present that would be unexpected by unfamiliar road users, overhead lane control signs should be installed at the signalized location over the appropriate lanes or projections thereof and in advance of the intersection over the appropriate lanes.

Where overhead mounting on the approach is impractical for the advance and/or intersection lane-use signs, one of the following alternatives should be employed:

A. At locations where through lanes become mandatory turn lanes, a mandatory movement lane control (R3-7) sign should be post-mounted on the left-hand side of the roadway where a through lane is becoming a mandatory left-turn lane on a one-way street or where a median of sufficient width for the Notice of Proposed Amendments – Part 2

Page 82 of 781

December 2020

- signs is available, or on the right-hand side of the roadway where a through lane is becoming a mandatory right-turn lane.
- B. At locations where a through lane is becoming a mandatory left-turn lane on a two-way street where a median of sufficient width for the signs is not available, and at locations where multiple-lane turns that include shared lanes for through and turning movements are present, an Advance Intersection Lane Control (R3-8 series) sign should be post-mounted in a prominent location in advance of the intersection, and consideration should be given to the use of an oversized version in accordance with Table 2B-1.

Standard: Changed to a Guidance to allow more flexibility

Use of an overhead sign for one approach lane <u>shall should</u> not require installation of overhead signs for the other lanes of that approach.

Option:

 Where the number of through lanes on an approach is two or less, the Intersection Lane Control signs-(R3-5, R3-6, or R3-8) may be overhead or post-mounted.

Intersection Lane Control signs may be omitted where:

- A. A turn bay has been provided by physical construction or pavement markings, and
- B. Only the road users using such turn bays are permitted to make a turn in that direction.

At roundabouts, Intersection Lane Control (R3-5, R3-6, and R3-8 series) signs may display any of the arrow symbol options shown in Figure 2B-51.

Figure 2B-5. Intersection Lane Control Sign Arrow Options for Roundabouts

Section 2B.202B.28 Mandatory Movement Lane Control Signs (R3-5, R3-5a, R3-7, R3-19 Series, and R3-20)

Standard:

If used, the-Mandatory Movement Lane Control (R3-5, R3-5a, and R3-7) signs, if used, sign (see Figure 2B-4) shall indicate only the single vehicle movement that is required from the lane. If used, the Mandatory Movement Lane Control sign shall be located in advance of the intersection, such as near the upstream end of the mandatory movement lane, and/or at the intersection where the regulation applies. When the mandatory movement applies to lanes exclusively designated for HOV traffic, the R3-5cP supplemental plaque shall be used. When the mandatory movement applies to lanes that are not HOV facilities, but are lanes exclusively designated for buses and/or taxis, the word message R3-5dP and/or R3-5gP supplemental plaques shall be used. Changed 2nd sentence to a Guidance, since it provides flexibility as to where to place the Mandatory Movement Lane Control sign

The Mandatory Movement Lane Control (R3-7) sign shall include the legend RIGHT (LEFT) LANE MUST TURN RIGHT (LEFT). The Mandatory Movement Lane Control (R3-5 and R3-5a) symbol signs shall include the legend ONLY.

The R3-7 word message sign shall be for post-mounting only. The R3-7 sign shall not be mounted at the far side of the intersection:

Where the number of lanes available to through traffic on an approach is three or more, Mandatory Movement Lane Control (R3-5 and R3-5a) symbol signs, if used, shall be mounted overhead over the specific lanes to which they apply (see Section 2B.1929).

Guidance:

If used, the Mandatory Movement Lane Control sign shall should be located in advance of the intersection, such as near the upstream end of the mandatory movement lane, and/or at the intersection where the regulation applies. This sentence was changed from a Standard (in paragraph 1) to a Guidance, since it provides flexibility as to where to place the Mandatory Movement Lane Control sign

If the R3-5 or R3-5a sign is post-mounted on an approach with two or fewer through lanes, a supplemental plaque (see Figure 2B-4), such as LEFT LANE (R3-5bP), HOV 2+ (R3-5cP), TAXI LANE (R3-5dP), CENTER LANE (R3-5eP), RIGHT LANE (R3-5fP), BUS LANE (R3-5gP), or BOTH LANES, should be added above the sign to indicate the specific lane to which the mandatory movement applies. If Mandatory Lane Movement Control (R3-5) symbol signs with supplemental R3-5bP or R3-5fP plaques are used, they should be mounted adjacent to and along only the full width portion of the turn lane.

The use of the Mandatory Movement Lane Control (R3-7) word message sign should be limited to only locations that are adjacent to the full-width portion of a mandatory turn lane. The R3-7 sign should not be installed adjacent to a through lane in advance of a turn bay taper or adjacent to a turn bay taper.

Mandatory Movement Lane Control signs should be accompanied by lane-use arrow markings, especially where traffic volumes are high, where there is a high percentage of commercial vehicles, or where other distractions exist.

Where the restriction does not apply to buses or bicycles an EXCEPT BUSES (R3-7aP) or EXCEPT BICYCLES (R3-7bP) plaque should be used.

Option:

The Straight Through Only (R3-5a) sign may be used to require a road user in a particular lane to proceed straight through an intersection.

When the Mandatory Movement Lane Control sign for a left turn lane is installed back to back with a Keep Right (R4-7) sign, the dimensions of the Mandatory Movement Lane Control (R3-5) sign may be the same as the Keep Right sign.

The diamond symbol may be used instead of the word message HOV on the R3-5cP supplemental plaque.

A LANE FOR LEFT TURN ONLY (R3-19) sign may be used where a mandatory left turn lane is added at a median location and may be post-mounted on the median at the beginning of the taper. Where a U turn is also allowed from a LANE FOR U AND LEFT TURNS ONLY (R3-19a) may be used. Where a R3-19 series sign is used, Mandatory Movement Lane Control signs along the turn lane in the median may be omitted.

The R3-19 series signs may be used where the added median turn lane is separated from the through lanes by a channelizing or divisional island.

TheOn a conventional road where a shoulder that is open to part-time travel (see Chapter 2G) becomes a mandatory turn lane, the BEGIN RIGHT TURN LANE (R3-20R) sign (see Figure 2B-4) may be post-mounted on the right-hand side of the roadway at the upstream end of the turn lane taper of a mandatory right-turn lane. Where the shoulder is on the left-hand side of the roadway, the BEGIN LEFT TURN LANE (R3-20L) sign (see Figure 2B-4) may be post-mounted on a median (or on the left-hand side of the roadway for a one-way street) at the upstream end of the turn lane taper of a mandatory left-turn lane.

Guidance:

Where the transition from a paved shoulder to a mandatory turn lane might not be apparent and traffic regularly enters the shoulder to access the turn lane, a DO NOT DRIVE ON SHOULDER (R4-17) sign (see Section 2B.36) should be used to supplement the standard Mandatory Movement Lane Control (R3-5 series and/or R3-7) signs.

Section 2B.212B.29 Optional Movement Lane Control Sign (R3-6 Series)

Standard:

If used, the Optional Movement Lane Control (R3-6, R3-6a and R3-6ab) signs, if used, (see Figure 2B-4) shall be used for two or more movements from a specific lane or to emphasize permitted movements. The Optional Movement Lane Control sign shall be mounted overhead over the specific lane to which it applies. Relocated from below If used, the Optional Movement Lane Control sign shall be located in advance of the intersection, such as near the upstream end of an adjacent mandatory movement lane, and/or at the intersection where the regulation applies. Changed 2nd sentence to a Guidance, since it provides flexibility as to where to place the Optional Movement Lane Control sign

If used, the Optional Movement Lane Control signs shall indicate all permissible movements from specific lanes.

Because more than one movement is permitted from the lane, the word message ONLY shall not be used on an Optional Movement Lane Control sign. Relocated from below

Optional Movement Lane Control signs shall be used for two or more movements from a specific lane where a movement, not not normally allowed by State statute or local ordinance, is permitted.

The Optional Movement Lane Control signs shall not be used alone to effect a turn prohibition.

Where the number of lanes available to through traffic on an approach is three or more, an Optional Movement Lane Control (R3-6) sign, if used, shall be mounted overhead over the specific lane to which it applies (see Section 2B.19). Moved above and revised

Guidance:

If used, the Optional Movement Lane Control sign shall-should be located overhead in advance of the intersection, such as near the upstream end of an adjacent mandatory movement lane, and/or overhead at the intersection where the regulation applies. This sentence was changed from a Standard (in paragraph 1) to a Guidance, since it provides flexibility as to where to place the Optional Movement Lane Control sign

If the Optional Movement Lane Control sign is post-mounted on an approach with two or fewer through lanes, a supplemental plaque (see Figure 2B-4), such as LEFT LANE (R3-5bP), HOV 2+ (R3-5cP), TAXI-LANE (R3-5dP), CENTER LANE (R3-5eP), RIGHT LANE (R3-5fP), or BUS LANE (R3-5gP), should be added above the R3-6 sign to indicate the specific lane from which the optional movements can be made.

Option:

The word message OK may be used within the border in combination with the arrow symbols of the R3-6-sign.

Standard: Relocated to above

Because more than one movement is permitted from the lane, the word message ONLY shall not be used on an Optional Movement Lane Control sign.

Section 2B.222B.30 Advance Intersection Lane Control Signs (R3-8 Series)

Option:

Advance Intersection Lane Control (R3-8, R3-8a, and R3-8b) signs (see Figure 2B-4) may be used to indicate the configuration of all lanes ahead.

The word messages ONLY, OK, THRU, ALL, or HOV 2+, TAXI, BUS, or BIKE, or the bicycle symbol, may be used within the border in combination with the arrow symbols of the R3-8 sign series. The HOV 2+, (R3-5cP, R3-5dP and R3-5gP)—supplemental plaques may be installed at the top outside border of the R3-8 sign over the applicable lane designation on the sign. The diamond symbol may be used instead of the word message HOV. The minimum allowable vehicle occupancy requirement may vary based on the level established for a particular facility.

Where a bicycle lane is between two general purpose lanes the R3-8 series signs may be modified to show the bicycle lane with a white legend on a black background in accordance with designs of the R3-8x series signs. (See Figure 2B-4).

Guidance:

If used When used, an Advance Intersection Lane Control sign should be placed at an adequate distance in advance of the intersection, either along the lane tapers or at the beginning of the turn lane so that road users can select the appropriate lane (see Figures 2A-4 and 2A-5 a and b). If used, the Advance Intersection Lane Control sign should be installed either in advance of the tapers or at the beginning of the turn lane.

Option:

An Advance Intersection Lane Control sign may be repeated closer to the intersection <u>along the approach</u> for additional emphasis.

Standard:

An Advance Intersection Lane Control (R3-8 series) sign shall not be mounted at the far side of an intersection to which it applies.

Where three or more approach lanes are available to traffic, Advance Intersection Lane Control (R3-8 series) signs, if used, shall be post-mounted in advance of the intersection and shall not be mounted overhead (see Section 2B.1929).

When only the two outermost lanes of the roadway are shown on a R3-8 sign, the R3-5bP and R3-5fP shall be mounted above.

Section 2B.232B.31 RIGHT (LEFT) LANE MUST EXIT Signs (R3-33, R3-33a)

46 Option:

A RIGHT (LEFT) LANE MUST EXIT (R3-33) sign (see Figure 2B-4) may be used to supplement an overhead EXIT ONLY guide sign to inform road users that traffic in the right-hand (left-hand) lane of a roadway that is approaching a grade-separated interchange is required to depart the roadway on the exit ramp at the next interchange.

1 The R3-33a sign may be used in place of the R3-33 sign where the roadside width is limited and will not accommodate the R3-33 sign.

Support:

Section 2C.4350 contains information regarding a warning sign that can be used in advance of lane drops at grade-separated interchanges.

Section 2B.242B.32 Two-Way Left Turn Only Signs (R3-9a, R3-9b)

Guidance:

Two-Way Left Turn Only (R3-9a or R3-9b) signs (see Figure 2B-6) should be used in conjunction with the required pavement markings where a non-reversible lane is reserved for the exclusive use of left-turning vehicles in either direction and is not used for passing, overtaking, or through travel.

Option:

The post-mounted R3-9b sign may be used as an alternate to or a supplement to the overhead R3-9a sign. The legend BEGIN or END may be used within the border of the main sign itself, or on an R3-9cP or R3-9dP plaque (see Figure 2B-6) mounted immediately above it.

15 Support:

Signing is especially helpful to drivers in areas where the two-way left turn only maneuver is new, in areas subject to environmental conditions that frequently obscure the pavement markings, and on peripheral streets with two-way left turn only lanes leading to an extensive system of routes with two-way left turn only lanes.

Section 2B.252B.33 BEGIN and END Plaques (R3-9cP, R3-9dP)

21 Option:

The BEGIN (R3-9cP) or END (R3-9dP) plaque (see Figure 2B-6), mounted directly above a regulatory sign, may be used to supplement a regulatory sign to inform road users of the location where a regulatory condition begins or ends.

Standard:

If used, the BEGIN or END plaque shall be mounted directly above a regulatory sign. Incorporated into Option statement, because it does not warrant a Standard

Section 2B.262B.34 Reversible Lane Control Signs (R3-9e through R3-9i)

Option:

A reversible lane may be used for through traffic (with left turns either permitted or prohibited) in alternating directions during different periods of the day, and the lane may be used for exclusive left turns in one or both directions during other periods of the day as well. Reversible Lane Control (R3-9e through R3-9i) signs (see Figure 2B-6) may be either static type or changeable message type. (See Chapter 4T for lane use control signals for reversible lanes). These signs may be either post-mounted or overhead.

Figure 2B-6. Center and Reversible Lane Control Signs and Plaques

Standard: Order of paragraphs reversed

Where it is determined by an engineering study that lane-use control signals or physical barriers are not necessary, the lane shall be controlled by overhead Reversible Lane Control signs (see Figure 2B-3).

Post-mounted Reversible Lane Control signs shall be used only as a supplement to overhead signs or signals. Post-mounted signs shall be identical in design to the overhead signs and an additional legend such as CENTER LANE shall be added to the top of the sign (R3-9f) to indicate which lane is controlled. For both word messages and symbols, this legend shall be at the top of the sign. Edited for clarity

Where it is determined by an engineering study that lane-use control signals or physical barriers are not necessary, the lane shall be controlled by overhead Reversible Lane Control signs (see Figure 2B-7).

Figure 2B-7. Location of Reversible Two-Way Left-Turn Signs

Option:

Reversing traffic flow may be controlled with pavement markings and Reversible Lane Control signs (without the use of lane control signals), when all of the following conditions are met:

- A. Only one lane is being reversed,
- B. An engineering study indicates that the use of Reversible Lane Control signs alone would result in an acceptable level of safety and efficiency, and
- C. There are no unusual or complex operations in the reversible lane pattern.

Standard:

Reversible Lane Control signs shall contain the legend or symbols designating the allowable uses of the lane and the time periods such uses are allowed. Where symbols and legends are used, their meanings shall be as shown in Table-2B-2.

Reversible Lane Control signs shall consist of a white background with a black legend and border, except for the R3-9e sign, where the color red is used.

Symbol signs, such as the R3-9e sign, shall consist of the appropriate symbol in the upper portion of the sign with the appropriate times of the day and days of the week below it. All times of the day and days of the week shall be accounted for on the sign to eliminate confusion to the road user.

In situations where more than one message is conveyed to the road user, such as on the R3-9e sign, the sign legend shall be arranged as follows:

- A. The prohibition or restriction message is the primary legend and shall be on the top for word message signs and to the far left for symbol signs,
- B. The permissive use message shall be displayed as the second legend, and
- C. The OTHER TIMES message shall be displayed at the bottom for word message signs and to the far right for symbol signs.

Table 2B-2. Meanings of Symbols and Legends on Reversible Lane Control Signs

Option:

The symbol signs may also include a downward pointing arrow with the legend THIS LANE. The term OTHER TIMES may be used for either the symbol or word message sign.

Standard:

A Reversible Lane Control sign shall be mounted over the <u>approximate</u> center of the lane that is being reversed and shall be perpendicular to the roadway alignment.

If the vertical or horizontal alignment is curved to the degree that a driver would be unable to see at least one sign, and preferably two signs, then additional overhead signs shall be installed. The placement of the signs shall be such that the driver will have a definite indication of the lanes specifically reserved for use at any given time. Special consideration shall be given to major generators introducing traffic between the normal sign placement.

Transitions at the entry to and exit from a section of roadway with reversible lanes shall be carefully reviewed, and include advance signs shall be installed to notify or warn drivers of the boundaries of the reversible lane controls. The R3-9g or R3-9h signs shall be used for this purpose.

Option:

More than one sign may be used at the termination of the reversible lane to emphasize the importance of the message (R3-9i).

Where longitudinal barriers separate opposing directions of traffic, the R3-9g or R3-9h signs may be omitted.

Standard:

Flashing beacons, if used to <u>accentuate supplement</u> the overhead Reversible Lane Control signs, shall comply with the applicable requirements for flashing beacons in Chapter-4L4S.

When used in conjunction with Reversible Lane Control signs, the Turn Prohibition signs (R3-1 to R3-4, R3-18) shall be mounted overhead and separate from the Reversible Lane Control signs. The Turn Prohibition signs shall be designed and installed in accordance with Section 2B.1828.

Guidance:

For additional emphasis, a supplemental plaque stating the distance of the prohibition, such as NEXT 1 MILE, should be added to the Turn Prohibition signs that are used in conjunction with Reversible Lane Control signs.

If used, overhead signs should be located at intervals not greater than 1/4 mile. The bottom of the overhead Reversible Lane Control signs should not be more than 19 feet above the pavement grade.

Where more than one sign is used at the termination of a reversible lane, they should be at least 250 feet apart. Longer distances between signs are appropriate for streets with speeds over 35 mph, but the separation should not exceed 1,000 feet.

Because left-turning vehicles have a significant impact on the safety and efficiency of a reversible lane operation, if an exclusive left-turn lane or two-way left-turn lane cannot be incorporated into the lane-use pattern for a particular peak or off-peak period, consideration should be given to prohibiting left turns and U-turns during that time period.

Reversible Lane Control signs and parking signs should be consistent in message during the same operational periods.

Section 2B.272B.35 Jughandle Signs (R3-23, R3-24, R3-25, and R3-26 Series)

Support:

 A jughandle turn is a left-turn or U-turn that because of special geometry is made by initially making a right turn. This type of turn can increase the operational efficiency of a roadway by eliminating the need for exclusive left-turn lanes and can increase the operational efficiency of a traffic control signal by eliminating the need for protected left-turn phases. A jughandle turn can also provide an opportunity for trucks and commercial vehicles to make a U-turn where the median and roadway are not of sufficient width to accommodate a traditional U-turn by these vehicles.

Figure 2B-8 shows the various signs that can be used for signing jughandle turns. Figure 2B-9 shows examples of regulatory and destination guide signing for various types of jughandle turns.

Standard:

On multi-lane roadways, since road users generally anticipate that they need to be in the left-hand lane when approaching a location where they desire to turn left or make a U-turn, an ALL TURNS FROM RIGHT LANE (R3-23) or a U TURN FROM RIGHT LANE (R3-23a) sign (see Figure 2B-95) shall be installed in advance of the location to inform drivers that left turns and/or U-turns will be made from the right-hand lane.

Option:

Where a median of sufficient width is available, supplemental regulatory or guide signs may also be placed on the left-hand side of the roadway.

Standard:

An R3-24 series sign with an upward diagonal arrow pointing to the right if the jughandle entrance is designed as an exit ramp (see Drawings A and B of Figure 2B-9) or an R3-25 series sign with a horizontal arrow pointing to the right if the jughandle entrance is designed as an intersection shall be installed on the right-hand side of the roadway at the entrance to the jughandle. The legend on the sign shall be ALL TURNS, U TURN, or U AND LEFT TURNS, as appropriate.

If the jughandle is designed such that the jughandle entrance is downstream of the location where the turn would normally have been made (see Drawing C of Figure 2B-9), an R3-26 series sign with an arrow pointing straight upward shall be installed on the right-hand side of the roadway at the intersection to inform road users that they need to proceed straight through the intersection in order to make a left turn or U-turn. The legend on the sign shall be U TURN or U AND LEFT TURNS, as appropriate.

Support:

The R3-24, R3-25, and R3-26 series of signs are designed to be mounted below conventional guide signs.

Section 2C.1412 contains information regarding the use of advisory exit and ramp speed signs for exit ramps.

Section 2D.39 contains information regarding the use of guide signs for jughandles.

1	Figure 2B-8. Jughandle Regulatory Signs
2	Figure 2B-9. Examples of Applications of Jughandle Regulatory and Guide Signing
3	

5 6

7

8

9

11

12

15

16

17

18

20 21

22

24

25

26

28

29

31

32

33

34

37

38

39

41 42

43 44

45

47

48

2 Section <u>2B.282B.36</u> <u>DO NOT PASS Sign (R4-1)</u>

Option:

The DO NOT PASS (R4-1) sign (see Figure 2B-10) may be used in addition to pavement markings (see Section 3B.0203) to emphasize the restriction on passing. The DO NOT PASS sign may be used at the beginning of, and at intervals within, a zone through which sight distance is restricted or where other conditions make overtaking and passing inappropriate.

If signing is needed on the left-hand side of the roadway for additional emphasis, NO PASSING ZONE (W14-3) signs may be used (see Section $2C.4\frac{5}{0.5}$.

10 Support:

Standards for determining the location and extent of no-passing zone pavement markings are set forth in Section 3B.0203.

13 Section 2B.292B.37 PASS WITH CARE Sign (R4-2)

14 Guidance:

The PASS WITH CARE (R4-2) sign (see Figure 2B-10) should be installed at the downstream end of a nopassing zone if a DO NOT PASS sign has been installed at the upstream end of the zone.

Section 2B.302B.38 KEEP RIGHT EXCEPT TO PASS Sign (R4-16) and SLOWER TRAFFIC KEEP RIGHT Sign (R4-3)

19 Option:

The KEEP RIGHT EXCEPT TO PASS (R4-16) sign (see Figure 2B-10) may be used on multi-lane roadways where there are two lanes in one direction of travel to direct drivers to stay in the right-hand lane except when they are passing another vehicle.

23 Guidance:

If used, the KEEP RIGHT EXCEPT TO PASS sign should be installed just beyond the beginning of a multitwo-lane section of roadway and at selected locations along multitwo-lane roadways for additional emphasis.

27 Option:

The SLOWER TRAFFIC KEEP RIGHT (R4-3) sign (see Figure 2B-10) may be used on multi-lane roadways to reduce unnecessary lane changing.

30 Guidance:

If used, the SLOWER TRAFFIC KEEP RIGHT sign should be installed just beyond the beginning of a multi-lane pavement, and at selected locations where there is a tendency on the part of some road users to drive in the left-hand lane (or lanes) below the normal speed of traffic. This sign should not be used on the approach to an interchange or through an interchange area.

35 Section 2B.312B.39 TRUCKS USE RIGHT LANE Sign (R4-5)

36 Guidance:

If an extra lane has been provided for trucks and other slow-moving traffic, a SLOWER TRAFFIC KEEP RIGHT (R4-3) sign (see Figure 2B-10), TRUCKS USE RIGHT LANE (R4-5) sign (see Figure 2B-10), or other appropriate sign should be installed at the beginning of the lane.

40 Option:

The SLOWER TRAFFIC KEEP RIGHT sign may be used as a supplement or as an alternative to the TRUCKS USE RIGHT LANE sign. Both signs may be used on multi-lane roadways to improve capacity and reduce lane changing.

The TRUCKS USE RIGHT LANE (R4-5) sign may be used on multi-lane roadways to reduce unnecessary lane changing.

46 Guidance:

If an extra lane has been provided for trucks and other slow-moving traffic, a Lane Ends sign (see Section 2C.4249) should be installed in advance of the point where the extra lane ends. Appropriate pavement

1 markings should be installed at both the upstream and downstream ends of the extra lane (see Section 3B.0912 and Figure 3B-13).

3 Support:

Section 2D.51 contains information regarding advance information signs for extra lanes that have been provided for trucks and other slow-moving traffic.

Section 2B.322B.40 Keep Right and Keep Left Signs (R4-7 Series, R4-8 Series)

Option:

6

7

8

9 10

11

12

13

14

15

16 17

18

19

20

2122

23

24

25

2627

28

29

30

31

32 33

34

35

36

37

38 39

40

41 42

43

44

46

47

The Keep Right (R4-7) sign (see Figure 2B-10) may be used at locations where it is necessary for traffic to pass only to the right-hand side of a roadway feature or obstruction. The Keep Left (R4-8) sign (see Figure 2B-10) may be used at locations where it is necessary for traffic to pass only to the left-hand side of a roadway feature or obstruction.

Guidance:

At locations where it is not readily apparent that traffic is required to keep to the right, a Keep Right sign should be used.

If used, the Keep Right sign should be installed as close as practical to approach ends of raised medians, parkways, islands, and underpass piers. The sign should be mounted on the face of or just in front of a pier or other obstruction separating opposite directions of traffic in the center of the highway such that traffic will have to pass to the right-hand side of the sign.

Where the approach end of the island channelizes traffic away from the approach direction, such as on a loop ramp, the word legend (R4-7a, R4-7b, R4-8a, or R4-8b) signs should be used instead of the symbol (R4-7 or R4-8) signs to emphasize the degree of curvature away from the approach direction (see Figure 2B-11).

Figure 2B-10. Passing, Keep Right, and Slow Traffic Signs

Figure 2B-11. Examples of Keep Right and Keep Left Sign Placement

Standard:

The Keep Right <u>(Left)</u> sign shall not be installed on the right-hand <u>(left-hand)</u> side of the roadway in a position where traffic must pass to the left-hand <u>(right-hand)</u> side of the sign.

Option:

The Keep Right sign may be omitted at intermediate ends of divisional islands and medians.

Word message KEEP RIGHT (LEFT) with an arrow (R4-7a or R4-7b) signs (see Figure 2B-10) may be used instead of the R4-7 or R4-8 symbol signs.

Where the obstruction obscures the Keep Right sign, the minimum placement height may be increased for better sign visibility. Unnecessary, already addressed in Chapter 2A

A narrow Keep Right (R4-7c) sign (see Figure 2B-10) may be installed on the approach end of a median island that is less than 4 feet wide at the point where the sign is to be located.

Standard:

A narrow Keep Right (R4-7c) sign shall not be installed on a median island that has a width of 4 feet or more at the point where the sign is to be located.

Option:

The Keep Right sign may be installed in the median of a divided highway crossing that functions as a single intersection such that it is visible to traffic on the divided highway and angled as needed toward the applicable crossroad approach as shown in Figure 2B-18.

Support:

Section 2B.40 provides more information about the use of the Keep Right sign in combination with or in lieu of ONE-WAY signs at divided highway crossings.

45 **Standard:**

If Keep Right signs are installed, they shall be placed as close as practical to the approach ends of the medians and shall be visible to traffic on the divided highway and angled toward the applicable crossroad approach as shown in Figure 2B-18.

5

7

8

13

15

16

17

19

20

21

22

2324

25

27

28

29

30

31

32

33

34

40

41

42

43

3 Option:

A STAY IN LANE (R4-9) sign (see Figure 2B-10) may be used on multi-lane highways to direct road users to stay in their lane until conditions permit shifting to another lane.

6 Guidance:

If a STAY IN LANE sign is used, it should be accompanied by a solid double white lane line(s) to prohibit lane changing.

9 Section 2B.342B.42 RUNAWAY VEHICLES ONLY Sign (R4-10)

10 Guidance:

11 A RUNAWAY VEHICLES ONLY (R4-10) sign (see Figure 2B-10) should be installed near a truck escape 12 (or runaway truck) ramp entrance to discourage other road users from entering the ramp.

Section 2B.352B.43 Slow Vehicle Turn-Out Signs (R4-12, R4-13, and R4-14)

14 Support:

On two-lane highways in areas where traffic volumes and/or vertical or horizontal curvature make passing difficult, turn-out areas are sometimes provided for the purpose of giving a group of faster vehicles an opportunity to pass a slow-moving vehicle.

18 Option:

A SLOW VEHICLES WITH XX OR MORE FOLLOWING VEHICLES MUST USE TURN-OUT (R4-12) sign (see Figure 2B-10) may be installed in advance of a turn-out area to inform drivers who are driving so slow that they have accumulated a specific number of vehicles behind them that they are required by the traffic laws of that State to use the turn-out to allow the vehicles following them to pass.

Support

The specific number of vehicles displayed on the R4-12 sign provides law enforcement personnel with the information they need to enforce this regulation.

26 Option:

If an R4-12 sign has been installed in advance of a turn-out area, a SLOW VEHICLES MUST USE TURN-OUT AHEAD (R4-13) sign (see Figure 2B-10) may also be installed downstream from the R4-12 sign, but upstream from the turn-out area, to remind slow drivers that they are required to use a turn-out that is a short distance ahead.

Standard:

If an R4-12 sign has been installed in advance of a turn-out area, a SLOW VEHICLES MUST TURN OUT (with arrow) (R4-14) sign (see Figure 2B-10) shall be installed at the entry point of the turn-out area.

35 Support:

36 Section 2D.52 contains information regarding advance information signs for slow vehicle turn-out areas.

Section 2B.362B.44 DO NOT DRIVE ON SHOULDER Sign (R4-17) and DO NOT PASS ON SHOULDER Sign (R4-18)

39 Option:

The DO NOT DRIVE ON SHOULDER (R4-17) sign (see Figure 2B-10) may be installed to inform road users that using the shoulder of a roadway as a travel lane is prohibited.

The DO NOT PASS ON SHOULDER (R4-18) sign (see Figure 2B-10) may be installed to inform road users that using the shoulder of a roadway to pass other vehicles is prohibited.

44 Section 2B.45 ALL TRAFFIC Sign (R4-20) and RIGHT (LEFT) TURN ONLY Sign (R4-21)

45 Option:

1	The ALL TRAFFIC (R4-20) sign may be used at an intersection where all traffic on the approach to the
2	intersection must turn in the direction indicated and the Movement Prohibition (see Section 2B.28) and/or One
3	Way (see Section 2B.51) signs do not adequately convey the allowable direction of travel.
4	The RIGHT (LEFT) TURN ONLY (R4-21) sign may be used at or on an approach to an intersection
5	where all traffic on that approach must turn in the direction indicated.
6	Guidance:
7	The RIGHT (LEFT) TURN ONLY sign should not be used for a channelized turn lane separated from the
8	adjacent travel lanes by an island.
9	Standard:
10	The ALL TRAFFIC sign shall not be used to substitute for the Keep Right (R4-7 series) or Keep
11	<u>Left (R4-8 series) signs.</u>
12	The RIGHT (LEFT) TURN ONLY sign shall not be used to substitute for the Mandatory
13	Movement Lane Control signs (see Sections 2B.29 and 2B.30).

distance from the intersection so as to be clearly visible to all road users turning into the roadway that has the exclusion. The NO PEDESTRIANS (R5-10c) or No Pedestrian Crossing (R9-3) sign (see Section 2B.512B.61) should be installed so as to be clearly visible to pedestrians who are at a location where an alternative route is available.

Option:

43

44

45

46

47

48

49

The NO PEDESTRIANS (R5-10c) or No Pedestrian Crossing (R9-3) sign may also be used at underpasses or elsewhere where pedestrian facilities are not provided.

The NO TRUCKS (R5-2a) word message sign may be used as an alternate to the No Trucks (R5-2) symbol sign.

1 2 3 4	The NO THRU TRAFFIC (R5-12) or NO THRU TRUCKS (R5-2b) signs may be used at locations to prohibit through traffic from using a particular roadway or facility. The EXCEPT LOCAL DELIVERIES (R5-2aP) plaque may be mounted below the R5-2 or R5-2b sign.
5	The No Snowmobiles Symbol sign (R9-15) may be used where snowmobiles are prohibited on roadways or shared-use paths.
7 8 9 10	The AUTHORIZED VEHICLES ONLY (R5-11) sign may be used at median openings and other locations to prohibit vehicles from using the median opening or facility unless they have special permission (such as law enforcement vehicles or emergency vehicles) or are performing official business (such as highway agency vehicles).
11 12	Figure 2B-12. Selective Exclusion Signs

Section 2B.382B.48 WRONG WAY Sign (R5-1a)

39 Option:

38

40

41

42

44

45

46

The WRONG WAY (R5-1a) sign (see Figure 2B-112B-13) may be used as a supplement to the DO NOT ENTER sign where an exit ramp intersects a crossroad or a crossroad intersects a one-way roadway in a manner that does not physically discourage or prevent wrong-way entry (see Figure 2B-1216).

43 Guidance:

If used, the WRONG WAY sign should be placed at a location along the exit ramp or the one-way roadway farther from the crossroad than the DO NOT ENTER sign (see Section 2B.4450).

The WRONG WAY sign should be placed on the same side of the road as the DO NOT ENTER sign.

47 Support:

Section <u>2B.41</u>2B.49 contains information regarding an optional lower mounting height for WRONG WAY signs <u>mounted below DO NOT ENTER signs</u> that are located along an exit ramp facing a road user who is traveling in the wrong direction.

Option:

White or red LEDs may be installed within the border of the WRONG WAY sign to enhance the conspicuity of the sign. The LEDs may be vehicle actuated to flash at the rates as shown in Section 2A.20.

Section 2B.41 2B.49 Wrong-Way Traffic Control at Interchange Ramps

Standard:

At interchange exit ramp terminals where the ramp intersects a crossroad in such a manner that wrong-way entry could inadvertently be made, the following signs shall be used (see Figure 2B-182B-19):

- A. At least one ONE WAY sign for each direction of travel on the crossroad shall be placed where the exit ramp intersects the crossroad.
- B. At least one DO NOT ENTER sign shall be conspicuously placed near the downstream end of the exit ramp in positions appropriate for full view of a road user starting to enter wrongly from the crossroad.
- C. At least one WRONG WAY sign shall be placed on the exit ramp facing a road user traveling in the wrong direction.

Guidance:

In addition, the following pavement markings should be used (see Figure $\frac{2B-18}{2B-19}$):

- A. On two-lane paved crossroads at interchanges, solid double yellow lines should be used as a center line for an adequate distance on both sides approaching the ramp intersections.
- B. Where crossroad channelization or ramp geometrics do not make wrong-way movements difficult, a lane-use arrow should be placed in each lane of an exit ramp near the crossroad terminal where it will be clearly visible to a potential wrong-way road user.

Option:

The following traffic control devices may be used to supplement the signs and pavement markings described in Paragraphs 1 and 2:

- A. Additional ONE WAY signs may be placed, especially on two-lane rural crossroads, appropriately in advance of the ramp intersection to supplement the required ONE WAY sign(s).
- B. Additional WRONG WAY signs may be used.
- C. Slender, elongated wrong-way arrow pavement markings (see Figure 3B-24) intended primarily to warn wrong-way road users that they are traveling in the wrong direction may be placed upstream from the ramp terminus (see Figure 2B-182B-19) to indicate the correct direction of traffic flow. Wrong-way arrow pavement markings may also be placed on the exit ramp at appropriate locations near the crossroad junction to indicate wrong-way movement. The wrong-way arrow markings may consist of pavement markings or bidirectional red-and-white raised pavement markers or other units that show red to wrong-way road users and white to other road users (see Figure 3B-243B-21).
- D. Lane-use arrow pavement markings may be placed on the exit ramp and crossroad near their intersection to indicate the permissive direction of flow.
- E. Freeway entrance signs (see Section 2D.4649) may be used.
- F. Lane control signs or movement prohibition signs may be used on the approaches to the exit ramp.
- G. A Keep Right (R4-7 or R4-7c) may be used on a ramp median nose for wrong-way traffic control.

Guidance:

On interchange entrance ramps where the ramp merges with the through roadway and the design of the interchange does not clearly make evident the direction of traffic on the separate roadways or ramps, a ONE WAY sign visible to traffic on the entrance ramp and through roadway should be placed on each side of the through roadway near the entrance ramp merging point as illustrated in Figure 2B-192B-20.

Option:

On interchange entrance ramps where the ramp merges with the through roadway and the design of the interchange does not clearly make evident the direction of traffic on the separate roadways or ramps a NO

LEFT TURN (R3-2) sign may be located on the left side of the entrance ramp at the gore. If a NO LEFT
 TURN (R3-2) sign is located on the left a supplemental R3-2 sign may be installed right side of the entrance ramp.

On interchange entrance ramps where the ramp merges with the through roadway and the design clearly indicates the direction of flow, a ONE WAY sign may be placed visible to traffic on the entrance ramp and/or a NO TURNS (R3-3) sign may be placed visible to traffic on the entrance ramp and through roadway at the gore area as illustrated in Figure 2B-20.

At locations where engineering judgment determines that a special need exists, other standard warning or prohibitive methods and devices may be used as a deterrent to the wrong way movement.

Where there are no parked cars, pedestrian activity or other obstructions such as snow or vegetation, and if an engineering study indicates that a lower mounting height would address wrong-way movements on freeway or expressway exit ramps, a DO NOT ENTER sign(s) and/or a WRONG WAY sign(s) that is located along the exit ramp at a location downstream from the intersection with the crossroad facing a road user who is traveling in the wrong direction may be installed at a minimum mounting height of 3 feet, measured vertically from the bottom of the sign to the elevation of the near edge of the pavement. At the intersection with the crossroad, a WRONG WAY sign may be mounted at a minimum height of 3 feet on the same support on which a DO NOT ENTER sign is mounted at a height that complies with the provisions of Section 2A.18. (See Figure 2B-14)

19 Support:

Sections 2B.3748, 2B.3849, and 2B.4253 contains further information on signing to avoid wrong-way movements at at-grade intersections on expressways.

Section 2B.402B.50 **ONE WAY Signs (R6-1, R6-2)**

Standard:

Except as provided in Paragraph 6, the ONE WAY (R6-1 or R6-2) sign (see Figure 2B-1315) shall be used to indicate streets or roadways upon which vehicular traffic is allowed to travel in one direction only.

ONE WAY signs shall be placed parallel to the one-way street at all alleys and roadways that intersect one-way roadways as shown in Figure 2B-142B-16.

At the crossing of a roadway with a divided highway that functions as two separate intersections, At an intersection with a divided highway that has a median width at the intersection itself of 30 feet or more, ONE WAY signs shall be placed, visible to each crossroad approach, on the near right and far left corners of each intersection with the directional roadways (see Figure 2B-152B-17).

At the crossing of a roadway with a divided highway that functions as a single intersection At an intersection with a divided highway that has a median width at the intersection itself of less than 30 feet, Keep Right (R4-7) (see Section 2B.42) signs and/or ONE WAY signs shall be installed (see Figures 2B-162B-10 and 2B-172B-11). If Keep Right signs are installed, they shall be placed as close as practical to the approach ends of the medians and shall be visible to traffic on the divided highway and angled (as needed) toward the applicable each crossroad approach as shown in Figure 2B-1618. If ONE WAY signs are installed, they shall be placed on the near right and far left corners of the intersection and shall be visible to each crossroad approach.

Option:

At the crossing of a roadway with a divided highway, regardless of function as a single or separate intersections. At an intersection with a divided highway that has a median width at the intersection itself of less than 30 feet, ONE WAY signs may also be placed on the far right corner of the intersection as shown in Figures 2B-17 and 2B-162B-18 and 2B-17.

ONE WAY signs may be omitted on the one-way roadways of divided highways, where the design of interchanges indicates the direction of traffic on the separate roadways.

Support:

See Section 2B.49 for the placement of ONE WAY signs at a crossroad with an interchange.

Standard:

If used at unsignalized intersections with one-way streets, ONE WAY signs shall be placed on the near right and the far left corners of the intersection facing traffic entering or crossing the one-way street (see Figure 2B-142B-16).

If used at signalized intersections with one-way streets, ONE WAY signs shall be placed near the appropriate signal faces, on the poles holding the traffic signals, on the mast arm or span wire holding the signals, or at the locations specified for unsignalized intersections.

At unsignalized T-intersections where the roadway at the top of the T-intersection is a one-way roadway, ONE WAY signs shall be placed on the near right and the far side of the intersection facing traffic on the stem approach (see Figure 2B-142B-16).

At signalized T intersections where the roadway at the top of the T intersection is a one-way roadway, ONE WAY signs shall be placed near the appropriate signal faces, on the poles holding the traffic signals, on the mast arm or span wire holding the signals, or at the locations specified for unsignalized intersections. Option:

Where the central island of a roundabout allows for the installation of signs, ONE WAY signs may be used instead of or in addition to Roundabout Directional Arrow (R6-4 series) signs One-Direction -Large Arrow Sign (see Section 2B.43542C.10) to direct traffic counter-clockwise around the central island. Standard:

When a One-Direction Large Arrow sign is used without a ONE WAY sign, the R6-5P plaque shall be mounted below the Yield sign on the approach to a roundabout.

Guidance:

Where used on the central island of a roundabout, the mounting height of a ONE WAY sign should be at least 4 feet, measured vertically from the bottom of the sign to the elevation of the near edge of the traveled way.

Support:

Examples of Regulatory and Warning signs for roundabouts are shown in Figures 2B-21 through 2B-23. Using ONE WAY signs on the central island of a roundabout might result in some drivers incorrectly concluding that the cross street is a one way street. Using Roundabout Directional Arrow signs might reduce this confusion. However, using ONE WAY signs might be necessary in States that have defined a roundabout as a series of T intersections.

Option:

The BEGIN ONE WAY (R6-6) sign (see Figure 2B-13) may be used to notify road users of the beginning point of a one direction of travel restriction on the street or roadway. The END ONE WAY (R6-7) sign (see Figure 2B-13) may be used to notify road users of the ending point of a one direction of travel restriction on the street or roadway.

Section 2B.4251 Divided Highway Crossing Signs (R6-3, R6-3a)

Standard:

On unsignalized minor-street approaches from which both left turns and right turns are permitted onto a divided highway that has a median width at the intersection itself of 30 feet or more at a crossing that functions as two separate intersections (see Section 2A.23), except as provided in Paragraph 2, a Divided Highway Crossing (R6-3 or R6-3a) sign (see Figure 2B-13) shall be used to advise road users that they are approaching an intersection with a divided highway (see Figure 2B-1517).

Option:

If the divided highway that has a median width at the intersection itself of 30 feet or more has a traffic volume of less than 400 AADT and a speed limit of 25 mph or less, at a crossing that functions as two separate intersections, the Divided Highway Crossing signs facing the unsignalized minor-street approaches may be omitted.

A Divided Highway Crossing sign may be used on signalized minor-street approaches from which both left turns and right turns are permitted onto a divided highway to advise road users that they are approaching an intersection with a divided highway.

Standard:

If a Divided Highway Crossing sign is used at a four-legged intersection, the R6-3 sign shall be used. If used at a T-intersection, the R6-3a sign shall be used.

The Divided Highway Crossing sign shall be located on the near right corner of the intersection, mounted beneath a STOP or YIELD sign or on a separate support.

52 Option:

1 2	An additional Divided Highway Crossing sign may be installed on the left-hand side of the approach to supplement the Divided Highway Crossing sign on the near right corner of the intersection.
3 4	Figure 2B-14. Examples of Low-Mounted Wrong-Way Signs with Do Not Enter Signs for Wrong Way Traffic Control
5	Figure 2B-15. Locations of ONE WAY Signs
6	Figure 2B-16. Locations of Do Not Enter and Wrong-Way Signing for Divided Highway
7	Crossings that Function as Two Separate Intersections
8	Figure 2B-17. ONE WAY Signing for Divided Highway Crossings that Function as Two
9	Separate Intersections
10	Figure 2B-18. ONE WAY, DO NOT ENTER, and WRONG WAY Signing for Divided
11	Highway Crossings that Function as a Single Intersection
12 13	Figure 2B-19. Example of Application of Regulatory Signing and Pavement Markings at an Exit Ramp Termination to Deter Wrong-Way Entry
14 15	Figure 2B-20. Example of Application of Regulatory Signing and Pavement Markings at an Entrance Ramp Terminal
16 17 18	Section 2B.43 Roundabout Directional Arrow Signs (R6-4, R6-4a, and R6-4b) Section deleted, see Section 2B.50 for the use of ONE WAY sign and Section 2C.10 for the use of a LARGE ARROW sign at a roundabout
19 20	Section <u>2B.44-2B.52</u> Roundabout Circulation Plaque (R6-5P) This text was relocated from existing Section 2B.44 and revised
21	Guidance:
22 23	Where the central island of a roundabout does not provide a reasonable place to install a sign, Roundabout Circulation (R6-5P) plaques should be placed below the YIELD signs on each approach.
24	Option:
25 26 27	At roundabouts where Roundabout Directional Arrow signs and/or ONE WAY and/or One-Direction Large Arrow signs have been installed in the central island, Roundabout Circulation plaques may be placed below the YIELD signs on approaches to roundabouts to supplement the central island signs.
28	The Roundabout Circulation plaque may be used at any type of circular intersection.
29	Figure 2B-21. Example of Regulatory and Warning Signs for a Mini-Roundabout
30	Figure 2B-22. Example of Regulatory and Warning Signs for a One-Lane Roundabout
31 32	Figure 2B-23. Example of Regulatory and Warning Signs for a Two-lane Roundabout with Consecutive Double Lefts
33 34 35	Section 2B.45 <u>Examples of Roundabout Signing</u> Figures retained in Chapter 2B; a separate section dedicated to examples is not needed
36	PARKING, STANDING, STOPPING, AND EMERGENCY SIGNS
37	Section 2B.46 2B.53 Parking, Standing, and Stopping Signs (R7 and R8 Series)
38	Support:
39 40 41 42	Signs governing Parking signs pertain to the parking, stopping, and standing of vehicles along the roadway and in designated parking areas. They cover a wide variety of regulations, and only general guidance can be provided here. The word "standing" when used on the R7 and R8 series of signs refers to the practice of a driver keeping the vehicle in a stationary position while continuing to occupy the vehicle.
43	Parking signs are categorized as either (1) prohibiting parking or (2) permitting parking with restrictions
44 45	on how parking is allowed. They are further categorized as either parking (R7 series) signs or emergency
45 46	parking (R8 series) signs. The types of parking prohibitions that might be encountered include, but are not limited to:
40 47	1. Parking, standing, or stopping is prohibited at all times.
T /	Notice of Proposed Amendments – Part 2 Page 100 of 781 December 2020

- 2. Parking, standing, or stopping is prohibited only certain times of the day and/or days of the week.
 - 3. Parking, standing, or stopping is prohibited with exceptions, such as for bus stops, loading/unloading zones, persons with disabilities, or electric vehicle charging stations.
 - 4. Parking, standing, or stopping is prohibited under certain conditions, such as Snow Emergency Routes.
 - Permissive parking signs allowing parking with restrictions include, but are not limited to:
 - 1. Parking only allowed for limited time duration, such as 30 minutes, 1 hour, etc.
 - 2. Metered parking requiring payment at an individual or a multi-space parking meter, or through electronic means such as by telephone or mobile application
 - 3. Reserved parking for persons with disabilities or patrons or employees of a business
 - 4. Angled or back-in angled parking when it is not commonly utilized in the area.
 - 5. Parking programs such as neighborhood/residential permits, school areas, or special events.
 - Typical examples of parking, stopping, and standing signs and plaques (see Figures 2B-24 and 2B-25) are as follows:
- 15 1. NO PARKING ANY TIME (R7-1);
 - 2. NO PARKING X:XX AM TO X:XX PM (R7-2, R7-2a);
- 3. NO PARKING EXCEPT SUNDAYS AND HOLIDAYS (R7-3);
- 18 4. NO STANDING ANY TIME (R7-4);
- 5. XX HOUR PARKING X:XX AM X:XX PM (R7-5);
- 20 6. NO PARKING LOADING ZONE (R7-6);
- 21 7. NO PARKING BUS STOP (R7-7, R7-107, R7-107a, R7-107b);
- 22 8. RESERVED PARKING for persons with disabilities (R7-8);
- 23 9. VAN ACCESSIBLE (R7-8P);
- 24 10. Pay Station (R7-20);
- 25 11. Pay Parking (R7-21, R7-21a, R7-22);
 - 12. Parking Permitted X:XX AM TO X:XX PM (R7-23);
- 27 13. Parking Permitted XX HOUR(S) XX AM XX PM (R7-23a);
- 28 14. XX HR PARKING X:XX AM TO X:XX PM (R7-108);

Figure 2B-24. Parking and Standing Signs and Plaques (R7 Series

Figure 2B-25. Parking And Stopping Signs and Plaques (R8 Series)

Section 2B.47 2B.54 Design of Parking, Standing, and Stopping Signs

Support:

2

3

4

5

6

7

8

9

1011

12

13 14

16

26

29

3031

32

33

34

35

36

37 38

39 40

41

42

43

46 47 Discussions of parking signs and parking regulations in this Section apply not only to parking, but also tostanding and stopping.

Standard:

Parking, Standing, or Stopping signs shall be rectangular or square.

Public agencies shall follow established law (state law, local ordinance, or regulation) as adopted by the authorized agency regarding what messages are allowed on parking signs.

The legend on parking signs shall state applicable regulations. Parking signs (see Figures 2B-24 and 2B-25) shall comply with the standards of shape, color, and location.

Prohibitive Parking signs (See Figure 2B-24 for some commonly used examples) shall be used where parking is prohibited at all times or at specific times. Where parking is prohibited at all times or at specific times, the basic design for Except as otherwise provided in this Section, Prohibitive

pParking signs shall have a red legend and border on a white background (Parking Prohibition signs), except that the R8-4 and R8-7 signs and the alternate design for the R7-201P plaque shall have a black

legend and border on a white background, and the R8-3 sign shall have a black legend and border and

a red circle and slash on a white background. and, when the parking prohibition symbol is used, the

48 <u>symbol "P" shall be black.</u>

<u>Permissive Parking signs shall be used Wwhere only limited-time-limited parking or parking in a particular manner are is permitted allowed.</u> the Permissive Parking signs shall have a green legend and border on a white background (Permissive Parking signs).

Guidance:

Parking <u>signs_information</u>, should <u>be</u> display<u>ed</u> the following information from top to bottom of the sign, as applicable, in the order listed:

- A. The restriction or prohibition;
- B. The times of the day that it is applicable, if not at all hours; and
- C. The days of the week that it is applicable, if not every day:
- D. Qualifying or supplementary information.;
- E. Exemptions to the restriction of prohibition; and-
- F. Any tow-away message or symbol.

If the parking restriction applies to a limited area or zone, the limits of the restriction should be shown by arrows or supplemental plaques. If arrows are used and if the sign is at the end of a parking zone, there should be a single-headed arrow pointing in the direction that the regulation is in effect. If the sign is at an intermediate point in a zone, there should be a double-headed arrow pointing both ways. When a single sign is used at the transition point between two parking zones, it should display a right and left arrow pointing in the direction that the respective restrictions apply.

Where special parking restrictions are imposed during heavy snowfall, Emergency Snow Route (R7-203) signs (see Figure 2B-24) should be installed. The legend will vary according to the regulations, but the signs should be vertical rectangles, having a white background with the upper part of the plate a red background.

Relocated to below

Standard:

The times and days for which the parking regulations are in effect shall be posted if they are not in effect at all times of day or all days of the week.

Where parking spaces that are reserved for persons with disabilities are designated to accommodate wheelchair vans, a VAN ACCESSIBLE (R7-8P) plaque shall be mounted below the R7-8 sign. The R7-8 sign (see Figure 2B-24) shall have a green legend and border and a white wheelchair symbol on a blue square, all on a white background. The R7-8P plaque (see Figure 2B-24) shall have a green legend and border on a white background. Relocated to below and revised

Option:

As an alternate to the use of arrows to show designated restriction zones, the following word messages such as may be used: BEGIN, END, HERE TO CORNER, HERE TO ALLEY, THIS SIDE OF SIGN, or BETWEEN SIGNS may be used.

If the sign is at an intermediate point in a zone, there may be a double-headed arrow pointing both ways.

To minimize the number of parking signs, blanket regulations that apply to a given district may, if legal, be posted at district boundary lines. Relocated to Section 2B.56 below

In rural areas (see Figure 2B-25), the legends NO PARKING ON PAVEMENT (R8-1) or NO STOPPING ON PAVEMENT (R8-5) are generally suitable and may be used. If a roadway has an adjacent paved shoulders, the legend NO PARKING EXCEPT ON SHOULDER sign (R8-2) or the NO STOPPING EXCEPT ON SHOULDER sign (R8-6) may be used as these signs would be less likely to cause confusion. The R8-3 symbol sign or the word message NO PARKING (R3-8a) sign may be used to prohibit any parking along a given highway roadway. Word message supplemental plaques may be mounted below the R8-3 or R8-3a-NO PARKING signs. The R8-3 series sign may seinclude word messagelegends—supplemental plaques may include but are not limited to legends—such as EXCEPT SUNDAYS—AND HOLIDAYS (R8-3bP), ON PAVEMENT(R8-3cP), ON BRIDGE (R8-3dP), ON TRACKS (R8-3eP), and EXCEPT ON SHOULDERS (R8-3fP), LOADING ZONE (R8-3gP), and X:XX AM to X:XX PM. (with arrow)(R8-3hP) Relocated from below and revised

Guidance:

Where special parking restrictions are imposed during heavy snowfall <u>or a declared snow emergency</u>, <u>Emergency</u> Snow <u>Emergency</u> Route (R7-203) signs (see Figure <u>2B-24</u>) should be installed. The legend <u>will-should be modified to display the specific vary according to the regulations, but the signs should be vertical.

Notice of Proposed Amendments – Part 2

Page 102 of 781

December 2020</u>

rectangles, having a white background with the upper part of the plate. The upper section of the sign should display the designation as a snow emergency route in a white legend and border on a red background.

Relocated from above and revised

If a fee is charged for <u>on-street</u> parking and <u>payments are made at</u> a <u>midblock pay station multi-space</u> <u>parking meter, is used</u> instead of individual parking meters for each parking space, <u>pay parking signs should be used. Pay Metered Parking (R7-21 through R7-22) signs (see Figure 2B-24)</u> should be used to define the area where the <u>pay station parking multi-space parking meter applies. The Pay Station Multi-Space Parking Meter (R7-20) signs (see Figure 2B-24) should be used at the <u>pay station meter location or</u> to direct road users to the <u>pay station meter.</u> Relocated from below Option:</u>

Where payments can be made electronically, such as by telephone or mobile application, the Mobile Parking Payment (R7-21aP) plaque may be installed below a Metered Parking sign.

Standard: Relocated from below

If the <u>metered</u> <u>pay</u> parking is subject to a maximum time limit, the appropriate time limit (number of hours or minutes) shall be displayed on the <u>PayMetered Parking</u> (R7-21-or R7-21a) <u>signs</u> and, <u>except as provided in Paragraph 16 of this Section</u>, on the <u>Multi-space Parking Meter</u> <u>Pay Station</u> (R7-20) signs.

Option:

Where the maximum time limit varies by the time of the day or day of the week, the display of the time limits may be omitted from the R7-20 sign and, instead, be displayed on the multi-space parking meter so that they are visible to pedestrians as they make payments.

Standard:

Where parking spaces are reserved for persons with disabilities, the Accessible Parking (R7-8) sign shall be used to designate the space and shall display the official International Symbol of Accessibility.

Where parking spaces that are reserved for persons with disabilities are designed to accommodate wheelchair vans, a VAN ACCESSIBLE (R7-8aP) plaque shall be mounted below the R7-8 sign. The R7-8 sign (see Figure 2B-24) shall have a green legend and border and a white wheelchair symbol on a blue square, all on a white background. The R7-8P plaque (see Figure 2B-24) shall have a green legend and border on a white background. Relocated from above and revised

Guidance: Based on 6/17/2013 FHWA Memorandum

Where parking spaces are designated for parking of electric vehicles, an Electric Vehicle Parking (R7-111 series, R7-112 series, and R7-113) sign (see Figure 2B-24) should be installed adjacent to the designated spaces. Where there is no time limit, a R7-111 series sign should be used. Where parking is subject to a time limit, a R7-112 series sign should be used. Where electric vehicles are only allowed to park in a space while charging, a R7-113 sign should be used.

Where parking spaces are designated for charging of electric vehicles, a R7-113 sign or R7-114 series sign (see Figure 2B-24) should be installed adjacent to the designated spaces.

Where additional restrictions apply while a vehicle occupies the designated space, the R7-113P series plaques should be installed below the R7-113 sign or the R7-114 series signs.

Ontion:

Where parking is prohibited during certain hours and time-limited parking or parking in a particular manner is <u>permitted allowed</u> during certain other time periods, the red Parking Prohibition and green Permissive Parking signs may be designed as follows:

- A. Two 12 x 18-inch parking signs may be used with the red Parking Prohibition sign (R7-1) installed above or to the left of the green Permissive Parking sign (R7-108); or
- B. A single sign (R7-200 or R7-200a) may be used The red Parking Prohibition sign and the green Permissive Parking sign may be combined (see Figure 2B-24) to form an R7-200 sign on a single 24 x 18 inch sign, or an R7-200a sign on a single 12 x 30 inch sign.

At the transition point between two parking zones, a single sign (R7-200 or R7-200a) or two signs mounted side-side-by-by-side may be used.

The words NO PARKING may be used as an alternative to the No Parking symbol (see R7-2 sign in Figure 2B-24). The supplemental educational plaque, NO PARKING, with a red legend and border on a white background, may be used above signs incorporating the No Parking symbol. Text unnecessary

The R7-201P plaque may have a black or red symbol and border on a white background.

Alternate designs for the R7-107 sign may be developed such as the R7-107a sign (see Figure 2B-24). Alternate designs may include, on a single sign, a transit logo, an approved bus symbol, a parking prohibition, the words BUS STOP, and an arrow. The preferred bus symbol color is black, but other dark colors may be used. Additionally, the transit logo may be displayed on the bus face in the appropriate colors instead of placing the logo separately. The reverse side of the R7-107 series signs may contain display bus routing information for pedestrians.

To make the parking regulations more effective and to improve public relations by giving a definite warning, Aa TOW-AWAY ZONE Tow-Away Zone (R7-201 or R7-201aP) plaque (see Figure 2B-24) may be mounted below appended to, or incorporated in, any parking prohibition sign. The Tow-Away Zone (R7-201P) symbol plaque may be used instead of the R7-201aP word message plaque. The R7-201P plaque may have either a black or red legend and border on a white background. The word legend TOW-AWAY ZONE may be incorporated into the parking prohibition sign in lieu of using a separate plaque.

Guidance: Relocated to above

If a fee is charged for parking and a midblock pay parking fee station is used instead of individual parking meters for each parking space, pay parking signs should be used. Pay Parking (R7-21 through R7-22) signs (see Figure 2B-24) should be used to define the area where the pay parking fee station parking applies. Pay Station (R7-20) signs (see Figure 2B-24) should be used at the pay station or to direct road users toto indicated the location of the pay station.

Standard: Relocated to above

If the pay parking is subject to a maximum time limit, the appropriate time limit (number of hours or minutes) shall be displayed on the Pay Parking (R7-21 or R7-21a) and Pay Station (R7-20) signs.

Option: Relocated to above

In rural areas (see Figure 2B-252B-15), the legends NO PARKING ON PAVEMENT (R8-1) or NO STOPPING ON PAVEMENT (R8-5) are generally suitable and may be used. If a roadway has paved shoulders, the NO PARKING EXCEPT ON SHOULDER sign (R8-2) or the NO STOPPING EXCEPT ON SHOULDER sign (R8-6) may be used as these signs would be less likely to cause confusion. The R8-3 symbol sign or the word message NO PARKING (R8-3a) sign may be used to prohibit any parking along a given highway. Word message supplemental plaques may be mounted below the R8-3 or R8-3a sign. These word message supplemental plaques may include legends such as EXCEPT SUNDAYS AND HOLIDAYS (R8-3bP), ON PAVEMENT (R8-3cP), ON BRIDGE (R8-3dP), ON TRACKS (R8-3eP), EXCEPT ON SHOULDERS (R8-3fP), LOADING ZONE (with arrow) (R8-3gP), and X:XX AM TO X:XX PM (with arrow) (R8-3hP).

Colors that are in compliance with the provisions of Section 2A.10 may be used for color coding of parking time limits.

Guidance:

If colors are used for color coding of parking time limits, the colors green, red, and black should be the only colors that are used.

When a legend other than that on the standard parking signs is necessary, letter height, symbol size, and basic sign layout should be consistent with the those shown on the standard parking signs as detailed in the "Standard Highway Signs and Markings" publication.

In general, the letter height of the principal legend on parking signs sized for urbanized applications should be at least 2 inches.

Section 2B.482B.55 Placement of Parking, Stopping, and Standing Signs

Support:

The efficacy of Parking, Stopping, and Standing signs, when used on conventional roads in urbanized or developed environments, depends on their visibility and consistent placement along a street or within a particular block. It is often not practicable for the entire legend to be legible from similar distances as for other types of signs. Therefore, it is important that their conventional form be recognizable from an adequate distance such that the road user can obtain the information upon closer inspection.

51 Guidance:

When signs with arrows are used to indicate the extent of the restricted zones, the signs should be set at an angle of not less than 30 degrees or more than 45 degrees with the line of traffic flow in order to be visible to approaching traffic.

When signs are placed at the head of perpendicular parking stalls, the signs should be parallel to the roadway facing the parking stall.

Spacing of signs should be based on legibility, conspicuity, and sign orientation.

If the zone is unusually long, signs showing a double arrow should be used at intermediate points within the zone.

Standard: Standard changed to Guidance

If the signs are mounted at an angle of 90 degrees to the curb line, two signs shall should be mounted back to back at the transition point between two parking zones, each with an appended THIS SIDE OF SIGN (R7-202P) supplemental plaque.

Guidance:

If the signs are mounted at an angle of 90 degrees to the curb line, signs without any arrows or appended plaques should be used at intermediate points within a parking zone, facing in the direction of approaching traffic. Otherwise, the standards of placement should be the same as for signs using directional arrows.

Option: Moved from previous section and revised

To minimize the number of parking signs, blanket Blanket regulations that apply to a given district an entire jurisdiction may, if legal, be posted at district in the vicinity of the jurisdictional boundary lines. Blanket regulations that apply to a posted zone or district may be posted at the entry points to the zone or district.

Section 2B.49 2B.56 Emergency Restriction Signs (R8-4, R8-7, R8-8)

Standard:

Emergency Restriction signs shall be rectangular and shall have a red or black legend and border on a white background. Relocated from later in Section

Option:

The EMERGENCY PARKING ONLY (R8-4) sign (see Figure 2B-25) or the EMERGENCY STOPPING ONLY (R8-7) sign (see Figure 2B-25) may be used to discourage or prohibit shoulder parking, particularly where scenic or other attractions create a tendency for road users to stop temporarily.

The DO NOT STOP ON TRACKS (R8-8) sign (see Figure 8B-1) may be used to discourage or prohibit parking or stopping on railroad or light rail transit tracks (see Section 8B.0907).

Standard:

Emergency Restriction signs shall be rectangular and shall have a red or black legend and border on a white background. Relocated to beginning of Section and revised

5

6

7

8

9

10 11

12

13

1415

17

18

19

20

21

22

23

24

2526

27

28

29

30

31

32 33

35

36

37

39

40

41 42

44

45

48

2 Section 2B.50 2B.57 WALK ON LEFT FACING TRAFFIC and No Hitchhiking Signs (R9-1, R9-4, R9-4a)

Option:

The WALK ON LEFT FACING TRAFFIC (R9-1) sign (see Figure 2B-26) may be used on highways where no sidewalks are provided.

Standard: Guidance:

If used, the WALK ON LEFT FACING TRAFFIC sign shall-should be installed on the right-hand side of the road where pedestrians walk on the pavement or shoulder in the absence of pedestrian pathways or sidewalks.

Option:

The No Hitchhiking (R9-4) sign (see Figure 2B-26) may be used to prohibit standing in or adjacent to the roadway for the purpose of soliciting a ride. The R9-4a word message sign (see Figure 2B-26) may be used as an alternate to the R9-4 symbol sign.

Section 2B.51 2B.58 Pedestrian Crossing Signs (R9-2, R9-3)

16 Option

Pedestrian Crossing signs (see Figure 2B-26) may be used to limit pedestrian crossing to specific locations.

Standard:

If used, Pedestrian Crossing signs shall be installed to face pedestrian approaches.

Option:

Where crosswalks are clearly defined, the CROSS ONLY AT CROSSWALKS (R9-2) sign may be used to prohibit pedestrians from crossing at locations away from crosswalks.

The No Pedestrian Crossing (R9-3) sign may be used to prohibit pedestrians from crossing a roadway at an undesirable location or in front of a school or other public building where a crossing is not designated.

The NO PEDESTRIAN CROSSING (R9-3a) word message sign may be used as an alternate to the R9-3 symbol sign. The USE CROSSWALK (R9-3bP) supplemental plaque, along with an arrow, may be installed below either sign to designate the direction of the crossing.

Support:

One of the most frequent uses of the Pedestrian Crossing signs is at signalized intersections that have three crossings that can be used and one leg that cannot be crossed. Pedestrians with low-vision capabilities might need additional features other than traffic control devices to communicate the prohibition of pedestrian crossing.

34 Guidance:

The R9-3bP plaque should not be installed in combination with educational plaques.

Section <u>2B.52-2B.59</u> <u>Traffic Signal Pedestrian and Bicycle Actuation Signs (R10-1 through R10-4, and R10-24 through R10-26)</u>

38 Standard:

Where manual actuation of a traffic signal is required for pedestrians or bicyclists to call a signal phase to cross the roadway, Traffic traffic Signal signs applicable to pedestrian actuation (see Figure 2B-26) or bicyclist actuation (see Figure 9B-12) shall be mounted immediately above or incorporated into the pushbutton detector units (see Section-4E.084I.06).

43 Support:

Traffic Signal signs applicable to pedestrians include:

- A. CROSS ONLY ON GREEN (symbolic circular green) (R10-1);
- 46 B. CROSS ONLY ON (symbolic walk indication) SIGNAL (R10-2);
- 47 C. Push Button for Walk Signal (R10-3 series); and
 - D. Push Button for Green Signal (R10-4 series).

Option:

The following signs may be used as an alternate for the R10-3 and R10-4 signs:

- A. Push Button to Cross Street Wait for Walk Signal (R10-3a); or
- B. Push Button to Cross Street Wait for Green Signal (R10-4a).

The name of the street to be crossed may be substituted for the word STREET in the legends on the R10-3a and R10-4a signs.

Guidance:

The finger in the pushbutton symbol on the R10-3, R10-3a, R10-4, and R10-4a signs should point in the same direction as the arrow on the sign.

Option:

Where symbol-type pedestrian signal indications are used, an educational sign (R10-3b) may be used instead of the R10-3 sign to improve pedestrian understanding of pedestrian indications at signalized intersections. Where word-type pedestrian signal indications are being retained for the remainder of their useful service life, the legends WALK/DONT WALK may be substituted for the symbols on the educational sign R10-3b, thus creating educational sign R10-3c. The R10-3d educational sign may be used to inform pedestrians that the pedestrian clearance time is sufficient only for the pedestrian to cross to the median at locations where pedestrians cross in two stages using a median refuge island. The R10-3e educational sign may be used where countdown pedestrian signals have been provided. In order to assist the pedestrian in understanding which pushbutton to push, the R10-3f to R10-3i educational signs that provide the name of the street to be crossed may be used instead of the R10-3b to R10-3e educational signs. The R10-3j sign may be used where a pedestrian pushbutton is only to activate the accessible pedestrian signals. The R10-3k sign may be used where a pedestrian pushbutton has sensors to allow for touch-free activation.

The R10-24 or R10-26 sign (see Section 9B.11) may be used where a pushbutton detector has been installed exclusively to actuate a green phase for bicyclists.

The R10-25 sign (see Figure 2B-26) may be used where a pushbutton detector has been installed for pedestrians to activate In-Roadway Warning Lights (see Chapter 4N4U) or flashing beacons that have been added to the pedestrian warning signs.

Support:

Section 4E.084I.06 contains information regarding the application of the R10-32P plaque.

Figure 2B-26. Pedestrian Signs and Plaques

2 Section 2B.532B.60 Traffic Signal Signs (R10-5 through R10-30)

Option:

To supplement traffic signal control, Traffic Signal signs R10-5 through R10-30 may be used to regulate road users.

Traffic Signal signs (see Figure 2B-27) may be installed at certain locations to clarify signal control. Among the legends that may be used for this purpose are LEFT ON GREEN ARROW ONLY (R10-5), STOP HERE ON RED (R10-6 or R10-6a) for observance of stop lines, DO NOT BLOCK INTERSECTION (R10-7) for avoidance of traffic obstructions, USE LANE(S) WITH GREEN ARROW (R10-8) for obedience to laneuse control signals (see Chapter-4M4T), LEFT TURN YIELD ON GREEN (symbolic circular green) (R10-12), LEFT TURN YIELD ON FLASHING YELLOW ARROW (R10-12a), and LEFT TURN YIELD ON FLASHING RED ARROW AFTER STOP (R10-27).

Guidance:

If used, the LEFT ON GREEN ARROW ONLY (R10-5) sign, the LEFT TURN YIELD ON GREEN (symbolic circular green) (R10-12) sign, the LEFT TURN YIELD ON FLASHING YELLOW ARROW (R10-12a), or the LEFT TURN YIELD ON FLASHING RED ARROW AFTER STOP (R10-27) sign should be located adjacent to the left-turn signal face.

18 Option:

If needed for additional emphasis, an additional LEFT TURN YIELD ON GREEN (symbolic circular green) (R10-12) sign with an AT SIGNAL (R10-31P) supplemental plaque (see Figure 2B-27) may be installed in advance of the intersection.

In situations where traffic control signals are coordinated for progressive timing, the Traffic Signal Speed (I1-1) sign may be used (see Section 2H.03).

Standard:

The LEFT TURN YIELD TO Bicycles (R10-12b) sign shall be limited to applications where the conflicting bicycle movement would be unexpected in direction, location, or some other quality that would run counter to the expectation of a turning motorist.

The LEFT TURN YIELD TO Bicycles sign shall not be installed for motor vehicle traffic subjected to a counter-flow bicycle operation when the opposing bicycle movement is controlled by a bicycle signal face (see Chapter 4H).

Support:

Situations where the LEFT TURN YIELD TO Bicycles sign may be appropriate include, but are not limited to, where drivers are turning across a separated bicycle lane or a buffer-separated bicycle lane.

Guidance:

The LEFT TURN YIELD TO Bicycles sign should be located adjacent to the left-turn signal face.

If needed for additional emphasis, an additional LEFT TURN YIELD TO Bicycles sign with an AT SIGNAL (R10-31P) supplemental plaque (see Figure 2B-27) may be installed in advance of the intersection for motor vehicles.

41 Standard:

The CROSSWALK—STOP ON RED (symbolic circular red) (R10-23) and WAIT ON STEADY RED- YIELD ON FLASHING RED AFTER STOP (R10-23a) signs (see Figure 2B-27) shall only be used in conjunction with pedestrian hybrid beacons (see Section 4F.024J.02).

The EMERGENCY SIGNAL (R10-13) sign (see Figure 2B-27) shall be used in conjunction with emergency-vehicle traffic control signals (see Section-4G.024M.02).

The EMERGENCY SIGNAL—STOP ON FLASHING RED (R10-14 or R10-14a) sign (see Figure 2B-27) shall be used in conjunction with emergency-vehicle hybrid beacons (see Section-4G.044N.02).

49 Option:

If needed for extra emphasis, a STOP HERE ON FLASHING RED (R10-14b) sign may be installed with an emergency-vehicle hybrid beacon.

Where conditions may warrant additional emphasis to drivers turning at a signalized intersection where potential pedestrian conflicts may not be readily apparent, a Turning Vehicles Yield to (Stop For) Pedestrians (R10-15, R10-15a), sign (see Figure 2B-27) may be used.

Standard:

The Turning Vehicles Stop for Pedestrians (R10-15a) sign shall only be used in jurisdictions where laws, ordinances or resolutions specifically require that a driver must stop for a pedestrian.

Option:

A U_TURN YIELD TO RIGHT TURN (R10-16) sign (see Figure 2B-27) may be installed near the left-turn signal face if U-turns are allowed on a protected left-turn movement on an approach from which a right-turn GREEN ARROW signal indication is simultaneously being displayed to drivers making a right turn from the conflicting approach to their left.

A U TURN SIGNAL (R10-10a) sign (see Figure 2B-27) may be installed adjacent to the signal face that exclusively controls a U-turn movement.

Figure 2B-27. Traffic Signal Signs and Plaques

Section 2B.54 2B.61 No Turn on Red Signs (R10-11 Series, R10-17a, and R10-30)

Standard:

Where a right turn on red (or a left turn on red from a one-way street to a one-way street) is to be prohibited, a symbolic NO TURN ON RED (R10-11, R10-11a) word message sign (symbolic circular red) (R10-11) sign (see Figure 2B-27) or a NO TURN ON RED (symbolic circular red) (R10-11b) sign (R10-11a, R10-11b) word message sign (see Figure 2B-27) shall be used.

Guidance:

If used, the No Turn on Red sign should be installed near the appropriate signal head.

A No Turn on Red sign should be considered when an engineering study finds that one or more of the following conditions exists:

- A. Inadequate sight distance to vehicles approaching from the left (or right, if applicable);
- B. Geometrics or operational characteristics of the intersection that might result in unexpected conflicts;
- C. An exclusive pedestrian phase;
- D. An unacceptable number of pedestrian conflicts with right-turn-on-red maneuvers, especially involving children, older pedestrians, or persons with disabilities;
- E. More than three right-turn-on-red accidents reported in a 12-month period for the particular approach; or
- F. The skew angle of the intersecting roadways creates difficulty for drivers to see traffic approaching from their left.

Option:

A supplemental R10-20aP plaque (see Figure 2B-27) showing times of day (similar to the S4-1P plaque shown in Figure 7B-1) with a black legend and border on a white background may be mounted below a No-Turn on Red sign to indicate that the restriction is in place only during certain times. Moved down to follow the next paragraph

Alternatively, aA blank-out part-time restriction prohibited movement (R3-1, R3-2, R3-4, R3-18, and R3-27) sign (See Section 2B.28) sign-may be used instead of a static NO TURN ON RED sign, to display either the NO TURN ON RED legend or the No Right Turn symbol or word message, as appropriate, only at certain times during the day or during one or more portion(s) of a particular cycle of the traffic signal.

Alternatively, aA supplemental R10-20aP plaque (see Figure 2B-27) showing times of day (similar to the S4-1P plaque shown in Figure 7B-1) with a black legend and border on a white background may be mounted below a No Turn on Red sign to indicate that the restriction is in place only during certain times.

White LEDs may be used in the border and activated during periods of turn prohibition to enhance the sign conspicuity.

On signalized approaches with more than one right-turn lane, a NO TURN ON RED EXCEPT FROM RIGHT LANE (R10-11c) sign (see Figure 2B-27) may be post-mounted at the intersection or a NO TURN

ON RED FROM THIS LANE (with down arrow) (R10-11d) sign (see Figure 2B-27) may be mounted directly over the approximate center of the lane from which turns on red are prohibited.

Guidance:

Where turns on red are permitted and the signal indication is a steady RED ARROW, the RIGHT (LEFT) ON RED ARROW AFTER STOP (R10-17a) sign (see Figure 2B-27) should be installed adjacent to the RED ARROW signal indication.

Option:

A RIGHT TURN ON RED MUST YIELD TO U-TURN (R10-30) sign (see Figure 2B-27) may be installed to remind road users that they must yield to conflicting U-turn traffic on the street or highway onto which they are turning right on a red signal after stopping.

Section 2B.552B.62 Photo Enforced Signs and Plaques (R10-18, R10-19P, R10-19aP, R10-18a) Option:

A TRAFFIC LAWS PHOTO ENFORCED (R10-18) sign (see Figure 2B-3) may be installed at a jurisdictional boundary to advise road users that some of the traffic regulations within that jurisdiction are being enforced by photographic equipment.

A Traffic Signal Photo Enforced (R10-18a) sign may be installed on an approach to a signalized location where red-light cameras are present on any approach to the signalized location. A Signal Ahead (W3-3) sign and a Traffic Signal Photo Enforced (R10-18a) sign may be used on the same approach provided that they are on separate supports.

A Photo Enforced (R10-19P) plaque or a PHOTO ENFORCED (R10-19aP) word message plaque (see Figure 2B-3) may be mounted below a regulatory sign to advise road users that the regulation is being enforced by photographic equipment.

A Traffic Signal PHOTO ENFORCED Sign (R10-18a sign may be installed in advance of or at a traffic signal to advise road users that signal compliance is being enforced by photographic equipment.

Standard:

The Traffic Signal Photo Enforced (R10-18a) sign shall not be installed on approaches to signalized locations where red-light cameras are not present on any of the approaches to the signalized location.

A Traffic Signal Photo Enforced (R10-18a) sign shall not be installed on the same support in combination with a Signal Ahead (W3-3) sign.

If used below a regulatory sign, the Photo Enforced (R10-19P or R10-19aP) plaque shall be a rectangle with a black legend and border on a white background.

Section 2B.56-2B.63 Ramp Metering Signs (R10-28 and R10-29)

Option:

When ramp control signals (see Chapter-414P) are used to meter traffic on a freeway or expressway entrance ramp, regulatory signs with legends appropriate to the control may be installed adjacent to the ramp control signal faces.

For entrance ramps with only one controlled lane, an XX VEHICLE(S) PER GREEN (R10-28) sign (see Figure 2B-28) may be used to inform road users of the number of vehicles that are permitted to proceed during each short display of the green signal indication. For entrance ramps with more than one controlled lane, an XX VEHICLE(S) PER GREEN EACH LANE (R10-29) (see Figure 2B-28) sign may be used to inform road users of the number of vehicles that are permitted to proceed from each lane during each short display of the green signal indication.

Figure 2B-28. Ramp Metering Signs

5

6

7

8

9

10

12

13

14

15

16 17

18

19

20 21

23

2425

26

28

29

31 32

33

34

35

36

37

3839

40

41

42 43

44 45

47

48

2 Section 2B.57-2B.64 KEEP OFF MEDIAN Sign (R11-1)

3 Option:

The KEEP OFF MEDIAN (R11-1) sign (see Figure 2B-29) may be used to prohibit driving into or parking on the median.

Guidance:

The KEEP OFF MEDIAN sign should be installed on the left-hand side of the roadway within the median at random intervals as needed wherever there is a tendency for encroachment.

Section 2B.58 2B.65 ROAD CLOSED Sign (R11-2) and LOCAL TRAFFIC ONLY Signs (R11-3 Series, R11-4)

11 Guidance:

The ROAD CLOSED (R11-2) sign should be installed where roads have been closed to all traffic (except authorized vehicles).

ROAD CLOSED—LOCAL TRAFFIC ONLY (R11-3) or ROAD CLOSED TO THRU TRAFFIC (R11-4) signs should be used where through traffic is not permitted, or for a closure some distance beyond the sign, but where the highway is open for local traffic up to the point of closure.

Standard:

The Road Closed (R11-2, R11-3 series, and R11-4) signs (see Figure 2B-29) shall be designed as horizontal rectangles. These signs shall be preceded by the applicable Advance Road Closed warning sign with the secondary legend AHEAD and, if applicable, an Advance Detour warning sign (see Section 6F.196H.04).

22 Option:

An intersecting street name or a well-known destination may be substituted for the XX MILES AHEAD legend in urban areas.

The word message BRIDGE OUT may be substituted for the ROAD CLOSED legend where applicable.

Section 2B.59-2B.66 Weight Limit Signs (R12-1 through R12-5)7)

27 *Guidance*:

Weight limit signs (see Figure 2B-29 for some commonly used examples) should be used to indicate a structure has a vehicle weight restriction.

30 Option:

The Weight Limit (R12-1) sign carrying the legend WEIGHT LIMIT XX TONS may be used to indicate vehicle weight restrictions including load.

Guidance:

The units shown on any weight limit sign should be consistent within a state or region with respect to pounds or tons.

<u>Vehicle weight restrictions should be depicted using gross vehicle weight. Vehicle weight restrictions</u> using weight per axle or empty vehicle weight should not be used unless local laws require the signs to depict weight restrictions in that manner.

Where the restriction applies to axle weight rather than gross load, the legend may be AXLE WEIGHT LIMIT XX TONS or AXLE WEIGHT LIMIT XX LBS (R12-2).

To restrict trucks of certain sizes by reference to empty weight in residential areas, the legend may be NOTRUCKS OVER XX TONS EMPTY WT or NO TRUCKS OVER XX LBS EMPTY WT (R12-3).

In areas where multiple regulations of the type described in Paragraphs 1 through 3 are applicable, a sign-combining the necessary messages on a single sign may be used, such as WEIGHT LIMIT XX TONS PER-AXLE, XX TONS GROSS (R12-4).

46 Option:

Posting of specific load limits may be accomplished by use of the Weight Limit symbol sign (R12-5). A sign containing the legend WEIGHT LIMIT on the top two lines, and showing up to three different truck

- symbols and their respective weight limits for which restrictions apply may be used, with the weight limits
- displayed to the right of each symbol as XX T. A bottom line of legend stating GROSS WT may be included if needed for enforcement purposes.
- 4 Support:
- Specialized Hauling Vehicles (SHVs) are closely spaced multi-axle single unit trucks. Examples include
 dump trucks, construction vehicles, solid waste trucks and other hauling trucks. SHVs typically have 4 to 7
- 7 axles.
- 8 Option:
- 9 The Weight Limit (R12-6) sign displaying the legend WEIGHT LIMIT SINGLE 2-3 AXLES XX TONS,
- 10 4-5 AXLES XX TONS, 6+ AXLES XX TONS, and COMBINATION XX TONS may be used to indicate
- vehicle weight restrictions for Specialized Hauling Vehicles.
- 12 **Standard:**
- The symbols shown on the R12-5 and R12-6 Weight Limit sign shall apply to all trucks of that configuration (single-unit, single-trailer or multi-trailer) regardless of the shape of the vehicle. Symbolic representations of other vehicle shapes or modifications of standard symbols shall not be used.
- 16 Option:
- 17 The facility type (i.e. "BRIDGE") may be added or omitted if the posting applies to a different facility
- 18 <u>type.</u>

23

24

25

26

27

32

33

34

36

37

40

41

42

43

- 19 Guidance:
- 20 Only trucks and axle configurations with weight limits should be shown.
- 21 **Standard:**
 - If the R12-5 sign depicts only one single-unit vehicle symbol, the weight limit associated with that single-unit vehicle symbol shall apply to all single-unit vehicles, regardless of number of axles.
 - The weight limit associated with the single-trailer vehicle symbol shall apply to all single-trailer vehicles, regardless of number of axles or vehicle shape.
 - The weight limit associated with the multi-trailer vehicle symbol shall apply to all multi-trailer vehicles with two or more trailers, regardless of number of axles or vehicle shape.
- 28 **Guidance**:
- 29 <u>The R12-5 and R12-6 Weight Limit sign should not show more than 3 symbols so as to not decrease comprehension of the sign by drivers.</u>
- 31 **Standard:**
 - If used, the Weight Limit sign (see Figure 2B-29), with an advisory distance ahead legend, shall be located in advance of the applicable section of highway or structure so that prohibited vehicles can detour or turn around prior to the limit zone. Revised to incorporate Guidance below
- 35 Guidance:
 - If used, the Weight Limit sign with an advisory distance ahead legend should be placed at approach road intersections or other points where prohibited vehicles can detour or turn around. Incorporated into
- 38 Standard above
- 39 Support:
 - An emergency vehicle is designed to be used under emergency conditions to transport personnel and equipment to support the suppression of fires and mitigation of other hazardous situations. Emergency vehicles are typically operated by fire departments and are primarily equipped for firefighting, but are also used to respond to and mitigate other hazardous situations in an emergency. They can create higher load effects compared to legal loads.
- 45 Option:
- The Emergency Vehicle Weight Limit (R12-7) sign carrying the legend EMERGENCY VEHICLE
- 47 WEIGHT LIMIT SINGLE AXLE XX TONS, TANDEM XX TONS, and GROSS XX TONS may be used to
- 48 <u>indicate vehicle weight restrictions for emergency vehicles.</u>
- 49 **Standard:**

1	When mounted below a primary Weight Limit sign the Emergency Vehicle Weight Limit plaque
2	(R12-7ap) shall be used.
3	Figure 2B-29. Road Closed and Weight Limit Signs
4	Section 2B.60 2B.67 Weigh Vehicle Inspection Area Station Signss (R13-1 Series)
5	Guidance:
6	An R13-1 sign with the legend TRUCKS OVER XX TONS MUST ENTER WEIGH STATION NEXT
7 8	RIGHT (see Figure 2B-30) should be used to direct appropriate traffic into a weigh inspection station. The R13-1 sign should be supplemented by the D8 series of guide signs (see Section 2D.4950).
9	Option:
10	The reverse color combination, a white legend and border on a black background, may be used for the
11	R13 1 sign. Option deleted to support uniformity
12	The R13-1 legend may be modified to match the specific type of inspection conducted at the station.
13	Section 2B.61 2B.68 TRUCK ROUTE Sign (R14-1)
14	Guidance:
15	The TRUCK ROUTE (R14-1) sign (see Figure 2B-30) should be used to mark a route that has been
16	designated to allow truck traffic.
17	OptionSupport:
18 19	On a numbered highway, See Section 2D.20 regarding the use of the TRUCK (M4-4) auxiliary sign may be used (see Section 2D.20) on a designated numbered alternative route.
20	Section 2B.622B.69 Hazardous Material Signs (R14-2, R14-3)
21	Option:
22 23	The Hazardous Material Route (R14-2) sign (see Figure 2B-30) may be used to identify routes that have been designated by proper authority for vehicles transporting hazardous material.
24 25	On routes where the transporting of hazardous material is prohibited, the Hazardous Material Prohibition (R14-3) sign (see Figure 2B-30) may be used.
26	Guidance:
27 28	If used, the Hazardous Material Prohibition sign should be installed on a street or roadway at a point where vehicles transporting hazardous material have the opportunity to take an alternate route.
29	Section 2B.63-2B.70 National Network Signs (R14-4, R14-5)
30	Support:
31	The signing of the National Network routes for trucking is optional.
32	Standard:
33 34	When a National Network route is signed, the National Network (R14-4) sign (see Figure 2B-30) shall be used.
35	Option:
36 37 38	The National Network Prohibition (R14-5) sign (see Figure 2B-30) may be used to identify routes, portions of routes, and ramps where trucks are prohibited. The R14-5 sign may also be used to mark the ends of designated routes.

1	OTHER REGULATORY SIGNS
2	Section 2B.652B.71 FENDER BENDER MINOR CRASHES MOVE VEHICLES FROM
3	TRAVEL LANES (R16-4) Sign
4	Option:
5 6 7	A FENDER BENDER STATE LAW MINOR CRASHES MOVE VEHICLES FROM TRAVEL LANES (R16-4) sign (see Figure 2B-3231) may be installed in accordance with the provisions of Section 2A.01 to
8	require motorists to move their vehicle out of the travel lanes if they have been involved in a crash. Legend of sign changed
9	Section 2B.72 Move Over or Reduce Speed Sign
10	Option:
11 12 13	A STATE LAW MOVE OVER OR REDUCE SPEED FOR VEHICLES STOPPED ON SHOULDER (R16-3) sign (see Figure 2B-31) may be installed in accordance with the provisions of Section 2A.01 to require motorists to change lanes and/or reduce speed when passing stopped emergency vehicles on the
14	shoulder.
15	Section 2B.73 No Hand-Held Phones by Driver Signs (R16-15, R16-15a)
16	Option:
17 18	A STATE LAW NO HAND-HELD PHONES BY DRIVER (R16-15, R16-15a) sign (see Figure 2B-31) may be installed in accordance with the provisions of Section 2A.01 to notify drivers that
19	they are prohibited from using hand-held telephones while driving.
20	Figure 2B-31. Other Regulatory Signs and Symbols
21	Section 2B.64 2B.74 Headlight Use Signs (R16-5 through R16-11)
22	Support:
23 24 25	Some States require road users to turn on their vehicle headlights under certain weather conditions, as a safety improvement measure on roadways experiencing high crash rates, or in special situations such as when driving through a tunnel.
26 27	Figure 2B-31-2B-32 shows the various signs that can be used for informing motorists of these requirements.
28	Option:
29 30 31 32	A LIGHTS ON WHEN USING WIPERS (R16-5) sign or a LIGHTS ON WHEN RAINING (R16-6) sign may be installed in accordance with the provisions of Section 2A.01 to inform road users of State laws regarding headlight use. Although these signs are typically installed facing traffic entering the State just inside the State border, they also may be installed at other locations within the State.
33	Guidance:
34 35 36 37	If a particular section of roadway has been designated as a safety improvement zone within which headlight use is required, a TURN ON HEADLIGHTS NEXT XX MILES (R16-7) sign or a BEGIN DAYTIME HEADLIGHT SECTION (R16-10) sign should be installed at the upstream end of the section, and a END DAYTIME HEADLIGHT SECTION (R16-11) sign should be installed at the downstream end of the section.
38	Option:
39 40 41 42	A TURN ON HEADLIGHTS (R16-8) sign may be installed to require road users to turn on their headlights in special situations such as when driving through a tunnel. A CHECK HEADLIGHTS (R16-9) sign may be installed downstream from the special situation to inform drivers that the using their headlights is no longer required.
43	Figure 2B-32. Headlight Use Signs
44	Section 2B.66 2B.75 Seat Belt Symbol
45	Standard:
46 47	When a seat belt symbol is used, the symbol shown in Figure 2B-32 shall be used. Not needed, since the design of symbols is covered in Section 2A 06
	10000000000000000000000000000000000000

1	Guidance:		
2	· · · · · · · · · · · · · · · · · · ·		
3	regulatory sign messages for mandatory seat belt use.		
4	BARRICADES AND GATES		
5	Section 2B.67-2B.76 Barricades		
6	Option:		
7	Barricades may be used to mark any of the following conditions:		
8	A. A roadway ends,		
9	B. A ramp or lane closed for operational purposes, or		
10	C. The permanent or semi-permanent closure or termination of a roadway.		
11	Standard:		
12	When used to warn and alert road users of the terminus of a roadway in other than temporary		
13	traffic control zones, barricades shall meet the design criteria of Section 6F.686K.07 for a Type 3		
14	Barricade, except that the colors of the stripes shall be retroreflective white and retroreflective red.		
15	Option:		
16	An end-of-roadway marker or markers may be used as described in Section 2C.6672.		
17	Guidance:		
18	Appropriate advance warning signs (see Chapter 2C) should be used.		
19 20	Support:		
	Support:		
21	Gates described in this section used for weather or other emergency conditions are typically permanently		
22 23	installed to enable the gate to be immediately deployed as needed to prohibit the entry of traffic to the highway segment(s).		
24 25	A gate typically features a gate arm that is moved from a vertical to a horizontal position or is rotated in a horizontal plane from parallel to traffic to perpendicular to traffic. Traffic is obstructed and required to stop		
25 26	when the gate arm is placed in a horizontal position perpendicular to traffic. Another type of gate consists of a		
27	segment of fence (usually on rollers) that swings open and closed, or that is retracted to open and then		
28	extended to close.		
29	Gates are sometimes used to enforce a required stop. Some examples of such uses are the following:		
30	A. Parking facility entrances and exits,		
31	B. Private community entrances and exits,		
32	C. Military base entrances and exits,		
33	D. Toll plaza lanes,		
34	E. Movable bridges (see Chapter 4J),		
35	F. Automated Flagger Assistance Devices (see Chapter 6E), and		
36	G. Grade crossings (see Part 8).		
37	Gates are sometimes used to periodically close a roadway or a ramp. Some examples of such uses are the		
38	following:		
39	A. Closing ramps to implement counter flow operations for evacuations,		
40	B. Closing ramps that lead to reversible lanes, and		
41	C. Closing roadways for weather events such as snow, ice, or flooding, or for other emergencies. Not		
42	needed – does not provide added value to the MUTCD		
43	Standard:		
44	Except as provided in Paragraph 6, gate arms, if used, shall be fully retroreflectorized		
45	retroreflective on both sides, have vertical stripes alternately red and white at 16-inch intervals		
46	measured horizontally as shown in Figure 8C-1. The width (which becomes the height of the		
47	retroreflective sheeting when the gate is in the down position) of the retroreflective sheeting on the from		
48	of the gate arm shall be at least 4 inches.		
49	Option:		

If used on a one-way roadway or ramp, the <u>retroreflectorization retroreflective sheeting</u> may be omitted on the side of the gate <u>(or rolling fence)</u> facing away from approaching traffic. <u>Incorporates last Option statement</u>

Where gate arms are used to block off ramps into reversible lanes or to redirect approaching traffic, the red and white striping may be angled such that the stripes slope downward at an angle of 45 degrees toward the side of the gate arm on which traffic is to pass.

Standard:

 The gate arm shall extend across the approaching lane or lanes of traffic to effectively block motor vehicle and/or pedestrian travel as appropriate.

When gate arms are in the vertical position or rotated to an open position, the closest part of the gate arm and support shall have a lateral offset of at least 2 feet from the face of the curb or the edge of the traveled way.

When gate arms that are located in the median or on an island are in the horizontal position or rotated to a closed position, the closest part of the counterweight or its supports shall have a lateral offset of at least 2 feet from the face of the curb or the edge of the traveled way of the open roadway on the opposite side of the median or island.

Guidance:

When a gate that is rotated in a horizontal plane is in the position where it is parallel to traffic (indicating that the roadway is open), the outer end of the gate arm should be rotated to the downstream direction (from the perspective of traffic in the lane adjacent to the gate support) to prevent spearing if the gate is struck by an errant vehicle.

If a pedestrian route is present and if it is not intended that pedestrian traffic be controlled by the gate, a minimum of 2 feet of lateral offset from supports, posts, counterweights, and gate mechanisms should be provided when the gate arm is in the open position and when the gate arm is in the closed position such that pedestrian travel is not impeded.

Option:

Red lights may be attached to traffic gates.

Standard:

If red lights are attached to a traffic gate, the red lights shall be steadily illuminated or flashed only during the period when the gate is in the horizontal or closed position and when the gate is in the process of being opened or closed.

Except as provided in Paragraph 163, rolling sections of fence, if used, shall include either a horizontal strip of retroreflectorized retroreflective sheeting on both sides of the fence with vertical stripes alternately red and white at 16-inch intervals measured horizontally to simulate the appearance of a gate arm in the horizontal position, or one or more Type 4 object markers (see Section 2C.6672), or both. If a horizontal strip of retroreflectorized retroreflective sheeting is used, the bottom of the sheeting shall be located 3.5 to 4.5 feet above the roadway surface.

Option:

If used on a one-way roadway or ramp, the retroreflectorization may be omitted on the side of the fence-facing away from approaching traffic. Incorporated into similar paragraph for gates

1		CHAPTER 2C. WARNING SIGNS AND OBJECT MARKERS
2		
3	Chapter 2C	Subchapter and Section Organization
4 5	General	
6	2C.01	Function and Application of Warning Signs
7	$\frac{2\text{C.01}}{2\text{C.02}}$	Design of Warning Signs
8	2C.03	Size of Warning Signs
9	2C.04	Placement of Warning Signs
10 11	2C.05	lignment Warning Signs Horizontal Alignment Warning Signs – General
12	2C.05 2C.06	Device Selection for Changes in Horizontal Alignment
13	2C.07	Horizontal Alignment Signs (W1-1 through W1-5, W1-11, W1-15)
13 14	2C.07 2C.08	Chevron Alignment Sign (W1-8)
15	2C.08	Combination Horizontal Alignment/Intersection Signs (W1-10 Series)
16	2C.10	One-Direction Large Arrow Sign (W1-6)
17	2C.11	Truck Rollover Sign (W1-13)
18	2C.12	Advisory Exit and Ramp Speed Signs (W13-2 and W13-3) and Combination Horizontal
19	<u> 2C.12</u>	Advisory Exit and Ramp Speed Signs (W13-2 and W13-3) and Combination Horizontal Alignment/Advisory Exit and Ramp Speed Signs (W13-6 through W13-11)
20	2C.13	Vehicle Speed Feedback Sign (W13-20, W13-20aP)
		•
21		le Warning Signs and Plaques
22	2C.14	Hill Signs (W7-1, W7-1a)
23 24	2C.15 2C.16	Truck Escape Ramp Signs (W7-4 Series) HILL BLOCKS VIEW Sign (W7-6)
	-	
25		ometry Warning Signs
26	2C.17	ROAD NARROWS Sign (W5-1)
27	2C.18	NARROW BRIDGE and NARROW UNDERPASS Signs (W5-2, W5-2a)
28	2C.19	ONE LANE BRIDGE and ONE LANE UNDERPASS Signs (W5-3, W5-3a)
29	2C.20	Divided Highway Sign (W6-1)
30	2C.21	Divided Highway Ends Sign (W6-2)
31	2C.22	Freeway or Expressway Ends Signs (W19 Series)
32	2C.23	Double Arrow Sign (W12-1)
33 34	2C.24	DEAD END/, NO OUTLET, and ROAD ENDS Signs (W14-1, W14-1a, W14-2, W14-2a, W2 26 W2 26)
3 4 35	2C.25	<u>W8-26, W8-26a)</u> Low Clearance Signs (W12-2, and W12-2a, W12-2b)
36		l Weather Condition Signs and Plaques
37	2C.26	BUMP and DIP Signs (W8-1, W8-2)
38	2C.27	SPEED HUMP Sign (W17-1)
39	2C.28	DRAW BRIDGE Sign (W3-6)
40	2C.29	PAVEMENT ENDS Sign (W8-3)
41	2C.30	Shoulder Signs (W8-4, W8-9, W8-17, W8-23, W8-25)
42	2C.31	Surface Condition Signs (W8-5, W8-7, W8-8, W8-11, W8-13, and W8-14)
43	2C.32	Warning Signs and Plaques for Motorcyclists (W8-15, W8-15P, and W8-16)
44 45	2C.33	NO CENTER LINE Sign (W8-12)
45 46	2C.34 2C.35	NO TRAFFIC SIGNS Sign (W18-1) Weather Condition Signs (W8-18, W8-19, W8-21, and W8-22)
	<u>2C.33</u>	weather Condition Signs (w8-18, w8-19, w8-21, and w8-22)
47		ol and Intersection Signs and Plaques
48	2C.36	Advance Traffic Control Signs (W3-1, W3-2, W3-3, W3-4)
49	2C.37	Actuated Advance Intersection Signs (W2-10 through W2-12))
50	2C.38	Advance Ramp Control Signal Signs (W3-7 and W3-8)
51	2C.39	NEW TRAFFIC PATTERN and SIGNAL OPERATION AHEAD Signs (W23-2, W23-2a)
52 52	2C.40	Reduced Speed Limit Ahead Signs (W3-5, W3-5a, W3-5b, W3-5c)
53	2C.41	WATCH FOR STOPPED TRAFFIC Sign (W23-3)
54	2C.42	Intersection Warning Signs (W2-1 through W2-8)

1	2C.43	Two-Direction Large Arrow Sign (W1-7)
2	2C.44	Traffic Signal Oncoming Extended Green Signs (W25-1, W25-2)
3	Merging and	Passing Signs and Plaques
4	2C.45	Merge Signs (W4-1, W4-5)
5	2C.46	Added Lane Signs (W4-3, W4-6)
6	2C.47	Lane Ends Signs (W4-2, W9-1)
7	2C.48	Lanes Merge Signs (W9-4, W4-8)
8	2C.49	HEAVY MERGE FROM LEFT (RIGHT) Sign (W4-7)
9	2C.50	RIGHT (LEFT) LANE FOR EXIT ONLY Sign (W9-7)
10	2C.51	Two-Way Traffic Sign (W6-3)
11	2C.52	Two-Way Traffic on a Three-Lane Roadway Sign (W6-5, W6-5a)
12	2C.53	NO PASSING ZONE Sign (W14-3)
13	Miscellaneou	s Warning Signs
14	2C.54	Vehicular Traffic Warning Signs (W8-6, W11-1, W11-5, W11-5a, W11-8, W11-10, W11-11,
15		W11-12P, W11-14, W11-15, and W11-15a)
16	2C.55	Non-Vehicular Warning Signs (W11-2, W11-3, W11-4, W11-6, W11-7, W11-9, and W11-16
17		through W11-22)
18	2C.56	Playground Sign (W15-1)
19	Supplementa	1 Plagues
20	2C.57	Use of Supplemental Warning Plaques
21	2C.58	Design of Supplemental Warning Plaques
22	2C.59	Advisory Speed Plaque (W13-1P) and Confirmation Advisory Speed Plaque (W13-1aP)
23	2C.60	NEW Plaque (W16-15P)
24	2C.61	Distance Plaques (W16-2 Series, W16-3 Series, W16-4P, W7-3aP)
25	2C.62	Supplemental Arrow Plaques (W16-5P, W16-6P)
26	2C.63	Hill-Related Plaques (W7-2 Series, W7-3 Series)
27	2C.64	Advance Street Name Plaque (W16-8P, W16-8aP)
28	2C.65	CROSS TRAFFIC DOES NOT STOP Plaque (W4-4P)
29	2C.66	IN ROAD and IN STREET Plaques (W16-1P, W16-1aP)
30	2C.67	Except Bicycles Plaque (W16-20P)
31	2C.68	Photo Enforced Plaque (W16-10P)
32	Object Marke	ers
33	2C.69	Object Marker Design and Placement Height
34	2C.70	Object Markers for Obstructions Within the Roadway
35	2C.71	Object Markers for Obstructions Adjacent to the Roadway
36	2C.72	Object Markers for Ends of Roadways
37	-	
38		

1 <u>GENERAL</u>

2 Section 2C.01 Function of Warning Signs Not needed, this information is elsewhere in MUTCD

3 Support:

4

5

6

7

8

10

11

12 13

14

15

16

18

19

20

21

22

23

24

25

26 27

28

29

30

31

33

34

35

36

37

38

39

40

41

42.

43 44

45

47

48

Warning signs call attention to unexpected conditions on or adjacent to a highway, street, or private roads open to public travel and to situations that might not be readily apparent to road users. Warning signs alert road users to conditions that might call for a reduction of speed or an action in the interest of safety and efficient traffic operations.

Section 2C.02 2C.01 Function and Application of Warning Signs

9 **Standard:**

The use of warning signs shall be based on an engineering study or on engineering judgment.

Warning signs shall be retroreflective or illuminated (see Section 2A.20). Added to be consistent with Chapter 2B

Guidance:

The use of warning signs should be kept to a minimum as the unnecessary use of warning signs tends to breed disrespect for all signs. In situations where the condition or activity is seasonal or temporary, the warning sign should be removed or covered when the condition or activity does not exist.

17 Option:

Consistent with the provisions of Chapter 2L, changeable message signs may be used to display a warning message.

Consistent with the provisions of Chapter 4L, a Warning Beacon may be used in combination with a standard warning sign.

Support:

The categories of warning signs are shown in Table 2C-1.

Warning signs provided in this Manual cover most of the conditions that are likely to be encountered. Additional warning signs for low volume roads (as defined in Section 5A.01), temporary traffic control zones, school areas, grade crossings, and bicycle facilities are discussed in Parts 5 through 9, respectively. Not needed

Section 1A.09 contains information regarding the assistance that is available to jurisdictions that do not have engineers on their staffs who are trained and/or experienced in traffic control devices. Not needed, this is covered in 1D.05

Section 2C.03 2C.02 Design of Warning Signs

32 Standard:

Except as provided in Paragraph 2 or unless specifically designated otherwise, all warning signs shall be diamond-shaped (square with one diagonal vertical) with a black legend and border on a yellow background. Warning signs shall be designed in accordance with the sizes, shapes, colors, and legends contained in the "Standard Highway Signs and Markings" book publication (see Section 1A.1105).

Option:

A warning sign that is larger than the size shown in the Oversized column in Table 2C-2 2C-1 for that particular sign may be diamond-shaped or may be rectangular or square in shape.

Support:

The use of a shape other than diamond-shaped is typically for overhead installations.

Section 2A.05 contains information on allowable methods to accommodate a diamond-shaped warning sign where the lateral space available in which to install a diamond-shaped warning sign is constrained, such as in urban locations, when mounting on a narrow median barrier or adjacent to a retaining wall, including the display of the standard legend in a vertically oriented rectangle.

46 Option:

Except for symbols on warning signs, minor modifications may be made to the design provided that the essential appearance characteristics are met. Modifications may be made to the symbols shown on combined

horizontal alignment/intersection signs (see Section 2C.112C.09) and intersection warning signs (see Section 22C.46 2C.4442) in order to approximate the geometric configuration of the intersecting roadway(s).

Word message warning signs other than those provided in this Manual may be developed and installed by State and local highway agencies for conditions otherwise not addressed by standard signs (see Section 2A.04).

Warning signs regarding conditions associated with pedestrians, bicyclists, and playgrounds may have a black legend and border on a yellow or fluorescent yellow-green background.

Warning signs may be enhanced with LEDs that illuminate steadily or flash at acceptable rates (See Section 2A.20) in the sign border matching the background color of the sign.

Standard:

Warning signs regarding conditions associated with school buses and schools and their related supplemental plaques shall have a black legend and border on a fluorescent yellow-green background-(see Section 7B.0701).

Table 2C-1. Warning Signs and Plaque Sizes

Section 2C.04 2C.03 Size of Warning Signs

Standard:

Except as provided in Section 2A.1107, the sizes for warning signs shall be as shown in Table 2C-2

18 2C-1.

19 Support:

Section 2A.11 <u>07</u> contains information regarding the applicability of the various columns in Table 2C 2. <u>2C-1.</u>

22 Standard:

Except as provided in Paragraph 5, the minimum size for all diamond-shaped warning signs facing traffic on a multi-lane conventional road where the posted speed limit is higher than 35 mph shall be 36 x 36 inches.

The minimum size for supplemental warning plaques that are not included in Table $\frac{2C-2}{2C-1}$ shall be as shown in Table $\frac{2C-3}{2C-2}$.

Table 2C-2. Minimum Size of Supplemental Warning Plaques

Option:

If a diamond-shaped warning sign is placed on the left-hand side of a multi-lane roadway to supplement the installation of the same warning sign on the right-hand side of the roadway, the minimum size identified in the Single Lane column in Table 2C 22C-1 may be used.

Signs and plaques larger than those shown in Tables $\frac{2C-2}{2C-1}$ and $\frac{2C-3}{2C-2}$ may be used (see Section 2A.11).

35 Guidance:

The minimum size for all diamond-shaped warning signs facing traffic on exit and entrance ramps at major interchanges connecting an Expressway or Freeway with an Expressway or Freeway (see Section 2E.11) should be the size identified in Table 2C 2C-1 for the mainline roadway classification (Expressway or Freeway). If a minimum size is not provided in the Freeway Column, the Expressway size should be used. If a minimum size is not provided in the Freeway or the Expressway Column, the Oversized size should be used.

The minimum size for all diamond-shaped warning signs facing traffic on exit and entrance ramps at all other interchanges (see Section 2E.11) should be 36" by 36".

The typical size of warning signs used on low-volume rural roads with operating speeds of 30 mph or less should be in accordance with the minimum column of Table 2C-1.

Section 2C.052C.04 Placement of Warning Signs

47 Support:

For information on placement of warning signs, see Sections 2A. 1612 to 2A. 2117.

The time needed for detection, recognition, decision, and reaction is called the Perception-Response Time (PRT). Table 2C 4 2C-3 is provided as an aid for determining warning sign location. The distances shown in Table 2C 4 2C-3 can be adjusted for roadway features, other signing, and to improve visibility.

Guidance:

Warning signs should be placed so that they provide an adequate PRT. The distances contained in Table 2C-4-2C-3 are for guidance purposes and should be applied with engineering judgment. Warning signs should not be placed too far in advance of the condition, such that drivers might tend to forget the warning because of other driving distractions, especially in urban areas. Not needed

Minimum spacing between warning signs with different messages should be based on the estimated PRT for driver comprehension of and reaction to the second sign.

The effectiveness of the placement of warning signs should be periodically evaluated under both day and night conditions.

Table 2C-3. Guidelines for Advanced Placement of Warning Signs

Option:

Warning signs that advise road users about conditions that are not related to a specific location, such as Deer Crossing or SOFT SHOULDER, may be installed in an appropriate location, based on engineering judgment, since they are not covered in Table 2C-4. This information is in Table 2C-3, not needed in the text

2

3 4

5

6

7

8

9

10

11 12

13 14

1516

17

18

19

20

21

22 23

24

25

27

28

29

32 33

34

35

36

37

38 39

40

41

42

43 44

46

47

48

49

52

54

Section 2C.06 2C.05 Horizontal Alignment Warning Signs - General

Support:

A variety of horizontal alignment warning signs (see Figure 2C-1), pavement markings (see Chapter 3B), and delineation (see Chapter 3F3G) can be used to advise motorists of a change in the roadway alignment. Uniform application of these traffic control devices with respect to the amount of change in the roadway alignment conveys a consistent message establishing driver expectancy and promoting effective roadway operations. The design and application of horizontal alignment warning signs to meet those requirements are addressed in Sections 2C.062C.05 through 2C.15.2C.13.

In advance of horizontal curves on freeways, on expressways, and on roadways with more than 1,000 AADT that are functionally classified as arterials or collectors, horizontal alignment warning signs shall be used in accordance with Table 2C-5 based on the speed differential between the roadway's posted or statutory speed limit or 85th percentile speed, whichever is higher, or the prevailing speed on the approach to the curve, and the horizontal curve's advisory speed. First portion of paragraph

deleted; second phrase relocated to Section 2C.06

Option:

Horizontal Alignment Warning signs may also be used on other roadways or on arterial and collector roadways with less than 1,00 AADT based on engineering judgment.

The following list identifies treatments that might be used in advance of or within a change in horizontal alignment.

- A. Horizontal alignment signs (Turn (W1-1), Curve (W1-2, W1-10 series, W1-11, W1-13, W1-15),

 Reverse Turn (W1-3), Reverse Curve (W1-4), Winding Road (W1-5), Exit Speed (W13-2), Ramp

 Speed (W13-3), Combination Horizontal Alignment (Advisory Exit or Ramp Speed W13-6 through W13-11) signs.
- B. Advisory Speed Plaque (W13-1P)
- 26 <u>C. Chevrons (W1-8)</u>
 - D. Delineators (Chapter 3G)
 - E. One Direction Large Arrow (W1-6) sign
 - F. Raised Retroreflective Pavement Markers (Section 3B.15 through 3B.16).
- G. Sign or marking conspicuity enhancements (See Section 2A.11)
- 31 H. Wide Edge Lines.
 - I. Pavement Word, Symbol and Arrow markings (symbol or words) (Section 3B.20 through 3B.22)
 - J. Rumble Strips
 - K. Vehicle Speed Feedback Sign (Section 2C.13)
 - L. Speed reduction markings (Section 3B.28)

In addition, considerations other than traffic control devices such as improved surface friction (high friction surface treatments), pavement edge treatments, lighting improvements, increased super elevation, and rumble strips might be used in advance of or within a change in horizontal alignment.

Guidance:

Except as provided in Section 2C.06, the selection of traffic control devices used to warn road users of a change in horizontal alignment or to provide guidance in navigating the change in horizontal alignment should be based on consideration of one or more of the following factors:

- A. The speed of traffic on the approach to the change in horizontal alignment.
- B. The recommended advisory speed for the change in horizontal alignment
- 45 *C. The difference between the speed limit and the advisory speed or the speed differential,*
 - for the change in horizontal alignment.
 - D. Daily traffic volumes on the roadway.
 - E. The typical mix of vehicle types on the roadway
 - *F. Sight distance throughout the change in horizontal alignment.*
- 50 <u>G. Other types of traffic control devices that are used in advance of and within the change in horizontal</u> alignment on the same roadway segment.
 - H. The crash history of the change in horizontal alignment.
- 53 I. The presence of driveways or intersections within the curve radius

Figure 2C-1. Horizontal Alignment Signs and Plaques

Section 2C.06 Device Selection for Changes in Horizontal Alignment

2 **Standard:**

1

5

7

9

10

11

12

13

14 15

16

17

18

19

20

21

23

24

25

26

27

28

29 30

31

32 33

34

35 36

37

38

39 40

41

42 43

44 45

46

47

48

49

3 Horizontal alignment warning signs, as indicated in Table 2C-4b, shall be used in advance of 4 horizontal curves in accordance with the criteria shown in Table 2C-4a, except as provided in paragraphs 3, 5, and 6 of this section. The speed differential shall be the difference between the 6 horizontal curve's advisory speed and the roadway's posted or statutory speed limit or 85th percentile speed, whichever is higher, or the prevailing speed on the approach to the curve. Second sentence 8 relocated from new Section 2C.05 and revised

Support:

Table 2C-4a represents existing AADT, type of roadway, and whether or not there are existing markings. Option:

A One Direction Large Arrow (W1-6) sign may be used in place of or to supplement delineators (see Section 3G.03) or Chevrons (W1-8) when geometric conditions limit the number of delineators or chevrons that are visible or when the number of delineators or chevrons that can be installed within the change in horizontal alignment is less than the spacing specified in Sections 2C.08 or 3F.04.

Additional or supplemental devices may be used for a change in horizontal alignment on the basis of engineering judgment.

Devices for changes in horizontal alignment may be omitted when the speed limit on the approach to an alignment change is 20 mph or less.

Devices for changes in horizontal alignment may be omitted on urban streets with an AADT of 1000 vehicles per day or less on the basis of engineering judgment.

22 Support:

> For purposes of selecting traffic control devices for changes in horizontal alignment, an arterial or collector is considered to have payement markings when either a centerline, edge lines, or both are present. See Sections 3B.02 and 3B.09 for centerline and edge line provisions.

Section 2C.07 Horizontal Alignment Signs (W1-1 through W1-5, W1-11, W1-15)

Standard:

If Table 2C-54a indicates that a horizontal alignment sign (see Figure 2C-1) is required, recommended, or allowed, the sign installed in advance of the curve shall be a Curve (W1-2) sign unless a different sign is recommended or allowed by the provisions of this Section.

A Turn (W1-1) sign shall be used instead of a Curve sign in advance of curves that have advisory speeds of 30 mph or less (see Figure 2C-2). Relocated to Guidance below.

Guidance:

A Turn sign (W1-1) should be used instead of a Curve sign (W1-2) in advance of curves when the advisory speed is half or less of the posted speed or a speed differential of 25 MPH or more. Revised and relocated from Standard above.

Where there are two changes in roadway alignment in opposite directions that are separated by a tangent distance of less than 600 feet, the Reverse Turn (W1-3) sign should be used instead of multiple Turn (W1-1) signs or the Reverse Curve (W1-4) sign should be used instead of multiple Curve (W1-2) signs.

Support:

Figure 2C-2 provides an example of warning signs used for a turn.

A Winding Road (W1-5) sign may be used instead of multiple Turn (W1-1) or Curve (W1-2) signs where there are three or more changes in roadway alignment each separated by a tangent distance of less than 600 feet.

A NEXT XX MILES (W7-3aP) supplemental distance plaque (see Section 2C.55 2C.60) may be installed below the Winding Road sign where continuous roadway curves exist for a specific distance.

If the curve has a change in horizontal alignment of 135 degrees or more, the Hairpin Curve (W1-11) sign may be used instead of a Curve or Turn sign.

1 2	If the curve has a change of direction of approximately 270 degrees, such as on a cloverleaf interchange ramp, the 270-degree Loop (W1-15) sign may be used instead of a Curve or Turn sign.
3	Guidance:
4 5	When the Hairpin Curve sign or the 270-degree Loop sign is installed, either a One-Direction Large Arrow (W1-6) sign or Chevron Alignment (W1-8) signs should be installed on the outside of the turn or curve.
6	Figure 2C-2. Example of Warning Signs for a Turn
7	NEW Table 2C-4a. Applications for the Selection of Devices for Changes in Horizontal
8	Alignment Alignment
9	NEW Table 2C-4b. Selection of Devices for Changes in Horizontal Alignment
10	Section 2C.092C.08 Chevron Alignment Sign (W1-8)
11	Standard:
12 13 14	The use of the Chevron Alignment (W1-8) sign (see Figures 2C-1 and 2C-2) to provide additional emphasis and guidance for a change in horizontal alignment shall be in accordance with the information shown in Table $\frac{2C-5}{2C-4b}$.
15	Option:
16	When used, Chevron Alignment signs may be used instead of or in addition to standard delineators.
17	Standard:
18 19	The Chevron Alignment sign shall be a vertical rectangle. No border shall be used on the Chevron Alignment sign.
20 21 22 23	If used, Chevron Alignment signs shall be installed on the outside of a turn or curve, in line with and at approximately a right angle to approaching traffic. Chevron Alignment signs shall be installed at a minimum height of 4 feet, measured vertically from the bottom of the sign to the elevation of the near edge of the traveled way.
24	Guidance:
25 26	The approximate spacing of Chevron Alignment signs on the turn or curve measured from the point of curvature (PC) should be as shown in Table $\frac{2C-6}{2C-5}$.
27 28	<u>If used,The</u> Chevron Alignment signs should be visible for a sufficient distance to provide the road user with adequate time to react to the change in alignment.
29	Option:
30 31	LEDs may be used to enhance the conspicuity of Chevron Alignment signs (See Section 2A.11) and if vehicle activated, the LEDs may be flashed on all signs concurrently.
32	Standard:
33	LEDs shall not be flashed from one sign to the next along the curve or turn.
34 35	The LEDs used in the Chevron Alignment sign shall consist of yellow LEDs outlining the chevron symbol.
36 37 38	Chevron Alignment signs shall not be placed on the far side of a T-intersection facing traffic on the stem approach to warn drivers that a through movement is not physically possible, as this is the function of a Two-Direction (or One-Direction) Large Arrow sign.
39	Chevron Alignment signs shall not be used to mark obstructions within or adjacent to the roadway,
40 41	including the beginning of guardrails or barriers, as this is the function of an object marker (see Section $\frac{2C.63}{2C.69}$).
42 43	Section 2C.10 Combination Supplemental Horizontal Alignment/Advisory Speed Signs (W1-1a, W1-2a) Section deleted
44	Table 2C-5. Typical Spacing of Chevron Alignment Signs on Horizontal Curves
45	Section 2C.112C.09 Combination Horizontal Alignment/Intersection Signs (W1-10 Series)
46	Option:

The Turn (W1-1) sign, the Curve (W1-2) sign, and the Reverse Curve (W1-4) may be combined with the Cross Road (W2-1) sign or the Side Road (W2-2 or W2-3) sign to create a combination Horizontal

Alignment/Intersection (W1-10 series) sign (see Figure 2C-1) that depicts the condition where an intersection occurs within or immediately adjacent to a turn or curve.

Guidance:

3

4

5

6

7

8

9

10

11

12

13

14

16

17 18

19

20

21

22

23

24

25

26

27

28

29

31

32

33

34

38

40

41

42

43 44

45

46

47 48

49

50

51

Elements of the combination Horizontal Alignment/Intersection sign related to horizontal alignment should comply with the provisions of Section-2C.07, and elements related to intersection configuration should comply with the provisions of Section-2C.46 2C.42. The symbol design should approximate the configuration of the intersecting roadway(s). No more than one Cross Road or two Side Road symbols should be displayed on any one combination Horizontal Alignment/Intersection sign.

Standard:

The use of the combination Horizontal Alignment/Intersection sign shall -be in accordance with the provisions of Section 2C.07 for the appropriate Turn or Curve sign information shown in Table 2C-5.

Section 2C.12 One-Direction Large Arrow Sign (W1-6)

15 Option:

A One-Direction Large Arrow (W1-6) sign (see Figure 2C-1) may be used either as a supplement or alternative to Chevron Alignment signs or delineators in order to delineate a change in horizontal alignment (see Figure 2C-2).

A One-Direction Large Arrow (W1-6) sign may be used to supplement a Turn or Reverse Turn sign (see Figure 2C-2) to emphasize the abrupt curvature.

Standard:

The One-Direction Large Arrow sign shall be a horizontal rectangle with an arrow pointing to the left or right.

If used, the One-Direction Large Arrow sign shall be installed on the outside of a turn or curve in line with and at approximately a right angle to approaching traffic.

The One-Direction Large Arrow sign shall not be used where there is no alignment change in the direction of travel, such as at the beginnings and ends of medians or at center piers.

The One-Direction Large Arrow sign directing traffic to the right shall not be used in the central island of a roundabout.

30 Option

The One-Direction Large Arrow sign directing traffic to the right may be used in the central island of a roundabout.

Support:

Examples of regulatory and warning signs for roundabouts are shown in Figures 2B-21 through 2B-23.

35 Guidance:

36 If used, <u>T</u>the One-Direction Large Arrow sign should be visible for a sufficient distance to provide the road user with adequate time to react to the change in alignment.

Section 2C.13 2C.11 Truck Rollover Warning Sign (W1-13)

39 Option:

A Truck Rollover Warning (W1-13) sign (see Figure 2C-1) may be used in lieu of a horizontal alignment warning sign to warn drivers of vehicles with a high center of gravity, such as trucks, tankers, and recreational vehicles, of a curve or turn where geometric conditions might contribute to a loss of control and a rollover as determined by an engineering study. there are:

- A. Past incidents of truck rollovers at the specific location;
- B. High volumes of trucks;
- C. Or where the differential (See Section 2C.06) might pose a greater risk for vehicles with high centers of gravity.

Guidance:

Where engineering judgement determines the need for the installation of a Truck Rollover (W1-13) sign, it should be located in advance of the curve where the horizontal alignment warning sign would otherwise be located.

Support:

Among the established engineering practices that are appropriate for the determination of the truck-rollover potential of a horizontal curve are the following:

- A. An accelerometer that provides a direct determination of side friction factors
- B. A design speed equation
- C. A traditional ball-bank indicator using 10 degrees of ball-bank

Standard:

If a Truck Rollover Warning (W1-13) sign is used, it shall be accompanied by an Advisory Speed (W13-1P) plaque indicating the recommended speed for vehicles with a higher center of gravity.

Option:

The Truck Rollover Warning sign may be displayed as a static sign, as a static sign supplemented by a flashing-warning beacon, or as a changeable message blank-out sign activated by the detection of an approaching vehicle with a high center of gravity that is traveling in excess of the recommended speed for the condition.

A Vehicle Speed Feedback (W13-20) sign (see Section 2C.13) may be used in conjunction with a Truck Rollover Warning sign.

Support:

The curved arrow on the Truck Rollover Warning sign shows the direction of roadway curvature. The truck tips in the opposite direction.

Section 2C.14 2C.12 Advisory Exit and Ramp Speed Signs (W13-2 and W13-3) and Combination Horizontal Alignment/Advisory Exit and Ramp Speed Signs (W13-6 through W13-13)

Standard:

The use of Advisory Exit Speed (W13-2) sign in advance of a freeway and expressway exit and the Advisory Ramp Speed (W13-3) sign in advance of a conventional road ramp to another roadway or roadside facility signs on freeway and expressway ramps shall be used in accordance with the information shown in Table 2C-52C-4b.

Option:

The Combination Horizontal Alignment/Advisory Exit Speed (W13-6, W13-8, W13-10, W13-12) signs may be use in lieu of the Advisory Exit Speed (W13-2) sign and the combination Horizontal Alignment/Advisory Ramp Speed (W13-7, W13-9, W13-11, W13-13) signs may be use in lieu of the W13-3 sign.

Standard:

Geometries represented on the Advisory Exit Speed, Advisory Ramp Speed, Combination

Horizontal Alignment/Advisory Exit and Combination Horizontal Alignment/Advisory Ramp Speed
signs (See Figure 2C-1) shall be limited to the standard signs shown in this manual.

The Advisory Exit Speed and Advisory Ramp Speed signs on turning roadways, exits and ramps shall be used when the difference between the mainline roadway speed limit and the exit or ramp advisory speed in the vicinity of the departure is 20 mph or greater.

Guidance:

The Advisory Exit Speed and Advisory Ramp Speed signs on turning roadway ramps should be used when the difference between the mainline roadway speed limit and the exit or ramp advisory speed in the vicinity of the departure is 15 mph or greater.

If used, the Advisory Exit Speed sign <u>and the Combination Horizontal Alignment/Advisory Exit Speed sign</u> should be installed along the deceleration lane. <u>See Section 2C.08 for the determination of the displayed advisory speed.</u> and the advisory speed displayed should be based on an engineering study. When a Truck Rollover (W1-13) sign (see Section 2C.13) is also installed for the ramp, the advisory exit speed should be based on the truck advisory speed for the horizontal alignment using recommended engineering practices.

If used, tThe Advisory Exit Speed and the Combination Horizontal Alignment/Advisory Exit signs should be visible in time for the road user to decelerate and make an exiting maneuver.

Regulatory Speed Limit signs (see Section 2B.22 should not be located in the vicinity of exit ramps or deceleration lanes, particularly where they will conflict with the advisory speed displayed on the Advisory

1 Exit or Ramp Speed signs. 2 Support: 3 Table 2C-42C-3 lists recommended advance sign placement distances for deceleration to various advisory 4 speeds. 5 Option: 6 Where there is a need to remind road users of the recommended advisory speed, a horizontal alignment 7 warning sign with an advisory speed plaque displaying the same advisory speed may be installed at a 8 downstream location along the ramp. 9 Guidance: 10 If the ramp curvature changes to the extent that it warrants a lower advisory speed, a horizontal 11 alignment warning sign with the new advisory speed should be displayed in advance of the change in 12 curvature. Option: 13 14 The One-Direction Large Arrow (W1-6) sign may be installed beyond the exit gore on the outside of the 15 curve to provide additional warning of an immediate change in curvature. When used in conjunction with the 16 exit speed, the One-Direction Large Arrow (W1-6) sign may be supplemented with a Confirmation Advisory Speed Plaque (W13-1aP) when the plaque is not used with the Exit Gore (E5-1 series) sign. 17 18 Guidance: 19 The horizontal alignment symbol displayed on the Combination Horizontal Alignment/Advisory Exit and 20 Ramp Speed signs should be consistent with the horizontal geometry of the ramp-. 21 If used, the Advisory Ramp Speed sign should be installed on the ramp to confirm the ramp advisory 22 speed. 23 If used, Chevron Alignment (W1-8) signs and/or One-Direction Large Arrow (W1-6) signs should be 24 installed on the outside of the exit curve as described in Sections 2C.09 and 2C.122C.10. 25 Option: 26 Where there is a need to remind road users of the recommended advisory speed, a horizontal alignment 27 warning sign with an advisory speed plaque may be installed at or beyond the beginning of the exit curve or 28 on the outside of the curve, provided that it is apparent that the sign applies only to exiting traffic. These signs 29 may also be used at intermediate points along the ramp, especially if the ramp curvature changes and the subsequent curves on the ramp have a different advisory speed than the initial ramp curve. 30 31 Support: 32 Figure 2C-3 shows an example of advisory speed signing for an exit ramp.

Figure 2C-3. Example of Advisory Speed Signing for an Exit Ramp

Section 2C.15 Combination Horizontal Alignment/Advisory Exit and Ramp Speed Signs (W13-6 Series and W13-7) Combined with Section 2C.12 above

Section 2C.13 Vehicle Speed Feedback Sign (W13-20, W13-20aP)

37 Option:

33

34

35

36

38

39

40 41 42

43 44

45

46

47

48

49

50

A Vehicle Speed Feedback (W13-20) sign or (W13-20aP) plaque (see Figure 2C-4) that displays the speed of an approaching vehicle back to the vehicle operator may be used to provide warning to drivers of their speed in relation to either a speed limit or horizontal alignment warning advisory speed sign.

Standard:

When used as a warning to motorist of their speed in relation to the posted speed limit, the Vehicle Speed Feedback Plaque (W13-20P) shall be mounted below a Speed Limit (R2-1) sign (see Section 2B.23).

When used to supplement a horizontal alignment warning sign advisory speed, the Vehicle Speed Feedback Sign (W13-20) shall be an independent installation near the point of curvature of a horizontal curve (see Section 2C.06).

The legend YOUR SPEED shall be a black legend on a yellow retroreflective background. The changeable legend displaying the speed of the approaching vehicle shall be a yellow luminous legend on a black opaque background.

1 2	The vehicle speed displayed on the changeable portion of the sign shall not flash or change color. The Vehicle Speed Feedback sign and plaque shall not flash, strobe or use other dynamic elements
3	integrated into the changeable legend display. When no vehicles are approaching, the changeable
4	display shall not display a legend.
5	Guidance:
6 7	The changeable portion of the Vehicle Speed Feedback legend should be approximately the same height, width, and stroke of those on the Speed Limit sign it supplements or is mounted below.
8	When a W13-20P is used with a Speed Limit sign it should be approximately the same width of the Speed
9	Limit sign it is mounted below.
10	Figure 2C-4. Vehicle Speed Feedback Signs
11	

3

4

5

6

7

8

9

10

11

12

13 14

15

16

17

18

19

2021

22

23

24

25

26

27

29

30

31

32.

33

34

35

36

38

39

40

41

42

44

45

46 47

Section 2C.16 2C.14 Hill Signs (W7-1, W7-1a)

Guidance:

The Hill (W7-1) sign (see Figure 2C-42C-5) should be used in advance of a downgrade on a freeway, expressway, or a conventional road where the length, percent of grade, horizontal curvature, and/or other physical features require special precautions on the part of road users.

The Hill sign and supplemental grade (W7-3P) plaque (see Section 2C.572C.63) used in combination, or the W7-1a sign used alone, should be installed in advance of downgrades for the following conditions:

- A. 5% grade that is more than 3,000 feet in length,
- B. 6% grade that is more than 2,000 feet in length,
- C. 7% grade that is more than 1,000 feet in length,
- D. 8% grade that is more than 750 feet in length, or
- E. 9% grade that is more than 500 feet in length.

These signs should also be installed for steeper grades or where crash experience and field observations indicate a need.

Supplemental plaques (see Section 2C.572C.63) and larger signs should be used for emphasis or where special hill characteristics exist. On longer grades, the use of the Hill sign with a distance (W7-3aP) plaque or the combination distance/grade (W7-3bP) plaque at periodic intervals of approximately 1-mile spacing should be considered.

Standard Deleted, redundant; covered in Section 2C.57

If the percent grade is displayed on a supplemental plaque, the plaque shall be placed below the Hill (W7-1) sign.

Option:

A USE LOW GEAR (W7-2P) or TRUCKS USE LOWER GEAR (W7-2bP) supplemental plaque (see Figure 2C-42C-5) may be used to indicate a situation where downshifting as well as braking might be advisable.

Section 2C.17 2C.15 Truck Escape Ramp Signs (W7-4 Series)

28 Guidance:

Where applicable, truck escape (or runaway truck) ramp advance warning signs (see Figure 2C-42C-5) should be located approximately 1 mile, and 1/2 mile in advance of the grade, and of the ramp. An additional W7-4b or W7-4c A sign also should be placed at the gore.

A RUNAWAY VEHICLES ONLY (R4-10) sign (see Section <u>2B.352B.43</u>) should be installed near the ramp entrance to discourage other road users from entering the ramp. No Parking (R8-3) signs should be placed near the ramp entrance.

Standard:

When truck escape ramps are installed, at least one of the W7-4 series signs shall be used.

37 Option:

A SAND (W7-4dP), GRAVEL (W7-4eP), or PAVED (W7-4fP) supplemental plaque (see Figure 2C 42C-5) may be used to describe the ramp surface. State and local highway agencies may develop appropriate word message signs for the specific situation.

Figure 2C-5. Vertical Grade Signs and Plaques

Section 2C.18 2C.16 HILL BLOCKS VIEW Sign (W7-6)

43 Option:

A HILL BLOCKS VIEW (W7-6) sign (see Figure 2C 45) may be used in advance of on the approach to a crest vertical curve where the vertical curvature provides inadequate stopping sight distance at the posted speed limit. to advise road users to reduce speed as they approach and traverse the hill as only limited stopping sight distance is available.

48 Guidance:

7

When a vertical curve results in a sight distance obstruction to a specific condition beyond the crest of the vertical curve, the sign for the specific condition beyond the vertical crest should be used rather than the HILL BLOCKS VIEW (W7-6) sign.

When a HILL BLOCKS VIEW sign is used, it should be supplemented by an Advisory Speed (W13-1P) plaque indicating the recommended speed for traveling over the hillcrest based on available stopping sight distance.

4

5

6

7

8

9

10

11

12

13

14

16

17

18 19

20

21

23

24

25

26

27

28

29

31

32

33

34

35

36

37

38

39

40

41

42.

43

44

46

47 48

2 Section 2C.19 2C.17 ROAD NARROWS Sign (W5-1)

Guidance:

Except as provided in Paragraph 2, a ROAD NARROWS (W5-1) sign (see Figure 2C-65) should be used in advance of a transition on two-lane roads where the pavement width is reduced abruptly to a width such that vehicles traveling in opposite directions cannot simultaneously travel through the narrow portion of the roadway without reducing speed.

Option:

The ROAD NARROWS (W5-1) sign may be omitted on low-volume local streets that have speed limits of 30 mph or less.

Additional emphasis may be provided by the use of object markers and delineators (see Sections 2C.69 through 2C.65-2C.72 and Chapter 3F3G). The Advisory Speed (W13-1P) plaque (see Section 2C.082C.59) may be used to indicate the recommended speed.

Section 2C.20 2C.18 NARROW BRIDGE and NARROW UNDERPASS Signs (W5-2, W5-2a)

15 Guidance:

A NARROW BRIDGE (W5-2) sign (see Figure 2C-65) should be used in advance of any bridge or culvert having a two-way roadway clearance width of 16 to 18 feet, or any bridge or culvert having a roadway clearance less than the width of the approach travel lanes. Where these conditions exist for an underpass, a NARROW UNDERPASS (W5-2a) sign should be used.

Additional emphasis should be provided by the use of object markers, delineators, and/or pavement markings.

22 Option:

A NARROW BRIDGE sign may be used in advance of a bridge or culvert on which the approach shoulders are narrowed or eliminated. Where these conditions exist for an underpass, a NARROW UNDERPASS (W5-2a) sign may be used.

The NARROW BRIDGE or NARROW UNDERPASS sign may be omitted on low-volume rural roads.

Figure 2C-6. Example of Signing at Narrow or One Lane Underpass

Section 2C.21 ONE LANE BRIDGE and ONE LANE UNDERPASS Signs (W5-3, W5-3a)

30 Guidance:

A ONE LANE BRIDGE (W5-3) sign (see Figure $2C-\underline{65}$) should be used on two-way roadways in advance of any bridge or culvert:

- A. Having a clear roadway width of less than 16 feet, or
- B. Having a clear roadway width of less than 18 feet when commercial vehicles constitute a high proportion of the traffic, or
- C. Having a clear roadway width of 18 feet or less where the sight distance is limited on the approach to the structure.

Where these conditions exist for an underpass, a ONE LANE UNDERPASS (W5-3a) sign should be used.

Additional emphasis should be provided by the use of object markers, delineators, and/or pavement markings.

Option:

The ONE LANE BRIDGE or ONE LANE UNDERPASS sign may be omitted on low-volume rural roads where there is adequate sight distance to the bridge from either approach.

Section 2C.222C.20 Divided Highway Sign (W6-1)

45 Guidance:

A Divided Highway (W6-1) sign (see Figure 2C-795) should be used on the approaches to a section of highway (not an intersection or junction) where the opposing flows of traffic are separated by a median or other physical barrier.

49 **Standard:**

The Divided Highway (W6-1) sign shall not be used instead of a Keep Right (R4-7 series) sign on the approach end of a median island.

Section 2C.23-2C.21 <u>Divided Highway Ends Sign (W6-2)</u>

4 Guidance:

3

5

6

7 8

9

11 12

13

14

15

16

17

18

19

20

21

22

23

25

26

27

29

30

31 32

33

3435

36

37

38

39

40

41

42

43

44

45

46

A Divided Highway Ends (W6-2) sign (see Figure $\frac{2C-5}{2C-7}$) should be used in advance of the end of a section of physically divided highway (not an intersection or junction) as a warning of two-way traffic ahead.

The Two-Way Traffic (W6-3) sign (see Section $\frac{2C.44}{2C.51}$) should be used to give warning and notice of the transition to a two-lane, two-way section.

Section 2C.24 2C.22 Freeway or Expressway Ends Signs (W19 Series)

10 Option:

A FREEWAY ENDS XX MILES (W19-1) sign or a FREEWAY ENDS (W19-3) sign (see Figure 2C-52C-7) may be used in advance of the end of a freeway.

An EXPRESSWAY ENDS XX MILES (W19-2) sign or an EXPRESSWAY ENDS (W19-4) sign (see Figure 2C-52C-7) may be used in advance of the end of an expressway.

The rectangular W19-1 and W19-2 signs may be post-mounted or may be mounted overhead for increased emphasis.

Guidance:

If the reason that the freeway is ending is that the next portion of the freeway is not yet constructed and as a result all traffic must use an exit ramp to leave the freeway, an ALL TRAFFIC MUST EXIT (W19-5) sign (see Figure 2C-52C-7) should be used in addition to the Freeway Ends signs in advance of the downstream end of the freeway.

Figure 2C-7. Miscellaneous Warning Signs

Section 2C.25 2C.23 Double Arrow Sign (W12-1)

24 Option:

The Double Arrow (W12-1) sign-(see Figure 2C-5) may be used to advise road users that traffic is permitted to pass on either side of an island, obstruction, or gore in the roadway. Traffic separated by this sign may either rejoin or change directions.

28 Guidance:

If used on an island, the Double Arrow sign should be mounted near the approach end.

If used in front of a pier or obstruction, the Double Arrow sign should be mounted on the face of, or just in front of, the obstruction. Where stripe markings are used on the obstruction, they should be discontinued to leave a 3-inch space around the outside of the sign.

Section 2C.26 2C.24 DEAD END/, NO OUTLET, and ROAD ENDS Signs (W14-1, W14-1a, W14-2, W14-2a, W8-26, W8-26a)

Option:

The DEAD END (W14-1) sign (see Figure 2C-52C-7) may be used at the entrance of a single road or street that terminates in a dead end or eul de sacturn-around. The NO OUTLET (W14-2) sign (see Figure 2C-52C-7) may be used at the entrance to a road or road network from which there is no other exit.

DEAD END (W14-1a) or NO OUTLET (W14-2a) signs (see Figure 2C-52C-7) may be used in combination with Street Name (D3-1) signs (see Section 2D.432D.45) to warn turning traffic that the cross street ends in the direction indicated by the arrow.

At locations where the cross street does not have a name, the W14-1a or W14-2a signs may be used alone in place of a street name sign.

Standard Guidance:

The DEAD END (W14-1a) and NO OUTLET (W14-2a) signs shall be horizontal rectangles with an arrow pointing to the left or right.

1 When the W14-1 or W14-2 sign is used, the sign shall should be posted as near as practical to the entry 2 point or at a sufficient advance distance to permit the road user to avoid the dead end or no outlet condition 3 by turning at the nearest intersecting street.

4 5

6

7

8

13

14 15

16

17

23

24

25

26

27

28

29

30

31

32

33

34 35

36

37

38

39

40

41

42

43

44

45 46

47

48

49

The DEAD END (W14-1a) or NO OUTLET (W14-2a) signs shall not be used instead of the W14-1 or W14-2 signs where traffic can proceed straight through the intersection into the dead end street or no outlet area.

Option:

9 The ROAD ENDS XX FT (W8-26) or STREET ENDS XX FT (W8-26a) sign (see Figure 2C-128) may 10 be used on the approach to the end of a conventional road or street that terminates in a dead end or turnaround. 11

12 Guidance:

If a W8-26 series sign is used on the approach to the end of a road or street, then Type 4 object markers (see Section 2C.72) should be used to mark the end of the road or street.

Standard:

The W8-26 and W8-26a signs shall not be used in place of the W14-1 series or W14-2 series signs at the entrance to such a road or street.

18 Support:

19 Section 2C.XX contains information on signs for use on the approach to the end of a freeway or 20 expressway.

21 Section 2C.27-2C.25 Low Clearance Signs (W12-2, and W12-2a, W12-2b)

22 **Standard:**

The Low Clearance Advance (W12-2) sign (see Figure 2C-52C-78) shall be used to warn road users of clearances less than 12 inches above the statutory maximum vehicle height.

Guidance:

The actual clearance should be displayed on the Low Clearance (W12-2, W12-2a, and W12-2b) sign to the nearest 1 inch not exceeding the actual clearance. However, in areas that experience changes in temperature causing frost action, a reduction, not exceeding 3 inches, should be used for this condition.

Clearances should be evaluated periodically, particularly when resurfacing operations have occurred.

Relocated from below

Where the clearance is less than the legal maximum vehicle height, the The W12-2 sign with a supplemental distance plaque should <u>also</u> be placed at the nearest intersecting road or wide point in the road at which a vehicle can detour or turn around.

Option: Relocated from below and revised; second sentenced deleted because sign is standardized

The Low Clearance Overhead (W12-2a or W12-2b) sign may be installed on or in advance of the structure to supplement the advance warning sign. If a sign is placed on the structure, it may be a rectangularshape (W12-2a) with the appropriate legend (see Figure 2C-5).

Guidance:

In the case of an arch or other structure under which the clearance varies greatly, two or more Low <u>Clearance Overhead (W12-2a or 12-2b)</u> signs should be <u>used as necessary</u> installed on the structure itself to give information as to the clearances over the entire the low clearance portions of the roadway.

Standard:

If used, the Low Clearance Overhead (W12-2b) sign shall indicate the portion of the structure with low clearance if the posted clearance does not apply to the entire structure.

Guidance: Relocated to above

Clearances should be evaluated periodically, particularly when resurfacing operations have occurred.

Option: Relocated to above

The Low Clearance sign may be installed on or in advance of the structure to supplement the advance warning sign. If a sign is placed on the structure, it may be a rectangular shape (W12 2a) with the appropriate legend (see Figure 2C-5).

ROADWAY AND WEATHER CONDITION SIGNS AND PLAQUES

2 Section <u>2C.28–2C.26</u> <u>BUMP and DIP Signs (W8-1, W8-2)</u>

3 *Guidance*:

1

4

5

7

8

9

10

11

12

13

21

22

23

25

26

27

28

31

32

33

BUMP (W8-1) and DIP (W8-2) signs (see Figure 2C-6) should be used to give warning of a sharp rise or depression in the profile of the road.

6 Option

These signs may be supplemented with an Advisory Speed plaque (see Section 2C.082C.59).

Standard Guidance: Changed from Standard to Guidance

The DIP sign shall should not be used at a short stretch of depressed alignment that might momentarily hide a vehicle.

Guidance:

A short stretch of depressed alignment that might momentarily hide a vehicle should be treated as a nopassing zone when center line striping is provided on a two-lane or three-lane road (see Section 3B.02).

14 Section <u>2C.29</u> <u>2C.27</u> <u>SPEED HUMP Sign (W17-1)</u>

15 Guidance:

The SPEED HUMP (W17-1) sign (see Figure 2C-6) should be used to give warning of a vertical deflection in the roadway that is designed to limit the speed of traffic.

18 If used, the SPEED HUMP sign should be supplemented by an Advisory Speed plaque (see Section 2C.082C.59).

20 Option:

If a series of speed humps exists in close proximity, an Advisory Speed plaque may be eliminated on all but the first SPEED HUMP sign in the series.

The legend SPEED BUMP may be used instead of the legend SPEED HUMP on the W17-1 sign.

24 Support:

Speed humps generally provide more gradual vertical deflection than speed bumps. Speed bumps limit the speed of traffic more severely than speed humps. Other forms of speed humps include speed tables and raised intersections. However, these differences in engineering terminology are not well known by the public, so for signing purposes these terms are interchangeable.

29 Section 2C.39 2C.28 DRAW BRIDGE Sign (W3-6)

30 Standard:

A DRAW BRIDGE (W3-6) sign (see Figure 2C-6) shall be used in advance of movable bridge signals and gates (see Section 4J.024Q.02) to give warning to road users, except in urban conditions where such signing would not be practical. Not needed

34 Section 2C.302C.29 PAVEMENT ENDS Sign (W8-3)

35 Guidance:

A PAVEMENT ENDS (W8-3) word message sign (see Figure 2C-6) should be used where a paved surface changes to either a gravel treated surface or an earth road surface.

38 Option:

An Advisory Speed plaque (see Section 2C.082C.59) may be used when the change in roadway condition requires a reduced speed.

41 Section 2C.312C.30 Shoulder Signs (W8-4, W8-9, W8-17, W8-23, and W8-25)

42 Option:

The SOFT SHOULDER (W8-4) sign (see Figure 2C 62C-8) may be used to warn of a soft shoulder condition.

The LOW SHOULDER (W8-9) sign (see Figure 2C-62C-8) may be used to warn of a shoulder condition where there is an elevation difference of less than 3 inches between the shoulder and the travel lane.

47 Guidance:

The Shoulder Drop Off (W8-17) sign (see Figure $\frac{2C-6}{2C-8}$) should be used where an unprotected shoulder drop-off, adjacent to the travel lane, exceeds 3 inches in depth for a significant continuous length along the roadway, based on engineering judgment.

Option

A SHOULDER DROP-OFF (W8-17P) supplemental plaque (see Figure $\frac{2C-62C-8}{2}$) may be mounted below the W8-17 sign.

The NO SHOULDER (W8-23) sign (see Figure 2C-62C-8) may be used to warn road users that a shoulder does not exist along a portion of the roadway.

The SHOULDER ENDS (W8-25) sign (see Figure 2C-62C-8) may be used to warn road users that a shoulder is ending.

Standard:

When used, shoulder signs shall be placed in advance of the condition (see Table 2C-4). Not needed

Guidance:

Additional shoulder signs should be placed at appropriate intervals along the road where the condition continually exists.

Figure 2C-8. Roadway and Weather Condition Signs and Plaques

Section 2C.322C.31 Surface Condition Signs (W8-5, W8-7, W8-8, W8-11, W8-13, and W8-14) Option:

The Slippery When Wet (W8-5) sign (see Figure 2C-62C-8) may be used to warn of unexpected slippery conditions. Supplemental plaques with legends such as ICE, WHEN WET, STEEL DECK, or EXCESS OIL may be used with the W8-5 sign to indicate the reason that the slippery conditions might be present.

The LOOSE GRAVEL (W8-7) sign (see Figure 2C-62C-8) may be used to warn of loose gravel on the roadway surface.

The ROUGH ROAD (W8-8) sign (see Figure 2C-62C-8) may be used to warn of a rough roadway surface.

An UNEVEN LANES (W8-11) sign (see Figure 2C-62C-8) may be used to warn of a difference in elevation between travel lanes.

The BRIDGE ICES BEFORE ROAD (W8-13) sign (see Figure 2C-62C-8) may be used in advance of bridges to advise bridge users of winter weather conditions. The BRIDGE ICES BEFORE ROAD sign may be removed or covered during seasons of the year when its message is not relevant.

The FALLEN ROCKS (W8-14) sign (see Figure $\frac{2C-62C-8}{2}$) may be used in advance of an area that is adjacent to a hillside, mountain, or cliff where rocks frequently fall onto the roadway.

Guidance:

When used, Surface Condition signs should be placed in advance of the beginning of the affected section (see Table $\frac{2C}{4}$ 4 $\frac{2C}{3}$), and additional signs should be placed at appropriate intervals along the road where the condition exists.

Section 2C.332C.32 Warning Signs and Plaques for Motorcyclists (W8-15, W8-15P, and W8-16)

Support:

The signs and plaques described in this Section are intended to give motorcyclists advance notice of surface conditions that might adversely affect their ability to maintain control of their motorcycle under wet or dry conditions. The use of some of the advance surface condition warning signs described in Section 2C.32, such as Slippery When Wet, LOOSE GRAVEL, or ROUGH ROAD, can also be helpful to motorcyclists if those conditions exist.

Option:

If a portion of a street or highway features a roadway pavement surface that is grooved or textured instead of smooth, such as a grooved skid resistance treatment for a horizontal curve or a brick pavement surface, a GROOVED PAVEMENT (W8-15) sign (see Figure 2C-62C-8) may be used to provide advance warning of this condition to motorcyclists, bicyclists, and other road users. Alternate legends such as TEXTURED PAVEMENT or BRICK PAVEMENT may also be used on the W8-15 sign.

If a bridge or a portion of a bridge includes a metal or grated surface, a METAL BRIDGE DECK (W8-16) sign (see Figure 2C-62C-8) may be used to provide advance warning of this condition to motorcyclists, bicyclists, and other road users.

A Motorcycle (W8-15P) plaque (see Figure 2C-62C-8) may be mounted below or above a W8-15 or W8-16 sign if the warning is intended to be directed primarily to motorcyclists.

Section 2C.34 2C.33 NO CENTER LINE Sign (W8-12)

7 Option:

4

5

6

8

9

10

16

17

18

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35 36

37

The NO CENTER LINE (W8-12) sign (see Figure 2C-62C-8) may be used to warn of a roadway without center line pavement markings.

Section 2C.34 NO TRAFFIC SIGNS Sign (W18-1)

11 Option

A W18-1 warning sign with the legend NO TRAFFIC SIGNS may be used only on low-volume rural roads to advise road users that no signs are installed along the distance of the road. The sign may be installed at the point where road users would enter the low volume road or where, based on engineering judgment, the road user might need this information.

A W7-3aP (see Figure 2C-5), W16-2P, or W16-9P supplemental plaque with the legend NEXT XX MILES, XX FEET, or AHEAD may be installed below the W18-1 sign when appropriate.

Section 2C.35 Weather Condition Signs (W8-18, W8-19, W8-21, and W8-22)

19 Option:

The ROAD MAY FLOOD (W8-18) sign (see Figure 2C-6 2C-8) may be used to warn road users that a section of roadway is subject to frequent flooding. A Depth Gauge (W8-19) sign (see Figure 2C-62C-8) may also be installed within a roadway section that frequently floods.

Standard Guidance: Changed from Standard to Guidance

If used, the Depth Gauge sign <u>shall-should</u> be in addition to the ROAD MAY FLOOD sign and <u>shall-should</u> be mounted at the appropriate <u>height to</u> indicate the depth of the water at the deepest point on the roadway.

Option:

The GUSTY WINDS AREA (W8-21) sign (see Figure 2C-62C-8) may be used to warn road users that wind gusts frequently occur along a section of highway that are strong enough to impact the stability of trucks, recreational vehicles, and other vehicles with high centers of gravity. A NEXT XX MILES (W7-3a) supplemental plaque (see Figure 2C-5) may be mounted below the W8-21 sign to inform road users of the length of roadway that frequently experiences strong wind gusts.

The FOG AREA (W8-22) sign (see Figure 2C 62C-8) may be used to warn road users that foggy conditions frequently reduce visibility along a section of highway. A NEXT XX MILES (W7-3a) supplemental plaque (see Figure 2C-5) may be mounted below the W8-22 sign to inform road users of the length of roadway that frequently experiences foggy conditions.

1 TRAFFIC CONTROL AND INTERSECTION SIGNS AND PLAQUES 2 Section 2C.36 Advance Traffic Control Signs (W3-1, W3-2, W3-3, W3-4) 3 **Standard:** 4 The Advance Traffic Control symbol signs (see Figure 2C-62C-9) including the Stop Ahead (W3-1), 5 Yield Ahead (W3-2), and Signal Ahead (W3-3) signs₋₁. These signs shall be installed on an approach to a primary traffic control device that is not visible for a sufficient distance to permit the road user to 6 respond to the device (see Table 2C-42C-3). The visibility criteria for a traffic control signal shall be 7 8 based on having a continuous view of at least two signal faces for the distance specified in Table 4D-2. Moved to Guidance below 9 10 Support: 11 Figures 2A-4 and 2A-5a and b shows the typical placement of an Advance Traffic Control sign. 12 Permanent obstructions causing the limited visibility might include roadway alignment or structures. Intermittent obstructions might include foliage or parked vehicles. 13 14 Guidance: 15 The visibility criteria for a traffic control signal should be based on having a continuous view of at least 16 two signal faces for the distance specified in Table 4D-2. Changed to Guidance and relocated from Standard above 17 18 Where intermittent obstructions occur, engineering judgment should determine the treatment to be 19 implemented. 20 Option: 21 An Advance Traffic Control sign may be used for additional emphasis of the primary traffic control 22 device, even when the visibility distance to the device is satisfactory. 23 Support: 24 See Section 2C.64 for the use of an advance street name plaque to identify an intersecting road. An advance street name plaque (see Section 2C.58) may be installed above or below an Advance Traffic-25 Control sign. Deleted; reference to Section added in Support 26 A warning beacon may be used with an Advance Traffic Control sign. Combined with existing Options 2.7 28 below 29 Option: 30 A BE PREPARED TO STOP (W3-4) sign (see Figure 2C-62C-9) may be used to warn of stopped traffic caused by a traffic control signal or in advance of a section of roadway that regularly experiences traffic 31 32 congestion. 33 A warning beacon (see Section 4S.03) or yellow LEDs within the border of the sign may be used with an Advance Traffic Control or BE PREPARED TO STOP sign. Existing Options combined and edited 34 35 Standard: 36 When a BE PREPARED TO STOP sign is used in advance of a traffic control signal, it shall be used in addition to a Signal Ahead sign and shall be placed downstream from the Signal Ahead (W3-3) sign. 37 38 Option: 39 The BE PREPARED TO STOP sign may be supplemented with a warning beacon (see Section 4L.03). Combined with existing Options above 40 41 Guidance: 42

When the warning beacon <u>or sign border LEDs are is</u>-interconnected with a traffic control signal or queue detection system, the BE PREPARED TO STOP sign should be supplemented with a WHEN FLASHING (W16-13P) plaque (see Figure 2C-12).

45 Support:

43 44

46

47

48

49

Section <u>2C.402C.47</u> contains information regarding the use of a NO MERGE AREA (W4-5P) supplemental plaque in conjunction with a Yield Ahead sign.

Figure 2C-9. Advance Traffic Control Signs

Section 2C.37 Actuated Advance Intersection Signs (W2-10 through W2-12)

Support:

1

2

3

8

Actuated Advance Intersection Signs are typically associated with restricted sight distance and gap selection at stop controlled intersections.

4 Option:

5 The TRAFFIC ENTERING WHEN FLASHING (W2-10) sign or a WATCH FOR ENTERING

TRAFFIC (W2-11) sign (See Figure 2C-11) may be used on the through roadway approach to a side or cross road stop controlled intersection to warn of entering traffic from the side or cross road.

The sign may be in diamond or rectangular shape.

The TRAFFIC APPROACHING WHEN FLASHING (W2-12) sign (See Figure 2C-11) may be used on the side road stop controlled approach to warn of traffic approaching on the through road.

11 **Standard:**

When used, the TRAFFIC ENTERING WHEN FLASHING sign, the WATCH FOR ENTERING TRAFFIC sign, and the TRAFFIC APPROACHING WHEN FLASHING sign shall be supplemented with an actuated warning system that activates when an approaching vehicle is detected.

15 16

17

18

19

20

21

22

23 24

26

27

28

29

31

32

33

34

35

36

37

38

39

40

42

43

44

45

47

48

49

Section 2C.37-2C.38 Advance Ramp Control Signal Signs (W3-7 and W3-8)

Option:

A RAMP METER AHEAD (W3-7) sign (see Figure $\frac{2C-6}{2C-9}$) may be used to warn road users that a freeway entrance ramp is metered and that they will encounter a ramp control signal (see Chapter $\frac{4I-4P}{2}$).

Guidance:

When the ramp control signals are operated only during certain periods of the day, a RAMP METERED WHEN FLASHING (W3-8) sign (see Figure 2C-62C-9) should be installed in advance of the ramp control signal near the entrance to the ramp, or on the arterial on the approach to the ramp, to alert road users to the presence and operation of ramp meters.

25 Standard:

The RAMP METERED WHEN FLASHING sign shall be supplemented with a warning beacon (see Section 4L.034S.03) that flashes when the ramp control signal is in operation.

Section 2C.52 2C.39 NEW TRAFFIC PATTERN and SIGNAL OPERATION AHEAD Signs (W23-2, W23-2a)

30 Option:

A NEW TRAFFIC PATTERN AHEAD (W23-2) sign (see Figure 2C-62C-9) may be used on the approach to an intersection or along a section of roadway to provide advance warning of a change in traffic patterns, such as revised lane usage, roadway geometry, or signal phasing.or roadway geometry.

A NEW SIGNAL OPERATION AHEAD (W23-2a) sign (see Figure 2C-9) may be used on the approach to a signalized intersection to provide advance warning of a change in signal phasing.

Guidance:

The NEW TRAFFIC PATTERN or SIGNAL OPERATION AHEAD sign should be removed when the traffic pattern returns to normal, when the changed pattern is no longer considered to be new, or within six months.

Section 2C.38 2C.40 Reduced Speed Limit Ahead Signs (W3-5, W3-5a, W3-5b, W3-5c)

41 Guidance:

A Reduced Speed Limit Ahead (W3-5 or W3-5a), Variable Speed Zone (W3-5b), or Truck Speed Zone (W3-5c) Ahead sign (see Figure 2C-72C-10) should be used to inform road users of a reduced speed zone where the speed limit is being reduced by more than 10 mph, or where engineering judgment indicates the need for advance notice to comply with the posted speed limit ahead.

46 **Standard:**

If used, Reduced Speed Limit, <u>Variable Speed Zone</u>, <u>or Truck Speed Zone</u> Ahead signs shall be followed by a Speed Limit (R2-1) sign installed at the beginning of the zone where the speed limit applies.

1 The speed limit displayed on the Reduced Speed Limit Ahead sign shall be identical to the speed 2 limit displayed on the subsequent Speed Limit sign. Figure 2C-10. Reduced Speed Limit Ahead Signs 3 4 Section 2C.41 WATCH FOR STOPPED TRAFFIC Sign (W23-3) 5 Option: 6 The WATCH FOR STOPPED TRAFFIC (W23-3) sign (see Figure 2C-08) may be used to warn road 7 users of the possibility of vehicles stopping abruptly in the travel lane due to recurring or expected congested 8 conditions. 9 Section 2C.46-2C.42 Intersection Warning Signs (W2-1 through W2-8) 10 Option: 11 A Cross Road (W2-1) symbol, Side Road (W2-2, or W2-3, or W2-3a) symbol, T-Symbol Intersection (W2-4), or Y-Symbol Intersection (W2-5) sign (see Figure 2C-92C-11) may be used in advance of an 12 13 intersection to indicate the presence of an intersection and the possibility of turning or entering traffic. The Circular Intersection (W2-6) symbol sign (see Figure 2C-92C-11) may be installed in advance of a 14 15 circular intersection (see Figures 2B-21 through 2B-23). 16 Guidance: 17 If an approach to a roundabout-circular intersection has a statutory or posted speed limit of 40 mph or 18 higher, the Circular Intersection (W2-6) symbol sign should be installed in advance of the circular 19 intersection. 20 Figure 2C-11. Intersection Warning Signs and Plaques 21 Option: 22 An educational plaque (see Figure 2C-92C-11) with a legend such as ROUNDABOUT (W16-12a7P) or 23 TRAFFIC CIRCLE (W16-12P) may be mounted below a Circular Intersection symbol sign. 24 The relative importance of the intersecting roadways may be shown by different widths of lines in the 25 symbol. 26 Support: 27 See Section 2C.64 for the use of An an advance street name plaque to identify an intersecting road (see 28 Section 2C.58) may be installed above or below an Intersection Warning sign. 29 Guidance: 30 The Intersection Warning sign should illustrate and depict the general configuration of the intersecting roadway, such as cross road, side road, T-intersection, or Y-intersection. 31 32 Intersection Warning signs, other than the Circular Intersection (W2-6) symbol sign, and the T-33 intersection (W2-4) symbol sign, and the Grade Crossing and Intersection Advance Warning (W10-2-and), W10-3, W10-4, W10-11, and W10-12) signs should not be used on approaches controlled by STOP signs, 34 35 YIELD signs, or signals. 36 If an Intersection Warning sign is used where the side roads are not opposite of each other, the Offset 37 Side Roads (W2-7) symbol sign (see Figure 2C-92C-11) should be used instead of the Cross Road symbol 38 sign. 39 If an Intersection Warning sign is used where two closely-spaced side roads are on the same side of the 40 highway, the Double Side Roads (W2-8) symbol sign (see Figure 2C-92C-11) should be used instead of the 41 Side Road symbol sign. 42 No more than two side road symbols should be displayed on the same side of the highway on a W2-7 or 43 W2-8 symbol sign, and no more than three side road symbols should be displayed on a W2-7 or W2-8 symbol 44 sign. 45 Support: 46 Figure 2A-4 shows the typical placement of an Intersection Warning sign.

47

48

Standard:

Section 2C.47-2C.43 Two-Direction Large Arrow Sign (W1-7)

The Two-Direction Large Arrow (W1-7) sign (see Figure 2C-9) (see Figure 2C-11) shall be a horizontal rectangle.

If used, it shall be installed on the far side of a T-intersection in line with, and at approximate

If used, it shall be installed on the far side of a T-intersection in line with, and at approximately a right angle to, traffic approaching from the stem of the T-intersection.

The Two-Direction Large Arrow sign shall not be used where there is no change in the direction of travel such as at the beginnings and ends of medians or at center piers.

The Two-Direction Large Arrow sign directing traffic to the left and right shall not be used in the central island of a roundabout.

Guidance:

4

5

6

7

8

9

10

11

12 13

14

15

16

17 18 The Two-Direction Large Arrow sign should be visible for a sufficient distance to provide the road user with adequate time to react to the intersection configuration.

Section 2C.48 2C.44 Traffic Signal Oncoming Extended Green Signs (W25-1, W25-2) Standard:

At locations where either a W25-1 or a W25-2 sign is required based on the provisions in Section 4D.054F.01, the W25-1 or W25-2 sign (see Figure 2C-9) (see Figure 2C-11) shall be installed near the left-most signal head. The W25-1 and W25-2 signs shall be vertical rectangles.

Section 2C.40 2C.45 Merge Signs (W4-1, W4-5)

Option:

A Merge (W4-1) sign-(see Figure 2C-8) (see Figure 2C-12) may be used to warn road users on the major roadway that merging movements might be encountered in advance of a point where lanes from two separate roadways converge as a single traffic lane and no turning conflict occurs.

A Merge sign may also be installed on the side of the entering roadway to warn road users on the entering roadway of the merge condition.

Guidance:

The Merge sign should be installed on the side of the major roadway where merging traffic will be encountered and in such a position as to not obstruct the road user's view of entering traffic.

Where two roadways of approximately equal importance converge, a Merge sign should be placed on each roadway.

When a Merge (W4-1) sign is installed on an entering roadway, the symbol should be oriented right or left as appropriate to depict the side from which the merge occurs, with the arrow representing the entering roadway and the curved stem representing the major roadway (see Figure 2C-1211). The sign should be located on the side of the entering roadway from which the merge occurs.

Figure 2C-12. Merging and Passing Signs and Plaques

Figure 2C-13. Example Sequences for Lane Ends and Lanes Merge Signs

Figure 2C-14. Examples of Merge and Added Lane Sign Placement for Entering and

Converging Roadways

When a Merge sign is to be installed on an entering roadway that curves before merging with the major roadway, such as a ramp with a curving horizontal alignment as it approaches the major roadway, the Entering Roadway Merge (W4-5) sign (see Figure 2C 82C-12) should be used to better portray the actual geometric conditions to road users on the entering roadway.

The Merge sign should not be used where two roadways converge and merging movements are not required.

Standard: Changed from Guidance to Standard

The Merge sign <u>should shall</u> not be used in place of a Lane Ends sign (see Section <u>2C.422C.47</u>) where lanes of traffic moving on a single roadway must merge because of a reduction in the actual or usable pavement width.

Option:

An Entering Roadway Merge (W4-5) sign with a NO MERGE AREA (W4-5P) supplemental plaque (see Figure 2C-82C-12) mounted below it may be used to warn road users on an entering roadway that they will encounter an abrupt merging situation without an acceleration lane at the downstream end of the ramp.

A Merge (W4-1) sign with a NO MERGE AREA (W4-5P) supplemental plaque mounted below it may be used to warn road users on the major roadway that traffic on an entering roadway will encounter an abrupt merging situation without an acceleration lane at the downstream end of the ramp.

For a yield-controlled channelized right-turn movement onto a roadway without an acceleration lane, a NO MERGE AREA (W4-5P) supplemental plaque may be mounted below a Yield Ahead (W3-2) sign and/or below a YIELD (R1-2) sign when engineering judgment indicates that road users would expect an acceleration lane to be present.

Section 2C.41 2C.46 Added Lane Signs (W4-3, W4-6)

Guidance:

The Added Lane (W4-3) sign (see Figure 2C-82C-12) should be installed in advance of a point where two roadways converge and merging movements are not required. When possible, the Added Lane sign should be placed such that it is visible from both roadways; if this is not possible, an Added Lane sign should be placed on the side of each roadway.

When an Added Lane (W4-3) sign is installed on an entering roadway, the symbol should be oriented right or left as appropriate to depict the side from which the major roadway converges, with the straight

arrow representing the entering roadway and the curved arrow representing the major roadway. The sign should be located on the side of the entering roadway from which the major roadway converges.

When an Added Lane sign is to be installed on a roadway that curves before converging with another roadway that has a tangent alignment at the point of convergence, the Entering Roadway Added Lane (W4-6) sign (see Figure 2C-82C-12) should be used to better portray the actual geometric conditions to road users on the curving roadway.

7 Section <u>2C.42 2C.47</u> <u>Lane Ends Signs (W4-2, W9-1, W9-2)</u>

Guidance: Support:

The LANE ENDS MERGE LEFT (RIGHT) (W9-2) sign or the Lane Ends (W4-2) and RIGHT (LEFT) LANE ENDS (W9-1) signs should be are used to warn of the reduction in the number of traffic lanes in the direction of travel on a multi-lane highway (see Figure 2C-12).

The sequence of the W4-2 and W9-1 signs is illustrated in Figure 2C-13.

Guidance:

 The Lane Ends (W4-2) sign should be installed at the approximate location of the start of the lane taper. Option:

The RIGHT (LEFT) LANE ENDS (W9-1) sign (see Figure 2C-12) (see Figure 2C-8) may should be used in advance of the LANE ENDS (W4-2) sign or the LANE ENDS MERGE LEFT (RIGHT) (W9-2) sign as additional warning or to emphasize to warn that the traffic a lane is ending and that a merging maneuver will be required. The W9-1 sign should be installed in accordance with Table 2C-3.

If used, the RIGHT (LEFT) LANE ENDS (W9-1) sign-should be installed adjacent to the Lane-Reduction Arrow pavement markings.

Option:

On low-speed roads in urban environments where space is limited at a signalized intersection, the W9-1 sign may be located at the far-side of the intersection to indicate the end of an auxiliary lane that is added for intersection capacity, but ends a short distance beyond the intersection and does not accommodate the advance placement distance indicated in Table 2C-3.

<u>Supplemental RIGHT (LEFT) LANE ENDS (W9-1) signs may be installed upstream of the W9-1 that is installed at the advanced placement distance.</u>

Guidance:

If supplemental W9-1 signs are installed, a Distance (W16-2P series or W16-3P series) plaque should be installed below the W9-1 sign.

Option:

On one-way streets or on divided highways where <u>the left-hand lane is ending and</u> the width of the median will permit, <u>two-the</u> Lane Ends signs <u>may-should</u> be placed facing approaching traffic, one on the right hand <u>side and the other</u> on the left-hand side or median.

Support:

Section <u>3B.093B.12</u> contains information regarding the use of pavement markings in conjunction with a lane reduction.

Guidance:

Where an extra lane has been provided for slower moving traffic (see Section 2B.31), a Lane Ends word sign or a Lane Ends (W4-2) symbol sign should be installed in advance of the downstream end of the extra lane.

Lane Ends signs should not be installed in advance of the downstream end of an acceleration lane.

Standard:

The W4-2 and W9-1 signs shall not be used in dropped lane situations. In dropped lane situations on conventional roads at intersections, regulatory signs (see Section 2B.202B.30) shall be used to inform road users that a through lane is becoming a mandatory turn lane. The W4-2, W9-1, and W9-2 signs shall not be used in dropped lane situations. Reversed order of sentences

- 49 Section 2C.48 Lanes Merge Signs (W9-4, W4-8)
- 50 Support:

1 The LANES MERGE (W9-4) and Single-Lane Transition (W4-8) signs are used to warn of the reduction of two lanes to one in the same direction of travel (See Figure 2C-12).

3 Guidance

The Lanes Merge (W9-4) sign should be used warn that the traffic lane is merging with the adjacent lane and a merging maneuver will be required for each lane. The W9-4 sign should be installed in accordance with Table 2C-3.

The Single-Lane Transition (W4-8) sign should be used to indicate the approximate location of the start of the lane taper.

Section 2C.49 HEAVY MERGE FROM LEFT (RIGHT) Sign (W4-7)

10 Option:

7

8

9

11

12

13

15

16

18

19 20

21

23

24

25

26

27

28

30

31

37

38

39

40 41

43

44

46

47

48

The HEAVY MERGE FROM LEFT (RIGHT) XX FT (W4-7) sign may be used to supplement a W4-1 sign at multilane approaches to congested areas to inform road users that it is desirable for through traffic to move out of a lane that will be occupied by large volumes of entering traffic.

14 **Standard:**

If used, the W4-7 sign shall be installed at a location upstream from the location of the W4-1 sign.

Section 2C.43-2C.50 RIGHT (LEFT) LANE FOR EXIT ONLY AHEAD Sign (W9-7)

17 Option:

The RIGHT (LEFT) LANE <u>FOR</u> EXIT ONLY <u>AHEAD</u> (W9-7) sign (see Figure <u>2C-82C-12</u>) may be used to provide advance warning to road users that traffic in the right-hand (left-hand) lane of a roadway that is approaching a grade separated interchange will be required to depart the roadway on an <u>exit-ramp</u> at the next interchange or intersection.

22 Standard:

The W9-7 sign shall be a horizontal rectangle with a black legend and border on a yellow-background.

Guidance:

If used, the W9-7 sign should be installed upstream from the first overhead guide sign that contains an EXIT ONLY sign panel or upstream from the first RIGHT (LEFT) LANE MUST EXIT (R3-33)_-regulatory sign, if used, whichever is farther upstream from the exit.

29 Option:

A legend displaying the distance may be added to the W9-7 sign where the distance along the dropped lane between the sign and the exit ramp is 1 mile or greater.

32 Support:

Section <u>2B.232B.32</u> contains information regarding a regulatory sign that can also be used for lane drops at grade-separated interchanges.

35 Section 2C.44-2C.51 Two-Way Traffic Sign (W6-3)

36 Guidance:

A Two-Way Traffic (W6-3) sign (see Figure $\frac{2C-82C-12}{2}$) should be used to warn road users of a transition from a multi-lane divided section of roadway to a two-lane, two-way section of roadway.

A Two-Way Traffic (W6-3) sign with an AHEAD (W16-9P) plaque (see Figure 2C-122C-17) should be used to warn road users of a transition from a one-way street to a two-lane, two-way section of roadway (see Figure 2B-14).

42 Option:

The Two-Way Traffic sign may be used at intervals along a two-lane, two-way roadway and may be used to supplement the Divided Highway (Road) Ends (W6-2) sign discussed in Section 2C.232C.21.

45 Support:

Section 6H.17 contains information on a Opposing Lane Traffic Divider Sign (W6-4) for use in temporary traffic control situations.

Section 2C.52 Two-Way Traffic on a Three-Lane Roadway Sign (W6-5, W6-5a)

1 Option: 2 The Two-way Traffic on a Three-Lane Roadway (W6-5 and W6-5a) signs may be installed along three-3 lane roadways with two lanes in one direction and one in the opposing direction. 4 **Standard:** 5 The W6-5 series signs shall match the lane configuration of the roadway. 6 Section 2C.452C.53 NO PASSING ZONE Sign (W14-3) 7 Standard: 8 The NO PASSING ZONE (W14-3) sign (see Figure 2C-82C-12) shall be a pennant-shaped isosceles 9 triangle with its longer axis horizontal and pointing to the right. When used, the NO PASSING ZONE sign shall be installed on the left-hand side of the roadway at the beginning of no-passing zones 10 identified by pavement markings or DO NOT PASS signs or both (see Sections 2B.282B.37 and 11 12 3B.023B.03).

Section 2C.49 2C.54 <u>Vehicular Traffic Warning Signs (W8-6, W11-1, W11-5, W11-5a, W11-8, W11-10, W11-11, W11-12P, W11-14, W11-15, and W11-15a)</u>

Option:

Vehicular Traffic Warning (W8-6, W11-1, W11-5, W11-5a, W11-8, W11-10, W11-11, W11-12P, W11-14, W11-15, and W11-15a) signs (see Figure 2C-102C-15) may be used to alert road users to locations where unexpected entries into the roadway by trucks, bicyclists, farm vehicles, emergency vehicles, golf carts, horse-drawn vehicles, or other vehicles might occur. The TRUCK CROSSING (W8-6) word message sign may be used as an alternate to the Truck Crossing (W11-10) symbol sign.

Support:

These locations might be relatively confined or might occur randomly over a segment of roadway.

Guidance:

Vehicular Traffic Warning signs should be used only at locations where the road user's sight distance is restricted, or the condition, activity, or entering traffic would be unexpected.

If the condition or activity is seasonal or temporary, the Vehicular Traffic Warning sign should be removed or covered when the condition or activity does not exist.

Figure 2C-15. Vehicular Traffic Warning Signs and Plaques

Option:

The combined Bicycle/Pedestrian (W11-15) sign may be used where both bicyclists and pedestrians might be crossing the roadway, such as at an intersection with a shared-use path. A TRAIL X-ING (W11-15P) supplemental plaque (see Figure 2C-102C-15) may be mounted below the W11-15 sign. The TRAIL CROSSING (W11-15a) sign may be used to warn of shared-use path crossings where pedestrians, bicyclists, and other user groups might be crossing the roadway.

The W11-1, W11-15, and W11-15a signs and their related supplemental plaques may have a fluorescent yellow-green background with a black legend and border.

Supplemental plaques (see Section 2C.532C.57) with legends such as AHEAD, XX FEET, NEXT XX MILES, IN STREET, or IN ROAD or SHARE THE ROAD may be mounted below Vehicular Traffic Warning signs to provide advance notice to road users of unexpected entries.

Guidance:

If used in advance of a pedestrian and bicycle crossing, a W11-15 or W11-15a sign should be supplemented with an AHEAD or XX FEET plaque to inform road users that they are approaching a point where crossing activity might occur.

Standard:

If a post-mounted W11-1, W11-11, W11-15, or W11-15a sign is placed at the location of the crossing point where golf carts, pedestrians, bicyclists, or other shared-use path users might be crossing the roadway, a diagonal downward pointing arrow (W16-7P) plaque (see Figure 2C-12) shall be mounted below the sign. If the W11-1, W11-11, W11-15, or W11-15a sign is mounted overhead, the W16-7P supplemental plaque shall not be used.

Option:

The crossing location identified by a W11-1, W11-11, W11-15, or W11-15a sign may be defined with crosswalk markings (see Section 3B.18Chapter 3C).

Standard:

The Emergency Vehicle (W11-8) sign (see Figure 2C-102C-15) with the EMERGENCY SIGNAL AHEAD (W11-12P) supplemental plaque (see Figure 2C-102C-15) shall be placed in advance of all emergency-vehicle traffic control signals (see Chapter 4G4M).

Option:

The Emergency Vehicle (W11-8) sign, or a word message sign indicating the type of emergency vehicle (such as rescue squad), may be used in advance of the emergency-vehicle station when no emergency-vehicle traffic control signal is present.

A Warning Beacon (see Section 4L.034S.03) may be used with any Vehicular Traffic Warning sign to indicate specific periods when the condition or activity is present or is likely to be present, or to provide enhanced sign conspicuity.

A supplemental WHEN FLASHING (W16-13P) plaque (see Figure 2C-12) may be used with any Vehicular Traffic Warning sign that is supplemented with a Warning Beacon to indicate specific periods when the condition or activity is present or is likely to be present.

Section 2C.50 2C.55 Non-Vehicular Warning Signs (W11-2, W11-3, W11-4, W11-6, W11-7, W11-9, and W11-16 through W11-22)

Option:

Non-Vehicular Warning (W11-2, W11-3, W11-4, W11-6, W11-7, W11-9, and W11-16 through W11-22) signs (see Figure 2C-112C-16) may be used to alert road users in advance of locations where unexpected entries into the roadway might occur or where shared use of the roadway by pedestrians, animals, or equestrians might occur.

Support:

These conflicts might be relatively confined, or might occur randomly over a segment of roadway. *Guidance:*

If used in advance of a pedestrian, snowmobile, or equestrian crossing, the W11-2, W11-6, W11-7, and W11-9 signs should be supplemented with plaques (see Section 2C.552C.61) with the legend AHEAD or XX FEET to inform road users that they are approaching a point where crossing activity might occur.

Standard:

If a post-mounted W11-2, W11-6, W11-7, or W11-9 sign is placed at the location of the crossing point where pedestrians, snowmobilers, or equestrians might be crossing the roadway, a diagonal downward pointing arrow (W16-7P) plaque (see Figure 2C-122C-17) shall be mounted below the sign. If the W11-2, W11-6, W11-7, or W11-9 sign is mounted overhead, the W16-7P plaque shall not be used.

Figure 2C-16. Non-Vehicular Warning Signs

Option:

A Pedestrian Crossing (W11-2) sign may be placed overhead or may be post-mounted with a diagonal downward pointing arrow (W16-7P) plaque at the crosswalk location where Yield Here To (Stop Here For) Pedestrians signs (see Section 2B.112B.20) have been installed in advance of the crosswalk.

Standard:

If a W11-2 sign has been post-mounted at the crosswalk location where a Yield Here To (Stop Here For) Pedestrians sign is used on the approach, the Yield Here To (Stop Here For) Pedestrians sign shall not be placed on the same post as or block the road user's view of the W11-2 sign.

Option:

An advance Pedestrian Crossing (W11-2) sign with an AHEAD or a distance supplemental plaque may be used in conjunction with a Yield Here To (Stop Here For) Pedestrians sign on the approach to the same crosswalk.

The crossing location identified by a W11-2, W11-6, W11-7, or W11-9 sign may be defined with crosswalk markings (see Section 3B.18Chapter 3C).

The W11-2 and W11-9 signs and their related supplemental plaques may have a fluorescent yellow-green background with a black legend and border.

Guidance:

When a fluorescent yellow-green background is used, a systematic approach featuring one background color within a zone or area should be used. The mixing of standard yellow and fluorescent yellow-green backgrounds within a selected site area should be avoided.

Option:

A Warning Beacon (see Section 4L.034S.03) may be used with any Non-Vehicular Warning sign to indicate specific periods when the condition or activity is present or is likely to be present, or to provide enhanced sign conspicuity.

A supplemental WHEN FLASHING (W16-13P) plaque (see Figure 2C-122C-17) may be used with any Non-Vehicular Warning sign that is supplemented with a Warning Beacon to indicate specific periods when the condition or activity is present or is likely to be present.

Section 2C.51 2C.56 Playground Sign (W15-1)

Option:

4 5

6

7

8

9

10

11 12

13

The Playground (W15-1) sign (see Figure 2C-112C-16) may be used to give advance warning of a designated children's playground that is located adjacent to the road.

The Playground sign may have a fluorescent yellow-green background with a black legend and border. *Guidance:*

If the access to the playground area requires a roadway crossing, the application of crosswalk pavement markings (see Section 3B.18Chapter 3C) and Non-Vehicular Warning signs (see Section 2C.502C.55) should be considered.

Section 2C.53 2C.57 Use of Supplemental Warning Plaques

Option:

A supplemental warning plaque (see Figure 2C-122C-17) may be displayed with a warning or regulatory sign when engineering judgment indicates that road users require additional warning information beyond that contained in the main message of the warning or regulatory sign.

Standard:

Supplemental warning plaques shall be used only in combination with <u>and installed on the same post(s) as</u> warning or regulatory signs. They shall not be mounted alone or displayed alone. <u>If used, a supplemental warning plaque shall be installed on the same post(s) as the warning or regulatory sign that it supplements. Edited for clarity</u>

Unless otherwise provided in this Manual for a particular plaque, supplemental warning plaques shall be mounted below the sign they supplement.

Figure 2C-17. Supplemental Warning Signs and Plaques

Section 2C.542C.58 Design of Supplemental Warning Plaques

16 Standard:

A supplemental warning plaque used with a warning sign shall have the same legend, border, and background color as the warning sign with which it is displayed. A supplemental warning plaque used with a regulatory sign shall have a black legend and border on a yellow background.

Supplemental warning plaques shall be square or rectangular.

Section 2C.08 2C.59 Advisory Speed Plaque (W13-1P) and Confirmation Advisory Speed Plaque (W13-1aP)

Option:

The Advisory Speed (W13-1P) plaque (see Figure 2C-1) may be used to supplement any <u>advance</u> warning sign to indicate the advisory speed for a condition.

The Confirmation Advisory Speed (W13-1aP) may be used to supplement a One-Direction Large Arrow Sign (W1-6) on the outside of a turn or curve in line with and at approximately a right angle to approaching traffic.

Standard:

The use of the Advisory Speed and Confirmation Advisory Speed plaques for horizontal curves shall be in accordance with Section 2C.06 and Table 2C-4bhe information shown in Table 2C-5. The Advisory Speed plaque shall also be used where an engineering study indicates a need to advise road users of the advisory speed for other roadway conditions.

If used, Tthe speed displayed on the Advisory and Confirmation Advisory Speed plaques shall carry the message XX MPH. The speed displayed shall be a multiple of 5 mph.

Except in emergencies or when the condition is temporary, an Advisory or Confirmation Advisory Speed plaque shall not be installed until the advisory speed has been determined by an engineering study.

The Advisory Speed plaque shall only be used to supplement an advance warning sign and shall not be installed as a separate sign installation.

The Confirmation Advisory Speed plaque shall only be used to supplement a One-Direction Large Arrow (W1-6) sign or an Exit Gore (E5-1 series) sign and shall not be installed as a separate sign installation.

The advisory speed shall be determined by an engineering study that follows established engineering practices.

Support:

<u>The "Traffic Control Devices Handbook" (see Section 1A.05) contains information on established</u> engineering practices for determining advisory speeds.

1 Among the established engineering practices that are appropriate for the determination of the 2 recommended advisory speed for a horizontal curve are the following: 3 A. Compass method B. Safety-based method 4 5 C. Ball-bank method 6 D. Design equation method 7 E. Accelerometer method 8 A. An accelerometer that provides a direct determination of side friction factors 9 B. A design speed equation 10 C. A traditional ball-bank indicator using the following criteria: 11 1. 16 degrees of ball-bank for speeds of 20 mph or less 12 2. 14 degrees of ball-bank for speeds of 25 to 30 mph 3. 12 degrees of ball-bank for speeds of 35 mph and higher 13 14 The 16, 14, and 12 degrees of ball bank criteria are comparable to the current AASHTO horizontal curve-15 design guidance. Research has shown that drivers often exceed existing posted advisory curve speeds by 7 to-16 10 mph. 17 Guidance: 18 The advisory speed should be determined based on free-flowing traffic conditions. 19 Because changes in conditions, such as roadway geometrics, surface characteristics, or sight distance, might affect the advisory speed, each location should be evaluated periodically or when conditions change. 20 21 Section <u>2C.62</u> <u>2C.60</u> <u>NEW Plaque (W16-15P)</u> 22 Option: 23 A NEW (W16-15P) plaque (see Figure 2C-12) may be mounted above a regulatory sign when a new regulation takes effect in order to alert road users to the new traffic regulation. A NEW plaque may also be 24 25 mounted above an advance warning sign (such as a Signal Ahead sign for a newly-installed traffic control signal) for a new traffic regulation. 26 27 **Standard:** The NEW plaque shall not be used alone. Not needed – redundant with Section 2C.57 28 **Guidance:** Changed from Standard to Guidance 29 30 The NEW plaque shall should be removed no later than 6 months after the regulation has been in effect it 31 was installed. 32 Section 2C.55-2C.61 Distance Plagues (W16-2 Series, W16-3 Series, W16-4P, W7-3aP) 33 Option: 34 The Distance Ahead (W16-2 series and W16-3 series) plaques (see Figure 2C-122C-17) may be used to 35 inform the road user of the distance to the condition indicated by the warning sign. 36 The Next Distance (W7-3aP and W16-4P) plaques (see also Figures 2C-42C-5 and 2C-12 2C-17) may be 37 used to inform road users of the length of roadway over which the condition indicated by the warning sign 38 exists. 39 Section 2C.562C.62 Supplemental Arrow Plaques (W16-5P, W16-6P) 40 Guidance:

If the condition indicated by a warning sign is located on an intersecting road and the distance between the intersection and condition is not sufficient to provide adequate advance placement of the warning sign, a Supplemental Arrow (W16-5P or W16-6P) plaque (see Figure 2C-122C-17) should be used below the warning sign.

Standard:

41

42

43

44

45

46

47

48

49

Supplemental Arrow plaques shall have the same legend design as the Advance Turn Arrow and Directional Arrow auxiliary signs (see Sections 2D.26 and 2D.28) except that they shall have a black legend and border on a yellow or fluorescent yellow-green background, as appropriate.

Guidance:

42.

Hill-Related (W7-2 series, W7-3 series) plaques (see Figure 2C-42C-5) or other appropriate legends and larger signs should be used for emphasis or where special hill characteristics exist.

On longer grades, the use of the distance plaque (W7-3aP or W7-3bP) at periodic intervals of approximately 1-mile spacing should be considered.

Section 2C.58 2C.64 Advance Street Name Plaque (W16-8P, W16-8aP)

Option:

An Advance Street Name (W16-8P or W16-8aP) plaque (see Figure 2C-12) may be used with any Intersection sign (W2 series, W10-2, W10-3, or W10-4) or Advance Traffic Control (W3 series) sign to identify the name of the intersecting street.

Support:

See Section 2D.46 for the use of an Advance Street Name sign posted at a separate location in cases where there is a need to provide advance notice of an intersecting street where warning signs other than those listed in Paragraph 1 are used, such as a Combination Horizontal Alignment/Intersection (W1-10 Series) sign.

Standard:

The lettering on Advance Street Name plaques shall be composed of a combination of lower-case letters with initial upper-case letters.

If two street names are used on the Advance Street Name plaque, a directional arrow pointing in the direction of the street shall be placed next to each street name. Arrows pointing to the left shall be placed to the left of the street name, and arrows pointing to the right shall be placed to the right of the street name.

Guidance:

If two street names are used on the Advance Street Name plaque, the street names and associated arrows should be displayed in the following order:

- A. For a single intersection, the name of the street to the left should be displayed above the name of the street to the right; or
- B. For two sequential intersections, such as where the plaque is used with an Offset Side Roads (W2-7) or a Double Side Road (W2-8) symbol sign, the name of the first street encountered should be displayed above the name of the second street encountered, and the arrow associated with the second street encountered should be an advance arrow, such as the arrow shown on the W16-6P arrow plaque (see Figure 2C-122C-17).

Section 2C.59 2C.65 CROSS TRAFFIC DOES NOT STOP Plaque Traffic Does Not Stop Plaques (W4-4P Series)

Option:

The CROSS TRAFFIC DOES NOT STOP (W4-4P) plaque (see Figure 2C-9) may be used in combination with a STOP sign when engineering judgment indicates that conditions are present that are causing or could cause drivers to misinterpret the intersection as an all-way stop.

Alternative messages (see Figure 2C-92C-11) such as TRAFFIC FROM LEFT (RIGHT) DOES NOT STOP (W4-4aP) or ONCOMING TRAFFIC DOES NOT STOP (W4-4bP) may be used when such messages more accurately describe the traffic controls established at the intersection.

41 Guidance:

Plaques with the appropriate alternative messages of TRAFFIC FROM LEFT (RIGHT) DOES NOT STOP or ONCOMING TRAFFIC DOES NOT STOP should be used at intersections where STOP signs control all but one approach to the intersection, unless the only non-stopped approach is from a one-way street.

Standard:

If a W4-4P plaque or a plaque with an alternative message is used, it shall be mounted below the STOP sign.

- 49 Section 2C.60 SHARE THE ROAD Plaque (W16-1P) Sign removed from MUTCD
- 50 Section 2C.66 IN ROAD and IN STREET Plaques (W16-1P, W16-1aP)

1 Option:

In situations where there is a need to warn drivers to watch for other slower forms of transportation traveling along the highway, such as bicycles, golf carts, horse-drawn vehicles, or farm machinery, an IN

4 ROAD (W16-1P) or IN STREET (W16-1aP) plaque may be used.

Standard:

The background color of the W16-1P or W16-1aP plaque shall match the background color of the warning sign with which it is displayed. If a W16-1P or W16-1aP plaque is used, it shall be mounted below either a Vehicular Traffic Warning sign (see Section 2C.54) or a Non-Vehicular Warning sign (see Section 2C.55), and shall not be mounted alone.

10 Option:

5

In situations where there is a need to warn drivers of the presence of bicycles entering the roadway or where bicyclists are expected or preferred to use the full lane a Bicycles May Use Full Lane (R4-11) sign (See Section 9B.14) may be used.

14 Section 2C.67 Except Bicycles Plaque (W16-20P)

15 Option:

Where it is desired to notify bicyclists that the conditions depicted by a warning sign are not applicable to bicycles, the Except Bicycles supplemental warning plaque (W16-20P) may be mounted below the warning

18 <u>sign.</u>

16

17

25

27

28

29

30

32

33

34

19 Support:

Examples of warning signs with which an Except Bicycles (W16-20P) plaque can be mounted include DEAD END (W14-1) or NO OUTLET (W14-2) signs.

22 **Standard:**

If used with a warning sign, The Except Bicycles (W16-20P) plaque shall be a rectangle with a black legend and border on a yellow background.

Section 2C.61 2C.68 Photo Enforced Plaque (W16-10P)

26 Option:

A Photo Enforced (W16-10P) plaque or a PHOTO ENFORCED (W16-10aP) word message plaque (see Figure 2C-12) may be mounted below a warning sign to advise road users that the regulations associated with the condition being warned about (such as a traffic control signal or a toll plaza) are being enforced by photographic equipment.

31 Standard:

If used below a warning sign, the Photo Enforced (W16-10P or W16-10aP) plaque shall be a rectangle with a black legend and border on a yellow background.

Section 2C.63 2C.69 Object Marker Design and Placement Height

Support:

Type 1, 2, and 3 object markers are used to mark obstructions within or adjacent to the roadway. Type 4 object markers are used to mark the end of a roadway.

Standard:

When used, object markers (see Figure 2C-132C-18) shall not have a border and shall consist of an arrangement of one or more of the following types:

Type 1—a diamond-shaped sign, at least 18 inches on a side, consisting of either a yellow (OM1-1) or black (OM1-2) sign with nine yellow retroreflective devices, each with a minimum diameter of 3 inches, mounted symmetrically on the sign, or an all-yellow retroreflective sign (OM1-3).

Type 2—either a marker (OM2-1V or OM2-1H) consisting of three yellow retroreflective devices, each with a minimum diameter of 3 inches, arranged either horizontally or vertically on a white sign measuring at least 6 x 12 inches; or an all-yellow horizontal or vertical retroreflective sign (OM2-2V or OM2-2H), measuring at least 6 x 12 inches.

Type 3—a striped marker, 12×36 inches, consisting of a vertical rectangle with alternating black and retroreflective yellow stripes sloping downward at an angle of 45 degrees toward the side of the obstruction on which traffic is to pass. The minimum width of the yellow and black stripes shall be 3 inches.

Type 4—a diamond-shaped sign, at least 18 inches on a side, consisting of either a red (OM4-1) or black (OM4-2) sign with nine red retroreflective devices, each with a minimum diameter of 3 inches, mounted symmetrically on the sign, or an all-red retroreflective sign (OM4-3).

Figure 2C-18. Object Markers

Support:

A better appearance can be achieved if the black stripes are wider than the yellow stripes.

Type 3 object markers with stripes that begin at the upper right side and slope downward to the lower left side are designated as right object markers (OM3-R). Object markers with stripes that begin at the upper left side and slope downward to the lower right side are designated as left object markers (OM3-L).

Guidance:

When used for marking obstructions within the roadway or obstructions that are 8 feet or less from the shoulder or curb, the minimum mounting height, measured from the bottom of the object marker to the elevation of the near edge of the traveled way, should be 4 feet.

When used to mark obstructions more than 8 feet from the shoulder or curb, the clearance from the ground to the bottom of the object marker should be at least 4 feet.

Object markers should not present a vertical or horizontal clearance obstacle for pedestrians.

36 Option

When object markers or markings are applied to an obstruction that by its nature requires a lower or higher mounting, the vertical mounting height may vary according to need.

Support:

Section 9B.269C.09 contains information regarding the use of object markers on shared-use paths.

Section 2C.64-2C.70 Object Markers for Obstructions Within the Roadway

Standard:

Obstructions within the roadway shall be marked with a Type 1 or Type 3 object marker. In addition to markers on the face of the obstruction, warning of approach to the obstruction shall be given by appropriate pavement markings (see Section 3B.103B.13).

Option:

To provide additional emphasis, a Type 1 or Type 3 object marker may be installed at or near the approach end of a median island.

To provide additional emphasis, large surfaces such as bridge piers may be painted with diagonal stripes, 12 inches or greater in width, similar in design to the Type 3 object marker.

Standard:

The alternating black and retroreflective yellow stripes (OM3-L, OM3-R) shall be sloped down at an angle of 45 degrees toward the side on which traffic is to pass the obstruction. If traffic can pass to either side of the obstruction, the alternating black and retroreflective yellow stripes (OM3-C) shall form chevrons that point upwards.

Option:

Appropriate signs (see Sections 2B.32 and 2C.252C.23) directing traffic to one or both sides of the obstruction may be used instead of the object marker.

Section 2C.65 2C.71 Object Markers for Obstructions Adjacent to the Roadway

Support:

Obstructions not actually within the roadway are sometimes so close to the edge of the road that they need a marker. These include underpass piers, bridge abutments, handrails, ends of traffic barriers, utility poles, and culvert headwalls. In other cases there might not be a physical object involved, but other roadside conditions exist, such as narrow shoulders, drop-offs, gores, small islands, and abrupt changes in the roadway alignment, that might make it undesirable for a road user to leave the roadway, and therefore would create a need for a marker.

Option:

Type 2 or Type 3 object markers may be used to mark an obstruction adjacent to the roadway. Standard Guidance: Changed from Standard to Guidance

If a Type 2 or Type 3 object marker is used to mark an obstruction adjacent to the roadway, the edge of the object marker that is closest to the road user <u>shall-should</u> be installed in line with the closest edge of the obstruction.

Where When a marker is Type 3 object markers are applied to the approach ends of guardrail or crash cushion terminals it should have the appearance of a Type 3 object marker and should be and other roadside appurtenances, sheeting without a substrate shall be directly affixed, without a substrate, to the approach end of the guardrail or crash cushion and generally conform in a rectangular shape conforming to the size and shape of the approach end of the guardrail or crash cushion with alternating black and retroreflective yellow stripes sloping downward at a angle of 45 degrees toward the side of the obstruction on which traffic is to pass.

Standard:

Type 1 and Type 4 object markers shall not be used to mark obstructions adjacent to the roadway.

34 Guidance:

Standard warning signs in this Chapter should also be used where applicable.

Section 2C.66 2C.72 Object Markers for Ends of Roadways

Support:

The Type 4 object marker is used to warn and alert road users of the end of a roadway in other than construction or maintenance areas.

Standard:

If an object marker is used to mark the end of a roadway, a Type 4 object marker shall be used.

42 Option:

The Type 4 object marker may be used in instances where there are no alternate vehicular paths.

Where conditions warrant, more than one marker, or a larger marker with or without a Type 3 Barricade (see Section 2B.672B.76), may be used at the end of the roadway.

Standard:

The minimum mounting height, measured vertically from the bottom of a Type 4 object marker to the elevation of the near edge of the traveled way, shall be 4 feet.

Guidance:

Appropriate advance warning signs in this Chapter should be used.

	CHAPTER 2D. GUIDE SIGNS—CONVENTIONAL RO
CI (AD	
	Subchapter and Section Organization
General Des	
2D.01	Scope of Conventional Road Guide Sign Standards and Application
2D.02	Color, Retroreflection, and Illumination
2D.03	Size of Signs
2D.04	Lettering Style
2D.05	Size of Lettering
2D.06	Amount of Legend
2D.07	Abbreviations
2D.08	Arrows
Route Signs	and Auxiliary Plagues
2D.09	Numbered Highway Systems
2D.10	Route Signs and Auxiliary Plaques
2D.11	Design of Route Signs
2D.12	Design of Route Sign Auxiliary Plaques
2D.13	Junction Auxiliary Plaque (M2-1P)
2D.14	Combination Junction Sign (M2-2)
2D.15	Cardinal Direction Auxiliary Plaques (M3-1P through M3-4P)
2D.16	Auxiliary Plaque for Alternative Routes (M4-1P through M4-4P)
2D.17	ALTERNATE Auxiliary Plagues (M4-1P, M4-1aP)
2D.18	BY-PASS Auxiliary Plaque (M4-2P)
2D.19	BUSINESS Auxiliary Plaque (M4-3P)
2D.20	TRUCK Auxiliary Plaque (M4-4P)
2D.21	TO Auxiliary Plaque (M4-5P)
2D.22	END Auxiliary Plaque (M4-6P)
2D.23	BEGIN Auxiliary Plaque (M4-14P)
2D.24	TEMPORARY Auxiliary Plaques (M4-7P, M4-7aP)
2D.25	Temporary Detour Signs and Auxiliary Plaques
2D.26	Advance Turn Arrow Auxiliary Plaques (M5-1P, M5-2P, M5-3P)
2D.27	Lane Designation Auxiliary Plaques (M5-4P, M5-5P, M5-6P)
2D.28	Directional Arrow Auxiliary Plaques (M6 Series)
Sign Assemb	Nige
2D.29	Route Sign Assemblies
$\frac{2D.29}{2D.30}$	Junction Assembly
2D.30 2D.31	Advance Route Turn Assembly
$\frac{2D.31}{2D.32}$	Directional Assembly
2D.33	Confirming or Reassurance Assemblies
2D.34	Trailblazer Assembly
-	
	and Distance Signs
2D.35	Destination and Distance Signs
2D.36	Destination Signs (D1 Series)
2D.37	Overhead Arrow-Per-Lane Destination Guide Signs
2D.38	Combination Lane-Use/Destination Overhead Guide Sign (D15-1)
2D.39	Destination Signs at Circular Intersections
2D.40	Destination Signs at Jughandles
<u>2D.41</u>	Destination Signs at Intersections with Indirect Turning Movements
2D.42	Location of Destination Signs
2D.43	Distance Signs (D2 Series)
<u>2D.44</u>	Location of Distance Signs

1 2 3 4	2D.45 2D.46 2D.47 2D.48	Street Name Signs (D3-1, D3-1a) Advance Street Name Signs (D3-2 Series) Parking Area Guide Sign (D4-1) PARK - RIDE Sign (D4-2)
5	Freeway Entra	nce Signs
6	2D.49	Signing on Conventional Roads on Approaches to Interchanges
7	2D.50	Freeway Entrance Signs (D13-3, D13-3a)
8	Lane, Passing	Lane, Crossover and Emergency and Slow Vehicle Turn-Out Signs
9	2D.51	WEIGH STATION Signing (D8 Series)
10	2D.52	Crossover Signs (D13-1, D13-2)
11	2D.53	Truck and Passing Lane Signs (D17-1, D17-2, D17-3, D17-4)
12	2D.54	Emergency and Slow Vehicle Turn-Out Signs (D17-5 through D17-7)
13	Other Guide Si	
14	2D.55	Community Wayfinding Signs
15	2D.56	Signing of Named Highways for Mapping and Address Purposes
16	<u>2D.57</u>	National Scenic Byways Sign and Plaque (D6-4, D6-4aP)
17	<u>2D.58</u>	State-Designated Scenic Byway, Historic Trail, and Auto Tour Route Signs
18	2D.59	EMERGENCY ROUTE and EMERGENCY ROUTE TO Signs and Plaques
19		

GENERAL DESIGN

3 Section 2D.01 Scope of Conventional Road Guide Sign Standards and Application Existing

4 Sections 2D.01 and 2D.02 combined into one section

Standard:

The provisions of this Chapter shall apply to any road or street other than low-volume roads (as defined in Section 5A.01), expressways, and freeways, except as stated elsewhere in this Manual. Moved from existing Section 2D.01

Support:

Guide signs are essential to direct road users along streets and highways, to inform them of intersecting routes, to direct them to cities, towns, villages, or other important destinations, to identify nearby rivers and streams, parks, forests, and historical sites, and generally to give such information as will help them along their way in the most simple, direct manner possible.

Chapter 2A addresses placement, location, and other general criteria for signs. Moved to later in this combined new Section 2D.01

Guidance:

The selection of primary or control destinations (those displayed consistently over longer distances along a route) displayed on guide signs should be meaningful to road users in navigation and orientation. The destinations selected should be identifiable on official maps.

The following 4 paragraphs moved from existing Section 5D.01

The familiarity of the road users with the road should be considered in determining the need for guide signs on low-volume roads.

Support:

Low-volume roads generally do not require guide signs to the extent that they are needed on higher classes of roads. Because guide signs are typically only beneficial as a navigational aid for road users who are unfamiliar with a low-volume road, guide signs might not be needed on low-volume roads that serve only local traffic.

Guidance:

If used on <u>low-volume roads</u>, destination names should be as specific and descriptive as possible. Destinations such as campgrounds, ranger stations, recreational areas, and the like should be clearly indicated so that they are not interpreted to be communities or locations with road user services. Option:

Guide signs may be used <u>on low-volume roads</u> at intersections to provide information for road users returning to a higher class of roads.

Support: Moved from earlier in existing Section 2D.02

Guide signs are essential to direct road users along streets and highways, to inform them of intersecting routes, to direct them to cities, towns, villages, or other important destinations, to identify nearby rivers and streams, parks, forests, and historical sites, and generally to give such information as will help them along their way in the most simple, direct manner possible.

Chapter 2A addresses placement, location, and other general criteria for signs.

Guide signs, other than Street Name signs, generally are not used on low-volume rural roads except as needed to guide road users back to the major roadways.

Many roadways within airport facilities (including terminal curbside roadways) would be considered conventional roads because they typically have frequent driveways and at-grade intersections and might have pedestrian activity along and/or across them.

Some airport roadways have full or partial control of access and operating speeds higher than 45 mph and thus would be classified as freeways or expressways for signing purposes (see Chapter 2E). Freeway or expressway conditions typically exist on the approaches to the airport from other highways, on the approaches to access points to terminals, parking, and other patron facilities, and on roadways that provide exits from the airport facility to connect with the local or regional highway network.

Roadways within airports and other similarly contained roadway networks with multiple closely-spaced access points to multiple destinations (such as terminals, parking facilities, rental car facilities, and other airport services) often present challenges for the application of guide signing. Closely spaced signs, excessive sign messaging either co-located or in succession, and the resulting excessive informational load imposed on the road user are of particular concern for such roadways.

An example of major guide signing within an airport facility roadway network is shown in Figure 2D-1.

Figure 2D-1. Example of Guide Signing Within an Airport Facility Roadway Network

Guidance:

1

2

3 4

5

6

7

8

9

10

11

12

13

14

16

17 18

19

20

21

22

23

24 25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

48

If adequate sign spacing cannot be provided due to the site and roadway characteristics of an airport or similar facility, then the speeds of vehicles on the roadway should be reduced to provide road users with adequate time to comprehend and respond, or sign letter heights should be increased, or both. Where a single terminal serves a large number of airlines, the airline information should be displayed on separate signs that appear in sequence to limit the number of airlines displayed on a single sign or at a single location. Changeable message signs (see Chapter 2L) should not be used to rotate the display airlines to an

15 approaching road user.

Section 2D.03 2D.02 Color, Retroreflection, and Illumination

Requirements for illumination, retroreflection, and color are stated under the specific headings for individual guide signs or groups of signs. General provisions are given in Sections 2A.07, 2A.08, and 2A.10.

Standard:

Except where otherwise provided in this Manual for individual signs or groups of signs, guide signs on streets and highways shall have a white message and border on a green background. All messages, borders, and legends shall be retroreflective and all backgrounds shall be retroreflective or illuminated.

Color coding is sometimes used to help road users distinguish between multiple potentially confusing destinations. Examples of valuable uses of color coding include guide signs for roadways approaching or inside an airport property with multiple terminals serving multiple airlines, and community wayfinding guide signs for various traffic generator destinations within a community or area.

Standard:

Except where otherwise provided in this Manual, different color sign backgrounds shall not be used to provide color coding of destinations. The color coding shall be accomplished by the use of different colored square or rectangular sign panels on the face of the guide signs.

Option:

The different colored sign panels on the face of a sign may include a black or white (whichever provides the better contrast with the panel color) letter, numeral, or other appropriate designation to identify an airport terminal or other destination.

Support:

Two eExamples of color-coded signs assemblies are shown in Figure 2D-12D-2. Section 2D.50-55 contains specific provisions regarding Community Wayfinding guide signs.

Figure 2D-2. Examples of Color-Coded Destination Guide Signs

- 41 Section 2D.04 2D.03 Size of Signs
- 42 **Standard:**

43 Except as provided in Section 2A.11, the sizes of conventional road guide signs that have standardized designs shall be as shown in Table 2D-1. 44

45 Support:

46 Section 2A.11 contains information regarding the applicability of the various columns in Table 2D-1.

47 Option:

Signs larger than those shown in Table 2D-1 may be used (see Section 2A.11).

Table 2D-1. Conventional Road Guide Sign Sizes

Support:

For other guide signs, the legends are so variable that a standardized design or size is not appropriate. The sign size is determined primarily by the length of the message, and the size of lettering and spacing necessary for proper legibility.

Option:

Reduced letter height, reduced interline spacing, and reduced edge spacing may be used on guide signs if sign size must be limited by factors such as lane width or vertical or lateral clearance.

Guidance:

Reduced spacing between the letters or words on a line of legend should not be used as a means of reducing the overall size of a guide sign, except where determined necessary by engineering judgment to meet unusual lateral space constraints. In such cases, the legibility distance of the sign legend should be the primary consideration in determining whether to reduce the spacing between the letters or the words or between the words and the sign border, or to reduce the letter height.

When a reduction in the prescribed size is necessary, the design used should be as similar as possible to the design for the standard size.

Section 2D.05 2D.04 Lettering Style

Standard:

The design of upper-case letters, lower-case letters, numerals, route shields, and spacing shall be as provided in the "Standard Highway Signs and Markings" book publication (see Section 1A.11).

The lettering for names of places, streets, and highways on conventional road guide signs shall be a combination of lower-case letters with initial upper-case letters (see Section 2A.13). The nominal loop height of the lower-case letters shall be 3/4 the height of the initial upper-case letter. When a mixed-case legend letter height is specified referring only to the initial upper-case letter, the height of the lower-case letters that follow shall be determined by this proportion. When the height of a lower-case letter is referenced, the reference is made to the nominal loop height—and___tThe height of the initial upper-case letter shall also be determined by this proportion.

All other word legends on conventional road guide signs shall be in upper-case letters.

The unique letter forms for each of the Standard Alphabet series shall not be stretched, compressed, warped, or otherwise manipulated. Modifications to the length of a word for a given letter height and series shall be accomplished only by the methods described in Section 2D.04.03

Section 2D.06 2D.05 Size of Lettering

Support:

Sign legibility is a direct function of letter size and spacing. Legibility distance has to be sufficient to give road users enough time to read and comprehend the sign. Under optimum conditions, a guide sign message can be read and understood in a brief glance. The legibility distance takes into account factors such as inattention, blocking of view by other vehicles, unfavorable weather, inferior eyesight, or other causes for delayed or slow reading. Where conditions permit, repetition of guide information on successive signs gives the road user more than one opportunity to obtain the information needed.

Standard:

Design layouts for conventional road guide signs showing interline spacing, edge spacing, and other specification details shall be as shown in the "Standard Highway Signs and Markings" book publication (see Section 1A.11).

Except as otherwise provided in this Manual, the The principal legend on post-mounted guide signs shall be in letters and numerals at least 6 inches in height for all upper-case letters, or a combination of 6 inches in height for upper-case letters and 4.5 inches in height (see Section 2D.04) for lower-case letters. On low-volume roads (as defined in Section 5A.01) with speeds of 25 mph or less, and on urban streets with speeds of 25 mph or less, the principal legend on post-mounted guide signs shall be in letters at least 4 inches in height for all upper-case letters, or a combination of 4 inches in height for upper-case letters and 3 inches in height for lower-case letters.

1 The principal legend on overhead guide signs shall be in letters and numerals at least 12 inches in 2 height for all upper-case letters, or a combination of 12 inches in height for upper-case letters and 9 inches in height (see Section 2D.04) for lower-case letters. 3 4 Option: 5 On conventional roadways with speed limits of 40 miles per hour or less, overhead guides sign destinations may use an upper-case letter at least 10.67 inches in height followed by lower-case letters 8 6 7 inches in height. 8 Guidance: 9 Lettering sizes should be consistent on any particular class of highway. 10 The minimum lettering and numeral sizes provided in this Manual (see Table 2D-2) should be exceeded 11 where conditions indicate a need for greater legibility. Table 2D-2. Minimum Letter and Numeral Sizes for Conventional Road Guide Signs by 12 13 Roadway Type 14 Section 2D.072D.06 Amount of Legend 15 Support: 16 The longer the legend on a guide sign, the longer it will take road users to recognize and comprehend it, 17 regardless of letter size. 18 Guidance: 19 Except where otherwise provided in this Manual, guide signs should be limited to no more than three lines 20 of destinations, which include place names, route numbers, street names, and cardinal directions. Where two 21 or more signs are included in the same overhead display, the amount of legend should be further minimized. 22 Where appropriate, a distance message or action information, such as an exit number, NEXT RIGHT, or 23 directional arrows, should be provided on guide signs in addition to the destinations. 24 Section 2D.07 Abbreviations Section relocated and edited from existing Section 2E.17 25 Support: 26 The use of commonly recognized abbreviations for certain words can be useful in reducing the apparent 27 complexity of a sign message. Descriptors and directional or quadrant orientations for street names and destinations, such as Boulevard (Blvd), North (N), and Southwest (SW), are some examples of commonly 28 29 recognized abbreviations. Examples of the use of abbreviations are shown in Figure 2D-3. 30 Figure 2D-3. Examples of the Use of Abbreviations 31 **Standard:** 32 The words NORTH, SOUTH, EAST, and WEST shall not be abbreviated when used to indicate 33 cardinal directions of numbered or named highways on guide signs. 34 Guidance: 35 Abbreviations should be kept to a minimum; however, they are useful when complete destination 36 messages produce excessively long signs. If used, abbreviations should be unmistakably recognized by road 37 users (see Section 1A.15). Longer commonly used words that are not part of a proper name and are readily 38 recognizable, such as street name descriptors (Street, Boulevard, and Avenue, etc.), should be abbreviated as 39

provided in Table 2D-3 to expedite recognition of the sign legend by reducing the amount and complexity of the legend. Shorter street name descriptors should not be abbreviated (see Table 2D-4

Periods, apostrophes, question marks, ampersands, or other punctuation or characters that are not letters, numerals, or hyphens should not be used in abbreviations, unless necessary to avoid confusion.

The solidus (slanted line or forward slash) is intended to be used for fractions only and should not be used to separate words on the same line of legend. Instead, a hyphen should be used for this purpose, such as "CARS TRUCKSTRUCKS - BUSES".

> Table 2D-3. Acceptable Abbreviations for Street Name Descriptors Table 2D-4. Street Name Descriptors Not Acceptable for Abbreviation

Section 2D.08 Arrows

40

41

42

43

44

45

46

47

48

Support:

Arrows are used for lane assignment and to indicate the direction toward designated routes or destinations. Figure 2D-2-2D-4 shows the various standard arrow designs that have been approved for use on guide signs. Detailed drawings and standardized sizes based on ranges of letter heights are shown for these arrows in the "Standard Highway Signs—and Markings" book—publication (see Section 1A.11).

Standard:

On overhead signs where it is desirable to indicate a lane to be followed, a down arrow shall be positioned approximately over the approximate center of the lane and shall point vertically downward toward the approximate center of that lane. Down arrows shall be used only on overhead guide signs that restrict the use of specific lanes to traffic bound for the destination(s) and/or route(s) indicated by these arrows. Down arrows shall not be used unless an arrow can be located over and pointed to the approximate center of each lane that can be used to reach the destination displayed on the sign.

If down arrows are used, having more than one down arrow pointing to the same lane on a single overhead sign (or on multiple signs on the same overhead sign structure) shall not be permitted.

Where a roadway is leaving the through lanes, a directional arrow shall point upward at an angle that approximates the alignment of the exit roadway in the vicinity of the point of departure.

Option:

Curved stem arrows (see Figure 2D-8) that represent the intended driver paths to destinations involving left-turn movements may be used on guide signs on approaches to circular intersections.

Standard:

<u>Curved-stem The Type E directional</u> arrows <u>for circular intersections</u> shall not be used on any sign that is not associated with a circular intersection.

Figure 2D-4. Arrows for Use on Guide Signs

Guidance:

If curved stem arrows are used, the principles set forth in Sections 2D.26 through 2D.29 should befollowed Relocated to below

The Type A directional arrow should be used on guide signs on freeways, expressways, and conventional roads to indicate the direction to a specific destination or group of destinations, except as otherwise provided in this Section and in Section 2E.19.

When a directional arrow in a vertical, upward-pointing orientation is placed to the side of a group of destinations to indicate a through movement, the Type A directional arrow should be used. When a directional arrow in a vertical, upward-pointing orientation is placed to the side of a single destination or under a destination or group of destinations, the Type B directional arrow should be used.

The Type B directional arrow should be used on guide signs on conventional roads when placed at any angle to the side of a single destination or when placed in a horizontal orientation to the side of a group of destinations.

The Type C advance turn directional arrow should be used on conventional road guide signs placed in advance of an intersection where a turn must be made to reach a posted destination or group of destinations.

The Type D directional arrow should be used primarily for sign applications other than guide signs, except as provided in Paragraph <u>16.15</u> of this Section.

If curved stem arrows are used If the Type E directional arrow is used, the principles set forth in Sections 2D.26 through 2D.29 should be followed. Relocated from above

Option:

The Type A-Extended directional arrow may be used on guide signs where additional emphasis regarding the direction is needed relative to the amount of legend on the sign.

The Type C directional arrow may be used to the side of the legend of an overhead guide sign to accentuate a sharp turn exit maneuver from a mainline roadway (see Section 2E.36 for additional information regarding Exit Direction signs for low advisory ramp speeds).

On conventional roads on the approach to an intersection where the Combination Lane-Use/Destination overhead guide sign (see Section 2D.<u>3338</u>) is not used, the Type C advance turn directional arrow may be

used beneath the legend of an overhead guide sign to indicate the fact that a turn must be made from a mandatory movement lane over which the sign is placed to reach the destination or destinations displayed on the sign.

The Type D directional arrow may be used on post-mounted guide signs on conventional roads with lower operating speeds if the height of the text on the sign is 8 inches or less.

The Type E directional arrow (see Figure 2D-4) may be used on guide signs on approaches to circular intersections to represent the intended driver paths to destinations involving left-turn movements around the circulatory island.

The directional and down arrows shown in Figure 2D-2-2D-4 may be used on signs other than guide signs for the purposes of providing directional guidance and lane assignment.

Guidance:

Arrows used on guide signs to indicate the directions toward designated routes or destinations should be pointed at the appropriate angle to clearly convey the direction to be taken. A horizontally oriented directional arrow design should be used at right-angle intersections.

On a post-mounted guide sign, a directional arrow for a straight-through movement should point upward. Except as provided in Section 2D.4650, for a turn, the arrow on a guide sign should point horizontally or at an upward angle that approximates the sharpness of the turn.

At an exit, an arrow should be placed at the side of the sign that will reinforce the movement of exiting traffic. The directional arrow design should be used.

Option:

Arrows may be placed below the principal sign legend or on the appropriate side of the legend that is consistent with the direction of the movement.

On a post-mounted sign at an exit where placement of the arrow to the side of the legend farthest from the roadway would create an unusually wide sign that limits the road user's view of the arrow, the directional arrow may be placed at the bottom portion of the sign, centered under the legend.

Guidance:

The width across the arrowhead for the Types A, B, and C directional arrows should be between 1.5 and 1.75 times the height of the upper-case letters of the principal legend on the sign. The width across the arrowhead for the Type D directional arrow should be at least equal to the height of the upper-case letters of the principal legend on the sign. For down arrows used on overhead signs, the width across the arrowhead should be approximately two times the height of the upper-case letters of the principal legend on the sign.

Arrows used in Overhead Arrow-per-Lane and Diagrammatic guide signing, if used on conventional roads, except for signs on approaches to roundabouts, should follow-comply with the principles set forth in provisions of Section 2E.19. Arrows used in Diagrammatic guide signing on approaches to roundabouts should follow the principles set forth in Section 2D.389.

Support:

The "Standard Highway Signs-and-Markings" book publication (see Section 1A.11) contains design details and standardized sizes of the various arrows based on ranges of letter heights of principal legends.

4

5

6

7 8

9

10

11

12

13

14

15

16

17 18

19

20

21

22

23

25

26 27

29

30

33

34

35

36

38

39

41

Section 2D.09 Numbered Highway Systems

3 Support:

The purpose of numbering and signing highway systems is to identify routes and facilitate travel.

The Interstate and United States (U.S.) highway systems are numbered by the American Association of State Highway and Transportation Officials (AASHTO) upon recommendations of the State highway organizations because the respective States own these systems. State and county road systems are numbered by the appropriate authorities.

The basic policy for numbering the Interstate and U.S. highway systems is contained in the following Purpose and Policy statements published by AASHTO (see Page i for AASHTO's address):

- A. "Establishment and Development of United States Numbered Highways," and
- B. "Establishment of a Marking System of the Routes Comprising the National System of Interstate and Defense Highways."
- Guidance:

The principles of these policies should be followed in establishing the highway systems described in Paragraph 2 and any other systems, with effective coordination between adjacent jurisdictions. Care should be taken to avoid the use of numbers or other designations that have been assigned to Interstate, U.S., or State routes in the same geographic area. Overlapping numbered routes should be kept to a minimum.

Standard:

Route systems shall be given preference in this order: Interstate, United States, State, and county. The preference shall be given by installing the highest-priority <u>legend-route number</u> on the top or the left of the sign, <u>except as provided in Paragraph 7</u>.

Interstate route numbering shall be approved by FHWA.

24 Option:

The prioritization of route systems may be modified when a different prioritization would better accommodate the expectancy of the road user and provide more effective direction, such as for separate decision points for routes that are encountered in a particular order.

28 Support:

Section 2D.53-<u>56</u> contains information regarding the signing of unnumbered highways to enhance route guidance and facilitate travel.

31 Section 2D.10 Route Signs and Auxiliary Signs Plaques

32 Standard:

Except as provided in Paragraph 9 of Section 2D.29, All—all numbered highway routes shall be identified by route signs and auxiliary signsplaques.

The signs for each system of numbered highways, which are distinctive in shape and color, shall be used only on that system and the approaches thereto.

37 Option:

Route signs and auxiliary signs plaques may be proportionally enlarged where greater conspicuity or legibility is needed.

40 Support:

- Route signs are typically mounted in assemblies with auxiliary signsplaques.
- 42 Section 2D.5755 contains information regarding the signing for National Scenic Byways.
- Section 2H.07 contains information regarding the signing for <u>State-designated scenic byways, historic</u>
- 44 trails, and Auto- auto Tour tour Routes routes.
- 45 Section 2D.11 Design of Route Signs
- 46 Standard:

The <u>design of standard route signs shall conform to the designs provided in the</u> "Standard Highway Signs and <u>Markings</u>" <u>book publication</u> (see Section 1A.11) <u>shall be used for designing route signs</u>. <u>The design of Oo</u>ther route signs <u>designs</u> shall be established by the authority having jurisdiction <u>and shall</u> <u>also</u> be in general conformance with the designs provided in the "Standard Highway Signs" publication.

Interstate Route (M1-1 and M1-1a) signs (see Figure 2D-32D-5) shall consist of a cutout shield, with the route number in white letters on a blue background, the word INTERSTATE in white upper-case letters on a red background, and a white border. This sign shall be used on all Interstate routes and in connection with route sign assemblies on intersecting highways.

Except as otherwise provided in this Manual, A-a-24 x 24-inch minimum sign size shall be used for Interstate route numbers with one or two digits, and a 30 x 24-inch minimum sign size shall be used for Interstate route numbers having three digits.

Figure 2D-5. Route Signs

Option:

When the Interstate Route sign is used in a Route Sign assembly (see Section 2D.29), the M1-1a Interstate Route signs, may containing the State name in white upper-case letters on a blue background as detailed in the "Standard Highway Signs" publication, may be used in place of the M1-1 sign.

Standard:

Use of the M1-1a sign shall be limited to Route Sign assemblies.

Off-Interstate Business Route (M1-2 and M1-3) signs (see Figure 2D-32D-5) shall consist of a cutout shield carrying displaying the number of the connecting Interstate route and the words BUSINESS and either LOOP (when the route rejoins the same Interstate route) or SPUR (when the route leaves the corresponding Interstate route and does not rejoin) in upper-case letters. The legend and border shall be white on a green background, and the shield shall be the same shape and dimensions as the Interstate Route sign. In no instance shall the word INTERSTATE appear on the Off-Interstate Business Route sign.

Option:

The Off-Interstate Business Route sign may be used on a major highway that is not a part of the Interstate system, but one that serves the business area of a city from an interchange on the system.

When used on a green guide sign, a white square or rectangle may be placed behind the shield to improve contrast.

Standard:

U.S. Route signs (see Figure 2D-32D-5) shall consist of black numerals on a white shield surrounded by a rectangular black background without a border. This sign shall be used on all U.S. routes and in connection with route sign assemblies on intersecting highways.

A 24 x 24-inch minimum sign size shall be used for U.S. route numbers with one or two digits, and a 30×24 -inch minimum sign size shall be used for U.S. route numbers having three digits.

State Route signs shall be designed by the individual State highway agencies.

The legend on State Route signs shall conform to the Standard Alphabets contained in the "Standard Highway Signs" publication.

Guidance:

State Route signs (see Figure 2D-32D-5) should be rectangular and should be approximately the same size as the U.S. Route sign. State Route signs should also be similar to the U.S. Route sign by containing approximately the same size black numerals on a white area surrounded by a rectangular black background without a border, and should be devoid of complex graphics. The shape of the white area should be circular in the absence of any determination to the contrary by the individual State concerned.

Where U.S. or State Route signs are used as components of guide signs, only the distinctive shape of the shield itself and the route numerals within should be used. The rectangular background upon which the distinctive shape of the shield is mounted, such as the black area around the outside of the shields on the M1-4 and standard M1-5 signs, should not be included on the guide sign. Where U.S. or State Route signs are used as components of other signs of non-contrasting background colors, the rectangular background should be used to so that recognition of the distinctive shape of the shield can be maintained.

Standard:

If county road authorities elect to establish and identify a special system of important county roads, a statewide policy for such signing shall be established that includes a uniform numbering system to uniquely identify each route. The County Route (M1-6) sign (see Figure $\frac{2D-3}{2D-5}$) shall consist of a pentagon shape with a yellow county name and route number and border on a blue background. County Route signs displaying two digits or the equivalent (letter and numeral, or two letters) shall be a minimum size of 18×18 inches; those carrying three digits or the equivalent shall be a minimum size of 24×24 inches.

If a jurisdiction uses letters instead of numbers to identify routes, all references to numbered routes in this Chapter shall be interpreted to also include lettered routes.

Guidance:

If used with other route signs in common assemblies, the County Route sign should be of a size compatible with that of the other route signs.

Option:

When used on a green guide sign, a yellow square or rectangle may be placed behind the County Route sign to improve cont

Standard:

The design of the National Forest Route (M1-7) sign (see Figure 2D-5) shall be as detailed in the "Standard Highway Signs" publication. Route signs (see Figure 2D-3) for other park and forest roads shall be designed with adequate an appropriate level of distinctiveness and adequate legibility, but in general compliance with the design principles for route signs and of a size compatible with other route signs used in common assemblies.

Section 2D.12 Design of Route Sign Auxiliaries Auxiliary Plaques

Standard:

Route sign auxiliaries <u>carrying displaying</u> word legends, except the JCT <u>signauxiliary plaque</u>, shall have a <u>minimum</u> standard size of 24 x 12 inches. <u>The JCT auxiliary plaque and Those those carrying auxiliary plaques displaying arrows symbols, or the JCT sign</u>, shall have a <u>minimum</u> standard size of 21 x 15 inches. All route sign <u>auxiliaries auxiliary plaques</u> shall match the color combination of the route sign that they supplement.

Guidance:

With route signs of larger heights, auxiliary signs should be suitably enlarged, but not such that they exceed the width of the route sign.

The background, legend, and border of a route sign auxiliary <u>plaque</u> should have the same colors as those of the route sign with which the auxiliary <u>plaque</u> is mounted in a route sign assembly (see Section 2D.29). For a route sign design that uses multiple background colors, such as the Interstate route sign, the background color of the corresponding auxiliary <u>plaque</u> should be that of the background area on which the route number is placed on the route sign.

Option:

A route sign and any auxiliary signs plaques used with it may be combined on a single sign as a guide sign.

Guidance:

If a route sign and its auxiliary signs are combined to form a single guide sign, the background color of the sign should be green and the design should comply with the basic principles for the design of guide signs. Guidance changed to Standard in the following paragraph

Standard:

If a route sign and its auxiliary signs plaques are combined to form a signal guide sign, the background color of the sign should shall be green and the design should shall comply with the basic principles for the design of guide signs. If a route sign and its auxiliary signs are combined on a single sign with a green background, tThe auxiliary messages shall be white legends placed

- directly on the green background. Auxiliary signs-plaques shall not be mounted directly to a 1
- 2 guide sign or other type of sign.
- 3 Support:
- 4 Chapter 2F contains information regarding auxiliary signs plaques for toll highways.
- 5 Section 2D.13 Junction Auxiliary Sign-Plaque (M2-1P)
- 6 **Standard:**

7 The Junction (M2-1) auxiliary sign-plaque (see Figure 2D-42D-6) shall earry display the 8 abbreviated legend JCT and shall be mounted at the top of an assembly (see Section 2D.30) directly 9 above the route sign, the sign for an alternative route (see Section 2D.17) that is part of the route designation, or the Cardinal Direction auxiliary signplaque where access is available only to one

10 11

direction of the intersected route. The minimum size of the Junction auxiliary sign-plaque shall be 21 x 12 15 inches for compatibility with auxiliary signs-plaques carrying displaying arrow symbols.

Figure 2D-6. Route Sign Auxiliaries

- Section 2D.14 Combination Junction Sign (M2-2)
- 15 Option:

13

14

20

21

23

24

25

26 27

33

34

16 As an alternative to the standard Junction assembly where more than one route is to be intersected or 17 joined, a rectangular guide sign may be used carrying displaying the word JUNCTION above the route 18 numbers.

- 19 **Standard:**
 - The Combination Junction (M2-2) sign (see Figure 2D-42D-6) shall have a green background with white border and lettering for the word JUNCTION.
- 22 Guidance:

The Combination Junction sign should comply with the specific provisions of Section 2D.11 regarding the incorporation of the route signs as components of guide signs.

Although the size of the Combination Junction sign will depend on the number of routes involved, the numerals should be large enough for clear legibility and should be of a size comparable with those in the individual route signs.

- 28 Section 2D.15 Cardinal Direction Auxiliary Signs Plaques (M3-1P through M3-4P)
- 29 Guidance:
- 30 Cardinal Direction auxiliary signs-plaques (see Figure 2D-42D-6) carrying-displaying the legend
- 31 NORTH, EAST, SOUTH, or WEST should be used to indicate the general direction of the entire route.
- 32 Standard:
 - To improve the readability and recognition of the cardinal directions, the first letter of the cardinal direction words shall be ten percent larger, rounded up to the nearest whole number size.
- 35 If used, the Cardinal Direction auxiliary sign-plaque shall be mounted directly above a route sign 36 or, if used, an auxiliary sign-plaque for an alternative route.
- 37 Section 2D.16 Auxiliary Signs Plaque for Alternative Routes (M4-1P through M4-4P Series)
- 38 Option:
- 39 Auxiliary signsplaques, earrying-displaying legends such as ALTERNATE, BY-PASS, BUSINESS, or
- 40 TRUCK, may be used to indicate an alternate route of the same number between two points on that route.
- 41 **Standard:**
- 42 If used, the auxiliary signs-plaques for alternative routes shall be mounted directly above a route 43 sign.
- 44 Section 2D.17 ALTERNATE Auxiliary Signs Plaques (M4-1P, M4-1aP)
- 45 Option:

The ALTERNATE (M4-1<u>P</u>) or the ALT (M4-1a<u>P</u>) auxiliary <u>sign plaque</u> (see Figure <u>2D-42D-6</u>) may be used to indicate an officially designated alternate routing of a numbered route between two points on that route.

Standard:

If used, the ALTERNATE or ALT auxiliary sign plaque shall be mounted directly above a route sign.

The M4-1P Series plaques shall not be used to sign an alternative routing that is not officially designated and incorporated into the numbered highway system, such as alternative routings for incident management or emergency detours.

10 Guidance:

5

6

7

8

9

11

12

13

15

16

17

19

22

23

24

26

27

29

30

31

33

34

36

37

38

39

40

41 42

43

The shorter (time or distance) or better-constructed route should retain the regular route number, and the longer or worse-constructed route should be designated as the alternate route.

Section 2D.18 <u>BY-PASS Auxiliary Sign-Plaque (M4-2P)</u>

14 Option:

The BY-PASS (M4-2<u>P</u>) auxiliary <u>sign-plaque</u> (see Figure <u>2D 42D-6</u>) may be used to designate a route that branches from the numbered route through a city, bypasses a part of the city or congested area, and rejoins the numbered route beyond the city.

18 **Standard:**

If used, the BY-PASS auxiliary sign-plaque shall be mounted directly above a route sign.

20 Section 2D.19 BUSINESS Auxiliary Sign-Plaque (M4-3P)

21 Option:

The BUSINESS (M4-3P) auxiliary sign-plaque (see Figure 2D-42D-6) may be used to designate an alternate route that branches from a numbered route, passes through the business portion of a city, and rejoins the numbered route beyond that area.

25 Standard:

If used, the BUSINESS auxiliary sign-plaque shall be mounted directly above a route sign.

Section 2D.20 TRUCK Auxiliary Sign-Plaque (M4-4P)

28 Option

The TRUCK (M4-4P) auxiliary sign-plaque (see Figure 2D 42D-6) may be used to designate an alternate route that branches from a numbered route, when it is desirable to encourage or require commercial vehicles to use the alternate route.

32 Standard:

If used, the TRUCK auxiliary sign-plaque shall be mounted directly above a route sign.

Section 2D.21 TO Auxiliary Sign Plaque (M4-5P)

35 Option:

The TO (M4-5<u>P</u>) auxiliary <u>sign-plaque</u> (see Figure <u>2D-42D-6</u>) may be used to provide directional guidance to a particular road facility from other highways in the vicinity (see Section 2D.<u>3534</u>).

Standard:

If used, the TO auxiliary sign plaque shall be mounted directly above a route sign or an auxiliary sign-plaque for an alternative route. If a Cardinal Direction auxiliary sign-plaque is also included in the assembly, the TO auxiliary sign-plaque shall be mounted directly above the Cardinal Direction auxiliary sign-plaque.

Section 2D.22 END Auxiliary SignPlaque (M4-6P)

44 Guidance:

The END (M4-6<u>P</u>) auxiliary <u>sign plaque</u> (see Figure <u>2D-42D-6</u>) should be used where the route being traveled ends, usually at a junction with another route.

Standard:

1

2

3

4

6

7 8

9

10

11

12

13

14

15

16

17 18

19

20

21

23

24

2526

27

30

31

33

34

35

36

37

38

39 40

41

42

43

44

If used, the END auxiliary sign plaque shall be mounted either directly above a route sign or above a sign for an alternative route that is part of the designation of the route being terminated.

Section 2D.23 BEGIN Auxiliary Sign Plaque (M4-14P)

5 Option:

The BEGIN (M4-14<u>P</u>) auxiliary sign plaque (see Figure 2D 42D-6) may be used where a route begins, usually at a junction with another route.

Standard:

If used, the BEGIN auxiliary sign-plaque shall be mounted at the top of the first Confirming assembly (see Section 2D.343) for the route that is beginning.

Guidance:

If a BEGIN auxiliary <u>sign-plaque</u> is included in the first Confirming assembly, a Cardinal Direction auxiliary <u>sign-plaque</u> should also be included in the assembly.

Standard:

If a Cardinal Direction auxiliary sign plaque is also included in the assembly, the BEGIN auxiliary sign plaque shall be mounted directly above the Cardinal Direction auxiliary signplaque.

Section 2D.24 <u>TEMPORARY Auxiliary Signs-Plaques (M4-7P, M4-7aP)</u>

Option:

The TEMPORARY (M4-7<u>P</u>) or the TEMP (M4-7a<u>P</u>) auxiliary <u>sign-plaque</u> (see Figure <u>2D-42D-6</u>) may be used for an interim period to designate a section of highway that is not planned as a permanent part of a numbered route, but that connects completed portions of that route.

22 Standard:

If used, the TEMPORARY or TEMP auxiliary sign-plaque shall be mounted directly above the route sign, above a Cardinal Direction signauxiliary plaque, or above an sign-auxiliary plaque for an alternate route that is a part of the route designation.

TEMPORARY or TEMP auxiliary signs plaques shall be promptly removed when the temporary route is abandoned.

28 Section 2D.25 Temporary Detour Signs and Auxiliary Signs Plaques

29 Support:

Chapter 6F contains information regarding Temporary Detour signs and Auxiliary signsplaques.

Section 2D.26 Advance Turn Arrow Auxiliary Signs Plaques (M5-1P, M5-2P, and M5-3P)

32 Standard:

If used, the Advance Turn Arrow auxiliary sign-plaque (see Figure 2D-52D-7) shall be mounted directly below the route sign in Advance Route Turn assemblies, and shall displays a right or left arrow, the shaft of which is bent at a 90-degree angle (M5-1) or at a 45-degree angle (M5-2).

If used, the <u>eurved-stemCircular Intersection</u> Advance Turn Arrow auxiliary (M5-3<u>P</u>) <u>sign-plaque</u> shall be used only on the approach to a circular intersection to depict a movement along the circulatory roadway around the central island and to the left, relative to the approach roadway and entry into the intersection.

Guidance:

If the M5-3<u>P</u> sign-plaque is used, then this arrow type should also be used consistently on any regulatory lane-use signs (see Chapter 2B), Destination signs (see Section 2D.<u>3736</u>), and pavement markings (see Part 3) for a particular destination or movement.

Figure 2D-7. Advance Turn and Directional Arrow Auxiliary Signs

45 Section 2D.27 <u>Lane Designation Auxiliary Signs-Plaques (M5-4P, M5-5P, and-M5-6P)</u>

46 Option:

A Lane Designation (M5-4<u>P</u>, M5-5<u>P</u>, or M5-6<u>P</u>) auxiliary <u>sign-plaque</u> (see Figure <u>2D-52D-7</u>) may be mounted directly below the route sign in an Advance Route Turn assembly on multi-lane roadways to allow road users to move into the appropriate lane prior to reaching the intersection or interchange.

Standard:

If used, the Lane Designation auxiliary signs-plaques shall be used only where the designated lane is a mandatory movement lane and shall be located adjacent to the full-width portion of the mandatory movement lane. The Lane Designation auxiliary signs plaques shall not be installed adjacent to a through lane in advance of a lane that is being added or along the taper for a lane that is being added.

Section 2D.28 <u>Directional Arrow Auxiliary Signs-Plaques (M6 Series)</u>

Standard:

If used, the Directional Arrow auxiliary sign plaque (see Figure 2D-52D-7) shall be mounted below the route sign and any other auxiliary signs plaques in Directional assemblies (see Section 2D.32), and shall displays a single- or double-headed arrow pointing in the general direction that the route follows.

A Directional Arrow auxiliary <u>sign-plaque</u> that displays a double-headed arrow shall not be mounted in any Directional assembly in advance of or at a circular intersection.

Option:

The downward pointing diagonal arrow auxiliary (M6-2aP) sign-plaque may be used in a Directional assembly at the far corner of an intersection to indicate the immediate entry point to a freeway or expressway entrance ramp (see Section 2D.4650).

Standard:

The M6-2a<u>P</u> sign-plaque shall not be used on the approach to or on the near side of an intersection, such as to designate an approach lane.

Section 2D.29 Route Sign Assemblies

Standard:

A Route Sign assembly shall consist of a route sign and auxiliary signs-plaques that further identify the route and indicate the direction. Except as provided in Paragraph 9, Route Sign assemblies shall be installed on all approaches to numbered routes that intersect with other numbered routes.

Where two or more routes follow the same section of highway, the route signs for Interstate, U.S., State, and county routes shall be mounted in that order from the left in horizontal arrangements and from the top in vertical arrangements. Subject to this order of precedence, route signs for lower-numbered routes shall be placed at the left or top.

Within groups of assemblies, information for routes intersecting from the left shall be mounted at the left in horizontal arrangements and at the top or center of vertical arrangements. Similarly, information for routes intersecting from the right shall be at the right or bottom, and for straight-through routes at the center in horizontal arrangements or top in vertical arrangements.

Route Sign assemblies shall be mounted in accordance with the general specifications for signs (Chapter 2A), with the lowest sign in the assembly at the height prescribed for single signs.

Guidance:

Assemblies for two or more routes, or for different directions on the same route, should be mounted in groups on a common support.

Where more than four Route signs would be needed in a single Advance Route Turn or Directional assembly, the Route signs should instead be mounted in a Guide sign to minimize the need for repetition of the same information on multiple Cardinal Direction and Directional Arrow auxiliary plaques (see Figure 2D-8).

Figure 2D-8. Example of Consolidation of Directional Assembly into Direction Guide Sign Option:

Route Sign assemblies may be installed on the approaches to numbered routes on unnumbered roads and streets that carry an appreciable amount of traffic destined for the numbered route.

The diagrammatic route guide sign format, such as the D1-5 and D1-5a signs shown in Figure 2D-82D-12, may be used on approaches to roundabouts circular intersections.

If engineering judgment indicates that groups of assemblies that include overlapping routes or multiple turns might be confusing, route signs or auxiliary signs may be omitted or combined, provided that clear directions are given to road users.

Route Sign assemblies may be omitted for routes that are part of an agency's internal numbering system, such as for maintenance or other purposes, and are not publicly mapped or intended to be used for navigational purposes by the general public.

Support:

Figure 2D-6-2D-9 shows-typical placements of route signs.

Figure 2D-9. Illustration of Directional Assemblies and Other Route Signs (Sheets 1-4)

Section 2D.30 Junction Assembly

39 Standard:

A Junction assembly shall consist of a Junction auxiliary sign-plaque (see Section 2D.13) and a route sign. The route sign shall earry display the number of the intersected or joined route.

The Junction assembly shall be installed in advance of every intersection where a numbered route is intersected or joined by another numbered route.

Guidance:

In urban areas, the Junction assembly should be installed in the block preceding the intersection. In urban areas where speeds are low, the Junction assembly should not be installed more than 300 feet in advance of the intersection.

In rural areas, the Junction assembly should be installed at least 400 feet in advance of the intersection.
 In rural areas, the minimum distance between a Junction assembly and either a Destination sign or an
 Advance Route Turn assembly should be 200 feet.

Where speeds are high, greater spacings should be used.

Option:

Where two or more routes are to be indicated, a single Junction auxiliary <u>sign-plaque</u> may be used for the assembly and all route signs grouped in a single mounting, or a Combination Junction (M2-2) sign (see Section 2D.14) may be used.

Section 2D.31 Advance Route Turn Assembly

10 Standard:

An Advance Route Turn assembly shall consist of a route sign, an Advance Turn Arrow or word message auxiliary signplaque, and a Cardinal Direction auxiliary signplaque, if needed. It shall be installed in advance of an intersection where a turn must be made to remain on the indicated route.

Option:

The Advance Route Turn assembly may be used to supplement the required Junction assembly in advance of intersecting routes.

Guidance:

Where a multiple-lane highway approaches an interchange or intersection with a numbered route, the Advance Route Turn assembly should be used to <u>pre-position provide advance notice so that</u> turning vehicles in the correct lanes from which to make their turn.

Option:

Lane Designation auxiliary signs plaques (see Section 2D.27) may be used in Advance Route Turn Assemblies in place of the Advance Turn Arrow auxiliary signs-plaques where engineering judgment indicates that specific lane information associated with each route is needed and overhead signing is not practical and the designated lane is a mandatory movement lane. An assembly with the Lane Designation auxiliary signs-plaques may supplement or substitute for an assembly with Advance Turn Arrow auxiliary signs-plaques.

Guidance:

In low-speed areas, the Advance Route Turn assembly should be installed not less than 200 feet in advance of the turn. In high-speed areas, the Advance Route Turn assembly should be installed not less than 300 feet in advance of the turn. In rural areas, the minimum distance between an Advance Route Turn assembly and either a Destination sign or a Junction assembly should be 200 feet.

Standard:

An assembly that includes an Advance Turn Arrow auxiliary sign plaque shall not be placed where there is an intersection between it and the designated turn.

Guidance:

Sufficient distance should be allowed between the assembly and any preceding intersection that could be mistaken for the indicated turn.

Section 2D.32 <u>Directional Assembly</u>

Standard:

A Directional assembly shall consist of a Cardinal Direction auxiliary signplaque, if needed; a route sign; and a Directional Arrow auxiliary signplaque. The various uses of Directional assemblies shall be as provided in Items A through D:

- A. Turn movements (indicated in advance by an Advance Route Turn assembly) shall be marked by a Directional assembly with a route sign displaying the number of the turning route and a single-headed arrow pointing in the direction of the turn.
- B. The beginning of a route (indicated in advance by a Junction assembly) shall be marked by a Directional assembly with a route sign displaying the number of that route and a single-headed arrow pointing in the direction of the route.

- C. An intersected route (indicated in advance by a Junction assembly) on a crossroad where the route is designated on both legs shall be designated by:
 - 1. Two Directional assemblies, each with a route sign displaying the number of the intersected route, a Cardinal Direction auxiliary signplaque, and a single-headed arrow pointing in the direction of movement on that route; or
 - 2. A Directional assembly with a route sign displaying the number of the intersected route and a double-headed arrow, pointing at appropriate angles to the left, right, or ahead.
 - D. An intersected route (indicated in advance by a Junction assembly) on a side road or on a crossroad where the route is designated only on one of the legs shall be designated by a Directional assembly with a route sign displaying the number of the intersected route, a Cardinal Direction auxiliary signplaque, and a single-headed arrow pointing in the direction of movement on that route.

Guidance:

Straight-through movements should be indicated by a Directional assembly with a route sign displaying the number of the continuing route and a vertical arrow. A Directional assembly should not be used for a straight-through movement in the absence of other assemblies indicating right or left turns, as the Confirming assembly sign beyond the intersection normally provides adequate guidance.

Directional assemblies should be located on the near right corner of the intersection. At major intersections and at Y or offset intersections, additional Directional assemblies should be installed on the far right or left corner to confirm the near-side assemblies. When the near-corner position is not practical for Directional assemblies, the far right corner should be the preferred alternative, with oversized signs, if necessary, for legibility. Where unusual conditions exist, the location of a Directional assembly should be determined by engineering judgment with the goal being to provide the best possible combination of view and safety.

Support:

It is more important that guide signs be readable, and that the information and direction displayed thereon be readily understood, at the appropriate time and place than to be located with absolute uniformity.

Figure 2D-62D-9 shows typical placements of Directional assemblies.

29 Section 2D.33 Combination Lane-Use/Destination Overhead Guide Sign (D15-1) This section was relocated to new Section 2D.38

31 Section 2D.34 2D.33 Confirming or Reassurance Assemblies

32 Standard:

If used, Confirming or Reassurance assemblies shall consist of a Cardinal Direction auxiliary signplaque and a route sign. Where the Confirming or Reassurance assembly is for an alternative route, the appropriate auxiliary sign-plaque for an alternative route (see Section 2D.16) shall also be included in the assembly.

Guidance:

A Confirming assembly should be installed just beyond intersections of numbered routes. It should be placed 25 to 200 feet beyond the far shoulder or curb line of the intersected highway.

If used, Reassurance assemblies should be installed between intersections in urban areas as needed, and beyond the built-up area of any incorporated city or town.

Route signs for either confirming or reassurance purposes should be spaced at such intervals as necessary to keep road users informed of their routes.

Section 2D.35 2D.34 Trailblazer Assembly

Support:

Trailblazer assemblies provide directional guidance to a particular road facility from other highways in the vicinity. This guidance is accomplished by installing Trailblazer assemblies at strategic locations to indicate the direction to the nearest or most convenient point of access. The use of the word TO indicates that the road

or street where the sign is posted is not a part of the indicated route, and that a road user is merely being directed progressively to the route.

Standard:

A Trailblazer assembly shall consist of a TO auxiliary sign_plaque (M4-5, see Section 2D.21), a route sign for a numbered or named highway (see Section 2D.5356) or an identification sign for a byway, historic trail, or Auto auto Tour_tour Route_route sign (see Section 2H.072D.57 and 2D.58), and a single-headed Directional Arrow auxiliary sign_plaque pointing in the direction leading to the route. Where the Trailblazer assembly is for an alternative route, the appropriate auxiliary sign_plaque for an alternative route (see Section 2D.16) shall also be included in the assembly.

Option:

A Cardinal Direction auxiliary <u>sign-plaque</u> (see <u>Section 2D.15</u>) may be used <u>with-in</u> a Trailblazer assembly <u>where the direction leading to the route provides access only to one direction of travel for that route</u>. *Guidance:*

The TO auxiliary signplaque, Cardinal Direction auxiliary signplaque, and Directional Arrow auxiliary sign-plaque should be of the standard size provided for auxiliary signs-plaques of their respective type. The route sign should be the size provided in Section 2D.11.

Option:

Trailblazer assemblies may be installed with other Route Sign assemblies, or alone, in the immediate vicinity of the designated facilities.

2 Section 2D.36 2D.35 Destination and Distance Signs

3 Support:

In addition to guidance by route numbers, it is desirable to supply the road user information concerning the destinations that can be reached by way of numbered or unnumbered routes. This is done by means of Destination signs and Distance signs.

Option:

Route shields and cardinal directions may be included on the Destination sign with the destinations and arrows.

10 Guidance:

If Route shields and cardinal directions are included on a Destination sign, the height of the Route shields should be at least two times the height of the upper-case letters of the principal legend and not less than 18 inches, and the <u>letter height</u> cardinal directions should be in all upper-case letters that are at least the minimum <u>letter</u> height specified for these signs.

If used, destination names on low-volume rural roads should be as specific and descriptive as possible. Destinations such as campgrounds, ranger stations, and recreational areas, and the like should be clearly indicated so that they are not interpreted to be communities or locations with road user services. Paragraph

relocated from existing Section 5D.01

Section 2D.37 2D.36 <u>Destination Signs (D1 Series)</u>

20 Standard:

Except on approaches to interchanges (see Section 2D.4549), the Destination (D1-1 through D1-3) sign (see Figure 2D-72D-10), if used, shall be a horizontal rectangle displaying the name of a city, town, village, or other traffic generator, and a directional arrow.

Option:

The distance (see Section 2D.4143) to the place named may also be displayed on the Destination (D1-1a through D1-3a) sign (see Figure 2D-710). If several destinations are to be displayed at a single point, the several names may be placed on a single sign with an arrow (and the distance, if desired) for each name. If more than one destination lies in the same direction, a single arrow may be used for such a group of destinations.

Guidance:

Adequate separation should be made between any destinations or group of destinations in one direction and those in other directions by suitable design of the arrow, spacing of lines of legend, heavy lines entirely across the sign, or separate signs.

Figure 2D-10. Destination and Distance Signs

Support:

Separation of destinations by direction by the use of a horizontal separator line can enhance the readability of a Destination sign by relating an arrow and its corresponding destination(s) and by eliminating the need for multiple arrows that point in the same direction and excessive space between lines of legend.

Standard:

Except as otherwise provided in this Manual, an arrow pointing to the right shall be at the extreme right of the sign, and an arrow pointing left or up shall be at the extreme left. The distance numerals, if used, shall be placed to the right of the destination names.

Option:

An arrow pointing up may be placed at the extreme right of the sign when the sign is mounted to the left of the traffic to which it applies.

Guidance:

Unless a sloping arrow will convey a clearer indication of the direction to be followed, the directional arrows should be horizontal or vertical.

1 If several individual name signs are assembled into a group, all signs in the assembly should be of the same horizontal width.

Destination signs should be used:

- A. At the intersections of U.S. or State numbered routes with Interstate, U.S., or State numbered routes; and
- B. At points where they serve to direct traffic from U.S. or State numbered routes to the business section of towns, or to other destinations reached by unnumbered routes.

Standard:

3

4

5 6

7

8

9

10

11 12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

32

33 34

36

37

38

39

Where a total of three or less-fewer destinations are provided-displayed on the Advance Gguide (see Section 2E.35) signs, no more than three destination names shall be used-displayed on a Destination sign. Where four destinations are provided-displayed by on the Advance Gguide and Supplemental Gguide signs, no more than four destination names shall be used-displayed on a Destination sign.

Guidance:

If space permits, four destinations should be displayed <u>on</u> *as two separate signs at two separate locations.* Option:

Where space does not permit, or where all four destinations are in one direction, a single sign may be used. Where a single sign is used and all destinations are in the same direction, the arrow may be placed below the destinations for the purpose of enhancing the conspicuity of the arrow.

Standard:

Where a single four-name sign assembly is used, a heavy line <u>approximating the width of the sign</u> <u>border</u> entirely across the sign or separate signs shall be used to separate destinations by direction.

Guidance:

The closest destination lying straight ahead should be at the top of the sign or assembly, and below it the closest destinations to the left and to the right, in that order. The destination displayed for each direction should ordinarily be the next county seat or the next principal city, rather than a more distant destination. In the case of overlapping routes, only one destination should be displayed in each direction for each route.

Standard:

If more than one destination is displayed in the same direction, the name of a nearer destination shall be displayed above the name of a destination that is **further** away.

31 Support:

Overhead destination guide signs are sometimes helpful on multi-lane conventional roadways with complex or unusual roadway alignments or geometrics at intersecting highways to provide positive direction to destinations and to assign lanes to be used for destinations.

35 Option:

Overhead signs using the Arrow-Per-Lane sign design configuration (See Figure 2E-3) may be used to provide lane assignments for some or all lane destinations at the approach to a multi-lane intersection (See Section 2D.37).

Section 2D.37 Overhead Arrow-Per-Lane Destination Guide Signs

40 <u>Support:</u>

Overhead Arrow-Per-Lane destination guide signs are sometimes used on multi-lane conventional roadways to provide positive direction to destinations and to indicated lanes to be used for those destinations.

These locations typically include complex or unusual roadway alignments or geometrics, such as those found at Diverging Diamond Interchanges. Unlike the Combined Lane-Use/Destination (D15-1) sign Overhead Arrow-Per-Lane signs can be used to provide lane assignments where the designated lane is not a mandatory

46 <u>movement lane.</u>

47 Option:

At complex intersection approaches involving multiple lanes and destinations, an Overhead Arrow-Per-Lane guide sign may be used to provide destination information for some or all of the lanes. Destination information may include cardinal direction, route numbers, street names, and/or place names.

As opposed to the Combination Lane-Use/Destination sign, the Overhead Arrow-Per-Lane signs may be used to provide lane assignments where the designated lane is not a mandatory movement lane.

Guidance:

Destination information should be kept to a minimum necessary to provide positive guidance without overloading the road user.

Option:

Overhead Arrow-Per-Lane signs may be used on conventional roads to indicate lane assignments for turns that do not include an option lane (See Figure 2D-11).

Standard:

The height of the straight arrow on an Overhead Arrow-Per-Lane sign use on a conventional road shall be a minimum of 36 inches.

Guidance:

Arrow heights greater than 36 inches should be use on high speed approaches to provide adequate time for road user enter the proper lane for their destination.

Figure 2D-11. Overhead Arrow-Per-Lane Guide Sign for a Multi-Lane Exit with an Option

Lane

Section <u>2D.332D.38</u> Combination Lane-Use/Destination Overhead Guide Sign (D15-1) This section was relocated from existing Section 2D.33

22 Option:

At complex intersection approaches involving multiple turn lanes and destinations, a Combination Lane-Use/Destination (D15-1) overhead guide sign that combines a lane-use regulatory sign with destination information such as a cardinal direction, a route number, a street name, and/or a place name may be used. Support:

At such locations, the combined information on the D15-1 signs can be even more effective than separate lane-use and guide signs for conveying to unfamiliar drivers which lane or lanes to use for a particular destination.

Figure 2D-7-10 shows an example of a D15-1 sign that combines lane-use and route number information and an example of a D15-1 sign that combines lane-use and street name information. Figure 2A-5 shows an example of the use of the D15-1 sign.

Standard:

The Combination Lane-Use/Destination (D15-1) overhead guide sign shall be used only where the designated lane is a mandatory movement lane. The D15-1 sign shall not be used for lanes with optional movements.

The D15-1 sign shall have a green background with a white border. As shown in Figure 2D-710, the lane-use sign (see Chapter 2B) shall be placed near the bottom of the sign and the destination information shall be placed near the top of the sign. The D15-1 sign shall be located approximately over the approximate center of the lane to which it applies.

- Section 2D.389 <u>Destination Signs at Circular Intersections</u>
- 42 Standard:

Destination signs that are used at circular intersections shall comply with the provisions of Section 2D.376, except as provided in this Section.

45 Option:

Exit destination (D1-1d, D1-1e) signs (see Figure 2D-<u>812</u>) with diagonal upward-pointing arrows or Directional assemblies (see Section 2D.32) may be used to designate a particular exit from a circular intersection.

Exit dDestination (D1-2d, D1-3d) signs (see Figure 2D-812) with curved-stem arrows may be used on approaches to circular intersections to represent the left-turn movements.

Curved-stem arrows on circular intersection destination signs may point in diagonal directions to depict the location of an exit relative to the approach roadway and entry into the intersection.

Exit dDestination (D1-5 or D1-5a) signs (see Figure 2D-812) with a diagram of the circular intersection may be used on approaches to circular intersections.

Figure 2D-12. Destination Signs for Circular Intersections

Guidance:

1

2

3

4

5

6

7

8

9

10

1112

13

14

15

16

17 18

19

20

21

22

23

24

25

2627

28

29

30

31

32

33

34

35

36

37

38

39

41

42

44

45

If curved-stem arrows are used on destination signs, then this arrow type should also be used consistently on any regulatory lane-use signs (see Chapter 2B), Directional assemblies (see Section 2D.32), and pavement markings (see Part 3) for a particular destination or movement.

Support:

Figure 2D-913 illustrates two examples of guide signing for circular intersections.

Diagrammatic guide signs (D1-5 or D1-5a) might be preferable where space is available and where the geometry of the circular intersection is non-typical, such as where more than four legs are present or where the legs are not at approximately 90-degree angles to each other. In such cases, minimizing the amount of legend for each destination and designing the sign so that the arrows for each destination clearly align with the roadway geometry will aid road user understanding of the sign and navigation through the area.

Standard:

If used, diagrammatic guide signs for circular intersections shall not depict the number of lanes within the intersection's circulatory roadway, or on its approaches or exits, through the use of lane lines, multiple arrow shafts for the same movement, or other methods.

Support:

Chapter 2B contains information regarding regulatory signs at circular intersections, Chapter 2C contains information regarding warning signs at circular intersections, and Chapter 3C contains information regarding pavement markings at circular intersections.

Figure 2D-13. Examples of Guide Signs for Roundabouts

Section 2D.3940 <u>Destination Signs at Jughandles</u>

Standard:

Destination signs that are used at jughandles shall comply with the provisions of Section 2D.3736, except as provided in this Section.

Option:

If engineering judgment indicates that standard destination signs alone are insufficient to direct road users to their destinations at a jughandle, a diagrammatic guide sign depicting the appropriate geometry may be used to supplement the normal destination signs.

Support:

Section 2B.27-36 contains information regarding regulatory signs for jughandle turns. Figure 2B-<u>9-5</u> shows examples of regulatory and destination guide signing for various types of jughandle turns.

Section 2D.41 Destination Signs at Intersections with Indirect Turning Movements

40 Guidance:

A system of guides signs along with associated lane markings should be used to direct traffic through intersections with indirect turning movements.

43 Support:

Figures 2D-14 shows examples of destination guide signing for intersections with indirect turning movements.

Figure 2D-14. Example of Signing for Intercepted Crossroad with left Turn Prohibited

46 47

Section 2D.402D.42 Location of Destination Signs

Guidance:

1

2

3

4

5

6

8

9

10

12

13

14

15

16

17

18

19

2021

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

3738

39

40

41

42

43

45

46

47

When used in high-speed areas, Destination signs should be located 200 feet or more in advance of the intersection, and following any Junction or Advance Route Turn assemblies that might be required. In rural areas, the minimum distance between a Destination sign and either an Advance Route Turn assembly or a Junction assembly should be 200 feet.

7 Option:

In urban areas, shorter advance distances may be used.

Because the Destination sign is of lesser importance than the Junction, Advance Route Turn, or Directional assemblies, the Destination sign may be eliminated when sign spacing is critical.

11 Support:

Figure 2D-6-2D-9 shows typical placements of Destination signs.

Section 2D.412D.43 Distance Signs (D2 Series)

Standard:

If used, the Distance (D2-1 through D2-3) sign (see Figure 2D-72D-10) shall be a horizontal rectangle of a size appropriate for the required legend, earrying displaying the names of no more than three cities, towns, junctions, or other traffic generators, and the distance (to the nearest mile) to those places.

The distance numerals shall be placed to the right of the destination names as shown in Figure 2D-72D-10.

Guidance:

The distance displayed should be selected on a case-by-case basis by the jurisdiction that owns the road or by statewide policy. A well-defined central area or central business district should be used where one exists. In other cases, the layout of the community should be considered in relation to the highway being signed and the decision based on where it appears that most drivers would feel that they are in the center of the community in question.

The top name on the Distance sign should be that of the next place on the route having a post office or a railroad station, a route number or name of an intersected highway, or any other significant geographical identity. The bottom name on the sign should be that of the next major destination or control city. If three destinations are displayed, the middle line should be used to indicate communities of general interest along the route or important route junctions.

Option:

The choice of names for the middle line may be varied on successive Distance signs to give road users additional information concerning communities served by the route.

Guidance:

The control city should remain the same on all successive Distance signs throughout the length of the route until that city is reached.

Option:

If more than one distant point may properly be designated, such as where the route divides at some distance ahead to serve two destinations of similar importance, and if these two destinations cannot appear on the same sign, the two names may be alternated on successive signs.

On a route continuing into another State, destinations in the adjacent State may be displayed.

Section 2D.422D.44 Location of Distance Signs

44 Guidance:

If used, Distance signs should be installed on important routes leaving municipalities and just beyond intersections of numbered routes in rural areas. If used, they should be placed just outside the municipal limits or at the edge of the built-up area if it extends beyond the limits.

Where overlapping routes separate a short distance from the municipal limits, the Distance sign at the municipal limits should be omitted. The Distance sign should be installed approximately 300 feet beyond the separation of the two routes.

Where, just outside of an incorporated municipality, two routes are concurrent and continue concurrently to the next incorporated municipality, the top name on the Distance sign should be that of the place where the routes separate; the bottom name should be that of the city to which the greater part of the through traffic is destined.

Support:

1

2

4

5

6

7

8

9

10

Figure 2D-62D-9 shows typical placements of Distance signs.

Notice of Proposed Amendments – Part 2

5

6

7

8

10

11

12 13

14

15

16

17

18 19

20

21

22

23

24

25

26

27

28

29

30

31

32

33 34

35

36

37

38

39

40

41 42

43 44

45

46

47

48

49

2 Section 2D.432D.45 Street Name Signs (D3-1, or D3-1a)

3 Guidance:

Street Name (D3-1 or D3-1a) signs (see Figure 2D-102D-15) should be installed in urban areas at all street intersections regardless of other route signs that might be present and should be installed in rural areas to identify important roads that are not otherwise signed.

To minimize wrong-way movements onto freeway or expressway exit ramps, Street Name signs should not be used at the intersection of a freeway or expressway exit ramp with the crossroad to display the name of the freeway or expressway to traffic on the crossroad.

Option:

For streets that are part of a U.S., State, or county numbered route, a D3-1a Street Name sign (see Figure 2D-102D-15) that incorporates a route shield may be used to assist road users who might not otherwise be able to associate the name of the street with the route number.

Figure 2D-15. Street Name and Parking Signs

Standard:

The lettering for names of streets and highways on Street Name signs shall be composed of a combination of lower-case letters with initial upper-case letters (see Section 2A.13).

Guidance

The determination of letter heights to be used on Street Name signs should be based on, but not limited to the following considerations:

- A. Use of Advance Street Name signs (see Section 2D.46);
- B. Number of lanes on the intersection approach;
- C. Length of turn lanes;
- D. Distance the Street Name sign is located across the intersection (if a sign is not provided on the near side of the intersection).

Lettering on post-mounted Street Name signs should be composed of initial upper-case letters at least 6 inches in height and lower-case letters at least 4.5 inches in height.

On multi-lane streets with speed limits greater than 40 mph, the lettering on post-mounted Street Name signs should be composed of initial upper-case letters at least 8 inches in height and lower-case letters at least 6 inches in height.

Option:

For <u>two-lane</u> local road<u>way</u>s with speed limits of 25 mph or less, the lettering on post-mounted Street Name signs may be composed of initial upper-case letters at least 4 inches in height and lower-case letters at least 3 inches in height.

Guidance:

If overhead Street Name signs are used, the lettering should be composed of initial upper-case letters at least 12 inches in height and lower-case letters at least 9 inches in height.

Support:

The recommended minimum letter heights for Street Name signs are summarized in Table 2D-25. The speed limits specified and the recommended minimum letter heights provided in this Section apply to the roadway that each Street Name sign faces rather than to the street that has its name displayed on the Street Name sign.

Table 2D-5. Minimum Letter Heights for Street Name Signs

Option:

Each Street Name sign in a sign assembly may use different letter heights determined by the speed limit of the street that each sign faces.

<u>The letter height of the street name descriptor Supplementary lettering to indicate the type of street</u> (such as Street, Avenue, or Road), or the section of the city <u>directional legend</u> (such as NW) or any other supplemental legend such as block or house numbers (see Paragraph 15) on the D3-1 and D3-1a signs may be

supplemental legend such as block of house numbers (see Faragraph 15) on the D3-1 and D3-1a signs may be

in smaller lettering, than that of the street name itself. composed of initial upper-case letters at least 3 inches in height and lower case letters at least 2.25 inches in height. Conventional abbreviations (see Section 1A.15) may be used except for the street name itself. Remainder of first sentence and second sentence changed to Guidance below

Guidance:

The letter height of the street name descriptor, the directional legend, or any other supplemental legend on the D3-1 and D3-1a signs should be at least two-thirds of the letter height of the street name itself, but not less than 3 inches for the initial upper-case letters and not less than 2.25 inches for the lower-case letters.

Conventional abbreviations (see Section 1A.15) <u>may should</u> be used except for the street name itself. <u>Acceptable abbreviations for street name descriptors such as "Ave" for Avenue and "Blvd" for Boulevard should be as provided in Table 2D-3 (see Section 2D.07). Table 2D-4 provides street name descriptors that <u>should not be abbreviated (see Section 2D.07).</u></u>

Option:

Block or house numbers may be displayed as a supplemental legend on a Street Name sign to aid emergency responders and road users in locating addresses.

Guidance:

If block or house numbers are displayed on a Street Name sign where only a single Street Name sign is provided for the cross street, the block or house numbers for the left and right blocks should be positioned at the left and right sides of the sign, respectively.

If block or house numbers are displayed on a Street Name sign where two Street Name signs are provided for the cross street, such as on diagonally opposite corners of an intersection, each Street Name sign should display only the block or house numbers associated with that block of the cross street.

Option:

A pictograph (see definition in Section 1A.13) representing the municipality may be used on a D3-1 sign.

25 Standard:

Pictographs shall not be displayed on D3-1a or Advance Street Name (D3-2) signs (see Section 2D.4446).

If a pictograph is used on a D3-1 sign, the height and width of the pictograph shall not exceed the upper-case letter height of the principal legend of the sign.

Guidance:

The pictograph should be positioned to the left of the street name.

32 Standard:

The Street Name sign shall be retroreflective or illuminated in accordance with the provisions of Section 2A.07 to show the same shape and similar color both day and night. The color of the legend (and border, if used) shall contrast with the background color of the sign.

Option:

The border may be omitted from a post-mounted Street Name sign.

Guidance:

The decision to omit the border from a post-mounted Street Name sign should be based on such factors as the visual complexity of the environment and the degree of conspicuity needed to provide for adequate recognition of the sign by the road user.

Option:

An alternative background color (see Paragraph 27) other than the normal standard guide sign color of green may be used for Street Name (D3-1 or D3-1a) signs where the highway agency determines this is necessary to assist road users in determining jurisdictional authority for roads.

Standard:

Alternative background colors shall not be used for Advance Street Name (D3-2) signs (see Section 2D.4446).

The only acceptable alternative background colors for Street Name (D3-1 or D3-1a) signs shall be blue, brown, or white. Regardless of whether green, blue, or brown is used as the background color for

Street Name (D3-1 or D3-1a) signs, the legend (and border, if used) shall be white. For Street Name signs that use a white background, the legend (and border, if used) shall be black.

Guidance:

1

2

3

4

5

6

7

8

9

10

11 12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

28

29

30

31

33

34

35

36

37 38

39

40

41

42

43

44

46

47

An alternative background color for Street Name signs, if used, should be applied to the Street Name (D3-1 or D3-1a) signs on all roadways under the jurisdiction of a particular highway agency.

In business or commercial areas and on principal arterials, Street Name signs should be placed at least on diagonally opposite corners. In residential areas, at least one Street Name sign should be mounted at each intersection. Signs naming both streets should be installed at each intersection. They should be mounted with their faces parallel to the streets they name.

Where used, especially in urban areas, Street Name signs should display their legends on both sides of the sign to facilitate navigation for pedestrians.

Option:

To optimize visibility, Street Name signs may be mounted overhead. Street Name signs may also be placed above a regulatory or STOP or YIELD sign with no required vertical separation.

Guidance:

In urban or suburban areas, especially where Advance Street Name signs for signalized and other major intersections are not used, the use of overhead Street Name signs should be strongly considered.

Option:

At intersection crossroads where the same road has two different street names for each direction of travel, both street names may be displayed on the same sign along with directional arrows, except where the arrow would point in a direction opposing the flow of traffic on a one-way street or where a turn in the direction of the arrow is not allowed.

On lower speed roadways, historic street name signs within locally identified historic districts that are consistent with the criteria contained in 36 CFR 60.4 for such structures and districts may be used remain in service without complying with the provisions of Paragraphs 3, 4, 6, 9, 12 through 14, and 18 through 20 of this section.

27 **Guidance:**

> <u>Streets or segments of a street that have been memorialized or dedicated should not use a second Street</u> Name sign to display the memorial or dedication name (see Section 2D.56). When signed, the Memorial or Dedication sign should be located to minimize its conspicuity to and potential for confusion by vehicular traffic.

32 Support:

> Information regarding the use of street names on supplemental plaques for use with intersection-related warning signs is contained in Section 2C.58.

Information regarding the identification of overcrossing and undercrossing roadways at grade separations is contained in Section 2H.10.

Section 2D.442D.46 Advance Street Name Signs (D3-2 Series)

Support:

Advance Street Name (D3-2) signs (see Figure 2D-102D-16) identify an upcoming a downstream intersection. Although this is often the next intersection, it could also be several intersections away in cases where the next signalized intersection is referenced.

Standard:

Advance Street Name (D3-2) signs, if used, shall supplement rather than be used instead of the Street Name (D3-1) signs at the intersection.

45 Option:

> Advance Street Name (D3-2) signs may be installed in advance of signalized or unsignalized intersections to provide road users with advance information to identify the name(s) of the next intersecting street to prepare for crossing traffic and to facilitate timely deceleration and/or lane changing in preparation for a turn.

48

49 Guidance:

On arterial highways in rural areas, Advance Street Name signs should be used in advance of all signalized intersections and in advance of all intersections with exclusive turn lanes.

In urban areas, Advance Street Name signs should be used in advance of all signalized intersections on major arterial streets, except where signalized intersections are so closely spaced that advance placement of the signs is impractical.

The heights of the letters on Advance Street Name signs should be the same as those used for Street Name signs (see Section 2D.43) comply with the provisions of Section 2D.05.

Standard:

1

2

3

4

5

6

7

8

9

10

11 12

13 14

15

16

17

18

19

20

21

22 23

24

25

26 27

28

29

30

31

32

33

34

35

36

37

38

39

If used, Advance Street Name signs shall have a white legend and border on a green background. Alternative background colors shall not be used on Advance Street Name signs.

If used, Advance Street Name signs shall provide the name(s) of the intersecting street(s) on the top line(s) of the legend and the distance to the intersecting streets or messages such as NEXT SIGNAL, NEXT INTERSECTION, NEXT ROUNDABOUT, or directional arrow(s) on the bottom line of the legend.

Pictographs shall not be displayed on Advance Street Name signs.

Option:

Directional arrow(s) may be placed to the right or left of the street name or message such as NEXT SIGNAL, as appropriate, rather than on the bottom line of the legend. Curved-stem arrows may be used on Advance Street Name signs on approaches to circular intersections.

For intersecting crossroads where the same road has a different street name for each direction of travel, the different street names may be displayed on the same Advance Street Name sign along with directional

In advance of two closely-spaced intersections where it is not practical to install separate Advance Street Name signs, the Advance Street Name sign may include the street names for both intersections along with appropriate supplemental legends for both street names, such as NEXT INTERSECTION, 2ND INTERSECTION, or NEXT LEFT and NEXT RIGHT, or directional arrows.

Guidance:

If two street names are used on the Advance Street Name sign, the street names should be displayed in the *following order:*

- A. For a single intersection where the same road has a different street name for each direction of travel, the name of the street to the left should be displayed above the name of the street to the right; or
- B. For two closely-spaced intersections, the name of the first street encountered should be displayed above the name of the second street encountered, and the arrow associated with the second street encountered should be an advance arrow, such as the arrow shown on the W16-6P arrow plaque (see *Figure 2C-12*).

Option:

An Advance Street Name (W16-8P or W16-8aP) plaque (see Section 2C.5864) with black legend on a yellow background, installed supplemental to supplement an Intersection (W2 series) or Advance Traffic Control (W3 series) warning sign may be used instead of an Advance Street Name guide sign.

40 Section 2D.45 Signing on Conventional Roads on Approaches to Interchanges This section was 41

relocated to new Section 2D.49

42 Section 2D.46 Freeway Entrance Signs (D13-3 and D13-3a) This section was relocated to new Section 2D.50 43

- 44 Section 2D.47 Parking Area Guide Sign (D4-1)
- 45 Option:

46 The Parking Area (D4-1) guide sign (see Figure 2D-102D-15) may be used to show the direction to a nearby public parking area or parking facility. 47

48 **Standard:** If used, the Parking Area (D4-1) guide sign shall be a horizontal rectangle with a standard size of 30 x 24 inches, or with a The smaller size of 18 x 15 inches for the Parking Area guide sign shall be limited to minor, low-speed streets. —It shall carry the word PARKING, with the letter P five times the height of the remaining letters, and a directional arrow. The legend and border shall be green on a retroreflectorized white background.

Guidance:

1

2

3

4

5

6

7

8

9

10

14

15

16

19

20

21

22

23

24

25

26 27

28 29

30

31

32

33

34

35

36

If used, the Parking Area guide sign should be installed on major thoroughfares at the nearest point of access to the parking facility and where it can advise drivers of a place to park. The sign should not be used more than four blocks from the parking area.

Section 2D.48 PARK - RIDE Sign (D4-2)

11 Option:

PARK - RIDE (D4-2) signs (see Figure 2D-102D-15) may be used to direct road users to park - ride facilities.

Standard:

The signs shall <u>contain display</u> the word message PARK - RIDE and direction information (arrow or word message).

17 Option:

PARK - RIDE signs may contain_display_the local transit pictograph and/or carpool symbol_on the sign.

Standard:

If used, the local transit pictograph and/or carpool symbol shall be located in the top part of the sign above the message PARK - RIDE. In no case shall the vertical dimension of the local transit pictograph and/or carpool symbol exceed 18 inches.

Guidance:

If the function of the parking facility is to provide parking for persons using public transportation, the local transit pictograph should be used on the guide sign. If the function of the parking facility is to serve carpool riders, the carpool symbol should be used on the guide sign. If the parking facility serves both functions, both the pictograph and carpool symbol should be used.

Standard:

These signs shall have a retroreflective white legend and border on a rectangular green background. The carpool symbol shall be as shown for the D4-2 sign. The color of the local transit pictograph shall be selected by the local transit authority.

Option:

To increase the target value and contrast of the local transit pictograph, and to allow the local transit pictograph to retain its distinctive color and shape, the pictograph may be included within a white border or placed on a white background.

11

12

13

14

15

16

17

18

19

20

2122

24

2526

27

28

29

30

31

32

33

34

36

37

38

39

40

41 42

43

45

47

48

- 2 Section 2D.45 2D.49 Signing on Conventional Roads on Approaches to Interchanges This
- 3 section was relocated from existing Section 2D.45
- 4 Support:
- 5 Because there are a number of different ramp configurations that are commonly used at interchanges with
- 6 conventional roads, drivers on the conventional road cannot reliably predict whether they will be required to
- turn left or right in order to enter the correct ramp to access the freeway or expressway in the desired direction
- 8 of travel. Consistently applied signing for conventional road approaches to freeway or expressway
- 9 interchanges is highly desirable.

10 Standard:

On multi-lane conventional roads approaching an interchange, guide signs shall be provided to identify which direction of turn is to be made and/or which specific lane to use for ramp access to each direction of the freeway or expressway.

Guidance:

The signing of conventional roads with one lane of traffic approaching an interchange should consist of a sequence containing the following signs (see Figure $\frac{2D-11}{2D-16}$):

- A. Junction Assembly
- B. Destination sign
- C. Directional Assembly or Entrance Direction sign for the first ramp
- D. Advance Route Turn Assembly or Advance Entrance Direction sign with an advance turn arrow
- E. Directional Assembly or Entrance Direction sign for the second ramp

Figure 2D-16. Example of Interchange Crossroad Signing for a One-Lane Approach

23 Standard:

If used, the Entrance Direction sign shall consist of a white legend and border on a green background. It shall contain the freeway or expressway route shield(s), cardinal direction, and directional arrow(s).

Option:

The Entrance Direction sign may contain a destination(s) and/or an action message such as NEXT RIGHT.

At minor interchanges, the following sequence of signs may be used (see Figure 2D-122D-17):

- A. Junction Assembly
- B. Directional Assembly for the first ramp
- C. Directional Assembly for the second ramp

Figure 2D-17. Example of Minor Interchange Crossroad Signing

35 Guidance:

On multi-lane conventional roads approaching an interchange, the sign sequence should contain the following signs (see Figures $\frac{2D-13}{2D-18}$ through $\frac{2D-15}{2D-20}$):

- A. Junction Assembly
- B. Advance Entrance Direction sign(s) for both directions (if applicable) of travel on the freeway or expressway
- C. Entrance Direction sign for first ramp
- D. Advance Turn Assembly
- E. Entrance Direction sign for the second ramp

44 Support:

Advance Entrance Direction signs are used to direct road users to the appropriate lane(s).

46 Standard:

The Advance Entrance Direction sign shall consist of a white legend and border on a green background. It shall contain the freeway or expressway route shield(s) and cardinal direction(s).

49 Option:

The Advance Entrance Direction sign may have destinations, directional arrows, and/or an action message such as KEEP LEFT, NEXT LEFT, or SECOND RIGHT. Signs in this sequence may be mounted overhead to improve visibility as shown in Figures 2D-13-2D-18 through 2D-152D-20.

Support:

A post-mounted Advance Entrance Direction diagrammatic guide sign (see Figure 2D-162D-21), within the sequence of approach guide signing described in Paragraphs 3, 6, and 7, might be helpful in depicting the location of a freeway or expressway entrance ramp that is in close proximity to an intervening intersection on the same side of the approach roadway and where signing for only the ramp might cause confusion to road users.

Figure 2D-18. Examples of Multi-Lane Crossroad Signing for a Diamond Interchange Figure 2D-19. Examples of Multi-Lane Crossroad Signing for a Partial Cloverleaf Interchange Figure 2D-20. Examples of Multi-Lane Crossroad Signing for a Cloverleaf Interchange Figure 2D-21. Example of Crossroad Signing for an Exit Ramp with a Nearby Frontage Road Standard:

If used, the post-mounted Advance Entrance Direction diagrammatic guide sign shall display only the two successive turns from the same side of the roadway, one of which shall be the entrance ramp. The post-mounted Advance Entrance Direction sign shall depict only the successive turns and shall not depict lane use with lane lines, multiple arrow shafts for the approach roadway, action messages, or other representations.

Support:

Examples of guide signing for single-point urban intersection and transposed-alignment crossroads for a diamond interchange are shown in Figures 2D-22 and 2D-23.

Section 2D.46-50 contains information regarding the use of a Directional assembly or a FREEWAY ENTRANCE sign to mark the entrance to a freeway or expressway at the far corner of an intersection.

Figure 2D-22. Guide Signs for Transposed-Alignment Crossroads at a Diamond Interchange
Figure 2D-23. Example of Crossroad Signing for a Transposed-Alignment Diamond
Interchange

Section <u>2D.46–2D.50</u> <u>Freeway Entrance Signs (D13-3, and D13-3a)</u> This section was relocated from existing Section 2D.46

30 Option:

FREEWAY ENTRANCE (D13-3) signs or FREEWAY ENTRANCE with downward pointing diagonal arrow (D13-3a) signs (see Figure 2D-142D-19) may be used on entrance ramps near the crossroad to inform road users of the freeway or expressway entrance, as appropriate.

The D13-3 and D13-3a signs may display an alternate legend in place of FREEWAY, such as EXPRESSWAY or PARKWAY, as appropriate, or may display the name of an unnumbered highway.

A Directional assembly (see Section 2D.32) with a downward pointing diagonal arrow auxiliary (M6-2a) sign-plaque (see Section 2D.28) may be used at the far left-hand corner of an intersection with a freeway or expressway entrance ramp as an alternative to the D13-3a sign, facing left-turning traffic on the conventional road approach to indicate the immediate point of entry to the freeway or expressway and distinguish the entrance ramp from an adjoining exit ramp terminal at the same intersection with the conventional road (see Figure 2D-142D-19). A similar Directional assembly may be used at the far right-hand corner of an intersection with a freeway or expressway entrance ramp where the entrance ramp and a crossroad or side road follow one another in close succession on the conventional road approach and the point of entry to the freeway or expressway might be difficult for the road user to distinguish from the crossroad or side road on the conventional road approach (see Figure 2D-142D-19).

46 Support:

Section 2B.41 contains information regarding the use of regulatory signs to deter wrong-way movements at intersections of freeway or expressway ramps with conventional roads, and in the area where entrance ramps intersect with the mainline lanes.

1 WEIGH STATION, TRUCK LANE, PASSING LANE, CROSSOVER AND EMERGENCY 2 AND SLOW VEHICLE TURN-OUT SIGNS 3 Section 2D.492D.51 Weigh Station WEIGH STATION Signing (D8 Series) 4 Support: 5 Independent facilities or areas have been added along many highways where certain commercial vehicles are directed to stop to be weighed or inspected. These areas are sometimes permanent, such as in a roadside 6 area, or temporary mobile facilities deployed along the roadway. 7 8 The general concept for signing permanent Weigh Station signing is similar to Rest Area signing (see 9 Section 2I.05) because in both cases traffic using either area remains within the right-of-way. 10 Standard: The standard installation sequence of signsing for a Weigh Station signing on a conventional 11 highway shall include three basic signs (see Figure 2D-24): 12 A. Advance Weigh Station Distance sign-(D8-1) sign, 13 14 B. Exit Direction sign Weigh Station Next Right (D8-2) sign, and C. Exit Gore signWeigh Station Exit Directional (D8-3) sign. 15 16 Guidance: 17 An Exit Gore sign with the same basic legend as the Weigh Station Exit Direction (D8-3) sign should also 18 be used to emphasize the entrance to the weigh station. 19 Support: 20 Example locations of these signs are shown in Figure 2D-17. 21 Figure 2D-24. Example of WEIGH STATION Signing 22 Option: 23 Where State law requires trucks of a certain weight to entera regulatory sign (R13-1) in advance of the 24 Weigh Station, a Weigh Station (R13-1) regulatory sign, a fourth sign (see Section 2B.60) may be located 25 following the Advance Weigh Station Distance sign (see Figure 2D-24). Edited to improve consistency 26 Where only commercial vehicle inspections are conducted in the inspection area, the WEIGH STATION 27 legend of the D8 series signs may be replaced with the alternate legend, COMMERCIAL VEHICLE **INSPECTION AREA.** Added to improve consistency 28 29 Guidance: 30 The Weigh Station Next Right Exit Direction sign (D8-2) Sign or the Advance Weigh Station Distance sign 31 (D8-1) sign should display, either within the sign border or on a supplemental plaque or sign panel, the 32 changeable message legend OPEN or CLOSED. 33 **Standard:** 34 When the WEIGH STATION legend of the D8 series signs is replaced with the COMMERCIAL VEHICLE INSPECTION AREA legend, as provided in Paragraph 6 of this Section, the WEIGH 35 STATION legend of the R13-1 sign shall be replaced with the alternate legend INSPECTION AREA. 36 Section 2D.50 Community Wayfinding Signs This section relocated to new Section 2D.55 37 38 Section 2D.54-52 Crossover Signs (D13-1, and D13-2) 39 Option: 40 Crossover signs may be installed on divided highways to identify median openings not otherwise 41 identified by warning or other guide signs. 42 **Standard:** 43 A CROSSOVER (D13-1) sign (see Figure 2D-212D-25) shall not be used to identify a median opening that is permitted to be used only by official or authorized vehicles. If used, the sign shall be a 44 horizontal rectangle of appropriate size to carry the word CROSSOVER and a horizontal directional 45 arrow. The CROSSOVER sign shall have a white legend and border on a green background. Text

46 47

48

Guidance:

deleted because it is covered in Standard Highway Signs publication

1 If used, the CROSSOVER sign should be installed immediately beyond the median opening, either on the 2 right-hand side of the roadway or in the median. 3 Option: 4 The Advance Crossover (D13-2) sign (see Figure 2D-212D-25) may be installed in advance of the 5 CROSSOVER sign to provide advance notice of the crossover. 6 **Standard:** 7 If used, the Advance Crossover sign shall be a horizontal rectangle of appropriate size to carry the 8 word CROSSOVER and the distance to the median opening. The sign shall have white legend and border on a green background. Text deleted because it is covered in Standard Highway Signs 9 10 publication 11 Guidance: 12 The distance displayed on the Advance Crossover sign should be 1 MILE, 1/2 MILE, or 1/4 MILE, unless 13 unusual conditions require some other distance. If used, the sign should be installed either on the right-hand 14 side of the roadway or in the median at approximately the distance displayed on the sign. 15 Figure 2D-25. Crossover Signs (D13-1, D13-2) 16 Section 2D.513 Truck and or, Passing, or Climbing Lane Signs (D17-1, and D17-2, D17-3, D17-17 <u>4)</u> 18 Guidance: 19 If an extra lane has been provided to the right-hand side of the travel lane for use by trucks and other 20 slow-moving traffic, a NEXT-TRUCK LANE XX1/2 MILES (D17-12) sign and/or a TRUCK LANE XX MILES 21 (D17-2) sign (see Figure 2D-2126) should be installed in advance of the lane. 22 If a series of truck lanes are provided along a highway, a NEXT TRUCK LANE XX MILES (D17-1) sign 23 (see Figure 2D-26) should be installed after each truck lane segment. 24 If an extra lane has been provided to the left-hand side of the travel lane for passing slower moving 25 vehicles in the travel lane, a PASSING LANE 1/2 MILE (D17-4) sign (see Figure 2D-26) should be installed in 26 advance of the lane. 27 If a series of passing lanes are provided along a highway, a NEXT PASSING LANE XX MILES (D17-3) 28 sign (See Figure 2D-26) should be installed after each passing lane segment. 29 Option: 30 Alternative legends such as PASSING LANE or CLIMBING LANE may be used instead of TRUCK-31 LANE. 32 Support: 33 An example of singing for a truck lane is shown in Figure 2D-27. An example of signing for an 34 intermittent passing lane is shown in Figure 2D-28. 35 Section 2B.31 contains information regarding regulatory signs for these types of lanes. 36 New Figure 2D-26. Truck and Passing Lane Signs (D17-1 through D17-4) 37 New Figure 2D-27. Example of Signing for a Truck Lane New Figure 2D-28. Example of Signing for an Intermittent Passing Lane 38 39 Section 2D.524 Emergency and Slow Vehicle Turn-Out Signs (D17-5 through D17-7) 40 Guidance: If an emergency turn-out area has been provided where a shoulder is not available for emergency 41 42 stopping, Emergency Turn-Out signs should be installed. The Emergency Turn-Out advance (D17-5) sign (see Figure 2D-29) should be installed between 1/4 mile and 500 feet in advance of the turn-out area. The 43 Emergency Turn-Out directional (D17-6) sign should be installed near the beginning of the turn-out area. 44 45 If a slow vehicle turn-out area has been provided for slow-moving traffic, a SLOW VEHICLE TURN-OUT 46 XX MILES (D17-7) sign (see Figure 2D-212D-29) should be installed in advance of the turn-out area. 47 OptionSupport: 48 An example of signing for an emergency turn-out is shown in Figure 2D-30.

1	Section 2B.35 contains information regarding regulatory signs for slow vehicle turn-out areas.
2	New Figure 2D-29. Emergency and Slow Vehicle Turn-Out Signs (D17-5 through D17-7)
3	New Figure 2D-30. Example of Emergency Turn-Out Signing
4	Section 2D.53 Signing of Named Highways This section relocated to new Section 2D.56
5 6	Section 2D.54 <u>Crossover Signs (D13-1 and D13-2)</u> This section revised and relocated to new Section 2D.52
7 8	Section 2D.55 National Scenic Byways Signs (D6-4, D6-4a) This section was relocated to new Section 2D.57
Λ	

Section 2D.50 2D.55 Community Wayfinding Signs

Support:

Community wayfinding guide signs are part of a coordinated and continuous system of signs that direct tourists and other road users to key civic, cultural, visitor, and recreational attractions and other <u>similar</u> <u>secondary</u> destinations within a city or a local urbanized or downtown area.

Community wayfinding guide signs are a type of destination guide sign for conventional roads with a common color and/or identification enhancement marker for destinations within an overall wayfinding guide sign plan for an area.

Figures 2D-18-31 through 2D-20-33 illustrate various examples of the design and application of community wayfinding guide signs.

Standard:

The use of community wayfinding guide signs shall be limited to conventional roads. Community wayfinding guide signs shall not be installed on freeway or expressway mainlines or ramps. Direction to community wayfinding destinations from a freeway or expressway shall be limited to the use of a Supplemental Guide sign (see Section 2E.35) on the mainline and a Destination sign (see Section 2D.3736) on the ramp to direct road users to the area or areas within which community wayfinding guide signs are used. The individual wayfinding destinations shall not be displayed on the Supplemental Guide and Destination signs except where the destinations are in accordance with the State or agency policy on Supplemental Guide signs.

Community wayfinding guide signs shall not be used to provide direction to primary destinations or highway routes or streets. Destination or other guide signs shall be used for this purpose as described elsewhere in this Chapter and shall have priority over any community wayfinding sign in placement, prominence, and conspicuity.

Because regulatory, warning, and other guide signs have a higher priority, community wayfinding guide signs shall not be installed where adequate spacing cannot be provided between the community wayfinding guide sign and other higher priority signs. Community wayfinding guide signs shall not be installed in a position where they would obscure the road users' view of other traffic control devices.

Community wayfinding guide signs shall not be mounted overhead.

Guidance:

If used, a community wayfinding guide sign system should be established on a local municipal or equivalent jurisdictional level or for an urbanized area of adjoining municipalities or equivalent that form an identifiable geographic entity that is conducive to a cohesive and continuous system of signs. Community wayfinding guide signs should not be used on a regional or statewide basis where infrequent or sparse placement does not contribute to a continuous or coordinated system of signing that is readily identifiable as such to the road user. In such cases, Destination or other guide signs detailed in this Chapter should be used to direct road users to an identifiable area in which the type of eligible destination described in Paragraph 1 is located.

When a system of community wayfinding guide signs is being considered, the entire system of existing signs should be evaluated for serviceability and general conformance with the provisions of this Manual. Systematic upgrading (see Paragraphs 22 through 24 of the Introduction to this Manual) of higher priority signs, such as regulatory, warning, and major Destination guide signs, should occur prior to the installation of the community wayfinding signs.

Figure 2D-31. Example of Community Wayfinding Guide Signs

Figure 2D-32. Example of a Community Wayfinding Guide Sign System Showing Direction from a Freeway or Expressway

Figure 2D-33. Example of a Color-Coded Community Wayfinding Guide Sign System

48 Support:

The specific provisions of this Section regarding the design of community wayfinding sign legends apply to vehicular community wayfinding signs and do not apply to those signs that are intended only to provide information or direction to pedestrians or other users of a sidewalk or roadside area.

Guidance:

Because pedestrian wayfinding signs typically use smaller legends that are inadequately sized for viewing by vehicular traffic and because they can provide direction to pedestrians that might conflict with that appropriate for vehicular traffic, wayfinding signs designed for and intended to provide direction to pedestrians or other users of a sidewalk or other roadside area should be located to minimize their conspicuity to vehicular traffic. Such signs should be located as far as practical from the street, such as at the far edge of the sidewalk. Where locating such signs farther from the roadway is not practical, the pedestrian wayfinding signs should have their conspicuity to vehicular traffic minimized by employing one or a combination of the following methods:

- A. Locating signs away from intersections where high-priority traffic control devices are present.
- B. Facing the pedestrian message toward the sidewalk and away from the street.
- C. Cantilevering the sign over the sidewalk if the pedestrian wayfinding sign is mounted at a height consistent with vehicular traffic signs, removing the pedestrian wayfinding signs from the line of sight in a sequence of vehicular signs.

To further minimize their conspicuity to vehicular traffic during nighttime conditions, pedestrian wayfinding signs should not be retroreflective.

Support:

Color coding is sometimes used on community wayfinding guide signs to help road users distinguish between multiple potentially confusing traffic generator destinations located in different neighborhoods or subareas within a community or area.

Option:

At the boundaries of the geographical area within which community wayfinding guide signing is used, an informational guide sign (see Figures 2D-18-31 and 2D-203133) may be posted to inform road users about the presence of wayfinding signing and to identify the meanings of the various color codes or pictographs that are being used.

Standard:

These informational guide signs shall have a white legend and border on a green background and shall have a design similar to that illustrated in Figures 2D-12 and 2D-18-31 and shall be consistent with the basic design principles for guide signs. These informational guide signs shall not be installed on freeway or expressway mainlines or ramps.

The color coding or a pictograph of the identification enhancement markers of the community wayfinding guide signing system shall be included on the informational guide sign posted at the boundary of the community wayfinding guide signing area. The color coding or pictographs shall apply to a specific, identifiable neighborhood or geographical subarea within the overall area covered by the community wayfinding guide signing. Color coding or pictographs shall not be used to distinguish between different types of destinations that are within the same designated neighborhood or subarea. The color coding shall be accomplished by the use of different colored square or rectangular panels on the face of the informational guide sign, each positioned to the left of the neighborhood or named geographic area to which the color-coding panel applies. The height of the colored square or rectangular panels shall not exceed two times the height of the upper-case letters of the principal legend on the sign.

Option:

The different colored square or rectangular panels may include either a black or a white (whichever provides the better contrast with the color of the panel) letter, numeral, or other appropriate designation to identify the destination.

Except for the informational guide sign posted at the boundary of the wayfinding guide sign area, community wayfinding guide signs may use background colors other than green in order to provide a color identification for the wayfinding destinations by geographical area within the overall wayfinding guide signing system. Color-coded community wayfinding guide signs may be used with or without the boundary

informational guide sign displaying corresponding color-coding panels described in Paragraphs 13 through 16. Except as provided in Paragraphs 18 and 19, in addition to the colors that are approved in this Manual for use on official traffic control signs (see Section 2A.10), other background colors may also be used for the color coding of community wayfinding guide signs.

Standard:

The standard colors of red, orange, yellow, purple, or the fluorescent versions thereof, fluorescent yellow-green, and fluorescent pink shall not be used as background colors for community wayfinding guide signs, in order to minimize possible confusion with critical, higher-priority regulatory and warning sign color meanings readily understood by road users.

The minimum contrast value of legend color to background color for community wayfinding guide signs shall be at least 0.70 (or 70%).

All messages, borders, legends, and backgrounds of community wayfinding guide signs and any identification enhancement markers shall be retroreflective (see Sections 2A.07 and 2A.08).

Community wayfinding guide signs, exclusive of any identification marker used, should shall be rectangular in shape. Changed from Guidance to Standard

Guidance:

Community wayfinding guide signs, exclusive of any identification enhancement marker used, should be rectangular in shape. Simplicity and uniformity in design, position, and application as described in Section 2A.06 are important and should be incorporated into the community wayfinding guide sign design and location plans for the area.

Community wayfinding guide signs should be limited to three destinations per sign (see Section 2D.0706).

Abbreviations (see Section 1A.15) should be kept to a minimum, and should include only those that are commonly recognized and understood.

Horizontal lines of a color that contrasts with the sign background color should be used to separate groups of destinations by direction from each other.

Support:

The basic requirement for all highway signs, including community wayfinding signs, is that they be legible to those for whom they are intended and that they be understandable in time to permit a proper response. Section 2A.06 contains additional information on the design of signs, including desirable attributes of effective designs.

Guidance:

Word messages should be as brief as practical and the lettering should be large enough to provide the necessary legibility distance.

Standard:

The minimum specific ratio of letter height to legibility distance shall comply with the provisions of Section 2A.13. The size of lettering used for destination and directional legends on community wayfinding signs shall comply with the provisions of minimum letter heights as provided in Section 2D.0605.

Interline and edge spacing shall comply with the provisions of Section 2D.06.05.

Except as provided in Paragraph 31,33, the lettering style used for destination and directional legends on community wayfinding guide signs shall comply with the provisions of Section 2D.05.04.

The lettering for destinations on community wayfinding guide signs shall be a combination of lower-case letters with initial upper-case letters (see Section 2D.0504). All other word messages on community wayfinding guide signs shall be in all upper-case letters.

Guidance:

Except as provided in Paragraphs 34 and 35, letters, numerals, and other characters should be composed of the Standard Alphabets as detailed in the "Standard Highway Signs" publication.

48 Option:

A lettering style other than the Standard Alphabets provided in the "Standard Highway Signs-and-Markings" book-publication may be used on community wayfinding guide signs if an engineering study

determines that the legibility and recognition values for the chosen lettering style meet or exceed the values for the Standard Alphabets for the same legend height and stroke width, as provided in Paragraph 32 of this Section.

Standard:

An alternative lettering style as provided in Paragraph 33 of this Section shall be conventional in form. The letters, numerals, and other characters shall not be italic, oblique, script, highly decorative, or of other unusual forms.

<u>In accordance with Section 1D.09</u>, <u>Except for signs that are <u>designed and located with the</u> intentded to be viewed only by pedestrians, bicyclists stopped out of the flow of traffic, or occupants of parked vehicles, Internet and e-mail addresses, including domain names and uniform resource locators (URL), <u>quick-response (QR) codes</u>, <u>barcodes</u>, <u>or other graphics intended for optical scanning to obtain information</u>, shall not be displayed on any community wayfinding guide sign or sign assembly.</u>

The arrow location and priority order of destinations shall follow the provisions described in Sections 2D.08 and 2D.3736. Arrows shall be of the designs provided in Section 2D.08.

Option:

Pictographs (see definition in Section 1A.13) may be used on community wayfinding guide signs.

Standard

If a pictograph is used, its height shall not exceed two times the height of the upper-case letters of the principal legend on the sign.

Except for pictographs, symbols that are not approved in this Manual for use on guide signs shall not be used on community wayfinding guide signs.

Business logos, commercial graphics, or other forms of advertising (see Section 1A.01) shall not be used on community wayfinding guide signs or sign assemblies.

Option:

Other graphics that specifically identify the wayfinding system, including identification enhancement markers, may be used on the overall sign assembly and sign supports.

Support:

An <u>enhancement</u>-<u>identification</u> marker consists of a shape, color, and/or pictograph that is used as a visual identifier for the community wayfinding guide signing system for an area. Figure <u>2D-18-2D-29</u> shows examples of identification <u>enhancement</u> marker designs that can be used with community wayfinding guide signs.

Option:

An identification enhancement—marker may be used in a community wayfinding guide sign assembly, or may be incorporated into the overall design of a community wayfinding guide sign, as a means of visually identifying the sign as part of an overall system of community wayfinding signs and destinations.

Standard:

The sizes and shapes of identification enhancement markers shall be smaller than the community wayfinding guide signs themselves. Identification enhancement markers shall not be designed to have an appearance that could be mistaken by road users as being a traffic control device.

Guidance:

The area of the identification enhancement marker should not exceed 1/5 of the area of the community wayfinding guide sign with which it is mounted in the same sign assembly.

Section 2D.532D.56 Signing of Named Highways for Mapping and Address Purposes Support:

A highway name is the officially designated name of a freeway, expressway, or conventional road for navigational, official mapping, and address purposes. Some highways are named in addition to or in lieu of being assigned a highway route number. Memorial, honorary, ceremonial, or other secondary names, such as touring route and byway names, are not considered to be highway names.

Option:

Guide signs may contain street or highway names if the purpose is to enhance driver communication and guidance; however, they are to be considered as supplemental information to route numbers.

Standard:

Highway names shall not replace official numeral designations.

Memorial, honorary, or other secondary names (see Section 2M.10) shall not appear on supplemental signs or on any other information sign on or along the highway or its intersecting routes.

The use of route signs shall be restricted to signs officially used for guidance of traffic in accordance with this Manual and the "Purpose and Policy" statement of the American Association of State Highway and Transportation Officials that applies to Interstate and U.S. numbered routes (see Page i for AASHTO's address).

11 Option:

Unnumbered routes having major importance to proper guidance of traffic may be signed if carried out in accordance with the aforementioned policies. For unnumbered highways, a name to enhance route guidance may be used where the name is applied consistently throughout its length.

Guidance:

Only one name should be used to identify any highway, whether numbered or unnumbered.

Section 2D.55 2D.57 National Scenic Byways Signs and Plaque (D6-4, D6-4aP)

Support:

Certain roads have been designated by the U.S. Secretary of Transportation as National Scenic Byways or All-American Roads based on their archeological, cultural, historic, natural, recreational, or scenic qualities.

<u>Direction along routes and to sites relies primarily on touring maps rather than directional signing and route marking for the byway itself.</u>

Option:

State and local highway agencies may install the National Scenic Byways (D6-4) sign or (D6-4aP) signs plaque at entrance points to a route that has been recognized by the U.S. Secretary of Transportation as a National Scenic Byway or an All-American Road. The D6-4 or D6-4 sign may be installed on route sign assemblies (see Figure 2D-22) or as part of larger roadside structures. National Scenic Byways signs may also be installed as independent Directional (see Section 2D.32) or Confirming (see Section 2D.33) assemblies at periodic intervals along the designated route and at-near intersections where the designated route turns or follows a different numbered highway. The D6-4aP plaque may be installed below a Route sign in a Confirming assembly. At locations where roadside features have been developed to enhance the traveler's experience such as rest areas, historic sites, interpretive facilities, or scenic overlooks, the National Scenic Byways sign or plaque may be placed on the associated sign assembly to inform travelers that the site contributes to the byway travel experience.

Guidance:

Where the byway is identified only by the National Scenic Byways sign, the Directional assembly should consist of the D6-4 sign and an M5 series or M6 series Auxiliary plaque when indication of a turn is necessary to remain on the byway route.

Where the name of the byway is to be displayed on identification signs along the byway route, the name should be displayed in a Directional or Confirming assembly as follows:

- A. On a plaque mounted below the D6-4 sign; or
- B. On an identification sign with the D6-4aP plaque mounted below the sign.

In either case, the size of the National Scenic Byways (D6-4) sign or the byway identification sign should be consistent with that specified for route signs (see Section 2D.10) for the roadway classification.

Where the name of the byway is to be displayed along the byway route as provided in Paragraph XX5 of this Section, the byway Directional or Confirming assemblies should be located separately from any Route Sign assemblies or Destination guide signs.

Standard:

When a National Scenic Byways sign is installed on a National Scenic Byway or an All-American Road, the design shown for the D6-4 <u>sign</u> or D6-4a<u>P</u> <u>sign_plaque</u> in Figure 2D-22-34 shall be used. Use of this design shall be limited to routes that have been designated as a National Scenic Byway or All-American Road by the U.S. Secretary of Transportation.

If used, the D6-4 <u>sign</u> or D6-4a<u>P</u> <u>sign_plaque</u> shall be placed such that the <u>roadway highway route</u> <u>Route</u> signs have primary visibility for the road user.

The D6-4 sign or the D6-4aP plaque shall not be installed as sign panels on a guide sign or as part of a guide sign assembly.

Figure 2D-34. Examples of Use of the National Scenic Byways Sign

Section 2D.58 State-Designated Scenic Byway, Historic Trail, and Auto Tour Route Signs
Section consisting of new and relocated provisions from existing Section 2H.07

Support:

Signing for historic trails, auto tour routes, and State-designated scenic byways, is similar in concept to that for National Scenic Byways as provided in Section 2D.57. Direction along routes and to sites relies primarily on touring maps rather than directional signing and route marking for the trail, tour route, or byway itself.

Named highways are officially designated and shown on official maps and serve the purpose of providing route guidance, primarily on unnumbered highways, and property addresses. A highway designated as a trail, auto tour route, or byway is not considered to be a named highway for the purposes of highway signing or road user navigation and orientation. Section 2D.56 contains provisions for the signing of named highways.

Section 1A.08 provides information on the authority for placement of traffic control devices within the highway right-of-way.

Guidance:

Route Sign assemblies and Destination guide signs should have priority in visibility and location over signing related to historic trails, auto tour routes, and byways,.

Option:

<u>Identification signs for a historic trail, such as the National Historic Trails administered by the National Park Service, may be installed along segments of conventional roads that coincide with the original route of the trail.</u>

<u>Identification signs for a State scenic byway may be installed along conventional roads that have been</u> designated as part of a State scenic byway system.

Where a National Scenic Byway is part of a State scenic byway system, the National Scenic Byways (D6-4aP) plaque (see Section 2D.57) may be installed in a Directional or Confirming assembly below the identification sign for the State scenic byway (see Figure 2D-35).

A State scenic byway system sign may be installed in a Directional or Confirming assembly with the name of the byway displayed on a plaque below the sign (see Figure 2D-35).

Figure 2D-35. Example of Use of National Historic Trails, National, State Scenic Byways Signs *Guidance:*

The design and size of historic trail and State scenic byway identification or system signs should comply with the general provisions and principles for Route signs (see Section 2D.10). Designs should be simple, dignified, and devoid of complex graphics. The size of the signs should not exceed the size of the Route signs used along a particular route.

Standard:

Scenic byway, historic trail and auto tours route signs shall not incorporate standard highway sign legend elements into their design.

Guidance:

Where used, historic trail and State scenic byway identification signs should be installed as Directional (see Section 2D.32) or Confirming (see Section 2D.33) assemblies at independent locations, separate from other Route Sign assemblies and Destination guide signs. Where used, Confirming assemblies for the trail or byway should be installed at less frequent intervals than Confirming assemblies for the numbered route.

Support: Relocated from Sec. 2H.07 and revised

Auto Tour Route signs are informational sings, plaques, or shields designed to provide road users with route guidance in following an auto tour route of particular cultural, historical, or educational significance.

Where all or part of the original route of a historic trail does not follow a roadway, an Signed auto tour routes are is sometimes established along a conventional road in the general vicinity of used in some cases to generally follow the historical route of the trail, such as the National Historic Trails administered by the National Park Service. Examples include auto tour routes following other routes that parallel the original routes of the Lewis and Clark National Historic Trail, the Oregon National Historic Trail, and the Santa Fe National Historic Trail. The auto tour route is shown on touring maps along State or other highways and provides access to sites on the trail from those highways.

A system of signing providing direction along conventional roads for a historic trail with an auto tour route is shown in Figure 2D-36. Examples of Destination and Supplemental guide signs (see Section 2E.55) providing direction to historic trail sites from a freeway or expressway interchange are shown in Figure 2D-36.

Figure 2D-36. Example of Guide and Directional Signing for a National Historic Trail

Guidance:

Signing for historic trails should be limited to Destination signs for the sites related to the trail and to Directional and Confirming assemblies for the original portions of the trail itself. If an auto tour route has been designated along other highways to provide access to sites along the original trail as described in Paragraph 11, then the signing should be limited to Destination signs for those sites and directional signing to access the original route of the trail. Identification signs for the auto tour route should not be installed. Instead, direction along the auto tour route should rely on the touring map and other directional signs for the highways that the auto tour route follows.

Standard:

Identification signs for historic trails, Aauto Ttour Rroutes, and scenic byways signs shall not be installed on freeways or expressways, except as necessary to provide continuity between discontinuous segments of conventional roadways that are designated as a trail, auto tour routes, or byway, for which the freeway or expressway provides the only connection between the segments. If installed on freeways or expressways, Auto Tour Route the identification signs shall be installed as independent trailblazer assemblies (see Sections 2D.35-34 and 2E.27) and shall not be installed with other Route signs or confirmation Cconfirming assemblies or on guide signs. If installed on freeways or expressways, Auto-Tour Route the trailblazer assemblies for the trail, auto tour route, or byway shall be installed at less frequent intervals than route confirmation Cconfirming assemblies for the highway route.

<u>Identification signs for historic trails, auto tour routes, and scenic byways shall not be installed as sign panels on a guide sign or as part of a guide sign assembly.</u>

Section 2D.59 EMERGENCY ROUTE and EMERGENCY ROUTE TO Signs and Plaques Added to reflect Official Ruling No. 6(09)-42(I)

Support:

As part of an agency's transportation incident management plan it is sometimes desirable to permanently sign routes that provide rerouting of traffic around highway segments susceptible to traffic incidents. Permanently installed EMERGENCY ROUTE and EMERGENCY ROUTE TO signs and plaques (see Figure 2D-37) provide direction on conventional roads from an exit off a highway upstream of an area susceptible to traffic incidents back to the original route at a point downstream of the incident susceptible area.

Option:

EMERGENCY ROUTE and EMERGENCY ROUTE TO signs or plaques used on a directional assembly may be permanently installed on conventional roadways to provide direction back to the highway when diverted off of it for a traffic incident.

49 Support:

1	The purpose of EMERGENCY ROUTE and EMERGENCY ROUTE TO signs is for corridor
2	management along routes that have reoccurring incidents and have reasonable rerouting paths
3	available. These signs are intended to be permanently installed to provide instant rerouting guidance
4	to motorists when backups first begin even before emergency responders could provide temporary
5	traffic control for rerouting traffic. These signs can be used as a standalone system or be a part of a
6	larger system which may incorporate other devices such as dynamic message signs. These signs
7	provide motorists assurance that a given exit point will lead them back to their original route of
8	travel.
9	Standard:
10	EMERGENCY ROUTE and EMERGENCY ROUTE TO signs shall only be installed at
11	departure points and along diversion routes for directing motorists around highway segments
12	in areas that are more susceptible to traffic incidents; see Figure 2D-38. EMERGENCY
13	ROUTE and EMERGENCY ROUTE TO signs shall be placed at each turning decision points
14	along the designated route until it rejoins the original route or until other directional signs
15	leading back to the original route are provided.
16	EMERGENCY ROUTE and EMERGENCY ROUTE TO signs shall have a green
17	background with white legend.
18	Option:
19	For emphasis the legend EMERGENCY ROUTE or EMERGENCY ROUTE TO may be
20	displayed in a yellow panel with black letters on the top of the sign; see Figure 2D-37.
21	Standard:
22	Orange or pink shall not be used as alternate colors on permanently installed signs or
23	plaques for rerouting traffic during an incident or other event. If a route shield is displayed as
24	part of the message, the wording of the sign or plaque shall be EMERGENCY ROUTE TO as
25	shown in Figure 2D-37.
26	Option:
27	An EMERGENCY ROUTE TO plaque with either a white legend on a green background or
28	black legend on a yellow background may be added to the top of a conventional Route Assembly on
29	a diversion route providing direction back to the original route past the incident; see Figure 2D-37.
30	Figure 2D-37. Example of Guide Signs for Rerouting Due to Traffic Incidents

Figure 2D-38. Example of Signing for Rerouting Due to Traffic Incidents

31

1	2E.46	Post-Interchange Signs
2	2E.47	Post-Interchange Distance Signs (E7-1 Series, E7-2 Series, E7-3 Series)
3	2E.48	Post-Interchange Travel Time Sign (E7-4 Series)
4	2E.49	Distance and Travel Time Sign and Comparative Travel Time Sign (E7-5, E7-6)
5	2E.50	Supplemental Guide Signs (E3 Series)
6	2E.51	Community Interchanges Identification Signs (E9-4 Series, E9-5 Series)
7	2E.52	NEXT XX EXITS Sign (E9-3 Series)
8	2E.53	Weigh Station Signing
9	2E.54	Route Signs and Trailblazer Assemblies
10	2E.55	Eisenhower Interstate System Signs (M1-10, M1-10a)
11	Signs for Rout	te Diversion by Vehicle Class
12	2E.56	Signs for Route Diversion by Vehicle Class
13	Signs for Inter	rsections at Grade
14	2E.57	Signs for Intersections at Grade
15	Interface with	Conventional Roadways
16	2E.58	Signing on Conventional Road Approaches and Connecting Roadways
17	2E.59	Wrong-Way Traffic Control at Interchange Ramps
17 18	2E.59	Wrong-Way Traffic Control at Interchange Ramps

1 <u>GENERAL</u>

Section 2E.01 Scope of Freeway and Expressway Guide Sign Standards

Support:

The provisions of this Chapter provide a uniform and effective system of signing for high-volume, high-speed motor vehicle traffic on freeways and expressways. The requirements and specifications for expressway signing exceed those for conventional roads (see Chapter 2D), but are less than those for freeway signing. Since there are many geometric design variables to be found in existing roads, a signing concept commensurate with prevailing conditions is the primary consideration. Section 1A.13 includes definitions of freeway and expressway.

Guide signs for freeways and expressways are primarily identified by the name of the sign rather than by an assigned sign designation. Guidelines for the design of guide signs for freeways and expressways are provided in the "Standard Highway Signs and Markings" book publication (see Section 1A.11).

Standard:

The provisions of this Chapter shall apply to any highway that meets the definition of freeway or expressway facilities.

Support:

The application of the provisions for freeway and expressway guide signs in tunnels can present unique challenges not encountered elsewhere due to the extended and continuous distances of constrained vertical and horizontal clearances in which to place signs. The effect of these constraints is particularly evident when there are interchange ramps or other geometric features inside the tunnel that warrant signs to provide adequate notice. Accordingly, it might not always be possible to employ the standardized layouts to all signs inside a tunnel. In addition, interchange guide signs might need to be limited to one destination only, with other destinations displayed separately on Supplemental guide signs (see Section 2E.50). Acceptable methods to modify the layout of a sign to limit the space required in a tunnel are provided in Paragraph 5 of this Section.

Option:

Overhead-mounted guide signs in tunnels may be modified in accordance with the following when needed to accommodate limited vertical clearance available for signs:

- A. Some sign legend elements may be arranged side by side, such as by placing route shields to the left of the destination instead of above.
- B. The Exit Number plaque (see Section 2E.23) may be placed at the left edge of the sign instead of at the top edge the sign. The legend of the Exit Number plaque may use a reduced letter height of 6 inches for the word EXIT(S) and 12 inches for numerals and suffixes while maintaining the standard vertical layout.
- C. Destination and roadway names may be displayed in reduced letter heights of 13.33 inches or 10.67 inches, when determined acceptable based on consideration of reduced speeds, fewer visual distractions, and other relevant factors, while maintaining adequate space between the legend and edges of the sign to ensure legibility and quick recognition.
- D. Unusually long destination and roadway names that cannot be adequately shortened or otherwise acceptably abbreviated may be displayed using series D letters in lieu of Series E(modified).

Support:

The visibility and retroreflectivity of sign sheeting inside tunnels can be reduced by the accumulation of residue that results from being unexposed to environmental elements such as rain. *Guidance:*

Overhead signs in tunnels should be illuminated to ensure adequate visibility between scheduled maintenance and cleanings.

One or more Interchange Sequence signs (see Section 2E.24) should be used on the approach to the tunnel entrance to display the distances to the next interchanges that have ramps inside the tunnel or immediately following the exit from the tunnel.

Supplementary pavement markings, such as word, arrow, and/or route shield markings (see Part 3), should be considered inside the tunnel in addition to the basic lane and edge line markings.

Standard:

4

5 6

7

8

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

34

35

36

37

38

39 40

41

42 43

44

45

46

47

49

51

Applicability of the provisions of Paragraph 5 of this Section shall be limited to those signs within the limits of the tunnel and not extended to the approaches to or departures from the tunnel.

Section 2E.02 Freeway and Expressway Signing Principles

Support:

The development of a signing system for freeways and expressways is approached on the premise that the signing is primarily for the benefit and direction of road users who are not familiar with the route or area. The signing furnishes road users with clear instructions for orderly progress to their destinations. Sign installations are an integral part of the facility and, as such, are best planned concurrently with the development of highway location and geometric design. For optimal results, plans for signing are analyzed during the earliest stages of preliminary design, and details are correlated as final design is developed. The excessive signing found on many major highways usually is the result of using a multitude of signs that are too small and that are poorly designed and placed to accomplish the intended purpose.

Freeway and expressway signing is to be considered and developed as a planned system of installations. An engineering study is sometimes necessary for proper solution of the problems of many individual locations, but, in addition, consideration of an entire route is necessary.

Guidance:

Road users should be guided with consistent signing on the approaches to interchanges, when they drive from one State to another, and when driving through rural or urban areas. Because geographical, geometric, and operating factors regularly create significant differences between urban and rural conditions, the signing should take these conditions into account.

Guide signs on freeways and expressways should serve distinct functions as follows:

- A. Give directions to destinations, or to streets or highway routes, at intersections or interchanges;
- B. Furnish advance notice of the approach to intersections or interchanges;
- C. Direct road users into appropriate lanes in advance of diverging or merging movements;
 - D. Identify routes and directions on those routes;
- 33 E. Show distances to destinations:
 - F. Indicate access to general motorist services, rest, scenic, and recreational areas; and
 - G. Provide other information of navigational value to the road user.

Section 2E.03 Guide Sign Classification

Support:

Freeway and expressway guide signs are classified and <u>addressed as follows</u>treated in the following categories: Item list reordered to reflect reorganized order of chapters and sections

- A. Interchange signs (see Sections 2E.30-21 through 2E.3924 and 2E.26 through 2E.45),
- B. Interchange Sequence signs (see Section 2E.402E.24).
- C. Post-Interchange signs (see Sections 2E.46 through 2E.48),
- D. Community Interchanges Identification signs (see Section 2E.412E.51),
- E. NEXT XX EXITS signs plaques (see Section 2E.422E.52),
- F. Weigh Station signing signs (see Section 2E.534),
 - G. Route signs and Trailblazer Assemblies (see Section 2E.272E.54),
- H. At-Grade Intersection signs (see Section 2E.292E.56),
- 48 I. Miscellaneous General iInformation signs (see Section 2H.04),
 - J. Reference Location signs (see Section 2H.05),
- 50 K. General Service signs (see Chapter 2I),
 - L. Rest and Scenic Area signs (see Section 2I.05),

- 1 M. Tourist Information and Welcome Center signs (see Section 2I.08),
- 2 N. Radio Information, Travel Information, and Roadside Assistance signing signs (see Sections 2I.09 3 through 2I.13),
- 4 O. Carpool and Ridesharing signing signs (see Section 2I.11),
 - P. Specific Service signs (see Chapter 2J), and
 - Q. Recreational and Cultural Interest Area signs (see Chapter 2M).
- Section 2E.04 General This section relocated to new Section 2E.08. 7
- 8 Section 2E.05 Color of Guide Signs This section relocated to new Section 2E.09.
- 9 Section 2E.06 Retroreflection or Illumination This section relocated to new Section 2E.10.
- Section 2E.072E.04 Characteristics of Urban Signing 10
- 11 Support:

5

6

14

15

16

17

18 19

22

23

24

25 26

27

28

29

30 31

32

33

37

39

40

41

42

44

45

46 47

48

- 12 Urban conditions are characterized not so much by city limits or other arbitrary boundaries, as by the 13 following features:
 - A. Mainline roadways with more than two lanes in each direction;
 - B. High traffic volumes on the through roadways;
 - C. High volumes of traffic entering and leaving interchanges:
 - D. Interchanges closely spaced;
 - E. Roadway and interchange lighting;
 - F. Three or more interchanges serving the major city;
- 20 G. A loop, circumferential, or spur <u>route</u> serving a sizable portion of the urban population; and
- H. Visual clutter from roadside development. 21
 - Operating conditions and road geometrics on urban freeways and expressways usually make special sign treatments desirable, including:
 - A. Use of Interchange Sequence signs (see Section 2E.402E.24);
 - B. Use of sign spreading to the maximum extent possible (see Section 2E.112E.43);
 - C. Elimination of General or Specific Service signing (see Chapters 2I and 2J);
 - D. Reduction to a minimum of post-interchange signs (see Section 2E.382E.46);
 - E. Display of advance signs at distances closer to the interchange, with appropriate adjustments in the legend (see Section 2E.332E.23);
 - F. Use of overhead signs on roadway structures and independent sign supports (see Section 2E.252E.19);
 - G. Use of Overhead Arrow-per-Lane or Diagrammatic guide signs in advance of intersections and interchanges (see Sections 2E.212E.40 and 2E.222E.41); and
 - H. Frequent use of street names as the principal message in guide signs.
- 34 Lower speeds which are often characteristic of urban operations do not justify lower signing standards.
- 35 Typical traffic patterns are more complex for the road user to negotiate, and large, easy-to-read legends are,
- 36 therefore, just as necessary as on rural highways.
 - Section 2E.082E.05 Characteristics of Rural Signing
- 38 Support:

Rural areas ordinarily have greater distances between interchanges, which permits adequate spacing for the sequences of signs on the approach to and departure from each interchange. However, the absence of traffic in adjoining lanes and on entering or exiting ramps often adds monotony or inattention to rural driving. This increases the importance of signs that call for decisions or actions.

43 Guidance:

> Where there are long distances between interchanges and the alignment is relatively unchanging, signs should be positioned for their best effect on road users. The tendency to group all signing in the immediate vicinity of rural interchanges should be avoided by considering the entire route in the development of signing plans. Extra effort should be given to the placement of signs at natural target locations to command the attention of the road user, particularly when the message requires an action by the road user.

Section **2E.092E.06** Signing of Named Highways

2 Guidance:

1

- Signing of named highways on freeways and expressways should comply with the provisions of Section
 2D.56.
- 5 Support:
- Section 2D.53 contains information, which is also applicable to freeways and expressways, regarding the use of highway names on the signing for unnumbered highways to enhance route guidance and facilitate travel. Changed to Guidance
- 9 Section 2M.10 contains information regarding memorial <u>or dedication</u> signing of routes, bridges, or 10 highway components.
- 11 Section 2E.10 Amount of Legend on Guide Signs This section relocated to new Section 2E.15
- 12 Section 2E.11 Number of Signs at an Overhead Installation and Sign Spreading This section
- relocated to new Section 2E.43
- 14 Section 2E.12 Pull-Through Signs (E6-2,E6-2a) This section relocated to new Section 2E.27
- 15 Section <u>2E.132E.07</u> <u>Designation of Destinations</u>
- 16 **Standard:**

17

18

19

20

22

23

24

25

26

27

28

29

30

31

32

33

34 35

36 37

38 39

40

41

42 43 The direction of a freeway and the major destinations or control cities along it shall be clearly identified through the use of appropriate destination legends (see Section 2D.37). Successive freeway guide signs shall provide continuity in destination names and consistency with available map information. At any decision point, a given destination shall be indicated by way of only one route.

21 Guidance:

- Control city legends should be used in the following situations along a freeway:
- A. At interchanges between freeways;
- B. At separation points of overlapping freeway routes;
 - C. On directional signs on intersecting routes, to guide traffic entering the freeway;
 - D. On Pull-Through signs; and
- E. On the bottom line of post-interchange distance signs.
- Support:

Continuity of destination names is also useful on expressways serving long-distance or intrastate travel.

The determination of major destinations or control cities is important to the quality of service provided by the freeway. Control cities on freeway guide signs are selected by the States and are contained in the "Guidelines for the Selection of Supplemental Guide Signs for Traffic Generators Adjacent to Freeways, 4th Edition/Guide Signs, Part II: Guidelines for Airport Guide Signing/Guide Signs, Part III: List of Control Cities for Use in Guide Signs on Interstate Highways," published by and available from the American Association of State and Highway Transportation Officials (see Section 1A.11).

In some instances the exit that provides the most direct or preferred access to one or more destinations is different in opposing directions of travel due to the configuration of the crossroads, the density of development on sections of the crossroads, etc.

Guidance:

The guide signs for exits in each direction of travel should display the destinations with the most direct or preferred access from that direction of travel even when this results in the destinations being different for an exit in opposing directions of travel (see Figure 2E-1).

Figure 2E-1. Designation of Destinations for Interchanges in Opposing Directions of Travel

44 45 4

5

6

7

8

9

11

12

13

15

16

17

18

20

21

23

24

25

2627

28

29

30

31

33

34

35

36

37

38

39

40

41

42

43 44

47

2 Section <u>2E.042E.08</u> General

3 Support:

Signs are designed so that they are legible to road users approaching them and readable in time to permit proper responses. Desired design characteristics include: (a) long visibility distances, (b) large lettering, symbols, and arrows, and (c) short legends for quick comprehension.

Standard:

Standard shapes and colors shall be used so that traffic signs can be promptly recognized by road-users.

10 Section <u>2E.05</u>2E.09 Color of Guide Signs

Standard:

Guide signs on freeways and expressways, except as otherwise provided in this Manual, shall have white letters, symbols, arrows, and borders on a green background.

14 Support:

Color requirements for route signs and trailblazers, signs with blank-out or changeable messages, signs for services, rest areas, park and recreational areas, and for certain miscellaneous signs are provided in the individual Sections dealing with the particular sign or sign group.

Section 2E.062E.10 Retroreflection or Illumination

19 **Standard:**

Letters, numerals, symbols, arrows, and borders of all guide signs shall be retroreflectorized. The background of all guide signs that are not independently illuminated shall be retroreflective.

22 Support:

Where there is no serious interference from extraneous light sources, retroreflectorized post-mounted signs usually provide adequate nighttime visibility.

On freeways and expressways where much driving at night is done with low-beam headlights, the amount of headlight illumination incident to an overhead sign display is relatively small.

Guidance:

Overhead sign installations should be illuminated unless an engineering study shows that retroreflectorization alone will perform effectively. The type of illumination chosen should provide effective and reasonably uniform illumination of the sign face and message.

Section 2E.322E.11 Interchange Classification

32 Support:

For signing purposes, interchanges are classified as major, intermediate, and minor. The minimum Minimum alphabet sizes based on interchange classification are contained in Tables 2E-2 and 2E-4 are based on this classification. Descriptions of these classifications are as follows:

- A. Major interchanges are subdivided into two categories: (a) interchanges with other expressways or freeways, or (b) interchanges with high-volume multi-lane highways, principal urban arterials, or major rural routes where the volume of interchanging traffic is heavy or includes many road users unfamiliar with the area.
- B. Intermediate interchanges are those with urban and rural routes not in the category of major or minor interchanges.
- C. Minor interchanges include those where traffic is local and very light, such as interchanges with land service access roads. Where the sum of exit volumes is estimated to be lower than 100 vehicles per day in the design year, the interchange is classified as minor.

The applicability of the alphabet sizes shown in the "Overhead" column of Tables 2E-2 and 2E-4 is provided in Section 2E.12.

Section **2E.14 2E.12** Size and Style of Letters and Signs

Standard:

Except as provided in Section 2A.11, the sizes of freeway and expressway guide signs that have standardized designs shall be as shown in Table 2E-1.

Support:

5 Section 2A.11 contains information regarding the applicability of the various columns in Table 2E-1.

Option:

Signs larger than those shown in Table 2E-1 may be used (see Section 2A.11).

Standard:

All names of places, streets, and highways on freeway and expressway guide signs shall be composed of lower-case letters with initial upper-case letters. The letters and the numerals used shall be FHWA Standard Alphabet Series E (modified) as provided in the "Standard Highway Signs" publication (see Section 1A.11). Series E(M) of the "Standard Highway Signs and Markings" book (see Section 1A.11). The nominal loop height of the lower-case letters shall be 3/4 of the height of the initial upper-case letter (see Paragraph 2 of Section 2D.05 for additional information on the specification of letter heights). Other word legends shall be composed of upper-case letters. Interline and edge spacing shall be as provided in Section 2E.135.Relocated from later in Standard

For all freeway and expressway signs that do not have a standardized design, the message dimensions shall be determined first, and the outside sign dimensions secondarily. Word messages in the legend of expressway guide signs shall be in letters at least 8 inches high <u>for words composed of all upper-case letters</u>. Larger lettering shall be used for major guide signs at or in advance of interchanges and for all overhead signs. Minimum numeral and letter sizes for expressway guide signs according to interchange classification, type of sign, and component of sign legend shall be as shown in Tables 2E-<u>2-3</u> and 2E-<u>34</u>. Minimum numeral and letter sizes for freeway guide signs according to interchange classification, type of sign, and component of sign legend shall be as shown in Tables 2E-<u>4-5</u> and 2E-<u>56</u>. The minimum numeral and letter sizes for overhead-mounted expressway and freeway guide signs shall be those shown in the "Overhead" columns of Tables 2E-2 and 2E-4, respectively, except where a larger minimum numeral or letter height is provided in the columns for the applicable type of interchange (Major, Intermediate, or Minor).

All names of places, streets, and highways on freeway and expressway guide signs shall be composed of lower-case letters with initial upper-case letters. The letters and the numerals used shall be Series E(M) of the "Standard Highway Signs and Markings" book (see Section 1A.11). The nominal loop height of the lower-case letters shall be 3/4 of the height of the initial upper-case letter (see Paragraph 2 of Section 2D.05 for additional information on the specification of letter heights). Other word legends shall be composed of upper-case letters. Interline and edge spacing shall be as provided in Section 2E.15. Relocated to earlier in Standard

Lettering size on freeway and expressway signs shall be the same for both rural and urban conditions.

Support:

Sign size is determined primarily in terms of the length of the message and the size of the lettering necessary for proper legibility. Letter style and height, and arrow design have been standardized for freeway and expressway signs to assure uniform and effective application.

Designs for upper-case and lower-case alphabets FHWA Standard Alphabets, together with tables of recommended letter spacing, are shown in the "Standard Highway Signs and Markings" book publication (see Section 1A.11).

Guidance:

Freeway lettering sizes (see Tables 2E-4 and 2E-5) should be used when expressway geometric design is comparable to freeway standards.

Other sign letter size requirements not specifically identified elsewhere in this Manual should be guided by these specifications. Abbreviations (see Section 2E.17) should be kept to a minimum, except as provided in Section 2E.16.

51 Support:

1 A sign mounted over a particular roadway lane to which it applies might have to be limited in horizontal 2 dimension to the width of the lane, so that another sign can be placed over an adjacent lane. The necessity to 3 maintain proper vertical clearance might also place a further limitation on the size of the overhead sign and 4 the legend that can be accommodated. 5 Table 2E-1. Freeway and Expressway Guide Sign and Plaque Sizes 6 Table 2E-2. Minimum Letter and Numeral Sizes for Expressway Guide Signs According to 7 **Interchange Classification** Table 2E-3. Minimum Letter and Numeral Sizes for Expressway Guide Signs According to 8 9 Sign Type Table 2E-4. Minimum Letter and Numeral Sizes for Freeway Guide Signs According to 10 **Interchange Classification** 11 Table 2E-5. Minimum Letter and Numeral Sizes for Freeway Guide Signs According to Sign 12 13 **Type**

Section 2E.15 2E.13 Interline and Edge Spacing

15 Guidance:

14

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

38

39

41

42

43

44

45

47

48

Interline spacing of upper-case letters should be approximately three-fourths the average of upper-case letter heights in adjacent lines of letters.

The spacings to the top and bottom borders should be equal to the average of the letter height of the adjacent line of letters. The lateral spacing to the vertical borders should be essentially the same as the height of the largest letter.

Section 2E.16 2E.14 Sign Borders

Standard:

Signs shall have a border of the same color as the legend in order to outline their distinctive shape and thereby give them easy recognition and a finished appearance. Relocated to existing Section 2A.10

Guidance:

For guide signs larger than 120 x 72 inches, the border should have a width of 2 inches. For smaller guide signs, a border width of 1.25 inches should be used, but the width should not exceed the stroke width of the lettering of the principal legend on the sign. On unusually large signs with oversized letter heights, route shields, or other legend elements, the border should be 2-½ inches wide and should not exceed 3 inches in width. In all cases, the width of the border should not exceed the stroke width of the lettering of the principal legend on the sign.

Corner radii of sign borders should be <u>approximately</u> 1/8 of the minimum sign dimension on guide signs, except that the radii should not exceed 12 inches on any sign.

Support:

The "Standard Highway Signs" publication contains detailed information on border widths and corner radii for ranges of sign sizes.

37 Option:

The sign material in the area outside of the corner radius may be trimmed.

Section **2E.15 Amount of Legend on Guide Signs**

40 Guidance:

No more than two destination names or street names should be displayed on any Advance Guide sign or Exit Direction sign. A city name and street name on the same sign should be avoided. Where two or three signs are placed on the same supports, destinations or <u>street</u> names should be limited to one per sign, or to a total of three in the display. Sign legends should not exceed three lines of copy, exclusive of the exit number and action or distance information.

46 Support:

Where only one interchange serves a community, the intersecting street name is generally superfluous to the city name on the Advance guide and Exit Direction signs. Where a community is served by multiple

- 1 <u>interchanges, either the NEXT XX EXITS (see Section 2E.52) or the Community Interchanges Identification</u>
- 2 (see Section 2E.51) signs are used to display the city name. Each interchange is then identified by its
- 3 intersecting roadway name on the Advance guide and Exit Direction signs rather than by the city name.

Section <u>2E.17</u> <u>2E.16</u> <u>Abbreviations</u>

5 **Standard:**

4

6

7

8

9

10 11

12 13

14

15

16

17

18

20

21

24

25

27

28

29

30

31

32

33

34

35

36

37

38

40

41

43

44

45

46

47 48

49

The use of abbreviations on freeway and expressway guide signs shall comply with the provisions of Section 2D.07 of this Manual.

Guidance:

Abbreviations should be kept to a minimum; however, they are useful when complete destination messages produce excessively long signs. If used, abbreviations should be unmistakably recognized by road users (see Section 1A.15). Longer commonly used words that are not part of a proper name and are readily recognizable, such as Street, Boulevard, and Avenue, should be abbreviated to expedite recognition of the sign legend by reducing the amount and complexity of the legend.

Periods, apostrophes, question marks, ampersands, or other punctuation or characters that are not letters, numerals, or hyphens should not be used in abbreviations, unless necessary to avoid confusion.

The solidus (slanted line or forward slash) is intended to be used for fractions only and should not be used to separate words on the same line of legend. Instead, a hyphen should be used for this purpose, such as "CARS—TRUCKS."

19 Standard:

The words NORTH, SOUTH, EAST, and WEST shall not be abbreviated when used with route signs to indicate cardinal directions on guide signs.

- 22 Section^{2E.18} 2E.17 Symbols
- 23 Standard:

Symbol designs shall be unmistakably like those shown in this Manual and in the "Standard Highway Signs and Markings" book (see Section 1A.11).

26 Support:

Symbols are not normally displayed on freeway and expressway guide signs. One exception is the Park – Ride Supplemental guide sign (see Section 2E.50), which displays the Carpool symbol. In some cases, General Information symbols (see Chapter 2H) might be included in the legend of a guide sign to shorten an unusually lengthy legend on the sign.

Guidance:

When a General Information symbol is incorporated into the legend of a guide sign, all components of the legend should be balanced in size and arrangement special effort should be made to balance legend components for maximum legibility of the symbol with the rest of the sign. The General Information (I series) sign, rather than the symbol alone, should be placed as a sign panel within the guide sign so that adequate recognition of the symbol is provided by the border. The General Information sign panel should be positioned to the left of the legend to which it applies. The size of the General Information sign panel should be the similar in size to that specified for a route shield for the type of guide sign on which it is displayed.

39 Option:

Educational plaques may be used below symbol signs where needed.

Section **2E.192E.18** Arrows for Interchange Guide Signs

42 Standard:

Arrows used on interchange guide signs shall be of the types shown in Figure 2D-2 and shall comply with the provisions of this Section and Section 2D.08.

Except on Overhead Arrow-per-Lane guide signs (see Section 2E.212E.40) and on Exit Direction signs for lane drops (see Section 2E.242E.28), and except as provided in Paragraphs 3 and 4 of this Section, directional arrows on all overhead and post-mounted Exit Direction signs shall point diagonally upward. and Directional arrows on overhead Exit Direction signs shall be located on the side of the sign consistent with the direction of the exiting movement. Directional arrows on post-

1 mounted Exit Direction signs shall be located at the bottom portion of the sign and centered under the legend.

Option:

3

4

5

6

7

8

9

10

11

12 13

14

15 16

17

18

19

20

21

22

23

24

2526

36

On post mounted overhead Exit Direction signs that are located fully over the tapered portion of the exit ramp at the theoretical gore, and where a directional arrow to the side of the legend farthest from the roadway might create an unusually wide sign that limits the road user's view of the arrow, the directional arrow may be placed at the bottom portion of the sign, centered under the legend.

Standard:

Directional arrows on guide signs for multi-lane exits shall be positioned below the legend approximately over the approximate center of each lane to which the arrow applies (see Figures 2E-4 2E-38 and 2E-8 2E-43).

On overhead signs where dDown arrows shall only be used on overhead signs are used to indicate a lane to be followed and, a down arrow shall be positioned approximately over the approximate center of each lane and shall pointing vertically downward toward the approximate center of that lane. Down arrows shall be used only on overhead guide signs that restrict the use of specific lanes to traffic bound for the destination(s) and/or route(s) indicated by these arrows. Down arrows shall not be used unless an arrow can be located over and pointed to the approximate center of each lane that can be used to reach the destination displayed on the sign.

If down arrows are used, having more than one down arrow pointing to the same lane on a single overhead sign (or on multiple signs on the same overhead sign structure) shall not be permitted.

Support:

Directional and down arrows for use on guide signs are shown in Figure 2D-24. Detailed drawings and standardized sizes based on ranges of letter heights for these arrows are provided in the "Standard Highway Signs—and Markings" book-publication (see Section 1A.11). Information on the dimensions for arrows used in Overhead Arrow-per-Lane and Diagrammatic guide signing is also provided in the "Standard Highway Signs—and—Markings" book-publication.

- 27 Section 2E.20 Signing for Option Lanes at Splits and Multi-Lane Exits This section relocated to
- new Section 2E.39
- 29 Section 2E.21 Design of Overhead Arrow-per-Lane Guide Signs for Option Lanes This section
- relocated to new Section 2E.40
- 31 Section 2E.22 Design of Freeway and Expressway Diagrammatic Guide Signs for Option
- 32 **Lanes** This section relocated to new Section 2E.41
- 33 Section 2E.23 Signing for Intermediate and Minor Interchange Multi-Lane Exits with an
- 34 Option Lane This section relocated to new Section 2E.42
- 35 Section 2E.24 Signing for Interchange Lane Drops This section relocated to new Section 2E.28

INSTALLATION

1

2

4

5

6

7

8

9

10

11

12

13

14

15

16 17

18

19

20

21

22

23

24 25

26

27

28

30

31

Section 2E.25 2E.19 Overhead Sign Installations

3 Support:

Specifications for the design and construction of structural supports for signs have been standardized by the American Association of State Highway and Transportation Officials (AASHTO). Overcrossing structures can often serve for the support of overhead signs, and might in some cases be the only practical location that will provide adequate viewing distance. Use of these structures as sign supports will eliminate the need for additional sign supports along the roadside. Conditions that might warrant Factors justifying the installation of overhead signs are given in Section 2A.17 and throughout this Chapter. Vertical clearance of overhead signs is discussed in Section 2A.18.

Section 2E.26 2E.20 Lateral Offset

Standard:

Except where shielded by a rigid traffic barrier, the The minimum lateral offset outside the usable roadway shoulder for post-mounted freeway and expressway signs or for overhead sign supports, either to the right-hand or left-hand side of the roadway, shall be 6 feet. This minimum clearance shall also apply outside of a curb. If located within the clear zone, the signs shall be mounted on crashworthy supports or shielded by appropriate crashworthy barriers.

Guidance:

Where practical, a sign should not be less than 10 feet from the edge of the nearest traffic lane. Large guide signs especially should be farther removed, preferably 30 feet or more from the nearest traffic lane.

Where an expressway median is 12 feet or less in width, consideration should be given to spanning both roadways without a center support.

Where overhead sign supports cannot be placed sufficiently far away from the line of traffic or in an otherwise protected shielded site, they should either be designed to minimize the impact forces, or be adequately shielded by a traffic barrier of suitable design.

Standard:

Butterfly-type sign supports and other overhead non-crashworthy sign supports shall not be installed in gores or other unshielded locations within the clear zone.

29 Option:

Lesser clearances, but not generally less than 6 feet, may be used on connecting roadways or ramps at interchanges.

- 32 Section 2E.27 Route Signs and Trailblazer Assemblies This section relocated to new Section 2E.54
- Section 2E.28 <u>Eisenhower Interstate System Signs (M1-10, M1-10a)</u> This section relocated to new Section 2E.55
- 35 Section 2E.29 Signs for Intersections at Grade This section relocated to new Section 2E.56

36

2 Section <u>2E.30</u> <u>2E.21</u> <u>Interchange Guide Signs</u>

3 Support:

For some applications, guide signing for interchanges depends upon the interchange classification as described in Section 2E.11. Sections 2E.23, 2E.25, 2E.30, 2E.39, and 2E.42 contain provisions on guide signing for interchanges that are based on interchange classification.

Standard:

The signs at interchanges and on their approaches shall include Advance Guide signs and Exit Direction signs. Consistent destination messages shall be displayed on these signs.

Guidance:

New destination information should not be introduced into the major sign sequence for one interchange, nor should destination information be dropped.

Reference should be made to Section 2E.11 and Sections 2E.33 through 2E.42 for a detailed description of the signs in the order that they should appear at the approach to and beyond each interchange. Guide signs placed in advance of an interchange deceleration lane should be spaced at least 800 feet apart.

<u>Use of Ssupplemental guide signing should be used sparingly minimized</u> as provided in Section <u>2E.35</u>2E.540.

18 Support:

Figure 2E-2 shows the typical sequence of interchange guide signs.

Figure 2E-2. Typical Sequence of Interchange Guide Signs

Section 2E.31 2E.22 Interchange Exit Numbering

Standard:

Interchange exit numbering shall use the reference location sign exit numbering method. The consecutive exit numbering method shall not be used. The exit numbers shall correspond to the posted Reference Location or Enhanced Reference Location signs.

26 Support:

Reference location sign exit numbering assists road users in determining their destination distances and travel mileage, reporting their location in the event of an incident or breakdown, assists responders in reporting to incidents, and assists highway agencies because the exit numbering sequence does not have to be changed if new interchanges are added to a route. Moved from later in Section and revised.

Interchange exit numbering provides valuable orientation for the road user on a freeway or expressway. The feasibility of numbering interchanges or exits on an expressway will depend largely on the extent to which grade separations are provided. Where there is appreciable continuity of interchange facilities, interrupted only by an occasional intersection at grade, the numbering will be helpful to the expressway user.

Standard:

Interchange <u>exit</u> numbering shall be used in signing each freeway interchange exit. Interchange exit numbers shall be displayed with each Advance Guide sign, Exit Direction sign, and Exit Gore sign. The exit number shall be displayed on a separate plaque <u>onat the</u> top of the Advance Guide or Exit Direction sign. The <u>eExit nNumber</u> (E1-5P <u>series</u>) plaques (see Figure <u>2E-22 2E-10</u>) <u>shall be 30 inches in height and</u> shall include the word EXIT <u>or EXITS</u> and the appropriate exit number in a single-line format.

Suffix letters shall only be used to supplement exit numbers where, from the same direction of travel on the freeway mainline, there is more than one exit at an interchange or where interchanges are so closely spaced that it is impracticable to use separate exit numbers associated with the reference mile points of the freeway. Suffix letters shall be used for exit numbering at a multi-exit interchange. The suffix letter shall also be included on the eExit nNumber plaque and shall be separated from the exit number by a space having a width of between 1/2 and 3/4 of the height of the suffix letter. The suffix letters assigned shall be in ascending alphabetical order starting with the letter A for ramps in the direction of travel with increasing exit numbers, and in descending alphabetical order ending in the

<u>letter A in the opposite direction of travel.</u> Exit numbers shall not include the cardinal <u>direction</u> initials corresponding to the directions of the cross route. <u>The Mminimum numeral and letter sizes shall be asare</u> given in Tables 2E-2 through 2E-5. If used, the interchange numbering system for expressways shall comply with the provisions prescribed for freeways.

At a multi-exit interchange wWhere suffix letters are used for exit numbering, an exit of the same number without a suffix letter shall not be used on the same route in the same direction. For example, if an exit is designated as EXIT 256 A, then there shall not be an exit designated as EXIT 256 on the same route in the same direction.

Guidance:

 To the extent practicable, exit numbering should correspond to the nearest reference location sign number of the freeway at the point the crossroad of the interchange intersects the freeway mainline. The following are examples of proper numbering under various interchange scenarios:

- 1. If a crossroad intersects the mainline approximately at or after mile 15 and before mile 16, the interchange should be designated as EXIT 15.
- 2. If the interchange crossroad is split into two roadways by direction where one direction of the crossroad is downstream of mile 18 and the other direction is upstream of mile 18, the interchange exit number should be EXIT 18..
- 3. If there are three closely spaced interchanges, e.g. less than 1 mile apart, starting before mile 16 and ending before mile 17, the interchanges should be designated as EXIT 15, EXIT 16 and EXIT 17.
- 4. If there are multiple interchanges so closely spaced together that it is impractical to designate the exit numbers by the freeway mainline reference mile numbers, or doing so would tend to not meet driver expectations, suffix letters should be used as provided in this Section.

Interchange exit numbering shall use the reference location sign exit numbering method. The consecutive exit numbering method shall not be used.

Support:

Reference location sign exit numbering assists road users in determining their destination distances and travel mileage, and assists highway agencies because the exit numbering sequence does not have to be changed if new interchanges are added to a route. Moved to earlier in Section and revised

Option:

Exit numbers may also be used with Supplemental Guide signs, in compliance with Section 2E.50, and Motorist Service signs, in compliance with Chapters 2I and 2J.

Guidance:

Exit number (E1-5P) plaques should be added to the top right-hand edge of the sign for an exit to the right. Incorporated into following Standard.

Standard:

Where exit suffix letters are used and the number of exits are not equal in both directions of travel, the exit suffix lettering for each direction shall be based on the number of exits in that direction. For example, if in the northbound direction of a freeway there are three exits for interchange number 25 and two exits in the southbound direction, the exit numbers northbound shall be EXIT 25 A, EXIT 25 B and EXIT 25 C; and southbound shall be EXIT 25 B followed by EXIT 25 A (see Drawing D of Figure 2E-3).

Exit numbers and suffix letters shall only be used to designate individual exit departure points directly from the freeway mainline. Exit numbers and suffix letters shall not be used for designating ramp splits into two ramps after leaving the mainline (see Drawings A and D of Figure 2E-3).

The Exit Number (E1-5P through E1-5eP) plaque shall be positioned directly above the top right-hand edge of the sign for an exit to the right.

Because road users might not expect an exit to the left and might have difficulty in maneuvering to the left, a $\frac{1}{L}$ eft $\frac{1}{L}$ eft

2E-14 2E-34 and 2E-15 2E-18). The word LEFT on the E1-5bPLeft Exit Number plaque shall be a 2 black legend on a yellow rectangular sign panel and shall be centered above the word EXIT.

Figure 2E-3. Examples of Interchange Exit Numbering

Support:

1

3

4

5

6

7

8

9

10

11 12

13 14

15

16 17

18

19

20

21

22

23

24

25

26

27 28

29

30

31

32

33

34

35 36

37

38

39

40

41 42

43

44

Example exit number plaque designs are shown in Figure 2E 222E-9. Figures 2E 3, 2E 7, 2E 22, 2E 26, and 2E-27 2E-9, 2E-12, 2E-13, 2E-35, and 2E-41 illustrate the incorporation of exit number plaques on guide signs.

Figure 2E-4 provides an example of Interstate route loops and spurs around major metropolitan areas. The general plan for numbering interchange exits is shown in Figures 2E-19-2E-5 through 2E-212E-8. Figure 2E 19-2E-5 shows a circumferential route, which is a route that makes a complete circle around a city or town and usually has two interchanges (one on each side of the city or town) with each of the mainline routes that travel through the city or town. Figure 2E-20-2E-6 shows a loop route, which is a route that departs from a mainline route and then rejoins the same mainline route at a subsequent point downstream, and Figure 2E-7 shows a spur route, which is a route that departs from a mainline route and never rejoins the same mainline route. For the purpose of Interstate route numbering, a three-digit Interstate route that provides connectivity between two different Interstate routes is defined as a loop. Figure 2E-21-2E-8 shows two mainline routes that overlap each other.

Standard:

Regardless of whether a mainline route originates within a State or crosses into a State from another State, the southernmost or westernmost terminus within that State shall be the beginning point for interchange numbering.

For circumferential routes, interchange numbering shall be in a clockwise direction. The numbering shall begin with the first interchange west of the south end of an imaginary north-south line bisecting the circumferential route, at a radial freeway or other Interstate route, or some other conspicuous landmark in the circumferential route near a south polar location (see Figure 2E-192E-5).

The interchange numbers on loop routes shall begin at the loop interchange nearest the south or west mainline junction and increase in magnitude toward the north or east mainline junction (see Figure **2E-202E-6**).

Spur route interchanges shall be numbered in ascending order starting at the interchange where the spur leaves the mainline route (see Figure 2E-202E-7).

If a circumferential, loop, or spur route crosses State boundaries, the numbering sequence shall be coordinated by the States to provide continuous interchange numbering.

Where numbered routes overlap, continuity of interchange numbering shall be established for only one of the routes (see Figure 2E-212E-8). If one of the routes is an Interstate and the other route is not an Interstate, the Interstate route shall maintain continuity of interchange numbering.

Guidance:

The route chosen for continuity of interchange numbering should also have reference location sign continuity (see Figure 2E-212E-8).

Figure 2E-4. Examples of Interchange Loops and Spurs

Figure 2E-5. Example of Interchange Numbering for Mainline and Circumferential Routes Figure 2E-6. Example of Interchange Numbering for Mainline and Loop Routes Figure 2E-7. Example of Interchange Numbering for Mainline and Spur Routes

Figure 2E-8. Example of Interchange Numbering for Overlapping Routes

- Section 2E.32 Interchange Classification This section relocated to new Section 2E.11
- 45 Section 2E.33 2E.23 Advance Guide Signs (E1 Series)
- 46 Support:
- 47 An Advance Guide guide sign (see Figure 2E-22E-9) gives notice well in advance of the exit point of the 48 principal destinations served by the next interchange and the distance to that interchange.
- 49 **Standard:**

Except as provided in Paragraph 15 of this Section, and in Section 2E.24, at least one Advance guide sign shall be used for all interchange classifications.

Guidance:

 For At major and intermediate interchanges (see Section 2E.322E.11), at least two Advance Guide signs should be used, placed at 1/2 mile and at 1 mile in advance of the exit. with a A third Advance Guide sign should be placed at 2 miles in advance of the exit if spacing permits.

At minor interchanges, only one the Advance G_g uide sign should be used. It should be located 1/2 to 1 mile from the exit gore.

Support:

Sections 2E.29 through 2E.43 contain additional provisions regarding the number, location, and mounting of Advance guide signs for certain interchange configurations.

Guidance:

If the Where an Advance guide sign is located less than 1/2 mile from the exit, the distance displayed should be to the nearest 1/4 mile. Where the distance to be displayed on an Advance guide sign is less than 1/4 mile, the distance should be displayed in feet, rather than miles, to the nearest 100 feet. Fractions of a mile, rather than decimals, should be displayed in all cases. Moved to next Standard

Standard:

<u>Fractions of a mile, rather than decimals, shall be displayed in all cases.</u> Changed from Guidance to Standard

<u>For numbered exits to the right, an Exit Number (E1-5P through E1-5eP) plaque (see Figure 2E-9)</u> shall be added to the top right-hand edge of the sign.

For numbered exits to the left, a <u>Left eExit nNumber (E1-5bfP through E1-5kP</u>) plaque (see Figure <u>2E-222E-9</u>) shall be added <u>directly above to</u> the top left-hand edge of the sign.

For non-numbered exits to the left, a LEFT (E1-5amP) plaque (see Figure 2E-222E-9) shall be added to the top left-hand edge of the sign.

Figure 2E-9. Examples of Interchange Advance Guide Signs, Exit Number Plaques, and LEFT Plaque

Support:

Section 2E.312E-22 contains additional information regarding exit numbering.

Standard:

Advance Guide signs for multi-lane exits having an optional exit lane that also carries the through route (see Figures 2E-4_2E-36, 2E-5_2E-37, 2E-82E-42, and 2E-92E-43) and for splits with an option lane (see Figures 2E-6_2E-38 and 2E-10_2E-44) shall be Overhead Arrow-per-Lane or diagrammatic signs designed in accordance with Sections 2E.202E.39 through 2E.222E.41.

Except as provided in Section 2E.242E.36, the legend on Advance Gguide signs, if used, shall contain the distance message. Except as provided in Paragraph 8 of this SectionFor each direction of travel, the legend on the Advance Gguide signs shall be the same as the legend on the Exit Direction sign, except that the last line shall be the distance message. The distance message and shall read XX MILE(S) where exit numbers are used. Where interchange exit numbers are not used, the distance message shall read EXIT XX MILE(S) for an interchange with one exit ramp, and EXITS XX MILE(S) for an. If the interchange has with two or more exit ramps. roadways, the bottom line shall read EXITS XX MILES.

Guidance:

Where interchange exit numbers are used, the word EXIT(S) should be omitted from the bottom line.

45 Incorporated into preceding Standard

Option:

Where the distance between interchanges is more than 1 mile, but less than 2 miles, the first Advance Guide sign may be closer than 2 miles, but not placed so as to overlap the signing for the previous exit. Duplicate Advance Guide signs or Interchange Sequence Series signs may be placed in the median on the opposite side of the roadway and are not included in the minimum requirements of interchange signing.

1 *Guidance*:

2

3 4

5

6

7

8

Where there is less than 800 feet between <u>the theoretical gores of successive</u> interchange<u>s entrance or exit ramps</u>, Interchange Sequence Series signs (see Section <u>2E.40</u>2E.24) should be used instead of Advance Guide signs for the affected interchanges.

The Advance Guide signs for the last exit from a highway before it becomes a facility on which toll payments are required should include the LAST EXIT BEFORE TOLL (W16-16P) plaque (see Section 2F.10 and Figure 2F-34). The plaque should be installed above the Advance Guide signs, but below the Exit Number or LEFT plaque, if used.

9 Option:

10 If there is insufficient space above the Advance Guide sign because of the presence of an exit number plaque, the W16-16P plaque may be installed below the Advance Guide sign.

- 12 Section 2E.34 Next Exit Plaques This section relocated to new Section 2E.45
- 13 Section 2E.35 Other Supplemental Guide Signs This section relocated to new Section 2E.50
- 14 Section 2E.36 Exit Direction Signs This section relocated to new Section 2E.25
- 15 Section 2E.37 Exit Gore Signs (E5-1 Series) This section relocated to new Section 2E.26
- 16 Section 2E.38 Post-Interchange Signs This section relocated to new Section 2E.46
- 17 Section 2E.39 Post-Interchange Distance Signs This section relocated to new Section 2E.48
- 18 Section 2E.40 2E.24 Interchange Sequence Signs (E9-1 Series, E9-2 Series)
- 19 OptionSupport:

20

21

2223

24

25

26

27

28

29

30

31

32

33

34

35

3637

38

39

40

41 42

43

44

45

46

If iInterchanges are <u>sometimes</u> closely spaced, particularly through large urban areas, so that <u>typical</u> guide signs cannot be adequately spaced. <u>In such cases</u>, Interchange Sequence signs identifying the next two or three interchanges <u>can provide the necessary exit destination guidance</u>. <u>may be used</u>.

Guidance:

If Where there is less than 800 feet between interchanges, the theoretical gores of successive interchange entrance or exit ramps, Interchange Sequence Series signs (see Section 2E.24) should be used instead of Advance Guide signs for the affected interchanges. Relocated from below and revised

If used, Interchange Sequence signs should be used over the entire length of a route in an urban area. Except as provided in Paragraph 3 of this Section, they should not be used on a single interchange basis.

If there is less than 800 feet between interchanges, Interchange Sequence signs should be used instead of the Advance Guide signs for the affected interchanges. Relocated above and revised

Support:

Interchange Sequence signs are generally supplemental to Advance Gguide signs. Signing of this type is illustrated in Figures 2E-30 2E-10 and 2E-31 2E-11, and is compatible with the sign spreading concept described in Paragraph 3 of Section 2E.112E.43.

These signs are installed in a series and display the next two or three interchanges by name or route-number with distances to the nearest 1/4 mile. Incorporated into following Standard

Standard:

Except as provided in Paragraph 3, Interchange Sequence signs, shall be installed in a series.

Interchange Sequence signs shall display the next two or three interchanges by name or route number with distances to the nearest 1/4 mile.

If used, tThe first Interchange Sequence sign in the series shall be located in advance of the first Advance Gguide sign for the first interchange.

Where the exit direction is to the left, a LEFT (E11-2) sign panel (see Figure 2E-132E-18) shall be displayed on the same line immediately to the right of the interchange name or route number.

Interchange Sequence signs shall not be substituted for Exit Direction signs.

Guidance:

1 Interchange Sequence signs should be located in the median. After the first of the series, Interchange 2 Sequence signs should be placed approximately midway between interchanges. 3 **Standard:** 4 Interchange Sequence signs located in the median shall be installed at overhead sign height (see 5 Section 2A.18). 6 Option: 7 Interchange numbers may be displayed to the left of the interchange name or route number. 8 Figure 2E-10. Examples of an Interchange Sequence Sign 9 Figure 2E-11. Example of Use of an Interchange Sequence Sign for Closely Spaced 10 **Interchanges** Section 2E.41 Community Interchanges Identification Signs This section relocated to new Section 11 12 2E.51 Section 2E.42 NEXT XX EXITS Sign This section relocated to new Section 2E.52 13 Section 2E.43 Signing by Type of Interchange This section relocated to new Section 2E.29 14 Section 2E.36 2E.25 Exit Direction Signs (E4 Series) 15 16 Support: 17 The Exit Direction sign (see Figure 2E-26 2E-12) repeats the route and destination information that was displayed on the Advance Guide sign(s) for the next exit, and thereby assures road users of the destination 18 19 served and indicates whether they exit to the right or left for that destination. 20 **Standard:** 21 Exit Direction signs shall be used at major and intermediate interchanges. Populations or other 22 similar information shall not be displayed on Exit Direction signs. 23 24 Exit Direction signs should be used at minor interchanges (see Section 2E.30). 25 Support: 26 Sections 2E.29, 2E.33, 2E.37, 2E.39, and 2E.41 through 2E.43 contain additional provisions regarding the use, location, and mounting of Exit Direction signs for certain interchange configurations. The placement 27 location of the Exit Direction sign at the interchange depends on how it is mounted, post-mounted or 28 29 overhead, and whether there is a deceleration lane (see Figure 2E-14) 30 Guidance: 31 When Prost-mounted, the Exit Direction signs should be installed at the beginning of the deceleration lane 32 (see Figure 2E-14). If there is less than 300 feet from the upstream end of the deceleration lane to the 33 theoretical gore (see Figure 3B-8), the Exit Direction sign should be installed overhead over the exiting lane 34 in the vicinity of the theoretical gore. 35 Standard: 36 Except where Overhead Arrow-per-Lane guide signs are used (see Sections 2E.212E.40 and 2E.42, 37 and Paragraph 67 of this Section), where a through lane is being terminated (dropped) at an exit, the 38 Exit Direction sign shall be placed overhead at the theoretical gore (see Figures 2E-8 through 2E-11, 39 and 2E-14 through 2E-16). (see Figures 2E-18, 2E-19, 2E-26, 2E-34, and 2E-42 through 2E-44). 40 Except as provided in Paragraph 4 in of Section 2E.212E.40, where Overhead Arrow-per-Lane guide signs are used for the Advance Gguide sign(s) for a multi-lane exit having an optional exit lane 41 42 that also carries the through route or for a split with an option lane (see Section 2E.212E.40), an 43 Overhead Arrow-per-Lane guide sign shall also be used instead of the Exit Direction sign. This 44 Overhead Arrow-per-Lane guide sign shall include the appropriate exit number (E1-5P or E1-5bP) 45 plaque (if a numbered exit) and it shall be and located near, but not downstream from, the point where the outside edge of the dropped lane begins to diverge from the mainline main roadway (see Figures 2E-46 47 4-2E-36 through 2E-6 2E-38). The Overhead Arrow-per-Lane guide sign shall be designed in accordance with the provisions of Section 2E.40. 48

The following provisions shall govern the design and application of overhead Exit Direction signs:

- A. The sign shall <u>carry display</u> the <u>eExit nNumber plaque</u> (if exit numbering is used), the route number, cardinal direction, and destination, as applicable, with a diagonally upward-pointing directional arrow (see Figure <u>2E-26 2E-12</u>).
- B. The message EXIT ONLY in black on a yellow sign panel (E11-1d or E11-1e) shall be used on the overhead Exit Direction sign to advise road users of a lane drop situation (see Figures 2E-8-through 2E-11 2E-42 through 2E-44 and 2E-46). The sign shall comply with the provisions of Section 2E.24 2E.28.

Figure 2E-12. Examples of Interchange Exit Direction Signs

Figure 2E-13. Examples of Interchange Exit Direction Signs with an Advisory Speed Panel Figure 2E-14. Exit Direction Sign Placement

Guidance:

For numbered exits to the right, an exit number (E1-5P) plaque (see Figure 2E-22) should be added to the top right hand edge of the sign. Incorporated into following Standard

Standard:

For numbered exits to the right, an Exit Number (E1-5P) plaque (see Figure 2E-9) shall be added to the top right-hand edge of the sign.

For numbered exits to the left, a \underline{L} eft \underline{eE} xit \underline{nN} umber (E1-5bP) plaque (see Figure $\underline{2E-22}\underline{2E-9}$) shall be added to the top left-hand edge of the sign.

For non-numbered exits to the left, a LEFT (E1-5aP) plaque (see Figure 2E-229) shall be added to the top left-hand edge of the sign.

Support:

Section 2E.312E.22 contains additional information regarding exit numbering.

Option:

In some cases, principally in urban areas, where restricted sight distance because of structures or unusual alignment make it impossible to locate the Exit Direction sign without violating the required minimum spacing (see Section 2E.33) between major guide signs, Interchange Sequence signs (see Section 2E.40) may be substituted for an Advance Guide sign. Relocated to later in Section

Guidance:

At multi-exit interchanges, the Exit Direction sign should be located directly over the exiting lane for the first exit, in accordance with this Section. An Advance guide sign for the second exit should be installed Aat the same location, and normally over the right-hand through lane, an Advance Guide sign for the second exit should be located. Only for those conditions where the through movement is not evident should a confirmatory message (Pull-Through sign as shown in Figure 2E-2_2E-16) be used over the left-hand lane(s) to guide road users traveling through an interchange. In the interest of sign spreading (see Section 2E.43), three-more than two signs on one structure should not be used. When Where the freeway or expressway is on an overpass, the Exit Direction sign for the second exit should be installed on an overhead support over the exit lane in advance of the gore point, as near as practicable to the theoretical gore.

Where the freeway or expressway passes under the crossroad and the exit roadway is located beyond the overcrossing structure, the overhead Exit Direction sign for the second exit should be placed either on the overcrossing structure (see Figures 2E-29 through 2E-31) or on a separate structure located immediately in front of the overcrossing structure.

Option:

If the second exit is beyond an underpass, the Exit Direction sign may be mounted on the face of the overhead structure. Incorporated into preceding Guidance above and reworded

Where extra emphasis of an especially low advisory ramp speed is needed, an EXIT XX MPH (E13-2) sign panel (see Figure 2E-272E-13) may be placed at the bottom of the Exit Direction sign to supplement, but not to replace, the exit or ramp advisory speed warning signs.

Warning Beacons in compliance with Paragraph 17 may be used with the E13-2 sign panel.

Standard:

Where Warning Beacons are used in conjunction with the E13-2 sign panel within a guide sign (see Figure 2E-13), the nearest edges of the beacons shall be placed at least 12 inches from the edges of the E13-2 sign panel, from the edges of the guide sign, and from any other legend within the guide sign. The design and operation of Warning Beacons shall otherwise comply with the provisions of Chapter 4L of this Manual.

Option:

 In some cases, principally in urban areas, where restricted sight distance is restricted because of structures or unusual alignment, principally in urban areas, makinge it impossible to locate the Exit Direction sign without violating the required minimum spacing (see Section 2E.33) between major guide signs (see Section 2E.23), Interchange Sequence signs (see Section 2E.4024) may be substituted for an Advance Guide sign.

Relocated from earlier in Section and reworded

12 Guidance:

At the last exit from a highway before it becomes a facility on which toll payments are required, the LAST EXIT BEFORE TOLL (W16-16P) plaque (see Section 2F.10 and Figure $2F-\frac{3}{4}$) should be installed above the Exit Direction sign, but below the Exit Number or LEFT plaque, if used.

16 Option:

If there is insufficient space above the Exit Direction sign because of the presence of an Exit Number (E1-5P) plaque, the W16-16P plaque may be mounted below the Exit Direction sign.

Section 2E.37 2E.26 Exit Gore Signs and Plaque (E5-1 Series)

20 Support:

The Exit Gore (E5 1 or E5 1a) sign (see Figure 2E 28 2E-15) in the gore indicates the exiting point or the place of departure from the main roadway. Consistent application of this sign at each exit is important to provide adequate visibility of the departure of the exit roadway from the main roadway.

Standard:

The gore shall be defined as the area located between the main roadway and the ramp just beyond where the ramp branches from the main roadway. The An Exit Gore sign shall be located in the gore for each ramp that departs from the main roadway of a freeway or expressway and shall earry-display the word EXIT (E5-1) if interchange numbering is not used or EXIT XX (E5-1a, E5-1c) if interchange numbering is used, and an appropriate upward slanting arrow. If suffix letters are used for exit numbering at a multi-exit interchange, the suffix letter shall also be included on the Exit Gore sign (E5-1a, E5-1c) or Exit Gore Number (E5-1bP) plaque and shall be separated from the exit number by a space having a width of between 1/2 and 3/4 of the height of the suffix letter. Breakaway or yielding supports shall be used.

Guidance:

The arrow should be aligned to approximate the angle of departure. Each gore should be treated similarly, whether the interchange has one exit roadway or multiple exits.

Option:

The Narrow Exit Gore (E5-1c) sign (see Figure 2E-15) may be used in gore areas of limited width where the width of the Exit Gore (E5-1a) sign would not permit sufficient lateral offset (see Section 2A.1921), such as for ramp departures that are nearly parallel to the main roadway where the Exit Gore sign would be mounted on a narrow island or barrier. Where the E5-1c sign is mounted at a height of 14 feet or more from the roadway, the directional arrow may point diagonally downward. Relocated from later in this section *Guidance:*

The E5-1c sign should not be used in gore areas where an E5-1a sign could be installed with sufficient lateral offset. Relocated from later in this section

46 Option:

Where extra emphasis of an especially low advisory ramp speed is needed, an E13 1Pthe Confirmation Advisory Speed (W13-1aP) plaque (see Section 2C.59) indicating the advisory speed may be mounted below the Exit Gore sign (see Figure 2E-28_2E-15) to supplement, but not to replace, the exit or ramp advisory speed warning signs.

To improve the visibility of the gore for exiting drivers, a Type 1 object marker (see Chapter 2C) may be installed 4 feet above the ground line on each sign support below the Exit Gore sign.

An Exit <u>Gore Number</u> (E5-1bP) plaque (see Figure <u>2E-222E-9</u>) may be installed above an existing Exit Gore (E5-1) sign when a non-numbered exit is converted to a numbered exit.

Standard:

 An Exit Gore (E5-1a) sign shall be used when the replacement of an existing assembly of an E5-1 sign and an E5-1bP plaque becomes necessary.

Option:

The Narrow Exit Gore (E5-1c) sign may be used in gore areas of limited width where the width of the Exit Gore (E5-1a) sign would not permit sufficient lateral offset (see Section 2A.19), such as for ramp-departures that are nearly parallel to the mainline roadway where the Exit Gore sign would be mounted on a narrow island or barrier. Where the E5-1c sign is mounted at a height of 14 feet or more from the roadway, the directional arrow may point diagonally downward. Relocated to earlier in this section

Guidance:

The E5-1c should not be used in gore areas where an E5-1a sign could be installed with sufficient lateral offset.

Relocated to earlier in this section

Figure 2E-15. Exit Gore Signs and Plaques

Section 2E.12 2E.27 Pull-Through Signs (E6-2,1 Series, E6-2a Series)

19 Support:

Pull-Through (E6-2,1 series and E6-2a series) signs (see Figure 2E-2 2E-16) are overhead guide signs intended for through traffic.

Guidance:

Pull-Through signs should be used where the geometrics of a given interchange are such that it is not clear to the road user as to which is the through roadway, or where additional route guidance is desired. Pull-Through signs with down arrows should be used where the alignment of the through lanes is curved and the exit direction is straight ahead, where the number of through lanes is not readily evident, and at multilane exits where there is a reduction in the number of through lanes. Pull-Through signs should not be used at exits with options lanes which use Overhead Arrow-Per-Lane or Diagrammatic guide signs.

Support:

Sections <u>2E.28 and Sections <u>2E.202E.39</u> through <u>2E.24 2E.42</u> contain information regarding the use of Overhead Arrow-per-Lane or Diagrammatic guide signs at multi-lane exits where there is a reduction in the number of through lanes and a through lane becomes an interior option lane for through or exiting traffic.</u>

Figure 2E-16. Pull-Through Signs

Section 2E.24 2E.28 Signing for Interchange Lane Drops

35 Standard:

The provisions of this Section shall only apply to lane drops at exits that do not have an optional exit lane. At exits that have an optional exit lane in addition to the dropped lane, the provisions of Sections 2E.202E.39 through 2E.232E.42 shall apply.

Except as provided in Paragraph 13 of this Section, Mmajor guide signs for all lane drops at interchanges shall be mounted overhead. An EXIT ONLY sign panel shall be used for all interchange lane drops at which the through route is carried on the mainlinemain roadway.

Except on Overhead Arrow-per-Lane and Diagrammatic guide signs (See Sections 2E.202E.39 through 2E.222E.41), the EXIT ONLY (down arrow) (E11-1 or E11-1f) sign panel (see Figure 2E-132E-17) shall be used on all signing of lane drops on all overhead Advance Guide signs of lane drops (see Figures 2E-14 through 2E-16 2E-18, 2E-19, and 2E-34). The number of arrows on each sign shall correspond to the number of dropped lanes at the location of each sign. Placement of the down arrow shall comply with the provisions of Section 2E.192E.18.

For lane drops, the Exit Direction sign (see Section 2E.362E.25 and Figure 2E-262E-12) shall be of the format shown in Figures 2E-15 2E-18 and 2E-162E-19. The bottom portion of the Exit Direction sign shall be yellow with a black border and shall include a diagonally upward-pointing black directional arrow (left or right) for each lane dropped at the exit, with the sign designed and placed so that each arrow is located over the approximate center of each lane being dropped. The Except as provided in Paragraph 5 of this Section, the words EXIT and ONLY shall be positioned to the left and right, respectively, of the arrow on the E11-1d sign panel for a single-lane drop. For a two-lane drop, the words EXIT ONLY shall be located between the two arrows on the E11-1e sign panel. The number of arrows on the sign shall correspond to the number of dropped lanes at the location of the sign.

Option:

Where an existing sign structure length or adjacent signs constrain the width or placement of the Advance guide sign on that structure, the down arrow may be positioned to the right or left of the words EXIT ONLY, in lieu of between the words, to allow for the positioning of the arrow over the approximate center of the lane. Where the width of the Exit Direction sign extends over the adjacent lane, the directional arrow may be placed to the right of the words EXIT ONLY for an exit to the right, or to the left of the words EXIT ONLY for an exit to the left, to allow for the positioning of the arrow over the dropped lane.

EXIT ONLY messages of either the combination of E11-1a and E11-1b, or <u>the E11-1c formats sign</u> <u>panels</u> may be used to retrofit existing signing to warn of a lane drop situation ahead.

Standard:

If used to retrofit an existing Advance Guide guide sign, the E11-1a and E11-1b sign panels (see Figure 2E-13 2E-17) shall be placed on either side of a white down arrow on an Advance guide sign and on either side of a white directional arrow on an Exit Direction sign. The E11-1c sign panel, if used to retrofit an existing Advance guide sign, shall be placed between the lower destination message and the white down arrow.

Guidance:

Except as provided in Paragraph <u>89 of this Section</u> for an auxiliary lane, Advance <u>G</u>guide signs for lane drops within 1 mile of the interchange should not <u>contain display</u> the distance message.

Where the dropped lane is an auxiliary lane that is provided between successive entrance and exit ramps of two separate interchanges and the distance between the two ramps is less than 1 mile, the first Advance Guide sign in the sequence downstream from the entrance ramp should contain display the distance message (See Figures 2E-20 and 2E-21).

Where ver the dropped lane carries the through route, signs should be used without the EXIT ONLY sign panel.

Support:

Figure 2E-20 and 2E-21 shows an example of guide sign for a dropped auxiliary lane between separate interchanges using overhead and post-mounted guide signs. Figure 2E-22 shows guides signs used for an auxiliary lane that is ½ mile or longer.

Sections $\frac{2E.20}{2E.39}$ through $\frac{2E.23}{2E.42}$ contain information on the signing of lane drops at exits that also have an option lane.

Section 2B.23 contains information regarding regulatory signs that can also be used for freeway lane drop situations and Section 2C.43 contains information regarding warning signs that can also be used for freeway lane drop situations.

Figure 2E-17. EXIT ONLY and LEFT Sign Panels

Figure 2E-18. Guide Signs for a Single-Lane Exit to the Left with a Dropped Lane
Figure 2E-19. Guide Signs for a Single-Lane Exit to the Right with a Dropped Lane
Figure 2E-20. Example of Guide Signs for a Dropped Auxiliary Lane between Separate
Interchange Ramps

Figure 2E-21. Example of Post-Mounted Advance Guide and Supplemental Warning Signs for a Dropped Auxiliary Lane Between Separate Interchange Ramps

Figure 2E-22. Example of Guide Signs for an Auxiliary Lane One-Half Mile or Longer Figure 2E-23. Examples of Signing for Mainline Lane Terminations within an Interchange

1 2 Guidance:

3

4 5

6

7 8

9

10

11

12

13

14

15 16

17 18

19

20

21

22

23

24

25

26

2.7

28

29

31

32 33 In limited cases in which conditions are so constrained that it is impossible to locate an Advance guide sign either overhead or partly over the dropped lane, precluding positioning of the down arrow as provided in Paragraph 5 of this Section, a sign panel displaying the legend RIGHT (LEFT) LANE ONLY in a black legend on a yellow background should be substituted for the EXIT ONLY panel on that sign. In such cases, the Advance guide signs should be alternated with Right Lane for Exit Only (W9-7 series) signs (see Section 2C.43).

Where a mainline lane is dropped immediately after an exit ramp, overhead and or post mounted warning signs should be used to warn traffic as shown in Figure 2E-23.

Section 2E.43 2E.29 Signing by Type of Interchange

Support:

Road users need signs to help identify the location of the exit, as well as to obtain route, direction, and destination information for specific exit ramps. Figures 2E-34 through 2E-40 2E-26 through 2E-33 show examples of guide signs for common types of interchanges. The interchange layouts shown in most of the figures illustrate only the major guide signs for one direction of traffic on the freeway and on the exit ramps. Section 2D.45 contains information regarding the signing of the crossroad approaches and connecting roadways to freeways and expressways.

Standard:

Interchange guide signing shall be consistent for each type of interchange along a route.

Guidance:

The signing layout for all interchanges of the same type having only one exit ramp in the direction of travel-should be similar, regardless of the interchange type. For the sake purpose of uniform application, the significant features of the signing plan for each of the more frequent kinds of interchanges (illustrated in Figures 2E-34 through 2E-40 2E-26 through 2E-33) should be followed as closely as possible. Even when unusual geometric features exist, variations in signing layout should be held to a minimum.

Where a single interchange combines a different type of ramp configuration for each direction of travel, the main roadway major guide signing should be determined by the specific interchange type for that direction of travel.

30 Support:

Figure 2E-24 shows an example of signing for a complex interchange that combines intermediate interchange ramps within a major interchange.

Figure 2E-25 shows an example of signing for an interchange exit ramp with a downstream split.

Figure 2E-24. Example of Signing for an Intermediate Interchange within a Major Interchange

Figure 2E-25. Example of Signing for an Interchange Exit Ramp with a Downstream Split

Section 2E.44 <u>Freeway-to-Freeway Interchange</u> This section has been relocated to new Section 2E.37.

39 Section 2E.45 Cloverleaf Interchange This section has been relocated to new Section 2E.33.

40 Section 2E.46 Cloverleaf Interchange with Collector-Distributor Roadways
41 been relocated to new Section 2E.34.

42 Section 2E.47 Partial Cloverleaf Interchange This section has been relocated to new Section 2E.35.

43 Section 2E.48 Diamond Interchange This section has been relocated to new Section 2E.31.

Section 2E.49 Diamond Interchange in Urban Area This section has been relocated to new Section

45 2E.32.

1	Section 2E.50 Closely-Spaced Interchanges This section has been relocated to new Section 2E.44.
2	Section 2E.51 2E.30 Minor Interchange
3	Option:
4 5	Less signing may be used for minor interchanges because such interchanges customarily serve low volumes of local traffic.
6	Support:
7	Examples of guide signs for minor interchanges are shown in Figure 2E-40 2E-26.
8	Standard:
9	In accordance with the provisions of Sections 2E.23, Aat least one Advance Guide sign and an Exit
10	Gore sign shall be used at a minor interchange.
11	Guidance:
12	An Exit Direction sign in compliance with Section 2E.25 should also be used.
13	Figure 2E-26. Examples of Guide Signs for a Minor Interchange
14	Section 2E.48 2E.31 Diamond Interchange
15	Support:
16	Examples of guide signs for diamond interchanges are shown in Figure 2E-38 2E-27.
17	Standard:
18	For numbered exits, the singular message EXIT shall be used on the Exit Number plaques (see
19	Section 2E.31) with the Advance Guide and Exit Direction signs. For non-numbered exits, the singular
2021	message EXIT shall be used as part of the distance message on the Advance Guide signs.
22	Support: The trained diamond interchange rooms deports from the mainline readyray such that a smead reduction
23	The typical diamond interchange ramp departs from the main line roadway such that a speed reduction generally is not necessary in order for a driver to negotiate an exit maneuver from the main line roadway onto
24	the ramp roadway. Section 2C.14 contains the provisions for the use of an Advisory Exit Speed (W13-2) sign
25	where a speed reduction is necessary.
26	Guidance:
27	When a speed reduction is not necessary, an <u>Advisory exit-Exit speed-Speed</u> sign should not be used.
28	Option:
29	An Advisory Exit Speed sign may be used where an engineering study shows that it is necessary to
30	display a speed reduction message for ramp signing (see Section 2C.14).
31	Guidance:
32	The Advisory Exit Speed sign, if used, should be located along the deceleration lane or along the ramp
33 34	such that it is visible to the driver far enough in advance to allow the driver to decelerate before reaching the curve associated with the exiting maneuver. <u>Use and placement of the Advisory Exit Speed sign should</u>
35	otherwise comply with Section 2C.14 of this Manual.
36	Option:
37	A Stop Ahead (W3-1) or Signal Ahead (W3-3) warning sign may be placed, where engineering judgment
38	indicates a need, along the ramp in advance of the cross street, to give notice to the driver (see Section 2C.36).
39	Guidance:
40	When used on two-lane ramps, Stop Ahead or Signal Ahead signs should be used in pairs with one sign on
41	each side of the ramp.

sign (see Section 2D.37) should be placed along the ramp that include each destination displayed on the Advance, Exit Direction, and Supplemental guide signs along the main roadway for that exit.

Where the exit ramp allows traffic to turn in either direction onto the crossroad, a Destination (D1 series)

42

43

44

Section 2E.49 2E.32 <u>Diamond Interchange in Urban Area</u>

Support:

1

2

3

4

5

6

7

8

9

10

11

12

14

15

16 17

18

19

20

21

22

23

24 25

26

27

28

29

30

31

32

33

34 35

36

37

42

43 44

45

46

Examples of guide signs for diamond interchanges in an urban area are shown in Figure 2E-39 2E-28. This example includes the use of the Community Interchanges Identification sign (see Section 2E.412E.51), which might be useful if two or more interchanges serve the same community.

In urban areas, street names are often displayed as the principal message in destination signs.

Option:

If interchanges are too closely spaced to properly locate the Advance Guide signs at the distances specified in Section 2E.23, they may be placed closer to the exit with the distances displayed adjusted accordingly.

Figure 2E-28. Examples of Guide Signs for a Diamond Interchange in an Urban Area

Section 2E.45 2E.33 Cloverleaf Interchange

13 Support:

A cloverleaf interchange has two exits for each direction of travel. The exits are closely spaced and have common Advance Guide signs. Examples of guide signs for cloverleaf interchanges are shown in Figure 2E-35 2E-29.

Guidance:

The Advance Guide signs should include two place names, one corresponding to each exit ramp, with the name of the place served by the first exit on the upper line.

Standard:

An overhead guide sign <u>assembly</u> shall be placed at the theoretical gore of the first exit ramp, with a diagonally upward-pointing directional arrow on the an Exit Direction sign for that exit and the an message XX MILES, or EXIT XX MILES if interchange numbering is not used, on the Advance Guide sign for the second exit, as shown in Figure 2E-352E-29. The second exit shall be indicated by an overhead Exit Direction sign over the auxiliary lane. An Exit Gore sign shall also be used at each gore (see Section 2E.37).

Interchanges with more than one exit from the main <a href="https://linearcollege.com/linearcollege.co

Diagrammatic signs shall not be used for cloverleaf interchanges except as otherwise provided in Section 2E.222E.41.

Guidance:

Where the <u>mainline main roadway</u> passes under the crossroad and the exit roadway is located beyond the overcrossing structure, <u>placement of</u> the overhead Exit Direction sign for the second exit should <u>be placed</u> either on the overcrossing structure comply with Section 2E.25 (see Figure 2E-352E-29) or on a separate structure located immediately in front of the overcrossing structure.

Figure 2E-29. Examples of Guide Signs for a Full Cloverleaf Interchange

Section 2E.46 2E.34 Cloverleaf Interchange with Collector-Distributor Roadways

38 Support:

Examples of guide signs for full cloverleaf interchanges with collector-distributor roadways are shown in Figure 2E-362E-30.

41 Guidance:

Signing on the collector-distributor roadways should be the same as the signing on the <u>mainline main</u> <u>roadway</u> of a cloverleaf interchange.

Standard:

Guide Exit Direction signs at exits from the collector-distributor roadways shall be overhead and located at the theoretical gore of the collector-distributor roadway and the exit ramp.

Option Guidance:

1

2

3

4

5

6

7 8

9

10 11

12

14

16

17

18

19

21

23

24

25

26

28

29

31

32

33

34

35

36

37

38

39

40

41

42

43 44

45

Exits from the collector-distributor roadways may should be numbered with an appropriate suffix. If the exits from a collector-distributor roadway are numbered with suffixes, the Advance Guide and Exit Direction signs on the mainline main roadway may should include, in addition to two place names, and their corresponding exit numbers and suffixes with the plural EXITS in the Exit Number (E1-5P series) plaque. If only the exit from the mainline roadway is numbered, the Advance guide and Exit Direction signs on the main roadway should use the singular EXIT in the Exit Number plaque. or ilf interchange numbering is not used, the Advance Guide signs on the mainline main roadway may should use the singular EXIT in the distance messages.

Figure 2E-30. Examples of Guide Signs for a Full Cloverleaf Interchange with Collector-Distributor Roadways

Section 2E.47 2E.35 Partial Cloverleaf Interchange

13 Support

Examples of guide signs for partial cloverleaf interchanges are shown in Figure 2E-37 2E-31.

15 Guidance:

For a partial cloverleaf with only one exit roadway in a direction of travel, Wwhere the main roadway passes under the crossroad and the exit roadway is located beyond the overcrossing structure, the overhead Exit Direction sign should be placed either on the overcrossing structure (see Figure 2E-372E-31) or on a separate structure located immediately in front of the overcrossing structure.

20 Standard:

A post-mounted Exit Gore sign shall also be installed in the ramp gore.

22 Support:

Partial cloverleaf interchanges with successive exit ramps from the same direction of travel are signed the same as cloverleaf interchanges for that direction of travel (see Section 2E.452E.33).

Figure 2E-31. Examples of Guide Signs for a Partial Cloverleaf Interchange

Section 2E.36 Collector-Distributor Roadways for Successive Interchanges

27 Support:

Examples of guide signs for a collector-distributor roadway that provides access to multiple interchanges are shown in Figure 2E-32.

30 Guidance:

Where access to successive interchanges is provided from a single collector-distributor roadway, the number of lines of destination information displayed on the major guide signs on the main roadway approach to the collector-distributor roadway should comply with the provisions of Section 2E.15. Where additional destinations are to be displayed on the main roadway, those destinations should be displayed on Supplemental guide signs (see Section 2E.50) on the approach to the collector-distributor roadway.

Where exit numbering is used, the exit numbers for exits accessed from the collector-distributor roadway should be displayed on the main roadway guide signs.

An Exit Gore sign (see Section 2E.26) should be placed in the gore where collector-distributor roadway departs from the main roadway.

Interchange guide signing along the collector-distributor roadway should comply with the provisions for interchange signing in this Chapter.

If services are available from more than one of the interchanges along the collector-distributor roadway and those services are signed, then General Service signs should be used on the main roadway in compliance with the provisions of Chapter 2I of this Manual. Services signed along the collector-distributor roadway

should use either General Service signs or Specific Service signs in compliance with the provisions of

46 Chapters 2I and 2J of this Manual.

Figure 2E-32. Examples of Guide Signs for Successive Interchanges with collector-Distributor 1 2 Roadways (2 Sheets) 3 Section **2E.44 2E.37** Freeway-to-Freeway Interchange 4 Support: 5 Freeway-to-freeway interchanges are major decision points where the effect of taking a wrong ramp cannot be easily corrected. Reversing direction on the connecting freeway or reentering to continue on the 6 7 intended course is usually not possible. Figure 2E-34-33 shows examples of guide signs at a freeway-to-8 freeway interchange. 9 Guidance: 10 The sign messages should contain only the route shield, cardinal direction, and the name of the next 11 control city on the route. Arrows should point as indicated in Section 2D.08, except where Overhead Arrow-12 per-Lane or Diagrammatic signs are used in accordance with the provisions of Sections 2E.202E.39 through 13 2E.222E.41. 14 Support: 15 At splits where the off-route movement is to the left or where there is an optional lane split, expectancy 16 problems usually result. 17 **Standard:** 18 At splits where the off-route movement is to the left, see Section 2E.22 for the use of the Left Exit Number (E1-5bfP through E1-5kP) plaque. shall be added at the top left-hand edge of the guide sign (see 19 20 Section 2E.31). Overhead Arrow-per-Lane or Diagrammatic guide signs (see Sections 2E.21 and 2E.22) 21 shall be used fFor freeway splits with an option lane and for multi-lane freeway-to-freeway exits having an 22 option lane, see Section 2E.39 for use of Overhead Arrow-per-lane or Diagrammatic guide signs. 23 **Standard:** 24 The roadway for the off-route shall be signed as an exit. If exit numbering is used, the signs shall 25 comply with the provisions of Section 2E.22. Distance messages on the Advance guide signs shall 26

comply with the provisions of Section 2E.23.

Overhead signs shall be used at a distance of 1 mile and at the theoretical gore of each connecting ramp, except as provided in Sections 2E.40 and 2E.41. When Overhead Arrow-per-Lane or Diagrammatic guide signs are used, they shall comply with the provisions of Sections 2E.21-40 and 2E.2241.

Option:

27

28

29 30

31

32

33

34

35

36

37

38

39

40

41

42

43

45

46 47

48

49

The Advance guide Overhead signs may also be used at the 1/2-mile and 2-mile locations may also be overhead-mounted.

The arrow and/or the name of the control city may be omitted on signs that indicate the straight-aheadcontinuation of a route on a Pull-Through sign (see Section 2E.12).

Guidance:

An Advisory Exit Speed (W13-2) sign may should be used where an engineering study shows that it is necessary to display a speed reduction message for ramp signing (see Section 2C.14).

Where extra emphasis of an especially low advisory ramp speed is needed, an EXIT XX MPH (E13-2) sign panel (see Figure 2E-27) may be placed at the bottom of the Exit Direction sign to supplement, but not toreplace, the exit or ramp advisory speed warning signs.

Figure 2E-33. Examples of Guide Signs for a Freeway-to-Freeway Interchange

Section 2E.38 Freeway Split with Dedicated Lanes

44 **Standard:**

> Signing for freeway splits with dedicated lanes shall use the sign designs shown in Figure 2E-34. The arrows on each Advance Guide sign shall match the number of lanes present at the location of the Advance Guide sign.

> The signs for this application shall be mounted overhead. When arrows are used, each arrow shall be located over the approximate center of the lane to which it applies.

Where one roadway of the split carries the through route, the other roadway of the split shall be signed as an exit. If exit numbering is used, the signs shall comply with the provisions of Section 2E.22. Distance messages on the Advance guide signs shall comply with the provisions of Section 2E.23.

The number and location of Advance guide signs shall comply with the provisions of Section 2E.23.

Guidance:

The Exit Direction and Pull-Through signs should be located at the theoretical gore.

The Exit Direction and Pull Through signs should display down arrows if the alignment is straight or diagonally upward pointing directional arrows if the alignment is curved (see Section 2D.08).

Standard:

The Exit Direction sign shall contain the EXIT ONLY (E11-l series) sign panel (see Section 2E.28).

Figure 2E-34. Guide Signs for a Split with Dedicated Lanes

Section **2E.202E.39** Signing for Option Lanes at Splits and Multi-Lane Exits

Support:

Some freeway and expressway splits or multi-lane exit interchanges contain an interior option lane serving both movements in which traffic can either leave the route or remain on the route, or choose either destination at a split, from the same lane.

Standard:

On freeways and expressways, either the Overhead Arrow-per-Lane or Diagrammatic guide sign designs as provided in Sections 2E.212E.40 and 2E.222E.41 shall be used for all multi-lane exits at major interchanges (see Section 2E.322E.11) that have an optional exit lane that also carries the through route (see Figures 2E-4, 2E-5, 2E-8, and 2E-9 2E-36, 2E-37, 2E-42, and 2E-43) and for all splits that include an option lane (see Figures 2E-6 2E-38 and 2E-102E-44). Overhead Arrow-per-Lane or Diagrammatic guide signs shall not be used on freeways and expressways for any other types of exits or splits, including single-lane exits and splits that do not have an option lane.

Guidance:

The Overhead Arrow-per-Lane guide sign design (see Section 2E.212E.40) should also be considered for multi-lane exits with an option lane at intermediate interchanges (see Section 2E.32 2E.11) based on such factors as the extent of the need to optimize the mainline operation by maximizing the usage of the option lane, the extent of the period(s) of the day during which the exiting volumes warrant the multi-lane exit arrangement, and the nature of the traffic that primarily uses the option lane during the high-volume periods.

Signing for multi-lane exits at minor interchanges (see Section <u>2E.322E.11</u>) that have an optional exit lane or at intermediate interchanges that have an optional exit lane at which it has been determined that the Overhead Arrow-per-Lane guide sign design is not warranted should use a combination of conventional guide signing and regulatory lane-use signing, in accordance with the provisions of Section <u>2E.232E.42</u>.

Section <u>2E.21</u>2E.40 <u>Design of Overhead Arrow-per-Lane Guide Signs for Option Lanes</u> Support:

Overhead Arrow-per-Lane guide signs (see Figure 2E-3 2E-35) are used where an option lane is present at freeway and expressway multi-lane exit interchanges and splits. They display an upward-pointing arrow above each lane that conveys the direction(s) of travel that the lane serves at the point of departure. At locations where an option lane is present at a multi-lane exit or split, Overhead Arrow-per-Lane guide signs have been shown to be superior to either conventional guide signs or Diagrammatic guide signs because they convey positive direction about which destination and direction each approach lane serves, particularly for the option lane, which is otherwise difficult to clearly sign.

Standard:

Overhead Arrow-per-Lane guide signs <u>as provided in Section 2E.39</u> shall be used <u>on at all new or reconstructed freeways and expressways <u>locations and at freeway and expressway locations where replacement of an existing sign support structure is necessitated by reconstruction, as described in Section 2E.2039.</u></u>

Where used, the Overhead Arrow-per-Lane guide sign at the exit or split shall be located at or in the immediate vicinity of the point where the exiting lanes begin to diverge from the through lanes or, for a split, at the point where the approach lanes begin to diverge from one another, preserving the relation of the arrows displayed on the sign to their respective lanes. The Overhead Arrow-per-Lane guide sign at the exit shall not be located at or near the theoretical gore.

Option:

At existing or non-reconstructed locations where <u>an overhead</u> Exit Direction—<u>and Pull Through</u> signs exists at the theoretical gore, <u>and</u> the existing sign support structure <u>is retained</u>, the <u>overhead Exit Direction sign</u> may remain—<u>in place</u>, or <u>may be replaced on the existing sign support structure continuing to use Exit Direction and Pull Through signs</u>, in conjunction with a replacement of the advance signs using the Overhead Arrow-per-Lane guide sign design.

Standard:

If existing Exit Direction and Pull-Through signs are being retained at an interchange as provided in Paragraph 4, an Overhead Arrow-per-Lane guide sign shall not be used at the location of the Exit Direction and Pull-Through signs at or in the vicinity of the theoretical gore. New installations of Exit Direction and Pull-Through signs shall not be permitted in conjunction with Overhead Arrow-per-Lane guide signs on new or reconstructed facilities.

Option:

For unusually long gore areas with narrow lane marking tapers, signs indicating the destinations allowed by each lane may be added to reinforce positive guidance (See Figure 2E-39).

Guidance:

Overhead Arrow-per-Lane guide signs should be located at approximately 1/2 mile and 1 mile in advance of the exit or split, and at approximately 2 miles in advance of the exit or split where space is available and conditions allow.

Standard:

Overhead Arrow-per-Lane guide signs used on freeways and expressways shall include one arrow above each lane and shall be designed in accordance with the following criteria:

- A. The sign shall include an upward-pointing arrow for each lane of the approach to the split or exit, and the shaft of each arrow shall be located approximately over the approximate center of the lane to which it applies.
- B. Arrows for continuing through lanes shall be vertically upward pointing (see Figure 2E-4 2E-36) unless those lanes are on a significantly curved alignment beyond the theoretical gore, in which case the arrows for the continuing through lanes shall indicate the approximate degree of curvature at the point of departure (see Figure 2E-52E-37).
- C. The arrow for a lane that must exit shall be curved in the direction of the exit and shall be accompanied by black-on-yellow EXIT (E11-1a) and ONLY (E11-1b) sign panels adjacent to the lower end of the arrow shaft. The E11-1a and E11-1b sign panels shall not be used for a split of two overlapping routes where neither of the diverging routes is designated as an exit. Where the through lanes curve and the exit continues on a straight alignment, upward-pointing vertical arrows shall be used for the exiting movement and curved arrows for the through movement.
- D. The arrow for an optional exit lane that also carries the through route shall have a single shaft that bifurcates into a vertically upward-pointing arrow and a curving arrow corresponding to the configuration of the through and exit lanes.
- E. For splits with an option lane, the arrow for the lane from which either direction of the split can be accessed shall have a single shaft that bifurcates into two upward-pointing curving arrows showing the approximate degrees of curvature of the two roadways beyond the theoretical gore (see Figure 2E-6 2E-38).
- F. A vertical white line shall be used to separate the route shields and destinations for the two diverging movements from each other.
- G. The distance to the exit or split shall be displayed below the off-movement destination on the advance signs at the 1-mile and 2-mile locations.

- H. The number of lanes displayed on a sign shall correspond to the number of lanes at the location of that sign. An advance sign shall not depict lanes that are added downstream of a sign location.
- I. For numbered exits, the Exit Number (E1-5P) or Left Exit Number (E1-5bP) plaque shall be used at the top of the sign in accordance with Section 2E.312E.23. For unnumbered left exits, the LEFT (E1-5aP) plaque shall be used at the top left edge of the sign.

Guidance:

 Overhead Arrow-per-Lane guide signs used on freeways and expressways should be designed in accordance with the following additional criteria:

- A. No more than one destination should be displayed for each movement, and no more than two destinations should be displayed per sign.
- B. The arrowhead(s) for the diverging movement should be positioned lower on the sign than the arrowhead(s) for the movement that continues straight ahead, independent of which movement carries the through route. Where the movements are freeway or expressway splits rather than exits, the arrowheads should be positioned at approximately the same height on the sign.
- C. Route shields, cardinal directions, and destinations should be positioned on the sign such that they are clearly related to the arrowhead(s) for the movement to which they apply.
- D. The cardinal direction should be placed adjacent to the route shield for exits or splits leading in a single cardinal direction.
- E. The vertical white line that is used to separate the route shields and destinations for the two diverging movements from each other should not descend below the top of the arrowheads for the through lanes, and should be positioned approximately halfway between the diverging arrowheads for the optional movement lane (see Figure 2E-32E-35).

Standard:

Overhead Arrow-per-Lane guide signs shall not be used to depict a downstream split of an exit ramp on a sign located on the mainline.

Support:

Specific guidelines for more detailed design of Overhead Arrow-per-Lane guide signs are contained in the "Standard Highway Signs and Markings" book publication (see Section 1A.11).

Option:

Where extra emphasis of an especially low advisory ramp speed is needed, an EXIT XX MPH (E13-2) sign panel (see Figure 2E-272E-13) may be placed below the applicable destination legend to supplement, but not to replace, the exit or ramp advisory speed warning signs.

Warning Beacons in compliance with the provisions of Section 2E.25 may be used with the E13-2 sign panel.

Figure 2E-35. Overhead Arrow-per-Lane Guide Sign for a Multi-Lane Exit with an Option Lane

- Figure 2E-36. Overhead Arrow-Per-Lane Guide Signs for a Two-Lane Exit to the Right with an Option Lane
- Figure 2E-37. Overhead Arrow-Per-Lane Guide Signs for a Two-Lane Exit to the Right with an Option Lane (Through Lanes Curve to the Left)
 - Figure 2E-38. Overhead Arrow-Per-Lane Guide Signs for a Split with an Option Lane
 Figure 2E-39. Use of Overhead Arrow-per-Lane and Exit Direction Signs for Option Lane
 with a Narrow Gore and Long Divergence
- Figure 2E-40. Use of Overhead Arrow-per-Lane and Exit Direction Signs for Option Lane with a Narrow Gore and Long Divergence where Through Route Curves and Exit Continues

 Straight
- Section 2E.222E.41 Design of Freeway and Expressway Diagrammatic Guide Signs for Option Lanes

ALTERNATE PROPOSAL FOR SECTION 2E.22: As an alternative to the following changes proposed to existing Section 2E.22 (proposed Section 2E.41), the Section would be deleted in its entirety for purposes of depicting specific lane use in freeway and expressway applications. References throughout other Sections would be deleted accordingly. Additional information on the alternate proposal is included in the Preamble for this Section.

Support:

1 2

Diagrammatic guide signs (see Figure 2E-7 2E-41) are guide signs that show a simplified graphic view of the exit arrangement in relationship to the main highway. While the use of such guide signs might be helpful for the purpose of conveying relative direction of each movement, Diagrammatic guide signs have been shown to be less effective than conventional or Overhead Arrow-per-Lane guide signs at conveying the destination or direction(s) that each approach lane serves, regardless of whether dedicated or option lanes are present.

Standard:

<u>Diagrammatic guide signs shall be designed in accordance with the following criteria</u> Diagrammatic guide signs used where an option lane is present at a freeway or expressway split or multi-lane exit shall be designed in accordance with the following criteria:

- A. The graphic legend shall be of a plan view showing the off-ramp arrangement.
- B. No other symbols or route shields shall be used as a substitute for arrowheads.
- C. They shall not be installed at the Exit Direction sign location (see Section 2E.362E.25).
- D. The EXIT ONLY sign panel shall not be used on diagrammatic guide signs in advance of the interchange.
- E. For numbered exits, the Exit Number (E1-5P) or Left Exit Number (E1-5bP) plaque shall be used at the top of the sign in accordance with Section 2E.312E.22. For unnumbered left exits, the LEFT (E1-5aP) plaque shall be used at the top left edge of the sign.
- F. The EXIT ONLY (E11-1e or E11-1f) sign panels shall be used on the Exit Direction sign at the theoretical gore, except at splits of two overlapping routes where neither of the routes is designated as an exit.

Guidance:

Diagrammatic guide signs used on freeways and expressways should be designed in accordance with the following additional criteria:

- A. The graphic should not depict deceleration lanes.
- B. No more than one destination should be displayed for each movement, and no more than two destinations should be displayed per sign.
- C. The arrowhead for the diverging movement should be positioned lower on the sign than the arrowhead for the movement that continues straight ahead, independent of which movement carries the through route (see Figures 2E-8-2E-42 and 2E-9 2E-43). Where the movements are freeway or expressway splits rather than exits, the arrowheads should be positioned at approximately the same height on the sign (see Figure 2E-102E-44).
- D. Arrow shafts should contain lane lines.
- E. Route shields, cardinal directions, and destinations should be positioned on the sign such that they are clearly related to the arrowhead(s), and the arrowhead for the off movement should point toward the route shield for the off movement.
- F. For exits or splits leading in a single direction, the cardinal direction should be placed adjacent to the route shield, and the destination should be placed below the route shield and cardinal direction.

Standard:

Diagrammatic guide signs shall not be used at cloverleaf interchanges for the purpose of depicting successive departures from the mainline or separate downstream departures from a collector-distributor roadway. The use of Diagrammatic guide signs at cloverleaf interchanges shall be limited to the following cases:

A. Where the outer (non-loop) exit ramp of the cloverleaf is a multi-lane exit having an optional exit lane that also carries the through route; and

B. At cloverleaf interchanges that include collector-distributor roadways, such as those illustrated in Figure 2E-362E-30, that are accessed from the mainline by a multi-lane exit having an optional exit lane that also carries the through route. In this case, the Diagrammatic guide sign shall only show the configuration of the lanes at the exit point to the collector-distributor roadway and not the entire interchange configuration.

<u>Diagrammatic guide signs shall not be used to depict a downstream split of an exit ramp on a sign located on the main roadway.</u>

Support:

 Specific guidelines for more detailed design of Diagrammatic guide signs are contained in the "Standard Highway Signs—and Markings" book—publication (see Section 1A.11).

Option:

Where extra emphasis of an especially low advisory ramp speed is needed, an EXIT XX MPH (E13-2) sign panel (see Figure 2E-272E-13) may be placed below the applicable destination legend to supplement, but not to replace, the exit or ramp advisory speed warning signs.

Warning Beacons in compliance with the provisions of Section 2E.25 may be used with the E13-2 sign panel.

Figure 2E-41. (Existing Figure 2E-7) Diagrammatic Guide Sign for a Multi-Lane Exit with an Option Lane

Figure 2E-42 (Existing Figure 2E-8) Diagrammatic Guide Signs for a Two-Lane Exit to the Right with an Option Lane

Figure 2E-43 (Existing Figure 2E-9) Diagrammatic Guide Signs for a Two-Lane Exit to the Right with an Option Lane (Through Lane Curve to the Left)

Figure 2E-44 (Existing Figure 2E-10). Diagrammatic Guide Signs for a Split with an Option Lane

Section <u>2E.232E.42</u> <u>Signing for Intermediate and Minor Interchange Multi-Lane Exits with an Option Lane</u>

Support:

Intermediate and minor multi-lane exits might have an operational need for the presence of an option lane for only the peak period during which excessive queues might otherwise develop if the option lane were not available. In such cases, the Overhead Arrow-per-Lane or Diagrammatic guide signing described for option lanes in Sections 2E.212E.40 and 2E.222E.41 might not be practical, depending on the level of use of the option lane and the spacing of nearby interchanges, particularly in non-rural areas.

Guidance:

Signing for an intermediate or minor interchange that has a multi-lane exit with an option lane that also carries the through route should use a modified form of the Overhead Arrow-per-Lane guide signs. The modified Overhead Arrow-per-Lane signs should display upward pointing arrows only for the optional and mandatory exit lanes (see Figure 2E-45). The legend displayed for the exit movement should be clearly aligned with the arrows pointing in the direction of the exit and not with the arrow depicting the through movement over the option lane.

Standard:

The through route and/or destination shall not be displayed on the modified Overhead Arrow-per-Lane guide sign to avoid the implication that the through route is restricted to the option lane.

Modified Overhead Arrow-per-Lane signs shall be located in compliance with the provisions of Section 2E.40 for unmodified Overhead Arrow-Per-Lane signs (see Figures 2E-46 and 2E-47).

45 Option:

At existing or non-reconstructed locations where an overhead Exit Direction sign exists at the theoretical gore, and the existing sign support structure is retained, the overhead Exit Direction sign may remain or may be replaced on the existing sign support structure in conjunction with a replacement of the advance signs using the modified Overhead Arrow-per-Lane guide sign design.

Guidance:

Where the modified Overhead Arrow-per-Lane guide signs described in this Section are not used.

Scigning for an intermediate or minor interchange that has a multi-lane exit with an option lane that also carries the through route should use the same basic principles as those for a conventional exit. In such cases, the option lane should not be signed on the Advance Guide signs. For such exits that involve the addition of an auxiliary lane that is not present at the Advance Guide sign locations, but do not involve a lane drop (see Figure 2E-12-49), a sequence of post-mounted or overhead-mounted Advance Guide signs should be used, located in accordance with the interchange classification (see Section 2E.322E.11). The Exit Direction sign should be located at the theoretical gore and display a diagonally upward-pointing directional arrow above each lane that departs from the mainline alignment. The Exit Direction sign should not contain the EXIT ONLY legend.

For such interchanges that also have a lane drop (see Figure 2E-11 2E-48), the Advance Guide and Exit Direction signs should follow the provisions of Section 2E.24-2E.28. The Exit Direction sign should be located at the theoretical gore and should contain the EXIT ONLY (E11-1e) sign panel.

Where the modified Overhead Arrow-per-Lane guide signs are not used, The the presence of the option lane should be conveyed by the use of post-mounted lane-use (R3-8 Series) signs (see Section 2B.22). When used, the R3-8 signs should be of an appropriate size for their application to optimize their conspicuity. The signs should be located in succession with the Advance Guide signs, where the option and exit lanes have developed (see Figure 2E-112E-48). In cases where the exiting lane or lanes have not developed and the option lane is created by the addition of an auxiliary lane that exits, the R3-8 signs should be located only adjacent to where the lanes have been fully developed and not in advance of the lane or along its transition (see Figure 2E-122E-49).

Support:

The use of a down arrow on overhead freeway or expressway guide signs has been shown to be misinterpreted by road users as an indication of a dedicated lane.

Standard:

Advance Guide signs that are mounted overhead shall not display a down arrow over an option lane.

Figure 2E-45. Partial Width Overhead Arrow-Per-lane Guide Sign for Intermediate or Minor Interchange

Figure 2E-46. Example of Overhead Arrow Per Lane Signing for a Two-Lane Intermediate or Minor Interchange Exit with an Option Lane and a Dropped Lane

Figure 2E-47. Example of Overhead Arrow Per Lane Signing for a Two-Lane Intermediate or minor Interchange Exit with an Option and Auxiliary Lanes

Figure 2E-48. Example of Conventional Signing for a Two-Lane Intermediate or minor Interchange Exit with an Option a Dropped Lane

Figure 2E-49. Example of Conventional Signing for a Two-Lane Intermediate or minor Interchange Exit with an Option and Auxiliary Lanes

Section2E.11 2E.43 Number of Signs at an Overhead Installation and Sign Spreading

Guidance:

If overhead signs are warranted, as set forth in Section 2A.17, the number of signs at these locations should be limited to only those essential in communicating pertinent destination information to the road user. Exit Direction signs for a single exit and the Advance Guide signs should have only one sign with one or two destinations. Regulatory signs, such as speed limits, should not be used in conjunction with overhead guide sign installations. Because road users have limited time to read and comprehend sign messages, there should not be more than three guide signs displayed at any one location either on the overhead structure or its support.

Option:

At overhead locations, more than one sign may be installed to advise of a multiple exit condition at an interchange. If the roadway ramp or crossing roadway has complex or unusual geometrics, additional signs with confirming messages may be provided to properly guide the road user.

Support:

Sign spreading is a concept where major overhead signs are spaced so that road users are not overloaded with a group of signs at a single location. Figure 2E-1-2E-50 illustrates an example of sign spreading. *Guidance:*

Where overhead signing is used, sign spreading should be used at all single_exit interchanges and to the extent possible at multi-exit interchanges. Sign spreading should be accomplished by use of the following:

- A. <u>Except as provided otherwise for cloverleaf interchanges (see Section 2E.33)</u>, <u>Fthe Exit Direction sign should be the only guide sign used in the vicinity of the gore (other than the Exit Gore sign)</u>. It should be located overhead near the theoretical gore and generally on an overhead sign support structure.
- B. The Advance Guide sign to indicate the next interchange exit should be placed near the crossroad location. If the crossroad goes over the mainline, the Advance Guide sign should be placed on the overcrossing structure or on a separate structure immediately in front of the overcrossing structure.

Figure 2E-50. Example of Sign Spreading

Section 2E.50 2E.44 Closely Spaced Interchanges

Support:

Section 2E.11 contains information regarding sign spreading where the Exit Direction sign and the Advance Guide sign for the next interchange are mounted overhead. Sign spreading is particularly beneficial where interchanges are closely spaced and overhead signing is used in conjunction with Interchange Sequence signs as provided in Paragraph 2.

Guidance:

Interchange Sequence signs (see Section $\frac{2E.40}{2E-24}$) should be used at closely spaced interchanges. When used, they should identify and show street names and distances for the next two or three exits as shown in Figure $\frac{2E-30}{2E-11}$.

Standard:

Advance Gguide signs for closely_spaced interchanges shall show information for only one interchange.

Notice of Proposed Amendments – Part 2

4

5

7

8

9

10

11 12

13

14

1516

17

18

19

20 21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

39

40

41

42

43

2 Section 2E.342E.45 Next Exit Plaques (E2-1P, E2-1aP)

3 Option:

Where the distance to the next interchange is unusually long, a Next Exit (E2-1P or E2-1aP) plaque (see Figure $\frac{2E-23}{2E-51}$) may be installed to inform road users of the distance to the next interchange.

6 Guidance:

The Next Exit plaque should not be used unless the distance between successive interchanges is more than 5 miles.

Where the Next Exit plaque is used, the E2-1P plaque should be used where the width of the Advance guide sign is equal to or greater than the width of the E2-1P plaque. The E2-1aP plaque should be used where the width of the E2-1P plaque exceeds the width of the Advance guide sign.

Standard:

The Next Exit plaque shall <u>earry display</u> the legend NEXT EXIT XX MILES. If the Next Exit plaque is used, it shall be placed below the Advance Guide sign nearest the interchange. It shall be mounted so as to not adversely affect the breakaway feature of the sign support structure.

Option:

The legend for the Next Exit plaque may be displayed in either one or two lines as shown in Figure 2E-23. Support:

The one line message on the Next Exit plaque is the more desirable choice unless the message causes the sign to have a horizontal dimension greater than that of the Advance Guide sign. Incorporated into Guidance above.

Figure 2E-51. Next Exit Plaques

Section **2E.382E.46** Post-Interchange Signs

Guidance:

If space between interchanges permits, as in rural areas, and where undue repetition of messages will not occur, a fixed sequence of signs should be displayed beginning 500 feet beyond the downstream end of the acceleration lane. At this point a Route sign assembly should be installed followed by a Speed Limit sign and a Distance sign, each at a spacing of 1,000 feet.

If space between interchanges does not permit placement of these three post-interchange signs without encroaching on or overlapping the Advance Guide signs necessary for the next interchange, or in rural areas where the interchanging traffic is primarily local, one or more of the post-interchange signs should be omitted.

Option:

Usually the Distance sign will be of less importance than the other two signs and may be omitted, especially if Interchange Sequence signs are used. If the sign for through traffic on an overhead assembly already contains the route sign, the post-interchange route sign assembly may also be omitted.

Section 2E.392E.47 Post-Interchange Distance Signs (E7-1 Series, E7-2 Series, E7-3 Series)

38 Standard:

If used, the Post-Interchange Distance sign shall consist of a two- or three-line sign carrying the names of significant destination points and the distances to those points. The top line of the sign shall identify the next meaningful interchange with the name of the community near or through which the route passes, or if there is no community, the route number or name of the intersected highway (see Figure 2E-292E-52).

44 Support:

The minimum sizes of the route shields identifying a significant destination point are prescribed in Tables 2E-3 and 2E-5.

47 Option:

1 The text identification of a route may be displayed instead of a route shield, such as "U_S _XX," "{[State 2 abbreviation]) Route XX;" (e.g., Del XX), or "County Route XX." 3 Guidance: 4 If a second line is used, it should be reserved for communities of general interest that are located on or immediately adjacent to the route or for major traffic generators along the route. 5 6 Option: 7 The choice of names for the second line, if it is used, may be varied on successive Distance signs to give 8 road users maximum information concerning communities served by the route. 9 Standard: 10 The third, or bottom line, shall contain the name and distance to a control city (if any) that has 11 national significance for travelers using the route. 12 Guidance: 13 Distances to the same destinations should not be shown more frequently than at 5-mile intervals. The distances displayed on these signs should be the actual distance to the destination points and not to the exit 14 15 from the freeway or expressway. The distance displayed for each community should comply with the provisions of Section 2D.41. 16 Figure 2E-52. Post-Interchange Distance Sign 17 18 Section 2E.48 Post-Interchange Travel Time Sign (E7-4 Series) 19 Support: 20 At certain locations, it might be more meaningful to the road user to display the travel time rather than the 21 distance to a destination. Such instances might be areas of adverse roadway conditions due to weather, such as in mountain passes or high elevations, or congestion that occurs during peak travel seasons. 22 23 Section 2E.49 contains information on Comparative Travel Time signs for alternative routes. 24 Section 2E.49 contains information on Distance and Travel Time signs for major junctions or 25 interchanges. 26 **Standard:** 27 The Post-Interchange Travel Time sign (see Figure 2E-53) shall comply with the provisions of 28 Paragraph 1 of Section 2E.48 with the following exceptions: 29 A. The distance shall be replaced with a changeable message element to display the current travel 30 time to the applicable destination; and 31 B. The abbreviation MINS shall follow the changeable message element. 32 If used, the Post-Interchange Travel Time sign shall be limited to locations that are susceptible to 33 congestion on a recurring or otherwise frequent basis. If used, the Post-Interchange Travel Time sign 34 shall replace of the Post-Interchange Distance sign in the series of post-interchange signs (see Section 35 2E.47). 36 Travel times shall not be used on Interchange guide signs (see Section 2E.21). 37 Figure 2E-53. Post-Interchange Travel Time Sign

Section 2E.49 Distance and Travel Time Sign and Comparative Travel Time Sign (E7-5, E7-6)

39 Support:

38

40

41

42 43

44

45

46

Some locations might benefit from a travel time message displayed with the distance, or comparative travel times for alternative routes to a common destination. These locations are typically in advance of a decision point where the road user can divert to an alternate route to avoid recurring congestion.

Section 2E.48 contains information on Post-Interchange Travel Time signs.

Section 2G.19 contains information on Comparative Travel Time signs for parallel lanes within the same highway route, such as for general-purpose lanes and managed lanes.

Standard:

The Distance and Travel Time sign (E7-5) shall display a major destination or junction, a distance message, and a travel time message, each on a separate line. The distance units shall be displayed in the distance message. The travel time shall be displayed in a changeable message element and the abbreviation MINS shall follow the changeable message element. The Distance and Travel Time sign shall not display distance and time to more than one destination or junction.

The Comparative Travel Time sign (E7-6) shall display a major destination or junction and two alternative routes with travel time messages. Each alternative route and associated travel time message shall be on a separate line. The travel time shall be displayed in a changeable message element and the abbreviation MINS shall follow the changeable message element.

Comparative travel times shall not be used to promote different modes of travel, such as personal vehicle highway travel compared with transit, or different forms of transit.

Guidance:

Where used, the Distance and Travel Time sign should be located between interchanges away from the interchange guide sign sequence or other major signs. The Distance and Travel time sign should desirably be located in advance of an urbanized area where interchanges become more closely spaced and/or in advance of a circumferential or other alternative route(s) where traffic can decide to divert depending on the destination.

Where used, the Comparative Travel Time sign should be located in advance of the interchange guide sign sequence to provide adequate time for the road user to decide whether to reroute.

20 Support:

Figure 2E-422E-54 shows examples of the application of the Distance and Travel Time sign and the Comparative Travel Time sign.

Figure 2E-54. Travel Time Sign

Section 2E.35 2E.50 Other Supplemental Guide Signs (E3 Series)

25 Support:

Supplemental <u>Guide guide</u> signs can be used to provide information regarding destinations accessible from an interchange, other than places displayed on the standard interchange signing. However, such Supplemental <u>Guide guide</u> signing can reduce the effectiveness of other more important guide signing because of the possibility of overloading the road user's capacity to receive visual messages and make appropriate decisions. "The AASHTO Guidelines for the Selection of Supplemental Guide Signs for Traffic Generators Adjacent to Freeways" is incorporated by reference in this section (see Page i for AASHTO's address).

Guidance:

Because most interchanges will not have a need for Supplemental guide signs, consideration of their use should be limited to situations where there is a demonstrated need to sign for more than the two primary destinations from an interchange that are displayed on the Advance guide and Exit Direction signs.

A Supplemental guide sign should not be installed unless a destination meets the criteria established by the State or agency policy. States and other agencies should adopt an appropriate policy for installing supplemental signs using Fthe "AASHTO Guidelines for the Selection of Supplemental Guide Signs for Traffic Generators Adjacent to Freeways." In developing policies for such signing, such items as population, amount of traffic generated, distance from the route, and the significance of the destination, should be taken into account. Moved from later in this section.

No more than one Supplemental Guide guide sign should be used on each interchange approach.

A Supplemental <u>Guide guide</u> sign (see Figure <u>2E-242E-55</u>) should <u>not list display no more than two</u> destinations <u>and no more than three lines of destination information</u>. Destination names should be followed by the interchange number (and suffix), or if interchanges are not numbered, by the legend NEXT RIGHT or SECOND RIGHT or both, as appropriate. The Supplemental <u>Guide guide</u> sign should be installed as an independent guide sign assembly.

Where two or more Advance <u>Guide guide</u> signs are used, the Supplemental <u>Guide guide</u> sign should be installed approximately midway between two of the Advance <u>Guide guide</u> signs. If only one Advance <u>Guide</u>

1 guide sign is used, the Supplemental Guide guide sign should follow it by at least 800 feet. If the interchanges 2 are numbered, the interchange number should be used for the action message. 3 A Supplemental guide sign should not be installed in the same location with or where it will detract from 4 guide signs for a different interchange. 5 States and other agencies should adopt an appropriate policy for installing supplemental signs using "The AASHTO Guidelines for the Selection of Supplemental Guide Signs for Traffic Generators Adjacent to 6 7 Freeways." In developing policies for such signing, such items as population, amount of traffic generated, distance from the route, and the significance of the destinationshould be taken into account. Incorporated 8

Standard:

into Guidance earlier in this section.

9

10

11

12

13 14

1516

17

18

19 20

21

22

23 24

25

26 27

28

2930

31

32

33

34

35

36 37

38 39

40

41

42

43

44

46

47

48 49 No more than four supplemental traffic generator destinations shall be signed from a single interchange along the main roadway (see Paragraphs 3 and 4 regarding the number of Supplemental guide signs at an interchange and the number of destinations displayed on a Supplemental guide sign).

<u>Supplemental guide signs shall not be placed at the same location as Advance guide, Exit Direction, or other signs related to that exit or interchange.</u>

Guide signs directing drivers to for park _ ride facilities shall be considered as Supplemental Guide guide signs (see Figure 2E-252E-56).

Guide signs for recreational or cultural interest destinations (see Chapter 2K) shall be considered as Supplemental guide signs, except where the interchange provides direct access to such a destination and is instead displayed on the Advance guide and Exit Direction signs.

Option:

A pictograph (see definition in Section 1A.13) may be used on a Supplemental Guide sign in conjunction with a destination that is associated with governmental agencies, military bases, universities, or other government-approved institutions.

<u>Pictographs shall not be displayed on Supplemental guide signs, except as provided in Paragraphs</u>

13 and 14 of this Section for the Park – Ride Supplemental guide sign.

Guidance:

The use of a transit pictograph and/or the carpool symbol on the Park – Ride Supplemental guide sign should comply with the provisions of Paragraph 5 of Section 2D.46.

Standard:

The maximum dimension (height or width) of a pictograph shall not exceed two times the upper-case letter height of the destination legend and shall not exceed the size of a route shield on the guide sign. If used, the pictograph shall be located to the left of the destination legend it represents, except as provided in Paragraph 9 for the park-ride Supplemental Guide sign.

When a transit pictograph is displayed on the Park - Ride <a href="Park - Ride park - Ride

A pictograph representing a State, county, or municipal corporation or other incorporated or unincorporated community shall not be displayed on a Supplemental Guide sign.

Pictographs shall otherwise comply with the provisions of Section 2A.06.

Figure 2E-55. Supplemental Guide Sign for a Multi-Exit Interchange Figure 2E-56. Supplemental Guide Sign for a Park-Ride Facility

Section 2E.41 2E.51 Community Interchanges Identification Signs (E9-4 Series, E9-5 Series)

45 Support:

For suburban or rural communities served by two or three interchanges, Community Interchanges Identification (see Figure 2E-57) signs are useful reduce the amount of information displayed on the Advance guide and Exit Direction signs by eliminating repetition of the same destinations for separate interchanges (see Figure 2E-322E-58).

50 Guidance:

1 In these cases, the name of the community followed by the word EXITS should be displayed on the top 2 line; the lines below should display the destination, road name or route number, and the corresponding 3 distances to the nearest 1/4 mile. 4 The sign should be located in advance of the first Advance Guide sign for the first interchange within the 5 6 The legend displayed on the Advance guide and Exit Direction signs for each interchange should be 7 consistent with the interchange names displayed on the Community Interchanges Identification sign. The name of the community displayed on the Community Interchanges Identification signs should be omitted from 8 9 the legends of the Advance guide and Exit Direction signs. 10 Option: 11 If interchanges are not conveniently identifiable or if there are more than three interchanges to be 12 identified, the NEXT XX EXITS sign (see Section 2E.42 2E.52) may be used. Figure 2E-57 Example of a Community Interchanges Identification Sign 13 14 Figure 2E-58. Example of Use of a Community Interchanges Identification Sign 15 Section 2E.422E.52 NEXT XX EXITS Sign (E9-3 Series) 16 Support: 17 Many freeways or expressways pass through historical or recreational regions, or urban areas served by a 18 succession of several interchanges. 19 Option: 20 Such regions or areas may be indicated by a NEXT XX EXITS (E9-3 series) sign (see Figure 2E-33 2E-21 59) located in advance of the Advance Guide sign or signs for the first interchange (see Figure 2E-60). 22 23 The sign legend should identify the region or area followed by the words NEXT XX EXITS. 24 The legend displayed on the Advance Guide and Exit Direction signs for each interchange should not 25 display the region or area name that is displayed on the NEXT XX EXITS sign. 26 Figure 2E-59. Example of a Next Exits Sign 27 Figure 2E-60. Example of Use of a Next Exits Sign Section 2E.52 Signing on Conventional Road Approaches and Connecting Roadways This 28 section has been relocated to new Section 2E.57. 29 30 Section 2E.53 Wrong-Way Traffic Control at Interchange Ramps This section has been relocated to new Section 2E.58. 31 32 Section 2E.534 Weigh Station Signing 33 Support: 34 <u>Independent facilities or areas have been added along many highways where certain commercial vehicles</u> 35 are directed to stop to be weighed or inspected. These areas are sometimes permanent, such as in a roadside 36 area, or temporary mobile facilities deployed along the roadway. 37 The general concept for signing permanent Weigh Station is similar to Rest Area signing (see Section 2I.05) because in both cases traffic using either area remains within the highway right-of-way. 38 39 **Standard:** 40 The standard sequence of signs for a Weigh Station on an expressway or Freeway shall include four 41 basic signs (see Figure 2E-59): A. Advance Weigh Station Distance (D8-1) sign, with the distance 1 MILE displayed, 42 43 B. Advance Weigh Station Distance (D8-1) sign, with the distance ½ MILE displayed, 44 C. Weigh Station Exit Directional (D8-3) sign, and D. Weigh Station Exit Gore Sign (same legend as the Exit Direction (D8-3) sign. 45 46 Option:

Where State law requires trucks of a certain weight to enter the weigh station, a Weigh Station (R13-1) regulatory sign (See section 2B.60) may be added to the sign sequence as shown in Figure 2E-61.

Where only commercial vehicle inspections are conducted in the inspection area and vehicles are not weighed, the WEIGH STATION legend of the D8 series signs may be replaced with the alternate legend, COMMERCIAL VEHICLE INSPECTION AREA.

Standard:

When the WEIGH STATION legend of the D8 series signs is replaced with COMMERCIAL VEHICLE INSPECTION AREA legend as provided for in this Section, the WEIGH STATION legend of the R13-1 sign shall be replaced with the alternate legend INSPECTION AREA.

A sign or plaque with a changeable legend display that displays either OPEN or CLOSED shall be included in the signing sequence to indicate when trucks are required to enter the weigh station.

Guidance:

The Weigh Station Advance sign (D8-2) or the Weigh Station Advance sign (D8-1) should display, either within the sign border or on a supplemental plaque or sign panel, the changeable legend OPEN or CLOSED.

Standard:

Weigh Station signing on freeways and expressways shall be the same as that provided in Section 2D.49, except for lettering size and the advance posting distance for the Exit Direction sign, which shall be located a minimum of 1,500 feet in advance of the gore.

Support:

Weigh <u>Station and Commercial Vehicle Inspection Area Station</u> sign layouts for freeway and expressway applications are shown in the "Standard Highway Signs—and <u>Markings</u>" <u>book publication</u> (see Section 1A.11)._

An example of weigh station signing for use on freeways and expressways is shown in Figure 2E-61.

Figure 2E-61. Example of Weigh Station Signing on Freeways

Section 2E.27 2E.54 Route Signs and Trailblazer Assemblies

Standard:

The official Route sign for the Interstate Highway System shall be the red, white, and blue retroreflective distinctive shield adopted by the American Association of State Highway and Transportation Officials (see Section 2D.11).

Guidance:

Route signs (see Figure <u>2E-172E-6</u>2) should be incorporated as cut-out shields or other distinctive shapes on large directional guide signs. Where the Interstate shield is displayed in an assembly or on the face of a guide sign with U.S. or State Route signs, the Interstate numeral should be at least equal in size to the numerals on the other Route signs. The use of independent Route signs should be limited primarily to route confirmation assemblies.

Route signs and auxiliary signs plaques showing junctions and turns should be used for guidance on approach roads, for route confirmation just beyond entrances and exits, and for reassurance along the freeway or expressway. When used along the freeway or expressway, the Route signs should be enlarged to a 36 x 36-inch minimum size for routes with one or two digits and to a 45 x 36-inch minimum size for routes with three digits as shown in the "Standard Highway Signs-and Markings" book-publication (see Section 1A.11). When independently mounted Route signs are used in place of Pull-Through signs (see Section 2E.27), they should be located just beyond the exit.

Option:

The standard Trailblazer Assembly (see Section 2D.3534) may be used on roads leading to the freeway or expressway. Component messages of the Trailblazer Assembly may be included onincorporated into a single sign in accordance with the provisions of Section 2D.12. Independently mounted Route signs may be used instead of Pull-Through signs (see Section 2E.12) as confirmation information.

47 Support

Section 2H.07 contains information regarding the design of signs for Auto Tour Routes.

Figure 2E-62. Interstate, Off-Interstate, and U.S. Route Signs

50 Option:

The commonly used name or trailblazer route sign for a toll highway (see Chapter 2F) may be displayed on non-toll sections of the Interstate Highway System at:

- A. The last exit before entering a toll section of the Interstate Highway System;
- B. The interchange or connection with a toll highway, whether or not the toll highway is a part of the Interstate Highway System; and
- C. Other locations within a reasonable approach distance of toll highways when the name or trailblazer symbol for the toll highway would provide better guidance to road users unfamiliar with the area than would place names and route numbers.

The toll highway name or route sign may be included as a part of the guide sign installations on intersecting highways and approach roads to indicate the interchange with a toll section of an Interstate route. Where needed for the proper direction of traffic, a trailblazer for a toll highway that is part of the Interstate Highway System may be displayed with the Interstate Trailblazer Assembly.

Support:

Chapter 2F contains additional information regarding signing for toll highways.

Section 2E.28 2E.55 Eisenhower Interstate System Signs (M1-10, M1-10a)

Option:

The Eisenhower Interstate System (M1-10 and M1-10a) signs (see Figure 2E-182E-63) may be used, in accordance with Paragraphs 2 and 3 of this Section, on Interstate highways at periodic intervals and in rest areas, scenic overlooks, or other similar roadside facilities on the Interstate Highway System.

Guidance Standard:

If used, the M1-10a sign should shall be used only in rest areas or other similar facilities where the sign can be viewed by occupants of parked vehicles or by pedestrians. The M1-10a sign should shall not be installed on Interstate highway mainlines, ramps, or other roadways where it can be viewed by vehicular traffic.

Standard:

The M1-10 and M1-10a signs shall not be used as part of a Junction, Advance Route Turn, Directional, or Trailblazer Assembly, or as part of a guide sign or similar assembly providing direction to a route or destination.

Figure 2E-63. Eisenhower Interstate System Signs

SIGNS FOR ROUTE DIVERSION BY VEHICLE CLASS

Section 2E.56 Signs for Route Diversion by Vehicle Class

Support:

On some highways, a physical condition or highway feature might limit certain types or classes of vehicles from proceeding along that route through the site of that condition beyond which those vehicles are otherwise allowed. Examples include a restriction on taller legal height vehicles through a tunnel with a low clearance; a restriction of hazardous materials through a tunnel or over a bridge; and a restriction on wider vehicles, such as large trucks, over a viaduct with narrow lanes. In such cases, the restricted vehicles might be diverted along another route to reach a destination beyond the location of the limiting condition.

Guidance:

Where certain vehicles are prohibited at a downstream location along a route and those vehicles must divert to reach a through destination beyond that location, regulatory, warning, and/or guide signs advising those vehicle operators of the diversion should be installed in advance of the decision point to leave the through route for the diversion route.

Option:

The interchange and pull-through guide signs for the last point at which restricted vehicles must exit may be modified to incorporate regulatory and/or warning panels with word legends, as shown in Figure 2E-64, to display the regulations and/or warning messages relative to the vehicle class restriction.

Standard post-mounted regulatory and warning signs, such as the No Hazardous Materials (R14-3) or Advance Low Clearance (W12-2) signs, may be used as provided elsewhere in this Manual at independent locations to supplement the regulatory and warning signs and panels referenced in Paragraphs 2 and 3 of this Section.

25 Support:

An example of signing for a route diversion by vehicle class is shown in Figure 2E-62.

Figure 2E-64. Example of Signing for a Route Diversion by Vehicle Class SIGNS FOR INTERSECTIONS AT GRADE

Section 2E.292E.57 Signs for Intersections at Grade

30 Guidance:

If there are intersections at grade within the limits of an expressway, guide sign types provided in Chapter 2D should be used. However, such signs should be of a size compatible with the size of other signing on the expressway.

Option:

Advance Guide signs for intersections at grade may take the form of diagrammatic layouts depicting the geometrics of the intersection along with essential directional information.

Where an expressway route with grade-separated interchanges is interrupted by a short segment of atgrade intersections, exit numbering, if used, may be maintained through that segment for the major intersections to provide continuity in navigation and signing between the grade-separated segments (see Figure 2E-63).

Figure 2E-63. Example of At-Grade Intersection Expressway Signing Using Exit Numbering

INTERFACE WITH CONVENTIONAL ROADWAYS

2	Section 2E.522E.58 Signing on Conventional Road Approaches and Connecting Roadways
3	Support:
4	Section 2D.45 contains information regarding the signing on conventional roads on the approaches to
5	interchanges and the signing on connecting roadways.
6	Section 2E.53 2E.59 Wrong-Way Traffic Control at Interchange Ramps
7	Support:
8	Section 2B.41 contains information regarding the use of regulatory signs to deter wrong-way movements
9	at intersections of freeway or expressway ramps with conventional roads, and in the area where entrance
10	ramps intersect with the mainline lanes.
11	Section 2D.46 contains information regarding the use of a Directional assembly or a guide sign to mark
12	the entrance to a freeway or expressway from a conventional road.

1 CHAPTER 2F. TOLL ROAD SIGNS 2 **Chapter 2F Subchapter and Section Organization** 3 4 General 5 2F.01 Scope 6 2F.02 Sizes of Toll Road Signs and Electronic Toll Collection (ETC) System Pictographs 7 2F.03 8 Regulatory Signs 9 2F.04 Regulatory Signs for Toll Plazas 10 2F.05 Electronic Toll Collection (ETC) Account-Only Regulatory Sign and Plaque (R3-31, R3-32P) 11 Warning Signs 2F.06 Pay Toll and Take Ticket Advance Warning Signs (W9-6, W9-6e) 12 Pay Toll and Take Ticket Advance Warning Plagues (W9-6bP, W9-6gP) 13 2F.07 14 Stop Ahead Pay Toll and Take Ticket Warning Signs (W9-6a, W9-6f) 2F.08 15 2F.09 Stop Ahead Pay Toll and Take Ticket Warning Plaques (W9-6cP, W9-6hP) LAST EXIT BEFORE TOLL Warning Plaques (W16-16P, W16-16aP) 2F.10 16 17 2F.11 TOLL Warning Plaque (W16-17P) 18 Guide Signs 19 2F.12 Toll Facility and Toll Plaza Guide Signs – General 20 2F.13 Electronic Toll Collection (ETC) Signs – General 21 2F.14 Advance Signs for Conventional Toll Plazas 22 2F.15 Advance Signs for Toll Plazas on Diverging Alignments from Open-Road ETC Account-23 Only Lanes 24 Toll Plaza Canopy Signs 2F.16 25 2F.17 Guide Signs for Entrances to ETC Account-Only Facilities 2F.18 Guide Signs for Entrances to ETC-Only Facilities 26 Guide Signs for ETC-Only Entrance Ramps to Non-Toll Highways 27 2F.19 **ETC Account Program Information Signs** 28 2F.20 29 30 **GENERAL** 31 Section 2F.01 Scope 32

Support:

33

34 35

36

37

38

39

40

41 42

43

44 45

46

47

48

49

50

Toll highways are typically limited-access freeway or expressway facilities. A portion of or an entire route might be a toll highway, or a bridge, tunnel, or other crossing point might be the only toll portion of a highway at which a toll is collected. A toll highway might be a conventional road. The general signing requirements for toll roads will depend on the type of facility and access (freeway, expressway, or conventional road). The provisions of Chapters 2D and 2E will generally apply for guide signs along the toll facility that direct road users within and off the facility where exit points and geometric configurations are not dependent specifically on the collection of tolls. The aspect of tolling and the presence of toll plazas or collection points necessitate additional considerations in the typical signing needs. The notification of the collection of tolls in advance of and at entry points to the toll highway also necessitates additional modifications to the typical signing.

The scope of this Section applies to a route or facility on which all lanes are tolled. Chapter 2G contains provisions for the signing of managed lanes within an otherwise non-toll facility that employ tolling or pricing as an operational strategy to manage congestion levels.

Standard:

Except where specifically provided in this Chapter, the provisions of other Chapters in Part 2 shall apply to toll roads.

Section 2F.02 Sizes of Toll Road Signs and Electronic Toll Collection (ETC) System

Pictographs

51 **Standard:**

Except as provided in Section 2A.11, the sizes of toll road signs that have standardized designs shall be as shown in Table 2F-1.

Support:

Section 2A.11 contains information regarding the applicability of the various columns in Table 2F-1.

5 Option:

Signs larger than those shown in Table 2F-1 may be used (see Section 2A.11).

Table 2F-1. Toll Road Sign and Plaque Minimum Sizes

The following paragraphs relocated from existing Section 2F.04 and revised

Standard:

The ETC <u>system</u> pictograph (see Chapter 2A) shall be of a size that makes it a prominent feature of the sign legend as necessary for conspicuity for those road users with registered ETC accounts seeking such direction, as well as for those road users who do not have ETC accounts so that it is clear to them to avoid such direction when applicable.

Guidance:

<u>Except as provided in Paragraph 6 of this Section, aAn ETC pictograph that is in the shape of a horizontally oriented</u> rectangle should have a minimum height <u>ofbetween approximately 1.5 and 2</u> times the upper-case letter height of the principal legend on the sign. The width of an ETC pictograph in the shape of a horizontal rectangle should be between approximately two and three times the height of the pictograph.

When the pictograph is the principal legend on the sign, such as for advance guide signs for open-road tolling lanes (see Section 2F.15), the minimum height of a horizontally oriented rectangular ETC pictograph should be consistent with that of a route shield prescribed for the particular application and type of sign.

For ETC pictographs whose shape is square, circular, or otherwise similar in height and width, or is a vertically oriented rectangle, the same basic principles for conspicuity and placement should be followed. ETC pictographs whose shape is not in that of a horizontally oriented rectangle should be suitably sized to facilitate conspicuity as described in Paragraph 14 and should be of a similar approximate area as the horizontally oriented rectangular pictographs designed in accordance with the height and width as provided in Paragraph 25.

Section 2F.03 <u>Use of Purple Backgrounds and Underlay Panels with ETC Account Pictographs</u>Color

Standard:

Use of the color purple on any sign shall comply with the provisions of Sections 1A.12 and 2A.10. Except as provided in Sections 2F.05 and 2F.12 and 2F.16, purple as a background color shall be used only when the information associated with the appropriate ETC account is displayed on that portion of the sign. The background color of the remaining portion of such signs shall comply with the provisions of Sections 1A.12 and 2A.10 as appropriate for a regulatory, warning, or guide sign. Purple shall not be used as a background color to display a destination, action message, or other legend that is not a display of the requirement for all vehicles to have a registered ETC account.

If only vehicles with registered ETC accounts are allowed to use a highway lane, a toll plaza lane, an open-road tolling lane, or all lanes of a toll highway or connection, the <u>guide</u> signs for such lanes or highways shall incorporate the pictograph (see Chapter 2A) adopted by the toll facility's ETC payment system and the regulatory message ONLY. Except for ETC pictographs whose predominant background color is purple, if incorporated within the green background of a guide sign, the ETC pictograph shall be on a white rectangular or square panel set on a purple underlay panel with a white border. For rectangular ETC pictographs whose predominant background color is purple, a white border shall be used at the outer edges of the purple rectangle to provide contrast between the pictograph and the sign background color.

If an ETC pictograph is used on a separate plaque with a guide sign in a route sign assembly (see Section 2F.05) or on a header panel within a guide sign, the plaque or the header panel shall have a purple background with a white border and the ETC pictograph shall have a white border to provide contrast between the pictograph and the background of the plaque or header panel.

Purple underlay panels for ETC pictographs or purple backgrounds for plaques and header panels shall only be used in the manner described in Paragraphs 1 through 3 to convey the requirement of a registered ETC account on signs for lanes reserved exclusively for vehicles with such an account and on

1 2	directional signs to an ETC account-only facility from a non-toll facility or from a toll facility that accepts multiple payment forms.
3	Support:
4 5	Figure 2F-1 shows examples of ETC account pictographs, their use with various background colors, and modifications involving underlay panels.
6	Section 2F.042F.02 contains provisions regarding the size of pictographs for ETC accounts.
7	Figure 2F-1. Examples of ETC Account Pictographs and Use of Purple Backgrounds and
8	Underlay Panels
9	Section 2F.04 Size of ETC Pictographs Relocated to Section 2F.02
10	

Section 2F.05 2F.04 Regulatory Signs for Toll Plazas

Support:

Toll plaza operations often include lane-specific restrictions on vehicle type, forms of payment accepted, and speed limits or required stops. Vehicles are typically required to come to a stop to pay the toll or receive a toll ticket in the attended and exact change or automatic lanes. Electronic toll collection (ETC) lanes with favorable geometrics typically allow vehicles to move through the toll plaza without stopping, but usually within a set regulatory speed limit or advisory speed. In some ETC lanes and in most lanes that accommodate non-ETC vehicles, a stop might be required while the ETC payment is processed because of geometric or other conditions.

Guidance:

Regulatory signs applicable only to a particular lane or lanes should be located in a position that makes their <u>lane</u> applicability clear to road users approaching the toll plaza.

Regulatory signs, or regulatory panels within guide signs, indicating restrictions on vehicle type and forms of toll payment accepted at a specific toll plaza lane should be installed over the applicable lane either on the toll plaza canopy or on a separate structure immediately in advance of the canopy located in a manner such that each sign is clearly related to an individual toll lane.

Support:

Section <u>2F.13 2F.12</u> contains information regarding the incorporation of regulatory messages into guide signs for toll plazas.

Section 2F.16 contains information regarding the design and use of toll plaza canopy signs.

Guidance:

One or more Speed Limit (R2-1) signs (see Section 2B.13) should be installed in the locations provided in Paragraph 8 for an ETC-Only lane at a toll plaza in which an enforceable regulatory speed limit is established for a lane in which it is intended that vehicles move through the toll plaza without stopping while toll payments requiring stops occur in other lanes at the toll plaza. The speed limit displayed on the signs should be based on an engineering study taking into account the geometry of the plaza and the lanes and other appropriate safety and operational factors.

A Speed Limit (R2-1) sign should not be installed for a toll plaza lane that is controlled by a STOP (R1-1) sign or where a stop is required.

Guidance Option: Changed from Option to Guidance and edited for clarity

Speed limit signs may be installed over the applicable lane on the toll plaza canopy, on the approach end of the toll booth island, on the toll booth itself, or on a vertical element of the canopy structure.

Where speed limit signs are installed over a toll plaza lane on the toll plaza canopy, on the approach end of the toll booth island, on the toll booth itself, or on a vertical element of the canopy structure, then Down down arrows or diagonally downward-pointing directional arrows mayshould be used to supplement the speed limit signs if an engineering study or engineering judgment indicates that there is a need the arrow is needed to clarify the applicability of a sign to a specific lane or to improve compliance.

Standard:

A STOP (R1-1) sign shall not be installed for a toll plaza lane that is operated as an ETC-Only lane and that is designed for tolls to be collected while vehicles continue moving.

Option

A STOP (R1-1) sign may be installed to require <u>all</u> vehicles to come to a complete stop to pay a toll in an attended or exact change lane, even if that lane is also available for optional use by vehicles with registered ETC accounts. A PAY TOLL (R3-29P) or TAKE TICKET (R3-30P) plaque (see Figure 2F-2), as appropriate to the operation, may be installed directly under the STOP (R1-1) sign for a toll plaza lane, if needed.

The mounting height of the STOP sign and any supplemental plaque may be less than the normal mounting height requirements if constrained by the physical features of the toll island or toll plaza.

The lateral offset of a STOP or other regulatory sign located within a toll plaza island may be reduced to a minimum of 1 foot from the face of the toll island or raised barrier to the nearest edge of the sign.

Guidance:

1 If used, a STOP (R1-1) sign for a toll plaza cash payment lane should be located in a longitudinal position 2 as near as practical to the point where a vehicle is expected to stop to pay the toll or take a ticket. 3 Option: 4 A Toll Rate (R3-28) sign (see Figure 2F-2) may be installed in advance of the toll plaza to indicate the toll 5 applicable to the various vehicle types. 6 Guidance: 7 If used, the Toll Rate (R3-28) sign should be located between the toll plaza and the first advance sign 8 informing road users of the toll plaza. 9 The R3-28 sign should not contain more than three lines of legend. Each lines that shows a toll amount 10 should display only a single toll amount. Option: 11 12 Additional toll rate information exceeding three lines of legend may be displayed on the toll booth 13 adjacent to the payment window of an attended lane or the payment receptacle of an exact change or automatic lane where it is visible to a road user who has stopped to pay the toll, but is not visible to 14 15 approaching road users who have not yet entered the toll lane. Figure 2F-2. Toll Plaza Regulatory Signs and Plaques 16 17 Section 2F.122F.05 Electronic Toll Collection (ETC) Account-Only Auxiliary Signs Regulatory Sign and Plaque (M4-16 and M4-20R3-31, R3-32P) 18 19 **Standard:** 20 In any route sign assembly providing directions from a non-toll highway to a toll facility, or to a 21 tolled segment of a highway, where electronic toll collection (ETC) is the only payment method accepted and all vehicles are required to have a registered ETC account, the ETC Account-Only (M4-20 R3-31) 22 23 sign auxiliary sign (see Figure 2F-42F-3) shall be mounted directly below the route sign of the numbered or named toll facility. The M4-20 R3-31 auxiliary sign shall have a white border and purple 24 25 background and incorporate the pictograph adopted by the toll facility's ETC payment system and the

word ONLY in black letters on a white panel set on the purple background of the sign. Option:

The NO CASH (M4-16 R3-32P) auxiliary sign plaque (see Figure 2F 42F-3) with a black legend and border on a white background may be used in a route-mounted directly below the M4-20 auxiliary R3-31 sign in a Directional or other sign assembly.

Figure 2F-3. ETC Account-Only Regulatory Sign and Plaque

31 32

26

27

28

29

Section 2F.06 Pay Toll and Take Ticket Advance Warning Signs (W9-6, W9-6e)

Standard:

The Pay Toll and Take Ticket Advance Warning (W9-6 and W9-6e) signs shall be a horizontal rectangle with a black legend and border on a yellow background. The legend shall include display the distance to the toll plaza and, except for toll-ticket facilities, the toll for passenger or 2-axle vehicles (see Figure 2F-32F-4). Where the toll for passenger or 2-axle vehicles is variable by time of day, a changeable message element shall be incorporated into the W9-6 sign to display the toll in effect. For toll plazas where road users entering a toll-ticket facility are issued a toll ticket, the legend PAY TOLL shall be replaced with a suitable legend such as TAKE TICKET.

Guidance:

The Pay Toll Advance Warning signs should be installed overhead at approximately 1 mile and 1/2 mile in advance of mainline toll plazas at which some or all lanes are required to come to a stop to pay a toll (see Sections 2F.14 and 2F.15).

<u>The Take Ticket Advance Warning sign should be installed overhead at approximately 1 mile and 1/2 mile in advance of mainline toll plazas at which some or all lanes are required to come to a stop to take a toll ticket (see Sections 2F.14 and 2F.15).</u>

<u>The Pay Toll and Take Ticket Advance Warning signs should be overhead-mounted.</u> Separated for distinction between recommendation for sign placement and recommendation for mounting type. Option:

If there is insufficient space for the W9-6<u>or W9-6e</u> sign at the 1-mile or 1/2-mile advance locations, the Pay Toll <u>or Take Ticket</u> Advance Warning (W9-6<u>b</u>P, <u>W9-6gP</u>) Advance Warning (W9-6P) plaque (see Section 2F.07) may be installed at those advance locations above the appropriate guide sign(s) that relate to toll payment types.

An additional W9-6 or W9-6e sign may be installed approximately 2 miles in advance of a mainline toll plaza. This sign may be either overhead_or post-mounted.

If the visibility of a ramp toll plaza at which some or all lanes are required to come to a stop to pay a toll or take a ticket is limited, the W9-6e sign may also be installed in advance of the ramp toll plaza.

Figure 2F-4. Toll Plaza Warning Signs and Plaques

Section 2F.07 Pay Toll and Take Ticket Advance Warning Plaques (W9-6bP, W9-6gP) Option:

The Pay Toll <u>or Take Ticket</u> Advance Warning (W9-6bP, W9-6gP) plaque (see Figure 2F-32F-4) may be installed above the appropriate guide sign(s) relating to toll payment types at the 1-mile and/or 1/2-mile advance locations on the approach to a toll plaza if there is insufficient space for the W9-6 <u>or W9-6e</u> sign (see Section 2F.06) at those advance locations.

Standard:

The W9-6bP and W9-6gP plaques shall be a horizontal rectangle with black legend and border on a yellow background. The legend shall include display the distance to the toll plaza and, except for toll-ticket facilities, the toll for passenger or 2-axle vehicles. Where the toll for passenger or 2-axle vehicles is variable by time of day, a changeable message element shall be incorporated into the W9-6bP plaque to display the toll in effect. For toll plazas where road users entering a toll-ticket facility are issued a toll-ticket, the legend PAY TOLL shall be replaced with a suitable legend such as TAKE TICKET.

Option:

The distance to the toll plaza may be omitted from the W9-6<u>b</u>P <u>and W9-6gP</u> plaque<u>s</u> if the distance is displayed on the guide sign that the plaque accompanies.

The toll for passenger or 2-axle vehicles may be omitted from the W9-6bP plaque if the toll information is displayed on the guide sign that the plaque accompanies.

- Section 2F.08 Stop Ahead Pay Toll and Take Ticket Warning Signs (W9-6a, W9-6f)
- **Standard:**

The Stop Ahead Pay Toll (W9-6a) sign shall be a horizontal rectangle with a black legend and border on a yellow background. The legend shall include display the toll for passenger or 2-axle vehicles (see Figure 2F-32F-4). Where the toll for passenger or 2-axle vehicles is variable by time of day, a changeable message element shall be incorporated into the W9-6a sign to display the toll in effect. For toll plazas where road users entering a toll-ticket facility are issued a toll ticket, the legend PAY TOLL shall be replaced with a suitable legend such as TAKE TICKET.

Guidance:

The Stop Ahead Pay Toll sign should be installed overhead downstream from the W9-6 sign that is 1/2 mile in advance of a mainline toll plaza where some or all of the lanes are required to come to a stop to pay a toll (see Sections 2F.14 and 2F.15). The location of the overhead sign should coincide with the approximate location where the mainline lanes begin to widen on the approach to the toll plaza lanes.

The Stop Ahead Pay Toll Advance Warning sign should be overhead-mounted. The location of the overhead sign should coincide with the approximate location where the mainline lanes begin to widen on the approach to the toll plaza lanes. Separated for distinction between recommendation for sign placement and recommendation for mounting type.

Where open-road tolling is used in addition to a toll plaza at a particular location, the W9-6a <u>or W9-6f</u> sign should be located such that the message is clearly related to the lanes that access the toll plaza and not to the open-road tolling lanes.

Option:

If there is insufficient space for the W9-6a or W9-6f sign at the recommended location, the Stop Ahead Pay Toll (W9-6ap6cP) or the Stop Ahead Take Ticket (W9-6hP) plaque (see Section 2F.09) may be installed at that location above the appropriate guide sign that relates to toll payment types.

If the visibility of a ramp toll plaza at which some or all lanes are required to come to a stop to pay a toll or take a ticket is limited, the W9-6a or W9-6f sign may also be installed in advance of the ramp toll plaza.

Section 2F.09 Stop Ahead Pay Toll and Take Ticket Warning Plaques (W9-6aP 6cP, W9-6hP)
Option:

The Stop Ahead Pay Toll (W9-6aP6cP) plaque (see Figure 2F-32F-4) may be installed above the appropriate guide sign at the location specified for the Stop Ahead Pay Toll (W9-6a) sign (see Section 2F.08) if there is insufficient space for the W9-6a sign at that location.

Standard.

The W9-6cP plaque shall be a horizontal rectangle with black legend and border on a yellow background. The legend shall include STOP AHEAD PAY TOLL and, except for toll-ticket facilities, display the toll for passenger or 2-axle vehicles. Where the toll for passenger or 2-axle vehicles is variable by time of day, a changeable message element shall be incorporated into the W9-6acP plaque to display the toll in effect. For toll plazas where road users entering a toll-ticket facility are issued a toll ticket, the legend PAY TOLL shall be replaced with a suitable legend such as TAKE TICKET.

37 Option:

The toll for passenger or 2-axle vehicles may be omitted from the W9-64P 6CP plaque if the toll information is displayed on the guide sign that the plaque accompanies.

Section 2F.10 LAST EXIT BEFORE TOLL Warning Plaques (W16-16P, W16-16aP)

Guidance:

The LAST EXIT BEFORE TOLL (W16-16P or W16-16aP) plaque (see Figure-2F-32F-4) should be used to notify road users of the last exit from a highway before it becomes a facility on which toll payments are required. The plaque should be installed above or below the appropriate guide signs for the exit (see Sections 2E.33 and 2E.36). For numbered exits, the Exit Number plaque (see Section 2E.XX) should be installed above the LAST EXIT BEFORE TOLL plaque.

47 Standard:

- The W16-16P plaque shall have a black legend and border on a yellow background.
- 49 Section 2F.11 TOLL Auxiliary SignWarning Plaque (M4-15W16-17P)
- 50 Standard:

1 2 3

4

5

Section 2F.13 2F.12 Toll Facility and Toll Plaza Guide Signs – General

Support:

Toll plazas are used on many toll highways, bridges, and tunnels for collection of tolls from road users. Electronic toll collection and/or open-road tolling might also be used on such facilities, either in addition to or in place of collecting toll payments at toll plazas.

Chapter 2G contains information regarding signs for preferential and managed lanes that are applicable to toll roads.

Chapter 3E contains information regarding pavement markings for certain toll plaza applications.

Standard:

Directional assemblies for entrances to a toll highway or to a road leading directly to a toll highway with no opportunity to exit before paying or being charged a toll, shall clearly indicate that the facility is a toll facility. Except where the State Toll Route sign (see Paragraph 8) is used, Tthe TOLL (M4-15W16-20P) auxiliary sign warning plaque (see Section 2F.11) shall be used above the route sign of a numbered toll facility in any route sign assembly that provides directions to the toll route from another highway-.

Except where the State Toll Route sign (see Paragraph 8) is used, A-a rectangular panel with the black legend TOLL on a yellow background shall be incorporated into the guide signs leading road users to a tolled highway (see Figure 2F-5)

Guide signs for toll highways, toll plazas, and tolled or priced managed lanes (see Chapter 2G) shall have white legends and borders on green backgrounds, except as specifically provided by Sections 2F.13 through 2F.16.

Option:

A State Toll Route sign (see Paragraph 8) may be used in lieu of the State Route (M1-5) sign in combination with the TOLL (W16-20P) warning plaque or the TOLL panel (see Paragraphs 10 and 11).

Standard:

A State Toll Route sign shall incorporate into its design the word TOLL using the same letter height, legend, background colors, and overall plaque dimensions specified for the W16-20P plaque.

The Interstate, Off-Interstate, and U.S. Route signs shall not be modified for tolled facilities.

Option:

Where conditions do not permit accommodate separate signs, or where it is important to associate a particular regulatory or warning message with specific guidance information, regulatory and/or warning messages may be combined with guide signs for toll plazas using plaques, header panels, or rectangular regulatory or warning panels incorporated within the guide signs, as long as the proper legend and background colors are preserved.

Standard:

When regulatory messages are incorporated within a guide sign, they shall be on a rectangular panel with $\underline{\mathbf{a}}$ black legend on a white background. When warning messages are incorporated within a guide sign, they shall be on a rectangular panel with $\underline{\mathbf{a}}$ black legend on a yellow background.

Figure 2F-5. Examples of Guide Signs for Entrances to Toll Highways or Ramps

Guidance:

Guide signs for toll plazas should be designed in accordance with the general principles of guide signs and the specific provisions of Chapter 2E.

Signs for toll plazas should systematically provide road users with advance and toll plaza lane-specific information regarding:

- A. The amount of the toll, the types of payment accepted, and the type(s) of registered ETC accounts accepted for payment;
- B. Which lane or lanes are required or allowed to be used for each available payment type; and
- C. Restrictions on the use of a toll plaza lane or lanes by certain types of vehicles (such as cars only or no trucks).

Standard:

1 Signs for attended lanes at toll plazas shall include word messages such as FULL-2 SERVICE, CASH, CHANGE, or RECEIPTS incorporate the Toll Taker (M4-17) symbol panel (see 3 Figures 2F-8-6 through 2F-11 2F-9). 4 5 Signs for Aattended lanes at toll plazas may incorporate the Toll Taker (M4-17) symbol also display word 6 legends such as FULL SERVICE, CASH, CHANGE, or RECEIPTS (see Figures 2F-8-6 and through 2F-119), 7 in a size that makes the symbol the predominant feature of the sign, to supplement the required word message 8 symbol panel when lanes have different services available through them. 9 Figure 2F-6. Examples of Conventional Toll Plaza Advance Signs Figure 2F-7. Examples of Toll Plaza Canopy Signs 10 11 Figure 2F-8. Examples of Mainline Toll Plaza Approach and Canopy Signing 12 Figure 2F-9. Examples of guide Signs for a Mainline Toll Plaza on a Diverging Alignment 13 from Open-Road ETC Lanes 14 **Standard:** 15 Signs for Exact Change lanes at toll plazas shall incorporate the Exact Change (M4-18) symbol panel an appropriate word message, such as EXACT CHANGE and, except for ticketed systems, 16 display the amount of the toll for passenger vehicles (see Figures 2F-8-6 through 2F-119). 17 18 Option: 19 Signs for Exact Change lanes at toll plazas may include include the Exact Change (M4-18) symbol-an 20 appropriate word legend, such as EXACT CHANGE (see Figures 2F-8-6 and 2F-9), in a size that makes the 21 symbol the predominant feature of the sign, to supplement the required word message symbol panel. 22 **Standard:** 23 H-When used, the M4-17 and M4-18 symbols panels shall be used only as panels within guide signs-24 that accompany the required word messages. The M4-17 and M4-18 symbols or panels shall not be 25 used as an independent sign or within a sign assembly. 26 If only vehicles with registered ETC accounts are allowed to use a toll plaza lane, the signs for such 27 lanes shall incorporate the pictograph adopted by the toll facility's ETC payment system and the 28 regulatory message ONLY (see Figures 2F-1, 2F-86, 2F-97, and 2F-119, 2F-10 and 2F-11). The use, size, 29 and placement of the ETC pictograph shall comply with the provisions of Sections 2F.02 and 2F.03 and 30 2F.04. 31 An Overhead-Arrow-Per-Lane Guide sign (see Figure 2F-10) shall be used in advance of a location where the mainline lanes split to separate traffic entering Open-Road ETC lanes from lanes entering a 32 33 toll plaza where other methods of payment are accepted and an option lane is provided at the split (see 34 Figure 2F-11). An Overhead-Arrow-Per-Lane sign shall not be used if there is no option lane at the 35 split. 36 Figure 2F-10. Overhead Arrow Per Lane Guide Sign for Split with Option Lane between 37 Open-Road ETC Lanes Only and Toll Plaza Lanes. 38 Figure 2F-11. Examples of Guide Signs for a Split with an Option Lane for a Mainline Toll 39 Plaza on a Diverging Alignment from Open-Road ETC Lanes 40 Option: 41 The ETC payment system's pictograph, without a purple underlay or purple header panel, may be used on 42 signs for Exact Change or attended lanes at toll plazas to indicate that vehicles with registered ETC accounts 43 may also use those lanes (see Figure 2F-97). 44 Section 2F.13 Electronic Toll Collection (ETC) Signs - General New Section with paragraphs from existing Section 2F.13 45 46 Support: 47 Figure 2F-5 shows examples of guide signs for entrances to various types of toll highways and for ETC 48 account-only entrances to non-toll highways.

49

Standard:

Signing for entrances to toll highways where ETC is employed only through license plate character recognition such that road users are not required to establish a toll account or register their vehicle equipment shall comply with the provisions of Paragraphs 4 and 5 (see Figure 2F-6) of Section 2F.12. Support:

Figure 2F-12 shows examples of guide signs for the entrance to a toll highway on which tolls are collected electronically only and registration in a toll-account program is not required.

If only vehicles with registered ETC accounts are allowed to use a toll highway, the guide signs for entrances to such facilities shall incorporate the pictograph adopted by the toll facility's ETC payment system and the regulatory message ONLY (see Figures 2F-1, 2F-5, <u>2F-10, 2F-11, and-2F-612</u>). The use, size, and placement of the ETC pictograph and the use and color of the background and underlay panel shall comply with the provisions of Sections <u>2F.02 and 2F.03 and 2F.04</u>.

Support:

Sections <u>2F.05</u>, 2F.11, 2F.12, and 2F.17 contain additional provisions regarding signs for toll highways that only accept ETC payments.

Sections 2G.16 through 2G.18 contain additional provisions regarding signs for priced managed lanes that only accept ETC payments.

Option: Relocated to new Section 2F.18

Where a toll highway on which tolls are collected only electronically also accepts payments from registered toll account users and those road users not registered in a toll account program are assessed a nominal surcharge in addition to the toll, or registered toll account users are assessed a discounted toll, such information may be displayed on a separate information sign near the entrance to such a facility (see Figure 2F 6).

Support:

Figure 2F-7-13 shows an example of guide signs for alternative toll and non-toll ramp connections to a non-toll highway (see Section 2F.19).

Many different ETC payment systems are used by the various toll facility operators. Some of these systems accept payment from other systems' accounts.

Option:

Where a facility will accept payments from other systems' accounts in addition to its primary ETC-account payment system, such information may be displayed on a separate information sign near the entrances to such a facility or in advance of a toll plaza or open-road tolling lanes, as space allows between primary signs.

Figure 2F-12. Examples of Guide Signs for the Entrance to a Toll Highway on which Tolls are Collected Electronically Only

Figure 2F-13. Examples of Guide Signs for Alternative Toll and Non-Toll Ramp

Connections to a Non-Toll Highway

Section 2F.14 Advance Signs for Conventional Toll Plazas

Guidance:

For conventional toll plazas (those without a divergence onto a separate alignment from mainline-aligned open-road tolling or ETC-Only lanes), one or more sets of overhead advance guide signs complying with the provisions of this Section should be provided. The advance guide signs for multi-lane toll plazas should provide information regarding which lanes to use for all of the toll payment methods accepted at the toll plaza. These signs should include toll plaza lane numbers (if used), or action messages or lane-use information such as LEFT LANE(S), CENTER LANE(S), RIGHT LANE(S), or down arrows over the approximate center of each applicable lane. These signs should also incorporate regulatory messages indicating any restrictions or prohibitions on the use of the lanes associated with the various types of payment methods by certain types of vehicles. For mainline toll plazas, these signs should be at least 1/2 mile in advance of the toll plaza, and farther if practical.

Additional guide signs with lane information for the toll payment types should be provided between approximately 1/4 mile and 800 feet in advance of the toll plaza at a location that avoids or minimizes obstruction of toll plaza canopy signs (see Section 2F.16) and lane-use control signals.

The number, mounting, and/or spacing of sets of advance signs for approaches to toll plazas on ramps, toll bridges, or tunnels, to accommodate a limited distance to the plaza from an intersection or from the start of the approach road to the bridge or tunnel, should be based on an engineering study or engineering judgment.

Support:

Figure 2F-10-8 shows examples of advance signs for a conventional toll plaza.

Section 2F.15 Advance Signs for Toll Plazas on Diverging Alignments from Open-Road ETC Account-Only Lanes

Support:

Open-Road ETC lanes are sometimes located on the normal mainline alignment while the lanes for other toll payment methods are located at a toll plaza on a separate alignment (see Figure 2F-119). Since road users paying cash tolls must diverge from the mainline alignment, similar to a movement for an exit, it is important that the guide signs in advance of and at the point of divergence clearly indicate the required lane use and/or movements.

Guidance:

For toll plazas located on a separate alignment that diverges from mainline-aligned Open-Road ETC lanes where vehicles are required to have a registered ETC account to use the Open-Road Tolling lanes, overhead advance signs should be provided at approximately 1 mile and 1/2 mile in advance of the divergence point. Both the 1-mile and 1/2-mile advance signs should include:

- A. The ETC (pictograph) Account-Only guide sign (see Figures 2F-<u>8-6</u> and 2F-<u>119</u>) with a down arrow over the <u>approximate</u> center of each lane that will become an Open-Road ETC lane;
- B. For the lane or lanes which will diverge to a toll plaza, guide signs conforming to the provisions of Section 2F.132F.12, indicating which lane or lanes will diverge to the toll plaza for the various cash toll payment methods; and
- C. Regulatory signs, plaques, or panels within the guide signs, indicating any restrictions or prohibitions of certain types of vehicles from toll plaza lanes associated with the various types of payment methods.

At or near the theoretical gore of the divergence point, an additional set of overhead guide signs should be provided and should include:

- A. The ETC (pictograph) Account-Only guide sign (see Figures 2F-<u>8-6</u> and 2F-<u>119</u>) with a down arrow over the approximate center of each Open-Road ETC lane;
- B. Guide signs conforming to the provisions of Section <u>2F.12</u> and <u>2F.13</u>, with diagonally upward-pointing directional arrow(s) over the approximate center of each lane indicating the direction of the divergence, and providing lane information for all types of payment methods accepted at the toll plaza; and
- C. Regulatory signs, plaques, or panels within the guide signs, indicating any restrictions or prohibitions on the use of the toll plaza lanes associated with the various types of payment methods by certain types of vehicles.

Approximately 800 feet in advance of the toll plaza at a location that avoids or minimizes any obstruction of the toll plaza canopy signs (see Section 2F.16) and lane-use control signals, an additional set of overhead advance signs with lane information for the toll payment types should be provided.

Standard:

The use of down and directional arrows on the signs at the locations described in Paragraphs 2 through 4 shall comply with the provisions of Section 2D.08.

Support:

Figure 2F-11-9 shows an example of advance signs for toll plazas on a diverging alignment from Open-Road ETC Account-Only Lanes.

Section 4K.02 contains information regarding the use of lane-use control signals for Open-Road ETC lanes for temporary lane closure purposes.

50 Section 2F.16 Toll Plaza Canopy Signs

51 Standard:

A sign complying with the provisions of Section 2F.13 2F.12 shall be provided above the approximate center of each lane that is not an Open-Road ETC lane, mounted on or suspended from the toll plaza canopy, or on a separate structure immediately in advance of the plaza located such that each sign is clearly related to an individual toll lane, indicating the payment type(s) accepted in the lane and any restrictions or prohibitions of certain types of vehicles that apply to the lane. Except for toll-ticket systems, the toll for passenger or 2-axle vehicles shall be included on the canopy sign or on a separate sign mounted on the upstream side of the tollbooth.

The background color of a canopy sign for an ETC Account-Only toll plaza lane shall be purple (see Figure 2F-97).

Option:

Where vehicles are required to have a registered ETC account to use the lane, one or two flashing yellow beacons (see Section 4K.04) may supplement a canopy sign over an ETC Account-Only lane to call special attention to the location of the ETC Account-Only lane within the plaza.

The canopy sign for an ETC-Only toll plaza lane in which a regulatory speed limit is not posted and in which vehicles are not required to stop may display an advisory speed within a horizontal rectangular panel with a black legend and yellow background within the bottom portion of the canopy sign.

Standard:

Flashing beacons supplementing a canopy sign over an ETC Account-Only lane shall be mounted directly above or alongside the sign in a manner that is separated from any lane-use control signals for that lane (see Figure 2F-97).

For multi-lane toll plazas, lane-use control signals (see Section 4K.02) shall be provided above the <u>approximate</u> center of each toll plaza lane that is not an Open-Road ETC lane to indicate the open or closed status of each lane. Lane-use control signals shall not be used to call attention to a lane for a specific toll payment type such as ETC Account-Only lanes.

25 Support:

- Part 6 contains information regarding the closing of a lane for temporary traffic control purposes.
- Figure 2F-9-7 shows examples of toll plaza canopy signs.

Section 2F.17 Guide Signs for Entrances to ETC Account-Only Facilities

29 Support:

Some toll highways, bridges, and tunnels are restricted to use only by vehicles with a specific registered ETC account.

Standard:

Where vehicles are required to have a registered ETC account to use an ETC Account-Only facility, guide signs for the facility shall comply with the applicable provisions of Chapter 2E and specifically with the applicable provisions of Section 2F.13.

Guide signs for the entrance ramps to such ETC Account-Only facilities shall incorporate the pictograph of the toll facility's ETC payment system and the word ONLY in a header panel or plaque designed in accordance with the provisions of Section 2F.13 (see Figure 2F-5).

Option:

A separate information sign displaying the route number, the TOLL warning panel (see Sections 2F.12 and 2F.13), and the legend NO CASH may be located within the sequence of the Advance guide signs on the approach to the entrance to an ETC Account-Only facility (see Figure 2F-12).

Exit Gore signs for entrance ramps to such ETC Account-Only facilities may incorporate the pictograph of the toll facility's ETC payment system and the word ONLY in a header panel or plaque designed in accordance with the provisions of Section 2F.13 (see Figure 2F-12 and Figure 2F-13)

Support:

Section <u>2F.122F.05</u>contains information regarding ETC <u>Account</u>-Only auxiliary <u>signs plaques</u> for use with route signs in route sign assemblies.

Section 2F.18 Guide Signs for Entrances to ETC-Only Facilities

50 Support:

Some toll highways, bridges, and tunnels collect tolls electronically using license plate character recognition in which the registered vehicle owner is then billed by postal mail. Registration in an ETC account program is not required. Registered ETC account users might have the option to be billed through their accounts if the facility also accepts such payments.

Standard:

1

2

3

4 5

6

7

8

9

10

11

12

13

14 15

16

17

19

20

22

23

24

25

26

27

28

29

30 31

32

33

35

36 37

38 39

41

43

44

45

47

48

49

50

Where vehicles are not required to have a registered ETC account to use an ETC-Only facility, guide signs for the facility shall comply with the applicable provisions of Chapter 2E and specifically with the applicable provisions of Section 2F.13.

Advance and Exit Direction guide signs for the entrances to such ETC-Only facilities that do not require the registration in an ETC toll account program shall not display a pictograph of an accepted ETC payment system or use purple as a background color on any portion of the signs.

If the ETC-Only facility collects tolls by post-travel billing of registered vehicle owners without registration in an ETC toll account program, a separate informational guide sign, if used, shall display one of the following legends (see Figure 2F-12):

- A. TOLL BILLED BY MAIL ONLY, if there is no alternative payment method; or
- B. TOLL BILLED BY MAIL OR [ETC Account Pictograph], if the facility also accepts payments from registered users of an ETC account program.

18 Option:

A plaque with the legend NO CASH may be added below the signs described in Paragraph 4 of this section.

21 Guidance:

> The signs described in Paragraph 4 of this Section should be located within the sequence of Advance Guide signs for the entrance to the facility and/or at a location along the facility itself (see Figure 2F-12). Option:

If the ETC-Only facility also accepts payments from other toll account programs, but does not require registration in the primary ETC account program associated with the facility in order to use the facility, then the pictographs of the other accepted ETC account programs may be displayed on the separate information sign displaying the legend TOLL BILLED BY MAIL or ETC System. (See Figure 2F-12).

If, in addition to a toll, a nominal surcharge (not a fine, penalty or violation) is assessed road users not registered in the toll account programin addition to the toll, or registered toll account users are assessed a discounted toll, such information may be displayed on a separate information sign nearon the approach to the entrance to such a facility (see Figure 2F-612). Paragraph 14 from existing Section 2F.13

Section 2F.19 Guide Signs for ETC-Only Entrance Ramps to Non-Toll Highways

34 Support:

> In some cases, access to or from a non-toll route might be provided by a ramp on which a toll is charged in order to manage congestion, limit access, or for other reasons. The toll ramp might be provided as an alternative to or in lieu of a ramp providing similar access without charging a toll. Figures 2F-5 and 2F-13 show examples of guide signs for a ramp on which a toll is charged to enter a non-toll route.

Standard:

40 Guide signs for ETC-Only Entrance Ramps to non-toll highways shall comply with the provisions of 2F.18.

42 Option:

> A NO-TOLL panel with a black legend and a yellow background may be included on the top section of the Exit Gore sign for an exit that provides access to the facility without charging a toll.

Section 2F.18-2F.20 ETC Account Program Information Signs

46 **Standard:**

> Except as provided in Paragraph 2, signs that inform road users of telephone numbers, Internet addresses, including domain names and uniform resource locators (URLs), or e-mail addresses for enrolling in an ETC account program of a toll facility or managed lane, obtaining an ETC transponder, and/or obtaining ETC account program information shall only be installed in rest areas, parking areas,

or similar roadside facilities where the signs are viewed only by pedestrians or occupants of parked vehicles.

Option:

1

2

3 4

5

6

8

9

ETC account program information signs displaying telephone numbers that have no more than four characters may be installed on roadways in locations where they will not obscure the road user's view of higher priority traffic control devices and that are removed from key decision points where the road user's view is more appropriately focused on other traffic control devices, roadway geometry, or traffic conditions, including exit and entrance ramps, intersections, toll plazas, temporary traffic control zones, and areas of limited sight distance.

General	
2G.01	Scope
2G.02	Sizes of Preferential and Managed Lane Signs
Regulatory S	
2G.03	Regulatory Signs for Preferential Lanes – General
2G.04	Vehicle Occupancy Definition Signs (R3-10 Series, R3-13 Series)
2G.05	Preferential Lane Operation Signs (R3-11 Series, R3-14 Series)
2G.06	Preferential Lane Advance Signs (R3-12, R3-12e, R3-12f, R3-15, R3-15a, R3-15d)
2G.07	Preferential Lane Ends Signs (R3-12a, R3-12b, R3-12c, R3-12d, R3-12g, R3-12h, R3-
	<u>R3-15c, R3-15e)</u>
Warning Sign	
2G.08	Warning Signs on Median Barriers for Preferential Lanes
<u>2G.09</u>	High-Occupancy Vehicle (HOV) Plaque (W16-11P)
Guide Signs	
2G.10	Preferential Lane Guide Signs – General
2G.11	Signing for Initial Entry Points to Preferential Lanes
2G.12	Signing for Intermediate Entry Points to Preferential Lanes
2G.13	Signing for Egress from Preferential Lanes to General-Purpose Lanes
2G.14	Signing for Direct Entrances to Preferential Lanes from Another Highway
<u>2G.15</u>	Signing for Direct Exits from Preferential Lanes to Another Highway
Managed Lar	ne Signs
2G.16	Signs for Managed Lanes – General
2G.17	Signs for Priced Managed Lanes – General
2G.18	Regulatory Signs for Priced Managed Lanes
2G.19	Guide Signs for Priced Managed Lanes
2G.20	Signs for Part-Time Travel on a Shoulder – General
<u>2G.21</u>	Regulatory Signs and Plaques for Part-Time Travel on a Shoulder
2G.22	Warning Signs for Part-Time Travel on a Shoulder
2G.23	Guide Signs for Part-Time Travel on a Shoulder
2G.24	Lane-Use Control Signals for Part-Time Travel on a Shoulder
<u>2G.25</u>	Lane-Use Control Signals for Active Lane Management on Freeways and
Expr	<u>ressways</u>
2G.26	Variable Speed Limits for Active Traffic Management on Freeways and Expres

Section 2G.01 Scope

Support:

Preferential lanes are lanes designated for special traffic uses such as high-occupancy vehicles (HOVs), light rail, buses, taxis, or bicycles. Preferential lane treatments might be as simple as restricting a turning lane to a certain class of vehicles during peak periods, or as sophisticated as providing a separate roadway system within a highway corridor for certain vehicles.

Preferential lanes might be barrier-separated (on a separate alignment or physically separated from the other travel lanes by a barrier or median), buffer-separated (separated from the adjacent general-purpose lanes only by a narrow buffer area created with longitudinal pavement markings), or contiguous (separated from the adjacent general-purpose lanes only by a lane line). Preferential lanes might allow continuous access with the adjacent general-purpose lanes or restrict access only to designated locations. Preferential lanes might be operated in a constant direction or operated as reversible lanes. Some reversible preferential lanes on a

divided highway might be operated counter-flow to the direction of traffic on the immediately adjacent general-purpose lanes.

Preferential lanes might be operated on a 24-hour basis, for extended periods of the day, during peak travel periods only, during special events, or during other activities.

Open-road tolling lanes and toll plaza lanes that segregate traffic based on payment method are not considered preferential lanes. Chapter 2F contains information regarding signing of open-road tolling lanes and toll plaza lanes.

Managed lanes typically restrict access with the adjacent general-purpose lanes to designated locations only.

Under certain operational strategies, such as the occupancy requirement of an HOV lane changing in response to actual congestion levels, a managed lane is a special type of preferential lane (see Sections 2G.03 through 2G.07).

A managed lane operated on a real-time basis in response to changing conditions might be operated as an HOV lane for a period of time as needed to manage congestion levels.

Sections $2G.\underline{16}.\underline{17}$ through $2G.\underline{18}.\underline{19}$ contain additional information regarding signs for managed lanes that use tolling or pricing as a management strategy.

Section 9B.04 contains information regarding Preferential Lane signs for bike lanes.

Standard:

1

2

3

4

5

6

7

8

9

10

11 12

13

1415

16

17

18

19

20

21

22

23

25

26

27

28

29

Unless otherwise provided, the provisions of this Chapter shall not apply to bike lanes.

Section 2G.02 Sizes of Preferential and Managed Lane Signs

Standard:

Except as provided in Section 2A.11, the sizes of preferential and managed lane signs that have standardized designs shall be as shown in Table 2G-1.

24 Support:

Section 2A.11 contains information regarding the applicability of the various columns in Table 2G-1. Option:

Signs larger than those shown in Table 2G-1 may be used (see Section 2A.11).

Table 2G-1. Managed and Preferential Lanes Sign and Plaque Minimum Sizes

2020 NPA – Chapter 2G

42.

Section 2G.03 Regulatory Signs for Preferential Lanes – General

Standard:

When a preferential lane is established, the Preferential Lane regulatory signs (see Figure 2G-1) and pavement markings (see Chapter $\frac{3D3E}{2}$) for these lanes shall be used to advise road users.

Support:

Preferential Lane (R3-10 series through R3-15 series) regulatory signs consist of several different general types of regulatory signs as follows (see Figure 2G-1):

- A. Vehicle Occupancy Definition signs define the vehicle occupancy requirements applicable to an HOV lane (such as "2 OR MORE PERSONS PER VEHICLE") or types of vehicles not meeting the minimum occupancy requirement (such as motorcycles or ILEVs) that are allowed to use an HOV lane (see Section 2G.04).
- B. Periods of Operation signs notify road users of the days and hours during which the preferential restrictions are in effect (see Section 2G.05).
- C. Preferential Lane Advance signs notify road users that a preferential lane restriction begins ahead (see Section 2G.06).
- D. Preferential Lane Ends signs notify users of the termination point of the preferential lane restrictions (see Section 2G.07).

Figure 2G-1. Preferential Lane Regulatory Signs and Plaques (2 Sheets)

Standard:

Regulatory signs applicable only to a preferential lane shall be distinguished from regulatory signs applicable to general-purpose lanes by the inclusion of the applicable symbol(s) and/or word(s) (see Figure 2G-1).

Support:

The symbol and word message displayed on a particular Preferential Lane regulatory sign will vary based on the specific type of allowed traffic and on other related operational constraints that have been established for a particular lane, such as an HOV lane, a bus lane, or a taxi lane.

Option:

Changeable message signs may supplement, substitute for, or be incorporated into static Preferential Lane regulatory signs where travel conditions change or where multiple types of operational strategies (such as variable occupancy requirements or vehicle types) are used and varied throughout the day or week, or on a real-time basis, to manage the use of, control of, or access to preferential lanes.

Support:

Figure 2G-1 illustrates examples of changeable messages incorporated into static Preferential Lane regulatory signs <u>displaying open and closed status using lane-use control signal indications (see Chapter 4M).</u>
The LED sign legends are normally the variable text such as the open and closed lane legends.

Standard:

When changeable message signs (see Chapter 2L) are used as regulatory signs for preferential lanes, they shall be the required sign size and shall display the required letter height and legend format that corresponds to the type of roadway facility and design speed.

Guidance:

When Preferential Lane regulatory signs are used on conventional roads, the decision regarding whether to use a post-mounted or overhead version of a particular type of sign should be based on an engineering study that considers the available space, the existing signs for the adjacent general-purpose traffic lanes, roadway and traffic characteristics, the proximity to existing overhead signs, the ability to install overhead signs, and any other unique local factors.

If overhead regulatory signs applicable only to a preferential lane are located in approximately the same longitudinal position along the highway as overhead signs applicable only to the general-purpose lanes, the signs for the preferential lane should be separated laterally from the signs for the general-purpose lanes to the maximum extent practical to minimize conflicting information, while maintaining their visual relationship to the lanes below necessitated by specific legend or arrows indicating lane assignment.

Standard:

If used, overhead Preferential Lane (R3-13 series, R3-14 series, and R3-15 series) regulatory signs shall be installed on the side of the roadway where the entrance to the preferential lane is located and any appropriate adjustments shall be made to the sign message.

Option:

Where a median of sufficient width is available, the R3-13 series and R3-15 series signs may be post-mounted.

Support:

The sizes for Preferential Lane regulatory signs will differ to reflect the design speeds for each type of roadway facility. Table 2G-1 provides sizes for each type of roadway facility.

Guidance:

The edges of Preferential Lane regulatory signs that are post-mounted on a median barrier should not project beyond the outer edges of the barrier, including in areas where lateral clearance is limited.

Option:

Where lateral clearance is limited, Preferential Lane regulatory signs that are post-mounted on a median barrier and that are 72 inches or less in width may be skewed up to 45 degrees in order to fit within the barrier width or may be mounted higher, such that the vertical clearance to the bottom of the sign, light fixture, or structural support, whichever is lowest, is not less than 14-17 feet above any portion of the pavement and shoulders.

Standard:

Where lateral clearance is limited, Preferential Lane regulatory signs that are post-mounted on a median barrier and that are wider than 72 inches shall be mounted with a vertical clearance that complies with the provisions of Section 2A.18 for overhead mounting if any portion of the sign extends over the roadway.

Guidance:

On conventional roadways, Preferential Lane regulatory sign spacing should be determined by engineering judgment based on speed, block length, distances from adjacent intersections, and other site-specific considerations.

Support:

Sections 2G.04 and 2G.05 contain provisions regarding the placement of Preferential Lane regulatory signs on freeways and expressways.

Standard:

The signs illustrated in Figure 2G-1 that incorporate the diamond symbol shall be used exclusively with preferential lanes for high-occupancy vehicles to indicate the particular occupancy requirement and time restrictions applying to that lane. The signs illustrated in Figure 2G-1 that do not have a diamond symbol shall be used with preferential lanes that are not HOV lanes, but are designated for use by other types of vehicles (such as bus and/or taxi use).

Option:

Agencies may select from either the HOV abbreviation or the diamond symbol, or use both, to reference the HOV lane designation.

Standard:

When the diamond symbol (or HOV abbreviation) is used without text on the post-mounted Preferential Lane (R3-10 series, R3-11 series, and R3-12 series) regulatory signs, it shall be centered on the top line of the sign. When the diamond symbol (or HOV abbreviation) is used with associated text on the post-mounted Preferential Lane (R3-10 series, R3-11 series, and R3-12 series) regulatory signs, it shall appear to the left of the associated text. When the diamond symbol is used on the overhead-Preferential Lane (R3-13, R3-13a, R3-14, and R3-14a) regulatory signs, it shall appear in the top left quadrant. The diamond symbol for the R3-15, R3-15a, R3-15b, and R3-15c signs shall appear on the left-hand side of the sign. The diamond symbol shall not be used on the bus, taxi, or bicycle Preferential Lane signs.

Vehicle Occupancy Definition, Periods of Operation, and Preferential Lane Advance regulatory signs for HOV lanes shall display the minimum allowable vehicle occupancy requirement established for each HOV lane, displayed immediately after the word message HOV-or the diamond symbol. Support:

The agencies that own and operate HOV lanes have the authority and responsibility to determine how they are operated and the minimum occupancy requirements. Information about federal requirements for certain types of vehicles not meeting the minimum occupancy requirement to be eligible to use HOV lanes that receive Federal-aid program funding and about requirements associated with proposed significant changes to the operation of an existing HOV lane and certain vehicles are contained in the "Federal-Aid Highway Program Guidance on High Occupancy Vehicle (HOV) Lanes" (see Section 1A.11).

Standard: Paragraphs Relocated to New Section 2G.16

The provisions of Sections 2G.03 through 2G.07 regarding regulatory signs for Preferential lanes shall apply to managed lanes operated at all times or at certain times by varying vehicle occupancy requirements (HOV) or by using vehicle type restrictions as a congestion management strategy. Such managed lanes shall use changeable message signs or changeable message elements within static signs to display the appropriate regulatory sign messages only when they are in effect.

When certain types of vehicles (such as trucks) are prohibited from using a managed lane or when a managed lane is restricted to use by only certain types of vehicles during certain operational strategies, regulatory signs or regulatory panels within the appropriate guide signs that include changeable message elements shall be used to display the open/closed status of the managed lane for such vehicle types.

When the vehicle occupancy required for use of an HOV lane is varied as a part of a managed lane operational strategy, regulatory signs that include changeable message elements shall be used to display the required vehicle occupancy in effect.

Support:

See Section 2G.17 for regulatory signs for managed lanes that use tolling or pricing as a congestion-management strategy, either exclusively or with other management strategies.

Figures 2G-2 and 2G-3 illustrate the use of regulatory signs for the beginning, along the length, and at the end of contiguous or buffer-separated preferential lanes that provide continuous access with the adjacent general-purpose lanes.

Figure 2G-2. Example of Signing for an Added Continuous-Access Contiguous of Buffer-Separated HOV Lane

Figure 2G-3. Example of Signing for a General Purpose Lane that Becomes a Continuous-Access Contiguous Buffer-Separated HOV Lane

Section 2G.04 <u>Preferential Lane Vehicle Occupancy Definition Regulatory Signs (R3-10 Series, and R3-13 Series)</u>

Standard:

The R3-10, R3-13, and R3-13a Vehicle Occupancy Definition signs (see Figure 2G-1) shall be used where agencies determine that it is appropriate to provide a sign that defines the minimum occupancy of vehicles that are allowed to use an HOV lane.

Guidance:

The Inherently Low Emission Vehicle (ILEV) (R3-10a) sign (see Figure 2G-1) should be used when it is permissible for a properly labeled and certified ILEV, regardless of the number of occupants, to use an HOV lane. When used, the ILEV signs should be post-mounted in advance of and at intervals along the HOV lane based upon engineering judgment and the placement of other Preferential Lane regulatory signs. The R3-10a sign is only applicable to HOV lanes and should not to be used with other preferential lane applications. Support:

ILEVs are defined by the Environmental Protection Agency (EPA) as vehicles having no fuel vapor

(hydrocarbon) emissions and are certified by the EPA as meeting the emissions standards and requirements specified in 40 CFR 88-311-93 40 CFR §88.311-93 and 40 CFR 88.312-93(c).

Guidance:

The legend format of the R3-10 and R3-13 signs should have the following sequence:

2020 NPA – Chapter 2G Page 259 of 781 December 2020

```
    A. Top Line: "HOV 2+ ONLY" (or 3+ or 4+ if appropriate)
    B. Bottom Lines: "2 OR MORE PERSONS PER VEHICLE" (or 3 or 4 if appropriate)
    The legend format of the R3-13a sign should have the following sequence:
    A. Top Line: "HOV 2+ ONLY" (or 3+ or 4+ if appropriate)
    B. Middle Lines: "2 OR MORE PERSONS PER VEHICLE" (or 3 or 4 if appropriate)
    C. Bottom Lines: Times and days the occupancy restriction is in effect
```

Support:

Section 2G.17 18 contains information regarding the legends of Vehicle Occupancy Definition signs for a priced managed lane that has an occupancy requirement for non-toll travel.

Standard:

For barrier- or buffer-separated or contiguous preferential lanes where access between the preferential and general-purpose lanes is restricted to designated locations on freeways and expressways, an overhead Vehicle Occupancy Definition (R3-13 or R3-13a) sign shall be installed at least 1/2 mile in advance of the beginning of or initial entry point to an HOV lane. These signs shall only be displayed in advance of the beginning of or initial or intermediate entry point to HOV lanes.

For buffer-separated or contiguous HOV lanes where access is restricted to designated locations on freeways and expressways, the sequence of a post-mounted Periods of Operation (R3-11a) sign (see Section 2G.05) followed by a post-mounted Vehicle Occupancy Definition (R3-10) sign shall be located at intervals not greater than 1/2 mile along the length of the access restricted HOV lane, at of designated gaps where vehicles are allowed to legally access the HOV lane, and within designated enforcement areas as defined by the operating agency. Relocated from later in Section, portions of provision changed to Option that follows

Option:

For buffer-separated or contiguous HOV lanes where access is restricted to designated locations on freeways and expressways, the sequence of a post-mounted Periods of Operation (R3-11a) sign (see Section 2G.05) followed by a post-mounted Vehicle Occupancy Definition (R3-10) sign may be located at intervals of approximately 1/2 mile along the length of the HOV lane.

For barrier-separated HOV lanes on freeways and expressways, the sequence of a post-mounted Periods of Operation (R3-11a) sign (see Section 2G.05) followed by a post-mounted Vehicle Occupancy Definition (R3-10) sign may be located at intervals of approximately 1/2 mile along the length of the HOV lane, at intermediate entry points, and at designated enforcement areas as defined by the operating agency.

Standard:

For buffer-separated or contiguous HOV lanes where access is restricted to designated locations, the sequence of a post-mounted Periods of Operation (R3-11a) sign followed by a post-mounted Vehicle-Occupancy Definition (R3-10) sign shall be located at intervals not greater than 1/2 mile along the length of the access restricted HOV lane, at designated gaps where vehicles are allowed to legally access the HOV lane, and within designated enforcement areas as defined by the operating agency. Relocated to earlier in Section, portions of provision changed to Option

For buffer-separated or contiguous HOV lanes where continuous access with the adjacent general-purpose lanes is provided on freeways and expressways, the sequence of a post-mounted Periods of Operation (R3-11a) sign (see Section 2G.05) followed by a post-mounted Vehicle Occupancy Definition (R3-10) sign, and ILEV (R3-10a) signs if appropriate, shall be located at intervals not greater than 1/2 mile along the length of the HOV lane.

Guidance:

<u>On freeways and expressways,</u> <u>Fthe signs within each Preferential Lane regulatory sign sequence should</u> be separated by a minimum distance of 800 feet and a maximum distance of 1,000 feet.

On conventional roads, the distance between Preferential Lane regulatory signs within each sequence should be determined by engineering judgment based on speed, block length, distances from adjacent intersections, and other site-specific considerations.

Standard:

For all types of direct access ramps that provide access to or lead to HOV lanes, a post-mounted Vehicle Occupancy Definition (R3-10) sign, and an ILEV (R3-10a) sign if appropriate, shall be used at the beginning or initial entry point for the direct access ramp.

Section 2G.05 <u>Preferential Lane Periods of Operation Regulatory Signs (R3-11 Series, and R3-14 Series)</u>

Guidance:

The sizes of post-mounted Periods of Operation (R3-11 series) signs should remain consistent to accommodate any manual addition or removal of a single line of text for each sign. Incorporated into following Support statement

Support:

The standardized sizes of post-mounted Preferential Lane Operation (R3-11 series) signs are consistent to accommodate any future addition or removal of a single line of legend for each sign. Each size accommodates two lines of legend for the times of day and days of week that the regulation is in effect. Consistent sign sizes are beneficial for agencies when ordering sign materials, as well as when making text-legend changes to existing signs if changes occur to operating times or occupancy restrictions in the future. For example, the R3-11c sign has space for one line located below "24 HOURS" if an agency determines that it is appropriate to display additional information (such as "MON—FRI"), yet the R3-11c sign has the same dimensions as the other R3-11 series signs.

Guidance:

Where the regulation is in effect during more than one time period of the day, such as during the morning and afternoon peak periods, the height of the R3-11 series signs should be suitably increased to accommodate the additional line(s) of legend.

Standard:

When used, the post-mounted <u>Periods of OperationPreferential Lane Operation</u> (R3-11 series) signs shall be located adjacent to the preferential lane, and the overhead <u>Preferential Lane Operation Periods of Operation</u> (R3-14 series) signs shall be mounted directly over the lane.

The legend format of the post-mounted <u>Preferential Lane Operation</u> Periods of Operation (R3-11 series) signs shall have the following sequence:

- A. Top Lines: Lanes applicable, such as "RIGHT LANE" or "2 RIGHT LANES" or "THIS LANE"
- B. Middle Lines: Eligible uses, such as "HOV 2+ ONLY" (or 3+ or 4+ if appropriate) or "BUSES ONLY" or other applicable uses or eligible turning movements
- C. Bottom Lines: Applicable times and days, such as "7 AM 9 AM" or "6:30 AM 9:30 AM, MON-FRI"

The legend format of the overhead <u>Preferential Lane Operation</u> <u>Periods of Operation</u> (R3-14 series) signs shall have the following sequence:

- A. Top Lines: Eligible uses, such as "HOV 2+ ONLY" (or 3+ or 4+ if appropriate) or "BUSES ONLY" or other applicable uses or eligible turning movements
- B. Bottom Lines: Applicable times and days, with the time and day placed above the down arrow, such as "7 AM 9 AM" or "6:30 AM 9:30 AM, MON-FRI" (When the operating periods exceed the available line width, the hours and days of the week shall be stacked as shown for the R3-14a sign in Figure 2G-1.)

For preferential lanes <u>restrictions</u> that are in effect on a full-time basis, <u>either</u> the full-<u>Preferential Lane Operation time Periods of Operation (R3-11b and R3-11b, R3-11c, R3-11e, R3-11g, R3-14b, R3-14e or R3-14g)</u> signs shall be <u>used, modified to display no legend relative to the period of operation or the legends of the part-time Periods of Operations (R3-11, R3-11a, R3-14, R3-14a) signs shall be <u>modified to display the legend 24 HOURS</u> except as provided in Paragraph 7. Deleted portion converted to Option that follows and text revised</u>

Option:

In lieu of using the full-time <u>Preferential Lane Operation</u> <u>Periods of Operation</u>-signs, <u>the legend 24 HOURS may be substituted for the times and days of the week on the part-time Preferential Lane Operation Periods of Operation</u> (R3-11, R3-11a, R3-11d, R3-11f, R3-14, R3-14d, and R3-14f) signs for preferential lane restrictions that are in effect on a full-time basis.

Support:

The 24 HOURS legend displayed on the R3-11c sign reinforces the full-time operation where several facilities in the same area have different hours of operation—some part-time, others full-time, or where the same lane changes from part-time to full-time operation somewhere along its length.

2020 NPA – Chapter 2G Page 261 of 781 December 2020

Standard:

The full-time <u>Preferential Lane Operation Periods of Operation (R3-11b, R3-11c, R3-11e, R3-11g, R3-14b, R3-14e, R3-14g)</u> signs shall not be used where the preferential lane <u>restriction</u> is in effect only on a part-time basis.

Option:

Where additional movements are <u>permitted_allowed</u> from a preferential lane <u>by vehicles not meeting the preferential lane regulation</u> on an approach to an intersection, the format and words used in the legend in the middle lines on the post-mounted <u>Preferential Lane Operation Periods of Operation (R3-11 series)</u> signs and on the top line of the overhead <u>Preferential Lane Operation Periods of Operation (R3-14 series)</u> signs may be modified to accommodate the <u>permitted_allowable_movements</u> (such as "HOV 2+ AND RIGHT TURNS ONLY").

A-The MOTORCYCLES ALLOWED (R3-11hP) plaque may be used where motorcycles, regardless of the number of occupants, are allowed to use an HOV lane.

Standard:

If used, the MOTORCYCLES ALLOWED plaque shall be mounted below a post-mounted Preferential Lane Periods of Operation (R3-11, R3-11a, or R3-11eb) sign.

For all barrier- or buffer-separated or contiguous preferential lanes where access is restricted to designated locations, an overhead Preferential Convention (R3-14 series) sign shall be used at the beginning or initial entry point on freeways, expressways, and at locations on conventional roadways where the preferential lane is not the outermost (far right or far left) lane of the roadway, and at any intermediate entry points or gaps in the barrier or buffer where vehicles are allowed to legally access enter the access-restricted preferential lanes. For all barrier-separated and buffer-separated preferential lanes, post-mounted Preferential Convention Operation Oper

For buffer-separated or contiguous preferential lanes where continuous access with the adjacent general-purpose lanes is provided, including those where a preferential lane is added to the roadway (see Figure 2G-2 for HOV lanes) and those where a general-purpose lane transitions into a preferential lane (see Figure 2G-3 for HOV lanes), an overhead Periods of Operation (R3-14 series) sign shall be used at the beginning or initial entry point of the preferential lane on freeways and expressways.

Option:

On conventional roads where preferential lane operations exist, R3-11 series post mounted signs may be used in lieu of or in addition to overhead R3-14 series signs, except where overhead signs are required as provided in Paragraph 14.

Guidance:

Overhead (R3-14 series) or post-mounted (R3-11 series) Periods of Operation signs should be installed at periodic intervals along the length of a contiguous or buffer separated preferential lane where continuous access with the adjacent general purpose lanes is provided.

Option:

Additional overhead (R3-14 series) or post-mounted (R3-11 series) <u>Preferential Lane Operation Periods of Operation</u> signs may be provided along the length of any type of preferential lane.

On conventional roads, the overhead Periods of Operation (R3-14 series) signs may be installed at the beginning or entry points and/or at intermediate points along preferential lanes in any geometric configuration.

Standard:

For all types of direct access ramps that provide access to or lead to preferential lanes, a post-mounted <u>Preferential Lane Operation</u> <u>Periods of Operation</u> (R3-11 series) sign shall be used at the beginning or initial entry point of the direct access ramp.

51 Option:

For direct access ramps to preferential lanes, an overhead <u>Preferential Lane Operation</u> <u>Periods of Operation</u> (R3-14 series) sign may be used at the beginning or initial entry point to supplement the required post-mounted signs.

Lane-use control signals (see Chapter 4M) may be used at access points to preferential lanes to indicate that a ramp or access roadway leading to the preferential lane or facility, or one or more specific lanes of the facility, are open or closed (see Figure 2G-1415).

Section 2G.06 <u>Preferential Lane Advance Regulatory Signs (R3-12, R3-12e, R3-12f, R3-15, R3-15a, and R3-15d)</u>

Guidance:

32.

The Preferential Lane Advance (R3-12, R3-12f, R3-15, and R3-15d) signs should be used for advance notification of a barrier-separated, buffer-separated, or contiguous preferential lane that is added to the general-purpose lanes (see Figure $2G-\frac{12}{13}$).

The Preferential Lane Advance (R3-12e and R3-15a) signs should be used for advance notification of a general-purpose lane that becomes a preferential lane (see Figure $2G-\frac{13}{14}$).

Option:

The legends on the R3-12f and R3-15d signs may be modified to suit the type of preferential lane.

Guidance:

On conventional roads, for general-purpose lanes that become preferential lanes, a post-mounted (R3-12e) or overhead (R3-15a) Preferential Lane Advance sign should be installed in advance of the beginning of or initial entry point to the preferential lane at a distance determined by engineering judgment based on speed, traffic characteristics, and other site-specific considerations. The distance selected should provide adequate opportunity for ineligible vehicles to vacate the lane prior to the beginning of the restriction.

On freeways and expressways, for general-purpose lanes that become preferential lanes, an overhead Preferential Lane Advance (R3-15a) sign should be installed at least 1 mile in advance of the beginning of the preferential lane restriction.

26 Option:

Additional post-mounted or overhead Preferential Lane Advance signs may be placed farther in advance of or closer to the beginning or initial entry points to a preferential lane.

Section 2G.07 <u>Preferential Lane Ends Regulatory Signs (R3-12a, R3-12b, R3-12c, R3-12d, R3-12d, R3-12b, R3-15b, R3-15c, and R3-15e)</u>

Standard:

A post-mounted Preferential Lane Ends (R3-12b or R3-12h) sign shall be installed at least 1/2 mile in advance of the termination of a preferential lane on freeways and expressways.

Except as provided in Paragraph 67 of this Section, a post-mounted Preferential Lane Ends (R3-12a or R3-12g) sign shall be installed at the point where a preferential lane and restriction end and traffic must merge into the general-purpose lanes.

A post-mounted Preferential Lane Ends (R3-12d) sign shall be installed at least 1/2 mile in advance of the point where a preferential lane restriction ends and the lane becomes a general-purpose lane <u>on</u> freeways and expressways.

Except as provided in Paragraph 78 of this Section, a post-mounted Preferential Lane Ends (R3-12c) sign shall be installed at the point where a preferential lane restriction ends and the lane becomes a general-purpose lane.

Guidance:

On conventional roads, the distance at which Preferential Lane Ends signs are installed in advance of the termination of a preferential lane and/or restriction should be determined by engineering judgment.

46 Option:

The legends on the R3-12g and R3-15e signs may be modified to suit the type of preferential lane.

An overhead Preferential Lane Ends (R3-15b or R3-15e) sign may be installed instead of or in addition to a post-mounted R3-12a or R3-12g sign at the point where a preferential lane and restriction ends and traffic must merge into the general-purpose lanes.

An overhead Preferential Lane Ends (R3-15c) sign may be installed instead of or in addition to a post-mounted R3-12c sign at the point where the preferential lane restriction ends and the lane becomes a general-purpose lane.

1 2 3

4

December 2020

WARNING SIGNS

Section 2G.08 Warning Signs on Median Barriers for Preferential Lanes

Option:

When a warning sign applicable only to a preferential lane is installed on a median barrier with limited lateral clearance to the adjacent travel lanes or shoulders, the warning sign may have a vertically oriented rectangular shape. For a High Occupancy Vehicle lane, such signs may be used instead of using the HOV Plaque (W16-11P) (see Section 2G.09) with a standard diamond-shaped warning sign.

Standard:

When a vertical<u>ly oriented</u> rectangular-shaped warning sign applicable only to a preferential lane is installed on a median barrier, the top portion of the sign shall be comprised of a white symbol or legend denoting the type of preferential lane (such as the diamond symbol for HOV or the legend BUS LANE) on a black background with a white border, and the bottom portion of the sign shall be comprised of the standard word message or symbol of the standard warning sign as a black legend on a yellow background with a black border (see Figure 2G-4).

Guidance:

Where lateral clearance is limited, such as when a post-mounted warning sign applicable only to a preferential lane is installed on a median barrier, the edges of the sign should not project beyond the outer edges of the barrier.

Option:

Where lateral clearance is limited, warning signs applicable only to a preferential lane that are post-mounted on a median barrier and that are 72 inches or less in width may be skewed up to 45 degrees in order to fit within the barrier width or may be mounted higher, such that the vertical clearance to bottom of the sign, light fixture, or its structural support, whichever is lowest, is not less than 14-17 feet above any portion of the pavement and shoulders.

Figure 2G-4. Examples of Warning Signs and Plaques Applicable Only to Preferential Lanes

Standard:

Where lateral clearance is limited, Preferential Lane warning signs that are post-mounted on a median barrier and that are wider than 72 inches shall be mounted with a vertical clearance that complies with the provisions of Section 2A.18 for overhead mounting.

Section 2G.09 High-Occupancy Vehicle (HOV) Plaque (W16-11P)

Option:

In situations where there is a need to warn drivers in an HOV lane of a specific condition, a-the HOV (W16-11P) plaque (see Figure 2G-4) may be used above a warning sign. The HOV plaque may be used to differentiate a warning sign specific for applicable to the HOV lanes when the sign is also visible to traffic on the adjacent general-purpose roadway. Among the warning signs that may be possible applications of the HOV plaque are the Advisory Exit Speed, Added Lane, and Merge signs.

The diamond symbol may be used instead of the word message HOV on the W16-11P plaque. When appropriate, the words LANE or ONLY may be used on this plaque.

Support:

Section 2G.08 contains information regarding warning signs that can be mounted on barriers for HOV or other types of preferential lanes.

Section 2G.10 Preferential Lane Guide Signs – General

Support:

Preferential lanes are used on freeways, expressways, and conventional roads. Except as otherwise provided, Sections 2G.10 through 2G.15 apply only to guide signs for preferential lanes on freeways and expressways.

Guidance:

On conventional roads, guide signs applicable only to preferential lanes are ordinarily not needed, but if used they should comply with the provisions for guide signs in Chapter 2D and any principles for Preferential Lane guide signs in Sections 2G.10 through 2G.15 that engineering judgment finds to be appropriate for the conditions.

Support:

Consistency in signs and pavement markings for preferential lanes plays a critical role in building public awareness, understanding, and acceptance, and makes enforcement more effective.

Additional guidance and standards related to the designation, operational considerations, signs, pavement markings, and other considerations for preferential lanes is are provided in Sections 2G.03 through 2G.07, and 2G.09, and Chapter 3D3E.

Guidance:

The appropriate combinations of pavement markings and standard overhead and post-mounted regulatory, warning, and guide signs for a specific preferential lane application should be selected based on an engineering study.

If overhead signs applicable only to a preferential lane are located in approximately the same longitudinal position along the highway as overhead signs applicable only to the general-purpose lanes, the signs for the preferential lane should be separated laterally from the signs for the general-purpose lanes to the maximum extent practical to minimize conflicting information.

The Preferential Lane signs should be designed and located to avoid overloading the road user. Based on the importance of the sign, regulatory signs should be given priority over guide signs. The order of priority of guide signs should be Advance Guide, Preferential Lane Entrance Direction, and finally Preferential Lane Exit Destination supplemental guide signs.

Standard:

Signs applicable only to a preferential lane shall be distinguished from signs applicable to general-purpose lanes by the inclusion of the applicable symbol(s) and/or word(s).

Support:

The symbol and/or word message that appears on a particular guide sign applicable only to a preferential lane will vary based on the specific type of allowed traffic allowed and on other related operational constraints that have been established for a particular lane, such as an HOV lane, a bus lane, or a taxi lane.

Standard:

For HOV lanes, the diamond symbol shall appear on each Advance Guide sign, Preferential Lane Entrance Direction sign, and Preferential Lane Entrance Gore sign, as shown in Figures 2G-5 through 2G-7 for the designated entry and exit points for barrier- and buffer-separated geometric configurations and direct access ramps to or from such lanes. The diamond symbol shall not be used with preferential lanes for other types of traffic, such as bus lanes or taxi lanes.

Signing for an HOV lane that is managed by means of varying the occupancy requirement in response to changing conditions shall also comply with these provisions.

The diamond symbol shall be displayed in the legend of each Preferential Lane guide sign at the designated entry and exit points for all types of HOV lanes (including barrier- and buffer-separated, contiguous, and direct access ramps) in order to alert motorists that there is a minimum allowable vehicle occupancy requirement for vehicles to use the HOV lanes. Guide signs shall not display the occupancy requirement for the preferential lane.

A combination of guide and regulatory signs shall be used in advance of and at the initial entry point and all intermediate entry points from general-purpose lanes or facilities to contiguous, barrier-

separated, and buffer-separated preferential lanes where access between the preferential and general-purpose lanes is restricted to designated locations. The regulatory signs shall comply with the provisions of Sections 2G.03 through 2G.07.

Regulatory signs alone shall be used in advance of, at the beginning of, and at periodic intervals along contiguous or buffer-separated preferential lanes that provide continuous access between the adjacent general-purpose lanes and the preferential lane (see Figures 2G-12-13 and 2G-13-14). The design and placement of the regulatory signs shall comply with the provisions of Sections 2G.03 through 2G.07.

Except as otherwise provided in Sections 2G.10 through 2G.13, guide signs applicable to a preferential lane with a vehicle occupancy requirement shall be distinguished from those applicable to general-purpose lanes by displaying the white diamond symbol on a black background at the left-hand edge of these signs.

Option:

When post-mounted guide signs applicable only to a preferential lane are installed on a median barrier with limited lateral clearance to the adjacent travel lanes or shoulders, the guide signs may have a vertical vertic

Standard:

When vertically oriented rectangular shaped guide signs applicable only to a preferential lane are installed on a median barrier, the top portion of the signs shall be comprised of the applicable white symbol or white word message that identifies the type of preferential lane (such as the diamond symbol for an HOV lane) on a black background with a white border, and the bottom portion of the sign shall be comprised of the appropriate guide sign legend on a green background with a white border (see Figures 2G-3, 2G-6, and 2G-7).

Guidance:

Where lateral clearance is limited, such as when a post-mounted Preferential Lane guide sign is installed on a median barrier, the edges of the sign should not project beyond the outer edges of the barrier.

Option:

Where lateral clearance is limited, Preferential Lane guide signs that are 72 inches or less in width may be skewed up to 45 degrees in order to fit within the barrier width or may be mounted higher, such that the vertical clearance to the bottom of the sign, light fixture, or its structural support, whichever is lowest, is not less than 14-17 feet above any portion of the pavement and shoulders.

Standard:

Where lateral clearance is limited, Preferential Lane guide signs that are post-mounted on a median barrier and that are wider than 72 inches shall be mounted with a vertical clearance that complies with the provisions of Section 2A.18 for overhead mounting.

Option:

Lane-use control signals (see Chapter 4M) may be used at access points to preferential lanes to indicate that a ramp or access roadway leading to or from the preferential lane or facility, or one or more specific lanes of the facility, are open or closed.

Changeable message signs may supplement, substitute for, or be incorporated into static guide signs (see Figure 2G-6) where travel conditions change or where multiple types of operational strategies (such as variable occupancy requirements, vehicle types, or pricing policies) are used and varied throughout the day or week to manage the use of, control of, or access to preferential lanes.

Standard:

When changeable message signs (see Chapter 2L) are used as guide signs for preferential lanes, they shall be the required sign size and shall display the required letter height and legend format that corresponds to the type of roadway facility and design speed.

Advance Guide signs, Preferential Lane Entrance Direction signs, and Preferential Lane Entrance Gore signs for the initial entry point and intermediate entry points into a preferential lane from the general-purpose lanes on the same designated route shall not identify the entry point as an exit by using the word "EXIT" on the sign or on a plaque.

Guidance:

Advance Guide signs and Preferential Lane Entrance Direction signs for initial and intermediate entry points into a preferential lane should use the word "ENTRANCE," such as "HOV LANE ENTRANCE" (see Figures 2G-5 and 2G-6) to convey the fact that vehicles are not leaving the designated route.

Preferential Lane Entrance Gore signs (see Figure 2G-7) at the initial entry point to a preferential lane should use the word "ENTRANCE." Preferential Lane Entrance Gore signs at intermediate entry points to a barrier-separated preferential lane where the sign would be located immediately adjacent to and directly viewed by traffic in the preferential lane should not use the word "ENTRANCE."

Figure 2G-5. Example of an Overhead Advance Guide Sign for a Preferential Lane Entrance

Figure 2G-6. Example of Overhead or Post-Mounted Preferential Lane Entrance Direction Signs

Figure 2G-7. Entrance Gore Signs for Barrier-Separated Preferential Lanes

Standard:

 When the entry point is on the left-hand side of the general-purpose lanes, a LEFT (E1-5aP) plaque (see Figure 2E-229) shall be added to the top left edge of the Advance Guide and Preferential Lane Entrance Direction signs. The LEFT plaque shall not be used on a preferential lane regulatory sign.

Section 2G.11 <u>Guide Signs Signing for Initial Entry Points to Preferential Lanes</u>

Standard:

Except where a buffer-separated or contiguous preferential lane is added or where a general-purpose lane becomes a buffer-separated or contiguous preferential lane, and provides continuous access with the adjacent general-purpose lanes as illustrated in Figures 2G-2 and 2G-3, an Advance Guide sign shall be provided at least 1/2 mile prior to the initial entry point to all types of preferential lanes in any type of geometric configuration on freeways and expressways. A Preferential Lane Entrance Direction sign shall also be provided at the initial entry point. Advance Guide and Preferential Lane Entrance Direction signs for such entry points shall not include the word "EXIT" (see Section 2G.10).

Where a general-purpose lane becomes a preferential lane that does not provide continuous access with the adjacent general purpose lanes, an Advance Guide sign shall also be provided at approximately 1 mile in advance of the initial entry point. The Advance Guide and Entrance Direction signs in this sequence shall include a panel at the bottom of the sign with a black legend and border on a yellow background displaying a down arrow and the word ONLY as illustrated in Figure 2G-8.

Guidance:

Except as required in Paragraph 2, an Advance Guide sign should also be installed and located approximately 1 mile in advance of the initial entry point to a preferential lane that restricts access with the adjacent general-purpose lanes to designated locations on freeways and expressways.

Option:

An Advance Guide sign may also be installed and located approximately 2 miles in advance of the initial entry point to a preferential lane that restricts access with the adjacent general-purpose lanes to designated locations.

Standard:

For barrier-separated, buffer-separated, or contiguous preferential lanes where entry is restricted to only designated points on freeways and expressways, the Advance Guide and Preferential Lane Entrance Direction signs shall be mounted overhead.

Guidance:

Preferential Lane Exit Destination guide signs, identifying final destination and downstream exit locations accessible from the preferential lane (see Figures 2G-82G-9, 2G-132G-14, 2G-142G-15, and 2G-162G-17), should be installed in advance of the initial entry points to access-restricted preferential lanes (such as barrier- and buffer-separated). These signs should be located based on the priority of the message, the available space, the existing signs on adjacent general-purpose traffic lanes, roadway and traffic characteristics, the proximity to existing overhead signs, the ability to install overhead signs, and other unique local factors.

Standard:

 Advance destination guide signs for preferential lanes shall include an upper section displaying a black legend that includes the type of preferential lane and the word "EXITS," such as "HOV EXITS," on a white background. For preferential lanes that incorporate a vehicle occupancy requirement, the white diamond symbol on a black background shall be displayed at the left-hand edge of this upper section (see Figure 2G-82G-9).

Support:

Figure 2G-8 shows and example of signing for a general-purpose lane that becomes a preferential lane that does not provide continuous access with the adjacent general purpose lanes.

Figure 2G-82G-9 shows an example of signs for the initial entry point to a preferential lane.

Figure 2G-8. Example of Advance Guide and Entrance Direction Signs for a General Purpose Lane that becomes a Preferential Lane

Figure 2G-9. Example Signing for an Entrance to Access-Restricted HOV Lanes

Section 2G.12 <u>Guide Signs Signing for Intermediate Entry Points to Preferential Lanes</u> Standard:

For barrier-separated, buffer-separated, and contiguous preferential lanes where entry is restricted only to designated points, an overhead Preferential Lane Entrance Direction sign shall be provided at intermediate entry points to the preferential lane from the general-purpose lanes.

Guidance:

For barrier- and buffer-separated preferential lanes where intermediate entry from the general-purpose lanes is provided via a separate lane or ramp (see Figure 2G-92G-10), at least one Advance Guide sign should be provided in addition to the Preferential Lane Entrance Direction sign.

For access-restricted preferential lanes where intermediate entrance and egress are at the same designated access location, the Preferential Lane Entrance Direction sign should be located between 1/2 and 1/4 of the length of the designated entry area, as measured from the downstream end of the entry area (see Figure $\frac{2G-102}{G-11}$).

Figure 2G-10. Example Signing for Intermediate Entry Point to a Barrier- or Buffer-Separated HOV Lane

Figure 2G-11. Example of Signing for the Intermediate Entry to, Egress from, and End of Access-Restricted HOV Lanes

Standard:

The Advance Guide signs, if used for intermediate entry points to a preferential lane from the general-purpose lanes, shall be overhead.

Option:

Advance Guide signs may be provided at approximately 1/2 mile, 1 mile, and 2 miles in advance of intermediate entry points from the general-purpose lanes to a preferential lane.

Standard:

Advance Guide and Preferential Lane Entrance Direction signs for intermediate entry points shall not include the word "EXIT" (see Section 2G.10).

Guidance:

Exit Destination guide signs, identifying the final destination and downstream exit locations accessible from the preferential lane, should be installed in advance of intermediate entry points from the general-purpose lanes to access-restricted preferential lanes.

Support:

Section 2G.11 contains information on the design and placement of Preferential Lane Exit Destination guide signs.

Figures <u>2G-92G-10</u> and <u>2G-102G-11</u> show examples of signs for various geometric configurations of intermediate entry to a barrier- or buffer-separated preferential lane where access is restricted to designated locations.

Section 2G.13 <u>Guide SignsSigning for Egress from Preferential Lanes to General-Purpose</u>
Lanes

Standard:

Except as provided in Paragraphs 4 and 5, For for barrier-separated, buffer-separated, and contiguous preferential lanes where egress is restricted only to designated points, post-mounted Advance Guide and post-mounted Intermediate Egress Direction signs (see Figure 2G-112G-12) shall be installed in the median or on median barriers that separate two directions of traffic prior to and at the intermediate exit points from the preferential lanes to the general-purpose lanes (see Figure 2G-92G-10).

The legends of these signs shall refer to the next exit or exits from the general-purpose lanes by displaying the appropriate destination information, exit number(s), or both. The Intermediate Egress Direction signs for egress from the preferential lanes to the general-purpose lanes shall not refer to the egress as an exit.

Support:

Section 2G.10 contains information on the design of post-mounted guide signs applicable to a preferential lane when installed on a median barrier. Figures 2G-92G-10 and 2G-122G-13 show examples of signs for various geometric configurations of intermediate egress from a barrier- or buffer-separated preferential lane where access is restricted to designated locations.

Guidance:

Where two or more adjacent preferential lanes are present in a single direction, consideration should be given to the use of overhead guide signs to display the information related to egress from the preferential lanes.

For barrier-separated and buffer-separated preferential lanes where egress from a preferential lane to the general-purpose lanes is restricted only to designated points via a separate lane or ramp, the Advance Guide and Intermediate Egress Direction signs for the egress should be mounted overhead and a Pull-Through sign should be mounted with the Intermediate Egress Direction sign (see Figure 2G-122G-13).

Figure 2G-12. Examples of Barrier-Mounted Guide Signs for an Intermediate Egress from Preferential Lanes

Figure 2G-13. Examples of Signs for an Intermediate Egress from a Barrier- or Buffer-Separated HOV Lane

Standard:

For preferential lanes that incorporate a vehicle occupancy requirement, the design of the overhead Advance Guide and Egress Direction signs for intermediate egress from the preferential lanes to the general-purpose lanes shall display a white diamond symbol on a black background at the left-hand edge of the signs.

The design of Pull-Through signs when used in conjunction with an Egress Direction sign at an intermediate egress from the preferential lanes to the general-purpose lanes shall be distinguished from those applicable to general-purpose lanes by inclusion of an upper section with the applicable black legend on a white background, such as HOV LANE. For preferential lanes that incorporate a vehicle occupancy requirement, the white diamond symbol on a black background shall be displayed at the left-hand edge of this upper section.

Section 2G.14 <u>Guide Signs Signing for Direct Entrances to Preferential Lanes from Another Highway</u>

Standard:

For direct access ramps to preferential lanes from a transit facility (such as a park - ride lot or a transit station or terminal) that is accessible from surface streets, advance guide signs shall be provided along the adjoining surface streets to direct traffic into and through the transit facility to the preferential lane (see Figure $\frac{2G-132G-14}{2}$).

Support:

Figure 2G-14 provides examples of recommended uses and layouts of signs for HOV lanes for direct access ramps, park - ride lots, and access from surface streets.

1 Figure 2G-14. Example of Signing for a Direct Entrance Ramp to an HOV Lane from a 2 Park-and-Ride Facility and a Local Street 3 Section 2G.15 Guide Signs Signing for Direct Exits from Preferential Lanes to Another 4 **Highway** 5 **Standard:** 6 For contiguous preferential lanes on the left-hand side of the roadway, Advance Guide signs, Exit Direction signs, and Exit Gore signs (see Figure 2G-142G-15) specifically applicable to the preferential 7 8 lanes shall be used for exits to direct access ramps, such as HOV lane ramps (see Figure 2G-152G-16) or 9 ramps to park - ride facilities. 10 The design of Advance Guide, Exit Direction, and Pull-Through signs for direct exits from preferential lanes shall be distinguished from those applicable to general-purpose lanes by inclusion of 11 12 an upper section with the applicable black legend on a white background, such as HOV LANE (for 13 Pull-Through signs) or HOV EXIT (for Advance Guide and Exit Direction signs). For preferential 14 lanes that incorporate a vehicle occupancy requirement, the white diamond symbol on a black 15 background shall be displayed at the left-hand edge of this upper section (see Figures 2G-152G-16 and 16 2G-162G-17). 17 Guidance: 18 Advance Guide and Exit Direction signs for exits to direct access ramps from a preferential lane should 19 be mounted overhead. A Pull-Through sign over the preferential lane should be used with the Exit Direction 20 sign at exits to direct access ramps. 21 **Standard:** 22 Post-mounted guide signs in a vertically oriented rectangular shape installed on a median barrier 23 shall not be used for the Advance Guide and Exit Direction signs for exits to direct access ramps. 24 Because direct access ramps for preferential lanes at interchanges connecting two freeways are 25 typically left-hand side exits and typically have design speeds similar to the preferential lane, overhead 26 Advance Guide signs and overhead Exit Direction signs shall be provided in advance of and at the entry point to each freeway-to-freeway preferential lane ramp (see Figure 2G-162G-17). 27 28 Guidance: 29 The use of guide signs for preferential lanes at freeway interchanges should comply with the provisions 30 for guide signs established in Chapter 2E of this Manual. 31 Support: 32 Guide signs for direct access ramps for preferential lanes at interchanges connecting two freeways are 33

similar to those for a connecting ramp between two freeway facilities.

Figure 2G-15. Exit Gore Sign for a Direct Exit from a Preferential Lane

Figure 2G-16. Examples of Guide Signs for Direct HOV Lane Entrance and Exit Ramps

Figure 2G-17. Examples of Guide Signs for a Direct Access Ramp between HOV Lanes on Separate Freeways

2020 NPA - Chapter 2G

34

35 36

37 38 22.

Section 2G.16 Signs for Managed Lanes – General Paragraphs from Existing Section 2G.03 Standard:

The provisions of Sections 2G.03 through 2G.07 regarding regulatory signs for Preferential lanes shall apply to managed lanes operated at all times or at certain times by varying vehicle occupancy requirements (HOV) or by using vehicle type restrictions as a congestion management strategy. Such managed lanes shall use changeable message signs or changeable message elements within static signs to display the appropriate regulatory sign messages only when they are in effect.

When certain types of vehicles (such as trucks) are prohibited from using a managed lane or when a managed lane is restricted to use by only certain types of vehicles during certain operational strategies, regulatory signs or regulatory panels within the appropriate guide signs that include changeable message elements shall be used to display the open/closed status of the managed lane for such vehicle types.

When the vehicle occupancy required for use of an HOV lane is varied as a part of a managed lane operational strategy, regulatory signs that include changeable message elements shall be used to display the required minimum vehicle occupancy in effect.

Support:

See Section 2G.17-18 for regulatory signs for managed lanes that use tolling or pricing as a congestion management strategy, either exclusively or with other management strategies.

Section <u>2G.16</u> <u>2G.17</u> <u>Signs for Priced Managed Lanes – General</u> Support:

A priced managed lane is a managed lane that employs tolling or pricing, typically through electronic toll collection, to manage congestion levels and maintain a certain level of service for users of the facility. A priced managed facility typically provides a less congested alternative to adjacent lanes along the same designated route, or to a nearby facility, that experience recurring congestion during peak periods. A priced managed lane might allow non-toll travel by certain vehicles based on occupancy or other criteria. A variety

of operational management strategies might be used in conjunction with tolling or pricing.

The number and combination of operational strategies that are applied to a managed lane to manage congestion or improve efficiency might be practically limited by the amount of information that can be legibly displayed on signs or in signing sequences and still be readily comprehended by road users. Such factors to consider when evaluating alternatives for managed lanes are locations of signs for general-purpose interchanges and for other roadway conditions, the number of intermediate access points between the managed and general-purpose lanes and the need to repeat the operational information, and the distance over which a signing sequence that displays all of the eligibility requirements can be displayed.

Because managed lanes have the capability to employ a variety of operational strategies on a changing basis, it is not practical to assign a naming convention to such lanes for the purpose of signing based on the specific operational management strategies, as is more readily accomplished with other types of preferential lanes, such as HOV, Bus, or Bike lanes. Instead, the various requirements, restrictions, and eligibility criteria are more appropriately conveyed through a sequence of regulatory and guide signs with a more encompassing designation for the purpose of providing directional information.

As priced managed lanes <u>have</u> become <u>more</u>-prevalent as an operational strategy, it <u>will beis</u> important to <u>establish maintain</u> a uniform naming convention to distinguish those lanes that are an alternative to travel on adjacent general-purpose lanes on the same designated route to effectively communicate to motorists the range of basic requirements for similar facilities in different regions.

Standard:

Priced managed lanes that are adjacent to general-purpose lanes along the same designated route shall be signed using the legend EXPRESS or EXPRESS LANE(S) as provided in this Chapter. This provision shall apply when any of the following operational strategies is used for a managed lane:

- A. All users of the managed lane are charged a fixed or variable toll;
- B. General-purpose traffic using the managed lane is charged a fixed or variable toll, but HOV traffic is allowed to travel without being charged a toll on either a full- or part-time basis;

D. General-purpose traffic using the managed lane is charged a fixed or variable toll, but HOV traffic registered with a local program travels at a discounted toll or without being charged a toll on either a full- or part-time basis (a transponder or other identifier is typically required of HOVs to indicate registration in conjunction with electronic or visual enforcement and verification of vehicle occupancy).

The legends EXPRESS and EXPRESS LANE(S) shall not be used on signs for entrances to highways on which all lanes are managed and there are no adjacent general-purpose lanes on the same designated route. The legends EXPRESS and EXPRESS LANE(S) shall not be used on signs for a managed ramp connection that provides an alternative to a general-purpose ramp connection (see Figure 2F-713), except where the ramp leads directly to a managed lane as described in Section 2G.14. The legends EXPRESS and EXPRESS LANE(S) shall not be used on signs for open-road tolling lanes that bypass a conventional toll plaza (see Chapter 2F).

The diamond symbol shall be reserved exclusively for preferential lanes whose operational strategy is occupancy-based only (see Sections 2G.03 through 2G.14) and shall not be used to designate a managed lane in which other operational strategies, such as tolling and pricing, are employed to allow general-purpose traffic to use the lane.

Section 2G.17 2G.18 Regulatory Signs for Priced Managed Lanes

Standard:

Except as otherwise provided in this Section, the provisions of Sections 2G.03 through 2G.07 regarding regulatory signs for Preferential lanes shall apply to priced managed lanes operated at all times or at certain times with a toll payment requirement of some or all vehicles to use the lane(s). Such managed lanes shall use changeable message signs or changeable message elements within static signs to display the appropriate regulatory sign messages only when they are in effect.

Regulatory signs for preferential lanes shall be appropriately modified for adaptation to a priced managed lane, where applicable, as shown in Figure $\frac{2G-17}{2G-18}$.

Regulatory signs shall be used to indicate the toll charged. If the toll varies, regulatory signs that include changeable message elements, such as the R3-48 and R3-48a signs that are shown in Figure 2G-172G-18, shall be used to display the actual toll amount in effect at any given time.

When only vehicles with a registered ETC account are allowed to use a managed lane where some or all vehicles are charged a toll, regulatory signs to indicate such a restriction shall be provided and shall incorporate the pictograph adopted by the toll facility's ETC payment system and the word ONLY (see Section 2G.18 for the incorporation of such regulatory legends into the guide signs for the entrances to such facilities). The display of the ETC system pictograph shall comply with the provisions of Sections 2F.03 and 2F.04 as shown in Figures 2G-172G-18 and 2G-182G-19.

When HOV traffic is allowed to use a priced managed lane without paying a toll and registration in a local program is not required to receive the toll exemption, the Vehicle Occupancy Definition (R3-10 or R3-13) signs (see Section 2G.04) shall be modified to delete the diamond symbol to create priced managed lane Vehicle Occupancy Definition (R3-40 and R3-43) signs to indicate the minimum occupancy related to the management strategy (see Figure 2G-172G-18).

A priced managed lane Periods of Operation (R3-44 or R3-44a) sign (see Figure 2G-172G-18) shall be installed at the beginning or initial entry point, and at any intermediate entry points where vehicles are allowed to legally enter an access-restricted priced managed lane.

When the vehicle occupancy required for non-toll use of a managed lane is varied as a part of a priced managed lane operational strategy, regulatory signs that include changeable message elements shall be used to display the required vehicle occupancy in effect for non-toll travel.

Option:

Where registration in a local program or ETC account is required for HOV traffic to travel in a priced managed lane without being charged a toll or by being charged a discounted toll, such information may be displayed on a separate sign within the sequence of the required regulatory and guide signs.

Figure 2G-18. Regulatory Signs for Managed Lanes

Figure 2G-19. Examples of Guide Signs for Entrances to Priced Managed Lanes

December 2020

2020 NPA – Chapter 2G Page 273 of 781

Standard:

R3-42 Series and R3-45 Series signs (see Figure 2G-172G-18) shall be installed in accordance with the provisions of Section 2G.07 to indicate the termination of a priced managed lane or restriction. The R3-42, R3-42a, and R3-45 signs shall be used only where the managed lane and restriction end and traffic must merge into the general-purpose lanes. The R3-42b, R3-42c, and R3-45a signs shall be used only where the managed lane restriction ends and the lane becomes a general-purpose lane.

Section 2G.18 2G.19 Guide Signs for Priced Managed Lanes

Standard:

Except as otherwise provided in this Section, guide signs for barrier-separated, buffer-separated, and contiguous managed lanes shall follow the specific provisions for Preferential Lane guide signs contained in Sections 2G.10 through 2G.15. Except as otherwise provided in this Section, guide signs for highways on which all lanes are managed shall follow the general provisions for freeway and expressway guide signs as contained in Chapter 2E as a whole. Guide signs for highways on which all lanes are managed and tolling or pricing is used as a management strategy shall follow the applicable provisions for toll road guide signs as contained in Chapter 2F, in addition to the general provisions of Chapter 2E.

If fixed or variable tolls are used as an operational strategy for a managed lane, the guide signs shall comply with the provisions of Sections 2F.03, 2F.04, and 2F.17 regarding the use, size, and placement of ETC-account pictographs.

Guide signs at the initial and intermediate entry points to a priced managed lane in which all general-purpose passenger vehicles are allowed shall include the legend EXPRESS or EXPRESS LANE(S). Except as provided in Paragraph 5, The the guide signs shall incorporate the pictograph of the ETC account system into a header panel within the guide sign in accordance with Sections 2F.03, 2F.04, and 2F.17. For a priced managed lane that allows non-toll travel by HOV traffic without registration in a local program, the header panel shall be modified to a regulatory format to display both the pictograph of the ETC account system and the minimum occupancy requirement for non-toll travel with a black legend on a white background (see Figure 2G-1819). Paragraph relocated from later in Section

Guide signs at the initial and intermediate entry points to a managed lane that allows only HOV traffic with either a fixed or variable occupancy requirement shall follow the provisions of Sections 2G.10 through 2G.12 and 2G.14. Paragraph relocated from later in Section

If registration in a toll-account program is not required for travel in a managed lane in which tolls are charged, then the ETC-account pictographs shall not be displayed on primary guide signs directing traffic to the managed lane. In such cases, the purple header panel shall be replaced with a warning header panel with a black legend and border on a yellow background displaying the word TOLL as illustrated in Figure 2G-20.

Option:

If the managed lane does not accept toll payments from an ETC account system and collects tolls only by post-travel billing of registered vehicle owners, then the legend TOLL BILLED BY MAIL ONLY may be displayed on a separate information sign within the sequence of primary guide signs in advance of the entrance to the managed lane.

If the managed lane accepts payments from registered ETC accounts, but does not require registration to use the lane, then the pictographs of the accepted ETC account programs may be displayed on a separate information sign within the sequence of primary guide signs in advance of the entrance to the managed lane. The information sign may also display the legend TOLL BILLED BY MAIL in addition to the pictograph of the accepted ETC account program.

Support:

Figure 2G-1819 shows examples of Guide signs for entrances to priced managed lanes and other ETC account-only toll facilities that incorporate header panels with ETC account pictographs and regulatory legends.

Figures 2G-21 through 2G-24 show examples of guide signs for various configurations of initial and intermediate entrances to a priced managed lane. Paragraph relocated from below

53 Guidance:

Exit Destination supplemental guide signs, identifying final destination and downstream exit locations accessible from the managed lane (see Figure 2G-1925), should be installed in advance of the initial entry points to priced managed lanes. These signs should be located in accordance with the provisions of Paragraph 5-6 of Section 2G.11.

For managed lanes that are available as an alternative to travel on adjacent general-purpose lanes on the same designated route, changeable message signs indicating the comparative travel times or congestion levels using the managed lanes versus the general-purpose lanes (see Figure 2G-202G-26) should be installed in advance of the initial and intermediate entry points to the managed lanes.

Option

Changeable message signs may also be used on non-managed highways to display comparative travel times or congestion levels for a nearby managed highway.

Standard: Paragraphs relocated to earlier in this Section

Guide signs at the initial and intermediate entry points to a priced managed lane in which all general-purpose passenger vehicles are allowed shall include the legend EXPRESS or EXPRESS LANE(S). The guide signs shall incorporate the pictograph of the ETC account system into a header panel within the guide sign in accordance with Sections 2F.03, 2F.04, and 2F.17. For a priced managed lane that allows non-toll travel by HOV traffic without registration in a local program, the header panel shall be modified to a regulatory format to display both the pictograph of the ETC account system and the minimum occupancy requirement for non-toll travel with a black legend on a white background (see Figure 2G-19.

Guide signs at the initial and intermediate entry points to a managed lane that allows only HOV traffic with either a fixed or variable occupancy requirement shall follow the provisions of Sections 2G.10 through 2G.12 and 2G.14.

Figure 2G-20. Signing for Entrance to Access Restricted Price managed Lane – No ETC

Account Required

Figure 2G-21. Signing for Entrance to Access Restricted Price managed Lane – ETC Account Required

Figure 2G-22. Example of Signing for the Entrance to an Access-Restricted Priced Managed Lane Where a General-Purpose Lane Becomes the Managed Lane

Figure 2G-23. Example of Signing for the Intermediate Entry to a Barrier-or Buffer-Separated Priced Managed Lane

Figure 2G-24. Example of Signing for the Intermediate Entry to, Egress from, and End of Access-Restricted Priced Managed Lanes

Figure 2G-25. Example of an Exit Destinations Sign for a Managed Lane

Figure 2G-26. Example of Comparative Travel Time Information Sign for Preferential or Managed Lanes

Support:

Figures 2G-21through 2G-24 show examples of guide signs for various configurations of initial and intermediate entrances to a priced managed lane. Paragraph relocated to above

Standard:

The use and locations of guide signs for intermediate egress locations and direct exits from a priced managed lane (see Figures 2G-24 and Figures through 2G-27 through 2G-29) shall comply with the provisions of Sections 2G.13 and 2G.15. The signs shall be suitably modified to display header messages of white legend on a green background that relate the guide sign legends to the managed lane(s) as appropriate in accordance with the following:

A. Post-mounted or overhead-mounted Advance Guide signs for intermediate egress to the generalpurpose lanes shall include the legend LOCAL EXITS in a header panel within the guide signs, destination information or the exit number(s) for the next exit(s) accessible from the general-

- 1 purpose lanes, and the appropriate distance information to the location of the egress (see 2 Figures 2G-24 and 2G- $\frac{25}{27}$). 3
 - B. Post-mounted or overhead-mounted Intermediate Egress Direction signs shall include the legend LOCAL EXITS in a header panel within the signs, the destination information or the exit number(s) of the next exit(s) accessible from the general-purpose lanes, and a diagonally upward-pointing directional arrow (see Figures 2G-24 and 2G-2527).
 - C. For direct exits to another roadway, the legend EXPRESS EXIT shall be used on the Advance Guide and Exit Direction signs (see Figure 2G-2628).
 - D. For pull-through signs, the legend EXPRESS LANE(S) shall be used, either as a header panel within the pull-through sign or as the principal legend of the sign without a header panel (see Figures 2G-2527, 2G-2628, and 2G-2729).

Support:

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18 19

20

21 22

23

24 25

26

27

28

29

30

31

32 33

34

35

36

37 38

39

40

41

42 43

44

45 46

47

49

Section 2G.13 contains information on the use of overhead-mounted guide signs for intermediate egress to the general-purpose lanes.

Figures 2G-282G-30 and 2G-292G-31 show examples of guide signing for direct entrances to a priced managed lane from a crossroad or surface street.

Figure 2G-27. Examples of Guide Signs for an Intermediate Egress from a Barrier- or **Buffer-Separated Managed Lane**

Figure 2G-28. Examples of Guide Signs for a Direct Managed Lane Entrance and Exit **Ramps**

Figure 2G-29. Examples of Guide Signs for a Direct Access Ramp between Managed Lanes on Separate Freeways

Figure 2G-30. Examples of Guide Signs for a Direct Entrance Ramp to a Priced Managed Lane and Trailblazing to a Nearby Entrance to the General-Purpose Lanes

Figure 2G-31. Examples of Guide Signs for Separate Entrance Ramps to General-Purpose and Priced Managed Lanes from the Same Crossroad

Section 2G.20 Signs for Part-Time Travel on a Shoulder – General

Support:

In some cases, paved shoulders are allowed to be used for driving use during peak periods to manage congestion. Configurations might be on freeways and expressways, as well as on conventional roads. Travel on the shoulder during these periods might be restricted to certain classes of vehicles, such as buses or HOV, or might be open to general traffic. When the part-time travel on a shoulder is limited to certain classes of vehicles, the signing is similar to that for preferential lanes. Additional signing is typically used to advise road users that the shoulder is not available for emergency use during these periods. Part-time travel on a shoulder might also employ lane-use control signals and/or blank-out signs to inform traffic of the allowable use of the shoulder. Depending on the design of exit ramp terminals and auxiliary lanes, guide signs must account for exit maneuvers during both shoulder use conditions and might necessitate changeable legend elements. However, additional guide signs are not normally necessary specifically for the condition when the shoulder is used for travel. The pavement markings might also be modified where travel allowed on the shoulder begins and ends.

Figure 2G-32 shows an example of signing for part-time travel on a shoulder.

Figure 2G-32. Example of signing for Part-time Travel on a Shoulder

Standard:

A shoulder that has been opened to travel on a permanent, full-time basis shall be considered a travel lane and shall be signed and marked in accordance with other provisions of this Manual. Support:

Section 3E.04 contains provisions regarding the placement of markings on paved shoulders that are open for part-time travel. 48

Section 2G.21 Regulatory Signs and Plaques for Part-Time Travel on a Shoulder

50 **Standard:**

Regulatory signs shall be used to notify road users of the periods of operation that travel is allowed on a paved shoulder. The Part-Time Travel on Shoulder Operation (R3-51) sign shall be used where traffic is allowed to travel on the shoulder during certain fixed periods of operation. The Part-Time
Travel on Shoulder Variable Operation (R3-51d) sign with two flashing beacons (see Chapter 4S)
mounted above it shall be used when the period of operation is variable

If certain classes of vehicles are not allowed to use the shoulder during these periods, then a Selective Exclusion (R3-51aP or R3-51bP) plaque shall be mounted below the R3-51 or R3-51d sign. If the travel on the shoulder is restricted to certain classes of vehicles, then the regulatory signs shall display that information.

10 Option:

6

7

8

9

11

12

14

15 16

24

25

26

27

28

29

34

36

37

38

The EMERGENCY STOPPING ONLY OTHER TIMES (R3-51cP) plaque may be mounted below the R3-51 sign if the R3-51aP or R3-51bP plaque is not used.

13 *Guidance:*

The TRAVEL ON SHOULDER BEGINS ½ MILE (R3-52c) sign should be used in advance of the location where part-time travel on shoulder first begins and followed by the DO NOT DRIVE ON SHOULDER (R4-17) sign appropriately spaced downstream.

17 **Standard:**

Approximately ½ mile from where part-time travel on shoulder ends the TRAVEL ON

SHOULDER ENDS (R3-52a) sign shall be used. At the location provided for traffic to transition from shoulder travel back to permanent highway lane travel, an END TRAVEL ON SHOULDER (R3-52) sign shall be used. After this transition location a DO NOT DRIVE ON SHOULDER (R4-17) sign shall be used.

23 **Guidance**:

Where a shoulder that allows part-time travel is interrupted by a deceleration lane for an exit, the BEGIN EXIT LANE (R3-56) sign should be used at the beginning of the deceleration lane where traffic is allowed to enter during the periods that travel is prohibited on the shoulder.

Where turnouts are provided for emergency stopping during periods when travel is allowed on the shoulder, the EMERGENCY STOPPING ONLY (R8-7) sign (see Section 2B.49) should be used adjacent to the turnout.

Where traffic on an entrance ramp is required to yield to traffic using the shoulder of the freeway or expressway mainline during the periods when travel is allowed on the shoulder, the TO TRAFFIC ON SHOULDER (R3-57P) plaque should be mounted below the Yield (R2-1) sign (see Section

33 <u>2B.08).</u>

Section 2G.22 Warning Signs for Part-Time Travel on a Shoulder

35 *Guidance*:

The Traffic Using Shoulder (W3-9) sign should be used on a ramp that enters a freeway or expressway on which part-time travel is allowed on the shoulder. When used, the W3-9 sign should be located on the side of the ramp from which the shoulder traffic approaches (see Figure 2G-32).

39 Option:

The W3-9 sign may be used on a conventional road that is required to stop for or yield to the through street or highway on which part-time travel is allowed on the shoulder.

42 Section 2G.23 Guide Signs for Part-Time Travel on a Shoulder

43 Support:

Guide signs for part-time travel on a freeway or expressway shoulder generally consist of the typical interchange guide sign sequence (see Chapter 2E). While specialized guide signs are not normally necessary, modifications to the typical guide signs might be necessary, especially where an interchange lane drop is created only during the periods when the shoulder is open to travel.

48 **Standard:**

Where an interchange lane drop is created only during the periods when a shoulder is open to travel, the Advance and Exit Direction guide signs (see Sections 2E.24 and 2E.26) shall be overhead-

2020 NPA – Chapter 2G Page 277 of 781 December 2020

- 1 mounted and shall be modified to include a blank-out or changeable EXIT ONLY message that
 2 complies with the provisions of Section 2E.29 and is displayed only during the periods that the shoulder
 3 is open to travel (see Figure 2G-32).
 - Guide signs located in conjunction with part-time travel on a shoulder shall otherwise comply with the provisions of Chapters 2D and 2E.
- **Guidance**:

Where turnouts are provided for emergency stopping during periods when travel is allowed on the shoulder, the Emergency Turn-Out directional (D17-6) sign should be used as provided in Section 2D.51.

Section 2G.24 Lane-Use Control Signals for Part-Time Travel on a Shoulder

10 Support:

<u>Lane-use control signals</u> (see Chapter 4T) are sometimes used for part-time travel on a paved shoulder, in <u>addition to signs</u>, to indicate the allowable use of the shoulder.

13 Option:

Overhead lane-use control signals may be used above a shoulder on which part-time travel is allowed.

Standard:

Except as otherwise provided in this Section, lane-use control signals that are used for part-time travel on a shoulder shall comply with the provisions of Chapter 4T. When used for part-time travel on a shoulder, lane-use control signals shall not be required above the lanes adjacent to the shoulder.

When used for part-time travel on a shoulder, a steady RED X signal indication shall be displayed when the shoulder is available for emergency stopping only and travel on the shoulder is otherwise prohibited.

When part-time travel on shoulder is allowed for variable periods of operation, lane-use control signals (see Chapter 4T) shall be used and evenly spaced approximately every $\frac{1}{2}$ mile or less and centered over the shoulder to indicate when the shoulder is open or closed to vehicle travel. The lane-use control signals shall display a green down arrow during times when travel is allowed on the shoulder, followed by a yellow X just before the shoulder is to be closed to travel, and a red X when shoulder travel is discontinued. Additionally, during the period when travel is allowed on the shoulder a lane-use control signal that continuously displays a yellow X shall be used approximately $\frac{1}{2}$ mile in advance of the location where part-time travel on the shoulder ends, and then displays a red X the travel on shoulder ends. A lane-use control signal with a red X shall be displayed at all times at the location where part-time travel on the shoulder ends.

32 Option:

For part-time travel on shoulder with variable periods of operation, post-mounted TRAVEL ON SHOULDER ALLOWED WHEN FLASHING (R3-51d) signs with flashing beacons may be used lieu of the lane-use control signals at the same intervals.

The TRAVEL ON SHOULDER ON GREEN AROW ONLY (R3-51e) sign may be used with a lane-use control signal; mounted adjacent to the signal head, elsewhere on the signal support, ground mounted next to, or in advance of, the signal.

Section 2G.25 Lane-Use Control Signals for Active Lane Management on Freeways and Expressways

Support:

Active lane management is a component of active traffic management in which the use of travel lanes and speed limits might be varied in real time in response to traffic conditions to manage congestion. Active lane management might employ lane-use control signals (see Chapter 4T) and/or changeable message signs (see Chapter 2L). Figure 2G-33 shows an example of lane-use control signals and Variable Speed Limit signs for active lane management during an incident

Figure 2G-33. Example of Lane-Use Control Signals and Variable Speed Limit Signs for Active Lane Management During an Incident

Standard:

Except as otherwise provided in this Section, lane-use control signals that are used for active lane management shall comply with the provisions of Chapter 4T. When used for active lane management

on a freeway or expressway, a steady YELLOW X signal indication shall be displayed to warn road users to vacate the lane when the next downstream lane-use control signal over the same lane is displaying a steady RED X signal indication.

Option:

A steady YELLOW X signal indication may be displayed on one or more lane-use control signals in advance of the steady YELLOW X signal indication required by Paragraph 2 as conditions warrant to warn road users to vacate the lane.

Support:

<u>Using too many YELLOW X signal indications could diminish the effectiveness of the YELLOW X in conveying the lane is closed a short distance ahead and the road user needs to vacate the lane soon</u>

Standard:

When operated in conjunction with a temporary planned lane closure, lane-use control signals shall only supplement the temporary traffic control devices as provided in Part 6 of this Manual.

Guidance:

Spacing of lane-use control signals for active lane management on freeways and expressways should be at ½-mile intervals. Closer spacing should be used where the viewing distance is limited by the roadway geometry, overcrossings or other sight obstructions, or where traffic entering from intervening interchange ramps is not adequately served by the ½-mile spacing.

Combining lane-use control signals with overhead sign support structures should be minimized to avoid overloading road users with too much information or conflicting or incorrect messages, such as exclusive lane use or lane drop implied by the display of a DOWNWARD GREEN ARROW below a guide sign.

Section 2G.26 Variable Speed Limits for Active Traffic Management on Freeways and Expressways

24 Support:

Active traffic management on freeways and expressways might employ variable speed limits as an element of an overall congestion management plan using changeable Speed Limit (R2-1) signs (see Section 2B.22).

Careful consideration is needed in locating Variable Speed Limit signs along the roadway and potential positioning adjacent to Guide signs or Lane-Use Control signals so that the speed displayed is clearly associated with the lane or lanes intended to be regulated and not other adjacent lanes, ramps or roadways. This might result in the need to place Variable Speed Limit signs on separate supports away from Guide and other signs or Lane-Use Control signals.

Standard:

The regulatory speed displayed on a changeable Speed Limit sign shall comply with Paragraph 2 of Section 2B.22 of this Manual.

Guidance:

The location and positioning of Variable Speed Limit signs should clearly associate the speed displayed to the lane or lanes intended to be regulated such that it would not present a conflict or confusion with other posted speed limit or advisory speeds for adjacent lanes, ramps or roadways.

In addition to the post-interchange Speed Limit sign (see Section 2E.38), the spacing of changeable Speed Limit signs on freeways and expressways should be based on an engineering study that considers such factors as recurring congestion, high-volume interchanges, weaving sections, and other location-specific factors that are known to affect travel speeds. The changeable Speed Limit signs should be placed far enough in advance of known congestion points to adequately adjust the operating speed to minimize the extent of vehicle queuing.

 Section <u>2H.01 Scope 2H.02 General Information Signs (I Series) This text has been relocated from existing Section 2H.02, reorganized, and revised</u>

Support:

Of interest to the traveler, though not directly necessary for guidance, are General Information signs provide road users with navigational or orientation, geographic, or other information useful for traffic operational purposes. numerous kinds of information that can properly be conveyed by General Information signs (see Figure 2H-1) or miscellaneous information signs (see Section 2H.04). They include such items as State lines, city limits, other political boundaries, time zones, stream names, elevations, landmarks, and similar items of geographical interestgeographic features, and safety and transportation related messages. Chapter 2M contains recreational and cultural interest area symbol signs that are sometimes used in combination with General Information signs. Section 1D.09 discusses unnecessary traffic control devices. Section 2A.03 discusses the excessive use of signs and sign clutter.

14 Option:

An information symbol sign (I3-5 through I3-9) may be used to identify a route leading to a transportation or general information facility, or to provide additional guidance to the facility provide direction to a transportation (I3 series signs) or General Information (I4 series signs) facility. The symbol sign may be supplemented by an educational plaque where necessary; also, the name of the facility may be used if needed to distinguish between similar facilities in the same area.

The Advance Turn (M5 series) or Directional Arrow (M6 series) auxiliary <u>signs-plaques</u> shown in Figure 2H-1 with white arrows on green backgrounds may be used with General Information symbol signs to create a General Information Directional Assembly.

Figure 2H-1. General Information and Miscellaneous Information Signs

Guidance:

General Information signs should not be installed within a series of guide signs, or at other equally critical locations, unless there are specific reasons for orienting the road user or identifying control points for activities that are clearly in the public interest. On all such signs, the designs should be simple and dignified, devoid of any tendency toward advertising, such as complex graphics or unnecessary messages, and in general compliance with other guide signing.

Standard:

Promotional descriptive messages that are not relevant to navigation and orientation, such as "Scenic" or "Historic," shall not be included in the legends of General Information signs, except as provided otherwise in this Chapter or in cases in which these terms are part of an official name, such as for a Scenic Byway or Historic District.

Except for political boundaryState Welcome signs (see Section 2H.07), Acknowledgment signs (see Section 2H.13), and Alternative Fuels Corridor signs (see Section 2H.14), General Information signs shall have white legends and borders on green rectangular-shaped backgrounds.

- Section 2H.012H.02 Sizes of General Information Signs
- 39 Standard:

Except as provided in Section 2A.11, the sizes of General Information signs that have a standardized design shall be as shown in Table 2H-1.

42 Support:

Section 2A.11 contains information regarding the applicability of the various columns in Table 2H-1.

44 Option:

Signs larger than those shown in Table 2H-1 may be used (see Section 2A.11), except where a maximum allowable size is specified.

Table 2H-1. General Information Sign Sizes

48 Option:

An information symbol sign (I-5 through I-9) may be used to identify a route leading to a transportation or general information facility, or to provide additional guidance to the facility. The symbol sign may be supplemented by an educational plaque where necessary; also, the name of the facility may be used if needed to distinguish between similar facilities. This text relocated to new Section 2H.01

The Advance Turn (M5 series) or Directional Arrow (M6 series) auxiliary signs shown in Figure 2H-1 with white arrows on green backgrounds may be used with General Information symbol signs to create a General Information Directional Assembly. This text relocated to new Section 2H.01

Guide signs for commercial service airports and non-carrier airports may be provided from the nearest-Interstate, other freeway, or conventional highway intersection directly to the airport, normally not to exceed-15 miles. The Airport (I3-5) symbol sign along with a supplemental plaque may be used to indicate the specific name of the airport. An Airport symbol sign, with or without a supplemental name plaque or the word AIRPORT, and an arrow may be used as a trailblazer. This text relocated to new Section 2H.03

Standard:

Adequate trailblazer signs shall be in place prior to installing the airport guide signs. This text relocated to new Section 2H.03

Support:

Location and placement of all airport guide signs depends upon the availability of longitudinal spacing on highways. This text relocated to new Section 2H.03

15 Option

The Recycling Collection Center (I-11) symbol sign may be used to direct road users to recycling collection centers.

18 Guidance:

The Recycline Collection Center symbol sign should not be used on freeways and expressways.

Standard:

If used on freeways or expressways, the Recycling Collection Center symbol sign shall be considered one of the supplemental sign destinations.

When a sign is used to display a safety or transportation-related message, the display format shall not be of a type that would be considered similar to advertising displays. Messages and symbols that resemble any official traffic control device shall not be used on safety or transportation-related message signs.

Option:

The pictograph of a political jurisdiction (such as a State, county, or municipal corporation) may be displayed on a political boundary General Information sign.

30 Standard:

If used, the height of a pictograph on a political boundary General Information sign shall not exceed two times the height of the upper-case letters of the principal legend on the sign. The pictograph shall comply with the provisions of Section 2A.06. This text relocated to new Section 2H.05

Section 2H.03 Airport Signs

Support:

Guide signs for commercial service airports and non-carrier airports may be provided from the nearest Interstate, other freeway, or conventional highway intersection directly to the airport, normally not to exceed 15 miles. The Airport (I-5) symbol sign along with a supplemental plaque may be used to indicate the specific name of the airport. An Airport symbol sign, with or without a supplemental name plaque or the word AIRPORT, and an arrow may be used as a trailblazer. This text relocated from existing Section 2H.02 Standard:

<u>Airport pictographs or other graphical representation of the specific airport shall not be used with or in place of the specific airport name on guide signs.</u>

Standard: Guidance:

<u>If airport guide signs are used, Aa</u>dequate trailblazer signs <u>shall</u> <u>should</u> be <u>used to provide motorist</u> <u>direction to the airport.in place prior to installing the airport guide signs.</u> This text relocated from existing Section 2H.02 and revised

48 Support:

Location and placement of all airport guide signs depends upon the availability of longitudinal spacing on highways. This text relocated from existing Section 2H.02

Section 2H.032H.04 Traffic Signal Speed Sign (I1-1)

Option:

The Traffic Signal Speed (II-1) sign (see Figure 2H-1), reading displaying the legend SIGNALS SET FOR XX MPH, may be used to indicate a section of street or highway on which the traffic control signals are coordinated into a progressive system timed for a specified speed at all hours during which they are operated in a coordinated mode.

If different system progression speeds are set for different times of the day, a changeable message element may be used for the numerals of the Traffic Signal Speed (II-1) sign. If the system is operated in coordinated mode only during certain times, a blank-out version of the Traffic Signal Speed (II-1) sign may be used to display the entire message only during those times.

Standard:

An electronic-display changeable section of the Traffic Signal Speed sign shall be a white legend on a black opaque or green background.

Guidance:

If used, the sign should be mounted as near as practical to each intersection where the timed speed changes, and at intervals of several blocks throughout any section where the timed speed remains constant.

16 Standard:

The Traffic Signal Speed sign shall be a minimum of 24 x 36 inches with the longer dimension vertical. It shall have a white message and border on a green background.

19 Section 2H.04 Miscellaneous Information Signs This section renumbered and edited and is now Section 2H.06

21 Section 2H.05 Jurisdictional Boundary (I2-1) Signs

22 Option:

The Jurisdictional Boundary (I2-1) sign may be used to mark the location of a jurisdictional boundary of a State, county, or municipality or the limits of an unincorporated municipal-level community.

25 Guidance:

If used, the Jurisdictional Boundary sign should be located at or as near as practicable to the jurisdictional boundary without interfering with higher priority traffic control devices. Notices of statutes or local ordinances should be located separately using regulatory signs (see Chapter 2B).

If used for an unincorporated community, the community should be one that is readily identifiable on official maps and be consistent with postal mailing addresses.

Standard:

In accordance with Section 2H.01, the Jurisdictional Boundary sign shall be rectangular in shape and shall have a white legend on a green background. The sign shall display only the name of the State, county, municipality, or other identifiable community, and an appropriate legend such as ENTERING, STATE LINE, County, or the municipal classification.

Names of elected officials or promotional messages, such as notable accomplishments or claims, shall not be displayed on a Jurisdictional Boundary sign.

Option:

A pictograph representing the jurisdiction may be displayed on the Jurisdictional Boundary sign.

Standard:

If a pictograph is displayed on the Jurisdictional Boundary sign, it shall be the official seal of the jurisdiction and shall comply with the provisions of Section 2A.06. The pictograph shall be placed to the left of the legend. The height of the pictograph shall not exceed two times the height of the initial upper-case letter of the principal legend.

Support:

Signs are not normally warranted to identify the boundaries of special-purpose governmental districts, such as school districts, sanitary districts, or improvement districts. Such signs are generally promotional in nature and do not provide navigational or orientation assistance in conjunction with official maps that are available to the general public.

Section 2H.07 contains information on State Welcome signs.

Section 2H.06 Geographical Feature (I2-2) Signs

2 Option:

The Geographical Feature (I2-2) sign may be used to mark the locations of land features such as river and stream crossings, and summits, that are identifiable on maps or serve as landmarks in providing navigational orientation or reference to the road user.

Guidance:

If used, the Geographical Feature (12-2) sign should display only the name of the geographical feature. Additional information that is unnecessary for navigational or orientation purposes, such as watershed or tributary names, should not be displayed on the sign.

Section 2H.07 State Welcome Signs

11 Support:

The design, placement, and function of State Welcome signs differ from Jurisdictional Boundary (I2-1) signs (see Section 2H.05) that are used to identify State lines. Because of these differences, it is necessary to distinguish State Welcome signs from State line Jurisdictional Boundary signs.

15 Option:

A State Welcome sign may be located at or in the vicinity of the State boundary except as prohibited in Paragraph 4.

State Welcome signs may display the State seal, the officially adopted State motto or slogan, and the name of the Governor, in addition to the State name. State Welcome signs may use legend and background colors that provide adequate visual contrast other than the standard sign colors.

Standard:

State Welcome signs shall not be located where they could interfere with or detract from other traffic control devices. If used, State Welcome signs shall be installed as independent, post-mounted sign assemblies.

State Welcome signs shall not display changeable or other electronic-display messages (see Chapter 2L). State Welcome signs shall not display messages that emulate promotional advertising of any type. State Welcome signs shall not incorporate Acknowledgment signs or messages (see Section 2H.13), or business identification sign panels or logos (see Section 2J.03) into their legends or assemblies. In accordance with Section 2A.04 of this Manual, telephone numbers, Internet addresses and e-mail addresses, including domain names and uniform resource locators (URL), and quick-response (QR) codes, bar codes, or other graphics intended for optical scanning for the purpose of obtaining information shall not be displayed in the legends of State Welcome signs or on their supports.

Guidance:

State Welcome signs should be located farther from the edge of the roadway than other traffic control
 devices.

The size of a State Welcome sign should be consistent with the prevailing size of other guide signs based on the roadway type.

Section 2H.08 Future Interstate Signs (I2-4, I2-4a)

39 Option:

The Future Interstate Route (I2-4) or Future Interstate Corridor (I2-4a) sign (see Figure 2H-2) may be used sparingly along an existing route that will be reconstructed as an Interstate route or along an existing route adjacent to a corridor through which an Interstate route will be constructed, in accordance with the Policy and Conditions stated in 23 CFR 470, Appendix C.

Where the route number has been approved by the FHWA, either the I2-4 or I2-4a sign may be used.

Standard:

The I2-4 sign shall not be used where the route number has not been approved by the FHWA.

Future Interstate signs shall not be located where they could interfere with or detract from other traffic control devices. If used, Future Interstate signs shall be installed as independent, post-mounted sign assemblies.

Future Interstate signs shall display a word legend only and shall not display the Interstate route marker or likeness thereof. Future Interstate signs shall not imply that an existing route has already

1 been designated and marked as an Interstate route. Signs indicating that an existing route is designated as a future Interstate route or corridor shall not provide directional or distance information. Route 2 3 Sign assemblies (see Section 2D.29) of any type shall not be used to sign a route as a future Interstate or 4 other route. 5 Figure 2H-2. Example of Future Interstate Corridor Sign 6 Guidance: 7 Future Interstate signs should be limited to strategic locations, such as at the beginning of the designated 8 route or corridor, or beyond interchanges connecting from existing Interstate highways. 9 Section 2H.09 Project Information Sign (I2-5)

10 Support:

11

12

13

14

15

16

17 18

19

2021

22

2324

25

26

27

28

29

30

31

32

34

35

36

39

40

41 42

43

44

45

46

47 48 The Project Information (I2-5) sign (see Figure 2H-3) provides limited information about a highway construction project on which work is ongoing.

Standard:

Project Information signs shall not be installed prior to the commencement of work or be used to provide advance notification of road work that will begin at some future date. Project Information signs shall be removed at the conclusion of work on the project, even if the final inspection or project closeout has not yet occurred.

The number of Project Information signs shall be limited to one per direction of travel on the roadway on which the project is based. The location of the Project Information sign shall not interfere with the temporary traffic control zone devices.

Figure 2H-3. Example of Project Information Signs

Section 2H.10 Grade Separation Identification Signs (I2-43, I2-43a)

Option:

<u>The Grade Separation Identification (I2-43, I2-43a) signs (see Figure 2H-4) may be used to identify a</u> grade separation of another highway or other transportation facility such as a railway, bikeway, or pathway.

Figure 2H-4. Grade Separation Identification Sign

Guidance:

Except as provided in Paragraph 4, when used to identify an overcrossing structure, the I2-43 sign should be mounted to the fascia of the structure above the travel lanes or shoulder of the highway below. Adequate separation from other overhead signs that are mounted to the structure should be provided.

When used to identify an undercrossing structure, the I2-43 or I2-43a sign should be post-mounted in advance of the structure as near to it as practicable.

33 Option:

When used to identify an overcrossing structure, the I2-43 or I2-43a sign may be post-mounted in front of an overcrossing or may be mounted to the abutment of the overcrossing facing approaching traffic.

Section 2H.052H.11 Reference Location Signs (D10-1 through D10-3) and Intermediate

37 Reference Location Signs (D10-1a through D10-3a)

38 Support:

There are two types of reference location signs:

- A. Reference Location (D10-1, 2, and 3) signs show an integer distance point along a highway, and
- B. Intermediate Reference Location (D10-1a, 2a, and 3a) signs also show a decimal between integer distance points along a highway.

Standard:

Except when Enhanced Reference Location signs (see Section 2H.062H.12) are used instead, Reference Location (D10-1 through D10-3) signs shall be placed on all expressway facilities that are located on a route where there is reference location sign continuity and on all freeway facilities to assist road users in estimating their progress, to provide a means for identifying the location of emergency incidents and traffic crashes, and to aid in highway maintenance and servicing.

49 Option:

Reference Location (D10-1 to through D10-3) signs (see Figure 2H-25) may be installed along any section of a highway route or ramp to assist road users in estimating their progress, to provide a means for identifying the location of emergency incidents and traffic crashes, and to aid in highway maintenance and servicing.

To augment the reference location sign system, Intermediate Reference Location (D10-1a to D10-3a) signs (see Figure 2H-36), which show the tenth of a mile with a decimal point, may be installed at one tenth of a mile, two tenths of a mile, or one-half mile intervals, or at some other regular spacing.

Figure 2H-5. Reference Location Signs

Figure 2H-6. Intermediate Reference Location Signs

Standard:

When Intermediate Reference Location (D10-1a to through D10-3a) signs are used to augment the reference location sign system, the reference location sign at the integer mile point shall display a decimal point and a zero numeral.

When placed on freeways or expressways, reference location signs shall contain 10-inch white numerals on a 12-inch wide green background with a white border. The signs shall be 24, 36, or 48-inches in height for one, two, or three digits, respectively, and shall contain the word MILE in 4-inch-white letters.

When placed on conventional roads, reference location signs shall contain 6-inch white numerals on a green background that is at least 10 inches wide with a white border. The signs shall contain the word MILE in 4-inch white letters.

Reference location signs shall have a minimum mounting height of 4 feet, measured vertically from the bottom of the sign to the elevation of the near edge of the roadway, and shall not be governed by the mounting height requirements prescribed in Section 2A.18.

The distance numbering shall be continuous for each route within a State, except where overlaps occur (see Section 2E.31). Where routes overlap, reference location sign continuity shall be established for only one of the routes. If one of the overlapping routes is an Interstate route, that route shall be selected for continuity of distance numbering.

Guidance:

The route selected for continuity of distance numbering should also have continuity in interchange exit numbering (see Section 2E.31).

On a route without reference location sign continuity, the first reference location sign beyond the overlap should indicate the total distance traveled on the route so that road users will have a means of correlating their travel distance between reference location signs with that shown on their odometer.

Standard:

For divided highways, the distance measurement shall be made on the northbound and eastbound roadways. The reference location signs for southbound or westbound roadways shall be set at locations directly opposite the reference location signs for the northbound or eastbound roadways.

Guidance:

Zero distance should begin at the south and west State lines, or at the south and west terminus points where routes begin within a State.

Standard:

Except as provided in Paragraph <u>1513</u>, reference location signs shall be installed on the right-hand side of the roadway.

Option:

Where conditions limit or restrict the use of reference location signs on the right-hand side of the roadway, they may be installed in the median. On two-lane conventional roadways, reference location signs may be installed on one side of the roadway only and may be installed back-to-back. Reference location signs may be placed up to 30 feet from the edge of the pavement.

If a reference location sign cannot be installed in the correct location, it may be moved in either direction as much as 50 feet.

Guidance:

2 Section 2H.06 2H.12 Enhanced Reference Location Signs (D10-4,) and Intermediate

Enhanced Reference Location Signs (D10-5)

Support:

1

3 4

5

6

7

8

9

10

11 12

13

1415

16

17

18 19

20

21

22 23

24 25

26

27

28

29

30

31

32

33

34

35

36

39

40 41

42

There are two types of enhanced reference location signs:

- A. Enhanced Reference Location signs (D10-4), and
- B. Intermediate Enhanced Reference Location signs (D10-5).

Option:

Enhanced Reference Location (D10-4) signs (see Figure 2H-47), which enhance the reference location sign system by identifying the route, may be placed on freeways or expressways (instead of Reference Location signs) or on conventional roads.

To augment an enhanced reference location sign system, Intermediate Enhanced Reference Location (D10-5) signs (see Figure 2H-47), which show the tenth of a mile with a decimal point, may be installed along any section of a highway route or ramp at one tenth of a mile intervals, or at some other regular spacing.

Figure 2H-7. Enhanced Reference Location Signs

Standard:

When Intermediate Enhanced Reference Location (D10-5) signs are used to augment the reference location sign system, the enhanced reference location sign at the integer mile point shall display a decimal point and a zero numeral.

If enhanced reference location signs are used, they shall be vertical signs having a blue or green backgrounds with white numerals, letters, legends and borders, except for the route shield, which shall be the standard color and shape. The top line shall consist of display the cardinal direction for the roadway. The second line shall consist of display the applicable route shield for the roadway. The third line shall identify the mile reference for the location and the bottom line of the Intermediate Enhanced Reference Location sign shall give the tenth of a mile reference for the location. The bottom line of the Intermediate Enhanced Reference Location sign shall contain a decimal point. The height of the legend on enhanced reference location signs shall be a minimum of 6 inches. The height of the route shield on enhanced reference location signs shall be a minimum of 12 inches.

The background color shall be the same for all enhanced reference location signs within a jurisdiction.

Support:

The provisions in Section <u>2H.052H.11</u> regarding mounting height, distance numbering and measurements, sign continuity, and placement with respect to the right-hand shoulder and/or median for reference location signs also apply to enhanced reference location signs.

Section 2H.07 <u>Auto Tour Route Signs</u> This section relocated to Chapter 2D and combined with Section 2D.57

37 Section 2H.082H.13 Acknowledgment Signs and Plaques (I20 Series)

38 Support:

Acknowledgment signs and plaques are a way of recognizing a company, business, or volunteer group that provides or sponsors a highway-related service. Acknowledgment signs include sponsorship signs for adopt-a-highway litter removal programs, maintenance of a parkway or interchange, and other highway maintenance or beautification sponsorship programs.

43 Guidance:

44 A State or local highway agency that elects to have <u>ana sponsorship</u> acknowledgement <u>sign</u>-program should 45 develop <u>an acknowledgement signa</u> policy <u>on Acknowledgment signs and plaques</u>. The policy should require

46 that eligible sponsoring organizations comply with State laws prohibiting discrimination based on race,

- 47 religion, color, age, sex, national origin, and other applicable laws. The acknowledgment sign policy should
- 48 include all of the provisions regarding sign placement and sign design that are described in this Section. This
- 49 text incorporated into the following Standard statement
- 50 Standard:

The State or local acknowledgment sign policy shall include all of the provisions regarding placement and design of Acknowledgment signs and plaques that are contained in this Section.

Because regulatory, warning, and guide signs have a higher priority, acknowledgment signs shall only be installed where adequate spacing is available between the acknowledgment sign and other higher priority signs. Acknowledgment signs shall not be installed in a position where they would obscure the road users' view of other traffic control devices.

Acknowledgment signs shall not be installed at any of the following locations:

- A. On the front or back of, adjacent to, or around any other traffic control device, including traffic signs, highway traffic signals, and changeable message signs;
- B. On the front or back of, adjacent to, or around the supports or structures of other traffic control devices, or bridge piers; or
- C. At key decision points where a road user's attention is more appropriately focused on other traffic control devices, roadway geometry, or traffic conditions, including exit and entrance ramps, merging or weaving areas, lane terminations, intersections, grade crossings, toll plazas, temporary traffic control zones, and areas of limited sight distance.

Acknowledgment signs and plaques shall have a white legend on a blue background.

Acknowledgment signs shall be independent post-mounted roadside installations only and shall not be overhead-mounted.

Option:

An Acknowledgment sign for the sponsor of a rest area or welcome center may be located on the highway mainline (one sign per direction of travel from which the rest area is accessible) at least 500 feet from other traffic control devices. An additional Acknowledgment sign may be used within the rest area provided that it is not visible from the highway mainline or ramps to and from the rest area.

Standard:

Acknowledgment signs for rest areas shall not display names or representations of specific products or services provided by the sponsor within the rest area. Acknowledgment signs for rest areas shall display the legend REST AREA as the program activity, such as REST AREA SPONSORED BY. In accordance with Paragraph 4, the Rest Area and Welcome Center Acknowledgment (I20-4 and I20-4a) signs shall not be combined in the same sign assembly with or substitute for the Rest Area General Service guide signs (see Section 2I.05).

Option:

If a State has officially adopted and is actively promoting a program to encourage the use of safety rest areas through the use of a program name, then that program name may be displayed in smaller lettering below the legend REST AREA on the Rest Area Acknowledgment sign.

Standard:

<u>Program name or slogans, as described in Paragraph 13, shall not be displayed on the rest area guide sign or other types of traffic signs.</u>

Guidance:

The minimum spacing between acknowledgment signs and any other traffic control signs, except parking regulation signs, should be:

- A. 150 feet on roadways with speed limits of less than 30 mph,
- B. 200 feet on roadways with speed limits of 30 to 45 mph, and
- C. 500 feet on roadways with speed limits greater than 45 mph.

If the placement of a newly-installed higher-priority traffic control device, such as a higher-priority sign, a highway traffic signal, or a temporary traffic control device, conflicts with an existing acknowledgment sign, the acknowledgment sign should be relocated, covered, or removed.

Option:

State or local highway agencies may develop their own acknowledgment sign designs and may also-use their own pictograph (see definition in Section 1A.13) and/or a brief jurisdiction-wide program slogan-name, such as "Adopt-A-Highway" or "Litter Removal," as part of any portion of the acknowledgment sign, provided that the signs comply with the provisions for shape, sign and legend size, color, and lettering style in this Chapter and in Chapter 2A.

53 Guidance:

Standard:

In addition to the general provisions for signs described in Chapter 2A and the sign design principles covered in the "Standard Highway Signs and Markings" book publication (see Section 1A.11), acknowledgment sign and plaque designs developed by State or local highway agencies shall comply with the following provisions:

- A. Neither the sign <u>or plaque</u> design nor the sponsor acknowledgment <u>name or logo</u> shall contain any contact information, directions, slogans (other than a brief jurisdiction-wide program <u>sloganname</u>, if used), telephone numbers, <u>or e-mail or Internet addresses</u>, including domain names and uniform resource locators (URL), <u>metadata tags</u> ("hash-tags"), or quick-response (QR) codes, bar codes, or similar graphics (see Section 2A.0504);
- B. Except for the lettering, if any, on the sponsor acknowledgment logo, all of the lettering shall be in upper-case letters of the Standard Alphabets as provided in the "Standard Highway Signs-and Markings" book-publication (see Section 1A.11);
- C. If a logo, instead of a word legend, is used to represent the sponsor, the logo shall be the primary logo that identifies the sponsoring entity. Secondary or alternate logos, slogans, products, mascots, spokespersons, or other items associated with the sponsoring entity's commercial advertising or marketing shall not be displayed on Acknowledgment signs or plaques;
- ED. In order to keep the main focus on the highway-related service and not on the sponsor acknowledgment name or logo, the area reserved for the sponsor acknowledgment name or logo (1) shall be a horizontally oriented rectangle with its width at least 1.67 times its height; (2) shall not be located at the top of the sign or plaque; (3) shall be a maximum of 8 square feet in area; and (4) for an Acknowledgment sign, shall not exceed 1/3 of the total area of the sign and shall be a maximum of 8 square feet, and shall not be located at the top of the sign;
- **<u>DE</u>**. The entire sign display area <u>of an Acknowledgment sign assembly</u> shall not exceed 24 square feet;
- **EF**. The sign <u>or plaque</u> shall not contain any messages, lights, symbols, or <u>trademarks logos</u> that resemble any official traffic control devices;
- **FG.** The sign <u>or plaque</u> shall not contain any external or internal illumination, light-emitting diodes, luminous tubing, fiber optics, luminescent panels, or other flashing, moving, or animated features; <u>and</u>
- **GH**. The sign <u>or plaque</u> shall not distract from official traffic control messages such as regulatory, warning, or guidance messages-:
- I. The sign or plaque shall be a horizontally oriented rectangle with the horizontal dimension longer than the vertical dimension;
- J. The area of the plaque shall not exceed the lesser of 1/3 the area of the General Service sign below which it is mounted or 24 square feet;
- K. The plaque size shall be based on the standard sizes as specified in Table 2I-1. If the size of the General Service sign is oversized for its application (greater than the size specified for the corresponding roadway application in Table 2I-1), or if the size of the General Service sign increases due to modification of the sign legend, a corresponding increase in the size of the plaque shall not be allowed; and
- L. The sign or plaque shall not display promotional or contact information about the agency's sponsorship program, including if the sign or plaque does not currently display a sponsor.

Option:

If a specific outlet of a business with multiple locations in the same area is the sponsoring entity, such as a franchisee, the area reserved for the sponsor acknowledgment name or logo may include the name of the municipality or neighborhood in which the sponsoring entity is located.

An Acknowledgment plaque may be mounted below the following General Service signs to acknowledge the sponsor of a corridor- or region-based highway-related service:

- A. Radio-Weather Information (D12-1) sign (see Section 2I.09);
- B. Radio-Traffic Information (D12-1a) sign (see Section 2I.09);
- 54 C. TRAVEL INFO CALL 511 (D12-5 and D12-5a) signs (see Section 2I.12);

1	D. Roadside Assistance (D12-0) sign (see Section 21.15).
2	Standard:
3	An Acknowledgment plaque shall not be mounted in conjunction with any other sign or other
4	traffic control device. An Acknowledgment plaque shall not be used alone or without one of the
5	General Service signs specified in Paragraph 14.
6	The general restrictions on the type of content allowed for display on Acknowledgment signs (see
7	Paragraph 13) shall apply to the legends of Acknowledgment plaques.
8	Support:
9	Examples of acknowledgment signs designs and plaques are shown in Figure 2H-58.
10	Figure 2H-8. Examples of Acknowledgement Sign Designs
11	Section 2H.14 Alternative Fuels Corridor Sign
12	Support:
13 14 15	The Alternative Fuels Corridor sign (D9-19) is sometimes used to inform motorist of an Alternative Fuels Corridor highway segment that have been designated by the Secretary of Transportation as alternative fuels "Corridor Ready."
16	Option:
17 18	The D18-1 sign may be used to identify an Alternative Fuels Corridor highway segment designated by the Secretary of Transportation as "Corridor Ready".
19	Standard:
20	Alternative Fuels Corridor signs shall only be used to designate alternative fuels corridor highway
21	segments that have been designated by the Federal Highway Administration as "Corridor Ready."
22	The appropriate General Service signs or plaques identifying the alternative fuels available in the
23	corridor shall be included with the Alternative Fuels Corridor signs in a sign assembly.
24 25	Alternative Fuels Corridor Signs shall only be post mounted on the side of the road and shall not be mounted in an overhead installation.
26 27	State or agency variations of the Alternative Fuels Corridor sign shall not be allowed. Acknowledgments of sponsors shall not be allowed in Alternative Fuels Corridor sign assemblies.
28	Support:
29	The Alternative Fuels Corridor sign provides limited information to travelers and therefore are used
30	sparingly.
31	Standard:
32	Except as provided in Paragraph 8, Alternative Fuels Corridor signs shall be limited to one sign at
33	or near the beginning of the Alternative Fuels Corridor in each direction of travel.
34	Option:
35	For long corridors, additional signs may be located beyond major intersections or major interchanges
36	following the typical post-interchange sign sequence.
37	The beginning of an Alternative Fuels Corridor may be indicated with a BEGIN (M4-14) plaque with a
38	white legend and border on a blue background mounted above the Alternative Fuels Corridor sign in the sign
39	assembly.
40 41	The end of an Alternative Fuels Corridor may be indicated with an END (M4-6) plaque with a white legend and border on a blue background mounted above the Alternative Fuels Corridor sign in the sign
42	assembly.
43	Standard:
44	The General Service signs shall not be used in the sign assembly indicating the end of a corridor.
45	
	Guidance:
46 47	When the availability of one or more of the alternative fuel facilities discontinues in an Alternative Fuels Corridor, the LAST IN CORRIDOR (W16-19P)(See Figure 2H-9) warning plaque should be included on the
48	last General Service Directional Assembly on the approach to the interchange or intersection.
49	Option:
50	When the availability of one or more of the alternative fuel facilities discontinues in an Alternative Fuels
51	Corridor, an Alternative Fuels Corridor sign with accompanying General Service signs indicating the types of

fuels still available in the corridor may be provided beyond the intersection or interchange where the last
 discontinues fuel facilities were available.

Standard:

4 The Alternative Fuels Corridor signs shall not be used as directional signs or be combined with other signs, except as provided herein.

Option:

<u>Up to three General Service symbol signs displaying the alternative fuels available in the designated</u> corridor may be installed below the Alternative Fuels Corridor sign, arranged horizontally (see Figure 2H-10).

Standard:

The size of the General Service symbol signs for the alternative fuels available shall not exceed 18 inches when mounted with the 24-inch Alternative Fuels Corridor sign and 24 inches when mounted with the 36-inch Alternative Fuels Corridor sign.

Guidance:

When the number of eligible alternative fuels available in the corridor exceeds three, a separate plaque with the two- or three-letter designations (D9-11gP or D9-11hP) of each of the fuels available should be used in place of the General Service symbol signs (see Figure 2H-10).

Standard:

When the Alternative Fuels Corridor sign is used in a designated corridor on a freeway or expressway, the applicable General Service sign(s) shall be installed on the approach to an interchange in the corridor from which the designated fuel services are available. If the services are not visible from the ramp of a single-exit interchange, the service signing shall be repeated at the intersection of the exit ramp and the crossroad. Where the alternative fuel facility is not located along the crossroad, additional General Service Directional Assemblies shall be installed in advance of each subsequent turn to reach the facility.

Support:

Because regulatory, warning, and guide signs are necessary for safe and efficient movement of traffic they have a higher priority in placement location over Alternative Fuels Corridor signs.

Figure 2H-9. Alternative Fuels Corridor Sign

Figure 2H-10. Example of Signing Alternative Fuels Corridors

Standard:

Alternative Fuels Corridor sign assemblies shall be limited to those locations where adequate spacing is available between the Alternative Fuels Corridor sign and other higher priority signs.

Alternative Fuels Corridor signs shall not be installed in a location where they would obscure the road users' view of other traffic control devices or distract driver's attention from the roadway in a complex roadway environment. Alternative Fuels Corridor sign shall not be installed at any of the following locations:

- A. On the front or back of, adjacent to, or around any other traffic control device, including traffic signs, highway traffic signals, and changeable message signs;
- B. On the front or back of, adjacent to, or around the supports or structures of other traffic control devices;
- C. At key decision points where a road user's attention is more appropriately focused on other traffic control devices, roadway geometry, or traffic conditions, including exit and entrance ramps, intersections, grade crossings, toll plazas, temporary traffic control zones, and areas of limited sight distance; or
- D. On routes other than those officially designated as Alternative Fuels Corridors, even if to provide directional information to such corridors, i.e., they shall not appear on supplemental signs or on any other information sign on or along the highway or its intersecting routes.

The minimum spacing between Alternative Fuels Corridor signs and any other traffic control signs, except parking regulation signs, should be:

- A. 150 feet on roadways with speed limits of less than 30 mph,
- B. 200 feet on roadways with speed limits of 30 to 45 mph, and

- C. 500 feet on roadways with speed limits greater than 45 mph.
 If the placement of a newly-installed, higher-priority traffic control device, such as a higher-priority sign, a highway traffic signal, or a temporary traffic control device, conflicts with an existing
 Alternative Fuels Corridor sign, the Alternative Fuels Corridor sign shall be relocated, covered, or
- 5 removed.

4

5

6

7

9

10

11

13

14

15

16 17

18

19

2021

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37 38

39

40

41

42.

43 44

45

46

47

2 Section 2I.01 Sizes of General Service Signs

3 Standard:

Except as provided in Section 2A.11, the sizes of General Service signs that have a standardized design shall be as shown in Table 2I-1.

Support:

Section 2A.11 contains information regarding the applicability of the various columns in Table 2I-1.

8 Option:

Signs larger than those shown in Table 2I-1 may be used (see Section 2A.11).

Table 2I-1. General Service Sign and Plaque Sizes

Section 2I.02 General Service Signs for Conventional Roads

12 Support:

On conventional roads, commercial services such as gas, food, and lodging generally are within sight and are available to the road user at reasonably frequent intervals along the route. Consequently, on this class of road there usually is no need for special signs calling attention to these services. Moreover, General Service signing is usually not required needed in urban areas except for hospitals, law enforcement assistance, tourist information centers, and camping.

Option:

General Service signs (see Figure 2I-1) may be used where such services are infrequent and are found only on an intersecting highway or crossroad.

Figure 2I-1. General Service Signs and Plaques

Standard:

All General Service signs and supplemental sign panels shall have white letters, symbols, arrows, legends and borders on a blue background.

Guidance:

General Service signs should be installed at a suitable distance in advance of the turn-off point or intersecting highway.

States that elect to provide General Service signing should establish a statewide policy or warrant for its use, and criteria for the availability of services. Local jurisdictions electing to use such signing should follow State policy for the sake of uniformity.

Option:

Individual States may sign for whatever alternative fuels are available at appropriate locations.

Standard:

General Service signs, if used at intersections, shall be accompanied by a directional message.

Option:

The Advance Turn (M5 series) or Directional Arrow (M6 series) auxiliary <u>signs plaques</u> with white arrows on blue backgrounds as shown in Figure 2I-1 may be used with General Service symbol signs to create a General Service Directional Assembly.

The General Service sign legends may be either symbols or word messages.

Standard:

Symbols and word message General Service legends shall not be intermixed on the same sign. The Pharmacy (D9-20) sign shall only be used to indicate the availability of a pharmacy that is open, with a State-licensed pharmacist present and on duty, 24 hours per day, 7 days per week, and that is located within 3 miles of an interchange on the Federal-aid system. The D9-20 sign shall have a 24 HR (D9-20aP) plaque mounted below it.

<u>Use of the Hospital (D9-2) sign or the HOSPITAL word message shall be limited to facilities that operate 24 hours per day, 7 days per week.</u>

48 Option:

49

The Emergency Medical Services (D9-13) sign (see Paragraph 19) may be used for facilities that provide emergency medical care but do not operate on a full-time basis.

Support:

Formats for displaying different combinations of these services are described in Section 2I.03.

Option

1

2

3

4

5 6

7

8

9

10

11 12

131415

16 17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36 37

38

39

40

41

42

43

44

45

46

47

48

49

50 51

52

If the distance to the next point at which services are available is 10 miles or more, a NEXT SERVICES XX MILES (D9-17P) plaque (see Figure 2I-2) may be installed below the General Service sign.

The International Symbol of Accessibility for the Handicapped (D9-6) sign may be used beneath General Service signs where paved ramps and rest room facilities accessible to, and usable by, the physically handicapped are provided.

Guidance:

When the D9-6 sign is used in accordance with Paragraph 13, and van-accessible parking is available at the facility, a VAN ACCESSIBLE (D9-6P) plaque (see Figure 2I-1) should be mounted below the D9-6 sign.

The Recreational Vehicle Sanitary Station (D9-12) sign may be used as needed to indicate the availability of facilities designed for the use of dumping wastes from recreational vehicle holding tanks.

The Litter Container (D9-4) sign may be placed in advance of roadside turnouts or rest areas, unless it distracts the driver's attention from other more important regulatory, warning, or directional signs.

The Emergency Medical Services (D9-13) symbol sign may be used to identify medical service facilities that have been included in the Emergency Medical Services system under a signing policy developed by the State and/or local highway agency.

Figure 2I-2. Example of Next Services Plaque

Standard:

The Emergency Medical Services symbol sign shall not be used to identify services other than qualified hospitals, ambulance stations, and qualified free-standing emergency medical treatment centers. If used, the Emergency Medical Services symbol sign shall be supplemented by a sign or plaque, as provided in Paragraph 21, identifying the type of service provided.

Option:

The Emergency Medical Services symbol sign may be used above the HOSPITAL (D9-13aP) plaque or Hospital (D9-2) symbol sign or above a plaque with the legend AMBULANCE STATION (D9-13bP), EMERGENCY MEDICAL CARE (D9-13cP), or TRAUMA CENTER (D9-13dP). The Emergency Medical Services symbol sign may also be used to supplement Telephone (D9-1), Channel 9 Monitored (D12-3), or POLICE (D9-14) signs.

Standard:

The legend EMERGENCY MEDICAL CARE shall not be used for services other than qualified free-standing emergency medical treatment centers.

Guidance:

Each State should develop <u>guidelines a policy</u> for the implementation of the Emergency Medical Services symbol sign.

The State should consider the following guidelines in the preparation of its policy:

A. AMBULANCE

- 1. 24-hour service, 7 days per week.
- 2. Staffed by two State-certified persons trained at least to the basic level.
- 3. Vehicular communications with a hospital emergency department.
- 4. Operator should have successfully completed an emergency-vehicle operator training course.

B. HOSPITAL

- 1. 24-hour service, 7 days per week.
- 2. Emergency department facilities with a physician (or emergency care nurse on duty within the emergency department with a physician on call) trained in emergency medical procedures on duty.
- 3. Licensed or approved for definitive medical care by an appropriate State authority.
- 4. Equipped for radio voice communications with ambulances and other hospitals.

- C. Channel 9 Monitored
 - 1. Provided by either professional or volunteer monitors.
 - 2. Available 24 hours per day, 7 days per week.
 - 3. The service should be endorsed, sponsored, or controlled by an appropriate government authority to guarantee the level of monitoring.

Section 2I.03 General Service Signs for Freeways and Expressways

Support:

1

2

3

4 5

6

7

8

9

10

11

12

13

14

15

16 17

18

19

20

21 22

23

24

25

26

27

28

29

30

31

32 33

34

35

3637

38

39

40

41

42

43

44

45

46 47

48

49 50

51

General Service (D9-18 series) signs (see Figure 2I-3) are generally not appropriate at major interchanges (see definition in Section 2E.32) and in urban areas.

Figure 2I-3. Examples of General Service Signs with and without Exit Numbering Standard:

General Service signs shall have white letters, symbols, arrows, legends and borders on a blue background. Letter and numeral sizes shall comply with the minimum requirements of Tables 2E-2 through 2E-5. All approved symbols shall be permitted as alternatives to word messages, but symbols and word service messages shall not be intermixed on the same sign. If the services are not visible from the ramp of a single-exit interchange, the service signing shall be repeated in smaller size at the intersection of the exit ramp and the crossroad. Such service signs shall use arrows to indicate the direction to the services.

Option:

For numbered interchanges, the exit number may be incorporated within the sign legend (D9-18b) or displayed on an Exit Number (E1-5P) plaque (see Section 2E.31). This text relocated to later in this section and revised

Guidance:

The D9-18 or D9-18a sign should be used for numbered interchanges.

Distance to services should be displayed on General Service signs <u>along the exit ramp</u> where distances are more than 1 mile <u>from the ramp intersection with the crossroad</u>.

General Service signing should only be provided at locations where the road user can return to the freeway or expressway and continue in the same direction of travel.

Option:

For numbered interchanges, the exit number may be incorporated displayed within the sign legend (D9-18b) or displayed on an Exit Number (E1-5P) plaque (see Section 2E.31) instead of within the General Service sign (D9-18 or D9-18a). This text relocated from earlier in this section and revised Guidance:

Only services that fulfill the needs of the road user should be displayed on General Service signs. If State or local agencies elect to provide General Service signing, there should be a statewide policy for such signing and criteria for the availability of the various types of services. The criteria should consider the following:

- A. Gas, Diesel, LP Gas, EV Charging, and/or other alternative fuels if all of the following are available:
 - 1. Vehicle services such as gas, oil, and water;
 - 2. Modern sanitary facilities and drinking water;
 - 3. Continuous operations at least 16 hours per day, 7 days per week; and
 - 4. Public telephone.
- B. Food if all of the following are available:
 - 1. Licensing or approval, where required;
 - 2. Continuous operation to serve at least two meals per day, at least 6 days per week;
 - 3. Public telephone; and
 - 4. Modern sanitary facilities.
- C. Lodging if all of the following are available:
 - 1. Licensing or approval, where required;
 - 2. Adequate sleeping accommodations;
 - 3. Public telephone; and
 - 4. Modern sanitary facilities.

- D. Public Telephone if continuous operation, 7 days per week is available.
- E. Hospital if continuous emergency care capability, with a physician on duty 24 hours per day, 7 days per week is available. A physician on duty would include the following criteria and should be signed in accordance with the priority as follows:
 - 1. Physician on duty within the emergency department;
 - 2. Registered nurse on duty within the emergency department, with a physician in the hospital on call; or
 - 3. Registered nurse on duty within the emergency department, with a physician on call from office or home.
- F. 24-Hour Pharmacy if a pharmacy is open, with a State-licensed pharmacist present and on duty, 24 hours per day, 7 days per week and is located within 3 miles of an interchange on the Federal-aid system.
- *G.* Camping if all of the following are available:
 - 1. Licensing or approval, where required;
 - 2. Adequate parking accommodations; and
 - 3. Modern sanitary facilities and drinking water.

Support:

Motorist expectations for facilities providing alternative fuels, e.g. EV Charging, compressed natural gas, liquefied natural gas, liquefied propane gas, and hydrogen, vary considerably and alternative fuel vehicles may have different needs than conventional fuel vehicles.

Option:

The policy criteria for alternative fuel vehicles may vary from other conventional fuel facilities, taking into account motorist needs, convenience and safety.

Standard:

For any service that is operated on a seasonal basis only, the General Service signs shall be removed or covered during periods when the service is not available.

The General Service signs shall be mounted in an effective location, between the Advance Guide sign and the Exit Direction sign, in advance of the exit leading to the available services.

Guidance:

The General Service sign should contain display the interchange number, if any applicable contain the interchange number, if any, as shown in Figure 2I-3.

Option:

If the distance to the next point where services are available is greater than 10 miles, a NEXT SERVICES XX MILES (D9-17P) plaque (see Figure 2I-2) may be installed below the Exit Direction sign.

Standard:

Signs for services shall comply with the format for General Service signs (see Section 2I.02) and as provided in this Manual. No more than six general road user services shall be displayed on one sign, which includes any appended supplemental signs or plaques. General Service signs shall earry display the legends for one or more of the following services: Food, Gas, Lodging, Camping, Phone, Hospital, 24-Hour Pharmacy, or Tourist Information.

The qualified services available shall be displayed at specific locations on the sign. To provide flexibility for the future when the services that might become available, the sign space normally reserved for a given service symbol or word shall be left blank when that service is not present. Incorporated into Guidance statement that follows

Guidance:

To provide flexibility for the future when the services that might become available, the sign space normally reserved for a given service symbol or word shall should be left blank when that service is not present.

The standard display of word messages should be FOOD and PHONE in that order on the top line, and GAS and LODGING on the second line. If used, HOSPITAL, <u>24-HR PHARMACY</u>, and CAMPING should be on separate lines (see Figure 21-3).

52 Option:

Signing for DIESEL, LP-<u>GASGas</u>, or other alternative fuel services may be substituted for any of the general services or appended to such signs. The International Symbol of Accessibility for the Handicapped (D9-6) sign (see Figure 2I-1) may be used for facilities that qualify.

Guidance.

When symbols are used for the road user services, they should be displayed as follows:

- A. Six services:
 - 1. Top row—GAS, FOOD, and LODGING
 - 2. Bottom row—PHONE, HOSPITAL, and CAMPING
- B. Four services:
 - 1. Top row—GAS and FOOD
 - 2. Bottom row—LODGING and PHONE
- C. Three services:
 - 1. Top row—GAS, FOOD, and LODGING

Option:

Substitutions of other services for any of the services described in Paragraph 16-18 may be made by placing the substitution in the lower right (four or six services) or extreme right (three services) portion of the sign. An action message or an interchange number may be used for symbol signs in the same manner as they are used for word message signs. The Diesel Fuel (D9-11) symbol or the LP-Gas (D9-1511d) symbol may be substituted for the symbol representing fuel -or appended to such assemblies. The Tourist Information (D9-10) symbol or the 24-Hour Pharmacy (D9-20 and D9-20aP) symbol may be substituted on any of the configurations provided in Paragraph 1618.

At rural interchange areas where limited road user services are available and where it is unlikely that additional services will be provided within the near future, a supplemental plaque (D9-18dP) displaying one to three services (words or symbols) may be appended mounted below a post-mounted interchange Advance guide sign.

Standard:

If more than three services become available at rural interchange areas where limited road user services were anticipated, the appended supplemental plaque described in Paragraph 18-20 shall be removed and replaced with an independently mounted General Service sign as described in this Section. Option:

A separate Telephone Service (D9-1) sign (see Figure 2I-1) may be installed if telephone facilities are located adjacent to the route at places where public telephones would not normally be expected.

The Recreational Vehicle Sanitary Station (D9-12) sign (see Figure 2I-1) may be used as needed to indicate the availability of facilities designed for dumping wastes from recreational vehicle holding tanks.

In some locations, signs may be used to indicate that services are not available.

A separate Truck Parking (D9-16) sign (see Figure 2I-1) may be mounted below the other general road user services to direct truck drivers to designated parking areas.

Section 2I.04 <u>Interstate Oasis Signing (D5-12 Series)</u>

Support:

An Interstate Oasis is a facility near an Interstate highway that provides products and services to the public, 24-hour access to public restrooms, and parking for automobiles and heavy trucks. Interstate Oasis guide signs inform road users on Interstate highways as to the presence of an Interstate Oasis at an interchange and which businesses have been designated by the State within which they are traveling as having met the eligibility criteria of the Federal Highway Administration's Interstate Oasis policy. The FHWA's policy, which is dated October 18, 2006, and which can be viewed on the MUTCD website at http://mutcd.fhwa.dot.gov/res-policy.htm, provides a more detailed definition of an Interstate Oasis and specifies the eligibility criteria for an Interstate Oasis designation in compliance with the requirements of laws enacted by Congress.

Guidance:

If a State elects to provide or allow Interstate Oasis signing (see Figure 2I-4), there should be a statewide policy, program, procedures, and criteria for the designation and signing of a facility as an Interstate Oasis that complies with FHWA's policy and with the provisions of this Section.

States electing to provide or allow Interstate Oasis signing should use the following signing practices on the freeway for any given exit to identify the availability of a designated Interstate Oasis:

- A. If adequate sign spacing allows, a separate Interstate Oasis (D5-12) sign should be installed in an effective location with spacing of at least 800 feet from other adjacent guide signs, including any Specific Service signs. This Interstate Oasis sign should be located upstream from the Advance Guide sign or between the Advance Guide sign and the Exit Direction sign for the exit leading to the Interstate Oasis. The Interstate Oasis sign should have a white legend with a letter height of at least 10 inches and a white border on a blue background and should contain display the words INTERSTATE OASIS and the exit number or, for an unnumbered interchange, an action message such as NEXT RIGHT. The names or logos of the businesses designated as Interstate Oases should not be included on this sign. Incorporated into Option statement that follows
- B. If the spacing of the other guide signs precludes the use of a separate sign as described in Item A, an INTERSTATE OASIS (D5-12aP) -supplemental plaque with a letter height of at least 10 inches and with a white legend and border on a blue background should be appended above or mounted below an existing D9-18 series General Service sign for the interchange.

If a separate Interstate Oasis (D5-12) sign is installed, an Interstate Oasis sign panel should be incorporated into the design of the sign (see Figure 2I 4).

Figure 2I-4. Examples of Interstate Oasis Signs and Plaques

Standard:

The Interstate Oasis sign panel shall only be used on the separate Interstate Oasis sign where it is accompanied by the words INTERSTATE OASIS and shall not be used independently without the words.

Option:

If Specific Service signing is provided at the interchange, a business designated as an Interstate Oasis and having a business logo sign panel on the Food and/or Gas Specific Service signs may use the bottom portion of the business logo sign panel to display the word OASIS.

If Specific Service signing is not provided at the interchange, the name of the business designated as an Interstate Oasis may be displayed on a business identification sign panel, in compliance with the provisions of Sections 2J.03 through 2J.05, below the INTERSTATE OASIS legend on the D5-12 sign.

Standard:

If Specific Services signs containing the OASIS legend as a part of the business logo(s) are not used on the ramp and if the Interstate Oasis is not clearly visible and identifiable from the exit ramp, an Interstate Oasis Directional (D5-12b) sign with a white INTERSTATE OASIS legend with a letter height of at least 6 inches and a white border on a blue background shall be provided on the exit ramp to indicate the direction and distance to the Interstate Oasis.

If needed, additional trailblazer guide signs shall be used along the crossroad to guide road users to an Interstate Oasis.

Section 2I.05 Rest Area and Other Roadside Area Signs (D5-1 through D5-11 series)

Standard:

Rest Area signs (see Figure 2I-5) shall have a retroreflective white legend and border on a blue background.

Signs that include the legend REST AREA shall be used only where parking and restroom facilities are available.

Guidance:

A roadside area that does not contain restroom facilities should be signed to indicate the major road user service that is provided. For example, the sign legends for an area with only parking should use the words PARKING AREA (D5-9 series) instead of REST AREA. The sign legends for an area with only picnic tables and parking should use words such as PICNIC AREA, ROADSIDE TABLE, or ROADSIDE PARK (D5-10 series) instead of REST AREA.

Rest areas that have tourist information and welcome centers should be signed as discussed provided in Section 21.08.

Scenic area signing should be consistent with that provided for rest areas, except that the legends should use words such as SCENIC AREA, SCENIC VIEW, or SCENIC OVERLOOK (D5-11 series) instead of REST AREA.

If a rest area or other roadside area is provided on a conventional road, a D5-1 and/or D5-1a sign should be installed in advance of the rest area or other roadside area to permit the driver to reduce speed in preparation for leaving the highway. A D5-5 sign (or a D5-2 sign if an exit ramp is provided) should be installed at the turnoff point where the driver needs to leave the highway to access the rest area or other roadside area.

If a rest area or other roadside area is provided on a freeway or expressway, a D5-1 sign should be placed 1 mile and/or 2 miles in advance of the rest area.

Figure 2I-5. Rest Area and Other Roadside Area Signs

Standard:

A D5-2a sign shall be placed at the rest area or other roadside area exit gore.

Option:

A D5-1a sign may be placed between the D5-1 sign and the exit gore on a freeway or expressway. A second D5-1 sign may be used in place of the D5-1a sign with a distance to the nearest 1/2 or 1/4 mile displayed as a fraction rather than a decimal for distances of less than 1 mile.

To provide the road user with information on the location of succeeding rest areas, a NEXT REST AREA XX MILES (D5-6) sign (see Figure 2I-5) may be installed independently or as a supplemental sign mounted below one of the REST AREA advance guide signs.

Standard:

All signs on freeways and expressways for rest and other roadside areas shall have letter and numeral sizes that comply with the minimum requirements of Tables 2E-2 through 2E-5. The sizes for General Service signs that have standardized designs shall be as shown in Table 2I-1.

Option:

If the rest area has facilities for the physically impaired (see Section 2I.02), the International Symbol of Accessibility for the Handicapped (D9-6) sign (see Figure 2I-1) may be placed with or beneath the REST AREA advance guide sign.

If telecommunication devices for the deaf (TDD) are available at the rest area, the TDD (D9-21) symbol sign (see Figure 2I-1) may be used to supplement the advance guide signs for the rest area.

If wireless Internet services are available at the rest area, the Wi-Fi (D9-22) symbol sign (see Figure 2I-1) may be used to supplement the advance guide signs for the rest area.

Section 2I.06 Brake Check Area Signs (D5-13-and, D5-14)

Guidance:

If an area has been provided for drivers to check the brakes on their vehicle, a BRAKE CHECK AREA XX MILES (D5-13) sign (see Figure 2I-6) should be installed in advance of the brake check area, and a D5-14 sign (see Figure 2I-6) should be placed at the entrance to the brake check area.

Figure 2I-6. Brake Check Area and Chain-Up Area Signs

Section 2I.07 Chain-Up Area Signs (D5-15-and, D5-16)

40 Guidance:

If an area has been provided for drivers to pull off of the roadway to install chains on their tires, a CHAIN-UP AREA XX MILES (D5-15) sign (see Figure 2I-6) should be installed in advance of the chain-up area, and a D5-16 sign (see Figure 2I-6) should be placed at the entrance to the chain-up area.

Section 2I.08 Tourist Information and Welcome Center Signs (D5-7 Series, D5-8)

45 Support:

Tourist information and welcome centers have been constructed within rest areas on freeways and expressways and are operated by either a State or a private organization. Others have been located within close proximity to these facilities and operated by civic clubs, chambers of commerce, or private enterprise.

49 Guidance:

An excessive The number of supplemental sign panels should not be installed with Tourist Information or Welcome Center signs should be limited to three so as not to overload impose an undue informational load on the road user.

Standard:

Tourist Information or Welcome Center signs (see Figure 2I-7) shall have a white legend and border on a blue background. Continuously staffed or unstaffed operation at least 8 hours per day, 7 days per week, shall be required.

If operated only on a seasonal basis, the Tourist Information or Welcome Center signs shall be removed or covered during the off seasons.

Guidance:

For freeway or expressway rest area locations that also serve as tourist information or welcome centers, the following signing criteria should be used:

- A. The locations for tourist information and welcome center Advance Guide, Exit Direction, and Exit Gore signs should meet the General Service signing requirements described in Section 2I.03.
- B. If the signing for the tourist information or welcome center is to be accomplished in conjunction with the initial signing for the rest areas, the message on the Advance Guide (D5-7) sign should be REST AREA, TOURIST INFO CENTER, XX MILES or REST AREA, STATE NAME (optional), WELCOME CENTER XX MILES. On the Exit Direction (D5-8 or D5-11) sign the message should be REST AREA, TOURIST INFO CENTER with a diagonally upward-pointing directional arrow (or NEXT RIGHT), or REST AREA, STATE NAME (optional), WELCOME CENTER with a diagonally upward-pointing directional arrow (or NEXT RIGHT).
- C. If the initial rest area Advance Guide and Exit Direction signing is in place, these signs should include, on supplemental signs, the legend TOURIST INFO CENTER or STATE NAME (optional), WELCOME CENTER.
- D. The Exit Gore sign should contain only the legend REST AREA with the arrow and should not be supplemented with any legend pertaining to the tourist information center or welcome center.

Option:

An As an alternative to the supplemental TOURIST INFO CENTER legend, is the Tourist Information (D9-10) sign (see Figure 2I-1) which may be appended beneath the REST AREA advance guide sign.

The name of the State or local jurisdiction may appear on the Advance Guide and Exit Direction tourist information/welcome center signs if the jurisdiction controls the operation of the tourist information or welcome center and the center meets the operating criteria set forth in this Manual and is consistent with State policies.

Guidance:

For tourist information centers that are located off the freeway or expressway facility, additional signing criteria should be as follows:

- A. Each State should adopt a policy establishing the maximum distance that a tourist information center can be located from the interchange in order to be included on official signs.
- B. The location of signing should be in accordance with requirements pertaining to General Service signing (see Section 2I.03).
- C. Signing along the crossroad should be installed to guide the road user from the interchange to the tourist information center and back to the interchange.

Option:

As an alternative, the Tourist Information (D9-10) sign (see Figure 2I-1) may be appended to the guide signs for the exit that provides access to the tourist information center. As a second alternative, the Tourist Information sign may be combined with General Service signing.

Figure 2I-7. Examples of Tourist Information and Welcome Center Signs

Section 2I.09 Radio Information Signing (D12-1 Series)

Option:

Radio-Weather Information (D12-1) signs (see Figure 2I-8) may be used in areas where difficult driving conditions commonly result from weather systems. Radio-Traffic Information (D12-1a) signs may be used in conjunction with traffic management systems.

Standard:

Radio-Weather and Radio-Traffic Information signs shall have a white legend and border on a blue background. Only the numerical indication of the radio frequency shall be used to identify a station broadcasting travel-related weather or traffic information. No more than three frequencies shall be displayed on each sign. Only radio stations whose signal will be of value to the road user and who agree to broadcast either of the following two items shall be identified on Radio-Weather and Radio-Traffic Information signs:

- A. Periodic weather warnings at a rate of at least once every 15 minutes during periods of adverse weather; or
- B. Driving condition information (affecting the roadway being traveled) at a rate of at least once every 15 minutes, or when required, during periods of adverse traffic conditions, and when supplied by an official agency having jurisdiction.

If a station to be considered operates only on a seasonal basis, its signs shall be removed or covered during the off season.

Guidance:

The radio station should have a signal strength to adequately broadcast 70 miles along the route. Signs should be spaced as needed for each direction of travel at distances determined by an engineering study. The stations to be included on the signs should be selected in cooperation with the association(s) representing major broadcasting stations in the area to provide: (1) maximum coverage to all road users on both AM and FM frequencies; and (2) consideration of 24 hours per day, 7 days per week broadcast capability.

Option:

The Urgent Message When Flashing (D12-1bP) plaque may be mounted below the D12-1 or D12-1a sign if supplemented by warning beacons (see Section 4L.03) that flash only when a message related to adverse travel conditions is being broadcast.

In roadway rest area locations, a smaller sign using a greater number of radio frequencies, but of the same general design, may be used.

Standard:

Radio-Weather and Radio-Traffic Information signs installed in rest areas shall be positioned such that they are not visible from the main roadway.

Option:

A Channel 9 Monitored (D12 3) sign (see Figure 2I-8) may be installed as needed. Official public agencies or their designees may be displayed as the monitoring agency on the sign.

Standard:

Only official public agencies or their designee shall be displayed as the monitoring agency on the Channel 9 Monitored sign. This text relocated to new Section 2I.10

36 Option:

An EMERGENCY CALL XX (D12-4) sign (see Figure 2I-8), along with the appropriate number to call, may be used for cellular phone communications. This text relocated to new Section 2I.11

Section 2I.10 Channel 9 Monitored Sign (D12-3) This text relocated from existing Section 2I.09 Option:

A Channel 9 Monitored (D12-3) sign (see Figure 2I-8) may be installed as needed. Official public agencies or their designees may be displayed as the monitoring agency on the sign.

Standard:

Only official public agencies or their designee shall be displayed as the monitoring agency on the Channel 9 Monitored sign.

Section 2I.11 EMERGENCY CALL XX Sign (D12-4)

47 Option:

An EMERGENCY CALL XX (D12-4) sign (see Figure 2I-8), along with the appropriate number to call, may be used for cellular <u>telephone</u> communications. This text relocated from existing Section 2I.09 and revised

Section 2I.10 Section 2I.12 TRAVEL INFO CALL 511 Signs (D12-5-and, D12-5a)

1

2 3

4

5

6

7

8 9

10

11

12

13 14

15

16

17

18

19

20

22

23

24

25

27

28

29

30

31

32

33

35

36

37

38

40

41

42

44

50

A TRAVEL INFO CALL 511 (D12-5, D12-5a) sign (see Figure 2I-8) may be installed if a 511 travel information services telephone number is available to road users for obtaining traffic, public transportation, weather, construction, or road condition information.

The pictograph of the transportation agency or the travel information service or program that is providing the travel information may be incorporated within displayed in place of the 511 pictograph on the D12-5a sign either above or below the TRAVEL INFO CALL 511 legend.

Standard:

The logo of a commercial entity shall not be incorporated within the TRAVEL INFO CALL 511 signs.

If the pictograph of the transportation agency or the travel information service or program is used in place of the 511 pictograph on the D12-5a sign (see Paragraph 2), the maximum height of the pictograph shall not exceed the height of the 511 pictograph on the standard sign size specified for the roadway classification in Table 2H-1.

The TRAVEL INFO CALL 511 signs shall have a white legend and border on a blue background.

Guidance:

If the pictograph of the transportation agency or the travel information service or program is used, the pictograph's maximum height should not exceed two times the letter height used in the legend of the sign.

Section 2I.13 Roadside Assistance Sign (D12-6)

21 Option:

> A Roadside Assistance (D12-6) sign (see Figure 2I-8) may be used along a highway that is served by an authorized roadside assistance program with authorized service vehicles and personnel that provide roadside vehicle repair assistance to road users free of charge.

Section 2I.11 Section 2I.14 Carpool and Ridesharing Signing (D12-2)

26 Option:

> In areas having carpool matching services, Carpool Information (D12-2) signs (see Figure 2I-8) may be provided adjacent to highways with preferential lanes or along any other highway.

> Carpool Information signs may include an Internet domain name or telephone number of more than four characters within the legend.

Guidance:

Because this is an information sign related to road user services, the Carpool Information sign should have a white legend and border on a blue

34 **Standard:**

> If a local transit pictograph or carpool symbol is incorporated into the Carpool Information sign, the maximum vertical dimension of the logo-pictograph or symbol shall not exceed 18 inches and the maximum horizontal dimension shall not exceed 30 inches.

Section 2I.15 Signing for Truck Parking Availability (D9-16b through D9-16e)

39 Option:

> General Service signs may be used to display the number of available truck parking spaces at roadside areas such as rest areas, welcome centers, and weigh stations, and at facilities off a highway that are open to the public and provide parking for commercial vehicles 24 hours a day, seven days a week.

43 Standard:

The Truck Parking Availability General Service (D9-16b through D9-16e) sign (see Figure 2I-9) shall include a changeable message element with a white changeable legend on a black opaque 45 background that displays only the number of parking spaces currently available at each location or the 46 legend FULL. The upper section of the sign shall display the Truck Parking (D9-16) symbol sign and 47 the legend SPACES OPEN. The sign shall display the number of available truck parking spaces for no 48

more than three parking facilities. Where two lines of legend, such as the location and a distance, are 49

displayed for a parking facility, not more than two parking facilities shall be displayed on the sign.

Where the truck parking facility is located off the main highway and is accessed from the crossroad, directional assemblies with the Truck Parking (D9-16) sign shall be installed along the ramp and along crossroads where the route to the facility requires a direction change, where it is questionable as to which roadway to follow, or where additional guidance is needed. Support: Displaying the number of parking spaces available at a facility when the number is small could result in truckers choosing to drive to a facility for parking just to find that facility full by the time they arrive. Option: The word FULL in a white legend may be displayed on a changeable message elements of a Truck Parking Space Availability General Service when the number of truck parking spaces available at the associated facility reaches a predetermined lower threshold. Guidance: Truck Parking Space Availability signs should be located three to five miles in advance of the nearest parking facility. The parking facilities displayed on the sign should be no more than 60 miles from the sign location. Support: Examples of Truck Parking Availability Signs are show in Figure 2I-9. Examples of uses of Truck Parking Space Availability signs are shown in Figure 2I-10. Figure 2I-9. Examples of Truck Parking Availability Signs Figure 2I-10. Examples of Use of Truck Parking Availability Signs

 3

4

5

6 7

8

9

10

11 12

13

14

15

16 17

18

19 20

21

2223

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

Section 2J.01 Eligibility

Standard:

Specific Service signs shall be defined as guide signs that provide road users with business identification and directional information for <u>eligible</u> services and <u>for eligible</u> attractions. Eligible service categories shall be limited to gas, food, lodging, camping, <u>and</u> attractions, <u>and 24-hour pharmacies</u>.

Guidance:

The use of Specific Service signs should be limited to areas primarily rural in character <u>with</u> or to areas where adequate space for all signs to sign spacing can be properly accommodated maintained.

Option:

Where an engineering study determines a need, Specific Service signs may be used on any class of highways, i.e. freeway, expressway, or conventional.

Guidance:

Specific Service signs should not be installed at an interchange where the road user cannot conveniently reenter the freeway or expressway and continue in the same direction of travel.

Standard:

Eligible service facilities shall comply with laws concerning the provisions of public accommodations without regard to race, religion, color, age, sex, or national origin, and laws concerning the licensing and approval of service facilities.

The attraction services shall include only facilities which have the primary purpose of providing amusement, historical, cultural, or leisure activities to the public.

Distances to eligible 24-hour pharmacies shall not exceed 3 miles in any direction of an interchange on the Federal-aid system.

Guidance:

Except as provided in Paragraph 98, distances to eligible services other than pharmacies should not exceed 3 miles in any direction.

Option:

If, within the 3-mile limit, facilities for the services being considered other than pharmacies are not available or choose not to participate in the program, the limit of eligibility may be extended in 3-mile increments until one or more facilities for the services being considered chooses to participate, or until 15 miles is reached, whichever comes first.

Guidance Standard: Guidance changed to Standard

If State or local agencies elect to provide Specific Service signing, there <u>should</u> shall be a statewide policy for such signing and criteria for the availability of the various types of services.

Guidance:

The criteria for the statewide policy should consider the following:

- A. To qualify for a GAS logo-business identification sign panel, a business should have:
 - 1. Vehicle services including gasoline and/or alternative fuels, oil, and water;
 - 2. Continuous operation at least 16 hours per day, 7 days per week for freeways and expressways, and continuous operation at least 12 hours per day, 7 days per week for conventional roads;
 - 3. Modern sanitary facilities and drinking water; and
 - 4. Public telephone.
- B. To qualify for a FOOD logo-business identification sign panel, a business should have:
 - 1. Licensing or approval, where required;
 - 2. Continuous operations to serve at least two meals per day, at least 6 days per week;
 - 3. Modern sanitary facilities; and
 - 4. Public telephone.
- C. To qualify for a LODGING logo-business identification sign panel, a business should have:
 - 1. Licensing or approval, where required;
 - 2. Adequate sleeping accommodations;

- 1 3. Modern sanitary facilities; and
 - 4. Public telephone.
 - D. To qualify for a CAMPING logo-business identification sign panel, a business should have:
 - 1. Licensing or approval, where required;
 - 2. Adequate parking accommodations; and
 - 3. Modern sanitary facilities and drinking water.
 - E. To qualify for an ATTRACTION logo-business identification sign panel, a facility should have:
 - 1. Regional significance, in compliance with the provisions of Paragraph 6; and
 - 2. Adequate parking accommodations.

Standard:

2

4

5

6

7 8

9

10

11

12 13

14

15

17

18

19

21

22

23

24

25

26

27

28

29

30

31

32

33

34 35

36

37

38

40

41

47

If State or local agencies elect to provide Specific Service signing for pharmacies, both of the following criteria shall be met for a pharmacy to qualify for signing:

- A. The pharmacy shall be continuously operated 24 hours per day, 7 days per week, and shall have a State-licensed pharmacist present and on duty at all times; and
- B. The pharmacy shall be located within 3 miles of an interchange on the Federal-aid system.

16 Support:

Section 2J.12 contains additional information on criteria for the statewide policy regarding signing.

Section 2I.04 contains information regarding the Interstate Oasis program.

Section 2J.02 Application

20 Standard:

The number of Specific Service signs along an approach to an interchange or intersection, regardless of the number of service types displayed, shall be limited to a maximum of four. In the direction of traffic <u>flow</u>, successive Specific Service signs shall be for <u>24-hour pharmacy</u>, attraction, camping, lodging, food, and gas services, in that order.

Guidance:

The Specific Service signs should be located to take advantage of natural terrain, to have the least impact on the scenic environment, and to avoid visual conflict with other signs within the highway right-of-way.

Relocated from later in this section

Where a service type is displayed on two signs, the signs for that service should follow one another in succession. Relocated from later in this section

Standard:

A Specific Service sign shall display the word message GAS, FOOD, LODGING, CAMPING, or ATTRACTION, or 24-HOUR PHARMACY, an appropriate directional legend such as the word message EXIT XX, NEXT RIGHT, SECOND RIGHT, or directional arrows, and the related logo business identification sign panels. Distances to eligible facilities shall not be displayed on the Specific Service signs on the approach to an interchange.

A business that does not offer gasoline but offers alternative fuels shall not be signed using GAS Specific Service signs.

39 Option:

A business that does not offer gasoline but offers alternative fuels may be signed using General Service signs for the alternative fuel provided.

42 Support:

43 General Service signs for facilities providing alternative fuels, including Electric Vehicle Charging,

44 <u>Compressed Natural Gas, Liquefied Natural Gas, Liquefied Propane Gas, and Hydrogen fuel, are provided in Chapter 2I.</u>

46 Specific S

Specific Service signs are intended for areas primarily rural in character. When services at an interchange are abundant, this is an indication that the character of the area is no longer primarily rural and General

48 <u>Service signs would be more appropriate.</u>

49 *Guidance*:

Due to the unique and widely varying characteristics of the services that qualify as attractions, and lesser recognition of their business identification sign panels (see Paragraph 10), ATTRACTION Specific Service signs should have no more than four business identification sign panels.

Support:

The types of services that meet the definition of attraction, i.e. those providing amusement, historical, cultural, or leisure activities to the public, vary considerably. In most cases, attractions do not include well-known services or easily recognizable logos, making it more difficult and requiring more time to distinguish between types of attractions shown on an ATTRACTION sign than for other categories of Specific Service signs.

Standard:

 No more than three types of services shall be represented on any sign or sign assembly. If three types of services are displayed on one sign, then the logo-business identification sign panels shall be limited to two for each service type (for a total of six logo-business identification sign panels). If two types of services are displayed on one sign, then the logo-business identification sign panels shall be limited to either three for each service type, (for a total of six logo-business identification sign panels or four for one service type and two for the other service type (for a total of six logo-business identification sign panels applicable to a service type shall be displayed such that the road user will not associate them with another service type on the same sign.

Other configurations or arrangements of business identification sign panels shall not be allowed.

No service type shall appear on more than two signs (see Paragraph 63 of this Section).

The signs shall have a blue background, a white border, and white legends of upper-case letters, numbers numerals, and arrows.

Guidance:

Where a service type is displayed on two signs, the signs for that service should follow one another in succession. Relocated to earlier in this Section

If a service type is no longer available from an interchange or intersection the sign should be removed when the business identification sign panels are removed. If a sign is to remain, but the service type is no longer available, then the service type legend should be covered so that road users do not misinterpret the sign as a General Service sign implying that the service is available.

No sign should be installed when a service type is not currently available from an interchange or intersection.

The Specific Service signs should be located to take advantage of natural terrain, to have the least impact on the scenic environment, and to avoid visual conflict with other signs within the highway right-of-way Relocated to earlier in this Section

Option:

If there is indication that a service of this type will again be available in the near future, the sign may be covered, in accordance with Paragraph 13, rather than removed.

<u>Separate installations of General Service signs</u> (see Sections 2I.02 and 2I.03) may be used in conjunction with Specific Service signs for eligible types of services that are not represented by a Specific Service sign.

40 Support

Examples of Specific Service signs are shown in Figure 2J-1. Examples of sign locations are shown in Figure 2J-2.

Figure 2J-1. Examples of Specific Service Signs

Figure 2J-2. Examples of Specific Service Sign Locations

Section 2J.03 Logos and Logo Business Identification Sign Panels

Standard:

A <u>business identification sign panel legend logo</u> shall be either an identification <u>symbol/trademark</u> or a word <u>message of the businesses name</u>. Each logo <u>or word message</u> shall be placed on a separate <u>logo sign panel business identification sign panel</u> that shall be attached to the Specific Service sign. <u>Symbols Logos</u> or trademarks used alone for a <u>business identification sign panel logo</u> shall be reproduced in the colors and general shape consistent with customary use, and any integral legend shall

be in proportionate size. A logo that resembles an official traffic control device shall not be used.

Guidance:

The logo or trademark used on a business identification sign panel should be consistent with the onpremise business identification signs at the location of the business that are visible from the roadway.

A word message <u>logobusiness identification sign panel</u>, not using a <u>symbol logo</u> or trademark, should have a blue background with white legend and border.

Support:

Section 2J.05 contains information regarding the minimum letter heights for <u>logo sign panelbusiness</u> <u>identification sign panels</u>.

Option:

Where business identification symbols or trademarks are used alone for a logo, the border may be omitted from the logo sign panel.

A portion of a <u>logo sign panel</u> <u>business identification sign panel</u> may be used to display a supplemental message horizontally along the bottom of the <u>logo sign panel</u> <u>business identification sign panel</u>, provided that the message displays essential motorist information <u>consistent with the service category type and related to the</u> operation of the business- (see Figure 2J-3).

Figure 2J-3. Examples of Supplemental Messages on Business Identification Sign Panels Standard:

All supplemental messages shall be displayed within the logo sign panel business identification sign panel and shall have letters and numerals that comply with the minimum height requirements shown in Table 2J-1. Supplemental messages promoting the availability of products, amenities, or services that are not directly related to the service category and/or those not available to non-patrons of the primary service provided for the service category, such as car wash, automated teller machines, Internet, lottery, or pool, shall not be displayed on business identification sign panels.

Messages related to the promotion or availability of business identification sign panel space shall not be displayed on Specific Service signs.

Option:

A Supplemental message identifying an alternative fuel available may be added only to the business identification sign -panels on the GAS Specific Services sign for gasoline facilities that provide the specified alternative fuel in addition to gasoline.

Table 2J-1. Minimum Letter and Numeral Sizes for Specific Service Signs According to Sign Type

Guidance:

A logo business identification sign panel should not display more than one supplemental message.

The supplemental message should be displayed in a color to contrast effectively with the background of the business sign or separated from the other legend or logo by a divider barblack legend on a yellow background for that portion of the business identification sign.

State or local agencies that elect to allow supplemental messages on logo business identification sign panels should develop a statewide policy for such messages.

Support:

Typical supplemental messages might include DIESEL, <u>LP-GAS</u>, 24 HOURS, CLOSED <u>SUNDAY</u> and the day of the week when the facility is closed, <u>ALTERNATIVE FUELS</u> (see Section 2I.03), and RV ACCESS.

43 Option:

The RV ACCESS supplemental message may be circular.

Standard:

If the RV ACCESS supplemental message is circular, it shall be the abbreviation RV in black letters inside a yellow circle with a black border and it shall be displayed within the logo sign panel near the lower right-hand corner (see Figure 2J-4).

49 Guidance:

If the circular RV ACCESS supplemental message is used, the circle should have a diameter of 10 inchesand the letters should have a height of 6 inches.

If a State or local agency elects to display the designation of businesses as providing on-premise accommodations for recreational vehicles with the RV ACCESS supplemental message or the RV Access circular message, there should be a statewide policy for such designation and criteria for qualifying businesses. The criteria should include such site conditions as access between the public roadway and the site, on-premise geometry, and parking.

Option:

If a business designated as an Interstate Oasis (see Section 2I.04) has a business <u>logo-identification</u> sign panel on the Food and/or Gas Specific Service signs, the word OASIS may be displayed on the bottom portion of the <u>logo sign panel</u>business identification sign panel for that business.

Standard:

A <u>logo sign panel</u> <u>business identification sign panel</u> shall not display the <u>symbol</u> <u>identification logo/trademark or name of more than one business. A business identification sign panel shall not display more than one name or identification logo/trademark for the same business. Slogans, e.g. <u>marketing slogans associated with the business, shall not be displayed on business identification sign panels or the Specific Service sign itself.</u></u>

Section 2J.04 Number and Size of Signs and Logo Business Identification Sign Panels

Guidance:

Sign sizes should be determined by the amount and height of legend and the number and size of logo sign panel business identification sign panels attached to the sign. All logo sign panel business identification sign panels on a sign should be the same size.

Standard:

Each Specific Service sign or sign assembly shall be limited to no more than six logo sign panel business identification sign panels.

Option:

Where more than six businesses of a specific service type are eligible for logo sign panelbusiness identification sign panels at the same interchange, additional logo sign panelbusiness identification sign panels of that same specific service type may also be displayed in accordance with the provisions of Paragraph 4. The additional logo sign panelbusiness identification sign panels may be displayed either by placing more than one specific service type on the same sign (see Paragraph 3-711 of Section 2J.02) or by using a second Specific Service sign of that specific service type if the additional sign can be added without exceeding the limit of four Specific Service signs at an interchange or intersection approach (see Paragraph 6-3 of Section 2J.02).

Standard:

Where <u>logo sign panel</u>business identification sign panels for more than six businesses of a specific service type are displayed at the same interchange or intersection approach, the following provisions shall apply:

- A. No more than 12 logo sign panel business identification sign panels of a specific service type shall be displayed on no more than two Specific Service signs or sign assemblies;
- B. No more than six <u>logo sign panel</u>business identification <u>sign panel</u>s shall be displayed on a single Specific Service sign; and
- C. No more than four Specific Service signs shall be displayed on the approach.

Support:

Section 2J.08 contains information regarding Specific Service signs for double-exit interchanges.

Section 2J.09 contains information regarding Specific Service signs for multiple interchanges that are accessed from collector-distributor roadways rather than from the highway mainline.

Standard:

Each logo sign panel business identification sign panel attached to a Specific Service sign shall have a rectangular shape be a horizontally oriented rectangle with a width longer than the height. A logo sign panel business identification sign panel on signs for freeways and expressways shall not exceed 60 inches in width and 36 inches in height (see Table 2J-2). A logo sign panel business identification sign panel on signs for conventional roads and freeway and expressway ramps shall not exceed 30 inches in width and 18 inches in height (see Table 2J-2). The vertical and horizontal spacing between logo sign panel business identification sign panels shall not exceed 8 inches and 12 inches, respectively.

1 Support:

4

7

8

12

14

15

16

17

18

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38 39

41

42

44

45

47

48

49

- 2 Sections 2A.14, 2E.15, and 2E.16 contain information regarding borders, interline spacing, and edge spacing.
 - Table 2J-2. Maximum Business Identification Sign Panel Sizes by Roadway Classification

5 Section 2J.05 Size of Lettering

6 **Standard:**

All Specific Service signs and <u>logo sign panel</u> <u>business identification sign panel</u>s shall have letter and numeral sizes that comply with the minimum requirements of Table 2J-1.

9 Guidance.

Any legend on a <u>symbol business identification graphic</u>/trademark should be proportional to the size of the <u>symbol graphic</u>/trademark.

Section 2J.06 Signs at Interchanges

13 **Standard:**

The Specific Service signs shall be installed between the preceding interchange and at least 800 feet in advance of the Exit Direction sign at the interchange from which the services are available (see Figure 2J-2).

Specific Service signs shall not be used at freeway-to-freeway interchanges (see Section 2E.37), except where the exit ramp also provides direct access to a conventional road within that interchange.

19 Guidance:

There should be at least an 800-foot spacing between the Specific Service signs, except for Specific Service ramp signs. However, excessive spacing is not desirable.

Specific Service ramp signs should be spaced at least 100 feet <u>longitudinally from beyond</u> the Exit Gore sign, from each other, and from the ramp terminal. <u>Specific Service ramp signs should be spaced at least 200 feet longitudinally from any Destination guide signs along the ramp. Longer longitudinal spacing should be provided between Specific Service ramp signs and any warning or regulatory signs along the ramp, and any intersection traffic control devices at the ramp terminal.</u>

Section 2J.07 Single-Exit Interchanges

Standard:

At numbered single-exit interchanges, the name of the service type followed by the exit number shall be displayed on one line above the <u>logo sign panel</u>business identification sign panels. At unnumbered interchanges, the directional legend NEXT RIGHT (LEFT) shall be used <u>in place of the exit number</u>.

At single-exit interchanges where traffic is allowed to turn onto the crossroad in either direction from the ramp, Specific Service ramp signs shall be installed along the ramp or at opposite the ramp terminal for facilities that have logo sign panel business identification sign panels displayed along the main roadway if the facilities are not readily visible from the ramp terminal. Directions to the service facilities shall be indicated by arrows on the ramp signs. Logo sign panel Business identification sign panels on Specific Service ramp signs shall be duplicates of those displayed on the Specific Service signs located in advance of the interchange, but shall be reduced in size (see Paragraph 6.74 of Section 2J.04).

40 Option:

Specific Service ramp signs may display distances (see Section 2A.08) to a service facility when the facility is not visible from ramp intersection with the crossroad.

43 Guidance:

Specific Service ramp signs should include distances to the service facilities. Distances of less than ¼ mile, when displayed, should be displayed to the nearest 1/10 mile.

46 Option:

An exit number plaque (see Section 2E.31) may be used instead of the exit number on the signs located in advance of an interchange.

Section 2J.08 Double-Exit Interchanges

Guidance:

At double-exit interchanges, the Specific Service signs should consist of two sections, one for each exit (see Figure 2J-1).

Standard:

At a double-exit interchange, the top section shall display the logo-sign-panelbusiness identification sign panels for the first exit and the bottom section shall display the logo-sign-panelbusiness identification sign panels for the second exit. At numbered interchanges, the name of the service type and the exit number shall be displayed above the logo-sign-panelbusiness identification sign panels in each section. At unnumbered interchanges, the word message NEXT RIGHT (LEFT) and SECOND RIGHT (LEFT) shall be used in place of the exit number. The number of logo-sign-panelbusiness identification sign-panels on the sign (total of both sections) or the sign assembly shall be limited to six.

Guidance:

At a double-exit interchange, where a service type is displayed on two Specific Service signs in accordance with the provisions of Section 2J.04, one of the signs should display the logo sign panelbusiness identification sign panels for that service type for the businesses that are accessible from one of the two exits and the other sign should display the logo sign panelbusiness identification sign panels for that service type for the businesses that are accessible from the other exit.

Option:

At a double-exit interchange where there are four logo sign panel business identification sign panels to be displayed for one of the exits and one or two logo sign panel business identification sign panels to be displayed for the other exit, the logo sign panel business identification sign panels may be arranged in three rows with two logo sign panel business identification sign panels per row.

At a double-exit interchange, where a service is to be signed for only one exit, one section of the Specific Service sign may be omitted, or a single exit interchange sign may be used. Signs on ramps and crossroads as described in Section 2J.07 may be used at a double-exit interchange.

Section 2J.09 Collector-Distributor Roadways for Successive Interchanges

Support:

Examples of guide signs for a collector-distributor roadway that provides access to multiple interchanges are shown in Figure 2J-4.

Guidance:

Where mainline access to successive interchanges is provided from a single collector-distributor roadway (see Section 2E.36), Specific Service signs, if used, should be limited to locations along the collector-distributor roadway in advance of each interchange in compliance with the provisions of Sections 2J.07 and 2J.08.

If services are available from more than one of the interchanges along the collector-distributor roadway and those services are signed with Specific Service signs as described in Paragraph, then General Service signs should be used on the mainline in conformance with the provisions of Chapter 2I.

Standard:

If Specific Service signs are located on the highway mainline for an interchange that is accessed from a collector-distributor roadway, then additional Specific Service signs shall not be allowed along the collector-distributor roadway. No more than four Specific Service signs shall be displayed on a highway mainline approach to a collector-distributor roadway, regardless of the number of interchanges that are accessed from the collector-distributor roadway.

Figure 2J-4. Example of Signing Services from Collector-Distributor Road Signs

Section 2J.092J.10 Specific Service Trailblazer Signs

Support:

Specific Service trailblazer signs (see Figure 2J-5) are guide signs with one to four logo sign panelbusiness identification sign panels that display business identification and directional information for services and for eligible attractions. Specific Service trailblazer signs are installed along crossroads for facilities that have logo sign panelbusiness identification sign panels displayed along the main roadway and ramp, and that require additional vehicle maneuvers.

1 2

Standard:

Specific Service trailblazer signs shall be installed along crossroads where the route to the business requires a direction change, where it is questionable as to which roadway to follow, or where additional guidance is needed. Where it is not feasible or practical to install Specific Service trailblazer signs to such businesses, those businesses shall not be considered eligible for signing from the ramp and main roadway. A Specific Service trailblazer sign shall not be required at the point where the business is visible from the roadway and its access is readily apparent.

Guidance:

If used, a Specific Service trailblazer sign should be located a maximum of 500 feet in advance of any required turn.

Standard:

The location of other traffic control devices shall take precedence over the location of a Specific Service trailblazer sign.

When used, each Specific Service trailblazer sign or sign assembly shall be limited to no more than four logo sign panel business identification sign panels. The logo sign panel business identification sign panels on Specific Service trailblazer signs shall be duplicates of those displayed on the Specific Service ramp signs.

Appropriate legends, such as directional arrows or the <u>word action</u> message NEXT RIGHT or SECOND RIGHT, shall be displayed with the <u>logo sign panel</u>business identification sign panel to provide proper guidance. The directional legend and border shall be white and shall be displayed on a blue background.

23 Option:

Specific Service trailblazer signs may contain various types of services on a single sign or on a sign assembly.

Specific Service trailblazer signs may be placed farther from the edge of the road than other traffic control signs.

Section **2J.10**2J.11 Signs at Intersections

Standard:

Where both tourist-oriented information (see Chapter 2K) and specific service information would be needed at the same intersection, the design of the tourist-oriented directional signs shall be used, and the needed specific service information shall be incorporated.

Guidance:

If both tourist-oriented information (See Chapter 2K) and specific service information are proposed to be used at the same intersection, the tourist-oriented directional and Specific Service signs should be spaced sufficiently apart from one another, as well as apart from other guide, warning an regulatory signs, to avoid confusion and allow sufficient time for road users to read and react to the information.

Standard:

If sufficient space to provide appropriate reading and reaction to all proposed signs is not available, priority shall be given the higher priority guide, warning and regulatory signs and either the tourist-oriented directional signs or the Specific Service signs, or both, shall not be used.

Guidance:

If Specific Service signs are used on conventional roads <u>based on an engineering study (see Paragraph 3 of Section 2J.01)</u> or at intersections on expressways, they should be installed between the previous interchange or intersection and at least 300 feet in advance of the intersection from which the services are available.

The spacing between signs should be determined on the basis of an engineering study.

<u>Logo sign panelBusiness identification sign panels</u> should not be displayed for a type of service for which a qualified facility is readily visible.

Standard:

If Specific Service signs are used on conventional roads or at intersections on expressways, the name of each type of service shall be displayed above its logo sign panelbusiness identification sign panel(s), together with an appropriate legend, such as NEXT RIGHT (LEFT) or a directional arrow, either displayed on the same line as the name of the type of service or displayed below the logo sign panelbusiness identification sign panel(s).

Option:

1

2

3

4 5

6

7

8

9

10

11 12

13

14

15

16

17 18

19

20

21

22

23

24

25

Signs similar to Specific Service ramp signs as described in Section 2J.07 may be provided on the crossroad.

Section **2J.112J.12** Signing Policy

Guidance Standard: Guidance changed to Standard

<u>In addition to a statewide policy for eligibility of service providers (see Section 2J.01), Each each highway agency that elects to use Specific Service signs should shall establish a signing policy.</u>

Guidance:

<u>The</u> signing policy that should includes, as at a minimum, the guidelines of Section 2J.01 and at least the following criteria:

- A. Selection of eligible businesses;
- B. Distances to eligible services;
- C. The use of logo sign panelbusiness identification sign panels, legends, and signs conforming complying with the provisions of this Manual and State design requirements;
- D. Removal or covering of <u>logo sign panel</u> <u>business identification sign panel</u>s during off seasons for businesses that operate on a seasonal basis;
- E. The circumstances, if any, under which Specific Service signs are permitted to be used in non-rural areas: and
- F. Determination of the costs to businesses for initial permits, installations, annual maintenance, and removal of logo sign panel business identification sign panels.

2 Section 2K.01 Purpose and Application

Support

Tourist-oriented directional signs are <u>post-mounted</u> guide sign<u>s</u> <u>assemblies</u> with one or more sign<u>s</u> <u>panels</u> that display the business identification of and directional information for eligible business, service, and activity facilities.

Standard:

A facility shall be eligible for tourist-oriented directional signs only if it derives its major portion of income or visitors during the normal business season from road users not residing in the area of the facility.

Option:

Tourist-oriented directional signs may include businesses involved with seasonal agricultural products.

Standard:

When used, The use of tourist-oriented directional signs shall be used only on limited to rural highways (see definition in Section 1C.02) conventional roads, and Tourist-oriented directional signs shall not be used installed on conventional roads in urban or urbanized areas or at interchanges on freeways or expressways main roadways or ramps.

Where both tourist-oriented directional signs and Specific Service signs (see Chapter 2J) would be needed at the same intersection, the tourist-oriented directional signs shall incorporate the needed information from, and be used in place of, the Specific Service signs.

21 Option:

Tourist-oriented directional signs may be used in conjunction with General Service signs (see Section 2I.02).

24 Support:

Section 2K.07 contains information on the adoption of a State policy for States that elect to use tourist-oriented directional signs.

Section 2K.02 <u>Design</u>

Standard:

Tourist-oriented directional signs <u>assemblies</u> shall have one or more signs <u>panels</u> (see <u>Figure 2K-1</u>) for the purpose of displaying the business identification of and directional information for eligible facilities. Each sign <u>panel</u>-shall be rectangular in shape and shall have a white legend and border on a blue background.

The content of the legend on each sign panel shall be limited to the identification and directional information for no more than one eligible business, service, or activity facility. The legends shall not include promotional advertising.

Guidance:

Each sign panel should have a maximum of two lines of legend including no more than one symbol (see Paragraph 4 of this Section), a separate directional arrow, and the distance to the facility displayed beneath the arrow. Arrows pointing to the left or up should be at the extreme left of the sign panel. Arrows pointing to the right should be at the extreme right of the sign panel. Symbols, when used, should be to the left of the word legend or logo business identification sign panel (see Paragraph 79 of this Section).

Option:

The General Service sign symbols (see Section 2I.02) and the symbols for recreational and cultural interest area signs (see Chapter 2M)- may be used on tourist-oriented directional signs.

Based on engineering judgment, the hours of operation may be displayed on the sign-panels. Relocated from later in this Section

Logo sign panel Business identification sign panels (see Section 2J.03) for specific businesses, services, and activities may also be used in place of word legends on tourist-oriented direction signs. Based on engineering judgment the hours of operation may be displayed on the sign panels. Relocated earlier in this Section

Standard:

When used, recreational and cultural interest area symbols shall be white on a brown background.

When used, symbols and logo sign panels shall be an appropriate size (see Section 2K.04). Business identification sign panels shall not exceed 24 inches in width and 15 inches in height. Logos resembling official traffic control devices shall not be permitted.

Option:

The tourist-oriented directional sign may display the word message TOURIST ACTIVITIES <u>may be displayed</u> at the top of the tourist-oriented directional sign <u>assembly</u>.

Standard:

The TOURIST ACTIVITIES word message shall have a white legend in all upper-case letters and a white border on a blue background. If used, it shall be placed above and in addition to the directional signs panels.

Support:

Examples of tourist-oriented directional signs are shown in Figures 2K-1 and 2K-2.

Figure 2K-1. Examples of Tourist-Oriented Directional Signs

Figure 2K-2. Examples of Intersection Approach Signs and Advance Signs for Tourist-Oriented Directional Signs

Section 2K.03 Style and Size of Lettering

19 Guidance:

All letters and numbers on tourist-oriented directional signs, except on the <u>logo sign panel</u> <u>business</u> <u>identification sign panel</u>s, should be upper-case and at least 6 inches in height. Any legend on a <u>logo business</u> <u>identification sign panel</u> should be proportional to the size of the <u>logo business identification sign panel</u>.

23 Standard:

Design standards for letters, numerals, and spacing shall be as provided in the "Standard Highway Signs-and Markings" book publication (see Section 1A.11).

Section 2K.04 Arrangement and Size of Signs

Standard:

The <u>size-total height of athe</u> tourist-oriented directional signs in a <u>sign assembly</u> shall be limited to a maximum <u>height</u>of 6 feet. Additional height shall be allowed to accommodate the addition of the optional TOURIST ACTIVITIES message provided in Section 2K.02 and the action messages provided in Section 2K.05.

Guidance:

The number of intersection approach signs assemblies (one sign assembly for tourist-oriented destinations to the left, one for destinations to the right, and one for destinations straight ahead) installed in advance of an intersection should not exceed three. The number of signs panels installed on in each sign assembly should not exceed four three. The signs panels for right-turn, left-turn, and straight-through destinations should be on separate signs assemblies. The left-turn destination sign assembly should be located farthest from the intersection, then the right-turn destination sign assembly, with the straight-through destination sign assembly located closest to the intersection (see Figure 2K-2). Signs for facilities in the straight-through direction should be considered only when there are signs for destinations in either the left or right direction.

If it has been determined to be appropriate to combine the left-turn and right-turn destination signs panels on a single sign assembly, the left-turn destination signs panels should be above the right-turn destination signs panels (see Figure 2K-1). When there are multiple destinations in the same direction, they should be in order based on their distance from the intersection. Except as provided in Paragraph 5, a straight-through sign panel should not be combined with in a sign assembly displaying left- and/or right-turn destinations.

The sign<u>s</u> panels should not exceed the size necessary to accommodate two lines of legend without crowding. Symbols and logo sign panels on a directional sign panel should not exceed the height of two lines of a word legend. All directional sign<u>s</u> panels and other parts of the sign <u>assembly</u> should be the same width, which should not exceed 6 feet.

Option:

At intersection approaches where three or fewer facilities are displayed, the left-turn, right-turn, and straight-through destination sign panels may be combined on the same sign.

Section 2K.05 Advance Signs

Guidance:

3

4

5

6

7

8

9

10

11 12

13

14

15 16

17 18

19

20

21

22

23

24

25

26

27 28

29

30

31

32

33

34

35

36

38

39

40

42

43

44

45

46

48

49

50

Advance signs should be limited to those situations where sight distance, intersection vehicle maneuvers, or other vehicle operating characteristics require advance notification of the destinations and their directions.

The design of the advance sign should be identical to the design of the intersection approach sign. However, the directional arrows and distances to the destinations should be omitted and the action messages NEXT RIGHT, NEXT LEFT, or AHEAD should be placed on the sign above the business identification signspanels. The action messages should have the same letter height as the other word messages on the directional signspanels (see Figures 2K-1 and 2K-2).

Standard:

The action message signs panels shall have a white legend in all upper-case letters and a white border on a blue background.

Option:

The legend RIGHT 1/2 MILE or LEFT 1/2 MILE may be used on advance signs assemblies when there are intervening minor roads.

The height required to add the directional word messages recommended for the advance sign <u>assembly</u> may be added to the maximum sign height of 6 feet.

Guidance:

The optional TOURIST ACTIVITIES message, when used on an advance sign <u>assembly</u>, and the action message should be combined on a single sign panel with TOURIST ACTIVITIES as the top line and the action message as the bottom line (see Figure 2K-2).

Section 2K.06 Sign Locations

Guidance:

If used, the intersection approach signs should be located at least 200 feet in advance of the intersection. Sign<u>s assemblies</u> should be spaced at least 200 feet apart and at least 200 feet from other traffic control devices.

If used, advance signs should be located approximately 1/2 mile from the intersection with 500 feet between these signs assemblies. In the direction of travel, the order of advance sign placement should be to show the destinations to the left first, then destinations to the right, and last, the destinations straight ahead.

Position, height, and lateral offset of signs assemblies should be governed by Chapter 2A except as permitted in this Section.

Option:

Tourist-oriented directional signs may be placed farther from the edge of the road than other traffic control signs.

37 Standard:

The location of other traffic control devices shall take precedence over the location of touristoriented directional signs.

Section 2K.07 State Policy

41 Standard:

To be eligible for tourist-oriented directional signing, facilities shall comply with applicable State and Federal laws concerning the provisions of public accommodations without regard to race, religion, color, age, sex, or national origin, and with laws concerning the licensing and approval of service facilities. Each State that elects to use tourist-oriented directional signs shall adopt a policy that complies with these provisions.

47 Guidance:

The State policy should include:

- A. A definition of tourist-oriented business, service, and activity facilities.
- B. Eligibility criteria for signs for facilities.

- C. Provision for incorporating Specific Service signs into the tourist-oriented directional signs as 2 required by Paragraph 5 of Section 2K.01. 3
 - D. Provision for covering signs during off seasons for facilities operated on a seasonal basis.
 - E. Provisions for signs to facilities that are not located on the crossroad when such facilities are eligible for signs.
 - F. A definition of the immediate area in compliance with the provisions of Paragraph 2 of Section 2K.01.
 - G. Maximum distances to eligible facilities. The maximum distance should be 5 miles.
 - H. Provision for information centers (plazas) when the number of eligible sign applicants exceeds the maximum permissible number of sign panel installations.
 - I. Provision for limiting the number of signs when there are more applicants than the maximum number of signs permitted.
 - J. Criteria for use at intersections on expressways.

4

5

6

7

8

9

10

11

12

13

14

15

- K. Provisions for controlling or excluding those businesses which have illegal signs as defined by the Highway Beautification Act of 1965 (23 U.S.C. 131).
- L. Provisions for States to charge fees to cover the cost of signs through a permit system.
- 16 M. A definition of the conditions under which the time of operation is displayed.
- 17 N. Provisions for determining if advance signs will be permitted, and the circumstances under which 18 they will be installed.

Section 2L.01 Description of Changeable Message Signs

Support

A changeable message sign (CMS) is a traffic control device that is capable of displaying one or more alternative messages. Some changeable message signs have a blank mode when no message is displayed, while others display multiple messages with only one of the messages displayed at a time (such as OPEN/CLOSED signs at weigh stations).

The provisions in this Chapter apply to both permanent and portable changeable message signs with electronic displays or the electronic display portion of an otherwise conventional static sign. Additional provisions that only apply to portable changeable message signs can be found in Section 6F.606L.05. The provisions in this Chapter generally do not apply to changeable message signs with non-electronic displays that are changed either manually or electromechanically, such as a hinged-panel, rotating-drum, or back-lit curtain or scroll CMS.

The CMS is a traffic control device at all times regardless of the type of message being displayed. Accordingly, the limitations on design, format and manner of displayed of a message conveyed on a traffic control device apply to changeable message signs regardless of the type of message being displayed at any given time. Some of the general provisions regarding traffic control devices are reiterated in this Chapter. However, this Chapter is not an independent or stand-alone reference for changeable message signs. Users of Chapter 2L are expected to consult the other chapters in this Manual for criteria on how to develop effective messages that comply with this Manual and meet the expectancy and limitations of the road user. In this regard, the engineering processes applied to decisions about whether to use a particular sign, for example, are no different for the decisions about the type and content of the message under consideration for display on a changeable message sign. The other limited use messages allowed on CMS as provided for in this chapter likewise fall under the same MUTCD provisions as the primary use traffic operation regulatory, warning and guidance messages except as stated otherwise in this chapter.

Standard:

Except as provided in Paragraph 2 of Section 2L.02, changeable message signs shall display only traffic operational, regulatory, warning, and guidance information. Advertising messages shall not be displayed on changeable message signs or its supports or other equipment. Relocated to 2L.02

The design of legends for non-electronic display changeable message signs shall comply with the provisions of Chapters 2A through 2K, 2M, and 2N of this Manual. All-oOther changeable message signs shall comply with the design and application principles established in this Chapter, and in Chapter 2A, and provisions elsewhere in this Manual for specific signs.

No items other than inventory or maintenance-related information (see Section 2A.05) shall be displayed on the front or back of a CMS or portable CMS. Names or logos of the manufacturer, brand, or model shall not be displayed on a CMS or portable CMS, either in the message display itself or on the exterior housing.

Guidance:

Blank-out signs that display only single-phase, predetermined electronic-display legends that are limited by their composition and arrangement of pixels or other illuminated forms in a fixed arrangement (such as a blank-out sign indicating a part-time turn prohibition, a blank-out or changeable lane-use sign, or a changeable OPEN/CLOSED sign for a weigh station) should comply with the provisions of the applicable Section for the specific type of sign, provided that the letter forms, symbols, and other legend elements are duplicates of the static messages as detailed in the "Standard Highway Signs-and-Markings" book-publication (see Section 1A.11). Because such a sign is effectively an illuminated version of a static sign, the size of its legend elements, the overall size of the sign, and placement of the sign should comply with the applicable provisions for the static version of the sign.

Section 2L.02 Applications of Changeable Message Signs

Standard: Relocated from 2L.01 and revised

Except as provided in Paragraph 2 of Section 2L.02, eChangeable message signs shall display only traffic operational, regulatory, warning, and guidance information except as otherwise provided for in this chapter. Advertising or other messages shall not related to traffic control shall not be displayed on changeable message signs or its supports or other equipment. Relocated from 2L.01 and revised

Option:

1

2 3

7 8

9

10

11

12 13

14

15

16

17 18

19

20

21

22

23

24

25

26

27

28

29

30 31

32

33

34

35

36 37

38

39

40

41 42

43 44

45

46

47

48

49

50

51

52 53

Changeable message signs may be used by State and local agencies to display traffic safety campaign 4 messages (as a supporting element of a broader safety campaign), transportation-related messages, emergency 5 homeland security messages, and America's Missing: Broadcast Emergency Response (AMBER) alert messages, all as provided for in this Chapter. Relocated and revised from later in this section. 6

CMS should not be used in place of static guide signs for conditions that do not change, except for blankout type signs used to display regulatory, warning, and guidance information that routinely reoccurs but only on a part-time basis. Similarly, when only certain elements of a message on a non-changeable sign is subject to change, only those elements of the sign should be in an electronic display, for example the prices shown on the R3-48 and R3-48a signs (see Figure 2G-17).

Support:

The purpose of Changeable message signs is to provide real-time traffic regulatory, warning or guidance messages as followshave a large number of applications including, but not limited to, the following:

- A. Incident management and route diversion
- B. Warning of adverse weather roadway conditions due to weather
- C. Special event applications associated with traffic control or conditions
- D. Control at crossing situations
 - ED.Lane, ramp, and roadway control
 - **FE**. Priced or other types of managed lanes
- **GF**. Travel times
 - Warning situations HG.
- **IH.** Traffic regulations
- JI. Speed control
- **KJ**. Destination guidance

CMS provide significant flexibility and capability in communicating many types of real-time traffic control messages to road users. While their intended purpose is the display of traffic regulatory, warning, or guidance information, other limited uses are also allowed under certain conditions, as provided in this Chapter. Their integrity as an official traffic control device rests significantly on their judicious use and proper messaging format and content, regardless of the message type being displayed.

Option:

Changeable message signs may be used by State and local highway agencies to display safety messages, transportation related messages, emergency homeland security messages, and America's Missing: Broadcast-Emergency Response (AMBER) alert messages. Relocated to earlier in this section

Standard Guidance:

State and local highway agencies that have permanently installed or positioned CMS shallould issuedevelop and establish and maintain a policy regarding the use and the display of all the types of messages to be used on their CMS provided in Paragraph 2. The policy shall define the types of messages that will be allowed, the priority of messages, the proper syntax of messages, the timing of messages, and other important messaging elements to ensure messages displayed meet the basic principles that govern the design and use of traffic control devices in general (see Section 1D.01) and traffic signs in particular as provided for in this Manual. Changed from Guidance to Standard and revised

Guidance:

State and local agencies that use CMS but do not have permanently installed or positioned signs should develop and establish a policy as discussed in the preceding paragraph.

When changeable message signs are used at multiple locations to address a specific situation, the message displays should be consistent along the roadway corridor and adjacent corridors, which might necessitate coordination among different operating agencies.

AMBER alerts, when displayed, should not pre-empt messages related to traffic or travel conditions. AMBER alert messages should be kept as brief as possible and display only that information which will direct road users to another source, such as broadcast or highway advisory radio, for detailed information about the 1 <u>alert. Other information, such as detailed descriptions of persons, vehicles, or license plate numbers, should</u>
2 <u>not be displayed in an AMBER alert message on a CMS.</u>

Standard:

Other types of "alert" messages that are unrelated to traffic or travel conditions shall not be displayed on CMS.

Support:

Examples of <u>traffic</u> safety <u>campaign</u> messages include "<u>FASTEN</u> SEAT BELT<u>S BUCKLED?" FINE + POINTS"</u> and "<u>DON'T DRINK AND DRIVEIMPAIRED DRIVERS LOSE LICENSE + JAIL</u>." Examples of transportation-related messages include "STADIUM EVENT SUNDAY, <u>EXPECT</u> DELAYS NOON TO 4 PM" and "OZONE ALERT <u>CODE RED</u>—USE TRANSIT."

Guidance:

When a CMS is used to display a <u>traffic</u> safety <u>campaign</u> or <u>transportation-transportation-related</u> message, the message should be simple, brief, legible, and clear <u>(see Section 1D.01)</u>. A CMS should not be used to display a <u>traffic</u> safety <u>campaign</u> or transportation-related message if doing so <u>would-could</u> adversely affect respect for the sign. "CONGESTION AHEAD" or other overly simplistic or vague messages should not be displayed alone. These messages should be supplemented with a message on the location or distance to the congestion or incident, delay and travel time, alternative route, or other similar messages.

When displayed, traffic safety campaign and transportation-related messages should be simple and direct (see Section 1D.01). Traffic safety campaign messages should emphasize the applicable regulation or warning and reference any penalties associated with violations of the regulation. Messages with obscure or secondary meanings, such as those with popular culture references, unconventional sign legend syntax, or that are intended to be humorous, should not be used as they may be misunderstood or understood only by a limited segment of road users and require greater time to process and understand. Similarly, slogan-type messages and the display of statistical information should not be used.

<u>Traffic safety campaign and transportation-related messages should be relevant to the road user on the roadway on which the message is displayed. For example, messages regarding school bus-stop safety should not be displayed on freeways where school bus stops are not found.</u>

Standard:

When a CMS is used to display a safety, transportation-related, emergency homeland security, or AMBER alert message, the display The format of CMS displays shall not be of a type that could be considered similar to advertising or promotional displays.

<u>Traffic safety campaign messages shall not be displayed on CMS unless they are part of an active, coordinated safety campaign that uses other media forms as the primary means of outreach.</u>

34 Guidance:

Traffic safety campaigns using CMS should include coordinated enforcement efforts where penalties or enforcement type warnings are part of the message displayed on the CMS.

Support:

In times of a declared state of emergency, it might be appropriate to display messages related to evacuation, homeland security or emergency information. Traffic patterns, movement or other situations might be atypical due to the emergency, necessitating unique messaging not specifically related to traffic conditions.

Standard:

Homeland security and emergency messages shall only be displayed in declared states of emergency when there is an imminent threat to the general population. Generic security or personal safety messages shall not be displayed when there is no context of a declared state of emergency or known imminent national security threat. Homeland security and emergency messages shall not be promotional or advisory in nature, including the message design, layout or manner of display.

48 <u>Guidance:</u>

Homeland Security and emergency messages should undergo significant levels of scrutiny prior to being approved for broadcast to ensure accuracy and consistency with emergency conditions. These messages should be designed to convey a clear and simple meaning in a similar format to traffic control messages.

52 Support:

Section 2B.1322 contains information regarding the design of changeable message signs that are used to display variable speed limits that change based on ambient or operational conditions, or that display the speed at which approaching drivers are traveling on the variable Speed Limit (R2-1) sign.

Section 2C.13 contains information regarding the design of changeable message signs that are used to display the speed at which approaching drivers are traveling on the Driver Speed Feedback (W13-20, W13-20aP) sign and plaque.

Section 2H.03 contains information regarding the design of changeable message signs that are used to display variable speeds for traffic signal progression on the Traffic Signal Speed (I1-1) sign.

Section 2L.03 Legibility and Visibility of Changeable Message Signs

Support:

 The maximum distance at which a driver can first correctly identify letters and words on a sign is called the legibility distance of the sign. Legibility distance is affected by the characteristics of the sign design and the visual capabilities of drivers. Visual capabilities, and thus legibility distances, vary among drivers.

For the more common types of changeable message signs, the longest measured legibility distances on sunny days occur during mid-day when the sun is overhead. Legibility distances are much shorter when the sun is behind the sign face, when the sun is on the horizon and shining on the sign face, or at night.

Visibility is the characteristic that enables a CMS to be seen. Visibility is associated with the point where the CMS is first detected, whereas legibility is the point where the message on the CMS can be read. Environmental conditions such as rain, fog, and snow impact the visibility of changeable message signs and can reduce the available legibility distances. During these conditions, there might not be enough viewing time for drivers to read the message.

Guidance:

Changeable message signs used on roadways with speed limits of 55 mph or higher should be visible from 1/2 mile under both day and night conditions. The message should be designed to be legible from a minimum distance of 600 feet for nighttime conditions and 800 feet for normal daylight conditions. When environmental conditions that reduce visibility and legibility are present, or when the legibility distances stated in the previous sentences in this paragraph cannot be practically achieved, messages composed of fewer units of information should be used and consideration should be given to limiting the message to a single phase (see Section 2L.05 for information regarding the lengths of messages displayed on changeable message signs).

The electronic display of standardized regulatory and warning signs used individually or as part of the legend for a larger sign should meet the size and legend requirements for those specific signs in Chapters 2B and 2C of this Manual.

Section 2L.04 Design Characteristics of Changeable Messages Signs

Standard:

Except as provided in Paragraph 2, Changeable messages signs shall not include advertising, animation, flashing, rapid flashing, dissolving, exploding, scrolling, or other dynamic display elements.

Support:

Section 6F.61 contains information regarding the use of arrow boards that use flashing or sequential displays for lane closures.

When a portable CMS is used as an arrow board that uses a flashing or sequential display for a lane or shoulder closure, the display and operation shall be considered that of an arrow board and shall comply with the provisions of Section 6F.61.

Guidance:

In developing messages for display on changeable message signs, the provisions of Section 1D.01 should be consulted for the principles of an effective traffic control device.

Standard:

All message displays on CMS, whether for traffic operational regulatory, warning or guidance information, or for the other allowable message types as defined in this section, shall follow the same design and display principles found in the MUTCD used for other traffic control signs, except as

51 provided elsewhere in this chapter.

Guidance:

Except in the case of a limited-legend CMS (such as a blank-out or electronic display changeable messagea part-time regulatory sign display) that is used in place of a static regulatory sign or an activated blank-out warning sign that supplements a static warning sign at a separate location, thechangeable message signs should be used as a supplement to and not as a substitute for conventional signs and markings unless otherwise provided for in this Manual.

Support:

When CMS are overused for messages not directly associated with real-time driving conditions, road users may pay less attention the sign thereby limiting its effectiveness as a traffic control device. Instead of limiting the use of such messages, some agencies have gone to other means in an attempt to draw attention back to the signs when the signs are displaying real-time driving conditions.

Guidance:

Warning beacons should not be installed on CMS for the purpose of drawing attention to certain types of messages over others. Instead, CMS should be used predominately to display messages that are critical to real-time travel conditions.

CMS <u>word messages</u> should be limited to no more than three lines, with no more than 20 characters per line.

The spacing between characters in a word should be between 25 to and 40 percent of the letter height. The spacing between words in a message should be between 75 and 100 percent of the letter height. Spacing between the message lines should be between 50 and 75 percent of the letter height. See Table 2L-1 for spacing between characters, words, and lines of text.

Except as provided in Paragraph 18 of this Section, and in Paragraph 5 of Section 2L.01, word messages on changeable message signs should be composed of all upper-case letters. The minimum letter height should be 18 inches for changeable message signs on roadways with speed limits of 45 mph or higher. The minimum letter height should be 12 inches for changeable message signs on roadways with speed limits of less than 45 mph. When a message is composed of two phases and higher informational load (see Section 2L.05), the letter height should be 18 inches, regardless of the speed limit, to optimize legibility distance and available viewing time.

Table 2L-1. Spacing Between Characters, Words and Lines of Text

29 Support:

Using letter heights of more than 18 inches will not result in proportional increases in legibility distance.

Guidance:

The width-to-height ratio of the sign characters should be between 0.7 and 1.0. The stroke width-to-height ratio should be 0.2.

Support:

The width-to-height ratio is commonly accomplished using a minimum font matrix density of five pixels wide by seven pixels high.

Standard:

Changeable message signs shall automatically adjust their brightness under varying light conditions to maintain legibility.

Guidance:

The luminance of -changeable message signs should meet industry criteria for daytime and nighttime conditions. Luminance contrast should be between 8 and 12 for all conditions.

Contrast orientation of changeable message signs should always be positive, that is, with luminous characters on a dark or less luminous background.

Support:

Legibility distances for negative-contrast changeable message signs are likely to be at least 25 percent shorter than those of positive-contrast messages. In addition, the increased light emitted by negative-contrast changeable message signs has not been shown to improve detection distances and might visually overwhelm the darker characters of the sign legend.

Standard:

The colors used for the legends and backgrounds on changeable message signs shall be as provided in Table 2A-2.

Guidance: Changed from Guidance to Standard and revised

If a black background is used, the color used for the legend on a changeable message sign should shall match the background color that would be used on a standard sign for that type of legend as specified in Table 2A-2 such as white for regulatory, yellow for warning, orange for temporary traffic control, red for stop or yield, fluorescent pink for incident management, and fluorescent yellow green for bicycle, pedestrian, and school warning.

Standard:

If a green background is used for a guide message on a CMS or if a blue background is used for a motorist services message on a CMS, the background color shall be provided by green or blue lighted pixels such that the entire CMS would be lighted, not just the white legend.

Support:

Some CMS that employ newer technologies have the capability to display an a near exact duplicate of a standard sign or other sign legend using standard symbols, the Standard Alphabets and letter forms, route shields, and other typical sign legend elements with no apparent loss of resolution or recognition to the road user when compared with a static version of the same sign legend. Such signs are of the full-matrix type and can typically display full-color legends. Use of such technologies for new CMS is encouraged for greater-legibility of their displays and enhanced recognition of the message as it pertains to regulatory, warning, or guidance information Figure 2L-1 shows comparative examples of the effects of varying pixel densities on legend form.

Guidance:

If used, the CMS described in the preceding paragraph should not display symbols or route shields unless they can do so in the appropriate <u>legend and background</u> color combinations. <u>Where an LED matrix is used to form the changeable legend, signs with pixel spacing greater than 20mm should display only word legends and no symbols or route shields.</u>

For a single-phase message where the Standard Alphabets and other legend elements of standard designs are used, the lettering style, size, and line spacing should comply with the applicable provisions for the type of message displayed as provided elsewhere in this Manual. For two-phase messages, larger legend heights should be used as described previously in this Section because of the need for such messages to be legible at a greater distance. Regardless of the number of phases, the CMS should comply with the legibility and visibility provisions of Section 2L.03.

Figure 2L-1. Example of Acceptable Message Layout on Full-Matrix Color and Monochrome CMS Displays

Section 2L.05 Message Length and Units of Information

Guidance:

The maximum length of a message should be dictated by the number of units of information contained in the message, in addition to the size of the CMS. A unit of information, which is a single answer to a single question that a driver can use to make a decision, should not be more than four words.

Support:

In order to illustrate the concept of units of information, Table 2L-1 shows an example message that is comprised of four units of information.

The maximum allowable number of units of information in a CMS message is based on the principles described in this Section, the current highway operating speed, the legibility characteristics of the CMS, and the lighting conditions.

Standard:

Each message shall consist of no more than two phases. A phase shall consist of no more than three lines of text. Each phase shall be understood by itself, and the meaning of the entire message shall be the same, regardless of the sequence in which it is read. Messages shall be centered within eEach line of legend shall be centered on the sign. Except for signs located on toll plaza structures or other facilities with a similar booth-lane arrangement, if more than one CMS is visible to road users, then only one sign shall display a sequential message at any given time.

Techniques of message display such as fading, rapid flashing, exploding, dissolving, or moving messages shall not be used. The text of the message shall not scroll or travel horizontally or vertically, across the face of the sign. Covered elsewhere in the MUTCD

Abbreviations displayed on CMS shall comply with the provisions of Section 1A.15. Relocated and modified from Guidance below - provisions of referenced section are Standard Guidance:

When designing and displaying messages on changeable message signs, the following principles relative to message design should be used:

- A. The minimum time that an individual phase is displayed should be based on 1 second per word or 2 seconds per unit of information, whichever produces a lesser value. The display time for a phase should never be less than 2 seconds.
- B. The maximum cycle time of a two-phase message should be 8 seconds.
- C. The duration between the display of two phases should not exceed 0.3 seconds.
- D. No more than three units of information should be displayed in on-a message phase of a message.
- E. No more than four units of information should be in a message when the traffic operating speeds are 35 mph or more.
- F. No more than five units of information should be in a message when the traffic operating speeds are less than 35 mph.
- G. Only one unit of information should appear on each line of the CMS.
- H. Compatible units of information should be displayed on the same message phase. Covered in P4 above

Support:

Table 2L-2 provides an example of the number of units of information in a message.

Table 2L-2. Examples of Units of Information

Option:

A unit of information consisting of more than one word may be displayed on more than one line. An additional changeable message sign at a downstream location may be used for the purpose of allowing the entire message to be read twice.

Guidance:

If more than two phases would be needed to display the necessary information, additional changeable message signs may should be used to display this information as a series of two distinct, independent messages with a maximum of two phases at each location, in accordance with the provisions of Paragraph 4 of this Section.

When the message on a CMS includes an abbreviation, the provisions of Section 1A.15 should be used. Relocated and changed to a Standard above

Support:

Table 2L-3 and Table 2L-4 provide examples of message construction for changeable message signs. Each example shows the message content, layout, and phasing for a potential message and an improved message. The improved message for each example has been optimized for recognition, comprehension, and effectiveness.

Table 2L-3. Examples of Message Construction on CMS

Table 2L-4. Examples of Message Construction on Portable CMS

Section 2L.06 Frequency of Display of Messages

Support:

Overuse of certain types of traffic control devices can result in a reduction of their effectives (see Section 2A.04) due to habituation, a phenomenon by which repeated exposure to a stimulus results in diminished response. With respect to signs, habituation can occur through repeated exposure to a message, especially those messages that might not be perceived has having relevance to the road user, resulting in diminished responsiveness of the road user to that sign or message. Because messages can be changed or extinguished, the effectiveness of changeable message signs is tied more to the messages displayed thereon, the frequency of displayed messages, and the relevance to the road user, rather than to the installation of the signs themselves.

Guidance:

Changeable message signs should be used judiciously to avoid habituation and preserve their effectiveness during the display of real-time messages about traffic conditions or traffic advisories.

Section 2L.07 Travel Time Messages

Support:

Travel times provide road users useful information about the level of congestion on segments of highways that motorist experience frequent incidents that slows traffic. Travel times are only helpful to the road user if they have a general understanding of the length of the road segment the travel time is related to so that they can compare that to the time it take them to travel a similar distance on a highway without congestion. However, travel time messages requires road users to read and process a significant amount of information and careful consideration is needed to ensure the overall message is not overloading the motorist. *Guidance:*

Travel times should be tied to the distance to a particular destination or junction so that road users can estimate the level of congestion based on the time to travel that distance. When travel times are displayed on changeable message signs, such as during peak traffic conditions, the message should comply with the provisions of Section. 2E.49 and 2E.50. If both a travel time and distance are displayed, the sign should display only one destination. A distance displayed as part of a travel time message should be displayed as an

integer rounded to the nearest whole mile.

16 Option:

A reference-location-based exit number (see Section 2E.22) may be displayed in lieu of a destination name or junction thereby providing the necessary distance information to the road user. If reference-location-based exit numbers are displayed, then up to two travel times may be displayed provided that the distance to the exit is not also displayed.

Section 2L.08 Traffic Safety Campaign Messages

22 Support

An allowable ancillary use of changeable message signs is the display of traffic safety messages in conjunction with a traffic safety campaign that includes other forms of media as the primary communication and education mechanism.

Guidance:

The broad traffic safety campaign marketing message should be appropriately shortened or otherwise modified to comply with the provisions of Section 2L.05 when a traffic safety campaign message is displayed on a changeable message sign.

For consistency on a national level, traffic safety campaigns should be coordinated with those on the National Highway Transportation Safety Administration's annual communications calendar.

Standard:

Traffic control messages shall have primacy over traffic safety campaign messages.

Section 2L.0609 Location Installation of Permanent Changeable Message Signs

35 Support:

Careful consideration of CMS installation location is important to having a safe and effective message, taking into account several factors. CMS message length and complexity will vary and often include two-phase displays, all of which may require longer glance times by motorists than would be required for conventional sign messages. CMS are also generally used on higher speed, multi-lane facilities with high traffic volumes where more time might be required to properly respond to a message, such as by changing lanes or reducing their speed. It is also not uncommon for other signs to be in the same vicinity of the desired location for a CMS raising the concern of overloading road users with information.

Guidance:

A CMS that is used in place of a static sign (such as a blank-out or variable legend regulatory sign) should be located in accordance with the provisions of Chapter 2A <u>and the provisions for the static sign it replaces</u>. The following factors should be considered when installing other permanent changeable message signs:

A. Changeable message signs should be located sufficiently upstream of known bottlenecks and high crash locations to enable road users to select an alternate route or take other appropriate action in response to a recurring condition.

- B. Changeable message signs should be located sufficiently upstream of major diversion decision points, such as interchanges, to provide adequate distance over which road users can change lanes to reach one destination or the other.
 - C. Changeable message signs should not be located within an interchange except for toll plazas or managed lanes.
 - D. Changeable message signs should not be positioned at locations where the information load on drivers is already high because of guide signs and other types of information.
 - E. Changeable message signs should not be located in areas where drivers frequently perform lane-changing maneuvers in response to static guide sign information, or because of merging or weaving conditions.

Support:

4

5

6

7

8

9

10

11

12

13

Information regarding the design and application of portable changeable message signs in temporary traffic control zones is contained in Section 6F.60.

CHAPTER 2M. RECREATIONAL AND CULTURAL INTEREST AREA SIGNS

2 Section 2M.01 Scope

3 Support:

1

4

5

6

7

8

9

11

12

13

1415

16

17 18

19

20

21

22

23

24

25

26

27

28

29

30 31

32

33

34

35

36 37

38

40

41

42

43 44

46

47

48

Recreational or cultural interest areas are attractions or traffic generators that are open to the general public for the purpose of play, amusement, or relaxation. Recreational attractions include such facilities as parks, campgrounds, <u>gaming game-hunting</u> facilities, and ski areas, while examples of cultural attractions include museums, art galleries, and historical buildings or sites.

The purpose of recreation and cultural interest area signs is to guide road users to a general area and then to specific facilities or activities within the area.

10 Option:

Recreational and cultural interest area guide signs directing road users to significant traffic generators may be used on freeways and expressways where there is direct access to these areas as provided in Section 2M.09.

Recreational and cultural interest area signs may be used off the road network, as appropriate.

Section 2M.02 Application of Recreational and Cultural Interest Area Signs

Support:

Provisions for signing recreational or cultural interest areas are subdivided into two different types of signs: (1) symbol signs and (2) destination guide signs.

Guidance:

When hHighway agencies decide to-providinge recreational and cultural interest area signing, these agencies should have a policy for such signing. The policy should establish a policy with signing criteria for the eligibility of the various types of services, accommodations, and facilities. These signs should not be used where they might be confused with other traffic control signs.

Option:

Recreational and cultural interest area guide signs may be used on any road to direct persons to facilities, structures, and places, and to identify various services available to the general public. These guide signs may also be used in recreational or cultural interest areas for signing non-vehicular events and amenities such as trails, structures, and facilities.

Standard:

Where a symbol for a recreational and cultural interest area application is used on a roadway outside a recreational and cultural interest area facility, and a standard symbol is prescribed elsewhere in this Manual for that message, the symbol shall be the standard design and size prescribed elsewhere in this Manual. Alternative symbol designs shall not be allowed. The legend and color of the sign shall be as prescribed for the standard symbol sign.

Support:

Symbols for use only within recreational and cultural interest area facilities are noted in Table 2M-1.

Section 2A.12 contains information regarding the use of recreational and cultural interest area symbols on other types of signs.

Section 2M.03 Regulatory and Warning Signs

39 Standard:

All regulatory and warning signs installed on public roads and streets open to public travel within recreational and cultural interest areas shall comply with the requirements of Chapters 2A, 2B, 2C, 7B, 8B, and 9B.elsewhere in this Manual.

Section 2M.04 General Design Requirements for Recreational and Cultural Interest Area Symbol Guide Signs

45 Standard:

When a General Information symbol contained in Chapter 2H is used in conjunction with recreational and cultural interest area signing on roadways outside a recreational and cultural interest

facility, the legend and background color of the General Information symbol sign shall be as prescribed

49 in Chapter 2H.

When a General Service symbol contained in Chapter 2I is used in conjunction with recreational and cultural interest area signing on roadways outside a recreational and cultural interest facility, the legend and background color of the General Information symbol sign shall be as prescribed in Chapter 2I.

Recreational and cultural interest area symbol guide signs shall be square or rectangular in shape and shall have a white symbol or message and white border on a brown background. The symbols shall be grouped into the following usage and series categories:

- A. General Applications,
- B. Accommodations,
- C. Services.
- D. Land Recreation,
- E. Water Recreation, and
- F. Winter Recreation.

Support:

1

2

3

4 5

6

7

8

9

10

11

12 13

14

15

16

17 18

19

20

22

23

24

25

27

28

29

31

32

33

35

37

38 39

41

42

43

44

45

46

47

48 49

50

Table 2M-1 contains a listing of the symbols within each series category.

Table 2M-1. Category Chart for Recreational and Cultural Interest Area Symbols

Option

Mirror images of symbols may be used where the reverse image will better convey the message <u>(see Section 2A.09)</u>.

Section 2M.05 Symbol Sign Sizes

21 Guidance:

Recreational and cultural interest area symbol signs should be 24 x 24 inches. Where greater visibility or emphasis is needed, larger sizes should be used. Symbol sign enlargements should be in 6-inch increments.

Recreational and cultural interest area symbol signs should be 30×30 inches when used on guide signs on freeways or expressways.

26 Option:

A smaller size of 18 x 18 inches may be used on low-speed, low-volume roadways and on non-road applications.

Section 2M.06 <u>Use of Educational Plaques</u>

30 Guidance:

Educational plaques should accompany all initial installations of recreational and cultural interest area symbol signs. The educational plaque should remain in place for at least 3 years after the initial installation. If used, the educational plaque should be the same width as the symbol sign.

34 Option:

Symbol signs that are readily recognizable by the public may be installed without educational plaques.

36 Support:

Figure 2M-1 illustrates some examples of the use of educational plaques.

Figure 2M-1. Examples of Use of Arrows, Educational Plaques, and Prohibitive Slashes

Section 2M.07 <u>Use of Prohibitive Circle and Diagonal Slash</u> for Non-Road Applications

40 Standard:

Where it is necessary to indicate a prohibition of an activity or an item within a recreational or cultural interest area for non-road use and a standard regulatory sign for such a prohibition is not provided in Chapter 2B, the appropriate recreational and cultural interest area symbol shall be used in combination with a red prohibitive circle and red-diagonal slash. The recreational and cultural interest area symbol and the sign border shall be black and the sign background shall be white. The symbol shall be scaled proportionally to fit completely within the circle. and the The diagonal slash shall be oriented from the upper left to the lower right portions of the circle as shown in Figure 2M-1 and as detailed in the "Standard Highway Signs" publication.

Requirements for retroreflection of the red circle and red diagonal slash shall be the same as those requirements for backgrounds, legends, symbols, arrows, and borders.

2	Standard:
3	If used, recreational and cultural interest area symbol signs shall be placed in accordance with the
4 5	general requirements contained in Chapter 2A. The symbol(s) shall be placed as sign panels in the uppermost part of the sign and the directional information shall be placed below the symbol(s).
6	Except as provided in Paragraph 3, iIf the name of the recreational or cultural interest area facility
7 8	or activity is displayed on a destination guide sign (see Section 2M.09) and a symbol is used, the symbol shall be placed below the name (see Figure 2M-2).
9	Figure 2M-2. Examples of Recreational and Cultural Interest Area Guide Signs
10	Option:
11 12 13	When the legend Wildlife Viewing Area is displayed with the RS-076 symbol on a destination guide sign, the symbol may be placed to the left or right of the legend and the arrow may be placed below the symbol (see Figure 2M-2).
14 15	The symbols displayed with the facility or activity name may be placed below the destination guide sign as illustrated in Figure 2M-2 instead of as sign panels placed with the destination guide sign.
16 17	Secondary symbols of a smaller size (18 x 18 inches) may be placed beneath the primary symbols (see Drawing A in Figure 2M-1), where needed.
18	Standard:
19 20	Recreational and cultural interest area symbols installed for non-road use shall be placed in accordance with the general sign position requirements of the authority having jurisdiction.
21	Support:
22 23 24	Figure 2M-3 illustrates typical height and lateral mounting positions. Figure 2M-4 illustrates some examples of the placement of symbol signs within a recreational or cultural interest area. Figures 2M-5 through 2M-10 illustrate some of the symbols that can be used.
25	Figure 2M-3. Arrangement, Height, and Lateral Position of Signs Located Within
26	Recreational and Cultural Interest Areas
27	Figure 2M-4. Examples of Symbol and Destination Guide Signing Layout
28 29	Figure 2M-5. Recreational and Cultural Interest Area Symbol Signs for General Applications
30	Figure 2M-6. Recreational and Cultural Interest Area Symbol Signs for Accommodations
31	
	Figure 2M-7. Recreational and Cultural Interest Area Symbol Signs for Services
32	Figure 2M-7. Recreational and Cultural Interest Area Symbol Signs for Services Figure 2M-8. Recreational and Cultural Interest Area Symbol Signs for Land Recreation
32 33	
	Figure 2M-8. Recreational and Cultural Interest Area Symbol Signs for Land Recreation
33	Figure 2M-8. Recreational and Cultural Interest Area Symbol Signs for Land Recreation Figure 2M-9. Recreational and Cultural Interest Area Symbol Signs for Water Recreation
33 34 35 36	Figure 2M-8. Recreational and Cultural Interest Area Symbol Signs for Land Recreation Figure 2M-9. Recreational and Cultural Interest Area Symbol Signs for Water Recreation Figure 2M-10. Recreational and Cultural Interest Area Symbol Signs for Winter Recreation Guidance:
33 34 35 36 37	Figure 2M-8. Recreational and Cultural Interest Area Symbol Signs for Land Recreation Figure 2M-9. Recreational and Cultural Interest Area Symbol Signs for Water Recreation Figure 2M-10. Recreational and Cultural Interest Area Symbol Signs for Winter Recreation Guidance: The number of symbols used in a single sign assembly should not exceed four.
33 34 35 36 37 38	Figure 2M-8. Recreational and Cultural Interest Area Symbol Signs for Land Recreation Figure 2M-9. Recreational and Cultural Interest Area Symbol Signs for Water Recreation Figure 2M-10. Recreational and Cultural Interest Area Symbol Signs for Winter Recreation Guidance: The number of symbols used in a single sign assembly should not exceed four. Option:
33 34 35 36 37 38 39	Figure 2M-8. Recreational and Cultural Interest Area Symbol Signs for Land Recreation Figure 2M-9. Recreational and Cultural Interest Area Symbol Signs for Water Recreation Figure 2M-10. Recreational and Cultural Interest Area Symbol Signs for Winter Recreation Guidance: The number of symbols used in a single sign assembly should not exceed four. Option: The Advance Turn (M5 series) or Directional Arrow (M6 series) auxiliary signs with white arrows on
33 34 35 36 37 38 39 40	Figure 2M-8. Recreational and Cultural Interest Area Symbol Signs for Land Recreation Figure 2M-9. Recreational and Cultural Interest Area Symbol Signs for Water Recreation Figure 2M-10. Recreational and Cultural Interest Area Symbol Signs for Winter Recreation Guidance: The number of symbols used in a single sign assembly should not exceed four. Option: The Advance Turn (M5 series) or Directional Arrow (M6 series) auxiliary signs with white arrows on brown backgrounds shown in Figure 2D-5 may be used with Recreational and Cultural Area Interest symbol
33 34 35 36 37 38 39	Figure 2M-8. Recreational and Cultural Interest Area Symbol Signs for Land Recreation Figure 2M-9. Recreational and Cultural Interest Area Symbol Signs for Water Recreation Figure 2M-10. Recreational and Cultural Interest Area Symbol Signs for Winter Recreation Guidance: The number of symbols used in a single sign assembly should not exceed four. Option: The Advance Turn (M5 series) or Directional Arrow (M6 series) auxiliary signs with white arrows on
33 34 35 36 37 38 39 40 41 42	Figure 2M-8. Recreational and Cultural Interest Area Symbol Signs for Land Recreation Figure 2M-9. Recreational and Cultural Interest Area Symbol Signs for Water Recreation Figure 2M-10. Recreational and Cultural Interest Area Symbol Signs for Winter Recreation Guidance: The number of symbols used in a single sign assembly should not exceed four. Option: The Advance Turn (M5 series) or Directional Arrow (M6 series) auxiliary signs with white arrows on brown backgrounds shown in Figure 2D-5 may be used with Recreational and Cultural Area Interest symbol guide signs to create a Recreational and Cultural Interest Area Directional Assembly. The symbols may be used singularly, or in groups of two, three, or four on a single sign assembly (see Figures 2M-1, 2M-3, and
33 34 35 36 37 38 39 40 41 42 43	Figure 2M-8. Recreational and Cultural Interest Area Symbol Signs for Land Recreation Figure 2M-9. Recreational and Cultural Interest Area Symbol Signs for Water Recreation Figure 2M-10. Recreational and Cultural Interest Area Symbol Signs for Winter Recreation Guidance: The number of symbols used in a single sign assembly should not exceed four. Option: The Advance Turn (M5 series) or Directional Arrow (M6 series) auxiliary signs with white arrows on brown backgrounds shown in Figure 2D-5 may be used with Recreational and Cultural Area Interest symbol guide signs to create a Recreational and Cultural Interest Area Directional Assembly. The symbols may be used singularly, or in groups of two, three, or four on a single sign assembly (see Figures 2M-1, 2M-3, and 2M-4).

Section 2M.08 Placement of Recreational and Cultural Interest Area Symbol Signs

should be as follows: (1) rectangular with a white legend and border on a green background; (2) rectangular with a white legend and border on a brown background; or (3) trapezoidal with a white legend and border on a brown background.

Standard:

When recreational or cultural interest area destinations are displayed on a Supplemental guide sign (see Section 2E.35), the sign shall be rectangular in shape with a white legend on a green or brown background.

Option:

<u>Trapezoidal shaped signs may be used to display recreational and cultural interest area destinations on conventional roads</u>.

Standard:

Whenever the trapezoidal shape is used, the color combination shall be a white legend and border on a brown background. When the trapezoidal shape is used for a sign with a directional arrow, a right-angled trapezoid with the wider dimension of the bases (parallel sides) at the top of the sign shall be used. The diagonal leg of the trapezoid shall be oriented in the same direction as the directional arrow. When the trapezoidal shape is used for an advance sign legend, such as with a distance or action message, an isosceles trapezoid with the wider dimension of the bases at the top of the sign shall be used. Added to increase clarity regarding sign shape

Option:

Destination guide signs with a white legend and border on a brown background may be posted at the first point where an access or crossroad intersects a highway where recreational or cultural interest areas are a significant destination along conventional roads, expressways, or freeways. Supplemental guide signs with a white legend and border on a brown background may be used along conventional roads, expressways, or freeways to direct road users to recreational or cultural interest areas. Where access or crossroads lead exclusively to the recreational or cultural interest area, the <u>aA</u>dvance guide sign (see Section 2E.33) and the <u>eExit dDirection sign (see Section 2E.36)</u> may have a white legend and border on a brown background.

Standard:

All Exit Gore (E5-1 and E5-1aseries) signs (see Section 2E.37) shall have a white legend and border on a green background. The background color of the interchange Exit Number plaque (E1-5P and E1-5bP,) plaque (see Section 2E.31) shall match the background color of the guide sign above which it is mounted. Design characteristics of conventional road, expressway, or freeway guide signs shall comply with Chapter 2D or 2E except as provided in this Section for color combination.

The \underline{aA} dvance guide sign and the Exit Direction sign shall retain the white-on-green color combination where the crossroad \underline{also} leads to a destination other than a recreational or cultural interest area.

Support:

Figure 2M-2 illustrates destination guide signs commonly used for identifying recreational or cultural interest areas or facilities.

Section 2M.10 Memorial or Dedication Signing

40 Support:

Legislative bodies will occasionally adopt an act or resolution memorializing or dedicating a highway, bridge, or other component of the highway.

Named highways (see Section 2D.53) are officially designated and shown on official maps and serve the purpose of providing route guidance, primarily on unnumbered highways, and property addresses. A highway designated as a memorial or dedication is not considered to be a named highway for the purposes of highway signing or road user navigation and orientation. Section 2D.53 contains provisions for the signing of named highways. Relocated from end of Section and revised

Section 2A.03 contains information regarding excessive use of signs. Because memorial or dedication names are not official highway names, memorial and dedication signing is not essential to providing navigational guidance.

Guidance:

Such memorial or dedication names should not appear on or along a highway, or be placed on bridges or other highway components. If a route, bridge, or highway component is officially designated as a memorial Notice of Proposed Amendments – Part 2 Page 328 of 781 December 2020

or dedication, and if notification of the memorial or dedication is to be made on the highway right-of-way, such notification should consist of installing a memorial or dedication marker in a rest area, scenic overlook, recreational area, or other appropriate location where parking is provided with the signing inconspicuously located relative to vehicle operations along the highway.

Option:

 If the installation of a memorial or dedication marker off the main roadway is not practical, memorial or dedication signs may be installed on the mainline.

Guidance:

Memorial or dedication signs should have a white legend and border on a brown background. <u>On all such signs, the design should be simple and dignified, devoid of any appearance of advertising, and in general compliance with other signing.</u>

The letter height of the principal legend on memorial or dedication signs should conform to the minimum letter height specified for Miscellaneous Information signs (see Section 2H.04). Memorial and Dedication signs should not be oversized.

The lettering for the name of the person or entity being recognized should be composed of a combination of lower-case letters with initial upper-case letters.

Relocated from later in this Section and changed to Guidance

Standard:

Where such memorial or dedication signs are installed on the https://memorial.org/high-provisions of Paragraph 3 cannot be met, (1) memorial or dedication names shall not appear on directional guide signs, (2) memorial or dedication signs shall not interfere with the placement of any other <a href="https://memorial.org/nemorial.org/high-provisions.org/high-placement-placem

Memorial or dedication signs shall be rectangular in shape. The legend displayed on memorial or dedication signs shall be limited to the name of the person or entity being recognized and a simple message preceding or following the name, such as "DEDICATED TO" or "Memorial Parkway." Additional legend, such as biographical information, shall not be displayed on memorial or dedication signs. Decorative or graphical elements, pictographs, logos, or symbols shall not be displayed on memorial or dedication signs. All letters and numerals displayed on memorial or dedication signs shall be as provided in the "Standard Highway Signs and Markings" book-publication (see Section 1A.11). The route number or officially mapped name of the highway shall not be displayed on the memorial or dedication sign.

Memorial or dedication signs shall not imply that a highway has been officially renamed.

Memorial or dedication names shall not appear on supplemental signs or on any other information sign on or along the highway or its intersecting routes.

Option:

The lettering for the name of the person or entity being recognized may be composed of a combination of lower case letters with initial upper case letters. Relocated above and changed to Guidance

Guidance:

Freeways and expressways should not be signed as memorial or dedicated highways.

When used, memorial or dedication signs should be located in accordance with the provisions for locating vanity signs (see Section 2A.03).

Support:

Paragraph 35 of Section 2D.43 contains provisions regarding the use of memorial or dedication signing in conjunction with Street Name signs.

Named highways are officially designated and shown on official maps and serve the purpose of providing route guidance, primarily on unnumbered highways. A highway designated as a memorial or dedication is not considered to be a named highway. Section 2D.53-56 contains provisions for the signing of named highways.

Relocated to above

1

4

5

6

7

8

9

10

11

12

13

14

15

16

17 18

19

20

21

22

23

25

26

27

30

32

33

34

35

36

37

38 39

40

41

42 43

44

46

47

48 49

2 Section 2N.01 Emergency Management

3 Guidance:

Contingency planning for an emergency evacuation should be considered by all State and local jurisdictions and should consider the use of all applicable roadways.

In the event of a disaster where highways that cannot be used will be closed, a successful contingency plan should account for the following elements: a controlled operation of certain designated highways, the establishment of traffic operations for the expediting of essential traffic, and the provision of emergency centers for civilian aid.

Section 2N.02 Design and Use of Emergency Management Signs

Standard:

Emergency Management signs shall be used to guide and control highway traffic during an emergency.

<u>Signs normally in place that conflict with Emergency Management signs shall be removed or covered until such time as the Emergency Management signs are no longer necessary.</u>

Except for Evacuation Route signs, Emergency Management signs that are no longer necessitated by the emergency shall be promptly removed and signs that normally provide guidance, warning or regulation that were removed or covered during the emergency shall be promptly displayed again. not permanently displace any of the standard signs that are normally applicable. Revised to improve clarity

Advance planning for transportation operations' emergencies shall be the responsibility of State and local authorities.

Support: Standard changed to Support

The Federal Government shall provides guidance to the States as necessitated by changing circumstances.

24 Standard:

Except as provided in Section 2A.11, the sizes for Emergency Management signs shall be as shown in Table 2N-1.

Support:

Section 2A.11 contains information regarding the applicability of the various columns in Table 2N-1.

29 Option:

Signs larger than those shown in Table 2N-1 may be used (see Section 2A.11).

31 Guidance:

As conditions permit, the Emergency Management signs should be replaced or augmented by standard signs.

<u>Except where specifically required elsewhere in this Chapter</u>, <u>T</u>the background of Emergency Management signs should be retroreflective.

Because Emergency Management signs might be needed in large numbers for temporary use during an emergency, consideration should be given to their fabrication from any light and economical material that can serve through the emergency period.

Option:

Any Emergency Management sign that is used to mark an area that is contaminated by biological or chemical warfare agents or radioactive fallout may be accompanied by the standard symbol that is illustrated in the upper left corner of the EM-7e4-1b and EM-7d4-1c signs in Figure 2N-1.

Table 2N-1. Emergency Management Sign Sizes

Figure 2N-1. Emergency Management Signs

45 Section 2N.03 Evacuation Route Signs (EM-1 and EM-1a EM1 Series)

Standard:

The Evacuation Route (EM-1_ and EM-1a) signs shall display a blue circular symbol on a white square sign without a border as shown in Figure 2N-1. The EM1-1 sign shall include a white directional arrow (except as provided in Paragraph 3) and a white legend EVACUATION ROUTE within the blue.

Notice of Proposed Amendments – Part 2

Page 330 of 781

December 2020

circular symbol. The EM-1a sign shall include a white EVACUATION ROUTE legend and the tsunami symbol within the blue circular symbol.

The EM-1 and EM-1a EM1 series signs and any plaques used to supplement the EM1 series signs shall be retroreflective.

An Advance Turn Arrow (M5 series) or Directional Arrow (M6 series) auxiliary sign-plaque as-shown in(see Figure 2ND-15), but with a white arrow on a blue background instead of a black arrow on a white background, shall be installed below the EM-1a1-2 series signs. Instead of including a directional arrow within the blue circular symbol on the EM-1 sign, an The Advance Turn Arrow (M5 series) or and Directional Arrow (M6 series) auxiliary sign-plaques as shown in Figure 2D-5, but with shall have a white arrow and border on a blue background instead of a black arrow on a white background, may be installed below the when used with EM2-1-2 series signs. Relocated from paragraph below and revised for clarification

Option:

Instead of including a directional arrow within the blue circular symbol on the EM-1 sign, an Advance Turn Arrow (M5 series) or Directional Arrow (M6 series) auxiliary sign as shown in Figure 2D-5, but with a white arrow on a blue background instead of a black arrow on a white background, may be installed below the EM-1 sign. Relocated to paragraph above

If desired Where different evacuation conditions use different evacuation routes in the same area, the word HURRICANE, or a word that describes some other type of evacuation route, may be added as a third line of text above the white EVACUATION ROUTE legend within the blue circular symbol on the EM1-1 sign.

An approved Emergency Management symbol with a diameter of 3.5 inches may appear near the bottom-of an Evacuation Route sign.

Standard:

The arrow designs, if used, on the EM1-1 sign shall include a straight, vertical arrow pointing upward, a straight horizontal arrow pointing to the left or right, or a bent arrow pointing to the left or right for advance warning of a turn.

Guidance Standard changed to Guidance

If used, the Evacuation Route sign, with the appropriate arrow, shall should be installed 150 to 300 feet in advance of, and at, any turn in an approved evacuation route. The sign shall should also be installed elsewhere for straight-ahead confirmation where needed.

Standard

If used in urban areas, the Evacuation Route sign shall be mounted at the right-hand side of the roadway, not less than 7 feet above the top of the curb, and at least 1 foot back from the face of the curb. If used in rural areas, the Evacuation Route sign shall be mounted at the right-hand side of the roadway, not less than 7 feet above the pavement and not less than 6 feet or more than 10 feet to the right of the right-hand roadway edge.

Evacuation Route signs shall not be placed where they will conflict with other signs. Where conflict in placement would occur between the Evacuation Route sign and a standard regulatory sign, the regulatory sign shall take precedence.

Option:

In case of conflict with guide or warning signs, the Evacuation Route sign may take precedence.

Guidance:

Placement of Evacuation Route signs should be made under the supervision of the officials having jurisdiction over the placement of other traffic signs. Coordination with Emergency Management authorities and agreement between contiguous political entities should occur to assure continuity of routes.

<u>Use of the specific Evacuation Route (EM1-2 series) signs should be limited to areas where different evacuation conditions use different evacuation routes.</u>

Section 2N.04 AREA CLOSED Sign (EM-22-1)

Standard: Guidance: Standard changed to Guidance

The AREA CLOSED (EM-22-1) sign (see Figure 2N-1) shall-should be used to close a roadway in order to prohibit traffic from entering the area. It shall should be installed on the shoulder as near as practical to

the right-hand edge of the roadway, or preferably, on a portable mounting or barricade partly or entirely in the roadway.

Guidance:

 For best visibility, particularly at night, the sign height should not exceed 4 feet measured vertically from the pavement to the bottom of the sign. Unless adequate advance warning signs are used, it should not be placed to create a complete and unavoidable blocked route. Where feasible, the sign should be located at an intersection that provides a detour route.

Section 2N.05 TRAFFIC CONTROL POINT Sign (EM-32-2)

Standard: Guidance: Standard changed to Guidance

The TRAFFIC CONTROL POINT (EM-32-2) sign (see Figure 2N-1) shall-should be used to designate a location where an official traffic control point has been set up to impose such controls as are necessary to limit congestion, expedite emergency traffic, exclude unauthorized vehicles, or protect the public.

The sign <u>shall should</u> be installed in the same manner as the AREA CLOSED sign (see Section 2N.04), and at the point where traffic must stop to be checked.

The standard STOP (R1-1) sign shall (see Section 2B.05) should be used in conjunction with the TRAFFIC CONTROL POINT sign. The TRAFFIC CONTROL POINT sign shall consist of a black legend and border on a retroreflectorized white background.

Guidance:

The TRAFFIC CONTROL POINT sign should be mounted directly below the STOP sign.

Standard:

The TRAFFIC CONTROL POINT sign shall be retroreflective.

Section 2N.06 MAINTAIN TOP SAFE SPEED Sign (EM-42-3)

Option:

The MAINTAIN TOP SAFE SPEED (EM-42-3) sign (see Figure 2N-1) may be used on highways where conditions are such that it is prudent to evacuate or traverse an area as quickly as possible.

Where an existing Speed Limit (R2-1) sign is in a suitable location, the MAINTAIN TOP SAFE SPEED sign may conveniently be mounted directly over the face of the speed limit sign that it supersedes.

28 Support:

Since any speed zoning would be impractical under such emergency conditions, no minimum speed limit can be prescribed by the MAINTAIN TOP SAFE SPEED sign in numerical terms. Where traffic is supervised by a traffic control point, official instructions will usually be given verbally, and the sign will serve as an occasional reminder of the urgent need for maintaining the proper speed.

Guidance:

The sign should be installed as needed, in the same manner as other standard speed signs.

Standard:

If used in rural areas, the MAINTAIN TOP SAFE SPEED sign shall be mounted on the right-hand side of the road at a horizontal distance of not less than 6 feet or more than 10 feet from the roadway edge, and at a minimum height, measured vertically from the bottom of the sign to the elevation of the near edge of the traveled way, of 5 feet. If used in urban areas, the minimum height, measured vertically from the bottom of the sign to the top of the curb, or in the absence of curb, measured vertically from the bottom of the sign to the elevation of the near edge of the traveled way, shall be 7 feet, and the nearest edge of the sign shall be not less than 1 foot back from the face of the curb.

Section 2N.07 ROAD (AREA) USE PERMIT REQUIRED FOR THRU TRAFFIC Sign (EM-52-4)

45 Support:

The intent of the ROAD (AREA) USE PERMIT REQUIRED FOR THRU TRAFFIC (EM-52-4) sign (see Figure 2N-1) is to notify road users of the presence of the traffic control point so that those who do not have priority permits issued by designated authorities can take another route, or turn back, without making a needless trip and without adding to the screening load at the post. Local traffic, without permits, can proceed as far as the traffic control post.

Standard:

If used, the ROAD (AREA) USE PERMIT REQUIRED FOR THRU TRAFFIC (EM-52-4) sign shall be used at an intersection that is an entrance to a route on which a traffic control point is located.

If used, the sign shall be installed in a manner similar to that of the MAINTAIN TOP SAFE SPEED sign (see Section 2N.06).

Section 2N.08 Emergency Aid Center Signs (EM-63-1 Series)

Standard:

In the event of emergency, State and local authorities shall establish various centers for civilian relief, communication, medical service, and similar purposes. To guide the public to such centers a series of directional signs shall be used.

Emergency Aid Center (EM-63-1 series) signs (see Figure 2N-1) shall <u>carry-display</u> the designation of the center and an arrow indicating the direction to the center. They shall be installed as needed, at intersections and elsewhere, on the right-hand side of the roadway, in urban areas at a minimum height, measured vertically from the bottom of the sign to the top of the curb, or in the absence of curb, measured vertically from the bottom of the sign to the elevation of the near edge of the traveled way, of 7 feet, and not less than 1 foot back from the face of the curb, and in rural areas at a minimum height, measured vertically from the bottom of the sign to the elevation of the near edge of the traveled way, of 5 feet, and at a horizontal distance of not less than 6 feet or more than 10 feet from the roadway edge.

Emergency Aid Center signs shall <u>earry_display</u> one of the following legends, as appropriate, or others designating similar emergency facilities:

- A. MEDICAL CENTER (EM-6a3-1),
- B. WELFARE CENTER (EM-6b3-1a),
- C. REGISTRATION CENTER (EM-6e3-1b), or
- D. DECONTAMINATION CENTER (EM-6d3-1c).

The Emergency Aid Center sign shall be a horizontally oriented rectangle. Except as provided in Paragraph 5, the identifying word and the word CENTER, the directional arrow, and the Emergency Aid Center signs shall have a black legend and border shall be black on a white background.

Option:

When Emergency Aid Center signs are used in an incident situation, such as during the aftermath of a nuclear or biological attack, the background color may be fluorescent pink (see Chapter 6I).

Section 2N.09 Shelter Directional Signs (EM-74-1 Series)

Standard:

Shelter Directional (EM-74-1 series) signs (see Figure 2N-1) shall be used to direct the public to selected shelters that have been licensed and marked for emergency use.

The installation of Shelter Directional signs shall comply with established signing standards. Where used, the signs shall not be installed in competition with other necessary highway guide, warning, and regulatory signs.

The Shelter Directional sign shall be a horizontally oriented rectangle. Except as provided in Paragraph 4, the identifying word and the word SHELTER, the directional arrow, the distance to the shelter, and the Shelter Directional signs shall have a black legend and border shall be black on a white background.

Option:

When Shelter Directional signs are used in an incident situation, such as during the aftermath of a nuclear or biological attack, the background color may be fluorescent pink (see Chapter 6I).

The distance to the shelter may be omitted from the sign when appropriate.

Shelter Directional signs may <u>earry display</u> one of the following legends, or others designating similar emergency facilities:

- A. EMERGENCY (EM-7a4-1),
- B. HURRICANE (EM-7b4-1a),
- 50 C. FALLOUT (EM-7c4-1b), or
- 51 D. CHEMICAL (EM-7d4-1c).

If appropriate, the name of the facility may be used. The Shelter Directional signs may be installed on the Interstate Highway System or any other major highway system when it has been determined that a need exists for such signs as part of a State or local shelter The Shelter Directional signs may be used to identify different routes to a shelter to provide for rapid

movement of large numbers of persons.

7 Guidance:

1

2

3

4 5

6

8

9

10

The Shelter Directional sign should be used sparingly and only in conjunction with approved plans of State and local authorities.

The Shelter Directional sign should not be posted more than 5 miles from a shelter.

CHAPTER 3A. GENERAL

Section 3A.01 Functions and Limitations Deleted (not needed)

Support:

Markings on highways and on private roads open to public travel have important functions in providing guidance and information for the road user. Major marking types include pavement and curb markings, delineators, colored pavements, channelizing devices, and islands. In some cases, markings are used to supplement other traffic control devices such as signs, signals, and other markings. In other instances, markings are used alone to effectively convey regulations, guidance, or warnings in ways not obtainable by the use of other devices.

Markings have limitations. Visibility of the markings can be limited by snow, debris, and water on or adjacent to the markings. Marking durability is affected by material characteristics, traffic volumes, weather, and location. However, under most highway conditions, markings provide important information while allowing minimal diversion of attention from the roadway.

Section 3A.02 3A.01 Standardization of Application

Support:

Markings are used to supplement other traffic control devices such as signs, signals, and other markings. In other instances, markings are used alone to effectively convey regulations, guidance, or warnings in ways not obtainable by the use of other devices.

Markings can take many forms including road surface markings, curb markings, delineators, colored pavements, and channelizing devices.

Standard:

Each standard marking shall be used only to convey the meaning prescribed for that marking in this Manual, including w When used for applications not described in this Manual, markings shall conform in all respects to the principles and standards set forth in this Manual.

Guidance:

Before any new highway, private road open to public travel (see definition in Section 1A.13), paved detour, or temporary route is opened to public travel, all necessary markings should be in place.

Relocated to Part 1

Standard:

Except as provided in Chapter 3H, Mmarkings that must be visible at night shall be retroreflective unless the markings are adequately visible under street or highway lighting. ambient illumination assures demonstrates that the markings are adequately visible. All markings on Interstate highways shall be retroreflective.

Markings that are no longer applicable for roadway conditions or restrictions and that might cause confusion for the road user shall be removed or obliterated to be unidentifiable as a marking as soon as practical.

Option:

Until they can be removed or obliterated, markings that are no longer applicable for roadway conditions or restrictions may be temporarily masked with non-reflective, preformed tape that is approximately the same color as the pavement surface.

Section 3A.043A.02 Materials

42 Support:

Pavement and curb markings are commonly placed by using paints or thermoplastics; however, other suitable marking materials, including raised pavement markers and colored pavements, are also

used. Delineators and channelizing devices are visibly placed in a vertical position similar to signs above the roadway. Not needed

Some marking systems consist of clumps or droplets of material with visible open spaces of bare pavement between the material droplets. These marking systems can function in a manner that is similar to the marking systems that completely cover the pavement surface and are suitable for use as pavement markings if they meet the other pavement marking requirements of the highway agency. Moved to the end of this section and rewritten as an Option

Guidance:

1

2

3

4 5

6 7

8

9

10

11

12

13

14

22

23

24

25

26

27

28 29

30

31

32

33

34

35

36

37

38

41

42

43

44

The materials used for markings should provide the specified color throughout their useful life.

Consideration should be given to selecting pavement marking materials that will minimize tripping or loss of traction for road users, including pedestrians, bicyclists, and motorcyclists.

Delineators should not present a vertical or horizontal clearance obstacle for pedestrians. Moved

to new Section 3G.04

Option:

Marking systems that consist of clumps or droplets of material with visible open spaces of bare

16 pavement between the material droplets, which can function in a manner that is similar to the marking

systems that completely cover the pavement surface, may be used as pavement markings if they meet

18 the other pavement marking requirements of the highway agency. Moved from Paragraph 2 of this

- 19 section and rewritten as an Option
- 20 Section <u>3A.05-3A.03</u> <u>Colors</u>
- 21 Standard:

Markings shall be yellow, white, red, blue, or purple. The colors for markings shall conform to the standard highway colors. Black in conjunction with one of the colors mentioned in the first sentence of this paragraph shall be a usable color.

Option:

Black <u>markings</u> may be used in combination with the colors mentioned in the first sentence of Paragraph 1 where to enhance the contrast with a light-colored pavement does not provide sufficient contrast with the markings.

Moved from Paragraph 8 of this section, with Paragraph 9 incorporated

Standard:

When used, yellow markings for longitudinal lines shall delineate:

- A. The separation of traffic traveling in opposite directions,
- B. The left-hand edge of the roadways of divided highways and one-way streets or ramps, or
- C. The separation of two-way left-turn lanes and reversible lanes from other lanes.

When used, white markings for longitudinal lines shall delineate: The sequence of this paragraph and the previous paragraph were reversed

- A. The separation of traffic flows in the same direction, or
- B. The right-hand edge of the roadway.
- When used, red raised pavement markers or delineators shall delineate:
- 40 **A.** Truck escape ramps, or
 - B. One-way roadways, ramps, or travel lanes that shall not be entered or used in the direction from which the markers are visible.
 - When used, blue markings shall supplement white markings for parking spaces for persons with disabilities.

When used, purple markings shall supplement lane line or edge line markings for toll plaza approach lanes that are restricted to use only by vehicles with registered electronic toll collection accounts, shall be in accordance with the provisions of Chapters 3F and 3H. Moved part of the Standard to new Chapter 3F and new Chapter 3H

Option:Standard: Changed from Option to Standard

Colors used for When pavement markings that simulate official route shield signs (see Section 2D.11) may be are used (see Section 3B.22), as colors of symbol markings to simulate route shields on the pavement (see Section 3B.20) the colors shall be the same as those that are used for the official route signs (see Section 2D.11). Rewritten as a Standard statement

Black may be used in combination with the colors mentioned in the first sentence of Paragraph 1 where a light-colored pavement does not provide sufficient contrast with the markings. Moved to follow Paragraph 1 of this section

Support:

When used in combination with other colors, black is not considered a marking color, but only a contrast enhancing system for the markings. Incorporated into the relocated Paragraph 8 of this section

Provisions regarding colored pavements are contained in Chapter 3H.

Section 3A.063A.04 Functions, Widths, and Patterns of Longitudinal Pavement

Markings

20 Standard:

- The general functions of longitudinal lines shall be as follows:
- A. A double line indicates maximum or special restrictions.
 - B. A solid line discourages or prohibits crossing (depending on the specific application).
 - C. A broken line indicates a permissive condition. and
- D. A dotted lane line provides guidance or warning of a downstream change in lane function.
 - E. A dotted line used as a lane line or edge line extension guides vehicles through an intersection, a taper area, or an interchange ramp area.

The widths and patterns of longitudinal lines shall be as follows:

- A. Normal width line 4 to 6 inches wide, 6 inches wide for freeways, expressways, and ramps; 6 inches for all other roadways with speed limits > 40 mph, 4 to 6 inches for all other roadways.
- B. Wide line—at least twice the width of a normal line at least 8 inches in width if 4 inch or 5 inch normal width lines are used and at least 10 inches in width if 6 inch normal width lines are used.
- C. Double line—two parallel lines separated by a discernible space. The pavement surface shall be visible between the lines in the same way that it is visible outside the lines, except where contrast markings are used in combination with the double line (see Section 3A.03).
 - D. Broken line—normal width line segments separated by gaps.
- E. Dotted line—noticeably shorter line segments separated by shorter gaps than used for a broken line. The width of a dotted line extension shall be at least the same as the width of the line it extends.
- 42 Guidance:
- The discernible space separating the parallel lines of a double line should not exceed that which is necessary to be recognized as a double line rather than two separate, disassociated single lines.

1	Support:
2	The width of the line indicates the degree of emphasis.
3	Wide edge lines have been shown to be beneficial when applied in combination with horizontal
4	alignment warning signs to enhance safety around curves and locations with a history of run off the
5	road crashes (see Section 3B.09).
6	Guidance:
7	Broken lines should consist of 10-foot line segments and 30-foot gaps, or dimensions in a similar
8	ratio of line segments to gaps as appropriate for traffic speeds and need for delineation, except within
9	the circulatory roadway of a circular intersection as provided in Section 3D.02.
10	Support:
11	Patterns for dotted lines depend on the application (see Sections 3B.04 and 3B.08.) Incorporated
12	into existing Paragraph 6 and edited
13	Guidance:
14	A dotted line used as a lane line (see Section 3B.07) should consist of 3-foot line segments and 9-
15	foot gaps. A dotted line for line extensions within an intersection, or taper area, or interchange ramp
16	<u>area (see Section 3B.11)</u> should consist of 2-foot line segments and 2- to 6-foot gaps. The sequence of
17	these sentences was reversed

Section3A.03 3A.05 Maintaining Minimum Pavement Marking Retroreflectivity

(This section reserved for future text based on FHWA rulemaking)

18

19

20

CHAPTER 3B. PAVEMENT AND CURB MARKINGS

Section 3B.01 Yellow Center Line Pavement Markings and Warrants

Standard:

Center line pavement markings, when used, shall be the pavement markings used to delineate the separation of traffic lanes that have opposite directions of travel on a roadway and shall be yellow.

Option:

Center line pavement markings may be placed at a location that is not the geometric center of the roadway.

On roadways without continuous center line pavement markings, short sections may be marked with center line pavement markings to control the position of traffic at specific locations, such as around curves, over hills, on approaches to grade crossings, at grade crossings, and at bridges.

Standard:

The center line markings on two-lane, two-way roadways shall be one of the following as shown in Figure 3B-1:

- A. Two-direction passing zone markings consisting of a normal width broken yellow line where crossing the center line markings for passing with care is permitted for traffic traveling in either direction;
- B. One-direction no-passing zone markings consisting of a double yellow line, one of which is a normal <u>width</u> broken yellow line and the other is a normal <u>width</u> solid yellow line, where crossing the center line markings for passing with care is permitted for the traffic traveling adjacent to the broken line, but is prohibited for traffic traveling adjacent to the solid line; or
- C. Two-direction no-passing zone markings consisting of two normal <u>width</u> solid yellow lines where crossing the center line markings for passing is prohibited for traffic traveling in either direction.

A single solid yellow line shall not be used as a center line marking on a two-way roadway.

Except where a reversible lane (see Section 3B.04) or a two-way left-turn lane (see Section 3B.05) is present, the center line markings on undivided two-way roadways with four or more lanes for moving motor vehicle traffic always available shall be the two-direction no-passing zone markings consisting of a solid double normal width double solid yellow lines as shown in Figure 3B-2.

Guidance:

On two-way roadways with three through lanes for moving motor vehicle traffic, two lanes should be designated for traffic in one direction by using one- or two-direction no-passing zone markings as shown in Figure 3B-3.

Figure 3B-1. Examples of Two-Lane, Two-Way Marking Applications
Figure 3B-2. Examples of Four-or-More Lane, Two-Way Marking Applications
Figure 3B-3. Examples of Three-Lane, Two-Way Marking Applications

Section 3B.02 Warrants for Yellow Center Lines New section comprised of Paragraphs 9 through 13 of existing Section 3B.01

Standard:

Center line markings shall be placed on all paved urban arterials and collectors that have a traveled way of 20 feet or more in width and an ADT of 6,000 vehicles per day or greater. Center

line markings shall also be placed on all paved two-way streets or highways that have three or more lanes for moving motor vehicle traffic.

Guidance:

Center line markings should be placed on paved urban arterials and collectors that have a traveled way of 20 feet or more in width and an ADT of 4,000 vehicles per day or greater. Center line markings should also be placed on all rural arterials and collectors that have a traveled way of 18 feet or more in width and an ADT of 3,000 vehicles per day or greater. Center line markings should also be placed on other traveled ways where an engineering study indicates such a need.

Engineering judgment should be used in determining whether to place center line markings on traveled ways that are less than 16 feet wide because of the potential for traffic encroaching on the pavement edges, traffic being affected by parked vehicles, and traffic encroaching into the opposing traffic lane.

Option:

Center line markings may be placed on other paved two-way traveled ways that are 16 feet or more in width.

If a traffic count is not available, the ADTs described in this Section may be estimates that are based on engineering judgment.

Section 3B.023B.03 No-Passing Zone Pavement Markings and Warrants

Standard:

No-passing zones shall be marked by either the one direction no-passing zone pavement markings or the two-direction no-passing zone pavement markings described in Section 3B.01 and shown in Figures 3B-1 and 3B-3.

When center line markings are used, no passing zone markings shall be used on two-way roadways at lane-reduction transitions (see Section 3B.09) and on approaches to obstructions that must be passed on the right (see Section 3B.10).

No-passing zone markings shall be used on: Changed to list form and edited

- A. Two-way roadways at lane-reduction transitions (see Section 3B.12),
- B. Approaches to obstructions that must be passed on the right (see Section 3B.13-), and
- C. Approaches to grade crossings (see Section 8C.02). Incorporated from Paragraph 8 below

On two-way, two- or three-lane roadways where center line markings are installed, nopassing zones shall be established at vertical and horizontal curves and other locations where an engineering study indicates that passing must be prohibited because of inadequate sight distances or other special conditions.

On roadways with center line markings, no-passing zone markings shall be used at horizontal or vertical curves where the passing sight distance is less than the minimum shown in Table 3B-1 for the 85th-per ntile speed or the posted or statutory speed limit. The passing sight distance on a vertical curve is the distance at which an object 3.5 feet above the pavement surface can be seen from a point 3.5 feet above the pavement (see Figure 3B-4). Similarly, the passing sight distance on a horizontal curve is the distance measured along the center line (or right-hand lane line of a three-lane roadway) between two points 3.5 feet above the pavement on a line tangent to the embankment or other obstruction that cuts off the view on the inside of the curve (see Figure 3B-4). Changed to Support

Support:

The passing sight distance on a vertical curve is the distance at which an object 3.5 feet above the pavement surface can be seen from a point 3.5 feet above the pavement (see Figure 3B-4). Similarly, the passing sight distance on a horizontal curve is the distance measured along the center line (or right-

hand lane line of a three-lane roadway) between two points 3.5 feet above the pavement on a line tangent to the embankment or other obstruction that cuts off the view on the inside of the curve (see Figure 3B-4).

The upstream end of a no-passing zone at point "a" in Figure 3B-4 is that point where the sight distance first becomes less than that specified in Table 3B-1. The downstream end of the no-passing zone at point "b" in Figure 3B-4 is that point at which the sight distance again becomes greater than the minimum specified.

The values of the minimum passing sight distances that are shown in Table 3B-1 are for operational use in marking no passing zones and are less than the values that are suggested for geometric design by the AASHTO Policy on Geometric Design of Streets and Highways (see Section 1A.11).

Guidance:

Where the distance between successive no-passing zones is less than 400 feet, no-passing markings should connect the zones.

Standard:

Where center line markings are used, no-passing zone markings shall be used on approaches to grade crossings in compliance with Section 8B.27. Incorporated into Paragraph 2 of this section

Support: Option:

<u>In addition to pavement markings, No-no-passing zone signs</u> (see Sections <u>2B.28 2B.38</u>, <u>2B.39</u>, and <u>2C.45 2C.53</u>) <u>are sometimes may be used to emphasize the existence and extent of a nopassing zone.</u>

Support:

Section 11-307 of the "Uniform Vehicle Code (UVC)" contains further information regarding required road user behavior in no passing zones. The UVC can be obtained from the National Committee on Uniform Traffic Laws and Ordinances at the address shown on Page i. Not needed

Standard:

On three-lane roadways where the direction of travel in the center lane transitions from one direction to the other, a no-passing buffer zone, consisting of a flush median island (see Section 3J.03) at least 50 feet in length, shall be provided in the center lane as shown in Figure 3B-5. A lane-reduction transition (see Section 3B.09-3B.12) shall be provided at approaching each end of the buffer zone.

The buffer zone shall be a flush median island formed by two sets of double yellow center line markings that is at least 50 feet in length.

Incorporated into previous paragraph

Yellow diagonal crosshatch markings (see Section 3B.24) may be placed in the flush median area between the two sets of no passing zone markings as shown in Figure 3B-5. Not needed because it has been incorporated into new Section 3J.03

Guidance:

For three-lane roadways having a posted or statutory speed limit of 45 mph or greater, the lane transition taper length should be computed by the formula L = WS. For roadways where the posted or statutory speed limit is less than 45 mph, the formula $L = WS^2/60$ should be used to compute the taper length. Not needed, information is provided in new Section 3B.12

Support:

Under both formulas, L equals the taper length in feet, W equals the width of the center lane or offset distance in feet, and S equals the 85th percentile speed or the posted or statutory speed limit, whichever is higher. Not needed, information is provided in new Section 3B.12

	\sim						
4		11	ட	11/	1	20	_

 The minimum lane transition taper length should be 100 feet in urban areas and 200 feet in rural areas. Not needed, information is provided in new Section 3B.12

Table 3B-1. Minimum Passing Sight Distances for No-Passing Zone Markings

Figure 3B-4. Method of Locating and Determining the Limits of No-Passing Zones at Curves

Figure 3B-5. Example of Application of Three-Lane, Two-Way Marking for Changing Direction of the Center Lane

Section 3B.033B.04 Other Yellow Longitudinal Pavement Markings for Reversible Lanes Existing Section 3B.03 was separated into two new Sections

Standard:

If reversible lanes are used, the lane line pavement markings on each side of reversible lanes shall consist of a normal <u>width</u> broken double yellow line to delineate the edge of a lane in which the direction of travel is reversed from time to time, such that each of these markings serve as the center line markings of the roadway during some period (see Figure 3B-6).

Signs (see Section 2B.26-2B.35), lane-use control signals (see Chapter 4M 4T), or both shall be used to supplement reversible lane pavement markings.

Support:

Section 3E.02 contains additional applications of pavement markings for counter-flow preferential lanes that also operate as reversible lanes.

Standard:

If a continuous flush median island formed by pavement markings separating travel in opposite directions is used, two sets of solid double yellow lines shall be used to form the island as shown in Figures 3B-2 and 3B-5. Other markings in the median island area shall also be yellow, except crosswalk markings which shall be white (see Section 3B.18). This Paragraph relocated to Section 3J.03 and edited

Figure 3B-6. Example of Reversible Lane Marking Application

Section 3B.05 Pavement Markings for Two-Way Left-Turn Lanes Standard:

If a two-way left-turn lane that is never operated as a reversible lane is used, the lane line pavement markings on each side of the two-way left-turn lane shall consist of a normal width broken yellow line and a normal width solid yellow line to delineate the edges of a lane that can be used by traffic in either direction as part of a left-turn maneuver. These markings shall be placed with the broken line toward the two-way left-turn lane and the solid line toward the adjacent traffic lane as shown in Figure 3B-7. Paragraph relocated from Section 3B.03

Guidance:

White two way left turn lane use arrows (see Figure 3B-7) should be used in conjunction with the longitudinal two way left turn markings at the locations described in Section 3B.20. Incorporated into the following paragraph

A two-way left turn lane-use arrow pavement marking, with opposing arrows spaced as shown in Figure 3B-7, White two-way left-turn lane-use arrows should be used at or just downstream from the beginning of a two-way left-turn lane. Paragraph relocated from Section 3B.20 and edited Option:

Additional two-way left-turn lane-use arrow markings may be used at other locations along a two-way left-turn lane where engineering judgment determines that such additional markings are needed to emphasize the proper use of the lane. Paragraph relocated from Section 3B.20

Standard:

1

2

3

4

5

6 7 8

9

10

11

12 13

14

15

16

17

18

19

20

21

22

23

24

25

26 27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

43

44

A single-direction lane-use arrow shall not be used in a lane bordered on both sides by yellow two-way left-turn lane longitudinal markings. Paragraph relocated from Section 3B.20

Guidance:

Signs should be used in conjunction with the two-way left turn markings (see Section 2B.24-2B.33). Two-way left-turn lane markings should not extend to intersections.

Support:

Two-way left-turn lanes can be transitioned to exclusive left turn lanes as shown in Figure 3B-7 or painted medians where they approach an intersection.

Section 8A.06 contains information for discontinuing a two-way left turn lane through a highway-rail grade crossing.

Figure 3B-7. Example of Two-Way Left-Turn Lane Marking Application

Section 3B.04 3B.06 White Lane Line Pavement Markings and Warrants

Paragraphs 6-19 and 23 were relocated to new Section 3B.07

Standard:

When used, lane line pavement markings delineating the separation of traffic lanes that have the same direction of travel shall be white.

Lane line markings shall be used on all freeways and Interstate highways.

Guidance:

Lane line markings should be used on all roadways that are intended to operate with two or more adjacent traffic lanes in the same direction of travel, except as otherwise required for reversible lanes. Lane line markings should also be used at congested locations where the roadway will accommodate more traffic lanes with lane line markings than without the markings. Changed to list

- A. On all roadways that are intended to operate with two or more adjacent traffic lanes in the same direction of travel, except as otherwise required for reversible lanes.
- B. At congested locations where the roadway will accommodate more traffic lanes with lane line markings than without the markings.

Support:

Examples of lane line markings are shown in Figures 3B-2, 3B-3, and 3B-7 through 3B-13.

Standard:

Except as provided in Paragraph 6 1 of Section 3B.07, where crossing the lane line markings with care is permitted not discouraged or prohibited, the lane line markings shall consist of a normal width broken white line.

Where crossing the lane line markings is discouraged, the lane line markings shall consist of a normal <u>width</u> or wide solid white line.

Guidance:

- A solid white lane line marking should be used on approaches to:
- A. Intersections to separate a through lane from a mandatory turn lane.
- 42 B. Intersections to separate contiguous mandatory turn lanes from each other.
 - C. Toll collection points to separate toll lanes, payment methods, channelized movements, or obstructions.

1	Option:
2	Solid white lane line markings may be used:
3	A. On approaches to intersections to separate contiguous through lanes.
4	B. To separate through traffic lanes from auxiliary lanes, such as an added uphill truck lane.
5	C. On approaches to crosswalks across multi-lane roadways
6	Option:
7	Where it is intended to discourage lane changing on the approach to an exit ramp, a wide solid
8	white lane line may extend upstream from the theoretical gore or, for multi-lane exits, as shown in
9	Drawing B of Figure 3B-10, for a distance that is determined by engineering judgment.
10	Where lane changes might cause conflicts, a wide or normal solid white lane line may extend
11	upstream from an intersection.
12	Support:
13	Section 3B.09 contains information about the lane line markings that are to be used for transition
14	areas where the number of through lanes is reduced. Not needed, as it is an exact duplicate of
15	Paragraph 19 in this section
16	Guidance:
17	On approaches to intersections, a solid white lane line marking should be used to separate a
18	through lane from an added mandatory turn lane. Moved to earlier in this Section
19	Option:
20	On approaches to intersections, solid white lane line markings may be used to separate adjacent
21	through lanes or adjacent mandatory turn lanes from each other. Relocated to earlier in this Section.
22	The second half of this statement was moved and upgraded to a Guidance statement.
23	Where the median width allows the left turn lanes to be separated from the through lanes to give
24	drivers on opposing approaches a less obstructed view of opposing through traffic, white pavement
25	markings may be used to form channelizing islands as shown in Figure 2B-17. Incorporated into
26	Paragraph 1 of new Section 3B.08
27 28	Solid white lane line markings may be used to separate through traffic lanes from auxiliary lanes, such as an added uphill truck lane or a preferential lane (see Section 3D.02). Relocated to earlier in
20 29	this Section
30	Wide solid lane line markings may be used for greater emphasis.
31	A curved transition may be used where an edge line, channelizing line, or dotted extension line
32	changes direction.
33	Support:
34	Examples of locations where a curved transition can have value include freeway exit and entrance
35	ramps, and turn lanes.
36	Standard:
37	Where crossing the lane line markings is prohibited, the lane line markings shall consist of a
38	double solid double white line (see Figure 3B-12).

Figure 3B-8. Examples of Dotted Line and Channelizing Line Applications for Exit Ramp Markings (2 sheets)

Figure 3B-9. Examples of Dotted Line and Channelizing Line Applications for **Entrance Ramp Markings (2 sheets)**

Figure 3B-10. Examples of Applications of Freeway and Expressway Lane-Drop Markings (5 sheets)

39 40

41

42

43

44

Figure 3B-11. Examples of Applications of Conventional Road Lane-Drop Markings (2 sheets)

Figure 3B-12. Example of Solid Double White Lines Used to Prohibit Lane Changing Figure 3B-13. Examples of Line Extensions through Intersections (2 sheets)

Section 3B.07 White Lane Line Markings for Non-Continuing Lanes This section contains paragraphs 6-19 and 23 from existing Section 3B.04

Standard:

<u>A normal width</u> dotted white line marking shall be used as the lane line to separate a through lane that continues beyond the interchange or intersection from an adjacent <u>deceleration or acceleration lane</u>. <u>for any of the following conditions:</u>

- A. A deceleration or acceleration lane,
- B. A through lane that becomes a mandatory exit or turn lane,
- C. An auxiliary lane 2 miles or less in length between an entrance ramp and an exit ramp, or
- D. An auxiliary lane 1 mile or less in length between two adjacent intersections.

For exit ramps with a parallel deceleration lane, a normal width dotted white lane line shall be installed from the upstream end of the full-width deceleration lane to the theoretical gore or to the upstream end of a solid white lane line, if used, that extends upstream from the theoretical gore as shown in Drawings A and C of Figure 3B-8.

Option:

For exit ramps with a parallel deceleration lane, a normal width dotted white line extension may shall be installed in the taper area upstream from the full-width deceleration lane as shown in Drawings A and C of Figure 3B-8.

For an exit ramp with a tapered deceleration lane, a normal width dotted white line extension may shall be installed from the theoretical gore through the taper area such that it meets the edge line at the upstream end of the taper as shown in Drawing B of Figure 3B-8.

Standard:

For entrance ramps with a parallel acceleration lane, a normal width dotted white lane line shall be installed from the theoretical gore or from the downstream end of a solid white lane line, if used, that extends downstream from the theoretical gore, to a point at least one-half the distance from the theoretical gore to the downstream end of the acceleration taper, as shown in Drawing A of Figure 3B-9.

Option:

For entrance ramps with a parallel acceleration lane, a normal width dotted white line extension shall may be installed from the downstream end of the dotted white lane line to the downstream end of the acceleration taper, as shown in Drawing A of Figure 3B-9.

For entrance ramps with a tapered acceleration lane, a normal width dotted white line extension shall may be installed from the downstream end of the channelizing line adjacent to the through lane to the downstream end of the acceleration taper, as shown in Drawings B and C of Figure 3B-9.

Standard:

A wide dotted white lane line shall be used:

- A. As a lane drop marking in advance of lane drops at exit ramps to distinguish a lane drop from a normal exit ramp (see Drawings A, B, and C of Figure 3B-10),
 - B. In advance of freeway route splits with dedicated lanes (see Drawing D of Figure 3B-10),

- C. In advance of freeway route splits with an option lane (see Drawing E of Figure 3B-10).
- C—D. To separate a through lane that continues beyond an interchange from an adjacent continuous auxiliary lane between an entrance ramp and an exit ramp (see Drawing E F of Figure 3B-10),
- **D**-E. As a lane drop marking in advance of lane drops at intersections to distinguish a lane drop from an intersection through lane (see Drawing A of Figure 3B-11), and
- **E**—<u>F.</u> To separate a through lane that continues beyond an intersection from an adjacent auxiliary lane between two intersections (see Drawing B of Figure 3B-11).

Guidance:

Lane drop markings used in advance of lane drops at freeway and expressway exit ramps should begin at least 1/2 mile in advance of the theoretical gore.

On the approach to a multi-lane exit ramp having an optional exit lane that also carries through traffic, lane line markings should be used as illustrated in Drawing B of Figure 3B-10. In this case, if the right-most exit lane is an added lane such as a parallel deceleration lane, the lane drop marking should begin at the upstream end of the full-width deceleration lane, as shown in Drawing C of Figure 3B-8.

Lane drop markings used in advance of lane drops at intersections should begin a distance in advance of the intersection that is determined by engineering judgment as suitable to enable drivers who do not desire to make the mandatory turn to move out of the lane being dropped prior to reaching the queue of vehicles that are waiting to make the turn. The lane drop marking should begin no closer to the intersection than the most upstream regulatory or warning sign associated with the lane drop.

The dotted white lane lines that are used for lane drop markings and that are used as a lane line separating through lanes from auxiliary lanes should consist of line segments that are 3 feet in length separated by 9-foot gaps.

Support:

Sections <u>3B.25 3B.21 and 3B.23</u> contains information regarding other markings that are associated with lane drops, such as <u>lane use arrow markings and ONLY</u> word <u>pavement</u> markings <u>and lane-use</u> arrows.

Section <u>3B.13</u> <u>3B.12</u> contains information about the lane line markings that are to be used for transition areas where the number of through lanes is reduced at a location that is not at an interchange or intersection.

Option:

In the case of a lane drop at an exit ramp or intersection, such a solid white line may replace a portion, but not all of the length of the wide dotted white lane line.

Section 3B.053B.08 Other White Longitudinal Pavement Markings Channelizing Lines
Support:

Option:

Channelizing lines may be are used to form channelizing islands where traffic traveling in the same direction is permitted on both sides of the island, such as at the neutral areas where traffic traveling in the same general direction is permitted on both sides of exit ramps including entrance and entrance ramps, access and egress points to and from managed-lanes, toll-plaza bypasses, and left turn lanes separated from through lanes (see Figure 2B-11). Text from existing Section 3B.04 and from two paragraphs below

Chapter 3J contains information for the application of channelizing lines used in conjunction with islands.

Standard:

A Except as provided in Paragraph 6 of Section 3J.05, a channelizing line shall be a solid wide or double white line. Moved from Paragraph 1 of this section

Other pavement markings in the channelizing island area shall be white. Replaced by new paragraph below

Support:

 Examples of channelizing line applications are shown in Figures 3B-8, 3B-9, and 3B-10, and in Drawing C of Figure 3B-15, and Figures 3J-1 through 3J-3.

Channelizing lines at exit ramps as shown in Figures 3B-8 and 3B-10 define the neutral area, direct exiting traffic at the proper angle for smooth divergence from the main lanes into the ramp, and reduce the probability of colliding with objects adjacent to the roadway. Incorporated into Paragraph 1 above

Channelizing lines at entrance ramps as shown in Figures 3B-9 and 3B-10 promote orderly and efficient merging with the through traffic. Incorporated into Paragraph 1 above

Standard:

For all exit ramps and for entrance ramps with parallel acceleration lanes, channelizing lines shall be placed on both sides of the neutral area (see of Figures 3B-8 and 3B-10 and Drawing A of Figure 3B-9).

For entrance ramps with tapered acceleration lanes, channelizing lines shall be placed along both sides of the neutral area to a point at least one-half of the distance to the theoretical gore (see Drawing C of Figure 3B-9).

<u>Channelizing lines shall be placed on both sides of the neutral area for bifurcations created from open-road tolling lanes that bypass a conventional toll plaza.</u>

Where neutral areas are formed at access and egress points to and from a managed-lane facility, channelizing lines shall be placed on both sides of the neutral area (see Figures 2G-8, 2G-9, 2G-22, 2G-23, and 2G-25).

Option:

For entrance ramps with tapered acceleration lanes, the channelizing lines may extend to the theoretical gore as shown in Drawing B of Figure 3B-9.

Standard:

Other pavement markings in the neutral area shall be white., such as chevron markings (see Section 3B.25) or retroreflective or internally illuminated raised pavement markers (see Sections 3B.17 and 3B.19), shall be white. This paragraph replaces existing Paragraph 3 of this section

White chevron crosshatch markings (see Section 3B.24) may be placed in the neutral area of exit ramp and entrance ramp gores for special emphasis as shown in Figures 3B-8 and 3B-10 and Drawing A of Figure 3B-9. The channelizing lines and the optional chevron crosshatch markings at exit ramp and entrance ramp gores may be supplemented with white retroreflective or internally illuminated raised pavement markers (see Sections 3B.11 and 3B.13) for enhanced nighttime visibility. This paragraph relocated to Section 3B.25 and edited

Support:

Pavement markings within the neutral area include chevron markings (see Section 3B.25), retroreflective raised pavement markers (see Section 3B.17), and internally illuminated raised pavement markers (see Section 3B.19).

Section 3B.25 contains information on chevron markings for the neutral area of exit and entrance ramps.

Section 3B.06 3B.09 Edge Line Pavement Markings The sequence of paragraphs 2, 3, and 4 has been revised

Standard:

1

2

3

4

5

6 7

8

9

10

11

12

13

14 15

16

17

18

19

20

21

22

23

24

25

26

28

29 30

31

32

33

34

36

37

38

39

40

41

If used, edge line pavement markings shall delineate the right or left edges of a roadway.

If used, right edge line pavement markings shall consist of a normal solid white line to delineate the right-hand edge of the roadway.

Except as provided in Paragraph 9 of Section 3E.04, right edge line pavement markings, if used, shall consist of a normal width solid white line to delineate the right-hand edge of the roadway.

Guidance:

<u>Regardless of the width of the normal line used on the roadway, edge lines on two-lane roadways</u> should be at least 6 inches wide.

Standard:

If used on the roadways of divided highways or one-way streets, or on any ramp in the direction of travel, left edge line pavement markings shall consist of a normal <u>width</u> solid yellow line to delineate the left-hand edge of a roadway or to indicate driving or passing restrictions left of these markings, except as provided in Paragraph 9 of Section 3E.04.

Except for dotted edge line extensions (see Section 3B.08), edge line markings shall not be continued through intersections or major driveways. Changed to Guidance, edited and relocated below

Guidance:

Edge line markings should not be broken for minor driveways. Relocated to new Section 3B.11

Guidance: Changed from Standard, edited, and relocated from above

Edge line markings should not be continued through intersections or major driveways, except for the following situations:

a. Dotted edge line extensions (see Section 3B.08), or

b. Through that part of an intersection with no intersection approach (such as the top of a *T*-intersection).

27 Support:

Edge line markings have unique value as visual references to guide road users during adverse weather and visibility conditions. Not needed

<u>Section 3B.11 contains information on the use and application of edge lines through intersections, interchanges, and driveways.</u>

Option:

Wide solid edge line markings may be used for greater emphasis.

Section 3B.07 3B.10 Warrants for Use of Edge Lines

35 **Standard:**

Edge line markings shall be placed on paved streets or highways with the following characteristics:

- A. Freeways,
- B. Expressways, and
- C. Rural arterials with a traveled way of 20 feet or more in width and an ADT of 6,000 vehicles per day or greater.
- 42 Guidance:

Edge line markings should be placed on paved streets or highways with the following characteristics:

- A. Rural arterials and collectors with a traveled way of 20 feet or more in width and an ADT of 3,000 vehicles per day or greater.
- B. On other paved streets and highways where an engineering study indicates a need for edge line markings.

Edge line markings should not be placed where an engineering study or engineering judgment indicates that providing them is likely to decrease safety.

Option

Edge line markings may be placed on streets and highways with or without center line markings.

Edge line markings may be excluded, based on engineering judgment, for reasons such as if the traveled way edges are delineated by curbs, parking, or other markings.

If a bicycle lane is marked on the outside portion of the traveled way, the edge line that would mark the outside edge of the bicycle lane may be omitted.

Edge line markings may be used where edge delineation is desirable to minimize unnecessary driving on paved shoulders or on refuge areas that have lesser structural pavement strength than the adjacent roadway.

Section 3B.08-3B.11 Extensions Application of Pavement Markings Through

Intersections or Interchanges

Support:

<u>Section 8C.05 contains information about the extension of edge lines through grade crossing areas.</u>
<u>Section 9E.03 contains information for the extensions of bicycle lanes through intersections.</u>

<u>In accordance with Definition 101 in Section 1C.02, driveway connections can be considered as intersections.</u>

Standard:

Except as provided in Paragraph 2, pavement Pavement markings extended into or continued through an intersection or interchange area shall be the same color and at least the same width as the line markings they extend (see Figure 3B-13). Reduced a portion of Standard to Guidance Guidance:

Pavement markings extended into or continued through an intersection or interchange area should be at least the same width as the line markings they extend. (See Figure 3B-13) Text from Paragraph 1 that has been reduced to Guidance

Option:

A normal line may be used to extend a wide line through an intersection. Redundant with Guidance above

Guidance:

Where highway design or reduced visibility conditions make it desirable to provide control or to guide vehicles through an intersection, or interchange, such as at offset, skewed, complex, or multilegged intersections, on curved roadways, where multiple turn lanes are used, or where offset left turn lanes might cause driver confusion, dotted <u>lane</u> line extension markings consisting of 2-foot line segments and 2- to 6-foot gaps should be used to extend longitudinal line markings through an intersection or interchange area.

Where greater restriction is required desired preferred, solid lane lines or channelizing lines should be extended into or continued through intersections or major driveways.

Standard:

Extensions of center lines through intersections shall be dotted lines.

Option:

Dotted edge line extensions may be placed through intersections or major driveways. Relocated from earlier in this Section

Standard:

Solid lines shall not be used to extend edge lines into or through intersections or major driveways except through that part of an intersection with no intersecting approach (such as at the top of a T-intersection).

Guidance:

<u>Edge line markings should be discontinued across intersecting approaches at intersections or interchanges.</u> Relocated from Section 3B.06, reduced to Guidance, and edited

<u>Driveways that do not meet the definition of an intersection should have edge line markings</u> <u>maintained across the intersecting approach of the driveway.</u> Relocated from Section 3B.06 and edited

Where a double line is extended through an intersection, a single line of equal width to one of the lines of the double line should be used.

To the extent possible, pavement marking extensions through intersections should be designed in a manner that minimizes potential confusion for drivers in adjacent or opposing lanes. Not needed

Section 3B.093B.12 Lane-Reduction Transitions Markings

Support:

<u>A lane-Lane-reduction transition markings are used is</u> where the number of through lanes is reduced at a location that is not at an interchange or intersection because of narrowing of the roadway or because of a section of on-street parking in what would otherwise be a through lane. Lane reduction transition markings are not used for lane drops.

Section 3B.07 contains information on pavement markings for lane drops and splits. Section 2C.48 contains information for warning signing used for lane reductions.

Standard:

Except as provided in Paragraph 3, where pavement markings are used, lane-reduction transition markings shall be used to guide traffic through transition areas where the number of through lanes is reduced, as shown in Figure 3B-14. On two-way roadways, no-passing zone markings shall be used to prohibit passing in the direction of the convergence, and shall continue through the transition area.

Lane-reduction transitions (see Figure 3B-14) shall include the following elements:

- A. A no-passing zone (see Section 3B.03) to prohibit passing in the direction of the convergence and through the transition area except where not applicable such as one-way streets, expressways, and freeways, and
- B. An edge line (see Section 3B.09) in the direction of the convergence and through the transition area, except as provided in Paragraph 11.

Guidance:

Except as provided in Paragraph 3 11 for low speed urban roadways, the edge line marking shown in Figure 3B-14 should be installed from the location of the Lane Ends warning sign to beyond the beginning of the narrower roadway. Paragraph relocated from later in Section and edited Option:

41 Option: 42 On

On low-speed urban-roadways with operating speeds less than 25 mph where curbs clearly define the roadway edge in the lane-reduction transition, or where a through lane becomes a parking lane, the edge line and/or delineators shown in Figure 3B-14 may be omitted as determined by engineering judgment.

Guidance:

Lane-reduction transitions should include the following elements:

A. Delineators installed adjacent to the lane or lanes reduced for the full length of the transition and should be so placed and spaced (see Section 3G.04) to show the reduction except as provided in Paragraph 11 and except as provided in Paragraph 2 of Section 3G.03 for freeways and expressways, and

B. Lane-reduction arrow markings (see Drawing F in Figure 3B-21) on the roadway with a speed limit of 45 mph or more, and

C. A termination of the broken white lane line at a point that is one-quarter of the advance warning distance (see Section 2C.04) between the Lane Ends sign (see Section 2C.47) and the point where the transition taper begins.

For roadways having a posted or statutory speed limit of 45 mph or greater, the transition taper length for a lane-reduction transition should be computed by the formula L = WS, where L could the taper length in feet, W equals the width of the offset distance in feet, and S equals the 85th public speed or the posted or statutory speed limit, whichever is higher. For roadways where the posted or statutory speed limit is less than 45 mph, the formula $L = WS^2/60$ should be used to compute the taper length.

The minimum lane transition taper length should be 100 feet in urban areas and 200 feet in rural areas. Relocated Guidance from existing Section 3B.02

Support:

Under both formulas, L equals the taper length in feet, W equals the width of the offset distance in feet, and S equals the 85th percentile speed or the posted or statutory speed limit, whichever is higher. Incorporated into previous Guidance above

Guidance:

Where observed speeds exceed posted or statutory speed limits, longer tapers should be used. Option:

The minimum taper length may be less than 100 feet on roadways where the operating speed is less than 25 mph.

On new construction, where no posted or statutory speed limit has been established, the design speed may be used in the transition taper length formula.

On low-speed urban roadways where curbs clearly define the roadway edge in the lane-reduction transition, or where a through lane becomes a parking lane, delineators may be omitted as determined by engineering judgment.

Where a lane-reduction transition occurs on a roadway with a speed limit of less than 45 mph, lane-reduction arrow markings may be used. This paragraph relocated from Paragraph 34 in Section 3B.20 and edited to be consistent with Note 1 of existing Figure 3B-14

Lane-reduction arrow markings may be used in long acceleration lanes based on engineering judgment. This paragraph relocated from Paragraph 35 in Section 3B.20

Guidance:

Lane line markings should be discontinued one quarter of the distance between the Lane Ends sign (see Section 2C.42) and the point where the transition taper begins. Incorporated into Item C of Guidance above

Support:

Pavement markings at lane-reduction transitions supplement the standard signs. Incorporated into Paragraph 2 See Section 3B.20 for provisions regarding use of lane-reduction arrows.

Figure 3B-14. Examples of Applications of Lane-Reduction Transition Markings Section 3B.103B.13 Approach Markings for Obstructions

Standard:

Pavement markings shall be used to guide traffic away from fixed obstructions within a paved roadway. Approach markings for bridge supports, refuge islands, median islands, toll plaza islands, and raised channelization islands shall consist of a tapered line or lines extending from the center line or the lane line to a point 1 to 2 feet to the right-hand side, or to both sides, of the approach end of the obstruction (see Figure 3B-15).

Support:

See Chapter 3E for additional information on approach markings for toll plaza islands. Not needed *Guidance*:

For roadways having a posted or statutory speed limit of 45 mph or greater, the taper length of the tapered line markings should be computed by the formula L = WS, where L equals the taper length in feet, W equals the width of the offset distance in feet, and S equals the 85th-percurve e speed or the posted or statutory speed limit, whichever is higher. For roadways where the posted or statutory speed limit is less than 45 mph, the formula $L = WS^2/60$ should be used to compute the taper length.

Support:

Under both formulas, L equals the taper length in feet, W equals the width of the offset distance in feet, and S equals the 85th-percentile speed or the posted or statutory speed limit, whichever is higher. Incorporated into previous paragraph

Guidance:

The minimum taper length should be 100 feet in urban areas and 200 feet in rural areas.

Option:

The minimum taper length may be less than 100 feet on roadways where the operating speed is less than 25 mph.

Support:

Examples of approach markings for obstructions in the roadway are shown in Figure 3B-15. Not needed

Standard:

If traffic is required to pass only to the right of the obstruction, the markings shall consist of a two-direction no-passing zone marking at least twice the length of the diagonal portion as determined by the appropriate taper formula (see Drawing A of Figure 3B-15).

Option:

If traffic is required to pass only to the right of the obstruction, yellow diagonal erosshatch markings (see Section 3B.24 3B.25) may be placed in the flush median area (see Section 3J.03) between the no-passing zone markings as shown in Drawings A and B of Figure 3B-15. Other markings, such as yellow delineators, yellow channelizing devices, yellow raised pavement markers, and white crosswalk pavement markings, may also be placed in the flush median area. The cross reference to new Section 3J.03 replaces this sentence

Standard:

If traffic can pass either to the right or left of the obstruction, the markings shall consist of two channelizing lines diverging from the lane line, one to each side of the obstruction. In advance of the point of divergence, a wide solid white line or normal width double solid double white line shall be extended in place of the broken lane line for a distance equal to the length of the diverging lines (see Drawing C of Figure 3B-15).

Option:

If traffic can pass either to the right or left of the obstruction, additional white chevron crosshatch markings (see Section 3B.24 3B.25) may be placed in the flush median neutral area between the

channelizing lines as shown in Drawing C of Figure 3B-15. Other markings, such as white delineators, white channelizing devices, white raised pavement markers, and white crosswalk markings may also be placed in the flush median-neutral area.

Figure 3B-15. Examples of Applications of Markings for Obstructions in the Roadway (2 sheets)

Section 3B.11 3B.14 Raised Pavement Markers – General

Support:

Section 9A.03 contains information for the application of raised pavement markers to bicycle facilities.

Standard:

The color of raised pavement markers under both daylight and nighttime conditions shall conform to the color of the marking for which they serve as a positioning guide, or for which they supplement or substitute.

Option:

The side of a raised pavement marker that is visible to traffic proceeding in the wrong direction may be red (see Section 3A.05).

Retroreflective or internally illuminated raised pavement markers may be used in the roadway immediately adjacent to curbed approach ends of raised medians and curbs of islands, or on top of such curbs (see Section 3B.23-3J.04).

Support:

Retroreflective and internally illuminated raised pavement markers are available in monodirectional and bidirectional configurations. The bidirectional marker is capable of displaying the applicable color for each direction of travel. Not needed

Blue raised pavement markers are sometimes used in the roadway to help emergency personnel locate fire hydrants. Not needed

Standard:

When used, internally illuminated raised pavement markers shall be steadily illuminated and shall not be flashed.

Support:

Flashing raised pavement markers are considered to be In-Roadway Lights (see Chapter 4N 4U). *Guidance:*

Non-retroreflective raised pavement markers should not be used alone, without supplemental retroreflective or internally illuminated markers, as a substitute for other types of pavement markings. Relocated to new Section 3B.17

Directional configurations should be used to maximize correct information and to minimize confusing information provided to the road user. Directional configurations also should be used to avoid confusion resulting from visibility of markers that do not apply to the road user. Not needed

The spacing of raised pavement markers used to supplement or substitute for other types of longitudinal markings should correspond with the pattern of broken lines for which the markers supplement or substitute.

Standard:

The value of N cited in Sections <u>3B.123B.14</u> through <u>3B.14</u> <u>3B.17</u> for the spacing of raised pavement markers shall equal the length of one line segment plus one gap of the broken lines used on the highway.

Option:

For additional emphasis, retroreflective raised pavement markers may be spaced closer than described in Sections <u>3B.12</u> <u>3B.14</u> through <u>3B.14</u> as determined by engineering judgment or engineering study.

Support:

Figures 9-20 through 9-22 in the "Traffic Control Devices Handbook" (see Section 1A.11) contain additional information regarding the spacing of raised pavement markers on longitudinal markings.

Not needed

Section 3B.123B.15 Raised Pavement Markers as Vehicle Positioning Guides with Other Longitudinal Markings

Option:

Retroreflective or internally illuminated raised pavement markers may be used as positioning guides with longitudinal line markings without necessarily conveying information to the road user about passing or lane-use restrictions. In such applications, markers may be positioned in line with or immediately adjacent to a single line marking, or positioned between the two lines of a double center line or double lane line marking.

Guidance:

Except as otherwise provided in Paragraphs 3 and 4, the spacing for such applications should be 2N, where N equals the length of one line segment plus one gap (see Section 3B.11-3B.14).

Option:

Where it is desired to alert the road user to changes in the travel path, such as on sharp curves or on transitions that reduce the number of lanes or that shift traffic laterally, the spacing may be reduced to N or less.

On freeways and expressways, the spacing may be increased to 3N for relatively straight and level roadway segments where engineering judgment indicates that such spacing will provide adequate delineation under wet night conditions.

Section 3B.13 3B.16 Raised Pavement Markers Supplementing Other Markings

Guidance:

The use of retroreflective or internally illuminated raised pavement markers for supplementing longitudinal line markings should comply with the following:

A. Lateral Positioning

- 1. When supplementing double line markings, pairs of raised pavement markers placed laterally in line with or immediately outside of the two lines should be used.
- 2. When supplementing wide line markings, pairs of raised pavement markers placed laterally adjacent to each other should be used.

B. Longitudinal Spacing

- 1. When supplementing solid line markings, raised pavement markers at a spacing no greater than N (see Section $\frac{3B.11}{3B.14}$) should be used, except that when supplementing channelizing lines or edge line markings, a spacing of no greater than N/2 should be used.
- 2. When supplementing broken line markings, a spacing no greater than 3N should be used. However, when supplementing broken line markings identifying reversible lanes, a spacing of no greater than N should be used.
- 3. When supplementing dotted lane line markings, a spacing appropriate for the application should be used.
- 4. When supplementing longitudinal line extension markings through at-grade intersections, one raised pavement marker for each short line segment should be used.

5. When supplementing line extensions through freeway interchanges, a spacing of no greater than N should be used.

Raised pavement markers should not supplement right-hand edge lines unless an engineering study or engineering judgment indicates the benefits of enhanced delineation of a curve or other location would outweigh possible impacts on bicycles using the shoulder, and the spacing of raised pavement markers on the right-hand edge is close enough to avoidminimize misinterpretation as a broken line during wet night conditions.

Option:

Raised pavement markers also may be used to supplement other markings such as channelizing islands, gore areas, approaches to obstructions, or wrong-way arrows.

To improve the visibility of horizontal curves, center lines may be supplemented with retroreflective or internally illuminated raised pavement markers for the entire curved section as well as for a distance in advance of the curve that approximates 5 seconds of travel time.

Section 3B.143B.17 Raised Pavement Markers Substituting for Pavement Markings

Option:

Retroreflective or internally illuminated raised pavement markers, or non-retroreflective raised pavement markers supplemented by retroreflective or internally illuminated markers, may be substituted for markings of other types.

Guidance.

If used, the pattern of the raised pavement markers should simulate the pattern of the markings for which they substitute.

Standard:

Non-retroreflective raised pavement markers should shall not be used alone, without supplemental retroreflective or internally illuminated markers, as a substitute for other types of pavement markings. Paragraph relocated from existing Section 3B.11

Standard:

If raised pavement markers are used to substitute for broken line markings, a group of three to five markers equally spaced at a distance no greater than N/8 (see Section 3B.11-3B.14) shall be used. If N is other than 40 feet, the markers shall be equally spaced over the line segment length (at 1/2 points for three markers, at 1/3 points for four markers, and at 1/4 points for five markers). At least one retroreflective or internally illuminated marker per group shall be used or a retroreflective or internally illuminated marker shall be installed midway in each gap between successive groups of non-retroreflective markers.

When raised pavement markers substitute for solid line markings, the markers shall be equally spaced at no greater than N/4, with retroreflective or internally illuminated units at a spacing no greater than N/2.

Guidance:

Raised pavement markers should not substitute for right-hand edge line markings unless an engineering study or engineering judgment indicates the benefits of enhanced delineation of a curve or other location would outweigh possible impacts on bicycles using the shoulder, and the spacing of raised pavement markers on the right-hand edge line is close enough to avoid minimize misinterpretation as a broken line during wet night conditions.

Standard:

When raised pavement markers substitute for dotted lines, they shall be spaced at no greater than N/4, with not less than one raised pavement marker per dotted line segment. At least one raised marker every N shall be retroreflective or internally illuminated.

Option:

1

2

3

4

5

6

7

8

9

10

11

12

13 14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30 31

32

33

34

35

36

37

38

39

When substituting for wide lines, raised pavement markers may be placed laterally adjacent to each other to simulate the width of the line.

Section 3B.15 Transverse Markings Not needed

Standard:

Transverse markings, which include shoulder markings, word and symbol markings, arrows, stop lines, yield lines, crosswalk lines, speed measurement markings, speed reduction markings, speed hump markings, parking space markings, and others, shall be white unless otherwise provided in this Manual.

Guidance:

Because of the low approach angle at which pavement markings are viewed, transverse lines should be proportioned to provide visibility at least equal to that of longitudinal lines.

Section 3B.23 3B.18 Curb Markings for Parking Regulations Paragraphs 7 through 11 from existing Section 3B.23 are relocated to Section 3J.04 and edited

Support:

Curb markings are most often used to indicate parking regulations or to delineate the curb. Not needed

Support: Guidance:

Except as provided in Paragraph 4, since yellow and white curb markings are frequently used for curb delineation and visibility, it is advisable to establish parking regulations should be established through the installation of standard signs (see Sections 2B.46-2B.56 through 2B.48-2B.57). Relocated from later in Section and changed to Guidance

Where curbs are marked to convey parking regulations in areas where curb markings are frequently obscured by snow and ice accumulation, signs shall should be used with the curb markings except as provided in Paragraph 4.

Guidance:

Except as provided in Paragraph 4, when curb markings are used without signs to convey parking regulations, a legible word marking regarding the regulation (such as "No Parking" or "No Standing") should be placed on the curb.

Curb markings without word markings or signs may be used to convey a general prohibition by statute of parking within a specified distance of a STOP sign, YIELD sign, driveway, fire hydrant, or crosswalk.

Local highway agencies may prescribe special colors for curb markings to supplement standard signs for parking regulation.

Option:

Retroreflective or internally illuminated raised pavement markers of the appropriate color may be placed on the payement in front of the curb and/or on the top of curbed noses of raised medians and eurbs of islands, as a supplement to or substitute for retroreflective eurb markings used for delineation.

40 Not needed since it is a duplicate provision of Paragraph 3 in existing Section 3I.05

- Section 3B.16 3B.19 Stop and Yield Lines The sequence of several paragraphs in this 41
- 42 section has been revised
- 43 Option:

Stop lines may be used to indicate the point behind which vehicles are required to stop in compliance with a STOP (R1-1) sign, a Stop Here For Pedestrians (R1-5b or R1-5c) sign, or some other traffic control device that requires vehicles to stop, except YIELD signs that are not associated with passive grade crossings.

Standard:

Stop lines shall consist of solid white lines extending across approach lanes to indicate the point at which the stop is intended or required to be made.

Except as provided in Section <u>8B.28-8C.03</u>, stop lines shall not be used at locations where drivers are required to yield in compliance with a YIELD (R1-2) sign, or a Yield Here To Pedestrians (R1-5 or R1-5a) sign or at locations on uncontrolled approaches where drivers or <u>bicyclists</u> are required by State law to yield to pedestrians.

Guidance:

Stop lines should be used to indicate the point behind which vehicles are required to stop in compliance with a traffic control signal.

Stop lines at midblock signalized locations should be placed at least 40 feet in advance of the nearest signal indication (see Section 4D.14 4D.07).

Stop lines should be 12 to 24 inches wide.

Support:

Section 4J.02 contains information regarding the use and application of stop lines in conjunction with a pedestrian hybrid beacon.

Option:

Yield lines may be used to indicate the point behind which vehicles are required to yield in compliance with a YIELD (R1-2) sign, or a Yield Here To Pedestrians (R1-5 or R1-5a) sign, or a Bieyeles Yield to Peds (R9-6) sign. This paragraph changed to the following Standard and edited

Standard:

If used, a yield line pavement marking shall not be installed without a Yield (R1-2) sign, a Yield Here To Pedestrians (R1-5 or R1-5a) sign, a Bicycles Yield to Peds (R9-6) Sign (see Figure 3B-16), or some other traffic control device that requires vehicles to yield. This paragraph changed from the previous Option to Standard and edited

Yield lines shall not be used at locations where drivers are required to stop in compliance with a STOP (R1-1) sign, a Stop Here For Pedestrians (R1-5b or R1-5c) sign, a traffic control signal, or some other traffic control device.

Yield lines (see Figure 3B-16) shall consist of a row of solid white isosceles triangles pointing toward approaching vehicles extending across approach lanes to indicate the point at which the yield is intended or required to be made.

Guidance:

The individual triangles comprising the yield line should have a base of 12 to 24 inches wide and a height equal to 1.5 times the base. The space between the triangles should be 3 to 12 inches.

If used, stop and yield lines should be placed a minimum of 4 feet in advance of the nearest crosswalk line at controlled intersections, except for yield lines at roundabouts as provided for in Section-3C.04 3D.04 and at midblock crosswalks. In the absence of a marked crosswalk, the stop line or yield line should be placed at the desired stopping or yielding point, but should not be placed more than 30 feet or less than 4 feet from the nearest edge of the intersecting traveled way.

If yield or stop lines are used at a crosswalk that crosses an uncontrolled multi-lane approach, the yield lines or stop lines should be placed 20 to 50 feet in advance of the nearest crosswalk line, and

parking should be prohibited in the area between the yield or stop line and the crosswalk (see Figure 3B-17). Relocated below and edited; a portion changed to a Standard

Standard:

If yield (stop) lines are used at a crosswalk that crosses an uncontrolled multi-lane approach, Yield Here To (Stop Here For) Pedestrians (R1-5 series) signs (see Section 2B.11 2B.20) shall be used.

When used to supplement a Yield Here To (Stop Here For) Pedestrians (R1-5 series) sign in advance of a crosswalk that crosses an uncontrolled multi-lane approach, the yield (stop) line shall be placed 20 to 50 feet in advance of the nearest crosswalk line. Relocated from Guidance above and changed to a Standard

Guidance:

If yield or stop lines are used in <u>advance of</u> a crosswalk that crosses an uncontrolled multi-lane approach, parking should be prohibited in the area between the yield or stop line and the crosswalk <u>(see Drawing B of Figure 3B-16)</u>. Relocated from above

Support:

Section 9B.12 contains information for providing signing applicable to bicycles also subject to a yielding requirement at a crosswalk that crosses an uncontrolled approach.

Guidance:

Yield (stop) lines and Yield Here To (Stop Here For) Pedestrians signs should not be used in advance of crosswalks that cross an approach to or departure from a roundabout circular intersection. Support:

Section—8B.28 <u>8C.03</u> contains information regarding the use of stop lines and yield lines at grade crossings.

When drivers yield or stop too close to crosswalks that cross uncontrolled multi-lane approaches, they place pedestrians at risk by blocking other drivers' views of pedestrians and by blocking pedestrians' views of vehicles approaching in the other lanes.

Not needed

Option:

Stop and yield lines may be staggered longitudinally on a lane-by-lane basis (see Drawing D of Figure 3B-13).

Support:

Staggered stop lines and staggered yield lines can improve the driver's view of pedestrians, provide better sight distance for turning vehicles, and increase the turning radius for left-turning vehicles.

Figure 3B-16. Examples of Yield Lines at Unsignalized Midblock Crosswalks

Section 3B.20 Pavement Word, Symbol, and Arrow Pavement Markings – General Several paragraphs within existing Section 3B.20 were rearranged, and Sections 3B.24 through 3B.28 were created from Section 3B.20. Paragraphs 34 and 35 were relocated to Section 3B.12 and edited

Support:

Word, symbol, and arrow markings on the pavement are used for the purpose of guiding, warning, or regulating traffic. These pavement markings can be helpful to road users in some locations by supplementing signs and providing additional emphasis for important regulatory, warning, or guidance messages, because the markings do not require diversion of the road user's attention from the roadway surface. Symbol messages are preferable to word messages. Examples of standard word and arrow pavement markings are shown in Figures 3B-23 and 3B-24.

45 Option:

```
1
         Word, symbol, and arrow markings, including those contained in the "Standard Highway Signs and
 2
     Markings" book (see Section 1A.11), may be used as determined by engineering judgment to
 3
     supplement signs and/or to provide additional emphasis for regulatory, warning, or guidance messages
 4
     provided by other devices. Among the word, symbol, and arrow markings that may be used are the
 5
     following:
 6
         A. Regulatory:
 7
         1. STOP
8
         2. YIELD
9
         3. RIGHT (LEFT) TURN ONLY
10
         4. 25 MPH
11
         5. Lane-use and wrong-way arrows
12
         6. Diamond symbol for HOV lanes
13
         7. Other preferential lane word markings
14
         B. Warning:
15
         1. STOP AHEAD
16
         2. YIELD AHEAD
17
         3. YIELD AHEAD triangle symbol
18
         4. SCHOOL XING
19
         5. SIGNAL AHEAD
20
         6. PED XING
21
         7. SCHOOL
         8. R X R
22
23
         9. BUMP
24
         10. HUMP
25
         11. Lane-reduction arrows
26
         C. Guide:
27
              Route numbers (route shield pavement marking symbols and/or words such as I 81, US 40,
28
     STATE 135, or ROUTE 10)
29

    Cardinal directions (NORTH, SOUTH, EAST, or WEST)

30
31
               Destination names or abbreviations thereof Not needed as the general details are
32
     included in the SHSM
33
     Support:
34
         For arrow pavement markings in the vicinity of highway-rail grade crossings, see Section 8C.04.
35
     Standard:
36
         Word, symbol, and arrow markings shall be white, except as otherwise provided in this
37
     Section. Not needed
38
         Pavement marking letters, numerals, symbols, and arrows shall be installed in accordance
     with the design details in the Pavement Markings chapter of the "Standard Highway Signs and
39
     Markings" book (see Section 1A.11 1A.05).
40
41
     Guidance:
```

interrelated message should not exceed three lines of information.

42

43

Word, symbol and/or arrow Word and symbol markings that are grouped together to formulate one

Except for the two opposing white arrows of a two-way left-turn lane marking (see Figure 3B-7) and the pavement word marking messages described in Items B and D of Paragraph 2 of Section 3B., the longitudinal space between word, or symbol, and/or message markings, including arrow markings that are used together to formulate one interrelated message should be at least four times the height of the characters for low-speed roads, but not more than ten times the height of the characters under any conditions.

The number of different word and symbol markings used should be minimized to provide effective guidance and avoid misunderstanding. Not needed

Except for the SCHOOL word marking (see Section 7C.03 7C.02), pavement word, symbol, and arrow markings should be no more than one lane in width.

Pavement word, symbol, and arrow markings should be proportionally scaled to fit within the width of the facility upon which they are applied.

Option:

On narrow, low-speed shared-use paths, the pavement words, symbols, and arrows may be smaller than suggested, but to the relative scale.

On roadways where the operating speed is less than 25 mph, word, symbol, and arrow markings may be reduced in size no less than ¼ size, but in relative proportion to the associated full-size word, symbol, or arrow.

Section 3B.21 Word Pavement Markings Contains paragraphs 5,7, 14, 15, 26, 32, and 33 from existing Section 3B.20

Guidance:

Letters and numerals should be 6 feet or more in height <u>except as provided in Section 9E.15 for a bicycle detector symbol.</u>

If a pavement marking word message consists of more than one line of information, it should read in the direction of travel. The first word of the message should be nearest to the road user.

Standard:

Except at the ends of aisles in parking lots, the word STOP shall not be used on the pavement unless accompanied by a stop line (see Section 3B.19 3B.16) and STOP sign (see Section 2B.05 2B.04). At the ends of aisles in parking lots, the word STOP shall not be used on the pavement unless accompanied by a stop line.

The word STOP shall not be placed on the pavement in advance of a stop line, unless every vehicle is required to stop at all times.

Guidance:

Where through lanes approaching an intersection become mandatory turn lanes, ONLY word pavement markings (see Figure 3B-17) should be used in addition to the required lane-use arrow markings (see Section 3B.23) and signs (see Sections 2B.29 and 2B.30). These markings and signs should be placed well in advance of the turn and should be repeated as necessary to prevent entrapment and to help the road user select the appropriate lane in advance of reaching a queue of waiting vehicles (see Drawing A of Figure 3B-11). Not needed

Option:

The ONLY word marking (see Figure 3B-18) may be used to supplement the lane-use arrow markings in lanes that are designated for the exclusive use of a single movement (see Figure 3B-25) such as turn bays. or to supplement a preferential lane word or symbol marking (see Section 3D.01).

The ONLY word marking may be used to supplement a preferential lane word or symbol marking (see Section 3D.03 3E.03).

Standard:

1 2	The ONLY word marking shall not be used in a lane that is shared by more than one movement.
3	Figure 3B-17. Example of Elongated Letters for Word Pavement Markings
4	Section 3B.22 Symbol Pavement Markings Contains paragraphs 12, 16, 17, 18, and 19
5	from existing Section 3B.20
6	Support:
7	Section 3E.03 contains information on the diamond shape symbol for high-occupancy vehicle
8	(HOV) lanes.
9	Section 9E.01 Chapter 9E contains information on symbol markings that can be used for bicycle
10 11	<u>lanes</u> . Section 9E.16 contains information on the bicycle detector symbol. Option:
12	Pavement markings simulating Interstate, U.S., State, and other official highway route shield signs
13 14	(see Figure 2D- <u>5</u> 3) with appropriate route numbers, but elongated for proper proportioning when viewed as a marking, may be used to guide road users to their destinations (see Figure <u>3B-253B-18</u>).
15	Guidance:
16	If route shield markings are provided to guide road users, those route shield markings should be
17	provided in option lanes if markings are provided in any lanes.
18 19	If two route shield markings are provided in an option lane, they should be placed together in sequence and not divided around an optional lane arrow.
20	Support:
21	Section 9E.14 contains information on route markers for designated bicycle routes that can be used
22	on shared-use paths.
23	Guidance:
24 25	The International Symbol of Accessibility parking space marking (see Figure 3B-223B-19) should be placed in each parking space designated for use by persons with disabilities.
26	Option:
27 28	A blue background with white border may supplement the wheelchair symbol as shown in Figure 3B-22 3B-19.
29 30 31	A yield-ahead triangle symbol (see Figure 3B-26) or YIELD AHEAD word pavement marking may be used on approaches to intersections where the approaching traffic will encounter a YIELD sign at the intersection.
32	Standard:
33 34 35	The yield-ahead triangle symbol or YIELD AHEAD word pavement marking shall not be used unless a YIELD sign (see Section—2B.08 2B.05) is in place at the intersection. The yield-ahead symbol marking shall be as shown in Figure 3B-26 3B-20.
36	Figure 3B-18. Examples of Elongated Route Shields for Pavement Markings
37	Figure 3B-19. International Symbol of Accessibility Parking Space Marking
38	Figure 3B-20. Yield Ahead Triangle Symbols
39	Option:
40	A pedestrian symbol pavement marking may be used on portions of facilities such as shared-use
41	paths that are reserved exclusively for pedestrian use.
42 43	Section 3B.23 Lane-Use Arrows Contains paragraphs 20, 21, 22, 23, 25, 26, 27, and 31 from existing Section 3B.20

Support:

Lane-use arrow markings (see Figure 3B-24 3B-21) are used to indicate the mandatory or permissible movements in certain lanes (see Figure 3B-27 3B-22) and in two-way left-turn lanes (see Figure 3B-7).

Section 8C.04 contains information about the placement of lane-use arrow markings in the vicinity of grade crossings.

Guidance:

Lane-use arrow markings (see Figure 3B-24) should be used in lanes and turn bays designated for the exclusive use of a turning movement, including turn bays, except where engineering judgment determines that physical conditions or other markings (such as a dotted extension of the lane line through the taper into the turn bay) clearly discourage unintentional use of a turn bay by through vehicles. Lane-use arrow markings should also be used in lanes from which movements are allowed that are contrary to the normal rules of the road (see Drawing B of Figure 3B-13). The last sentence of this paragraph was placed in a new paragraph

When used in turn lanes, at least two arrows should be used, one at or near the upstream end of the full-width turn lane and one an appropriate distance upstream from the stop line or intersection (see Drawing A of Figure 3B-11).

Where opposing offset channelized left-turn lanes exist, lane-use arrow markings should be placed near the downstream terminus of the offset left-turn lanes to reduce wrong-way movements (see Figure 2B-17)1.

21 Option:

An additional arrow or arrows may be used in a turn lane. When arrows are used for a short turn lane, the second (downstream) arrow may be omitted based on engineering judgment.

Support:

An arrow at the downstream end of a turn lane can help to prevent wrong way movements.

Standard:

Where through lanes approaching an intersection become mandatory turn lanes, <u>turn</u> laneuse arrow markings (see <u>Drawing A of Figure 3B-11</u> and Figure <u>3B-24</u> <u>3B-21</u>) shall be used and shall be accompanied by standard signs.

Guidance:

Where through lanes approaching an intersection become mandatory turn lanes, ONLY word markings (see Figure 3B-23 3B-17) should be used in addition to the required turn lane-use arrow markings and signs (see Sections 2B.19 2B.29 and 2B.20 2B.30). These markings and signs should be placed well in advance of the turn and should be repeated as necessary to provide the through motorist advance notification to vacate the lane prevent entrapment and to help the road user select the appropriate lane in advance of prior to reaching a point where roadway geometrics or a queue of waiting vehicles forces the motorist to make an unintended turn (see Drawing A of Figure 301-11 3B-11).

Option:

On freeways or expressways where a through lane becomes a mandatory exit lane, lane-use arrow markings may be used on the approach to the exit in the dropped lane and in an adjacent optional through-or-exit lane if one exists.

Lane-use, lane-reduction, and wrong-way arrow markings shall be designed as shown in Figure 3B-24 and in the "Standard Highway Signs and Markings" book (see Section 1A.11). Not needed

Figure 3B-21. Examples of Standard Arrows for Pavement Markings

Figure 3B-22. Examples of Lane-Use Control Word and Arrow Pavement Markings

Section 3B.24 Wrong-Way Arrows
 3 B.20 Contains paragraphs 36 and 37 from existing Section

Guidance:

1

4

5

6

7

8

10

11 12

13

14

15

16

17

18

19

20 21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

39

40

41

42

43

Where crossroad channelization or ramp geometrics do not make wrong-way movements difficult, the appropriate lane-use arrow should be placed in each lane of an exit ramp near the crossroad terminal where it will be clearly visible to a potential wrong-way road user (see Figure 2B-182B-12). Option:

The wrong-way arrow markings shown in Drawing D in Figure 3B-24 3B-21 may be placed near the downstream terminus of a ramp as shown in Figures 2B-182B-12 and 2B-192B-13A, or at other locations where lane-use arrows are not appropriate, to indicate the correct direction of traffic flow and to discourage drivers from traveling in the wrong direction.

Section 3B.24 3B.25 Chevron and Diagonal Crosshatch Markings

Option:

Chevron and diagonal crosshatch markings may be used to discourage travel on certain paved areas, such as shoulders, gore areas, flush median areas between solid double yellow center line markings or between white channelizing lines approaching obstructions in the roadway (see Section 3B.10 and Figure 3B-15), between solid double yellow center line markings forming flush medians or channelized travel paths at intersections (see Figures 3B-2 and 3B-5), buffer spaces between preferential lanes and general purpose lanes (see Figures 3D-2 and 3D-4), and at grade crossings (see Part 8).

Support:

Chevron or diagonal markings are used to discourage travel on certain paved areas, such as shoulders, neutral areas, and flush median areas.

Guidance:

Chevron markings should be used:

- A. On approaches to obstructions in the roadway (see Section 3B.13), or
- B. For channelized travel paths on approaches to intersections (see Figure 2B-12), or
- C. In buffer spaces between preferential lanes and general-purpose lanes (see Drawing A of Figure 3E-2), or
- D. In the neutral area of exit ramp and entrance ramp gores (see Figure 3B-8, Drawing A of Figure 3B-9, and Figure 3B-10), or
- E. In the neutral area of bifurcations created from open-road tolling lanes that bypass a conventional toll plaza, or
- F. In neutral areas, where used, at access and egress points to and from a managed-lane facility (see Figures 2G-9, 2G-10, 2G-22, 2G-23, and 2G-25) and,
- G. In neutral areas of islands (see Figures 3J-1 through 3J-3).

38 Option:

Chevron markings may be supplemented with white retroreflective or internally illuminated raised pavement markers (see Sections 3B.15 and 3B.17) for enhanced nighttime visibility.

Chevron markings may be used at other locations for special emphasis where traffic flows in the same general direction as determined by engineering judgment.

Standard:

When <u>chevron erosshatch</u> markings are used in paved areas that separate traffic flows in the same general direction, they shall be white <u>and they shall be shaped as chevron markings</u>, with the point of each chevron facing toward approaching traffic, as shown in Figure 3B-8, Drawing A of Figure 3B-9, Figure 3B-10, <u>and Drawing C of Figure 3B-15</u> and Figures 3J-1 through 3J-3.

Guidance:

Diagonal markings for opposing directions of traffic should be used:

- A. On approaches to obstructions in the roadway (see Figure 3B-15), or
- B. In flush median areas between double solid yellow center line markings (see Figure 3B-5), or
- C. In buffer spaces between preferential lanes and general-purpose lanes (see Drawing D of Figure 3E-4).

Option:

Diagonal markings may be used on paved shoulders or in no-parking zones.

<u>Diagonal markings may be used at other locations for special emphasis where traffic flows in the opposite direction as determined by engineering judgment.</u>

Standard:

When <u>diagonal erosshatch</u> markings are used in paved areas that separate opposing directions of traffic, they shall be yellow diagonal markings that slant away from traffic in the adjacent travel lanes, as shown in Figures 3B-2 and 3B-5 and Drawings A and B of Figure 3B-15.

When <u>diagonal erosshatch</u> markings are used on paved shoulders <u>or in on-street no-parking zones</u> (see <u>Figure 3B-24</u>), they shall be diagonal markings that slant away from traffic in the adjacent travel lane. The diagonal markings shall be yellow when used on the left-hand shoulders of the roadways of divided highways and on the left-hand shoulders of one-way streets or ramps. The diagonal markings shall be white when used on right-hand shoulders.

Guidance:

Except as provided in Paragraph 13, The ehevrons and diagonal lines used for erosshatch chevrons and diagonal markings should be at least 12 inches wide for roadways having a posted or statutory speed limit of 45 mph or greater, and at least 8 inches wide for roadways having posted or statutory speed limit of less than 45 mph, and at least 4 inches wide on roadways where the operating speed is less than 25 mph. The longitudinal spacing of the chevrons or diagonal lines should be determined by engineering judgment considering factors such as speeds and desired visual impacts. The chevrons and diagonal lines should form an angle of approximately 30 to 45 degrees with the longitudinal lines that they intersect.

Diagonal markings used in on-street no-parking zones should be white.

34 Option

The lines used for diagonal markings in no-parking zones may be 4 inches wide (see Figure 3B-24).

Section 3B.17 3B.26 Do Not Block Intersection Markings

Option:

Do Not Block Intersection markings may be used to mark the edges of an intersection area that is in close proximity to a signalized intersection, railroad crossing, or other nearby traffic control that might cause vehicles to stop within the intersection and impede other traffic entering the intersection. If authorized by law, Do Not Block Intersection markings with appropriate signs may also be used at other locations.

Standard:

If used, Do Not Block Intersection markings (see Figure 3B-18-3B-23) shall consist of one of the following alternatives:

- A. Wide solid white lines that outline the intersection area that vehicles must not block;
- B. Wide solid white lines that outline the intersection area that vehicles must not block and a white word message such as DO NOT BLOCK or KEEP CLEAR;
- C. Wide solid white lines that outline the intersection area that vehicles must not block and white cross-hatching within the intersection area; or
- D. A white word message, such as DO NOT BLOCK or KEEP CLEAR, within the intersection area that vehicles must not block.

Do Not Block Intersection markings shall be accompanied by one or more DO NOT BLOCK INTERSECTION (DRIVEWAY) (CROSSING) (R10-7) signs (see Section 2B.53-2B.63), one or more DO NOT STOP ON TRACKS (R8-8) signs (see Section 8B.09-8B.07), or one or more similar signs.

Figure 3B-23. Do Not Block Intersection Markings

Section 3B.19 3B.27 Parking Space Markings The sequence of some of the paragraphs has been revised

Support:

 Marking of parking space boundaries encourages more orderly and efficient use of parking spaces where parking turnover is substantial. Parking space markings tend to prevent encroachment into fire hydrant zones, bus stops, loading zones, approaches to intersections, curb ramps, and clearance spaces for islands and other zones where parking is restricted. The first two sentences are not needed Examples of parking space markings are shown in Figure 3B-21. The last sentence was edited and

relocated to later in the section

Standard:

On-street parking space markings shall be white.

Support:

Examples of on-street parking space markings are shown in Figure 3B-24.

Option:

Blue lines may supplement white parking space markings of each parking space designated for use only by persons with disabilities (see Figure 3B-24).

Support:

Additional parking space markings for the purpose of designating spaces for use only by persons with disabilities are discussed in Section 3B.20-3B.22 and illustrated in Figure 3B-22-3B-19. The design and layout of accessible parking spaces for persons with disabilities is provided in the "Americans with Disabilities Act Accessibility Guidelines (ADAAG)" (see Section 1A.11). Not needed

Figure 3B-24. Examples of Parking Space Markings

Section 3B.21 Speed Measurement Markings Section deleted

Section 3B.22 3B.28 Speed Reduction Markings

38 Support:

Speed reduction markings (see Figure 3B-28-3B-25) are transverse markings that are placed on the roadway within a lane (along both edges of the lane) in a pattern of progressively reduced spacing to give drivers the impression that their speed is increasing. These markings might be placed in advance of an unexpectedly severe horizontal or vertical curve or other roadway feature where drivers need to decelerate prior to reaching the feature and where the desired reduction in speeds has not been achieved by the installation of warning signs and/or other traffic control devices.

Speed Reduction Markings have been shown to enhance safety around curves and locations with a history of run off the road crashes when applied in combination with horizontal alignment warning signs (See Section 2C.05).

Guidance:

If used, speed reduction markings should be reserved for unexpected curves and should not be used on long tangent sections of roadway or in areas frequented mainly by local or familiar drivers, (e.g., school zones). If used, speed reduction markings should supplement the appropriate warning signs and other traffic control devices and should not substitute for these devices.

Standard:

If used, Sspeed reduction markings shall be a series of white transverse lines on both sides of the lane that are perpendicular to the center line, edge line, or lane line. The longitudinal spacing between the markings shall be progressively reduced from the upstream to the downstream end of the marked portion of the lane. The second sentence was reduced to a Guidance statement and made into its own paragraph

Guidance:

The longitudinal spacing between the markings should be progressively reduced from the upstream to the downstream end of the marked portion of the lane.

Speed reduction markings should not be greater than 12 inches in width, and should not extend more than 18 inches into the lane.

Standard:

Speed reduction markings shall not be used only in lanes that do not have a longitudinal line (center line, edge line, or lane line) on both sides of the lane.

Figure 3B-25. Example of the Application of Speed Reduction Markings

Section 3B.25 3B.29 Speed Hump Markings

Standard:

If speed hump markings are used, they shall be a series of white markings placed on a speed hump to identify its location. If markings are used for a speed hump that does not also function as a crosswalk or speed table, the markings shall comply with Option A, B, or C shown in Figure 3B-29-3B-26. If markings are used for a speed hump that also functions as a crosswalk or speed table, the markings shall comply with Option A or B shown in Figure 3B-30-3B-27.

Option:

Where used, center line markings, lane line markings, and edge lines may be discontinued on the profile of the speed hump.

Standard:

Where a speed hump specifically incorporates a crossing movement for pedestrians, bicycles, equestrians, etc. and functions as a raised crosswalk, crosswalk markings (see Chapter 3C) shall be provided.

Figure 3B-26. Pavement Markings for Speed Humps without Crosswalks
Figure 3B-27. Pavement Markings for Speed Tables or Speed Humps with
Crosswalks

Section 3B.26 3B.30 Advance Speed Hump Markings

42 Option:

Advance speed hump markings (see Figure 3B-31-3B-28) may be used in advance of speed humps or other engineered vertical roadway deflections such as dips where added visibility is desired or where such deflection is not expected.

Advance <u>word</u> pavement <u>wording markings</u> such as BUMP or HUMP (see Section 3B.20) may be used on the approach to a speed hump either alone or in conjunction with advance speed hump markings. Appropriate advance warning signs may be used in compliance with Section 2C.29 <u>2C.28</u>.

Standard:

If advance speed hump markings are used, they shall be a series of eight white 12-inch transverse lines that become longer and are spaced closer together as the vehicle approaches the speed hump or other deflection. If advance markings are used, they shall comply with the detailed design shown in Figure 3B-31-3B-28.

Guidance:

If used, advance speed hump markings should be installed in each approach lane.

Figure 3B-28. Advance Warning Markings for Speed Humps

Section 3B.31 Markings for Diamond Interchange with Transposed Alignment Crossroad

Support:

Markings used in a diamond interchange with transposed alignment crossroad can be advantageous for minimizing wrong-way movements. The potential for wrong-way movements is greatest at the intersections where the alignment becomes transposed.

Standard:

On the transposed alignment, each direction shall be considered a one-way roadway whereas the edge line convention shall be in accordance with Section 3B.09. Both yellow and white edge lines shall be used.

<u>A lane-use arrow (see Section 3B.23) shall be used in each approach lane at the crossing point.</u> Support:

Section 3C.11 contains information on crosswalks and pedestrian movements for diamond interchanges with a transposed alignment crossroad.

Standard:

Flush median islands (see Section 3J.03) shall not be used to divide the inverted flow of traffic. *Guidance:*

Edge line and lane lines extensions (see Section 3B.11) should be provided through the crossing points.

34 Support:

Figure 3B-29 illustrates an example of pavement markings for a diamond interchange with a transposed alignment crossroad.

Figure 3B-29. Example of Pavement Markings for a Diamond Interchange with a Transposed Alignment Crossroad

CHAPTER 3C. CROSSWALKS

Section 3B.18 3C.01 Crosswalk Markings General

Standard:

Crosswalk markings shall be provided at non-intersection crosswalk locations.

Support:

Crosswalk markings provide guidance for pedestrians who are crossing roadways by defining and delineating paths on approaches to and within signalized intersections, and on approaches to other intersections where traffic stops.

In conjunction with signs and other measures, crosswalk markings help to alert road users of a designated pedestrian crossing point across roadways at locations that are not controlled by traffic control signals or STOP or YIELD signs.

At non-intersection locations, crosswalk markings legally establish the crosswalk.

Option:

For added visibility, the area of the crosswalk may be marked with white diagonal lines at a 45-degree angle to the line of the crosswalk or with white longitudinal lines parallel to traffic flow as shown in Figure 3B-19. This paragraph relocated to Section 3C.07 and edited

When diagonal or longitudinal lines are used to mark a crosswalk, the transverse crosswalk lines may be omitted. This type of marking may be used at locations where substantial numbers of pedestrians cross without any other traffic control device, at locations where physical conditions are such that added visibility of the crosswalk is desired, or at places where a pedestrian crosswalk might not be expected.

Guidance:

If used, the diagonal or longitudinal lines should be 12 to 24 inches wide and separated by gaps of 12 to 60 inches. The design of the lines and gaps should avoid the wheel paths if possible, and the gap between the lines should not exceed 2.5 times the width of the diagonal or longitudinal lines. This paragraph relocated to new Sections 3C.06, 3C.07, and 3C.08

Support:

Detectable warning surfaces mark boundaries between pedestrian and vehicular ways where there is no raised curb. Detectable warning surfaces are required by 49 CFR, Part 37 and by the Americans with Disabilities Act (ADA) where curb ramps are constructed at the junction of sidewalks and the roadway, for marked and unmarked crosswalks. Detectable warning surfaces contrast visually with adjacent walking surfaces, either light-on-dark, or dark-on-light. The "Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" (see Section 1A.11-1A.05) contains specifications for design and placement of detectable warning surfaces.

<u>Provisions for aesthetic treatments for the interior portion of a legally established crosswalk are</u> contained in Section 3H.03.

Standard:

If paving materials are used to function as the white transverse lines to establish a marked crosswalk, white additives shall be part of the mixture to produce a white surface. The white paving materials shall be retroreflective.

Section 3C.02 Application of Crosswalk Markings Contains paragraphs 7, 8, 9, and 10 from existing Section 3B.18

Support:

Chapter 4F-4J contains information on Pedestrian Hybrid Beacons. Section 4L.03-4S.03 contains information regarding Warning Beacons to provide active warning of a pedestrian's presence. Section 4N.02-4U.02 contains information regarding In-Roadway Warning Lights at crosswalks. Chapter 7C

contains information on school crosswalks. Chapter 7D contains information regarding school crossing supervision.

Guidance:

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

17

18

22

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

44

Crosswalk lines-markings should not be used indiscriminately. An engineering study should be performed before a marked crosswalk is installed at a location away from a traffic control signal or an approach controlled by a STOP or YIELD sign. The engineering study should consider the number of lanes, the presence of a median, the distance from adjacent signalized intersections, the pedestrian volumes and delays, the average daily traffic (ADT), the posted or statutory speed limit or 85thpercentile speed, the geometry of the location, the possible consolidation of multiple crossing points, the availability of street lighting, and other appropriate factors.

The following criteria should be considered in an engineering study for the installation of a marked crosswalk:

- A. Total number of approach lanes,
- B. The presence of a median,
- C. The distance from adjacent signalized intersections where crosswalks are provided,
- 16 D. Pedestrian volumes,
 - E. Pedestrian ages,
 - F. Pedestrian delays,
- G. Average daily traffic (ADT), 19
- H. Speed limit or the 85th-percen speed. 20
- 21 I. The geometry of the crossing location,
 - J. The possible consolidation of multiple crossing points,
- 23 K. The availability of street lighting, and
 - L. Other appropriate factors.

New marked crosswalks alone, without other measures designed to reduce traffic speeds, shorten crossing distances, enhance driver awareness of the crossing, and/or provide active warning of pedestrian presence, should not be installed across uncontrolled roadways where the speed limit exceeds 40 mph and either any of the following conditions exist:

- A. The roadway has four or more lanes of travel without a raised median or pedestrian refuge island and an ADT of 12,000 vehicles per day or greater; or
- B. The roadway has four or more lanes of travel with a raised median or pedestrian refuge island and an ADT of 15,000 vehicles per day or greater, or
 - C. The posted speed limit is 40 mph or greater, or

D.A crash study reveals that multiple-threat crashes are the <u>predominant crash type on a multi-</u> lane approach or when adequate visibility cannot be provided by parking prohibitions.

At locations controlled by traffic control signals or on approaches controlled by STOP or YIELD signs, crosswalk lines markings should be installed where engineering judgment indicates they are needed to direct pedestrians to the proper crossing path(s).

Section 3C.03 Design of Crosswalk Markings Contains paragraphs 4, 11, 12, and 17 40 from existing Section 3B.18

41 Support:

42 Section 3B.21-3B.19 contains information regarding placement of stop line markings near 43 crosswalk markings.

Standard:

1 When crosswalk lines are used, they shall consist of solid white lines that mark the crosswalk. 2 They shall not be less than 6 inches or greater than 24 inches in width. Crosswalk markings shall be white. When used, transverse lines shall not be less than 6 inches or greater than 24 inches in 3 4 width. 5 Support: 6 The allowable upper limit approaching 24 inches for the width of the transverse lines is normally applied where no stop or yield line is used in advance of the crosswalk or when approach speeds exceed 7 8 35 miles per hour. 9 Crosswalk markings are classified as basic or high visibility. Basic crosswalk markings consist of 10 two transverse lines. High visibility markings consist of longitudinal lines parallel to traffic flow with 11 or without transverse lines. Figure 3C-1 presents examples of crosswalk markings. 12 **Standard:** 13 Except as provided in Paragraph 5, the minimum width of a marked crosswalk shall be 6 feet. 14 At a non-intersection crosswalk where the posted speed limit is 40 mph or greater, the 15 minimum width of the crosswalk shall be 8 feet. 16 Guidance: 17 Because non-intersection pedestrian crossings are generally unexpected by the road user, warning 18 signs (see Section 2C.50-2C.55) and high visibility crosswalk markings (such as shown in Figure 3C-1) 19 should be installed for all marked-crosswalks at non-intersection locations-and adequate visibility 20 should be provided by parking prohibitions. 21 Option: 22 Added visibility may be provided by parking prohibitions on the approach to marked crosswalks. 23 **Standard:** 24 Where curb ramps are provided, crosswalk markings shall be located so that the curb ramps 25 are within the extension of the crosswalk markings. 26 Guidance: 27 Transverse crosswalk markings should extend across the full width of pavement or to the edge of 28 the intersecting crosswalk to discourage diagonal walking between crosswalks. 29 **Section 3C.04 Basic Crosswalks** 30 Support: 31 The basic crosswalk marking design is limited to two parallel transverse lines (See Figure 3C-1). 32 Option: 33 Basic crosswalk markings may be used if an engineering study determines that establishing a 34 crosswalk would be beneficial to: 35 A. Define where the channelization of pedestrians or other non-motorized users is necessary to 36 facilitate crossing the roadway. 37 B. Alert motorists to the location of where pedestrians and other non-motorized users may be 38 expected when crossing the roadway. 39 C. Establish a crosswalk at a controlled intersection. 40 D. Fulfill a legal need to mark the crosswalk. Figure 3C-1. Examples of Crosswalk Markings 41

Option:

42 43 Section 3C.05 High-Visibility Crosswalks

Notice of Proposed Amendments - Part 3

High-visibility crosswalk markings may be used where additional conspicuity is desired for a crosswalk over basic transverse crosswalk markings.

Support:

High-visibility crosswalk markings are limited to the Longitudinal Bar, Perpendicular, and Double Paired designs (See Figure 3C-1).

High-visibility crosswalk markings can provide benefits to crosswalk operations including:

- A. Providing greater detection distances for the approaching motorist.
- B. Establishing a crosswalk where substantial numbers of pedestrians cross without any other traffic control device.
 - C. Establishing a crosswalk at an uncontrolled intersection.
- D. Emphasizing the location where a high number of conflicts between turning motorists and users of the crosswalk are expected.
- E. Improving visibility of the crosswalk location for otherwise difficult to detect pedestrians or other non-motorized users of the crosswalk.
 - F. Establishing a school crossing.

Standard:

The minimum number of individual longitudinal elements to establish a high-visibility crosswalk shall be three. For the double-paired crosswalk design (see Section 3C.08), a coupling set of two longitudinal bars shall be considered to be one individual longitudinal element.

The dimensions of the individual longitudinal element and the lateral spacing between subsequent individual longitudinal elements for a high-visibility crosswalk shall be uniform when establishing the crosswalk.

The dimensions of the individual longitudinal element and the lateral spacing between subsequent individual longitudinal elements for a high-visibility crosswalk shall be uniform on both sides of a median refuge island if one is present.

Guidance:

The dimensions of the individual longitudinal element and the lateral spacing between subsequent individual longitudinal elements for a high-visibility crosswalk should be uniform when establishing separate crosswalks on multiple approaches to the same intersection.

The individual longitudinal elements of a high-visibility crosswalk should be angled such that they are parallel to approaching traffic.

Section 3C.06 Longitudinal Bar Crosswalks

Support:

The longitudinal bar crosswalk marking design provides for improved detection and recognition over the basic crosswalk for people with low vision and cognitive impairments.

Standard:

The width of an individual longitudinal bar shall not be less than 12 inches or greater than 24 inches.

The lateral spacing between subsequent longitudinal bars shall not be less than 12 inches or greater than 60 inches. The lateral spacing of the longitudinal bars shall not exceed 2.5 times the width of a longitudinal bar.

Section 3C.07 Perpendicular Crosswalks

43 Support:

Perpendicular crosswalks implement a pattern where interior longitudinal bars are perpendicular to the transverse lines used to define the limits of the crosswalk.

Since the longitudinal component of the perpendicular crosswalk marking design is similar to the benefits provided by the longitudinal bar crosswalk design, the perpendicular crosswalk design is normally used to discourage or prohibit diagonal walking between crosswalks.

Standard:

1

2

3

4

5

6

7

8

9

10

11

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

40

41

42

43

The transverse lines used to establish the limits of the perpendicular crosswalk shall not be less than 6 inches or greater than 24 inches in width.

The width of an individual interior longitudinal bar shall not be less than 12 inches or greater than 24 inches.

The lateral spacing between subsequent interior longitudinal bars shall not be less than 12 inches or greater than 60 inches. The lateral spacing of the interior longitudinal bars shall not exceed 2.5 times the width of an interior longitudinal bar.

12 Option:

Where it may be necessary to alleviate a parallax phenomenon due to approaching roadway geometry that curves or to accommodate low approach angles of the approaching motorist, the interior longitudinal bars may be rotated up to 45 degrees to the transverse lines to remain parallel to approaching traffic.

Section 3C.08 Longitudinal Bar Pair Crosswalks

Support:

Longitudinal bar pair crosswalks can provide the same benefits as other high visibility crosswalk designs with the opportunity for less maintenance.

Longitudinal bar pair crosswalks can be useful in locations that are susceptible to slip and fall incidents exacerbated by extreme or inclement weather, or in locations where high motorcycle or bicycle use is expected in order to maximize wheel traction with the road surface.

Standard:

The width of an individual longitudinal bar that establishes one-half of the bar pair shall not be less than 8 inches or greater than 12 inches. The lateral space between successive individual longitudinal bars within the same bar pair shall be equal to the width of one longitudinal bar.

The lateral spacing between each of the longitudinal bars in a bar pair shall not be less than 24 inches or greater than 60 inches, or 2.5 times the width of the total width of a bar pair.

Longitudinal bar pair crosswalks shall not be installed with accompanying transverse lines.

Section 3C.05 3C.09 Crosswalk Markings at Roundabouts Circular Intersections

Standard:

<u>Crosswalk markings shall not be provided</u> Pedestrian crosswalks shall not be marked to or from the central island of roundabouts.

Guidance:

If pedestrian facilities are provided, crosswalks (see Section 3B.18) should be marked across roundabout entrances and exits to indicate where pedestrians are intended to cross.

Crosswalks should be a minimum of 20 feet from the edge of the circulatory roadway.

39 Support

Various arrangements of crosswalks at roundabouts are illustrated in the figures in this Chapter.

Not needed

<u>Chapter 3D provides figures that illustrate examples of crosswalk markings in circular intersections.</u>

Section 3C.10 Crosswalks for Exclusive Pedestrian Phases that Permit Diagonal

Crossings

Option:

When an exclusive pedestrian phase that permits diagonal crossing of an intersection is provided at a traffic control signal, a marking as shown in Figure 3B-20-3C-2 may be used for the crosswalk.

Paragraph 16 from existing Section 3B.18

Guidance:

The segments of the crosswalk marking that facilitate the diagonal crossing should not use highvisibility crosswalk markings.

Figure 3C-2. Example of Crosswalk Markings for an Exclusive Pedestrian Phase that Permits a Diagonal Crossing

Section 3C.11 Crosswalks at Diamond Interchanges with a Transposed Alignment Crossroad

Support:

<u>Pedestrian crossing movements at a diamond interchange with a transposed alignment crossroad are</u> provided at the crossover points where motor vehicle traffic becomes inverted.

Pedestrian crossing movements provided downstream on the ramp terminals can violate driver expectancy. Devices such as the pedestrian hybrid beacon and the rectangular-rapid flashing beacon do not alleviate these deficiencies in this setting.

Pedestrian crossing movements provided downstream on the ramp terminals can disorient pedestrians with limited vision or cognitive impairments by subjecting the pedestrian to cross the same ramp twice.

Guidance:

<u>Crossings for pedestrians at diamond interchanges with a transposed alignment crossroad should</u> <u>be consolidated and provided where pedestrian desire lines have been demonstrated or established.</u>

The most direct pedestrian paths should be provided to minimize pedestrians whom may cross outside of crosswalks where drivers are less likely to expect them.

Option:

Where the pedestrian movement is facilitated using the median on a shared-use path, Destination Guide signs for shared-use paths may be used (see Section 9D.12).

Support:

Figure 3B-29 illustrates the location of pedestrian crossings at diamond interchanges with a transposed alignment crossroad.

Section 31.06-3C.12 Pedestrian Islands and Medians

35 Support:

Raised islands or medians of sufficient width that are placed in the center area of a street or highway can serve as a place of refuge for pedestrians who are attempting to cross at a midblock or intersection location. Center islands or medians allow pedestrians to find an adequate gap in one direction of traffic at a time, as the pedestrians are able to stop, if necessary, in the center island or median area and wait for an adequate gap in the other direction of traffic before crossing the second half of the street or highway. The minimum widths for accessible refuge islands and for design and placement of detectable warning surfaces are provided in the "Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" (see Section 1A.11-1A.05).

1	CHAPTER 3C 3D. ROUNDABOUT CIRCULAR INTERSECTION MARKINGS
2	Section 3C.01 3D.01 General
3	Support:
4 5	A roundabout (see definition in Section 1A.13) is a specific type of circular intersection designed to control speeds and having specific traffic control features. Not needed
6	Guidance:
7 8	Pavement markings and signing for a roundabout should be integrally designed to correspond to the geometric design and intended lane use of a roundabout.
9 10	Markings on the approaches to a roundabout and on the circulatory roadway should be compatible with each other to provide a consistent message to road users and should facilitate movement through
11 12 13 14 15	the roundabout such that vehicles do not have to change lanes within the circulatory roadway in order to exit the roundabout in a given direction. The markings should supplement the signing, both conveying the optional and mandatory movements such that road users will know to choose the proper lane in the approach to the roundabout and remain in that lane throughout departure from the circulatory roadway.
16	Support:
17 18 19 20 21	Figure 3C-13D-1 provides an example of the pavement markings for approach and circulatory roadways at a roundabout. Figure 3C-2 shows the options that are available for lane use pavement marking arrows on approaches to roundabouts. Figures 3C-3-3D-2 through 3C-14-3D-8 illustrate examples of markings for roundabouts of various geometric and lane-use configurations. First two sentences are not needed
22 23	Traffic control signals, or pedestrian hybrid beacons, and rectangular rapid flashing beacons (see Part 4) are sometimes used at roundabouts to facilitate the crossing of pedestrians or to meter traffic.
24 25	Section <u>8C.12-8A.12</u> contains information about roundabouts that contain or are in close proximity to grade crossings.
26 27	Section 9C.04-9E.05 contains information regarding bicycle lane markings at roundabouts. This paragraph relocated from existing Section 3C.02
28 29	Figure 3D-1. Example of Markings for Approach and Circulatory Roadways at a Roundabout
30	Figure 3D-2. Example of Markings for a One-Lane Roundabout
31 32	Figure 3D-3. Example of Markings for a Two-Lane Roundabout with One- and Two-Lane Approaches (2 sheets)
33 34	Figure 3D-4. Example of Markings for a Two-Lane Roundabout with One-Lane Exits
35 36	Figure 3D-5. Example of Markings for a Two-Lane Roundabout with Two-Lane Exits
37 38	Figure 3D-6. Example of Markings for a Two-Lane Roundabout with a Double Left Turn
39	Figure 3D-7. Example of Markings for a Two-Lane Roundabout with a Double Right
40	Turn
41 42	Figure 3D-8. Example of Markings for a Diamond Interchange with Two Circular-Shaped Roundabout Ramp Terminals
43	Section 3C.02-3D.02 White Lane Line Pavement Markings for Roundabouts

44

Standard:

1 Multi-lane approaches to roundabouts shall have lane lines.

A through lane on a roadway that becomes a dropped lane (mandatory <u>left-turn</u> or <u>right-turn</u> lane) at a roundabout shall be marked with a dotted white lane line in accordance with Section <u>3B.04-3B.07</u>.

Guidance:

2

3

5

6

78

9

10

11

12

13

14 15

16

17 18

24

25

26

27

29

32

33

35

36

37

38

39

Multi-lane roundabouts should have lane line markings within the circulatory roadway to <u>continuously</u> channelize traffic <u>in the circulatory roadway and through the departure movement.</u> to the appropriate exit lane.

Standard:

Continuous concentric lane lines shall not be used within the circulatory roadway of roundabouts.

Option:

If broken lane line markings are used in the circulatory roadway of multi-lane roundabouts, the spacing of a broken lane line may be altered to reduce the gap between 10-ft lane lines (down to a 10-ft space between lines).

A buffer space, also referred to as striped islands, may be used on the approaches to multilane roundabouts including the circulatory roadway to separate traffic lanes, discourage lane changing, and/or compensate for off-tracking of larger trucks and vehicles.

- 19 roundabouts.
- 20 Support:
- Reducing the spacing between lines of a broken lane line allows better delineation of the lower radius
 curves typically found in circular intersections.
- 23 Support:

Section 9C.04 contains information regarding bicycle lane markings at roundabouts. This Paragraph relocated to new Section 3D.01

Section 3C.03 3D.03 Edge Line Pavement Markings for Roundabout Circulatory Roadways

28 Guidance:

A white edge line should be used on the outer (right-hand) side of the circulatory roadway.

Where a white edge line is used for the circulatory roadway, it should be as follows (see Figure $\frac{3C}{4-3D-1}$):

- A. A solid line adjacent to the splitter island, and
- *B.* A wide dotted line across the lane(s) entering the roundabout.

34 Standard:

Edge lines and edge line extensions shall not be placed across the exits from the circulatory roadway at roundabouts.

Option:

A yellow edge line may be placed around the inner (left-hand) edge of the circulatory roadway (see Figure 3C-1-3D-1) and may be used to channelize traffic (see Drawing B of Figure 3C-4-3D-3).

- 40 Section 3C.04 3D.04 Yield Lines for Roundabouts
- 41 **Standard:**
- A yield line (see Section 3B.19) shall be used at multilane roundabout entries to indicate the point in each entry lane behind which vehicles are required to yield to all circulating lanes at the entrance to a roundabout (see Figure 3D-2).

_						
S	11	n	n	_	**	۴٠
	u	U	U	u	ш	L.

See Section 2B.09 regarding the TO ALL LANES (R1-2bP) plaque use beneath the YIELD sign.

3 Option:

A yield line may be used at single-lane roundabout entries to indicate the point behind which vehicles are required to yield at the entrance to a roundabout.

Option:

A yield line (see Section 3B.16 <u>3B.19</u>) may be used to indicate the point behind which vehicles are required to yield at the entrance to a roundabout (see Figures 3C-1 <u>3D-1</u> and <u>3D-2</u>).

Section 3C.05 Crosswalks Markings at Roundabouts Relocated to new Section 3C.05

Section <u>3C.06</u> <u>3D.05</u> <u>Word, and Symbol, and Arrow Pavement Markings for Roundabouts</u> Paragraphs 1, 4, 5, and 6 relocated to new Section 3D.06

12 Option:

YIELD (word) and YIELD AHEAD (symbol or word) pavement markings (see Figure 3C-1-3D-1) may be used on approaches to roundabouts.

Word and/or route shield pavement markings may be used on an approach to or within the circulatory roadway of a roundabout to provide route and/or destination guidance information to road users (see Figure 3C 14-3D-8).

Section 3D.06 Arrow Pavement Markings for Roundabouts Contains paragraphs 1, 4, 5, and 6 from existing Section 3C.06

Guidance:

<u>Lane-use arrow pavement markings should not be used on single-lane approaches to circular intersections.</u>

On two-lane approaches to circular intersections, where the left-hand lane on the approach is for left turns, and the right-hand lane contains an optional movement for through- and right-turns, laneuse arrow pavement markings should not be used in the right-hand lane containing the optional movement.

<u>Lane-use arrows should be used on approaches to circular intersections with dual left or dual right turns.</u>

Standard:

<u>Lane-use arrow pavement markings shall not be provided between a crosswalk and a wide</u> <u>dotted line across the lane(s) entering the circular roadway.</u>

Option:

Lane use arrows may be used on any approach to and within the circulatory roadway of any roundabout.

Where If lane-use arrows are used on the approaches to a roundabout, lane use arrows they may be either normal or fish hook elongated arrows, either with or without with an oval symbolizing the central island, as shown in Figure 3C 2.

Guidance:

If lane-use arrows are used on the approaches to a roundabout, the style used should match the style of lane-use arrows (normal or elongated) used on the regulatory lane-use signs on the approach.

<u>If lane-use arrow pavement markings are used.</u> within the circulatory roadway of multi-lane roundabouts, normal lane-use arrows (see Section <u>3B.20-3B.23</u> and Figure <u>3B-24-3B.21</u>) should be used, with an oval symbolizing the central island.

1 2	On multi-lane approaches with double left-turn and/or double right-turn lanes, lane-use arrows as shown in Figures 3C-7 and 3C-8 should be used.
3	Support:
4	Details and sizes of the standard and elongated arrows that can be used for circular intersections are
5	contained in the "Standard Highway Signs and Markings" book.
6	Section 3C.07 3D.07 Markings for Other Circular Intersections
7	Support:
8	Other circular intersections include, but are not limited to, rotaries, traffic circles, and residential
9	traffic calming designs. Incorporated into the next paragraph
10	Option:
11	The markings shown in this Chapter may be used at other circular intersections, such as rotaries,
12	<u>traffic circles</u> , and <u>residential traffic calming designs</u> , if engineering judgment indicates that their
13	presence will benefit drivers, pedestrians, or other road users.
14	

CHAPTER 3D-3E. MARKINGS FOR PREFERENTIAL LANES MARKINGS FOR MOTOR VEHICLES

Section 3E.01 General Existing Section 3D.01 was changed to new Section 3E.03 Support:

Preferential lanes are established for one or more of a wide variety of special uses, including, but not limited to, high-occupancy vehicle (HOV) lanes, electronic toll collection (ETC) lanes, high-occupancy toll (HOT)-priced managed lanes, bicycle lanes, bus only lanes, taxi only lanes, and light rail transit only lanes. Paragraph 1 from existing Section 3D.01

This chapter contains the pavement marking provisions for preferential lanes used by motor vehicles and light rail transit. Part 9 contains information for pavement markings for bicycle lanes.

Chapter 3H contains information for the use and application of colored pavement that can be used in preferential lanes to supplement the pavement markings described in this Chapter.

Section 3D.02 3E.02 Preferential Lane Longitudinal Markings for Motor Vehicles Support:

Preferential lanes can take many forms depending on the level of usage and the design of the facility. They might be barrier-separated or buffer-separated from the adjacent general-purpose lanes, or they might be contiguous with the adjacent general-purpose lanes. Barrier-separated preferential lanes might be operated in a constant direction or be operated as reversible lanes. Some reversible preferential lanes on a divided highway might be operated counter-flow to the direction of traffic on the immediately adjacent general-purpose lanes. See Section 1A.13-1C.02 for definitions of terms.

Preferential lanes might be operated full-time (24 hours per day on all days), for extended periods of the day, part-time (restricted usage during specific hours on specified days), or on a variable basis (such as a strategy for a managed lane).

Standard:

Longitudinal pavement markings The left- and right-hand edge lines used for preferential lanes that are adjacent to general purpose lanes where traffic is flowing in the same direction be in accordance with Table 3E-1. as follows (these same requirements are presented in tabular form in Table 3D-1):

- A. Barrier-separated, non-reversible preferential lane—the longitudinal pavement markings for preferential lanes that are physically separated from the other travel lanes by a barrier or median shall consist of a normal solid single yellow line at the left-hand edge of the travel lane(s), and a normal solid single white line at the right-hand edge of the travel lane(s) (see Drawing A in Figure 3D-1).
- B. Barrier-separated, reversible preferential lane—the longitudinal pavement markings for reversible preferential lanes that are physically separated from the other travel lanes by a barrier or median shall consist of a normal solid single white line at both edges of the travel lane(s) (see Drawing B in Figure 3D-1).
- C. Buffer-separated (left-hand side) preferential lane—the longitudinal pavement markings for a full-time or part-time preferential lane on the left-hand side of and separated from the other travel lanes by a neutral buffer space shall consist of a normal solid single yellow line at the left-hand edge of the preferential travel lane(s) and one of the following at the right-hand edge of the preferential travel lane(s):
- 1. A wide solid double white line along both edges of the buffer space where crossing the buffer space is prohibited (see Drawing A in Figure 3D-2).
- 2. A wide solid single white line along both edges of the buffer space where crossing the buffer space is discouraged (see Drawing B in Figure 3D-2).

4

5

6 7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41 42

43

44

45

46

- 3. A wide broken single white line along both edges of the buffer space, or a wide broken single white lane line within the allocated buffer space (resulting in wider lanes), where crossing the buffer space is permitted (see Drawing C in Figure 3D-2).
- D. Buffer-separated (right-hand side) preferential lane—the longitudinal pavement markings for a full-time or part-time preferential lane on the right-hand side of and separated from the other travel lanes by a neutral buffer space shall consist of a normal solid single white line at the right-hand edge of the preferential travel lane(s) if warranted (see Section 3B.07) and one of the following at the left-hand edge of the preferential travel lane(s) (see Drawing D in Figure 3D-2):
- 1. A wide solid double white line along both edges of the buffer space where crossing the buffer space is prohibited.
- 2. A wide solid single white line along both edges of the buffer space where crossing of the buffer space is discouraged.
- 3. A wide broken single white line along both edges of the buffer space, or a wide broken single white line within the allocated buffer space (resulting in wider lanes), where crossing the buffer space is permitted.
- 4. A wide dotted single white lane line within the allocated buffer space (resulting in wider lanes) where crossing the buffer space is permitted for any vehicle to perform a right-turn maneuver.
- E. Contiguous (left-hand side) preferential lane—the longitudinal pavement markings for a full-time or part-time preferential lane on the left-hand side of and contiguous to the other travel lanes shall consist of a normal solid single yellow line at the left-hand edge of the preferential travel lane(s) and one of the following at the right-hand edge of the preferential travel lane(s):
- A wide solid double white lane line where crossing is prohibited (see Drawing A in Figure 3D-3).
- 2. A wide solid single white lane line where crossing is discouraged (see Drawing B in Figure 3D-3).
- 3. A wide broken single white lane line where crossing is permitted (see Drawing C in Figure 3D-3).
- F. Contiguous (right-hand side) preferential lane—the longitudinal pavement markings for a full-time or part-time preferential lane on the right-hand side of and contiguous to the other travel lanes shall consist of a normal solid single white line at the right-hand edge of the preferential travel lane(s) if warranted (see Section 3B.07) and one of the following at the lefthand edge of the preferential travel lane(s) (see Drawing D in Figure 3D-3):
 - 1. A wide solid double white lane line where crossing is prohibited.
 - A wide solid single white lane line where crossing is discouraged.
 - A wide broken single white lane line where crossing is permitted.
- 4. A wide dotted single white lane line where crossing is permitted for any vehicle to perform a right-turn maneuver. The same information that is shown in text format in Items A through F is already shown in a tabular format in Table 3E-1

Table 3E-1. Standard Edge Line and Lane Line Markings for Preferential Lanes

If there are two or more preferential lanes for traffic moving in the same direction, the lane lines between the preferential lanes shall be normal width broken white lines.

Preferential lanes for motor vehicles shall also be marked with the appropriate word or symbol pavement markings in accordance with Section 3D.01 and shall have appropriate regulatory signs in accordance with Sections 2G.03 through 2G.07.

Support:

Figure 3E-1 illustrates pavement markings used for barrier-separated preferential lanes.

Guidance:

Engineering judgment should determine the need for supplemental devices such as tubular markers, traffic cones, or other channelizing devices (see Chapter 3H-3I). Paragraph 13 from

existing Section 3D.01

Where preferential lanes and other travel lanes are separated by a buffer space wider than 4 feet and crossing the buffer space is prohibited, chevron markings (see Section 3B.24 3B.25) should be placed in the buffer area (see Drawing A in Figure 3D-2-3E-2). The chevron spacing should be 100 feet or greater.

The buffer space for a conventional road should be designed so that it is not misinterpreted as onstreet parking, a bicycle lane, or any other type of lane.

Option:

If a full-time or part-time contiguous preferential lane is separated from the other travel lanes by a wide broken single white line (see Drawing C in Figure 3D-3-3E-3), the spacing or skip pattern of the line may be reduced and the width of the line may be increased.

Support:

Figure 3E-2 illustrates pavement markings used for buffer-separated preferential lanes. Figure 3E-3 illustrates pavement markings used for contiguous preferential lanes.

Guidance:

At direct exits from a preferential lane, dotted white line markings should be used to separate the tapered or parallel deceleration lane for the direct exit (including the taper) from the adjacent continuing preferential through lane, to reduce the chance of unintended exit maneuvers.

Standard:

On a divided highway, a part-time counter-flow preferential lane that is contiguous to the travel lanes in the opposing direction shall be separated from the opposing direction lanes by the standard reversible lane longitudinal marking, a normal width broken double yellow line (see Section 3B.03 and Drawing A of Figure 3D-4). If a buffer space is provided between the part-time counter-flow preferential lane and the opposing direction lanes, a normal width broken double yellow line shall be placed along both edges of the buffer space (see Drawing B of Figure 3D-4). Signs (see Section 2B.26-2B.36), lane-use control signals (see Chapter 4M-4T), or both shall be used to supplement the reversible lane markings on a divided highway where a part-time counter-flow preferential lane is present.

The deleted information is being shown in a new Table 3E-2

On a divided highway, a full-time counter-flow preferential lane that is contiguous to the travel lanes in the opposing direction shall be separated from the opposing direction lanes by a solid double yellow center line marking (see Drawing C of Figure 3D-4). If a buffer space is provided between the full-time counter-flow preferential lane and the opposing direction lanes, a normal width solid double yellow line shall be placed along both edges of the buffer space (see Drawing D of Figure 3D-4). The deleted information is being shown in a new Table 3E-2

The longitudinal pavement markings used for preferential lanes that are adjacent to general purpose lanes where traffic is flowing in the opposite direction (see Figure 3E-4) shall be in accordance with Table 3E-2.

Table 3E-2. Longitudinal Payement Markings Used for Preferential Lanes

Support:

Figure 3E-4 illustrates pavement markings used for counter-flow preferential lanes on divided highways or on transitions to and from other divided highways such as bridges and crossovers.

Option:

Cones, tubular markers, or other channelizing devices (see Chapter 3H-3I) may also be used in addition to longitudinal markings to separate the opposing lanes when a counter-flow preferential lane operation is in effect.

Figure 3E-1. Markings for Barrier-Separated Preferential Lanes

Figure 3E-2. Markings for Buffer-Separated Preferential Lanes (2 sheets)

Figure 3E-3. Markings for Contiguous Preferential Lanes

Figure 3E-4. Markings for Counter-Flow Preferential Lanes on Divided Highways

Section 3D.01-3E.03 Preferential Lane Word and Symbol Markings Paragraphs in this section were reordered, paragraph 1 was relocated to new Section 3E.01 and paragraph 13 was relocated to new Section 3E.02

Support:

Sections 3B.20 through 3B.22 contain information on general applications of word and symbol markings.

Standard:

When a lane is assigned full or part time to a particular class or classes of vehicles, the preferential lane word and symbol markings described in this Section and the preferential lane longitudinal markings described in Section 3D.02 shall be marked with one or more of the following word or symbol markings for the preferential lane use specified: used.

- A. HOV lane—the preferential lane-use marking for high-occupancy vehicle lanes shall consist of white lines formed in a diamond shape symbol or the word message HOV. The diamond shall be at least 2.5 feet wide and 12 feet in length. The lines shall be at least 6 inches in width.
- B. HOT Priced managed lane or ETC Account-Only lane—except as provided in Paragraph 8, the preferential lane-use marking for a HOT lane or an ETC Account-Only lane shall consist of a word marking or pictograph using the name of the ETC payment system required for use of the lane, such as E-Z PASS ONLY.
- C. Bicycle lane—the preferential lane-use marking for a bicycle lane shall consist of a bicycle symbol or the word marking BIKE LANE (see Chapter 9C and Figures 9C-1 and 9C-3 through 9C-6).
- D-C. Bus only lane or bus stop—the preferential lane-use marking for a bus only lane shall consist of the word marking BUS ONLY or BUS STOP.
- E-D. Taxi only lane or taxi stand the preferential lane-use marking for a taxi only lane shall consist of the word marking TAXI ONLY or TAXI STAND.
- F_E. Light rail transit lane—the preferential lane-use marking for a light rail transit lane shall consist of the word marking LRT ONLY.
- G-F. Other type of preferential lane—the preferential lane-use markings shall consist of a word marking appropriate to the restriction.

Guidance:

If multiple preferential lane uses are allowed in a single lane, engineering judgment should be used to prioritize and select the preferential lane word or symbol markings to be installed contingent on characteristics and needs of the road user. Consideration should be given to preferential lane word or symbol markings that can also be supported or supplemented through regulatory signing rather than

the selection of preferential lane word or symbol markings that would exist alone or otherwise encompass all allowable uses that cannot be disseminated by a regulatory sign(s).

Standard:

Pavement word or symbol markings for motorcycles and Inherently Low Emission Vehicles (ILEV) shall not be used to mark the preferential lane if motorcycles and ILEVs are allowed to use the preferential lane.

Support:

Motorcycles and Inherently Low Emission Vehicles (ILEV) that are allowed to use a preferential lane are granted an exception such as through an established High Occupancy Vehicle (HOV) regulation. Communicating that motorcycles and ILEVs are allowed to use the preferential lane is accomplished through regulatory signing (see Sections 2G.03 and 2G.04) that complements HOV signing.

Standard:

Static or changeable message regulatory signs (see Sections 2G.03 to 2G.07) shall be used with preferential lane word or symbol markings.

All preferential lane word and symbol markings shall be white and shall be positioned laterally in the approximate center of the preferential lane.

Where a preferential lane use exists contiguous to a general-purpose lane or is separated from a general-purpose lane by a flush buffered space that can be traversed by motor vehicles, the preferential lane shall be marked with one or more of the following symbol or word markings for the preferential lane use specified:

If two or more preferential lane uses are permitted in a single lane, the symbol or word marking for each preferential lane use shall be installed.

Option:

Preferential lane-use symbol or word markings may be omitted at toll plazas where physical conditions preclude the use of the markings (see Section 3E.01).

Guidance:

All longitudinal pavement markings, as well as word and symbol pavement markings, associated with a preferential lane shall should end at approximately where the Preferential Lane Ends (R3-12a or R3-12c) sign (see Section 2G.07) designating the downstream end of the preferential only lane restriction is installed. Relocated from the beginning of this section and reduced to Guidance

The spacing of the markings should be based on engineering judgment that considers the prevailing operating speed, block lengths, distance from intersections, and other factors that affect clear communication to the road user.

Support:

Markings spaced as close as 80 feet apart might be appropriate on city streets, while markings spaced as far as 1,000 feet apart might be appropriate for freeways. Not needed

Guidance:

In addition to a regular spacing interval, the preferential lane marking should be placed at strategic locations such as major decision points, direct exit ramp departures from the preferential lane, and along access openings to and from adjacent general-purpose lanes. At decision points, the preferential lane marking should be placed on all applicable lanes and should be visible to approaching traffic for all available departures. At direct exits from preferential lanes where extra emphasis is needed, the use of word markings (such as "EXIT" or "EXIT ONLY") in the deceleration lane for the direct exit and/or on the direct exit ramp itself just beyond the exit gore should be considered.

Option:

A numeral indicating the vehicle occupancy requirements established for a high-occupancy vehicle lane may be included in sequence after the diamond symbol or HOV word message.

Section 3E.04 Markings for Part-Time Travel on a Shoulder

Support:

Shoulders are sometimes used to add capacity to a roadway in peak hour conditions to provide for transit or HOV priority or to provide higher throughput at reduced speeds when open to all traffic.

A shoulder that has been opened to travel on a permanent, rather than part-time basis is considered to be a travel lane and is signed and marked in accordance with other provisions of this Manual.

Standard:

When part-time travel on a shoulder is open to all traffic, pavement word and symbol markings shall not be used in the shoulder.

When a shoulder is assigned part-time to a particular class or classes of vehicles, the shoulder shall be marked with one or more pavement word markings that identify the special use of the shoulder such as BUS ONLY, TRANSIT ONLY, HOV, or instead of the HOV pavement word marking, white lines formed in a diamond shape symbol (see Section 3E.03). Pavement word or symbol marking shall be provided in the shoulder immediately after an exit ramp (see Figure 3E-5) or immediately departing an intersection at the full-width shoulder (see Figure 3E-6). Appropriate regulatory signing (see Section 2G.03) shall be installed with the pavement word or symbol markings.

The channelizing line emanating from the entrance ramp shall be dashed through the intersecting alignment of the shoulder to the theoretical gore (see Drawings A and B of Figure 3E-5). At exit ramps, the channelizing line proceeding from the theoretical gore across the intersecting alignment of the shoulder shall be dashed (see Figure 3E-5).

If used, the extension of the channelizing line at entrance ramps proceeding from the theoretical gore across the opening of the on-ramp alignment shall be dashed (see Drawing C of Figure 3E-5) where it is demonstrated that traffic entering from an on-ramp stops or yields to traffic on the shoulder of the highway mainline.

An additional outside solid edge line shall be provided on the shoulder in accordance with Sections 3B.09 and 3B.10.

Guidance:

<u>Changes in edge line pattern or direction should occur at appropriate regulatory signs.</u> <u>ption:</u>

At locations where traffic is allowed to enter, exit, or merge with the shoulder, a dashed edge line may be used either in a continuous manner or angled to the pavement edge (see Figure 3E-6).

When part-time travel on a shoulder is limited to transit vehicles only, a yield line pavement marking may be installed unaccompanied by a Yield sign on the shoulder where transit vehicles on the shoulder yield to traffic entering from an on-ramp (see Drawing A of Figure 3E-5).

Shoulders that allow only transit vehicles may use red colored pavement (see Section 3H.07).

Standard:

If used, red colored pavement shall be discontinued on the shoulder through the influence area of the ramp (see Figure 3H-5).

Figure 3E-5. Markings for Part-Time Travel on Shoulder and Application of Pavement Word Markings

Figure 3E-6. Markings for Part-Time Travel on Shoulder Through an Intersection

CHAPTER 3E-3F. MARKINGS FOR TOLL PLAZAS

Section 3E.01 3F.01 Markings for Toll Plazas General

Support:

1

2

3

4

5

6 7

8

11 12

13

14

15

16

17

18 19

20

21

22

23

24

25

26 27

28

29

30

31

32

33

34

35

36

39

40

41

42

43

At toll plazas, pavement markings help road users identify the proper lane(s) to use for the type of toll payment they plan to use, to channelize movements into the various lanes, and to delineate obstructions in the roadway.

Section 3H.08 contains information on the use and application of purple colored pavement at toll plazas for vehicles with registered electronic toll collection (ETC) accounts.

9 Section 3F.02 Longitudinal Markings Contains paragraphs 5-8 from existing Section 3E.01

Guidance:

Solid white lane line markings should be used to separate toll lanes, payment methods, or to channelize movements at toll plazas.

Solid white lane line markings should begin at the upstream end of the full-width toll lane and be continued to the toll plaza.

Option:

For a toll plaza approach lane that is restricted to use only by vehicles with registered ETC accounts, the solid white lane line or edge line on the right-hand side of the ETC Account-Only lane and the solid white lane line or solid yellow edge line on the left-hand side of the ETC Account-Only lane may be supplemented with purple solid longitudinal markings placed contiguous to the inside edges of the lines defining the lane.

Standard:

If used, the purple solid longitudinal markings described in the previous-Paragraph 53 are used, the purple markings shall be a minimum of at least 3 inches in width wide, and a maximum width equal to the width of the line it supplements, and ETC Account-Only preferential lane word markings (see Section 3D.01) shall be installed within the lane.

Guidance:

If the purple solid longitudinal markings described in Paragraph 3 are used, the purple markings should not be wider than the line they supplement.

Standard:

Toll booths and the islands on which they are located are considered to be obstructions in the roadway and they shall be provided with markings that comply with the provisions of Section 3B.10 3B.13 and Chapter 3G-3J.

Option:

Longitudinal pavement markings may be omitted alongside toll booth islands between the approach markings and any departure markings.

37 Section 3F.03 Pavement Word and Symbol Markings

38 Support:

Section 3E.03 contains information on the use of pavement word and symbol markings for ETC Account-Only lanes not specific to toll plazas.

Standard:

Except as provided in Paragraph 4, when a lane on the approach to a toll plaza is restricted to use only by vehicles with registered ETC accounts, the ETC Account-Only lane word markings or

<u>pictograph</u> described in Section <u>3E.03 3D.01 and the preferential lane longitudinal markings</u> described in Section 3D.02 shall be used (see Figure 3H-6).

When one or more <u>open road tolling (ORT)</u> lanes that are restricted to use only by vehicles with registered ETC accounts bypass a mainline toll plaza on a separate alignment, these <u>pavement</u> word markings <u>and longitudinal markings or pictographs</u> shall be used on the approach to the point where the ORT lanes diverge from the lanes destined for the mainline toll plaza (see Figure 3H-6). Broken into 2 separate Paragraphs

Option:

Preferential lane-use symbol or word markings may be omitted at toll plazas where physical conditions or preclude the use of the markings.

Guidance:

If an ORT lane that is immediately adjacent to a mainline toll plaza is not separated from adjacent cash payment toll plaza lanes by a curb or barrier, then channelizing devices (see Section 3H.01 3I.01), and/or longitudinal payement markings that discourage or prohibit lane changing should be used to separate the ORT lane from the adjacent cash payment lane. This separation should begin on the approach to the mainline toll plaza at approximately the point where the vehicle speeds in the adjacent cash lanes drop below 30 mph during off-peak periods and should extend downstream beyond the toll plaza approximately to the point where the vehicles departing the toll plaza in the adjacent cash lanes have accelerated to 30 mph.

Section 3F.01—3G.01 Delineators—General

Support:

Delineators are particularly beneficial at locations where the alignment might be confusing or unexpected, such as at lane-reduction transitions and curves. Delineators are effective guidance devices at night and during adverse weather. An important advantage of delineators in certain locations is that they remain visible when the roadway is wet or snow covered.

Delineators are considered guidance devices <u>to help road users navigate the roadway alignment</u>, rather than warning devices.

Option:

Delineators may be used on long continuous sections of highway or through short stretches where there are changes in horizontal alignment.

Section 3F.02 3G.02 Delineator Design

Standard:

Delineators shall consist of retroreflective devices that are capable of clearly retroreflecting light under normal atmospheric conditions from a distance of 1,000 feet when illuminated by the high beams of standard automobile lights.

Retroreflective elements for delineators shall have a minimum <u>vertical and horizontal</u>, <u>or diametric</u> dimension of 3 inches.

Support:

Within a series of delineators along a roadway, delineators for a given direction of travel at a specific location are referred to as single delineators if they have one retroreflective element for that direction, double delineators if they have two identical retroreflective elements for that direction mounted together, or vertically elongated delineators if they have a single retroreflective element with an elongated vertical dimension to approximate the vertical dimension of two separate single delineators.

Option:

A vertically elongated delineator of appropriate size may be used in place of a double delineator.

Section 3F.03 3G.03 Delineator Application

Standard:

The color of delineators shall comply with the color of edge lines stipulated in Sections 3B.06 3A.03 and 3B.09.

A series of single delineators shall be provided on the right-hand side of freeways and expressways and on at least one side of interchange ramps, except when either Condition A or Condition B is met, as follows:

- A. On tangent sections of freeways and expressways when both of the following conditions are met:
- 1. Raised pavement markers are used continuously on lane lines throughout all curves and on all tangents to supplement pavement markings, and
 - 2. Roadside delineators are used to lead into all curves.
- **B.** On sections of roadways where continuous lighting is in operation between interchanges. Option:

Delineators may be provided on other classes of roads. A series of single delineators may be provided on the left hand side of roadways.

A series of single delineators may be provided on the left-hand side of roadways. The second sentence from the previous paragraph was provided in a separate paragraph Standard:

Delineators on the left-hand side of a two-way roadway shall be white (see Figure 3F-1-3G-1). *Guidance:*

A series of single delineators should be provided on the outside of curves on interchange ramps.

Where median crossovers are provided for official or emergency use on divided highways and where these crossovers are to be marked with pavement markings, a double yellow delineator should be placed on the left-hand side of the through roadway on the far side of the crossover for each roadway.

Double or vertically elongated delineators should be installed at <u>approximately</u> 100-foot intervals along acceleration and deceleration lanes.

A series of delineators should be used wherever guardrail or other longitudinal barriers are present along a roadway or ramp.

Option:

 Red delineators may be used on the reverse side of any delineator where it would be viewed by a road user traveling in the wrong direction on that particular ramp or roadway.

Delineators of the appropriate color may be used to indicate a lane reduction transition where either an outside or inside lane merges into an adjacent lane. This paragraph was relocated to the next paragraph and edited

Guidance:

Except as provided in Paragraph 11 of Section 3B.12, delineators of the appropriate color should be used to indicate a lane-reduction transition where either an outside or inside lane merges into an adjacent lane.

When used for lane-reduction transitions, the delineators should be installed adjacent to the lane or lanes reduced for the full length of the transition and should be so placed and spaced to show the reduction (see Section 3B.12 and Figure 3B-14).

Support:

Delineators are not necessary for traffic moving in the direction of a wider pavement or on the side of the roadway where the alignment is not affected by the lane reduction transition. Not needed Guidance:

On a highway with continuous delineation on either or both sides, delineators should be carried through transitions.

Option:

On a highway with continuous delineation on either or both sides, the spacing between a series of delineators may be closer. Moved to new Section 3G.04

Standard:

When used on a truck escape ramp, delineators shall be red.

Guidance:

Red delineators should be placed on both sides of truck escape ramps. The delineators should be spaced at 50 foot intervals for a distance sufficient to identify the ramp entrance. Delineator spacing beyond the ramp entrance should be adequate for guidance according to the length and design of the escape ramp. Moved to Section 3G.04 and edited

- 43 Section 3F.04 3G.04 Delineator Placement and Spacing
- 44 Guidance:

<u>Except as provided in Paragraph 2</u>, delineators should be mounted on suitable supports at a mounting height, measured vertically from the bottom of the lowest retroreflective device to the elevation of the near edge of the roadway, of approximately 4 feet.

Option:

When mounted on the face of or on top of guardrails or other longitudinal barriers, delineators may be mounted at a lower elevation than the normal delineator height recommended in Paragraph $2\underline{1}$.

Delineators should be placed 2 to 8 feet outside the outer edge of the shoulder, or if appropriate, in line with the roadside barrier that is 8 feet or less outside the outer edge of the shoulder.

Delineators should be placed at a constant distance from the edge of the roadway, except that where an obstruction intrudes into the space between the pavement edge and the extension of the line of the delineators, the delineators should be transitioned to be in line with or inside the innermost edge of the obstruction. If the obstruction is a guardrail or other longitudinal barrier, the delineators should be transitioned to be just behind, directly above (in line with), or on the innermost edge of the guardrail or longitudinal barrier.

<u>Delineators should not present a vertical or horizontal clearance obstacle for pedestrians.</u> Moved from existing Section 3A.04

Delineators should be spaced 200 to 530 feet apart on mainline tangent sections. Delineators should be spaced 100 feet apart on ramp tangent sections.

Option:

On a highway with continuous delineation on either or both sides, the spacing between a series of delineators may be closer. Moved from existing Section 3F.03

When uniform spacing is interrupted by such features as driveways and intersections, delineators which would ordinarily be located within the features may be relocated in either direction for a distance not exceeding one quarter of the uniform spacing. Delineators still falling within such features may be eliminated.

Delineators may be transitioned in advance of a lane transition or obstruction as a guide for oncoming traffic.

Guidance:

The spacing of delineators should be adjusted on approaches to and throughout horizontal curves so that several delineators are always simultaneously visible to the road user. The approximate spacing shown in Table $\frac{3F-1}{3G-1}$ should be used.

The spacing between red delineators that are placed on both sides of a truck escape ramp should not exceed 50 feet for a distance that is sufficient to identify the ramp entrance. The spacing between red delineators that are placed beyond the ramp entrance should be such that adequate guidance is provided based on the length and design of the escape ramp. Moved from existing Section 3F.03 and edited

Option:

When needed for special conditions, delineators of the appropriate color may be mounted in a closely-spaced manner on the face of or on top of guardrails or other longitudinal barriers to form a continuous or nearly continuous "ribbon" of delineation.

Support:

Examples of delineator installations are shown in Figure 3F-1-3G-1. Moved from Paragraph 6 of this section

Table 3G-1. Approximate Spacing for Delineators on Horizontal Curves
Figure 3G-1. Examples of Delineator Placement

CHAPTER 3G-3H COLORED PAVEMENT

Section 3G.01 3H.01 General Standardization of Application

Support:

Colored pavements consist of differently colored road paving materials, such as colored asphalt or concrete, or paint or other marking materials applied to the surface of a road or island to simulate a colored pavement.

If non-retroreflective colored pavement, including bricks and other types of patterned surfaces, is used as a purely aesthetic treatment and is not intended to communicate a regulatory, warning, or guidance message to road users, the colored pavement is not considered to be a traffic control device, even if it is located between the lines of a crosswalk. Relocated to new Section 3H.03 and edited

Standard:

If colored pavement is used within the traveled way, on flush or raised islands, or on shoulders to regulate, warn, or guide or otherwise communicate with traffic or if retroreflective colored pavement retroreflectivity is used, the colored pavement is shall be considered to be a traffic control device and shall be limited to the following colors and applications: specified in this Chapter.

- A. Yellow pavement color shall be used only for flush or raised median islands separating traffic flows in opposite directions or for left-hand shoulders of roadways of divided highways or one-way streets or ramps.
- B. White pavement color shall be used for flush or raised channelizing islands where traffic passes on both sides in the same general direction or for right-hand shoulders.

<u>Except where provided in Paragraph 4 of Section 3H.07</u>, colored pavements shall not be used as a traffic control device, unless the device is applicable at all times.

Guidance:

Colored pavements used as traffic control devices should be used only where they contrast significantly with adjoining paved areas.

Support:

The chromaticity coordinates that define the ranges of acceptable colors to be used in pavement marking applications are found in the Appendix to Subpart F of 23 CFR 655.

Standard:

<u>Colored pavement shall be limited to uses only where it supplements other markings as provided in this Manual.</u>

Support:

<u>Longitudinal pavement markings, crosswalks, pavement marking symbols, and elongated route markers are not considered colored pavements.</u>

Standard:

Colors other than those specified in this Chapter shall not be used for colored pavement.

38 <u>Section 3H.02</u> <u>Materials</u>

39 Option:

Colored pavements may be retroreflective.

Standard:

The intentional non-use of retroreflectivity shall not exempt colored pavement from the provisions of this Manual.

Guidance:

If marking materials applied to the roadway surface are used to simulate a colored pavement, consideration should be given to selecting pavement marking materials that will minimize loss of traction for pedestrians, bicyclists, etc. (see Paragraph 2 of Section 3A.02).

Support:

<u>Providing for retroreflectivity, such as incorporating glass beads, can increase the friction of pavement markings and can reduce the potential for slip and fall incidents.</u>

Installation of colored pavement to one lane or an area or portion of a multi-lane traveled way can create differentials in skid resistance values between the colored pavement and the general-purpose lanes that might be unexpected by the road user.

The acceleration of heavy vehicles might cause abnormal wear to colored pavement especially at bus stops. The selection of the material properties for these areas is important.

Section 3H.03 Aesthetic Treatments in Crosswalks

Support:

If non-retroreflective colored pavement, including bricks and other types of patterned surfaces, is used as a purely aesthetic treatment within the criteria presented in this Section and is not intended to communicate a regulatory, warning, or guidance message to road users, the colored pavement is not considered to be a traffic control device, even if it is located between the lines of a crosswalk.

Paragraph relocated from existing Section 3G.01

Guidance:

Since the right-of-way is dedicated exclusively to highway-related functions, a policy for using aesthetic treatments in crosswalks should consider whether their use or design is appropriate for the right-of-way.

Colored pavement located between crosswalk lines should not use colors or patterns that degrade the contrast of white crosswalk lines, or that might be mistaken by road users as a traffic control application. Paragraph relocated from existing Section 3G.01

Aesthetic treatments within crosswalks should only be used on roadways with a speed limit of 30 mph or less.

Support:

Examples of materials for the interior portions of a crosswalk include brick, paving bricks, paving stones, setts, cobbles, or other resources designed to simulate such paving. Examples of geometries for the interior portions of a crosswalk include honeycomb, lattice, mesh, grid, and regular polygon patterns. Examples of colors for the interior portions of a crosswalk incorporated into the material or geometry are brick red, rust, brown, burgundy, clay, tan, or similar earth tone equivalents (see Figure 3H-1).

Standard:

Patterns that constitute a purely aesthetic treatment for the interior portion of a crosswalk shall be devoid of advertising, pictographs, symbols, multiple color arrangements counter to Paragraph 4, and shall not implement elements of retroreflectivity.

Patterns that constitute a purely aesthetic treatment for the interior portion of a crosswalk shall not be designed to encourage other road users such as pedestrians to loiter in the crosswalk, engage in the pattern, or otherwise not encourage those users to vacate the street in an expedient manner.

Aesthetic treatments for the interior portions of crosswalks shall not be of a surface that can confuse vision-impaired pedestrians that rely on tactile treatments or cues for navigation.

Option:

1 2	<u>To create contrast, a gap of at least one-half of the width of the white transverse line used to</u> establish the crosswalk may be used between the white transverse crosswalk line and the aesthetic
3	treatment, such as unmarked pavement or a black contrast line.
4	Figure 3H-1. Examples of Colors for the Interior Portions of Crosswalks
5	Section 3H.04 Yellow-Colored Pavement
6	Standard:
7	If used, yellow-colored pavement shall be limited to:
8	A. Flush or raised median islands separating traffic flows in opposite directions,
9	B. Left-hand shoulders of divided highways, and
10	C. Left-hand shoulders of one-way streets or ramps.
11	Yellow-colored pavement shall not be incorporated into elements of the roadway that
12	<u>function as reversible lanes or two-way left turn lanes.</u>
13	Yellow-colored pavement shall not be used on channelizing islands where traffic travels in the
14 15	same general direction on both sides.
15	Option:
16 17	Yellow-colored pavement may be installed for the entire length of the roadway, island, or shoulder or for only a portion or portions of the roadway, island or shoulder.
18	Support:
19	Examples of applications of yellow-colored pavement are shown in Figure 3H-2.
20	Figure 3H-2. Examples of Application of Yellow-Colored Pavement
21	Section 3H.05 White-Colored Pavement
22	Standard:
23	If used, white-colored pavement shall be limited to:
24	A. Flush or raised channelizing islands where traffic passes on both sides in the same general
25	direction,
26	B. Right-hand shoulders,
27	C. Exit gore areas, and
28	D. Entrance gore areas.
29	Guidance:
30	When used on right-hand shoulders, white-colored pavement should be limited to areas not
31	intended for use by motor vehicle traffic except those shoulders designated for emergency use.
32	Option:
33	White-colored pavement may be installed for the entire length of the roadway, island, or shoulder,
34	or for only a portion or portions of the roadway, island or shoulder.
35 36	White-colored pavement may be used instead of chevron markings (see Sections 3B.13 and 3B.25) in neutral areas.
37	Support:
38	Examples of applications of white-colored pavement are shown in Figure 3H-3.
39	Figure 3H-3. Examples of Application of White-Colored Pavement
40	Section 3H.06 Green-Colored Pavement for Bicycle Facilities
41	Support:

Green-colored pavement is used to enhance the conspicuity of locations where bicyclists are expected to operate, and areas where bicyclists and other roadway traffic might have potentially conflicting weaving or crossing movements. Green-colored pavement is also used to enhance the conspicuity of word, symbol, and/or arrow pavement markings when these markings are used in certain bicycle facilities (see Figure 3H-4).

Standard:

- If used, green-colored pavement shall be limited to:
- A. Bicycle lanes (See Section 9E.01),
- B. Extensions of bicycle lanes through intersections (See Section 9E.03),
- C. Extensions of bicycle lanes through areas where motor vehicles enter an exclusive turn lane in which motor vehicles must weave across bicycle traffic in bicycle lanes,
 - D. Two-stage turn boxes (See Section 9E.11),
 - E. Bicycle Box (see Section 9E.12),
 - F. Bicycle detector symbol (See Section 9E.16), and
- 15 G. Separated bicycle lanes within the roadway.

Green-colored pavement shall not be incorporated into shared-use paths, shared-lane markings, crosswalks, separated bicycle lanes on an independent alignment, or electric-vehicle parking stations or parking stalls.

19 Option:

Green-colored pavement may be installed for the entire length of a bicycle lane or bicycle lane extension or for only a portion (or portions) of the bicycle lane or bicycle lane extension.

Green-colored pavement may be installed for the entire length of a physically-separated bikeway within the roadway or for only a portion (or portions) of the physically-separated bikeway.

Standard:

Green-colored pavement shall not be used instead of dotted lines used to extend a bicycle lane or a separated bicycle lane within a roadway across an intersection, driveway, or ramp. The pattern of the green-colored pavement shall match the pattern of the dotted lines, thus filling in only the areas that are directly between a pair of dotted line segments.

Guidance:

Appropriate regulatory (see Chapter 9B) or guide signing (see Chapter 9D) should be installed to provide related information to the presence of the colored pavement.

Figure 3H-4. Examples of Green-Colored Pavement

Section 3H.07 Red-Colored Pavement for Public Transit Systems

Support:

Red-colored pavement is used to enhance the conspicuity of locations, station stops or travel lanes in the roadway exclusively reserved for vehicles of public transit systems or multi-modal facilities where public transit is the primary mode. These public transit vehicles include buses, taxis, streetcars, trolleys, light-rail trains, and rapid transit fleets.

Optio Company

Red-colored pavement may be used where an engineering study determines that one or more of the following conditions are expected to result from its application:

A. Increased travel speeds will be expected by the public transport vehicle after an exclusive lane or facility is provided.

1 2	B. Reduced overall service time through the corresponding will be expected by the public transport vehicle,
3	C. Decreased rates of illegal parking or occupation of the transit or multi-mode lane or facility will
4	be expected.
5	Standard:
6	If used, red-co d pavement shall be applied only in lanes, areas, or locations where
7	general-purpose traffic is not allowed to use, queue, wait, idle, or otherwise occupy the lane, area
8	or location where red-colored pavement is used.
9	Red-colored payent shall be installed for the full width of the lane.
10	Option:
11	Red-colored pavement may be used for full-time or part-time operations.
12 13	Red-colored pavement may be installed for the entire length of a restricted lane or for only a portion (or portions) of the restricted lane.
14 15 16	Red-colored pavement may be installed in a broken pattern where entrance into the transit lane is permitted by general traffic, for example where general traffic is allowed in a transit lane in advance of a turn.
17	Standard:
18	Regulatory signs (see Sections 2B.02 and 2G.03) shall be used to establish the allowable use of
19	the lane, area, or location. Regulatory signs shall also be used when it is determined that other
20	vehicles will be allowed to enter the lane to turn or bypass queues.
21	Guidance:
22	If red-colored pavement is used on public transit facilities separated from the roadway or on
23 24	facilities on an independent alignment, it should be used only at the entrances to those facilities from roadways open to public travel.
25	
26	Support: Examples of applications of red-colored pavement are shown in Figure 3H-5.
27	Figure 3H-Examples of Application of Red-Colored Pavement
28	Section 3H.08 Purple-Colored Pavement for Electronic Toll Collection (ETC) Account-
29	Only Preferential Lanes
30	Standard:
31	Purple-colored pavement shall be limited to:
32	A. Lanes on the approach to a toll plaza where the lane is restricted to use only with a
33	registered ETC account, and B. Longs or approaches to an open read talling (ODT) collection facility that hypogens the
34 35	B. Lanes or approaches to an open-road tolling (ORT) collection facility that bypasses the physical toll plaza, where the ORT facility is restricted for use only by vehicles with registered
36	ETC accounts.
37	Purple-colored pavement shall not be used in an approach lane that also facilitates additional
38	payment methods downstream.
39	If used approaching a physical toll plaza, purple-colored pavement shall be flanked by white
40	solid longitudinal lines that establish the toll lane.
41	If used on an ORT collection facility that bypasses the physical toll plaza, purple-colored
42	pavement shall be flanked by appropriate edge lines, and if applicable in multi-lane bypasses,
43	appropriate longitudinal solid or broken white lane lines.

Option:

44

1	Purple-colored pavement may be installed for the entire length of a toll lane or ORT collection
2	facility or for only a portion (or portions) of the toll lane or ORT collection facility.
3	Support:
4	Figure 3H-6 illustrates an example of purple-colored pavement for use at toll plazas.
5	Figure 3H-6. Examples of Application of Purple-Colored Pavement
6	

CHAPTER 3H-3I. CHANNELIZING DEVICES USED FOR EMPHASIS OF PAVEMENT MARKING PATTERNS

Section 3H.01 3I.01 Channelizing Devices

Option:

 Channelizing devices, as described in (see Sections 6F.63 through 6F.73, and 6F.75, 6F.69 and as shown in Figure 6F-7) such as cones, tubular markers, vertical panels, and drums, lane separators, and raised islands, barricades may be used for general traffic control purposes such as adding emphasis to reversible lane delineation, channelizing lines, or islands, or bicycle facilities. Channelizing devices may also be used along a center line to preclude turns or along lane lines to preclude lane changing, as determined by engineering judgment.

Support:

Although they are not considered to be traffic control devices, raised islands (see Chapter 3J) are also sometimes used to channelize traffic.

Standard:

Except for color, the design of channelizing devices, including but not limited to retroreflectivity, minimum dimensions, and mounting height, shall comply with the provisions of Chapter $\frac{6F-6K}{6}$.

Except as provided in Paragraph 5, Tthe color of channelizing devices used outside of temporary traffic control zones shall be either orange or the same color as the pavement marking that they supplement, or for which they are substituted, in accordance with Section 3A.05.

Option:

The color of channelizing devices used to emphasize pavement marking patterns outside of temporary traffic control zones may be orange provided that the application of the orange-colored channelizing device is not permanent.

Support:

Emergency incidents and planned special events are the most common temporary traffic control zones that would justify orange channelizing devices to emphasize standard pavement marking colors. These events do not necessitate police officers or other authorized personnel to obtain and deploy channelizing devices that match the color of the existing pavement marking.

Standard:

For nighttime use, channelizing devices shall be retroreflective (as described in Part 6) or internally illuminated. On channelizing devices used outside of temporary traffic control zones, retroreflective sheeting or bands shall be white if the devices separate traffic flows in the same direction and shall be yellow if the devices separate traffic flows in the opposite direction or are placed along the left-hand edge line of a one-way roadway or ramp.

Guidance:

Channelizing devices should be kept clean and bright to maximize target value. Not needed

Section 3I.02 Tubular Markers

Standard:

<u>Tubular markers shall be made with a material that can be struck without causing damage to the impacting vehicle. Tubular markers shall be a minimum of 28 inches in height and shall be a minimum of 2 inches wide facing road users.</u>

Guidance:

- 1 Tubular markers should be affixed to the pavement or other surface either directly or by means of
 2 an attachment system that is affixed to the pavement or other surface. Tubular markers should be
 3 normally spaced no greater than N as cited in Section 3B.11.
- 4 Option:
- 5 Other spacing may be used based on engineering judgment.

1 CHAPTER 31-31. MARKING AND DELINEATION OF ISLANDS AND CURB 2 EXTENSIONS

Section 3I.01 3J.01 General

Support:

This Chapter addresses the <u>characteristics marking and delineation</u> of islands (see definition in Section <u>1A.13-1C.02</u>) and also curb extensions <u>designated by pavement markings as traffic control devices.</u> <u>Definitions, types, sizes, and other Ccriteria for the design of islands are set forth in "A Policy on Geometric Design of Highways and Streets" (see Section <u>1A.11-1A.05</u>).</u>

Section 3C.12 contains information on pedestrian islands and medians.

Sections 3H.04 and 3H.05 contain information on colored pavement that can be used within islands.

Option:

An island may be designated by curbs, pavement edges, pavement markings, channelizing devices, or other devices.

Section 3I.02 3J.02 Approach-End Treatment

Support:

An approach-end treatment to an island consists of longitudinal pavement markings and/or channelizing devices upstream of the island followed by a divergence of those pavement markings and/or channelizing devices concluding with a transition to other pavement markings that demarcate or outline the island (see Figure 3J-1).

<u>Section 3B.13 contains information on pavement marking that function as approach-end treatments for obstructions.</u>

Guidance:

The ends of islands first approached by traffic should be preceded by diverging longitudinal pavement markings on the roadway surface, provided an approach-end treatment, or curb markings (see Section 3J.04), or both to guide vehicles into desired paths of travel along the island edge.

Support:

The neutral area between approach end markings that can be readily crossed even at considerable speed sometimes contains slightly raised (usually less than 1 inch high) sections of coarse aggregate or other suitable materials to create rumble sections that provide increased visibility of the marked areas and that produce an audible warning to road users traveling across them. For additional discouragement to driving in the neutral area, bars or buttons projecting 1 to 3 inches above the pavement surface are sometimes placed in the neutral area. These bars or buttons are designed so that any wheel encroachment within the area will be obvious to the vehicle operator, but will result in only minimal effects on control of the vehicle. Such bars or buttons are sometimes preceded by rumble sections or their height is gradually increased as approached by traffic. Not needed

Guidance:

When raised bars or buttons that project more than 1 inch above the pavement surface are used to create a rumble section in these neutral areas, they raised bars or buttons should be marked with white or yellow retroreflective materials, as determined by the direction or directions of travel they separate.

Standard:

Channelizing devices, when used in advance of islands having raised curbs, shall not be placed in such a manner as to constitute an unexpected obstacle. Not needed Option:

Pavement markings may be used with raised bars to better designate the island area. Not needed

1	Figure 3J-1. Example of Markings for Approach End-Treatment to an Island
2	Section 3J.03 Islands Designated by Pavement Markings
3	Standard:
4	Except as provided in Paragraph 2, islands formed by pavement markings only shall be
5	established using channelizing lines, and shall be white when separating traffic flows in the same
6	general direction or yellow when separating opposing directions of traffic.
7	If a continuous flush median island formed by pavement markings separating travel in
8 9	opposite directions is used, two sets of solid double yellow lines shall be used to form the island (as shown in see Figures 3B-2 and 3B-5). Other markings in the median island area, such as diagonal
10	lines (see Section 3B.25), shall also be yellow, except crosswalk markings which shall be white (see
11	Section 3B.18 see Chapter 3C). Relocated from existing Section 3B.03 and edited
12	If used, chevrons and diagonal markings (see Section 3B.25) within the island shall be the
13	same color as the channelizing line.
14	Option:
15	Both chevrons and diagonal markings of the same color may be used within the same island based
16	on engineering judgment.
17	Support:
18	Figure 3J-2 illustrates examples of islands designated by pavement markings.
19	Figure 3J-2. Examples of Islands Designated by Pavement Markings
20	Section 3J.04 Curb Markings for Raised Islands Paragraphs 7 through 12 from existing
21	Section 3B.23
22	Standard:
23	Where curbs are marked for delineation or visibility purposes, the colors shall comply with
24	the general principles of markings (see Section 3A.05-3A.03).
25	Guidance:
26	Retroreflective solid yellow <u>curb</u> markings should be placed on the approach ends of raised
27	medians and curbs of islands that are located in the line of traffic flow where the curb serves to channel
28	traffic to the right of the obstruction (see Figure 3J-3).
29 30	Retroreflective solid white <u>curb</u> markings should be used when traffic is permitted to pass on either
31	side of the island (see Figure 3J-3).
31 32	The retroreflective area should be of sufficient length to denote the general alignment of the edge of the island along which vehicles travel, including the approach end, when viewed from the approach to
33	the island. Paragraph 2 of existing Section 3I.04
34	Support: Option:
35	Where the curbs of the islands become parallel to the direction of traffic flow or where the island is
36	illuminated or marked with delineators, it is not necessary to mark the curb markings may be
37	discontinued unless an based on engineering judgment or study indicates the need for this type of
38	delineation.
39	<u>Curb markings curbs</u> at openings in a continuous median island need not be marked may be omitted
40	unless an based on engineering judgment or study indicates the need for this type of marking.
41	Figure 3J-3. Example of Markings for Approach End-Treatment to a Channelized
42	Island
43	Section 3J.05 Pavement Markings for Raised Islands

Support:

1 Pavement markings for raised islands include the approach-end treatment (see Section 3J.02), channelizing lines, edge lines, and chevron or diagonal markings. 2 3 Option: 4 Solid yellow edge lines may be used adjacent to raised islands separating travel in opposite 5 directions (see Drawing A of Figure 3J-3). 6 **Standard:** 7 Except as provided in Paragraph 4 and 6, raised islands separating traffic flows in the same general direction shall be outlined with white channelizing lines (see Drawing A of Figure 3J-4). 8 9 Option: 10 Payement markings for smaller raised islands may be omitted based on engineering judgment. 11 Guidance: 12 Smaller raised islands that do not apply channelizing lines, edge lines, or chevron or diagonal lines 13 should be provided curb markings (see Section 3J.04). 14 Where traffic passes on the right of a raised island separating traffic flows in the same general 15 direction, a vellow edge line may be used adjacent to raised islands of discernible size or length instead of continuing the white channelizing line from the approach-end treatment (see Drawing B of Figure 16 17 3J-4). 18 Support: 19 Yellow edge lines adjacent to raised islands that separate traffic flows in the same general direction 20 can be advantageous as a countermeasure for wrong-way entry or travel if the yellow edge line is of 21 discernible length. 22 Option: 23 Chevron markings may be used in neutral areas formed by diverging channelizing lines at raised islands separating traffic flows in the same general direction. 24 25 Diagonal markings of an appropriate color may be used in buffer areas between the channelizing line and the raised island (see Figure 3J-5). 26 27 Figure 3J-4. Examples of Pavement Markings for Raised Islands 28 Figure 3J-5. Example of Diagonal Color Payement Markings for Channelizing Line 29 and the Raised Island Section 31.03 Island Marking Application—Section deleted; not needed 30 Section 31.04 Island Marking Colors Section deleted; paragraphs 2 and 3 relocated to new 31 Section 3J.04 32 33 Section 31.05-3J.06 Island Delineation 34 Standard: 35 Delineators installed on islands shall be the same colors as the related channelizing or edge 36 lines except that, when facing wrong-way traffic, they shall be red (see Section 3F.3 3G-3). 37 Each roadway through an intersection shall be considered separately in positioning 38

delineators to assure maximum effectiveness.

Option:

39

40

41

42

43

Retroreflective or internally illuminated raised pavement markers of the appropriate color may be placed on the pavement in front of the curb and/or on the top of curbed approach ends of raised medians and curbs of islands, as a supplement to or as a substitute for retroreflective curb markings.

Section 3J.07 Curb Extensions Designated by Pavement Markings

1	Sur	port:

<u>Curb extensions are used to extend the sidewalk or other pedestrian space, shorten crossing distances for pedestrians, alter the roadway geometry for speed control or channelizing, and for other purposes.</u>

<u>Curb extensions are typically created by physical infrastructure including concrete or asphalt, but</u> can also be designated by pavement markings.

For the purposes of this Section, the paved areas between the solid double line forming the curb extension (see Paragraph 4 of this Section) and the sidewalk or other roadside area are considered to be outside of the street.

Standard:

<u>Curb extensions formed by pavement markings shall be established using solid double lines.</u>

The color of the solid double line shall comply with the general principles of markings (see Section 3A.03).

Guidance:

<u>Physical separation or delineation should be provided where curb extensions are created by pavement markings and pedestrian travel can be expected within the area created by the curb extension.</u>

Option:

<u>Channelizing devices such as tubular markers (see Chapter 3I) may be used along the solid double line of a curb extension created by pavement markings.</u>

Other methods of physical separation may be used beyond the solid double line outside of the limits of the street.

Guidance:

Diagonal markings (see Section 3B.24) or colored pavement (see Chapter 3H) should be used within the marked curb extension to emphasize that the area is outside of the street.

26 Support:

Curb extensions are distinct from areas within the street such as shoulders, flush medians, or gore areas where travel is discouraged by the presence of diagonal markings (see Section 3B.24). Curb extensions designate areas outside of the street where travel is prohibited.

Guidance:

Where pedestrian travel can be expected within curb extensions created by pavement markings, adequate provisions should be made for pedestrians with disabilities.

Support:

Additional information on the design and construction of accessible facilities is found in publications listed in Section 1A.05 (see Publications 12 and 42).

Figure 3J-6 illustrates examples of curb extensions designated by pavement markings.

Figure 3J-6. Examples of Curb Extensions Designed by Pavement Markings

CHAPTER 3J-3K. RUMBLE STRIP MARKINGS

Section 3J.01 3K.01 Longitudinal Rumble Strip Markings

Support:

Longitudinal rumble strips consist of a series of rough-textured or slightly raised or depressed road surfaces intended to alert inattentive drivers through vibration and sound that their vehicle has left the travel lane. Shoulder rumble strips are typically installed along the shoulder near the travel lane. On divided highways, rumble strips are sometimes installed on the median side (left-hand side) shoulder as well as on the outside (right-hand side) shoulder. On two-way roadways, rumble strips are sometimes installed along the center line.

This Manual contains no provisions regarding the design and placement of longitudinal rumble strips. The provisions in this Manual address the use of markings in combination with a longitudinal rumble strip. Figure 3J-1-3K-1 illustrates markings used with or near longitudinal rumble strips.

Sentence moved from existing Paragraph 6 of this section

<u>Longitudinal rumble strip markings have been shown to be beneficial when applied in combination</u> with horizontal alignment warning signs to enhance safety around curves and locations with a history of run off the road crashes.

Option:

An edge line or center line may be located over a longitudinal rumble strip to create a rumble stripe.

Standard:

The color of an edge line or center line associated with a longitudinal rumble stripe shall be in accordance with Section $\frac{3A.05}{3A.03}$.

An edge line shall not be used in addition to a rumble stripe that is located along a shoulder.

Figure 3K-1. Examples of Longitudinal Rumble Strip Markings

Section 3J.02 3K.02 Transverse Rumble Strip Markings

Support:

Transverse rumble strips consist of intermittent narrow, transverse areas of rough-textured or slightly raised or depressed road surface that extend across the travel lanes to alert drivers to unusual vehicular traffic conditions. Through noise and vibration, they attract the attention of road users to features such as unexpected changes in alignment and conditions requiring a reduction in speed or a stop.

This Manual contains no provisions regarding the design and placement of transverse rumble strips that approximate the color of the pavement. The provisions in this Manual address the use of markings in combination with a transverse rumble strip.

Standard:

Except as otherwise provided in Section 6F.87 6M.06 for TTC zones, if the color of a transverse rumble strip used within a travel lane is not the color of the pavement, the color of the transverse rumble strip shall be either black or white.

Guidance:

White transverse rumble strips used in a travel lane should not be placed in locations where they could be confused with other transverse markings such as stop lines or crosswalks.

Section 4A.01 Types

Support:

The following types and uses of highway traffic signals are discussed in Part 4: traffic control signals; bicycle signal faces; pedestrian signals heads; hybrid beacons; rectangular rapid flashing beacons; emergency-vehicle traffic control signals; traffic control signals for one-lane, two-way facilities; traffic control signals for freeway entrance ramps; traffic control signals for movable bridges traffic signals; toll plaza traffic signals; flashing beacons; lane-use control signals; and in-roadway warning lights.

Section 4A.02 Definitions Relating to Highway Traffic Signals

Support:

Definitions and aeronyms pertaining to Part 4 are provided in Sections 1A.13 and 1A.14.

Section 4D.04 4A.02 Meanings of Vehicular Signal Indications Paragraphs in this Section were relocated to new Sections 4A.03 and 4A.04

Support:

The "Uniform Vehicle Code" (see Section 1A.0511) is the primary source for the standards for the meanings of vehicular signal indications to both vehicle operators and pedestrians as provided in this Sections 4A.04 and 4A.05, and the standards for the meanings of separate pedestrian signal head indications as provided in Section 4E.02 4A.06.

The physical area that is defined as being "within the intersection" is dependent upon the conditions that are described in the definition of intersection in Section $\frac{1.13}{10.02}$.

Section 4A.03 Meanings of Steady Vehicular Signal Indications

Text was relocated from Items A,
B, and C in Paragraph 3 in existing Section 4D.04

Standard:

The following meanings shall be given to <u>steady</u> highway traffic signal indications for vehicles and pedestrians:

- A. Steady green signal indications shall have the following meanings:
 - 1. Vehicular traffic facing a CIRCULAR GREEN signal indication is permitted to proceed straight through or turn right or left or make a U-turn movement except as such movement is modified by lane-use signs, turn prohibition signs, lane markings, roadway design, separate turn signal indications, or other traffic control devices.

Such vehicular traffic, including vehicles turning right or left or making a U-turn movement, shall yield the right-of-way to:

- (a) Pedestrians lawfully within an associated crosswalk, and
- (b) Other vehicles lawfully within the intersection.

In addition, vehicular traffic turning left or making a U-turn movement to the left shall yield the right-of-way to other vehicles approaching from the opposite direction so closely as to constitute an immediate hazard during the time when such turning vehicle is moving across or within the intersection.

2. Vehicular traffic facing a GREEN ARROW signal indication, displayed alone or in combination with another signal indication, is permitted to cautiously enter the intersection only to make the movement indicated by such arrow, or such other movement as is permitted by other signal indications displayed at the same time.

Such vehicular traffic, including vehicles turning right or left or making a U-turn movement, shall yield the right-of-way to:

- (a) Pedestrians lawfully within an associated crosswalk, and
- (b) Other vehicles lawfully within the intersection.
- 3. Pedestrians facing a CIRCULAR GREEN signal indication, unless otherwise directed by a pedestrian signal indication or other traffic control device, are permitted to proceed across the roadway within any marked or unmarked associated crosswalk. The pedestrian shall

yield the right-of-way to vehicles lawfully within the intersection or so close as to create an immediate hazard at the time that the green signal indication is first displayed.

4. Pedestrians facing a GREEN ARROW signal indication, unless otherwise directed by a pedestrian signal indication or other traffic control device, shall not cross the roadway.

B. Steady yellow signal indications shall have the following meanings:

1. Vehicular traffic facing a steady CIRCULAR YELLOW signal indication is thereby warned that the related green movement or the related flashing arrow movement is being terminated or that a steady red signal indication will be displayed immediately thereafter when vehicular traffic shall not enter the intersection. The rules set forth concerning vehicular operation under the movement(s) being terminated shall continue to apply while the steady CIRCULAR YELLOW signal indication is displayed.

2. Vehicular traffic facing a steady YELLOW ARROW signal indication is thereby warned that the related GREEN ARROW movement or the related flashing arrow movement is being terminated. The rules set forth concerning vehicular operation under the movement(s) being terminated shall continue to apply while the steady YELLOW ARROW signal indication is displayed.

3. Pedestrians facing a steady CIRCULAR YELLOW or YELLOW ARROW signal indication, unless otherwise directed by a pedestrian signal indication or other traffic control device shall not start to cross the roadway.

C. Steady red signal indications shall have the following meanings:

 1. Vehicular traffic facing a steady CIRCULAR RED signal indication, unless entering the intersection to make another movement permitted by another signal indication, shall stop at a clearly marked stop line; but if there is no stop line, traffic shall stop before entering the crosswalk on the near side of the intersection; or if there is no crosswalk, then before entering the intersection; and shall remain stopped until a signal indication to proceed is displayed, or as provided below.

Except when a traffic control device is in place prohibiting a turn on red or a steady RED ARROW signal indication is displayed, vehicular traffic facing a steady CIRCULAR RED signal indication is permitted to enter the intersection to turn right, or to turn left from a one-way street into a one-way street, after stopping. The right to proceed with the turn shall be subject to the rules applicable after making a stop at a STOP sign.

2. Vehicular traffic facing a steady RED ARROW signal indication shall not enter the intersection to make the movement indicated by the arrow and, unless entering the intersection to make another movement permitted by another signal indication, shall stop at a clearly marked stop line; but if there is no stop line, before entering the crosswalk on the near side of the intersection; or if there is no crosswalk, then before entering the intersection; and shall remain stopped until a signal indication or other traffic control device permitting the movement indicated by such RED ARROW is displayed.

When a traffic control device is in place permitting a turn on a steady RED ARROW signal indication, vehicular traffic facing a steady RED ARROW signal indication is permitted to enter the intersection to make the movement indicated by the arrow signal indication, after stopping. The right to proceed with the turn shall be limited to the direction indicated by the arrow and shall be subject to the rules applicable after making a stop at a STOP sign.

3. Unless otherwise directed by a pedestrian signal indication or other traffic control device, pedestrians facing a steady CIRCULAR RED or steady RED ARROW signal indication shall not enter the roadway.

Section 4A.04 Meanings of Flashing Vehicular Signal Indications

Text was relocated from Items

D, E, and F in Paragraph 3 in existing Section 4D.04

Standard:

The following meanings shall be given to flashing highway traffic signal indications for vehicles and pedestrians:

A. A flashing green signal indication has no meaning and shall not be used.

7 8

10 11

12

17

18

19 20 21

22 23 24

25

26

37

31

32

42

43

44 45 46

52

1. Vehicular traffic, on an approach to an intersection, facing a flashing CIRCULAR YELLOW signal indication is permitted to cautiously enter the intersection to proceed straight through or turn right or left or make a U-turn except as such movement is modified by lane-use signs, turn prohibition signs, lane markings, roadway design, separate turn signal indications, or other traffic control devices.

Such vehicular traffic, including vehicles turning right or left or making a U-turn, shall vield the right-of-way to:

- (a) Pedestrians lawfully within an associated crosswalk, and
- (b) Other vehicles lawfully within the intersection.

In addition, vehicular traffic turning left or making a U-turn to the left shall yield the right-of-way to other vehicles approaching from the opposite direction so closely as to constitute an immediate hazard during the time when such turning vehicle is moving across or within the intersection.

2. Vehicular traffic, on an approach to an intersection, facing a flashing YELLOW ARROW signal indication, displayed alone or in combination with another signal indication, is permitted to cautiously enter the intersection only to make the movement indicated by such arrow, or other such movement as is permitted by other signal indications displayed at the same time.

Such vehicular train, including vehicles turning right or left or making a U-turn, shall yield the right-of-way to:

- (a) Pedestrians lawfully within an associated crosswalk, and
- (b) Other vehicles lawfully within the intersection.

In addition, vehicular traffic turning left or making a U-turn to the left shall yield the right-of-way to other vehicles approaching from the opposite direction so closely as to constitute an immediate hazard during the time when such turning vehicle is moving across or within the intersection.

- 3. Pedestrians facing any flashing yellow signal indication at an intersection, unless otherwise directed by a pedestrian signal indication or other traffic control device, are permitted to proceed across the roadway within any marked or unmarked associated crosswalk. Pedestrians shall yield the right-of-way to vehicles lawfully within the intersection at the time that the flashing yellow signal indication is first displayed.
- 4. When a flashing CIRCULAR YELLOW signal indication(s) is displayed as a beacon (see Chapter 4S) to supplement another traffic control device, road users are notified that there is a need to pay extra attention to the message contained thereon or that the regulatory or warning requirements of the other traffic control device, which might not be applicable at all times, are currently applicable.
- C. Flashing red signal indications shall have the following meanings:
 - Vehicular traffic, on an approach to an intersection, facing a flashing CIRCULAR RED signal indication shall stop at a clearly marked stop line; but if there is no stop line, before entering the crosswalk on the near side of the intersection; or if there is no crosswalk, at the point nearest the intersecting roadway where the driver has a view of approaching traffic on the intersecting roadway before entering the intersection. The right to proceed shall be subject to the rules applicable after making a stop at a STOP sign.
 - 2. Vehicular traffic, on an approach to an intersection, facing a flashing RED ARROW signal indication if intending to turn in the direction indicated by the arrow shall stop at a clearly marked stop line; but if there is no stop line, before entering the crosswalk on the near side of the intersection; or if there is no crosswalk, at the point nearest the intersecting roadway where the driver has a view of approaching traffic on the intersecting roadway before entering the intersection. The right to proceed with the turn shall be limited to the direction indicated by the arrow and shall be subject to the rules applicable after making a stop at a STOP sign.

16 <u>Standard:</u>17 The following

- 3. Pedestrians facing any flashing red signal indication at an intersection, unless otherwise directed by a pedestrian signal indication or other traffic control device, are permitted to proceed across the roadway within any marked or unmarked associated crosswalk. Pedestrians shall yield the right-of-way to vehicles lawfully within the intersection at the time that the flashing red signal indication is first displayed.
- 4. When a flashing CIRCULAR RED signal indication(s) is displayed as a beacon (see Chapter 4S) to supplement another traffic control device, road users are notified that there is a need to pay extra attention to the message contained thereon or that the regulatory requirements of the other traffic control device, which might not be applicable at all times, are currently applicable. Use of this signal indication shall be limited to supplementing STOP (R1-1), DO NOT ENTER (R5-1), or WRONG WAY (R5-1a) signs, and to applications where compliance with the supplemented traffic control device requires a stop at a designated point.

Section 4A.05 Meanings of Bicycle Symbol Signal Indications
Approval 16

Approval 16

The following meanings shall be given to bicycle traffic signal indications for bicyclists:

- A. Bicyclists facing a steady GREEN BICYCLE signal indication are permitted to cautiously enter the intersection only to make the movement indicated by the lane-use arrow(s) displayed on the Bicycle Signal sign (see Section 9B.22) that is located immediately adjacent to the signal face.

 Bicyclists proceeding into the intersection during the display of the steady GREEN BICYCLE signal indication shall yield the right-of-way to pedestrians lawfully within an associated crosswalk, and to other vehicles lawfully within the intersection.
- B. Bicyclists facing a steady YELLOW BICYCLE signal indication are thereby warned that the related green movement is being terminated and that a steady RED BICYCLE signal indication will be displayed immediately thereafter when bicyclists shall not enter the intersection. The rules set forth concerning bicycle operation under the movement being terminated shall continue to apply while the steady YELLOW BICYCLE signal indication is displayed.
- C. Bicyclists facing a steady RED BICYCLE signal indication shall not enter the intersection to make the movement indicated by the lane-use arrow(s) displayed on the Bicycle Signal (RX-XX) sign that is located immediately adjacent to the signal face and, unless entering the intersection to make another movement permitted by another bicycle symbol signal indication, shall stop at a clearly marked stop line; but if there is no stop line, before entering the crosswalk on the near side of the intersection; or if there is no crosswalk, then before entering the intersection; and shall remain stopped until a GREEN BICYCLE signal indication permitting the movement indicated by such RED BICYCLE signal indication is displayed.

Except when a traffic control device is in place prohibiting a turn on red, bicyclists facing a steady RED BICYCLE signal indication are permitted to enter the intersection to turn right if there are no approach lanes for motor vehicle traffic to their right, or to turn left from a one-way street into a one-way street if there are no approach lanes for motor vehicle traffic to their left, after stopping. The right to proceed with the turn shall be subject to the rules applicable after making a stop at a STOP sign.

- D. A flashing GREEN BICYCLE signal indication has no meaning and shall not be used.
- E. Bicyclists facing a flashing YELLOW BICYCLE signal indication are permitted to cautiously enter the intersection only to make the movement indicated by the lane-use arrow(s) displayed on the Bicycle Signal sign (see Section 9B.22) that is located immediately adjacent to the signal face. Bicyclists proceeding into the intersection during the display of the flashing YELLOW BICYCLE signal indication shall yield the right-of-way to pedestrians lawfully within an associated crosswalk, and to other vehicles lawfully within the intersection.
- F. Bicyclists facing a flashing RED BICYCLE signal indication shall stop at a clearly marked stop line; but if there is no stop line, before entering the crosswalk on the near side of the intersection; or if there is no crosswalk, at the point nearest the intersecting roadway where the bicyclist has a view of approaching traffic on the intersecting roadway before entering the intersection. The right to proceed in the direction indicated by the lane-use arrow(s) displayed

on the Bicycle Signal (RX-XX) sign that is located immediately adjacent to the signal face shall be subject to the rules applicable after making a stop at a STOP sign.

Section 4E.02 4A.06 Meanings of Pedestrian Signal Head Indications

Standard:

Pedestrian signal **head**-indications shall have the following meanings:

- A. A flashing WALKING PERSON (symbolizing WALK) signal indication has no meaning and shall not be used. Text was relocated from below, formerly Item D
- B. Pedestrians facing a steady WALKING PERSON (symbolizing WALK) signal indication means that a pedestrian facing the signal indication is shall be permitted to start to cross the roadway in the direction of the signal indication, possibly in conflict with turning vehicles. The Pedestrians shall yield the right-of-way to vehicles lawfully within the intersection at the time that the WALKING PERSON (symbolizing WALK) signal indication is first shown.
- C. Pedestrians facing a flashing UPRAISED HAND (symbolizing DONT WALK) signal indication means that a pedestrian shall not start to cross the roadway in the direction of the signal indication. but that Any pedestrian who has already started to cross the roadway on a steady WALKING PERSON (symbolizing WALK) signal indication shall continue to proceed to the far side of the traveled way of the street or highway, unless otherwise directed by a traffic control device to proceed only to the median of a divided highway or only to some other a safety island or pedestrian refuge area.
- D. <u>Pedestrians facing</u> a steady UPRAISED HAND (symbolizing DONT WALK) signal indication means that a pedestrian shall not enter the roadway in the direction of the signal indication.

Section 4D.33 4A.07 Lateral Offset of Signal Supports and Cabinets

Guidance:

The following items should be considered when placing signal supports and cabinets:

- A. Reference should be made to the American Association of State Highway and Transportation Officials (AASHTO) "Roadside Design Guide" (see Section 1A.0511) and to the U.S. Department of Justice 2010 ADA Standards for Accessible Design, September 15, 2010 and Code of Federal Regulations.

 Title 28, Parts 35 and 36. Americans with Disabilities Act of 1990 "Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" (see Section 1A.0511).
- B. Signal supports should be placed as far as practical from the edge of the traveled way without adversely affecting the visibility of the signal indications.
- C. Where supports cannot be located based on the recommended AASHTO clearances, consideration should be given to the use of appropriate safety devices.
- D. No part of a concrete base for a signal support should extend more than 4 inches above the ground level at any point. This limitation does not apply to the concrete base for a rigid support.
- E. In order to minimize hindrance to the passage of persons with physical disabilities, a signal support or controller cabinet should not obstruct the sidewalk, or access from the sidewalk to the crosswalk.
- F. Controller cabinets should be located as far as practical from the edge of the roadway.
- G. On medians, the minimum clearances provided in Items A through E for signal supports should be obtained if practical.

Section 4D.34-4A.08 Use of Signs at Signalized Locations

Support:

Traffic signal signs are sometimes used at highway traffic signal locations to instruct or guide pedestrians, bicyclists, or motorists. Among the signs typically used at or on the approaches to signalized locations are movement prohibition signs (see Section 2B.1826), lane control signs (see Sections 2B.19 to 2B.222B.27 to 2B.29), pedestrian crossing signs (see Section 2B.5158), pedestrian actuation signs (see Section 2B.5259), traffic signal signs (see Sections 2B.5360 and 2C.4844), Signal Ahead warning signs (see Section 2C.36), Street Name signs (see Section 2D.4446). *Guidance:*

Regulatory, warning, and guide signs should be used at <u>highway</u> traffic-control signal locations as provided in Part 2 and as specifically provided elsewhere in Part 4.

Traffic signal signs should be located adjacent to the signal face to which they apply. This text was relocated to new Section 2B.63

Support:

Section 2B.<u>19-27</u> contains information regarding the use of overhead lane control signs on signalized approaches where lane drops, multiple-lane turns involving <u>shared</u> through-and-turn lanes, or other lane-use regulations that would be unexpected by unfamiliar road users are present.

Standard Guidance: Standard changed to Guidance

If used, illuminated traffic signal signs shall-should be designed and mounted in such a manner as to avoid glare and reflections that seriously detract from the signal indications. Highway traffic control-signal faces shall-should be given dominant position and brightness to maximize their priority in the overall display. Standard:

The minimum vertical clearance and horizontal offset of the total assembly of traffic signal signs (see Section 2B.5360) shall comply with the provisions of Sections 4D.1508 and 4D.1609.

STOP signs shall not be used in conjunction with any <u>highway</u> traffic control signal operation, except in either of the following cases:

- A. If the signal indication for an approach is a flashing red at all times, or
- B. If a minor street or driveway is located within or adjacent to the an area controlled by the a traffic control signal, but does not require separate traffic signal control because an extremely low potential for conflict exists.

Section 4D.35 4A.09 Use of Pavement Markings at Signalized Locations

Support:

Pavement markings (see Part 3) that clearly communicate the operational plan of an intersection to road users play an important role in the effective operation of https://example.com/highway traffic entrol signals. By designating the number of lanes, the use of each lane, the length of additional lanes on the approach to an intersection, and the proper stopping points, the engineer can design the signal phasing and timing to best match the goals of the operational plan.

Guidance:

Pavement markings should be used at <u>highway</u> traffic control signal locations as provided in Part 3. If the road surface will not retain pavement markings, signs should be installed to provide the needed road user information.

Section 4D.02 4A.10 Responsibility for Operation and Maintenance

Guidance:

Prior to installing any <u>highway</u> traffic control signal, the responsibility for the maintenance of the signal and all of the appurtenances, hardware, software, and the timing plan(s) should be clearly established <u>by the</u>—

The responsible agency should provide for the maintenance of the highway traffic control signal and all of its appurtenances in a competent manner. Revised to reflect Official Change Request (60)

To this end the agency should:

- A. Keep every controller assembly in effective operation in accordance with its predetermined timing schedule; check the operation of the controller assembly frequently enough to verify that it is operating in accordance with the predetermined timing schedule; and establish a policy to maintain a record of all timing changes and that only authorized persons are permitted to make timing changes;
- B. Clean the optical system of the signal sections and replace the light sources as frequently as experience proves necessary;
- C. Clean and service equipment and other appurtenances as frequently as experience proves necessary;
- D. Provide for alternate operation of the traffic control signal during a period of failure, using flashing mode or manual control, or manual traffic direction by proper authorities as might be required by traffic volumes or congestion, or by erecting other traffic control devices;
- E. Have properly skilled maintenance personnel available without undue delay for all signal malfunctions and signal indication failures;

- F. Provide spare equipment to minimize the interruption of <u>highway</u> traffic control signal operation as a result of equipment failure;
- G. Provide for the availability of properly skilled maintenance personnel for the repair of all components; and
- H. Maintain the appearance of the signal displays and equipment.

2

3 4

5

6

3

4

5

6

7

8

14

15

16 17

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38 39

40

41

42 43

44 45

46

47

48

49

2 Section 4B.01 General

Support:

Words such as pedestrians and bicyclists are used redundantly in selected Sections of Part 4 to encourage sensitivity to these elements of "traffic."

Standards for traffic control signals are important because traffic control signals need to attract the attention of a variety of road users, including those who are older, those with impaired vision, as well as those who are fatigued or distracted, or who are not expecting to encounter a signal at a particular location.

9 Section 4B.02 <u>Basis of Installation or Removal of Traffic Control Signals</u>

10 Guidance:

11 The selection and use of traffic control signals should be based on an engineering study of roadway, traffic, and other conditions.

13 Support:

A careful analysis of traffic operations, pedestrian and bicyclist needs, and other factors at a large number of signalized and unsignalized locations, coupled with engineering judgment, has provided a series of signal warrants, described in Chapter 4C, that define the minimum conditions under which installing traffic control signals might be justified. The sequence of Paragraphs 1 and 2 was reversed

18 Guidance:

Engineering judgment should be applied in the review of operating traffic control signals to determine whether the type of installation and the timing program meet the current requirements of all forms of traffic.

22 If changes in traffic patterns eliminate the need for a traffic control signal, consideration should be given to removing it and replacing it with appropriate alternative traffic control devices, if any are needed.

If the engineering study indicates that the traffic control signal is no longer justified, and a decision is made to remove the signal, removal should be accomplished using the following steps:

- A. Determine the appropriate traffic control to be used after removal of the signal.
- B. Remove any sight-distance restrictions as necessary.
- C. Inform the public of the removal study.
- D. Flash or cover the signal heads for a minimum of 90 days, and install the appropriate stop control or other traffic control devices.
- E. Remove the signal if the engineering data collected during the removal study period confirms that the signal is no longer needed.

Option:

Because Items C, D, and E in Paragraph 5 are not relevant when a temporary traffic control signal (see Section 4D.32) is removed, a temporary traffic control signal may be removed immediately after Items A and B are completed.

Instead of total removal of a traffic control signal, the poles, controller cabinet, and cables may remain in place after removal of the signal heads for continued analysis.

The selection and use design (including the phasing, operation, and timing) of new traffic control signals should be based on an engineering study of roadway, traffic, and other conditions.

<u>Traffic control signals should not be installed or operated for the purpose of penalizing drivers who are speeding, especially in conjunction with signs that have a legend that informs drivers that speeding triggers a red light.</u>

Section 4B.03 Basis of Removal of Traffic Control Signals Text was relocated from Section 4B.02 *Guidance:*

Engineering judgment should be applied in the review of operating traffic control signals to determine whether the type of installation and the timing program meet the current requirements of all forms of traffic.

If changes in traffic patterns eliminate the need for a traffic control signal, consideration should be given to removing it and replacing it with appropriate alternative traffic control devices, if any are needed.

If the engineering study indicates that the traffic control signal is no longer justified, and a decision is made to remove the signal, removal should be accomplished using the following steps:

- A. Determine the appropriate traffic control to be used after removal of the signal.
- B. Remove any sight-distance restrictions as necessary.
- *C. Inform the public of the removal study.*
- D. Flash or cover the signal heads for a minimum of 90 days, and install the appropriate stop control or other traffic control devices.
- E. Remove the signal if the engineering data collected during the removal study period confirms that the signal is no longer needed.

Option:

3

4

5

6

7

8

9

10

11

12

13

14

15

16 17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41 42

43

44 45

46

47

48

Because Items C, D, and E in Paragraph 3 are not relevant when a temporary traffic control signal (see Section 4D.10) is removed, a temporary traffic control signal may be removed immediately after Items A and B are completed.

Instead of total removal of a traffic control signal, the poles, controller cabinet, and cables may remain in place after removal of the signal heads for continued analysis.

Section 4B.03 4B.04 Advantages and Disadvantages of Traffic Control Signals

Support:

When properly used, traffic control signals are valuable devices for the control of vehicular and pedestrian traffic. They assign the right-of-way to-control the various traffic movements by alternating between directing them to stop and permitting them to proceed and thereby profoundly influence traffic flow.

Traffic control signals that are properly designed, located, operated, and maintained will have one or more of the following advantages:

- A. They provide for the orderly movement of traffic.
- B. They increase the traffic-handling capacity of the intersection if:
 - 1. Proper physical layouts and control measures are used, and
 - 2. The signal operational parameters are reviewed and updated (if needed) on a regular basis (as engineering judgment determines that significant traffic flow and/or land use changes have occurred) to maximize the ability of the traffic control signal to satisfy current traffic demands.
- C. They reduce the frequency and severity of certain types of crashes, especially right-angle collisions.
- D. They are coordinated to provide for continuous or nearly continuous movement of traffic at a definite speed along a given route under favorable conditions.
- E. They are used to interrupt heavy traffic at intervals to permit other traffic, vehicular or pedestrian, to cross.

Traffic control signals are often considered a panacea for all traffic problems at intersections. This belief has led to traffic control signals being installed at many locations where they are not needed, adversely affecting the safety and efficiency of vehicular, bicycle, and pedestrian traffic.

Traffic control signals, even when justified by traffic and roadway conditions, can be ill-designed, ineffectively placed, improperly operated, or poorly maintained. Improper or unjustified traffic control signals can result in one or more of the following disadvantages:

- A. Excessive delay,
- B. Excessive disobedience of the signal indications,
- C. Increased use of less adequate routes as road users attempt to avoid the traffic control signals, and
- D. Significant increases in the frequency of collisions (especially rear-end collisions).

Section 4B.04 4B.05 Alternatives to Traffic Control Signals

Guidance:

Since vehicular delay and the frequency of some types of crashes are sometimes greater higher under traffic signal control than under STOP sign control, consideration should be given to providing alternatives to traffic control signals even if one or more of the signal warrants has been satisfied.

49 Option:

These alternatives may include, but are not limited to, the following:

- A. Installing signs along the major street to warn road users approaching the intersection;
 - B. Relocating the stop line(s) and making other changes to improve the sight distance at the intersection;
 - C. Installing measures designed to reduce speeds on the approaches;
 - D. Installing a flashing beacon at the intersection to supplement STOP sign control;
 - E. Installing flashing beacons on warning signs in advance of a STOP sign controlled intersection on major- and/or minor-street approaches;
 - F. Adding one or more lanes on a minor-street approach to reduce the number of vehicles per lane on the approach;
 - G. Revising the geometrics at the intersection to channelize vehicular movements and reduce the time required for a vehicle to complete a movement, which could also assist pedestrians;
 - H. Revising the geometrics at the intersection to add pedestrian median refuge islands and/or curb extensions;
 - I. Installing roadway light if a disproportionate number of crashes occur at night;
 - J. Restricting one or more turning movements, perhaps on a time-of-day basis, if alternate routes are available;
 - K. If the warrant is satisfied, installing multi-way STOP sign control;
 - L. Installing a pedestrian hybrid beacon (see Chapter 4J) or In-Roadway Warning Lights (see Chapter 4U) if pedestrian safety is the major concern;
 - M. Installing a roundabout to reduce vehicular conflicts; and
 - N. Employing other alternatives, depending on conditions at the intersection.

Support:

1

2

3

4

5

6

7

8

9

10

11

12

13 14

15

16

17 18

19 20

21

22

23

24 25

26

Where installation of a roundabout as an alternative to a traffic control signal is in close proximity to a grade crossing, refer to Section 8C.12 for additional information.

Section 4B.05 Adequate Roadway Cape Section deleted; content not specific to traffic control devices

Section 4C.01 Studies and Factors for Justifying Traffic Control Signals

Standard:

Except for temporary traffic control signals (see Section 4D.10), before a traffic control signal is installed at a particular location, an engineering study of traffic conditions, pedestrian characteristics, and physical characteristics of the location shall be performed to determine whether installation of a traffic control signal is justified at a particular that location.

The investigation of the need for a traffic control signal shall include an analysis of factors related to the existing operation and safety at the study location and the potential to improve these conditions, and the applicable factors contained in the following traffic signal warrants:

- Warrant 1, Eight-Hour Vehicular Volume
 - Warrant 2, Four-Hour Vehicular Volume
- Warrant 3, Peak Hour
- Warrant 4, Pedestrian Volume
- 15 Warrant 5, School Crossing
- Warrant 6, Coordinated Signal System
- Warrant 7, Crash Experience
- 18 Warrant 8, Roadway Network
 - Warrant 9, Intersection Near a Grade Crossing

The satisfaction of a traffic signal warrant or warrants shall not in itself require the installation of a traffic control signal.

Support:

Sections 8C.09 and 8C.10—Sections 8D.08 and 8D.14 contain information regarding the use of traffic control signals instead of gates and/or flashing-light signals at highway—light_rail_transit_grade crossings-and-highway—light rail transit grade crossings, respectively.

Guidance:

When considering the installation of a traffic control signal, alternatives to traffic control signals, including those listed in Section 4B.05, should also be considered.

A traffic control signal should not be installed unless one or more of the factors described in this Chapter are met.

A traffic control signal should not be installed unless an engineering study indicates that installing a traffic control signal will improve the overall safety and/or operation of the intersection.

A traffic control signal should not be installed if it will seriously disrupt progressive traffic flow.

The study should consider the effects of the right-turn vehicles from the minor-street approaches. Engineering judgment should be used to determine what, if any, portion of the right-turn traffic is subtracted from the minor-street traffic count when evaluating the count against the signal warrants listed in Paragraph 2.

Engineering judgment should also be used in applying various traffic signal warrants to cases where major-street approaches consist of one lane plus one left-turn or right-turn lane. The site-specific traffic characteristics should dictate whether an major-street approach is considered as one lane or two lanes. For example, for an major-street approach with one lane for through and right-turning traffic plus a left-turn lane, if engineering judgment indicates that it should be considered a one-lane approach because the traffic using the left-turn lane is minor, the total traffic volume approaching the intersection should be applied against the signal warrants as a one-lane approach. The major-street approach should be considered two lanes if approximately half of the traffic on the approach turns left and the left-turn lane is of sufficient length to accommodate all left-turn vehicles.

Similar engineering judgment and rationale should be applied to a <u>minor-street</u> approach with one through/left-turn lane plus a right-turn lane. In this case, the degree of conflict of minor-street right-turn traffic with traffic on the major street should be considered. Thus, right-turn traffic should not be included in the minor-street volume if the movement enters the major street with minimal conflict. The <u>minor-street</u> approach should be evaluated as a one-lane approach with only the traffic volume in the through/left-turn Notice of Proposed Amendments – Part 4

Page 412 of 781

December 2020

lane considered. If a minor-street approach has an exclusive left-turn lane, the approach should either be analyzed as a two-lane approach based on the sum of the traffic volumes using both lanes or as a one-lane approach based on only the traffic volume in the approach lane with the highest volume.

At a location that is under development or construction and or at a location where it is not possible to obtain a traffic count that would represent future traffic conditions, hourly volumes should be estimated as part of an engineering study for comparison with traffic signal warrants. Except for locations where the engineering study uses the satisfaction of Warrant 8 to justify a signal, a traffic control signal installed under projected conditions should have an engineering study done within 1 year of putting the signal into steady (stop-and-go) operation to determine if the signal is justified. If not justified, the signal should be taken out of steady (stop-and-go) operation or removed.

Option:

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15 16

17

18

19

20

21

22 23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45 46 47

48

49

50 51

For signal warrant analysis, a location with a wide median, even if the median width is greater than 30feet, should may be considered analyzed as one intersection or as two intersections based on engineering judgment.

Option:

At an intersection with a high volume of left-turn traffic from the major street, the signal warrant analysis may be performed in a manner that considers the higher of the major-street left-turn volumes as the "minorstreet" volume and the corresponding single direction of opposing traffic on the major street as the "majorstreet" volume.

For signal warrants requiring conditions to be present for a certain number of hours in order to be satisfied, any four sequential consecutive 15-minute periods may be considered as 1 hour if the separate 1hour periods used in the warrant analysis do not overlap each other and both the major-street volume and the minor-street volume are for the same specific one-hour periods.

For signal warrant analysis, bicyclists may be counted as either vehicles or pedestrians.

Support:

When performing a signal warrant analysis, bicyclists riding in the street with other vehicular traffic are usually counted as vehicles and bicyclists who are clearly using pedestrian facilities are usually counted as pedestrians.

Option:

Engineering study data may include the following:

- A. The number of vehicles entering the intersection in each hour from each approach during 12 hours of an average day. It is desirable that the hours selected contain the greatest percentage of the 24-hour traffic volume.
- B. Vehicular volumes for each traffic movement from each approach, classified by vehicle type (heavy trucks, passenger cars and light trucks, public-transit vehicles, and, in some locations, bicycles), during each 15-minute period of the 2 hours in the morning and 2 hours in the afternoon during which total traffic entering the intersection is greatest.
- C. Pedestrian volume counts on each crosswalk during the same periods as the vehicular counts in Item B and during hours of highest pedestrian volume. Where young, elderly, and/or persons with physical or visual disabilities need special consideration, the pedestrians and their crossing times may be classified by general observation.
- D. Information about nearby facilities and activity centers that serve the young, elderly, and/or persons with disabilities, including requests from persons with disabilities for accessible crossing improvements at the location under study. These persons might not be adequately reflected in the pedestrian volume count if the absence of a significant restrains their mobility.

 E. The posted or statutory speed limit or the 85th percentile speed on the uncontrolled approaches to the
- location.
- F. A condition diagram showing details of the physical layout, including such features as intersection geometrics, channelization, grades, sight-distance restrictions, transit stops and routes, parking conditions, pavement markings, roadway lighting, driveways, nearby railroad crossings, distance to nearest traffic control signals, utility poles and fixtures, and adjacent land use.

G. A collision diagram showing crash experience by type, location, direction of movement, severity, weather, time of day, date, and day of week for at least 1 year.

The following data, which are desirable for a more precise understanding of the operation of the intersection, may be obtained during the periods described in Item B of Paragraph 17:

- A. Vehicle-hours of stopped time delay determined separately for each approach.
- B. The number and distribution of acceptable gaps in vehicular traffic on the major street for entrance from the minor street.
- C. The posted or statutory speed limit or the 85th-pentile speed on controlled approaches at a point near to the intersection but unaffected by the control.
- D. Pedestrian delay time for at least two 30-minute peak pedestrian delay periods of an average weekday or like periods of a Saturday or Sunday.
- E. Queue length on stop-controlled approaches.

Section 4C.02 Warrant 1, Eight-Hour Vehicular Volume

Support:

 The Minimum Vehicular Volume, Condition A, is intended for application at locations where a large volume of intersecting traffic is the principal reason to consider installing a traffic control signal.

The Interruption of Continuous Traffic, Condition B, is intended for application at locations where Condition A is not satisfied and where the traffic volume on a major street is so heavy that traffic on a minor intersecting street suffers excessive delay or conflict in entering or crossing the major street.

It is intended that Warrant 1 be treated as a single warrant. If Condition A is satisfied, then Warrant 1 is satisfied and analyses of Condition B and the combination of Conditions A and B are not needed. Similarly, if Condition B is satisfied, then Warrant 1 is satisfied and an analysis of the combination of Conditions A and B is not needed.

Standard Guidance: Standard changed to Guidance; revised to reflect Official Interpretation 4(09)-59(I)

The need for a traffic control signal shall-should be considered if an engineering study finds that one of the following conditions exist for each of any 8 hours of an average day:

- A. The vehicles per hour given in both of the 100 percent columns of Condition A in Table 4C-1 exist on the major-street and the <u>higher volume more critical</u> minor-street approaches, respectively, to the intersection; or
- B. The vehicles per hour given in both of the 100 percent columns of Condition B in Table 4C-1 exist on the major-street and the <u>higher volume more critical</u> minor-street approaches, respectively, to the intersection.

Table 4C-1. Warrant 1, Eight-Hour Vehicular Volume

Standard:

In applying each condition the These major-street and minor-street volumes shall be for the same 8 hours for each condition; however, the 8 hours that are selected for the Condition A analysis shall not be required to be the same 8 hours that are selected for the Condition B analysis. Second sentence changed to Support and moved to next paragraph

Support:

On the minor street, the higher-more critical volume shall is not be required to be on the same approach during each of these 8 hours. The more critical minor-street volume is the one that meets the warranting criteria for that approach, and in the case of a one-lane minor-street approach that is opposite from a multilane minor-street approach might not have the higher volume. Revised to reflect Official Interpretation 4(09)-59(1)

Option:

If the posted or statutory speed limit or the 85th centile speed on the major street exceeds 40 mph, or if the intersection lies within the built-up area of an isolated community having a population of less than 10,000, the traffic volumes in the 70 percent columns in Table 4C-1 may be used in place of the 100 percent columns.

49 Guidance:

The combination of Conditions A and B is intended for application at locations where Condition A is not satisfied and Condition B is not satisfied and should be applied only after an adequate trial of other alternatives that could cause less delay and inconvenience to traffic has failed to solve the traffic problems.

Standard: Standard changed to Guidance; revised to reflect Official Interpretation 4(09)-59(I)

The need for a traffic control signal shall should be considered if an engineering study finds that both of the following conditions exist for each of any 8 hours of an average day:

- A. The vehicles per hour given in both of the 80 percent columns of Condition A in Table 4C-1 exist on the major-street and the higher-volume more critical minor-street approaches, respectively, to the intersection; and
- B. The vehicles per hour given in both of the 80 percent columns of Condition B in Table 4C-1 exist on the major-street and the higher-volume more critical minor-street approaches, respectively, to the intersection.

Standard:

 These major-street and minor-street volumes shall be for the same 8 hours for each condition; however, the 8 hours satisfied in Condition A shall not be required to be the same 8 hours satisfied in Condition B. The second sentence was changed to Support and moved to the next paragraph

Support:

On the minor street, the <u>higher-more critical</u> volume <u>shall is</u> not <u>be-required</u> to be on the same approach during each of the 8 hours. The more critical minor-street volume is the one that meets the warranting criteria for that approach, and in the case of a one-lane minor-street approach that is opposite from a multi-lane minor-street approach might not have the higher volume. Revised to reflect Official Interpretation 4(09)-59(I)

Option:

If the posted or statutory speed limit or the 85th-perentile speed on the major street exceeds 40 mph, or if the intersection lies within the built-up area of an isolated community having a population of less than 10,000, the traffic volumes in the 56 percent columns in Table 4C-1 may be used in place of the 80 percent columns.

Section 4C.03 Warrant 2, Four-Hour Vehicular Volume

Support:

The Four-Hour Vehicular Volume signal warrant conditions are intended to be applied where the volume of intersecting traffic is the principal reason to consider installing a traffic control signal.

Standard Guidance: Standard changed to Guidance; revised to reflect Official Interpretation 4(09)-59(I)

The need for a traffic control signal shall-should be considered if an engineering study finds that, for each of any 4 hours of an average day, the plotted points representing the vehicles per hour on the major street (total of both approaches) and the corresponding vehicles per hour on the higher volume more critical minor-street approach (one direction only) all fall above the applicable curve in Figure 4C-1 for the existing combination of approach lanes. The second sentence was changed to Support and moved to the next

36 paragraph

Support:

On the minor street, the higher-more critical volume shall is not be required to be on the same approach during each of these 4 hours. The more critical minor-street volume is the one that meets the warranting criteria for that approach, and in the case of a one-lane minor-street approach that is opposite from a multilane minor-street approach might not have the higher volume. Revised to reflect Official Interpretation 4(09)-59(1)

Option:

If the posted or statutory speed limit or the 85 precentile speed on the major street exceeds 40 mph, or if the intersection lies within the built-up area of an isolated community having a population of less than 10,000, Figure 4C-2 may be used in place of Figure 4C-1.

Figure 4C-1. arrant 2, Four-Hour Vehicular Volume
Figure 4C-2. Warrant 2, Four-Hour Vehicular Volume (70% Factor)

Section 4C.04 Warrant 3, Peak Hour

Support:

The Peak Hour signal warrant is intended for use at a location where traffic conditions are such that for a minimum of 1 hour of an average day, the minor-street traffic suffers undue delay when entering or crossing the major street.

Standard changed to Guidance

This signal warrant shall should be applied only in unusual cases, such as office complexes, manufacturing plants, industrial complexes, or high-occupancy vehicle facilities that attract or discharge large numbers of vehicles over a short time.

Standard changed to Guidance; revised to reflect Official Interpretation 4(09)-59(I)

The need for a traffic control signal shall should be considered if an engineering study finds that the criteria in either of the following two categories are met:

- A. If all three of the following conditions exist for the same 1 hour (any four consecutive 15-minute periods) of an average day:
 - 1. The total stopped time delay experienced by the traffic on one minor-street approach (one direction only) controlled by a STOP sign equals or exceeds: 4 vehicle-hours for a one-lane approach or 5 vehicle-hours for a two-lane approach; and
 - 2. The volume on the same minor-street approach (one direction only) equals or exceeds 100 vehicles per hour for one moving lane of traffic or 150 vehicles per hour for two moving lanes; and
 - 3. The total entering volume serviced during the hour equals or exceeds 650 vehicles per hour for intersections with three approaches or 800 vehicles per hour for intersections with four or more approaches.
- B. The plotted point representing the vehicles per hour on the major street (total of both approaches) and the corresponding vehicles per hour on the higher volume more critical minor-street approach (one direction only) for 1 hour (any four consecutive 15-minute periods) of an average day falls above the applicable curve in Figure 4C-3 for the existing combination of approach lanes.

Figure 4C-3. Warrant 3, Peak Hour

Option:

If the posted or statutory speed limit or the 85th-percentile speed on the major street exceeds 40 mph, or if the intersection lies within the built-up area of an isolated community having a population of less than 10,000, Figure 4C-4 may be used in place of Figure 4C-3 to evaluate the criteria in the second category of the Standard.

Figure 4C-4. Warrant 3, Peak Hour (70% Factor)

If this warrant is the only warrant met and a traffic control signal is justified by an engineering study, the traffic control signal may be operated in the flashing mode during the hours that the volume criteria of this warrant are not met.

Guidance:

If this warrant is the only warrant met and a traffic control signal is justified by an engineering study, the traffic control signal should be traffic-actuated.

Section 4C.05 Warrant 4, Pedestrian Volume

Support:

The Pedestrian Volume signal warrant is intended for application where the traffic volume on a major street is so heavy that pedestrians experience excessive delay in crossing the major street.

Standard Guidance: Standard changed to Guidance

The need for a traffic control signal at an intersection or midblock crossing shall should be considered if an engineering study finds that one of the following criteria is met:

A. For each of any 4 hours of an average day, the plotted points representing the vehicles per hour on the major street (total of both approaches) and the corresponding pedestrians per hour crossing the major street (total of all crossings) all fall above the curve in Figure 4C-5; or

1 2 3 4	В.	For 1 hour (any four consecutive 15-minute periods) of an average day, the plotted point representing the vehicles per hour on the major street (total of both approaches) and the corresponding pedestrians per hour crossing the major street (total of all crossings) falls above the curve in Figure 4C-7.
5		Figure 4C-5. Warrant 4, Pedestrian Four-Hour Volume
6	Option	

9 10

11 12

13 14

15

16

17 18

19

20

21 22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

If the posted or statutory speed limit or the 85th-pointile speed on the major street exceeds 35 mph, or if the intersection lies within the built-up area of an isolated community having a population of less than 10,000, Figure 4C-6 may be used in place of Figure 4C-5 to evaluate Criterion A in Paragraph 2, and Figure 4C-8 may be used in place of Figure 4C-7 to evaluate Criterion B in Paragraph 2.

Figure 4C-6. Warrant 4, Pedestrian Four-Hour Volume (70% Factor)

Figure 4C-7. Warrant 4, Pedestrian Peak Hour

Figure 4C-8. Warrant 4, Pedestrian Peak Hour (70% Factor)

Where there is a divided street having a median of sufficient width for pedestrians to wait, the criteria in Items A and B of Paragraph 2 may be applied separately to each direction of vehicular traffic. Added to reflect Official Interpretation 4(09)-25(I).

Standard Guidance: Standard changed to Guidance

The Pedestrian Volume signal warrant shall should not be applied at locations where the distance to the nearest traffic control signal or STOP sign controlling the street that pedestrians desire to cross is less than 300 feet, unless the proposed traffic control signal will not restrict the progressive movement of traffic.

If this warrant is met and a traffic control signal is justified by an engineering study, the traffic control signal shall be equipped with pedestrian signal heads complying with the provisions set forth in Chapter 4E 4I.

Guidance:

If this warrant is met and a traffic control signal is justified by an engineering study, then:

- A. If it is installed at an intersection or major driveway location, the traffic control signal should also control the minor-street or driveway traffic, should be traffic-actuated, and should include pedestrian detection.
- B. If it is installed at a non-intersection crossing, the traffic control signal should be installed at least 100 feet from side streets or driveways that are controlled by STOP or YIELD signs, and should be pedestrian-actuated. If the traffic control signal is installed at a non-intersection crossing, at least one of the signal faces should be over the traveled way for each approach, parking and other sight obstructions should be prohibited for at least 100 feet in advance of and at least 20 feet beyond the crosswalk or site accommodations should be made through curb extensions or other techniques to provide adequate sight distance, and the installation should include suitable standard signs and pavement markings.
- C. Furthermore, if it is installed within a signal system, the traffic control signal should be coordinated. Option:

The criterion for the pedestrian volume crossing the major street may be reduced as much as 50 percent if the 15th-percentile crossing speed of pedestrians is less than 3.5 feet per second.

A traffic control signal may not be needed at the study location if adjacent coordinated traffic control signals consistently provide gaps of adequate length for pedestrians to cross the street.

Section 4C.06 Warrant 5, School Crossing

Support:

The School Crossing signal warrant is intended for application where the fact that schoolchildren cross the major street is the principal reason to consider installing a traffic control signal. For the purposes of this warrant, the word "schoolchildren" includes elementary through high school students.

Standard Guidance: Standard changed to Guidance

The need for a traffic control signal shall should be considered when an engineering study of the frequency and adequacy of gaps in the vehicular traffic stream as related to the number and size of groups of schoolchildren at an established school crossing across the major street shows that the number of adequate gaps in the traffic stream during the period when the schoolchildren are using the crossing is less than the number of minutes in the same period (see Section 7A.03) and there are a minimum of 20 schoolchildren during the highest crossing hour.

Before a decision is made to install a traffic control signal, consideration shall be given to the implementation of other remedial measures, such as warning signs and flashers, school speed zones, school crossing guards, or a grade-separated crossing.

The School Crossing signal warrant <u>shall should</u> not be applied at locations where the distance to the nearest traffic control signal along the major street is less than 300 feet, unless the proposed traffic control signal will not restrict the progressive movement of traffic.

Standard:

If this warrant is met and a traffic control signal is justified by an engineering study, the traffic control signal shall be equipped with pedestrian signal heads complying with the provisions set forth in Chapter 4I.

Guidance:

If this warrant is met and a traffic control signal is justified by an engineering study, then:

- A. If it is installed at an intersection or major driveway location, the traffic control signal should also control the minor-street or driveway traffic, should be traffic-actuated, and should include pedestrian detection.
- B. If it is installed at a non-intersection crossing, the traffic control signal should be installed at least 100 feet from side streets or driveways that are controlled by STOP or YIELD signs, and should be pedestrian-actuated. If the traffic control signal is installed at a non-intersection crossing, at least one of the signal faces should be over the traveled way for each approach, parking and other sight obstructions should be prohibited for at least 100 feet in advance of and at least 20 feet beyond the crosswalk or site accommodations should be made through curb extensions or other techniques to provide adequate sight distance, and the installation should include suitable standard signs and pavement markings.
- C. Furthermore, if it is installed within a signal system, the traffic control signal should be coordinated.

Section 4C.07 Warrant 6, Coordinated Signal System

Support:

Progressive movement in a coordinated signal system sometimes necessitates installing traffic control signals at intersections where they would not otherwise be needed in order to maintain proper platooning of vehicles.

Standard Guidance: Standard changed to Guidance

The need for a traffic control signal shall should be considered if an engineering study finds that one of the following criteria is met:

- A. On a one-way street or a street that has traffic predominantly in one direction, the adjacent traffic control signals are so far apart that they do not provide the necessary degree of vehicular platooning.
- B. On a two-way street, adjacent traffic control signals do not provide the necessary degree of platooning and the proposed and adjacent traffic control signals will collectively provide a progressive operation.

Guidance:

The Coordinated Signal System signal warrant should not be applied where the resultant spacing of traffic control signals would be less than 1,000 feet.

Section 4C.08 Warrant 7, Crash Experience

Support:

The Crash Experience signal warrant conditions are intended for application where the severity and frequency of crashes are the principal reasons to consider installing a traffic control signal.

Standard Guidance: Standard changed to Guidance

The need for a traffic control signal shall should be considered if an engineering study finds that all of the following criteria are met:

- A. Adequate trial of alternatives with satisfactory observance and enforcement has failed to reduce the crash frequency; and
- B. Five or more reported erashes, of types susceptible to correction by a traffic control signal, have occurred within a 12-month period, each crash involving personal injury or property damage-At least one of the following conditions applies to the reported crash history (where each reported crash considered is related to the intersection and apparently exceeding exceeds the applicable requirements for a reportable crash): Revised to reflect Interim Approval 19 and Official Change Request 4(09)-42
 - 1. The number of reported angle crashes and pedestrian crashes within a one-year period equals or exceeds the threshold number in Table 4C-2 for total angle crashes and pedestrian crashes (all severities); or
 - 2. The number of reported fatal-and-injury angle crashes and pedestrian crashes within a one-year period equals or exceeds the threshold number in Table 4C-2 for total fatal-and-injury angle crashes and pedestrian crashes; or
 - 3. The number of reported angle crashes and pedestrian crashes within a three-year period equals or exceeds the threshold number in Table 4C-3 for total angle crashes and pedestrian crashes (all severities); or
 - 4. The number of reported fatal-and-injury angle crashes and pedestrian crashes within a three-year period equals or exceeds the threshold number in Table 4C-3 for total fatal-and-injury angle crashes and pedestrian crashes; and
- C. For each of any 8 hours of an average day, the vehicles per hour (vph) given in both of the 80 percent columns of Condition A in Table 4C-1 (see Section 4C.02), or the vph in both of the 80 percent columns of Condition B in Table 4C-1 exists on the major-street and the higher-volume more critical minor-street approach, respectively, to the intersection, or the volume of pedestrian traffic is not less than 80 percent of the requirements specified in the Pedestrian Volume warrant. Revised to reflect Official Interpretation 4(09)-59(1)

Table 4C-2. Minimum Number of Reported Crashes in a One-Year Period - Urban Area Table 4C-3. Minimum Number of Reported Crashes in a Three-Year Period - Urban Area Standard:

These major-street and minor-street volumes shall be for the same 8 hours. The second sentence was changed to Support and moved to the next paragraph

Support:

1 2

On the minor street, the higher-more critical volume shall is not be required to be on the same approach during each of these 8 hours. The more critical minor-street volume is the one that meets the warranting criteria for that approach, and in the case of a one-lane minor-street approach that is opposite from a multilane minor-street approach might not have the higher volume. Revised to reflect Official Interpretation 4(09)-59(I)

Option:

If the posted or statutory speed limit or the 85th-per ile speed on the major street exceeds 40 mph, or if the intersection lies within the built-up area of an isolated community having a population of less than 10,000:

- A. The traffic volumes in the 56 percent columns in Table 4C-1 may be used in place of the 80 percent columns.
- B. Tables 4C-4 and 4C-5 may be used in place of Tables 4C-2 and 4C-3. Text added to reflect Interim Approval IA-19 and Official Change Request 4(09)-42
 - Table 4C-4. Minimum Number of Reported Crashes in a One-Year Period Rural Area Table 4C-5. Minimum Number of Reported Crashes in a Three-Year Period Rural Area

Section 4C.09 Warrant 8, Roadway Network

Support:

 Installing a traffic control signal at some intersections might be justified to encourage concentration and organization of traffic flow on a roadway network.

Standard Changed to Guidance

The need for a traffic control signal shall should be considered if an engineering study finds that the common intersection of two or more major routes meets one or both of the following criteria:

- A. The intersection has a total existing, or immediately projected, entering volume of at least 1,000 vehicles per hour during the peak hour of a typical weekday and has 5-year projected traffic volumes, based on an engineering study, that meet one or more of Warrants 1, 2, and 3 during an average weekday; or
- B. The intersection has a total existing or immediately projected entering volume of at least 1,000 vehicles per hour for each of any 5 hours of a non-normal business day (Saturday or Sunday).

A major route as used in this signal warrant shall should have at least one of the following characteristics: Standard changed to Guidance

- A. It is part of the street or highway system that serves as the principal roadway network for through traffic flow.
- B. It includes rural or suburban highways outside, entering, or traversing a city.
- C. It appears as a major route on an official plan, such as a major street plan in an urban area traffic and transportation study.

Section 4C.10 Warrant 9, Intersection Near a Grade Crossing

Support:

The Intersection Near a Grade Crossing signal warrant is intended for use at a location where none of the conditions described in the other eight traffic signal warrants are met, but the proximity to the intersection of a grade crossing on an intersection approach controlled by a STOP or YIELD sign at a highway-highway intersection is the principal reason to consider installing a traffic control signal.

Guidance:

This signal warrant should be applied only after adequate consideration has been given to other alternatives or after a trial of an alternative has failed to alleviate the safety concerns associated with the grade crossing. Among the alternatives that should be considered or tried are:

- A. Providing additional pavement that would enable vehicles to clear the track or that would provide space for an evasive maneuver, or
- B. Reassigning the stop controls at the <u>highway-highway</u> intersection to make the approach across the track a non-stopping approach.

Standard: Standard changed to Guidance

The need for a traffic control signal shall should be considered if an engineering study finds that both of the following criteria are met:

- A. A grade crossing exists on an approach controlled by a STOP or YIELD sign <u>at a highway-highway</u> <u>intersection</u> and the center of the track nearest to the intersection is within 140 feet of the stop line or yield line on the approach; and
- B. During the highest traffic volume hour during which rail traffic uses the crossing, the plotted point representing the vehicles per hour on the major street (total of both approaches) of the highway-highway intersection and the corresponding vehicles per hour on the minor-street approach that crosses the track (one direction only, approaching the intersection) falls above the applicable curve in Figure 4C-9 or 4C-10 for the existing combination of approach lanes over the track and the distance D, which is the clear storage distance as defined in Section 1A.13-1C.02.

Figure 4C-9. Warrant 9, Intersection Near a Grade Crossing (One Approach Lane at the Track Crossing)

Figure 4C-10. Warrant 9, Intersection Near a Grade Crossing (Two or More Approach Lanes at the Track Crossing)

Guidance:

The following considerations apply when plotting the traffic volume data on Figure 4C-9 or 4C-10:

- A. Figure 4C-9 should be used if there is only one lane approaching the <u>highway-highway</u> intersection at the track crossing location and Figure 4C-10 should be used if there are two or more lanes approaching the <u>highway-highway</u> intersection at the track crossing location.
- B. After determining the actual distance D, the curve for the distance D that is nearest to the actual distance D should be used. For example, if the actual distance D is 95 feet, the plotted point should be compared to the curve for D = 90 feet.
- C. If the rail traffic arrival times are unknown, the highest traffic volume hour of the day should be used. Option:

The <u>traffic volume on the minor-street</u> approach volume to the highway-highway intersection may be multiplied by up to three adjustment factors as provided in Paragraphs 6 through 8.

Because the curves are based on an average of four occurrences of rail traffic per day, the vehicles per hour on the minor-street approach may be multiplied by the adjustment factor shown in Table 4C-6 4C-2 for the appropriate number of occurrences of rail traffic per day.

Table 4C-6. Warrant 9, Adjustment Factor for Daily Frequency of Rail Traffic

Because the curves are based on typical vehicle occupancy, if at least 2% of the vehicles crossing the track are buses carrying at least 20 people, the vehicles per hour on the minor-street approach may be multiplied by the adjustment factor shown in Table 4C-7 4C-3 for the appropriate percentage of high-occupancy buses.

Table 4C-7. Warrant 9, Adjustment Factor for Percentage of High-Occupancy Buses

Because the curves are based on tractor-trailer trucks comprising 10% of the vehicles crossing the track, the vehicles per hour on the minor-street approach may be multiplied by the adjustment factor shown in Table 4C-8 4C-4 for the appropriate distance and percentage of tractor-trailer trucks.

Table 4C-8. Warrant 9, Adjustment Factor for Percentage of Tractor-Trailer Trucks Standard:

If this warrant is met and a traffic control signal at the <u>highway-highway</u> intersection is justified by an engineering study, then:

- A. The traffic control signal shall have actuation on the minor street;
- B. Preemption control shall be provided in accordance with Sections 4D.27, 8C.09, and 8C.10 4F.19 and 8D.09; and
- C. The grade crossing shall have flashing-light signals (see Section 8C 8D.02).

Guidance:

If this warrant is met and a traffic control signal at the <u>highway-highway</u> intersection is justified by an engineering study, the grade crossing should have automatic gates (see Section_8C 8D.03).

CHAPTER 4D. DESIGN OF TRAFFIC CONTROL SIGNALS FEATURES

Section 4D.01 General

Support:

The features of traffic control signals of interest to road users are the location, design, and meaning of the signal indications. Uniformity in the design features that affect the traffic to be controlled, as set forth in this Manual, is especially important for the safety and efficiency of operations.

Traffic control signals can be operated in pretimed, semi-actuated, or full-actuated modes. For isolated (non-interconnected) signalized locations on rural high-speed highways, full-actuated mode with advance vehicle detection on the high-speed approaches is typically used. These features are designed to reduce the frequency with which the onset of the yellow change interval is displayed when high-speed approaching vehicles are in the "dilemma zone" such that the drivers of these high-speed vehicles find it difficult to decide whether to stop or proceed.

Standard:

The design and operation of traffic control signals shall take into consideration the needs of all modes of traffic. Added to reflect Official Change Request 4(09)-69

When a traffic control signal is not in operation, such as before it is placed in service, during seasonal shutdowns, or when it is not desirable to operate the traffic control signal, the signal faces shall be covered, turned, or taken down to clearly indicate that the traffic control signal is not in operation.

Guidance: Added to reflect Official Interpretation 4(09)-1(I)

If a cover is placed over a traffic control signal face that is not in operation and that has a yellow retroreflective strip along the perimeter of its signal backplate (see Paragraph 22 in Section 4D.05), the entire signal face, including the backplate, should be covered. If a traffic control signal face that is not in operation and that has a yellow retroreflective strip along the perimeter of its signal backplate is turned, the turned signal face should be oriented such that the yellow backplate border will not reflect light back to road users on any of the approaches to the intersection.

Support:

Seasonal shutdown is a condition in which a permanent traffic <u>control</u> signal is turned off or otherwise made non-operational during a particular season when its operation is not justified. This might be applied in a community where tourist traffic during most of the year justifies the permanent signalization, but a seasonal shutdown of the signal during an annual period of lower tourist traffic would reduce delays; or where a major traffic generator, such as a large factory, justifies the permanent signalization, but the large factory is shut down for an annual factory vacation for a few weeks in the summer.

Standard:

A traffic control signal shall control traffic only at the intersection or midblock location where the signal faces are placed.

Guidance: Standard changed to Guidance

Midblock crosswalks shall should not be signalized if they are located within 300 feet from the nearest traffic control signal, unless the proposed traffic control signal will not restrict the progressive movement of traffic.

Guidance:

A midblock crosswalk location should not be controlled by a traffic control signal if the crosswalk is located within 100 feet from side streets or driveways that are controlled by STOP signs or YIELD signs.

Engineering judgment should be used to determine the proper phasing and timing for a traffic control signal. Since traffic flows and patterns change, phasing and timing should be reevaluated regularly and updated if needed.

Traffic control signals within 1/2 mile of one another along a major route or in a network of intersecting major routes should be coordinated, preferably with interconnected controller units. Where traffic control signals that are within 1/2 mile of one another along a major route have a jurisdictional boundary or a boundary between different signal systems between them, coordination across the boundary should be considered.

Support:

Signal coordination need not be maintained between control sections that operate on different cycle lengths.

For coordination with grade crossing signals and movable bridge signals, see Sections_4D.27, 4J.03, 8C.09, and 8C.10-4F.19, 4Q.03, 8D.09.

Section 4D.02 Responsibility for Operation and Maintenance

Text was relocated to new Section

4A.09

Section 4D.03 4D.02 Provisions for Pedestr Revisions throughout Section to reflect Official Change Request 4(09)-69

Support:

Chapter_4E_4I contains additional information regarding pedestrian signals and Chapter 4F_4J contains additional information regarding pedestrian hybrid beacons.

Standard:

The design and operation of traffic control signals shall take into consideration the needs of pedestrian as well as vehicular traffic.

Pedestrian signal heads shall be used in conjunction with vehicular traffic control signals under any of the following conditions, unless the crossing is prohibited or as provided in the Option in Paragraph 05a:

- A. If the basis for a traffic control signal is installation was justified by an engineering study and meetings either Warrant 4, Pedestrian Volume or Warrant 5, School Crossing (see Chapter 4C);
- B. If an exclusive <u>pedestrian</u> signal phase is provided or made available for pedestrian movements in one or more directions, with all conflicting vehicular movements being stopped;
- C. At an established signalized school crossing at any signalized location;
- D. Where there are existing pedestrian accommodations and engineering judgment determines that multi-phase signal indications (as with split-phase timing) would tend to confuse or cause conflicts with pedestrians using a crosswalk guided only by vehicular signal indications;

Text was relocated from existing Section 4E.03 and revised based on Official Change Request 4(09)-

Guidance:

Pedest signal heads should be installed at each marked crosswalk at a location controlled by a traffic control signal.

If engineering judgment indicates the need for provisions for a given pedestrian movement, signal faces conveniently visible to pedestrians shall be provided by pedestrian signal heads (see Chapter 41) or a vehicular signal face(s) for a concurrent vehicular movement.

Guidance:

Accessible pedestrian signals (see Chapter_4E.09 through 4E.13 4K) that provide information in non-visual formats (such as audible tones, speech messages, and/or vibrating surfaces) should be provided where determined appropriate by engineering judgment based on the results of an engineering study considering the factors listed in Section 4K.01.

Where pedestrian movements regularly occur, pedestrians should be provided with sufficient time to cross the roadway by adjusting the traffic control signal operation and timing to provide sufficient crossing time every cycle or by providing pedestrian detectors.

If it is necessary or desirable to prohibit certain pedestrian movements at a traffic control signal location, No Pedestrian Crossing (R9-3) signs (see Section_2B.51-2B.61) should be used if it is not practical to provide a barrier or other physical feature to physically prevent-discourage the pedestrian movements.

Pedestrian signal heads may be used under other conditions based on engineering judgement.

This text was relocated from existing Section 4E.03

Section 4D.03 Provisions for Bicyclists Added to reflect Interim Approval 16

50 Option:

- Where it is desired to provide separate signal indications to control bicycle movements at a traffic control signal, bicycle signal faces may be used (see Chapter 4H).
- 3 Section 4D.04 Meaning of Vehicular Signal Indications
 4 A.04 Relocated to new Sections 4A.02 through
- 5 Section 4D.05 Application of Steady Signal Indications Relocated to new Section 4F.01
- 6 Section 4D.06 Signal Indications Design, Illumination, Color, and Shape Relocated to new Section 4E.01
- 8 Section 4D.07 Size of Vehicular Signal Indications Relocated to new Section 4E.02
- 9 Section 4D.08 Positions of Signal Indications Within a Signal Face General Relocated to new Section 4E.03
- 11 Section 4D.09 Positions of Signal Indications Within a Vertical Signal Face Relocated to new Section 4E.04
- 13 Section 4D.10 Positions of Signal Indications Within a Horizontal Signal Face Relocated to new Section 4E.05
- 15 Section 4D.11 4D.04 Number of Signal Faces on an Approach
- 16 **Standard:**

18

19

20

21

22

23

24 25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

The signal faces for each approach to an intersection or a midblock location shall be provided as follows:

- A. If a signalized <u>motor vehicle</u> through movement exists on an approach, a minimum of two primary signal faces shall be provided for the through movement. If a signalized <u>motor vehicle</u> through movement does not exist on an approach, a minimum of two primary signal faces shall be provided for the signalized <u>motor vehicle</u> turning movement that is considered to be the major movement from the approach (also see Section 4D.25 4F.16).
- B. See Sections_4D.17 through 4D.20 4F.02 through 4F.08 for left-turn (and U-turn to the left) signal faces.
- C. See Sections 4D.21 through 4D.24 4F.09 through 4F.15 for right-turn (and U-turn to the right) signal faces.
- Option:

Where a movement (or a certain lane or lanes) at the intersection never conflicts with any other signalized vehicular or pedestrian movement, a continuously-displayed single-section GREEN ARROW signal indication may be used to inform road users that the movement is free-flow and does not need to stop.

Support:

In some circumstances where the through movement never conflicts with any other signalized vehicular or pedestrian movement at the intersection, such as at T-intersections with appropriate geometrics and/or pavement markings and signing, an engineering study might determine that the through movement (or certain lanes of the through movement) can be free-flow and not signalized.

Guidance:

If two or more left-turn lanes are provided for a separately controlled protected only mode left-turn movement, or if a left-turn movement represents the major movement from an approach, two or more primary left-turn signal faces should be provided.

If two or more right-turn lanes are provided for a separately controlled right-turn movement, or if a right-turn movement represents the major movement from an approach, two or more primary right-turn signal faces should be provided.

Support:

Locating primary signal faces overhead on the far side of the intersection has been shown to provide safer operation by reducing intersection entries late in the yellow interval and by reducing red signal violations, as compared to post-mounting signal faces at the roadside or locating signal faces overhead within the

intersection on a diagonally-oriented mast arm or span wire. On approaches with two or more lanes for the through movement, one signal face per through lane, centered over each through lane, has also been shown to provide safer operation.

Guidance:

If the posted or statutory speed limit or the 85^{th} percentile speed on an approach to a signalized location is 45 mph or higher, signal faces should be provided as follows for all new or reconstructed signal installations (see Figure 4D-14D-3):

- A. The minimum number and location of primary (non-supplemental) signal faces for through traffic should be provided in accordance with Table 4D-1.
- B. If the number of overhead primary signal faces for through traffic is equal to the number of through lanes on an approach, one overhead signal face should be located approximately over the center of each through lane.
- C. Except for shared left-turn and right-turn signal faces, any primary signal face required by Sections_4D.17 though 4D.25-4F.02 through 4F.16 for an exclusive turn lane should be located overhead approximately over the center of each exclusive turn lane.
- D. All primary signal faces should be located on the far side of the intersection.
- E. In addition to the primary signal faces, one or more supplemental pole-mounted or overhead signal faces should be considered to provide added visibility for approaching traffic that is traveling behind large vehicles.
- F. All signal faces should have backplates.

Table 4D-1. Recommended Minimum Number of Primery Signal Faces for Through Traffic on Approaches with Posted, Statutory, or 85t ercentile Speed of 45 mph or Higher

Figure 4D-1. Recommended Vehicular Signal Faces for Approaches with Posted, Statutory, or 85th centile Speed of 45 mph or Higher

This layout of signal faces should also be considered for any major urban or suburban arterial street with four or more lanes and for other approaches with speeds of less than 45 mph.

Section 4D.12 4D.05 Visibility, Aiming, and Shielding of Signal Faces

Standard Guidance: Standard changed to Guidance

The <u>primary most important</u> consideration in signal face placement, aiming, and adjustment <u>shall should</u> be to optimize the visibility of signal indications to approaching traffic.

Road users approaching a signalized intersection or other signalized area, such as a midblock crosswalk, shall should be given a clear and unmistakable indication of their right of way assignment whether they are being directed to stop or permitted to proceed.

The geometry of each intersection to be signalized, including vertical grades, horizontal curves, and obstructions as well as the lateral and vertical angles of sight toward a signal face, as determined by typical driver-eye position, shall should be considered in determining the vertical, longitudinal, and lateral position of the signal face.

Guidance:

The two primary signal faces required as a minimum for each approach should be continuously visible to traffic approaching the traffic control signal, from a point at least the minimum sight distance provided in Table 4D-2 in advance of and measured to the stop line. This range of continuous visibility should be provided unless precluded by a physical obstruction or unless another signalized location is within this range.

Table 4D-2. Minimum Sight Distance for Signal Visibility

There should be legal authority to prohibit the display of any unauthorized sign, signal, marking, or device that interferes with the effectiveness of any official traffic control device (see Section 11-205 of the "Uniform Vehicle Code").

At signalized midblock crosswalks, at least one of the signal faces should be over the traveled way for each approach.

Standard: Standard changed to Guidance

If approaching traffic does not have a continuous view of at least two signal faces for at least the minimum sight distance shown in Table 4D-2, a sign (see Section_2C.36-2C.37) shall should be installed to warn approaching traffic of the traffic control signal.

Option:

If a sign is installed to warn approaching road users of the traffic control signal, the sign may be supplemented by a Warning Beacon (see Section_4L.03 4S.03).

A Warning Beacon used in this manner may be interconnected with the traffic signal controller assembly in such a manner as to flash yellow during the period when road users passing this beacon at the legal speed for the roadway might encounter a red signal indication (or a queue resulting from the display of the red signal indication) upon arrival at the signalized location.

If the sight distance to the signal faces for an approach is limited by horizontal or vertical alignment, supplemental signal faces aimed at a point on the approach at which the signal indications first become visible may be used.

Guidance:

Supplemental signal faces should be used if engineering judgment has shown that they are needed to achieve intersection visibility both in advance and immediately before the signalized location.

If supplemental signal faces are used, they should be located to provide optimum visibility for the movement to be controlled.

Standard: Standard changed to Guidance

In cases where irregular street design necessitates placing signal faces for different street approaches with a comparatively small angle between their respective signal indications, each signal indication shall should, to the extent practical, be visibility-limited by signal visors, signal louvers, or other means so that an approaching road user's view of the signal indication(s) controlling movements on other approaches is minimized.

Standard:

Signal visors exceeding 12 inches in length shall not be used on free-swinging signal faces.

Guidance:

Signal visors should be used on signal faces to aid in directing the signal indication specifically to approaching traffic, as well as to reduce "sun phantom," which can result when external light enters the lens.

The use of signal visors, or the use of signal faces or devices that direct the light without a reduction in intensity, should be considered as an alternative to signal louvers because of the reduction in light output caused by signal louvers.

Option:

Special signal faces, such as visibility-limited signal faces, may be used such that the road user does not see signal indications intended for other approaches before seeing the signal indications for their own approach, if simultaneous viewing of both signal indications could cause the road user to be misdirected.

Guidance:

If the posted or statutory speed limit or the 85th percentile speed on an approach to a signalized location is 45 mph or higher, signal backplates should be used on all of the signal faces that face the approach. Signal backplates should also be considered for use on signal faces on approaches with posted or statutory speed limits or 85th-percentile speeds of less than 45 mph where sun glare, bright sky, and/or complex or confusing backgrounds indicate a need for enhanced signal face target value.

Support:

The use of backplates enhances the contrast between the traffic signal indications and their surroundings for both day and night conditions, which is also helpful to older drivers.

Standard:

If backplates are used, an ary legends of any kind that identify the purpose or operation of the signal face shall not be placed on the backplate.

The inside of signal visors (hoods), the entire surface of louvers and fins, and the front surface of backplates shall have a dull black finish to minimize light reflection and to increase contrast between the signal indication and its background.

Option:

A yellow retroreflective strip with a minimum width of 1 inch and a maximum width of 3 inches may be placed along the perimeter of the face of a signal backplate to project a rectangular appearance at night.

Section 4D.13 4D.06 Lateral Positioning of Signal Faces

Standard:

At least one and preferably both of the minimum of two primary signal faces required for the through movement (or the major turning movement if there is no through movement) on the approach shall be located between two lines intersecting with the center of the approach at a point 10 feet behind the stop line, one making an angle of approximately 20 degrees to the right of the center of the approach extended, and the other making an angle of approximately 20 degrees to the left of the center of the approach extended. The signal face that satisfies this requirement shall simultaneously satisfy the longitudinal placement requirement described in Section_4D.14 4D.07 (see Figure 4D-2 4D 4).

Figure 4D-2. Lateral and Longitudinal Location of Primary Signal Faces

If both of the minimum of two primary signal faces required for the through movement (or the major turning movement if there is no through movement) on the approach are post-mounted, they shall both be on the far side of the intersection, one on the right and one on the left of the approach lane(s).

The required signal faces for through traffic on an approach shall be located not less than 8 feet apart measured horizontally perpendicular to the approach between the centers of the signal faces.

If more than one separate turn signal face is provided for a turning movement and if one or both of the separate turn signal faces are located over the roadway, the signal faces shall be located not less than 8 feet apart measured horizontally perpendicular to the approach between the centers of the signal faces.

Guidance:

Separate turn signal faces should be located at least 3 feet from the nearest traffic signal face for a different movement on the same approach measured either horizontally perpendicular to the approach between the centers of the signal faces or vertically from the center of the lowest signal indication of the top signal face to the center of the highest signal indication of the bottom signal face. If horizontally-arranged or clustered signal faces are used, the minimum 3-foot horizontal separation between the two signal faces should be measured from the center of the right-most signal indication in the signal face on the left to the center of the left-most signal indication in the signal face on the right.

If a signal face controls a specific lane or lanes of an approach, its position should make it readily visible to road users making that movement.

Support:

Section_4D.11-4D.04 contains additional provisions regarding teral positioning of signal faces for approaches having a posted or statutory speed limit or an 85th-per title speed of 45 mph or higher.

Standard Guidance: Standard changed to Guidance

If an exclusive left-turn, right-turn, or U-turn lane is present on an approach and if a primary separate turn signal face controlling that lane is mounted over the roadway, the primary separate turn signal face shall should not be positioned any further to the right than the extension of the right-hand edge of the exclusive turn lane or any further to the left than the extension of the left-hand edge of the exclusive turn lane.

Support: Standard changed to Support

Supplemental turn signal faces mounted over the roadway shall are not be subject to the positioning requirements recommendations in the previous paragraph.

Guidance:

For new or reconstructed signal installations, on an approach with an exclusive turn lane(s) for a permissive left-turn (or U-turn to the left) movement and with opposing vehicular traffie, signal faces that Notice of Proposed Amendments – Part 4
Page 427 of 781

December 2020

display a CIRCULAR GREEN signal indication should not be post-mounted on the far-side median or mounted overhead above the exclusive turn lane(s) or the extension of the lane(s).

Standard:

If supplemental post-mounted signal faces are used, the following limitations shall apply:

- A. Left-turn arrows and U-turn arrows to the left shall not be used in near-right signal faces that are located to the right of the through and/or right-turn lanes.
- B. Right-turn arrows and U-turn arrows to the right shall not be used in far-left signal faces that are located to the left of the through and/or left-turn lanes. A far-side median-mounted signal face shall be considered a far-left signal face for this application.

Section 4D.14 4D.07 Longitudinal Positioning of Signal Faces

Standard:

Except where the width of an intersecting roadway or other conditions make it physically impractical, the signal faces for each approach to an intersection or a midblock location shall be provided as follows:

- A. A signal face installed to satisfy the requirements for primary left-turn signal faces (see Sections 4F.02 through 4F.08) and primary right-turn signal faces (see Sections 4F.09 through 4F.15), and at least one and preferably both of the minimum of two primary signal faces required for the through movement (or the major turning movement if there is no through movement) on the approach shall be located:
 - 1. No less than 40 feet beyond the stop line, and
 - 2. No more than 180 feet beyond the stop line unless a supplemental near-side signal face is provided, and
 - 3. As near as practical to the line of the driver's normal view, if mounted over the roadway.
- B. The primary signal faces that are used to satisfies satisfy this the requirement s of Item A shall simultaneously satisfy the lateral placement requirement described in Section 4D.06 (see Figure 4D-2-4D-4).

Guidance: Standard changed to Guidance

B.—Where the nearest signal face is located between 150 and 180 feet beyond the stop line, engineering judgment of the conditions, including the worst-case visibility conditions, shall should be used to determine if the provision of a supplemental near-side signal face would be beneficial. This text was relocated from Item B of the previous paragraph

Supplemental near-side signal faces should be located as near as practical to the stop line.

Support:

Section 4D.04 contains additional provisions regarding longitudinal positioning of signal faces for approaches having a posted or 85th-per ntile speed of 45 mph or higher. Text relocated from above

Section 4D.15 4D.08 Mounting Height of Signal Faces

Standard:

The bottom of the signal housing and any related attachments to a vehicular signal face located over any portion of a highway that can be used by motor vehicles shall be at least 15 feet above the pavement.

The bottom of the signal housing (including brackets) of a vehicular signal face that is vertically arranged and not located over a roadway:

- A. Shall be a minimum of 8 feet and a maximum of 19 feet above the sidewalk or, if there is no sidewalk, above the pavement grade at the center of the roadway.
- B. Shall be a minimum of 4.5 feet and a maximum of 19 feet above the median island grade of a center median island if located on the near side of the intersection. Revised to reflect Official Change Request 4(09)-42(C)
- The bottom of the signal housing (including brackets) of a vehicular signal face that is horizontally arranged and not located over a roadway:

- A. Shall be a minimum of 8 feet and a maximum of 22 feet above the sidewalk or, if there is no sidewalk, above the pavement grade at the center of the roadway.
- B. Shall be a minimum of 4.5 feet and a maximum of 22 feet above the median island grade of a center median island if located on the near side of the intersection.

 Revised to reflect Official Change Request 4(09)-42(C)

Guidance:

The top of the signal housing of a vehicular signal face located over any portion of a highway that can be used by motor vehicles shall not be more than 25.6 feet above the pavement. Text relocated from above: Standard changed to Guidance

For viewing distances between 40 and 53 feet from the stop line, the maximum mounting height to the top of the signal housing of a vehicular signal face located over any portion of a highway that can be used by motor vehicles shall should be as shown in Figure 4D-3 4D-5. Text relocated from above; Standard changed to Guidance

Figure 4D-3. Maximum Mounting Height of Signal Faces Located Between 40 Feet and 53 Feet from Stop Line

The bottom of the signal housing (including brackets) of a vehicular signal face that is vertically arranged and not located over a roadway: Added to reflect Official Change Request 4(09)-42

- A. Should be a maximum of 19 feet above the sidewalk or, if there is no sidewalk, above the pavement grade at the center of the roadway.
- B. Should be a maximum of 19 feet above the median island grade of a center median island if located on the near side of the intersection.
- The bottom of the signal housing (including brackets) of a vehicular signal face that is horizontally arranged and not located over a roadway: Added to reflect Official Change Request 4(09)-42
- A. Should be a maximum of 22 feet above the sidewalk or, if there is no sidewalk, above the pavement grade at the center of the roadway.
- B. Should be a maximum of 22 feet above the median island grade of a center median island if located on the near side of the intersection.

Section 4D.16 4D.09 Lateral Offset (Clearance) of Signal Faces

Standard Guidance: Standard changed to Guidance

Signal faces mounted at the side of a roadway with curbs at less than 15 feet from the bottom of the housing and any related attachments shall should have a horizontal offset of not less than 2 feet from the face of a vertical curb, or if there is no curb, not less than 2 feet from the edge of a shoulder.

Section 4D.32 4D.10 Temporary and Portable Traffic Control Signals

Support:

A temporary traffic control signal is generally installed using methods that minimize the costs of installation, relocation, and/or removal. Typical temporary traffic control signals are for specific purposes, such as for one-lane, two-way facilities in temporary traffic control zones (see Chapter_4H-4O), for a haul-road intersection, or for access to a site that will have a permanent access point developed at another location in the near future.

Portable traffic signals are temporary traffic signals.

Added to reflect Official Change Request 4(09)-42

Because a portable traffic control signals is considered to be a type of temporary traffic control signal, the provisions for temporary traffic control signals are also applicable to portable traffic control signals.

Standard:

- Advance signing shall be used when employing a temporary traffic control signal.
- A temporary traffic control signal shall:
 - A. Meet the physical display and operational requirements of a conventional traffic control signal.
 - B. Be removed when no longer needed.
- C. Be placed in the flashing mode when not being used if it will be operated in the steady mode within 5 working days; otherwise, it shall be removed.

C. Except as provided in Paragraph 5, be placed in the flashing mode during periods when it is not desirable to operate the signal in the steady mode, or the signal heads shall be covered, turned, or taken down to indicate that the signal is not in operation.

Option:

If the temporary traffic control signal is capable of being operated in a semi-actuated mode, such that green signal indications are continually shown to major-street traffic except when responding to a minor-street approach vehicle call, it may be operated in a semi-actuated mode instead of being placed in a flashing mode.

Guidance:

A temporary traffic control signal should be used only if engineering judgment indicates that installing the signal will improve the overall safety and/or operation of the location.

The use of temporary traffic control signals by a work crew on a regular basis in their work area should be subject to the approval of the jurisdiction having authority over the roadway.

A temporary traffic control signal should not operate longer than 30 days unless associated with a longer-term temporary traffic control zone project.

For use of temporary traffic control signals in temporary traffic control zones, reference should be made to Section 6F.84 6L.01.

Section 4D.06 4E.01 Signal Indications – Design, Illumination, Color, and Shape

Standard:

The illuminated part of each signal indication shall be circular or arrow, except those used for bicycle symbol signal indications, pedestrian signal heads, and lane-use control signals, shall be circular or arrow. Edited to reflect Official Change Request 4(09)-43

Letters or numbers (including those associated with countdown displays) shall not be displayed as part of a vehicular signal indication.

Strobes shall not be used within or adjacent to any signal indication.

Except for the flashing <u>vehicular and pedestrian</u> signal indications and the preemption confirmation <u>lights</u> that are expressly allowed by the provisions of this <u>Chapter Part</u>, flashing displays shall not be used within or adjacent to any signal indications.

Each circular signal indication shall emit a single color: red, yellow, or green.

Except as provided in Paragraph 7, each arrow signal indication shall emit a single color: red, yellow, or green except that the alternate display (dual arrow signal section) of a GREEN ARROW and a YELLOW ARROW signal indication, both pointing in the same direction, shall be permitted, provided that they are not displayed simultaneously.

A dual-arrow signal section that is capable of alternating between the display of a GREEN ARROW signal indication and the display of a YELLOW ARROW signal indication, both pointing in the same direction, shall be permitted provided that both colors are never displayed simultaneously.

The arrow, which shall show only one direction, shall be the only illuminated part of an arrow signal indication.

Arrows shall be pointed:

- A. Vertically upward to indicate a straight-through movement, or
- B. Horizontally in the direction of the turn to indicate a turn at approximately or greater more than a right angle, or
- C. Upward with a slope at an angle approximately equal to that of the turn if the angle of the turn is substantially less than a right angle, or
- D. In a manner that directs the driver through the turn if a U-turn arrow is used (see Figure 4E-1 4D-1).

Figure 4E-1. Example of U-Turn Signal Face

Except as provided in Paragraph_10-11, the requirements of Chapters 1 and 2 of the publication entitled "Vehicle Traffic Control Signal Heads Equipment and Materials Standards of the Institute of Transportation Engineers" (see Section_1A.11-1A.05) that pertain to the aspects of the signal head design that affect the display of the signal indications shall be met for signal optical units that use incandescent lamps within optical assemblies that include lenses. Except as provided in Paragraph 11, the requirements of the publications entitled "Vehicle Traffic Control Signal Heads: Light Emitting Diode (LED) Circular Signal Supplement" and "Vehicle Traffic Control Signal Heads: Light Emitting Diode (LED) Vehicle Arrow Traffic Signal Supplement" (see Section 1A.05) that pertain to the aspects of the signal head design that affect the display of the signal indications shall be met for light emitting diode (LED) traffic signal modules. Edited to reflect Official Interpretation 4(9)-28

Guidance:

The intensity and distribution of light from each illuminated signal lens <u>or LED signal module</u> should comply with the publications entitled "Vehicle Traffic Control Signal Heads" and "Traffic Signal Lamps" (see Section 1A.11) specified in Paragraph 10, as appropriate.

Standard:

Support: Standard changed to Support; incorporated into existing Paragraph 12

References to signal lenses in this section shall are not be used intended to limit signal optical units to incandescent lamps within optical assemblies that include lenses. Research has resulted in signal optical units

that are not lenses, such as, but not limited to, light emitting diode (LED) traffic signal modules. Some units are practical for all signal indications, and some are practical for specific types such as visibility-limited signal indications.

Guidance:

 If a signal indication is so bright that it causes excessive glare during nighttime conditions, some form of automatic dimming should be used to reduce the brilliance of the signal indication.

Section 4D.07 4E.02 Size of Vehicular Signal Indications

Standard:

There shall be two nominal diameter sizes for vehicular signal indications: 8 inches and 12 inches.

Twelve-inch signal indications shall be used for all arrow signal indications.

Except as provided in Pharagraph 3 below the next paragraph, 12-inch signal indications shall be used for all <u>circular</u> signal <u>sections</u> indications in all new signal faces.

Option:

Eight-inch circular signal indications may be used in new signal faces only for:

- A. The green or flashing yellow signal indications in an emergency-vehicle traffic control signal (see 4G.02-Section 4N.02);
- B. The circular indications in signal faces controlling the approach to the downstream location where two adjacent signalized locations are close to each other and it is not practical because of factors such as high approach speeds, horizontal or vertical curves, or other geometric factors to install visibility-limited signal faces for the downstream approach;
- C. The circular indications in a signal face that is located less than 120 feet from the stop line on a roadway with a posted or statutory speed limit <u>or operating speed</u> of 30 mph or less;
- D. The circular indications in a supplemental near-side signal face;
- E. The circular indications in a supplemental signal face installed for the sole purpose of controlling pedestrian movements (see Section 4D.03-4D.02) rather than vehicular movements; and
- F. The circular indications in a signal face installed for the sole purpose of controlling a bikeway or a bicycle movement; and
- G. The circular indications in a flashing beacon (see Chapter 4S). Added to reflect Official Interpretation 4(09)-7(I)

Existing 8-inch circular signal indications that are not included in Items A through_F-G in_Paragraph 3 the previous paragraph may be retained for the remainder of their useful service life.

Different sizes of signal indications may be used in the same signal face or signal head, provided that the signal face or signal head complies with the requirements contained in Paragraphs 2 through 4.

Section 4D.08 4E.03 Positions of Signal Indications Within a Signal Face – General

Support:

Standardization of the number and arrangements of signal sections in vehicular traffic control signal faces enables road users who are color vision deficient to identify the illuminated color by its position relative to other signal sections.

Standard:

Unless otherwise provided in this Manual for a particular application, each signal face at a signalized location shall have three, four, or five signal sections. Unless otherwise provided in this Manual for a particular application, if a vertical signal face includes a cluster (see Section_4D.09_4E.04), the signal face shall have at least three vertical positions.

A single-section signal face shall be permitted at a traffic control signal if it consists of a continuously-displayed GREEN ARROW signal indication that is being used to indicate a continuous movement.

The signal sections in a signal face shall be arranged in a vertical or horizontal straight line, except as otherwise provided in Section_4D.09_4E.04.

The arrangement of adjacent signal sections in a signal face shall follow the relative positions listed in Sections 4D.09 or 4D.10 4E.04 or 4E.05, as applicable.

If a signal section that displays a CIRCULAR YELLOW signal indication is used, it shall be located between the signal section that displays the red signal indication and all other signal sections.

If a U-turn arrow signal section is used in a signal face for a U-turn to the left, its position in the signal face shall be the same as stated in Sections 4D.09 and 4D.10 4E.04 and 4E.05 for a left-turn arrow signal section of the same color. If a U-turn arrow signal section is used in a signal face for a U-turn to the right, its position in the signal face shall be the same as stated in Sections 4D.09 and 4D.10 4E.04 and 4E.05 for a right-turn arrow signal section of the same color.

A U-turn arrow signal indication pointing to the left shall not be used in a signal face that also contains a left-turn arrow signal indication. A U-turn arrow signal indication pointing to the right shall not be used in a signal face that also contains a right-turn arrow signal indication.

1

2

3

4

5

6

7

8

9

10

11

12

13 14

15

16

17

18

19

20

21

22

23

24

25 26

27

28

29

30

31

32

33

34

35

36

37

38

39

41

42

47

50

Within a signal face, two identical CIRCULAR RED or RED ARROW signal indications may be displayed immediately horizontally adjacent to each other in a vertical signal face (see Drawing A in Figure 4E-2) or immediately horizontally adjacent to each other in a horizontal signal face (see Drawing B in Figure 4E-2 4D-2) for emphasis.

Horizontally-arranged and vertically-arranged signal faces may be used on the same approach provided they are separated to meet the lateral separation spacing required in Section 4D.13-4D.06. Support:

Figure 4E-24D-2 illustrates some of the typical arrangements of signal sections in signal faces that do not control separate turning movements. Figures 4F-1 through 4F-7 4D-6 through 4D-12 illustrate the typical arrangements of signal sections in left-turn signal faces. Figures 4F-8 through 4F-14 4D-13 through 4D-19 illustrate the typical arrangements of signal sections in right-turn signal faces.

Figure 4E-2. Typical Arrangements of Signal Sections in Signal Faces That Do Not Control **Turning Movements**

Section 4D.09 4E.04 Positions of Signal Indications Within a Vertical Signal Face

Standard:

In each vertically-arranged signal face, all signal sections that display red signal indications shall be located above all signal sections that display vellow and green signal indications.

In vertically-arranged signal faces, each signal section that displays a YELLOW ARROW signal indication shall be located above the signal section that displays the GREEN ARROW signal indication to which it applies.

The relative positions of signal sections in a vertically-arranged signal face, from top to bottom, shall be as follows:

CIRCULAR RED

Steady and/or flashing left-turn RED ARROW

Steady and/or flashing right-turn RED ARROW

CIRCULAR YELLOW

40 CIRCULAR GREEN

Straight-through GREEN ARROW

Steady left-turn YELLOW ARROW

43 Flashing left-turn YELLOW ARROW

44 **Left-turn GREEN ARROW**

45 **Steady right-turn YELLOW ARROW**

Flashing right-turn YELLOW ARROW 46

Right-turn GREEN ARROW

48 If a dual-arrow signal section (capable of alternating between the display of a GREEN ARROW 49

and a YELLOW ARROW signal indication see Section 4E.01) is used in a vertically-arranged signal

face, the dual-arrow signal section shall occupy the same position relative to the other sections as the

signal section that displays the GREEN ARROW signal indication in a vertically-arranged signal face would occupy.

Option:

3

4

5

6 7

8

9

10

11 12

13

14

15

16 17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

39

41

42

44

46

47

49

In a vertically-arranged signal face, signal sections that display signal indications of the same color may be arranged horizontally adjacent to each other at right angles to the basic straight line arrangement to form a clustered signal face (see Figures 4E-2, 4F-4, 4F-6, 4F-11, 4F-13, and 4F-15-4D-2, 4D-9, 4D-11, 4D-16, and 4D-18).

Standard:

Such clusters shall be limited to the following:

- A. Two identical signal sections,
- B. Two or three different signal sections that display signal indications of the same color, or
- C. For only the specific case described in Section_4D.25 4F.16 (see Drawing B of Figure 4F-15 4D-20), two signal sections, one of which displays a GREEN ARROW signal indication and the other of which displays a flashing YELLOW ARROW signal indication.

Except as otherwise provided in Sections 4F.08 and 4F.15 for a three-section separate turn signal face with a flashing YELLOW ARROW signal indication, the signal section that displays a flashing yellow signal indication during steady mode operation:

- A. Shall not be placed in the same vertical position as the signal section that displays a steady yellow signal indication, and
- B. Shall be placed below the signal section that displays a steady yellow signal indication.

Support:

Sections_4F.02 and 4G.04-4J.02 and 4N.02 contain exceptions to the provisions of this Section that are applicable to hybrid beacons.

Section 4D.10 4E.05 Positions of Signal Indications Within a Horizontal Signal Face

Standard:

In each horizontally-arranged signal face, all signal sections that display red signal indications shall be located to the left of all signal sections that display yellow and green signal indications.

In horizontally-arranged signal faces, each signal section that displays a YELLOW ARROW signal indication shall be located to the left of the signal section that displays the GREEN ARROW signal indication to which it applies.

The relative positions of signal sections in a horizontally-arranged signal face, from left to right, shall be as follows:

CIRCULAR RED

Steady and/or flashing left-turn RED ARROW

Steady and/or flashing right-turn RED ARROW

36 **CIRCULAR YELLOW**

37 Steady left-turn YELLOW ARROW

38 Flashing left-turn YELLOW ARROW

Left-turn GREEN ARROW

40 **CIRCULAR GREEN**

Straight-through GREEN ARROW

Steady right-turn YELLOW ARROW

43 Flashing right-turn YELLOW ARROW

Right-turn GREEN ARROW

45 If a dual-arrow signal section (eapable of alternating between the display of a GREEN ARROW

and a YELLOW ARROW signal indication see Section 4E.01) is used in a horizontally-arranged signal

face, the signal section that displays the dual left-turn arrow signal indication shall be located

48 immediately to the right of the signal section that displays the CIRCULAR YELLOW signal indication,

the signal section that displays the straight-through GREEN ARROW signal indication shall be located

50 immediately to the right of the signal section that displays the CIRCULAR GREEN signal indication,

1	and the signal section that displays the dual right-turn arrow signal indication shall be located to the
2	right of all other signal sections.
3	The signal section that displays a flashing yellow signal indication during steady mode operation:
4	A. Shall not be placed in the same horizontal position as the signal section that displays a steady
5	yellow signal indication, and
6	B. Shall be placed to the right of the signal section that displays a steady yellow signal indication.

7

Section 4D.05 4F.01 Application of Steady and Flashing Signal Indications during Steady (Stop-and-Go) Operation

Standard:

When a traffic control signal is being operated in a steady (stop-and-go) mode, at least one indication in each signal face shall be displayed at any given time.

A signal face(s) that controls a particular vehicular movement during any interval of a cycle shall control that same movement during all intervals of the cycle.

Steady and flashing signal indications shall be applied as follows:

A. A steady CIRCULAR RED signal indication:

- 1. Shall be displayed when it is intended to prohibit traffic, except pedestrians directed by a pedestrian signal head, from entering the intersection or other controlled area. Turning after stopping is permitted as stated in Item C.1 in Paragraph 3-1 of Section 4D.044A.03.
- 2. Shall be displayed with the appropriate GREEN ARROW signal indications when it is intended to permit traffic to make a specified turn or turns, and to prohibit traffic from proceeding straight ahead through the intersection or other controlled area, except in protected only mode operation (see Sections 4D.19 and 4D.234F.06 and 4F.13), or in protected/permissive mode operation with separate turn signal faces (see Sections 4D.20 and 4D.244F.08 and 4F.15).

B. A steady CIRCULAR YELLOW signal indication:

- 1. Shall be displayed following a CIRCULAR GREEN or straight-through GREEN ARROW signal indication in the same signal face.
- 2. Shall not be displayed in conjunction with the change from the CIRCULAR RED signal indication to the CIRCULAR GREEN signal indication.
- 3. Shall be followed by a CIRCULAR RED signal indication except that, when entering preemption operation, the return to the previous CIRCULAR GREEN signal indication shall be permitted following a steady CIRCULAR YELLOW signal indication (see Section 4D.274F.19).
- 4. Shall not be displayed to an approach from which drivers are turning left permissively <u>using a shared signal face</u> or making a U-turn to the left permissively <u>using a shared signal face</u> unless one of the following conditions exists:
 - (a) A steady CIRCULAR YELLOW signal indication is also simultaneously being displayed to the opposing approach;
 - (b) An engineering study has determined that, because of unique intersection conditions, the condition described in Item (a) cannot reasonably be implemented without causing significant operational or safety problems and that the volume of impacted left-turning or U-turning traffic is relatively low, and those left-turning or U-turning drivers are advised that a steady CIRCULAR YELLOW signal indication is not simultaneously being displayed to the opposing traffic if this operation occurs continuously by the installation near the left most signal head of a W25-1 sign (see Section 2C.482C.46) with the legend ONCOMING TRAFFIC HAS EXTENDED GREEN; or
 - (c) Drivers are advised of the operation if it occurs only occasionally, such as during a preemption sequence, by the installation near the left most signal head of a W25-2 sign (see Section 2C.48-2C.46) with the legend ONCOMING TRAFFIC MAY HAVE EXTENDED GREEN.
- C. A steady CIRCULAR GREEN signal indication shall be displayed only when it is intended to permit traffic to proceed in any direction that is lawful and practical.
- D. A steady RED ARROW signal indication shall be displayed when it is intended to prohibit traffic, except pedestrians directed by a pedestrian signal head, from entering the intersection or other controlled area to make the indicated turn. Except as described in Item C.2 in

- E. A flashing RED ARROW signal indication shall be displayed as part of a steady (stop-and-go) mode of operation only when it is intended to permit traffic, after coming to a full stop, to cautiously enter the intersection to make a turn in the direction indicated by the arrow after yielding to pedestrians, if any, and/or to opposing traffic, if any.
- F. A steady YELLOW ARROW signal indication:

- 1. Shall be displayed in the same direction as a GREEN ARROW signal indication following a GREEN ARROW signal indication in the same signal face, unless:
 - (a) The GREEN ARROW signal indication and a CIRCULAR GREEN (or straight-through GREEN ARROW) signal indication terminate simultaneously in the same signal face, or
 - (b) The green arrow is a straight-through GREEN ARROW (see Item B.1).
- 2. Shall be displayed in the same direction as a flashing YELLOW ARROW signal indication or flashing RED ARROW signal indication following a flashing YELLOW ARROW signal indication or flashing RED ARROW signal indication in the same signal face, when the flashing arrow indication is displayed as part of a steady mode operation, if the signal face will subsequently display a steady red signal indication.
- 3. Shall not be displayed in conjunction with the change from a steady RED ARROW, flashing RED ARROW, or flashing YELLOW ARROW signal indication to a GREEN ARROW signal indication, except when entering preemption operation as provided in Item 5(a).
- 4. Shall not be displayed when any conflicting vehicular movement has a green or yellow signal indication (except for the situation regarding U-turns to the left provided in Paragraph 4) or any conflicting pedestrian movement has a WALKING PERSON (symbolizing WALK) or flashing UPRAISED HAND (symbolizing DONT WALK) signal indication, except that a steady left-turn (or U-turn to the left) YELLOW ARROW signal indication used to terminate a flashing left-turn (or U-turn to the left) YELLOW ARROW or a flashing left-turn (or U-turn to the left) RED ARROW signal indication in a signal face controlling a permissive left-turn (or U-turn to the left) movement as described in Sections 4F.04 and 4F.08 shall be permitted to be displayed when a CIRCULAR YELLOW signal indication is displayed for the opposing through movement. Vehicles departing in the same direction shall not be considered in conflict if, for each turn lane with moving traffic, there is a separate departing departure lane, and pavement markings or raised channelization clearly indicate which departure lane to use.
- 5. Shall not be displayed to terminate a flashing arrow signal indication on an approach from which drivers are turning left permissively or making a U-turn to the left permissively unless one of the following conditions exists:
 - (a) A steady CIRCULAR YELLOW signal indication is also simultaneously being displayed to the opposing approach;
 - (b) An engineering study has determined that, because of unique intersection conditions, the condition described in Item (a) cannot reasonably be implemented without causing significant operational or safety problems and that the volume of impacted left-turning or U-turning traffic is relatively low, and those left-turning or U-turning drivers are advised that a steady CIRCULAR YELLOW signal indication is not simultaneously being displayed to the opposing traffic if this operation occurs continuously by the installation near the left most signal head of a W25-1 sign (see Section 2C.48-2C.46) with the legend ONCOMING TRAFFIC HAS EXTENDED GREEN; or
 - (c) Drivers are advised of the operation if it occurs only occasionally, such as during a preemption sequence, by the installation near the left most signal head of a W25-2 sign (see Section 2C.482C.46) with the legend ONCOMING TRAFFIC MAY HAVE EXTENDED GREEN.
- 6. Shall be terminated by a RED ARROW signal indication for the same direction or a CIRCULAR RED signal indication except:

- 4 5 6 7
- 8 9 10 11

17

18

19

12

24

25

> 31 32 33

34

35

30

36 37 38

> 40 41

42

39

43 44 45

46 47

Support:

Standard:

48

49

50

51

Notice of Proposed Amendments - Part 4

December 2020

(b) When the movement controlled by the arrow is to continue on a permissive mode basis during an immediately following signal phase, the display of a CIRCULAR GREEN signal indication or flashing YELLOW ARROW signal indication shall be permitted following a steady YELLOW ARROW signal indication. G. A flashing YELLOW ARROW signal indication shall be displayed as part of a steady (stop-

indication or a flashing arrow signal indication shall be permitted following a steady

and-go) mode of operation only when it is intended to permit traffic to cautiously enter the intersection to make a turn in the direction indicated by the arrow after yielding to pedestrians, if any, and/or to opposing traffic, if any,

(a) When entering preemption operation, the display of a GREEN ARROW signal

H. A steady GREEN ARROW signal indication:

YELLOW ARROW signal indication.

- 1. Shall be displayed only to allow vehicular movements, in the direction indicated, that are not in conflict with other vehicles moving on a green or yellow signal indication (except for the situation regarding U-turns provided in Paragraph 4 and straight-thru GREEN ARROWs provided in Paragraph 5), even if the other vehicles are required to yield the right-of-way to the traffic moving on the GREEN ARROW signal indication, and are not in conflict with pedestrians crossing in compliance with a WALKING PERSON (symbolizing WALK) or flashing UPRAISED HAND (symbolizing DONT WALK) signal indication. Vehicles departing in the same direction shall not be considered in conflict if, for each turn lane with moving traffic, there is a separate departing departure lane, and pavement markings or raised channelization clearly indicate which departure lane to use.
- 2. Shall be displayed on a signal face that controls a left-turn movement when said movement is not in conflict with other vehicles moving on a green or yellow signal indication (except for the situation regarding U-turns provided in Paragraph 4) and is not in conflict with pedestrians crossing in compliance with a WALKING PERSON (symbolizing WALK) or flashing UPRAISED HAND (symbolizing DONT WALK) signal indication. Vehicles departing in the same direction shall not be considered in conflict if, for each turn lane with moving traffic, there is a separate departing departure lane, and pavement markings or raised channelization clearly indicate which departure lane to use.
- 3. Shall not be required on the stem of a T-intersection or for turns from a one-way street.

Option:

If U-turns are permitted from the approach and a right-turn GREEN ARROW signal indication is simultaneously being displayed to road users making a right turn from the conflicting approach to the left, road users making a U-turn may be advised of the operation by the installation near the left-turn signal face of a U-TURN YIELD TO RIGHT TURN (R10-16) sign (see Section 2B.53 2B.63).

If not otherwise prohibited, a A steady straight-through GREEN ARROW signal indication may be used instead of a CIRCULAR GREEN signal indication in a signal face to discourage wrong way turns under the following conditions, even if opposed by a simultaneous permissive left-turn movement:

- A. on an approach intersecting a one-way street; to discourage wrong-way turns
- B. on an approach intersecting an interchange exit ramp; or
- C. on an approach with unique geometric design that prohibits turns.

If not otherwise prohibited, steady red, yellow, and green turn arrow signal indications may be used instead of steady circular red, yellow, and green signal indications in a signal face on an approach where all traffic is required to turn or where the straight-through movement is not physically possible.

Section 4D.25 4F.16 contains information regarding the signalization of approaches that have a sharedcombined left-turn/right-turn lane and no through movement.

- If supplemental signal faces are used, the following limitations shall apply:
- A. Left-turn arrows and U-turn arrows to the left shall not be used in near-right signal faces.

B. Right-turn arrows and U-turn arrows to the right shall not be used in far-left signal faces. A far-side median-mounted signal face shall be considered a far-left signal for this application.

A straight-through RED ARROW signal indication or a straight-through YELLOW ARROW signal indication shall not be displayed on any signal face, either alone or in combination with any other signal indication.

The following combinations of signal indications shall not be simultaneously displayed on any one signal face:

- A. CIRCULAR RED with CIRCULAR YELLOW with CIRCULAR RED;
- B. CIRCULAR GREEN with CIRCULAR RED; or
- C. Straight-through GREEN ARROW with CIRCULAR RED;

Additionally Except as provided in Paragraph 13, the above combinations shall not be simultaneously displayed on an approach as a result of the combination of displays from multiple signal faces unless the display is created by a signal face(s) devoted exclusively to the control of a right-turning movement and:

- A. The signal face(s) controlling the right-turning movement is visibility-limited from the adjacent through movement or positioned to minimize potential confusion to approaching road users, or
- B. A RIGHT TURN SIGNAL (R10-10) sign (see Sections_4D.21 through 4D.24 4F.09, 4F.11, 4F.13, and 4F.15) is mounted adjacent to the signal face(s) controlling the right-turning movement.

<u>Except as provided in Paragraph 13</u>, the following combinations of signal indications shall not be simultaneously displayed on any one signal face or as a result of the combination of displays from multiple signal faces on an approach:

- A. CIRCULAR GREEN with CIRCULAR YELLOW;
- B. Straight-through GREEN ARROW with CIRCULAR YELLOW;
- C. GREEN ARROW with YELLOW ARROW pointing in the same direction;
- D. RED ARROW with YELLOW ARROW with RED ARROW pointing in the same direction; or
- E. GREEN ARROW with RED ARROW pointing in the same direction.

If a separate signal face is provided at a pre-signal (see Section 8D.11) for a left-turn and/or right-turn lane that extends from the downstream signalized intersection back to and across a grade crossing, the following combinations of signal indications shall be permitted to be simultaneously displayed as a result of the combination of displays from multiple signal faces at the pre-signal:

- A. Straight-through GREEN ARROW with CIRCULAR RED;
- B. Straight-through GREEN ARROW with CIRCULAR YELLOW; and
- C. CIRCULAR YELLOW with CIRCULAR RED.

Except as otherwise provided in Sections 4F.03 and 4G.04 4F.08, 4F.15, 4J.03, and 4N.03, the same signal section shall not be used to display both a flashing yellow and a steady yellow indication during steady mode operation. Except as otherwise provided in Sections 4D.18, 4D.20, 4D.22, 4D.24 4F.04, 4F.08, 4F.11, and 4F.13, the same signal section shall not be used to display both a flashing red and a steady red indication during steady mode operation.

Guidance:

No movement that creates an unexpected crossing of pathways of moving vehicles or pedestrians should be allowed during any green or yellow interval, except when all three of the following conditions are met:

- A. The movement involves only slight conflict, and
- B. Serious traffic delays are substantially reduced by permitting the conflicting movement, and
- C. Drivers and pedestrians subjected to the unexpected conflict are effectively warned thereof by a sign.

Section 4D.17-4F.02 Signal Indications for Left-Turn Movements – General

Standard Support: Standard changed to Support

In Sections 4D.17-4D.20-4F.03 through 4F.08, provisions applicable to left-turn movements and left-turn lanes shall are also apply applicable to signal indications for U-turns to the left that are provided at locations where left turns are prohibited or not geometrically possible.

Support:

- Left-turning traffic is controlled by one of four modes as follows:
 - A. Permissive Only Mode—turns made on a CIRCULAR GREEN signal indication, a flashing left-turn YELLOW ARROW signal indication, or a flashing left-turn RED ARROW signal indication after yielding to pedestrians, if any, and/or opposing traffic, if any.
 - B. Protected Only Mode—turns made only when a left-turn GREEN ARROW signal indication is displayed.
 - C. Protected/Permissive Mode—both modes can occur on an approach during the same cycle.
 - D. Variable Left-Turn Mode—the operating mode changes among the protected only mode and/or the protected/permissive mode and/or the permissive only mode during different periods of the day or as traffic conditions change.

Option:

In areas having a high percentage of older drivers, special consideration may be given to the use of protected only mode left-turn phasing, when appropriate.

Stand

During a permissive left-turn movement, the signal faces for through and right-turning traffic on the opposing approach shall simultaneously display green or steady yellow signal indications. If pedestrians crossing the lane or lanes used by the permissive left-turn movement to depart the intersection are controlled by pedestrian signal heads, the signal indications displayed by those pedestrian signal heads shall not be limited to any particular display during the permissive left-turn movement.

During a protected left-turn movement, the signal faces for through traffic on the opposing approach shall simultaneously display steady CIRCULAR RED signal indications. During a protected left-turn movement, a GREEN ARROW or a YELLOW ARROW signal indication shall not simultaneously be displayed to right-turn traffic on the opposing approach, except where a separate departure lane is available for each left-turn and right-turn lane with moving traffic and pavement markings or raised channelization clearly indicate which departure lane to use (see Item H.1 in Paragraph 3 in Section 4F.01). If pedestrians crossing the lane or lanes used by the protected left-turn movement to depart the intersection are controlled by pedestrian signal heads, the pedestrian signal heads shall display a steady UPRAISED HAND (symbolizing DONT WALK) signal indication during the protected left-turn movement.

If a combined left-turn/through lane exists on an approach, a protected only mode left-turn movement that does not begin and terminate at the same time as the adjacent through movement a left-turn GREEN ARROW or left-turn YELLOW ARROW signal indication or a flashing left-turn RED ARROW signal indication shall not be provided on displayed to an the approach simultaneously with a CIRCULAR RED signal indication for the through movement unless an exclusive left-turn lane exists, and a left-turn RED ARROW signal indication shall not be displayed to the approach simultaneously with a CIRCULAR GREEN or CIRCULAR YELLOW signal indication for the through movement.

A yellow change interval for the left-turn movement shall not be displayed when the status of the left-turn operation is changing from permissive to protected within any given signal sequence.

If the operating mode changes among the protected only mode and/or the protected/permissive mode and/or the permissive only mode during different periods of the day or as traffic conditions change, the requirements in Sections 4D.18 through 4D.20 4F.03 through 4F.08 that are appropriate to that mode of operation shall be met, subject to the following:

- A. The CIRCULAR GREEN and CIRCULAR YELLOW signal indications shall not be displayed when operating in the protected only mode.
- B. The left-turn GREEN ARROW and left-turn YELLOW ARROW signal indications shall not be displayed when operating in the permissive only mode.

Option: Added to reflect Official Interpretation 4(09)-15(I) and Revised to reflect Official Change Request 4(09)-42

When variable-mode left-turn phasing is used for an approach that includes both an exclusive left-turn lane and a combined left-and-through lane and a flashing yellow arrow is used as the permissive turn display, a five-section shared left-turn signal face containing both circular and arrow indications may be used in

combination with one or more separate left-turn signal faces for the exclusive left-turn lane(s) on the same approach. The steady left-turn YELLOW ARROW signal indication and the flashing left-turn YELLOW ARROW signal indication may be displayed in the same section of the five-section shared left-turn signal face.

Additional static signs or changeable message signs may be used to meet the requirements for the variable left-turn mode or to inform drivers that left-turn green arrows will not be available during certain times of the day.

Support:

2 3

Sections 4D.17 through 4D.20 4F.03 through 4F.08 describe the use of the following two types of signal faces for controlling left-turn movements:

- A. Shared signal face This type of signal face controls both the left-turn movement and the adjacent movement (usually the through movement) and can serve as one of the two required primary signal faces for the adjacent movement. A shared signal face always displays the same color of circular indication that is displayed by the signal face or faces for the adjacent movement. If a shared signal face that provides protected/permissive mode left turns is mounted overhead at the intersection for an approach that includes an exclusive left-turn lane, it is usually positioned over or slightly to the right of the extension of the lane line separating the left-turn lane from the adjacent lane. If a shared signal face that provides protected/permissive mode left turns is mounted overhead for an approach that does not include an exclusive left-turn lane, it is usually positioned over the center of the combined left-turn/straight-through lane.
- B. Separate left-turn signal face This type of signal face controls only the left-turn movement and cannot serve as one of the two required primary signal faces for the adjacent movement (usually the through movement) because it displays signal indications that are applicable only to the left-turn movement. This type of signal face is used only for an approach that has an exclusive left-turn lane(s). If a separate left-turn signal face is mounted overhead at the intersection, it is positioned over the extension of the exclusive left-turn lane. In a separate left-turn signal face, a flashing left-turn YELLOW ARROW signal indication or a flashing left-turn RED ARROW signal indication is used to control permissive left-turning movements.

Section 4D.13-4D.06 contains provisions regarding the lateral positioning of signal faces that control left-turn movements.

It is not necessary that the same mode of left-turn operation or same type of left-turn signal face be used on every approach to a signalized location. Selecting different modes and types of left-turn signal faces for the various approaches to the same signalized location is acceptable.

Option:

A signal face that is shared by left-turning and right-turning traffic may be provided for a shared combined left-turn/right-turn lane on an approach that has no through traffic (see Section 4D.25-4F.16).

Section 4D.18 4F.03 Signal Indications for Permissive Only Mode Left-Turn Movements in a Shared Signal Face Paragraphs from this Section were relocated to new Section 4F.04

Standard:

If a shared signal face is provided for a permissive only mode left turn, it shall meet the following requirements (see Figure $\frac{4F-1}{4D-6}$):

- A. It shall be capable of displaying the following signal indications: steady CIRCULAR RED, steady CIRCULAR YELLOW, and CIRCULAR GREEN. Only one of the three indications shall be displayed at any given time.
- B. During the permissive left-turn movement, a CIRCULAR GREEN signal indication shall be displayed.
- C. A permissive only shared signal face, regardless of where it is positioned and regardless of how many adjacent through signal faces are provided, shall always simultaneously display the same color of circular indication that the adjacent through signal face or faces display.
- D. If the permissive only mode is not the only left-turn mode used for the approach, the signal face shall be the same shared signal face that is used for the protected/permissive mode (see Section

1 2	4D.20-4F.07) except that the left-turn GREEN ARROW and left-turn YELLOW ARROW signal indications shall not be displayed when operating in the permissive only mode.
3	Figure 4F-1. Typical Position and Arrangements of Shared Signal Faces for Permissive
4	Only Mode Left Turns

<u>Section 4F.04 Signal Indications for Permissive Only Mode Left-Turn Movements in a Separate Signal Face</u> Paragraphs were relocated from existing Section 4D.18

Standard:

A separ eft-turn signal face shall not be used for an approach that does not include an exclusive left-turn lane.

If a separate left-turn signal face is being operated in a permissive only left-turn mode, a CIRCULAR GREEN signal indication shall not be used in that face.

If a separate left-turn signal face is being operated in a permissive only left-turn mode and a flashing left-turn YELLOW ARROW signal indication is provided, it shall meet the following requirements (see Figure 4F-24D-7):

- A. It shall be capable of displaying the following signal indications: steady left-turn RED ARROW, steady left-turn YELLOW ARROW, and flashing left-turn YELLOW ARROW. Only one of the three indications shall be displayed at any given time.
- B. During the permissive left-turn movement, a flashing left-turn YELLOW ARROW signal indication shall be displayed.
- C. A steady left-turn YELLOW ARROW signal indication shall be displayed following the flashing left-turn YELLOW ARROW signal indication.
- D. It shall be permitted to display a flashing left-turn YELLOW ARROW signal indication for a permissive left-turn movement while the signal faces for the adjacent through movement display steady CIRCULAR RED signal indications and the opposing left-turn signal faces display left-turn GREEN ARROW signal indications for a protected left-turn movement.
- E. During steady mode (stop-and-go) operation, the signal section that displays the steady left-turn YELLOW ARROW signal indication during change intervals shall not be used to display the flashing left-turn YELLOW ARROW signal indication for permissive left turns unless a signal section capable of alternating between the display of a steady YELLOW ARROW and a flashing YELLOW ARROW signal indication is used. Added to reflect Official Change Request 4(09)-42
- F. During flashing mode operation (see <u>Section</u> Chapter 4G), the display of a flashing left-turn YELLOW ARROW signal indication shall be only from the signal section that displays a steady left-turn YELLOW ARROW signal indication during steady mode (stop-and-go) operation.
- G. If the permissive only mode is not the only left-turn mode used for the approach, the signal face shall be the same separate left-turn signal face with a flashing YELLOW ARROW signal indication that is used for the protected/permissive mode (see Section 4D.20-4F.08) except that the left-turn GREEN ARROW signal indication shall not be displayed when operating in the permissive only mode.

Figure 4F-2. Typical Position and Arrangements of Separate Signal Faces with Flashing Yellow Arrow for Permissive Only Mode Left Turns

Option:

A separate left-turn signal face with a flashing left-turn RED ARROW signal indication during the permissive left-turn movement may be used for unusual geometric conditions, such as wide medians with offset left-turn lanes, but only when an engineering study determines that each and every vehicle must successively come to a full stop before making a permissive left turn.

Standard:

If a separate left-turn signal face is being operated in a permissive only left-turn mode and a flashing left-turn RED ARROW signal indication is provided, it shall meet the following requirements (see Figure 4F-3-4D-8):

- A. It shall be capable of displaying the following signal indications: steady or flashing left-turn RED ARROW, steady left-turn YELLOW ARROW, and left-turn GREEN ARROW. Only one of the three indications shall be displayed at any given time. The GREEN ARROW indication is required in order to provide a three-section signal face, but shall not be displayed during the permissive only mode.
- B. During the permissive left-turn movement, a flashing left-turn RED ARROW signal indication shall be displayed, thus indicating that each and every vehicle must successively come to a full stop before making a permissive left turn.
- C. A steady left-turn YELLOW ARROW signal indication shall be displayed following the flashing left-turn RED ARROW signal indication.
- D. It shall be permitted to display a flashing left-turn RED ARROW signal indication for a permissive left-turn movement while the signal faces for the adjacent through movement display steady CIRCULAR RED signal indications and the opposing left-turn signal faces display left-turn GREEN ARROW signal indications for a protected left-turn movement.
- E. A supplementary sign shall not be required. If used, it shall be a LEFT TURN YIELD ON FLASHING RED ARROW AFTER STOP (R10-27) sign (see Section 2B-27-2B.63).

Figure 4F-3. Typical Position and Arrangements of Separate Signal Faces with Flashing Red Arrow for Permissive Only Mode and Protected/Permissive Mode Left Turns

Option:

 The requirements of Item A in Paragraph 5 may be met by a vertically-arranged signal face with a horizontal cluster of two left-turn RED ARROW signal indications, the left-most of which displays a steady indication and the right-most of which displays a flashing indication (see Figure 4F-3-4D-8).

Section 4D.19 4F.05 Signal Indications for Protected Only Mode Left-Turn Movements in a Shared Signal Face Paragraphs from this Section were relocated to new Section 4F.06

Standard:

A shared signal face shall not be used for protected only mode left turns unless the CIRCULAR GREEN and left-turn GREEN ARROW signal indications always begin and terminate together. If a shared signal face is provided for a protected only mode left turn, it shall meet the following requirements (see Figure 4F-44D-9):

- A. It shall be capable of displaying the following signal indications: steady CIRCULAR RED, steady CIRCULAR YELLOW, CIRCULAR GREEN, and left-turn GREEN ARROW. Only one of the three colors shall be displayed at any given time.
- B. During the protected left-turn movement, the shared signal face shall simultaneously display both a CIRCULAR GREEN signal indication and a left-turn GREEN ARROW signal indication.
- C. The shared signal face shall always simultaneously display the same color of circular indication that the adjacent through signal face or faces display.
- D. If the protected only mode is not the only left-turn mode used for the approach, the signal face shall be the same shared signal face that is used for the protected/permissive mode (see Section_4D.20-4F.07).

Figure 4F-4. Typical Positions and Arrangements of Shared Signal Faces for Protected Only Mode Left Turns

Option:

A straight-through GREEN ARROW signal indication may be used instead of the CIRCULAR GREEN signal indication in Items A and B in Paragraph 1 on an approach where right turns are prohibited and a straight-through GREEN ARROW signal indication is also used instead of a CIRCULAR GREEN signal indication in the other signal face(s) for through traffic.

Section 4F.06 Signal Indications for Protected Only Mode Left-Turn Movements in a Separate Signal Face These paragraphs are from existing Section 4D.19

Standard:

A separate left-turn signal face shall not be used for an approach that does not include an exclusive left-turn lane.

If a separate left-turn signal face is provided for a protected only mode left turn, it shall meet the following requirements (see Figure 4F-54D-10):

- A. It shall be capable of displaying, the following signal indications: steady left-turn RED ARROW, steady left-turn YELLOW ARROW, and left-turn GREEN ARROW. Only one of the three indications shall be displayed at any given time. A signal instruction sign shall not be required with this set of signal indications. If used, it shall be a LEFT ON GREEN ARROW ONLY (R10-5) sign (see Section 2B.63). Deleted to reflect Official Change Request 4(09)-73(C)
- B. During the protected left-turn movement, a left-turn GREEN ARROW signal indication shall be displayed.
- C. A steady left-turn YELLOW ARROW signal indication shall be displayed following the left-turn GREEN ARROW signal indication.
- D. If the protected only mode is not the only left-turn mode used for the approach, the signal face shall be the same separate left-turn signal face that is used for the protected/permissive mode (see Section 4F.08 and Figures 4F-34D-8 and 4F-74D-12) except that the flashing left-turn YELLOW ARROW or flashing left-turn RED ARROW signal indication shall not be displayed when operating in the protected only mode.

Figure 4F-5. Typical Position and Arrangements of Separate Signal Faces for Protected Only Mode Left Turns

Section 4D.20 4F.07 Signal Indications for Protected/Permissive Mode Left-Turn Movements in a Shared Signal Face Paragraph in this Section were relocated to new Section 4F.08

Standard:

 If a shared signal face is provided for a protected/permissive mode left turn, it shall meet the following requirements (see Figure $\frac{4F-6}{4D-11}$):

- A. It shall be capable of displaying the following signal indications: steady CIRCULAR RED, steady CIRCULAR YELLOW, CIRCULAR GREEN, steady left-turn YELLOW ARROW, and left-turn GREEN ARROW. Only one of the three circular indications shall be displayed at any given time. Only one of the two arrow indications shall be displayed at any given time. If the left-turn GREEN ARROW signal indication and the CIRCULAR GREEN signal indication(s) for the adjacent through movement are always terminated together, the steady left-turn YELLOW ARROW signal indication shall not be required.
- B. During the protected left-turn movement, the shared signal face shall simultaneously display a left-turn GREEN ARROW signal indication and a circular signal indication that is the same color as the signal indication for the adjacent through lane on the same approach as the protected left turn.
- C. A steady left-turn YELLOW ARROW signal indication shall be displayed following the left-turn GREEN ARROW signal indication, unless the left-turn GREEN ARROW signal indication and the CIRCULAR GREEN signal indication(s) for the adjacent through movement are being terminated together. When the left-turn GREEN ARROW and CIRCULAR GREEN signal indications are being terminated together, the required display following the left-turn GREEN ARROW signal indication shall be either the display of a CIRCULAR YELLOW signal indication alone or the simultaneous display of the CIRCULAR YELLOW and left-turn YELLOW ARROW signal indications.
- D. During the permissive left-turn movement, the shared signal face shall display only a CIRCULAR GREEN signal indication.
- E. A protected/permissive shared signal face, regardless of where it is positioned and regardless of how many adjacent through signal faces are provided, shall always simultaneously display the same color of circular indication that the adjacent through signal face or faces display.
- F. A supplementary sign shall not be required. If used, it shall be a LEFT TURN YIELD ON GREEN (symbolic circular green) (R10-12) sign (see Section 2B.63).

Section 4F.08 Signal Indications for Protected/Permissive Mode Left-Turn Movements in a
Separate Signal Face Paragraphs were relocated from existing Section 4D.20

Standard:

A separate left-turn signal face shall not be used for an approach that does not include an exclusive left-turn lane.

If a separate left-turn signal face is being operated in a protected/permissive left-turn mode, a CIRCULAR GREEN signal indication shall not be used in that face.

If a separate left-turn signal face is being operated in a protected/permissive left-turn mode and a flashing left-turn YELLOW ARROW signal indication is provided, it shall meet the following requirements (see Figure 4F-74D-12):

- A. It shall be capable of displaying the following signal indications: steady left-turn RED ARROW, steady left-turn YELLOW ARROW, flashing left-turn YELLOW ARROW, and left-turn GREEN ARROW. Only one of the four indications shall be displayed at any given time.
- B. During the protected left-turn movement, a left-turn GREEN ARROW signal indication shall be displayed.
- C. A steady left-turn YELLOW ARROW signal indication shall be displayed following the left-turn GREEN ARROW signal indication. It shall be permitted to display a steady left-turn RED ARROW signal indication immediately following the steady left-turn YELLOW ARROW signal indication to provide a red clearance interval.
- D. During the permissive left-turn movement, a flashing left-turn YELLOW ARROW signal indication shall be displayed.
- E. A steady left-turn YELLOW ARROW signal indication shall be displayed following the flashing left-turn YELLOW ARROW signal indication if the permissive left-turn movement is being terminated and the separate left-turn signal face will subsequently display a steady left-turn RED ARROW indication.
- F. It shall be permitted to display a flashing left-turn YELLOW ARROW signal indication for a permissive left-turn movement while the signal faces for the adjacent through movement display steady CIRCULAR RED signal indications and the opposing left-turn signal faces display left-turn GREEN ARROW signal indications for a protected left-turn movement.
- G. When a permissive left-turn movement is changing to a protected left-turn movement, a left-turn GREEN ARROW signal indication shall be displayed immediately upon the termination of the flashing left-turn YELLOW ARROW signal indication. A steady left-turn YELLOW ARROW signal indication shall not be displayed between the display of the flashing left-turn YELLOW ARROW signal indication and the display of the steady left-turn GREEN ARROW signal indication.
- H. The display shall be either:
 - 1. A four-section signal face with the steady left-turn YELLOW ARROW signal indication being displayed in a different section than the flashing left-turn YELLOW ARROW signal indication; except that or
 - 2. A three-section signal face containing a dual-arrow signal section shall be permitted where signal head height limitations (or lateral positioning limitations for a horizontally-mounted signal face) will not permit the use of a four section signal face with the steady left-turn YELLOW ARROW signal indication and the flashing left-turn YELLOW ARROW signal indication being displayed in the same section. The dual-arrow signal section, where used, shall display a GREEN ARROW for the protected left-turn movement and a flashing YELLOW ARROW for the permissive left-turn movement. Revised to reflect Interim Approval 17
- I. During steady mode (stop-and-go) operation where a four-section signal face is used, the signal section that displays the steady left-turn YELLOW ARROW signal indication during change

- intervals shall not be used to display the flashing left-turn YELLOW ARROW signal indication for permissive left turns.
 - J. During flashing mode operation (see Chapter 4G) where a four-section signal face is used, the display of a flashing left-turn YELLOW ARROW signal indication shall be only from the signal section that displays a steady left-turn YELLOW ARROW signal indication during steady mode (stop-and-go) operation.

Figure 4F-7. Typical Position and Arrangements of Separate Signal Faces with Flashing Yellow Arrow for Protected/Permissive Mode and Protected Only Mode Left Turns

If a separate left-turn signal face includes a dual-arrow signal section (capable of displaying a GREEN ARROW for the protected left-turn movement and a flashing YELLOW ARROW for the permissive left-turn movement) along with a steady left-turn YELLOW ARROW signal indication and a steady left-turn RED ARROW signal indication, it shall be considered to be a four-section signal face that is compliant with Item H.1 of the previous paragraph.

Option:

A separate left-turn signal face with a flashing left-turn RED ARROW signal indication during the permissive left-turn movement may be used for unusual geometric conditions, such as wide medians with offset left-turn lanes, but only when an engineering study determines that each and every vehicle must successively come to a full stop before making a permissive left turn.

Standard:

If a separate left-turn signal face is being operated in a protected/permissive left-turn mode and a flashing left-turn RED ARROW signal indication is provided, it shall meet the following requirements (see Figure 4F-34D-8):

- A. It shall be capable of displaying the following signal indications: steady or flashing left-turn RED ARROW, steady left-turn YELLOW ARROW, and left-turn GREEN ARROW. Only one of the three indications shall be displayed at any given time.
- B. During the protected left-turn movement, a left-turn GREEN ARROW signal indication shall be displayed.
- C. A steady left-turn YELLOW ARROW signal indication shall be displayed following the left-turn GREEN ARROW signal indication.
- D. During the permissive left-turn movement, a flashing left-turn RED ARROW signal indication shall be displayed.
- E. A steady left-turn YELLOW ARROW signal indication shall be displayed following the flashing left-turn RED ARROW signal indication if the permissive left-turn movement is being terminated and the separate left-turn signal face will subsequently display a steady left-turn RED ARROW indication.
- F. When a permissive left-turn movement is changing to a protected left-turn movement, a left-turn GREEN ARROW signal indication shall be displayed immediately upon the termination of the flashing left-turn RED ARROW signal indication. A steady left-turn YELLOW ARROW signal indication shall not be displayed between the display of the flashing left-turn RED ARROW signal indication and the display of the steady left-turn GREEN ARROW signal indication.
- G. It shall be permitted to display a flashing left-turn RED ARROW signal indication for a permissive left-turn movement while the signal faces for the adjacent through movement display steady CIRCULAR RED signal indications and the opposing left-turn signal faces display left-turn GREEN ARROW signal indications for a protected left-turn movement.
- H. A supplementary sign shall not be required. If used, it shall be a LEFT TURN YIELD ON FLASHING RED ARROW AFTER STOP (R10-27) sign (see Section 2B.63).

Option:

The requirements of Item A in Paragraph 5 may be met by a vertically-arranged signal face with a horizontal cluster of two left-turn RED ARROW signal indications, the left-most of which displays a steady indication and the right-most of which displays a flashing indication (see Figure 4F-34D-8).

Section 4D.21 4F.09 Signal Indications for Right-Turn Movements – General

Standard Support: Standard changed to Support

In Sections 4F.10 through 4F.154F.09 through 4F.14, provisions applicable to right-turn movements and right-turn lanes shall are also apply applicable to signal indications for U-turns to the right that are provided at locations where right turns are prohibited or not geometrically possible.

Support:

 Right-turning traffic is controlled by one of four modes as follows:

- A. Permissive Only Mode—turns made on a CIRCULAR GREEN signal indication, a flashing right-turn YELLOW ARROW signal indication, or a flashing right-turn RED ARROW signal indication after yielding to pedestrians, if any.
- B. Protected Only Mode—turns made only when a right-turn GREEN ARROW signal indication is displayed.
- C. Protected/Permissive Mode—both modes occur on an approach during the same cycle.
- D. Variable Right-Turn Mode—the operating mode changes among the protected only mode and/or the protected/permissive mode and/or the permissive only mode during different periods of the day or as traffic conditions change.

Standard:

During a permissive right-turn movement, the signal faces, if any, that exclusively control U-turn traffic that conflicts with the permissive right-turn movement (see Item H.1 in Section 4F.01) shall simultaneously display steady U-turn RED ARROW signal indications. If pedestrians crossing the lane or lanes used by the permissive right-turn movement to depart the intersection are controlled by pedestrian signal heads, the signal indications displayed by those pedestrian signal heads shall not be limited to any particular display during the permissive right-turn movement.

During a protected right-turn movement, a GREEN ARROW or a YELLOW ARROW signal indication the signal faces for left turn traffic, if any, on the opposing approach shall not simultaneously be displayed a steady left turn GREEN ARROW or steady left turn YELLOW ARROW signal indication, to left-turn traffic on the opposing approach, except where a separate departure lane is available for each left-turn and right-turn lane with moving traffic and pavement markings or raised channelization clearly indicate which departure lane to use (see Item H.1 in Paragraph 3 in Section 4F.01). and Signal faces, if any, that exclusively control U-turn traffic that conflicts with the protected right-turn movement (see Item F.1 in Section 4D.05) shall simultaneously display steady U-turn RED ARROW signal indications. If pedestrians crossing the lane or lanes used by the protected right-turn movement to depart the intersection are controlled by pedestrian signal heads, the pedestrian signal heads shall display a steady UPRAISED HAND (symbolizing DONT WALK) signal indication during the protected right-turn movement.

If a combined right-turn/through lane exists on an approach, a protected only mode right turn-movement that does not begin and terminate at the same time as the adjacent through movement a right-turn GREEN ARROW or right-turn YELLOW ARROW signal indication or a flashing right-turn RED ARROW signal indication shall not be provided on displayed to an the approach simultaneously with a CIRCULAR RED signal indication for the through movement unless an exclusive right turn lane exists, and a right-turn RED ARROW signal indication shall not be displayed to the approach simultaneously with a CIRCULAR GREEN or CIRCULAR YELLOW signal indication for the through movement.

A yellow change interval for the right turn movement shall not be displayed when the status of the right turn operation is changing from permissive to protected within any given signal sequence.

If the operating mode changes among the protected only mode and/or the protected/permissive mode and/or the permissive only mode during different periods of the day or as traffic conditions change, the requirements in Sections 4F.09 through 4F.144F.10 through 4F.15 that are appropriate to that mode of operation shall be met, subject to the following:

- A. The CIRCULAR GREEN and CIRCULAR YELLOW signal indications shall not be displayed when operating in the protected only mode.
- B. The right-turn GREEN ARROW and right-turn YELLOW ARROW signal indications shall not be displayed when operating in the permissive only mode.

Option: Added to reflect Official Interpretation 4(09)-15(I)

When variable-mode right-turn phasing is used for an approach that includes both an exclusive right-turn lane and a combined right-and-through lane and a flashing yellow arrow is used as the permissive turn display, a five-section shared right-turn signal face containing both circular and arrow indications may be used in combination with one or more separate right-turn signal faces for the exclusive right-turn lane(s) on the same approach. The steady right-turn YELLOW ARROW signal indication and the flashing right-turn YELLOW ARROW signal indication may be displayed in the same section of the five-section shared right-turn signal face.

Additional static signs or changeable message signs may be used to meet the requirements for the variable right-turn mode or to inform drivers that right-turn green arrows will not be available during certain times of the day.

Support:

 Sections <u>4F.09 through 4F.144F.10 through 4F.15</u> describe the use of the following two types of signal faces for controlling right-turn movements:

- A. Shared signal face This type of signal face controls both the right-turn movement and the adjacent movement (usually the through movement) and can serve as one of the two required primary signal faces for the adjacent movement. A shared signal face always displays the same color of circular indication that is displayed by the signal face or faces for the adjacent movement.
- B. Separate right-turn signal face This type of signal face controls only the right-turn movement and cannot serve as one of the two required primary signal faces for the adjacent movement (usually the through movement) because it displays signal indications that are applicable only to the right-turn movement. If a separate right-turn signal face is mounted overhead at the intersection, it is positioned over the extension of the exclusive right-turn lane. In a separate right-turn signal face, a flashing right-turn YELLOW ARROW signal indication or a flashing right-turn RED ARROW signal indication is used to control permissive right-turning movements.

Section 4D.06 contains provisions regarding the lateral positioning of signal faces that control right-turn movements.

It is not necessary that the same mode of right-turn operation or same type of right-turn signal face be used on every approach to a signalized location. Selecting different modes and types of right-turn signal faces for the various approaches to the same signalized location is acceptable.

Option:

A signal face that is shared by left-turning and right-turning traffic may be provided for a shared combined left-turn/right-turn lane on an approach that has no through traffic (see Section 4F.16).

Section 4D.22 4F.10 Signal Indications for Permissive Only Mode Right-Turn Movements in a Shared Signal Face Paragraphs in this Section were relocated to new Section 4F.11

Standard:

If a shared signal face is provided for a permissive only mode right turn, it shall meet the following requirements (see Figure $\frac{4F-8}{4D-13}$):

- A. It shall be capable of displaying the following signal indications: steady CIRCULAR RED, steady CIRCULAR YELLOW, and CIRCULAR GREEN. Only one of the three indications shall be displayed at any given time.
- B. During the permissive right-turn movement, a CIRCULAR GREEN signal indication shall be displayed.
- C. A permissive only shared signal face, regardless of where it is positioned and regardless of how many adjacent through signal faces are provided, shall always simultaneously display the same color of circular indication that the adjacent through signal face or faces display.
- D. If the permissive only mode is not the only right-turn mode used for the approach, the signal face shall be the same shared signal face that is used for the protected/permissive mode (see Section 4F.144F.13) except that the right-turn GREEN ARROW and right-turn YELLOW ARROW signal indications shall not be displayed when operating in the permissive only mode.

Section 4F.11 Signal Indications for Permissive Only Mode Right-Turn Movements in a

Separate Signal Face These paragraphs were relocated from existing Section 4D.22

Standard:

A separate right-turn signal face shall not be used for an approach that does not include an exclusive right-turn lane.

If a separate right-turn signal face is being operated in a permissive only right-turn mode, a CIRCULAR GREEN signal indication shall not be used in that face.

If a separate right-turn signal face is being operated in a permissive only right-turn mode and a flashing right-turn YELLOW ARROW signal indication is provided, it shall meet the following requirements (see Figure 4F-94D-14):

- A. It shall be capable of displaying one of the following sets of signal indications:
 - 1. Steady right-turn RED ARROW, steady right-turn YELLOW ARROW, and flashing right-turn YELLOW ARROW. Only one of the three indications shall be displayed at any given time
 - 2. Steady CIRCULAR RED, steady right-turn YELLOW ARROW, and flashing right-turn YELLOW ARROW. Only one of the three indications shall be displayed at any given time. If the CIRCULAR RED signal indication is sometimes displayed when the signal faces for the adjacent through lane(s) are not displaying a CIRCULAR RED signal indication, a RIGHT TURN SIGNAL (R10-10R) sign (see Section 2B.63) shall be used unless the CIRCULAR RED signal indication in the separate right-turn signal face is shielded, hooded, louvered, positioned, or designed such that it is not readily visible to drivers in the through lane(s).
- B. During the permissive right-turn movement, a flashing right-turn YELLOW ARROW signal indication shall be displayed.
- C. A steady right-turn YELLOW ARROW signal indication shall be displayed following the flashing right-turn YELLOW ARROW signal indication.
- D. When the separate right-turn signal face is providing a message to stop and remain stopped, a steady right-turn RED ARROW signal indication shall be displayed if it is intended that right turns on red not be permitted (except when a traffic control device is in place permitting a turn on a steady RED ARROW signal indication) or a steady CIRCULAR RED signal indication shall be displayed if it is intended that right turns on red be permitted.
- E. It shall be permitted to display a flashing right-turn YELLOW ARROW signal indication for a permissive right-turn movement while the signal faces for the adjacent through movement display steady CIRCULAR RED signal indications.
- F. During steady mode (stop-and-go) operation, the signal section that displays the steady right-turn YELLOW ARROW signal indication during change intervals shall not be used to display the flashing right-turn YELLOW ARROW signal indication for permissive right turns unless a signal section capable of alternating between the display of a steady YELLOW ARROW and a flashing YELLOW ARROW signal indication is used. Added to reflect Official Change Request 4(09)-42
- G. During flashing mode operation (see Chapter 4G), the display of a flashing right-turn YELLOW ARROW signal indication shall be only from the signal section that displays a steady right-turn YELLOW ARROW signal indication during steady mode (stop-and-go) operation.
- H. If the permissive only mode is not the only right-turn mode used for the approach, the signal face shall be the same separate right-turn signal face with a flashing YELLOW ARROW signal indication that is used for the protected/permissive mode (see Section 4F.144F.15) except that the right-turn GREEN ARROW signal indication shall not be displayed when operating in the permissive only mode.

1 2

Figure 4F-9. Typical Position and Arrangements of Separate Signal Faces with Flashing Yellow Arrow for Permissive Only Mode Right Turns

Option:

 When an engineering study determines that each and every vehicle must successively come to a full stop before making a permissive right turn, a separate right-turn signal face with a flashing right-turn RED ARROW signal indication during the permissive right-turn movement may be used.

Standard:

If a separate right-turn signal face is being operated in a permissive only right-turn mode and a flashing right-turn RED ARROW signal indication is provided, it shall meet the following requirements (see Figure 4F-104D-15):

- A. It shall be capable of displaying one of the following sets of signal indications:
 - 1. Steady or flashing right-turn RED ARROW, steady right-turn YELLOW ARROW, and right-turn GREEN ARROW. Only one of the three indications shall be displayed at any given time. The GREEN ARROW indication is required in order to provide a three-section signal face, but shall not be displayed during permissive only mode.
 - 2. Steady CIRCULAR RED on the left and steady right-turn RED ARROW on the right of the top position, steady right-turn YELLOW ARROW in the middle position, and right-turn GREEN ARROW in the bottom position. Only one of the four indications shall be displayed at any given time. The GREEN ARROW indication is required in order to provide three vertical positions, but shall not be displayed during permissive only mode. If the CIRCULAR RED signal indication is sometimes displayed when the signal faces for the adjacent through lane(s) are not displaying a CIRCULAR RED signal indication, a RIGHT TURN SIGNAL (R10-10R) sign (see Section 2B.63) shall be used unless the CIRCULAR RED signal indication in the separate right-turn signal face is shielded, hooded, louvered, positioned, or designed such that it is not readily visible to drivers in the through lane(s).
- B. During the permissive right-turn movement, a flashing right-turn RED ARROW signal indication shall be displayed, thus indicating that each and every vehicle must successively come to a full stop before making a permissive right turn.
- C. A steady right-turn YELLOW ARROW signal indication shall be displayed following the flashing right-turn RED ARROW signal indication.
- D. When the separate right-turn signal face is providing a message to stop and remain stopped, a steady right-turn RED ARROW signal indication shall be displayed if it is intended that right turns on red not be permitted (except when a traffic control device is in place permitting a turn on a steady RED ARROW signal indication) or a steady CIRCULAR RED signal indication shall be displayed if it is intended that right turns on red be permitted.
- E. The display of a flashing right-turn RED ARROW signal indication for a permissive right-turn movement while the signal faces for the adjacent through movement display steady CIRCULAR RED signal indications and the opposing left-turn signal faces display left-turn GREEN ARROW signal indications for a protected left-turn movement shall be permitted.
- F. A supplementary sign shall not be required. If used, it shall be a RIGHT TURN YIELD ON FLASHING RED ARROW AFTER STOP (R10-27) sign (see Section 2B.63).
- Figure 4F-10. Typical Position and Arrangements of Separate Signal Faces with Flashing Red Arrow for Permissive Only Mode and Protected/Permissive Mode Right Turns

Option:

The requirements of Item A.1 in Paragraph 5 may be met by a vertically-arranged signal face with a horizontal cluster of two right-turn RED ARROW signal indications, the left-most of which displays a steady indication and the right-most of which displays a flashing indication (see Figure 4F-104D-15).

Section 4D.23 4F.12 Signal Indications for Protected Only Mode Right-Turn Movements in a Shared Signal Paragraphs from this Section were relocated to new Section 4F.13

Standard:

A shared signal face shall not be used for protected only mode right turns unless the CIRCULAR GREEN and right-turn GREEN ARROW signal indications always begin and terminate together. If a shared signal face is provided for a protected only right turn, it shall meet the following requirements (see Figure 4F-114D-16):

- A. It shall be capable of displaying the following signal indications: steady CIRCULAR RED, steady CIRCULAR YELLOW, CIRCULAR GREEN, and right-turn GREEN ARROW. Only one of the three colors shall be displayed at any given time.
- B. During the protected right-turn movement, the shared signal face shall simultaneously display both a CIRCULAR GREEN signal indication and a right-turn GREEN ARROW signal indication.
- C. The shared signal face shall always simultaneously display the same color of circular indication that the adjacent through signal face or faces display.
- D. If the protected only mode is not the only right-turn mode used for the approach, the signal face shall be the same shared signal face that is used for the protected/permissive mode (see Section 4F.14).

Figure 4F-11. Typical Positions and Arrangements of Shared Signal Faces for Protected Only Mode Right Turns

Option:

A straight-through GREEN ARROW signal indication may be used instead of the CIRCULAR GREEN signal indication in Items A and B in Paragraph 1 on an approach where left turns are prohibited and a straight-through GREEN ARROW signal indication is also used instead of a CIRCULAR GREEN signal indication in the other signal face(s) for through traffic.

Section 4F.13 Signal Indications for Protected Only Mode Right-Turn Movements in a

Separate Signal Face These paragraphs were relocated from existing Section 4D.23

Standard:

A separate right-turn signal face shall not be used for an approach that does not include an exclusive right-turn lane.

If a separate right-turn signal face is provided for a protected only mode right turn, it shall meet the following requirements (see Figure 4F-124D-17):

- A. It shall be capable of displaying one of the following sets of signal indications:
 - 1. Steady right-turn RED ARROW, steady right-turn YELLOW ARROW, and right-turn GREEN ARROW. Only one of the three indications shall be displayed at any given time. A signal instruction sign shall not be required with this set of signal indications. If used, it shall be a RIGHT ON GREEN ARROW ONLY (R10-5a) sign (see Section 2B.63). Revised to reflect Official Change Request 4(09)-73(C)
 - 2. Steady CIRCULAR RED, steady right-turn YELLOW ARROW, and right-turn GREEN ARROW. Only one of three indications shall be displayed at any given time. If the CIRCULAR RED signal indication is sometimes displayed when the signal faces for the adjacent through lane(s) are not displaying a CIRCULAR RED signal indication, a RIGHT TURN SIGNAL (R10-10R) sign (see Section 2B.63) shall be used unless the CIRCULAR RED signal indication is shielded, hooded, louvered, positioned, or designed such that it is not readily visible to drivers in the through lane(s).
- B. During the protected right-turn movement, a right-turn GREEN ARROW signal indication shall be displayed.
- C. A steady right-turn YELLOW ARROW signal indication shall be displayed following the right-turn GREEN ARROW signal indication.
- D. When the separate signal face is providing a message to stop and remain stopped, a steady right-turn RED ARROW signal indication shall be displayed if it is intended that right turns on red not be permitted (except when a traffic control device is in place permitting a turn on a

E. If the protected only mode is not the only right-turn mode used for the approach, the signal face shall be the same separate right-turn signal face that is used for the protected/permissive mode (see Section 4F.154F.14 and Figure 4F-144D-19) except that a flashing right-turn YELLOW ARROW or flashing right-turn RED ARROW signal indication shall not be displayed when operating in the protected only mode.

Figure 4F-12. Typical Position and Arrangements of Separate Signal Faces for Protected Only Mode Right Turns

Section 4D.24 4F.14 Signal Indications for Protected/Permissive Mode Right-Turn Movements
in a Shared Signal Face Paragraphs in this Section were relocated in new Section 4F.15
Standard:

If a shared signal face is provided for a protected/permissive mode right turn, it shall meet the following requirements (see Figure 4F-134D-18):

- A. It shall be capable of displaying the following signal indications: steady CIRCULAR RED, steady CIRCULAR YELLOW, CIRCULAR GREEN, steady right-turn YELLOW ARROW, and right-turn GREEN ARROW. Only one of the three circular indications shall be displayed at any given time. Only one of the two arrow indications shall be displayed at any given time. If the right-turn GREEN ARROW signal indication and the CIRCULAR GREEN signal indication(s) for the adjacent through movement are always terminated together, the steady right-turn YELLOW ARROW signal indication shall not be required.
- B. During the protected right-turn movement, the shared signal face shall simultaneously display a right-turn GREEN ARROW signal indication and a circular signal indication that is the same color as the signal indication for the adjacent through lane on the same approach as the protected right turn.
- C. A steady right-turn YELLOW ARROW signal indication shall be displayed following the right-turn GREEN ARROW signal indication, unless the right-turn GREEN ARROW signal indication and the CIRCULAR GREEN signal indication(s) for the adjacent through movement are being terminated together. When the right-turn GREEN ARROW and CIRCULAR GREEN signal indications are being terminated together, the required display following the right-turn GREEN ARROW signal indication shall be either the display of a CIRCULAR YELLOW signal indication alone or the simultaneous display of the CIRCULAR YELLOW and right-turn YELLOW ARROW signal indications.
- D. During the permissive right-turn movement, the shared signal face shall display only a CIRCULAR GREEN signal indication.
- E. A protected/permissive shared signal face, regardless of where it is positioned and regardless of how many adjacent through signal faces are provided, shall always simultaneously display the same color of circular indication that the adjacent through signal face or faces display.

Figure 4F-13. Typical Positions and Arrangements of Shared Signal Faces for Protected/Permissive Mode Right Turns

Section 4F.15 Signal Indications for Protected/Permissive Mode Right-Turn Movements in a

Separate Signal Face These paragraphs were relocated from existing Section 4D.24

Standard:

A separate right-turn signal face shall not be used for an approach that does not include an exclusive right-turn lane.

If a separate right-turn signal face is being operated in a protected/permissive right-turn mode, a CIRCULAR GREEN signal indication shall not be used in that face.

If a separate right-turn signal face is being operated in a protected/permissive right-turn mode and a flashing right-turn YELLOW ARROW signal indication is provided, it shall meet the following requirements (see Figure 4F-144D-19):

A. It shall be capable of displaying one of the following sets of signal indications:

- 1. Steady right-turn RED ARROW, steady right-turn YELLOW ARROW, flashing right-turn YELLOW ARROW, and right-turn GREEN ARROW. Only one of the four indications shall be displayed at any given time.
 - 2. Steady CIRCULAR RED, steady right-turn YELLOW ARROW, flashing right-turn YELLOW ARROW, and right-turn GREEN ARROW. Only one of the four indications shall be displayed at any given time. If the CIRCULAR RED signal indication is sometimes displayed when the signal faces for the adjacent through lane(s) are not displaying a CIRCULAR RED signal indication, a RIGHT TURN SIGNAL (R10-10R) sign (see Section 2B.63) shall be used unless the CIRCULAR RED signal indication in the separate right-turn signal face is shielded, hooded, louvered, positioned, or designed such that it is not readily visible to drivers in the through lane(s).
- B. During the protected right-turn movement, a right-turn GREEN ARROW signal indication shall be displayed.
- C. A steady right-turn YELLOW ARROW signal indication shall be displayed following the right-turn GREEN ARROW signal indication. It shall be permitted to display a steady right-turn RED ARROW signal indication immediately following the steady right-turn YELLOW ARROW signal indication to provide a red clearance interval.
- D. During the permissive right-turn movement, a flashing right-turn YELLOW ARROW signal indication shall be displayed.
- E. A steady right-turn YELLOW ARROW signal indication shall be displayed following the flashing right-turn YELLOW ARROW signal indication if the permissive right-turn movement is being terminated and the separate right-turn signal face will subsequently display a steady red indication.
- F. When a permissive right-turn movement is changing to a protected right-turn movement;
 - 1. If a permissive left-turn movement from the opposing approach is being terminated simultaneously with the termination of the permissive right-turn movement, a steady right-turn YELLOW ARROW signal indication, and, if needed, a steady right-turn RED ARROW signal indication, shall be displayed following the flashing right-turn YELLOW ARROW signal indication.
 - 2. If a permissive left-turn movement from the opposing approach that is being terminated simultaneously with the termination of the permissive right-turn movement is not present,
 - a right-turn GREEN ARROW signal indication shall be displayed immediately upon the termination of the flashing right-turn YELLOW ARROW signal indication. In this situation, a steady right-turn YELLOW ARROW signal indication shall not be displayed between the display of the flashing right-turn YELLOW ARROW signal indication and the display of the steady right-turn GREEN ARROW signal indication.
- G. When the separate right-turn signal face is providing a message to stop and remain stopped, a steady right-turn RED ARROW signal indication shall be displayed if it is intended that right turns on red not be permitted (except when a traffic control device is in place permitting a turn on a steady RED ARROW signal indication) or a steady CIRCULAR RED signal indication shall be displayed if it is intended that right turns on red be permitted.
- H. It shall be permitted to display a flashing right-turn YELLOW ARROW signal indication for a permissive right-turn movement while the signal faces for the adjacent through movement display steady CIRCULAR RED signal indications.
- I. A signal face containing a dual-arrow signal section in place of separate flashing right-turn YELLOW ARROW and right-turn GREEN ARROW signal sections shall be permitted where signal head height limitations (or lateral positioning limitations for a horizontally mounted signal face) are a concern. The dual-arrow signal section, where used, shall display a GREEN ARROW for the protected right-turn movement and a flashing YELLOW ARROW for the permissive right-turn movement. The display shall be either:
 - 1. A four-section signal face with the steady right-turn YELLOW ARROW signal indication being displayed in a different section than the flashing right-turn YELLOW ARROW signal indication, or

- 2. A three-section signal face with the steady right-turn YELLOW ARROW signal indication and the flashing right-turn YELLOW ARROW signal indication being displayed in the same section. Added to reflect Interim Approval-17
- J. During steady mode (stop-and-go) operation where a four-section signal face is used, the signal section that displays the steady right-turn YELLOW ARROW signal indication during change intervals shall not be used to display the flashing right-turn YELLOW ARROW signal indication for permissive right turns.
- K. During flashing mode operation (see Chapter 4G) where a four-section signal face is used, the display of a flashing right-turn YELLOW ARROW signal indication shall be only from the signal section that displays a steady right-turn YELLOW ARROW signal indication during steady mode (stop-and-go) operation.
- Figure 4F-14. Typical Position and Arrangements of Separate Signal Faces with Flashing Yellow Arrow for Protected/Permissive Mode and Protected Only Mode Right Turns

If a separate right-turn signal face includes a dual-arrow signal section (capable of displaying a GREEN ARROW for the protected right-turn movement and a flashing YELLOW ARROW for the permissive right-turn movement) along with a steady right-turn YELLOW ARROW signal indication and a steady right-turn RED ARROW signal indication, it shall be considered to be a four-section signal face that is compliant with Item I.1 of the previous paragraph.

Option:

When an engineering study determines that each and every vehicle must successively come to a full stop before making a permissive right turn, a separate signal face that has a flashing right-turn RED ARROW signal indication during the permissive right-turn movement may be used.

Standard:

If a separate right-turn signal face is being operated in a protected/permissive right-turn mode and a flashing right-turn RED ARROW signal indication is provided, it shall meet the following requirements (see Figure 4F-104D-15):

- A. It shall be capable of displaying one of the following sets of signal indications:
 - 1. Steady or flashing right-turn RED ARROW, steady right-turn YELLOW ARROW, and right-turn GREEN ARROW. Only one of the three indications shall be displayed at any given time.
 - 2. Steady CIRCULAR RED on the left and steady or flashing right-turn RED ARROW on the right of the top position, steady right-turn YELLOW ARROW in the middle position, and right-turn GREEN ARROW in the bottom position. Only one of the four indications shall be displayed at any given time. If the CIRCULAR RED signal indication is sometimes displayed when the signal faces for the adjacent through lane(s) are not displaying a CIRCULAR RED signal indication, a RIGHT TURN SIGNAL (R10-10R) sign (see Section 2B.63) shall be used unless the CIRCULAR RED signal indication in the separate right-turn signal face is shielded, hooded, louvered, positioned, or designed such that it is not readily visible to drivers in the through lane(s).
- B. During the protected right-turn movement, a right-turn GREEN ARROW signal indication shall be displayed.
- C. A steady right-turn YELLOW ARROW signal indication shall be displayed following the right-turn GREEN ARROW signal indication.
- D. During the permissive right-turn movement, the separate right-turn signal face shall display a flashing right-turn RED ARROW signal indication.
- E. A steady right-turn YELLOW ARROW signal indication shall be displayed following the flashing right-turn RED ARROW signal indication if the permissive right-turn movement is being terminated and the separate right-turn signal face will subsequently display a steady red indication.
- F. When a permissive right-turn movement is changing to a protected right-turn movement, a right-turn GREEN ARROW signal indication shall be displayed immediately upon the termination of the flashing right-turn RED ARROW signal indication. A steady right-turn

- YELLOW ARROW signal indication shall not be displayed between the display of the flashing right-turn RED ARROW signal indication and the display of the steady right-turn GREEN ARROW signal indication.
 - G. When the separate right-turn signal face is providing a message to stop and remain stopped, a steady right-turn RED ARROW signal indication shall be displayed if it is intended that right turns on red not be permitted (except when a traffic control device is in place permitting a turn on a steady RED ARROW signal indication) or a steady CIRCULAR RED signal indication shall be displayed if it is intended that right turns on red be permitted.
 - H. It shall be permitted to display a flashing right-turn RED ARROW signal indication for a permissive right-turn movement while the signal faces for the adjacent through movement display steady CIRCULAR RED signal indications and the opposing left-turn signal faces display left-turn GREEN ARROW signal indications for a protected left-turn movement.
 - I. A supplementary sign shall not be required. If used, it shall be a RIGHT TURN YIELD ON FLASHING RED ARROW AFTER STOP (R10-27) sign (see Section 2B.63).

Option:

The requirements of Item A.1 in Paragraph 5 may be met by a vertically-arranged signal face with a horizontal cluster of two right-turn RED ARROW signal indications, the left-most of which displays a steady indication and the right-most of which displays a flashing indication (see Figure 4F-104D-15).

Section 4D.25 4F.16 Signal Indications for Approaches with Shared Left-Turn/Right-Turn

Lanes and No Through Movement Section revised to reflect Official Change Request 4(09)-23

Support:

This provisions of this section apply only to approaches where no through movement exists, such as the stem of a T-intersection or where the opposite approach is a one-way roadway in the opposing direction.

Standard:

A minimum of two primary signal faces shall be provided for the signalized turning movement that is considered to be the major movement from the approach (see Section 4D.04).

Option:

The required two primary signal faces and any supplemental primary signal faces may continuously display a steady CIRCULAR RED signal indication during times when the traffic control signal is being operated in the steady (stop-and-go) mode.

Standard:

CIRCULAR GREEN and CIRCULAR YELLOW signal indications shall not be displayed to an approach with no through movement if:

- A. The posted or statutory speed limit on the approach is 35 mph or higher,
- B. The one-way roadway that opposes the approach is an exit ramp from a freeway or expressway, or
- C. The one-way roadway that opposes the approach has a posted or statutory speed limit of 35 mph or higher.

Support:

A lane that is shared by from which left-turn and right-turn movements can both be made is sometimes provided on an approach that has no through movement, such as the stem of a T intersection or where the opposite approach is a one-way roadway in the opposing direction either as the only approach lane or as one of several approach lanes.

Option:

If all of the lanes on the approach are designated as exclusive turn lanes and no lane is designated as a combined left-turn/right-turn lane, the left-turn and right-turn movements may start and terminate independently, and the left-turn and right-turn movements each may be operated in one or more of the modes of operation as described in Sections 4F.02 through 4F.14.

Standard:

When a shared combined left-turn/right-turn lane exists on an signalized approach, the left-turn and right-turn movements shall start and terminate simultaneously and the red signal indication used in each of the signal faces on the approach shall be a CIRCULAR RED.

Support:

This requirement for the use of CIRCULAR RED signal indications in signal faces for approaches having a shared-combined lane for left-turn and right-turn movements is a specific exception to other provisions in this Chapter that would otherwise require the use of RED ARROW signal indications.

Standard:

The signal faces provided for an approach with a shared combined left-turn/right-turn lane and no through movement shall be one of the following:

- A. Except as provided in Paragraph 6 of Section 4F.01 and Paragraph 4 of this Section, two or more signal faces, each capable of displaying CIRCULAR RED, CIRCULAR YELLOW, and CIRCULAR GREEN signal indications, shall be provided for the approach. This display shall be permissible regardless of the number of exclusive left-turn and/or right-turn lanes that exist on the approach in addition to the shared combined left-turn/right-turn lane and regardless of whether or not there are pedestrian or opposing vehicular movements that conflict with the left-turn or right-turn movements. However, if there is an opposing approach and the signal phasing protects the left-turn movement on the approach with the shared combined left-turn/right-turn lane from conflicts with the opposing vehicular movements and any signalized pedestrian movements, a left-turn GREEN ARROW signal indication shall also be included in the left-most signal face and shall be displayed simultaneously with the CIRCULAR GREEN signal indication.
- B. If the approach has one or more exclusive turn lanes in addition to the **shared combined** left-turn/right-turn lane and there is no conflict with a signalized vehicular or pedestrian movement, and GREEN ARROW signal indications are used in place of CIRCULAR GREEN signal indications on the approach, the signal faces for the approach shall be:
 - 1. A signal face(s) capable of displaying CIRCULAR RED, YELLOW ARROW, and GREEN ARROW signal indications for the exclusive turn lane(s), with the arrows pointing in the direction of the turn, and
 - 2. A shared left-turn/right-turn signal face capable of displaying CIRCULAR RED, left-turn YELLOW ARROW, left-turn GREEN ARROW, right-turn YELLOW ARROW, and right-turn GREEN ARROW signal indications, in an arrangement of signal sections that complies with the provisions of Section 4E.04-4E.03 or 4E.054E.04.
- C. If the approach has one or more exclusive turn lanes in addition to the shared combined left-turn/right-turn lane and there is a conflict with a signalized vehicular or pedestrian movement, and flashing YELLOW ARROW signal indications are used in place of CIRCULAR GREEN signal indications on the approach, the signal faces for the approach shall be as described in Items B.1 and B.2, except that flashing YELLOW ARROW signal indications shall be used in place of the GREEN ARROW signal indications for the turning movement(s) that conflicts with the signalized vehicular or pedestrian movement.

Support:

Figure <u>4F-15 4D 20</u>-illustrates application of these Standards on approaches that have only a <u>shared</u> <u>combined</u> left-turn/right-turn lane, and on approaches that have one or more exclusive turn lanes in addition to the <u>shared combined</u> left-turn/right-turn lane.

Option:

If the lane-use regulations on an approach are variable such that at certain times all of the lanes on the approach are designated as exclusive turn lanes and no lane is designated as a shared combined left-turn/right-turn lane:

A. During the times that no lane is designated as a shared combined left-turn/right-turn lane, the left-turn and right-turn movements may start and terminate independently, and the left-turn and right-turn movements may be operated in one or more of the modes of operation as described in Sections 4F.02 through 4F.154F.14; and

B. If a protected/permissive mode is used, the <u>operation of the</u> shared left-turn/right-turn signal face provided in Paragraph 9 may be modified to include a dual arrow signal section capable of displaying both a GREEN ARROW signal indication and a flashing YELLOW ARROW signal indication for a turn movement(s) to display the steady left-turn (right-turn) YELLOW ARROW signal indication and the flashing left-turn (right-turn) YELLOW ARROW signal indication in the same section in order to not exceed the maximum of five sections per signal face provided in Section 4E.03. Revised to reflect Official Interpretation 4(09)-15(I)

Figure 4F-15. Signal Indications for Approaches with a Combined Left-Turn/Right-Turn

Lane and No Through Movement

Section 4D.26-4F.17 Yellow Change and Red Clearance Intervals

Support: The sequence of Paragraphs 1 and 2 was switched and Paragraph 2 changed from Standard to Support

The exclusive function of the yellow change interval shall be is to warn traffic approaching a signalized location of an impending change in the right of way assignment that their permission to proceed is being terminated after which they will be directed to stop, or in the case of a protected/permissive turning movement that their protected movement is being terminated after which they will need to perform their turn in a permissive manner.

Standard:

A steady yellow signal indication shall be displayed following every CIRCULAR GREEN or GREEN ARROW signal indication and following every flashing YELLOW ARROW or flashing RED ARROW signal indication displayed as a part of a steady mode operation. This requirement shall not apply when a CIRCULAR GREEN, a flashing YELLOW ARROW, or a flashing RED ARROW signal indication is followed immediately by a GREEN ARROW signal indication.

The duration of the yellow change interval shall be determined using engineering practices.

Support:

Section 4F.01 contains provisions regarding the display of steady CIRCULAR YELLOW signal indications to approaches from which drivers are allowed to make permissive left turns.

Guidance:

When indicated by the application of engineering practices, the yellow change interval should be followed by a red clearance interval to provide additional time before conflicting traffic movements, including pedestrians, are released.

Standard:

When used, the duration of the red clearance interval shall be determined using engineering practices.

Support:

Engineering practices for determining the duration of yellow change and red clearance intervals can be found in ITE's "Traffic Control Devices Handbook" and in ITE's "Manual of Traffic Signal Design" "Guidelines for Determining Traffic Signal Change and Clearance Intervals: A Recommended Practice of the Institute of Transportation Engineers" (see Section 1A.05).

Standard:

The durations of yellow change intervals and red clearance intervals shall be consistent with the determined values within the technical capabilities of the controller unit.

The duration of a yellow change interval shall not vary on a cycle-by-cycle basis within the same signal timing plan.

Except as provided in Paragraph 12, the duration of a red clearance interval shall not be decreased or omitted on a cycle-by-cycle basis within the same signal timing plan.

Option:

The duration of a red clearance interval may be extended from its predetermined value for a given cycle based upon the detection of a vehicle that is predicted to violate the red signal indication.

When an actuated signal sequence includes a signal phase for permissive/protected (lagging) left-turn movements in both directions, the red clearance interval may be shown during those cycles when the lagging left-turn signal phase is skipped and may be omitted during those cycles when the lagging left-turn signal phase is shown.

The duration of a yellow change interval or a red clearance interval may be different in different signal timing plans for the same controller unit.

Guidance:

A yellow change interval should have a minimum duration of 3 seconds, and a maximum duration of 6 seconds for through movements and 7 seconds for turning movements. The longer intervals should be reserved for use on approaches with higher speeds.

Except when clearing a one-lane, two-way facility (see Section 40.02) or when clearing an exceptionally wide intersection, a red clearance interval should have a duration not exceeding 6-seconds.

Standard:

Except for warning beacons mounted on advance warning signs on the approach to a signalized location (see Section 2C.37), signal displays that are intended to provide a "pre-yellow warning" interval, such as flashing green signal indications, vehicular countdown displays, or other similar displays, shall not be used at a signalized location.

Support:

The use of signal displays (other than warning beacons mounted on advance warning signs) that convey a "pre-yellow warning" have been found by research to increase the frequency of crashes.

Section 4D.27-4F.18 Preemption and Priority Control of Traffic Control Signals – General Paragraphs from this Section were relocated to new Sections 4F.19 and 4F.20

Option:

Traffic control signals may be designed and operated to respond to certain classes of approaching vehicles by altering the normal signal timing and phasing plan(s) during the approach and passage of those vehicles. The alternative plan(s) may be as simple as extending a currently displayed green interval or as complex as replacing the entire set of signal phases and timing.

Support:

Some types or classes of vehicles supersede others when a traffic control signal responds to more than one type or class. In general, a vehicle that is more difficult to control supersedes a vehicle that is easier to control.

Option:

Preemption or priority control of traffic control signals may also be a means of assigning priority right of way-indicating to specified classes of vehicles at certain non-intersection locations, such as on approaches to one-lane bridges and tunnels, movable bridges, highway maintenance and construction activities, metered freeway entrance ramps, and transit operations, that they are permitted to proceed.

Guidance:

When a traffic control signal that is returning to a steady mode from a dark mode (typically upon restoration from a power failure) receives a preemption or priority request, care should be exercised to minimize the possibility of vehicles or pedestrians being misdirected into a conflict with the vehicle making the request.

Option:

During the change from a dark mode to a steady mode under a preemption or priority request, the display of signal indications that could misdirect road users may be prevented by one or more of the following methods:

- A. Having the traffic control signal remain in the dark mode,
- B. Having the traffic control signal remain in the flashing mode,
 - C. Altering the flashing mode,

- D. Executing the normal start-up routine before responding, or
- E. Responding directly to initial or dwell period.

Guidance:

1

2

3

4

5

6

7

8

9 10

11

12

13

14

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41 42

43

44

45

46

47

48

49

Traffic control signals operating under preemption control or under priority control should be operated in a manner designed to keep traffic moving.

Traffic control signals that are designed to respond under preemption or priority control to more than one type or class of vehicle should be designed to respond in the relative order of importance or difficulty in stopping the type or class of vehicle. The order of priority should be: train, boat, heavy vehicle (fire vehicle, emergency medical service), light vehicle (law enforcement), light rail transit, rubber-tired transit.

Option:

If engineering judgment indicates that light rail transit signal indications would reduce road user confusion that might otherwise occur if standard traffic signal indications were used to control these movemen ght rail transit signal indications complying with Section 8C.11 8D.15 and as illustrated in Figure 8C 3 8D-4 may be used for preemption or priority control of the following exclusive movements at signalized interpiions:

A. For transit buses in "queue jumper" s, and
B. Bus rapid transit in semi-exclusive or mixed-use alignments.

Section 4F.19 Preemption Control of Traffic Control Signals These paragraphs relocated from existing Section 4D.27

Support:

Preemption control (see definition in Section 1C.02) is typically given to trains, boats, emergency vehicles, and light rail transit.

Examples of preemption control include the following:

- A. The prompt displaying of green signal indications at signalized locations ahead of fire vehicles, law enforcement vehicles, ambulances, and other official emergency vehicles;
- B. A special sequence of signal phases and timing to expedite and/or provide additional clearance time for vehicles to clear the tracks prior to the arrival of rail traffic; and
- C. A special sequence of signal phases to display a steady red indication to prohibit turning movements toward the tracks during the approach or passage of rail traffic.

Standard:

During the transition into preemption control:

- A. The yellow change interval, and any red clearance interval that follows, shall not be shortened or omitted.
- B. The shortening or omission of any pedestrian walk interval and/or pedestrian change interval shall be permitted.
- C. The shortening or omission of any pedestrian change interval shall be permitted only when the traffic control signal is being preempted because a boat is approaching a movable bridge or because rail traffic is approaching a grade crossing. Added to reflect Official Change Request 4(09)-36
- D. The return to the previous green signal indication shall be permitted following a steady yellow signal indication in the same signal face, omitting the red clearance interval, if any.

During preemption control and during the transition out of preemption control:

- A. The shortening or omission of any yellow change interval, and of any red clearance interval that follows, shall not be permitted.
- B. A signal indication sequence from a steady yellow signal indication to a green signal indication shall not be permitted.

Option:

A distinctive indication may be provided at the intersection to inform law enforcement personnel who are escorting traffic (such as a parade or funeral procession) that the traffic control signal has changed to a red

indication not because of normal cycling, but because it has been preempted by rail traffic approaching an adjacent grade crossing or by boat traffic approaching an adjacent moveable bridge.

A distinctive indication may be provided at the intersection to show that an emergency vehicle has been given control of the traffic control signal (see Section 11-106 of the "Uniform Vehicle Code"). In order to assist in the understanding of the control of the traffic <u>control</u> signal, a common distinctive indication may be used where drivers from different agencies travel through the same intersection when responding to emergencies.

Guidance:

Except for traffic control signals interconnected with light rail transit systems, traffic control signals with railroad preemption or coordinated with flashing-light signal systems should be provided with a back-up power supply. The backup power supply should provide for a minimum operating period sufficient to allow the implementation of alternative traffic control measures during a power outage.

If a traffic control signal <u>or hybrid beacon</u> is installed near or within a grade crossing or if a grade crossing with active traffic control devices is within or near a signalized highway intersection, Chapter 8D should be consulted. Revised to reflect Official Change Request 4(09)-42

16 Support:

Section 8D.09 contains additional information regarding preemption for grade crossings. Section 8D.10 contains information regarding prohibiting movements towards the grade crossing during preemption.

Sections 8D.11 and 8D.12 contain additional information regarding pre-signals and queue cutter signals, respectively, for grade crossings.

Section 4F.20 Priority Control of Traffic Control Signals

These paragraphs were relocated from existing Section 4D.27

23 Support:

Priority control (see definition in Section 1C.02) is typically given to certain non-emergency vehicles such as light-rail transit vehicles operating in a mixed-use alignment and buses.

Examples of priority control include the following:

- A. The displaying of early or extended green signal indications at an intersection to assist public transit vehicles in remaining on schedule, and
- B. Special phasing to assist public transit vehicles in entering the travel stream ahead of the platoon of other waiting traffic.

Standard:

During priority control and during the transition into or out of priority control:

- A. The shortening or omission of any yellow change interval, and of any red clearance interval that follows, shall not be permitted.
- B. The shortening of any pedestrian walk interval below that time described in Section 4I.07 shall not be permitted.
- C. The omission of a pedestrian walk interval and its associated change interval shall not be permitted unless the associated vehicular phase is also omitted or the pedestrian phase is exclusive.
- D. The shortening or omission of any pedestrian change interval shall not be permitted.
- E. A signal indication sequence from a steady yellow signal indication to a green signal indication shall not be permitted.

CHAPTER 4G. FLASHING OPERATION OF TRAFFIC CONTROL SIGNALS

2 Section 4D.284G.01 Flashing Operation of Traffic Control Signals – General

Standard:

The light source of a flashing signal indication shall be flashed continuously at a rate of not less than 50 or more than 60 times per minute.

The displayed period of each flash shall be a minimum of 1/2 and a maximum of 2/3 of the total flash cycle.

Flashing signal indications shall comply with the requirements of other Sections of this Manual regarding visibility-limiting or positioning of conflicting signal indications, except that flashing yellow signal indications for through traffic shall not be required to be visibility-limited or positioned to minimize visual conflict for road users in separately controlled turn lanes.

Each traffic control signal shall be provided with an independent flasher mechanism that operates in compliance with this Section.

The flashing operation shall not be terminated by removal or turn off of the controller unit or of the conflict monitor (malfunction management unit) or both.

A manual switch , a conflict monitor (malfunction management unit) circuit, and, if appropriate, automatic means shall be provided to initiate the flashing mode. If appropriate, a conflict monitor (malfunction management unit) circuit and/or an automatic means shall also be provided to initiate the flashing mode.

Option:

Based on engineering study or engineering judgment, traffic control signals may be operated in the flashing mode on a scheduled basis during one or more periods of the day rather than operated continuously in the steady (stop-and-go) mode.

Support:

Sections <u>4I.06</u>4I.07 and 4K.04 contain information regarding the operation of pedestrian signal heads and accessible pedestrian signal detector push button locator tones, respectively, during flashing operation.

Section 4D.29 4G.02 Flashing Operation – Transition Into Flashing Mode

Standard Option: Standard changed to Option

The transition from steady (stop-and-go) mode to flashing mode, if initiated by a conflict monitor (malfunction management unit) or by a manual switch, shall be permitted to may be made at any time.

Standard:

Programmed changes from steady (stop-and-go) mode to flashing mode shall be made under either of the following circumstances:

- A. At the end of the common major-street red interval (such as just prior to the start of the green in both directions on the major street), or
- B. Directly from a CIRCULAR GREEN signal indication to a flashing CIRCULAR YELLOW signal indication, or from a GREEN ARROW signal indication to a flashing YELLOW ARROW signal indication, or from a flashing YELLOW ARROW signal indication (see Sections 4F. 0304, 4F.0506, 4F.0608, 4F.0911, 4F.1113, and 4F.1315) to a flashing YELLOW ARROW signal indication (in a different signal section if the signal face displays the steady YELLOW ARROW signal indication in a different section than the flashing YELLOW ARROW signal indication).

During programmed changes into flashing mode, no green signal indication or flashing yellow signal indication shall be terminated and immediately followed by a steady red or flashing red signal indication without first displaying the steady yellow signal indication.

- 46 Section 4D.304G.03 Flashing Operation Signal Indications During Flashing Mode
- 47 Guidance:

When a traffic control signal is operated in the flashing mode, a flashing yellow signal indication should be used for the major street and a flashing red signal indication should be used for the other approaches unless flashing red signal indications are used on all approaches.

Standard:

When a traffic control signal is operated in the flashing mode, all of the green signal indications at the signalized location shall be dark (non-illuminated) and shall not be displayed in either a steady or flashing manner, except for single-section GREEN ARROW signal indications as provided elsewhere in this Section.

Flashing yellow signal indications shall be used on more than one approach to a signalized location only if those approaches do not conflict with each other.

Except as provided in Paragraph 5, when a traffic control signal is operated in the flashing mode, one and only one signal indication in every signal face at the signalized location shall be flashed.

Option:

If a signal face has two identical CIRCULAR RED or RED ARROW signal indications (see Section 4E.04), both of those identical signal indications may be flashed simultaneously.

Standard:

No steady indications, other than a single-section signal face consisting of a continuously-displayed GREEN ARROW signal indication that is used alone to indicate a continuous movement in the steady (stop-and-go) mode, shall be displayed at the signalized location during the flashing mode. A single-section GREEN ARROW signal indication shall remain continuously-displayed when the traffic control signal is operated in the flashing mode.

If a signal face includes both circular and arrow signal indications of the color that is to be flashed, only the circular signal indication shall be flashed.

All signal faces that are flashed on an approach shall flash the same color, either yellow or red, except that separate turn signal faces (see Sections <u>4F.02_4F.03</u> and <u>4F.09_4F.10</u>) shall be permitted to flash a RED ARROW signal indication when the adjacent through movement signal indications are flashed yellow. Shared signal faces (see Sections <u>4F.02_4F.03</u> and <u>4F.09_4F.10</u>) for turn movements shall not be permitted to flash a CIRCULAR RED signal indication when the adjacent through movement signal indications are flashed yellow.

The appropriate RED ARROW or YELLOW ARROW signal indication shall be flashed when a signal face consists entirely of arrow indications. A signal face that consists entirely of arrow indications and that provides a protected only turn movement during the steady (stop-and-go) mode or that provides a flashing YELLOW ARROW or flashing RED ARROW signal indication for a permissive turn movement during the steady (stop-and-go) mode shall be permitted to flash the YELLOW ARROW signal indication during the flashing mode if the adjacent through movement signal indications are flashed yellow and if it is intended that a permissive turn movement not requiring a full stop by each turning vehicle be provided during the flashing mode.

Section 4D.31 4G.04 Flashing Operation – Transition Out of Flashing Mode

Standard:

All changes from flashing mode to steady (stop-and-go) mode shall be made under one of the following procedures:

- A. Yellow-red flashing mode: Changes from flashing mode to steady (stop-and-go) mode shall be made at the beginning of the major-street green interval (when a green signal indication is displayed to through traffic in both directions on the major street), or if there is no common major-street green interval, at the beginning of the green interval for the major traffic movement on the major street.
- B. Red-red flashing mode: Changes from flashing mode to steady (stop-and-go) mode shall be made by changing the flashing red indications to steady red indications followed by appropriate green indications to begin the steady mode cycle. These green indications shall be the beginning of the major-street green interval (when a green signal indication is displayed to through traffic

in both directions on the major street) or if there is no common major-street green interval, at the beginning of the green interval for the major traffic movement on the major street.

Guidance:

The steady red clearance interval provided during the change from red-red flashing mode to steady (stop-and-go) mode should have a duration of 6 seconds.

When changing from the yellow-red flashing mode to steady (stop-and-go) mode at a location where there is a common major-street green interval, the flashing red signal indications for the minor street should immediately change to steady red signal indications, and the flashing yellow signal indications for the through movements on the major street should change to green signal indications in both directions (after the minor-street signal indications have been steady red for a short time, if desired), or the flashing yellow signal indications for the through movements on the major street should change to steady yellow signal indications followed by a steady red clearance interval before changing to green signal indications in both directions.

When changing from the yellow-red flashing mode to steady (stop-and-go) mode, if at a location where there is no common major-street green interval, the provision of a steady red clearance interval for the other approaches before changing from a flashing yellow or a flashing red signal indication to a green signal indication on the major approach should be considered the flashing red signal indications for the minor street should immediately change to steady red signal indications, and the flashing yellow signal indications for the through movements on the major street should change to steady yellow signal indications followed by a steady red clearance interval before changing to green signal indications for the major traffic movement on the major street.

Standard:

During programmed changes out of flashing mode, no flashing yellow signal indication shall be terminated and immediately followed by a steady red or flashing red signal indication without first displaying the a steady yellow signal indication.

Option:

Because special midblock signals that rest in flashing circular yellow in the position normally occupied by the green signal indication do not have a green signal indication in the signal face, these signals may go directly from flashing circular yellow (in the position normally occupied by the green signal indication) to steady yellow without going first to a green signal indication.

- Section 4D.32 Temporary and Portable Traffic Control Signals

 This section was relocated to new Section 4D.10
- 32 Section 4D.33 Lateral Offset of Signal Supports and Cabinets
 33 Section 4A.06
- 34 Section 4D.34 Use of Signs at Signalized Locations
 This section was relocated to new Section
 4A.07
- 36 Section 4D.35 Use of Pavement Markings at Signalized Locations
 This section was relocated to new Section 4A.08

CHAPTER 4H. BICYCLE SIGNALS

New Chapter added to reflect Interim Approval 16, Official Change Request 4(09)-43, and Official Change Request 4(09)-68

4 Section 4H.01 Use of Bicycle Signal Faces

5 Option:

A bicycle signal face may be used to provide separate control of a bicycle movement for various situations, including the following:

- A. To provide a leading or lagging bicycle interval.
- B. To continue a through bicycle lane on the right-hand side of an exclusive right-turn lane (or on the left-hand side of an exclusive left-turn lane) that would otherwise be in non-compliance with Paragraph 1 of Section 9E.02 or Paragraph 7 of Section 9E.06.
- C. To provide a bicycle interval for a counter-flow bicycle facility.
- D. To provide for unusual or unexpected arrangements of the bicycle movement through complex intersections, conflict areas, or signal control.
- E. Bicyclist non-compliance with the previous traffic control.

Guidance:

Agend should exercise consistency with the decision to introduce bicycle signal faces to a roadway or bikeway network and use caution with any non-systematic policy to use bicycle signal faces.

Support:

The use of bicycle traffic signal faces containing bicycle symbol indications and bicycle signal faces containing circular indications in the same corridor or jurisdiction could create comprehension issues by the roadway user or violate bicyclist expectation.

A bicycle signal face rouse be used at a mid-block traffic control signal where there are no motor vehicle movements parallel to the bicycle crossing.

Standard:

If used, a bicycle gnal face shall only be used to control bicycle movements from a designated bicycle lane or from a separate facility, such as a shared use path.

If used, a bicycle signal face shall only be used to control bicycle movements where bicyclists moving on a GREEN BICYCLE or YELLOW BICYCLE signal indication are not in conflict with any simultaneous motor vehicle movement at the signalized location, including right (or left) turns on red from the same approach as the bicycle movement.

32 Option:

A bicycle signal face may be used to control bicycle movements where bicycles moving on a GREEN BICYCLE or YELLOW BICYCLE signal indication are in conflict with a simultaneous permissive turning movement only if the bicycle movement is from a one-way bicycle lane in the same direction as the adjacent general purpose lane, a flashing yellow arrow indication is shown to vehicles turning across the bicycle movement, and lane extension markings are provided for the bicycle lane across the intersection.

38 Guidance:

If used where motor vehicle traffic can make the same movements as bicyclists, a bicycle signal face should only be used if the bicycle movement controlled by the bicycle signal face is sometimes allowed to proceed or sometimes required to stop at times when motor vehicle traffic, making the same movement and controlled by other vehicular signal faces, is required to stop or allowed to proceed, respectively.

Section 4H.02 Prohibited Uses of Bicycle Signal Faces

Standard:

Bicycle signal faces shall not be used to control simultaneous bicycle movements from perpendicular or nearly perpendicular directions.

Bicycle signal faces shall not be used for controlling any bicycle movement that is sharing a lane with motor vehicle traffic.

- Bicycle signal faces shall not be used in any manner with respect to the design and operation of a
- 2 **hybrid beacon.**
 - Section 4H.03 Warrants for Bicycle Signal Faces
- 4 Standard:

3

9

10

- New designs or installations for any traffic control signal shall be based on an engineering study in accordance with Paragraph 1 of Section 4C.01. For the purposes of an engineering study, the appropriate warrant(s) provided in Chapter 4C shall be followed.
- 8 **Guidance**:
 - The decision as to whether to incorporate a bicycle signal face(s) into a new traffic control signal design should be made during the engineering study performed in accordance with Paragraph 1 of Section 4C.01.
- Engineering judgment should be exercised in determining whether or not it would be advantageous or beneficial to install a bicycle signal face(s) at an existing traffic control signal.
- 13 Support:
- Retrofitting existing traffic signals with bicycle signal faces is analogous to retrofitting existing traffic signals with pedestrian signals where such a determination is not required through an engineering study.
- For the purpose of warrant analyses, provisions for classifying bicycles are provided in Paragraph 15 of Section 4C.01 and Paragraph 2 of Section 9F.01.
- 18 Section 4H.04 Bicycle Signal Signs
- 19 Support:
- The primary purposes of the Bicycle Signal (R10-40, R10-40a, R10-41, R10-41a, R10-41b) sign (see Section 9B.22) are to inform road users that the signal indications in the bicycle signal face are intended only
- for bicyclists, and to inform bicyclists which specific bicycle movements are controlled by the bicycle signal
- 23 face.
- 24 **Standard:**
- Except as provided in Paragraph 3, a Bicycle Signal (R10-40, R10-40a, R10-41, R10-41a, or R10-
- 26 41b) sign shall be installed immediately adjacent to (including above or below) every bicycle signal face.
- The Bicycle Signal sign shall have a minimum size of 24 inches x 36 inches if it is placed next to an
- overhead-mounted bicycle signal face and shall have a minimum size of 12 inches x 21 inches if it is
- 29 placed next to a post-mounted bicycle signal face.
- 30 Option:
- The Bicycle Signal sign may be omitted adjacent to a supplemental near-side bicycle signal face
- 32 containing 4-inch indications.
- 33 <u>Section 4H.05 Application of Bicycle Symbol Signal Indications during Steady (Stop-and-Go)</u>
 34 Operation
- 35 **Standard:**

37

38

39

40

41

42

43

44 45

46 47

48

- 36 Steady bicycle symbol signal indications shall be applied as follows:
 - A. A steady RED BICYCLE signal indication shall be displayed when it is intended to prohibit bicycle traffic from entering the intersection or other controlled area. Turning after stopping shall be permitted as stated in Item C in Paragraph 1 of Section 4A.05.
 - B. A steady YELLOW BICYCLE signal indication shall be displayed following a GREEN

 BICYCLE signal indication in the same bicycle signal face. A YELLOW BICYCLE signal
 indication shall not be displayed in conjunction with the change from the RED BICYCLE signal
 indication to a GREEN BICYCLE signal indication. The YELLOW BICYCLE signal
 indication shall be followed by a RED BICYCLE signal indication.
 - C. A steady GREEN BICYCLE signal indication shall be displayed only when it is intended to permit bicyclists to make the movement(s) indicated by the lane-use arrow(s) displayed on the Bicycle Signal (R10-35 or R10-35a) sign that is located immediately adjacent to the bicycle signal face.

Section 4H.06 Application of Bicycle Symbol Signal Indications during Flashing Operation Standard:

The mode of operation of the bicycle signal faces at a traffic control signal shall be the same as the mode of operation of the other traffic signal faces at the same signalized location. Bicycle signal faces shall operate in the steady (stop-and-go) mode when the other traffic signal faces are operating in the steady (stop-and-go) mode. Bicycle signal faces shall operate in the flashing mode when the other signal faces are operating in the flashing mode. Bicycle signal faces shall not be placed in a dark mode when other vehicular traffic signal faces are operating in the flashing mode.

Guidance:

3

4

5

6

7

8

9

10

11 12

13

14

15

16

17

24

25

26

28

29

30

31 32

33

34

35

36

37 38

39

40

41 42

44

When a traffic control signal is operated in the flashing mode, bicycle signal faces should display a flashing RED BICYCLE signal indication if the other vehicular signal faces on the same approach are displaying flashing red signal indications or if there are no other vehicular signal faces on the same approach.

When a traffic control signal is operated in the flashing mode, bicycle signal faces should display a flashing YELLOW BICYCLE signal indication if the other vehicular signal faces for the through lanes on the same approach are displaying flashing yellow signal indications unless it is determined by engineering judgment that a flashing RED BICYCLE signal indication would provide a safer operation.

18 Option:

19 A flashing YELLOW BICYCLE signal indication may be used to indicate the presence of turning
20 vehicles, which would be operating under a flashing yellow arrow indication, as described in Section 4H.01
21 paragraph 07.

22 <u>Section 4H.07 Layout of Bicycle Signal Faces</u>

23 **Standard:**

Bicycle signal faces shall consist of all bicycle symbol signal indications (see Figure 4H-1). Circular or arrow signal indications shall not be used in a bicycle signal face.

Figure 4H-1. Example of Bicycle Signal Face

27 Option:

Bicycle signal faces may be oriented vertically or horizontally.

Standard:

The layouts and arrangements of the bicycle signal face shall be in accordance with the following provisions:

- A. Only the bicycle symbol shown on Page 6-7 in the 2004 Standard Highway Signs book shall be used for bicycle symbol signal indications and shall be proportioned to fit within the signal lens. The bicycle symbol shall only be positioned horizontally and shall face to the left.
- B. The RED BICYCLE, YELLOW BICYCLE, and GREEN BICYCLE signal indications shall be in the same relative position to each other as specified for the CIRCULAR RED, CIRCULAR YELLOW, and CIRCULAR GREEN signal indications, respectively, in Sections 4E.04 and 4E.05.
- C. As a specific exception to Paragraph 5 of Section 4E.04, two YELLOW BICYCLE signal indications or two GREEN BICYCLE signal indications shall not be arranged horizontally adjacent to each other at right angles to the basic straight line arrangement to form a clustered signal face.

43 Option:

- Backplates (see Paragraphs 19 and 20 in Section 4D.05) may be used with bicycle signal faces.
- 45 If a bicycle signal face having 4-inch signal indications is used, the accompanying visors may be omitted.

46 Section 4H.08 Size of Bicycle Symbol Signal Indications

47 **Standard:**

There shall be three nominal diameter sizes for bicycle signal indications: 4 inches, 8 inches, and 12

- 1 All signal indications in a bicycle signal face shall be of the same size.
- Four-inch signal indications shall not be used for any bicycle signal face other than a supplemental, post-mounted, near-side bicycle signal face.
- 4 Section 4H.09 Placement of Bicycle Signal Faces
- **Standard:**

The provisions of Sections 4D.04 through 4D.07 shall apply to the placement of the bicycle signal faces except as follows:

- A. As a specific exception to Item A in Paragraph 1 of Section 4D.04, a minimum of one primary bicycle signal face shall be provided to control traffic for the bicycle movement, even if a bicycle through movement exists.
- B. The primary bicycle signal face shall have either 8-inch or 12-inch signal indications, even if it is located at the near side of the signal-controlled location.
- C. When the primary bicycle signal face is located more than 120 feet beyond the stop line, a supplemental near-side bicycle signal face shall be provided.

Guidance:

When the primary bicycle signal face is located more than 80 feet and up to 120 feet beyond the stop line, a supplemental near-side bicycle signal face should be provided.

A bicycle signal face should be separated horizontally or vertically from the nearest vehicular traffic signal face for the same approach by at least 3 feet measured either horizontally perpendicular to the approach between the centers of the signal faces or vertically from the center of the lowest signal indication of the top signal face to the center of the highest signal indication of the bottom signal face. If horizontally-arranged or clustered signal faces are used, the minimum 3-foot horizontal separation between the two signal faces should be measured from the center of the right-most signal indication in the signal face on the left to the center of the left-most signal indication in the signal face on the right.

Bicycle signal faces should be placed such that visibility is maximized for bicyclists and minimized for adjacent or conflicting vehicle movements not controlled by the bicycle signal face. Consideration should be given to using visibility-limited bicycle signal faces in situations where drivers not controlled by the bicycle signal face might be confused by viewing the bicycle signal indications, such as when the bicycle movement controlled by the bicycle signal face is sometimes allowed to proceed or sometimes required to stop at times when motor vehicle traffic, making the same movement and controlled by other vehicular signal faces, is required to stop or allowed to proceed, respectively.

Section 4H.10 Mounting Height of Bicycle Signal Faces

Standard:

The provisions of Section 4D.08 shall apply to the mounting height of bicycle signal faces except as follows:

- A. The bottom of the signal housing (including brackets) of a bicycle signal face that is not located over a roadway shall be a minimum of 7 feet above the sidewalk or ground, except where the Bicycle Signal (R10-35 or R10-35a) sign is installed below the bicycle signal face. If the Bicycle Signal sign is installed below the bicycle signal face, the minimum mounting height to the bottom of the sign shall be 6 feet. If the bottom of the sign is mounted less than 7 feet above a pedestrian sidewalk or pathway, the sign shall not project more than 4 inches into the pedestrian facility.
- B. If 4-inch signal indications are used in a supplemental, post-mounted, near-side bicycle signal face, the bottom of the signal housing (including brackets) shall be a minimum of 4 feet and a maximum of 8 feet above the sidewalk or ground. Bicycle signal faces with 4-inch signal indications installed above a pedestrian sidewalk or pathway shall not project more than 4 inches into the pedestrian facility.
- 48 Section 4H.11 Intensity and Light Distribution of Bicycle Signal Faces
- *Guidance*:

1	Except for the 4-inch nominal size of the lens diameter, the intensity and distribution of light from each
2	illuminated bicycle signal face should be similar to that recommended for vehicular traffic signal faces in
3	accordance with Paragraph 11 of Section 4E.01 to the extent practical.

Section 4H.12 Yellow Change and Red Clearance Intervals for Bicycle Signal Faces

5 **Standard:**

4

6

7

8

9

The provisions of Section 4F.17 shall apply to the duration of the yellow change and the red clearance intervals of a bicycle signal phase except that the minimum duration of the yellow change interval shall be 3 seconds.

Support:

10 The exclusive function of the yellow change interval is to warn bicyclists approaching a signalized 11 location that their permission to proceed is being terminated after which they will be directed to stop. 12

Providing clearance time for a bicyclist to travel through the intersection or conflict area is the purpose of the

13 red clearance interval rather than the yellow change interval.

CHAPTER 4E-4I. PEDESTRIAN CONTROL FEATURES

Section 4E.01 4I.01 Pedestrian Signal Heads

Support:

Pedestrian signal heads provide special types of traffic signal indications exclusively intended for controlling pedestrian traffic. These signal indications consist of the illuminated symbols of a WALKING PERSON (symbolizing WALK) and an UPRAISED HAND (symbolizing DONT WALK).

See Section 4D.02 for information on when to use pedestrian signal heads.

Guidance:

Engineering judgment should determine the need for separate pedestrian signal heads (see Section 4D.02) and accessible pedestrian signals (see Section 4K.01).

Accessible pedestrian signals (see Chapter 4K) that provide information in non-visual formats (such as audible tones, speech messages, and/or vibrating surfaces) should be provided based on the results of an engineering study considering the factors listed in Section 4K.01.

Support:

Chapter 4J contains information regarding the use of pedestrian hybrid beacons and Chapter 4U contains information regarding the use of In-Roadway Warning Lights at unsignalized marked crosswalks.

Section 4E.02 Meaning of Pedestrian Signal Head Indications Section was relocated to new Section 4A.05

Section 4E.03 Application of Pedestrian Signal Heads
P1 and P3 were relocated to new Section
4D.02, P2 deleted; Section deleted

Section <u>4E.04 4I.02</u> Size, Design, and Illumination of Pedestrian Signal Head Indications Standard:

All new pedestrian signal head indications shall be displayed within a rectangular background and shall consist of symbolized messages (see Figure 4I-14E-1), except that existing pedestrian signal head indications with lettered or outline style symbol messages shall be permitted to be retained for the remainder of their useful service life. The symbol designs that are set forth in the "Standard Highway Signs and Markings" book (see Section 1A.05) shall be used. Each pedestrian signal head indication shall be independently displayed and emit a single color.

Figure 4I-1. Typical Pedestrian Signal Indications

If a two-section pedestrian signal head is used, the UPRAISED HAND (symbolizing DONT WALK) signal section shall be mounted directly above the WALKING PERSON (symbolizing WALK) signal section. If a one-section pedestrian signal head is used, the symbols shall be either overlaid upon each other or arranged side-by-side with the UPRAISED HAND symbol to the left of the WALKING PERSON symbol, and a light source that can display each symbol independently shall be used.

The WALKING PERSON (symbolizing WALK) signal indication shall be white, conforming to the publication entitled "Pedestrian Traffic Control Signal Indications" (see Section 1A.11), with all except the symbol obscured by an opaque material for signal optical units that use incandescent lamps within optical assemblies that include lenses. The UPRAISED HAND (symbolizing DONT WALK) signal indication shall be Portland orange, conforming to the publication entitled "Pedestrian Traffic Control Signal Indications" (see Section 1A.11), with all except the symbol obscured by an opaque material for signal optical units that use incandescent lamps within optical assemblies that include lenses.

Except as provided in Paragraph 5, the requirements of Chapter 3 of the publication entitled "Equipment and Materials Standards of the Institute of Transportation Engineers" (see Section 1A.05) that pertain to the aspects of the pedestrian signal head design that affect the display of the signal indications shall be met for signal optical units that use incandescent lamps within optical assemblies that include lenses. Except as provided in Paragraph 5, the requirements of the publication entitled "Pedestrian Traffic Control Signal Indicators – Light Emitting Diode (LED) Signal Modules" (see Section 1A.05) that pertain to the aspects of the signal head design that affect the display of the signal indications shall be met for light emitting diode (LED) pedestrian signal head modules.

Guidance:

The intensity and distribution of light from each illuminated pedestrian signal lens or LED pedestrian signal head module should comply with the publications specified in Paragraph 4, as appropriate.

When not illuminated, the WALKING PERSON (symbolizing WALK) and UPRAISED HAND (symbolizing DONT WALK) symbols shall-should not be readily-visible to pedestrians at the far end of the crosswalk that the pedestrian signal head indications control. Standard changed to Guidance

Standard:

For pedestrian signal head indications, the symbols shall be at least 6 inches high.

The light source of a flashing UPRAISED HAND (symbolizing DONT WALK) signal indication shall be flashed continuously at a rate of not less than 50 or more than 60 times per minute. The displayed period of each flash shall be a minimum of 1/2 and a maximum of 2/3 of the total flash cycle.

Guidance:

Pedestrian signal head indications should be conspicuous and recognizable to pedestrians at all distances from the beginning of the controlled crosswalk to a point 10 feet from the end of the controlled crosswalk during both day and night.

For crosswalks where the pedestrian enters the crosswalk more than 100 feet from the pedestrian signal head indications, the symbols should be at least 9 inches high.

If the pedestrian signal indication is so bright that it causes excessive glare in nighttime conditions, some form of automatic dimming should be used to reduce the brilliance of the signal indication.

Option:

An animated eyes symbol may be added to a pedestrian signal head in order to prompt pedestrians to look for vehicles in the intersection during the time that the WALKING PERSON (symbolizing WALK) signal indication is displayed.

Standard:

If used, the animated eyes symbol shall consist of an outline of a pair of white steadily-illuminated eyes with white eyeballs that scan from side to side at a rate of approximately once per second. The animated eyes symbol shall be at least 12 inches wide with each eye having a width of at least 5 inches and a height of at least 2.5 inches. The animated eyes symbol shall be illuminated at the start of the walk interval and shall terminate at the end of the walk interval.

Section 4E.05 4I.03 Location and Height of Pedestrian Signal Heads

Standard:

Pedestrian signal heads shall be mounted with the bottom of the signal housing including brackets not less than 7 feet or more than 10 feet above sidewalk level, and shall be positioned and adjusted to provide maximum visibility at the beginning of the controlled sidewalk.

Guidance: Standard changed to Guidance

If pedestrian signal heads are mounted on the same support as vehicular signal heads, there shall be a physical separation between them.

Section 4E.06 Pedestrian Intervals and Signal Phases

This section was relocated to new Section

4I.06

40 Section 4E.07 4I.04 Countdown Pedestrian Signals

Standard:

All pedestrian signal heads used at crosswalks where the pedestrian change interval is more than 7 seconds shall include a pedestrian change interval countdown display in order to inform pedestrians of the number of seconds remaining in the pedestrian change interval.

45 Option:

Pedestrian signal heads used at crosswalks where the pedestrian change interval is 7 seconds or less may include a pedestrian change interval countdown display in order to inform pedestrians of the number of seconds remaining in the pedestrian change interval.

Standard:

Where countdown pedestrian signals are used, the countdown shall always be displayed simultaneously with the flashing UPRAISED HAND (symbolizing DONT WALK) signal indication displayed for that crosswalk.

Countdown pedestrian signals shall consist of Portland orange numbers that are at least 6 inches in height on a black opaque background. The countdown pedestrian signal shall be located immediately adjacent to the associated UPRAISED HAND (symbolizing DONT WALK) pedestrian signal head indication (see Figure 4I-14E-1).

The display of the number of remaining seconds shall begin only at the beginning of the pedestrian change interval (flashing UPRAISED HAND). After the countdown displays zero, the display shall remain dark until the beginning of the next countdown.

The countdown pedestrian signal shall display the number of seconds remaining until the termination of the pedestrian change interval (flashing UPRAISED HAND). Countdown displays shall not be used during the walk interval. or Countdown displays shall not be used during the red clearance interval of a concurrent vehicular phase that is ending simultaneously with or after the end of the pedestrian phase.

Guidance:

If used with a pedestrian signal head that does not have a concurrent vehicular phase, the pedestrian change interval (flashing UPRAISED HAND) should be set to be approximately 4 seconds less than the required pedestrian clearance time (see Section 41.07) and an additional clearance interval (during which a steady UPRAISED HAND is displayed) should be provided prior to the start of the conflicting vehicular phase.

For crosswalks where the pedestrian enters the crosswalk more than 100 feet from the countdown pedestrian signal display, the numbers should be at least 9 inches in height.

Because some technology includes the countdown pedestrian signal logic in a separate timing device that is independent of the timing in the traffic signal controller, care should be exercised by the engineer when timing changes are made to pedestrian change intervals.

If the pedestrian change interval is interrupted or shortened as a part of a transition into a preemption sequence (see Section 4F.19), the countdown pedestrian signal display should be discontinued and go dark immediately upon activation of the preemption transition.

Section 4E.08 4I.05 Pedestrian Detectors

Option:

Pedestrian detectors may be push buttons or passive detection devices. <u>Pedestrian detectors may include</u> features that allow touch-free activation in addition to all other push button features required in this section. Support:

Passive detection devices register the presence of a pedestrian in a position indicative of a desire to cross, without requiring the pedestrian to push a button. Some passive detection devices are capable of tracking the progress of a pedestrian as the pedestrian crosses the roadway for the purpose of extending or shortening the duration of certain pedestrian timing intervals.

The provisions in this Section place pedestrian push buttons within easy reach of pedestrians who are intending to cross each crosswalk and make it obvious which push button is associated with each crosswalk. These provisions also position push button poles in optimal locations for installation of accessible pedestrian signals (see Chapter 4K). Information regarding reach ranges can be found in the <u>U.S. Department of Justice 2010 ADA Standards for Accessible Design, September 15, 2010 and Code of Federal Regulations. Title 28, Parts 35 and 36. Americans with Disabilities Act of 1990 "Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" (see Section 1A.05).</u>

Guidance:

If pedestrian push buttons are used, they should be capable of easy activation <u>requiring no more than 5</u> <u>pounds of force, not require tight grasping, pinching, or twisting of the wrist, and be conveniently located</u>

near each end of the crosswalks. Except as provided in Paragraphs 5 and 6, pedestrian push buttons should be located to meet all of the following criteria (see Figure 4I-24E-3):

- A. Unobstructed and accessible within one or more of the reach ranges specified in Section 308, and from a clear ground clearance as specified in Section 305, of the 2010 ADA Standards for Accessible Designadjacent to a level all weather surface to provide access from a wheelchair;
- B. Where there is an all weather surface, <u>To provide</u> a wheelchair accessible route from the push button to the ramp;
- C. Between the edge of the crosswalk line (extended) farthest from the center of the intersection and the side of a the curb ramp (if present), but not greater than 5 feet from said crosswalk line; On the side of the curb ramp which is farthest from the center of the intersection;
- D. Not greater than 10 feet from the edge of the associated curb ramp which is farther from the center of the intersection;
- E. Not greater than 5 feet from the outside edge of the marked crosswalk farthest from the center of the intersection;
- <u>F. Not farther from the crosswalk than the stop line is, if present;</u>
- D.G. Between 1.5 and 6 feet from the edge face of the curb; or from the outside edge of the shoulder; (or if no shoulder exists, from the edge of the pavement);
- E.H. With the face of the push button parallel to the crosswalk to be used; and
- I. F. At a mounting height of approximately 3.5 feet, but no more than 4 feet, above the sidewalk;
- J. Allowing a minimum 4-foot continuous clear width for a pedestrian access route; and
- F.K. Outside the flared side of the curb ramp, if present.

Figure 4I-2. Pushbutton Location Area

Figure 4I-3. Typical Pushbutton Locations

Where there are physical constraints that make it impractical to place the pedestrian push button adjacent to a level all-weather surface, the surface should be as level as feasible.

Where there are physical constraints that make it impractical to place the pedestrian push button between 1.5 and 6 feet from the <u>edge</u> face of the curb<u><u></u>, or from the outside edge of the shoulder<u></u>, (or if no shoulder exists, from the edge of the pavement), it should not be farther than 10 feet from the <u>edge</u> face of the curb<u></u>, or from the outside edge of the shoulder<u></u>, (or if no shoulder exists, from the edge of the pavement).</u>

Except as provided in Paragraph 8, where two pedestrian push buttons are provided on the same corner of a signalized location, the push buttons should be separated by a distance of at least 10 feet.

Option:

Where there are physical constraints on a particular corner that make it impractical to provide the 10-foot separation between the two pedestrian push buttons, or when an exclusive pedestrian phase is used at an intersection and the pedestrian signals controlling the crosswalks on a given corner of the intersection both operate together such that the "Walk" indication is always simultaneous for both crosswalks, the push buttons may be placed closer together or on the same pole. Revised to reflect Official Change Request 4(09)-42 Support:

Figure 4I-3 4E-4 shows typical pedestrian push button locations for a variety of situations.

Standard:

If a pedestrian push button is provided, a signs (see Section 2B.62) shall also be mounted adjacent to or integral with installed explaining the purpose and use of the pedestrian push buttons detector, explaining their purpose and use.

Option:

At certain locations, a supplemental sign in a more visible location may be used to call attention to the pedestrian push button.

Standard:

The positioning of pedestrian push buttons and the legends on the pedestrian push button signs shall elearly indicate which crosswalk signal is actuated by each pedestrian push button. Revised to reflect Official Change Request 4(09)-42

If the pedestrian clearance time is sufficient only to cross from the curb or shoulder to a median of sufficient width for pedestrians to wait and the signals are pedestrian actuated, an additional pedestrian detector shall be provided in the median.

Guidance:

The use of additional pedestrian detectors on islands or medians where a pedestrian might become stranded should be considered.

If used, special purpose push buttons (to be operated only by authorized persons) should include a housing capable of being locked to prevent access by the general public and do not need an instructional sign.

Standard:

If used, a pilot light or other means of indication installed with a pedestrian push button shall not be illuminated until actuation. Once it is actuated, the pilot light shall remain illuminated until the pedestrian's green or WALKING PERSON (symbolizing WALK) signal indication is displayed.

If a pilot light is used at an accessible pedestrian signal location (see Sections 4E.09 through 4E.13), each actuation shall be accompanied by the speech message "wait." Repeat of P23 in existing 4E.11 Option:

At signalized locations with a demonstrated need and subject to equipment capabilities, pedestrians with special needs may be provided with additional crossing time by means of an extended push button press.

Standard:

If additional crossing time is provided by means of an extended push button press, a PUSH BUTTON FOR 2 SECONDS FOR EXTRA CROSSING TIME (R10-32P) plaque (see Section 2B.62) shall be mounted adjacent to or integral with the pedestrian pushbutton installed.

Section 4E.06 4I.06 Pedestrian Intervals and Signal Phases

Standard:

At intersections equipped with pedestrian signal heads, the pedestrian signal indications shall be displayed except when the vehicular traffic control signal is being operated in the flashing mode. At those times, the pedestrian signal indications shall not be displayed.

Except as provided in Paragraph 3, when the pedestrian signal heads associated with a crosswalk are displaying either a steady WALKING PERSON (symbolizing WALK) or a flashing UPRAISED HAND (symbolizing DONT WALK) signal indication, a steady or a flashing red signal indication shall be shown to any conflicting vehicular movement that is approaching the intersection or midblock location perpendicular or nearly perpendicular to the crosswalk.

When the pedestrian signal heads at a pedestrian hybrid beacon (see Chapter 4J) location are displaying a flashing UPRAISED HAND (symbolizing DONT WALK) signal indication, a flashing red signal indication shall be shown to any conflicting vehicular movement that is approaching the intersection or midblock location perpendicular or nearly perpendicular to the crosswalk.

When pedestrian signal heads are used, a WALKING PERSON (symbolizing WALK) signal indication shall be displayed only when pedestrians are permitted to leave the curb or shoulder.

A pedestrian change interval consisting of a flashing UPRAISED HAND (symbolizing DONT WALK) signal indication shall begin immediately following the WALKING PERSON (symbolizing WALK) signal indication. Following the pedestrian change interval, a buffer interval consisting of a steady UPRAISED HAND (symbolizing DONT WALK) signal indication shall be displayed for at least 3-2 seconds prior to the release of any conflicting vehicular movement. The sum of the time of the pedestrian change interval and the buffer interval shall not be less than the calculated pedestrian clearance time (see Paragraphs 8 through 17). The buffer interval shall not begin later than the beginning of the red clearance interval, if used. Revised to reflect Official Change Request 4(09)-42

46 Option:

During the yellow change interval, the UPRAISED HAND (symbolizing DON'T WALK) signal indication may be displayed as either a flashing indication, a steady indication, or a flashing indication for an initial portion of the yellow change interval and a steady indication for the remainder of the interval.

50 Support:

Figure 41-4 4E-2-illustrates the pedestrian intervals and their possible relationships with associated vehicular signal phase intervals.

Figure 4I-4. Pedestrian Intervals

Guidance:

Except as provided in Paragraph 9, the pedestrian clearance time should be sufficient to allow a pedestrian crossing in the crosswalk who left the curb or shoulder-edge of pavement at the end of the WALKING PERSON (symbolizing WALK) signal indication to travel at a walking speed of 3.5 feet per second to at least the far side of the traveled way or to a median of sufficient width for pedestrians to wait.

Option:

A walking speed of up to 4 feet per second may be used to evaluate the sufficiency of the pedestrian clearance time at locations where an extended push button press function has been installed to provide slower pedestrians an opportunity to request and receive a longer pedestrian clearance time. Passive pedestrian detection may also be used to automatically adjust the pedestrian clearance time based on the pedestrian's actual walking speed or actual clearance of the crosswalk.

The additional time provided by an extended push button press to satisfy pedestrian clearance time needs may be added to either the walk interval or the pedestrian change interval.

Guidance:

Where pedestrians who walk slower than 3.5 feet per second, or pedestrians who use wheelchairs, routinely use the crosswalk, a walking speed of less than 3.5 feet per second should be considered in determining the pedestrian clearance time.

Except as provided in Paragraph 13, the walk interval should be at least 7 seconds in length so that pedestrians will have adequate opportunity to leave the curb or shoulder before the pedestrian clearance time begins.

Option:

If pedestrian volumes and characteristics do not require a 7-second walk interval, walk intervals as short as 4 seconds may be used.

Support:

The walk interval is intended for pedestrians to start their crossing. The pedestrian clearance time is intended to allow pedestrians who started crossing during the walk interval to complete their crossing. Longer walk intervals are often used when the duration of the vehicular green phase associated with the pedestrian crossing is long enough to allow it.

Guidance:

The total of the walk interval and pedestrian clearance time should be sufficient to allow a pedestrian crossing in the crosswalk who left the pedestrian detector (or, if no pedestrian detector is present, a location 6 feet from behind the face of the curb or from 6 feet behind the edge of the pavement) at the beginning of the WALKING PERSON (symbolizing WALK) signal indication to travel at a walking speed of 3 feet per second to the far side of the traveled way being crossed or to the median if a two-stage pedestrian crossing sequence is used. Any additional time that is required to satisfy the conditions of this paragraph should be added to the walk interval.

Option:

On a street with a median of sufficient width for pedestrians to wait, a pedestrian clearance time that allows the pedestrian to cross only from the curb or shoulder to the median may be provided.

Standard:

Where the pedestrian clearance time is sufficient only for crossing from the curb or shoulder to a median of sufficient width for pedestrians to wait, median-mounted pedestrian signals, with pedestrian detectors (see Sections 4I.06 and 4K.02) if actuated operation is used, shall be provided and signing such as the R10-3d sign (see Section 2B.62) shall be provided to notify pedestrians to cross only to the median to await the next WALKING PERSON (symbolizing WALK) signal indication.

49 Guidance:

Where median-mounted pedestrian signals and detectors are provided, the use of accessible pedestrian signals (see Chapter 4K) should be considered

Option:

During the transition into preemption, the walk interval and the pedestrian change interval may be shortened or omitted as described in Section 4F.19.

At intersections with high pedestrian volumes and high conflicting turning vehicle volumes, a brief leading pedestrian interval, during which an advance WALKING PERSON (symbolizing WALK) indication is displayed for the crosswalk while red indications continue to be displayed to parallel through and/or turning traffic, may be used to reduce conflicts between pedestrians and turning vehicles.

Guidance:

If a leading pedestrian interval is used, the use of accessible pedestrian signals (see Sections 4E.09 through 4E.13 Chapter 4K) should be considered.

Support:

If a leading pedestrian interval is used without accessible features, pedestrians who are visually impaired with vision disabilities can be expected to begin crossing at the onset of the vehicular movement when drivers are not expecting them to begin crossing.

Guidance:

If a leading pedestrian interval is used, it should be at least 3 seconds in duration and should be timed to allow pedestrians to cross at least one lane of traffic or, in the case of a large corner radius, to travel far enough for pedestrians to establish their position ahead of the turning traffic before the turning traffic is released.

If a leading pedestrian interval is used, consideration should be given to prohibiting turns across the crosswalk during the leading pedestrian interval.

Standard:

At locations where a leading pedestrian interval is used without accessible pedestrian signals, the minimum required time for the Walk Interval shall be displayed in addition to the time provided for the leading pedestrian interval.

Support:

At intersections with pedestrian volumes that are so high that drivers have difficulty finding an opportunity to turn across the crosswalk, the duration of the green interval for a parallel concurrent vehicular movement is sometimes intentionally set to extend beyond the pedestrian clearance time to provide turning drivers additional green time to make their turns while the pedestrian signal head is displaying a steady UPRAISED HAND (symbolizing DONT WALK) signal indication after pedestrians have had time to complete their crossings.

Section 4F.01 4J.01 Application of Pedestrian Hybrid Beacons

Support:

A pedestrian hybrid beacon is a special type of hybrid beacon used to warn and control traffic at an unsignalized location to assist pedestrians in crossing a street or highway at a marked crosswalk.

Option:

A pedestrian hybrid beacon may be considered for installation to facilitate pedestrian crossings at a location that does not meet traffic signal warrants (see Chapter 4C), or at a location that meets traffic signal warrants under Sections 4C.05 and/or 4C.06 but a decision is made to not install a traffic control signal.

Standard:

If used, pedestrian hybrid beacons shall be used in conjunction with signs and pavement markings to warn and control traffic at locations where pedestrians enter or cross a street or highway. A pedestrian hybrid beacon shall only be installed at a marked crosswalk.

Guidance:

If one of the signal warrants of Chapter 4C is met and a traffic control signal is justified by an engineering study, and if a decision is made to install a traffic control signal, it should be installed based upon the provisions of Chapters 4D through 4I and 4K.

If a traffic control signal is not justified under the signal warrants of Chapter 4C and if gaps in traffic are not adequate to permit pedestrians to cross, or if the speed for vehicles approaching on the major street is too high to permit pedestrians to cross, or if pedestrian delay is excessive, the need for a pedestrian hybrid beacon should be considered on the basis of an engineering study that considers major-street volumes, speeds, widths, and gaps in conjunction with pedestrian volumes, walking speeds and delay.

For a major street where the posted or statutory speed limit or the 85th-percenters speed is 35 mph or less, the need for a pedestrian hybrid beacon should be considered if the engineering study finds that the plotted point representing the vehicles per hour on the major street (total of both approaches) and the corresponding total of all pedestrians crossing the major street for 1 hour (any four consecutive 15-minute periods) of an average day falls above the applicable curve in Figure 4J-1 4F-1 for the length of the crosswalk.

For a major street where the posted or statutory speed limit or the 85th-p ntile speed exceeds 35 mph, the need for a pedestrian hybrid beacon should be considered if the engineering study finds that the plotted point representing the vehicles per hour on the major street (total of both approaches) and the corresponding total of all pedestrians crossing the major street for 1 hour (any four consecutive 15-minute periods) of an average day falls above the applicable curve in Figure 4.1-2 4F-2 for the length of the crosswalk.

For crosswalks that have lengths other than the four that are specifically shown in Figures 4J-1 4F-1 and 4J-2 4F-2, the values should be interpolated between the curves.

Figure 4J-1. Guidelines for the Installation of Pedestrian Hybrid Beacons on Low-Speed Roadways

Figure 4J-2. Guidelines for the Installation of Pedestrian Hybrid Beacons on High-Speed
Roadways

Option:

The criteria for the pedestrian volume crossing the major street shown in Figures 4J-1 and 4J-2 may be reduced as much as 50 percent if the 15th-percentile crossing speed of pedestrians is less than 3.5 feet per second.

Where there is a divided street having a median of sufficient width for pedestrians to wait, the criteria for the major-street traffic volume shown in Figures 4J-1 and 4J-2 may be applied separately to each direction of vehicular traffic. Added to reflect Official Interpretation 4(09)-25(I)

- Section 4F.02 4J.02 Design of Pedestrian Hybrid Beacons
- 47 Standard:

Except as otherwise provided in this Section, a pedestrian hybrid beacon shall meet the provisions of Chapters 4D through 4G, 4I, and 4J.

A pedestrian hybrid beacon face shall consist of three signal sections, with a CIRCULAR YELLOW signal indication centered below two horizontally aligned CIRCULAR RED signal indications (see Figure 4J-34F-3).

When an engineering study finds that installation of a pedestrian hybrid beacon is justified, then:

- A. At least two pedestrian hybrid beacon faces shall be installed for each approach of the major street,
- B. A stop line shall be installed for each approach to the crosswalk,
- C. A pedestrian signal head eonforming to complying with the provisions set forth in Chapter 4I shall be installed at each end of the marked crosswalk, and
- D. The pedestrian hybrid beacon shall be pedestrian actuated, and
- E. If the pedestrian hybrid beacon is installed at or immediately adjacent to an intersection with a minor street, a STOP sign shall be installed for each minor-street approach.

 Official Change Request 4(09)-16

Figure 4J-3. Sequence for a Pedestrian Hybrid Beacon

Guidance:

When an engineering study finds that installation of a pedestrian hybrid beacon is justified, then:

- A. The pedestrian hybrid beacon should be installed at least 100 feet from side streets or driveways that are controlled by STOP or YIELD signs, Deleted to reflect Official Change Request 4(09)-16
- A. Parking and other sight obstructions should be prohibited for at least 100 feet in advance of and at least 20 feet beyond the marked crosswalk, or site accommodations should be made through curb extensions or other techniques to provide adequate sight distance, and
- C. The installation should include suitable standard signs and pavement markings, and
- B. If installed within a signal system, the pedestrian hybrid beacon should be coordinated.

On approaches having posted or statutory speed limits or 85th-pe tile speeds in excess of 35 mph and on approaches having traffic or operating conditions that would tend to obscure visibility of roadside hybrid beacon face locations, both of the minimum of two pedestrian hybrid beacon faces should be installed over the roadway.

On multi-lane approaches having posted or statutory speed limits or 85th centile speeds of 35 mph or less, either a pedestrian hybrid beacon face should be installed on each side of the approach (if a median of sufficient width exists) or at least one of the pedestrian hybrid beacon faces should be installed over the roadway.

A pedestrian hybrid beacon should comply with the signal face location provisions described in Sections 4D.04 through 4D.09.

Accessible pedestrian signals should be installed in conjunction with a pedestrian hybrid beacon.

Revised to reflect Official Change Request 4(09)-42

Standard Option: Standard changed to Option; text revised to reflect Official Interpretation 4(09)-61(I) and Official Change Request 4(09)-42

A CROSSWALK STOP ON RED (symbolic circular red) (R10-23) sign or a STOP ON RED— PROCEED ON FLASHING RED WHEN CLEAR (R10-23a) sign (see Section 2B.63) shall-may be mounted installed adjacent to a pedestrian hybrid beacon face on facing each major street approach.

If an overhead pedestrian hybrid beacon face is provided, the sign shall be mounted adjacent to the overhead signal face.

Text was relocated to new Section 2B.63

Option:

A Pedestrian (W11-2) warning sign (see Section 2C.55) with an AHEAD (W16-9P) supplemental plaque may be placed in advance of a pedestrian hybrid beacon. A warning beacon may be installed to supplement the W11-2 sign.

Guidance:

1 If a warning beacon supplements a W11-2 sign in advance of a pedestrian hybrid beacon, it should be programmed to flash only when the pedestrian hybrid beacon is not in the dark mode.

Standard:

If a warning beacon is installed to supplement the W11-2 sign, the design and location of the warning beacon shall comply with the provisions of Sections 4S.01 and 4S.03.

Bicycle signal faces (see Chapter 4H) shall not be used at a pedestrian hybrid beacon.

Section 4F.03 4J.03 Operation of Pedestrian Hybrid Beacons

Standard:

Pedestrian hybrid beacon indications shall be dark (not illuminated) during periods between actuations.

Upon Following an actuation by a pedestrian, a pedestrian hybrid beacon face shall display a flashing CIRCULAR YELLOW signal indication, followed by a steady CIRCULAR YELLOW signal indication, followed by both steady CIRCULAR RED signal indications during the pedestrian walk interval, followed by alternating flashing CIRCULAR RED signal indications during the pedestrian change interval (see Figure 4J-34F-3). Upon termination of the pedestrian change interval, the pedestrian hybrid beacon faces shall revert to a dark (not illuminated) condition.

Except as provided in Paragraph 4, the pedestrian signal heads shall continue to display a steady UPRAISED HAND (symbolizing DONT WALK) signal indication when the pedestrian hybrid beacon faces are either dark or displaying flashing or steady CIRCULAR YELLOW signal indications. The pedestrian signal heads shall display a WALKING PERSON (symbolizing WALK) signal indication when the pedestrian hybrid beacon faces are displaying steady CIRCULAR RED signal indications. The pedestrian signal heads shall display a flashing UPRAISED HAND (symbolizing DONT WALK) signal indication when the pedestrian hybrid beacon faces are displaying alternating flashing CIRCULAR RED signal indications. Upon termination of the pedestrian change interval, the pedestrian signal heads shall revert to a steady UPRAISED HAND (symbolizing DONT WALK) signal indication.

Option:

Where the pedestrian hybrid beacon is installed adjacent to a roundabout to facilitate crossings by pedestrians with visual disabilities and an engineering study determines that pedestrians without visual disabilities can be allowed to cross the roadway without actuating the pedestrian hybrid beacon, the pedestrian signal heads may be dark (not illuminated) when the pedestrian hybrid beacon faces are dark.

Guidance:

The duration of the flashing yellow interval should be determined by engineering judgment.

If the pedestrian hybrid beacon is coordinated as a part of a signal system:

- A. The duration of the flashing yellow interval should not vary on a cycle-by-cycle basis.
- B. The pedestrian hybrid beacon should remain in the dark condition after a pedestrian actuation has been received until the point in the background cycle when the predetermined duration of the flashing yellow interval needs to be initiated in order to achieve the appropriate coordinated offset.

Option:

If a minimum dark time between activations of the pedestrian hybrid beacon has been set on the controller, the pedestrian hybrid beacon may remain in the dark condition after a pedestrian actuation has been received until the minimum dark time has been provided.

Added to reflect Official Interpretation 4(09)-32(1)

Standard:

The duration of the steady yellow change interval shall be determined using engineering practices <u>in</u> accordance with the provisions in Section 4F.17.

47 Guidance:

A yellow change interval should have a minimum duration of 3 seconds and a maximum duration of 6 seconds (see Section 4F.17). The longer intervals should be reserved for use on approaches with higher speeds.

1	Option:
2	A steady red clearance interval may be used after the steady yellow change inter

A steady red clearance interval may be used after the steady yellow change interval. Added to reflect Official Interpretation 4(09)-14 (I)

The alternating flashing CIRCULAR RED signal indications may continue to flash for a short period after the pedestrian change interval has terminated to provide a buffer interval for pedestrians. Added to reflect Official Interpretation 4(09)-14 (I)

A pedestrian hybrid beacon that is located in close proximity to an active grade crossing may be preempted in accordance with the applicable provisions in Sections 4F.19 and 8D.09.

Standard:

3

4

5

6

7

8

9

10

11 12

13

14

If a pedestrian hybrid beacon is placed into a flashing mode by a conflict monitor (malfunction management unit) or by a manual switch, the pedestrian hybrid beacon faces shall display flashing CIRCULAR YELLOW signal indications to each approach of the major street and the pedestrian signal heads shall revert to a dark (not illuminated) condition.

CHAPTER 4K. ACCESSIBLE PEDESTRIAN SIGNALS AND DETECTORS

Section 4E.09 4K.01 Accessible Pedestrian Signals and Detectors—General

Support

Accessible pedestrian signals and detectors provide information in non-visual formats (such as audible tones, speech messages, and/or vibrating surfaces).

The primary technique that pedestrians who have visual disabilities use to cross streets at signalized locations is to initiate their crossing when they hear the traffic in front of them stop and the traffic alongside them begin to move, which often corresponds to the onset of the green interval. The existing environment is often not sufficient to provide the information that pedestrians who have visual disabilities need to cross a roadway at a signalized location.

Guidance:

If a particular signalized location presents difficulties for pedestrians who have <u>visual vision</u> disabilities to cross the roadway, an engineering study should be conducted that considers the needs of pedestrians in general, as well as the information needs of pedestrians with <u>visual vision</u> disabilities. The engineering study should consider the following factors:

- A. Potential demand for accessible pedestrian signals;
- B. A request for accessible pedestrian signals;
- C. Traffic volumes during times when pedestrians might be present, including periods of low traffic volumes or high turn-on-red volumes;
- D. The complexity of traffic signal phasing (such as split phases, protected turn phases, leading pedestrian intervals, and exclusive pedestrian phases); and
- E. The complexity of intersection geometry.

Support:

The factors that make crossing at a signalized location difficult for pedestrians who have visual disabilities include: increasingly quiet cars, right turn on red (which masks the beginning of the through phase), continuous right-turn movements, complex signal operations, traffic circles, and wide streets. Furthermore, low traffic volumes might make it difficult for pedestrians who have visual disabilities to discern signal phase changes.

Local organizations, providing support services to pedestrians who have visual and/or hearing disabilities, can often act as important advisors to the traffic engineer when consideration is being given to the installation of devices to assist such pedestrians. Additionally, orientation and mobility specialists or similar staff also might be able to provide a wide range of advice. The U.S. Access Board (www.access-board.gov) provides technical assistance for making pedestrian signal information available to persons with visual disabilities (see Page i for the address for the U.S. Access Board).

Standard:

When used, accessible pedestrian signals shall be used in combination with pedestrian signal timing.

The information provided by an accessible pedestrian signal shall elearly indicate which pedestrian crossing is served by each device. Revised to reflect Official Change Request 4(09)-42

Under <u>steady (stop-and-go)</u> operation, accessible pedestrian signals shall not be limited in operation by the time of day or day of week.

Option:

Accessible pedestrian signal detectors may be push buttons or passive detection devices.

Guidance:

At locations with pretimed traffic control signals or non-actuated approaches where it is not necessary for pedestrians to push a push button detector to receive a WALKING PERSON signal indication, pedestrian push buttons may should be used to activate the accessible pedestrian signals and to provide information in non-visual formats to assist pedestrians with visual disabilities.

48 Support:

Accessible pedestrian signals are typically integrated into the pedestrian detector (push button), so the audible tones and/or messages come from the push button housing. They have a push button locator tone and a vibrotactile arrow, and can include audible beaconing and other special features.

Option:

The name of the street to be crossed may also be provided in accessible format, such as Braille or raised print. Tactile maps of crosswalks may also be provided.

Support:

Specifications regarding the use of Braille or raised print for traffic control devices can be found in the U.S. Department of Justice 2010 ADA Standards for Accessible Design, September 15, 2010 and Code of Federal Regulations. Title 28, Parts 35 and 36. Americans with Disabilities Act of 1990 "Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" (see Section 1A.05).

Standard:

At accessible pedestrian signal locations where <u>pressing the</u> pedestrian push buttons are used is <u>necessary to activate the walk interval</u>, each <u>pressing the pedestrian</u> push button shall activate both the walk interval and the accessible pedestrian signals.

Section 4E.10 4K.02 Accessible Pedestrian Signals and Detectors—Location

17 Support:

Accessible pedestrian signals that are located as close as possible to pedestrians waiting to cross the street provide the clearest and least ambiguous indication of which pedestrian crossing is served by a device.

Guidance:

Push buttons for accessible pedestrian signals should be located in accordance with the provisions of Section 41.06-05 and should be located as close as possible to the crosswalk line furthest from the center of the intersection and as close as possible to the curb ramp.

Standard:

Except for the situation regarding simultaneous "Walk" indications for both crosswalks as described in Paragraph 8 of Section 4I.06, if two accessible pedestrian push buttons are placed less than 10 feet apart or on the same pole (see Paragraphs 7 and 8 in Section 4I.06), each accessible pedestrian push button shall be provided with the following features (see Sections 4K.03 through 4K.05): Revised to reflect Official Interpretation 4(09)-3(1)

A. A pushbutton locator tone,

B. A tactile arrow,

- A. A speech walk message for the WALKING PERSON (symbolizing WALK) indication (see Section 4K.03), and
- B. A speech push button information message (see Section 4K.05).

If the pedestrian clearance time is sufficient only to cross from the curb or shoulder to a median of sufficient width for pedestrians to wait and accessible pedestrian signal detectors are used, an additional accessible pedestrian signal detector shall be provided in the median.

Section 4E.11 4K.03 Accessible Pedestrian Signals and Detectors—Walk Indications

Support:

Technology that provides different sounds for each non-concurrent signal phase has frequently been found to provide ambiguous information. Research indicates that a rapid tick tone for each crossing coming from accessible pedestrian signal devices on separated poles located close to each crosswalk provides unambiguous information to pedestrians who are blind or visually impaired. Vibrotactile indications provide information to pedestrians who are blind and deaf and are also used by pedestrians who are blind or who have low vision to confirm the walk signal in noisy situations.

Standard:

Accessible pedestrian signals shall have both audible and vibrotactile walk indications.

Vibrotactile walk indications shall be provided by a <u>vibro</u>tactile arrow <u>that is located</u> on the push button <u>or on the speaker box</u> (see <u>Paragraph 1 in Section 4K.04</u>) that. The vibrotactile arrow shall vibrates during the walk interval.

Accessible pedestrian signals shall have an audible walk indication during the walk interval only.

The audible walk indication shall be audible <u>from at</u> the beginning of the associated crosswalk. The accessible walk indication shall have the same duration as the pedestrian walk signal except when the pedestrian signal rests in walk.

Guidance:

If the pedestrian signal rests in walk, the accessible walk indication should be limited to the first 7 seconds of the walk interval. The accessible walk indication should be recalled by a button press during the walk interval provided that the crossing time remaining is greater-longer than the pedestrian change interval.

Standard:

Where two accessible pedestrian signals are separated by a distance of at least 10 feet, the audible walk indication shall be a percussive tone. Where two accessible pedestrian signals on one corner, or in a median, that are associated with different phases are not separated by a distance of at least placed less than 10 feet apart, the audible walk indication shall be a speech walk message (see Paragraph 3 in Section 4K.02). In all other cases, including at midblock crossings, on corners where only one accessible pedestrian signal is present, in a median, and on corners where two accessible pedestrian signals are separated by a distance of at least 10 feet, the audible walk indication shall be a percussive tone.

Audible tone walk indications shall repeat at eight to ten ticks per second. Audible tones used as walk indications shall consist of multiple frequencies with a dominant component at 880 Hz.

Guidance:

The volume of audible walk indications and push button locator tones (see Section 4K.04) should be set to be a maximum of 5 dBA louder than ambient sound, except when audible beaconing is provided in response to an extended push button press.

Standard:

Automatic volume adjustment <u>up to a maximum volume of 100 dBA</u> in response to ambient traffic sound level shall be provided up to a maximum volume of 100 dBA.

Guidance:

The sound level of audible walk indications and push button locator tones should be adjusted to be low enough to avoid misleading pedestrians who have visual disabilities when the following conditions exist:

- A. Where there is an island that allows unsignalized right turns across a crosswalk between the island and the sidewalk.
- B. Where multi-leg approaches or complex signal phasing require more than two pedestrian phases, such that it might be unclear which crosswalk is served by each audible tone.
- C. At intersections where a diagonal pedestrian crossing is allowed, or where one street receives a WALKING PERSON (symbolizing WALK) signal indication simultaneously with another street.

Option:

An alert tone, which is a very brief burst of high-frequency sound at the beginning of the audible walk indication that rapidly decays to the frequency of the walk tone, may be used to alert pedestrians to the beginning of the walk interval.

Support:

An alert tone can be particularly useful if the walk tone is not easily audible in some traffic conditions.

Speech walk messages communicate to pedestrians which street has the walk interval. Speech messages might be either directly audible or transmitted, requiring a personal receiver to hear the message. To be a useful system, the words and their meaning need to be correctly understood by all users in the context of the street environment where they are used. Because of this, tones are the preferred means of providing audible walk indications except where two accessible pedestrian signals on one corner are not separated by a distance of at least 10 feet.

If speech walk messages are used, pedestrians have to know the names of the streets that they are crossing in order for the speech walk messages to be unambiguous. In getting directions to travel to a new location, pedestrians with visual disabilities do not always get the name of each street to be crossed. Therefore, it is desirable to give users of accessible pedestrian signals the name of the street controlled by the push button. This can be done by means of a speech push button information message (see Section 4K.05) during the flashing or steady UPRAISED HAND intervals, or by raised print and Braille labels on the push button housing.

By combining the information from the push button message or Braille label, the vibrotactile arrow aligned in the direction of travel on the relevant crosswalk, and the speech walk message, pedestrians with visual disabilities are able to correctly respond to speech walk messages even if there are two push buttons on the same pole.

Standard:

1

2

3

4

5

6

7

8

9

10

11

12

13

14 15

16

17

18

19

20

21

22

23

24 25

26

27

28

29

30

31

32

33

34

35

36 37

38

39

40 41

42

43

44

45

46

If speech walk messages are used to communicate the walk interval, they shall provide a clear message that the walk interval is in effect, as well as to which crossing it applies. Speech walk messages shall be used only at intersections where it is technically infeasible to install two accessible pedestriansignals at one corner separated by a distance of at least 10 feet.

Guidance: The following three paragraphs changed from Standard to Guidance

Speech walk messages that are used at intersections having pedestrian phasing that is concurrent with vehicular phasing shall should be patterned after the model: "Broadway. Walk sign is on to cross Broadway."

Speech walk messages that are used at intersections having exclusive pedestrian phasing shall should be patterned after the model: "Walk sign is on for all crossings."

Speech walk messages shall should not contain any additional information, except they shall should include designations such as "Street" or "Avenue" where this information is necessary to avoid ambiguity at a particular location.

Guidance:

Speech walk messages should not state or imply a command to the pedestrian, such as "Cross Broadway now." Speech walk messages should not tell pedestrians that it is "safe to cross," because it is always the pedestrian's responsibility to check actual traffic conditions.

Standard:

A speech walk message is not required at times when the walk interval is not timing, but, if provided:

- A. It shall begin with the term "wait."
- B. It need not be repeated for the entire time that the walk interval is not timing.

If a pilot light (see Section 4I.06) is used at an accessible pedestrian signal location, each actuation shall be accompanied by the speech message "wait."

Option:

Accessible pedestrian signals that provide speech walk messages may provide similar messages in languages other than English, if needed., except for the terms "walk sign" and "wait."

If used, speech walk messages in a language other than English shall be stated first in English, and then repeated in the second language, alternating back and forth while the walk interval is timing.

Following the audible walk indication, accessible pedestrian signals shall revert to the pushbuttonlocator tone (see Section 4E.12) during the pedestrian change interval. Text was relocated into Paragraph 4 of new Section 4K.04

47 Section 4E.12 4K.04 Accessible Pedestrian Signals and Detectors—Vibrotactile Arrows and 48

Locator Tones

49 **Standard:** To enable pedestrians who have visual disabilities to distinguish and locate the appropriate push button at an accessible pedestrian signal location, and to help them align with the crosswalk, each push buttons shall clearly indicate by means of a vibrotactile arrows which crosswalk signal is actuated by each the push button. Vibrotactile arrows shall be located on the button of the push button assembly or immediately adjacent to the button on the same surface of the push button assembly housing, shall have high visual contrast (light on dark or dark on light), and shall be aligned parallel to the direction of travel on the associated crosswalk. If a push button is not provided for pedestrian detection or to activate the accessible pedestrian signal features, the vibrotactile arrow shall be located on the speaker box, and the speaker box shall be located in compliance with Section 4I.06.

An accessible pedestrian pushbutton shall incorporate A locator tone shall be incorporated into the accessible pedestrian signal equipment to help pedestrians with visual disabilities locate the tactile arrow, and the associated push button if a push button is provided.

Support:

1

2

3

4

5

6

7

8

9

10

11 12

13

14

15

16

17

18

19

20

21

31

32

33

34

35

3637

38

39

40

41

42 43

4445

46

47

48

49

50

A push button locator tone is a repeating sound that informs approaching pedestrians that a push button to actuate pedestrian timing or receive additional information exists, and that enables pedestrians with visual disabilities to locate the push button.

Standard:

Push button locator tones shall have a duration of 0.15 seconds or less, and except as provided in Paragraph 5, push button locator shall repeat at 1-second intervals at all times that the audible walk indication is not active, including during the pedestrian change interval and during the time that the pedestrian signal is resting in walk (see Paragraph 6 in Section 4K.03).

22 Option:

- 23 The push button locator tone may default to a deactivated mode during periods when the steady UPRAISED
- 24 HAND (symbolizing DONT WALK) signal indication is being displayed for the associated crosswalk if a
- 25 passive pedestrian detection system is implemented that activates the locator tone at all times (other than when
- 26 the audible walk indication is active) that a pedestrian is present within a 12-foot radius from the push button
- 27 <u>location. Where pedestrian facilities (such as sidewalks) are present, the passive detection requirement may</u>
- be reduced such that it only applies to pedestrians who are on the pedestrian facilities within the 12-foot radius
- 29 from the push button location. Added to reflect Official Interpretation 4(09)-26(I)

30 **Standard:**

Push button locator tones shall be deactivated when the traffic control signal <u>or pedestrian hybrid beacon</u> is operating in a flashing mode. This requirement shall not apply to traffic control signals or pedestrian hybrid beacons that are activated from a flashing or dark mode to a <u>steady</u> (stop-and-go) mode by pedestrian actuations.

Push button locator tones shall be intensity responsive to ambient sound, and be audible 6 to 12 feet from the pushbutton, or to the building line, whichever is less. Standard changed to Guidance below *Guidance*:

<u>Push button locator tones should be audible 6 to 12 feet from the push button, or to the building line, whichever is less.</u>

Support:

Section 4K.03 contains additional provisions regarding the volume and sound level of push button locator tones.

Section <u>4E.13 4K.05 Accessible Pedestrian Signals and Detectors - Extended Push Button</u>

<u>Press Features</u> Revised to reflect Official Change Request 4(09)-42

Option:

Pedestrians may be provided with additional features such as increased crossing time, audible beaconing, or a speech push button information message as a result of an extended push button press.

Standard:

If an extended push button press (see Paragraph 18 in Section 4I.06) is used to provide any additional feature(s), a push button press of less than one second shall actuate only the pedestrian

timing and any associated accessible walk indication, and a push button press of one second or more shall actuate the pedestrian timing, any associated accessible walk indication, and any additional feature(s).

If additional crossing time is provided by means of an extended pushbutton press, a PUSH BUTTON FOR 2 SECONDS FOR EXTRA CROSSING TIME (R10 32P) plaque (see Section 2B.62) shall be mounted adjacent to or integral with the pedestrian pushbutton.

Support:

Audible beaconing is the use of an audible signal in such a way that pedestrians with visual disabilities can home in on the signal that is located on the far end of the crosswalk as they cross the street.

Not all crosswalks at an intersection need audible beaconing; audible beaconing can actually cause confusion if used at all crosswalks at some intersections. Audible beaconing is not appropriate at locations with channelized turns or split phasing, because of the possibility of confusion.

Guidance:

Audible beaconing should only be considered following an engineering study at:

- A. Crosswalks longer than 70 feet, unless they those crosswalks are divided by a median that has another accessible pedestrian signal with a locator tone;
- B. Crosswalks that are skewed;
- C. Intersections with irregular geometry, such as more than four legs;
- D. Crosswalks where audible beaconing is requested by an individual with visual disabilities; or
- E. Other locations where a study indicates audible beaconing would be beneficial.

Option Guidance:

<u>If</u> audible beaconing <u>is used, it may should</u> be provided in several ways, any of which are initiated by an extended push button press.

Standard:

If audible beaconing is used, the volume of the push button locator tone during the pedestrian change interval of the called pedestrian phase shall be increased to a maximum of 100 dBA, and operated in one of the following ways: shall come from a loudspeaker that is mounted at the far end of the crosswalk at a height of 7 to 10 feet above the pavement.

- A. The louder audible walk indication and louder locator tone comes from the far end of the crosswalk, as pedestrians cross the street,
- B. The louder locator tone comes from both ends of the crosswalk, or
- C. The louder locator tone comes from an additional speaker that is aimed at the center of the crosswalk and that is mounted on a pedestrian signal head.

Guidance:

The audible beaconing loudspeaker mounted at the far end of the crosswalk should be within the width of the crosswalk.

Support:

When the locator tone is active during the pedestrian change interval at a traffic control signal or pedestrian hybrid beacon where audible beaconing is used, both the audible beaconing loudspeaker and the accessible pedestrian signal emit the tone.

Option:

The sound level of the accessible pedestrian signal walk indication and subsequent push button locator tone may be increased by an extended push button press.

Speech push button information messages may provide intersection identification, as well as information about unusual intersection signalization and geometry, such as notification regarding exclusive pedestrian phasing, leading pedestrian intervals, split phasing, diagonal crosswalks, and medians or islands.

Standard:

If speech push button information messages are made available by actuating the accessible pedestrian signal detector, they shall only be actuated when the walk interval is not timing. They shall begin with the term "Wait," followed by intersection identification information modeled after: "Wait to

cross Broadway at Grand." If information on intersection signalization or geometry is also given, it shall follow the intersection identification information.

Guidance:

1

2

4

5

6

7

8

9

Speech push button information messages should not be used to provide landmark information or to inform pedestrians with visual disabilities about detours or temporary traffic control situations.

Support:

Additional information on the structure and wording of speech push button information messages is included in ITE's "Electronic Toolbox for Making Intersections More Accessible for Pedestrians Who Are Blind or Visually Impaired," which is available at ITE's website (see Page i).

CHAPTER 4L. RECTANGULAR RAPID FLASHING BEACONS

2 Chapter added to reflect Interim Approval 21, Official Interpretations 4-376(I), 4(09)-5(I), 4(09)-17(I), 4(09)-21(I), 4(09)-22(I), 4(09)-24(I), 4(09)-37(I), 4(09)-38(I), 4(09)-41(I), and 4(09)-58(I)

4 Section 4L.01 Application of Rectangular Rapid Flashing Beacons

Option:

A pedestrian-activated rectangular rapid flashing beacon (RRFB) may be used to provide supplemental emphasis to pedestrian, school, and trail warning signs at marked crosswalks across uncontrolled approaches.

Standard:

An RRFB shall only be installed to function as a Warning Beacon (see Section 4S.03). Except as otherwise provided in this Chapter, all other provisions of the MUTCD applicable to Warning Beacons shall apply to RRFBs.

An RRFB shall only be used to supplement a post-mounted W11-2 (Pedestrian), S1-1 (School), or W11-15 (Trail) crossing warning sign with a diagonal downward arrow (W16-7P) plaque, or an overhead-mounted W11-2, S1-1, or W11-15 crossing warning sign, located at or immediately adjacent to a marked crosswalk.

Except for crosswalks across the approach to or egress from a roundabout, or crosswalks across free-flow right turn lanes separated by a channelizing island, an RRFB shall not be used for crosswalks across approaches controlled by YIELD signs, STOP signs, traffic control signals, or pedestrian hybrid beacons.

20 Option:

In the event sight distance approaching the crosswalk at which an RRFB is used is less than deemed necessary by the engineer, an additional RRFB may be installed on that approach in advance of the crosswalk, as a Warning Beacon to supplement a W11-2 (Pedestrian), S1-1 (School), or W11-15 (Trail) crossing warning sign with an AHEAD (W16-9P) or distance (W16-2P or W16-2aP) plaque.

Standard:

If an additional RRFB is installed on the approach in advance of the crosswalk, it shall be supplemental to and not a replacement for the RRFB at the crosswalk itself.

Section 4L.02 Design of Rectangular Rapid Flashing Beacons

Standard:

Each RRFB unit shall consist of two rapidly-flashed rectangular-shaped yellow indications, each with an LED-array based pulsing light source. The size of each RRFB indication shall be at least 5 inches wide by at least 2 inches high.

The two RRFB indications for each RRFB unit shall be aligned horizontally, with the longer dimension horizontal and with a minimum space between the two indications of at least 7 inches, measured from nearest edge of one indication to the nearest edge of the other indication. The outside edges of the RRFB indications, including any housings, shall not project beyond the outside edges of the W11-2, S1-1, or W11-15 sign that it supplements.

An RRFB unit shall not be installed independent of the crossing warning signs for the approach that the RRFB faces. If the RRFB unit is supplementing a post-mounted sign, the RRFB unit shall be installed on the same support as the associated W11-2, S1-1, or W11-15 crossing warning sign and plaque. If the RRFB unit is supplementing an overhead-mounted sign, the RRFB unit shall be mounted directly below the bottom of the sign.

Option:

As a specific exception to Paragraph 6 of Section 4S.01, the RRFB unit associated with a post-mounted sign and plaque may be located between and immediately adjacent to the bottom of the crossing warning sign and the top of the supplemental downward diagonal arrow plaque (or, in the case of a supplemental advance sign, the AHEAD or distance plaque) or within 12 inches above the crossing warning sign, rather than the recommended minimum of 12 inches above or below the sign assembly.

Standard:

1 For any approach on which RRFBs are used to supplement post-mounted signs, at least two W11-2, 2 S1-1, or W11-15 crossing warning signs (each with an RRFB unit and a W16-7P plaque) shall be 3 installed at the crosswalk, one on the right-hand side of the roadway and one on the left-hand side of the 4 roadway. 5 Guidance: 6 On a divided highway, the left-hand side RRFB assembly should be installed on the median, if practical, 7 rather than on the far left side of the highway. 8 **Standard:** 9 For any approach on which RRFBs are used to supplement an overhead-mounted sign, at least one 10 W11-2, S1-1, or W11-15 crossing warning sign (without a W16-7P plaque) located approximately over the center of the lanes of the approach (or where optimum visibility can be achieved) shall be installed 11 12 at the crosswalk. 13 Option: 14 RRFBs may be installed at intersections with more than one crosswalks on the same uncontrolled 15 approach. 16 **Standard:** 17 If used at intersections, the design of the RRFBs shall conform to the requirements for post-18 mounted or overhead placement described in paragraph X. 19 Option: If used at intersections with two crosswalks on an uncontrolled approach, post-mounted RRFBs may be 20 21 installed to face only one direction of travel at the first crosswalk that traffic encounters (see Figure 4L-1). 22 Figure 4L-1. Example of Post-Mounted RRFBs Installed to Face Only One Direction of Travel 23 at Intersections with Two Crosswalks on an Uncontrolled Approach 24 The light intensity of the yellow indications during daytime conditions shall meet the minimum 25

specifications for Class 1 yellow peak luminous intensity in the Society of Automotive Engineers (SAE) Standard J595 (Directional Flashing Optical Warning Devices for Authorized Emergency,

27 Maintenance, and Service Vehicles) dated January 2005 or the minimum specifications in subsequent 28 versions of SAE J595.

29 Option:

26

30

31

32

33

34

35

36

38

39 40

41 42

44

45

46

47

48

49

If the RRFB indications are so bright that they cause excessive glare during nighttime conditions, an automatic signal dimming device may be used to reduce the brilliance of the RRFB indications during nighttime conditions.

Standard:

If pedestrian push button detectors (rather than passive detection) are used to actuate the RRFB indications, a PUSH BUTTON TO TURN ON WARNING LIGHTS (R10-25) sign (see Section 2B.62) shall be installed explaining the purpose and use of the pedestrian push button detector.

37 Guidance:

An audible information device should be used with RRFBs to assist pedestrians with visual disabilities.

A small light directed at and visible to pedestrians in the crosswalk may be installed integral to the RRFB or pedestrian push button detector to give confirmation that the RRFB is in operation.

Section 4L.03 Operation of Rectangular Rapid Flashing Beacons

43 **Standard:**

> The RRFB shall be normally dark, shall initiate operation only upon pedestrian actuation, and shall cease operation at a predetermined time after the pedestrian actuation or, with passive detection, after the pedestrian clears the crosswalk.

> All RRFB units associated with a given crosswalk (including those with an advance crossing sign, if used) shall, when activated, simultaneously commence operation of their rapid flashing indications and shall cease operation simultaneously.

Guidance:

The duration of a predetermined period of operation of the RRFBs following each actuation should be based on the procedures for the timing of pedestrian clearance times for pedestrian signals (see Section 41.07).

Standard:

The predetermined flash period shall be immediately initiated each and every time that a pedestrian is detected either through passive detection or as a result of a pedestrian pressing a push button detector, including when pedestrians are detected while the RRFBs are already flashing and when pedestrians are detected immediately after the RRFBs have ceased flashing.

When activated, the two yellow indications in each RRFB unit shall flash in a rapidly flashing sequence. As a specific exception to the requirements for the flash rate of beacons provided in Paragraph 3 of Section 4S.01, RRFBs shall use a much faster flash rate and shall provide 75 flashing sequences per minute.

Except as provided in Paragraph 7, during each 800-millisecond flashing sequence, the left and right RRFB indications shall operate using the following sequence:

- A. The RRFB indication on the left-hand side shall be illuminated for approximately 50 milliseconds.
- B. Both RRFB indications shall be dark for approximately 50 milliseconds.
- C. The RRFB indication on the right-hand side shall be illuminated for approximately 50 milliseconds.
- D. Both RRFB indications shall be dark for approximately 50 milliseconds.
- E. The RRFB indication on the left-hand side shall be illuminated for approximately 50 milliseconds.
- F. Both RRFB indications shall be dark for approximately 50 milliseconds.
- G. The RRFB indication on the right-hand side shall be illuminated for approximately 50 milliseconds.
- H. Both RRFB indications shall be dark for approximately 50 milliseconds.
- I. Both RRFB indications shall be illuminated for approximately 50 milliseconds.
- J. Both RRFB indications shall be dark for approximately 50 milliseconds.
- K. Both RRFB indications shall be illuminated for approximately 50 milliseconds.
- L. Both RRFB indications shall be dark for approximately 250 milliseconds.

The flash rate of each individual RRFB indication, as applied over the full flashing sequence, shall not be more than 5 flashes per second, to avoid frequencies that might cause seizures.

Option:

Existing RRFB units that use the flashing sequence that was specified in the Interim Approval 11 memorandum and a subsequent interpretation (the RRFB indication on the left-hand side emits two slow pulses of light after which the RRFB indication on the right-hand side emits four rapid pulses of light followed by one long pulse of light) may be retained for the remainder of their useful service life.

Standard: Added to reflect Official Change Request 4(09)-42

If an audible information device is used in conjunction with an RRFB, the audible information device shall not use vibrotactile indications or percussive indications.

Guidance: Added to reflect Official Change Request 4(09)-42

If an audible information device is used in conjunction with an RRFB, the audible message should be a speech message that says, "Yellow lights are flashing". The audible message should be spoken twice.

CHAPTER 4G-4M. TRAFFIC CONTROL SIGNALS AND HYBRID BEACONS FOR EMERGENCY-VEHICLE ACCESS

Section 4G.01 4M.01 Application of Emergency-Vehicle Traffic Control Signals and Hybrid Beacons

Support:

An emergency-vehicle traffic control signal is a special traffic control signal that assigns the right of way to directs all conflicting traffic to stop in order to permit the driver of an authorized emergency vehicle to proceed into the roadway or intersection.

Option:

An emergency-vehicle traffic control signal may be installed at a location that does not meet other traffic signal warrants such as at an intersection or other location to permit direct access from a building housing the emergency vehicle.

An emergency-vehicle hybrid beacon may be installed instead of an emergency-vehicle traffic control signal under conditions described in Section 4N.01.

Guidance:

If a traffic control signal is not justified under the signal warrants of Chapter 4C and if gaps in traffic are not adequate to permit the timely entrance of emergency vehicles, or the stopping sight distance for vehicles approaching on the major street is insufficient for emergency vehicles, installing an emergency-vehicle traffic control signal should be considered. If one of the signal warrants of Chapter 4C is met and a traffic control signal is justified by an engineering study, and if a decision is made to install a traffic control signal, it should be installed based upon the provisions of Chapters 4D through 4I.

The sight distance determination should be based on the location of the visibility obstruction the critical approach lane for each street or drive and the posted or statutory speed limit or 85th-petitile speed on the major street, whichever is higher.

Section 4G.02 4M.02 Design of Emergency-Vehicle Traffic Control Signals

Standard:

Except as otherwise provided in this Section, an emergency-vehicle traffic control signal shall meet the requirements of this Manual.

An Emergency Vehicle (W11-8) sign (see Section 2C.54) with an EMERGENCY SIGNAL AHEAD (W11-12P) supplemental plaque shall be placed in advance of all emergency-vehicle traffic control signals. If a warning beacon is installed to supplement the W11-8 sign, the design and location of the beacon shall comply with the Standards of Sections 4S.01 and 4S.03.

Guidance:

At least one of the two required signal faces for each approach on the major street should be located over the roadway.

The following size signal indications should be used for emergency-vehicle traffic control signals: 12-inch diameter for steady red and steady yellow circular signal indications and any arrow indications, and 8-inch diameter for green or flashing yellow circular signal indications.

Standard:

An EMERGENCY SIGNAL (R10-13) sign (see Section 2B.63) shall be mounted installed adjacent to a signal face on facing each major street approach.

If an overhead signal face is provided, the EMERGENCY SIGNAL sign shall be mounted adjacent to the overhead signal face.

Option:

An approach that only serves emergency vehicles may be provided with only one signal face consisting of one or more signal sections.

Besides using an 8-inch diameter signal indication, other appropriate means to reduce the flashing yellow light output may be used.

Section 4G.03 4M.03 Operation of Emergency-Vehicle Traffic Control Signals

Standard:

Right of way Green signal indications for emergency vehicles at signalized locations operating in the steady (stop-and-go) mode shall be obtained as provided in Section 4F.19.

As a minimum, the signal indications, sequence, and manner of operation of an emergency-vehicle traffic control signal installed at a midblock location shall be as follows:

- A. The signal indication, between emergency-vehicle actuations, shall be either green or flashing yellow. If the flashing yellow signal indication is used instead of the green signal indication, it shall be displayed in the normal position of the green signal indication, while the steady red and steady yellow signal indications shall be displayed in their normal positions.
- B. When an emergency-vehicle actuation occurs, a steady yellow change interval followed by a steady red interval shall be displayed to traffic on the major street.
- C. A yellow change interval is not required following the green interval for the emergency-vehicle driveway.

Guidance:

Emergency-vehicle traffic control signals located at intersections shall-should either be operated in the flashing mode (see Sections 4G.01 and 4G.03) between emergency-vehicle actuations or be full-actuated or semi-actuated to accommodate normal vehicular and pedestrian traffic on the streets. Standard changed to Guidance

Warning beacons, if used with an emergency-vehicle traffic control signal, shall-should be flashed only:

- A. For an appropriate time in advance of and during the steady yellow change interval for the major street; and
- B. During the steady red interval for the major street. Standard changed to Guidance

Guidance:

The duration of the steady red interval for traffic on the major street should be determined by on-site test-run time studies, but should not exceed 1.5 times the time required for the emergency vehicle to clear the path of conflicting vehicles.

Option:

An emergency-vehicle traffic control signal sequence may be initiated manually from a local control point such as a fire station or law enforcement headquarters or from an emergency vehicle equipped for remote operation of the signal.

CHAPTER 4N. HYBRID BEACONS FOR EMERGENCY-VEHICLE ACCESS

Section 4G.04 4N.01 Application of Emergency-Vehicle Hybrid Beacons
Section were relocated to new Sections 4N.02 and 4N.03

Standard:

Emergency-vehicle hybrid beacons shall be used only in conjunction with signs to warn and control traffic at an unsignalized location where emergency vehicles enter or cross a street or highway. Emergency-vehicle hybrid beacons shall be actuated only by authorized emergency or maintenance

8 personnel.

Guidance:

Emergency-vehicle hybrid beacons should only be used when all of the following criteria are satisfied:

- A. The conditions justifying an emergency-vehicle traffic control signal (see Section 4M.01) are met; and
- B. An engineering study, considering the road width, approach speeds, and other pertinent factors, determines that emergency-vehicle hybrid beacons can be designed and located in compliance with the requirements contained in this Section and in Section 4S.01, such that they effectively warn and control traffic at the location; and
- C. The location is not at or within 100 feet from an intersection or driveway where the side road or driveway is controlled by a STOP or YIELD sign.

Section 4N.02 Design of Emergency-Vehicle Hybrid Beacons Paragraphs were relocated from existing Section 4G.04

20 Standard:

Except as otherwise provided in this Section, an emergency-vehicle hybrid beacon shall meet the requirements of this Manual.

An emergency-vehicle hybrid beacon face shall consist of three signal sections, with a CIRCULAR YELLOW signal indication centered below two horizontally aligned CIRCULAR RED signal indications (see Figure 4N-14C-1).

Figure 4N-1. Sequence for an Emergency-Vehicle Hybrid Beacon

At least two emergency-vehicle hybrid beacon faces shall be installed for each approach of the major street and a stop line shall be installed for each approach of the major street.

Guidance:

On approaches having posted or statutory speed limits or 85 recentile speeds in excess of 40 mph, and on approaches having traffic or operating conditions that would tend to obscure visibility of roadside beacon faces, both of the minimum of two emergency-vehicle hybrid beacon faces should be installed over the roadway.

On multi-lane approaches having posted or statutory speed limits or 85th-percentile speeds of 40 mph or less, either an emergency-vehicle hybrid beacon face should be installed on each side of the approach (if a median of sufficient width exists) or at least one of the emergency-vehicle hybrid beacon faces should be installed over the roadway.

An emergency-vehicle hybrid beacon should comply with the signal face location provisions described in Sections <u>4D.11 through 4D.16</u> 4D.04 through 4D.09.

Standard:

Stop lines and EMERGENCY SIGNAL—STOP ON FLASHING RED (R10-14 or R10-14a) signs (see Section 2B.53-2B.63) shall be used with emergency-vehicle hybrid beacons for each approach of the major street.

Option:

If needed for extra emphasis, a STOP HERE ON FLASHING RED (R10-14b) sign (see Section_2B.53-2B.63) may be installed with an emergency-vehicle hybrid beacon.

Emergency-vehicle hybrid beacons may be equipped with a light or other display visible to the operator of the egressing emergency vehicle to provide confirmation that the beacons are operating.

Emergency-vehicle hybrid beacons may be supplemented with an advance warning sign, which may also be supplemented with a Warning Beacon (see Section 4L.03-4S.03).

Guidance:

If a Warning Beacon is used to supplement the advance warning sign, it should be programmed to flash only when the emergency-vehicle hybrid beacon is not in the dark mode.

Section 4N.03 Operation of Emergency-Vehicle Hybrid Beacons Paragraphs relocated from existing Section 4G.04

Standard:

Emergency-vehicle hybrid beacons shall be placed in a dark mode (no indications displayed) during periods between actuations.

Upon actuation by authorized emergency personnel, the emergency-vehicle hybrid beacon faces shall each display a flashing yellow signal indication, followed by a steady yellow change interval, prior to displaying two CIRCULAR RED signal indications in an alternating flashing array for a duration of time adequate for egress of the emergency vehicles. The alternating flashing red signal indications shall only be displayed when it is required that drivers on the major street stop and then proceed subject to the rules applicable after making a stop at a STOP sign. Upon termination of the flashing red signal indications, the emergency-vehicle hybrid beacons shall revert to a dark mode (no indications displayed) condition.

19 Guidance:

The duration of the flashing yellow interval should be determined by engineering judgment.

Standard:

The duration of the steady yellow change interval shall be determined using engineering practices <u>in</u> accordance with the provisions in Section 4F.17.

Guidance:

<u>The A</u> yellow change interval should have a minimum duration of 3 seconds and a maximum duration of 6 seconds (see Section_4D.26 4F.17). The longer intervals should be reserved for use on approaches with higher speeds.

Option:

A steady red clearance interval may be used after the steady yellow change interval.

An emergency-vehicle hybrid beacon that is located in close proximity to an active grade crossing may be preempted in accordance with the applicable provisions in Sections 4F.19 and 8D.09.

Standard:

If an emergency-vehicle hybrid beacon is placed into a flashing mode by a conflict monitor (malfunction management unit) or by a manual switch, the emergency-vehicle hybrid beacon faces shall display flashing yellow signal indications to each approach of the major street.

CHAPTER 4H-4O. TRAFFIC CONTROL SIGNALS FOR ONE-LANE, TWO-WAY FACILITIES

Section 4H.01 4O.01 Application of Traffic Control Signals for One-Lane, Two-Way Facilities

Support:

A traffic control signal at a narrow bridge, tunnel, or roadway section is a special signal that assigns the right-of-way for alternates which direction of vehicles passing over a bridge or through a tunnel or roadway section that is not of sufficient width for two opposing vehicles to pass is directed to stop and which direction is permitted to proceed.

Temporary traffic control signals (see Sections 4D.32 and 6F.84-4D.10 and 6L.01) are the most frequent application of one-lane, two-way facilities.

Guidance:

Sight distance across or through the one-lane, two-way facility should be considered as well as the approach speed and sight distance approaching the facility when determining whether traffic control signals should be installed.

Option:

At a narrow bridge, tunnel, or roadway section where a traffic control signal is not justified under the conditions of Chapter 4C, a traffic control signal may be used if gaps in opposing traffic do not permit the flow of traffic through the one-lane section of roadway.

Section 4H.02 4O.02 Design of Traffic Control Signals for One-Lane, Two-Way Facilities Standard:

The provisions of Chapters 4D <u>through 4G</u> shall apply to traffic control signals for one-lane, two-way facilities, except that:

- A. Durations of red clearance intervals shall be adequate to clear the one-lane section of conflicting vehicles.
- B. Adequate means, such as interconnection, shall be provided to prevent conflicting signal indications, such as green and green, at opposite ends of the section.
- Section 4H.03 40.03 Operation of Traffic Control Signals for One-Lane, Two-Way Facilities Standard:
- Traffic control signals at one-lane, two-way facilities shall operate in a manner consistent with traffic requirements.

When in the flashing mode, the signal indications shall flash red.

32 Guidance:

Adequate time should be provided to allow traffic to clear the narrow facility before opposing traffic is allowed to move. Engineering judgment should be used to determine the proper timing for the signal.

CHAPTER 41-4P. TRAFFIC CONTROL SIGNALS FOR FREEWAY ENTRANCE RAMPS

2 Section 41.01 4P.01 Application of Freeway Entrance Ramp Control Signals

Support:

Ramp control signals are traffic control signals that control the flow of traffic entering the freeway facility. This is often referred to as "ramp metering."

Freeway entrance ramp control signals are sometimes used if controlling traffic entering the freeway could reduce the total expected delay to traffic in the freeway corridor, including freeway ramps and local streets.

Guidance:

The installation of ramp control signals should be preceded by an engineering study of the physical and traffic conditions on the highway facilities likely to be affected. The study should include the ramps and ramp connections and the surface streets that would be affected by the ramp control, as well as the freeway section concerned.

Support:

Information on conditions that might justify freeway entrance ramp control signals, factors to be evaluated in traffic engineering studies for ramp control signals, design of ramp control signals, and operation of ramp control signals can be found in the FHWA's "Ramp Management and Control Handbook" (see Section 1A.11-1A.05).

Section 41.02 4P.02 Design of Freeway Entrance Ramp Control Signals The sequence of paragraphs in this section was revised

Standard:

Ramp control signals shall meet all of the standard design specifications for traffic control signals, except as otherwise provided in this Section.

The signal face for freeway entrance ramp control signals shall be either a two-section signal face containing red and green signal indications or a three-section signal face containing red, yellow, and green signal indications.

Option:

Ramp control signals may be placed in the dark mode (no indications displayed) when not in use.

Ramp control signals may be used to control some, but not all, lanes on a ramp, such as when non-metered HOV bypass lanes are provided on a ramp.

Standard:

If only one <u>controlled</u> lane is present on an entrance ramp, or if more than one <u>controlled</u> lane is present on an entrance ramp and the ramp control signals are operated such that green signal indications are always displayed simultaneously to all of the <u>controlled</u> lanes on the ramp, then a minimum of two signal faces per ramp shall face entering traffic.

If more than one lane is two controlled lanes are present on an entrance ramp and the ramp control signals are operated such that green signal indications are not always displayed simultaneously to all both of the controlled lanes on the ramp, a minimum of two signal faces shall be provided for each of the two lanes then one signal face shall be provided over the approximate center of each separately controlled lane. Added to reflect Official Interpretation 4(09)-29(I)

If three or more controlled lanes are present on an entrance ramp and the ramp control signals are operated such that green signal indications are not always displayed simultaneously to all of the controlled lanes on the ramp, then one signal face shall be provided over the approximate center of each separately-controlled lane. Added to reflect Official Interpretation 4(09)-29(I)

45 Guidance:

Additional side-mounted signal faces should be considered for ramps with two_three or more separately-controlled lanes. Revised to reflect Official Interpretation 4(09)-29(I)

48 Option:

The required signal faces, if located at the side of the ramp roadway, may be mounted such that the height above the pavement grade at the center of the ramp roadway to the bottom of the signal housing of the lowest signal face is between 4.5 and 6 feet. Text incorporated into the next paragraph

For entrance ramps with only one controlled lane, the two required signal faces may both be mounted at the side of the roadway on a single pole (as a specific exception to the normal 8-foot minimum lateral separation of signal faces required by Section 4D.06), with one face at the normal mounting height and one the lower signal face mounted lower as provided in Paragraph 9 installed at a minimum mounting height of 4.5 feet, as a specific exception to the normal 8-foot minimum lateral separation of signal faces required by Section 4D.13.

For entrance ramps with two or more controlled lanes, if two signal faces are installed for the right-hand lane or for the left-hand lane, the two signal faces for that lane may both be mounted at the closest side of the roadway on a single pole (as a specific exception to the normal 8-foot minimum lateral separation of signal faces required by Section 4D.06), with the lower signal face installed at a minimum mounting height of 4.5 feet.

Guidance:

Ramp control signals <u>shall should</u> be located and designed to minimize their viewing by mainline freeway traffic. Standard changed to Guidance

Regulatory signs with legends appropriate to the control, such as XX VEHICLE(S) PER GREEN or XX VEHICLE(S) PER GREEN EACH LANE (see Section_2B.56-2B.66), should be installed adjacent to the ramp-control signal faces.

When ramp control signals are installed on a freeway-to-freeway ramp, special consideration should be given to assuring adequate visibility of the ramp control signals, and multiple advance warning signs with flashing warning beacons should be installed to warn road users of the metered operation.

Section 41.03 4P.03 Operation of Freeway Entrance Ramp Control Signals

Guidance:

Operational strategies for ramp control signals, such as periods of operation, metering rates and algorithms, and queue management, should be determined by the operating agency prior to the installation of the ramp control signals and should be closely monitored and adjusted as needed thereafter.

When the ramp control signals are operated only during certain periods of the day, a RAMP METERED WHEN FLASHING (W3-8) sign (see Section 2C.37-2C.39) should be installed in advance of the ramp control signal near the entrance to the ramp, or on the arterial on the approach to the ramp, to alert road users to the presence and operation of ramp meters.

Standard:

The RAMP METERED WHEN FLASHING sign shall be supplemented with a warning beacon (see Section 4L.03 4S.03) that flashes when the ramp control signal is in operation. Flashing light emitting diode (LED) units shall not be used within the legend or border of the sign to inform road users that the ramp control signal is in operation.

1 2

3 4

5

6 7

8

9

10

1112

13

14

15

1617

18

19

20

21

22

23

24

25

26

27 28

31

32 33

34

36

37

38

39

40 41

42

43

44

45

46

Section 4J.01 4Q.01 Application of Traffic Control for Movable Bridges

Support:

Traffic control signals for movable bridges are a special type of highway traffic signal installed at movable bridges to notify road users to stop because of a road closure rather than alternately giving the right-of way to controlling the flow of conflicting traffic movements. The signals are operated in coordination with the opening and closing of the movable bridge, and with the operation of movable bridge warning and resistance gates, or other devices and features used to warn, control, and stop traffic.

Movable bridge warning gates installed at movable bridges decrease the likelihood of vehicles and pedestrians passing the stop line and entering an area where potential hazards exist because of bridge operations.

A movable bridge resistance gate is sometimes used at movable bridges and located downstream of the movable bridge warning gate. A movable bridge resistance gate provides a physical deterrent to road users when placed in the appropriate position. The movable bridge resistance gates are considered a design feature and not a traffic control device; requirements for them are contained in AASHTO's "Standard Specifications for Movable Highway Bridges" (see Page i for AASHTO's address).

Standard:

Traffic control at movable bridges shall include both signals and gates, except in the following cases:

- A. Neither is required if other traffic control devices or measures considered appropriate are used under either of the following conditions:
 - 1. On low-volume roads (roads of less than 400 vehicles average daily traffic), or
 - 2. At manually operated bridges if electric power is not available.
- B. Only signals are required in urban areas if intersecting streets or driveways make gates ineffective.
- C. Only movable bridge warning gates are required if a traffic control signal that is controlled as part of the bridge operations exists within 500 feet of the movable bridge resistance gates and no intervening traffic entrances exist.
- 29 Section 4J.02 4Q.02 Design and Location of Movable Bridge Signals and Gates
- 30 Standard:
 - The signal faces and mountings of movable bridge signals shall comply with the provisions of Chapters 4D through 4G except as provided in this Section.
 - Signal faces with 12-inch diameter signal indications shall be used for all new movable bridge signals.
- 35 Option:
 - Existing signal faces with 8-inch diameter lenses may be retained for the remainder of their useful service life.
 - Standard:

Since movable bridge operations cover a variable range of time periods between openings, the signal faces shall be one of the following types:

- A. Three-section signal faces with red, yellow, and green signal indications; or
- B. Two one-section signal faces with red signal indications in a vertical array separated by a STOP HERE ON RED (R10-6) sign (see Section 2B.53 2B.63).

Regardless of which signal type is selected, at least two signal faces shall be provided for each approach to the movable span and a stop line (see Section 3B.16-3B.19) shall be installed to indicate the point behind which vehicles are required to stop.

- 47 Guidance:
- 48 If movable bridge operation is frequent, the use of three-section signal faces should be considered.

Insofar as practical, the height and lateral placement of signal faces should comply with the requirements for other traffic control signals in accordance with Chapter 4D. They should be located no more than 50 feet in advance of the movable bridge warning gate.

Option:

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

31

32

3334

35

36

37

38

39 40

41 42

43

44

45

47

48

Movable bridge signals may be supplemented with audible warning devices to provide additional warning to drivers and pedestrians.

Standard Guidance: Standard changed to Guidance

A DRAW BRIDGE (W3-6) sign (see Section 2C.39-2C.29) shall should be used in advance of movable bridge signals and gates to give warning to road users, except in urban conditions where such signing would not be practical.

Standard:

If physical conditions prevent a road user from having a continuous view of at least two signal indications for the distance specified in Table 4D-2, an auxiliary device (either a supplemental signal face or the mandatory DRAW BRIDGE (W3-6) sign to which has been added a warning beacon that is interconnected with the movable bridge controller unit) shall be provided in advance of movable bridge signals and gates.

Option:

The DRAW BRIDGE (W3-6) sign may be supplemented by a Warning Beacon (see Section_4L.03-4S.03).

Standard-Support: Standard changed to Support

If two sets of gates (both a warning and a resistance gate) are used for a single direction, highway traffic signals shall are not be required to accompany the resistance gate nearest the span opening.

Standard:

Movable bridge warning gates, if used, shall be at least standard railroad size, striped with 16-inch alternate vertical, fully reflectorized red and white stripes. Flashing red lights in accordance with the Standards for those on railroad gates (see Section 8C.04-8D.03) shall be included on the gate arm and they shall only be operated if the gate is closed or in the process of being opened or closed.

Guidance: Standard changed to Guidance

In the horizontal position, the top of the gate shall should be approximately 4 feet above the pavement.

30 Guidance:

Movable bridge warning gates should be of lightweight construction. In its normal upright position, the gate arm should provide adequate lateral clearance.

Option:

The movable bridge resistance gates may be delineated, if practical, in a manner similar to the movable bridge warning gate.

Standard-Guidance: Standard changed to Guidance

Movable bridge warning gates, if used, shall-should extend at least across the full width of the approach lanes if movable bridge resistance gates are used. On divided highways in which the roadways are separated by a barrier median, movable bridge warning gates, if used, shall-should extend across all roadway lanes approaching the span openings.

Guidance:

If movable bridge resistance gates are not used on undivided highways, movable bridge warning gates, if used, should extend across the full width of the roadway.

Option:

A single full-width gate or two half-width gates may be used.

46 Support:

The locations of movable bridge signals and gates are determined by the location of the movable bridge resistance gate (if used) rather than by the location of the movable spans. The movable bridge resistance gates

for high-speed highways are preferably located 50 feet or more from the span opening except for bascule and lift bridges, where they are often attached to, or are a part of, the structure.

Standard Guidance: Standard changed to Guidance

Except where physical conditions make it impractical, movable bridge warning gates shall should be located 100 feet or more from the movable bridge resistance gates or, if movable bridge resistance gates are not used, 100 feet or more from the movable span.

Guidance:

On bridges or causeways that cross a long reach of water and that might be hit by large marine vessels, within the limits of practicality, traffic should not be halted on a section of the bridge or causeway that is subject to impact.

In cases where it is not practical to halt traffic on a span that is not subject to impact, traffic should be halted at least one span from the opening. If traffic is halted by signals and gates more than 330 feet from the movable bridge warning gates (or from the span opening if movable bridge warning gates are not used), a second set of gates should be installed approximately 100 feet from the gate or span opening.

If the movable bridge is close to a grade crossing and traffic might possibly be stopped on the crossing as a result of the bridge opening, a traffic control device should notify the road users to not stop on the railroad tracks.

Section 4J.03 4Q.03 Operation of Movable Bridge Signals and Gates

Standard:

Traffic control devices at movable bridges shall be coordinated with the movable spans, so that the signals, gates, and movable spans are controlled by the bridge tender through an interlocked control.

If the three-section type of signal face is used, the green signal indication shall be displayed at all times between bridge openings, except that if the bridge is not expected to open during continuous periods in excess of 5 hours, a flashing yellow signal indication shall be permitted to be used. The signal shall display a steady red signal indication when traffic is required to stop. The duration of the yellow change interval between the display of the green and steady red signal indications, or flashing yellow and steady red signal indications, shall be determined using engineering practices (see Section 4D.26-4F.17).

If the vertical array of red signal indications is the type of signal face selected, the red signal indications shall flash alternately only when traffic is required to stop.

Guidance:

The yellow change interval should have a minimum duration of 3 seconds and a maximum duration of 6 seconds. The longer intervals should be reserved for use on approaches with higher speeds.

Traffic control signals on adjacent streets and highways should be interconnected with the drawbridge control if indicated by engineering judgment. When such interconnection is provided, the traffic control signals at adjacent intersections should be preempted by the operation of the movable bridge in the manner described in Section 4D.27-4F.19.

CHAPTER 4K-4R. HIGHWAY TRAFFIC SIGNALS AT TOLL PLAZAS

2 Section 4K.01 4R.01 Traffic Signals at Toll Plazas

Standard:

1

3 4

5

6

7

8

9

10

11

12

14

15

16

17

18

19

20

21

2223

24

25

27

28

29

30

31

32

33

34

35

36

Traffic control signals or devices that closely resemble traffic control signals that use red or green circular indications shall not be used at toll plazas to indicate the open or closed status of the toll plaza lanes.

Guidance:

Traffic control signals or devices that closely resemble traffic control signals that use red or green circular indications should not be used for new or reconstructed installations at toll plazas to indicate the success or failure of electronic toll payments or to alternately direct drivers making cash toll payments to stop and then proceed.

Section 4K.02 4R.02 Lane-Use Control Signals at or Near Toll Plazas

13 Standard:

Lane-use control signals used at toll plazas shall comply with the provisions of Chapter 4M-4T except as otherwise provided in this Section.

At toll plazas with multiple lanes where one or more lanes is sometimes closed to traffic, a lane-use control signal shall be installed above the center of each toll plaza lane to indicate the open or closed status of the controlled lane.

Option:

The bottom of the signal housing of a lane-use control signal above a toll plaza lane having a canopy may be mounted lower than 15 feet above the pavement, but not lower than the vertical clearance of the canopy structure.

Lane-use control signals may also be used to indicate the open or closed status of an Open-Road ETC lane as a supplement to other devices used for the temporary closure of a lane (see Part 6).

Section 4K.03 4R.03 Warning Beacons at Toll Plazas

26 Standard:

Warning Beacons used at toll plazas shall comply with the provisions of Chapter 4L-4S except as otherwise provided in this Section.

Guidance:

Warning Beacons, if used with a toll plaza canopy sign (see Section 2F.16) to assist drivers of such vehicles in locating the dedicated ETC Account-Only lane(s), should be installed in a manner such that the beacons are distinctly separate from the lane-use control signals (see Section 4T.01) for the toll plaza lane. Option:

Warning Beacons that are mounted on toll plaza islands, behind impact attenuators in front of toll plaza islands, and/or on toll booth pylons (ramparts) to identify them as objects in the roadway may be mounted at a height that is appropriate for viewing in a toll plaza context, even if that height is lower than the normal minimum of 8 feet above the pavement.

3738

Section 4L.01-4S.01 General Design and Operation of Flashing Beacons

Support

A Flashing Beacon is a highway traffic signal with one or more signal sections that operates in a flashing mode. It can provide traffic control when used as an intersection control beacon (see Section 4L.02-4S.02) or it can provide warning when used in other applications (see Sections 4L.03, 4L.04, and 4L.05-4S.03, 4S.04, and 4S.05).

Standard:

Flashing Beacon units and their mountings shall comply with the provisions of Chapters 4D <u>and 4E</u>, except as otherwise provided in this Chapter.

Beacons shall be flashed at a rate of not less than 50 or more than 60 times per minute. The illuminated period of each flash shall be a minimum of 1/2 and a maximum of 2/3 of the total cycle.

A beacon shall not be included within the border of a sign except for <u>Interchange Exit Direction</u> signs with advisory speed panels (see Section 2E.26) School Speed Limit Sign Beacons (see Sections 4L.04 and 7B.15). Revised to reflect Official Change Request 4(09)-30

There shall be two nominal diameter sizes for flashing beacon signal indications: 8 inches and 12 inches. Added to reflect Official Interpretation 4(09)-7(I)

Guidance:

If used to supplement a warning or regulatory sign, the edge of the beacon signal housing should normally be located no closer than 12 inches outside of the nearest edge of the sign or from the nearest edge of any of the signs and plaques in a sign assembly.

Option:

An automatic dimming device may be used to reduce the brilliance of flashing yellow signal indications during night operation.

Section 41.02 4S.02 Intersection Control Beacon

Standard:

An Intersection Control Beacon shall consist of one or more signal faces directed toward each approach to an intersection. Each signal face shall consist of one or more signal sections of a standard traffic signal face, with flashing CIRCULAR YELLOW or CIRCULAR RED signal indications in each signal face. They shall be installed and used only at an intersection to control two or more directions of travel.

Application of Intersection Control Beacon signal indications shall be limited to the following:

- A. Yellow on one route (normally the major street) and red for the remaining approaches that are controlled by STOP signs, and
- B. Red for all approaches (if the warrant described in Section 2B.07 for a multi-way stop is satisfied all of the intersection approaches are controlled by STOP signs). Revised to reflect Official Change Request 4(09)-42

Flashing yellow signal indications shall not face conflicting vehicular approaches.

A STOP sign (see Section 2B.04) shall be used on approaches to which a flashing red signal indication is displayed on an Intersection Control Beacon (see Section 2B.04).

If two horizontally aligned red signal indications are used on an approach for an Intersection Control Beacon, they shall be flashed simultaneously to avoid being confused with grade crossing flashing-light signals. If two vertically aligned red signal indications that have a physical separation between them are used on an approach for an Intersection Control Beacon, they shall be flashed alternately.

Twelve-inch signal indications shall be used for Intersection Control Beacons facing approaches where: Added to reflect Official Change Request 4(09)-18

A. Road users view both flashing beacon and lane-use control signal indications simultaneously; or

B. The nearest flashing beacon signal face is more than 120 feet beyond the stop line, unless a supplemental near-side flashing beacon signal face is provided.

Guidance:

1

2

3

4 5

6 7

8

9

10

11

12

13

14

15 16

17 18

19

20 21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38 39

40

41

42

43

44

45

46

47

48

49

Twelve-inch signal indications should be used for Intersection Control Beacons facing approaches where:

A. The posted or statutory speed limit or the 85th-pentile approach speed is higher than 40 mph; or

B. Where only post-mounted flashing beacon signal faces are used.

Added to reflect Official Change Request 4(09)-18

An Intersection Control Beacon should not be mounted on a pedestal in the roadway unless the pedestal is within the confines of a traffic or pedestrian island.

Option:

Supplemental signal indications may be used on one or more approaches in order to provide adequate visibility to approaching road users.

Intersection Control Beacons may be used at intersections where traffic or physical conditions do not justify conventional traffic control signals but crash rates indicate the possibility of a special need.

An Intersection Control Beacon is generally located over the center of an intersection; however, it may be used at other suitable locations.

Section 4L.03 4S.03 Warning Beacon

Support:

Typical applications of Warning Beacons include the following:

- A. At-As supplemental emphasis to signs or object markers on or in front of obstructions that are in or immediately adjacent to the roadway;
- B. As supplemental emphasis to warning signs;
- C. As emphasis for midblock crosswalks;
- D. As supplemental emphasis to regulatory signs, except STOP, DO NOT ENTER, WRONG WAY, and SPEED LIMIT signs; and
- E. In conjunction with a regulatory or warning sign that includes the phrase WHEN FLASHING in its legend or on a supplemental plaque to indicate that the regulation is in effect or that the condition is present only at certain times. It is not appropriate to use flashing light emitting diode (LED) units within the legend or border of the sign to inform road users that the regulation is in effect or that the condition is present.

Standard:

A Warning Beacon shall consist of one or more signal sections of a standard traffic signal face with a flashing CIRCULAR YELLOW signal indication in each signal section.

A Warning Beacon shall be used only to supplement an appropriate warning or regulatory sign or marker.

Warning Beacons, if used at intersections, shall not face conflicting vehicular approaches.

If a Warning Beacon is suspended over the roadway, the clearance above the pavement shall be a minimum of 15 feet and a maximum of 19 feet Removed to reflect Official Interpretation 4(09)-11(I)

Guidance:

The condition or regulation justifying Warning Beacons should largely govern their location with respect to the roadway.

If an obstruction is in or adjacent to the roadway, illumination of the lower portion or the beginning of the obstruction or illumination of at the sign on or in front of the obstruction, in addition to the beacon, should be considered.

Warning Beacons should be operated only during those periods or times when the condition or regulation exists.

Option:

Warning Beacons that are actuated by pedestrians, bicyclists, or other road users may be used as appropriate to provide additional warning to vehicles approaching a crossing or other location.

1 If Warning Beacons have more than one signal section, they may be flashed either alternately or 2 simultaneously.

A flashing vellow Warning bBeacon interconnected with a traffic signal controller assembly may be used with a traffic signal warning BE PREPARED TO STOP (W3-4) sign and a WHEN FLASHING (W16-13P) plaque (see Section 2C.36-2C.37).

6 Guidance:

3

4

5

7

9

10

11 12

13 14

15

16

17

19

20

21

22

23

24

25

26

27

28 29

30

31 32

33

34

35

37

38

39

40

41

42

43

44 45

46

An audible information device should be used with pedestrian-actuated Warning Beacons to assist 8 pedestrians with visual disabilities.

Standard: Added to reflect Official Change Request 4(09)-42

If an audible information device is used in conjunction with a pedestrian-actuated Warning Beacon at a pedestrian crossing, the audible information device shall not use vibrotactile indications or percussive indications.

Guidance: Added to reflect Official Change Request 4(09)-42

If an audible information device is used in conjunction with a pedestrian-actuated Warning Beacon at a pedestrian crossing, the audible message should be a speech message that says, "Yellow lights are flashing". The audible message should be spoken twice.

Section 4L.04 4S.04 Speed Limit Sign Beacon

18 Standard:

A Speed Limit Sign Beacon shall be used only to supplement a Speed Limit sign.

A Speed Limit Sign Beacon shall consist of one or more signal sections of a standard traffic control signal face, with a flashing CIRCULAR YELLOW signal indication in each signal section. The signal indications shall have a nominal diameter of not less than 8 inches. If two signal indications are used, they shall be vertically aligned, except that they shall be permitted to be horizontally aligned if the Speed Limit (R2-1) sign is longer horizontally than vertically. If two or more signal indications are used, they shall be alternately flashed.

Option:

A Speed Limit Sign Beacon may be used with a fixed or variable Speed Limit sign. If applicable, a flashing Speed Limit Sign Beacon (with an appropriate accompanying sign) may be used to indicate that the displayed speed limit is in effect.

A Speed Limit Sign Beacon may be included within the border of a School Speed Limit (S5-1) sign (see Section 7B.15). Deleted to reflect Official Change Request 4(09)-30

Standard:

Flashing light emitting diode (LED) units shall not be used within the legend or border of a Speed Limit sign to indicate that the displayed speed limit is in effect.

Section 4L.05 4S.05 Stop Beacon

36 **Standard:**

> A Stop Beacon shall be used only to supplement a STOP sign, a DO NOT ENTER sign, or a WRONG WAY sign.

A Stop Beacon shall consist of one or more signal sections of a standard traffic signal face with a flashing CIRCULAR RED signal indication in each signal section. If two horizontally aligned signal indications are used for a Stop Beacon, they shall be flashed simultaneously to avoid being confused with grade crossing flashing-light signals. If two vertically aligned signal indications are used for a Stop Beacon, they shall be flashed alternately.

Guidance: Standard changed to Guidance

The bottom-edge of the signal housing of a Stop Beacon shall should be not less than 12 inches or more than 24 inches above the top from the nearest edge of a the STOP sign, a DO NOT ENTER sign, or WRONG WAY sign that it supplements.

47 48

Section 4M.01 4T.01 Application of Lane-Use Control Signals

Support

Lane-use control signals are special overhead signals that permit or prohibit the use of specific lanes of a street or highway or that indicate the impending prohibition of their use. Lane-use control signals are distinguished by placement of special signal faces over a certain lane or lanes of the roadway and by their distinctive shapes and symbols. Supplementary signs are sometimes used to explain their meaning and intent.

Lane-use control signals are most commonly used for reversible-lane control, but are also used in certain non-reversible lane applications and for toll plaza lanes (see Section 4K.02 4R.02).

Guidance:

An engineering study should be conducted to determine whether a reversible-lane operation can be controlled satisfactorily by static signs (see Section 2B.26-2B.36) or whether lane-use control signals are necessary. Lane-use control signals should be used to control reversible-lane operations if any of the following conditions are present:

- A. More than one lane is reversed in direction;
- B. Two-way or one-way left turns are allowed during peak-period reversible operations, but those turns are from a different lane than used during off-peak periods;
- C. Other unusual or complex operations are included in the reversible-lane pattern;
- D. Demonstrated crash experience occurring with reversible-lane operation controlled by static signs that can be corrected by using lane-use control signals at the times of transition between peak and off-peak patterns; and/or
- E. An engineering study indicates that the safety and efficiency of the traffic operations of a reversible-lane system would be improved by lane-use control signals.

Standard:

Pavement markings (see Section 3B.03 3B.04) shall be used in conjunction with reversible-lane control signals.

Option:

Lane-use control signals may also be used if there is no intent or need to reverse lanes, but there is a need to indicate the open or closed status of one or more lanes, such as:

- A. On a freeway, if it is desired to close certain lanes at certain hours to facilitate the merging of traffic from a ramp or other freeway;
- B. On a freeway, near its terminus, to indicate a lane that ends;
- C. On a freeway or long bridge, to indicate that a lane may be temporarily blocked by a crash, breakdown, construction or maintenance activities, or similar temporary conditions; and
- D. On a conventional road or driveway, at access or egress points to or from a facility, such as a parking garage, where one or more lanes of the access or egress are opened or closed at various times.

<u>A USE LANE(S) WITH GREEN ARROW (R10-8) sign (see Section 2B.63) may be used in conjunction</u> with lane-use control signals.

Section 4M.02 4T.02 Meaning of Lane-Use Control Signal Indications

Standard:

The meanings of lane-use control signal indications shall be as follows:

- A. A steady DOWNWARD GREEN ARROW signal indication shall mean that a road user is permitted to drive in the lane over which the arrow signal indication is located over is open to vehicle travel in that direction.
- B. A steady YELLOW X signal indication shall mean that the lane with the Yellow X signal indication located over it is about to be closed to vehicle traffic in that direction and shall be followed by a road user is to prepare to vacate the lane over which the signal indication is located because a lane control change is being made to a steady RED X signal indication.
- C. A steady WHITE TWO-WAY LEFT-TURN ARROW signal indication (see Figure 4M-1 4T-1) shall mean that the lane with the turning arrows indication located over it is open to traffic

- making a road user is permitted to use a lane over which the signal indication is located for a left turn from either direction of travel, but not for through travel, with the understanding that common use of the lane by oncoming road users for left turns is also permitted.
- D. A steady WHITE ONE-WAY LEFT-TURN ARROW signal indication (see Figure 4T-14M-1) shall mean that the lane with the turning arrow indication located over it is open to traffic making a road user is permitted to use a lane over which the signal indication is located for a left turn in that direction (without opposing turns in the same lane), but not for through travel.
- E. A steady RED X signal indication shall mean that the lane with the Red X signal indication over it is closed to vehicle traffic in the direction viewed by the a-road user, is not permitted to use the lane over which the signal indication is located and that this signal indication shall modify accordingly the meaning of other traffic controls present.

Figure 4T-1. Left-Turn Lane-Use Control Signals

Section 4M.03 4T.03 Design of Lane-Use Control Signals

Standard:

All lane-use control signal indications shall be in units with rectangular signal faces and shall have opaque backgrounds. Except as provided in Paragraph 13, the nominal minimum height and width of each DOWNWARD GREEN ARROW, YELLOW X, and RED X signal face shall be 18 inches for typical applications. Except as provided in Paragraph 13, the WHITE TWO-WAY LEFT-TURN ARROW and WHITE ONE-WAY LEFT-TURN ARROW signal faces shall have a nominal minimum height and width of 30 inches.

Each lane to be reversed or closed shall have signal faces with <u>at least</u> a DOWNWARD GREEN ARROW and a RED X symbol.

Each reversible lane that also operates as a two-way or one-way left-turn lane during certain periods shall have signal faces that also include the applicable WHITE TWO-WAY LEFT-TURN ARROW or WHITE ONE-WAY LEFT-TURN ARROW symbol.

Each non-reversible lane immediately adjacent to a reversible lane shall have signal indications that display a DOWNWARD GREEN ARROW to traffic traveling in the permitted direction and a RED X to traffic traveling in the opposite direction.

If in separate signal sections, the relative positions, from left to right, of the signal indications shall be RED X, YELLOW X, DOWNWARD GREEN ARROW, WHITE TWO-WAY LEFT-TURN ARROW, WHITE ONE-WAY LEFT-TURN ARROW.

Guidance:

The color of lane-use control signal indications shall-should be clearly visible for 2,300 feet at all times under normal atmospheric conditions, unless otherwise physically obstructed. Standard changed to Guidance

Lane-use control signal faces shall should be located approximately over the center of the lane controlled. Standard changed to Guidance

If the area to be controlled is more than 2,300 feet in length, or if the vertical or horizontal alignment is curved, intermediate lane-use control signal faces shall should be located over each controlled lane at frequent intervals. This location shall should be such that road users will at all times be able to see at least one signal indication and preferably two along the roadway, and will have a definite indication of the lanes specifically reserved for their use. Standard changed to Guidance

All lane-use control signal faces shall should be located in a straight line across the roadway approximately at right angles to the roadway alignment. Standard changed to Guidance

On roadways having intersections controlled by traffic control signals, the lane-use control signal face shall-should be located sufficiently far in advance of or beyond such traffic control signals to prevent them from being misconstrued as traffic control signals. Standard changed to Guidance

Standard:

Except as provided in Paragraph 12, the bottom of the signal housing of any lane-use control signal face shall be a minimum of 15 feet and a maximum of 19 feet above the pavement grade.

Option:

The bottom of a lane-use control signal housing may be lower than 15 feet above the pavement if it is mounted on a canopy or other structure over the pavement, but not lower than the vertical clearance of the structure.

Except for lane-use control signals at toll plazas (see Section 4K.02-4R.02), in areas with minimal visual clutter and with speeds of less than 40 mph, lane-use control signal faces with nominal height and width of 12 inches may be used for the DOWNWARD GREEN ARROW, YELLOW X, and RED X signal faces, and lane-use control signal faces with nominal height and width of 18 inches may be used for the WHITE TWO-WAY LEFT-TURN ARROW and WHITE ONE-WAY LEFT-TURN ARROW signal faces.

Other sizes of lane-use control signal faces larger than 18 inches with proportional dimensions and with message recognition distances appropriate to signal spacing may be used for the DOWNWARD GREEN ARROW, YELLOW X, and RED X signal faces.

Non-reversible lanes not immediately adjacent to a reversible lane on any street so controlled may also be provided with signal indications that display a DOWNWARD GREEN ARROW to traffic traveling in the permitted direction and a RED X to traffic traveling in the opposite direction.

The signal indications provided for each lane may be in separate signal sections or may be superimposed in the same signal section.

Section 4M.04 4T.04 Operation of Lane-Use Control Signals

Standard:

All lane-use control signals shall be coordinated so that all the signal indications along the controlled section of roadway are operated uniformly and consistently. The lane-use control signal system shall be designed to reliably guard against showing any prohibited combination of signal indications to any traffic at any point in the controlled lanes.

For reversible-lane control signals, the following combination of signal indications shall not be simultaneously displayed over the same lane to both directions of travel:

- A. DOWNWARD GREEN ARROW in both directions,
- B. YELLOW X in both directions,
- C. WHITE ONE-WAY LEFT-TURN ARROW in both directions,
- D. DOWNWARD GREEN ARROW in one direction and YELLOW X in the other direction,
- E. WHITE TWO-WAY LEFT-TURN ARROW or WHITE ONE-WAY LEFT-TURN ARROW in one direction and DOWNWARD GREEN ARROW in the other direction,
- F. WHITE TWO-WAY LEFT-TURN ARROW in one direction and WHITE ONE-WAY LEFT-TURN ARROW in the other direction, and
- G. WHITE ONE-WAY LEFT-TURN ARROW in one direction and YELLOW X in the other direction.

A moving condition in one direction shall be terminated either by the immediate display of a RED X signal indication or by a YELLOW X signal indication followed by a RED X signal indication.

Guidance: Standard changed to Guidance

In either case, the duration of the RED X signal indication shall should be sufficient to allow clearance of the lane before any moving condition is allowed in the opposing direction.

Standard:

Whenever a DOWNWARD GREEN ARROW signal indication is changed to a WHITE TWO-WAY LEFT-TURN ARROW signal indication, the RED X signal indication shall continue to be displayed to the opposite direction of travel for an appropriate duration to allow traffic time to vacate the lane being converted to a two-way left-turn lane.

If an automatic control system is used, a manual control to override the automatic control shall be provided.

Guidance:

The type of control provided for reversible-lane operation should be such as to permit either automatic or manual operation of the lane-use control signals.

Standard:

If used, lane-use control signals shall be operated continuously, except that lane-use control signals that are used only for special events or other infrequent occurrences and lane-use control signals on non-reversible freeway lanes shall be are permitted to be darkened when not in operation. The change from normal operation to non-operation shall occur only when the lane-use control signals display signal indications that are appropriate for the lane use that applies when the signals are not operated. The lane-use control signals shall display signal indications that are appropriate for the existing lane use when changed from non-operation to normal operations. Also, traffic control devices shall clearly indicate the proper lane use when the lane control signals are not in operation.

Support:

Section_2B.26 2B.36 contains additional information concerning considerations involving left-turn prohibitions in conjunction with reversible-lane operations. Section 2G.24 contains additional information concerning lane-use control signals used for part-time travel on a shoulder. Section 2G.25 contains additional information concerning lane-use control signals used for active lane management on freeways and expressways.

Section 4N.01 4U.01 Application of In-Roadway Warning Lights

Support:

In-Roadway <u>Warning</u> Lights are special types of highway traffic signals installed in the roadway surface to warn road users that they are approaching a condition on or adjacent to the roadway that might not be readily apparent and might require the road users to <u>slow down reduce their speed</u> and/or come to a stop. This includes situations warning of marked school crosswalks, marked midblock crosswalks, marked crosswalks on uncontrolled approaches, marked crosswalks in advance of roundabouts as described in Chapter 3C 3D, and other roadway situations involving pedestrian crossings.

Standard:

In-Roadway Warning Lights shall not be used for any application that is not described in this Chapter.

When used, In-Roadway Warning Lights shall be flashed and shall not be steadily illuminated.

Support:

Steadily-illuminated lights installed in the roadway surface are considered to be internally-illuminated raised pavement markers (see Section 3B.11-3B.14).

Option:

In-Roadway Warning Lights may be flashed in a manner that includes a continuous flash of varying intensity and time duration that is repeated to provide a flickering effect (see Section 4N.02-4U.02).

Guidance: This paragraph was relocated from earlier in this section; Standard changed to Guidance

If used, In-Roadway <u>Warning</u> Lights <u>shall-should</u> not exceed a height of 3/4 inch above the roadway surface.

Section 4N.02-4U.02 In-Roadway Warning Lights at Crosswalks

Option:

In-Roadway <u>Warning</u> Lights may be installed at certain marked crosswalks, based on an engineering study or engineering judgment, to provide additional warning to road users.

Standard:

If used, In-Roadway Warning Lights at crosswalks shall be installed only at marked crosswalks with applicable warning signs. They shall not be used at crosswalks controlled by YIELD signs, STOP signs, or pedestrian hybrid beacons.

If In-Roadway Warning Lights are used at a crosswalk, the following requirements shall apply:

- A. Except as provided in Paragraphs 7 and 8, they shall be installed along both sides of the crosswalk and shall span its entire length.
- B. They shall initiate operation based on pedestrian actuation and shall cease operation at a predetermined time after the pedestrian actuation or, with passive detection, after the pedestrian clears the crosswalk.
- C. They shall display a flashing yellow light when actuated. The flash rate shall be at least 50, but no more than 60, flash periods per minute. If they are flashed in a manner that includes a continuous flash of varying intensity and time duration that is repeated to provide a flickering effect, the flickers or pulses shall not repeat at a rate that is between 5 and 30 per second to avoid frequencies that might cause seizures.
- D. They shall be installed in the area between the outside edge of the crosswalk line and 10 feet from the outside edge of the crosswalk.
- E. They shall face away from the crosswalk if unidirectional, or shall face away from and across the crosswalk if bidirectional.

If used on one-lane, one-way roadways, a minimum of two In-Roadway Warning Lights shall be installed on the approach side of the crosswalk. If used on two-lane roadways, a minimum of three In-Roadway Warning Lights shall be installed along both sides of the crosswalk. If used on roadways with

more than two lanes, a minimum of one In-Roadway Warning Light per lane shall be installed along both sides of the crosswalk.

Guidance:

 If used, In-Roadway Warning Lights should be installed in the center of each travel lane, at the center line of the roadway, at each edge of the roadway or parking lanes, or at other suitable locations away from the normal tire track paths.

The location of the In-Roadway Warning Lights within the lanes should be based on engineering judgment.

Option:

On one-way streets, In-Roadway Warning Lights may be omitted on the departure side of the crosswalk.

Based on engineering judgment, the In-Roadway Warning Lights on the departure side of the crosswalk on the left-hand side of a median may be omitted.

Unidirectional In-Roadway Warning Lights installed at crosswalk locations may have an optional, additional yellow light indication in each unit that is visible to pedestrians in the crosswalk to indicate to pedestrians in the crosswalk that the In-Roadway Warning Lights are in fact flashing as they cross the street. These yellow lights may flash with and at the same flash rate as the light module in which each is installed. *Guidance:*

If used, the period of operation of the In-Roadway Warning Lights following each actuation should be sufficient to allow a pedestrian crossing in the crosswalk to leave the curb or shoulder and travel at a walking speed of 3.5 feet per second to at least the far side of the traveled way or to a median of sufficient width for pedestrians to wait. Where pedestrians who walk slower than 3.5 feet per second, or pedestrians who use wheelchairs, routinely use the crosswalk, a walking speed of less than 3.5 feet per second should be considered in determining the period of operation.

An audible information device should be used with In-Roadway Warning Lights to provide assistance for pedestrians with visual disabilities.

Standard:

If pedestrian push buttons (<u>rather than passive detection</u>) are used to actuate the In-Roadway <u>Warning Lights</u>, a PUSH BUTTON TO TURN ON WARNING LIGHTS (<u>with pushbutton symbol</u>) (R10-25) sign (see Section <u>2B.26-2B.62</u>) shall be <u>mounted adjacent to or integral with each installed explaining the purpose and use of the pedestrian push button <u>detector</u>.</u>

Where the period of operation is sufficient only for crossing from a curb or shoulder to a median of sufficient width for pedestrians to wait, median-mounted pedestrian actuators shall be provided.

<u>If an audible information device is used in conjunction with In-Roadway Warning Lights, the</u> audible information device shall not use vibrotactile indications or percussive indications.

Guidance: Added to reflect Official Change Request 4(09)-42

If an audible information device is used in conjunction with In-Roadway Warning Lights, the audible message during the time that the lights are flashing should be a speech message that says, "Yellow lights are flashing." The audible message should be spoken twice.

PART 5 – AUTOMATED VEHICLES

CHAPTER 5A. GENERAL

3 Section 5A.01 Purpose and Scope

Support:

The purpose of this Chapter is to provide agencies with general considerations for vehicle automation as they assess their infrastructure needs, prepare their roadways for automated vehicle (AV) technologies, and to support the safe deployment of automated vehicle technology.

This Chapter provides an overview of foundational AV technology terminology, key principles, considerations for traffic control device selection, and topics for agencies to consider. The MUTCD does not address standardizing several areas that might be important to AV technologies such as digital infrastructure, geometric road design, setting maintenance levels for all traffic control devices, and setting minimum condition levels for paving materials.

It is important for early implementers of automated vehicles to understand the ramifications of traffic control devices in a mixed fleet environment and to consider the needs of both human and machine led road users. Partial automation technologies are already commercially available in the vehicle fleet and are operating under current infrastructure conditions. The overall effectiveness of the automation is impacted by the uniformity and consistent application of the highway infrastructure, including traffic control devices.

Section 5A.02 Overview of Connected and Automated Vehicles

20 Support:

Connected vehicle technology enables cars, buses, trucks, trains, roads and roadside infrastructure, as well as other devices such as cellular telephones, to communicate with one another. This technology enables every vehicle on the road to be aware of where other nearby vehicles are. Drivers would receive notifications and alerts of dangerous situations, such as a vehicle about to run a red traffic signal as it nears an intersection or an oncoming car, out of sight beyond a curve, swerving into the opposing lane to avoid an object on the road.

AV technology automates some or all aspects of the driving tasks to assist or replace the human vehicle operator. Automated vehicle features may include adaptive cruise control, adaptive headlights, automatic emergency braking, lane tracking assist, or other technology based features used to control some or all aspects of the vehicle. AVs are vehicles in which at least one element of vehicle control (e.g. steering, speed control, braking) occurs without direct driver input. AVs work by gathering information from a suite of sensors:

- A. Cameras;
- 34 B. Radar;
- 35 <u>C. Light detection and ranging (LiDAR);</u>
- 36 <u>D. Ultrasonic; and</u>
- E. Infrared.

AVs may combine sensor data with other inputs including detailed map data and information from other connected vehicles or infrastructure. AVs may be able to detect and classify objects in their surroundings and may predict how they are likely to behave.

Section 5A.03 Definitions and Terms

- **Support**:
- The following definitions and terms, found in the Society of Automotive Engineers standard SAE J3016 and other sources, are used extensively in automated vehicle technology. Their definitions are
- 45 <u>summarized for reference and for use with the provisions of this Manual:</u>

- A. Automated Driving Systems (ADS) The hardware and software that are collectively capable of performing the entire dynamic driving task (DDT) on a sustained basis, regardless of whether it is limited to a specific operational design domain (ODD); this term is used specifically to describe a level 3, 4, or 5 driving automation system (DAS).
- B. Advanced Driver Assistance Systems (ADAS) are electronic systems that aid a vehicle driver with one or more driving tasks while driving. They are intended to increase safe operation of a vehicle and includes applications such as automatic braking, lane keep assistance, adaptive cruise control, and others.
- C. Automation Levels:
 - 1. Level 0 The full-time performance by the human driver of all aspects of the DDT, even when enhanced by warning or intervention systems.
 - 2. Level 1 The driving mode specific execution by a driver assistance system of either steering or acceleration/deceleration using information about the driving environment and with the expectation that the human driver performs all remaining aspects of the DDT.
 - 3. Level 2 The driving mode specific execution by one or more driver assistance systems of both steering or acceleration/deceleration using information about the driving environment and with the expectation that the human driver performs all remaining aspects of the DDT.
 - 4. Level 3 The driving mode specific performance by an ADS of all aspects of the DDT with the expectation that the human driver will respond appropriately to a request to intervene.
 - 5. Level 4 The driving mode specific performance by an ADS of all aspects of the DDT, even if a human driver does not respond appropriately to a request to intervene.
 - 6. Level 5 The full-time performance by an ADS of all aspects of the DDT under all roadway and environmental conditions that can be managed by a human driver.
- D. Cooperative Automation technology that enables communication with other vehicles and the infrastructure to coordinate automated vehicle operation.
- E. DAS The hardware and software that are collectively capable of performing part or all of the DDT on a sustained basis; this term is used generically to describe any system capable of level 1-5 driving automation.
- F. DDT All of the real-time operational and tactical functions required to operate a vehicle in onroad traffic, excluding the strategic functions such as trip scheduling and selection of destinations and waypoints.
- G. ODD Operating conditions under which a given DAS or feature thereof is specifically designed to function, including, but not limited to, environmental, geographical, and time-of-day restrictions, and/or the requisite presence or absence of certain traffic or roadway characteristics.

Section 5A.04 Traffic Control Device Design and Use Considerations

Support:

The interaction of traffic control devices with DAS can create many challenges for agencies in determining traffic control device selection and application. The lack of tolerance of DAS for non-uniformity in traffic control device design and application is a limiting factor of current DAS sophistication, i.e. DAS has limited ability to interpolate across gaps in traffic control device cues to the vehicle in the following situations:

- A. The DAS technologies ability to adapt to existing traffic control device design and typical quality, e.g. the refresh rates of electronic changeable message sign displays or the overall quality of a device that has been out on the roadway for many years;
- B. The color perception of signs;
- C. The electronically perceptible conspicuity and contrast of markings in different environments and lighting conditions;

- D. The DAS camera technologies and device photometric characteristics in reading various types of
 traffic signals
 - E. The ability to discern and comprehend temporary traffic control devices and their varying applications, e.g. active electronic display devices, flaggers, etc.;
 - F. The ability to decipher traffic control at rail grade crossings, especially with passive control.

These and other challenges might limit the functionality of DAS making them less effective or functional. The uniform design and consistent application of standardized traffic control devices supports the functionality of DAS technology in many situations. Similarly, good traffic control device maintenance practices and programs will help improve the potential for vehicle DAS to operate properly in many roadway environments.

Guidance:

<u>Agencies should adopt traffic control device maintenance policies and or practices with</u> <u>consideration to both the human vehicle operator and DAS technology needs (see Sections 1A.12, 2A.18, 3A.05 and 4A.10 of this Manual).</u>

Engineering judgment (see Section 1D.03 of this Manual) used to determine traffic control device selection and placement should consider uniformity in application and location needed to support both the human vehicle operator and DAS technology.

Support:

A systematic approach to traffic control device selection, application, and maintenance taking into consideration certain fundamental principles, will help agencies considering the inclusion of DAS vehicles on their roadways. Generally, improvements to traffic control device uniformity and improved maintenance policies and practices that keep traffic control devices in good working order with high levels of conspicuity that benefit the human vehicle operator will benefit DAS vehicles as well.

Guidance:

Agencies should apply the following fundamental principles and considerations as they evaluate traffic control devices and other maintenance practices to support AV technologies during maintenance and infrastructure improvements:

- A. The uniform and consistent application of traffic control devices on each type of roadway; applying a similar approach to traffic control at similar locations in similar situations.
- B. Established maintenance policies that incorporate effective practices to ensure the clear message intended to the road user on traffic control devices reaching the end of their useful life, or are damaged or otherwise no longer serviceable, be identified, fixed or replaced in a timely manner.
- C. Temporary or emergency traffic control, to the extent practical, is planned in advance using devices that comply with the provisions of this Manual and following policies designed to ensure uniformity throughout the site and across jurisdiction.
- D. Removal of extraneous devices that are no longer necessary or that provide limited benefit to vehicle operation or navigation.

CHAPTER 5B. PROVISIONS FOR TRAFFIC CONTROL DEVICES

Section 5B.01 Signs

3 Support:

1

2

4

5

6

7

8

9

10

11 12

13

14

15

16

17 18

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

44 45 DAS uses machine vision technology to locate, read, and comprehend traffic signs and appropriately make vehicle operational decisions. Location, condition, uniformity, design characteristics, and consistent application all affect the ability of machine vision to perform these functions.

Guidance:

Sign location and application should be clearly associated with the displayed message to the specific lane or road to which it applies, such as in the case of parallel roads or lanes with different speed limits or restrictions.

The practice of sign and information spreading (see Section 2A.19) should be used to limit the amount of information displayed in one location or on one sign to minimize sign clutter.

Signs with designs that are otherwise not provided for in this Manual or the Standard Highway Signs publication should use standardized sign design practices and features as provided for in this Manual for the type of sign, the location, and character of the roadway on which it is used.

The illuminated portion of electronic-display signs using LEDs should have a standard refresh/flicker rate. The refresh rate of the LEDs should be greater than 200 Hz to be easier for the camera to detect.

Section 5B.02 Markings

19 Support:

DAS uses machine vision technology to locate, read and comprehend pavement markings. Location, condition, uniformity, design characteristics, and consistent application all have some effect on the ability of machine vision to perform this function. Certain pavement marking applications and practices have been shown through research to better support AV operations, while also benefiting, or at least not detracting from, the performance of the human operator. Such practices include the following:

- A. Normal-width longitudinal lines on freeways, expressways, and ramps of at least 6 inches wide (see Section 3A.04).
- B. Edge lines of at least 6 inches in width on roadways with posted speeds greater than 40 mph (see Section 3B.09).

Guidance:

The following should be considered to better accommodate machine vision used to support the automation of vehicles:

- A. Normal-width longitudinal lines of at least 6 inches wide on conventional roadways.
- B. Edge lines of at least 6 inches in width on conventional roadways with posted speeds of 40 mph or less.
- C. Dotted edge line extensions along all entrance and exit ramps, all auxiliary lanes, and all tapers where a deceleration or auxiliary lane is added (see Section 3B.11).
- D. Chevron markings (see Section 3B.25) in the neutral areas of exit gores to distinguish them from travel lanes.
- E. Continuous markings at the beginning of work zones and in all lane transitions.
- <u>F.</u> Raised pavement markers only as a supplement to, rather than as a substitute for, markings (see <u>Sections 3B.16 and 3B.17).</u>
- G. Uniform contrast markings on light-colored pavements to create greater contrast.
- 43 H. Broken lines (see Section 3B.06) of at least 10 ft in length with a maximum gap of 30 ft.
 - I. Avoidance of decorative elements in crosswalks.

Section 5B.03 Highway Traffic Signals

46 *Guidance*:

The following considerations should be used to better accommodate machine vision used to support the automation of vehicles and benefit the performance of the human vehicle operator:

- A. Traffic signal design should be consistent along corridors with respect to the placement of signal faces overhead on span-wire and mast arms versus post-mounting on the side of the roadway.
- B. The number of signal faces for approach lanes and the selection of signal indications and signal clusters should be consistent along a corridor to promote uniform displays for identical or similar situations.
- C. The refresh rate of the LED traffic signals should be consistent throughout the jurisdiction and be greater than 200 Hz to allow greater consistency in machine vision detection.

Support:

Achieving uniformity along a corridor is desirable for machine vision technology, but can be challenging. Multiple options are available for traffic signal displays to allow design variations based on specific intersection variables such as available overhead clearance, utility conflicts, signal support design constraints and other factors. Where possible, connected and automated vehicles (CAV) needs with respect to traffic signals are better addressed through vehicle to infrastructure (V2I) for the reasons stated above and for reliability and accuracy of critical communications under all environmental conditions.

Section 5B.04 Temporary Traffic Control

Guidance:

<u>Considerations should be given to better accommodate machine vision used to support the automation of vehicles and benefit the performance of the human vehicle operator in and through work zones.</u>

The type of signs, spacing and mounting height should follow the requirements of Section 6B.04

Advance Warning Area and 6F.02 Sign Placement. The END ROAD WORK (G20-2) sign should be used to establish the end of the work zone.

Standard:

Existing pavement markings shall be maintained in all long-term stationary (see Section 6G.02) temporary traffic control zones in accordance with Chapters 3A and 3B, except as otherwise provided for temporary pavement markings in Section 6F.78. Pavement markings shall match the alignment of the markings in place at both ends of the TTC zone. Pavement markings shall be placed along the entire length of any paved detour or temporary roadway prior to the detour or roadway being opened to road users.

For long-term stationary operations, pavement markings in the temporary traveled way that are no longer applicable shall be removed or obliterated as soon as practical. Pavement marking obliteration shall remove the non-applicable pavement marking material, and the obliteration method shall minimize pavement scarring. Painting over existing pavement markings with black paint or spraying with asphalt shall not be accepted as a substitute for removal or obliteration.

Guidance:

To better accommodate machine vision used to support the automation of vehicles, -channelizing devices should be at least 8 inches wide with retroreflective material for reliable machine detection in all weather conditions. Markings entering the work zone and through lane shifts should be made with highly visible and continuous materials, not intermittent buttons and reflectors.

42 Section 5B.05 Traffic Control for Railroad and Light Rail Transit Grade Crossings

Guidance:

For passive and active grade crossings, placement of signs and markings should be consistent along a corridor to promote uniformity and to improve the ability of machine vision technology to recognize highway-rail grade crossings.

- 1 For active grade crossings, V2I communication should be used to relay information on the arrival or presence of a train at a highway-rail grade crossing.
- To better accommodate machine vision used to support the automation of vehicles, the signs and pavement markings associated with railroad crossings and tracks that are no longer active should be removed.
- 6 Support:
- Where possible, CAV needs with respect to highway-rail grade crossings are better addressed through V2I infrastructure for reasons of reliability and accuracy of critical communications under all environmental conditions.
- 10 <u>Section 5B.06 Traffic Control for Bicycle Facilities</u>
- 11 *Guidance:*
- 12 <u>To better accommodate machine vision used to support the automation of vehicles, bicycle facilities</u> 13 <u>should be segregated from other vehicle traffic using physical barriers where practicable.</u>
- 14 Road markings should indicate the end of a bike lane that is merged with other traffic.

CHAPTER 5C. FUTURE CONSIDERATIONS

2 (Reserved)

1

2 Section 6A.01 General

3 Support:

Whenever the acronym "TTC" is used in Part 6, it refers to "temporary traffic control."

Standard:

The needs and control of all road users (motorists, bicyclists, and pedestrians within the highway, or on private roads site roadways open to public travel (see definition in Section 1A.131C.02), including persons with disabilities in accordance with the Americans with Disabilities Act of 1990 (ADA), Title II, Paragraph 35.130) through a TTC zone shall be an essential part of highway construction, utility work, maintenance operations, and the management of traffic incidents. Edited to improve consistency Support:

When the normal function of the roadway, or a <u>private road site roadway</u> open to public travel, is suspended, TTC planning provides for continuity of the movement of motor vehicle, bicycle, and pedestrian traffic (including accessible passage); transit operations; and access (and accessibility) to property and utilities. **Edited to improve consistency**

The primary function of TTC is to provide for the reasonably safe and effective facilitate movement of road users through or around TTC zones while reasonably protecting road users, workers, responders to traffic incidents, and equipment. Edited to improve accuracy

Of equal importance to the public traveling through the TTC zone is the safety of workers performing the many varied tasks within the work space. TTC zones present constantly changing conditions that are unexpected by the road user. This creates an even higher degree of vulnerability for the workers and incident management responders on or near the roadway (see Section 6D.036C.04). At the same time, the TTC zone provides for the efficient completion of whatever activity interrupted the normal use of the roadway.

Consideration for road user safety, worker and responder safety, and the efficiency of road user flow is an integral element of every TTC zone, from planning through completion. A concurrent objective of the TTC is the efficient construction and maintenance of the highway and the efficient resolution of traffic incidents.

No one set of TTC devices can satisfy all conditions for a given project or incident. At the same time, defining details that would be adequate to cover all applications is not practical. Instead, Part 6 displays typical applications that depict common applications of TTC devices. The TTC selected for each situation depends on type of highway, road user conditions, duration of operation, physical constraints, and the nearness of the work space or incident management activity to road users.

The temporary traffic control for low-volume rural and special purpose roads will generally be minimal, recognizing the lower speeds and traffic volumes. A limited number of signs, maintenance vehicle warning flashers, or a single flagger could be adequate for most situations. Added due to elimination of Part 5

Improved road user performance might be realized through a well-prepared public relations effort that covers the nature of the work, the time and duration of its execution, the anticipated effects upon road users, and possible alternate routes and modes of travel. Such programs have been found to result in a significant reduction in the number of road users traveling through the TTC zone, which reduces the possible number of conflicts.

Operational improvements might be realized by using intelligent transportation systems (ITS) in work zones. The use in work zones of ITS technology, such as portable camera systems, highway advisory radio, variable speed limits, ramp metering, traveler information, merge guidance, warning systems for vehicles exiting the work space and queue detection information, is aimed at increasing safety for both workers and road users and helping to ensure a more efficient traffic flow. The use in work zones of ITS technologies has been found to be effective in providing traffic monitoring and management, data collection, and traveler information.

Standard:

TTC plans and devices shall be the responsibility of the authority of a public body or official or the owners of site roadways open to public travel having jurisdiction for guiding road users. Edited to improve consistency

Guidance: Standard changed to Guidance

There <u>shall should</u> be adequate statutory authority for the implementation and enforcement of needed road user regulations, parking controls, speed zoning, and the management of traffic incidents. Such statutes <u>shall should</u> provide sufficient flexibility in the application of TTC to meet the needs of changing conditions in the TTC zone.

Support:

Temporary facilities, including pedestrian routes around worksites, are also covered by the accessibility requirements of the Americans with Disabilities Act of 1990 (ADA) (Public Law 101-336, 104 Stat. 327, July 26, 1990. 42 U.S.C. 12101-12213 (as amended)). Deleted; redundant with Standard statement above *Guidance:*

The TTC plan should start in the planning phase and continue through the design, construction, and restoration phases. The TTC plans and devices should follow the principles set forth in Part 6. The management of traffic incidents should follow the principles set forth in Chapter 61. This text was relocated to new Section 6B.01

Option:

TTC plans may deviate from the typical applications described in Chapter 6H to allow for conditions and requirements of a particular site or jurisdiction. This text was relocated to new Section 6P.01

Support:

The provisions of Part 6 apply to both rural and urban areas. A rural highway is normally characterized by lower volumes, higher speeds, fewer turning conflicts, and less conflict with pedestrians. An urban street is typically characterized by relatively low speeds, wide ranges of road user volumes, narrower roadway lanes, frequent intersections and driveways, significant pedestrian activity, and more businesses and houses.

The determination as to whether a particular facility at a particular time of day can be considered to be a high-volume roadway or can be considered to be a low-volume roadway is made by the public agency or official having jurisdiction.

Special plans preparation and coordination with transit, other highway agencies, law enforcement and other emergency units, utilities, schools, <u>trucking associations</u> and railroad companies might be needed to reduce unexpected and unusual road user operation situations. This text was relocated from existing Section 6B.01

Section 6B.016A.02 Fundamental Principles of Temporary Traffic Control

Support:

Construction, maintenance, utility, and incident zones can all benefit from TTC to compensate for the unexpected or unusual situations faced by road users. When planning for TTC in these zones, it can be assumed that it is appropriate for road users to exercise caution. Even though road users are assumed to be using caution, special care is still needed in applying TTC techniques. Deleted; redundant with new Part 1 language on target road users

Special plans preparation and coordination with transit, other highway agencies, law enforcement and other emergency units, utilities, schools, and railroad companies might be needed to reduce unexpected and unusual road user operation situations. This text was relocated to new Section 6A.01

During TTC activities, commercial vehicles might need to follow a different route from passenger vehicles because of bridge, weight, clearance, or geometric restrictions. Also, vehicles carrying hazardous materials might need to follow a different route from other vehicles. The Hazardous Materials and National Network signs are included in Sections 2B.62 and 2B.63, respectively. This was text relocated to new Section 6B.01

Experience has shown that following the fundamental principles of Part 6 will assist road users and help protect workers in the vicinity of TTC zones.

47 Standard:

Before any new detour or temporary route is opened to traffic, all necessary signs shall be in place. Relocated from below and deleted; redundant with new Standard in new Section 1D.11

All TTC devices shall be removed as soon as practical when they are no longer needed. When work is suspended for short periods of time, TTC devices that are no longer appropriate shall be removed or covered. Relocated from below

Guidance:

Road user and worker safety and accessibility in TTC zones should be an integral and high-priority element of every project from planning through design and construction. Similarly, maintenance and utility work should be planned and conducted with the safety and accessibility of all motorists, bicyclists, pedestrians (including those with disabilities), and workers being considered at all times. If the TTC zone includes a grade crossing, early coordination with the railroad company or light rail transit agency should take place.

Support:

Formulating specific plans for TTC at traffic incidents is difficult because of the variety of situations that can arise. This text was relocated to new Section 6B.01

Guidance:

The following are the seven fundamental principles of TTC:

- 1. General plans or guidelines should be developed to provide safety for motorists, bicyclists, pedestrians, workers, enforcement/emergency officials, and equipment, with the following factors being considered:
 - A. The basic safety principles governing the design of permanent roadways and roadsides should also govern the design of TTC zones. The goal should be to route road users through such zones using roadway geometrics, roadside features, and TTC devices as nearly as possible comparable to those for normal highway situations.
 - B. A TTC plan, in detail appropriate to the complexity of the work project or incident, should be prepared and understood by all responsible parties before the site is occupied. Any changes in the TTC plan should be approved by an official who is knowledgeable (for example, trained and/or certified) in proper TTC practices.
- 2. Road user movement should be inhibited as little as practical, based on the following considerations:
 - A. TTC at work and incident sites should be designed on the assumption that drivers will only reduce their speeds if they clearly perceive a need to do so (see Section 6C.016B.01).
 - B. Frequent and abrupt changes in geometrics such as lane narrowing, dropped lanes, or main roadway transitions that require rapid maneuvers, should be avoided.
 - C. Work should be scheduled in a manner that minimizes the need for lane closures or alternate routes, while still getting the work completed quickly and the lanes or roadway open to traffic as soon as possible.
 - D. Attempts should be made to reduce the volume of traffic using the roadway or freeway to match the restricted capacity conditions. Road users should be encouraged to use alternative routes. When the roadway capacity is reduced due the lane closures, the demand will exceed the available capacity and result in either a lengthy stopped or slow moving queue of vehicles that may extend past the normal signs shown in the typical advance warning area. An assessment of the expected queue length should be a part of the temporary traffic control plan design process and adjustments to the sign spacing and number of signs as well as the possibility of using more conspicuous devices may be provided to increase the distance and conspicuity of the advance warning area. Added to reflect NTSB H-15-16 recommendation For high-volume roadways and freeways, the closure of selected entrance ramps or other access points and the use of signed diversion routes should be evaluated.
 - E. Bicyclists and pedestrians, including those with disabilities, should be provided with access and reasonably safe passage through the TTC zone. Edited to improve consistency
 - F. If work operations permit, lane closures on high-volume streets and highways should be scheduled during off-peak hours. Night work should be considered if the work can be accomplished with a series of short-term operations.
 - G. Early coordination with officials having jurisdiction over the affected cross streets and providing emergency services should occur if significant impacts to roadway operations are anticipated.

- 1 2 3
- 4 5 6 7 8
- 10 11 12 13 14

16 17 18

19

15

- 20 21 22 23
- 24 25 26 27 28
- 29 30 31 32
- 33 34 35 36
- 37 38 39
- 41 42 43

44

45

40

- 46 47 48
- 49 50
- 51 52

- 3. Motorists, bicyclists, and pedestrians should be guided in a clear and positive manner while approaching and traversing TTC zones and incident sites. The following principles should be applied:
 - A. Adequate warning, delineation, and channelization should be provided to assist in guiding road users in advance of and through the TTC zone or incident site by using proper pavement marking, signing, or other devices that are effective under varying conditions. Providing information should be provided in that is in usable formats by for pedestrians with visual disabilities should also be considered. Edited to reflect 28 CFR 35.160 (subpart a)
 - B. TTC devices inconsistent with intended travel paths through TTC zones should be removed or covered. However, in intermediate-term stationary, short-term, and mobile operations, where visible permanent devices are inconsistent with intended travel paths, devices that highlight or emphasize the appropriate path should be used. Providing Traffic control devices should provide information in usable formats for pedestrians with visual disabilities. that are accessible to and usable by pedestrians with disabilities should be considered. Edited to reflect 28 CFR **35.160** (subpart a)
 - C. Flagging procedures, when used, should provide positive guidance to road users traversing the TTC zone.
- 4. To provide acceptable levels of operations, routine day and night inspections of TTC elements should be performed as follows:
 - A. Individuals who are knowledgeable (for example, trained and/or certified) in the principles of proper TTC should be assigned responsibility for safety in TTC zones. The most important duty of these individuals should be is to check that all TTC devices of on the project are consistent with the TTC plan and are effective for motorists, bicyclists, pedestrians, and workers. Edited to improve consistency
 - B. As the work progresses, temporary traffic controls and/or working conditions should be modified, if appropriateas needed, in order to provide mobility and positive guidance to the facilitate road user movement and to-provide worker safety. The individual responsible for TTC should have the authority to halt work until applicable or remedial safety measures are taken. Edited to improve consistency
 - C. TTC zones should be carefully monitored under varying conditions of road user volumes, light, and weather to check that applicable TTC devices are effective, clearly visible, clean, and in compliance with the TTC plan.
 - D. When warranted, an engineering study should be made (in cooperation with law enforcement officials) of reported crashes occurring within the TTC zone. Crash records in TTC zones should be monitored to identify the need for changes in the TTC zone.
- 5. Attention should be given to the maintenance of roadside safety during the life of the TTC zone by applying the following principles:
 - A. To accommodate run-off-the-road incidents, disabled vehicles, or emergency situations, unencumbered roadside recovery areas or clear zones should be provided where practical.
 - B. Channelization of road users should be accomplished by the use of pavement markings, signing, and crashworthy, detectable channelizing devices.
 - C. Work equipment, workers' private vehicles, materials, and debris should be stored in such a manner to reduce the probability of being impacted by run-off-the-road vehicles.
- 6. Each person whose actions affect TTC zone safety, from the upper-level management through the field workers, should receive training appropriate to the job decisions each individual is required to make. Only those individuals who are trained in proper TTC practices and have a basic understanding of the principles (established by applicable standards and guidelines, including those of this Manual) should supervise the selection, placement, and maintenance of TTC devices used for TTC zones and for incident management.
- 7. Good public relations should be maintained by applying the following principles:
 - A. The needs of all road users should be assessed such that appropriate advance notice is given and clearly defined alternative paths are provided.

- B. The cooperation of the various news media should be sought in publicizing the existence of and reasons for TTC zones because news releases can assist in keeping the road users well informed.
- C. The needs of abutting property owners, residents, and businesses should be assessed and appropriate accommodations made.
- D. The needs of emergency service providers (law enforcement, fire, and medical) should be assessed and appropriate coordination and accommodations made.
- E. The needs of railroads and transit should be assessed and appropriate coordination and accommodations made.
- F. The needs of operators of commercial vehicles such as buses and large trucks should be assessed and appropriate accommodations made.

Standard:

Before any new detour or temporary route is opened to traffic, all necessary signs shall be in place.

All TTC devices shall be removed as soon as practical when they are no longer needed. When work is suspended for short periods of time, TTC devices that are no longer appropriate shall be removed or covered. Relocated to above

Section 6F.016A.03 Types of TTC Devices New Section with paragraphs from existing Section 6F.01 and section title changed

Guidance:

The design and application of TTC devices used in TTC zones should consider the needs of all road users (motorists, bicyclists, and pedestrians), including those with disabilities.

Standard:

Traffic control devices shall be defined as all signs, signals, markings, channelizing devices, and or other devices that used colors, shapes, symbols, words, sounds, or tactile information for the primary purpose of communicating a to-regulateory, warning, or guideance message to road users, placed on, over, or adjacent to a street, highway, pedestrian facility, bikeway, pathway, or private roads site roadways open to public travel (see definition in Section 1A.13), pedestrian facility, or bikeway by authority of a public body or official having jurisdiction.

Revised for consistency with revised definition in Part 1.

All traffic control devices used for construction, maintenance, utility, or incident management operations on a street, highway, or private road site roadways open to public travel (see definition in Section 1A.13) shall comply with the applicable provisions of this Manual. Edited to improve consistency

Section 6A.04 Crashworthiness of TTC Devices Section 6F.01 New Section with paragraphs from existing

Support:

Various Sections of the MUTCD require certain traffic control devices, their supports, and/or related appurtenances to be crashworthy. Such MUTCD crashworthiness provisions apply to all streets, highways, and site roadways open to public travel. FHWA policy requires that all roadside appurtenances such as traffic-barriers, barrier terminals and crash cushions, bridge railings, sign and light pole supports, and work zone-hardware used on the National Highway System meet the crashworthy performance criteria contained in the National Cooperative Highway Research Program (NCHRP) Report 350, "Recommended Procedures for the Safety Performance Evaluation of Highway Features." The FHWA website at "http://safety.fhwa.dot.gov/programs/roadside_hardware.htm" identifies all such hardware and includes copies of FHWA acceptance letters for each of them. In the case of proprietary items, links are provided to manufacturers' websites as a source of detailed information on specific devices. The website also contains an "Ask the Experts" section where questions on roadside design issues can be addressed.

Various Sections of the MUTCD require certain traffic control devices, their supports, and/or related appurtenances to be crashworthy. Such MUTCD crashworthiness provisions apply to all streets, highways, and private roads open to public travel. Also, State Departments of Transportation and local agencies might have expanded the NCHRP Report 350 crashworthy criteria to apply to certain other roadside appurtenances.

As defined in Section 1A.13, "crashworthy" is a characteristic of a roadside appurtenance that has been successfully crash tested in accordance with a national standard such as the NCHRP Report 350, "Recommended Procedures for the Safety Performance Evaluation of Highway Features. Edited to improve clarity

Section 6A.05 Night Work New section with paragraphs 2-5 from existing Section 6G.19 Support:

Conducting highway construction and maintenance activities during night hours could provide an advantage when traditional daytime traffic control strategies cannot achieve an acceptable balance between worker and public safety, traffic and community impact, and constructability. The two basic advantages of working at night are reduced traffic congestion and less involvement with business activities. However, the two basic conditions that must normally be met for night work to offer any advantage are reduced traffic volumes and easy set up and removal of the traffic control patterns on a nightly basis.

Shifting work activities to night hours, when traffic volumes are lower and normal business is less active, might offer an advantage in some cases, as long as the necessary work can be completed and the worksite restored to essentially normal operating conditions to carry the higher traffic volume during non-construction hours.

Although working at night might offer advantages, it also includes safety issues. Reduced visibility inherent in night work impacts the performance of both drivers and workers. Because traffic volumes are lower and congestion is minimized, speeds are often higher at night necessitating greater visibility at a time when visibility is reduced. Finally, the incidence of impaired (alcohol or drugs), fatigued, or drowsy drivers might be higher at night.

Working at night also involves other factors, including construction productivity and quality, social impacts, economics, and environmental issues. A decision to perform construction or maintenance activities at night normally involves some consideration of the advantages to be gained compared to the safety and other issues that might be impacted.

See Section 6N.18 for specific provisions on TTC for work during nighttime hours. Added to reflect reorganization of material between Section 6A.05 and Section 6N.18

CHAPTER 6B. FUNDAMENTAL PRINCIPLES Section 6B.01 Fundamental Principles of Temporary Traffic Control has been moved to new Section 6A.02

Section 6C.016B.01 Temporary Traffic Control Plans

Support

Each TTC zone is different. Many variables, such as location of work, highway type, geometrics, vertical and horizontal alignment, intersections, interchanges, road user volumes, road vehicle mix (buses, trucks, and cars), and road user speeds affect the needs of each zone. The goal of TTC in work zones is safety with minimum disruption to road users. The key factor in promoting TTC zone safety is proper judgment. This text was relocated from existing Section 6G.01

A TTC plan describes TTC measures to be used for facilitating road users through a work zone or an incident area. TTC plans play a vital role in providing continuity of effective facilitating road user flow when a work zone, incident, or other event temporarily disrupts normal road user flow. Important auxiliary provisions that cannot conveniently be specified on project plans can easily be incorporated into Special Provisions within the TTC plan. Edited to improve consistency

TTC plans range in scope from being very detailed to simply referencing typical drawings contained in this Manual, standard approved highway agency drawings and manuals, or specific drawings contained in the contract documents. The degree of detail in the TTC plan depends entirely on the nature and complexity of the situation.

During TTC activities, commercial vehicles might need to follow a different route from passenger vehicles because of bridge, weight, clearance, or geometric restrictions. Also, vehicles carrying hazardous materials might need to follow a different route from other vehicles. The Hazardous Materials and National Network signs are included in Sections 2B.7262 and 2B.6373, respectively. This text was relocated from existing Section 6B.01.

Guidance:

<u>A TTC plan should be developed for any activity, either planned or unplanned, that will affect road users.</u>

Added to improve accuracy

The TTC plan should start in the planning phase and continue through the design, construction, and restoration phases. The TTC plans and devices should follow the principles set forth in Part 6. The management of traffic incidents should follow the principles set forth in Chapter 6160. This text was relocated from existing Section 6A.01.

TTC plans should be prepared by persons knowledgeable (for example, trained and/or certified) about the fundamental principles of TTC and work activities to be performed. The design, selection, and placement of TTC devices for a TTC plan should be based on engineering judgment.

Coordination should be made between adjacent or overlapping projects to check that duplicate signing is not used and to check compatibility of traffic control between adjacent or overlapping projects.

Traffic control planning should be completed for all highway construction, utility work, maintenance operations, and incident management including minor maintenance and utility projects prior to occupying the TTC zone. Planning for all road users should be included in the process.

For any planned special event that will have an impact on the traffic on any street or highway, a TTC plan should be developed in conjunction with and be approved by the agency or agencies that have jurisdiction over the affected roadways. This text was relocated from existing Section 6G.01

Provisions for effective continuity of accessible circulation paths for pedestrians should be incorporated into the TTC processplan. Where existing pedestrian routes are blocked or detoured, information should be provided about alternative routes that are usable by pedestrians with disabilities, particularly those who have visual disabilities. Access to temporary bus stops, travel across intersections with accessible pedestrian signals (see Section 4E.09), and other routing issues should be considered where temporary pedestrian routes are channelized. Barriers and channelizing devices that are detectable by people with visual disabilities should be provided. Deleted; redundant with other text in this section

Option

Provisions may be incorporated into the project bid documents that enable contractors to develop an alternate TTC plan.

Modifications of TTC plans may be necessary because of changed conditions or a determination of better methods of safely and efficiently handling road users.

Guidance:

This alternate or modified plan should have the approval of the responsible highway agency or owner of site roadways open to public travel prior to implementation. Edited to improve consistency

Provisions for effective continuity of transit service should be incorporated into the TTC planning process because often public transit buses cannot efficiently be detoured in the same manner as other vehicles (particularly for short-term maintenance projects). Where applicable, the TTC plan should provide for features such as accessible temporary bus stops, pull-outs, and satisfactory waiting areas for transit patrons, including persons with disabilities, if applicable (see Section 8A.0814 for additional light rail transit issues to consider for TTC).

Provisions for effective continuity of railroad service and acceptable access to abutting property owners and businesses should also be incorporated into the TTC planning process.

Reduced speed zoning (lowering the regulatory speed limit) should be avoided as much as practical because drivers will reduce their speeds only if they clearly perceive a need to do so. Relocated from below

If Rreduced speed limits are used, they should be used only in the specific portion of the TTC zone where conditions or restrictive features are present. However, frequent changes in the speed limit should be avoided. A TTC plan should be designed so that vehicles can travel through the TTC zone with a speed limit reduction of no more than 10 mph. Edited to improve consistency

A reduction of more than 10 mph in the speed limit should be used only when required by restrictive features in the TTC zone. Where restrictive features justify a speed reduction of more than 10 mph, additional driver notification should be provided. The speed limit should be stepped down in advance of the location requiring the lowest speed, and additional TTC warning devices should be used.

Support:

Research has demonstrated that large reductions in the speed limit, such as a 30 mph reduction, increase speed variance and the potential for crashes. Smaller reductions in the speed limit of up to 10 mph cause smaller changes in speed variance and lessen the potential for increased crashes. A reduction in the regulatory speed limit of only up to 10 mph from the normal speed limit has been shown to be more effective.

<u>Chapter 6P contains</u> Typical applications (TAs) of TTC zones that are organized according to duration, location, type of work, and highway type. Table 6H-16P-1 is an index of these typical applications. These typical applications include the use of various TTC methods, but do not include a layout for every conceivable work situation. This text was relocated from existing Section 6G.01 and edited to improve clarity

Decisions regarding the selection of the most appropriate typical application to use as a guide for a specific TTC zone require an understanding of each situation. Although there are many ways of categorizing TTC zone applications, the four factors mentioned earlier (work duration, work location, work type, and highway type) are used to characterize the typical applications illustrated in Chapter 6H6P. This text was relocated from existing Section 6G.01 and edited to improve consistency

Guidance:

Typical applications should be altered, when necessary, to fit the conditions of a particular TTC zone. This text was relocated from existing Section 6G.01

Option:

Other devices may be added to supplement the devices shown in the typical applications, while others may be deleted. The sign spacings and taper lengths may be increased to provide additional time or space for driver response. This text was relocated from existing Section 6G.01

Support:

Formulating specific plans for TTC at traffic incidents is difficult because of the variety of situations that can arise. This text was relocated from existing Section 6B.01

Well-designed TTC plans for planned special events will likely be developed from a combination of treatments from several of the typical applications. This text was relocated from existing Section 6G.01

Section 6C.026B.02 Temporary Traffic Control Zones

Support:

A TTC zone is an area of a highway where road user conditions are changed because of a work zone, an incident zone, or a planned special event through the use of TTC devices, uniformed law enforcement officers, or other authorized personnel.

A work zone is an area of a highway with construction, maintenance, or utility work activities. A work zone is typically marked by signs, channelizing devices, barriers, pavement markings, and/or work vehicles. It extends from the first warning sign or high-intensity rotating, flashing, oscillating, or strobe lights on a vehicle to the END ROAD WORK sign or the last TTC device.

An incident zone is an area of a highway where temporary traffic controls are imposed by authorized officials in response to a traffic incident (see Section 6160.01). It extends from the first warning device (such as a sign, light, or cone) to the last TTC device or to a point where road users return to the original lane alignment and are clear of the incident.

A planned special event often creates the need to establish altered traffic patterns to handle the increased traffic volumes generated by the event. The size of the TTC zone associated with a planned special event can be small, such as closing a street for a festival, or can extend throughout a municipality for larger events. The duration of the TTC zone is determined by the duration of the planned special event.

Section 6C.036B.03 Components of Temporary Traffic Control Zones

Support:

Most A TTC zones are is often divided into four areas as needed, based on engineering judgment: the advance warning area, the transition area, the activity area, and the termination area. Figure 6C 16B-1 illustrates these four areas typically included in a TTC zone. These four areas are described in Sections 6C6B.04 through 6C6B.07. Edited to improve clarity

Figure 6B-1. Component Parts of a Temporary Traffic Control Zone

Section 6C.046B.04 Advance Warning Area

Support:

The advance warning area is the section of highway where road users are informed about the upcoming work zone transition and activity areas or incident area. Edited to improve clarity

28 Option:

The advance warning area may vary from a single sign or high-intensity rotating, flashing, oscillating, or strobe lights on a vehicle to a series of signs in advance of the TTC zone activity area.

Guidance:

Typical distances for placement of advance warning signs on freeways and expressways should be longer because drivers are conditioned to uninterrupted flow. Therefore, the advance warning sign placement should extend on these facilities as far as 1/2 mile or more.

On urban streets, the effective placement of the first nearest warning sign to the TTC zone, in feet, should range from 4 to 8 times the speed limit in mph, with the high end of the range being used when speeds are relatively high. Edited to improve clarity When a single advance warning sign is used (in cases such as low-speed residential streets), the advance warning area can be as short as 100 feet. Guidance changed to Option and relocated to paragraph below When two or more advance warning signs are used on higher-speed streets, such as major arterials, the advance warning area should extend a greater distance (see Table 6C-16B-1).

42 Option:

When a single advance warning sign is used (in cases such as low-speed residential streets), the advance warning area may be as short as 100 feet. Guidance changed to Option and relocated from paragraph

45 above

Guidance:

Since rural highways are normally characterized by higher speeds, the effective placement of the first warning sign in feet should be substantially longer—from 8 to 12 times the speed limit in mph. Since two or

more advance warning signs are normally used for these conditions, the advance warning area should extend 1,500 feet or more for open highway conditions (see Table 6C-16B-1).

The distances contained in Table 6C-16B-1 are approximate, are intended for guidance purposes only, and should be applied with engineering judgment. These distances should be adjusted for field conditions, if necessary, by increasing or decreasing the recommended distances.

Support:

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16 17

18

19

2021

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

40

41

43

44

45

46

47

The need to provide additional reaction time for a condition is one example of justification for increasing the sign spacing. Conversely, decreasing the sign spacing might be justified in order to place a sign immediately downstream of an intersection or major driveway such that traffic turning onto the roadway in the direction of the TTC zone will be warned of the upcoming condition.

Option:

Advance warning may be eliminated when the activity area is sufficiently removed from the road users' path so that it does not interfere with the normal flow.

Table 6B-1. Recommended Advance Warning Sign Minimum Spacing

*Speed category to be determined by the highway agency or owner of roadways open to public travel

Section 6C.056B.05 Transition Area

Support:

The transition area is that section of highway where road users are redirected out of their normal path. Transition areas usually involve strategic use of tapers, which because of their importance are discussed separately in detail.

Standard:

When redirection of the road users' normal path is required, they shall be directed from the normal path to a new path, with signs, arrow boards, and/or channelizing devices, except for short-term or mobile operations. Edited to improve consistency

Option:

Because it is impractical in mobile operations to redirect the road user's' normal path with stationary channelization, more dominant vehicle-mounted traffic control devices, such as arrow boards, portable changeable message signs, and high-intensity rotating, flashing, oscillating, or strobe lights, may be used instead of channelizing devices to establish a transition area.

Section 6C.066B.06 Activity Area

Support:

The activity area is the section of the highway where the work activity takes place. It is comprised of the work space, the traffic space, and the buffer space.

The work space is that portion of the highway closed to road users and set aside for workers, equipment, and material, and a shadow vehicle if one is used upstream. Work spaces are usually delineated for road users by channelizing devices or, to exclude vehicles and pedestrians, by temporary barriers.

Option:

The work space may be stationary or may move as work progresses.

39 Guidance:

Since there might be several work spaces (some even separated by several miles) within the project limits, each work space should be adequately signed to inform road users and reduce confusion.

42 Support:

The traffic space is the portion of the highway in which road users are routed through the activity area.

The buffer space is a lateral and/or longitudinal area that separates road user flow from the work space or an unsafe area, and might provide some recovery space for an errant vehicle.

Guidance:

Neither work activity nor storage of equipment, vehicles, or material should occur within a buffer space.

Option:

1

2

3

4

5

6

7

8

9

10

11 12

13

14

15

16

17

18

19

21

22

23

24

25

26

28

29

30

31

32

33

34

35

36

3738

39

40

41

42

43

44

45

46

47

Buffer spaces may be positioned either longitudinally or laterally with respect to the direction of road user flow. The activity area may contain one or more lateral or longitudinal buffer spaces.

A longitudinal buffer space may be placed in advance of a work space.

The longitudinal buffer space may also be used to separate opposing road user flows that use portions of the same traffic lane, as shown in Figure 6C-26B-2.

If a longitudinal buffer space is used, the values shown in Table $\frac{6C-26B-2}{2}$ may be used to determine the length of the longitudinal buffer space.

Support:

Typically, the buffer space is formed as a traffic island and defined by channelizing devices.

When a shadow vehicle, arrow board, or changeable message sign is placed in a closed lane in advance of a work space, only the area upstream of the vehicle, arrow board, or changeable message sign constitutes the buffer space.

Option:

The lateral buffer space may be used to separate the traffic space from the work space, as shown in Figures 6C 16B-1 and 6C 26B-2, or such areas as excavations or pavement-edge drop-offs. A lateral buffer space also may be used between two travel lanes, especially those carrying opposing flows.

Guidance:

The width of a lateral buffer space should be determined by engineering judgment.

20 Option:

When work occurs on a high-volume, highly congested facility, a vehicle storage or staging space may be provided for incident response and emergency vehicles (for example, tow trucks and fire apparatus) so that these vehicles can respond quickly to road user incidents.

Figure 6B-2. Types of Tapers and Buffer Spaces

Table 6B-2. Stopping Sight Distance as a Function of Speed

Section 6C.076B.07 Termination Area

27 Support:

The termination area is the section of the highway where road users are returned to their normal driving path. The termination area extends from the downstream end of the work area to the last TTC device such as END ROAD WORK signs, if posted.

Option:

An END ROAD WORK sign, a Speed Limit sign, or other signs may be used to inform road users that they can resume normal operations.

A longitudinal buffer space may be used between the work space and the beginning of the downstream taper.

Section 6C.086B.08 Tapers

Option

Tapers may be used in both the transition and termination areas. Whenever tapers are to be used in close proximity to an interchange ramp, crossroads, curves, or other influencing factors, the length of the tapers may be adjusted.

Support:

Tapers are created by using a series of channelizing devices and/or pavement markings to move traffic out of or into the normal path. Types of tapers are shown in Figure 6C-26B-2.

Longer tapers are not necessarily better than shorter tapers (particularly in urban areas with characteristics such as short block lengths or driveways) because extended tapers tend to encourage sluggish operation and to encourage drivers to delay lane changes unnecessarily. The test concerning adequate lengths of tapers involves observation of driver performance after TTC plans are put into effect.

1	Guidance:
2	The appropriate taper length (L) should be determined using the criteria shown in Tables $\frac{6C-3}{6B-3}$ and
3	6C-4 <u>6B-4</u> .
4	The maximum distance in feet between devices in a taper should not exceed 1.0 times the speed limit in
5	mph. This text was relocated to new Section 6K.01
6	Support:
7 8	A merging taper requires the longest distance because drivers are required to merge into common road space.
9	Guidance:
10 11 12	A merging taper should be long enough to enable merging drivers to have adequate advance warning and sufficient length to adjust their speeds and merge into an adjacent lane before the downstream end of the transition.
13	Support:
14 15 16	A shifting taper is used when a lateral shift is needed. When more space is available, a longer than minimum taper distance can be beneficial. Changes in alignment can also be accomplished by using horizontal curves designed for normal highway speeds.
17	Guidance:
18	A shifting taper should have a length of approximately $1/2$ L (see Tables $6C-36B-3$ and $6C-46B-4$).
19	Support:
20 21 22	A shoulder taper might be beneficial on a high-speed roadway where shoulders are part of the activity area and are closed, or when improved shoulders might be mistaken as a driving lane. In these instances, the same type, but abbreviated, closure procedures used on a normal portion of the roadway can be used.
23	Guidance:
24 25 26	If used, shoulder tapers should have a length of approximately $1/3$ L (see Tables $\frac{6C-3}{6B-3}$ and $\frac{6C-4}{6B-4}$). If a shoulder is used as a travel lane, either through practice or during a TTC activity, a normal merging or shifting taper should be used.
27	Support:
28 29	A downstream taper might be useful in termination areas to provide a visual cue to the driver that access is available back into the original lane or path that was closed.
30	Guidance:
31 32	If used, a downstream taper should have a minimum length of 50 feet and a maximum length of 100 feet with devices placed at a spacing of approximately 20 feet.
33	Support:
34 35	The one-lane, two-way taper is used in advance of an activity area that occupies part of a two-way roadway in such a way that a portion of the road is used alternately by traffic in each direction.
36	Guidance:
37 38 39 40	Traffic should be controlled by a flagger or temporary traffic control signal (if sight distance is limited), or a STOP or YIELD sign. Deleted; redundant with Chapter 3E A short taper having a minimum length of 50 feet and a maximum length of 100 feet with channelizing devices at approximately 20-foot spacing should be used to guide traffic into the one-lane section, and a downstream taper should be used to guide traffic back
41	into their original lane. Edited to improve accuracy
42	Support:
43	An example of a one-lane, two-way traffic taper is shown in Figure 6C-36B-3.
44	Figure 6B-3. Example of a One-Lane, Two-Way Traffic Taper
45	Table 6B-3. Taper Length Criteria for Temporary Traffic Control Zones
46	Table 6B-4. Formulas for Determining Taper Length

1	Support:
2	A detour is a temporary rerouting of road users onto an existing highway in order to avoid a TTC zone.
3	Guidance:
4 5	Detours should be clearly signed over their entire length so that road users can easily use existing highways to return to the original highway.
6	Support:
7 8	A diversion is a temporary rerouting of road users onto a temporary highway or alignment placed around the work area.
9 10	Section 6C.10 One-Lane, Two-Way Traffic Control This text was relocated to new Section 6E.01
11 12	Section 6C.11 Flagger Method of One-Lane, Two-Way Traffic Control This text was relocated to new Section 6E.02
13 14	Section 6C.12 Flag Transfer Method of One-Lane, Two-Way Traffic Control This text was relocated to new Section 6E.03
15 16	Section 6C.13 Pilot Car Method of One-Lane, Two-Way Traffic Control This text was relocated to new Section 6E.04
17 18	Section 6C.14 Temporary Traffic Control Signal Method of One-Lane, Two-Way Traffic Control This text was relocated to new Section 6E.05
19 20 21	Section 6C.15 Stop or Yield Control Method of One Lane, Two Way Traffic Control This text was relocated to new Section 6E.06

2 <u>Section 6C.01 Pedestrian and Worker Safety – General</u>

3 Standard:

The various TTC provisions for pedestrian and worker safety set forth in Part 6 shall be applied by knowledgeable (for example, trained and/or certified) persons after appropriate evaluation and engineering judgment. This text was relocated from existing Section 6D.01

Section 6D.016C.02 Pedestrian Considerations

Support:

A wide range of pedestrians might be affected by TTC zones, including the young, elderly, and people with disabilities such as hearing, visual, or mobility. These pPedestrians need a clearly delineated and usable travel path. Considerations for pedestrians with disabilities are addressed in Section $6D_{6C}.0203$.

Standard:

The various TTC provisions for pedestrian and worker safety set forth in Part 6 shall be applied by knowledgeable (for example, trained and/or certified) persons after appropriate evaluation and engineering judgment. This text was relocated to new Section 6C.01

Guidance: Standard changed to Guidance and edited to improve consistency

<u>Prior to closing a Advance notification of sidewalk, closures shall be provided by the maintaining agency should advise users of the future closure.</u>

Standard:

If the TTC zone affects the movement of pedestrians, adequate pedestrian access and walkways shall be provided. If the TTC zone affects an accessible and detectable pedestrian facility, the accessibility and detectability shall be maintained along the alternate pedestrian route. Deleted; redundant with new Section 6N.04

Option:

If establishing or maintaining an alternate pedestrian route is not feasible during the project, an alternate means of providing for pedestrians may be used, such as adding free bus service around the project or assigning someone the responsibility to assist pedestrians with disabilities through the project limits.

If an existing pedestrian route is impacted by a short-duration or short term work zone that is attended with project personnel, establishing an alternate pedestrian route may not be necessary if the work can be stopped and pedestrians can navigate the work zone. Pedestrians may be delayed for a short period of time for project personnel to move equipment and material to facilitate passage. Work zone personnel may also provide assistance to the pedestrian as necessary. Added to improve accuracy

Support:

It must be recognized that pPedestrians are reluctant to retrace their steps to a prior intersection for a crossing or to add distance or out-of-the-way travel to a destination. Edited to improve accuracy This is especially true for site roadways open to public travel where pedestrians will seek the shortest route, e.g., from a site building to their parked vehicle. Added to improve consistency

Guidance:

The following three items should be considered when planning for pedestrians in TTC zones:

- A. Pedestrians should not be led into conflicts with vehicles, equipment, and operations.
- B. Pedestrians should not be led into conflicts with vehicles moving through or around the worksite.
- C. Pedestrians should be provided with a convenient and accessible path that replicates as nearly as practical the most desirable characteristics of the existing sidewalk(s) or footpath(s).

A pedestrian route should not be severed and/or moved for non-construction activities such as parking for vehicles and equipment.

Consideration should be made to separate pedestrian movements from both worksite activity and vehicular traffic. Unless an acceptable route that does not involve crossing the roadway can be provided, pedestrians should be appropriately directed with advance signing that encourages them to cross to the

opposite side of the roadway. In urban and suburban areas with high vehicular traffic volumes, these signs should be placed at intersections (rather than midblock locations) so that pedestrians are not confronted with midblock worksites that will induce them to attempt skirting the worksite or making a midblock crossing.

<u>Due to the likelihood of high pedestrian presence in site roadways open to public travel, TTC zones</u> <u>should be designed to minimize conflicts between vehicular and pedestrian movements.</u> Added to improve

consistency

Support:

Figures 6H6P-28 and 6H6P-29 show typical TTC device usage and techniques for pedestrian movement through work zones.

Guidance:

To accommodate the needs of pedestrians, including those with disabilities, the following considerations should be addressed when temporary pedestrian pathways in TTC zones are designed or modified:

- A. Provisions for continuity of accessible paths for pedestrians should be incorporated into the TTC plan.
- B. Access to transit stops should be maintained.
- C. A smooth, continuous hard surface should be provided throughout the entire length of the temporary pedestrian facility. There should be no curbs or abrupt changes in grade or terrain that could cause tripping or be a barrier to wheelchair use. The geometry and alignment of the facility should meet the applicable requirements of the "U.S. Department of Justice 2010 ADA Standards for Accessible Design, September 15, 2010 and Code of Federal Regulations. Title 28, Parts 35 and 36. Americans with Disabilities Act of 1990 Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" (see Section 1A.1105).
- D. The width of the existing pedestrian facility should be provided for the temporary facility if practical. Traffic control devices and other construction materials and features should not intrude into the usable width of the sidewalk, temporary pathway, or other pedestrian facility. When it is not possible to maintain a minimum width of 60 inches throughout the entire length of the pedestrian pathway, a 60 x 60-inch passing space should be provided at least every 200 feet to allow individuals in wheelchairs to pass.
- E. Blocked routes, alternate crossings, and sign and signal information should be communicated to pedestrians with visual disabilities by providing devices such as audible information devices, accessible pedestrian signals, or barriers and channelizing devices that are detectable to the pedestrians traveling with the aid of a long cane or who have lowhave vision disabilities. Where pedestrian traffic is detoured to a TTC signal, engineering judgment should be used to determine if pedestrian signals or accessible pedestrian signals should be considered for crossings along an alternate route.
- F. When channelization is used to delineate a pedestrian pathway, a continuous detectable edging should be provided throughout the length of the facility such that pedestrians using a long cane can follow it. These detectable edgings should comply with the provisions of Section 6F6M.7404.
- G. Signs and other devices mounted lower than 7 feet above the temporary pedestrian pathway should not project more than 4 inches into accessible pedestrian facilities.

Option:

Whenever it is feasible, closing off the worksite from pedestrian intrusion may be preferable to channelizing pedestrian traffic along the site with TTC devices.

Guidance:

Fencing should not create sight distance restrictions for road users. Fences should not be constructed of materials that would be hazardous if impacted by vehicles. Wooden railing, fencing, and similar systems placed immediately adjacent to motor vehicle traffic should not be used as substitutes for crashworthy temporary traffic barriers.

Ballast for TTC devices should be kept to the minimum amount needed and should be mounted low to prevent penetration of the vehicle windshield.

Movement by work vehicles and equipment across designated pedestrian paths should be minimized and, when necessary, should be controlled by flaggers or other TTC. Edited to improve accuracy Staging or

Notice of Proposed Amendments – Part 6

Page 532 of 781

December 2020

stopping of work vehicles or equipment along the side of pedestrian paths should be avoided, since it encourages movement of workers, equipment, and materials across the pedestrian path.

Access to the work space by workers and equipment across pedestrian walkways should be minimized because the access often creates unacceptable changes in grade, and rough or muddy terrain, and pedestrians will tend to avoid these areas by attempting non-intersection crossings where no curb ramps are available.

Option:

A canopied walkway may be used to protect pedestrians from falling debris, and to provide a covered passage for pedestrians.

Guidance:

Covered walkways should be sturdily constructed and adequately lighted for nighttime use.

When pedestrian and vehicle paths are rerouted to a closer proximity to each other, consideration should be given to separating them by a temporary traffic barrier.

If a temporary traffic barrier is used to shield pedestrians, it should be designed to accommodate site conditions.

Support:

Depending on the possible vehicular speed and angle of impact, temporary traffic barriers might deflect upon impact by an errant vehicle. Guidance for locating and designing temporary traffic barriers can be found in Chapter 9 of AASHTO's "Roadside Design Guide" (see Section 1A.1105).

Standard:

Short intermittent segments of temporary traffic barrier shall not be used because they nullify the containment and redirective capabilities of the temporary traffic barrier, improve the potential for serious injury both to vehicle occupants and pedestrians, and encourage the presence of blunt, leading ends. This text was relocated to new Section 6M.02. All upstream leading ends that are present shall be appropriately flared or protected with properly installed and maintained erashworthy cushions. Deleted; redundant with new Section 6M.02 Adjacent temporary traffic barrier segments shall be properly connected in order to provide the overall strength required for the temporary traffic barrier to perform properly. This text was relocated to new Section 6M.02

Normal vertical curbing shall not be used as a substitute for temporary traffic barriers when temporary traffic barriers are needed.

Option:

Temporary traffic barriers or longitudinal channelizing devices may be used to discourage pedestrians from unauthorized movements into the work space. They may also be used to inhibit conflicts with vehicular traffic by minimizing the possibility of midblock crossings.

Support:

A major concern for pedestrians is urban and suburban building construction encroaching onto the contiguous sidewalks, which forces pedestrians off the curb into direct conflict with moving vehicles. Edited to improve consistency

Guidance:

If a significant potential exists for vehicle incursions into the pedestrian path, pedestrians should be rerouted or temporary traffic barriers should be installed.

Support:

TTC devices, <u>jersey temporary concrete</u> barriers, and wood or chain link fencing with a continuous detectable edging can satisfactorily delineate a pedestrian path. **Edited to improve accuracy**

44 Guidance:

Tape, rope, or plastic chain strung between devices are not detectable, and are therefore not accessible to and usable by individuals with disabilities. Such items do not comply with the design standards in the "Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" (see Section 1A.05), and should not be used as a control for pedestrian movements. Edited to improve accuracy

In general, pedestrian routes should be preserved in urban and commercial suburban areas. Alternative routing should be discouraged.

The highway agency in charge of the TTC zone should regularly inspect the activity area so that effective pedestrian TTC is maintained.

Section 6D.026C.03 Accessibility Considerations

Support:

Additional information on the design and construction of accessible temporary facilities is found in publications listed in Section 1A.1105 (see Publications 12, 38, 39, and 42).

9 Guidance:

Adequate provisions should be made for pedestrians with disabilities. The extent of pedestrian needs for such provisions should be determined through engineering judgment or by the individual responsible for each TTC zone situation. The sequence of the sentences has been rearranged

Standard:

When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility. Where pedestrians with visual disabilities normally use the closed sidewalk, a A barrier that is detectable by a person with a visual disability traveling with the aid of a long cane shall be placed across the full width of the closed sidewalk. Edited to improve accuracy

Support:

Maintaining a detectable, channelized pedestrian route is much more useful to pedestrians who have visual disabilities than closing a walkway and providing audible directions to an alternate route involving additional crossings and a return to the original route. Braille is not useful in conveying such information because it is difficult to find. Audible instructions might be provided, but the extra distance and additional street crossings might add complexity to a trip.

Guidance:

Because printed signs and surface delineation are not usable by pedestrians with visual disabilities, blocked routes, alternate crossings, and sign and signal information should be communicated to pedestrians with visual disabilities by providing audible information devices, accessible pedestrian signals, and barriers and channelizing devices that are detectable to pedestrians traveling with the aid of a long cane or who have low vision disabilities.

Support:

The most desirable way to provide information to pedestrians with visual disabilities that is equivalent to visual signing for notification of sidewalk closures is a speech message provided by an audible information device. Devices that provide speech messages in response to passive pedestrian actuation are the most desirable. Other devices that continuously emit a message, or that emit a message in response to use of a pushbutton, are also acceptable. Signing information can also be transmitted to personal receivers, but currently such receivers are not likely to be carried or used by pedestrians with visual disabilities in TTC zones. Audible information devices might not be needed if detectable channelizing devices make an alternate route of travel evident to pedestrians with visual disabilities.

Guidance:

If a pushbutton is used to provide equivalent TTC information to pedestrians with visual disabilities, the pushbutton should be equipped with a locator tone to notify pedestrians with visual disabilities that a special accommodation is available, and to help them locate the pushbutton.

Section 6D.036C.04 Worker Safety Considerations

45 Support:

Equally as important as the safety of road users traveling through the TTC zone is the safety of workers. TTC zones present temporary and constantly changing conditions that are unexpected by the road user. This creates an even higher degree of vulnerability for workers on or near the roadway.

Maintaining TTC zones with road user flow inhibited as little as possible, and using TTC devices that get the road user's' attention and provide positive direction are of particular importance. Likewise, equipment and vehicles moving within the activity area create a risk to workers on foot. When possible, the separation of moving equipment and construction vehicles from workers on foot provides the operator of these vehicles with a greater separation clearance and improved sight lines to minimize exposure to the hazards of moving vehicles and equipment.

Guidance:

The following are the key elements of worker safety and TTC management that should be considered to improve worker safety:

- A. Training—all workers should be trained on how to work next to motor vehicle traffic in a way that minimizes their vulnerability. Workers having specific TTC responsibilities should be trained in TTC techniques, device usage, and placement.
- B. Temporary Traffic Barriers—temporary traffic barriers should be placed along the work space depending on factors such as lateral clearance of workers from adjacent traffic, speed of traffic, duration and type of operations, time of day, and volume of traffic.
- C. Speed Reduction—reducing the speed of vehicular traffic, mainly through regulatory speed zoning, funneling, lane reduction, or the use of uniformed law enforcement officers or flaggers, should be considered.
- D. Activity Area—operations entering and departing the work space, and within the work space, should be planned to minimize backing maneuvers by construction vehicles and equipment to minimize the risk of runover and backover accidents planning the internal work activity area to minimize backing up maneuvers of construction vehicles should be considered to minimize the exposure to risk. Edited to improve clarity
- E. Worker Safety Planning—a trained person designated by the employer should conduct a basic hazard assessment for the worksite and job classifications required in the activity area. This safety professional should determine whether engineering, administrative, or personal protection measures should be implemented. This plan should be in accordance with the Occupational Safety and Health Act of 1970, as amended, "General Duty Clause" Section 5(a)(1) Public Law 91-596, 84 Stat. 1590, December 29, 1970, as amended, and with the requirement to assess worker risk exposures for each job site and job classification, as per 29 CFR 1926.20 (b)(2) of "Occupational Safety and Health Administration Regulations, General Safety and Health Provisions" (see Section 1A. 1105).

Standard:

All workers, including emergency responders, within the right-of-way who are exposed either to traffic (vehicles using the highway for purposes of travel) or to work vehicles and construction equipment within the TTC zone shall wear high-visibility safety apparel that meets the Performance Class 2 or 3 requirements of the ANSI/ISEA 107-2004 publication entitled "American National Standard for High-Visibility Safety Apparel and Headwear" (see Section 1A.11), or equivalent-revisions, and labeled as meeting the ANSI 107-2004 standard performance for Class 2 or 3 risk-exposure, except as provided in Paragraph 5. A person designated by the employer to be responsible for worker safety shall make the selection of the appropriate class of garment. This text was relocated to new Section 6C.05 and combined with text from existing Section 6E.02

Option:

Emergency and incident responders and law enforcement personnel within the TTC zone may wear high-visibility safety apparel that meets the performance requirements of the ANSI/ISEA 207-2006 publication-entitled "American National Standard for High-Visibility Public Safety Vests" (see Section 1A.11), or equivalent revisions, and labeled as ANSI 207-2006, in lieu of ANSI/ISEA 107-2004 apparel. This text was relocated to new Section 6C.05

Standard:

When uniformed law enforcement personnel are used to direct traffic, to investigate crashes, or tohandle lane closures, obstructed roadways, and disasters, high-visibility safety apparel as described in this Section shall be worn by the law enforcement personnel. This text was relocated to new Section 6C.05 Except as provided in Paragraph 8, firefighters or other emergency responders working within the right-of-way shall wear high-visibility safety apparel as described in this Section. This text was relocated to new Section 6C.05

Option:

Firefighters or other emergency responders working within the right of way and engaged in emergency operations that directly expose them to flame, fire, heat, and/or hazardous materials may wear retroreflective turn out gear that is specified and regulated by other organizations, such as the National Fire Protection Association. This text was relocated to new Section 6C.05

The following are additional elements of TTC management that may be considered to improve worker safety:

- A. Shadow Vehicle—in the case of mobile and constantly moving operations, such as pothole patching and striping operations, a shadow vehicle, equipped with appropriate lights and warning signs, may be used to protect the workers from impacts by errant vehicles. The shadow vehicle may be equipped with a rear-mounted impact attenuator.
- B. Road Closure—if alternate routes are available to handle road users, the road may be closed temporarily. This may also to facilitate project completion and thus further reduce worker vulnerability. Edited to improve accuracy
- C. Law Enforcement Use—in highly vulnerable work situations, particularly those of relatively short duration, law enforcement units may be stationed to heighten the awareness of passing vehicular traffic and to improve safety through the TTC zone.
- D. Lighting—for nighttime work, the TTC zone and approaches may be lighted.
- E. Special Devices—these include rumble strips, changeable message signs, hazard identification beacons, flags, and warning lights. Intrusion warning devices may be used to alert workers to the approach of errant vehicles.

Support:

Judicious use of the special devices described in Item E in Paragraph 94 might be helpful for certain difficult TTC situations, but misuse or overuse of special devices or techniques might lessen their effectiveness.

Section 6E.026C.05 <u>High-Visibility Safety Apparel</u> This text was relocated from existing Section 6E.02 and incorporates text from existing Section 6D.03 to improve consistency

Standard:

For daytime and nighttime activity, flaggers all workers, including emergency responders, within the right-of-way who are exposed either to traffic (vehicles using the highway for purposes of travel) or to work vehicles and construction equipment within the TTC zone shall wear high-visibility safety apparel that meets the Performance Class 2 or 3 requirements of the ANSI/ISEA 107–20042015 publication entitled "American National Standard for High-Visibility Safety Apparel and Headwear" (see Section 1A.1105), or equivalent revisions, and labeled as meeting the ANSI 107–2004 standard performance for Class 2 or 3 risk exposure except as provided in Paragraph 4. A person designated by the employer to be responsible for worker safety shall make the selection of the appropriate class of garment. Edited to incorporate text from existing Section 6D.03 and to improve consistency

The apparel background (outer) material color shall be fluorescent orange-red, fluorescent yellow-green, or a combination of the two as defined in the ANSI standard. The retroreflective material shall be orange, yellow, white, silver, yellow-green, or a fluorescent version of these colors, and shall be visible at a minimum distance of 1,000 feet. The retroreflective safety apparel shall be designed to clearly identify the wearer as a person. Edited to improve consistency

46 Guidance:

For nighttime activity, high visibility safety apparel that meets the Performance Class 3 requirements of the ANSI/ISEA 107–2004 publication entitled "American National Standard for High-Visibility Apparel and Headwear" (see Section 1A.11) and labeled as meeting the ANSI 107–2004 standard performance for Class 3-risk exposure should be considered for flagger wear. Relocated below

When uniformed law enforcement officers personnel are used to direct traffic within a TTC zone, to investigate crashes, or to handle lane closures, obstructed roadways, and disasters, they shall wear high-visibility safety apparel as described in this Section shall be worn by the law enforcement personnel. Edited to incorporate text from existing Section 6D.03 and to improve consistency

Option:

In lieu of ANSI/ISEA 107-2004 apparel, Emergency and incident responders and law enforcement personnel within the TTC zone may wear high-visibility safety apparel that meets the performance requirements of the ANSI/ISEA 207-2006 publication entitled "American National Standard for High-Visibility Public Safety Vests" (see Section 1A.1105), or equivalent revisions, and labeled as ANSI 207-2006, in lieu of ANSI/ISEA 107-2004 apparel. Edited to incorporate text from existing Section 6D.03 and to improve accuracy

Standard:

Except as provided in Paragraph <u>86</u>, firefighters or other emergency responders working within the right-of-way shall wear high-visibility safety apparel as described in this Section. This text was relocated from existing Section 6D.03

Option:

Firefighters or other emergency responders working within the right-of-way and engaged in emergency operations that directly expose them to flame, fire, heat, and/or hazardous materials may wear retroreflective turn-out gear that is specified and regulated by other organizations, such as the National Fire Protection Association. This text was relocated from existing Section 6D.03

Guidance:

For <u>flagger wear during</u> nighttime activity, high-visibility safety apparel that meets the Performance Class 3 requirements of the ANSI/ISEA 107–2004-2015 publication entitled "American National Standard for High-Visibility Apparel and Headwear" (see Section 1A.<u>1105</u>), or equivalent revision, and labeled as meeting the ANSI 107-2004-2015 standard performance for Class 3 risk exposure should be considered worn for flagger wear.

Relocated from above and edited to improve consistency

4

5

6

7

8

9

10

11

12

13

14

19

20

21

22

23

24

2526

272829

30

32

33

34

35

3637

38

39

40

41

42

43

44

45

46

47

48

49

Section 6E.016D.01 Qualifications for Flaggers

3 Guidance:

Because flaggers are responsible for public safety and make the greatest number of contacts with the public of all highway workers, they should be trained in <u>safeproper</u> traffic control practices and public contact techniques. Flaggers should be able to satisfactorily demonstrate the following abilities:

- A. Ability to receive and communicate specific instructions clearly, firmly, and courteously;
- B. Ability to move and maneuver quickly in order to avoid danger from errant vehicles;
- C. Ability to control signaling devices (such as paddles and flags) in order to provide clear and positive guidance to drivers approaching a TTC zone in frequently changing situations;
- D. Ability to understand and apply <u>safeproper</u> traffic control practices, sometimes in stressful or emergency situations; and
- E. Ability to recognize dangerous traffic situations and warn workers in sufficient time to avoid injury. Edited to improve accuracy
- 15 Section 6E.02 High-Visibility Safety Apparel This text was relocated to new Section 6C.05
- Section 6E.036D.02 Hand-Signaling Devices STOP/SLOW Paddle for Hand-Signaling Text from existing Section 6E.03 was divided into new Sections 6D.02, 6D.03, and 6D.04
- 18 Guidance:

The STOP/SLOW paddle should be the primary and preferred hand-signaling device because the STOP/SLOW paddle gives road users more positive guidance than red flags. Use of flags should be limited to emergency situations. This text was relocated to new Section 6D.03

Standard:

The STOP/SLOW paddle (W20-8) shall have an octagonal shape on a rigid handle. STOP/SLOW paddles shall be at least 18 inches wide with letters at least 6 inches high. The STOP (R1-1) face shall have white letters and a white border on a red background. The SLOW (W20-8) face shall have black letters and a black border on an orange background. When used at night, the STOP/SLOW paddle shall be retroreflectorized. Deleted; redundant with the "Standard Highway Signs and Markings" book Option

A STOP/STOP or a SLOW/SLOW paddle may be used in certain situations (see Section 6D.05), provided the device meets the size and shape requirements for the STOP/SLOW paddle. Added to improve flexibility

31 Guidance:

The STOP/SLOW paddle should be fabricated from light semi-rigid material.

Support:

The optimum method of displaying a STOP or SLOW message is to place the STOP/SLOW paddle on a rigid staff that is tall enough that when the end of the staff is resting on the ground, the message is high enough to be seen by approaching or stopped traffic.

Option:

The STOP/SLOW paddle may be modified to improve conspicuity by incorporating either white or red flashing lights on the STOP face, and either white or yellow flashing lights on the SLOW face. The flashing lights may be arranged in any of the following patterns:

- A. Two white or red lights, one centered vertically above and one centered vertically below the STOP legend; and/or two white or yellow lights, one centered vertically above and one centered vertically below the SLOW legend;
- B. Two white or red lights, one centered horizontally on each side of the STOP legend; and/or two white or yellow lights, one centered horizontally on each side of the SLOW legend;
- C. One white or red light centered below the STOP legend; and/or one white or yellow light centered below the SLOW legend;
- D. A series of eight or more small white or red lights no larger than 1/4 inch in diameter along the outer edge of the paddle, arranged in an octagonal pattern at the eight corners of the border of the STOP

face; and/or a series of eight or more small white or yellow lights no larger than 1/4 inch in diameter along the outer edge of the paddle, arranged in a diamond pattern along the border of the SLOW face; or

E. A series of white lights forming the shapes of the letters in the legend.

Standard:

If flashing lights are used on the STOP face of the paddle, their colors shall be all white or all red. If flashing lights are used on the SLOW face of the paddle, their colors shall be all white or all yellow.

If more than eight flashing lights are used, the lights shall be arranged such that they clearly convey the octagonal shape of the STOP face of the paddle and/or the diamond shape of the SLOW face of the paddle.

If flashing lights are used on the STOP/SLOW paddle, the flash rate shall be at least 50, but not more than 60, flashes per minute.

Section 6D.03 Flag for Hand-Signaling Text from existing Section 6E.03 was divided into new Sections 6D.02, 6D.03, and 6D.04

15 Guidance:

Use of flags should be limited to emergency situations. This text was relocated from existing Section 6E.03

Standard:

Flags, when used, shall be red or fluorescent orange/_red in color, shall be a minimum of 24 inches square, and shall be securely fastened to a staff that is approximately 36 inches in length. Edited to reflect Official Interpretation 6(09)-001(I)

22 Guidance:

The free edge of a flag should be weighted so the flag will hang vertically, even in heavy winds.

Standard:

When used at nighttime, flags shall be retroreflectorized red or fluorescent orange-red. Edited to reflect Official Interpretation 6(09)-001(I)

Section 6D.04 Flashlight for Hand-Signaling Text from existing Section 6E.03 was relocated into new Sections 6D.02, 6D.03, and 6D.04

Option:

When flagging in an emergency situation at night in a non-illuminated flagger station, a flagger may use a flashlight with a red glow cone to supplement the STOP/SLOW paddle or flag.

Standard:

When a flashlight is used for flagging in an emergency situation at night in a non-illuminated flagger station, the flagger shall hold the flashlight in the left hand, shall hold the paddle or flag in the right hand as shown in Figure 6E-36D-1, and shall use the flashlight in the following manner to control approaching road users:

- A. To inform road users to stop, the flagger shall hold the flashlight with the left arm extended and pointed down toward the ground, and then shall slowly wave the flashlight in front of the body in a slow arc from left to right such that the arc reaches no farther than 45 degrees from vertical.
- B. To inform road users to proceed, the flagger shall point the flashlight at the vehicle's bumper, slowly aim the flashlight toward the open lane, then hold the flashlight in that position. The flagger shall not wave the flashlight.
- C. To alert or slow traffic, the flagger shall point the flashlight toward oncoming traffic and quickly wave the flashlight in a figure eight motion.

Figure 6D-1. Use of Hand-Signaling Devices by Flaggers

Section 6E.04 Automated Flagger Assistance Devices This text was relocated to new Section 6L.02

- 1 Section 6E.05 STOP/SLOW Automated Flagger Assistance Devices
 has been relocated to new Section 6L.03
- 3 Section 6E.06 Red/Yellow Lens Automated Flagger Assistance Devices
 4 Section has been relocated to new Section 6L.04
 - Section 6E.076D.05 Flagger Procedures
- 6 Support:

The use of paddles and flags by flaggers is illustrated in Figure 6E-36D-1.

Standard:

Flaggers shall use a STOP/SLOW paddle, a flag, or an Automated Flagger Assistance Device (AFAD) (see Sections 6L.02 through 6L.04) to control road users approaching a TTC zone. The use of hand movements alone without a paddle, flag, or AFAD to control road users shall be prohibited when controlling traffic in a one-lane two-way operation except when the control is provided by for law enforcement personnel or emergency responders at incident scenes as described in Section 6L6O.01 or provided by uniformed law enforcement officers. Edited to reflect Official Interpretation 6(09)-16(1)

The following methods of signaling with a paddles shall be used: Edited to improve accuracy

- A. To stop road users, the flagger shall face road users and aim the STOP paddle face toward road users in a stationary position with the arm extended horizontally away from the body. The free arm shall be held with the palm of the hand above shoulder level toward approaching traffic.
- B. To direct stopped road users to proceed, the flagger shall face road users with the SLOW paddle face aimed toward road users in a stationary position with the arm extended horizontally away from the body. The flagger shall motion with the free hand for road users to proceed.
- C. To alert or slow traffic, the flagger shall face road users with the SLOW paddle face aimed toward road users in a stationary position with the arm extended horizontally away from the body.

Option:

To further alert or slow traffic, the flagger holding the SLOW paddle face toward road users may motion up and down with the free hand, palm down.

Standard:

The following methods of signaling with a flag shall be used:

- A. To stop road users, the flagger shall face road users and extend the flag staff horizontally across the road users' lane in a stationary position so that the full area of the flag is visibly hanging below the staff. The free arm shall be held with the palm of the hand above shoulder level toward approaching traffic.
- B. To direct stopped road users to proceed, the flagger shall face road users with the flag and arm lowered from the view of the road users, and shall motion with the free hand for road users to proceed. Flags shall not be used to signal road users to proceed.
- C. To alert or slow traffic, the flagger shall face road users and slowly wave the flag in a sweeping motion of the extended arm from shoulder level to straight down without raising the arm above a horizontal position. The flagger shall keep the free hand down.

Guidance:

The flagger should stand either on the shoulder adjacent to the road user being controlled or in the closed lane prior to stopping road users. A flagger should only stand in the lane being used by moving road users after road users have stopped. The flagger should be clearly visible to the first approaching road user at all times. The flagger also should be visible to other road users. The flagger should be stationed sufficiently in advance of the workers to warn them (for example, with audible warning devices such as horns or whistles) of approaching danger by out-of-control vehicles. The flagger should stand alone, away from other workers, work vehicles, or equipment.

Option:

In certain conditions, it may be more appropriate for a flagger to use a STOP/STOP or a SLOW/SLOW paddle to convey the appropriate message to approaching road users and avoid confusing those that are approaching the operation from the opposing direction. Added to improve flexibility and consistent with new Section 6D.02

Option:

1

2

3

5

6 7

8

9

10

11

12

13

14 15

16

17

18 19

20

21

22

23

24

25

26

27

28

At spot lane closures where adequate sight distance is available for the reasonably safe handling of traffic, the use of one flagger may be sufficient.

Guidance:

When a single flagger is used, the flagger should be stationed on the shoulder opposite the spot lane closure or work space, or in a position where good visibility and traffic control can be maintained at all times. Deleted; redundant with new Section 6E.02

Section 6E.086D.06 Flagger Stations

Standard: Guidance: Standard changed to Guidance

Flagger stations shall should be located such that approaching road users will have sufficient distance to stop at an intended stopping point.

Option:

The distances shown in Table 6E-16D-1, which provides information regarding the stopping sight distance as a function of speed, may be used for the location of a flagger station. These distances may be increased for downgrades and other conditions that affect stopping distance.

Guidance:

Flagger stations should be located such that an errant vehicle has additional space to stop without entering the work space. The flagger should identify an escape route that can be used to avoid being struck by an errant vehicle.

Standard:

Except in emergency situations, flagger stations shall be preceded by an advance warning sign or signs. Except in emergency situations, flagger stations shall be illuminated when flagging is used at night. Edited to improve accuracy

Table 6D-1. Stopping Sight Distance as a Function of Speed

1 CHAPTER 6E. ONE-LANE, TWO-WAY TRAFFIC CONTROL 2 New Chapter with text from existing Sections 6C.10 through 6C.15 3 Section 6C.106E.01 One-Lane, Two-Way Traffic Control – General 4 **Standard:** 5 Except as provided in Paragraph 54, when traffic in both directions must use a single lane for a limited distance, movements from each end shall be coordinated. 6 7 Guidance: 8 Provisions should be made for alternate one-way movement through the constricted section via methods 9 such as flagger control, a flag transfer, a pilot car, traffic control signals, or stop or yield control. 10 Control points at each end should be chosen to permit easy passing of opposing lanes of vehicles. 11 If traffic on the affected one lane roadway is not visible from one end to the other, then flagging 12 procedures, a pilot car with a flagger used as described in Section 6C.13, or a traffic control signal should be used to control opposing traffic flows. Deleted; redundant with other Sections 13 14 Option: 15 If the work space on a low-volume street or road is short and road users from both directions are able to see the traffic approaching from the opposite direction through and beyond the worksite, the movement of 16 traffic through a one-lane, two-way constriction may be self-regulating. 17 Section 6C.116E.02 Flagger Method-of One-Lane, Two-Way Traffic Control Title edited to 18 19 reflect new Chapter 20 Guidance: 21 Except as provided in Paragraph 2, traffic should be controlled by a flagger at each end of a constricted 22 section of roadway. One of the flaggers should be designated as the coordinator. To provide coordination of 23 the control of the traffic, the flaggers should be able to communicate with each other orally, electronically, or 24 with manual signals. These manual signals should not be mistaken for flagging signals. 25 Option: 26 When a one-lane, two-way TTC zone is short enough to allow a flagger to see from one end of the zone to 27 the other, traffic may be controlled by either a single flagger or by a flagger at each end of the section. 28 Guidance: 29 When a single flagger is used, the flagger should be stationed on the shoulder opposite the constriction or 30 work space, or in a position where good visibility and traffic control can be maintained at all times. When 31 good visibility and traffic control cannot be maintained by one flagger station, traffic should be controlled by 32 a flagger at each end of the section. Section 6C.126E.03 Flag Transfer Method of One-Lane, Two-Way Traffic Control Title edited 33 to reflect new Chapter 34 35 Support: 36 The driver of the last vehicle proceeding into the one-lane section is given a red flag (or other token) and 37 instructed to deliver it to the flagger at the other end. The opposite flagger, upon receipt of the flag, then knows that traffic can be permitted to move in the other direction. A variation of this method is to replace the 38 39 use of a flag with an official pilot car that follows the last road user vehicle proceeding through the section. 40 Guidance: 41 The flag transfer method should be employed only where the one-way traffic is confined to a relatively 42 short length of a road, usually no more than 1 mile in length. 43 Section 6C.136E.04 Pilot Car Method of One-Lane, Two-Way Traffic Control Title edited to reflect 44 new Chapter 45 Option:

46

A pilot car may be used to guide a queue of vehicles through the TTC zone or detour.

1	Guidance:
2	The pilot car should have the name of the contractor or contracting authority prominently displayed.
3	Standard:
4	The PILOT CAR FOLLOW ME (G20-4) sign (see Section 6F.58) shall be mounted on the top or on
5	the rear of the pilot vehicle (see Section 6H.37). Edited to improve consistency
6	A flagger shall be stationed on the approach to the activity area to control vehicular traffic until the
7	pilot vehicle is available. The pilot car operation shall be coordinated with flagging operations or other
8	methods of control at each end of the one lane section of the work zone.
9	If an Automated Flagger Assistance Device (AFAD) is used in pilot car operations, it shall be
10	operated by a flagger. Added to improve accuracy
11	Section 6C.146E.05 Temporary Traffic Control Signal Method of One-Lane, Two-Way Traffic Control
12	Title edited to reflect new Chapter
13	Option:
14	Traffic control signals may be used to control vehicular traffic movements in one-lane, two-way TTC
15	zones (see Figure 6H6P-12 and Chapter 4HO).
16	Section 6C.156E.06 Stop or Yield Control Method of One-Lane, Two-Way Traffic Control
17	Title edited to reflect new Chapter
18	Option:
19	STOP or YIELD signs may be used to control traffic on low-volume roads at a one-lane, two-way TTC
20	zone when drivers are able to see the other end of the one-lane, two-way operation and have sufficient
21	visibility of approaching vehicles.
22	Guidance:
23	If the STOP or YIELD sign is installed for only one direction, then the STOP or YIELD sign should face
24	road users who are driving on the side of the roadway that is closed for the work activity area.

Where the color orange is required, the fluorescent orange color may also be used.

19

20

21

22

23

24

25

26

27 28

29

30 31

32

33

34

35

36 37

38

39

40

41

42

43

44

45

46

47

48

The fluorescent version of orange provides higher conspicuity than standard orange, especially during twilight.

Option:

Existing warning signs that are still applicable may remain in place. This text was relocated to new Section 6H.01

In order to maintain the systematic use of yellow or fluorescent yellow green backgrounds for pedestrian, bicycle, and school warning signs in a jurisdiction, the yellow or fluorescent yellow green background for pedestrian, bicycle, and school warning signs may be used in TTC zones. Deleted; redundant with new Section 6H.01

Standard orange flags, flashing beacons, or flashing warning lights may be used in conjunction with signs. Edited to improve consistency with Part 2

Standard:

When standard orange flags or flashing warning lights are used in conjunction with signs, they shall not block the sign face.

Except as provided in Section 2A.1107, the sizes for TTC signs and plaques shall be as shown in Tables 6F-16G-1, 6H-1, and 6I-1. The sizes in the minimum column shall only be used on low-volume rural roads, local streets, or roadways where the 85th-percentile operating speed or posted speed limit is 30 mph or less than 35 mph. Edited to improve consistency

Option:

The dimensions of signs and plaques shown in Tables 6F-1 6G-1, 6H-1, and 6I-1 may be increased wherever necessary for greater legibility or emphasis.

Standard: Guidance: Standard changed to Guidance

Deviations from standard sizes as prescribed in this Manual shall be in 6-inch increments.

Support:

Sign design details are contained in the "Standard Highway Signs and Markings" book (see Section 1A.1105).

Section 2A.0604 contains additional information regarding the design of signs, including an Option allowing the development of special word message signs if a standard word message or symbol sign is not available to convey the necessary regulatory, warning, or guidance information.

Notice of Proposed Amendments – Part 6

Standard:

1

2

3

4

5

6

10

14 15

16

18

19

20

21

22

2324

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40 41

42.

43

44

45

46

47

48

All signs used at night shall be either retroreflective with a material that has a smooth, sealed outer surface or illuminated to show the same shape and similar color both day and night. Edited to improve consistency

The requirement for sign illumination shall not be considered to be satisfied by street, highway, or strobe lighting.

- 7 Option:
- 8 Sign illumination may be either internal or external.
- 9 Signs may be made of rigid or flexible material.

Section 6F.0302 Sign Placement

- 11 Guidance:
- 12 Signs should be located on the right-hand side of the roadway unless otherwise provided in this Manual.
- 13 Option:

Where special emphasis is needed, signs may be placed on both the left-hand and right-hand sides of the roadway. Signs mounted on portable supports may be placed within the roadway itself. Signs may also be mounted on or above barricades.

17 Support:

The provisions of this Section regarding mounting height apply unless otherwise provided for a particular sign elsewhere in this Manual.

Standard:

The minimum height, measured vertically from the bottom of the sign to the elevation of the near edge of the pavement, of signs installed at the side of the road in rural areas shall be 5 feet (see Figure 6F-1).

The minimum height, measured vertically from the bottom of the sign to the top of the curb, or in the absence of curb, measured vertically from the bottom of the sign to the elevation of the near edge of the traveled way, of signs installed at the side of the road in business, commercial, or residential areas where parking or pedestrian movements are likely to occur, or where the view of the sign might be obstructed, shall be 7 feet (see Figure 6F-1).

The minimum height, measured vertically from the bottom of the sign to the sidewalk, of signs installed above sidewalks shall be 7 feet.

The bottom of a sign mounted on a barricade, or other portable support, shall be at least 1 foot above the traveled way. Relocated from below

Option:

The height to the bottom of a secondary sign mounted below another sign may be 1 foot less than the height provided in Paragraphs 4 through 6.

Guidance:

Neither portable nor permanent sign supports should be located on sidewalks, bicycle facilities, or areas designated for pedestrian or bicycle traffic. If the bottom of a secondary sign that is mounted below another sign is mounted lower than 7 feet above a pedestrian sidewalk or pathway (see Section 6D.02), the secondary sign should not project more than 4 inches into the pedestrian facility. Deleted; redundant with Part 2

Standard:

Where it has been determined that the accommodation of pedestrians with disabilities is necessary, s_Signs shall be mounted and placed in accordance with Section 3074.4 of the "2010 ADA Standards for Accessible Design the "Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" (see Section 1A.1105). Edited to improve accuracy

Signs mounted on barricades and barricade/sign combinations shall be crashworthy. Deleted; redundant with Section 6A.04

Guidance:

1 Except as provided in Paragraph 12, signs mounted on portable sign supports that do not meet the 2 minimum mounting heights provided in Paragraphs 4 through 6Part 2 should not be used for a duration of 3 more than 3 days. Edited to improve consistency 4 Option: 5 The R9-8 through R9-11a series, R11 series, W1-6 through W1-8 series, M4-10, E5-1, or other similar 6 type signs (see Figures 6F 36G-1, 6F 46H-1, and 6F 56I-1) may be used on portable sign supports that do not 7 meet the minimum mounting heights provided in Paragraphs 4 through 6 Part 2 for longer than 3 days. Edited 8 to improve consistency 9 Support: 10 Methods of mounting signs other than on posts are illustrated in Figure 6F-2. 11 12 Signs mounted on Type 3 Barricades should not cover more than 50 percent of the top two rails or 33 13 percent of the total area of the three rails. 14 **Standard:** 15 Signs and sign supports used together shall be crashworthy. Edited to improve clarity Where large signs having an area exceeding 50 square feet are installed on multiple breakaway posts, the 16 clearance from the ground to the bottom of the sign shall be at least 7 feet. 17 18 The bottom of a sign mounted on a barricade, or other portable support, shall be at least 1 foot-19 above the traveled way. Relocated to above 20 Option: 21 For mobile operations, a sign may be mounted on a work vehicle, a shadow vehicle, or a trailer stationed 22 in advance of the TTC zone or moving along with it. 23 Support: 24 If alterations are made to specific traffic control device supports that have been successfully crash tested-25 in accordance with NCHRP Report 350, the altered supports might not be considered to be crashworthy. Deleted to improve clarity 26 Figure 6F-1. Height and Lateral Location of Signs – Typical Installations 27 28 Figure 6F-2. Methods of Mounting Signs Other Than on Posts 29 Section 6F.0403 Sign Maintenance 30 Guidance: 31 Signs should be properly maintained for cleanliness, visibility, retroreflectivity, and correct positioning. 32 Edited to improve consistency with Part 2. 33 Signs that have lost significant legibility should be promptly replaced. Support: 35 36

34

37

Section 2A.9821 contains information regarding the retroreflectivity of signs, including the signs that are used in TTC zones.

2	Section 6F.056G.01 Regulatory Sign Authority
3	Support:
4 5	Regulatory signs such as those shown in Figure 6F-36G-1 inform road users of traffic laws or regulations and indicate the applicability of legal requirements that would not otherwise be apparent.
6	Standard:
7 8	Regulatory signs shall be authorized by the public agency or official having jurisdiction and shall conform with Chapter 2B.
9	Section 6F.066G.02 Regulatory Sign Design
10	Standard:
11 12	TTC regulatory signs shall comply with the Standards for regulatory signs presented in Part 2 and in the FHWA's "Standard Highway Signs and Markings" book (see Section 1A.1105).
13	Support: Deleted; redundant with Part 2
14 15	Regulatory signs are generally rectangular with a black legend and border on a white background. Exceptions include the STOP, YIELD, DO NOT ENTER, WRONG WAY, and ONE WAY signs.
16	Option: Deleted; redundant with Part 2
17	The ONE WAY sign may be either a horizontal or vertical rectangular sign.
18	Table 6G-1. Temporary Traffic Control Zone Regulatory Sign and Plaque Sizes
19	Figure 6G-1. Regulatory Signs and Plaques in Temporary Traffic Control Zones
20	Section 6F.076G.03 Regulatory Sign Applications
21	Standard:
22 23 24 25	If a TTC zone requires regulatory measures different from those existing, the existing permanent regulatory devices shall be removed or covered and superseded by the appropriate temporary regulatory signs. This change shall be made in compliance with applicable ordinances or statutes of the jurisdiction.
26	Section 6F.086G.04 ROAD (STREET) CLOSED Sign (R11-2)
27	Guidance:
28 29 30 31	The ROAD (STREET) CLOSED (R11-2) sign (see Figure 6F-36G-1) should be used when the roadway is closed to all road users except contractors' equipment or officially authorized vehicles. The R11-2 sign should be accompanied by appropriate warning and detour signing. Option:
32 33	The words BRIDGE OUT (or BRIDGE CLOSED) may be substituted for ROAD (STREET) CLOSED where applicable.
34	Guidance:
35 36	The ROAD (STREET) CLOSED sign should be installed at or near the center of the roadway on or above a Type 3 Barricade that closes the roadway (see Section 6F.686K.07).
37	Standard:
38	The ROAD (STREET) CLOSED sign shall not be used where road user flow is maintained through
39 40	the TTC zone with a reduced number of lanes on the existing roadway or where the actual closure is some distance beyond the sign.
41	Section 6F.096G.05 Local Traffic Only Signs (R11-3a, R11-4)
42	Guidance:
43	The Local Traffic Only signs (see Figure $\frac{6F-36G-1}{}$) should be used where road user flow detours to avoid
44 45	a closure some distance beyond the sign, but where local road users can use the roadway to the point of closure. These signs should be accompanied by appropriate warning and detour signing.

Page 547 of 781

December 2020

Notice of Proposed Amendments – Part 6

CHAPTER 6G. TTC ZONE REGULATORY SIGNS

- 1 In rural applications, the Local Traffic Only sign should have the legend ROAD CLOSED XX MILES 2 AHEAD, LOCAL TRAFFIC ONLY (R11-3a).
- 3 Option:

7

12

13

14

- In urban areas, the legend ROAD (STREET) CLOSED TO THRU TRAFFIC (R11-4) or ROAD CLOSED, LOCAL TRAFFIC ONLY may be used.
 - In urban areas, a word message that includes the name of an intersecting street name or well-known destination may be substituted for the words XX MILES AHEAD on the R11-3a sign where applicable.
- The words BRIDGE OUT (or BRIDGE CLOSED) may be substituted for the words ROAD (STREET)
 CLOSED on the R11-3a or R11-4 sign where applicable.
- 10 Section 6F.10 6G.06 Weight Limit Signs (R12-1, R12-2, R12-5)
- 11 Standard:
 - A Weight Limit sign (see Figure 6F-36G-1), which shows the gross weight or axle weight that is permitted on the roadway or bridge, shall be consistent with State or local regulations and shall not be installed without the approval of the authority having jurisdiction over the highway.
- When weight restrictions are imposed because of the activity in a TTC zone, a marked detour shall be provided for vehicles weighing more than the posted limit.
- 17 Section 6F.116G.07 STAY IN LANE Signs (R4-9, R4-9a)
- 18 Option:
- A STAY IN LANE (R4-9) sign (see Figure 6F-36G-1) may be used where a multi-lane shift has been incorporated as part of the TTC on a highway to direct road users around road work that occupies part of the roadway on a multi-lane highway.
- 22 Guidance:
- 23 <u>A STAY IN LANE TO MERGE POINT (R4-9a) (see Figure 6G-1) should be used during late merge</u> 24 operations to use all available lanes until the merge point is reached.
- 25 Section 6F.126G.08 Work Zone and Higher Fines Signs and Plaques
- 26 Option:

27

28

29

31

32

33

- A WORK ZONE (G20-5aP) plaque (see Figure 6F-36G-1) may be mounted above a Speed Limit sign to emphasize that a reduced speed limit is in effect within a TTC zone. An END WORK ZONE SPEED LIMIT (R2-12) sign (see Figure 6F-36G-1) may be installed at the downstream end of the reduced speed limit zone.
- 30 Guidance:
 - A BEGIN HIGHER FINES ZONE (R2-10) sign (see Figure 6F-36G-1) should be installed at or near the upstream end beginning of a work zone where increased fines are imposed for traffic violations, and an END HIGHER FINES ZONE (R2-11) sign (see Figure 6F-36G-1) should be installed at or near the downstream end of the work TTC zone. Edited to improve consistency
- 35 Option:
- Alternate legends such as BEGIN (or END) DOUBLE FINES ZONE may also be used for the R2-10 and R2-11 signs.
- A FINES HIGHER, FINES DOUBLE, or \$XX FINE plaque (see Section 2B.1727 and Figure 6F.36G-1) may be mounted below the Speed Limit sign if increased fines are imposed for traffic violations within the TTC zone.
- Individual signs and plaques for work zone speed limits and higher fines may be combined into a single sign or may be displayed as an assembly of signs and plaques.
- 43 Section 6F.136G.09 PEDESTRIAN CROSSWALK Sign (R9-8)
- 44 Option:
- The PEDESTRIAN CROSSWALK (R9-8) sign (see Figure 6F-36G-1) may be used to indicate where a temporary crosswalk has been established.

Standard:

 If a temporary crosswalk is established, it shall be accessible to pedestrians with disabilities in accordance with Section 6D.026C.03.

Section 6F.146G.10 SIDEWALK CLOSED Signs (R9-9, R9-10, R9-11, R9-11a)

5 Guidance:

SIDEWALK CLOSED signs (see Figure 6F-36G-1) should be used where pedestrian flow is restricted. Bicycle/Pedestrian Detour (M4-9a) signs or Pedestrian Detour (M4-9b) signs should be used where pedestrian flow is rerouted (see Section 6F.5961.02).

The SIDEWALK CLOSED (R9-9) sign should be installed at the beginning of the closed sidewalk, at the intersections preceding the closed sidewalk, and elsewhere along the closed sidewalk as needed.

The SIDEWALK CLOSED, (ARROW) USE OTHER SIDE (R9-10) sign should be installed at the beginning of the restricted sidewalk when a parallel sidewalk exists on the other side of the roadway.

The SIDEWALK CLOSED AHEAD, (ARROW) CROSS HERE (R9-11) sign should be used to indicate to pedestrians that sidewalks beyond the sign are closed and to direct them to open crosswalks, sidewalks, or other travel paths.

The SIDEWALK CLOSED, (ARROW) CROSS HERE (R9-11a) sign should be installed just beyond the point to which pedestrians are being redirected.

Support:

These signs are typically mounted on a detectable barricade to encourage compliance and to communicate with pedestrians that the sidewalk is closed. Printed signs are not useful to many pedestrians with visual disabilities. A barrier or barricade detectable by a person with a visual disability is sufficient to indicate that a sidewalk is closed. If the barrier is continuous with detectable channelizing devices for an alternate route, accessible signing might not be necessary. An audible information device is needed when the detectable barricade or barrier for an alternate channelized route is not continuous.

Deleted to improve consistency with new Section 6C.03

Section 6G.11 TURN OFF 2-WAY RADIO AND CELLPHONE (RXX-X) Sign Added Section to improve consistency

Standard:

The TURN OFF 2-WAY RADIO AND CELL PHONE (RXX-X) sign (see Figure 6G-1) shall be used to require road users to turn off mobile radio transmitters and cellular telephones where blasting operations occur.

32 Support:

See Section 6H.25 for the full sequence of signs for blasting zones and the specific requirements for location of this regulatory sign.

35 Section 6F.156G.12 Special Other Regulatory Signs Edited to improve consistency

36 Option:

Special rRegulatory word message signs other than those classified and specified in this Manual and the "Standard Highways Signs and Markings" book (see Section 1A.05) may be developed and may be used based on engineering judgment consistent with regulatory requirements to aid the enforcement of other laws or regulations in TTC zones. Edited to improve consistency with paragraph 2 in existing Section 2B.02

41 Guidance:

Special regulatory signs should comply with the general requirements of color, shape, and alphabet size and series. The sign message should be brief, legible, and clear.

1	CHAPTER 6H. TTC ZONE WARNING SIGNS
2	Section 6F.166H.01 Warning Sign Function, Design, and Application
3	Support:
4 5	TTC zone warning signs (see Figure 6F 46H-1) notify road users of specific situations or conditions on or adjacent to a roadway that might not otherwise be apparent.
6	Table 6H-1. Temporary Traffic Control Zone Warning Sign and Plaque Sizes
7	Figure 6H-1. Warning Signs and Plaques in Temporary Traffic Control Zones
8	Standard:
9 10	TTC warning signs shall comply with the Standards for warning signs presented in Part 2 and in FHWA's "Standard Highway Signs and Markings" book (see Section 1A.1105).
11	Except as provided in Paragraph 3 the Option below, TTC warning signs shall be diamond-shaped
12 13	with a black legend and border on an orange background, except for the <u>Grade Crossing Advance</u> <u>Warning (W10-1 sign)</u> , which shall have a black legend and border on a yellow background, and except
14	for signs that are required or recommended in Parts 2 or 7 to have fluorescent yellow-green
15	backgrounds. Edited to improve consistency
16	Option:
17	Warning signs that are required or recommended in Parts 2 or 7 to have a fluorescent yellow-green
18	background may have that color background in TTC zones. Added to improve consistency
19 20	Existing warning signs with a yellow background that are still applicable may remain in place. This text was relocated from existing Section 6F.02 and edited to improve clarity
21	Warning signs used for TTC incident management situations may have a black legend and border on a
22	fluorescent pink background.
23 24	Mounting or space considerations may justify a change from the standard diamond shape to a rectangular shape. Edited to improve accuracy
25 26	In emergencies, available warning signs having yellow backgrounds may be used if signs with orange or fluorescent pink backgrounds are not at hand.
27	Guidance:
28 29 30	Where roadway or road user conditions require greater emphasis, larger than standard size warning signs should be used, with the symbol or legend enlarged approximately in proportion to the outside dimensions.
31 32	Where any part of the roadway is obstructed or closed by work activities or incidents, advance warning signs should be installed to alert road users well in advance of these obstructions or restrictions.
33 34	Where road users include pedestrians, the provision of supplemental audible information or detectable barriers or barricades should be considered provided for people with visual disabilities.
35	Support:
36 37	Detectable barriers or barricades communicate very clearly to pedestrians who have visual disabilities that they can no longer proceed in the direction that they are traveling.
38	Option:
39	Advance warning signs may be used singly or in combination.
40 41	Where distances are not displayed on warning signs as part of the message, a supplemental plaque with the distance legend may be mounted immediately below the sign on the same support.
42 43	Section 6F.176H.02 Position of Advance Warning Signs Guidance:

45

46

47

Where highway conditions permit, warning signs should be placed in advance of the <u>transition and</u> <u>activity areas TTC zone</u> at varying distances depending on roadway type, condition, and posted speed. Table

6C-16B-1 contains information regarding the spacing of advance warning signs. Where a series of two or

more advance warning signs is used, the closest sign to the <u>transition and activity areas</u> should be

1 placed approximately 100 feet for low-speed urban streets to 1,000 feet or more for freeways and 2 *expressways.* Edited to improve clarity 3 Where multiple advance warning signs are needed on the approach to a transition and activity area TTC 4 zone, the ROAD WORK AHEAD (W20-1) sign should be the first advance warning sign encountered by road users. Edited to improve clarity 5 6 Support: 7 Various conditions, such as limited sight distance or obstructions that might require a driver to reduce 8 speed or stop, might require additional advance warning signs. 9 Option: 10 As an alternative to a specific distance on advance warning signs, the word AHEAD may be used. 11 Support: 12 At TTC zones on lightly-traveled roads, all of the advance warning signs prescribed for major 13 construction might not be needed. 14 Option: 15 Utility work, maintenance, or minor construction can occur within the TTC zone limits of a major 16 construction project, and additional warning signs may be needed. 17 Guidance: 18 Utility, maintenance, and minor construction signing and TTC should be coordinated with appropriate 19 authorities so that road users are not confused or misled by the additional TTC devices. 20 Section 6F.186H.03 ROAD (STREET) WORK Sign (W20-1) 21 Guidance: 22 The ROAD (STREET) WORK (W20-1) sign (see Figure 6F 46H-1), which serves as a general warning of 23 obstructions or restrictions, should be located in advance of the work space or any detour, on the road where 24 the work is taking place. 25 Where traffic can enter a TTC zone from a crossroad or a major (high-volume) driveway, an advance 26 warning sign should be used on the crossroad or major driveway. 27 **Standard:** 28 The ROAD (STREET) WORK (W20-1) sign shall have the legend ROAD (STREET) WORK, XX FEET, XX MILES, or AHEAD. Deleted; redundant with the "Standard Highway Signs and Markings" 29 30 book and the new Option below 31 Option: 32 The legend STREET may be substituted for ROAD and the distance legend may be either XX FEET, XX 33 MILES, or AHEAD. Standard changed to Option 34 Section 6F.196H.04 DETOUR Sign (W20-2) 35 Guidance: 36 37 a different roadway or route. 38

The DETOUR (W20-2) sign (see Figure $\frac{6F-46H-1}{}$) should be used in advance of a road user detour over

Standard:

39 The DETOUR sign shall have the legend DETOUR, XX FEET, XX MILES, or AHEAD. Deleted; 40 redundant with the "Standard Highway Signs and Markings" book and the new Option below

41 Option:

42

The distance legend may be either XX FEET, XX MILES, or AHEAD. Standard changed to Option

- 43 Section 6F.206H.05 ROAD (STREET) CLOSED Sign (W20-3)
- 44 Guidance:
- 45 The ROAD (STREET) CLOSED (W20-3) sign (see Figure 6F-46H-1) should be used in advance of the 46 point where a highway is closed to all road users, or to all but local road users.

- 1 **Standard:** 2 The ROAD (STREET) CLOSED sign shall have the legend ROAD (STREET) CLOSED, XX FEET, XX MILES, or AHEAD. Deleted; redundant with the "Standard Highway Signs and Markings" book 3 4 and the new Option below 5 Option: 6 The legend STREET may be substituted for ROAD and the distance legend may be either XX FEET, XX MILES, or AHEAD. Standard changed to Option 7 8 Section 6F.216H.06 ONE LANE ROAD Sign (W20-4) 9 Standard: 10 The ONE LANE ROAD (W20-4) sign (see Figure 6F-46H-1) shall be used only in advance of that 11 point where motor vehicle traffic in both directions must use a common single lane (see Section 12 6C.106E.01). It shall have the legend ONE LANE ROAD, XX FEET, XX MILES, or AHEAD. Deleted; redundant with the "Standard Highway Signs and Markings" book and the new Option below 13 14 Option: 15 The distance legend may be either XX FEET, XX MILES, or AHEAD. Standard changed to Option Section 6F.226H.07 Lane(s) Closed Signs (W20-5, W20-5a, and W9-3) The text in existing 16 Section 6F.23 was incorporated into this Section 17 18 **Standard:** 19 The Lane(s) Closed sign (see Figure 6F-46H-1) shall be used in advance of that point where one or 20 more through lanes of a multi-lane roadway are closed.
- For a single lane closure, the Lane Closed (W20-5) sign (see Figure 6F-46H-1) shall have use the legend RIGHT (LEFT) LANE CLOSED, XX FEET, XX MILES, or AHEAD. Where two adjacent lanes are closed, the W20-5a sign (see Figure 6F-46H-1) shall have use the legend XX RIGHT (LEFT)
- 24 LANES CLOSED, XX FEET, XX MILES, or AHEAD. Edited to improve consistency
- 25 Option:
- 26 The distance legend may be either XX FEET, XX MILES, or AHEAD. Standard changed to Option
- 27 Section 6F.23 CENTER LANE CLOSED AHEAD Sign (W9-3) The text in this section was incorporated into new Section 6H.07
- 29 Guidance:
- The CENTER LANE CLOSED AHEAD (W9-3) sign (see Figure 6F 46H-1) should be used in advance of that point where work occupies the center lane(s) and approaching motor vehicle traffic is directed to the right or left of the work zone in the center lane.
- 33 Section 6F.246H.08 Lane Ends Signs (W4-2, W9-2a)
- 34 Option:
- The Lane Ends (W4-2) symbol sign (see Figure 6F 46H-1) may be used to warn drivers of the reduction in the number of lanes for moving motor vehicle traffic in the direction of travel on a multi-lane roadway.
- 37 *Guidance*:
- The MERGE HERE TAKE TURNS (W9-2a) (see Figure 6H-1) should be used to identify the merge point and to take turns merging during Late Merge applications (see Figure 6N-1).
- 40 Section 6F.256H.09 ON RAMP Plaque (W13-4P)
- 41 Guidance:
- When work is being done on a ramp, but the ramp remains open, the ON RAMP (W13-4P) plaque (see Figure 6F-46H-1) should be used to supplement the advance ROAD WORK sign.
- 44 Section 6F.266H.10 RAMP NARROWS Sign (W5-4)
- 45 Guidance:

1 The RAMP NARROWS (W5-4) sign (see Figure 6F-46H-1) should be used in advance of the point where work on a ramp reduces the normal width of the ramp along a part or all of the ramp.

Section 6F.276H.11 SLOW TRAFFIC AHEAD Sign (W23-1)

4 Option:

3

9

11

12

13

The SLOW TRAFFIC AHEAD (W23-1) sign (see Figure 6F-46H-1) may be used on a shadow vehicle, usually mounted on the rear of the most upstream shadow vehicle, along with other appropriate signs for mobile operations to warn of slow moving work vehicles. A ROAD WORK (W20-1) sign may also be used with the SLOW TRAFFIC AHEAD sign.

Section 6F.286H.12 EXIT OPEN and EXIT CLOSED Signs (E5-2, E5-2a)

10 Option:

An EXIT OPEN (E5-2) or EXIT CLOSED (E5-2a) sign (see Figure 6F-56H-1) may be used to supplement other warning signs where work is being conducted in the vicinity of an exit ramp and where the exit maneuver for vehicular traffic using the ramp is different from the normal condition.

14 Guidance:

- When an exit ramp is closed, an EXIT CLOSED sign panel with a black legend and border on an orange
- 16 background should be placed diagonally across the interchange/intersection guide signs. This text was
- 17 relocated to new Section 6I.03
- 18 Section 6F.296H.13 EXIT ONLY Sign (E5-3)
- 19 Option:
- An EXIT ONLY (E5-3) sign (see Figure 6F-56H-1) may be used to supplement other warning signs where work is being conducted in the vicinity of an exit ramp and where the exit maneuver for vehicular traffic using the ramp is different from the normal condition.

23 Section 6F.306H.14 NEW TRAFFIC PATTERN AHEAD Sign (W23-2)

24 Option:

25

26

27

A NEW TRAFFIC PATTERN AHEAD (W23-2) sign (see Figure 6F 46H-1) may be used on the approach to an intersection or along a section of roadway to provide advance warning of a change in traffic patterns, such as revised lane usage, roadway geometry, or signal phasing.

28 Guidance:

To retain its effectiveness, the W23-2 sign should be displayed for up to 2 weeks, and then it should be covered or removed until it is needed again.

31 Section 6F.316H.15 Flagger Signs (W20-7, W20-7a)

32 Guidance:

The Flagger (W20-7) symbol sign (see Figure 6F-46H-1) should be used in advance of any point where a flagger is stationed to control road users.

35 Option:

36

37

38

41

43

44

45

A distance legend may be displayed on a supplemental plaque below the Flagger sign. The sign may be used with appropriate legends or in conjunction with other warning signs, such as the BE PREPARED TO STOP (W3-4) sign (see Figure 6F 46H-1).

The FLAGGER (W20-7a) word message sign with distance legends may be substituted for the Flagger (W20-7) symbol sign.

Section 6F.326H.16 Two-Way Traffic Sign (W6-3)

42 Guidance:

When one roadway of a normally divided highway is closed, with two-way vehicular traffic maintained on the other roadway, the Two-Way Traffic (W6-3) sign (see Figure 6F-46H-1) should be used at the beginning of the two-way vehicular traffic section and at intervals to remind road users of opposing vehicular traffic.

```
Section 6F.766H.17 Opposing Lane Traffic Divider and Sign (W6-4) This Section relocated
 1
          from existing Section 6F.76 because this device was reclassified from a channelizing device
 2
         to a warning sign
 3
 4
      Standard:
 5
          The Opposing Lane Traffic Divider (W6-4) sign (see Figure 6F-46H-1) shall be an upright,
 6
      retroreflective orange-colored sign placed on a flexible support and sized at least 12 inches wide by 18
 7
      inches high. Relocated from below
 8
      Support:
 9
         The Opposing traffic IL and Traffic dDividers (W6-4) sign is intended for mounting only on a flexible
10
      support are delineation devices used as center lane dividers in a series along the center lane to separate
11
      opposing vehicular traffic on a two-lane, two-way operation. Edited to improve consistency
12
      Standard:
13
          Opposing traffic Lane Traffic dDividers signs shall not be placed across within pedestrian
14
      crossings. Edited to improve consistency
          The Opposing Traffic Lane Divider (W6-4) sign (see Figure 6F-4) shall be an upright,
15
      retroreflective orange-colored sign placed on a flexible support and sized at least 12 inches wide by 18-
16
17
      inches high. Relocated to above
      Section 6F.336H.18 Workers Signs (W21-1, W21-1a)
18
19
      Option:
20
          A Workers (W21-1) symbol sign (see Figure 6F 46H-1) may be used to alert road users of workers in or
21
      near the roadway.
22
      Guidance:
23
         In the absence of other warning devices, a Workers symbol sign should be used when workers are in the
24
      roadway.
25
      Option:
26
          The WORKERS (W21-1a) word message sign may be used as an alternate to the Workers (W21-1)
27
      symbol sign.
28
      Section 6F.346H.19 FRESH OIL (TAR) Sign (W21-2)
29
      Guidance:
30
          The FRESH OIL (TAR) (W21-2) sign (see Figure 6F-46H-1) should be used to warn road users of the
31
      surface treatment.
32
      Section 6F.356H.20 ROAD MACHINERY AHEAD Sign (W21-3)
33
      Option:
34
          The ROAD MACHINERY AHEAD (W21-3) sign (see Figure 6F-46H-1) may be used to warn of
35
      machinery operating in or adjacent to the roadway.
36
      Section 6F.366H.21 Motorized Traffic Signs (W8-6, W11-10)
37
      Option:
38
          Motorized Traffic (W8-6, W11-10) signs may be used to alert road users to locations where unexpected
39
      travel on the roadway or entries into or departures from the roadway by construction vehicles might occur.
      The TRUCK CROSSING (W8-6) word message sign may be used as an alternate to the Truck Crossing
40
      (W11-10) symbol sign (see Figure 6F 46H-1) where there is an established construction vehicle crossing of
41
42
      the roadway.
```

44

45

Support:

These locations might be relatively confined or might occur randomly over a segment of roadway.

- 1 Support:
- Shoulder Work signs (see Figure 6F-46H-1) warn of maintenance, reconstruction, or utility operations on the highway shoulder where the roadway is unobstructed.
- 4 Standard:
- The Shoulder Work sign shall have the legend SHOULDER WORK (W21-5), RIGHT (LEFT)
 SHOULDER CLOSED (W21-5a), or RIGHT (LEFT) SHOULDER CLOSED XX FT or AHEAD (W21-
- 7 **5b**).
- 8 Option:
- The Shoulder Work sign may be used in advance of the point on a non-limited access highway where there is shoulder work. It may be used singly or in combination with a ROAD WORK NEXT XX MILES or
- 11 ROAD WORK AHEAD sign.
- 12 Guidance:
- On freeways and expressways, the RIGHT (LEFT) SHOULDER CLOSED XX FT or AHEAD (W21-5b) sign followed by RIGHT (LEFT) SHOULDER CLOSED (W21-5a) sign should be used in advance of the point
- 15 where the shoulder work occurs and should be preceded by a ROAD WORK AHEAD sign.
- 16 Section 6F.386H.23 SURVEY CREW Sign (W21-6)
- 17 Guidance:
- 18 The SURVEY CREW (W21-6) sign (see Figure 6F-46H-1) should be used to warn of surveying crews
- 19 working in or adjacent to the roadway.
- 20 Section 6F.396H.24 UTILITY WORK Sign (W21-7)
- 21 Option:
- The UTILITY WORK (W21-7) sign (see Figure 6F-46H-1) may be used as an alternate to the ROAD
- 23 (STREET) WORK (W20-1) sign for utility operations on or adjacent to a highway.
- 24 Support:
- Typical examples of where the UTILITY WORK sign is used appear in Figures 6H6P-4, 6H6P-6, 6H6P-
- 26 10, 6H6P-15, 6H6P-18, 6H6P-21, 6H6P-22, 6H6P-26, and 6H6P-33.
- 27 Standard:
- 28 The UTILITY WORK sign shall carry the legend UTILITY WORK, XX FEET, XX MILES, or
- 29 AHEAD. Deleted; redundant with the "Standard Highway Signs and Markings" book and the new
- 30 Option below
- 31 Option:
- The distance legend may be either XX FEET, XX MILES, or AHEAD. Standard changed to Option
- 33 Section 6F.406H.25 Signs for Blasting Areas The text in this Section was combined from
- existing Sections 6F.40 thru 6F.43 and edited
- 35 Support:
- Radio-Frequency (RF) energy can cause the premature firing of electric detonators (blasting caps) used in
- 37 TTC zones.
- 38 **Standard:**
- Road users shall be warned to turn off mobile radio transmitters and cellular telephones where
- 40 blasting operations occur. A sequence of signs shall be prominently displayed to warn all road users of
- 41 a blasting operations and to direct operators of mobile radio equipment, including cellular telephones,
- 42 to turn off transmitters in a blasting area. These signs shall be covered or removed when there are no
- explosives in the area or the area is otherwise secured. Edited to improve consistency
- 44 Section 6F.41 BLASTING ZONE AHEAD Sign (W22-1) The text in this section was combined into new
- 45 **Section 6H.25**
- 46 Standard:

```
1
         The BLASTING ZONE AHEAD (W22-1) sign (see Figure 6F-46H-1) shall be used in advance of
 2
      any TTC zone where explosives are being used. The TURN OFF 2-WAY RADIO AND CELL PHONE
 3
     (RXX-X) and END BLASTING ZONE (W22-3) signs shall be used in sequence with this sign.
     Section 6F.42 TURN OFF 2-WAY RADIO AND CELL PHONE Sign (W22-2) The text in this
 4
 5
         section was combined into new Section 6H.25
 6
     Standard:
 7
         The TURN OFF 2-WAY RADIO AND CELL PHONE (W22-2RXX-X) sign (see Section 6G.11 and
     Figure 6F-46G-1) shall follow the BLASTING ZONE AHEAD (W22-1) sign and shall be placed at least
 8
 9
      1.000 feet before the beginning of the blasting zone.
     Section 6F.43 END BLASTING ZONE Sign (W22-3) The text in this section was combined
10
         into new Section 6H.25
11
12
     Standard:
13
         The END BLASTING ZONE (W22-3) sign (see Figure 6F-46H-1) shall be placed a minimum of
14
      1,000 feet past the blasting zone.
15
      Option:
16
         The END BLASTING ZONE sign may be placed either with or preceding the END ROAD WORK sign.
17
      Section 6F.446H.26 Shoulder Signs and Plaque (W8-4, W8-9, W8-17, and W8-17P)
18
     Option:
19
         The SOFT SHOULDER (W8-4) sign (see Figure 6F-46H-1) may be used to warn of a soft shoulder
20
      condition.
21
         The LOW SHOULDER (W8-9) sign (see Figure 6F-46H-1) may be used to warn of a shoulder condition
22
      where there is an elevation difference of 3 inches or less between the shoulder and the travel lane.
23
      Guidance:
24
         The Shoulder Drop Off (W8-17) sign (see Figure 6F-46H-1) should be used when an unprotected
25
     shoulder drop-off, adjacent to the travel lane, exceeds 3 inches in depth for a continuous length along the
      roadway, based on engineering judgment.
26
27
      Option:
28
         A SHOULDER DROP-OFF (W8-17P) supplemental plaque (see Figure 6F-46H-1) may be mounted
29
     below the W8-17 sign.
30
     Section 6F.456H.27 UNEVEN LANES Sign (W8-11)
31
      Guidance:
32
         The UNEVEN LANES (W8-11) sign (see Figure \frac{6F-4}{6H-1}) should be used during operations that create
33
      a difference in elevation between adjacent lanes that are open to travel.
34
     Section 6F.466H.28 STEEL PLATE AHEAD Sign (W8-24)
35
      Option:
36
         A STEEL PLATE AHEAD (W8-24) sign (see Figure 6F-46H-1) may be used to warn road users that the
37
     presence of a temporary steel plate(s) might make the road surface uneven and might create slippery
38
      conditions during wet weather.
     Section 6F.476H.29 NO CENTER LINE Sign (W8-12)
39
40
      Guidance:
41
         The NO CENTER LINE (W8-12) sign (see Figure 6F-46H-1) should be used when the work obliterates
42
      the center line pavement markings. This sign should be placed at the beginning of the TTC zone and repeated
43
      at 2-mile intervals in long TTC zones.
44
```

Section 6F.786J.02 contains information regarding temporary markings.

Page 556 of 781

December 2020

45

Notice of Proposed Amendments – Part 6

Section 6F.486H.30 Reverse Curve Signs (W1-4 Series)

Guidance:

1

2

3

4

5

6

7

8

9

10

11

12

13

14

16

17

18

19

20

21

22

23

24

25

26

27

28

29

34

35

36

37

38

39

40

41 42

43

44

45

46

In order to give road users advance notice of a lane shift, a Reverse Curve (W1-4, W1-4b, or W1-4c) sign (see Figure 6F-46H-1) should be used when a lane (or lanes) is being shifted to the left or right. If the design speed of the curves is 30 mph or less, a Reverse Turn (W1-3) sign should be used.

Standard:

If a Reverse Curve (or Turn) sign is used, the direction of the reverse curve (or turn) shall be appropriately illustrated. Except as provided in Paragraph 3, the number of lanes illustrated on the sign shall be the same as the number of through lanes available to road users.

Option:

Where two or more lanes are being shifted, a W1-4 (or W1-3) sign with an ALL LANES (W24-1cP) plaque (see Figure 6F-46H-1) may be used instead of a sign that illustrates the number of lanes.

Where more than three lanes are being shifted, the Reverse Curve (or Turn) sign may be rectangular.

Section 6F.496H.31 Double Reverse Curve Signs (W24-1 Series)

15 Option:

The Double Reverse Curve (W24-1, W24-1a, or W24-1b) sign (see Figure 6F-46H-1) may be used where the tangent distance between two reverse curves is less than 600 feet, thus making it difficult for a second Reverse Curve (W1-4 series) sign to be placed between the curves. If the design speed of the curves is 30 mph or less, Double Reverse Turn signs should be used.

Standard:

If a Double Reverse Curve (or Turn) sign is used, the direction of the double reverse curve (or turn) shall be appropriately illustrated. Except as provided in Paragraph 3, the number of lanes illustrated on the sign shall be the same as the number of through lanes available to road users.

Option:

Where two or more lanes are being shifted, a W24-1 (or Double Reverse Turn sign showing one lane) sign with an ALL LANES (W24-1cP) plaque (see Figure 6F-46H-1) may be used instead of a sign that illustrates the number of lanes.

Where more than three lanes are being shifted, the Double Reverse Curve (or Turn) sign may be rectangular.

- 30 Section 6F.50 Other Warning Signs This text was relocated to new Section 6H.38
- 31 Section 6F.51 Special Warning Signs This text was relocated to new Section 6H.38
- 32 Section 6F.526H.32 Advisory Speed Plaque (W13-1P)
- 33 Option:

In combination with a warning sign, an Advisory Speed (W13-1P) plaque (see Figure 6F-46H-1) may be used to indicate a recommended speed through the TTC zone.

Standard:

The Advisory Speed plaque shall not be used in conjunction with any sign other than a warning sign, nor shall it be used alone. When used with orange TTC zone signs, this plaque shall have a black legend and border on an orange background. The sign-plaque shall be at least 24 x 24 inches in size when used with a sign that is 36 x 36 inches or larger. Except in emergencies, an Advisory Speed plaque shall not be mounted until the recommended speed is determined by the highway agency. Edited to improve consistency

Support:

Warning signs with advisory speed plaques inform drivers of the recommended operating speed based on temporary conditions within a TTC zone (see Section 2C.58). Examples include narrow lanes, temporary diversion (reverse curves), lane shifts, sight distance restrictions, rough road surface, bumps, low/no shoulder,

workers on foot, work vehicles or equipment close to the open travel lane, or other conditions that indicate the need for reduced speed.

AASHTO and ITE design documents contain established engineering practices for the determination of the recommended advisory speeds for horizontal curves or locations with limited sight distance. Added to

improve consistency

Section 6F.536H.33 Supplementary Distance Plaque (W7-3aP)

Option:

3

4

5

6 7

8

9

10

11

12 13

14

15

16

17 18

21

22

23

In combination with a warning sign, a Supplementary Distance (W7-3aP) plaque (see Figure 6F 46H-1) with the legend NEXT XX MILES may be used to indicate the length of highway over which a work activity is being conducted, or over which a condition exists in the TTC zone.

In long TTC zones, Supplementary Distance plaques with the legend NEXT XX MILES may be placed in combination with warning signs at regular intervals within the zone to indicate the remaining length of highway over which the TTC work activity or condition exists.

Standard:

The Supplementary Distance plaque with the legend NEXT XX MILES shall not be used in conjunction with any sign other than a warning sign, nor shall it be used alone. When used with orange TTC zone signs, this plaque shall have a black legend and border on an orange background. The $\frac{\text{sign}}{\text{plaque}}$ shall be at least 30 x 24 inches in size when used with a sign that is 36 x 36 inches or larger.

Edited to improve consistency

20 Guidance:

When used in TTC zones, the Supplementary Distance plaque with the legend NEXT XX MILES should be placed below the initial warning sign designating that, within the approaching zone, a temporary work activity or condition exists.

24 Section 6F.546H.34 Motorcycle Plaque (W8-15P)

25 Option:

A Motorcycle (W8-15P) plaque (see Figure 6F-46H-1) may be mounted below a LOOSE GRAVEL (W8-

27 7) sign, a GROOVED PAVEMENT (W8-15) sign, a METAL BRIDGE DECK (W8-16) sign, or a STEEL

- 28 PLATE AHEAD (W8-24) sign if the warning is intended to be directed primarily to motorcyclists.
- 29 Section 6F.55 Guide Signs The text in this section was relocated to new Section 6I.01

30 Section 6F.566H.35 ROAD WORK NEXT XX MILES Sign (G20-1)

31 *Guidance:*

The ROAD WORK NEXT XX MILES (G20-1) sign (see Figure 6F-46H-1) should be installed in advance of TTC zones that are more than 2 miles in length.

34 Option:

38

39

45

46

The ROAD WORK NEXT XX MILES sign may be mounted on a Type 3 Barricade. The sign may also be used for TTC zones of shorter length.

37 Standard:

The distance displayed on the ROAD WORK NEXT XX MILES sign shall be stated to the nearest whole mile.

40 Section 6F.576H.36 END ROAD WORK Sign (G20-2)

41 Guidance:

When used, the END ROAD WORK (G20-2) sign (see Figure 6F-46H-1) should be placed near the downstream end of the termination area, as determined by engineering judgment.

44 Option:

The END ROAD WORK sign may be installed on the back of a warning sign facing the opposite direction of road users or on the back of a Type 3 Barricade.

1	Section 6F.586H.37 PILOT CAR FOLLOW ME Sign (G20-4)
2	Standard:
3 4 5	The PILOT CAR FOLLOW ME (G20-4) sign (see Figure 6F-46H-1) shall be mounted in a conspicuous position on the top or on the rear of a vehicle used for guiding one-way vehicular traffic through or around a TTC zone (see Section 6C.136E.04). Edited to improve consistency
6	Section 6F.506H.38 Other Warning Signs This text was relocated from existing Sections 6F.50
7	Option:
8	Advance warning signs may be used by themselves or with other advance warning signs.
9 10	Besides the warning signs specifically related to TTC zones, several other warning signs in Part 2 may apply in TTC zones.
11 12 13 14	Special Word message warning signs other than those classified and specified in this Manual and the "Standard Highways Signs and Markings" book (see Section 1A.1105) may be developed and used based on engineering judgment to warn of special conditions in TTC zones. Relocated from below and edited to improve consistency with paragraph 2 in existing Section 2B.02
15	Standard:
16 17	Except as provided in Sections 6F.0201 and 6H.01, other warning signs that are used in TTC zones shall have black legends and borders on an orange background.
18	Section 6F.51 Special Warning Signs This Section was combined into new Section 6H.38
19	Option:
20	Special warning signs may be used based on engineering judgment. Relocated to above
21	Guidance:
22 23 24	Special warning signs should comply with the general requirements of color, shape, and alphabet size and series. The sign message should be brief, legible, and clear.

5

6

7

8

9

10

11

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34 35

36

37

38

39

40

41 42

43

44

45

46

47

2 Section 6F.556I.01 Guide Signs - General The text in this section was relocated from existing Section 6F.55

Support:

Guide signs along highways provide road users with information to help them along their way through the TTC zone. The design of guide signs is presented in Part 2.

Guidance:

The following guide signs should be used in TTC zones as needed:

- A. Standard route markings, where temporary route changes are necessary,
- B. Directional signs and street name signs, and
- C. Special guide signs relating to the condition or work being done.

12 Standard:

If additional temporary guide signs are used in TTC zones, they shall have a black legend and border on an orange background.

Option:

Guide signs used in TTC incident management situations may have a black legend and border on a fluorescent pink background.

When <u>temporary</u> directional signs and <u>temporary</u> street name signs are used in conjunction with detour routing, these signs may have a black legend and border on an orange background. **Edited to improve consistency**

When permanent directional signs or permanent street name signs are used in conjunction with detour signing, they may have a white legend on a green background (see Section 2D.59).

Table 6I-1. Temporary Traffic Control Zone Guide Sign and Plaque Sizes

Section 6F.596I.02 <u>Detour Signs (M4-8, M4-8a, M4-8b, M4-9, M4-9a, M4-9b, M4-9c, and M4-10)</u>

Standard:

Each detour shall be adequately marked with standard temporary route signs and destination signs. Option:

Detour signs in TTC incident management situations may have a black legend and border on a fluorescent pink background.

The Detour Arrow (M4-10) sign (see Figure 6F-56I-1) may be used where a detour route has been established.

The DETOUR (M4-8) sign (see Figure 6F-56I-1) may be mounted at the top of a route sign assembly to mark a temporary route that detours from a highway, bypasses a section closed by a TTC zone, and rejoins the highway beyond the TTC zone.

Guidance:

The Detour Arrow (M4-10) sign should normally be mounted just below the ROAD CLOSED (R11-2, R11-3a, or R11-4) sign. The Detour Arrow sign should include a horizontal arrow pointed to the right or left as required.

The DETOUR (M4-9) sign (see Figure 6F 561-1) should be used for unnumbered highways, for emergency situations, for periods of short durations, or where, over relatively short distances, road users are guided along the detour and back to the desired highway without route signs.

A Street Name sign should be placed above, or the street name should be incorporated into, a DETOUR (M4-9) sign to indicate the name of the street being detoured.

Option:

The END DETOUR (M4-8a) or END (M4-8b) sign (see Figure 6F-56I-1) may be used to indicate that the detour has ended.

1	Coilman
1	Guidance:
2 3	When the END DETOUR sign is used on a numbered highway, the sign should be mounted above a route sign after the downstream end of the detour.
4	The Pedestrian/Bicycle Detour (M4-9a) sign (see Figure $\frac{6F-5}{6I-1}$) should be used where a
5	pedestrian/bicycle detour route has been established because of the closing of a pedestrian/bicycle facility to
6	through traffic.
7	Standard:
8	If used, the Pedestrian/Bicycle Detour sign shall have an arrow pointing in the appropriate
9	direction.
10	Option:
11	The arrow on a Pedestrian/Bicycle Detour sign may be on the sign face or on a supplemental plaque.
12	The Pedestrian Detour (M4-9b) sign or Bicycle Detour (M4-9c) sign (see Figure 6F-56I-1) may be used
13	where a pedestrian or bicycle detour route (not both) has been established because of the closing of the
14	pedestrian or bicycle facility to through traffic.
15	Figure 6I-1. Exit Open and Closed and Detour Signs
16	Section 6I.03 EXIT CLOSED Panel This text was relocated from existing Section 6F.28
17	Guidance:
18	When an exit ramp is closed, an EXIT CLOSED sign panel with a black legend and border on an orange
19	background should be placed diagonally across the interchange/intersection guide signs.
20	Section 6F.60 Portable Changeable Message Signs The text in this Section was relocated to new
21	Section 6L.05
22	Section 6F.61 Arrow Boards The text in this Section was relocated to new Section 6L.06
23	Section 6F.62 High-Level Warning Devices (Flag Trees) The text in this Section was relocated
24	to new Section 6L.08

CHAPTER 6J. TTC ZONE PAVEMENT MARKINGS

New Chapter with text from existing Sections 6F.77 through 6F.80

3 Section 6F.776J.01 Pavement Markings in TTC Zones

Support:

42.

Pavement markings are installed or existing markings are maintained or enhanced in TTC zones to provide road users with a clearly defined path for travel through the TTC zone in day, night, and twilight periods under both wet and dry pavement conditions.

Guidance:

The work should be planned and staged to provide for the placement and removal of the pavement markings in a way that minimizes the disruption to traffic flow approaching and through the TTC zone during the placement and removal process.

Standard:

Existing pavement markings shall be maintained in all long-term stationary (see Section 6G.026N.01) TTC zones in accordance with Chapters 3A and 3B, except as otherwise provided for temporary pavement markings in Section 6F.786J.02. Pavement markings shall match the alignment of the markings in place at both ends of the TTC zone. Pavement markings shall be placed along the entire length of any paved detour or temporary roadway prior to the detour or roadway being opened to road users.

Guidance: Standard changed to Guidance

For long-term stationary operations, pavement markings in the temporary traveled way that are no longer applicable <u>shall-should</u> be removed or obliterated as soon as practical. Pavement marking obliteration <u>shall-should</u> remove the non-applicable pavement marking material, and the obliteration method <u>shall-should</u> minimize pavement scarring.

Standard:

Painting over existing pavement markings with black paint or spraying with asphalt shall not be accepted as a substitute for removal or obliteration.

Option:

Removable, non-reflective, preformed tape that is approximately the same color as the pavement surface may be used where markings need to be covered temporarily.

Section 6F.786J.02 Temporary Markings

Support:

Temporary markings are those pavement markings or devices that are placed within TTC zones to provide road users with a clearly defined path of travel through the TTC zone when the permanent markings are either removed or obliterated during the work activities. Temporary markings are typically needed during the reconstruction of a road while it is open to traffic, such as overlays or surface treatments or where lanes are temporarily shifted on pavement that is to remain in place.

Guidance:

Unless justified based on engineering judgment, temporary pavement markings should not remain in place for more than 14 days after the application of the pavement surface treatment or the construction of the final pavement surface on new roadways or over existing pavements.

The temporary use of edge lines, channelizing lines, lane-reduction transitions, gore markings, and other longitudinal markings, and the various non-longitudinal markings (such as stop lines, railroad crossings, crosswalks, words, symbols, or arrows) should be in accordance with the State's or highway agency's policy.

Standard:

Warning signs, channelizing devices, and delineation shall be used to indicate required road user paths in TTC zones where it is not possible to provide a clear path by pavement markings.

Except as otherwise provided in this Section, all temporary pavement markings for no-passing zones shall comply with the requirements of Chapters 3A and 3B. All temporary broken-line pavement

1 markings shall use the same cycle length as permanent markings and shall have line segments that are at least 2 feet long.

Guidance:

All pavement markings and devices used to delineate road user paths should be reviewed during daytime and nighttime periods.

Option:

Half-cycle lengths with a minimum of 2-foot stripes may be used on roadways with severe curvature (see Section 3A.0604) for broken line center lines in passing zones and for lane lines.

For temporary situations of 14 days or less, for a two- or three-lane road, no-passing zones may be identified by using DO NOT PASS (R4-1), PASS WITH CARE (R4-2), and NO PASSING ZONE (W14-3) signs (see Sections 2B.2838, 2B.2939, and 2C.4552) rather than pavement markings. Also, DO NOT PASS, PASS WITH CARE, and NO PASSING ZONE signs may be used instead of pavement markings on roads with low volumes for longer periods in accordance with the State's or highway agency's policy.

Guidance:

If used, the DO NOT PASS, PASS WITH CARE, and NO PASSING ZONE signs should be placed in accordance with Sections 2B.2838, 2B.2939, and 2C.4552.

If used, the NO CENTER LINE sign should be placed in accordance with Section 6F.476H.29.

Section 6F.796J.03 Temporary Raised Pavement Markers

Option:

Retroreflective or internally illuminated raised pavement markers, or non-retroreflective raised pavement markers supplemented by retroreflective or internally illuminated markers, may be substituted for markings of other types in TTC zones.

Standard:

If used, the color and pattern of the raised pavement markers shall simulate the color and pattern of the markings for which they substitute.

If temporary raised pavement markers are used to substitute for broken line segments, a group of at least three retroreflective markers shall be equally spaced at no greater than N/8 (see Section 3B.14) 5 feet shall be installed every 40 feet. The value of N for a broken or dotted line shall equal the length of one line segment plus one gap. Edited to improve consistency

If temporary raised pavement markers are used to substitute for solid lines, the markers shall be equally spaced at no greater than N/4 10 feet, with retroreflective or internally illuminated units at a spacing no greater than N/2. 20 feet. The value of N referenced for solid lines shall equal the N for the broken or dotted lines that might be adjacent to or might extend the solid lines (see Section 3B.11). Edited to improve consistency

Option:

Temporary raised pavement markers may be used to substitute for broken line segments by using at least two retroreflective markers placed at each end of a segment of 2 to 5 feet in length, using the same cycle length as permanent markings.

Guidance:

Temporary raised pavement markers used on 2- to 5 foot segments to substitute for broken line segments should not be in place for more than 14 days unless justified by engineering judgment. Deleted; redundant with new Section 6J.02.

Raised pavement markers should be considered for use along surfaced detours or temporary roadways, and other changed or new travel-lane alignments.

Option:

Retroreflective or internally illuminated raised pavement markers, or non-retroreflective raised pavement markers supplemented by retroreflective or internally illuminated markers, may also be used in TTC zones to supplement markings as prescribed in Chapters 3A and 3B.

1	Section 6F.806J.04 Delineators
2	Option:
3	Delineators may be used in TTC zones to indicate the alignment of the roadway and to outline the
4	required vehicle path through the TTC zone. Relocated from below
5	Standard:
6	When used, delineators shall combine with or supplement other TTC devices. They shall be
7	mounted on crashworthy supports so that the reflecting unit is approximately 4 feet above the near
8	roadway edge. The standard color for delineators used along both sides of two-way streets and
9	highways and the right-hand side of one-way roadways shall be white. Delineators used along the left-
10	hand side of one-way roadways shall be yellow, and shall be in accordance with Chapter 3G. Deleted;
11	redundant with Chapter 3F
12	Guidance:
13	Spacing along roadway curves should be as set forth in Section 3FG.04 and should be such that several
14	delineators are constantly visible to the an approaching driver. Edited to improve clarity
15	Option:

Delineators may be used in TTC zones to indicate the alignment of the roadway and to outline the required vehicle path through the TTC zone. Relocated to above

2 Section 6F.636K.01 Channelizing Devices – General

Standard

Designs of various channelizing devices shall be as shown in Figure $\frac{6F-76K-1}{2}$. All channelizing devices shall be crashworthy.

Support:

The function of channelizing devices is to warn road users of conditions created by work activities in or near the roadway and to guide road users. Channelizing devices include cones, tubular markers, vertical panels, drums, barricades, and longitudinal channelizing devices.

Channelizing devices provide for smooth and gradual vehicular traffic flow from one lane to another, onto a bypass or detour, or into a narrower traveled way. They are also used to channelize vehicular traffic away from the work space, pavement drop-offs, pedestrian or shared-use paths, or opposing directions of vehicular traffic.

Standard: This text was relocated to new Section 6K.02

Devices used to channelize pedestrians shall be detectable to users of long canes and visible to persons having low vision.

Where channelizing devices are used to channelize pedestrians, there shall be continuous detectable bottom and top surfaces to be detectable to users of long canes. The bottom of the bottom surface shall be no higher than 2 inches above the ground. The top of the top surface shall be no lower than 32 inches above the ground.

Option: Deleted; redundant with Standard statement above

A gap not exceeding 2 inches between the bottom rail and the ground surface may be used to facilitate drainage.

Guidance:

Where multiple channelizing devices are aligned to form a continuous pedestrian channelizer, connection points should be smooth to optimize long cane and hand trailing. Deleted; redundant with new Guidance in Section 6K.02

The spacing between cones, tubular markers, vertical panels, drums, and barricades should not exceed a distance in feet equal to 1.0 times the speed limit in mph when used for taper channelization, and a distance in feet equal to 2.0 times the speed limit in mph when used for tangent channelization.

When channelizing devices have the potential of leading vehicular traffic out of the intended vehicular traffic space as shown in Figure 6H6P-39, the channelizing devices should be extended a distance in feet of 2.0 times the speed limit in mph beyond the downstream end of the transition area.

Option:

Warning lights (see Section 6F.836L.07) may be added to channelizing devices in areas with frequent fog, snow, or severe roadway curvature, or where visual distractions are present.

A series of sequential flashing warning lights may be placed on channelizing devices that form a merging taper in order to increase driver detection and recognition of the merging taper. Relocated from below Support:

The flashing rates and patterns for warning lights used on channelizing devices are specified in Section 6L.07. Added to improve consistency

Standard:

Warning lights shall flash when placed on channelizing devices used alone or in a cluster to warn of a condition. Except for the sequential flashing warning lights discussed in Paragraphs 12 and 13, warning lights placed on channelizing devices used in a series to channelize road users shall be steadyburn. This text was relocated to new Section 6L.07

47 Option:

A series of sequential flashing warning lights may be placed on channelizing devices that form a retaper in order to increase driver detection and recognition of the merging taper. Relocated to above	nerging
Standard:	
When used, the successive flashing of the sequential warning lights shall occur from the upst	ream
end of the merging taper to the downstream end of the merging taper in order to identify the deserbic vehicle path. Each warning light in the sequence shall be flashed at a rate of not less than 55 not than 75 times per minute. Deleted; redundant with new Section 6L.07	sired
The retroreflective material used on channelizing devices shall have a smooth, sealed outer s	urfaca
that will display a similar color day or night. Edited to improve consistency	urrace
Except as provided in Paragraph 11, information identifying the owner or manufacturer of	the
channelizing device shall not be displayed on any portion of the device that can be seen by road	
approaching the device. Added to reflect Official Interpretation 6(09)-11(I)	
Option:	
The name and telephone number of the highway agency, contractor, or supplier may be displayed non-retroreflective surface of all types of channelizing devices.	on the
Standard:	
The letters and numbers of area containing the name and telephone number shall be non-	_
retroreflective and not over 2 inches in height. Added to reflect Official Interpretation 6(09)-11(1	()
Guidance:	
Particular attention should be given to maintaining the channelizing devices to keep them clean, v	isible,
and properly positioned at all times.	
Standard: Standard changed to Guidance	
Devices that are damaged or have lost a significant amount of their retroreflectivity and effectives shall should be replaced.	iess
Figure 6K-1. Channelizing Devices	
Section 6K.02 Pedestrian Channelizing Devices New Section added to improve consister	ncy
Support:	
Pedestrian channelizing devices indicate a suitable path of pedestrian travel around or through the zone.	work_
Guidance:	
Pedestrian channelizing devices should be provided when work activities impact sidewalks or other pedestrian facilities or when the design of the temporary pedestrian facility does not otherwise includes	
accessibility features consistent with the features in the existing pedestrian facility.—	_
The pedestrian channelizing devices should be used both to close sidewalks and to delineate an al	ternate
route.	
Support:	
An example of a Pedestrian Channelizing Device is depicted in Figure 6K-2.	
Figure 6K-2. Example of Pedestrian Channelizing Device	
Standard:	
Pedestrian channelizing devices shall be crashworthy when exposed to vehicular traffic.	
Devices used to channelize pedestrians shall be detectable to users of long canes and visible to	O
persons having lowpedestrians with vision disabilities. This text was relocated from existing Sect	
6F.63 and editied	
6F.63 and editied	
6F.63 and editied When used as a sidewalk closure, the device shall cover the entire width of the sidewalk.	

- 1 ground walkway. The top edge of the bottom portion shall measure at least 8 inches above the walkway.
 2 The top of the top surfaceportion shall be no lower than 32 inches above the ground walkway. This text
- was relocated from existing Section 6F.63 and edited to improve consistency The top surface shall be
- 4 smooth to optimize hand-trailing. Both upper and lower surfaces shall share a common vertical plane.

5 Option:

6

7

8

9

10

12

14

15

17

18

19

21

22

24

2526

27

29

30

32

33

34

35

36

37

38

39

40

41

42 43 44

45

46

47

48

A continuous wall may be used as a pedestrian channelizing device.

Guidance:

When used, a continuous wall should have a lower edge no more than 2 inches above the walkway, should extend a minimum of 32 inches above the walkway, should have a common vertical face, and should have alternating, contrasting sheeting positioned 32 inches above the walkway.

11 Option:

The continuous wall may extend to any height above the 32 inch minimum.

13 *Guidance*:

When pedestrian channelizing devices are combined in a series, the gap between devices should not exceed one inch.

16 Support:

A Hand-Trailing Edge is the upper surface of the upper rail on a pedestrian channelizing device, as shown in Figure 6K-2 It is provided to allow pedestrians with vision disabilities to follow the pedestrian channelizing device with their hand. The Hand-Trailing Edge is not a weight bearing railing.

20 **Standard:**

When exposed to vehicular traffic the bottom and top surfaces of the Pedestrian Channelizing Device shall have sheeting complying with Section 6K.01 Paragraph 9.

23 **Guidance:**

When not exposed to vehicular traffic, the Pedestrian Channelizing device should have a contrasting pattern in alternating light and dark colors to provide visual contrast on the upper surface consisting of a minimum of 6 inches of sheeting or other contrasting materials. Non-retroreflective materials may be used on the pedestrian side of the Pedestrian Channelizing device.

28 Option:

The sheeting on the side of the device on the pedestrian side of the Pedestrian Channelizing device may have sheeting with a vertical orientation.

31 Support:

The contrast of the light and dark stripes on the barricade sheeting assists pedestrians with vision disabilities in following the designated detour.

See also Section 6M.04 regarding detectable edging for pedestrian channelization.

Section 6F.646K.03 Cones

Standard:

Cones (see Figure 6F-76K-1) shall be predominantly orange and shall be made of a material that can be struck without causing damage to the impacting vehicle. For daytime and low-speed roadways, cones shall be not less than 18 inches in height. When cones are used on freeways and other high-speed highways or at night on all highways, or when more conspicuous guidance is needed, cones shall be a minimum of 28 inches in height.

For night time use, cones shall be retroreflectorized or equipped with lighting devices for maximum visibility troreflectorization of cones that are 28 to 36 inches in height shall be provided by a 6-inch wide white band located 3 to 4 inches from the top of the cone and an additional 4-inch wide white band located approximately 2 inches below the 6-inch band.

Retroreflectorization of cones that are more than 36 inches in height shall be provided by horizontal, circumferential, alternating orange and white retroreflective stripes that are 4 to 6 inches wide. Each cone shall have a minimum of two orange and two white stripes with the top stripe being

orange. Any non-retroreflective spaces between the orange and white retroreflective stripes shall not exceed 3 inches in width. Edited to improve clarity

Option:

3

4

5

6

8

9

13

14

15

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36 37

38

39

40

41

43

44

Traffic cones may be used to channelize road users, divide opposing vehicular traffic lanes, divide lanes when two or more lanes are kept open in the same direction, and delineate short duration maintenance and utility work.

7 Guidance:

Steps should be taken to minimize the possibility of cones being blown over or displaced by wind or moving vehicular traffic.

10 Option:

11 Cones may be doubled up to increase their weight.

12 Support:

Some cones are constructed with bases that can be filled with ballast. Others have specially weighted bases, or weight such as sandbag rings that can be dropped over the cones and onto the base to provide added stability.

16 Guidance:

Ballast should be kept to the minimum amount needed.

Section 6F.656K.04 Tubular Markers

Standard:

Tubular markers (see Figure 6F-76K-1) shall be predominantly orange for temporary traffic control zone applications and shall be not less than 18 inches high and 2 inches wide facing road users. Edited to improve clarity They shall be made of a material that can be struck without causing damage to the impacting vehicle.

Tubular markers shall be a minimum of 28 inches in height when they are used on freeways and other high-speed highways, on all highways during nighttime, or whenever more conspicuous guidance is needed.

For nighttime use, tubular markers shall be retroreflectorized. Retroreflectorization of tubular markers that have a height of less than 42 inches shall be provided by two 3-inch wide white bands placed a maximum of 2 inches from the top with a maximum of 6 inches between the bands. Retroreflectorization of tubular markers that have a height of 42 inches or more shall be provided by four 4- to 6-inch wide alternating orange and white stripes with the top stripe being orange.

Guidance:

Tubular markers have less visible area than other devices and should be used only where space restrictions do not allow for the use of other more visible devices.

Tubular markers should be stabilized by affixing them to the pavement, by using weighted bases, or weights such as sandbag rings that can be dropped over the tubular markers and onto the base to provide added stability. Ballast should be kept to the minimum amount needed.

Option:

Tubular markers may be used effectively to divide opposing lanes of road users, divide vehicular traffic lanes when two or more lanes of moving vehicular traffic are kept open in the same direction, and to delineate the edge of a pavement drop off where space limitations do not allow the use of larger devices.

42 Standard:

A tubular marker shall be attached to the pavement to display the minimum 2-inch width to the approaching road users.

- 45 Section 6F.666K.05 Vertical Panels
- 46 Standard:

Vertical panels (see Figure 6F-76K-1) shall have retroreflective striped material that is 8 to 12 inches in width and at least 24 inches in height. They shall have alternating diagonal orange and white retroreflective stripes sloping downward at an angle of 45 degrees in the direction vehicular traffic is to pass.

Where the height of the retroreflective material on the vertical panel is 36 inches or more, a stripe width of 6 inches shall be used.

Option:

Where the height of the retroreflective material on the vertical panel is less than 36 inches, a stripe width of 4 inches may be used.

Where space is limited, vertical panels may be used to channelize vehicular traffic, divide opposing lanes, or replace barricades.

Section 6F.676K.06 Drums

Standard:

Drums (see Figure 6F-76K-1) used for road user warning or channelization shall be constructed of lightweight, deformable materials. They shall be a minimum of 36 inches in height and have at least an 18-inch minimum width regardless of orientation. Metal drums shall not be used. The markings on drums shall be horizontal, circumferential, alternating orange and white retroreflective stripes 4 to 6 inches wide. Each drum shall have a minimum of two orange and two white stripes with the top stripe being orange. Any non-retroreflectorized spaces between the horizontal orange and white stripes shall not exceed 3 inches wide. Drums shall have closed tops that will not allow collection of construction debris or other debris.

22 Support:

Drums are highly visible, have good target value, give the appearance of being formidable obstacles and, therefore, command the respect of road users. They are portable enough to be shifted from place to place within a TTC zone in order to accommodate changing conditions, but are generally used in situations where they will remain in place for a prolonged period of time.

Option:

Although drums are most commonly used to channelize or delineate road user flow, they may also be used alone or in groups to mark specific locations.

30 Guidance:

Drums should not be weighted with sand, water, or any material to the extent that would make them hazardous to road users or workers when struck. Drums used in regions susceptible to freezing should have drain holes in the bottom so that water will not accumulate and freeze causing a hazard if struck by a road user.

Standard:

Ballast shall not be placed on the top of a drum.

Section 6F.686K.07 Type 1, 2, or 3 Barricades

38 Support:

A barricade is a portable or fixed device having from one to three rails with appropriate markings and is used to control road users by closing, restricting, or delineating all or a portion of the right-of-way.

As shown in Figure 6F-76K-1, barricades are classified as Type 1, Type 2, or Type 3.

Standard:

Stripes on barricade rails shall be alternating orange and white retroreflective stripes sloping downward at an angle of 45 degrees in the direction road users are to pass. Except as provided in Paragraph 4, the stripes shall be 6 inches wide.

46 Option:

When rail lengths are less than 36 inches, 4-inch wide stripes may be used.

Standard:

The minimum length for Type 1 and Type 2 Barricades shall be 24 inches, and the minimum length for Type 3 Barricades shall be 48 inches. Each barricade rail shall be 8 to 12 inches wide. Barricades used on freeways, expressways, and other high-speed roadways shall have a minimum of 270 square inches of retroreflective area facing road users.

Guidance:

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

2223

24

25

27

28

30

31

33

34

36

37

38

40

41

Where barricades extend entirely across a roadway, the stripes should slope downward in the direction toward which road users must turn.

Where both right and left turns are provided, the barricade stripes should slope downward in both directions from the center of the barricade or barricades.

Where no turns are intended, the stripes should be positioned to slope downward toward the center of the barricade or barricades.

Barricade rails should be supported in a manner that will allow them to be seen by the road user, and in a manner that provides a stable support that is not easily blown over or displaced.

The width of the existing pedestrian facility should be provided for the temporary facility if practical. Traffic control devices and other construction materials and features should not intrude into the usable width of the sidewalk, temporary pathway, or other pedestrian facility. When it is not possible to maintain a minimum width of 60 inches throughout the entire length of the pedestrian pathway, a 60 x 60-inch passing space should be provided at least every 200 feet to allow individuals in wheelchairs to pass.

Barricade rail supports should not project into pedestrian circulation routes more than 4 inches from the support between 27 and 80 inches from the surface as described in Section 3074.4.1 of the "2010 ADA Standards for Accessible DesignAmericans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" (see Section 1A.1105). Edited to improve consistency

Option:

For Type 1 Barricades, the support may include other unstriped horizontal rails necessary to provide stability.

26 Guidance:

On high-speed expressways or in other situations where barricades may be susceptible to overturning in the wind, ballasting should be used.

29 Option:

Sandbags may be placed on the lower parts of the frame or the stays of barricades to provide the required ballast.

32 Support:

Type 1 or Type 2 Barricades are intended for use in situations where road user flow is maintained through the TTC zone.

35 Option:

Barricades may be used alone or in groups to mark a specific condition or they may be used in a series for channelizing road users.

Type 1 Barricades may be used on conventional roads or urban streets.

39 Guidance:

Type 2 or Type 3 Barricades should be used on freeways and expressways or other high-speed roadways. Type 3 Barricades should be used to close or partially close a road.

42 Option:

Type 3 Barricades used at a road closure may be placed completely across a roadway or from curb to curb.

45 Guidance:

Where provision is made for access of authorized equipment and vehicles, the responsibility for Type 3
Barricades should be assigned to a person who will provide proper closure at the end of each work day.

48 Support:

1 When a highway is legally closed but access must still be allowed for local road users, barricades usually 2 are not extended completely across the roadway. 3

Standard:

4 A sign shall be installed with the appropriate legend concerning permissible use by local road users 5 (see Section 6F.096G.05).

Guidance: Standard changed to Guidance

Adequate visibility of the barricades from both directions shall should be provided.

8 Option:

6

7

9

11

12

13

14

15 16

17

18

20

21

23

24

25

27

28

29

30

31

32

33

34

35

36 37

38

39

40

41

42

43

44

45

47

Signs may be installed on barricades (see Section 6F.036F.02).

10 Section 6F.696K.08 Direction Indicator Barricades

Standard:

The Direction Indicator Barricade (see Figure 6F-76K-1) shall consist of a One-Direction Large Arrow (W1-6) sign mounted above a diagonal striped, horizontally aligned, retroreflective rail.

The One-Direction Large Arrow (W1-6) sign shall be black on an orange background. The stripes on the bottom rail shall be alternating orange and white retroreflective stripes sloping downward at an angle of 45 degrees in the direction road users are to pass. The stripes shall be 4 inches wide. The One-Direction Large Arrow (W1-6) sign shall be 24 x 12 inches. The bottom rail shall have a length of 24 inches and a height of 8 inches.

19 Option:

> The Direction Indicator Barricade may be used in tapers, transitions, and other areas where specific directional guidance to drivers is necessary.

22 Guidance:

> If used, Direction Indicator Barricades should be used in series to direct the driver through the transition and into the intended travel lane.

Section 6F.706K.09 Temporary Traffic Barriers as Channelizing Devices

26 Support:

> Temporary traffic barriers (see Section 6M.02) are not TTC devices in themselves; however, when placed in a position identical to a line of channelizing devices and marked and/or equipped with appropriate channelization features to provide guidance and warning both day and night, they serve as TTC devices.

Standard:

Temporary traffic barriers serving as TTC devices shall comply with requirements for such devices as set forth throughout Part 6.

Temporary traffic barriers (see Section 6F.856M.02) shall not be used solely to channelize road users, but also to protect the work space. If used to channelize vehicular traffic, the temporary traffic barrier shall be supplemented with delineation, pavement markings, or channelizing devices for improved daytime and nighttime visibility.

Guidance:

Temporary traffic barriers should not be used for a merging taper except in low-speed urban areas.

When it is necessary to use a temporary traffic barrier for a merging taper in low-speed urban areas or for a constricted/restricted TTC zone, the taper length should be designed to optimize road user operations considering the available geometric conditions.

Standard:

When it is necessary to use a temporary traffic barrier for a merging taper in low-speed urban areas or for a constricted/restricted TTC zone, the taper shall be delineated using channelizing devices, and/or an edge line, and/or delineators on the barrier. Edited to improve clarify

46 Guidance:

When used for channelization, temporary traffic barriers should be of a light color for increased visibility.

Section 6F.716K.10 Longitudinal Channelizing Devices

2 Support:

1

3

4

5

6

7

8

9

10

11

12

13

14

16

17

18 19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

343536

37

38

39

40

41

42

43

45

46

47

Longitudinal channelizing devices are lightweight, deformable devices that are highly visible, have good target value, and can be connected together.

Standard:

If used singly as Type 1, 2, or 3 barricades, longitudinal channelizing devices shall comply with the general size, color, stripe pattern, retroreflectivity, and placement characteristics established for the devices described in this Chapter.

Guidance:

If used to channelize vehicular traffic at night, longitudinal channelizing devices should be supplemented with retroreflective material or delineation for improved nighttime visibility.

Option:

- Longitudinal channelizing devices may be used instead of a line of cones, drums, or barricades.
- Longitudinal channelizing devices may be hollow and filled with water as a ballast.
- Longitudinal channelizing devices may be used for pedestrian traffic control.

Standard:

If used for pedestrian traffic control, longitudinal channelizing devices shall be interlocked to delineate or channelize flow. The interlocking devices shall not have gaps that allow pedestrians to stray from the channelizing path.

Guidance:

Longitudinal channelizing devices have not met the crashworthy requirements for temporary traffic barriers and should not be used to shield obstacles or provide positive protection for pedestrians or workers.

Section 6F.726K.11 Temporary Lane Separators

Option:

Temporary lane separators may be used to channelize road users, to divide opposing vehicular traffic lanes, <u>and</u> to divide lanes when two or more lanes are open in the same direction, and to provide continuous pedestrian channelization.

Standard:

Temporary lane separators shall be crashworthy. Deleted; redundant with new Section 6K.01 Temporary lane separators shall consist of a longitudinal base component with have a maximum height of 4 inches and a maximum width of 1 foot, and The longitudinal base shall have sloping sides in order to facilitate crossover by emergency vehicles. One or more of types of channelizing devices, such as tubular markers, vertical panels, or Opposing Lane Traffic Divider (W6-4) signs mounted on flexible supports, shall be affixed to the longitudinal base. Edited to improve accuracy

Temporary lane separators may be supplemented with any of the approved channelizing devices contained in this Chapter, such as tubular markers, vertical panels, and opposing traffic lane dividers. Deleted; redundant with edited Standard above

Standard:

If appropriate eChannelizing devices are used to supplement affixed to the longitudinal base of a temporary lane separator, the channelizing devices shall be retroreflectorized to provide nighttime visibility. If channelizing devices are not used, the temporary lane separator shall contain retroreflectorization to enhance its visibility. Edited to improve clarity

44 Guidance:

A temporary lane separator should be stabilized by affixing it to the pavement in a manner suitable to its design, while allowing the unit to be <u>shifted intentionally moved</u> from place to place within the TTC zone in order to accommodate changing conditions. Edited to improve clarity

1 Temporary Lane Separators should not be used to shield obstacles or provide positive protection for 2 pedestrians or workers, because these devices have not met the crashworthy requirements for temporary 3 traffic barriers. Added to improve consistency 4 **Standard:** 5 At pedestrian crossing locations, temporary lane separators shall have an opening or be shortened 6 to provide a pathway that is at least 60 inches wide for crossing pedestrians. 7 Section 6F.736K.12 Other Channelizing Devices 8 Option: 9 Channelizing devices other than those described in this Chapter may be used in special situations based on 10 an engineering study. 11 Guidance: 12 Other channelizing devices should comply with the general size, color, stripe pattern, retroreflection, and 13 placement characteristics established for the devices described in this Chapter. Section 6F.74 Detectable Edging for Pedestrians This text was relocated to new Section 6M.04 14 Section 6F.75 Temporary Raised Islands This text was relocated to new Section 6M.03 15 Section 6F.76 Opposing Traffic Lane Divider and Sign (W6-4) This Section was relocated to 16 new Section 6H.17 because this device was reclassified from a channelizing device to a warning 17 sign 18 Section 6F.77 Pavement Markings This text was relocated to new Section 6J.01 19 Section 6F.78 Temporary Markings This text was relocated to new Section 6J.02 20 Section 6F.79 Temporary Raised Payement Markers This text was relocated to new Section 21 22 6J.03Section 6F.80 Delineators This text was relocated to new Section 6J.04 23 24

CHAPTER 6L. OTHER TTC ZONE TRAFFIC CONTROL DEVICES

2 Section 6F.846L.01 Temporary Traffic Control Signals This text was relocated from existing Section 6F.84

Standard:

1

4

5

6

7

8

9

1011

12

13

14

15

16

17

19

20

21

22

23

24

25

26 27

28

29

30

32 33

34 35

36 37

42

Temporary traffic control signals (see Section 4D. $32\underline{10}$) used to control road user movements through TTC zones and in other TTC situations shall comply with the applicable provisions of Part 4.

Support:

Temporary traffic control signals are typically used in TTC zones such as temporary haul road crossings; temporary one-way operations along a one-lane, two-way highway; temporary one-way operations on bridges, reversible lanes, and intersections.

Standard:

A temporary traffic control signal that is used to control traffic through a one-lane, two-way section of roadway shall comply with the provisions of Section 4<u>HO</u>.02.

Guidance:

Where pedestrian traffic is detoured to a temporary traffic control signal, engineering judgment should be used to determine if pedestrian signals or an accessible pedestrian signals (see Section 4E.094K.01) are needed should be provided for crossing along an alternate route. Edited to improve consistency with new Section 4K 01

18 Section 4K.01

When temporary traffic control signals are used, conflict monitors typical of traditional traffic control signal operations should be used.

Option:

Temporary traffic control signals may be portable or temporarily mounted on fixed supports.

Guidance:

Temporary traffic control signals should only be used in situations where temporary traffic control signals are preferable to other means of traffic control, such as changing the work staging or work zone size to eliminate one-way vehicular traffic movements, using flaggers to control one-way or crossing movements, using STOP or YIELD signs, and using warning devices alone.

Support:

Factors related to the design and application of temporary traffic control signals include the following:

- A. Safety and road user needs;
- 31 B. Work staging and operations;
 - C. The feasibility of using other TTC strategies (for example, flaggers, providing space for two lanes, or detouring road users, including bicyclists and pedestrians);
 - D. Sight distance restrictions;
 - E. Human factors considerations (for example, lack of driver familiarity with temporary traffic control signals);
 - F. Road-user volumes including roadway and intersection capacity;
- 38 G. Affected side streets and driveways:
- 39 H. Vehicle speeds;
- I. The placement of other TTC devices;
- 41 J. Parking;
 - K. Turning restrictions;
- 43 L. Pedestrians;
- M. The nature of adjacent land uses (such as residential or commercial);
- N. Legal authority;
- O. Signal phasing and timing requirements;
- 47 P. Full-time or part-time operation;
- 48 Q. Actuated, fixed-time, or manual operation;
- 49 R. Power failures or other emergencies;
- S. Inspection and maintenance needs;

- T. Need for detailed placement, timing, and operation records; and
- U. Operation by contractors or by others.

Although temporary traffic control signals can be mounted on trailers or lightweight portable supports, fixed supports offer superior resistance to displacement or damage by severe weather, vehicle impact, and vandalism.

Guidance:

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15 16

17 18

19

20

21

22 23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40 41

42

43

44

46

47

48

Other TTC devices should be used to supplement temporary traffic control signals, including warning and regulatory signs, pavement markings, and channelizing devices.

Temporary traffic control signals not in use should be covered or removed.

If a temporary traffic control signal is located within 1/2 mile of an adjacent traffic control signal, consideration should be given to interconnected operation.

Standard:

Temporary traffic control signals shall not be located within 200 feet of a grade crossing unless the temporary traffic control signal is provided with preemption in accordance with Section 4D.274F.18, or unless a uniformed officer or flagger is provided at the crossing to prevent vehicles from stopping within the crossing.

Section <u>6E.046L.02</u> <u>Automated Flagger Assistance Devices – General</u> This text was relocated from existing Section 6E.04

Support:

Automated Flagger Assistance Devices (AFADs) enable a flagger(s) to be positioned out of the lane of traffic and are used to control road users through temporary traffic control zones. These devices are designed to be remotely operated either by a single flagger at one end of the TTC zone or at a central location, or by separate flaggers near each device's location.

There are two types of AFADs:

- A. An AFAD (see Section 6E.056L.03) that uses a remotely controlled STOP/SLOW sign on either a trailer or a movable cart system to alternately control right-of-way.
- B. An AFAD (see Section 6E.066L.04) that uses remotely controlled red and yellow lenses and a gate arm to alternately control right-of-way.

AFADs might be appropriate for short-term and intermediate-term activities (see Section 6G.026N.01). Typical applications include TTC activities such as, but not limited to:

- A. Bridge maintenance;
- B. Haul road crossings; and
- C. Pavement patching.

Standard:

AFADs shall only be used in situations where there is only one lane of approaching traffic in the direction to be controlled.

When used at night, the AFAD location shall be illuminated in accordance with Section 6E.086D.06. *Guidance:*

AFADs should not be used for long-term stationary work (see Section 6G.026N.01).

Standard:

Because AFADs are not traffic control signals, they shall not be used as a substitute for or a replacement for a continuously operating temporary traffic control signal as described in Section 6F.846L.01.

AFADs shall meet the crashworthy performance criteria contained in Section 6F.016A.04.

45 Guidance:

If used, AFADs should be located in advance of one-lane, two-way tapers and downstream from the point where approaching traffic is to stop in response to the device.

Standard:

If used, AFADs shall be placed so that all of the signs and other items controlling traffic movement are readily visible to the driver of the initial approaching vehicle with advance warning signs alerting other approaching traffic to be prepared to stop.

If used, an AFAD shall be operated only by a flagger (see Section 6E.016D.01) who has been trained on the operation of the AFAD. The flagger(s) operating the AFAD(s) shall not leave the AFAD(s) unattended at any time while the AFAD(s) is being used.

The use of AFADs shall conform to one of the following methods:

- A. An AFAD at each end of the TTC zone (Method 1), or
- B. An AFAD at one end of the TTC zone and a flagger at the opposite end (Method 2).

Except as provided in Paragraph 14, two flaggers shall be used when using either Method 1 or Method 2.

12 Option:

1

2

3

4

5

6

7

8

9

10

11

13

14

15

16

17

19

20

21

22

23

24

25

26

27

28

29

30

31

34

35

37

38

40

41

42

43

44

45

46

47

48

A single flagger may simultaneously operate two AFADs (Method 1) or may operate a single AFAD on one end of the TTC zone while being the flagger at the opposite end of the TTC zone (Method 2) if both of the following conditions are present:

- A. The flagger has an unobstructed view of the AFAD(s), and
- B. The flagger has an unobstructed view of approaching traffic in both directions.

18 Guidance:

> When an AFAD is used, the advance warning signing should include a ROAD WORK AHEAD (W20-1) sign, a ONE LANE ROAD (W20-4) sign, and a BE PREPARED TO STOP (W3-4) sign.

Standard:

When the AFAD is not in use, the signs associated with the AFAD, both at the AFAD location and in advance, shall be removed or covered.

Guidance:

A State or local agency that elects to use AFADs should adopt a policy, based on engineering judgment, governing AFAD applications. The policy should also consider more detailed and/or more restrictive requirements for AFAD use, such as the following:

- A. Conditions applicable for the use of Method 1 and Method 2 AFAD operation,
- B. Volume criteria,
- C. Maximum distance between AFADs,
- D. Conflicting lenses/indications monitoring requirements,
- 32 E. Fail safe procedures,
- 33 F. Additional signing and pavement markings,
 - G. Application consistency,
 - H. Larger signs or lenses to increase visibility, and
- 36 I. Use of backplates.

Section 6E.056L.03 STOP/SLOW Automated Flagger Assistance Devices The text was

relocated from existing Section 6E.05

39 **Standard:**

> A STOP/SLOW Automated Flagger Assistance Device (AFAD) (see Section 6E.04) shall include a STOP/SLOW sign that alternately displays the STOP (R1-1) face and the SLOW (W20-8) face of a STOP/SLOW paddle (see Figure 6E-16L-1).

The AFAD's STOP/SLOW sign shall have an octagonal shape, shall be fabricated of rigid material, and shall be mounted with the bottom of the sign a minimum of 6 feet above the pavement on an appropriate support. The size of the STOP/SLOW sign shall be at least 24 x 24 inches with letters at least 8 inches high. The background of the STOP face shall be red with white letters and border. The background of the SLOW face shall be diamond shaped and orange with black letters and border.

Both faces of the STOP/SLOW sign shall be retroreflectorized.

The AFAD's STOP/SLOW sign shall have a means to positively lock, engage, or otherwise maintain the sign assembly in a stable condition when set in the STOP or SLOW position.

The AFAD's STOP/SLOW sign shall be supplemented with active conspicuity devices by incorporating either:

- A. White or red flashing lights within the STOP face and white or yellow flashing lights within the SLOW face meeting the provisions contained in Section 6E.036D.02; or
- B. A Stop Beacon (see Section 4L4S.05) mounted a maximum of 24 inches above the STOP face and a Warning Beacon (see Section 4L4S.03) mounted a maximum of 24 inches above, below, or to the side of the SLOW face. The Stop Beacon shall not be flashed or illuminated when the SLOW face is displayed, and the Warning Beacon shall not be flashed or illuminated when the STOP face is displayed. Except for the mounting locations, the beacons shall comply with the provisions of Chapter 4L4S.

Option:

Type B warning light(s) (see Section 6F.836L.07) or strobe lights may be used in lieu of the Warning Beacon during the display of the SLOW face of the AFAD's STOP/SLOW sign. Edited to improve flexibility

Standard:

If Type B warning lights <u>or strobe lights</u> are used in lieu of a Warning Beacon, they shall flash continuously when the SLOW face is displayed and shall not be flashed or illuminated when the STOP face is displayed. Edited to improve flexibility

Option:

The faces of the AFAD's STOP/SLOW sign may include louvers to improve the stability of the device in windy or other adverse environmental conditions.

Standard:

If louvers are used, the louvers shall be designed such that the full sign face is visible to approaching traffic at a distance of 50 feet or greater.

Guidance:

The STOP/SLOW AFAD should include a gate arm that descends to a down position across the approach lane of traffic when the STOP face is displayed and then ascends to an upright position when the SLOW face is displayed.

Option:

In lieu of a stationary STOP/SLOW sign with a separate gate arm, the STOP/SLOW sign may be attached to a mast arm that physically blocks the approach lane of traffic when the STOP face is displayed and then moves to a position that does not block the approach lane when the SLOW face is displayed.

Standard:

Gate arms, if used, shall be fully retroreflectorized on both sides, and shall have vertical alternating red and white stripes at 16-inch intervals measured horizontally as shown in Figure 8CD-1. When the arm is in the down position blocking the approach lane:

- A. The minimum vertical aspect of the arm and sheeting shall be 2 inches; and
- B. The end of the arm shall reach at least to the center of the lane being controlled.
- A WAIT ON STOP (R1-7) sign (see Figure 6E-16L-1) shall be displayed to road users approaching the AFAD.
- 43 Option
 - A GO ON SLOW (R1-8) sign (see Figure 6E-16L-1) may also be displayed to road users approaching the AFAD.
 - The WAIT ON STOP/ GO ON SLOW (R1-7a) sign (see Figure 6L-1) may also be used to display both messages to approaching road users. Added to improve consistency
- **Standard:**

The GO ON SLOW sign, if used, and the WAIT ON STOP sign shall be positioned on the same support structure as the AFAD or immediately adjacent to the AFAD such that they are in the same direct line of view of approaching traffic as the sign faces of the AFAD. Both signs shall have black legends and borders on white backgrounds. Each of these signs shall be rectangular in shape and each shall be at least 24 x 30 inches in size with letters at least 6 inches high. Deleted; redundant with Part 2 and Section 6G.02

To inform road users to stop, the AFAD shall display the STOP face and the red or white lights, if used, within the STOP face shall flash or the Stop Beacon shall flash. To inform road users to proceed, the AFAD shall display the SLOW face and the yellow or white lights, if used, within the SLOW face shall flash or the Warning Beacon or the Type B warning lights shall flash.

If STOP/SLOW AFADs are used to control traffic in a one-lane, two-way TTC zone, safeguards shall be incorporated to prevent the flagger(s) from simultaneously displaying the SLOW face at each end of the TTC zone. Additionally, the flagger(s) shall not display the AFAD's SLOW face until all oncoming vehicles have cleared the one-lane portion of the TTC zone.

Figure 6L-1. Example of the Use of a STOP/SLOW Automated Flagger Assistance Device (AFAD)

Section 6E.066L.04 Red/Yellow Lens Automated Flagger Assistance Devices This text was relocated from existing Section 6E.06

Standard:

A Red/Yellow Lens Automated Flagger Assistance Device (AFAD) (see Section 6E.04) shall alternately display a steadily illuminated CIRCULAR RED lens and a flashing CIRCULAR YELLOW lens to control traffic without the need for a flagger in the immediate vicinity of the AFAD or on the roadway (see Figure 6E-26L-2).

Red/Yellow Lens AFADs shall have at least one set of CIRCULAR RED and CIRCULAR YELLOW lenses that are 12 inches in diameter. Unless otherwise provided in this Section, the lenses and their arrangement, CIRCULAR RED on top and CIRCULAR YELLOW below, shall comply with the applicable provisions for traffic signal indications in Part 4. If the set of lenses is post-mounted, the bottom of the housing (including brackets) shall be at least 7 feet above the pavement. If the set of lenses is located over any portion of the highway that can be used by motor vehicles, the bottom of the housing (including brackets) shall be at least 15 feet above the pavement.

Option:

Additional sets of CIRCULAR RED and CIRCULAR YELLOW lenses, located over the roadway or on the left-hand side of the approach and operated in unison with the primary set, may be used to improve visibility and/or conspicuity of the AFAD.

Standard:

A Red/Yellow Lens AFAD shall include a gate arm that descends to a down position across the approach lane of traffic when the steady CIRCULAR RED lens is illuminated and then ascends to an upright position when the flashing CIRCULAR YELLOW lens is illuminated. The gate arm shall be fully retroreflectorized on both sides, and shall have vertical alternating red and white stripes at 16-inch intervals measured horizontally as shown in Figure 8©D-1. When the arm is in the down position blocking the approach lane:

- A. The minimum vertical aspect of the arm and sheeting shall be 2 inches; and
- B. The end of the arm shall reach at least to the center of the lane being controlled.

A Stop Here On Red (R10-6 or R10-6a) sign (see Section 2B.5363) shall be installed on the right-hand side of the approach at the point at which drivers are expected to stop when the steady CIRCULAR RED lens is illuminated (see Figure 6E-26L-2).

To inform road users to stop, the AFAD shall display a steadily illuminated CIRCULAR RED lens and the gate arm shall be in the down position. To inform road users to proceed, the AFAD shall display a flashing CIRCULAR YELLOW lens and the gate arm shall be in the upright position.

If Red/Yellow Lens AFADs are used to control traffic in a one-lane, two-way TTC zone, safeguards shall be incorporated to prevent the flagger(s) from actuating a simultaneous display of a flashing CIRCULAR YELLOW lens at each end of the TTC zone. Additionally, the flagger shall not actuate the AFAD's display of the flashing CIRCULAR YELLOW lens until all oncoming vehicles have cleared the one-lane portion of the TTC zone.

A change interval shall be provided as the transition between the display of the flashing CIRCULAR YELLOW indication and the display of the steady CIRCULAR RED indication. During the change interval, the CIRCULAR YELLOW lens shall be steadily illuminated. The gate arm shall remain in the upright position during the display of the steadily illuminated CIRCULAR YELLOW change interval.

A change interval shall not be provided between the display of the steady CIRCULAR RED indication and the display of the flashing CIRCULAR YELLOW indication.

Guidance:

 The steadily illuminated CIRCULAR YELLOW change interval should have a duration of at least 5 seconds, unless a different duration, within the range of durations recommended by Section 4D.264F.17, is justified by engineering judgment.

Figure 6L-2. Example of the Use of a Red/Yellow Lens Automated Flagger Assistance Device (AFAD)

Section 6F.606L.05 Portable Changeable Message Signs This text was relocated from existing Section 6F.60

Support:

Portable changeable message signs (PCMS) are TTC devices installed for temporary use with the flexibility to display a variety of messages. In most cases, portable changeable message signs follow the same provisions for design and application as those given for changeable message signs in Chapter 2L. The information in this Section describes situations where the provisions for portable changeable message signs differ from those given in Chapter 2L.

Portable changeable message signs are used most frequently on high-density urban freeways, but have applications on all types of highways where highway alignment, road user routing problems, or other pertinent conditions require advance warning and information.

Portable changeable message signs have a wide variety of applications in TTC zones including: roadway, lane, or ramp closures; incident management; width restriction information; speed control or reductions; advisories on work scheduling; road user management and diversion; warning of adverse conditions or special events; and other operational control.

The primary purpose of portable changeable message signs in TTC zones is to advise the road user of unexpected situations. Portable changeable message signs are particularly useful as they are capable of:

- A. Conveying complex messages,
- B. Displaying real time information about conditions ahead, and
- C. Providing information to assist road users in making decisions prior to the point where actions must be taken.

Some typical applications include the following:

- A. Where the speed of vehicular traffic is expected to drop substantially;
- B. Where significant queuing and delays are expected;
- C. Where adverse environmental conditions are present;
- D. Where there are changes in alignment or surface conditions;
- E. Where advance notice of ramp, lane, or roadway closures is needed;
- F. Where crash or incident management is needed; and/or
 - G. Where changes in the road user pattern occur.
- 49 Guidance:

The components of a portable changeable message sign should include: a message sign, control systems, a power source, and mounting and transporting equipment. The front face of the sign should be covered with a protective material.

Standard:

4

5

6

7

8

9

10

11

12

13

14

15

16

17

19

21

22

23

24

25

26

27

28

29

30

31

32

3334

35

36

37

38

39

40

41

42

43

44

45

46

47

48

Portable changeable message signs shall comply with the applicable design and application principles established in Chapter 2A. Portable changeable message signs shall display only traffic operational, regulatory, warning, and guidance information, and shall not be used for advertising messages.

Support:

Section 2L.02 contains information regarding overly simplistic or vague messages that is also applicable to portable changeable message signs.

Standard:

The colors used for legends on portable changeable message signs shall comply with those shown in Table 2A-5.

Support:

Section 2L.04 contains information regarding the luminance, luminance contrast, and contrast orientation that is also applicable to portable changeable message signs.

18 Guidance:

Portable changeable message signs should be visible from 1/2 mile under both day and night conditions.

20 Support:

Section 2B.1323 contains information regarding the design of portable changeable message signs that are used to display speed limits that change based on operational conditions, or are used to display the speed at which approaching drivers are traveling.

Guidance:

A portable changeable message sign should be limited to three lines of eight characters per line or should consist of a full matrix display.

Except as provided in Paragraph 15, the letter height used for portable changeable message sign messages should be a minimum of 18 inches.

Option:

For portable changeable message signs mounted on service patrol trucks or other incident response vehicles, a letter height as short as 10 inches may be used. Shorter letter sizes may also be used on a portable changeable message sign used on low speed facilities provided that the message is legible from at least 650 feet.

The portable changeable message sign may vary in size.

Guidance:

Messages on a portable changeable message sign should consist of no more than two phases, and a phase should consist of no more than three lines of text. Each phase should be capable of being understood by itself, regardless of the order in which it is read. Messages should be centered within each line of legend. If more than one portable changeable message sign is simultaneously legible to road users, then only one of the signs should display a sequential message at any given time.

Support:

Road users have difficulties in reading messages displayed in more than two phases on a typical three-line portable changeable message sign.

Standard:

Except when being used to simulate an Arrow Board display (see Section 6L.06), Ttechniques of message display such as animation, rapid flashing, dissolving, exploding, scrolling, travelling horizontally or vertically across the face of the sign, or other dynamic elements shall not be used. Edited to reflect Official Interpretation 6(09)-18(I)

49 Guidance:

All messages should be designed with consideration given to the principles provided in this Section and also taking into account the following:

- A. The message should be as brief as possible and should contain three thoughts (with each thought preferably shown on its own line) that convey:
 - 1. The problem or situation that the road user will encounter ahead,
 - 2. The location of or distance to the problem or situation, and
 - 3. The recommended driver action.
- B. If more than two phases are needed to display a message, additional portable changeable message signs should be used. When multiple portable changeable message signs are needed, they should be placed on the same side of the roadway and they should be separated from each other by a distance of at least 1,000 feet on freeways and expressways, and by a distance of at least 500 feet on other types of highways.

Standard:

When the word messages shown in Tables 1A1D-1 or 1A1D-2 need to be abbreviated on a portable changeable message sign, the provisions described in Section 1A.151D.10 shall be followed.

In order to maintain legibility, portable changeable message signs shall automatically adjust their brightness under varying light conditions.

The control system shall include a display screen upon which messages can be reviewed before being displayed on the message sign. The control system shall be capable of maintaining memory when power is unavailable.

Portable changeable message signs shall be equipped with a power source and a battery back-up to provide continuous operation when failure of the primary power source occurs.

The mounting of portable changeable message signs on a trailer, a large truck, or a service patrol truck shall be such that the bottom of the message sign shall be a minimum of 7 feet above the roadway in urban areas and 5 feet above the roadway in rural areas when it is in the operating mode.

Guidance:

Portable changeable message signs should be used as a supplement to and not as a substitute for conventional signs and pavement markings.

When portable changeable message signs are used for route diversion, they should be placed far enough in advance of the diversion to allow road users ample opportunity to perform necessary lane changes, to adjust their speed, or to exit the affected highway.

Portable changeable message signs should be sited and aligned to provide maximum legibility and to allow time for road users to respond appropriately to the portable changeable Message sign message.

Portable changeable message signs should be placed off the shoulder of the roadway and behind a traffic barrier, if practical. Where a traffic barrier is not available to shield the portable changeable message sign, it should be placed off the shoulder and outside of the clear zone. If a portable changeable message sign has to be placed on the shoulder of the roadway or within the clear zone, it should be delineated with retroreflective TTC devices.

When portable changeable message signs are used in TTC zones, they should display only TTC messages.

When portable changeable message signs are not being used to display TTC messages, they should be relocated such that they are outside of the clear zone or shielded behind a traffic barrier and turned away from traffic. If relocation or shielding is not practical, they should be delineated with retroreflective TTC devices.

Portable changeable message sign trailers should be delineated on a permanent basis by affixing retroreflective material, known as conspicuity material, in a continuous line on the face of the trailer as seen by oncoming road users.

Section 6F.61 Arrow Boards This text was relocated from existing Section 6F.61

Standard:

An arrow board shall be a sign with a matrix of elements capable of either flashing or sequential displays. This sign shall provide additional warning and directional information to assist in merging and controlling road users through or around a TTC zone.

Guidance:

An arrow board in the arrow or chevron mode should be used to advise approaching traffic of a lane closure along major multi-lane roadways in situations involving heavy traffic volumes, high speeds, and/or limited sight distances, or at other locations and under other conditions where road users are less likely to expect such lane closures.

If used, an arrow board should be used in combination with appropriate signs, channelizing devices, or other TTC devices.

An arrow board should be placed on the shoulder of the roadway or, if practical, farther from the traveled lane. It should be delineated with retroreflective TTC devices. When an arrow board is not being used, it should be removed; if not removed, it should be shielded; or if the previous two options are not feasible, it should be delineated with retroreflective TTC devices.

Standard:

Arrow boards shall meet the minimum size, legibility distance, number of elements, and other specifications shown in Figure 6F-66L-3.

Figure 6L-3. Advance Warning Arrow Board Display Specifications

Support:

Type A arrow boards are appropriate for use on low-speed urban streets. Type B arrow boards are appropriate for intermediate-speed facilities and for maintenance or mobile operations on high-speed roadways. Type C arrow boards are intended to be used on high-speed, high-volume motor vehicle traffic control projects. Type D arrow boards are intended for use on vehicles authorized by the State or local agency.

Standard:

Type A, B, and C arrow boards shall have solid rectangular appearances. A Type D arrow board shall conform to the shape of the arrow.

All arrow boards shall be finished in non-reflective black. The arrow board shall be mounted on a vehicle, a trailer, or other suitable support.

Guidance:

The minimum mounting height, measured vertically from the bottom of the board to the roadway below it or to the elevation of the near edge of the roadway, of an arrow board should be 7 feet, except on vehicle-mounted arrow boards, which should be as high as practical.

A vehicle-mounted arrow board should be provided with remote controls.

Standard:

Arrow board elements shall be capable of at least a 50 percent dimming from full brilliance. The dimmed mode shall be used for nighttime operation of arrow boards.

39 Guidance:

Full brilliance should be used for daytime operation of arrow boards.

41 Standard:

The arrow board shall have suitable elements capable of the various operating modes. The color presented by the elements shall be yellow.

44 Guidance:

If an arrow board consisting of a bulb matrix is used, the elements should be recess-mounted or equipped with an upper hood of not less than 180 degrees.

Standard:

The minimum element on-time shall be 50 percent for the flashing mode, with equal intervals of 25 percent for each sequential phase. The flashing rate shall be not less than 25 or more than 40 flashes per minute.

An arrow board shall have the following three mode selections:

- A. A Flashing Arrow, Sequential Arrow, or Sequential Chevron mode;
- B. A flashing Double Arrow mode; and
 - C. A flashing Caution or Alternating Diamond mode.

An arrow board in the arrow or chevron mode shall be used only for stationary or moving lane closures on multi-lane roadways.

For shoulder work, blocking the shoulder, for roadside work near the shoulder, or for temporarily closing one lane on a two-lane, two-way roadway, an arrow board shall be used only in the caution mode.

Guidance:

4

5

6

7

8

9

10

11 12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

37 38

39

40

41 42

44

45

46

47

48

For a stationary lane closure, the arrow board should be located on the shoulder at the beginning of the merging taper.

Where the shoulder is narrow, the arrow board should be located in the closed lane.

Standard:

When arrow boards are used to close multiple lanes, a separate arrow board shall be used for each closed lane.

Guidance:

When arrow boards are used to close multiple lanes, if the first arrow board is placed on the shoulder, the second arrow board should be placed in the first closed lane at the upstream end of the second merging taper (see Figure 6H6P-37). When the first arrow board is placed in the first closed lane, the second arrow board should be placed in the second closed lane at the downstream end of the second merging taper.

For mobile operations where a lane is closed, the arrow board should be located to provide adequate separation from the work operation to allow for appropriate reaction by approaching drivers.

Standard:

A vehicle displaying an arrow board shall be equipped with high-intensity rotating, flashing, oscillating, or strobe lights.

Arrow boards shall only be used to indicate a lane closure. Arrow boards shall not be used to indicate a lane shift.

Option:

A portable changeable message sign may be used to simulate an arrow board display.

Section 6F.836L.07 Flashing Beacons and Warning Lights

This text was relocated from existing Section 6F.83 and title was edited for clarity

36 Guidance:

Lighting devices should be provided in TTC zones based on engineering judgment. This text was relocated from existing Section 6F.81

Option:

Lighting devices Flashing beacons (see Chapter 4S) and/or warning lights may be used to supplement retroreflectorized signs, barriers, and channelizing devices. This text was relocated from existing Section 6F.81

43 Support:

Type A, Type B, Type C, and Type D 360-degree warning lights are portable, powered, yellow, lens-directed, enclosed lights.

Standard:

Warning lights shall be in accordance comply with the current ITE "Purchase Specification for Flashing and Steady-Burn Warning Lights" provisions in Chapter 13 of the publication entitled,

"Equipment and Materials Standards of the Institute of Transportation Engineers" (see Section 1A.1105). Edited to improve accuracy

When warning lights are used, they shall be mounted on signs or channelizing devices in a manner that, if hit by an errant vehicle, they will not be likely to penetrate the windshield.

5 Guidance:

 The maximum spacing for warning lights should be identical to the channelizing device spacing requirements.

Support:

The light weight and portability of warning lights are advantages that make these devices useful as supplements to the retroreflectorization on signs and channelizing devices. The flashing lights are effective in attracting road users' attention.

Option:

Warning lights may be used in either a steady-burn or flashing mode.

Standard:

Warning lights shall flash when placed on channelizing devices used alone or in a cluster to warn of a condition. This text was relocated from existing Section 6F.63

Except for the sequential flashing warning lights discussed in Paragraphs 12 and 13, warning lights placed on channelizing devices used in a series to channelize road users shall be steady-burn. This text was relocated from existing Section 6F.63

Except for the sequential flashing warning lights that are described in Paragraphs 8 and 9 12, flashing warning lights shall not be used for delineation, as a series of flashers fails to identify the desired vehicle path.

Option:

A series of sequential flashing warning lights may be placed on channelizing devices that form a merging taper in order to increase driver detection and recognition of the merging taper. Deleted; redundant with new Section 6K.01

Standard:

If a series of sequential flashing warning lights is used <u>on channelizing devices that form a merging taper</u>, the successive flashing of the lights shall occur from the upstream end of the merging taper to the downstream end of the merging taper in order to identify the desired vehicle path. Each flashing warning light in the sequence shall be flashed at a rate of not less than 55 or more than 75 times per minute. Edited to improve consistency

Type A Low-Intensity Flashing warning lights, Type C Steady-Burn warning lights, and Type D 360-degree Steady-Burn warning lights shall be maintained so as to be capable of being visible on a clear night from a distance of 3,000 feet. Type B High-Intensity Flashing warning lights shall be maintained so as to be capable of being visible on a sunny day when viewed without the sun directly on or behind the device from a distance of 1,000 feet.

Warning lights shall have a minimum mounting height of 30 inches to the bottom of the lens.

39 Support:

Type A Low-Intensity Flashing warning lights are used to warn road users during nighttime hours that they are approaching or proceeding in a potentially hazardous area.

Option:

Type A warning lights may be mounted on channelizing devices.

44 Support:

Type B High-Intensity Flashing warning lights are used to warn road users during both daylight and nighttime hours that they are approaching a potentially hazardous area.

Option:

Type B warning lights are designed to operate 24 hours per day and may be mounted on advance warning signs or on independent supports.

1 Type C Steady-Burn warning lights and Type D 360-degree Steady-Burn warning lights may be used 2 during nighttime hours to delineate the edge of the traveled way. 3 Guidance: 4 When used to delineate a curve, Type C and Type D 360-degree warning lights should only be used on 5 devices on the outside of the curve, and not on the inside of the curve. 6 Section 6F.626L.08 High-Level Warning Devices (Flag Trees) The text in this Section was 7 relocated from existing Section 6F.62 8 Option: 9 A high-level warning device (flag tree) may supplement other TTC devices in TTC zones. 10 A high-level warning device is designed to be seen over the top of typical passenger cars. A typical high-11 12 level warning device is shown in Figure 6F-26F-1. 13 **Standard:** 14 A high-level warning device shall consist of a minimum of two flags with or without a Type B highintensity flashing warning light. The distance from the roadway to the bottom of the lens of the light 15 and to the lowest point of the flag material shall be not less than 8 feet. The flag shall be 16 inches 16 square or larger and shall be orange or fluorescent red-orange in color. 17 18 Option: An appropriate warning sign may be mounted below the flags.

19

20

21

22

23

High-level warning devices are most commonly used in high-density road user situations to warn road users of short-term operations.

CHAPTER 6M. TTC ZONE DESIGN FEATURES AND DEVICES THAT ARE NOT TRAFFIC
CONTROL DEVICES
New Chapter with text from existing Sections 6F.74, 6F.75, 6F.82, and 6F.85 through 6F.88
Section 6M.01 General Added to improve accuracy
Support:
Although certain devices and design features, such as lighting, barriers, dividers, crash cushions, and
screens, are sometimes used in TTC zones to supplement traffic control devices or enhance traffic operations
or safety for road users, they are not considered to be traffic control devices. The following Sections describe
the most commonly used of such devices and design features. See also Section 1D.04 for additional
<u>information.</u>
Section 6F.856M.02 Positive Protection and Temporary Traffic Barriers This text was
relocated from existing Section 6F.85
Standard:
The need for longitudinal traffic barrier and other positive protection devices shall be based on an
engineering study. At a minimum, positive protection devices shall be considered in work zone
situations that place workers at increased risk from motorized traffic, and where positive protection
devices offer the highest potential for increased safety for workers and road users. Guidance changed
to Standard to reflect CFR 630.1108 Work Zone Safety Management Measures and Strategies (subpar
K) and relocated from below
Support:
Consider positive protection under the following circumstances:
A. Work zones that provide workers no means of escape from motorized traffic such as tunnels or
bridges;
B. Long-term stationary work zones of two weeks or more resulting in substantial worker exposure
to motorized traffic;
C. Projects with anticipated operating speeds of 45 mph or greater, especially when combined with
high traffic volumes;
D. Work operations that place workers close to travel lanes open to traffic; and
E. Roadside hazards, such as drop-offs or unfinished bridge decks, that will remain in place
overnight or longer.
Work zone setups vary depending on the nature of the positive protection used.
For additional guidance refer to 23 CFR Part 630.1108(a). Added to reflect CFR 640.1108 Work Zone
Safety Management Measures and Strategies
Temporary traffic barriers, including shifting portable or movable barriers, are devices designed to help
prevent penetration by vehicles while minimizing injuries to vehicle occupants, and to protect workers,
bicyclists, and pedestrians.
The four primary functions of temporary traffic barriers are:
A. To keep vehicular traffic from entering work areas, such as excavations or material storage sites;
B. To separate workers, bicyclists, and pedestrians from motor vehicle traffic; C. To separate opposing directions of vehicular traffic; and
D. To separate opposing directions of venicular traffic; and D. To separate vehicular traffic, bicyclists, and pedestrians from the work area such as false work for
bridges and other exposed objects. Deleted; redundant with new Support statements above
Option:
Temporary traffic barriers may be used to separate two-way vehicular traffic.

45

Guidance:

Because the protective requirements of a TTC situation have priority in determining the need for temporary traffic barriers, their use should be based on an engineering study. Guidance changed to

Standard and relocated to above

Standard:

Temporary traffic barriers shall be supplemented with standard delineation, pavement markings, or channelizing devices for improved daytime and nighttime visibility if they are used to channelize vehicular traffic. The delineation color shall match the applicable pavement marking color.

Temporary traffic barriers, including their end treatments, shall be crashworthy. In order to-mitigate the effect of striking the upstream end of a temporary traffic barrier, the end shall be installed in accordance with AASHTO's "Roadside Design Guide" (see Section 1A.11) by flaring until the end is outside the acceptable clear zone or by providing crashworthy end treatments.

Deleted; redundant with new Section 6A.04

Short intermittent segments of temporary traffic barrier shall not be used because they nullify the containment and redirective capabilities of the temporary traffic barrier, increase the potential for serious injury both to vehicle occupants and pedestrians, and encourage the presence of blunt leading ends. Adjacent temporary traffic barrier segments shall be properly connected in order to provide the overall strength required for the temporary traffic barrier to perform properly. This text was relocated from existing Section 6D.01

Option:

<u>Steady-burn Wwarning lights or steady burn (see Section 6L.07) lamps</u> may be mounted on temporary traffic barrier installations. <u>Edited to improve clarity</u>

Support:

Movable barriers <u>may include movable concrete</u>, <u>movable steel or highly mobile barriers</u>. <u>Movable barrier may be moved laterally and/or longitudinally when needed and/or from site to site.</u> are capable of being repositioned laterally using a transfer vehicle that travels along the barrier. Movable barriers enable short-term closures to be installed and removed on long term projects. Providing a barrier protected work space for short-term closures and providing unbalanced flow to accommodate changes in the direction of peak period traffic flows are two of the advantages of using movable barriers.

Figure 6H-45 shows a temporary reversible lane using movable barriers. The notable feature of the movable barrier is that in both Phase A and Phase B, the lanes used by opposing traffic are separated by a barrier.

Figure 6H-34 shows an exterior lane closure using a temporary traffic barrier. Notes 7 through 9 address the option of using a movable barrier. By using a movable barrier, the barrier can be positioned to close the lane during the off peak periods and can be relocated to open the lane during peak periods to accommodate peak traffic flows. With one pass of the transfer vehicle, the barrier can be moved out of the lane and onto the shoulder. Furthermore, if so desired, with a second pass of the transfer vehicle, the barrier could be moved to the roadside beyond the shoulder. Edited to improve clarity and broaden the description of movable barrier

More specific information on the use of temporary traffic barriers is contained in Chapters 8 and 9 of AASHTO's "Roadside Design Guide" (see Section 1A.1105).

Section 6F.75 6M.03 Temporary Raised Islands This text was relocated from existing Section 6F.75

43 Standard:

Temporary raised islands shall be used only in combination with pavement striping and other suitable channelizing devices.

46 Option:

A temporary raised island may be used to separate vehicular traffic flows in two-lane, two-way operations on roadways having a vehicular traffic volume range of 4,000 to 15,000 average daily traffic (ADT) and on freeways having a vehicular traffic volume range of 22,000 ADT to 60,000 ADT.

Temporary raised islands also may be used in other than two-lane, two-way operations where physical separation of vehicular traffic from the TTC zone is not required.

Guidance:

Temporary raised islands should have the basic dimensions of 4 inches high by at least 12 inches wide and have rounded or chamfered corners.

The temporary raised islands should not be designed in such a manner that they would cause a motorist to lose control of the vehicle if the vehicle inadvertently strikes the temporary raised island. If struck, pieces of the island should not be dislodged to the extent that they could penetrate the occupant compartment or involve other vehicles.

Standard:

At pedestrian crossing locations, temporary raised islands shall have an opening or be shortened to provide at least a 60-inch wide pathway for the crossing pedestrian.

Section 6F.746M.04 Detectable Edging for Pedestrians This text was relocated from existing Section 6F.74

Support:

Individual channelizing devices, tape or rope used to connect individual devices, other discontinuous barriers and devices, and pavement markings are not detectable by persons with visual disabilities and are incapable of providing detectable path guidance on temporary or realigned sidewalks or other pedestrian facilities.

Guidance:

When it is determined that a facility should be accessible to and detectable by pedestrians with visual disabilities, a- A continuously detectable edging should be provided throughout the length of the facility such that it can be followed by pedestrians using long canes for guidance. This edging should protrude at least 6-8 inches above the surface of the sidewalk or pathway, with the bottom of the edging a maximum of 2 inches above the surface. This edging should be continuous throughout the length of the facility except for gaps at locations where pedestrians or vehicles will be turning or crossing. This edging should consist of a prefabricated or formed-in-place curbing or other continuous device that is placed along the edge of the sidewalk or walkway. This edging should be firmly attached to the ground or to other devices. Adjacent sections of this edging should be interconnected such that the edging is not displaced by pedestrian or vehicular traffic or work operations, and such that it does not constitute a hazard to pedestrians, workers, or other road users. Edited to improve consistency with new Section 6K.02

Support:

Examples of detectable edging for pedestrians include:

- A. Prefabricated lightweight sections of plastic, metal, or other suitable materials that are interconnected and fixed in place to form a continuous edge.
- B. Prefabricated lightweight sections of plastic, metal, or other suitable materials that are interconnected, fixed in place, and placed at ground level to provide a continuous connection between channelizing devices located at intervals along the edge of the sidewalk or walkway.
- C. Sections of lumber interconnected and fixed in place to form a continuous edge.
- D. Formed-in-place asphalt or concrete curb.
- E. Prefabricated concrete curb sections that are interconnected and fixed in place to form a continuous edge.
- F. Continuous temporary traffic barrier or longitudinal channelizing barricades placed along the edge of the sidewalk or walkway that provides a pedestrian edging at ground level.
- G. Chain link or other fencing equipped with a continuous bottom rail.

46 Guidance:

Detectable pedestrian edging should be orange, white, or yellow and should match the color of the adjacent channelizing devices or traffic control devices, if any are present.

Section 6F.81 Lighting Devices Section deleted and 3 paragraphs relocated to other Sections

Guidance:

1

2

3

4

5

6

7

8

9

10

11

13

14

15

22

23

24

25

26 27

28

29

30 31

32

33

34

35

36

37

38

39

40

41 42

44

45

46

Lighting devices should be provided in TTC zones based on engineering judgment. This text was relocated to new Section 6L.07

When used to supplement channelization, the maximum spacing for warning lights should be identical to the channelizing device spacing requirements. Deleted; redundant with new Section 6L.07

Option:

Lighting devices may be used to supplement retroreflectorized signs, barriers, and channelizing devices.

This text was relocated to new Section 6L.07

During normal daytime maintenance operations, the functions of flashing warning beacons may be provided by high-intensity rotating, flashing, oscillating, or strobe lights on a maintenance vehicle. Deleted – covered elsewhere in Part 6.

12 Standard:

Although vehicle hazard warning lights are permitted to be used to supplement high-intensity rotating, flashing, oscillating, or strobe lights, they shall not be used instead of high-intensity rotating, flashing, oscillating, or strobe lights. Moved to new Section 6N.01

- 16 Section 6F.82 Floodlights This text was relocated to new Section 6M.08
- 17 Section 6F.83 Warning Lights This text was relocated to new Section 6L.07
- 18 Section 6F.84 Temporary Traffic Control Signals This text was relocated to new Section 6L.01
- 19 Section 6F.85 Temporary Traffic Barriers This text was relocated to new Section 6M.02
- 20 Section 6F.866M.05 Crash Cushions
- 21 Support:

Crash cushions are systems that mitigate the effects of errant vehicles that strike obstacles, either by smoothly decelerating the vehicle to a stop when hit head-on, or by redirecting the errant vehicle. The two types of crash cushions that are used in TTC zones are stationary crash cushions and truck-mounted attenuators. Crash cushions in TTC zones help protect the drivers from the exposed ends of barriers, fixed objects, shadow vehicles, and other obstacles. Specific information on the use of crash cushions can be found in AASHTO's "Roadside Design Guide" (see Section 1A.1105).

Standard:

Crash cushions shall be crashworthy. They shall also be designed for each application to stop or redirect errant vehicles under prescribed conditions. Crash cushions shall be periodically inspected to verify that they have not been hit or damaged. Damaged crash cushions shall be promptly repaired or replaced to maintain their crashworthiness.

Support:

Stationary crash cushions are used in the same manner as permanent highway installations to protect drivers from the exposed ends of barriers, fixed objects, and other obstacles.

Standard:

Stationary crash cushions shall be designed for the specific application intended.

Truck-mounted attenuators shall be energy-absorbing devices attached to the rear of shadow trailers or trucks and shall be used in accordance with the manufacturer's specifications. Guidance from below changed to Standard and combined with existing Standard statement If used, the shadow vehicle with the attenuator shall be located in advance of the work area, workers, or equipment to reduce the severity of rear-end crashes from errant vehicles.

43 Support:

Trucks or trailers are often used as shadow vehicles to protect workers or work equipment from errant vehicles. These shadow vehicles are normally equipped with flashing arrows, changeable message signs, and/or high-intensity rotating, flashing, oscillating, or strobe lights located properly in advance of the workers

and/or equipment that they are protecting. However, these shadow vehicles might themselves cause injuries to occupants of the errant vehicles if they are not equipped with truck-mounted attenuators.

Guidance:

The shadow truck should be positioned a sufficient distance in advance of the workers or equipment being protected so that there will be sufficient distance, but not so much so that errant vehicles will travel around the shadow truck and strike the protected workers and/or equipment.

Support:

Chapter 9 of AASHTO's "Roadside Design Guide" (see Section 1A. 1105) contains additional information regarding the use of shadow vehicles.

Guidance:

If used, the truck mounted attenuator should be used in accordance with the manufacturer's specifications. Guidance changed to Standard and combined with Standard above

Section 6F.876M.06 Rumble Strips

Support:

Transverse rumble strips consist of intermittent, narrow, transverse areas of rough-textured or slightly raised or depressed road surface that extend across the travel lanes to alert drivers to unusual vehicular traffic conditions. Through noise and vibration they attract the driver's attention to such features as unexpected changes in alignment and to conditions requiring a stop.

Longitudinal rumble strips consist of a series of rough-textured or slightly raised or depressed road surfaces located along the shoulder to alert road users that they are leaving the travel lanes.

Standard:

If it is desirable to use a color other than the color of the pavement for a longitudinal rumble strip, the color of the rumble strip shall be the same color as the longitudinal line the rumble strip supplements.

If the color of a transverse rumble strip used within a travel lane is not the color of the pavement, the color of the rumble strip shall be white, black, or orange.

Option:

Intervals between transverse rumble strips may be reduced as the distance to the approached conditions is diminished in order to convey an impression that a closure speed is too fast and/or that an action is imminent. A sign warning drivers of the onset of rumble strips may be placed in advance of any transverse rumble strip installation.

Guidance:

Transverse rumble strips should be placed transverse to vehicular traffic movement. They should not adversely affect overall pavement skid resistance under wet or dry conditions.

In urban areas, even though a closer spacing might be warranted, transverse rumble strips should be designed in a manner that does not promote unnecessary braking or erratic steering maneuvers by road users.

Transverse rumble strips should not be placed on sharp horizontal or vertical curves.

Rumble strips should not be placed through pedestrian crossings or on bicycle routes.

Transverse rumble strips should not be placed on roadways used by bicyclists unless a minimum clear path of 4 feet is provided at each edge of the roadway or on each paved shoulder as described in AASHTO's "Guide to the Development of Bicycle Facilities" (see Section 1A. 1105).

Longitudinal rumble strips should not be placed on the shoulder of a roadway that is used by bicyclists unless a minimum clear path of 4 feet is also provided on the shoulder.

44 Section 6F.886M.07 Screens

45 Support:

Screens are used to block the road users' view of activities that can be distracting. Screens might improve safety and motor vehicle traffic flow where volumes approach the roadway capacity because they discourage gawking and reduce headlight glare from oncoming motor vehicle traffic.

Guidance:

Screens should not be mounted where they could adversely restrict road user visibility and sight distance and adversely affect the reasonably safe operation of vehicles. Edited to improve accuracy

Option:

Screens may be mounted on the top of temporary traffic barriers that separate two-way motor vehicle traffic.

10 Guidance:

Design of screens should be in accordance with Chapter 9 of AASHTO's "Roadside Design Guide" (see Section 1A.4405).

Section 6F.826M.08 Floodlights Lighting for Night Work This text was relocated from existing Section 6F.82 and edited to improve accuracy

Support:

Utility, maintenance, or construction activities on highways are frequently conducted during nighttime periods when vehicular traffic volumes are lower. Large construction projects are sometimes operated on a double-shift basis requiring night work (see Section 6G.196N.18).

Guidance:

When nighttime work is being performed, floodlights should be used to illuminate the work area, equipment crossings, and other areas

When used, Ffloodlighting sha bould not produce a disabling be installed in a manner that minimizes glare condition forto approaching road users, flaggers, or workers. Standard changed to Guidance and relocated from below

The adequacy of the floodlight placement and elimination of potential glare should be determined by driving through and observing the floodlighted area from each direction on all approaching roadways after the initial floodlight setup, at night, and periodically. Relocated from below Lighting should be sufficient so as to clearly identify a worker as a person. Care should be taken to minimize the potential for shadows to conceal workers within the work area. Added to improve accuracy

Support:

Desired illumination levels vary depending upon the nature of the task involved. An average horizontal luminance of 5 foot candles can be adequate for general activities. Tasks requiring high levels of precision and extreme care can require an average horizontal luminance of 20 foot candles. Relocated from below

Standard:

Except in emergency situations, flagger stations shall be illuminated at night.

Floodlighting shall not produce a disabling glare condition for approaching road users, flaggers, or workers. Standard changed to Guidance and relocated to above

Guidance:

The adequacy of the floodlight placement and elimination of potential glare should be determined by driving through and observing the floodlighted area from each direction on all approaching roadways after the initial floodlight setup, at night, and periodically. Relocated to above

Support:

Desired illumination levels vary depending upon the nature of the task involved. An average horizontal luminance of 5 foot candles can be adequate for general activities. Tasks requiring high levels of precision and extreme care can require an average horizontal luminance of 20 foot candles. Relocated to above

CHAPTER 6G6N. TYPE OF TEMPORARY TRAFFIC CONTROL ZONE ACTIVITIES

2 Section 6G.01 Typical Applications This text was relocated to new Section 6B.01

3 Section 6G.026N.01 Work Duration

4 Support:

1

5

6

7 8

9

10

11

12

13

14

15

16 17

18 19

20

21

22

23

24

2526

27

28

29 30

31 32

33

34

36

37

38

39

40

41

42

43

44 45

46

47

Work duration is a major factor in determining the number and types of devices used in TTC zones. The duration of a TTC zone is defined relative to the length of time a work operation occupies a spot location.

Standard: Guidance: Standard changed to Guidance

The five categories of work duration and their time at a location shall should be defined as follows:

- A. Long-term stationary is work that occupies a location more than 3 days.
- B. Intermediate-term stationary is work that occupies a location more than one daylight period up to 3 days, or nighttime work lasting more than 1 hour.
- C. Short-term stationary is daytime work that occupies a location for more than 1 hour within a single daylight period.
- D. Short duration is work that occupies a location up to 1 hour.
- E. Mobile is work that moves intermittently or continuously.

Support

At long-term stationary TTC zones, there is ample time to install and realize benefits from the full range of TTC procedures and devices that are available for use. Generally, larger channelizing devices, temporary roadways, and temporary traffic barriers are used.

Standard:

Since long-term operations extend into nighttime, retroreflective and/or illuminated devices shall be used in long-term stationary TTC zones.

Guidance:

<u>Inappropriate Temporary</u> -markings in long-term stationary TTC zones should be removed and replaced with temporary markings installed in accordance with Section 6J.01. Edited to improve consistency with

6J.01.

Support:

In intermediate-term stationary TTC zones, it might not be feasible or practical to use procedures or devices that would be desirable for long-term stationary TTC zones, such as altered pavement markings, temporary traffic barriers, and temporary roadways. The increased time to place and remove these devices in some cases could significantly lengthen the project, thus increasing exposure time.

Standard:

Since intermediate-term operations extend into nighttime, retroreflective and/or illuminated devices shall be used in intermediate-term stationary TTC zones.

35 Support:

Most maintenance and utility operations are short-term stationary work.

As compared to stationary operations, mobile and short-duration operations are activities that might involve different treatments. Devices having greater mobility might be necessary such as signs mounted on trucks. Devices that are larger, more imposing, or more visible can be used effectively and economically.

The mobility of the TTC zone is important.

Guidance:

Safety in short-duration or mobile operations should not be compromised by using fewer devices simply because the operation will frequently change its location.

Option 4 1

Appropriately colored or marked vehicles with high-intensity rotating, flashing, oscillating, or strobe-lights may be used in place of signs and channelizing devices for short duration or mobile operations. These-vehicles may be augmented with signs or arrow boards.

Deleted; redundant with other sections in Part 6

48 Support:

During short-duration work, it often takes longer to set up and remove the TTC zone than to perform the work. Workers face hazards in setting up and taking down the TTC zone. Also, since the work time is short, delays affecting road users are significantly increased when additional devices are installed and removed.

4 Option:

1

2

3

5

6

7

8

9

10

11

12

131415

16

17

19

20

21

22

23

24

25

2627

28

29

30

31

32 33

34

3536

37

38

39 40

41 42

43

44 45

46

Considering these factors, simplified control procedures may be warranted for short-duration work. A reduction in the number of devices may be offset by the use of other more dominant devices such as high-intensity rotating, flashing, oscillating, or strobe lights on work vehicles.

Support:

Mobile operations often involve frequent short stops for activities such as litter cleanup, pothole patching, or utility operations, and are similar to short-duration operations.

Guidance:

Warning signs and high intensity rotating, flashing, oscillating, or strobe lights should be used on the vehicles that are participating in the mobile work. Deleted; redundant with other sections in Part 6

Option:

Flags and/or channelizing devices may additionally be used and moved periodically to keep them near the mobile work area.

Flaggers may be used for mobile operations that often involve frequent short stops.

18 Support

Mobile operations also include work activities where workers and equipment move along the road without stopping, usually at slow speeds. The advance warning area moves with the work area.

Guidance:

When mobile operations are being performed, a shadow vehicle equipped with an arrow board or a sign should follow the work vehicle, especially when vehicular traffic speeds or volumes are high. Where feasible, warning signs should be placed along the roadway and moved periodically as work progresses.

Under high-volume conditions, consideration should be given to scheduling mobile operations work during off-peak hours.

If there are mobile operations on a high-speed travel lane of a multi-lane divided highway, arrow boards should be used.

Standard:

Mobile operations shall have appropriate devices on the equipment (that is, high-intensity rotating, flashing, oscillating, or strobe lights, signs, or special lighting), or shall use a separate vehicle with appropriate warning devices. Although vehicle hazard warning lights are permitted to be used to supplement high-intensity rotating, flashing, oscillating, or strobe lights, they shall not be used instead of high-intensity rotating, flashing, oscillating, or strobe lights these devices. Last sentence was relocated from existing Section 6F.81 and edited to improve clarity

Option:

For mobile operations that move at speeds of less than 3 mph, mobile signs or stationary signing that is periodically retrieved and repositioned in the advance warning area may be used.

Support:

A rolling roadblock is a method of temporary traffic control used to slow or stop traffic as a means of temporarily removing traffic from a roadway. The rolling roadblock closes all lanes of traffic by using pacing vehicles to create a gap so that construction activities can be performed. Rolling roadblocks are used where long-term road closures using temporary traffic control devices (TTCD) are not needed. A rolling roadblock requires one blocking/pacing vehicle per lane of traffic, a clearing vehicle, and an advance warning vehicle. The rolling roadblock is normally performed by law enforcement officers during off-peak hours. Added to

reflect NTSB H-17-2 recommendation

- 47 Section 6G.036N.02 Location of Work
- 48 Support:

Chapter 6D6C and Sections 6F.746M.04 and 6G.056N.04 contain additional information regarding the steps to follow when pedestrian or bicycle facilities are affected by the worksite.

The choice of TTC needed for a TTC zone depends upon where the work is located. As a general rule, the closer the work is to road users (including bicyclists and pedestrians), the greater the number of TTC devices that are needed. Procedures are described later in this Chapter for establishing TTC zones in the following locations:

- A. Outside the shoulder.
- B. On the shoulder with no encroachment,
- C. On the shoulder with minor encroachment,
- D. Within the median, and
 - E. Within the traveled way.

12 Standard:

1

2

3

4

5

6

7

8 9

10

11

13

14

15

16

17

19

20

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43 44

45

46

47

50

When the work space is within the traveled way, except for short-duration and mobile operations, advance warning shall provide a general message that work is taking place and shall supply information about highway conditions. TTC devices shall indicate how vehicular traffic can move clearly delineate the path roadway users are to follow through the TTC zone. Edited to improve clarity

Section 6C.046N.03 Modifications To Fulfill Special Needs

18 Support:

The typical applications in Chapter 6H-6P illustrate commonly encountered situations in which TTC devices are employed.

21 Option:

Other devices may be added to supplement the devices provided in the typical applications, and device spacing may be adjusted to provide additional reaction time. When conditions are less complex than those depicted in the typical applications, fewer devices may be needed.

Guidance:

When conditions are more complex, typical applications should be modified by giving particular attention to the provisions set forth in Chapter 6B-6A and by incorporating appropriate devices and practices from the following list:

- A. Additional devices:
 - 1. Signs
 - 2. Arrow boards
 - 3. More channelizing devices at closer spacing (see Section 6F.746M.04 for information regarding detectable edging for pedestrians)
 - 4. Temporary raised pavement markers
 - 5. High-level warning devices
 - 6. Portable changeable message signs
 - 7. Temporary traffic control signals (including pedestrian signals and accessible pedestrian signals)
 - 8. Temporary traffic barriers
- 9. Crash cushions
 - 10. Screens
 - 11. Rumble strips
 - 12. More delineation
 - B. Upgrading of devices:
 - 1. A full complement of standard pavement markings
 - 2. Brighter and/or wider pavement markings
 - 3. Larger and/or brighter signs
 - 4. Channelizing devices with greater conspicuity
- 48 5. Temporary traffic barriers in place of channelizing devices
- 49 C. Improved geometrics at detours or crossovers
 - D. Increased distances:

- 1. Longer advance warning area
 - 2. Longer tapers
- 3 E. Lighting:

2

4

5

6

7

8

9

10

11

13

14 15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38 39

40

41

43

44

45

46 47

48

49

- 1. Temporary roadway lighting
 - 2. Steady-burn lights used with channelizing devices
 - 3. Flashing lights for isolated hazards
 - 4. Illuminated signs
 - 5. Floodlights
- F. Pedestrian routes and temporary facilities
- G. Bicycle diversions and temporary facilities

Section 6G.056N.04 Work Affecting Pedestrian and Bicycle Facilities

12 Support:

It is not uncommon, particularly in urban areas, that road work and the associated TTC will affect existing pedestrian or bicycle facilities. It is essential that the needs of all road users, including pedestrians with disabilities, are considered in TTC zones.

In addition to specific provisions identified in Sections 6G.066N.05 through 6G.146N.13, there are a number of provisions that might be applicable for all of the types of activities identified in this Chapter. *Guidance:*

Where pedestrian or bicycle usage is high, the typical applications should be modified by giving particular attention to the provisions set forth in Chapter 6D6C, this Chapter, Section 6F.746M.04, and in other Sections of Part 6 related to accessibility and detectability provisions in TTC zones.

Pedestrians should be separated from the worksite by appropriate devices that maintain the accessibility and detectability for pedestrians with disabilities.

Bicyclists and pedestrians should not be exposed to unprotected excavations, open utility access, overhanging equipment, or other such conditions.

Except for short duration and mobile operations, when a highway shoulder is occupied, a SHOULDER WORK (W21-5) sign should be placed in advance of the activity area. When work is performed on a paved shoulder 8 feet or more in width, channelizing devices should be placed on a taper having a length that conforms to the requirements of a shoulder taper. Signs should be placed such that they do not narrow any existing pedestrian passages to less than 48 inches.

Pedestrian detours should be avoided since pedestrians rarely observe them and the cost of providing accessibility and detectability might outweigh the cost of maintaining a continuous route. Whenever possible, work should be done in a manner that does not create a need to detour pedestrians from existing routes or crossings.

Standard:

Where pedestrian routes are closed, alternate pedestrian routes shall be provided.

When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and shall include accessibility features consistent with the features present in the existing pedestrian facility.

Guidance:

The continuity of a bikeway should be maintained through the TTC zone if practical.

42 Support:

The continuity of a bikeway through the TTC zone is particularly important where bicyclists have been traveling on a shoulder, bike lane, or shared-use path adjacent to a lane (having a speed limit greater than or equal to 35 miles per hour) and there would be a significant safety concern if bicyclists were to share that lane through the TTC zone.

On roadways which are not bikeways but where bicyclists (when present) typically share lanes with motor vehicle traffic, the TTC plan and Typical Applications for general traffic will usually be adequate for bicyclists as well.

1 <u>In order to maintain room for bicycle lanes through the TTC zone on a multi-lane roadway, one or more travel lanes could be closed.</u>

Guidance:

If a bikeway detour is unavoidable, it should be as short and direct as practical.

On-road bicyclists should not be directed onto a path or sidewalk intended for pedestrian use except where such a path or sidewalk is a shared-use path, or where no practical alternative is available (such as might be the case on a bridge in the course of a rehabilitation project).

If a portion of a bikeway is to be closed due to construction activities and the detoured bikeway follows a complex path not in the original bikeway corridor, then a full detour plan should be developed and implemented. The TTC for the detour of the bikeway should include all necessary advance warning (W21 series) signs, detour (W4-9 series) signs, and any other TTC devices necessary to guide bicyclists along the detour route.

13 Support:

Figures 6P-49 through 6P-53 provide examples and contain additional information for accommodating bicycles through or around typical work zones.

16 Option:

If an on-street bikeway had a wide travel lane or lanes in which bicycles traveled side by side with motor vehicles prior to construction, and construction activities reduce the lane width(s) to less than 17 feet through the TTC zone, then the BICYCLES MAY USE FULL LANE (R4-11) sign may be used.

Standard:

The minimum TTC sign and plaque sizes for shared-use paths shall conform to those shown in Table 9B-1. The minimum TTC sign and plaque sizes for on-street bikeways shall conform to Chapters 6G, 6H, and 6I. Added to improve consistency

Section 6C.066N.05 Work Outside of the Shoulder

25 Support:

When work is being performed off the roadway (beyond the shoulders, but within the right-of-way), little or no TTC might be needed. TTC generally is not needed where work is confined to an area 15 feet or more from the edge of the traveled way. However, TTC is appropriate where distracting situations exist, such as vehicles parked on the shoulder, vehicles accessing the worksite via the highway, and equipment traveling on or crossing the roadway to perform the work operations (for example, mowing). For work beyond the shoulder, see Figure 6H6P-1.

Guidance:

Where the situations described in Paragraph 1 exist, a single warning sign, such as ROAD WORK AHEAD (W20-1), should be used. If the equipment travels on the roadway, the equipment should be equipped with appropriate flags, high-intensity rotating, flashing, oscillating, or strobe lights, and/or a SLOW MOVING VEHICLE (W21-4) sign.

If work vehicles are on the shoulder, a SHOULDER WORK (W21-5) sign may should be used. Option changed to Guidance and relocated from below

A general warning sign like ROAD MACHINERY AHEAD (W21-3) should be used if workers and equipment must occasionally move onto the shoulder. Relocated from below Option:

If work vehicles are on the shoulder, a SHOULDER WORK (W21-5) sign may be used. Option changed to Guidance and relocated to above For mowing operations, the sign MOWING AHEAD (W21-8) may be used.

Where the activity is spread out over a distance of more than 2 miles, the SHOULDER WORK (W21-5) sign may be repeated every 1 mile.

A supplementary plaque with the message NEXT XX MILES (W7-3aP) may be used.

Guidance:

1 A general warning sign like ROAD MACHINERY AHEAD (W21-3) should be used if workers and equipment must occasionally move onto the shoulder. Relocated to above

Section 6G.076N.06 Work on the Shoulder with No Encroachment

Support:

The provisions of this Section apply to short-term through long-term stationary operations.

Standard:

When paved shoulders having a width of 8 feet or more are closed, at least one advance warning sign shall be used. In addition, channelizing devices shall be used to close the shoulder in advance to delineate the beginning of the work space and direct motor vehicle traffic to remain within the traveled way.

Guidance:

When paved shoulders having a width of 8 feet or more are closed on freeways and expressways, road users should be warned about potential disabled vehicles that cannot get off the traveled way. An initial general warning sign, such as ROAD WORK AHEAD (W20-1), should be used, followed by a RIGHT or LEFT SHOULDER CLOSED (W21-5a) sign. Where the downstream end of the shoulder closure extends beyond the distance that can be perceived by road users, a supplementary plaque bearing the message NEXT XX FEET (W16-4P) or MILES (W7-3aP) should be placed below the SHOULDER CLOSED (W21-5a) sign. On multi-lane, divided highways, signs advising of shoulder work or the condition of the shoulder should be placed only on the side of the affected shoulder.

When an improved shoulder is closed on a high-speed roadway, it should be treated as a closure of a portion of the road system because road users expect to be able to use it in emergencies. Road users should be given ample advance warning that shoulders are closed for use as refuge areas throughout a specified length of the approaching TTC zone. The sign(s) should read SHOULDER CLOSED (W21-5a) with distances indicated. The work space on the shoulder should be closed off by a taper or channelizing devices with a length of 1/3 L using the formulas in Tables 6C 36B-3 and 6C 46B-4.

When the shoulder is not occupied but work has adversely affected its condition, the LOW SHOULDER (W8-9) or SOFT SHOULDER (W8-4) sign should be used, as appropriate.

Where the condition extends over a distance in excess of 1 mile, the sign should be repeated at 1-mile intervals.

Option:

In addition, a supplementary plaque bearing the message NEXT XX MILES (W7-3aP) may be used. Temporary traffic barriers may be needed to inhibit encroachment of errant vehicles into the work space and to protect workers.

Standard:

When used for shoulder work, arrow boards shall operate only in the caution mode.

36 Support:

A typical application for stationary work operations on shoulders is shown in Figure 6H6P-3. Short duration or mobile work on shoulders is shown in Figure 6H6P-4. Work on freeway shoulders is shown in Figure 6H6P-5.

Section 6G.086N.07 Work on the Shoulder with Minor Encroachment

41 Support:

Chapter 6D 6C and Sections 6F.746M.04 and 6G.056N.04 contain additional information regarding the steps to follow when pedestrian or bicycle facilities are affected by the worksite.

44 Guidance:

When work takes up part of a lane, vehicular traffic volumes, vehicle mix (buses, trucks, cars, and bicycles), speed, and capacity should be analyzed to determine whether the affected lane should be closed. Unless the lane encroachment permits a remaining lane width of 10 feet, the lane should be closed.

1 Truck off-tracking should be considered when determining whether the minimum lane width of 10 feet is 2 adequate.

Option:

3

4

5

6

7

8

9

11

12

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

40

42

43

45

46

A lane width of 9 feet may be used for short-term stationary work on low-volume, low-speed roadways when vehicular traffic does not include longer and wider heavy commercial vehicles.

Support:

Figure 6H6P-6 illustrates a method for handling vehicular traffic where the stationary or short duration work space encroaches slightly into the traveled way.

Section 6G.096N.08 Work Within the Median

10 Support:

Chapter 6D 6C and Sections 6F.746M.04 and 6G.056N.04 contain additional information regarding the steps to follow when pedestrian or bicycle facilities are affected by the worksite.

13 Guidance:

If work in the median of a divided highway is within 15 feet from the edge of the traveled way for either direction of travel, TTC should be used through the use of advance warning signs and channelizing devices.

Section 6C.106N.09 Work Within the Traveled Way of a Two-Lane Highway

Support:

Chapter 6D-6C and Sections 6F.746M.04 and 6G.056N.04 contain additional information regarding the steps to follow when pedestrian or bicycle facilities are affected by the worksite.

Detour signs are used to direct road users onto another roadway. At diversions, road users are directed onto a temporary roadway or alignment placed within or adjacent to the right-of-way. Typical applications for detouring or diverting road users on two-lane highways are shown in Figures 6H6P-7, 6H6P-8, and 6H6P-9. Figure 6H6P-7 illustrates the controls around an area where a section of roadway has been closed and a diversion has been constructed. Channelizing devices and pavement markings are used to indicate the transition to the temporary roadway.

Guidance:

When a detour is long, Detour (M4-8, M4-9) signs should be installed to remind and reassure road users periodically that they are still successfully following the detour.

When an entire roadway is closed, as illustrated in Figure 6H6P-8, a detour should be provided and road users should be warned in advance of the closure, which in this example is a closure 10 miles from the intersection. If local road users are allowed to use the roadway up to the closure, the ROAD CLOSED AHEAD, LOCAL TRAFFIC ONLY (R11-3a) sign should be used. The portion of the road open to local road users should have adequate signing, marking, and delineation.

Detours should be signed so that road users will be able to traverse the entire detour route and back to the original roadway as shown in Figure 6H6P-9.

Support:

Techniques for controlling vehicular traffic under one-lane, two-way conditions are described in Section 6C.106E.01.

39 Option:

Flaggers may be used as shown in Figure 6H6P-10.

41 STOP/YIELD sign control may be used on roads with low traffic volumes as shown in Figure 6H6P-11.

A temporary traffic control signal may be used as shown in Figure 6H6P-12.

Section 6C.116N.10 Work Within the Traveled Way of an Urban Street

44 Support:

Chapter 6D-6C and Sections 6F.746M.04 and 6G.056N.04 contain additional information regarding the steps to follow when pedestrian or bicycle facilities are affected by the worksite.

In urban TTC zones, decisions are needed on how to control vehicular traffic, such as how many lanes are required, whether any turns need to be prohibited at intersections, and how to maintain access to business, industrial, and residential areas.

Pedestrian traffic needs separate attention. Chapter 6D-6C contains information regarding pedestrian movements near TTC zones.

Standard:

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31 32

33

34

35

36

37

38

39

40

41

42

43

44

46

If the TTC zone affects the movement of bicyclists, adequate access to the roadway or shared-use paths shall be provided (see Part 9).

Where transit stops are affected or relocated because of work activity, both pedestrian and vehicular access to the affected or relocated transit stops shall be provided.

Guidance:

If a designated bicycle route is closed because of the work being done, a signed alternate route should be provided. Bicyclists should not be directed onto the path used by pedestrians.

Worksites within the intersection should be protected against inadvertent pedestrian incursion by providing detectable channelizing devices.

Support:

Utility work takes place both within and outside the roadway to construct and maintain services such as power, gas, light, water, or telecommunications. Operations often involve intersections, since that is where many of the network junctions occur. The work force is usually small, only a few vehicles are involved, and the number and types of TTC devices placed in the TTC zone is usually minimal.

Standard:

All TTC devices shall be retroreflective or illuminated if utility work is performed during nighttime hours. Deleted; redundant with other sections in Part 6

Guidance:

As discussed under short-duration projects, however, the reduced number of devices in utility work zones should be offset by the use of high-visibility devices, such as high-intensity rotating, flashing, oscillating, or strobe lights on work vehicles or high-level warning devices.

Support:

Figures 6H6P-6, 6H6P-10, 6H6P-15, 6H6P-18, 6H6P-21, 6H6P-22, 6H6P-23, 6H6P-26, and 6H6P-33 are examples of typical applications for utility operations. Other typical applications might apply as well.

Section 6G.126N.11 Work Within the Traveled Way of a Multi-Lane, Non-Access Controlled Highway

Support:

Chapter 6D6C and Sections 6F.746M.04 and 6G.056N.04 contain additional information regarding the steps to follow when pedestrian or bicycle facilities are affected by the worksite.

Work on multi-lane (two or more lanes of moving motor vehicle traffic in one direction) highways is divided into right-lane closures, left-lane closures, interior-lane closures, multiple-lane closures, and closures on five-lane roadways.

Standard:

When a lane is closed on a multi-lane road for other than a mobile operation, a transition area containing a merging taper shall be used.

Guidance:

When justified by an engineering study, temporary traffic barriers (see Section <u>6F.706K.09</u>) should be used to prevent incursions of errant vehicles into hazardous areas or work space.

45 Support:

Figure 6H6P-34 illustrates a lane closure in which temporary traffic barriers are used.

47 Option:

When the right-hand lane is closed, TTC similar to that shown in Figure 6H6P-33 may be used for undivided or divided four-lane roads.

Guidance:

If morning and evening peak hour vehicular traffic volumes in the two directions are uneven and the greater volume is on the side where the work is being done in the right-hand lane, consideration should be given to closing the inside lane for opposing vehicular traffic and making the lane available to the side with heavier vehicular traffic, as shown in Figure 6H6P-31.

If the larger vehicular traffic volume changes to the opposite direction at a different time of the day, the TTC should be changed to allow two lanes for opposing vehicular traffic by moving the devices from the opposing lane to the center line. When it is necessary to create a temporary center line that is not consistent with the pavement markings, channelizing devices should be used and closely spaced.

Option:

When closing a left-hand lane on a multi-lane undivided road, as vehicular traffic flow permits, the two interior lanes may be closed, as shown in Figure 6H6P-30, to provide drivers and workers additional lateral clearance and to provide access to the work space.

Standard:

When only the left-hand lane is closed on undivided roads, channelizing devices shall be placed along the center line as well as along the adjacent lane.

Guidance:

When an interior lane is closed, an adjacent lane should also be considered for closure to provide additional space for vehicles and materials and to facilitate the movement of equipment within the work space.

When multiple lanes in one direction are closed, a capacity analysis should be made to determine the number of lanes needed to accommodate motor vehicle traffic needs. Vehicular traffic should be moved over one lane at a time. As shown in Figure $\frac{6H6P}{5}$ -37, the tapers should be separated by a distance of 2L, with L being determined by the formulas in Tables $\frac{6C-3}{5}$ and $\frac{6C-4}{5}$.

Option:

If operating speeds are 40 mph or less and the space approaching the work area does not permit moving traffic over one lane at a time, a single continuous taper may be used.

Standard:

When a directional roadway is closed, inapplicable WRONG WAY signs and markings, and other existing traffic control devices at intersections within the temporary two-lane, two-way operations section shall be covered, removed, or obliterated.

Option:

When half the road is closed on an undivided highway, both directions of vehicular traffic may be accommodated as shown in Figure 6H6P-32. When both interior lanes are closed, temporary traffic controls may be used as provided in Figure 6H6P-30. When a roadway must be closed on a divided highway, a median crossover may be used (see Section 6G.166N.15).

Support:

TTC for lane closures on five-lane roads is similar to other multi-lane undivided roads. Figure $\frac{6H_{6P}}{32}$ can be adapted for use on five-lane roads. Figure $\frac{6H_{6P}}{35}$ can be used on a five-lane road for short duration and mobile operations.

Section 6G.136N.12 Work Within the Traveled Way at an Intersection

Support:

Chapter 6D6C and Sections 6F.746M.04 and 6G.056N.04 contain additional information regarding the steps to follow when pedestrian or bicycle facilities are affected by the worksite.

The typical applications for intersections are classified according to the location of the work space with respect to the intersection area (as defined by the extension of the curb or edge lines). The three classifications are near side, far side, and in-the-intersection. Work spaces often extend into more than one Notice of Proposed Amendments – Part 6

Page 600 of 781

December 2020

portion of the intersection. For example, work in one quadrant often creates a near-side work space on one street and a far-side work space on the cross street. In such instances, an appropriate TTC plan is obtained by combining features shown in two or more of the intersection and pedestrian typical applications.

TTC zones in the vicinity of intersections might block movements and interfere with normal road user flows. Such conflicts frequently occur at more complex signalized intersections having such features as traffic signal heads over particular lanes, lanes allocated to specific movements, multiple signal phases, signal detectors for actuated control, and accessible pedestrian signals and detectors.

Guidance:

The effect of the work upon signal operation should be considered, and temporary corrective actions should be taken, if necessary, such as revising signal phasing and/or timing to provide adequate capacity, maintaining or adjusting signal detectors, and relocating signal heads to provide adequate visibility as described in Part 4.

Standard:

When work will occur near an intersection where operational, capacity, or pedestrian accessibility problems are anticipated, the highway agency having jurisdiction shall be contacted.

Guidance:

For work at an intersection, advance warning signs, devices, and markings should be used on all cross streets, as appropriate. The typical lications depict urban intersections on arterial streets. Where the posted speed limit, the off-peak 85th entitle speed prior to the work starting, or the anticipated speed exceeds 40 mph, additional warning signs should be used in the advance warning area.

Pedestrian crossings near TTC sites should be separated from the worksite by appropriate barriers that maintain the accessibility and detectability for pedestrians with disabilities.

Support:

Near-side work spaces, as depicted in Figure 6H6P-21, are simply handled as a midblock lane closure. A problem that might occur with near-side lane closure is a reduction in capacity, which during certain hours of operation could result in congestion and backups.

Option:

When near-side work spaces are used, an exclusive turn lane may be used for through vehicular traffic.

Where space is restricted in advance of near-side work spaces, as with short block spacings, two warning signs may be used in the advance warning area, and a third action-type warning or a regulatory sign (such as Keep Left) may be placed within the transition area.

Support:

Far-side work spaces, as depicted in Figures $6\underline{H}\underline{6P}$ -22 through $6\underline{H}\underline{6P}$ -25, involve additional treatment because road users typically enter the activity area by straight-through and left- or right-turning movements.

Guidance.

When a lane through an intersection must be closed on the far side, it should also be closed on the near-side approach to preclude merging movements within the intersection.

Option:

If there are a significant number of vehicles turning from a near-side lane that is closed on the far side, the near-side lane may be converted to an exclusive turn lane.

Support:

Figures 6H6P-26 and 6H6P-27 provide guidance on applicable procedures for work performed within the intersection.

Option:

If the work is within the intersection, any of the following strategies may be used:

- A. A small work space so that road users can move around it, as shown in Figure 6H6P-26;
- B. Flaggers or uniformed law enforcement officers to direct road users, as shown in Figure 6H6P-27;
 - C. Work in stages so the work space is kept to a minimum; and
 - D. Road closures or upstream diversions to reduce road user volumes.

Guidance:

Depending on road user conditions, a flagger(s) and/or a uniformed law enforcement officer(s) should be used to control road users.

Support:

Work at a roundabout can present a challenge for developing an effective TTC plan. Figures 6P-47 and 6P-48 provide guidance on applicable procedures for work performed within a roundabout. Added to improve consistency

Section 6G.146N.13 Work Within the Traveled Way of a Freeway or Expressway

Support:

Problems of TTC might occur under the special conditions encountered where vehicular traffic must be moved through or around TTC zones on high-speed, high-volume roadways. Although the general principles outlined in the previous Sections of this Manual are applicable to all types of highways, high-speed, access-controlled highways need special planning and attention in order to accommodate vehicular traffic while also protecting road users and workers. The road user volumes, road vehicle mix (buses, trucks, cars, and bicycles, if permitted), and speed of vehicles on these facilities require that careful TTC procedures be implemented, for example, to induce critical merging maneuvers well in advance of work spaces and in a manner that creates minimum turbulence and delay in the vehicular traffic stream. These situations often require more conspicuous devices than specified for normal rural highway or urban street use. However, the same important basic considerations of uniformity and standardization of general principles apply for all roadways.

Edited to reflect NTSB H-15-16 recommendation

Work under high speed, high volume vehicular traffic on a controlled access highway is complicated by the roadway design and operational features. The presence of a median that establishes separate roadways for directional vehicular traffic flow might prohibit the closing of one of the roadways or the diverting of vehicular traffic to the other roadway. Lack of access to and from adjacent roadways prohibits rerouting of vehicular traffic away from the work space in many cases. Other conditions exist where work must be limited to night hours, thereby necessitating increased use of warning lights, illumination of work spaces, and advance warning systems.

Often, when the roadway capacity is reduced due the lane closures, the demand will exceed the available capacity and result in either a lengthy stopped or slow moving queue of vehicles that may extend past the normal signs shown in the typical advance warning area. An assessment of the expected queue length should be a part of the temporary traffic control plan design process and adjustments to the sign spacing and number of signs as well as the possibility of using more conspicuous devices may be provided to increase the distance and conspicuity of the advance warning area. Added to reflect NTSB H-15-16 recommendation

One strategy often employed to mitigate the extended queue issue is to work during off peak hours or at night. When the work is limited to night hours, increased us of warning lights, illumination of work spaces, and intelligent advance warning systems may be necessary.

Added to reflect NTSB H-15-16 recommendation

TTC for a typical lane closure where a queue is not anticipated to accumulate on a divided highway is shown in Figure 6H6P-33. Edited to reflect NTSB H-15-16 recommendation Temporary traffic controls for short duration and mobile operations on freeways are shown in Figure 6H6P-35. A typical application for shifting vehicular traffic lanes around a work space is shown in Figure 6H6P-36. TTC for multiple and interior lane closures on a freeway is shown in Figures 6H6P-37 and 6H6P-38.

Guidance:

The method for closing an interior lane when the open lanes have the capacity to carry vehicular traffic should be as shown in Figure 6H6P-37. When the capacity of the other lanes is needed, the method shown in Figure 6H6P-38 should be used.

Section 6G.156N.14 Two-Lane, Two-Way Traffic on One Roadway of a Normally Divided Highway

49 Support:

Two-lane, two-way operation on one roadway of a normally divided highway is a typical procedure that requires special consideration in the planning, design, and work phases, because unique operational problems (for example, increasing the risk of head-on crashes) can arise with the two-lane, two-way operation.

Standard:

When two-lane, two-way traffic control must be maintained on one roadway of a normally divided highway, opposing vehicular traffic shall be separated with either temporary traffic barriers (concrete safety-shape or approved alternate), channelizing devices, Opposing Lane Traffic Divider (W6-4) signs on flexible supports (see Section 6H.17), or a temporary raised island throughout the length of the two-way operation. Edited to improve clarity The use of markings and complementary signing, by themselves, shall not be used.

Support:

Figure 6H6P-39 shows the procedure for two-lane, two-way operation. Treatments for entrance and exit ramps within the two-way roadway segment of this type of work are shown in Figures 6H6P-40 and 6H6P-41.

Section 6G.166N.15 Crossovers

15 Guidance:

The following are considered good guiding principles for the design of crossovers:

- A. Tapers for lane drops should be separated from the crossovers, as shown in Figure 6H6P-39.
- B. Crossovers should be designed for speeds no lower than 10 mph below the posted speed, the off-peak 85th-pentile speed prior to the work starting, or the anticipated operating speed of the roadway, unless unusual site conditions require that a lower design speed be used.
- C. A good array of channelizing devices, delineators, and full-length, properly placed pavement markings should be used to provide drivers with a clearly defined travel path.
- D. The design of the crossover should accommodate all vehicular traffic, including trucks and buses.

24 Support:

Temporary traffic barriers and the excessive use of TTC devices cannot compensate for poor geometric and roadway cross-section design of crossovers.

Section 6G.176N.16 Interchanges

Guidance:

Access to interchange ramps on limited-access highways should be maintained even if the work space is in the lane adjacent to the ramps. Access to exit ramps should be clearly marked and delineated with channelizing devices. For long-term projects, conflicting pavement markings should be removed and new ones placed. Early coordination with officials having jurisdiction over the affected cross streets and providing emergency services should occur before ramp closings.

Option:

If access is not possible, ramps may be closed by using signs and Type 3 Barricades. As the work space changes, the access area may be changed, as shown in Figure 6H6P-42. A TTC zone in the exit ramp may be handled as shown in Figure 6H6P-43.

When a work space interferes with an entrance ramp, a lane may need to be closed on the freeway (see Figure 6H6P-44). A TTC zone in the entrance ramp may require shifting ramp vehicular traffic (see Figure 6H6P-44).

Section 6G.186N.17 Work in the Vicinity of a Grade Crossing

Standard:

When grade crossings exist either within or in the vicinity of a TTC zone, lane restrictions, flagging, or other operations shall not create conditions where vehicles can be queued across the tracks. If the queuing of vehicles across the tracks cannot be avoided, a uniformed law enforcement officer or flagger shall be provided at the crossing to prevent vehicles from stopping on the tracks, even if automatic warning devices are in place.

48 Support:

Figure 6H6P-46 shows work in the vicinity of a grade crossing.

Section 8A.<u>0814</u> contains additional information regarding temporary traffic control zones in the vicinity of grade crossings.

4 Guidance:

Early coordination with the railroad company or light rail transit agency should occur before work starts.

Section 6C.196N.18 Temporary Traffic Control Work During Nighttime Hours

Support:

Chapter 6D and Sections 6F.74 and 6G.05 6A.05 contains additional information regarding the steps to follow when pedestrian or bicycle facilities are affected by the worksite considerations for conducting work operations during nighttime hours. Edited to reflect reorganization of text into new Section 6A.05

Conducting highway construction and maintenance activities during night hours could provide an advantage when traditional daytime traffic control strategies cannot achieve an acceptable balance between worker and public safety, traffic and community impact, and constructability. The two basic advantages of working at night are reduced traffic congestion and less involvement with business activities. However, the two basic conditions that must normally be met for night work to offer any advantage are reduced traffic volumes and easy set up and removal of the traffic control patterns on a nightly basis. This text was relocated to new Section 6A.05

Shifting work activities to night hours, when traffic volumes are lower and normal business is less active, might offer an advantage in some cases, as long as the necessary work can be completed and the worksite restored to essentially normal operating conditions to carry the higher traffic volume during non-construction hours. This text was relocated to new Section 6A.05

Although working at night might offer advantages, it also includes safety issues. Reduced visibility inherent in night work impacts the performance of both drivers and workers. Because traffic volumes are lower and congestion is minimized, speeds are often higher at night necessitating greater visibility at a time-when visibility is reduced. Finally, the incidence of impaired (alcohol or drugs), fatigued, or drowsy drivers—might be higher at night. This text was relocated to new Section 6A.05

Working at night also involves other factors, including construction productivity and quality, social impacts, economics, and environmental issues. A decision to perform construction or maintenance activities at night normally involves some consideration of the advantages to be gained compared to the safety and other issues that might be impacted. This text was relocated to new Section 6A.05

Guidance:

Considering the safety issues inherent to night work, consideration should be given to enhancing traffic controls (see Section 6G.046N.03) to provide added visibility and driver guidance, and increased protection for workers.

In addition to the enhancements listed in Section <u>6G.046N.03</u>, consideration should be given to providing additional lights and retroreflective markings to workers, work vehicles, and equipment.

Option:

Where reduced traffic volumes at night make it feasible, the entire roadway may be closed by detouring traffic to alternate facilities, thus removing the traffic risk from the activity area.

Guidance:

Consideration should be given to stationing uniformed law enforcement officers and lighted patrol cars at night work locations where there is a concern that high speeds or impaired drivers might result in undue risks for workers or other drivers.

Standard:

Except in emergencies, temporary lighting shall be provided at all flagger stations <u>used during</u> <u>nighttime work</u>. Edited to improve clarity

47 Support

Desired illumination levels vary depending upon the nature of the task involved. An average horizontal luminance of 5 foot candles can be adequate for general activities. An average horizontal luminance of 10

1 foot candles can be adequate for activities around equipment. Tasks requiring high levels of precision and 2 extreme care can require an average horizontal luminance of 20 foot candles. 3 Section 6N.19 Late Merge Added to improve clarity 4 Support: 5 The Late Merge is designed to use all available lanes until the merge point is reached at the lane closure 6 taper rather than merging as soon as possible into the open lane. The Late Merge addresses many of the 7 problems associated with traffic operations in advance of lane closures at work zones to include queue length, 8 capacity and driver satisfaction. 9 Option: 10 Late merging systems may consist of static or portable changeable message signs. 11 Guidance: 12 Static Late Merge signing should consist of the STAY IN LANE TO MERGE POINT (R4-9a) sign and the MERGE HERE TAKE TURNS (W9-2a) sign (see Figure 6N-1). 13 14 If used, the Late Merge should not be used on high speed or low volume roadways. 15 Option: 16 The following messages may be used on changeable message signs during the late merge application: 17 A. "STAY IN YOUR LANE / MERGE AHEAD" B. "USE BOTH LANES / TO MERGE POINT"; "TAKE YOUR TURN / MERGE HERE" 18 19 C. "SLOW TRAFFIC AHEAD / USE BOTH LANES", "STAY IN YOUR LANE / MERGE AHEAD XX MILES", "TAKE YOUR TURN / MERGE HERE" 20 D. "USE BOTH LANES," "STOP TRAFFIC AHEAD," "MERGE HERE," and "TAKE TURNS" 21 22 E. "STAY IN YOUR LANE" / "MERGE AHEAD"

2324

CHAPTER 6160. CONTROL OF TRAFFIC THROUGH TRAFFIC INCIDENT MANAGEMENT AREAS

Section 61.016O.01 General

Support:

The National Incident Management System (NIMS) requires the use of the Incident Command System (ICS) at traffic incident management scenes.

A traffic incident is an emergency road user occurrence, a natural disaster, or other unplanned event that affects or impedes the normal flow of traffic.

A traffic incident management area is an area of a highway where temporary traffic controls are installed, as authorized by a public authority or the official having jurisdiction of the roadway, in response to a road user incident, natural disaster, hazardous material spill, or other unplanned incident. It is a type of TTC zone and extends from the first warning device (such as a sign, light, or cone) to the last TTC device or to a point where vehicles return to the original lane alignment and are clear of the incident.

Traffic incidents can be divided into three general classes of duration, each of which has unique traffic control characteristics and needs. These classes are:

- A. Major—expected duration of more than 2 hours,
- B. Intermediate—expected duration of 30 minutes to 2 hours, and
- C. Minor—expected duration under 30 minutes.

The primary functions of TTC at a traffic incident management area are to inform road users of the incident and to provide guidance information on the path to follow through the incident area. Alerting road users and establishing a well-defined path to guide road users through the incident area will serve to protect the incident responders and those involved in working at the incident scene and will aid in moving road users expeditiously past or around the traffic incident, will reduce the likelihood of secondary traffic crashes, and will preclude unnecessary use of the surrounding local road system. Examples include a stalled vehicle blocking a lane, a traffic crash blocking the traveled way, a hazardous material spill along a highway, and natural disasters such as floods and severe storm damage.

Guidance:

In order to reduce response time for traffic incidents, highway agencies, appropriate public safety agencies (law enforcement, fire and rescue, emergency communications, emergency medical, and other emergency management), and private sector responders (towing and recovery and hazardous materials contractors) should mutually plan for occurrences of traffic incidents along the major and heavily traveled highway and street system.

On-scene responder organizations should train their personnel in TTC practices for accomplishing their tasks in and near traffic and in the requirements for traffic incident management contained in this Manual. On-scene responders should take measures to move the incident off the traveled roadway or to provide for appropriate warning. All on-scene responders and news media personnel should constantly be aware of their visibility to oncoming traffic and wear high-visibility apparel. Planning and training should include incorporation of estimated time durations to clear the event as part of their initial incident estimate. When events are deemed as probable Major Traffic Incidents that may or will generate prolonged lane or road closures, notification of all affected agencies should be initiated and may be included as part of the initial incident report that is provided to the emergency communications center who would then be responsible for making notifications to appropriate state, regional and local agencies and resources for the purpose of ramping up and responding as quickly as possible thus facilitating a more rapid transition from emergency TTC to MUTCD compliant work zone when warranted. Added to improve accuracy

Emergency vehicles <u>arriving at an incident</u> should be <u>safe</u>-positioned (<u>see definition in Section 1A.13</u>) <u>in a manner that attempts to protect both the responders performing their duties and road users traveling through the incident scene, while minimizing, to the extent practical, disruption of the adjacent traffic flow.

<u>Emergency vehicle positions should such that optimize</u> traffic flow through the incident scene <u>is optimized</u>.

<u>Edited to improve accuracy</u> All emergency vehicles that subsequently arrive should be positioned in a manner that does not interfere with the established temporary traffic flow.</u>

Responders arriving at a traffic incident should estimate the magnitude of the traffic incident, the expected time duration of the traffic incident, and the expected vehicle queue length, and then should set up the appropriate temporary traffic controls for these estimates. Option: Warning and guide signs used for TTC traffic incident management situations may have a black legend and border on a fluorescent pink background (see Figure 61-160-1). Support: While some traffic incidents might be anticipated and planned for, emergencies and disasters might pose more severe and unpredictable problems. The ability to quickly install proper temporary traffic controls might greatly reduce the effects of an incident, such as secondary crashes or excessive traffic delays. An essential part of fire, rescue, spill clean-up, highway agency, and enforcement activities is the proper control of road users through the traffic incident management area in order to protect responders, victims, and other personnel at the site. These operations might need corroborating legislative authority for the implementation and enforcement of appropriate road user regulations, parking controls, and speed zoning. It is desirable for these statutes to provide sufficient flexibility in the authority for, and implementation of, TTC to respond to the needs of changing conditions found in traffic incident management areas. Option: For traffic incidents, particularly those of an emergency nature, TTC devices on hand may be used for the initial response as long as they do not themselves create unnecessary additional hazards. Support: The establishment, maintenance, and prompt removal of lane diversions can be effectively managed by interagency planning that includes representatives of highway and public safety agencies. This text was relocated from existing Section 6I.02 Guidance: All traffic control devices needed to set up the TTC at a traffic incident should be available so that they can be readily deployed for all major traffic incidents. The TTC should include the proper traffic diversions, tapered lane closures, and upstream warning devices to alert traffic approaching the queue and to encourage early diversion to an appropriate alternative route. This text was relocated from existing Section 6I.02 Attention should be paid to the upstream end of the traffic queue such that warning is given to road users approaching the back of the queue. This text was relocated to new Section 61.02 If manual traffic control is needed, it should be provided by qualified flaggers or uniformed law enforcement officers. This text was relocated to new Section 6I.02 Option: If flaggers are used to provide traffic control for an incident management situation, the flaggers may use

appropriate traffic control devices that are readily available or that can be brought to the traffic incident scene on short notice. This text was relocated to new Section 61.02

Guidance:

1

2

3

4

5

6

7

8

9

10

11 12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30 31

32 33

34

35

36 37

38

39

40

41

42

43

44

45

46

47

48

When light sticks or flares are used to establish the initial traffic control at incident scenes, channelizing devices (see Section 6F.636K.01) should be installed as soon thereafter as practical. This text was relocated to new Section 6I.02

Option:

The light sticks or flares may remain in place if they are being used to supplement the channelizing devices. This text was relocated to new Section 6I.02

Guidance:

The light sticks, flares, and channelizing devices should be removed after the incident is terminated. This text was relocated to new Section 6I.02

Figure 6O-1. Examples of Traffic Incident Management Area Signs

Section 61.0260.02 Major Traffic Incidents

Support:

Major traffic incidents are typically traffic incidents involving hazardous materials, fatal traffic crashes involving numerous vehicles, and other natural or man-made disasters. These traffic incidents typically involve closing all or part of a roadway facility for a period exceeding 2 hours.

Guidance:

If the traffic incident is anticipated to last more than 24 hours, applicable procedures and devices set forth in other Chapters of Part 6 should be used.

Support:

A road closure can be caused by a traffic incident such as a road user crash that blocks the traveled way. Road users are usually diverted through lane shifts or detoured around the traffic incident and back to the original roadway. A combination of traffic engineering and enforcement preparations is needed to determine the detour route, and to install, maintain or operate, and then to remove the necessary traffic control devices when the detour is terminated. Large trucks are a significant concern in such a detour, especially when detouring them from a controlled-access roadway onto local or arterial streets.

During traffic incidents, large trucks might need to follow a route separate from that of automobiles because of bridge, weight, clearance, or geometric restrictions. Also, vehicles carrying hazardous material might need to follow a different route from other vehicles.

Some traffic incidents such as hazardous material spills might require closure of an entire highway. Through road users must have adequate guidance around the traffic incident. Maintaining good public relations is desirable. The cooperation of the news media in publicizing the existence of, and reasons for, traffic incident management areas and their TTC can be of great assistance in keeping road users and the general public well informed.

Support:

The establishment, maintenance, and prompt removal of lane diversions can be effectively managed by interagency planning that includes representatives of highway and public safety agencies. This text was relocated to new Section 6O.01

Guidance:

All traffic control devices needed to set up the TTC at a traffic incident should be available so that they can be readily deployed for all major traffic incidents. The TTC should include the proper traffic diversions, tapered lane closures, and upstream warning devices to alert traffic approaching the queue and to encourage early diversion to an appropriate alternative route. This text was relocated to new Section 60.01

Attention should be paid to the upstream end of the traffic queue such that warning is given to road users approaching the back of the queue. This text was relocated to new Section 60.01

If manual traffic control is needed, it should be provided by qualified flaggers or uniformed law enforcement officers. This text was relocated to new Section 60.01

Option:

If flaggers are used to provide traffic control for an incident management situation, the flaggers may use appropriate traffic control devices that are readily available or that can be brought to the traffic incident scene on short notice. This text was relocated to new Section 60.01

Guidance:

When light sticks or flares are used to establish the initial traffic control at incident scenes, channelizing devices (see Section 6F.63) should be installed as soon thereafter as practical. This text was relocated to new Section 6O.01

Option:

The light sticks or flares may remain in place if they are being used to supplement the channelizing devices. This text was relocated to new Section 60.01

47 Guidance:

The light sticks, flares, and channelizing devices should be removed after the incident is terminated. This text was relocated to new Section 60.01

Section 61.0360.03 Intermediate Traffic Incidents

Support:

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16 17

18 19

20

21

22

24

25

26

28

29

31

32

33

35

36

37

38

39

40

41

42

43

44

46

47

Intermediate traffic incidents typically affect travel lanes for a time period of 30 minutes to 2 hours, and usually require traffic control on the scene to divert road users past the blockage. Full roadway closures might be needed for short periods during traffic incident clearance to allow traffic incident responders to accomplish their tasks.

The establishment, maintenance, and prompt removal of lane diversions can be effectively managed by interagency planning that includes representatives of highway and public safety agencies. Deleted; redundant with new Section 60.01

Guidance:

All traffic control devices needed to set up the TTC at a traffic incident should be available so that they can be readily deployed for intermediate traffic incidents. The TTC should include the proper traffic diversions, tapered lane closures, and upstream warning devices to alert traffic approaching the queue and to encourage early diversion to an appropriate alternative route. Deleted; redundant with new Section 60.01

Attention should be paid to the upstream end of the traffic queue such that warning is given to road users approaching the back of the queue. Deleted; redundant with new Section 60.01

If manual traffic control is needed, it should be provided by qualified flaggers or uniformed law enforcement officers. Deleted; redundant with new Section 60.01

Option:

If flaggers are used to provide traffic control for an incident management situation, the flaggers may use appropriate traffic control devices that are readily available or that can be brought to the traffic incident scene on short notice. Deleted; redundant with new Section 60.01

23 Guidance:

When light sticks or flares are used to establish the initial traffic control at incident scenes, channelizing devices (see Section 6F.63) should be installed as soon thereafter as practical.

Deleted; redundant with new Section 6O.01

27 Option:

The light sticks or flares may remain in place if they are being used to supplement the channelizing devices. Deleted; redundant with new Section 60.01

30 Guidance:

The light sticks, flares, and channelizing devices should be removed after the incident isterminated. Deleted; redundant with new Section 60.01

Section 61.0460.04 Minor Traffic Incidents

34 Support:

Minor traffic incidents are typically disabled vehicles and minor crashes that result in lane closures of less than 30 minutes. On-scene responders are typically law enforcement and towing companies, and occasionally highway agency service patrol vehicles.

Diversion of traffic into other lanes is often not needed or is needed only briefly. It is not generally possible or practical to set up a lane closure with traffic control devices for a minor traffic incident. Traffic control is the responsibility of on-scene responders.

Guidance:

When a minor traffic incident blocks a travel lane, it should be removed from that lane to the shoulder as quickly as possible.

Section 61.0560.05 Use of Emergency-Vehicle Lighting

45 Support:

The use of emergency-vehicle lighting (such as high-intensity rotating, flashing, oscillating, or strobe lights) is essential, especially in the initial stages of a traffic incident, for the safety of emergency responders

and persons involved in the traffic incident, as well as road users approaching the traffic incident. Emergency-vehicle lighting, however, provides warning only and provides no effective traffic control. The use of too many lights at an incident scene can be distracting and can create confusion for approaching road users, especially at night. Road users approaching the traffic incident from the opposite direction on a divided facility are often distracted by emergency-vehicle lighting and slow their vehicles to look at the traffic incident posing a hazard to themselves and others traveling in their direction.

The use of emergency-vehicle lighting can be reduced if good traffic control has been established at a traffic incident scene. This is especially true for major traffic incidents that might involve a number of emergency vehicles. If good traffic control is established through placement of advance warning signs and traffic control devices to divert or detour traffic, then public safety agencies can perform their tasks on scene with minimal emergency-vehicle lighting.

Guidance:

Public safety agencies should examine their policies on the use of emergency-vehicle lighting, especially after a traffic incident scene is secured, with the intent of reducing the use of this lighting as much as possible while not endangering those at the scene. Special consideration should be given to reducing or extinguishing forward facing emergency-vehicle lighting, especially on divided roadways, to reduce distractions to oncoming road users.

Because the glare from floodlights or vehicle headlights can impair the nighttime vision of approaching road users, any floodlights or vehicle headlights that are not needed for illumination, or to provide notice to other road users of an incident response vehicle being in an unexpected location, should be turned off at night.

Section 6H.016P.01 Typical Applications

Support:

Chapter 6G-6N contains discussions of typical TTC activities. Section 6A.02 contains discussions on development of TTC plans for the various activities. Added to reflect reorganization of text into new Section 6A.02 This Chapter presents typical applications for a variety of situations commonly encountered. While not every situation is addressed, the information illustrated can generally be adapted to a broad range of conditions. In many instances, an appropriate TTC plan is achieved by combining features from various typical applications. For example, work at an intersection might present a near-side work zone for one street and a far-side work zone for the other street. These treatments are found in two different typical applications, while a third typical application shows how to handle pedestrian crosswalk closures. For convenience in using the typical application diagrams, Tables 6C-16B-1 and 6C-46B-4 are reproduced in this Chapter as Tables 6H-36P-5 and 6H-46P-4, respectively.

Procedures for establishing TTC zones vary with such conditions as road configuration, location of the work, work activity, duration of work, road user volumes, road vehicle mix (buses, trucks, cars, motorcycles, and bicycles), and road user speeds. Deleted; redundant with new Section 6B.01

In general, the procedures illustrated represent minimum solutions for the situations depicted. Except for the notes (which are clearly classified using headings as being Standard, Guidance, Option, or Support), the information presented in the typical applications can generally be regarded as Guidance.

TTC plans may deviate from the typical applications described in <u>this</u> Chapter-6H to allow for conditions and requirements of a particular site or jurisdiction. This text was relocated from existing Section 6A.01

Other devices may be added to supplement the devices and device spacing may be adjusted to provide additional reaction time or delineation. Fewer devices may be used based on field conditions.

Support:

Figures and tables found throughout Part 6 provide information for the development of TTC plans. Also, Table 6H-3 is used for the determination of sign spacing and other dimensions for various area and roadway types. Relocated to below

Table 6H6P-1 is an index of the 46 typical applications. Typical applications are shown on the right-hand page with notes on the facing page to the left. The legend for the symbols used in the typical applications is provided in Table 6H6P-2. In many of the typical applications, sign spacings and other dimensions are indicated by letters using the criteria provided in Table 6H6P-3. The formulas for determining taper lengths are provided in Table 6H 46P-4. Also, Table 6H 36P-4 is used for the determination of sign spacing and other dimensions for various area and roadway types. Relocated from above

Most of the typical applications show TTC devices for only one direction.

Table 6P-1. Index to Typical Applications

Table 6P-2. Meaning of Symbols on Typical Application Diagrams

Table 6P-3. Meaning of Letter Codes on Typical Application Diagrams

Table 6P-4. Formulas for Determining Taper Length

Table 6P-5. Recommended Advance Warning Sign Minimum Spacing

1	Notes for Figure 6H6P-1—Typical Application 1
2	Work Beyond a Shoulder
3	Guidance:
4 5	1. If the work space is in the median of a divided highway, an advance warning sign should also be placed on the left-hand side of the directional roadway.
6	Option:
7 8 9	The ROAD WORK AHEAD sign may be replaced with other appropriate signs such as the SHOULDER WORK sign. The SHOULDER WORK sign may be used for work adjacent to the shoulder.
10 11	3. The ROAD WORK AHEAD sign may be omitted where the work space is behind a barrier, more than 24 inches behind the curb, or 15 feet or more from the edge of any roadway.
12 13 14	4. For short-term, short duration or mobile operation, all signs and channelizing devices may be eliminated if a vehicle with activated high-intensity rotating, flashing, oscillating, or strobe lights is used.
15 16	5. Vehicle hazard warning signals may be used to supplement high-intensity rotating, flashing, oscillating, or strobe lights.
17	Standard:
18 19	6. Vehicle hazard warning signals shall not be used instead of the vehicle's high-intensity rotating flashing, oscillating, or strobe lights.
20	Figure 6P-1. Work Beyond the Shoulder (TA-1)
21	

1	Notes for Figure 6H6P-2—Typical Application 2
2	Blasting Zone
3	Standard:
4 5	1. Whenever blasting caps are used within 1,000 feet of a roadway, the signing shown shall be used.
6 7	2. The signs shall be covered or removed when there are no explosives in the area or the area is otherwise secure.
8 9 10	3. Whenever a side road intersects the roadway between the BLASTING ZONE AHEAD sign and the END BLASTING ZONE sign, or a side road is within 1,000 feet of any blasting cap, similar signing, as on the mainline, shall be installed on the side road.
11 12 13	4. Prior to blasting, the blaster in charge shall determine whether road users in the blasting zone will be endangered by the blasting operation. If there is danger, road users shall not be permitted to pass through the blasting zone during blasting operations.
14	Guidance:
15	5. On a divided highway, the signs should be mounted on both sides of the directional roadways.
16 17	Figure 6P-2. Blasting Zone (TA-2)

1	Notes for Figure 6H6P-3—Typical Application 3
2	Work on Shoulders
3	Guidance:
4 5	1. A SHOULDER WORK sign should be placed on the left-hand side of the roadway for a divided or one-way street only if the left-hand shoulder is affected.
6	Option:
7 8 9 10 11 12 13 14 15	 Positive protection devices may be used per Section 6M.02. The Workers symbol signs may be used instead of SHOULDER WORK signs. The SHOULDER WORK AHEAD sign on an intersecting roadway may be omitted where drivers emerging from that roadway will encounter another advance warning sign prior to this activity area. For short duration operations of 60 minutes or less, all signs and channelizing devices may be eliminated if a vehicle with activated high-intensity rotating, flashing, oscillating, or strobe lights is used. Vehicle hazard warning signals may be used to supplement high-intensity rotating, flashing, oscillating, or strobe lights.
16	Standard:
17 18 19 20 21 22	 6-7. Vehicle hazard warning signals shall not be used instead of the vehicle's high-intensity rotating, flashing, oscillating, or strobe lights. 7-8. When paved shoulders having a width of 8 feet or more are closed, at least one advance warning sign shall be used. In addition, channelizing devices shall be used to close the shoulder in advance to delineate the beginning of the work space and direct vehicular traffic to remain within the traveled way.
23	Figure 6P-3. Work on the Shoulders (TA-3)
24	

1	Notes for Figure 6H6P 4 — Typical Application 4
2	Short Duration or Mobile Operation on a Shoulder
3	Guidance:
4 5	1. In those situations where multiple work locations within a limited distance make it practical to place stationary signs, the distance between the advance warning sign and the work should not exceed 5
6 7 8	miles. 2. In those situations where the distance between the advance signs and the work is 2 miles to 5 miles, a Supplemental Distance plaque should be used with the ROAD WORK AHEAD sign.
9	Option:
10 11 12 13 14 15 16	 Additional positive protection devices may be used per Section 6M.02 3.4. The ROAD WORK NEXT XX MILES sign may be used instead of the ROAD WORK AHEAD sign if the work locations occur over a distance of more than 2 miles. 4.5. Stationary warning signs may be omitted for short duration or mobile operations if the work vehicle displays high-intensity rotating, flashing, oscillating, or strobe lights. 5.6. Vehicle hazard warning signals may be used to supplement high-intensity rotating, flashing, oscillating, or strobe lights.
17	Standard:
18 19	6-7. Vehicle hazard warning signals shall not be used instead of the vehicle's high-intensity rotating, flashing, oscillating, or strobe lights.
20	7.8. If an arrow board is used for an operation on the shoulder, the caution mode shall be used.
21	8.9. Vehicle-mounted signs shall be mounted in a manner such that they are not obscured by
22 23	equipment or supplies. Sign legends on vehicle-mounted signs shall be covered or turned from
24	view when work is not in progress. Figure 6P-4. Short Duration or Mobile Operation on a Shoulder (TA-4)

1		Notes for Figure 6H6P-5 — Typical Application 5
2		Shoulder Closure on a Freeway
3	Guidan	oce:
4 5 6 7 8		SHOULDER CLOSED signs should be used on limited-access highways where there is no opportunity for disabled vehicles to pull off the roadway. If drivers cannot see a pull-off area beyond the closed shoulder, information regarding the length of the shoulder closure should be provided in feet or miles, as appropriate. The use of a temporary traffic barrier should be based on engineering judgment.
9	Standa	
10		Temporary traffic barriers, if used, shall comply with the provisions of Section 6F.856M.02.
11	Option	
12 13		The barrier shown in this typical application is an example of one method that may be used to close a shoulder of a long-term project.
14	6.	The warning lights shown on the barrier may be used.
15		Figure 6P-5. Shoulder Closure on a Freeway (TA-5)
16		

1	Notes for Figure 6H6P-6 — Typical Application 6
2	Shoulder Work with Minor Encroachment
3	Guidance:
4 5	1. All lanes should be a minimum of 10 feet in width as measured to the near face of the channelizing devices.
6 7	2. The treatment shown should be used on a minor road having low speeds. For higher-speed traffic conditions, a lane closure should be used.
8	Option:
9 10	3. Additional positive protection devices may be used per Section 6M.02. 3.4. For short-term use on low-volume, low-speed roadways with vehicular traffic that does not include
11 12 13	longer and wider heavy commercial vehicles, a minimum lane width of 9 feet may be used. 4.5. Where the opposite shoulder is suitable for carrying vehicular traffic and of adequate width, lanes may be shifted by use of closely-spaced channelizing devices, provided that the minimum lane width of 10
14	feet is maintained.
15	5.6. Additional advance warning may be appropriate, such as a ROAD NARROWS sign.
16	6-7. Temporary traffic barriers may be used along the work space.
17	7-8. The shadow vehicle may be omitted if a taper and channelizing devices are used.
18	8.9. A truck-mounted attenuator may be used on the shadow vehicle.
19 20	9.10. For short-duration work, the taper and channelizing devices may be omitted if a shadow vehicle with activated high-intensity rotating, flashing, oscillating, or strobe lights is used.
21 22	10.11. Vehicle hazard warning signals may be used to supplement high-intensity rotating, flashing, oscillating, or strobe lights.
23	Standard:
24 25	11.12. Vehicle-mounted signs shall be mounted in a manner such that they are not obscured by equipment or supplies. Sign legends on vehicle-mounted signs shall be covered or turned from
26	view when work is not in progress.
27	12.13. Shadow and work vehicles shall display high-intensity rotating, flashing, oscillating, or
28	strobe lights.
29 30	13.14. Vehicle hazard warning signals shall not be used instead of the vehicle's high-intensity rotating, flashing, oscillating, or strobe lights.
50	i vuotiila iiudiiiila voliiiuliila vi oli vol illiida

1	Notes for Figure 6H6P-7 — Typical Application 7
2	Road Closure with a Diversion
3	Support:
4	1. Signs and object markers are shown for one direction of travel only.
5	Standard:
6 7 8 9	 Devices similar to those depicted shall be placed for the opposite direction of travel. Pavement markings no longer applicable to the traffic pattern of the roadway shall be removed or obliterated before any new traffic patterns are open to traffic. Temporary barriers and end treatments shall be crashworthy.
10	Guidance:
11 12 13 14 15 16 17 18	 If the tangent distance along the temporary diversion is more than 600 feet, a Reverse Curve sign, left first, should be used instead of the Double Reverse Curve sign, and a second Reverse Curve sign, right first, should be placed in advance of the second reverse curve back to the original alignment. When the tangent section of the diversion is more than 600 feet, and the diversion has sharp curves with recommended speeds of 30 mph or less, Reverse Turn signs should be used. Where the temporary pavement and old pavement are different colors, the temporary pavement should start on the tangent of the existing pavement and end on the tangent of the existing pavement. Delineators or channelizing devices should be used along the diversion. Changed from Option to Guidance and relocated from below
20	Option:
21 22 23 24	8.9. Flashing warning lights and/or flags may be used to call attention to the warning signs. 9.10. On sharp curves, large arrow signs may be used in addition to other advance warning signs. 10. Delineators or channelizing devices may be used along the diversion. Changed from Option to Guidance and relocated to above
2526	Figure 6P-7. Road Closure with a Diversion (TA-7)

1		Notes for Figure 6H6P-8 — Typical Application 8
2		Road Closure with an Off-Site Detour
3	Guidan	ace:
4	1.	Regulatory traffic control devices should be modified as needed for the duration of the detour.
5	Option	
6 7 8	2.	If the road is opened for some distance beyond the intersection and/or there are significant origin/destination points beyond the intersection, the ROAD CLOSED and DETOUR signs on Type 3 Barricades may be located at the edge of the traveled way.
9 10	3.	A Route Sign Directional assembly may be placed on the far left corner of the intersection to augment or replace the one shown on the near right corner.
11	4.	Flashing warning lights and/or flags may be used to call attention to the advance warning signs.
12	5.	Cardinal direction plaques may be used with route signs.
13		Figure 6P-8. Road Closure with an Off-Site Detour (TA-8)
14		

1	Notes for Figure 6H6P-9 — Typical Application 9	
2	Overlapping Routes with a Detour	
3	Support:	
4	1. TTC devices are shown for one direction of travel only.	
5	Standard:	
6	2. Devices similar to those depicted shall be placed for the opposite direction of travel.	
7	Guidance:	
8 9	3. STOP or YIELD signs displayed to side roads should be installed as needed along the temporary route.	
10	Option:	
11 12 13	4. Flashing warning lights and/or flags may be used to call attention to the advance warning signs.5. Flashing warning lights may be used on the Type 3 Barricades.6. Cardinal direction plaques may be used with route signs.	
14	Figure 6P-9. Overlapping Routes with a Detour (TA-9)	
15		

1	Notes for Figure 6H6P-10 —Typical Application 10
2	Lane Closure on a Two-Lane Road Using Flaggers
3	Option:
4	1. Positive protection devices may be used per Section 6M.02.
5	4.2. For low-volume situations with short work zones on straight roadways where the flagger is visible to
6	road users approaching from both directions, a single flagger, positioned to be visible to road users
7	approaching from both directions, may be used (see Chapter <u>6E6D</u>).
8 9	2.3. The ROAD WORK AHEAD and the END ROAD WORK signs may be omitted for short-duration operations.
10	3.4. Flashing warning lights and/or flags may be used to call attention to the advance warning signs. A BE
11	PREPARED TO STOP sign may be added to the sign series.
12	Guidance:
13	4.5. The buffer space should be extended so that the two-way traffic taper is placed before a horizontal (or
14	crest vertical) curve to provide adequate sight distance for the flagger and a queue of stopped
15	vehicles.
16	Standard:
17	5.6. At night, flagger stations shall be illuminated, except in emergencies.
18	Guidance:
19	6.7. When used, the BE PREPARED TO STOP sign should be located between the Flagger sign and the
20	ONE LANE ROAD sign.
21 22	7.8. When a grade crossing exists within or upstream of the transition area and it is anticipated that queues resulting from the lane closure might extend through the grade crossing, the TTC zone should
23	be extended so that the transition area precedes the grade crossing.
24	8.9. When a grade crossing equipped with active warning devices exists within the activity area,
25	provisions should be made for keeping flaggers informed as to the activation status of these warning
26	devices.
27 28	9.10. When a grade crossing exists within the activity area, drivers operating on the left-hand side of the normal center line should be provided with comparable warning devices as for drivers
29	of the normal center line should be provided with comparable warning devices as for arrivers operating on the right-hand side of the normal center line.
30	10.11. Early coordination with the railroad company or light rail transit agency should occur before
31	work starts.
32	Option:
33	41.12. A flagger or a uniformed law enforcement officer may be used at the grade crossing to
34	minimize the probability that vehicles are stopped within 15 feet of the grade crossing, measured from
35	both sides of the outside rails.

Figure 6P-10. Lane Closure on a Two-Lane Road Using Flaggers (TA-10)

36

1	Notes for Figure 6H6P-11 — Typical Application 11
2	Lane Closure on a Two-Lane Road with Low Traffic Volumes
3	Option:
4	1. Positive protection devices may be used per Section 6M.02.
5 6	1.2. This TTC zone application may be used as an alternate to the TTC application shown in Figure 6H6F 10 (using flaggers) when the following conditions exist:
7 8 9	a. Vehicular traffic volume is such that sufficient gaps exist for vehicular traffic that must yield.b. Road users from both directions are able to see approaching vehicular traffic through and beyond the worksite and have sufficient visibility of approaching vehicles.
10 11	2.3. The Type B flashing warning lights may be placed on the ROAD WORK AHEAD and the ONE LANE ROAD AHEAD signs whenever a night lane closure is necessary.
12	Figure 6P-11. Lane Closure on a Two-Lane Road with Low Traffic Volumes
13	

1 Notes for Figure 6H6P-12 — Typical Application 12 2 Lane Closure on a Two-Lane Road Using Traffic Control Signals 3 **Standard:** 4 1. Temporary traffic control signals shall be installed and operated in accordance with the provisions of Part 4. Temporary traffic control signals shall meet the physical display and 5 6 operational requirements of conventional traffic control signals. 7 2. Temporary traffic control signal timing shall be established by authorized officials. Durations 8 of red clearance intervals shall be adequate to clear the one-lane section of conflicting vehicles. 9 3. When the temporary traffic control signal is changed to the flashing mode, either manually or 10 automatically, red signal indications shall be flashed to both approaches. 11 4. Stop lines shall be installed with temporary traffic control signals for intermediate and long-12 term closures. Edited to improve consistency Existing conflicting pavement markings and 13 raised pavement marker reflectors between the activity area and the stop line shall be removed. 14 After the temporary traffic control signal is removed, the stop lines and other temporary 15 pavement markings shall be removed and the permanent pavement markings restored. 5. Safeguards shall be incorporated to avoid the possibility of conflicting signal indications at each 16 17 end of the TTC zone. 18 Guidance: 19 6. Where no-passing lines are not already in place, they should be added. 20 7. Adjustments in the location of the advance warning signs should be made as needed to accommodate 21 the horizontal or vertical alignment of the roadway, recognizing that the distances shown for sign 22 spacings are minimums. Adjustments in the height of the signal heads should be made as needed to 23 conform to the vertical alignment. 24 Option: 25 8. Positive protection devices may be used per Section 6M.02. 8.9. Flashing warning lights shown on the ROAD WORK AHEAD and the ONE LANE ROAD AHEAD 26 27 signs may be used. 28 9.10. Removable pavement markings may be used.

29 Support:

- 10.11. Temporary traffic control signals are preferable to flaggers for long-term projects and other activities that would require flagging at night.
- 11.12. The maximum length of activity area for one-way operation under temporary traffic control signal control is determined by the capacity required to handle the peak demand.
- Figure 6P-12. Lane Closure on a Two-Lane Road Using Traffic Control Signals (TA-12)

30

31

32 33

1		Notes for Figure 6H6P-13 — Typical Application 13
2		Temporary Road Closure
3	Support	t:
4	1.	Conditions represented are a planned closure not exceeding 20 minutes during the daytime.
5	Standa	rd:
6 7 8	2.	A flagger or uniformed law enforcement officer shall be used for this application. The flagger if used for this application, shall follow the procedures provided in Sections $6E.076D.05$ and $6E.086D.06$.
9	Guidan	ce:
10 11	3.	The uniformed law enforcement officer, if used for this application, should follow the procedures provided in Sections 6E.076D.05 and 6E.086D.06.
12	Option:	
13	4.	A BE PREPARED TO STOP sign may be added to the sign series.
14	<u>5.</u>	Positive protection devices may be used per Section 6M.02.
15	Guidan	ce:
16	<u>5.6.</u>	When used, the BE PREPARED TO STOP sign should be located before the Flagger symbol sign.
17		Figure 6P-13. Temporary Road Closure (TA-13)
18		

1	Notes for Figure 6H6P-14 — Typical Application 14	
2	Haul Road Crossing	
3	Guidance:	
4 5	 Floodlights should be used to illuminate haul road crossings where existing light is inadequate. Where no-passing lines are not already in place, they should be added. 	
6	Standard:	
7	3. The traffic control method selected shall be used in both directions.	
8	Flagging Method	
9	4. When a road used exclusively as a haul road is not in use, the haul road shall be closed with	
10	Type 3 Barricades and the Flagger symbol signs covered.	
11	5. The flagger shall follow the procedures provided in Sections 6E.076D.05 and 6E.086D.06.	
12	6. At night, flagger stations shall be illuminated, except in emergencies.	
13	Signalized Method	
14	7. When a road used exclusively as a haul road is not in use, the haul road shall be closed with	
15	Type 3 Barricades. The signals shall either:	
16 17	a. flash yellow on the main road and flash red on the haul road or be covered, and the Signal Ahead and STOP HERE ON RED signs shall be covered or hidden from view;	
18	or	
19	b. display green on the main road and steady red on the haul road, but only if actuated	
20	signal operation is used such that green is always displayed to the main road except	
21	when a vehicle is detected on the haul road. Edited to reflect Official Interpretation	
22	6(09)-7(1)	
23	8. The temporary traffic control signals shall control both the highway and the haul road and sha	ıll
24	meet the physical display and operational requirements of conventional traffic control signals	as
25	described in Part 4. Traffic control signal timing shall be established by authorized officials.	
26	9. Stop lines shall be used on existing highway with temporary traffic control signals.	
27 28	10. Existing conflicting pavements markings between the stop lines shall be removed. After the	
28 29	temporary traffic control signal is removed, the stop lines and other temporary pavement markings shall be removed and the permanent pavement markings restored.	
30	Guidance:	
31	Signalized Method	
32	11. If actuated signal operation is used (see item 7.b. above) and pedestrian facilities, such as sidewalks	
33	are present in the area of the haul road crossing, then consideration should be given to providing	_
34	pedestrian actuation capability at the temporary traffic control signal to accommodate any	
35	pedestrians who might be depending upon a pedestrian phase to cross the main road. Added to	
36	reflect Official Interpretation 6(09)-7(I)	
37	Figure 6P-14. Haul Road Crossing (TA-14)	

1	Notes for Figure 6H6P-15 — Typical Application 15
2	Work in the Center of a Road with Low Traffic Volumes
3	Guidance:
4	1. The lanes on either side of the center work space should have a minimum width of 10 feet as
5	measured from the near edge of the channelizing devices to the edge of the pavement or the outside
6	edge of the paved shoulder.
7	Option:
8	2. Positive protection devices may be used per Section 6M.02.
9	2.3. Flashing warning lights and/or flags may be used to call attention to the advance warning signs.
10	3.4. If the closure continues overnight, warning lights may be used on the channelizing devices.
11	4.5. A lane width of 9 feet may be used for short-term stationary work on low-volume, low-speed
12	roadways when motor vehicle traffic does not include longer and wider heavy commercial vehicles.
13	5.6. A work vehicle displaying high-intensity rotating, flashing, oscillating, or strobe lights may be used
14	instead of the channelizing devices forming the tapers or the high-level warning devices.
15	6.7. Vehicle hazard warning signals may be used to supplement high-intensity rotating, flashing,
16	oscillating, or strobe lights.
17	Standard:
18	7-8. Vehicle hazard warning signals shall not be used instead of the vehicle's high-intensity rotating
19	flashing, oscillating, or strobe lights.
20	Figure 6P-15. Work in the Center of a Road with Low Traffic Volumes (TA-15)
21	

11	information illustrated in Figure <mark>6H<u>6P</u>-10.</mark>
12	Option:
13 14	5. A high-level warning device may be used to protect a surveying device, such as a target on a tripod.6. Cones may be omitted for a cross-section survey.
15 16	 7. ROAD WORK AHEAD signs may be used in place of the SURVEY CREW AHEAD signs. 8. Flags may be used to call attention to the advance warning signs.
17	9. If the work is along the shoulder, the flagger may be omitted.
18 19	10. For a survey along the edge of the road or along the shoulder, cones may be placed along the edge line.
20	11. A BE PREPARED TO STOP sign may be added to the sign series.
21	Guidance:
22	12. When used, the BE PREPARED TO STOP sign should be located before the Flagger symbol sign.
23	Figure 6P-16. Surveying Along the Center Line of a Road with Low Traffic Volumes (TA-16)
24	

Notes for Figure 6H6P-16 — Typical Application 16

Surveying Along the Center Line of a Road with Low Traffic Volumes

measured from the near edge of the channelizing devices to the edge of the pavement or the outside

1. The lanes on either side of the center work space should have a minimum width of 10 feet as

4. For surveying on the center line of a high-volume road, one lane shall be closed using the

2. Cones should be placed 6 to 12 inches on either side of the center line.3. A flagger should be used to warn workers who cannot watch road users.

1

2

3

4

5 6

7

8 9

10

Guidance:

Standard:

edge of the paved shoulder.

1		Notes for Figure 6H6P-17 — Typical Application 17
2		Mobile Operations on a Two-Lane Road
3	Standard	l :
4 5 6	ec	ehicle-mounted signs shall be mounted in a manner such that they are not obscured by quipment or supplies. Sign legends on vehicle-mounted signs shall be covered or turned from iew when work is not in progress.
7 8	2. S. li	hadow and work vehicles shall display high-intensity rotating, flashing, oscillating, or strobe ghts.
9	3. If	f an arrow board is used, it shall be used in the caution mode.
0	Guidance	:
1 2	a	Where practical and when needed, the work and shadow vehicles should pull over periodically to llow vehicular traffic to pass.
13 14 15	m	Whenever adequate stopping sight distance exists to the rear, the shadow vehicle should maintain the ninimum distance from the work vehicle and proceed at the same speed. The shadow vehicle should low down in advance of vertical or horizontal curves that restrict sight distance.
6	6. T	the shadow vehicles should also be equipped with two high-intensity flashing lights mounted on the ear, adjacent to the sign.
8	Option:	
19 20 21	7. <u>8.</u> T	ositive protection devices may be used per Section 6M.02. The distance between the work and shadow vehicles may vary according to terrain, paint drying time and other factors.
22 23		additional shadow vehicles to warn and reduce the speed of oncoming or opposing vehicular traffic hay be used. Law enforcement vehicles may be used for this purpose.
21 22 23 24 25 26	9. 10. 10. 11	. If the work and shadow vehicles cannot pull over to allow vehicular traffic to pass frequently
		DO NOT PASS sign may be placed on the rear of the vehicle blocking the lane.
27	Support:	
28	11. 12	-
29	Standard	l :
30 31	12. 13	Vehicle hazard warning signals shall not be used instead of the vehicle's high-intensity otating, flashing, oscillating, or strobe lights.

Figure 6P-17. Mobile Operations on a Two-Lane Road (TA-17)

32

1	Notes for Figure 6H6P-18 — Typical Application 18
2	Lane Closure on a Minor Street
3	Standard:
4	1. This TTC shall be used only for low-speed facilities having low traffic volumes.
5	Option:
6 7	2. Where the work space is short, where road users can see the roadway beyond, and where volume is low, vehicular traffic may be self-regulating.
8	Standard:
9 10	3. Where vehicular traffic cannot effectively self-regulate, one or two flaggers shall be used as illustrated in Figure 6H6P-10.
11	Option:
12 13 14	 4. Flashing warning lights and/or flags may be used to call attention to the advance warning signs. 5. A truck-mounted attenuator may be used on the work vehicle and the shadow vehicle. 6. Positive protection devices may be used per Section 6M.02.
15	Figure 6P-18. Lane Closure on a Minor Street (TA-18)
16	

1		Notes for Figure 6H6P-19 — Typical Application 19
2		Detour for One Travel Direction
3	Guidar	nce:
4	1.	This plan should be used for streets without posted route numbers.
5	2.	On multi-lane streets, Detour signs with an Advance Turn Arrow should be used in advance of a turn.
6	Option	:
7	3.	The STREET CLOSED legend may be used in place of ROAD CLOSED.
8	4.	Additional DO NOT ENTER signs may be used at intersections with intervening streets.
9	5.	Warning lights may be used on Type 3 Barricades.
10	6.	Detour signs may be located on the far side of intersections.
11	7.	A Street Name sign may be mounted with the Detour sign. The Street Name sign may be either white
12		on green or black on orange.
13	Standa	ard:
14	8.	When used, the Street Name sign shall be placed above the Detour sign.
15		Figure 6P-19. Detour for One Travel Direction (TA-19)
16		

1	Notes for Figure 6H6P-20 — Typical Application 20
2	Detour for a Closed Street
3	Guidance:
4 5	 This plan should be used for streets without posted route numbers. On multi-lane streets, Detour signs with an Advance Turn Arrow should be used in advance of a turn.
6	Option:
7 8 9 10 11	 Flashing warning lights and/or flags may be used to call attention to the advance warning signs. Flashing warning lights may be used on Type 3 Barricades. Detour signs may be located on the far side of intersections. A Detour sign with an advance arrow may be used in advance of a turn. A Street Name sign may be mounted with the Detour sign. The Street Name sign may be either white on green or black on orange.
13	Standard:
14	7. When used, the Street Name sign shall be placed above the Detour sign.
15	Support:
16	8. See Figure 6H6P-9 for the information for detouring a numbered highway.
17 18	Figure 6P-20. Detour for a Closed Street (TA-20)

1	Notes for Figure 6H6P-21 —Typical Application 21
2	Lane Closure on the Near Side of an Intersection
3	Standard:
4 5	1. The merging taper shall direct vehicular traffic into either the right-hand or left-hand lane, but not both.
6	Guidance:
7 8 9 10	 In this typical application, a left taper should be used so that right-turn movements will not impede through motor vehicle traffic. However, the reverse should be true for left-turn movements. If the work space extends across a crosswalk, the crosswalk should be closed using the information and devices shown in Figure 6H6P-29.
11	Option:
12 13 14 15 16 17 18	 4. Positive protection devices may be used per Section 6M.02. 4.5. Flashing warning lights and/or flags may be used to call attention to the advance warning signs. 5.6. A shadow vehicle with a truck-mounted attenuator may be used. 6.7. A work vehicle with high-intensity rotating, flashing, oscillating, or strobe lights may be used with the high-level warning device. 7.8. Vehicle hazard warning signals may be used to supplement high-intensity rotating, flashing, oscillating, or strobe lights.
19	Standard:
20 21	8.9. Vehicle hazard warning signals shall not be used instead of the vehicle's high-intensity rotating, flashing, oscillating, or strobe lights.
22	Figure 6P-21. Lane Closure on the Near Side of an Intersection (TA-21)
23	

1 Notes for Figure 6H6P-22 — Typical Application 22 2 Right-Hand Lane Closure on the Far Side of an Intersection 3 Guidance: 4 1. If the work space extends across a crosswalk, the crosswalk should be closed using the information 5 and devices shown in Figure 6H6P-29. 6 Option: 7 2. Positive protection devices may be used per Section 6M.02. 8 2.3. The normal procedure is to close on the near side of the intersection any lane that is not carried 9 through the intersection, as shown. However, wWhen this results in the closure of a right-hand lane 10 having significant right turning movements, then the right-hand lane may be restricted to right turns only, requiring through traffic to use the left laneas shown. This procedure increases the through 11 eapacity by eliminating right turns from the open through lane. Option changed to Support and 12 13 relocated to below 14 3.4. For intersection approaches reduced to a single lane, left-turning movements may be prohibited to 15 maintain capacity for through vehicular traffic. 4.5. Flashing warning lights and/or flags may be used to call attention to the advance warning signs. 16 5.6. Where the turning radius is large, it may be possible to create a right-turn island using channelizing 17 18 devices or pavement markings. 19 7. If dimension "A" is not available to create a temporary right turn lane, continuous channelizers may 20 be installed from the end of the taper to the intersection and, as a result, the RIGHT LANE MUST 21 TURN RIGHT signs would not be installed. Added to improve consistency 22 Support: 23 8. By first closing off the left-hand lane and then reopening it as a turn bay, the through capacity is

8. By first closing off the left-hand lane and then reopening it as a turn bay, the through capacity is increased by eliminating right turns from the open through lane. Option changed to Support and relocated from above

Figure 6P-22. Right-Hand Lane Closure on the Far Side of an Intersection (TA-22)

24

25

Notes for Figure 6H6P-23 — Typical Application 23 Left-Hand Lane Closure on the Far Side of an Intersection Guidance: 1. If the work space extends across a crosswalk, the crosswalk should be closed using the information and devices shown in Figure 6H6P-29. Option:

- 2. Positive protection devices may be used per Section 6M.02.
- 2.3. Flashing warning lights and/or flags may be used to call attention to the advance warning signs.
- 3.4. The normal procedure is to close on the near side of the intersection any lane that is not carried through the intersection. However, when this results in the closure of a left-hand lane having significant left-turning movements, then the left-hand lane may be reopened as a turn bay for left turns only, as shown.

Support:

7

8

9

10

11 12

13

14

15

16

17

18 19

20

- 4.5. By first closing off the left-hand lane and then reopening it as a turn bay, the left-turn bay allows storage of turning vehicles so that the movement of through traffic is not impeded. A left-turn bay that is long enough to accommodate all turning vehicles during a traffic signal cycle will provide the maximum benefit for through traffic. Also, an island is created with channelizing devices that allows the LEFT LANE MUST TURN LEFT sign to be repeated on the left adjacent to the lane that it controls.
 - Figure 6P-23. Left-Hand Lane Closure on the Far Side of an Intersection (TA-23)

1	Notes for Figure 6H6P-24 — Typical Application 24
2	Half Road Closure on the Far Side of an Intersection
3	Guidance:
4 5 6 7	 If the work space extends across a crosswalk, the crosswalk should be closed using the information and devices shown in Figure 6H6P-29. When turn prohibitions are implemented, two turn prohibition signs should be used, one on the near side and, space permitting, one on the far side of the intersection.
8	Option:
9 10 11 12 13 14 15	 3. Positive protection devices may be used per Section 6M.02. 3.4. A buffer space may be used between opposing directions of vehicular traffic as shown in this application. 4.5. The normal procedure is to close on the near side of the intersection any lane that is not carried through the intersection, as shown. However, if there is When this results in the closure of a right-hand lane having a significant right-turning movements, then the right-hand lane may be restricted to
16 17 18	right turns only, requiring through traffic to use the left laneas shown. Edited to improve consistency 5.6. Where the turning radius is large, a right-turn island using channelizing devices or pavement markings may be used. 6.7. There may be insufficient space to place the back-to-back Keep Right sign and No Left Turn symbol
19 20 21 22 23	signs at the end of the row of channelizing devices separating opposing vehicular traffic flows. In this situation, the No Left Turn symbol sign may be placed on the right and the Keep Right sign may be omitted. 7.8. For intersection approaches reduced to a single lane, left-turning movements may be prohibited to maintain capacity for through vehicular traffic.
24 25 26	 8.9. Flashing warning lights and/or flags may be used to call attention to advance warning signs. 9.10. Temporary pavement markings may be used to delineate the travel path through the intersection.
27 28 29	11. If dimension "A" is not available to create a temporary right turn lane, continuous channelizers may be installed from the end of the taper to the intersection and, as a result, the RIGHT LANE MUST TURN RIGHT signs would not be installed. Added to improve consistency
30	Support:
31 32 33 34 35	 10.Keeping the right hand lane open increases the through capacity by eliminating right turns from the open through lane. 11.A temporary turn island reinforces the nature of the temporary exclusive right turn lane and enables a second RIGHT LANE MUST TURN RIGHT sign to be placed in the island. Deleted to improve consistency
36 37	Figure 6P-24. Half Road Closure on the Far Side of an Intersection (TA-24)

1	Notes for Figure 6H6P-25 — Typical Application 25
2	Multiple Lane Closures at an Intersection
3	Guidance:
4 5	1. If the work space extends across a crosswalk, the crosswalk should be closed using the information and devices shown in Figure 6H6P-29.
6 7 8 9	2. If the left-hand through lane is closed on the near-side approach, the LEFT LANE MUST TURN LEFT sign should be placed in the median to discourage through vehicular traffic from entering the left-turn bay. Deleted to improve consistency
10	Support:
11 12	3.2. The normal procedure is to close on the near side of the intersection any lane that is not carried through the intersection, as shown. Edited to refer to figure
13	Option:
14 15 16 17	 Positive protection devices may be used per Section 6M.02. If the left-turning movement that normally uses the closed turn bay is small and/or the gaps in opposing vehicular traffic are frequent, left turns may be permitted on that approach. Flashing warning lights and/or flags may be used to call attention to the advance warning signs.
18 19	Figure 6P-25. Multiple Lane Closures at an Intersection (TA-25)

1	Notes for Figure 6H6P-26 —Typical Application	26
2	Closure in the Center of an Intersection	
3	Guidance:	
4 5	 All lanes should be a minimum of 10 feet in width as measured to the nedevices. 	ear face of the channelizing
6	Option:	
7 8 9	 A high-level warning device may be placed in the work space, if there i For short-term use on low-volume, low-speed roadways with vehicular longer and wider heavy commercial vehicles, a minimum lane width of 	traffic that does not include
10	4. Flashing warning lights and/or flags may be used to call attention to ad	
11 12	5. Unless the streets are wide, it may be physically impossible to turn left, Left turns may be prohibited as required by geometric conditions.	0 0
13 14 15	 For short-duration work operations, the channelizing devices may be el displaying high-intensity rotating, flashing, oscillating, or strobe lights space. 	
16 17	7. Vehicle hazard warning signals may be used to supplement high-intens oscillating, or strobe lights.	ity rotating, flashing,
18	Standard:	
19 20	8. Vehicle hazard warning signals shall not be used instead of the vehicle flashing, oscillating, or strobe lights.	icle's high-intensity rotating,
21 22	Figure 6P-26. Closure in the Center of an Intersection	on (TA-26)

1	Notes for Figure 6H6P-27 — Typical Application 27
2	Closure at the Side of an Intersection
3	Guidance:
4 5 6	 The situation depicted can be simplified by closing one or more of the intersection approaches. If this cannot be done, and/or when capacity is a problem, through vehicular traffic should be directed to other roads or streets.
7 8	 Depending on road user conditions, flagger(s) or uniformed law enforcement officer(s) should be used to direct road users within the intersection.
9	Standard:
10	3. At night, flagger stations shall be illuminated, except in emergencies.
11	Option:
12 13 14 15	4. Flashing warning lights and/or flags may be used to call attention to the advance warning signs.5. For short-duration work operations, the channelizing devices may be eliminated if a vehicle displaying high-intensity rotating, flashing, oscillating, or strobe lights is positioned in the work space.
16	6. A BE PREPARED TO STOP sign may be added to the sign series.
17	Guidance:
18 19	7. When used, the BE PREPARED TO STOP sign should be located before the Flagger symbol sign.8. ONE LANE ROAD AHEAD signs should also be used to provide adequate advance warning.
20	Support:
21 22	9. Turns can be prohibited as required by vehicular traffic conditions. Unless the streets are wide, it might be physically impossible to make certain turns, especially for large vehicles.
23	Option:
24	10. Positive protection devices may be used per Section 6M.02.
25 26	10.11. Vehicle hazard warning signals may be used to supplement high-intensity rotating, flashing, oscillating, or strobe lights.
27	Standard:
28 29	11.12. Vehicle hazard warning signals shall not be used instead of the vehicle's high-intensity rotating, flashing, oscillating, or strobe lights.
30	Figure 6P-27. Closure at the Side of an Intersection (TA-27)

	Notes for Figure 6H6P-28 — Typical Application 28
	Sidewalk Detour or Diversion
Standa	ard:
1.	When crosswalks or other pedestrian facilities are closed or relocated, temporary facilities shall detectable and shall include accessibility features consistent with the features present in the exist pedestrian facility. Deleted and replaced with Standards below
<u>1.</u>	When existing pedestrian facilities are disrupted, closed, or relocated in a TTC zone, the temporary facilities shall be detectable and include accessibility features consistent with the features present in the existing pedestrian facility. A pedestrian channelizing device, Figure 2, that is detectable by a person with a visual disability traveling with the aid of a long can be placed across the full width of the closed sidewalk.
<u>2.</u>	When used, temporary ramps shall provide a 12:1 (8%) or flatter slope, with a slip-resista surface. The ramp landing area shall provide a 48 inch x 48 inch minimum area with a 2% flatter cross-slope.
<u>3.</u>	When used, Longitudinal Channelizing Devices used for temporary pedestrian routes shal comply with Section 6K.02.
<u>4.</u>	Temporary traffic barriers, if used, shall comply with the provisions of Section 6M.02.
<u>5.</u>	SIDEWALK CLOSED CROSS HERE signs shall include audible information devices to provide adequate communication to pedestrians with visual disabilities. Added to reflect 2 CFR 35.160 (subpart a)
<u>6.</u>	Audible information devices shall be provided where midblock closings and changed cross areas cause inadequate communication to be provided to pedestrians who have visual disabilities. Guidance changed to Standard to reflect 28 CFR 35.160 (subpart a) and reloc from below
Guidan	ace:
2.	Where high speeds are anticipated, a temporary traffic barrier and, if necessary, a crash cushic should be used to separate the temporary sidewalks from vehicular traffic. Deleted and replace with Guidance below
<u>7.</u>	The surface of an alternate pathway should meet the requirements of the Americans with Disab Act.
8	The protective requirements of a TTC situation have priority in determining the need for tempo traffic barriers and their use in this situation should be based on engineering judgment. Added improve accuracy
3.	Audible information devices should be considered where midblock closings and changed crosss areas cause inadequate communication to be provided to pedestrians who have visual disability Guidance changed to Standard and relocated to above

- 5.10. Only the TTC devices related to pedestrians are shown. Other devices, such as lane closure signing or ROAD NARROWS signs, may be used to control vehicular traffic.
- 6.11. For nighttime closures, Type A Flashing warning lights may be used on barricades that support signs and close sidewalks.
- 7.12. Type C Steady-Burn or Type D 360-degree Steady-Burn warning lights may be used on channelizing devices separating the temporary sidewalks from vehicular traffic flow.
- 8.13. Signs, such as KEEP RIGHT (LEFT), may be placed along a temporary sidewalk to guide or direct pedestrians.

44

45

46

47

48

1	14. The width of the alternate pedestrian route may be 48 inches with a passing area of 60 inches every
2	200 feet. Added to improve accuracy
3	Figure 6P-28. Sidewalk Detour or Diversion (TA-28)

Notes for Figure 6H6P-29 — Typical Application 29 Crosswalk Closures and Pedestrian Detours

Standard:

- 1. When crosswalks or other pedestrian facilities are closed or relocated, temporary facilities shall be detectable and shall include accessibility features consistent with the features present in the existing pedestrian facility.
- 2. Curb parking shall be prohibited for at least 50 feet in advance of the midblock crosswalk.
- 3. SIDEWALK CLOSED CROSS HERE signs shall include audible information devices to provide adequate communication to pedestrians with visual disabilities. Added to reflect 28 CFR 35.160 (subpart a)
- 4. Audible information devices shall be provided where midblock closings and changed crosswalk areas cause inadequate communication to be provided to pedestrians who have visual disabilities Guidance changed to Standard to reflect 28 CFR 35.160 (subpart a) and relocated from below

Guidance:

- 3. Audible information devices should be considered where midblock closings and changed crosswalk areas cause inadequate communication to be provided to pedestrians who have visual disabilities.

 Guidance changed to Standard to reflect 28 CFR 35.160 (subpart a) and relocated to above
- 4.5. Pedestrian traffic signal displays controlling closed crosswalks should be covered or deactivated.

Option:

- 5.6. Street lighting may be considered.
- 6.7. Only the TTC devices related to pedestrians are shown. Other devices, such as lane closure signing or ROAD NARROWS signs, may be used to control vehicular traffic.
- 7.8. For nighttime closures, Type A Flashing warning lights may be used on barricades supporting signs and closing sidewalks.
- 8.9. Type C Steady-Burn or Type D 360-degree Steady-Burn warning lights may be used on channelizing devices separating the work space from vehicular traffic.
- 9.10. In order to maintain the systematic use of the fluorescent yellow-green background for pedestrian, bicycle, and school warning signs in a jurisdiction, the fluorescent yellow-green background for pedestrian, bicycle, and school warning signs may be used in TTC zones.

Figure 6P-29. Crosswalk Closures and Pedestrian Detours (TA-29)

1	Notes for Figure 6H6P-30 — Typical Application 30
2	Interior Lane Closure on a Multi-Lane Street
3	Guidance:
4 5	1. This information applies to low-speed, low-volume urban streets. Where speed or volume is higher, additional signing such as LEFT LANE CLOSED XX FT should be used between the signs shown.
6	Option:
7 8 9 10	 2. Positive protection devices may be used per Section 6M.02. 2.3. The closure of the adjacent interior lane in the opposing direction may not be necessary, depending upon the activity being performed and the work space needed for the operation. 3.4. Shadow vehicles with a truck-mounted attenuator may be used.
11	Figure 6P-30. Interior Lane Closure on a Multi-Lane Street (TA-30)
12	

1 Notes for Figure 6H6P-31 —Typical Application 31 2 Lane Closure on a Street with Uneven Directional Volumes 3 **Standard:** 4 1. The illustrated information shall be used only when the vehicular traffic volume indicates that two lanes of vehicular traffic shall be maintained in the direction of travel for which one lane is 5 6 closed. 7 Option: 8 2. The procedure may be used during a peak period of vehicular traffic and then changed to provide two 9 lanes in the other direction for the other peak. 10 Guidance: 11 3. For high speeds, a LEFT LANE CLOSED XX FT sign should be added for vehicular traffic 12 approaching the lane closure, as shown in Figure 6H6P-32. 13 4. Conflicting payement markings should be removed for long-term projects. For short-term and 14 intermediate-term projects where this is not practical, the channelizing devices in the area where the 15 pavement markings conflict should be placed at a maximum spacing of 1/2 S feet where S is the speed 16 in mph. Temporary markings should be installed where needed. 17 5. If the lane shift has curves with recommended speeds of 30 mph or less, Reverse Turn signs should be 18 used. 19 6. Where the shifted section is long, a Reverse Curve sign should be used to show the initial shift and a 20 second sign should be used to show the return to the normal alignment. 21 7. If the tangent distance along the temporary diversion is less than 600 feet, the Double Reverse Curve 22 sign should be used at the location of the first Two Lane Reverse Curve sign. The second Two Lane 23 Reverse Curve sign should be omitted. 24 Standard: 25 8. The number of lanes illustrated on the Reverse Curve or Double Reverse Curve signs shall be 26 the same as the number of through lanes available to road users, and the direction of the reverse 27 curves shall be appropriately illustrated. 28 Option: 29 9. Positive protection devices may be used per Section 6M.02. 30 A longitudinal buffer space may be used in the activity area to separate opposing vehicular 9.10. 31 traffic. 32 Where two or more lanes are being shifted, a W1 4Reverse Curve (or W1 3Reverse Turn) 10.11.

sign with an ALL LANES (W24-1cP) plaque (see Figure 6F-46H-1) may be used instead of a sign

Figure 6P-31. Lane Closure on a Street with Uneven Directional Volumes (TA-31)

Where more than three lanes are being shifted, the Reverse Curve (or Turn) sign may be

A work vehicle or a shadow vehicle may be equipped with a truck-mounted attenuator.

that illustrates the number of lanes. Edited to improve consistency with Figure

33 34

35

36

37

38

11.12.

12.13.

rectangular.

1 Notes for Figure 6H6P-32 — Typical Application 32 2 Half Road Closure on a Multi-Lane, High-Speed Highway 3 **Standard:** 4 1. Pavement markings no longer applicable shall be removed or obliterated as soon as practical. 5 Except for intermediate-term and short-term situations, temporary markings shall be provided 6 to clearly delineate the temporary travel path. For short-term and intermediate-term situations 7 where it is not feasible to remove and restore pavement markings, channelization shall be made 8 dominant by using a very close device spacing. 9 Guidance: 10 2. When paved shoulders having a width of 8 feet or more are closed, channelizing devices should be 11 used to close the shoulder in advance of the merging taper to direct vehicular traffic to remain within 12 the traveled way. 13 3. Where channelizing devices are used instead of pavement markings, the maximum spacing should be 14 1/2 S feet where S is the speed in mph. 15 4. If the tangent distance along the temporary diversion is less than 600 feet, a Double Reverse Curve 16 sign should be used instead of the first Reverse Curve sign, and the second Reverse Curve sign should 17 be omitted. 18 Option: 19 5. Positive protection devices may be used per Section 6M.02. 20 5.6. Warning lights may be used to supplement channelizing devices at night.

6.7. A truck-mounted attenuator may be used on the work vehicle and/or the shadow vehicle.

21

1	Notes for Figure 6H6P-33 — Typical Application 33
2	Stationary Lane Closure on a Divided Highway
3	Standard:
4 5 6 7 8	 This information also shall be used when work is being performed in the lane adjacent to the median on a divided highway. In this case, the LEFT LANE CLOSED signs and the corresponding Lane Ends signs shall be substituted. When a side road intersects the highway within the TTC zone, additional TTC devices shall be placed as needed.
9	Guidance:
10 11 12	3. When paved shoulders having a width of 8 feet or more are closed, channelizing devices should be used to close the shoulder in advance of the merging taper to direct vehicular traffic to remain within the traveled way.
13	Option:
14	4. A truck-mounted attenuator may be used on the work vehicle and/or shadow vehicle.
15	4.5. Positive protection devices may be used per Section 6M.02.
16	Support:
17 18	5.6. Where conditions permit, restricting all vehicles, equipment, workers, and their activities to one side of the roadway might be advantageous.
19	Standard:
20 21 22	6-7. An arrow board shall be used when a freeway lane is closed. When more than one freeway lane is closed, a separate arrow board shall be used for each closed lane. Figure 6P-33. Stationary Lane Closure on a Divided Highway (TA-33)
23	

Notes for Figure 6H6P-34 — Typical Application 34 Lane Closure with a Temporary Traffic Barrier

Standard:

1. This information also shall be used when work is being performed in the lane adjacent to the median on a divided highway. In this case, the LEFT LANE CLOSED signs and the corresponding Lane Ends signs shall be substituted.

Guidance:

- 2. For long-term lane closures on facilities with permanent edge lines, a temporary edge line should be installed from the upstream end of the merging taper to the downstream end of the downstream taper, and conflicting pavement markings should be removed.
- 3. The use of a barrier should be based on engineering judgment.

Standard:

- 4. Temporary traffic barriers, if used, shall comply with the provisions of Section 6F.856M.02.
- 5. The barrier shall not be placed along the merging taper. The lane shall first be closed using channelizing devices and pavement markings.

Option:

- 6. Type C Steady-Burn warning lights may be placed on channelizing devices and the barrier parallel to the edge of pavement for nighttime lane closures.
- 7. The barrier shown in this typical application is an example of one method that may be used to close a lane for a long-term project. If the work activity permits, a movable barrier may be used and relocated to the shoulder during non-work periods or peak-period vehicular traffic conditions, as appropriate.

Standard:

8. If a movable barrier is used, the temporary white edge line shown in the typical application shall not be used. During the period when the right-hand lane is opened, the sign legends and the channelization shall be changed to indicate that only the shoulder is closed, as illustrated in Figure 6H6P-5. The arrow board, if used, shall be placed at the downstream end of the shoulder taper and shall display the caution mode.

Guidance:

- 9. If a movable barrier is used, the shift should be performed in the following manner. When closing the lane, the lane should be initially closed with channelizing devices placed along a merging taper using the same information employed for a stationary lane closure. The lane closure should then be extended with the movable-barrier transfer vehicle moving with vehicular traffic. When opening the lane, the movable-barrier transfer vehicle should travel against vehicular traffic from the termination area to the transition area. The merging taper should then be removed using the same information employed for a stationary lane closure.
 - Figure 6P-34. Lane Closure with a Temporary Traffic Barrier (TA-34)

1 Notes for Figure 6H6P-35 — Typical Application 35 2 Mobile Operation on a Multi-Lane Road 3 **Standard:** 4 1. Arrow boards shall, as a minimum, be Type B, with a size of 60 x 30 inches. 5 2. Vehicle-mounted signs shall be mounted in a manner such that they are not obscured by 6 equipment or supplies. Sign legends on vehicle-mounted signs shall be covered or turned from 7 view when work is not in progress. 8 3. Shadow and work vehicles shall display high-intensity rotating, flashing, oscillating, or strobe 9 lights. 10 4. An arrow board shall be used when a freeway lane is closed. When more than one freeway lane 11 is closed, a separate arrow board shall be used for each closed lane. 12 Guidance: 13 5. Vehicles used for these operations should be made highly visible with appropriate equipment, such as 14 flags, signs, or arrow boards. 15 6. Shadow Vehicle 1 should be equipped with an arrow board and truck-mounted attenuator. 16 7. Shadow Vehicle 2 should be equipped with an arrow board. An appropriate lane closure sign should 17 be placed on Shadow Vehicle 2 so as not to obscure the arrow board. 18 8. Shadow Vehicle 2 should travel at a varying distance from the work operation so as to provide 19 adequate sight distance for vehicular traffic approaching from the rear. 20 9. The spacing between the work vehicles and the shadow vehicles, and between each shadow vehicle 21 should be minimized to deter road users from driving in between. 22 10. Work should normally be accomplished during off-peak hours. 23 11. When the work vehicle occupies an interior lane (a lane other than the far right or far left) of a 24 directional roadway having a right-hand shoulder 10 feet or more in width, Shadow Vehicle 2 should 25 drive the right-hand shoulder with a sign indicating that work is taking place in the interior lane. 26 Option: 27 12. A truck-mounted attenuator may be used on Shadow Vehicle 2. 28 13. Positive protection devices may be used per Section 6M.02. 29 On high-speed roadways, a third shadow vehicle (not shown) may be used with Shadow 30 Vehicle 1 in the closed lane, Shadow Vehicle 2 straddling the edge line, and Shadow Vehicle 3 on the

- shoulder.
- 14.15. Where adequate shoulder width is not available, Shadow Vehicle 3 may also straddle the edge line.

Figure 6P-35. Mobile Operation on a Multi-Lane Road (TA-35)

31

32

33

34

1 Notes for Figure 6H6P-36 — Typical Application 36 2 Lane Shift on a Freeway 3 Guidance: 4 1. The lane shift should be used when the work space extends into either the right-hand or left-hand lane of a divided highway and it is not practical, for capacity reasons, to reduce the number of available 5 6 7 Support: 8 2. When a lane shift is accomplished by using (1) geometry that meets the design speed at which the 9 permanent highway was designed, (2) full normal cross-section (full lane width and full shoulders), 10 and (3) complete payement markings, then only the initial general work-zone warning sign is 11 required. 12 Guidance: 13 3. When the conditions in Note 2 are not met, the information shown in the typical application should be 14 employed and all the following notes apply. 15 **Standard:** 16 4. Temporary traffic barriers, if used, shall comply with the provisions of Section 6F.856M.02. 17 5. The barrier shall not be placed along the shifting taper. The lane shall first be shifted using channelizing devices and pavement markings. 18 19 Guidance: 20 6. A warning sign should be used to show the changed alignment. 21 Standard: 22 7. The number of lanes illustrated on the Reverse Curve signs shall be the same as the number of 23 through lanes available to road users, and the direction of the reverse curves shall be 24 appropriately illustrated. 25 Option: 26 8. Where two or more lanes are being shifted, a W1-4 (or W1-3) sign with an ALL LANES (W24-1cP) 27 plaque (see Figure 6F 46H-1) may be used instead of a sign that illustrates the number of lanes. 28 9. Where more than three lanes are being shifted, the Reverse Curve (or Turn) sign may be rectangular. 29 Guidance: 30 10. Where the shifted section is longer than 600 feet, one set of Reverse Curve signs should be used to 31 show the initial shift and a second set should be used to show the return to the normal alignment. If 32 the tangent distance along the temporary diversion is less than 600 feet, a Double Reverse Curve sign 33 should be used instead of the first Reverse Curve sign, and the second Reverse Curve sign should be 34 omitted. 35 11. If a STAY IN LANE sign is used, then solid white lane lines should be used. 36 37 12. The minimum width of the shoulder lane shall be 10 feet. 38 13. For long-term stationary work, existing conflicting pavement markings shall be removed and 39 temporary markings shall be installed before traffic patterns are changed. 40 Option: 41 14. For short-term stationary work, lanes may be delineated by channelizing devices or removable 42 pavement markings instead of temporary markings. 43 Guidance:

44

45 46

16. The use of a barrier should be based on engineering judgment.

15. If the shoulder cannot adequately accommodate trucks, trucks should be directed to use the travel

1 2	17. Type C Steady-Burn warning lights may be placed on channelizing devices and the barrier parallel to the edge of the pavement for nighttime lane closures.
3	Figure 6P-36. Lane Shift on a Freeway (TA-36)
4	

3	Standard:
4 5	1. An arrow board shall be used when a freeway lane is closed. When more than one freeway lane is closed, a separate arrow board shall be used for each closed lane.
6	Guidance:
7 8 9	2. Ordinarily, the preferred position for the second arrow board is in the closed exterior lane at the upstream end of the second merging taper. However, the second arrow board should be placed in the closed interior lane at the downstream end of the second merging taper in the following situations:
10 11	 a. When a shadow vehicle is used in the interior closed lane, and the second arrow board is mounted on the shadow vehicle;
12 13	b. If alignment or other conditions create any confusion as to which lane is closed by the second arrow board; and
14 15	c. When the first arrow board is placed in the closed exterior lane at the downstream end of the first merging taper (the alternative position when the shoulder is narrow).
16	Option:
17 18 19	 Flashing warning lights and/or flags may be used to call attention to the initial warning signs. A truck-mounted attenuator may be used on the shadow vehicle. Positive protection devices may be used per Section 6M.02.
20 21 22	5.6. If a paved shoulder having a minimum width of 10 feet and sufficient strength is available, the left-hand and adjacent interior lanes may be closed and vehicular traffic carried around the work space on the right-hand lane and a right-hand shoulder.
23	Guidance:
24 25	6.7. When a shoulder lane is used that cannot adequately accommodate trucks, trucks should be directed to use the normal travel lanes.
26	Figure 6P-37. Double Lane Closure on a Freeway (TA-37)
27	

Notes for Figure 6H6P-37 —Typical Application 37

Double Lane Closure on a Freeway

1 Notes for Figure 6H6P-38 —Typical Application 38 2 **Interior Lane Closure on a Freeway** 3 **Standard:** 4 1. An arrow board shall be used when a freeway lane is closed. When more than one freeway lane 5 is closed, a separate arrow board shall be used for each closed lane. 6 2. If temporary traffic barriers are installed, they shall comply with the provisions and 7 requirements in Section 6F.856M.02. 8 3. The barrier shall not be placed along the shifting taper. The lane shall first be shifted using 9 channelizing devices and pavement markings. 10 4. For long-term stationary work, existing conflicting pavement markings shall be removed and temporary markings shall be installed before traffic patterns are changed. 11 12 Guidance: 13 5. For a long-term closure, a barrier should be used to provide additional safety to the operation in the 14 closed interior lane. A buffer space should be used at the upstream end of the closed interior lane. 15 6. The first arrow board displaying an arrow pointing to the right should be on the left-hand shoulder at 16 the beginning of the taper. The arrow board displaying a double arrow should be centered in the 17 closed interior lane and placed at the downstream end of the shifting taper. 18 7. If the two arrow boards create confusion, the 2L distance between the end of the merging taper and 19 beginning of the shift taper should be extended so that road users can focus on one arrow board at a 20 time. 21 8. The placement of signs should not obstruct or obscure arrow boards. 22 9.7. For long-term use, the dashed broken lane lines should be made solid white in the two-lane section. 23 Option: 24 10.8. As an alternative to initially closing the left-hand lane, as shown in the typical application, the 25 right-hand lane may be closed in advance of the interior lane closure with appropriate channelization 26 and signs. The Interior Lane Shift Ahead (W9-4) symbol sign may be mirrored to indicate a right lane 27 shift. 28 11.9. A short, single row of channelizing devices in advance of the vehicular traffic split to restrict 29 vehicular traffic to their respective lanes may be added. 30 DO NOT PASS signs may be used. 31 13.11. If a paved shoulder having a minimum width of 10 feet and sufficient strength is available, 32 the left-hand and center lanes may be closed and motor vehicle traffic carried around the work space 33 on the right-hand lane and a right-hand shoulder. 34 12. A work vehicle with a truck mounted attenuator may be utilized within the closed interior lane 35 between the buffer space and the work area. 13. Positive protection devices may be used per Section 6M.02. 36

Guidance:

37

38

39

40 41 14. When a shoulder lane is used that cannot adequately accommodate trucks, trucks should be directed to use the normal travel lanes.

Figure 6P-38. Interior Lane Closure on a Freeway (TA-38)

1		Notes for Figure 6H6P-39 — Typical Application 39
2		Median Crossover on a Freeway
3	Standa	ard:
4 5	1.	Channelizing devices or temporary traffic barriers shall be used to separate opposing vehicular traffic.
6 7	2.	An arrow board shall be used when a freeway lane is closed. When more than one freeway lane is closed, a separate arrow board shall be used for each closed lane.
8	Guidan	ce:
9 10	3.	For long-term work on high-speed, high-volume highways, consideration should be given to using a temporary traffic barrier to separate opposing vehicular traffic.
11	Option	
12 13 14		When a temporary traffic barrier is used to separate opposing vehicular traffic, the Two-Way Traffic, DO NOT PASS, KEEP RIGHT, and DO NOT ENTER signs may be eliminated. The alignment of the crossover may be designed as a reverse curve.
15	3. Guidan	
16 17	0.	When the crossover follows a curved alignment, the design criteria contained in the AASHTO "Policy on the Geometric Design of Highways and Streets" (see Section 1A.4405) should be used.
18 19 20	7.	When channelizing devices have the potential of leading vehicular traffic out of the intended traffic space, the channelizing devices should be extended a distance in feet of 2.0 times the speed limit in mph beyond the downstream end of the transition area as depicted.
21	8.	Where channelizing devices are used, the Two-Way Traffic signs should be repeated every 1 mile.
22	Option	
23 24	9.	NEXT XX MILES Supplemental Distance plaques may be used with the Two-Way Traffic signs, where XX is the distance to the downstream end of the two-way section.
25	Suppor	t:
26 27		When the distance is sufficiently short that road users entering the section can see the downstream end of the section, they are less likely to forget that there is opposing vehicular traffic.
28 29 30	11.	The sign legends for the four pairs of signs approaching the lane closure for the non-crossover direction of travel are not shown. They are similar to the series shown for the crossover direction, except that the left-hand lane is closed.
31		Figure 6P-39. Median Crossover on a Freeway (TA-39)
32		Light of the filedian Crossover on a receiving (111 57)

1	Notes for Figure 6H6P-40 — Typical Application 40
2	Median Crossover for an Entrance Ramp
3	Guidance:
4 5	1. The typical application illustrated should be used for carrying an entrance ramp across a closed directional roadway of a divided highway.
6	2. A temporary acceleration lane should be used to facilitate merging.
7	3. When used, the YIELD or STOP sign should be located far enough forward to provide adequate sight
8	distance of oncoming mainline vehicular traffic to select an acceptable gap, but should not be located
9	so far forward that motorists will be encouraged to stop in the path of the mainline traffic. If needed,
10	yield or stop lines should be installed across the ramp to indicate the point at which road users should
11 12	yield or stop. Also, a longer acceleration lane should be provided beyond the sign to reduce the gap size needed.
13	Option:
14	4. Positive protection devices may be used per Section 6M.02.
15	4.5. If vehicular traffic conditions allow, the ramp may be closed.
16	5.6. A broken edge line may be carried across the temporary entrance ramp to assist in defining the
17	through vehicular traffic lane.
18	6.7. When a temporary traffic barrier is used to separate opposing vehicular traffic, the Two-Way Traffic
19	signs and the DO NOT ENTER signs may be eliminated.
20	Figure 6P-40. Median Crossover for an Entrance Ramp (TA-40)

1 Notes for Figure 6H6P-41 —Typical Application 41 2 **Median Crossover for an Exit Ramp** 3 Guidance: 4 1. This typical application should be used for carrying an exit ramp across a closed directional roadway 5 of a divided highway. The design criteria contained in the AASHTO "Policy on the Geometric Design 6 of Highways and Streets" (see Section 1A.1105) should be used for determining the curved alignment. 7 2. The guide signs should indicate that the ramp is open, and where the temporary ramp is located. 8 Conversely, if the ramp is closed, guide signs should indicate that the ramp is closed. 9 3. When the exit is closed, a black on orange EXIT CLOSED sign panel should be placed diagonally 10 across the interchange/intersection guide signs and channelizing devices should be placed to 11 physically close the ramp. 12 4. In the situation (not shown) where channelizing devices are placed along the mainline roadway, the 13 devices' spacing should be reduced in the vicinity of the off ramp to emphasize the opening at the 14 ramp itself. Channelizing devices and/or temporary pavement markings should be placed on both 15 sides of the temporary ramp where it crosses the median and the closed roadway. 5. Advance guide signs providing information related to the temporary exit should be relocated or 16 17 duplicated adjacent to the temporary roadway. 18 **Standard:** 19 6. A temporary EXIT sign shall be located in the temporary gore. For better visibility, it shall be 20 mounted a minimum of 7 feet from the pavement surface to the bottom of the sign. 21 Option: 22 7. Positive protection devices may be used per Section 6M.02. 23 7.8. Guide signs referring to the exit may need to be relocated to the median.

- 8.9. The temporary EXIT sign placed in the temporary gore may be either black on orange or white on
- In some instances, a temporary deceleration lane may be useful in facilitating the exiting 9.10. maneuver.
- When a temporary traffic barrier is used to separate opposing vehicular traffic, the Two-Way 10.11. Traffic signs may be omitted.

Figure 6P-41. Median Crossover for an Exit Ramp (TA-41)

24

25 26

27

28

29

30

2	Work in the Vicinity of an Exit Ramp
3	Guidance:
4 5	1. The guide signs should indicate that the ramp is open, and where the temporary ramp is located. However, if the ramp is closed, guide signs should indicate that the ramp is closed.
6 7	2. When the exit ramp is closed, a black on orange EXIT CLOSED sign panel should be placed diagonally across the interchange/intersection guide signs.
8 9	3. The design criteria contained in the AASHTO "Policy on the Geometric Design of Highways and Streets" (see Section 1A. 1105) should be used for determining the alignment.
10	Standard:
11 12	4. A temporary EXIT sign shall be located in the temporary gore. For better visibility, it shall be mounted a minimum of 7 feet from the pavement surface to the bottom of the sign.
13	Option:
14 15 16 17 18	 5. Positive protection devices may be used per Section 6M.02. 5.6. The temporary EXIT sign placed in the temporary gore may be either black on orange or white on green. 6.7. An alternative procedure that may be used is to channelize exiting vehicular traffic onto the right-hand shoulder and close the lane as necessary.
19	Standard:
20 21	7.8. An arrow board shall be used when a freeway lane is closed. When more than one freeway lane is closed, a separate arrow board shall be used for each closed lane.
22	Figure 6P-42. Work in the Vicinity of an Exit Ramp (TA-42)

Notes for Figure 6H6P-42 —Typical Application 42

1

1	Notes for Figure 6H6P-43 — Typical Application 43
2	Partial Exit Ramp Closure
3	Guidance:
4 5	1. Truck off-tracking should be considered when determining whether the minimum lane width of 10 feet is adequate (see Section $\frac{6G.08}{6N.07}$).
6	Option:
7	2. Positive protection devices may be used per Section 6M.02.
8	Figure 6P-43. Partial Exit Ramp Closure (TA-43)
9	

1 Notes for Figure 6H6P-44 — Typical Application 44 2 Work in the Vicinity of an Entrance Ramp 3 Guidance: 4 1. An acceleration lane of sufficient length should be provided whenever possible as shown on the 5 diagram on the left. 6 **Standard:** 7 2. For the information shown on the diagram on the right-hand side of the typical application, 8 where inadequate acceleration distance exists for the temporary entrance, the YIELD sign shall be replaced with STOP signs (one on each side of the approach). 9 10 Guidance: 11 3. When used, the YIELD or STOP sign should be located so that ramp vehicular traffic has adequate 12 sight distance of oncoming mainline vehicular traffic to select an acceptable gap in the mainline 13 vehicular traffic flow, but should not be located so far forward that motorists will be encouraged to 14 stop in the path of the mainline traffic. Also, a longer acceleration lane should be provided beyond 15 the sign to reduce the gap size needed. If insufficient gaps are available, consideration should be 16 given to closing the ramp. 17 4. Where STOP signs are used, a temporary stop line should be placed across the ramp at the desired 18 stop location. 19 5. The mainline merging taper with the arrow board at its starting point should be located sufficiently in 20 advance so that the arrow board is not confusing to drivers on the entrance ramp, and so that the 21 mainline merging vehicular traffic from the lane closure has the opportunity to stabilize before 22 encountering the vehicular traffic merging from the ramp. 23 6. If the ramp curves sharply to the right, warning signs with advisory speeds located in advance of the 24 entrance terminal should be placed in pairs (one on each side of the ramp). 25 Option: 26 7. Positive protection devices may be used per Section 6M.02. 27 7.8. A Stop Beacon (see Section 4L4S.05) or a Type B high-intensity warning flasher with a red lens may 28 be placed above the STOP sign. 29 8.9. Where the acceleration distance is significantly reduced, a supplemental plaque may be placed below 30 the Yield Ahead sign reading NO MERGE AREA. 31 **Standard:** 32 **9.10.** An arrow board shall be used when a freeway lane is closed. When more than one 33

freeway lane is closed, a separate arrow board shall be used for each closed lane.

Figure 6P-44. Work in the Vicinity of an Entrance Ramp (TA-44)

34

Notes for Figure 6H6P-45 — Typical Application 45

Temporary Reversible Lane Using Movable Barriers

Support:

1. This application addresses one of several uses for movable barriers (see Section 6F.856M.02) in highway work zones. In this example, one side of a 6-lane divided highway is closed to perform the work operation, and vehicular traffic is carried in both directions on the remaining 3-lane roadway by means of a median crossover.

To accommodate unbalanced peak-period vehicular traffic volumes, the direction of travel in the center lane is switched to the direction having the greater volume, with the transfer typically being made twice daily. Thus, there are four vehicular traffic phases described as follows:

- a. Phase A—two travel lanes northbound and one lane southbound;
- b. Transition A to B—one travel lane in each direction:
- c. Phase B—one travel lane northbound and two lanes southbound; and
- d. Transition B to A—one travel lane in each direction.

The typical application on the left illustrates the placement of devices during Phase A. The typical application on the right shows conditions during the transition (Transition A to B) from Phase A to Phase B.

Guidance:

2. For the reversible-lane situation depicted, the ends of the movable barrier should terminate in a protected area or a crash cushion should be provided. During Phase A, the transfer vehicle should be parked behind the downstream end of the movable barrier for southbound traffic as shown in the typical application on the left. During Phase B, the transfer vehicle should be parked behind between the downstream ends of the movable barriers at the north end of the TTC zone as shown in the typical application on the right.

The transition shift from Phase A to B should be as follows:

- a. Change the signs in the northbound advance warning area and transition area from a LEFT LANE CLOSED AHEAD to a 2 LEFT LANES CLOSED AHEAD. Change the mode of the second northbound arrow board from Caution to Right Arrow.
- b. Place channelizing devices to close the northbound center lane.
- c. Move the transfer vehicle from south to north to shift the movable barrier from the west side to the east side of the reversible lane.
- d. Remove the channelizing devices closing the southbound center lane.
- e. Change the signs in the southbound transition area and advance warning area from a 2 LEFT LANES CLOSED AHEAD to a LEFT LANE CLOSED AHEAD. Change the mode of the second southbound arrow board from Right Arrow to Caution.
- 3. Where the lane to be opened and closed is an exterior lane (adjacent to the edge of the traveled way or the work space), the lane closure should begin by closing the lane with channelizing devices placed along a merging taper using the same information employed for a stationary lane closure. The lane closure should then be extended with the movable-barrier transfer vehicle moving with vehicular traffic. When opening the lane, the transfer vehicle should travel against vehicular traffic. The merging taper should be removed in a method similar to a stationary lane closure.

Option:

- 4. The procedure may be used during a peak period of vehicular traffic and then changed to provide two lanes in the other direction for the other peak.
- 5. A longitudinal buffer space may be used in the activity area to separate opposing vehicular traffic.
- 6. A work vehicle or a shadow vehicle may be equipped with a truck-mounted attenuator.

Standard:

7. An arrow board shall be used when a freeway lane is closed. When more than one freeway lane is closed, a separate arrow board shall be used for each closed lane.

Figure 6P-45. Temporary Reversible Lane Using Movable Barriers (TA-45)

1 Notes for Figure 6H6P-46 — Typical Application 46 2 Work in the Vicinity of a Grade Crossing 3 Guidance: 4 1. When grade crossings exist either within or in the vicinity of roadway work activities, extra care 5 should be taken to minimize the probability of conditions being created, by lane restrictions, flagging, 6 or other operations, where vehicles might be stopped within the grade crossing, considered as being 7 15 feet on either side of the closest and farthest rail. 8 Standard: 9 2. If the queuing of vehicles across active rail tracks cannot be avoided, a uniformed law 10 enforcement officer or flagger shall be provided at the grade crossing to prevent vehicles from stopping within the grade crossing (as described in Note 1), even if automatic warning devices 11 12 are in place. 13 Guidance: 14 3. Early coordination with the railroad company or light rail transit agency should occur before work 15 16 4. In the example depicted, the buffer space of the activity area should be extended upstream of the 17 grade crossing (as shown) so that a queue created by the flagging operation will not extend across the 18 grade crossing. 19 5. The DO NOT STOP ON TRACKS sign should be used on all approaches to a grade crossing within 20 the limits of a TTC zone. 21 Option: 22 6. Positive protection devices may be used per Section 6M.02. 23 6.7. Flashing warning lights and/or flags may be used to call attention to the advance warning signs. 24 7.8. A BE PREPARED TO STOP sign may be added to the sign series. 25 Guidance: 26 8.9. When used, the BE PREPARED TO STOP sign should be located before the Flagger symbol sign. 27 **Standard:**

At night, flagger stations shall be illuminated, except in emergencies.

Figure 6P-46. Work in the Vicinity of a Grade Crossing (TA-46)

28

29

9.10.

1	Notes for Figure 6P-47–Typical Application 47
2	Bicycle Lane Closure without Detour
3	Added to improve accuracy and consistency with new Section 6N.04
4	Guidance:
5 6 7	1. If a bicycle lane on a roadway having a speed limit of 35 mph or higher is closed and conditions are not appropriate to direct bicyclists into a shared lane, a separate bicycle facility or detour route should be considered. Refer to Figure 6P-48 or Figure 6P-51.
8	Option:
9 10	2. If a bicycle lane on a roadway having a speed limit of 30 mph or less is closed, and the adjacent travel lane is less than 17 feet wide, then BICYCLES MAY USE FULL LANE signs may be used.
11 12 13	3. If a bicycle lane on a roadway having a speed limit of 30 mph or less is closed, and the adjacent travel lane is at least 17 feet wide throughout the TTC zone, then Bicycle Warning signs in association with ON STREET or ON ROADWAY plaques may be used.
14	Figure 6P-47. Bicycle Lane Closure without Detour (TA-47)
15	

1	Notes for Figure 6P-48 – Typical Application 48
2	Bicycle Lane Closure with On-Road Detour
3	Added to improve accuracy and consistency with new Section 6N.04
4	<u>Guidance:</u>
5 6	1. A detour route for bicycle traffic where a section of bicycle lane is closed should use the most direct route practical on roadways where conditions are appropriate for bicycling.
7 8	2. Bicycle related regulatory and/or warning signs should be considered along the bicycle detour based on engineering judgment and traffic conditions.
9 10	3. A Street Name sign or Bike Route Name sign should be mounted with the Bike Detour sign. The Street Name sign or Bike Route Name sign may be either white on green or black on orange.
11	Standard:
12 13	4. Where used, the Street Name sign or Bike Route Name sign shall be placed above the Bike Detour sign.
14	Figure 6P-48. Bicycle Lane Closure with On-Road Detour (TA-48)
15	

1	Notes for Figure 6P-49_Typical Application 49
2	Shared-Use Path Closure with a Diversion
3	Added to improve accuracy and consistency with new Section 6N.04
4	Guidance:
5	1. The temporary paved shared-use path should be at least as wide as the shared-use path that was
6	temporarily closed.
7	Figure 6P-49. Shared-Use Path Closure with a Diversion (TA-49)
8	

1	Notes for Figure 6P-50-Typical Application 50
2	On-Road Detour for Shared-Use Path
3	Added to improve accuracy and consistency with new Section 6N.04
4	Guidance:
5 6	1. The on-road detour route for bicycle traffic should use the most direct route practical on roadways where conditions are appropriate for bicycling.
7 8	2. Bicycle related regulatory and/or warning signs should be considered along the bicycle detour based on engineering judgment and traffic conditions.
9 10	3. A Street Name sign or Bike Route Name sign should be mounted with the Bike Detour sign. The Street Name sign or Bike Route Name sign may be either white on green or black on orange.
11	Standard:
12 13	4. Where used the Street Name sign or Bike Route Name sign shall be placed above the Bike Detour sign.
14	Figure 6P-50. On-Road Detour for Shared-Use Path (TA-50)
15	
16	

1	Notes for Figure 6P-51-Typical Application 51
2	Paved Shoulder Closure with Bicycle Diversion onto Temporary Path
3	Added to improve accuracy and consistency with new Section 6N.04
4	Option:
5	1. This plan may be used where a paved shoulder is closed and a temporary paved path is provided
6	for bicyclists.
7	
8	Guidance:
9	2. This plan should be used where a paved shoulder is closed on a roadway having a speed limit
10	greater than or equal to 45 mph that is part of a bikeway system (local, county or state) and a
11	temporary paved path is provided for bicyclists.
12	3. The A, B, C dimensions should be based on anticipated bicycle speeds.
13	Figure 6P-51. Paved Shoulder Closure with Bicycle Diversion onto Temporary Path (TA-51)
14	

1 2 3 4	Notes for Figure 6P-52 – Typical Application 52 Short-Term or Short Duration Work in a Roundabout Added to improve consistency
5	Option:
6 7	1. Flashing warning lights and/or flags may be used to call attention to the advance warning signs. A BE PREPARED TO STOP sign may be added to the sign series.
8	2. If closure continues overnight, warning lights may be used on the channelizing devices.
9	Standard:
10 11	3. Where a quadrant of the roundabout is closed as shown in Figure 6P-47, only one direction of approach traffic shall be released at a time.
12	4. At night, flagger stations shall be illuminated, except in emergencies.
13	5. WRONG WAY signs shall be covered.
14	<u>Guidance:</u>
15 16	6. When used, the BE PREPARED TO STOP sign should be located between the Flagger sign and the ONE LANE ROAD sign.
17	7. YIELD, ONE WAY, and Directional arrow signs should be covered or removed.
18	8. Confusing or misleading guide or lane-use control signs should be covered.
19	Option:
20	9. Crosswalks may be closed.
21 22	10. As an alternative to closing crosswalks, warning signs may be added informing pedestrians that there is traffic coming from the left.
23	Guidance:
24 25	11. Since the geometrics of the roundabout will be temporarily altered, consideration should be given to
	establishing a truck detour for the duration of the project.
26 27	12. For intermediate or long-term work, the roundabout should be closed and traffic detoured, with appropriate detour signing provided.
28	Figure 6P-52. Short-Term or Short Duration Work in a Roundabout (TA-52)
29	right of the bhold form of bhold bulleton if off in a roundabout (111 52)

1 2 3		Notes for Figure 6P-53 – Typical Application 53 Flagging Operation on a Single-Lane Roundabout Added to improve consistency
4		Added to improve consistency
5		
6	Standa	<u>urd:</u>
7	<u>1.</u>	Flaggers shall follow the procedures provided in Sections 6D.05 and 6D.06.
8	<u>2.</u>	When crosswalks or other pedestrian facilities are closed or relocated, temporary facilities shall
9		be detectable and shall include accessibility features consistent with the features present in the
10		existing pedestrian facility. See Figure 6P-29. Crosswalk Closures and Pedestrian Detours (TA-
11		<u>29).</u>
12	<u>3.</u>	At night, flagger stations shall be illuminated, except in emergencies.
13	G . I	
14	<u>Guidan</u>	
15	<u>4.</u>	Flaggers on each approach to the intersection should coordinate with each other so that traffic may
16	_	proceed through the roundabout from only one entry point at any one time.
17	<u>3.</u>	When designing the temporary traffic control and installing the channelizing devices for work
18		activities at roundabouts, accommodations for the turning radius of wider heavy commercial vehicles
19 20	6	should be considered.
21	<u>0.</u>	Since the geometrics of the roundabout will temporarily be altered, consideration should be given to establishing a truck detour for the duration of the project.
22	7	
23	<u>/.</u>	For intermediate or long-term work, the roundabout should be closed if traffic cannot be
24		accommodated, and traffic detoured with appropriate detour signing provided. See Figure 6P-8, Road Closure with an Off-Site Detour (TA-8).
25	o	Conflicting pavement markings should be removed for long-term projects. For short-term and
26	<u>o.</u>	
27		intermediate-term projects where this is not practical, the channelizing devices in the area where the pavement markings conflict should be placed at a maximum spacing of 1/2 S feet where S is the speed
28		in mph. Temporary markings should be installed where needed.
29	O	When used, the BE PREPARED TO STOP sign should be located between the 96 Flagger sign and
30	<u> </u>	the ONE LANE ROAD sign.
31	10	The buffer space should be extended so that the two-way traffic taper is placed before a 98 horizonta
32	<u>10.</u>	(or crest vertical) curve to provide adequate sight distance for the flagger 99 and a queue of stopped
33		vehicles.
34	11	Care should be exercised when establishing the limits of the work zone to ensure adequate sight
35	11.	distance in advance of the transition.
		assumed in durance of the transmort.
36 37	Option	:
38	_	Periodic adjustments to the channelizing devices may be allowed in an active work zone to
39		accommodate the turning movements of tractor trailer vehicles and other large vehicles.
40	13.	On the approaches where traffic flow will be split, two pilot vehicles may be used to guide traffic
41		through the roundabout.
42		Figure 6P-53. Flagging Operation on a Single-Lane Roundabout (TA-53)
43		

1	Notes for Figure 6P-54 Typical Application 54	
2 3	Inside Lane Closure on a Multi-Lane Roundabout	
3	Added to improve consistency	
4		
5	Standard:	
6	1. When crosswalks or other pedestrian facilities are closed or relocated, temporary facilities	shall
7	be detectable and shall include accessibility features consistent with the features present in	the
8	existing pedestrian facility. See Figure 6P-29. Crosswalk Closures and Pedestrian Detours	(TA-
9	29).	
10		
11	Guidance:	
12	2. Care should be exercised when establishing the limits of the work zone to sight distance in advan	nce o
13	the transition.	
14	3. When designing the temporary traffic control and installing the channelizing devices for work	
15	activities at roundabouts, accommodations for the turning radius of wider heavy commercial vel	hicles
16	should be considered.	
17	4. Since the geometrics of the roundabout will temporarily be altered, consideration should be give	en to
18	establishing a truck detour for the duration of the project.	
19	5. For intermediate or long-term work, the roundabout should be closed if traffic cannot be	
20	accommodated, and traffic detoured with appropriate detour signing provided. See Figure 6P-8	<u>. </u>
21	Road Closure with an Off-Site Detour (TA-8).	
22	6. Conflicting pavement markings should be removed for long-term projects. For short-term and	
23	intermediate-term projects where this is not practical, the channelizing devices in the area wher	e the
24	pavement markings conflict should be placed at a maximum spacing of 1/2 S feet where S is the	speed
25	in mph. Temporary markings should be installed where needed.	
26		
27	Option:	
28	7. A portable changeable message sign may be utilized as part of the temporary traffic control plan	to
29	provide clear guidance to motorist on all approaches of the roundabout.	
30	8. On a multi-lane approach, either lane may be closed.	
31	Figure 6P-54. Inside Lane Closure on a Multi-Lane Roundabout (TA-54)	

4

5

6

7

8

9

10

11

12

13 14

15

16

17

18

19

20

21

22

23

24

25

26

2728

29

30

31

32

33

34

35

3637

38

39

40

41

42 43

44

45

2 Section 7A.0401 Introduction Scope Content relocated from existing Section 7A.04

Standard Support:

Part 7 sets forth basic principles and prescribes standards that shall be followed in the for the design, application, installation, and maintenance of all traffic control devices (including signs, signals, and markings) and other controls (including adult crossing guards) required that are necessary for the special pedestrian conditions in school areas.

Support:

Sections 1A.01 and 1A.08 contain information regarding unauthorized devices and messages. Sections 1A.02 and 1A.07 contain information regarding the application of standards. Section 1A.05 contains information regarding the maintenance of traffic control devices. Section 1A.08 contains information regarding placement authority for traffic control devices. Section 1A.09 contains information regarding engineering studies and the assistance that is available to jurisdictions that do not have engineers on their staffs who are trained and/or experienced in traffic control devices.

Provisions contained in Chapter 2A and Section 2B.06 are applicable in school areas.

Part 3 contains provisions regarding pavement markings that are applicable in school areas.

Part 4 contains provisions regarding highway traffic signals that are applicable in school areas. The School Crossing signal warrant is described in Section 4C.06.

Section 7A.01 Need for Standards Section not needed, Guidance relocated to Section 7A.02

Section 7A.02 School Route Planss and Established School Crossings

Guidance: Relocated four Guidance paragraphs from existing Section 7A.01

A school route plan for each school serving elementary to high school students should be prepared in order to develop uniformity in the use of school area traffic controls and to serve as the basis for a school traffic control plan for each school.

The school route plan, developed in a systematic manner by the school, law enforcement, and traffic officials responsible for school pedestrian safety, should consist of a map (see Figure 7A-1) showing streets, the school, existing traffic controls, established school walk routes, and established school crossings.

The type(s) of school area traffic control devices used, either warning or regulatory, should be related to the volume and speed of vehicular traffic, street width, and the number and age of the students using the crossing.

School area traffic control devices should be included in a school traffic control plan.

Support:

To establish a safer route to and from school for schoolchildren, the application of planning criterion for school walk routes might make it necessary for children to walk an indirect route to an established school crossing located where there is existing traffic control and to avoid the use of a direct crossing where there is no existing traffic control.

Guidance:

School walk routes should be planned to take advantage of existing traffic controls.

The following factors should be considered when determining the feasibility of requiring children to walk a longer distance to a crossing with existing traffic control:

- A. The availability of adequate sidewalks or other pedestrian walkways to and from the location with existing control,
- B. The number of students using the crossing,
- C. The age levels of the students using the crossing, and
- D. The total extra walking distance.

46 Section 7A.03 School Crossing Control Criteria Separate section not needed

47 Support:

1 2 3 4 5 6 7	The frequency of gaps in the traffic stream that are sufficient for student crossing is different at each erossing location. When the delay between the occurrences of adequate gaps becomes excessive, students might become impatient and endanger themselves by attempting to cross the street during an inadequate gap. In these instances, the creation of sufficient gaps needs to be considered to accommodate the crossing demand. Not necessary A recommended method for determining the frequency and adequacy of gaps in the traffic stream is given in the "Traffic Control Devices Handbook" (see Section 1A.11). Relocated to Section 7D.01
8	Section 7A.04 Scope Relocated and revised to become new Section 7A.01 and title changed
9	Figure 7A-1. Example of School Route Plan Map
10	

2	Section 7B.01 Size Design of School Signs
3	Standard:
4 5	Except as provided in Section 2A.1107, the sizes of signs and plaques to be used on conventional roadways in school areas shall be as shown in Table 7B-1.
6 7	The sizes in the Conventional Road column shall be used unless engineering judgment determines that a minimum or oversized sign size would be more appropriate.
8 9	The sizes in the Minimum column shall be used only where traffic volumes are low and speeds are 30 mph or lower, as determined by engineering judgment.
10 11	The sizes in the Oversized column shall be used on expressways. Not needed, redundant with Section 2A.11
12	Guidance:
13 14	The sizes in the Oversized column should be used on roadways that have four or more lanes with posted speed limits of 40 mph or higher.
15	Option:
16 17	The sizes in the Oversized column may also be used at other locations that require increased emphasis, improved recognition, or increased legibility Not needed, redundant with Section 2A.11
18	Signs and plaques larger than those shown in Table 7B-1 may be used (see Section 2A.1107).
19	Section 7B.02 Illumination and Reflectorization Section title deleted; text combined with
20	Section 7B.01
21	Standard:
22	School warning signs, including the "SCHOOL" portion of the School Speed Limit (S5-1) sign and
23	including any supplemental plaques used in association with these warning signs, shall have a
24	fluorescent yellow-green background with a black legend and border unless otherwise provided in this
25 26	Manual for a specific sign. The signs wood for school area troffic control shall be retroveflectorized not receive or
26 27	The signs used for school area traffic control shall be retroreflectorized retroreflective or illuminated.
28	Section 7B.03 Position of Signs Section title deleted; text combined with Section 7B.01
29	Support:
30 31	Sections 2A. 16 12 and 2A. 17 13 contain provisions regarding the <u>installation</u> , placements, and locations of signs. Relocated from existing Section 7B.06
32 33	Section 2A. <u>18-14</u> contains provisions regarding the mounting height of signs. Relocated from existing Section 7B.04
34 35	Section 2A. 19 - <u>15</u> contains provisions regarding the lateral offsets of signs. Relocated from existing Section 7B.06
36 37	The "Standard Highway Signs and Markings" book (see Section 1A.1105) contains information regarding sign lettering. Relocated from existing Section 7B.06
38	Option:
39 40	In-roadway signs for school traffic control areas may be used consistent with the requirements of Sections 2B. 12 21, and 7B. 11 03, and 7B.12 .
41	Table 7B-1 . School Area Sign and Plaque Sizes
42	Section 7B.04 Height of Signs Section title deleted, text combined with Section 7B.01
43	Section 7B.05 Installation of Signs Section title deleted, text combined with Section 7B.01
44	Section 7B.06 Lettering Section title deleted, text combined with Section 7B.01

Section 7B.08 Section 7B.02 School Area Signs (S1-1) and Plaques

Support:

Many state and local jurisdictions find it beneficial to advise road users that they are approaching a school that is adjacent to a highway, where additional care is needed, even though no school crossing is involved and the speed limit remains unchanged. Additionally, some jurisdictions designate school zones that have a unique legal standing in that fines for speeding or other traffic violations within designated school zones are increased or special enforcement techniques such as photo radar systems are used. It is important and sometimes legally necessary to mark the beginning and end points of these designated school zones so that the road user is given proper notice.

The School (S1-1) sign (see Figure 7B-1) has the following four applications:

- A. School Area the S1-1 sign can be used to warn road users that they are approaching a school area that might include school buildings or grounds, a school crossing, or school related activity adjacent to the highway.
- B. School Zone the S1-1 sign can be used to identify the location of the beginning of a designated school zone (see Section 7B.09).
- C. School Advance Crossing if combined with an AHEAD (W16-9P) plaque or an XX FEET (W16-2P or W16-2aP) plaque to comprise the School Advance Crossing assembly, the S1-1 sign can be used to warn road users that they are approaching a crossing where schoolchildren cross the roadway (see Section 7B. 1103).
- D. School Crossing if combined with a diagonal downward pointing arrow (W16-7P) plaque to comprise the School Crossing assembly, the S1-1 sign can be used to warn approaching road users of the location of a crossing where schoolchildren cross the roadway (see Section 7B.1203).

Option:

If a school area is located on a cross street in close proximity to the intersection, a School (S1-1) sign with a supplemental arrow (W16-5P or W16-6P) plaque may be installed on each approach of the street or highway to warn road users making a turn onto the cross street that they will encounter a school area soon after making the turn.

Section 7B.09 School Zone Sign (S1-1) and Plaques (S4-3P, S4-7P) and END SCHOOL ZONE Sign (S5-2) Section title deleted, text combined with new Section 7B.02

Standard:

If a school zone has been designated under State or local statute, a School (S1-1) sign (see Figure 7B-1) shall be installed to identify the beginning point(s) of the designated school zone (see Figure 7B-2). Option:

A School Zone (S1-1) sign may be supplemented with a SCHOOL (S4-3P) plaque (see Figure 7B-1).

A School Zone (S1-1) sign may be supplemented with an ALL YEAR (S4-7P) plaque (see Figure 7B-1) if the school operates on a 12-month schedule.

The downstream end of a designated school zone may be identified with an END SCHOOL ZONE (S5-2) sign (see Figures 7B-1 and 7B-2).

If a school zone is located on a cross street in close proximity to the intersection, a School Zone (S1-1) sign with a supplemental arrow (W16-5P or W16-6P) plaque may be installed on each approach of the street or highway to warn road users making a turn onto the cross street that they will encounter a school zone soon after making the turn.

- 45 Section 7B.10 Higher Fines Zone Signs (R2-10, R2-11) and Plaques Combined with new Section 7B.02
- 47 Standard: Guidance: Standard changed to Guidance

Where increased fines are imposed for traffic violations within a designated school zone, a BEGIN HIGHER FINES ZONE (R2-10) sign (see Figure 7B-1) or a FINES HIGHER (R2-6P), FINES DOUBLE (R2-6aP), or \$XX FINE (R2-6bP) plaque (see Figure 2B-3) shall-should be installed as a supplement to the School Zone (S1-1) sign to identify the beginning point of the higher fines zone (see Figures 7B-2 and 7B-3).

If the portion of the roadway that is subject to higher fines does not begin at the location of the School Zone (S1-1) sign, a BEGIN HIGHER FINES ZONE (R2-10) sign should be placed at the point where the higher fines begin. Paragraph added per Official Interpretation 7(09)-3 (I)

Option:

<u>If a BEGIN HIGHER FINES ZONE (R2-10) sign is used, a FINES HIGHER (R2-6P), FINES DOUBLE</u> (R2-6aP), or \$XX FINE (R2-6bP) plaque may be placed beneath the School Zone (S1-1) sign.

Where appropriate, one of the following plaques may be mounted below the sign that identifies the beginning point of the higher fines zone:

- A. An S4-1P plaque (see Figure 7B-1) specifying the times that the higher fines are in effect,
- B. A WHEN CHILDREN ARE PRESENT (S4-2P) plaque (see Figure 7B-1), or
- C. A WHEN FLASHING (S4-4P) plaque (see Figure 7B-1) if used in conjunction with a yellow flashing beacon.

Standard:

Where a BEGIN HIGHER FINES ZONE (R2-10) sign or a FINES HIGHER (R2-6P), FINES DOUBLE (R2-6aP), or \$XX FINE (R2-6bP) plaque supplementing a School Zone (S1-1) sign is posted to notify road users of increased fines for traffic violations, an END HIGHER FINES ZONE (R2-11) sign (see Figure 7B-1) or an END SCHOOL ZONE (S5-2) sign shall be installed at the downstream end of the zone to notify road users of the termination of the increased fines zone (see Figures 7B-2 and 7B-3).

If exceeding the speed limit is the only traffic violation that is subject to higher fines, a FINES HIGHER (R2-6P), FINES DOUBLE (R2-6aP), or \$XX FINE (R2-6bP) plaque shall not be posted beneath the School Zone (S1-1) sign. Paragraph added per Official Interpretation 7(09)-3 (I)

Figure 7B-1. School Area Signs

Section 7B.11 7B.03 School Advance Crossing Assembly Signs

Standard:

The School Advance Crossing assembly (see Figure 7B-1) shall consist of a School (S1-1) sign supplemented with an AHEAD (W16-9P) plaque or an XX FEET (W16-2P or W16-2aP) plaque.

Except as provided in Paragraph 3, a School Advance Crossing assembly shall be used in advance (see Table 2C-4 for advance placement guidelines) of the first School Crossing assembly (see Section 7B.12) that is encountered in each direction as traffic approaches a school crosswalk (see Figure 7B-4). Option:

The School Advance Crossing assembly may be omitted (see Figure 7B-5) where a School Zone (S1-1) sign (see Section 7B.09) is installed to identify the beginning of a school zone in advance of the School Crossing assembly.

If a school crosswalk is located on a cross street in close proximity to an intersection, a School Advance Crossing assembly with a supplemental arrow (W16-5P or W16-6P) plaque may be installed on each approach of the street or highway to warn road users making a turn onto the cross street that they will encounter a school crosswalk soon after making the turn. A 12-inch reduced size in-street School (S1-1) sign (see Figure 7B-6), installed in compliance with the mounting height and special mounting support requirements for In-Street Pedestrian Crossing (R1-6 or R1-6a) signs (see Section 2B.12), may be used in advance of a school crossing to supplement the post-mounted school warning signs. A 12 x 6-inch reduced size AHEAD (W16-9P) plaque may be mounted below the reduced size in-street School (S1-1) sign.

- Section 7B.12 School Crossing Assembly Combined with new Section 7B.03
- **Standard:**

If used, the School Crossing assembly (see Figure 7B-1) shall be installed at the school crossing (see Figures 7B-4 and 7B-5), or as close to it as possible, and shall consist of a School (S1-1) sign supplemented with a diagonal downward pointing arrow (W16-7P) plaque to show the location of the crossing.

The School Crossing assembly shall not be used at crossings other than those adjacent to schools and those on established school pedestrian routes.

The School Crossing assembly shall not be installed on <u>an</u> approaches controlled by a STOP or YIELD sign.

Guidance:

<u>The School Crossing assembly should not be installed on an approach controlled by a YIELD sign.</u>
Option:

The School Crossing assembly may be installed on an approach to a roundabout where the crosswalk is at least one car length in advance of the yield point at the entrance to the roundabout.

At a signalized or Stop-controlled intersection the School Crossing assembly may be installed on an approach to a channelized right turn lane controlled by a YIELD sign.

A Yield Here To (Stop Here For) Pedestrians (R1-5a or R1-5c) sign (see Figure 7B-6) may be used, in accordance with the provisions of Section 2B.20, in advance of a marked crosswalk that crosses an uncontrolled multi-lane approach within school zones.

The In-Street Pedestrian Crossing (R1-6 or R1-6a) sign (see Section 2B.12 and Figure 7B-6) or the In-Street Schoolchildren School Crossing (R1-6b or R1-6c) sign (see Figure 7B-6) may be used at unsignalized school crossings on approaches that are not controlled by a traffic control signal, a pedestrian hybrid beacon, or emergency vehicle hybrid beacon. If used at a school crossing, a 12 x 4-inch SCHOOL (S4-3P) plaque (see Figure 7B-6) may be mounted above the sign. The STATE LAW legend on the R1-6 series signs may be omitted.

The In-Street Pedestrian Crossing (R1-6 or R1-6a) sign or In-Street School Crossing (R1-6b or R1-6c) sign may be used at intersections or midblock crossings with flashing beacons.

The Overhead Pedestrian School Crossing (R1-9b or R1-9a9c) sign (see Section 2B.12 and Figure 2B-2) may be modified to replace the standard pedestrian symbol with the standard schoolchildren symbol and may be used at unsignalized school crossings on approaches that are not controlled by a traffic control signal, pedestrian hybrid beacon, or an emergency vehicle hybrid beacon. The STATE LAW legend on the R1-9 series signs may be omitted.

A 12-inch reduced size in-street School (S1-1) sign (see Figure 7B-6) may be used at an unsignalized school crossing instead of the In-Street Pedestrian Crossing (R1-6 or R1-6a) or the In-Street Schoolchildren-School Crossing (R1-6b or R1-6c) sign at a school crossing on approaches that are not controlled by a traffic control signal, pedestrian hybrid beacon, or an emergency vehicle hybrid beacon. A 12 x 6-inch reduced size diagonal downward pointing arrow (W16-7P) plaque may be mounted below the reduced size in-street School (S1-1) sign.

Standard:

If an In-Street Pedestrian Crossing sign, an In-Street Schoolehildren Crossing sign, or a reduced size in-street School (S1-1) sign is placed in the roadway, the sign support shall comply with the mounting height and special mounting support requirements for In-Street Pedestrian Crossing (R1-6 or R1-6a) signs (see Section 2B.12).

The In-Street Pedestrian Crossing sign, the In-Street School Crossing sign, the Overhead Pedestrian Crossing sign, and the reduced size in-street School (S1-1) sign shall not be used—at signalized locations on approaches that are controlled by a traffic control signal, pedestrian hybrid beacon, or an emergency vehicle hybrid beacon.

Section 7B.13 Section 7B.04 School Bus Stop Ahead Signs (S3-1)

48 Guidance:

The School Bus Stop Ahead (S3-1) sign (see Figure 7B-1) should be installed in advance of locations where a school bus, when stopped to pick up or discharge passengers, is not visible to road users for an Notice of Proposed Amendments – Part 7 Page 673 of 781 December 2020

adequate distance and where there is no opportunity to relocate the school bus stop to provide adequate sight
 distance.

Section 7B.14 SCHOOL BUS TURN AHEAD Sign (S3-2) Combined with new Section 7B.04

4 Option:

The SCHOOL BUS TURN AHEAD (S3-2) sign (see Figure 7B-1) may be installed in advance of locations where a school bus turns around on a roadway at a location not visible to approaching road users for a distance as determined by the "0" column under Condition B of Table 2C-4, and where there is no opportunity to relocate the school bus turn around to provide the distance provided in Table 2C-4.

9 Section 7B.05 School Bus Stop When Flashing Sign

10 Option:

A "STOP FOR SCHOOL BUS WHEN RED LIGHTS FLASH" (S5-4) sign may be used to remind drivers of the requirement to stop for school buses when the flashing red lights on the school bus are in operation.

Standard:

The legend "STATE LAW" shall be used with black letters on yellow background on the top line of the sign.

Support:

A "STOP FOR SCHOOL BUS WHEN RED LIGHTS FLASH" (S5-4) sign is typically used where special regulatory emphasis is needed. This sign provides regulatory notice to inform drivers of applicable laws along sections of roadway with multiple bus stops or those that have a particularly high incidence of drivers passing or not stopping for school buses when the red lights are flashing.

Section 7B.15-06 School Speed Limit Assembly (S4-1P, S4-2P, S4-3P, S4-4P, S4-6P, S5-1) and END SCHOOL SPEED LIMIT Sign (S5-3)Signs and Plaques

Standard:

A School Speed Limit assembly (see Figure 7B-1) or a School Speed Limit (S5-1) sign (see Figure 7B-1) shall be used to indicate the speed limit where a reduced school speed limit zone has been established based upon an engineering study or where a reduced school speed limit is specified for such areas by statute. The School Speed Limit assembly or School Speed Limit sign shall be placed at or as near as practical to the point where the reduced school speed limit zone begins (see Figures 7B-3 and 7B-5).

If a reduced school speed limit zone has been established, a School (S1-1) sign shall be installed in advance (see Table 2C-4 for advance placement guidelines) of the first School Speed Limit sign assembly or S5-1 sign that is encountered in each direction as traffic approaches the reduced school speed limit zone (see Figures 7B-3 and 7B-5).

Where increased fines are imposed for traffic violations within a reduced school speed limit zone, a FINES HIGHER (R2-6P), FINES DOUBLE (R2-6aP), or \$XX FINE (R2-6bP) plaque (see Figure 2B-3) shall be installed as a supplement to the reduced school speed limit sign to notify road users. Changed to Guidance and relocated below

Except as provided in Paragraph 5, the downstream end of an authorized and posted reduced school speed limit zone shall be identified with an END SCHOOL SPEED LIMIT (S5-3) sign (see Figures 7B-1, 7B-3, and 7B-5).

Option:

If a reduced school speed limit zone ends at the same point as a higher fines zone, an END SCHOOL ZONE (S5-2) sign may be used instead of a combination of an END HIGHER FINES ZONE (R2-11) sign and an END SCHOOL SPEED LIMIT (S5-3) sign.

A standard Speed Limit sign showing the speed limit for the section of highway that is downstream from the authorized and posted reduced school speed limit zone may be mounted on the same post above the END SCHOOL SPEED LIMIT (S5-3) sign or the END SCHOOL ZONE (S5-2) sign.

Guidance:

The beginning point of a reduced school speed limit zone should be at least 200 feet in advance of the school grounds; or a school crossing, or other school related activities; however, this 200-foot distance should be increased if the reduced school speed limit is 30 mph or higher. The maximum beginning point of a reduced school speed limit zone should not be greater than 500 feet.

Where increased fines are imposed for traffic violations within a reduced school speed limit zone, a FINES HIGHER (R2-6P), FINES DOUBLE (R2-6aP), or \$XX FINE (R2-6bP) plaque (see <u>Figure 2B-37B-3 and 7B-5</u>) <u>shall should</u> be installed as a supplement to the reduced school speed limit sign to notify road users. Relocated from above and changed to Guidance

If other traffic violations in addition to exceeding the speed limit are subject to higher fines, then the duplicate FINES HIGHER (R2-6P), FINES DOUBLE (R2-6aP), or \$XX FINE (R2-6bP) plaque should be omitted (see Section 7B.02). Added per Official Interpretation 7(09)-3 (I)

Standard:

The School Speed Limit assembly shall be either a fixed-message sign assembly or a changeable message sign.

The fixed-message School Speed Limit assembly shall consist of a top plaque (S4-3P) with the legend SCHOOL, a Speed Limit (R2-1) sign, and a bottom plaque (S4-1P, S4-2P, S4-4P, or S4-6P) indicating the specific periods of the day and/or days of the week that the special school speed limit is in effect (see Figure 7B-1).

Option:

Changeable message signs (see Chapter 2L and Section 6F.606L.05) may be used to inform drivers of the school speed limit. If the sign is internally illuminated, it may have a white legend on a black background. Changeable message signs with flashing beacons may be used for situations where greater emphasis of the special school speed limit is needed.

Guidance:

Even though it might not always be practical because of special features to make changeable message signs conform in all respects to the standards in this Manual for fixed-message signs, during the periods that the school speed limit is in effect, their basic shape, message, legend layout, and colors should comply with the standards for fixed-message signs.

A confirmation light or device to indicate that the speed limit message is in operation should be considered for inclusion on the back of the changeable message sign.

Standard:

Fluorescent yellow-green pixels shall be used when the "SCHOOL" message is displayed on a changeable message sign for a school speed limit.

Option:

Changeable message signs may use blank-out messages or other methods in order to display the school speed limit only during the periods it applies.

A Vehicle Speed Feedback plaque (W13-20aP) Changeable message signs that displays the speed of approaching drivers (see Section 2B.243 and 2C.13) may be used in a school speed limit zone.

A Speed Limit Sign Beacon (see Section 4<u>L</u>4<u>S</u>.04) also may be used, with a WHEN FLASHING legend, to identify the periods that the school speed limit is in effect.

Section 7B.16 Reduced School Speed Limit Ahead Sign (S4-5, S4-5a) Section titled deleted; text combined with new Section 7B.06

Guidance:

A Reduced School Speed Limit Ahead (S4-5, S4-5a) sign (see Figure 7B-1) should be used to inform road users of a reduced speed zone where the speed limit is being reduced by more than 10 mph, or where engineering judgment indicates that advance notice would be appropriate.

Standard:

1 2	If used, the Reduced School Speed Limit Ahead sign shall be followed by a School Speed Limit sign or a School Speed Limit assembly.
3	The speed limit displayed on the Reduced School Speed Limit Ahead sign shall be identical to the
4	speed limit displayed on the subsequent School Speed Limit sign or School Speed Limit assembly.
5	Section 7B.1707 Parking and Stopping Signs (R7 and R8 Series)
6	Option:
7 8 9	Parking and stopping regulatory signs may be used to prevent parked or waiting vehicles from blocking pedestrians' views, and drivers' views of pedestrians, and to control vehicles as a part of the school traffic plan.
10	Support:
11 12	Parking signs and other signs governing the stopping and standing of vehicles in school areas cover a wide variety of regulations. Typical examples of regulations are as follows:
13 14 15 16 17	 A. No Parking NO PARKING X:XX AM to X:XX PM School Days Only, SCHOOL DAYS ONLY B. No Stopping NO STOPPING X:XX AM to X:XX PM SCHOOL DAYS ONLY School Days Only, C. XX Min Loading XX MIN LOADING X:XX AM to X:XX PM SCHOOL DAYS ONLY School Days Only, and D. No Standing NO STANDING X:XX AM to X:XX PM SCHOOL DAYS ONLY School Days Only.
18 19	Sections 2B.4654, 2B.4755, and 2B.48-56 contain information regarding the signing of parking regulations in school zone areas.
20	Figure 7B-2. Example of Signing for a Higher Fines School Zone without a School Crossing
21 22	Figure 7B-3. Example of Signing for a Higher Fines School Zone with a School Speed Limit
23	Figure 7B-4. Example of Signing for a School Zone Crossing Outside of a School Zone
24	Figure 7B-5. Example of Signing for a School Zone with a School Speed Limit and a School
25	Crossing
26	Figure 7B-6. Pedestrian Crossing In-Street Signs in School Areas

1	CHAPTER 7C. MARKINGS
2	Section 7C.01 Functions and Limitations Not needed, redundant with Section 3A.01
3	Section 7C.02 Section 7C.01 Crosswalk Markings
4	Guidance:
5 6 7 8	Crosswalks should be marked at all intersections on established routes to a school where there is substantial conflict between motorists, bicyclists, and student movements; where students are encouraged to cross between intersections; where students would not otherwise recognize the proper place to cross; or where motorists or bicyclists might not expect students to cross (see Figure 7A-1).
9 10 11	Crosswalk lines should not be used indiscriminately. An engineering study considering the factors described in Section 3B.183C.02 should be performed before a marked crosswalk is installed at a location away from a traffic control signal or an approach controlled by a STOP or YIELD sign.
12 13 14 15	Because non-intersection school crossings are generally unexpected by the road user, warning signs (see Sections 7B.11-03 and 7B.12) should be installed for all marked school crosswalks at non-intersection locations. Adequate visibility of students by approaching motorists and of approaching motorists by students should be provided by parking prohibitions or other appropriate measures.
16 17 18 19 20	Support: Section <u>3B.183C.03</u> contains provisions regarding the placement and design of crosswalks, and Section 3B. <u>16-19</u> contains provisions regarding the placement and design of the stop lines and yield lines that are associated with them. Provisions regarding the curb markings that can be used to establish parking regulations on the approaches to crosswalks are contained in Section 3B. <u>1823</u> .
21	Section 7C.03Section 7C.02 Pavement Word, Symbol, and Arrow Markings
22	Option:
23	If used, the SCHOOL word marking may extend to the width of two approach lanes (see Figure 7C-1).
24	Guidance:
25	If the two-lane SCHOOL word marking is used, the letters should be 10 feet or more in height.

26 Support:

Section 3B.20 contains provisions regarding other word, symbol, and arrow pavement markings that can be used to guide, warn, or regulate traffic.

Figure 7C-1. Two-Lane Pavement Marking of "SCHOOL"

29 30

27

7

8

9

10 11

12

13 14

16

17

18

19

20

21

22

23

24

28

29

33

34

35 36

37

38

39

40

41

42

43 44

45

46 47

- 2 Section 7D.01 Types of Crossing Supervision Section deleted, not needed
- Section 7D.02 Adult Crossing Guards Relocated to new Section 7D.01 3
- Section 7D.03 7D.01 Qualifications of Adult Crossing Guards 4
- 5 Option:

Adult crossing guards may be used to provide gaps in traffic at school crossings where an engineering study has shown that adequate gaps need to be created (see Section 7A.03), and where authorized by law.

Relocated from existing Section 7D.02

A recommended method for determining the frequency and adequacy of gaps in the traffic stream is given in the "Traffic Control Devices Handbook" (see Section 1A.4405). Relocated from existing Section 7A.03 Support:

High standards for selection of adult crossing guards are essential because they are responsible for the safety of and the efficient crossing of the street by schoolchildren within and in the immediate vicinity of school crosswalks.

15 Guidance:

Adult crossing guards should possess the following minimum qualifications:

- A. Average intelligence;
 - B. Good physical condition, including sight, hearing, and ability to move and maneuver quickly in order to avoid danger from errant vehicles;
 - C. Ability to control a STOP paddle effectively to provide approaching road users with a clear, fully direct view of the paddle's STOP message during the entire crossing movement;
 - D. Ability to communicate specific instructions clearly, firmly, and courteously;
 - E. Ability to recognize potentially dangerous traffic situations and warn and manage students in sufficient time to avoid injury.
- 25 F. Mental alertness;
- 26 G. Neat appearance;
- 27 H. Good character;
 - I. Dependability; and
 - *J.* An overall sense of responsibility for the safety of students.
- Section 7D.04 Uniform of Adult Crossing Guards Relocated to new Section 7D.02 30
- 31 Section 7D.05 7D.02 Operating Procedures for Adult Crossing Guards
- 32 **Standard:**

Law enforcement officers performing school crossing supervision and adult crossing guards shall wear high-visibility retroreflective safety apparel labeled as ANSI 107-2004 standard performance for Class 2 as described in Section 6E.026C.05. Relocated from existing Section 7D.04

Adult crossing guards shall not direct traffic in the usual law enforcement regulatory sense. In the control of traffic, they shall pick opportune times to create a sufficient gap in the traffic flow. At these times, they shall stand in the roadway to indicate that pedestrians are about to use or are using the crosswalk, and that all vehicular traffic must stop.

Adult crossing guards shall use a STOP paddle. The STOP paddle shall be the primary handsignaling device.

The STOP paddle shall comply with the provisions for a STOP/SLOW paddle (see Section 6D.02) except both sides shall be a STOP face. Added a reference to Section 6D.02

The STOP (R1-1) paddle shall be an octagonal shape. The background of the STOP face shall be red with at least 6-inch series upper-case white letters and border. The paddle shall be at least 18inches in size and have the word message STOP on both sides. Removed redundant text The paddle shall be retroreflectorized retroreflective or illuminated when used during hours of darkness.

Notice of Proposed Amendments – Part 7

1	Option: Removed – redundant with Section 6D.02 (existing Section 6E.03)
2	The STOP paddle may be modified to improve conspicuity by incorporating white or red flashing lights
3	on both sides of the paddle. Among the types of flashing lights that may be used are individual LEDs or
4	groups of LEDs.
5	The white or red flashing lights or LEDs may be arranged in any of the following patterns:
6	A. Two white or red lights centered vertically above and below the STOP legend,
7	B. Two white or red lights centered horizontally on each side of the STOP legend,
8	C. One white or red light centered below the STOP legend,
9	D. A series of eight or more small white or red lights having a diameter of 1/4 inch or less along the outer
10	edge of the paddle, arranged in an octagonal pattern at the eight corners of the STOP paddle (more-
11	than eight lights may be used only if the arrangement of the lights is such that it clearly conveys the
12	octagonal shape of the STOP paddle), or
13	E. A series of white lights forming the shapes of the letters in the legend.
14	Standard: Removed – redundant with Section 6D.02 (existing Section 6E.03)

If flashing lights are used on the STOP paddle, the flash rate shall be at least 50, but no more than 60, flash periods per minute.

15

Section 8A.01 <u>Introduction</u> Paragraphs 8 through 12 have been relocated to a new Section 8A.02

Support:

Whenever the acronym "LRT" is used in Part 8, it refers to "light rail transit."

Part 8-Chapters 8A, 8B, 8C, and 8D describes the traffic control devices that are used at highway-rail and highway-LRT grade crossings. Unless otherwise provided in the text or on a figure or table, the provisions of Part 8 are applicable to both highway-rail and highway-LRT grade crossings. When the phrase "grade crossing" is used by itself without the prefix "highway-rail" or "highway-LRT," it refers to both highway-rail and highway-LRT grade crossings.

Chapter 8E describes the traffic control devices that are used at pathway and sidewalk grade crossings.

Traffic control for grade crossings includes all signs, signals, markings, other warning devices, and their supports along highways approaching and at grade crossings. The function of this traffic control is to promote safety and provide effective operation of rail and/or LRT and highway traffic at grade crossings.

For purposes of design, installation, operation, and maintenance of traffic control devices at grade crossings, it is recognized that the crossing of the highway and rail tracks is situated on a right-of-way available for the joint use of both highway traffic and railroad or LRT traffic.

Grade crossings and the traffic control devices that are associated with them are unique in that in many cases, both the highway agency or authority with jurisdiction, and the regulatory agency with statutory authority (if applicable), and the railroad company or transit agency are jointly determine the need and selection of devices at a grade crossing involved in the development of engineering judgment or the performance of an engineering study. This joint process is accomplished through the efforts of a Diagnostic Team. Edited to improve consistency

In Part 8, the combination of <u>traffic control</u> devices selected or installed at a specific grade crossing is referred to as a "traffic control system."

The combination of railroad or LRT active traffic control devices used to inform road users at a grade crossing of the approach or presence of rail traffic and the necessary control equipment for the devices are referred to as a "grade crossing warning system." Part 1.1.1 of the "AREMA Communications & Signals Manual" (see Section 1A.05) published by the American Railway Engineering & Maintenance-of-Way Association (AREMA) contains further information about grade crossing warning systems. Added to improve accuracy

Standard:

Except at private grade crossings of privately-owned roadways (see Defintion 159 in Section 1A.13), the traffic control devices, systems, and practices described in this Manual shall be used at all grade crossings open to public travel, consistent with Federal, State, and local laws and regulations. Edited for consistency with changes to Part 1 and deletion of Part 5

Support: This text was relocated to new Section 8A.02

- Part 8 also describes the traffic control devices that are used in locations where light rail LRT vehicles are operating along streets and highways in mixed traffic with automotive vehicles.
- LRT is a mode of metropolitan transportation that employs LRT vehicles (commonly known as light rail vehicles, streetears, or trolleys) that operate on rails in streets in mixed traffic, and LRT traffic that operates in semi-exclusive rights of way, or in exclusive rights of way. Grade erossings with LRT can occur at intersections or at midblock locations, including public and private driveways.
- An initial educational campaign along with an ongoing program to continue to educate new drivers is beneficial when introducing LRT operations to an area and, hence, new traffic control devices.
- 48 LRT alignments can be grouped into one of the following three types:
 - A. Exclusive: An LRT right-of-way that is grade-separated or protected by a fence or traffic-barrier. Motor vehicles, pedestrians, and bieyeles are prohibited within the right-of-way.

- Subways and aerial structures are included within this group. This type of alignment does not have grade crossings and is not further addressed in Part 8.
 - B. Semi-exclusive: An LRT alignment that is in a separate right-of-way or along a street or railroad right of way where motor vehicles, pedestrians, and bicycles have limited access and cross at designated locations only.
 - C. Mixed-use: An alignment where LRT operates in mixed traffic with all types of road users.

 This includes streets, transit malls, and pedestrian malls where the right of way is shared.

Standard:

 Where LRT and railroads use the same tracks or adjacent tracks, the traffic control devices, systems, and practices for highway-rail grade crossings shall be used.

Support:

To promote an understanding of common terminology between highway and railroad and LRT signaling issues, definitions and aeronyms pertaining to Part 8 are provided in Sections 1A.13 and 1A.14.

Section 8A.02 Highway-LRT Grade Crossings This section is comprised primarily of Paragraphs 8 through 12 of existing Section 8A.01 and edited to improve consistency

Support:

Part 8 also describes the traffic control devices that are used in locations where light rail <u>transit (LRT)</u> vehicles are operating along streets and highways in mixed traffic with automotive vehicles all types of road users.

LRT is a mode of metropolitan public transportation that employs LRT vehicles (commonly known as light rail vehicles, streetcars, or trolleys) that operate on rails in streets in mixed traffic, and LRT traffic that operates in semi-exclusive rights-of-way, or in exclusive rights-of-way. Grade crossings with LRT can occur at intersections or at midblock locations, including public and private driveways.

An initial educational campaign along with an ongoing program to continue to educate new drivers is beneficial when introducing LRT operations to an area and, hence, new traffic control devices.

LRT alignments can be grouped into one of the following three types (see definitions in Section A.131C.02):

- A. Exclusive: An LRT right-of-way that is grade-separated or protected by a fence or traffic barrier. Motor vehicles, pedestrians, and bicycles are prohibited within the right-of-way. Subways and aerial structures are included within this group. This type of alignment does not have grade crossings and is not further addressed in Part 8.
- B. Semi-exclusive: An LRT alignment that is in a separate right-of-way or along a street or railroad right-of-way where motor vehicles, pedestrians, and bicycles have limited access and cross at designated locations only, such as at grade crossings where road users must yield the right-of-way to the light rail transit or the bus rapid transit traffic.
- C. Mixed-use: An alignment where LRT operates in mixed traffic with all types of road users. This includes streets, transit malls, and pedestrian malls where the right of way is shared. In a mixed-use alignment, the light rail transit traffic does not have the right-or-way over other road users at grade crossings and intersections. If the LRT traffic is controlled by traffic control signals or LRT signal faces at an intersection with a roadway, the alignment is considered to be mixed-use even if some of the approaches to the intersection are used exclusively by LRT traffic.

Guidance:

If When a highway-LRT grade crossing is equipped with a flashing-light signal system and is located within 200 feet of an intersection or midblock location controlled by a traffic control signal, a pedestrian hybrid beacon, or an emergency-vehicle hybrid beacon, the highway traffic control signal should be provided with preemption in accordance with Section 4D.274F.19 and 8D.10 unless otherwise determined by a Diagnostic Team. Text relocated from existing section 8C.10 and edited to improve accuracy Option:

Where LRT vehicles are operating in a mixed-use alignment, traffic signal priority or preemption may be used as determined by a Diagnostic Team. Added to improve consistency

Standard:

Where LRT and railroads use the same tracks or adjacent tracks, the traffic control devices, systems, and practices for highway-rail grade crossings shall be used.

Section 8A.02 8A.03 Use of Standard Devices, Systems, and Practices at Highway Rail Grade Crossings

Support:

Because of the large number of significant variables to be considered, no single standard system of traffic control devices is universally applicable for all highway-rail-grade crossings.

Guidance:

The appropriate traffic control system to be used at a highway LRT grade crossing should be determined by an engineering study conducted by the LRT or highway agency in cooperation with other appropriate State and local organizations.

Option:

The engineering study may include the Highway-Rail Intersection (HRI) components of the National-Intelligent Transportation Systems (ITS) architecture, which is a USDOT accepted method for linking the highway, vehicles, and traffic management systems with rail operations and wayside equipment.

19 Support:

More detail on Highway Rail Intersection components is available from the USDOT's Federal Railroad-Administration, 1200 New Jersey Avenue, SE, Washington, DC 20590, or www.fra.dot.gov.-paragraphs-2-4 relocated to new Section 8A.05

Standard:

Traffic control devices, systems, and practices shall be consistent with the design and application of the Standards contained in this Manual-Deleted; redundant with new Section 1B

Before any new highway-rail grade crossing traffic control system is installed or before modifications are made to an existing system, approval shall be obtained from the highway agency with the jurisdictional and/or the regulatory agency with statutory authority(if applicable), and from the railroad company and/or transit agency.

The Diagnostic Team members shall reach a determination, documented in an engineering study (see Section 8A.05), on new grade crossing traffic control systems and on proposed changes to an existing grade crossing traffic control system. The Diagnostic Team determination shall be made after the Diagnostic Team members reach a consensus during site visits, meetings, conference calls, or a combination of some or all of these methods. Added to improve consistency

Except as provided in Paragraph 5, operational changes made to a grade crossing traffic control system requiring the use of engineering judgment or an engineering study shall be conducted and approved by a Diagnostic Team. Among the types of changes at a grade crossing for which a Diagnostic Team shall conduct an engineering study are additions to or modifications of the lanes approaching or traversing the grade crossing; additions or modifications to sidewalks; additions or modifications to bicycle lanes, especially if a counter-flow bike lane is added on a one-way street; changes to roadway use, including conversion to or from one-way operation or reversible lanes; implementation of quiet zones; and the installation of or significant operational changes to traffic control signals that might affect the grade crossing. Added to improve consistency

Option:

When determined by the responsible public agency, the railroad company, and/or the transit agency, general maintenance activities or minor operational changes to the grade crossing traffic control system that do not have a negative impact on the overall operation of the traffic control system may be made without a review and determination by a Diagnostic Team. Added to improve consistency

49 Support:

Many other details of highway-rail-grade crossing traffic control systems that are not set forth in Part 8 are contained in the publications listed in Section 1A.1105, including the "2000-latest version of the "AREMA Communications & Signals Manual" published by the American Railway Engineering & Maintenance-of-Way Association (AREMA) and the 2006-edition-latest version of "Preemption of Traffic Signals Near

Railroad Crossings" published by the Institute of Transportation Engineers (ITE).

Section 8A.03 8A.04 Use of Standard Devices, Systems, and Practices at Highway-LRT Grade Crossings

Support:

The combination of devices selected or installed at a specific highway-LRT grade crossing is referred to as a "Light Rail Transit Traffic Control System."

Because of the large number of significant variables to be considered, no single standard system of traffic control devices is universally applicable for all highway LRT grade crossings. Deleted; redundant with new Section 8A.03

For the safety and integrity of operations by highway and LRT users, the highway agency with jurisdiction, the regulatory agency with statutory authority, if applicable, and the LRT authority jointly determine the need and selection of traffic control devices and the assignment of priority to LRT at a highway LRT grade crossing. Deleted; redundant with new Standard in new Section 8A.03

The normal rules of the road and traffic control priority identified in the "Uniform Vehicle Code" and its successor documents govern the order assigned to the movement of vehicles at an intersection unless the local agency determines that it is appropriate to assign a higher priority to LRT vehicles. Examples of different types of LRT priority control include separate traffic control signal phases for LRT movements, restriction of movement of roadway vehicles in favor of LRT operations, and preemption of highway traffic signal control to accommodate LRT movements.

Guidance: This text has been relocated to new Section 8A.05

The appropriate traffic control system to be used at a highway LRT grade crossing should be determined by an engineering study conducted by the LRT or highway agency in cooperation with other appropriate State and local organizations.

Standard:

Traffic control devices, systems, and practices shall be consistent with the design and application of the Standards contained in this Manual. Deleted; redundant with new Section 1B

The traffic control devices, systems, and practices described in this Manual shall be used at all highway-LRT grade crossings. Deleted; redundant with new Section 1B

Before any new highway-LRT grade crossing traffic control system is installed or before modifications are made to an existing system, approval shall be obtained from the highway agency with the jurisdictional and/or statutory authority, and from the LRT agency. Deleted; redundant with new Standard in new Section 8A.03

Guidance:

To stimulate effective responses from road users, these devices, systems, and practices should use the five-basic considerations employed generally for traffic control devices and described fully in Section 1A.02: design, placement, operation, maintenance, and uniformity. Deleted; redundant with new Section 1D.01 Support:

Many other details of highway LRT grade crossing traffic control systems that are not set forth in Part 8 are contained in the publications listed in Section 1A.11. Deleted; redundant with new Section 8A.03

Standard:

Highway-LRT grade crossings in semi-exclusive alignments <u>outside of a roadway</u> shall be equipped with <u>a combination of automatic gates and</u> flashing-light signals, <u>with</u> or <u>flashing light signals</u> <u>onlywithout automatic gates</u>, <u>or traffic control signals</u>, unless <u>an engineering study a Diagnostic Team</u> <u>indicates determines</u> that the use of Crossbuck Assemblies, STOP signs, or YIELD signs alone would be adequate. <u>Edited to improve accuracy and consistency</u>

Option:

Highway-LRT grade crossings in mixed-use alignments may be equipped with traffic control signals unless an engineering study indicates that the use of Crossbuck Assemblies, STOP signs, or YIELD signs alone would be adequate. Deleted; redundant with new Section 8A.05

4 Support:

Sections 8B.03 and 8B.04 contain provisions regarding the use and placement of Crossbuck signs and Crossbuck Assemblies. Section 8B.05 describes the appropriate conditions for the use of STOP or YIELD signs alone at a highway LRT grade crossing. Sections 8C.10 and 8C.11 contain provisions regarding the use of traffic control signals at highway LRT grade crossings. Deleted; redundant with other Part 8 sections

Section 8A.04 Uniform Provisions This section has been relocated to new Section 8A.06

Section 8A.05 Engineering Studies at Grade Crossings This section is comprised of Paragraphs 2 through 4 of existing Section 8A.02 and Paragraph 5 of existing Section 8A.03, and edited to improve consistency

Guidance Standard: Guidance changed to Standard

The appropriate traffic control system to be used at a highway rail grade crossing should shall be determined by an engineering study conducted by a Diagnostic Team involving both the highway agency with jurisdiction, the regulatory agency with statutory authority (if applicable), and the railroad company and/or transit agency (as applicable).

Guidance: Added to improve consistency

Among the factors that should be considered in the determination by a Diagnostic Team of which traffic control devices would be appropriate to install at a grade crossing are road geometrics, stopping sight distance, clearing sight distance, the proximity of nearby roadway intersections (including the traffic control devices at the intersections), adjacent driveways, traffic volume across the grade crossing, extent of queuing upstream or downstream from the grade crossing, train volume, pedestrian volume, operation of passenger trains, presence of nearby passenger station stops, variable train speeds, accelerating and decelerating trains, multiple tracks, high-speed train operation, number of school buses or hazardous material haul vehicles, and the crash history at or near the location.

Option:

The engineering study may include the Highway-Rail Intersection (HRI) components of the National Intelligent Transportation Systems (ITS) architecture, which is a USDOT accepted method for linking the highway, vehicles, and traffic management systems with rail operations and wayside equipment.

Support:

More detail on Highway-Rail Intersection components is available from the USDOT's Federal Railroad Administration, 1200 New Jersey Avenue, SE, Washington, DC 20590, or www.fra.dot.gov.

Section 8A.04 8A.06 Uniform Provisions This section has been relocated from existing section 8A.04

Standard:

All signs used in grade crossing traffic control systems shall be retroreflectorized retroreflective or illuminated as described in Section 2A.0720 to show the same shape and similar color to an approaching road user during both day and night.

No sign or signal shall be located in the center of an undivided highway, unless it is crashworthy (breakaway, yielding, or shielded with a longitudinal barrier or crash cushion) or unless it is placed on a raised island.

Guidance:

Any signs or signals placed on a raised island in the center of an undivided highway should be installed with a clearance of at least 2 feet from the outer edge of the raised island to the nearest edge of the sign or signal, except as permitted in Section 2A.195.

Where the distance between tracks, measured along the highway between the inside rails, exceeds 100 feet, additional signs or other appropriate traffic control devices should be used to inform approaching road users of the long distance to cross the tracks.

Where a raised median island is installed supplemental to an automatic gate to discourage road users from driving around a lowered gate, the Diagnostic Team should consider the length of the vehicle queues that typically form on the approach to the grade crossing when determining how far in advance of the grade crossing to extend the island.

If the roadway at a grade crossing includes a two-way left-turn lane (see Section 3B.05), the two-way left-turn lane should be discontinued in the immediate vicinity of the grade crossing by installing median islands, by designating the lane for left turns in one direction only, or by installing yellow diagonal markings in the lane (see Figure 3B-5). If yellow diagonal markings are used, the use of channelizing devices (see Section 3I.01), such as supplemental tubular markers, should also be considered. Added to improve consistency

Section 8A.07 Minimum Track Clearance Distance New section added to improve accuracy and consistency

12 Support:

- The upstream point of the minimum track clearance distance is determined in the following manner:
 - A. If an automatic gate is present on the approach, the upstream point is the portion of the automatic gate arm that is farthest from the nearest rail.
 - B. If an automatic gate is not present on the approach, the upstream point is the portion of the stop line that is farthest from the nearest rail.
 - C. If the roadway is not paved, the upstream point is the point that is farthest from the nearest rail that is 10 feet measured perpendicular from the nearest rail.

The downstream point of the minimum track clearance distance is 6 feet beyond the track(s) measured perpendicular to the farthest rail, along the center line or edge line of the highway, as appropriate, to obtain the longer distance. Where an Exit Gate system (see Section 8D.05) is present, the downstream point is the point where the rear of the vehicle would be clear of the exit gate arm. In cases where the exit gate arm is not perpendicular to the highway, the distance is measured either along the center line or edge line of the highway, as appropriate, to obtain the longer distance.

Where two adjacent grade crossings are located within 200 feet of each other as measured along the highway, the minimum track clearance distance is measured from a point that is upstream of the first grade crossing to a point that is downstream from the second grade crossing.

Where a highway-highway intersection is located beyond a grade crossing, the clear storage distance defines on a lane-by-lane basis the area of the roadway between the downstream point of the minimum track clearance distance and the intersection stop line, yield line, or normal stopping point on the highway.

The minimum track clearance distance and the clear storage distance are used by the Diagnostic Team to determine the appropriate traffic control devices and/or roadway treatments to be used at the grade crossing, and to determine the queue start-up and queue clearance time necessary where a traffic signal or hybrid beacon is interconnected with a grade crossing active warning system.

Section 8A.08 Adjacent Grade Crossings New section added to improve consistency

Support:

Adjacent grade crossings sometimes exist within 200 feet of each other as measured along the highway. These closely-spaced grade crossings sometimes result from separate railroads or from a railroad and an LRT alignment operating in parallel corridors.

Guidance:

Where adjacent grade crossings are located within 200 feet of each other along the highway, the Diagnostic Team should consider the possibility that rail traffic might arrive at a grade crossing when rail traffic is already occupying the adjacent grade crossing.

Where the distance between the tracks at adjacent grade crossings, measured along the highway between the inside rails, is 100 feet or less, the grade crossings should be treated as one individual grade crossing.

Where the distance between the tracks at adjacent grade crossings, measured along the highway between the inside rails, is more than 100 feet, additional signs or other appropriate traffic control devices should be used to inform approaching road users of the long distance to cross the tracks.

Where active traffic control devices are installed between adjacent grade crossings that are less than 200 feet apart, the operation of the devices should provide additional time for vehicles to clear the extended minimum track clearance distance (see Section 8A.07) that results from the closely-spaced grade crossings.

Where the distance between the tracks at adjacent grade crossings, measured along the highway between the inside rails, is more than 200 feet, the grade crossings should be treated as individual grade crossings and traffic control devices should be installed between the grade crossings.

Support:

Part 3.1.11 of the "AREMA Communications & Signals Manual" (see Section 1A.05) published by the American Railway Engineering & Maintenance-of-Way Association (AREMA) contains further information and recommendations about the location and operation active traffic control devices at adjacent grade crossings that are located within 200 feet of each other.

Section 8A.05 8A.09 Grade Crossing Elimination

Option:

If a particular grade crossing appears to be redundant or unnecessary, an engineering study may be conducted to determine the costs and benefits of eliminating the crossing. Added to improve consistency *Guidance*:

If an engineering study is conducted, the costs associated with any necessary improvements to adjacent grade crossings and the surrounding roadway network to accommodate diverted traffic should also be included in the analysis. Added to improve consistency

If the conclusion of the engineering study is that the grade crossing should be eliminated, a Diagnostic Team should use the engineering study to determine the appropriate steps that need to be taken to accomplish the grade crossing elimination. Added to improve consistency

Because grade crossings are a potential source of crashes and congestion, agencies should conduct engineering studies to determine the cost and benefits of eliminating these crossings. Deleted; redundant with new guidance statements above

Standard: Standards changed to Guidance

When a grade crossing is eliminated, the traffic control devices for the crossing shall should be removed.

If the existing traffic control devices at a multiple-track grade crossing become improperly placed or inaccurate are no longer applicable because of the removal of some of the tracks, the existing devices shall be relocated and/or modified.

Guidance:

Any grade crossing that cannot be justified should be eliminated. Deleted; redundant with new guidance statements above

Where a roadway is removed from a grade crossing, the roadway approaches in the railroad or LRT right-of-way should also be removed and appropriate signs and object markers should be placed at the roadway end in accordance with Section 2C.6671.

Where a railroad or LRT is eliminated at a grade crossing, the tracks should be removed or covered. Option:

Based on engineering judgment, the TRACKS OUT OF SERVICE (R8-9) sign (see Figure 8B-1) may be temporarily installed until the tracks are removed or covered. The length of time before the tracks will be removed or covered may be considered in making the decision as to whether to install the sign.

Section 8A.06 8A.10 Illumination at Grade Crossings

Support:

Illumination is sometimes installed at or adjacent to a grade crossing in order to provide better nighttime visibility of trains or LRT equipment and the grade crossing (for example, where a substantial amount of railroad or LRT operations are conducted at night, where grade crossings are blocked for extended periods of time, or where crash history indicates that road users experience difficulty in seeing trains or LRT equipment or traffic control devices during hours of darkness).

Recommended types and locations of luminaires for illuminating grade crossings are contained in the American National Standards Institute's (ANSI) "Practice for Roadway Lighting RP-8," which is available from the Illuminating Engineering Society (see Section 1A.0511).

Section 8A.07-8A.11 Quiet Zone Treatments at Highway-Rail Grade Crossings

5 Support:

4

6

7

8

9

10

11 12

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

30

31

34

35 36

37

38

39 40

41 42

43

45

46 47 49 CFR Part 222 (Use of Locomotive Horns at Highway-Rail Grade Crossings; Final Rule) prescribes Quiet Zone requirements and treatments.

Standard:

Any traffic control device and its application where used as part of a Quiet Zone shall comply with all applicable provisions of the MUTCD.

Section 8C.12 8A.12 Grade Crossings Within or In Close Proximity to Circular Intersections This section was relocated from existing section 8C.12

13 Support:

At circular intersections, such as roundabouts and traffic circles, that include or are within close proximity to a grade crossing, a queue of vehicular traffic could cause highway vehicles to stop on the grade crossing.

Standard Changed to Guidance

Where circular intersections include or are within 200 feet of a grade crossing, an engineering study shall should be made to determine if queuing could impact the grade crossing. If traffic queues impact the grade crossing, provisions shall should be made to clear highway traffic from the grade crossing prior to the arrival of rail traffic.

Support:

Among the actions that can be taken to keep the grade crossing clear of traffic or to clear traffic from the grade crossing prior to the arrival of rail traffic are the following:

- A. Elimination of the circular intersection.
- B. Geometric design revisions,
- A. Grade crossing regulatory and warning devices,
- B. Highway traffic signals,
- C. Traffic metering devices,
- D. Activated signs,
 - E. Geometric design revisions, including reconstruction or elimination of the circular intersection, or
 - F. A combination of these or other actions. Edited to improve clarity

32 Section 8A.13 Busway Grade Crossings New section added to improve consistency

33 <u>Support:</u>

A busway can be operated either as an exclusive or as a semi-exclusive alignment. An exclusive alignment does not have grade crossings and is not further addressed in Part 8.

Because the design and operation of a busway in a semi-exclusive alignment is similar to light-rail transit in a semi-exclusive alignment, all of the provisions in Part 8 that pertain to the traffic control devices used at LRT grade crossings in semi-exclusive alignments also pertain to the traffic control devices used at busway grade crossings in semi-exclusive alignments unless otherwise specified in this Manual. The primary difference between a busway and an LRT system is that a busway is used by transit vehicles with rubber tires on pavement and an LRT system is used by transit vehicles with steel wheels that operate on rails.

Busway grade crossings can occur at intersections or at midblock locations, including public and private driveways.

44 *Guidance*:

<u>Highway-busway grade crossings should be equipped with an active busway grade crossing warning system unless an engineering study indicates that the use of STOP signs or YIELD signs alone would be adequate.</u>

48 **Standard:**

Where a busway grade crossing and a railroad or LRT grade crossing are adjacent to one another such that the active railroad or LRT grade crossing warning system and the active busway grade crossing warning system share common grade crossing traffic control devices, the warning system for the railroad or LRT grade crossing shall control the operation of all grade crossing traffic control devices, and the warning system for the busway shall be interconnected with the active railroad or LRT grade crossing warning system to provide notification of an approaching bus to the active grade crossing warning system.

Option:

Automatic gates may be used at highway-busway grade crossings.

DO NOT BLOCK INTERSECTION (R10-7) signs (see Section 2B.63) may be installed at highway-busway grade crossings.

Standard:

Busway automatic gates, if used, shall comply with the provisions set forth in Section 8D.03 for automatic gates and shall be standard railroad size, striped with 16-inch alternate vertical, fully retroreflective red and white stripes. Flashing red lights shall be included on the gate arm and they shall only be operated if the gate is closed or in the process of being opened or closed. In the horizontal position, the top of the gate shall be approximately 4 feet above the payement.

Busway automatic entrance gates shall be designed to fail-safe in the down position unless other provisions, such as activated blank-out signs or LRT Signals, are used to ensure the bus operator is alerted to slow down and proceed with caution when gates are malfunctioning.

Four-Quadrant Busway automatic gates shall comply with the provisions set forth in Section 8D.05.

If an active busway grade crossing warning system is used at a pathway-busway or sidewalk-busway grade crossing, a bell or other audible warning device shall be provided for each pathway or sidewalk approach to the crossing.

BUSWAY CROSSING (W10-21) signs with SIGNAL AHEAD (W10-21aP) supplemental plaques shall be used in advance of busway crossings.

On paved roadways, pavement markings in advance of a busway grade crossing shall consist of a word message BUS XING and a no-passing zone marking (on two-lane, two-way highways with center line markings in compliance with Section 3B.01). The symbol X and the transverse lines used in advance of a railroad or LRT grade crossing shall not be used for a busway grade crossing.

Section 8A.08 8A.14 Temporary Traffic Control Zones

Support:

Temporary traffic control planning provides for continuity of operations (such as movement of traffic, pedestrians and bicycles, transit operations, and access to property/utilities) when the normal function of a roadway at a grade crossing is suspended because of temporary traffic control operations. Temporary traffic control planning is also needed when traffic is detoured over an existing passive grade crossing.

Standard:

Traffic controls for temporary traffic control zones that include grade crossings shall be as outlined provided in Part 6.

Guidance: Standard changed to Guidance

When a grade crossing exists either within or in the vicinity of a temporary traffic control zone, lane restrictions, flagging (see Chapter 6D), or other operations shall should not be performed in a manner that would cause highway vehicles to stop on the railroad or LRT tracks, unless a flagger or uniformed law enforcement officer is provided at the grade crossing to minimize the possibility of highway vehicles stopping on the tracks, even if automatic warning devices are in place.

When a temporary traffic control zone extends over a grade crossing equipped with automatic gates and either one-lane two-way or reversible lane operation is used, any improperly located gate arms that might cause vehicles to stop within the minimum track clearance distance (see Section 8A.07) should be removed. At locations where a gate arm is removed, a railroad company or transit agency employee serving as a flagger and at least one uniformed law enforcement officer should be in place at all times that rail traffic might approach or occupy the grade crossing.

When traffic is detoured over an existing passive grade crossing, a temporary traffic control plan (see Section 6B.01) should be prepared. Added to improve consistency

Guidance:

Public and private agencies, including-emergency services, businesses, and railroad or LRT-companies or transit agencies; should meet to plan appropriate traffic detours and the necessary signing, marking, signalization, and flagging requirements for operations during temporary traffic control zone activities or during the period when traffic is being detoured over an existing passive grade crossing. Consideration should be given to the length of time that the grade crossing is to be closed, the length of time that a detour is to be in place, the type of rail or LRT and highway traffic affected, the time of day, and the materials and techniques of repair. Edited to improve accuracy

The agencies responsible for the operation of the LRT and highway should be contacted when the initial planning begins for any temporary traffic control zone that might directly or indirectly influence the flow of traffic on mixed-use facilities where LRT vehicles and road users operate on a mixed-use alignment. Edited to improve accuracy

Temporary traffic control operations should minimize the inconvenience, delay, and crash potential to affected traffic. Prior notice should be given to affected public or private agencies, emergency services, businesses, railroad or LRT-companies or transit agencies, and road users before the free movement of road users or rail traffic is infringed upon or blocked.

Temporary traffic control zone activities should not be permitted to extensively prolong the closing of $\frac{de}{dt}$ grade crossing.

The width, grade, alignment, and riding quality of the highway surface at a grade crossing should, at a minimum, be restored to correspond with the quality of the approaches to the grade crossing.

Support:

Section 6G.186N.17 contains additional information regarding temporary traffic control zones in the vicinity of grade crossings, and Figure 6H-46 shows an example of a typical situation that might be encountered.

1 2

3 4

5

6

7

8

9

10

11

12

13

14

17

18

20

21

22

24

25

26

28

29

30

31

32

33

34 35

36

37

38

39 40

41

42 43

44

45

46

47 48

Section 8B.01 Purpose and Application

Support:

Passive traffic control systems, consisting of signs and pavement markings only, identify and direct attention to the location of a grade crossing and advise road users to slow down-reduce their speed or stop at the grade crossing as necessary in order to yield to any rail traffic occupying, or approaching and in proximity to, the grade crossing.

Signs and markings regulate, warn, and guide the road users so that they, as well as LRT vehicle operators on mixed-use alignments, can take appropriate action when approaching a grade crossing.

Standard: Standard changed to Support

<u>Unless otherwise provided in this Chapter</u>, the <u>design and location of signs shall comply with the</u> provisions of Part 2 are applicable to the <u>design and location of signs at grade crossings</u>, and the <u>design and location of pavement markings shall comply with the</u> provisions of Part 3 are applicable to the <u>design and location of pavement markings at grade crossings</u>.

15 Section 8B.02 Sizes of Grade Crossing Signs

16 Standard:

The minimum sizes of grade crossing signs shall be as shown in Table 8B-1. Edited to reflect Official Interpretation 8(09)-7(I)

19 Option:

Signs larger than those shown in Table 8B-1 may be used (see Section 2A.4407).

Section 8B.03 <u>Grade Crossing (Crossbuck) Sign (R15-1) and Number of Tracks Plaque (R15-2P) at Active and Passive Grade Crossings</u>

23 Standard:

The Grade Crossing (R15-1) sign (see Figure 8B-1), commonly identified as the Crossbuck sign, shall be retroreflectorized retroreflective white with the words RAILROAD CROSSING in black lettering, mounted as shown in Figure 8B-2.

27 Support:

In most States, the Crossbuck sign requires road users to yield the right-of-way to rail traffic at a grade crossing.

Standard:

As a minimum, one Crossbuck sign shall be used on each highway approach to every highway-rail grade crossing, alone or in combination with other traffic control devices.

As a minimum, one Crossbuck sign shall be used on each highway approach to every gated highway-LRT grade crossing on a semi-exclusive alignment, alone or in combination with other traffic control devices. Added to improve consistency

Option:

A Crossbuck sign may be used on a highway approach to a highway-LRT grade crossing on a semi-exclusive or mixed-use alignment or non-gated semi-exclusive alignment, alone or in combination with other traffic control devices. Edited to improve consistency

Standard:

If automatic gates are not present and if there are two or more tracks at a grade crossing, the number of tracks shall be indicated on a supplemental Number of Tracks (R15-2P) plaque (see Figure 8B-1) of inverted T shape mounted below the Crossbuck sign in the manner shown in Figure 8B-2.

On each approach to a highway-rail grade crossing and, if used, on each approach to a highway-LRT grade crossing, the Crossbuck sign shall be installed on the right-hand side of the highway on each approach to the grade crossing. Where restricted sight distance or unfavorable highway geometry exists on an approach to a grade crossing, or where there is a one-way multi-lane approach, an additional Crossbuck sign shall be installed on the left-hand side of the highway, possibly placed back-

to-back with the Crossbuck sign for the opposite approach, or otherwise located so that two Crossbuck signs are displayed for that approach.

At all passive grade crossings where Crossbuck signs have been installed, a strip of retroreflective white material not less than 2 inches in width shall be used on the back of each blade of each Crossbuck sign for the length of each blade, at all grade crossings where Crossbuck signs have been installed, except those where Crossbuck signs have been installed back-to-back or where double-faced Crossbuck signs have been installed.

Except as provided in Paragraph 14, where there is a curb, a lateral offset of at least 2 feet shall be provided from the face of the vertical curb to the closest part of the Crossbuck sign.

Except as provided in Paragraph 14, where there is no curb, a lateral offset to the closest part of the Crossbuck sign of at least 6 feet from the edge of the traveled way, and at least 2 feet from the edge of a paved or surfaced shoulder shall be provided. Added to improve accuracy

Guidance:

<u>Crossbuck signs should be located such that all physical aspects of the sign and its support are at least 12</u> <u>feet from the center of the nearest track.</u> Added to improve consistency

Crossbuck signs should be located with respect to the highway pavement or shoulder in accordance with the criteria in Chapter 2A and Figures 2A-2 and 2A-3, and should be located with respect to the nearest trackin accordance with Figure 8C 2.

The minimum lateral offset for the nearest edge of the Crossbuck sign should be 6 feet from the edge of the shoulder (or $\frac{12-6}{6}$ feet from the edge of the traveled way if no shoulder is present) in rural areas-(whichever is greater), and 2 feet from the face of the curb in urban areas.

Table 8B-1. Grade Crossing Sign and Plaque Minimum Sizes

Figure 8B-1. Regulatory Signs and Plaques for Grade Crossings

Figure 8B-2. Crossbuck Assembly with a YIELD or STOP Sign on the Crossbuck Sign Support

Figure 8B-3. Crossbuck Assembly with a YIELD or STOP Sign on a Separate Sign Support

Where unusual conditions make variations in location and lateral offset appropriate, engineering judgment should be used to provide the best practical combination of view and safety-clearances (see Section 2A.15).

Except as provided in Paragraph 16, the mounting height of Crossbuck signs, measured vertically from the center of the sign to the elevation of the nearest edge of the pavement, should be approximately 9 feet (see Figure 8B-2).

Option:

The 9-foot mounting height for the Crossbuck sign may be varied as required by local conditions and may be increased to accommodate signs mounted below the Crossbuck sign. Added to improve consistency

Section 8B.04 <u>Crossbuck Assemblies with YIELD or STOP Signs at Passive Grade Crossings</u> Standard:

A grade crossing Crossbuck Assembly shall consist of a Crossbuck (R15-1) sign, and a Number of Tracks (R15-2P) plaque if two or more tracks are present, that complies with the provisions of Section 8B.03, and either a YIELD (R1-2) or STOP (R1-1) sign installed on the same support, except as provided in Paragraph 10. If used at a passive grade crossing, a YIELD or STOP signs used at passive grade crossings shall be installed in compliance with the provisions of Part 2, Section 2B.2030, and Figures 8B-2 and 8B-3.

At all public highway-rail grade crossings that are not equipped with the active traffic control systems that are described in Chapter 8D, except crossings where road users are directed by an authorized person on the ground to not enter the crossing at all times that an approaching train is about to occupy the crossing, a Crossbuck Assembly shall be installed on the right-hand side of the highway on each approach to the highway-rail grade crossing.

If a Crossbuck sign is used on a highway approach to a public highway-LRT grade crossing that is not equipped with the active traffic control systems that are described in Chapter 8D, a Crossbuck Assembly shall be installed on the right-hand side of the highway on each approach to the highway-LRT grade crossing.

Where restricted sight distance or unfavorable highway geometry exists on an approach to a grade crossing that has a Crossbuck Assembly, or where there is a one-way multi-lane approach, an additional Crossbuck Assembly shall be installed on the left-hand side of the highway.

A YIELD sign shall be the default traffic control device for Crossbuck Assemblies on all highway approaches to passive grade crossings unless an engineering study performed by the regulatory agency or highway authority having jurisdiction over the roadway approach determines that a STOP sign is appropriate.

Guidance:

The use of STOP signs at passive grade crossings should be limited to unusual conditions where requiring all highway vehicles to make a full stop is deemed essential by an engineering study. Among the factors that should be considered in the engineering study are the line of sight to approaching rail traffic (giving due consideration to seasonal crops or vegetation beyond both the highway and railroad or LRT rights-of-ways), the number of tracks, the speeds of trains or LRT equipment and highway vehicles, and the crash history at the grade crossing.

Where a passive grade crossing on the stem of a T-intersection creates an inadequate clear storage distance between the tracks and the parallel roadway, and where adequate sight distance to oncoming traffic on the parallel roadway is available to road users stopped on the approach to the grade crossing, consideration should be given to installing a STOP sign at the Crossbuck Assembly instead of at the highway-highway intersection for traffic approaching the T-intersection. If the STOP sign is installed at the Crossbuck Assembly instead of at the highway-highway intersection, consideration should be given to installing a YIELD sign or some other intersection traffic control device at the highway-highway intersection. Added to improve

consistency

Standard:

If a Crossbuck Assembly is installed on the approach to a passive grade crossing located at a highway-highway intersection controlled by a traffic control signal that is not interconnected with the grade crossing and not preempted by the approach of rail traffic, a YIELD sign with a TO TRAINS (R15-9P) supplemental plaque shall be installed on the Crossbuck Assembly. A STOP sign shall not be installed on a Crossbuck Assembly in this situation. Added to improve consistency

Support:

Sections 8A.01 through 8A.05 contain information regarding the responsibilities of the highway agency and the railroad company or LRT agency regarding the selection, design, and operation of traffic control devices placed at grade crossings.

Option:

If a YIELD or STOP sign is installed for a Crossbuck Assembly at a grade crossing, it may be installed on the same support as the Crossbuck sign or it may be installed on a separate support at a point where the highway vehicle is to stop, or as near to that point as practical, but in either case, the YIELD or STOP sign is considered to be a part of the Crossbuck Assembly.

Standard:

If a YIELD or STOP sign is installed on an existing Crossbuck sign support, the minimum mounting height, measured vertically from the bottom of the YIELD or STOP sign to the top of the curb, or in the absence of curb, measured vertically from the bottom of the YIELD or STOP sign to the elevation of the nearest edge of the traveled way, shall be at least 4 feet (see Figure 8B-2).

If a Crossbuck Assembly is installed on a new sign support (see Figure 8B-2) or if the YIELD or STOP sign is installed on a separate support (see Figure 8B-3), the minimum-mounting height, measured vertically from the bottom of the YIELD or STOP sign to the top of the curb, or in the absence of curb, measured vertically from the bottom of the YIELD or STOP sign to the elevation of the nearest edge of the traveled way, shall be at least 5 feet in rural areas and shall be at least 7 feet if the Crossbuck Assembly is installed in an-areas where parking or pedestrian movements are likely to occur.

Guidance:

If a YIELD or STOP sign is installed for a Crossbuck Assembly at a grade crossing on a separate support than the Crossbuck sign (see Figure 8B-3), the YIELD or STOP sign should be placed at a point where the

highway vehicle is to stop, or as near to that point as practical, but no closer than 15 feet measured perpendicular from the nearest rail in the same plane as the Crossbuck sign and closer to the traveled way than the Crossbuck sign. The minimum separation between the nearest point of the YIELD or STOP sign and the nearest point of the Crossbuck sign should be 2 inches as shown in Figure 8B-3. On roadways where no curb exists, the minimum lateral offset of the YIELD or STOP sign should be 6 feet from the edge of the traveled way. Except as provided in Paragraph 14 in Section 8B.03, on roadways where a curb exists, the minimum lateral offset of the YIELD or STOP sign should be 2 feet from the face of the curb. Added to improve accuracy and support the dimensions shown in Figure 8B-3

Support:

The meaning of a Crossbuck Assembly that includes a YIELD sign is that a road user approaching the grade crossing needs to be prepared to decelerate, and when necessary, yield the right-of-way to any rail traffic that might be occupying the crossing or might be approaching and in such close proximity to the crossing that it would be unsafe for the road user to cross.

Certain commercial motor vehicles and school buses are required to stop at all grade crossings in accordance with 49 CFR 392.10 even if a YIELD sign (or just a Crossbuck sign) is posted.

The meaning of a Crossbuck Assembly that includes a STOP sign is that a road user approaching the grade crossing must come to a full and complete stop not less than 15 feet short of the nearest rail, and remain stopped while the road user determines if there is rail traffic either occupying the crossing or approaching and in such close proximity to the crossing that the road user must yield the right-of-way to rail traffic. The road user is permitted to proceed when it is safe to cross.

Standard:

A vertical strip of retroreflective white material, not less than 2 inches in width, shall be used on each Crossbuck support at passive grade crossings for the full length of the back of the support from the Crossbuck sign or Number of Tracks plaque to within 2 feet above the ground or elevation of the near edge of the traveled way (whichever is higher), except as provided in Paragraph 18. A white retroreflective strip wrapped around a round support shall satisfy this requirement as long as the round support has an outside diameter of at least 2 inches. Added to reflect Official Interpretation 8(09)-001(1)

Option:

The vertical strip of retroreflective material may be omitted from the back sides of Crossbuck sign supports installed on one-way streets and at pathway or sidewalk grade crossings (see Section 8E.05).

If a YIELD or STOP sign is installed on the same support as the Crossbuck sign, a vertical strip of red (see Section 2A.1721) or white retroreflective material that is at least 2 inches wide may be used on the front of the support from the YIELD or STOP sign to within 2 feet above the ground or elevation of the near edge of the traveled way (whichever is higher). Edited to improve consistency

Standard:

If a Crossbuck sign support at a passive grade crossing does not include a YIELD or STOP sign (either because the YIELD or STOP sign is placed on a separate support or because a YIELD or STOP sign is not present on the approach), a vertical strip of retroreflective white material, not less than 2 inches in width, shall be used for the full length of the front of the support from the Crossbuck sign or Number of Tracks plaque to within 2 feet above the ground or elevation of the near edge of the traveled way (whichever is higher). A white retroreflective strip wrapped around a round support shall satisfy this requirement as long as the round support has an outside diameter of at least 2 inches. Added to reflect Official Interpretation 8(09)-001(I)

At all grade crossings where YIELD or STOP signs are installed, Yield Ahead (W3-2) or Stop Ahead (W3-1) signs shall also be installed if the criteria for their installation in Section 2C.36 is met. Support:

Section 8B.288C.03 contains provisions regarding the use of stop lines or yield lines at grade crossings.

Section 8B.05 <u>Use of STOP (R1-1) or YIELD (R1-2) Signs without Crossbuck Signs at Highway-LRT Grade Crossings</u>

Standard:-Relocated to below

For all highway-LRT grade crossings where only STOP (R1-1) or YIELD (R1-2) signs are installed, the placement shall comply with the requirements of Section 2B.10. Stop Ahead (W3-1) or Yield Ahead (W3-2) Advance Warning signs (see Figure 2C-6) shall also be installed if the criteria for their installation given in Section 2C.36 is met.

Guidance:

The use of only STOP or YIELD signs for road users at highway-LRT grade crossings should be limited to those crossings where the need and feasibility is established by an engineering study. Such crossings should have all of the following characteristics:

- A. The crossing roadways should be are secondary in character (such as a minor street with one lane in each direction, an alley, or a driveway) with low traffic volumes and low speed limits. The specific thresholds of traffic volumes and speed limits should be determined by the local agencies.
- B. LRT speeds do not exceed 25 mph.
- B. The line of sight for an approaching LRT operator is adequate from a sufficient distance such that the operator can sound an audible signal and bring the LRT equipment to a stop before arriving at the crossing.
- C. The road user has sufficient sight distance at the stop line to permit the vehicle to cross the tracks before the arrival of the LRT equipment.
- D. If at an intersection of two roadways, the intersection does not meet the warrants for a traffic control signal as provided in Chapter 4C.
- E. The LRT tracks are located such that highway vehicles are not likely to stop on the tracks while waiting to enter a cross street or highway.

Standard: Relocated from above

For all highway-LRT grade crossings where only STOP (R1-1) or YIELD (R1-2) signs are installed, the placement shall comply with the requirements of Section 2B.1020. Stop Ahead (W3-1) or Yield Ahead (W3-2) Advance Warning signs (see Figure 2C-6) shall also be installed if the criteria for their installation given in Section 2C.36 is met.

Section 8B.06 <u>Grade Crossing Advance Warning Signs (W10-1 through W10-4Series)</u> Standard:

A Highway-Rail Grade Crossing Advance Warning (W10-1) sign (see Figure 8B-4) shall be used on each highway in advance of every highway-rail grade crossing, and every highway-LRT grade crossing in semi-exclusive alignments, except in the following circumstances:

- A. On an approach to a grade crossing from an T-intersection with a parallel highway if the distance from the edge of the track to the edge of the parallel roadway is less than 100 feet and W10-2, W10-3, or W10-4 signs are used on both the approaches of the parallel highway (see Paragraph 5);
- B. On low-volume, low-speed highways crossing minor spurs or other tracks that are infrequently used and road users are directed by an authorized person on the ground to not enter the crossing at all times that approaching rail traffic is about to occupy the crossing;
- C. In business or commercial areas where active grade crossing traffic control-devices systems are in use; or
- D. Where physical conditions do not permit even a partially effective display of the sign; or E. At highway-LRT grade crossings where Crossbuck signs are not used.

The placement of the Grade Crossing Advance Warning sign shall be in accordance with Section 2C.054 and Table 2C-43.

If a YIELD or STOP sign is present at a passive grade crossing, a Yield Ahead (W3-2) or Stop Ahead (W3-1) Advance Warning sign (see Figure 2C-6) shall also be installed if the criteria for their installation given in Section 2C.36 is met. If a Yield Ahead or Stop Ahead sign is installed on the approach to the crossing, the W10-1 sign shall be installed upstream from the Yield Ahead or Stop Ahead sign. The Yield Ahead or Stop Ahead sign shall be located in accordance with Table 2C-43. The minimum distance between the signs shall be in accordance with Section 2C.0504 and Table 2C-43.

On divided highways and one-way streets, an additional W10-1 sign may be installed on the left-hand side of the roadway.

Standard:

42.

 If the distance between the tracks and a parallel highway, from the edge of the tracks to the edge of the parallel roadway, is less than 100 feet, W10-2, W10-3, or W10-4 signs (see Figure 8B-4) shall be installed on each approach of the parallel highway to warn road users making a turn that they will encounter a grade crossing soon after making a turn, and a W10-1 sign for the approach to the tracks shall not be required to be between the tracks and the parallel highway.

If the W10-2, W10-3, or W10-4 signs are used, sign placement in accordance with the guidelines for Intersection Warning signs in Table 2C-43 using the speed of through traffic shall be measured from the highway intersection.

Guidance:

If the distance between the tracks and the parallel highway, from the edge of the tracks to the edge of the parallel roadway, is 100 feet or more, a W10-1 sign should be installed in advance of the grade crossing, and the W10-2, W10-3, or W10-4 signs should not be used on the parallel highway.

Figure 8B-4. Warning Signs and Plaques for Grade Crossings

Section 8B.07 EXEMPT Highway-Rail Grade Crossing Plaques (R15-3P, W10-1aP) This section has been relocated to new Section 8B.11

Section 8B.08 Turn Restrictions During Preemption This section has been relocated to Section 8D.11

Section-8B.09 8B.07 DO NOT STOP ON TRACKS Sign (R8-8)

21 Guidance:

A DO NOT STOP ON TRACKS (R8-8) sign (see Figure 8B-1)should be installed whenever an engineering study determines that the potential for highway vehicles stopping on the tracks at a grade crossing is significant. Placement of the R8-8 sign should be determined as part of the engineering study. The sign, if used, should be located on the right hand side of the highway on either the near or far side of the grade crossing, depending upon which position provides better visibility to approaching drivers. Relocated to below

If a STOP or YIELD sign is installed at a location, including at a circular intersection, that is downstream from the grade crossing such that highway vehicle queues are likely to extend beyond onto the tracks, a DO NOT STOP ON TRACKS (R8-8) sign should be used.

Except where a pre-signal (see Section 8D.12) is installed for the purpose of keeping the area between the tracks and a nearby downstream traffic control signal clear of vehicles, if a traffic control signal is installed within 200 feet downstream from the grade crossing such that highway vehicle queues are likely to extend onto the tracks, a DO NOT STOP ON TRACKS (R8-8) sign should be used. Added to improve consistency

A DO NOT STOP ON TRACKS (R8-8) sign should be installed whenever an engineering study determines that the potential for highway vehicles stopping on the tracks at a grade crossing is significant.

Placement of the R8 8 sign should be determined as part of the engineering study. The R8-8 sign, if used, should be located on the right-hand side of the highway on either the near or far side of the grade crossing, depending upon which position provides better visibility to approaching drivers. Deleted to improve clarity Option:

DO NOT STOP ON TRACKS signs may be placed on both sides of the track.

On divided highways and one-way streets, a second DO NOT STOP ON TRACKS sign may be placed on the near or far left-hand side of the highway at the grade crossing to further improve visibility of the sign.

Section 8B.10 8B.08 TRACKS OUT OF SERVICE Sign (R8-9)

45 Option:

The TRACKS OUT OF SERVICE (R8-9) sign (see Figure 8B-1) may be used at a grade crossing instead of a Crossbuck (R15-1) sign and a Number of Tracks (R15-2P) plaque or instead of a Crossbuck Assembly when railroad or LRT tracks have been temporarily or permanently abandoned, but only until such time that the tracks are removed or covered.

Standard:

When tracks are out of service, <u>except as provided in Paragraphs 3 and 4,</u> traffic control devices and gate arms shall be removed and the signal heads shall be removed or hooded or turned from view to clearly indicate that they are not in operation.

When tracks are out of service, even if TRACKS OUT OF SERVICE (R8-9) signs have been installed, Emergency Notification System (I-13) signs (see Section 8B.26) shall be retained at the grade crossing and shall be visible to road users. Added to improve consistency

Option:

Warning signs, such as the Low Ground Clearance Grade Crossing (W10-5) sign and the Skewed Crossing (W10-12) sign, that warn road users about physical roadway conditions that are still present at the grade crossing may be left in place after the tracks are taken out of service until the tracks have been removed or covered. Added to improve consistency

Standard:

The R8-9 sign shall be removed when the tracks have been removed or <u>eovered paved over</u> or when the grade crossing is returned to service. <u>The Emergency Notification System (I-13) signs shall be removed when the tracks have been removed or paved over. Added to improve consistency</u>

Section 8B.11-8B.09 STOP HERE WHEN FLASHING Sign (R8-10, R8-10a)

18 Option:

The STOP HERE WHEN FLASHING (R8-10, R8-10a) sign (see Figure 8B-1) may be used at a grade crossing to inform drivers of the location of the stop line or the point at which to stop when the flashing-light signals (see Section 8D.02) are activated.

22 Section 8B.12 8B.10 STOP HERE ON RED Sign (R10-6, R10-6a)

23 Support:

The STOP HERE ON RED (R10-6, R10-6a) sign (see Figure 8B-1) defines and facilitates observance of stop lines at traffic control signals.

Option:

A STOP HERE ON RED sign may be used at locations where highway vehicles frequently violate the stop line or where it is not obvious to road users where to stop.

Guidance:

If possible, stop lines should be placed at a point where the highway vehicle driver has adequate sight distance along the track.

Section 8B.07 8B.11 EXEMPT Highway Rail Grade Crossing Plaques (R15-3P, W10-1aP) This Section relocated from existing Section 8B.07

34 Option:

When authorized by law or regulation, an supplemental EXEMPT (R15-3P) plaque (see Figure 8B-1) with a white background may be used below the Crossbuck sign or Number of Tracks plaque, if present, at the grade crossing, and an supplemental EXEMPT (W10-1aP) plaque (see Figure 8B-4) with a yellow background may be used below the Grade Crossing Advance Warning (W10-1 through W10-4Series) sign.

Where neither the Crossbuck sign nor the advance warning signs exist for a particular highway-LRT grade crossing, an EXEMPT (R15-3P) plaque with a white background may be placed on its own post on the near right-hand side of the approach to the crossing.

Support:

These supplemental plaques inform drivers of highway vehicles carrying passengers for hire, school buses carrying students, or highway vehicles carrying hazardous materials that a stop is not required at certain designated grade crossings, except when rail traffic is approaching or occupying the grade crossing, or the driver's view is blocked.

47 Section 8B.13 8B.12 Light Rail Transit Only Lane Signs (R15-4 Series)

48 Support:

The Light Rail Transit Only Lane (R15-4 Series) signs (see Figure 8B-1) are used for multi-lane operations, where road users might need additional guidance on lane use and/or restrictions.

3 Option:

6

7

8

10

11

13

14

17

18

19

21

22

23

24

26

27

29

30

32

33

35

3637

38

39

41

44

45

46

4 Light Rail Transit Only Lane signs may be used on a roadway lane limited to only LRT use to indicate the restricted use of a lane in semi-exclusive and mixed alignments.

Guidance:

If used, the R15-4a, R15-4b, and R15-4c signs should be installed on posts adjacent to the roadway containing the LRT tracks or overhead above the LRT only lane.

9 Option:

If the trackway is paved, preferential lane markings (see Chapter 3E) may be installed, but only in combination with Light Rail Transit Only Lane signs.

12 Support:

The trackway is the continuous way designated for LRT, including the entire dynamic envelope. Section 8C.06 contains more information regarding the dynamic envelope.

15 Section 8B.14 8B.13 Do Not Pass Light Rail Transit Signs (R15-5, R15-5a)

16 Support:

A Do Not Pass Light Rail Transit (R15-5) sign (see Figure 8B-1) is used to indicate that motor vehicles are not allowed to pass LRT vehicles that are loading or unloading passengers where there is no raised platform or physical separation from the lanes upon which other motor vehicles are operating.

20 Option:

The R15-5 sign may be used in mixed-use alignments and may be mounted overhead where there are multiple lanes.

Instead of the R15-5 symbol sign, a regulatory sign with the word message DO NOT PASS STOPPED TRAIN (R15-5a) may be used (see Figure 8B-1).

25 Guidance:

If used, the R15-5 sign should be located immediately before the LRT boarding area.

Section 8B.15 8B.14 No Motor Vehicles On Tracks Signs (R15-6, R15-6a)

28 Support:

The No Motor Vehicles On Tracks (R15-6) sign (see Figure 8B-1) is used where there are adjacent traffic lanes separated from the LRT lane by a curb or pavement markings.

31 Guidance:

The DO NOT ENTER (R5-1) sign should be used where a road user could wrongly enter an LRT only street.

34 Option:

A No Motor Vehicles On Tracks sign may be used to deter motor vehicles from driving on the trackway. It may be installed on a 3-foot flexible post between double tracks, on a post alongside the tracks, or overhead.

Instead of the R15-6 symbol sign, a regulatory sign with the word message DO NOT DRIVE ON TRACKS (R15-6a) may be used (see Figure 8B-1).

A reduced size of 12 x 12 inches may be used if the R15-6 sign is installed between double tracks.

40 Standard:

The smallest size for the R15-6 sign shall be 12 x 12 inches.

42 Section 8B.16 8B.15 Divided Highway with Light Rail Transit Crossing Signs (R15-7 Series)

43 Option:

The Divided Highway with Light Rail Transit Crossing (R15-7) sign (see Figure 8B-1) may be used as a supplemental sign on the approach legs of a roadway that intersects with a divided highway where LRT equipment operates in the median. The sign may be placed beneath a STOP sign or mounted separately.

47 Guidance:

- 1 The number of tracks displayed on the R15-7 sign should be the same as the actual number of tracks.
- 2 **Standard:**

3

7

10

11

12

13

14

15

16

17

18

19

20

21 22

23

24

25 26

27

28

29

30

31

32

33

34

35

36 37

38 39

40

41

42

43

44

45

46

47

- When the Divided Highway With Light Rail Transit Crossing sign is used at a four-legged 4 intersection, the R15-7 sign shall be used. When used at a T-intersection, the R15-7a sign shall be used.
- Section 8B.17 LOOK Sign (R15-8) Deleted; redundant with new Section 8E.03 5
- 6 Section 8B.18 Emergency Notification Sign (I-13) This Section relocated to new Section 8B.26
- Section 8B.23 8B.16 Low Ground Clearance Grade Crossing Sign (W10-5) This Section 8 relocated from existing Section 8B.23
- 9 Guidance:

If the highway profile conditions are sufficiently abrupt to create a hang-up situation for long wheelbase vehicles or for trailers with low ground clearance, the Low Ground Clearance Grade Crossing (W10-5) sign (see Figure 8B-4) should be installed in advance of the grade crossing.

Standard:

Because this symbol might not be readily recognizable by the public, the Low Ground Clearance Grade Crossing (W10-5) warning sign shall be accompanied by a LOW GROUND CLEARANCE (W10-5P) educational plaque. The LOW GROUND CLEARANCE educational plaque shall remain in place for at least 3 years after the initial installation of the W10-5 sign (see Section 2A.1209).

Guidance:

Because other vehicle types and combinations also face the potential risk of hanging up at a grade crossing, word message warning signs and selective exclusion regulatory signs (see Section 2B.52) for specific vehicle types and combinations should be used in addition to, or in place of, the Low Ground Clearance Grade Crossing (W10-5) sign.

Support:

While not all inclusive, some potential low ground clearance vehicles and combinations include singleunit trucks, buses, motor coaches, low-boy trailers, car carriers, and recreational vehicles. Added to improve clarity

Guidance:

Auxiliary plagues such as AHEAD, NEXT CROSSING, or USE NEXT CROSSING (with appropriate arrows), or a supplemental distance plaque should be placed below the W10-5 sign at the nearest intersecting highway where a vehicle can detour or at a point on the highway wide enough to permit a U-turn.

If engineering judgment of roadway geometric and operating conditions confirms that highway vehicle speeds across the tracks should be below the posted speed limit, a W13-1P advisory speed plaque should be posted.

Guidance:

A signed detour should be installed to guide potential hang-up vehicles to alternate nearby crossings to avoid the potential hang-up condition. Added to improve clarity

Option:

If the grade crossing is rough, word message signs such as BUMP, DIP, or ROUGH CROSSING may be installed. A W13-1P advisory speed plaque may be installed below the word message sign in advance of rough crossings. This text was relocated to new Section 8B.24

Support:

Information on ground clearance requirements at grade crossings is available in the "American Railway Engineering and Maintenance-of-Way Association's Engineering Manual," or the American Association of State Highway and Transportation Officials' "Policy on Geometric Design of Highways and Streets" (see Section 1A.1105).

An inventory of crossings with low ground clearance concerns, including a list of potential vehicle types that could hang-up on the crossing, can be useful in tracking locations of low ground clearance crossings. Specific geometric conditions, known incidents, or anecdotal evidence of vehicle hang-ups can also be used to

48

49 identify crossings with low ground clearance concerns. Added to improve clarity

Section 8B.19 8B.17 Light Rail Transit Approaching-Activated Blank-Out Warning Sign (W10-7)

Support:

The Light Rail Transit Approaching-Activated Blank-Out (W10-7) warning sign (see Figure 8B-4) supplements the traffic control devices to warn road users crossing the tracks of approaching LRT equipment. Option:

A Light Rail Transit Approaching-Activated Blank-Out warning sign may be used at signalized intersections near highway-LRT grade crossings or at crossings controlled by STOP signs or automatic gates.

The provisions contained in Chapter 2L for blank-out signs are applicable to the W10-7 sign. Added to improve consistency

Section 8B.20-8B.18 TRAINS MAY EXCEED 80 MPH Sign (W10-8)

Guidance:

Where trains are permitted to travel at speeds exceeding 80 mph, a TRAINS MAY EXCEED 80 MPH (W10-8) sign (see Figure 8B-4) should be installed facing road users approaching the highway-rail grade crossing.

If used, the TRAINS MAY EXCEED 80 MPH signs should be installed between the Grade Crossing Advance Warning (W10<u>-1 through W10-4Series</u>) sign (see Figure 8B-4) and the highway-rail grade crossing on all approaches to the highway-rail grade crossing. The locations should be determined based on specific site conditions.

Section 8B.21-8B.19 NO TRAIN HORN Sign or Plaque (W10-9, W10-9P)

22 Standard:

Either a NO TRAIN HORN (W10-9) sign (see Figure 8B-4) or a NO TRAIN HORN (W10-9P) plaque shall be installed in each direction at each highway-rail grade crossing where a quiet zone has been established in compliance with 49 CFR Part 222. If a W10-9P plaque is used, it shall supplement and be mounted directly below the Grade Crossing Advance Warning (W10-1 through W10-4Series) sign (see Figure 8B-4).

Section 8B.24 8B.20 Storage Space Signs (W10-11, W10-11a, W10-11b) This Section relocated from existing Section 8B.24

Guidance:

A Storage Space (W10-11) sign supplemented by a word message Storage Distance (W10-11a) sign (see Figure 8B-4) should be used where there is a highway intersection in close proximity to the grade crossing and an engineering study determines that adequate space is not available to store a design vehicle(s) between the highway intersection and the train or LRT equipment dynamic envelope.

The Storage Space (W10-11 and W10-11a) signs should be mounted in advance of the grade crossing at an appropriate location to advise drivers of the space available for highway vehicle storage between the highway intersection and the grade crossing.

Option:

A Storage Space (W10-11b) sign (see Figure 8B-4) may be mounted beyond the grade crossing at the highway intersection under the STOP or YIELD sign or just prior to the signalized intersection to remind drivers of the storage space between the tracks and the highway intersection.

Standard:

The Storage Space sign shall not be used as a replacement for the required Advance Warning (W10-1) sign. If used, the Storage Space sign shall supplement the W10-1 sign and shall be mounted on a separate post. Added to improve consistency

Section 8B.25 8B.21 Skewed Crossing Sign (W10-12) This Section relocated from existing Section 8B.25

48 Option:

The Skewed Crossing (W10-12) sign (see Figure 8B-4) may be used at a skewed grade crossing to warn road users that the tracks are not perpendicular to the highway.

Guidance:

3

4

5

6 7

8

9

10

1112

24

25

26 27

28

29 30

37

38

39

42

43

44

47

If the Skewed Crossing sign is used, the symbol should show the direction of the crossing (near left to far right as shown in Figure 8B-4, the sign image, or the mirror image if the track goes from far left to near right). If the Skewed Crossing sign is used where the angle of the crossing is significantly different than 45 degrees, the symbol should show the approximate angle of the crossing.

Standard:

The Skewed Crossing sign shall not be used as a replacement for the required Advance Warning (W10-1) sign. If used, the Skewed Crossing sign shall supplement the W10-1 sign and shall be mounted on a separate post.

Section 8B.22 NO GATES OR LIGHTS Plaque (W10-13P)

13 Option:

The NO GATES OR LIGHTS (W10-13P) plaque (see Figure 8B-4) may be mounted below the Grade Crossing Advance Warning (W10-1 through W10-4 Series) sign at grade crossings that are not equipped with automatic gates or automated signals.

- 17 Section 8B.23 Low Ground Clearance Grade Crossing Sign (W10-5) This Section relocated to new Section 8B.16. The fifth paragraph was relocated to new section 8B.24
- 19 Section 8B.24 Storage Space Signs (W10-11, W10-11a, W10-11b) This Section relocated to new Section
- 20 8B.20
- 21 Section 8B.25 Skewed Crossing Sign (W10-12) This Section relocated to new Section 8B.21
- 22 <u>Section 8B.23 Next Crossing Plaques (W10-14P, W10-14aP)</u> Added to improve consistency
 23 Option:

The NEXT CROSSING (W10-14P) plaque may be mounted below the Low Ground Clearance (W10-5) sign (see Section 8B.16) or Skewed Crossing (W10-12) sign to indicate to a road user that the warning is associated with the next grade crossing. This plaque may be used where multiple grade crossings exist in close proximity to one another.

The USE NEXT CROSSING (W10-14aP) plaque may be mounted below the Low Ground Clearance (W10-5) sign (see Section 8B.16) to advise a road user with a low clearance load to use the crossing after the upcoming crossing to avoid encountering a low ground clearance situation.

31 <u>Section 8B.24 ROUGH CROSSING Plaque (W10-15P)</u> Added to improve consistency Option:

The ROUGH CROSSING (W10-15P) plaque may be mounted below the Grade Crossing Advance
Warning (W10-1 through W10-4) sign on the approach to a grade crossing to provide supplemental

information that the surface or condition of the grade crossing might require a reduced speed or some other
 appropriate action by the road user.

If the grade crossing is rough, word message signs such as BUMP, DIP, or ROUGH CROSSING may be installed. A W13-1P advisory speed plaque may be installed below the word message sign in advance of rough crossings. This text was relocated from existing Section 8B.23

40 Section 8B.26 8B.25 Light Rail Transit Station Sign (I-12)

41 Option:

The Light Rail Transit Station (I-12) sign (see Figure 2H-1Section 2H.01) may be used to direct road users to an LRT station or boarding location. It may be supplemented by the name of the transit system and by arrows as provided in Section 2D.08.

Section 8B.18 8B.26 Emergency Notification System Sign (I-13) This section was relocated from existing Section 8B.18 and the sequence of paragraphs was revised.

Guidance Standard: Guidance changed to Standard to comply with CFR 234.311

1 Emergency Notification System (I-13) signs (see Figure 8B-5) should shall be installed on each 2 approach at all highway-rail grade crossings, and at all highway-LRT grade crossings on semi-exclusive 3 alignments, to provide information to road users so that they can notify the railroad company or LRT 4 agency about emergencies or malfunctioning traffic control devices. 5 Standard: 6 When Emergency Notification System signs are used at a highway-rail grade crossing, they shall, at 7 a minimum, include the USDOT grade crossing inventory number and the emergency contact telephone 8 number. 9 When Emergency Notification System signs are used at a highway-LRT grade crossing, they shall, 10 at a minimum, include a unique crossing identifier and the emergency contact telephone number. 11 The minimum width of the Emergency Notification System sign shall be 12 inches and the minimum 12 height shall be 9 inches. The lettering on Emergency Notification System signs for the telephone 13 number, the grade crossing inventory number, and the explanation of the purpose of the sign shall be composed of numerals and upper-case letters that are at least 1 inch in height. Added to comply with 14 15 CFR 234.309 16 Emergency Notification System signs should shall be retroreflective. Relocated from below and 17 edited to comply with CFR 234.309 18 Except as provided in Paragraph 7, Emergency Notification System signs shall have a white legend 19 and border on a blue background. 20 The Emergency Notification signs shall be positioned so as to not obstruct any traffic control-21 devices or limit the view of rail traffic approaching the grade crossing. Relocated to below 22 23 The seven-character grade crossing inventory number may be shown on the sign as a black legend on a 24 white rectangular background. Added to comply with CFR 234.309 25 Guidance: 26 Emergency Notification signs should be retroreflective. Relocated to above 27 Except as provided in Paragraph 12, Emergency Notification System signs should be attached to the 28 Crossbuck Assemblies or grade crossing signal masts on the right-hand side of each roadway approach to the 29 grade crossing rather than on the railroad or LRT signal control equipment housings. Emergency 30 Notification System signs should be oriented so as to the face highway vehicles stopped on or at the grade crossing or on the traveled way near the grade crossing of the sign is approximately parallel to the edge of 31 32 the roadway or pathway and is visible to road users or pathway users. Edited to improve consistency 33 At station crossings, Emergency Notification signs or information should be posted in a conspicuous 34 location. Relocated to below 35 The Emergency Notification <u>System</u> signs <u>shall</u> <u>should</u> be positioned so as to not obstruct any traffic control devices or limit the view of rail traffic approaching the grade crossing. Relocated from above, 36 37 Standard changed to Guidance to be consistent with CRF 234.311 38 Emergency Notification System signs mounted on Crossbuck Assemblies or signal masts should only be 39 large enough to provide the necessary contact information. Use of larger signs that might obstruct the view of 40 rail traffic or other highway vehicles should be avoided. 41 At station crossings, Emergency Notification System signs or information should be posted in a 42 conspicuous location. Relocated from above 43 **Option:** Added to improve consistency 44 Emergency Notification System signs may be located on a separate post.

Additional Emergency Notification System signs may be installed at a grade crossing.

Figure 8B-5. Example of an Emergency Notification Sign

47 Section 8B.27 Pavement Markings This Section relocated to new Section 8C.02

Section 8B.28 Stop and Yield Lines This Section relocated to new Section 8C.03

Section 8B.29 Dynamic Envelope Markings This Section relocated to new Section 8C.06

45

46

48 49

Section 8C.01 Purpose and Application Added to improve consistency

Support:

Passive traffic control systems, consisting of signs and pavement markings only, identify and direct attention to the location of a grade crossing and advise road users to reduce their speed or stop at the grade crossing as necessary in order to yield to any rail traffic occupying, or approaching and in proximity to, the grade crossing.

Signs and markings regulate, warn, and guide the road users so that they, as well as LRT vehicle operators on mixed-use alignments, can take appropriate action when approaching a grade crossing.

<u>Unless otherwise provided in this Chapter, the provisions of Part 3 are applicable to the design and location of pavement markings at grade crossings.</u>

Section 8B.27 8C.02 Pavement Markings This Section relocated from existing Section 8B.27 and edited to improve consistency

Standard:

All grade crossing pavement markings shall be retroreflectorized white. All other markings shall be in accordance with Part 3. Relocated to below

On paved roadways, pavement markings in advance of a grade crossing shall consist of an X, the letters RR, a no-passing zone marking (on two-lane, two-way highways with center line markings in compliance with Section 3B.01), and certain transverse lines as shown in Figures 8B-6 and 8B-7. Relocated to below

<u>Except as provided in Paragraphs 2 and 3, Identical pavement</u> markings shall be placed in each approach lane on all paved approaches to <u>highway-rail</u> grade crossings where signals or automatic gates are located, and at all other grade crossings where the posted or statutory highway speed is 40 mph or <u>greaterhigher</u>.

Pavement markings shall not be required at highway-rail grade crossings where the posted or statutory highway speed is less than 40 mph if an engineering study indicates that other installed devices provide suitable warning and control.

Pavement markings shall not be required at <u>highway-rail</u> grade crossings in urban areas if an engineering study indicates that other installed devices provide suitable warning and control.

Pavement markings shall be placed in each approach lane on all paved approaches to highway-LRT grade crossings where a Crossbuck sign is placed at the grade crossing.

If pavement markings are used on a multi-lane approach to a grade crossing, identical markings shall be placed in each approach lane that crosses the tracks. Added to improve consistency

All grade crossing pavement markings shall be retroreflectorized retroreflective white. All other markings shall be in accordance with Part 3. Relocated from above

On paved roadways, pavement markings in advance of a grade crossing shall consist of an X, the letters RR, a no-passing zone marking (on two-lane, two-way highways with center line markings in compliance with Section 3B.01), and certain transverse lines as shown with detailed dimensions in Figures 8B-68C-1 and 8B-78C-2. Relocated from above

Guidance:

When pavement markings are used, a portion of the X symbol should be directly opposite the Grade Crossing Advance Warning sign. The X symbol and letters should be elongated to allow for the low angle at which they will be viewed. Deleted to improve consistency with Figure 8C-1 and 8C-2

Option:

When justified by engineering judgment, supplemental pavement marking symbol(s) may be placed between the Grade Crossing Advance Warning sign and the grade crossing.

Guidance:

If supplemental pavement marking symbol(s) are placed between the Grade Crossing Advance Warning sign and the grade crossing, the downstream transverse line should be at least 50 feet upstream from the stop or yield line at the grade crossing. Added to improve consistency with Figure 8C-1 and 8C-2

1 Figure 8C-1. Example of Placement of Warning Signs and Pavement Markings at Grade 2 **Crossings** 3 Figure 8C-2. Grade Crossing Pavement Markings Section 8B.28 8C.03 Stop and Yield Lines This Section relocated from existing Section 8B.28 and 4 5 edited to improve consistency 6 **Standard:** 7 On paved roadways at grade crossings that are equipped with active control devices such as 8 flashing-light signals, gates, or traffic control signals, a stop line (see Section 3B.16) shall be installed to 9 indicate the point behind which highway vehicles are or might be required to stop. Relocated to below 10 Guidance: 11 On paved roadway approaches to passive grade crossings where a STOP sign is installed in conjunction 12 with the Crossbuck sign, a stop line should be installed to indicate the point behind which highway vehicles 13 are required to stop or as near to that point as practical. 14 If a stop line is used, it should be a transverse line at a right angle to the traveled way and should be placed approximately 8 feet in advance of the gate (if present), but no closer than 15 feet in advance of the 15 nearest rail. Relocated to below 16 17 Option: 18 On paved roadway approaches to passive grade crossings where a YIELD sign is installed in conjunction 19 with the Crossbuck sign, a yield line (see Section 3B.196) or a stop line may be installed to indicate the point 20 behind which highway vehicles are required to yield or stop or as near to that point as practical. 21 Guidance: If a yield line (see Figure 3B-16) or stop line is used at a passive grade crossing, it should be a transverse 22 23 line (see Figure 3B-16) at a right angle to the traveled way and should be placed no closer than 15 feet in 24 advance of the nearest rail (see Figure 8B-7). 25 **Standard:** 26 On paved roadways at grade crossings that are equipped with active control devices such as 27 flashing-light signals, automatic gates, or traffic control signals, a stop line (see Section 3B.196) shall be 28 installed to indicate the point behind which highway vehicles are or might be required to stop. 29 Relocated from above 30 Guidance: 31 If a stop line is used at an active grade crossing where road users are controlled by flashing-light signals, 32 it should be a transverse line at a right angle to the traveled way and should be placed approximately 8 feet in 33 advance of the flashing-light signals or automatic gate (if present), whichever is further from the track(s), but 34 no closer than 15 feet in advance of the nearest rail (see Figure 8C-1). Relocated from above 35 If a stop line is used at an active grade crossing where road users are controlled by a traffic control signal, it should be a transverse line at a right angle to the traveled way and should be placed no closer than 36 15 feet in advance of the nearest rail. Added to improve consistency 37 38 **Standard:** 39 If a stop line is used at an active grade crossing where road users are controlled by a traffic control signal, it shall be placed such that the lateral and longitudinal positions of the signal faces for the 40 approach comply with the provisions of Sections 4D.06 and 4D.07. Added to improve consistency 41 Section 8C.04 Lane-Use Arrow Markings Added to improve consistency 42 43 **Standard:** 44 Lane-use arrow markings (see Section 3B.23) that indicate that a turning movement must be made 45 or is permitted to be made from a lane that crosses a grade crossing shall not be placed between the 46 stop line for the grade crossing and the track(s).

47

Guidance:

Lane-use arrow markings that indicate that a turning movement must be made or is permitted to be made
 from a lane that crosses a grade crossing should not be placed less than 100 feet upstream from the stop line
 for the grade crossing or less than 20 feet beyond the farthest rail.

Section 8C.05 Edge Lines, Lane Lines, Raised Pavement Markers, and Tubular Markers Added to improve consistency

Guidance:

Except as provided in Paragraph 2, if edge lines (see Section 3B.09) or lane lines (see Section 3B.06) are used on an approach to a grade crossing, the edge lines and lane lines should extend up to and across the track(s) to reduce the likelihood that road users might inadvertently turn into the track area.

Option:

The edge lines and lane lines may be omitted from the highway surface at a grade crossing if the surface cannot retain the application of the edge line or lane line marking.

If recommended by a Diagnostic Team, raised pavement markers (see Section 3B.16) may be used to supplement the edge lines or lane lines that extend up to and across the track(s).

If recommended by a Diagnostic Team, tubular markers (see Section 3I.01) may be used to supplement the edge lines that extend up to and across the track(s).

Guidance:

Tubular markers should not be installed within 6 feet of any rail.

Standard:

The color under both daytime and nighttime conditions of raised pavement markers or tubular markers that are used at a grade crossing shall be the same color as the edge line or lane line that they supplement.

Section 8B.29 8C.06 Dynamic Envelope Markings This Section relocated from existing Section 8B.29 and edited to improve consistency

Support:

The dynamic envelope (see Figures 8B-8 and 8B-9) markings indicate the clearance required for the trainor LRT equipment overhang resulting from any combination of loading, lateral motion, or suspension failure.

Option:

Dynamic envelope markings may be installed at all a grade crossings, unless a Four Quadrant Gatesystem (see Section 8C.06) is used to mark the edges of the train dynamic envelope.

Standard:

If used, pavement markings for indicating the dynamic envelope shall comply with the provisions of Part 3 and shall be a 4-inch normal solid white line not less than 4 inches nor greater than 24 inches in width be a 4-inch normal solid white line or contrasting pavement color (see Section 3A.035 and Chapter 3HG) and/or contrasting pavement texture.

Guidance:

If pavement markings are a 4-inch normal solid white line is used to convey the dynamic envelope, they the line should be placed completely outside of the dynamic envelope. If used, dynamic envelope pavement markings should be placed on the highway at a distance of 6 feet from and parallel to the nearest rail unless the operating railroad company or LRT agency advises otherwise. The If used, dynamic envelope pavement markings should extend across the roadway as shown in Figure 8B 88C-3. The Dynamic envelope pavement markings should not be placed perpendicular to the roadway at skewed grade crossings.

Option:

If 4-inch normal solid white lines are used to indicate the dynamic envelope, white cross-hatching lines may also be placed on the highway pavement within the dynamic envelope as a supplement to, but not as a substitute for, the 4-inch normal solid white lines. White cross-hatching lines (see Section 3B.26 Do Not Block intersection markings) may also be placed on the pavement to mark areas adjacent to the dynamic envelope where vehicles are not intended to stop or stand as shown in Figure 8C-4. Added to improve consistency

1 2	In semi-exclusive LRT alignments, the dynamic envelope markings may be along the LRT trackway between intersections where the trackway is immediately adjacent to travel lanes and no physical barrier is
3	present.
4	In mixed-use LRT alignments, the dynamic envelope markings may be continuous between intersections
5	(see Figure 8B-9 8C-5).
6	In mixed-use LRT alignments, pavement markings for adjacent travel or parking lanes may be used
7	instead of dynamic envelope markings if the lines are outside the dynamic envelope.
8	Figure 8C-3. Example of Dynamic Envelope Pavement Markings at Grade Crossings
9	Figure 8C-4. Example of Do Not Block Pavement Markings at Grade Crossings
10	Figure 8C-5. Examples of Light Rail Transit Vehicle Dynamic Envelope Markings for Mixed-Use
11	Alignments Alignments
12	

CHAPTER 8C-8D. FLASHING-LIGHT SIGNALS, <u>AUTOMATIC</u> GATES, AND TRAFFIC CONTROL SIGNALS

Section 8C.01 8D.01 Introduction

Support:

Active traffic control systems inform road users of the approach or presence of rail traffic at grade crossings. These systems include Four-Quadrant Exit Gate systems, automatic gates, flashing-light signals, traffic control signals, actuated blank-out and variable message signs, and other active traffic control devices that are used in conjunction with the signs and pavement markings that are described in Chapters 8B and 8C, respectively.

A composite drawing (see Figure 8CD-1) shows a post-mounted flashing-light signal (two light units mounted in a horizontal line), a flashing-light signal mounted on an overhead structure, and an automatic gate assembly.

When LRT speed is cited in this Part, it refers to the maximum speed at which LRT equipment is permitted to traverse a particular grade crossing.

Relocated from below Option:

Post-mounted and overhead flashing-light signals may be used separately or in combination with each other as determined by an engineering study. Also, flashing-light signals may be used without automatic gate assemblies, as determined by an engineering study.

Standard:

The meaning of flashing-light signals and <u>automatic</u> gates shall be as stated in the "<u>Uniform Vehicle</u> Code" <u>UVC</u> (see Sections 11-701 and 11-703) of the <u>UVC</u>), which is available from the National Committee on Uniform Traffic Laws and Ordinances (see Page i for the address).

Location and clearance dimensions for flashing-light signals and <u>automatic</u> gates shall be as shown in Figure 8CD-1.

When there is a curb, a horizontal offset of at least 2 feet shall be provided from the face of the vertical curb to the elosest nearest part of the signal or automatic gate arm in its upright position. When a cantilevered-arm flashing-light signal is used, the vertical clearance shall be at least 17 feet above the crown of the highway to the lowest point of the signal unit.

Where there is a shoulder, but no curb, a horizontal offset of at least 2 feet from the edge of a paved or surfaced shoulder shall be provided, with an offset of at least 6 feet from the edge of the traveled way.

Where there is no curb or shoulder, the minimum horizontal offset shall be 6 feet from the edge of the traveled way.

Minimum clearance dimensions for flashing lights and automatic gates relative to the proximity to the closest track shall conform to standards provided by the railroad company and/or transit agency.

Added to improve clarity

Guidance:

When the automatic gate is in its upright position, no portion of the physical features of flashing-light signals and gates, including the support hardware, should be closer than 12 feet from the center of the nearest track. Added to improve consistency

Equipment housings (controller cabinets) should have a lateral offset of at least 30 feet from the edge of the highway, and where railroad or LRT property and conditions allow, at least 25 feet from the nearest rail.

If a pedestrian route is provided, sufficient clearance from supports, posts, and <u>automatic</u> gate mechanisms should be maintained for pedestrian travel.

When determined by an engineering study, a lateral escape route to the right of the highway in advance of the grade crossing traffic control devices should be kept free of guardrail or other ground obstructions. Where guardrail is not deemed necessary or appropriate, barriers should not be used for protecting signal supports.

The same lateral offset and roadside safety features should apply to flashing-light signal and automatic gate locations on both the right-hand and left-hand sides of the roadway.

Option:

In industrial or other areas involving only low-speed highway traffic or where signals are vulnerable to damage by turning truck traffic, guardrail may be installed to provide protection for the signal assembly.

Guidance:

Where both traffic control signals and flashing-light signals (with or without automatic gates) are in operation at the same highway-LRT grade crossing, the operation of the devices should be coordinated to avoid any display of conflicting signal indications.

Support:

LRT typically operates through grade crossings in semi-exclusive and mixed use alignments at speeds between 10 and 65 mph. Deleted to improve accuracy

When LRT speed is cited in this Part, it refers to the maximum speed at which LRT equipment is permitted to traverse a particular grade crossing. Relocated to above Option:

If highway traffic signals must be located within close proximity to the flashing-light signal system, the highway traffic signals may be mounted on the same overhead structure as the flashing-light signals.

This text was relocated from existing Section 8C.09

Figure 8D-1. Composite Drawing of Active Traffic Control Devices for Grade Crossings Showing Clearances

Section 8C.02 8D.02 Flashing-Light Signals

20 Support:

Section <u>8C.038D.04</u> contains additional information regarding flashing-light signals at highway-LRT grade crossings in semi-exclusive and mixed-use alignments.

Standard:

If used, the flashing-light signal assembly (shown in Figure 8DC-1) on the side of the highway shall include a standard Crossbuck (R15-1) sign, and where there is more than one track, a supplemental Number of Tracks (R15-2P) plaque, all of which indicate to motorists, bicyclists, and pedestrians the location of a grade crossing.

Guidance:

The bottom of the Number of Tracks (R15-2P) plaque (when used) should be located as low as practical above the flashing-light backgrounds. The Crossbuck (R15-1) sign should be located just above the Number of Tracks (R15-2P) plaque or, if no plaque is present, the bottom of the Crossbuck sign should be located as low as practical above the flashing-light backgrounds. Added to improve consistency

33 Support:

Additional information regarding sizes and clearances of components used on flashing-light signals can be found in Part 3 of the current edition of the American Railway Engineering and Maintenance-of-Way Communication and Signal Manual of Recommended Practice. Added to improve consistency

Option:

At highway-rail grade crossings, bells or other audible warning devices may be included in the assembly and may be operated in conjunction with the flashing lights to provide additional warning for pedestrians, bicyclists, and/or other non-motorized road users.

Standard:

When indicating the approach or presence of rail traffic, the flashing-light signal shall display toward approaching highway traffic two red lights mounted in a horizontal line flashing alternately.

If used, flashing-light signals shall be placed to the right of approaching highway traffic on all highway approaches to a grade crossing. They shall be located laterally with respect to the highway in compliance with Figure 8DC-1 except where such location would adversely affect signal visibility.

If used at a grade crossing with highway traffic in both directions, back-to-back pairs of lights flashing-light signals shall be placed on each side of the tracks. On multi-lane one-way streets and divided highways, flashing-light signals shall be placed on the approach side of the grade crossing on both sides of the roadway or shall be placed above the highway.

Each red signal unit in the flashing-light signal shall flash alternately. The number of flashes per minute for each lamp shall be 35 minimum and 65 maximum. Each lamp shall be illuminated approximately the same length of time. The total time of illumination of each pair of lamps shall be the entire operating time.

Flashing-light units shall use either 8-inch or 12-inch nominal diameter lenses.

Guidance:

In choosing between the 8-inch or 12-inch nominal diameter lenses for use in grade crossing flashing-light signals, consideration should be given to the principles stated in Section 4D.074E.02.

If flashing-light signals are used, at least one pair of flashing lights should be provided for each approach lane of the roadway. Added to improve consistency

The center to center distance between the two red lights in a flashing-light unit should be approximately 30 inches. Added to support dimensions shown in Figure 8D-1

The mounting height of the flashing-light units, measured from the bottom of the flashing-light unit housing to the elevation of the crown of the roadway, should be between 8 feet and 9 feet. Added to support dimensions shown in Figure 8D-1

The top of the support pole foundation should be no more than 4 inches above the surface of the ground and should be at the same elevation as the crown of the roadway. Added to support dimensions shown in Figure 8D-1

Standard:

Grade crossing flashing-light signals shall operate at a low voltage using storage batteries either as a primary or stand-by source of electrical energy. Provision shall be made to provide a source of energy for charging batteries.

Option:

Additional pairs of flashing-light units signals may be mounted on the same supporting post and directed toward vehicular traffic approaching the grade crossing from other than the principal highway route, such as where there are approaching routes on highways closely adjacent to and parallel to the track(s).

Guidance: Added to improve consistency

Where the storage distance for vehicles approaching a grade crossing is less than a design vehicle length, the Diagnostic Team should consider providing additional flashing-light signals aligned toward the movement turning toward the grade crossing.

The Diagnostic Team should consider the use of additional flashing-light signals to provide supplemental warning to pedestrians, especially on one way streets and divided highways.

Standard:

References to lenses in this Section shall not be used to limit flashing-light signal optical units to incandescent lamps within optical assemblies that include lenses.

Support:

Research has resulted in flashing-light signal optical units that are not lenses, such as, but not limited to, light emitting diode (LED) flashing-light signal modules.

Option:

<u>If a Diagnostic Team determines that it is appropriate, the</u> flashing-light signals may be installed on overhead structures or cantilevered supports as shown in Figure 8CD-1 where needed for additional emphasis, or for better visibility to approaching traffic, particularly on multi-lane approaches or highways with profile restrictions.

If it is determined by an engineering study a Diagnostic Team that one set of flashing_lights signal on the cantilever arm is not sufficiently visible to road users, one or more additional sets of flashing_lights signals may be mounted on the supporting post and/or on the cantilever arm.

Standard:

Breakaway or frangible bases shall not be used on the supporting posts on the supporting posts for overhead structures or cantilevered supports arms that support overhead flashing-light signals.

Except as otherwise provided in Paragraphs 13 through 15, flashing-light signals mounted overhead shall comply with the applicable provisions of this Section.

Deleted; redundant with other text in this Section

Section 8C.03 Flashing-Light Signals at Highway-LRT Grade Crossings
This Section was relocated to new Section 8D.04

6 Section 8C.04 8D.03 Automatic Gates

Support:

42.

An automatic gate is a traffic control device used in conjunction with flashing-light signals.

Standard:

The automatic gate (see Figure 8CD-1) shall consist of a drive mechanism and a fully retroreflectorized retroreflective red- and white-striped gate arm with lights. When in the down position, the gate arm shall extend across the approaching lanes of highway traffic.

In the normal sequence of operation, unless constant warning time detection or other advanced system requires otherwise, the flashing-light signals and the lights on the gate arm (in its normal upright position) shall be activated immediately upon detection of approaching rail traffic. The gate arm shall start its downward motion not less than 3 seconds after the flashing-light signals start to operate, shall reach its horizontal position at least 5 seconds before the arrival of the rail traffic, and shall remain in the down position as long as the rail traffic occupies until the rail traffic completely clears the grade crossing.

When the rail traffic clears the grade crossing, and if no other rail traffic is detected, the gate arm shall ascend to its upright position, following which the flashing-light signals and the lights on the gate arm shall cease operation.

Gate arms shall be fully retroreflectorized retroreflective on both sides and shall have vertical stripes alternately red and white at 16-inch intervals measured horizontally. The width (which becomes the height of the retroreflective sheeting when the automatic gate is in the down position) of the retroreflective sheeting on the front of the gate arm shall be at least 4 inches. Added to support the dimensions in Figure 8D-1

Support:

It is acceptable to replace a damaged gate <u>arm</u> with a gate <u>arm</u> having vertical stripes even if the other existing gates <u>arms</u> at the same grade crossing have diagonal stripes; however, it is also acceptable to replace a damaged gate <u>arm</u> with a gate <u>arm</u> having diagonal stripes if the other existing gates <u>arms</u> at the same grade crossing have diagonal stripes in order to maintain consistency per the provisions of Paragraph 24 of the Introduction.

Standard:

Gate arms shall have at least three red lights as provided shown in Figure 8CD-1.

When activated, the gate arm light nearest the tip shall be illuminated continuously and the other lights shall flash alternately in unison with the flashing-light signals such that the left-most flashing gate arm light(s) flashes simultaneously with the left-hand light of the flashing-light signals and the right-most flashing gate arm light(s) flashes simultaneously with the right-hand light of the flashing-light signals. Edited to improve clarity

Support:

The red lights mounted on a gate arm are typically approximately 4 inches in diameter if they are circular.

Rectangular red lights of approximately the same size are sometimes used on gate arms instead of circular lights. Added to improve consistency

Standard:

The entrance gate arm mechanism shall be designed to fail safe in the down position.

47 Guidance.

The gate arm should ascend to its upright position in 12 seconds or less.

In its normal upright position, when no rail traffic is approaching or occupying the grade crossing, the gate arm should be either vertical or nearly so (see Figure 8 $\stackrel{\frown}{E}$ D-1).

In the design of individual installations, consideration should be given to timing the operation of the gate 2 arm to accommodate large and/or slow-moving highway vehicles.

The gates arms should cover the approaching highway to block all highway vehicles from being driven around the gate arms without crossing the center line.

The tip of the gate arm when it is in the down position should be at least 10 feet from the center of the nearest track.

The height of the gate arm when it is in the down position should be between 3.5 feet and 4.5 feet above the crown of the roadway.

When the gate arm is in the upright position, no portion of the gate arm or support pole hardware should extend more than 25.4 inches further from the roadway than the outside edge of the support pole. When the gate arm is in the down position, no portion of the counterweight should extend more than 4.25 feet further from the roadway than the center of the support pole. Added to support the dimensions shown in Figure 8D-1

Option:

1

3

4

5

6

7

8

9

10

11

12

13 14

15

16 17

18

19

20

21

22

23

24

26

27 28

29

30

31 32

33

34

35

36

37

38 39

40

41 42

43

44 45

46

47

The effectiveness of automatic gates may be enhanced by the use of channelizing devices or raised median islands to discourage driving around lowered automatic gates.

Where automatic gates are located in the median, additional median width may be required to provide the minimum clearance for the counterweight supports.

Automatic gates may be supplemented by cantilevered flashing-light signals (see Figure 8€D-1) where there is a need for additional emphasis or better visibility.

Section 8C.05 Use of Automatic Gates at LRT Grade Crossings This Section has been replaced by new Section 8D.04

Section 8D.04 Use of Active Traffic Control Systems at LRT Grade Crossings This Section relocated from existing Sections 8C.03 and 8C.05 and edited

25 Support:

> Section 8C.02 contains additional provisions regarding the design and operation of flashing light signals, including those installed at highway LRT grade crossings. Relocated to below

Standard:

At Hhighway-LRT grade crossings in semi-exclusive alignments shall be equipped with flashinglight signals where LRT speeds exceed 3540 mph, active traffic control systems (see Section 8D.01), including automatic gates, shall be used. Flashing-light signals shall be clearly visible to motorists, pedestrians, and bievelists.

If flashing-light signals are in operation at a highway-LRT crossing that is used by pedestrians, bicyclists, and/or other non-motorized road users, an audible device such as a bell shall also be provided and shall be operated in conjunction with the flashing-light signals. Relocated to below

At highway-LRT grade crossings \text{\text{W}} where the crossing is at a location other than an intersectionand LRT operating speeds exceed 25 mph, flashing-light signals active traffic control systems shouldshall be usedinstalled. Guidance changed to Standard and edited

Guidance: Added to improve consistency

At highway-LRT grade crossings where LRT operating speeds are 25 mph or less, active traffic control systems should be used unless an engineering study indicates that the use of Crossbuck Assemblies, STOP signs alone, or YIELD signs alone would be adequate.

Traffic control signals alone should not be used where the highway-LRT grade crossing is at a location other than an intersection and LRT operating speeds exceed 20 mph.

Support:

Sections 8CD.02 and 8D.03 contain additional provisions regarding the design and operation of flashinglight signals and automatic gates, respectively including those installed at highway LRT grade crossings.

Relocated from above and edited 48

49 **Standard:** If flashing-light signals are in operation at a highway-LRT crossing that is used by pedestrians, bicyclists, and/or other non-motorized road users, an audible device such as a bell shall also be provided and shall be operated in conjunction with the flashing-light signals. Relocated from above

Section 8C.06 8D.05 Exit Gate and Four-Quadrant Gate Systems

Option

Four Quadrant Exit Gate systems may be installed to improve safety at grade crossings based on an engineering study when less restrictive measures, such as automatic gates and median islands, are not effective.

Support: Added to improve clarity

A grade crossing that includes exit gates on some, but not all, of the exiting lanes is an Exit Gate system, but is not considered to be a Four-Quadrant Gate system.

The term Four-Quadrant Gate system is used in a generic sense in that it refers to the fact that all entrances and exits from a grade crossing are controlled by automatic gates in order to provide a full closure to all entering and exiting lanes. The term Four-Quadrant Gate system does not refer to the number of gates installed, but rather the fact that a full closure is provided.

Standard:

The Four Quadrant Exit Gate system shall use a series of drive mechanisms and automatic gates with fully retroreflectorized retroreflective red- and white-striped gate arms with lights, and when in the down position the gate arms extend individually across the entrance and exit lanes of the roadway as shown in Figure 8CD-2. Standards contained in Section 8C.018D.02 for flashing-light signals shall be followed for signal specifications, location, and clearance distances.

Gate arm design, colors, and lighting requirements shall be in accordance with the Standards contained in Section 8C.048D.03. Relocated from below

Support:

The provisions contained in Section 8D.03 for automatic gates are applicable to exit gates.

Standard:

In the normal sequence of operation, unless constant warning time detection or other advanced system requires otherwise, the flashing-light signals and the lights on the gate arms (in their normal upright positions) shall be activated immediately upon the detection of approaching rail traffic. The entrance gate arms for the entrance lanes of traffic shall start their downward motion not less than 3 seconds after the flashing-light signals start to operate and shall reach their horizontal position at least 5 seconds before the arrival of the rail traffic. Exit gate arm activation and downward motion shall be based on detection or timing requirements established by an engineering study of the individual site a Diagnostic Team. If an Exit Gate system is present, the queue clearance time (see Section 8D.10) shall be long enough to permit the exit gate arm to lower after a design vehicle of maximum length is clear of the minimum track clearance distance (see Section 8A.07). The gate arms shall remain in the down position as long as the rail traffic occupies the grade crossing. Edited to improve consistency with Queue Clearance Time definition in Part 1

When the rail traffic clears the grade crossing, and if no other rail traffic is detected, the gate arms shall ascend to their upright positions, following which the flashing-light signals and the lights on the gate arms shall cease operation.

Gate arm design, colors, and lighting requirements shall be in accordance with the Standards contained in Section 8C.04. Relocated to above

Except as provided in Paragraph $\frac{1920}{}$, the exit gate arm mechanism shall be designed to fail-safe in the up position.

At locations where gate arms are offset a sufficient distance for highway vehicles to drive between the entrance and exit gate arms, median islands (see Figure $8 \leftarrow D$ -2) shall be installed in accordance with the needs established by an engineering study.

Guidance:

The gate arm should ascend to its upright position in 12 seconds or less.

Four-Quadrant Gate systems should only be used in locations with Constant warning time detection circuits should be used with Exit Gate systems where practical.

The operating mode of the exit gates should be determined based upon an engineering study, with input from the affected railroad company or LRT agency by a Diagnostic Team.

If the Timed Exit Gate Operating Mode is used, the <u>engineering study</u>, <u>with input from the affected</u> <u>railroad company or LRT agency</u>, <u>Diagnostic Team</u> should also determine the Exit Gate Clearance Time (see definition in Section <u>1C.021A.13</u>).

If the Dynamic Exit Gate Operating Mode is used, highway vehicle intrusion detection devices that are part of a system that incorporates processing logic to detect the presence of highway vehicles within the minimum track clearance distance (see Section 8A.07) should be installed to control exit gate operation. Exit gates should be independently controlled for each direction of roadway traffic.

Regardless of which exit gate operating mode is used, the Exit Gate Clearance Time should be considered when determining additional time requirements for the Minimum Warning Time.

If an Four Quadrant Exit Gate system is used at a location that is adjacent to an intersection that could cause highway vehicles to queue within the minimum track clearance distance (see Section 8A.07), the Dynamic Exit Gate Operating Mode should be used unless an engineering study indicates otherwise.

If an Four Quadrant Exit Gate system is interconnected with a highway traffic signal (see Section 8D.10), backup or standby power should be considered for the highway traffic signal. Also, circuitry should be installed to prevent the highway traffic signal from leaving the track clearance green interval until all of the gates are lowered.

At locations where sufficient space is available, exit gates should be positioned downstream from the track a distance that provides a safety zone long enough to accommodate at least one design vehicle between the exit gate and the nearest rail.

Four Quadrant Exit Gate systems should include remote health (status) monitoring capable of automatically notifying railroad or LRT signal maintenance personnel when anomalies have occurred within the system.

Option:

Exit gate arms may fail in the down position if the grade crossing is equipped with remote health (status) monitoring.

Four Quadrant Exit Gate system installations may include median islands between opposing lanes on an approach to a grade crossing.

Guidance:

Where sufficient space is available, median islands should be at least 60 feet in length.

Figure 8D-2. Example of Location Plan for Flashing-Light Signals and Four-Quadrant Gates

Section 8C.07 8D.06 Wayside Horn Systems

Option:

A wayside horn system (see definition in Section 1A.131C.02) may be installed in compliance with 49 CFR Part 222 to provide audible warning directed toward the road users at a highway-rail or highway-LRT-grade crossing or at a pathway grade crossing.

Standard:

Wayside horn systems used at grade crossings where the locomotive horn is not sounded shall be equipped and shall operate in compliance with the requirements of Appendix E to 49 CFR Part 222.

Guidance:

The same lateral clearance and roadside safety features should apply to wayside horn systems as described in the Standards contained in Section 8 \bigcirc D.01. Wayside horn systems, when mounted on a separate pole assembly, should be installed no closer than 15 feet from the center of the nearest track and should be positioned to not obstruct the motorists' line of sight of the flashing-light signals.

Section 8D.07 Another Train Coming

Support:

Conflicts between pedestrians and multiple trains can occur at multi-track crossings on sidewalks, pathways, and at crossings in station areas where grade crossing users might not consider the arrival of another train on a different track.

Guidance:

The decision to provide notification of another train should be made by a diagnostic team. In making this determination, the diagnostic team should consider the pedestrian utilization, pedestrian collision history, train speeds and volumes, operating plans and/or schedules, and the presence of a nearby station or transit center.

Option:

An ANOTHER TRAIN COMING train-activated blank-out sign may be used to provide notification of another train coming. For added sign conspicuity, a Warning Beacon may be used in accordance with the requirements of Section 4S.03.

Section 8C.08 8D.08 Rail Traffic Detection

14 Standard:

The devices employed in active traffic control systems shall be actuated by some form of rail traffic detection.

Rail traffic detection circuits, insofar as practical, shall be designed on the fail-safe principle.

Flashing-light signals shall operate for at least 20 seconds before the arrival of any rail traffic, except as provided in Paragraph 4.

Option:

On tracks where all rail traffic operates at less than 20 mph and where road users are directed by an authorized person on the ground to not enter the crossing at all times that approaching rail traffic is about to occupy the crossing, a shorter signal operating time for the flashing-light signals may be used.

Additional warning time may be provided when determined by an engineering study.

Guidance:

Where the speeds of different rail traffic on a given track vary considerably under normal operation, special devices or circuits should be installed to provide reasonably uniform notice in advance of all rail traffic movements over the grade crossing. Special control features should be used to eliminate the effects of station stops and switching operations within approach control circuits to prevent excessive activation of the traffic control devices while rail traffic is stopped on or switching upon the approach track control circuits.

Section 8C.09 8D.09 Use of Traffic Control Signals at or Near Highway-Rail Grade Crossings
This Section has been reorganized into new Sections 8D.09, 8D.10, and 8D.12

Standard:

Except as provided in Paragraph 2, traffic control signals shall not be used instead of flashing-light signals to control road users at a mainline highway-rail grade crossing.

Relocated from below Option:

Traffic control signals may be used instead of flashing-light signals to control road users at industrial highway-rail grade crossings and other places where train movements are very slow, such as in switching operations the maximum speed of trains is 10 mph or less. Edited to improve accuracy

Support:

Section 8D.04 contains information regarding the use of traffic control signals at highway-LRT grade crossings. Added to improve clarity

Standard:

The appropriate provisions of Part 4 relating to traffic control signal design, installation, and operation shall be applicable where traffic control signals are used to control road users instead of flashing-light signals at highway-rail grade crossings.

Traffic control signals shall not be used instead of flashing-light signals to control road users at a mainline highway-rail grade crossing. Relocated to above

Guidance: These paragraphs relocated to new Section 8D.10

If a highway-rail grade crossing is equipped with a flashing-light signal system and is located within 200 feet of an intersection or midblock location controlled by a traffic control signal, the traffic control signal should be provided with preemption in accordance with Section 4D.27.

Coordination with the flashing light signal system, queue detection, or other alternatives should be considered for traffic control signals located farther than 200 feet from the highway rail grade crossing. Factors to be considered should include traffic volumes, highway vehicle mix, highway vehicle and train approach speeds, frequency of trains, and queue lengths.

The highway agency or authority with jurisdiction and the regulatory agency with statutory authority, if applicable, should jointly determine the preemption operation and the timing of traffic control signals interconnected with highway rail grade crossings adjacent to signalized highway intersections.

Support: This text was relocated to new Section 8D.10

Section 4D.27 includes a recommendation that traffic control signals that are adjacent to highway rail-grade crossings and that are coordinated with the flashing light signals or that include railroad preemption-features be provided with a back-up power supply.

Standard: These paragraphs relocated to new Section 8D.10

Information regarding the type of preemption and any related timing parameters shall be provided to the railroad company so that they can design the appropriate train detection circuitry.

If preemption is provided, the normal sequence of traffic control signal indications shall be preempted upon the approach of trains to avoid entrapment of highway vehicles on the highway-rail-grade crossing.

This preemption feature shall have an electrical circuit of the closed-circuit principle, or a supervised communication circuit between the control circuits of the highway-rail grade crossing warning system and the traffic control signal controller. The traffic control signal controller preemptor-shall be activated via the supervised communication circuit or the electrical circuit that is normally energized by the control circuits of the highway-rail grade crossing warning system. The approach of a train to a highway-rail grade crossing shall de-energize the electrical circuit or activate the supervised-communication circuit, which in turn shall activate the traffic control signal controller preemptor. This shall establish and maintain the preemption condition during the time the highway-rail grade crossing warning system is activated, except that when crossing gates exist, the preemption condition shall be maintained until the crossing gates are energized to start their upward movement. When multiple or successive preemptions occur, train activation shall receive first priority.

Guidance: This text was relocated to new Section 8D.12

If a highway rail grade crossing is located within 50 feet (or within 75 feet for a highway that is regularly used by multi-unit highway vehicles) of an intersection controlled by a traffic control signal, the use of presignals to control traffic approaching the grade crossing should be considered.

Standard: This text was relocated to new Section 8D.12

If used, the pre-signals shall display a steady red signal indication during the track clearance portion of a signal preemption sequence to prohibit additional highway vehicles from crossing the railroad track.

Guidance: This text was relocated to new Section 8D.12

Consideration should be given to using visibility limited signal faces (see definition in Section 1A.13) at the intersection for the downstream signal faces that control the approach that is equipped with pre-signals.

Option: This text was relocated to new Section 8D.12

The pre-signal phase sequencing may be timed with an offset from the downstream signalized intersection such that the railroad track area and the area between the railroad track and the downstream signalized intersection is generally kept clear of stopped highway vehicles.

Standard: This text was relocated to new Section 8D.12

If a pre-signal is installed at an interconnected highway-rail grade crossing near a signalized intersection, a STOP HERE ON RED (R10-6) sign shall be installed near the pre-signal or at the stop-line if used. If there is a nearby signalized intersection with insufficient clear storage distance for a design vehicle, or the highway-rail grade crossing does not have gates, a No Turn on Red (R10-11, R10-

1 11a, or R10-11b) sign (see Section 2B.53) shall be installed for the approach that crosses the railroad track, if applicable.

Option:

At locations where a highway rail grade crossing is located more than 50 feet (or more than 75 feet for a highway regularly used by multi-unit highway vehicles) from an intersection controlled by a traffic control signal, a pre-signal may be used if an engineering study determines a need. This text was relocated to new Section 8D.12

If highway traffic signals must be located within close proximity to the flashing light signal system, the highway traffic signals may be mounted on the same overhead structure as the flashing light signals. This text was relocated to new Section 8D.01

Support: These paragraphs relocated to new Section 8D.10

Section 4C.10 describes the Intersection Near a Grade Crossing signal warrant that is intended for use at a location where the proximity to the intersection of a grade crossing on an intersection approach controlled by a STOP or YIELD sign is the principal reason to consider installing a traffic control signal.

Section 4D.27 describes additional considerations regarding preemption of traffic control signals at or near highway rail grade crossings.

Section 8D.10 Preemption of Highway Traffic Signals at or Near Grade Crossings New Section with paragraphs from existing Section 8C.09

Support: Added to improve consistency

Traffic signal preemption for grade crossings is a complex topic that requires a specific understanding of grade crossing warning systems and highway traffic signal operations. While most traffic signal operations are governed only by the traffic signal controller unit and the associated traffic signal equipment, preemption for grade crossings is also governed by the grade crossing warning system. Active grade crossing warning systems include flashing-light signals and possibly automatic gates, as well as various types of train detection equipment. When the traffic signal controller unit is interconnected with the grade crossing warning system for the purpose of preemption, a combined system is created. It is the combined system that requires a thorough understanding of the design and operating parameters in order to provide proper operation of the preemption system.

The Federal Railroad Administration (FRA) has issued two documents that provide additional information relating to preemption of highway traffic signals at or near grade crossings. The first document is "Technical Bulletin S-12-01, Guidance Regarding the Appropriate Process for the Inspection of Highway-Rail Grade Crossing Warning System Pre-emption Interconnections with Highway Traffic Signals" and the second document is "Safety Advisory 2010-02, Signal Recording Devices for Highway-Rail Grade Crossing Active Warning Systems that are Interconnected with Highway Traffic Signal Systems."

Guidance:

If a highway rail grade crossing is equipped with a flashing-light signal system and is located within 200 feet of an intersection or midblock location controlled by a traffic control signal or hybrid beacon, the highway traffic control signal should be provided with preemption in accordance with Section 4D.274F.18.

Coordination with the flashing-light signal system, <u>such as using queue detection and queue cutter signals</u>, or other alternatives, should be considered for <u>highway</u> traffic <u>control</u> signals located farther than 200 feet from the highway-rail grade crossing. Factors to be considered should include traffic volumes, highway vehicle mix, highway vehicle and train approach speeds, frequency of trains, <u>presence of midblock driveways or unsignalized intersections</u>, and <u>queue lengths</u> the potential for vehicular <u>queues resulting from an adjacent downstream grade crossing or highway traffic signal to extend into the minimum track clearance distance (see Section 8A.07).</u>

The highway agency or authority with jurisdiction and the regulatory agency with statutory authority, if applicable, should jointly determine the preemption operation and the timing of <u>highway</u> traffic control signals interconnected with highway rail grade crossings adjacent to signalized highway intersectionslocations.

If a highway traffic signal is installed near a passive grade crossing and traffic is likely to queue onto the tracks, an active grade crossing warning system should be installed at the grade crossing to provide a means

to preempt the highway traffic signal in order to clear vehicles from the minimum track clearance distance (see Section 8A.07) upon approach of rail traffic.

If a highway traffic signal is interconnected with a flashing-light signal system, the flashing-light signal system should be provided with automatic gates to prevent additional vehicles from being drawn into the minimum track clearance distance (see Section 8A.07) during the track clearance interval prior to the arrival of rail traffic unless a Diagnostic Team determines otherwise.

The highway agency or authority with jurisdiction, and the regulatory agency with statutory authority, if applicable, and the railroad company or transit agency should jointly inspect and verify the preemption operation, the amount of warning time and/or advanced preemption time being provided by the grade crossing warning system, and the timing of highway traffic signals interconnected and/or coordinated with the flashing-light signals at least once per year. Paragraphs added to improve clarity and consistency

Support:

 Section <u>4F.194D.27</u> includes a recommendation that traffic control signals that are adjacent to highway-rail grade crossings and that are coordinated with the flashing-light signals <u>at the grade crossing</u> or that include railroad preemption features be provided with a back-up power supply.

Standard:

Information regarding the type of preemption and any related timing parameters shall be provided to the railroad company <u>or transit agency</u> so that <u>they the railroad company or transit agency</u> can design the appropriate train detection circuitry.

If preemption is provided, <u>unless otherwise determined by a Diagnostic Team</u>, the normal sequence of <u>traffic control highway traffic signal</u> indications shall be preempted upon the approach of <u>through</u> trains to <u>avoid entrapment of provide a track clearance interval to provide an opportunity for highway vehicles on at the <u>highway-rail</u> grade crossing <u>to clear the minimum track clearance distance (see Section 8A.07)</u> prior to the arrival of rail traffic.</u>

Where a flashing-light signal system is in place at a grade crossing, any highway traffic signal faces installed within 50 feet of any rail shall be preempted upon the approach of rail traffic. The highway traffic signal faces that control movements across the grade crossing shall display RED indications in accordance with Section 4F.18 in order to avoid the display of signal indications that conflict with the flashing-light signal system. Added to improve consistency

Guidance:

Where a flashing-light signal system is in place at a grade crossing, the operation of any flashing yellow beacon installed within 50 feet of any rail should be considered by a Diagnostic Team to determine whether the operation of the beacon should be terminated during the approach and passage of rail traffic. Added to improve consistency

Standard:

This The preemption feature special control mode shall have an electrical circuit of the closedeireuit principle, or be activated by a supervised communication circuit preemption interconnection using fail-safe design principles (such as "1570-2002 - Institute of Electrical and Electronics Engineers Standard for the Interface Between the Rail Subsystem and the Highway Subsystem at a Highway Rail Intersection") between the control circuits of the highway-rail-grade crossing warning system and the traffic control signal controller unit. The traffic control signal controller preemptor shall be activated via the supervised communication circuit or the electrical circuit that is normally energized by the control circuits of the highway rail grade crossing warning system. The approach of a train rail traffic to a highway-rail-grade crossing shall de-energize the electrical circuit or activate the supervised communication circuit the interconnection or send a message via a fail-safe data communication protocol, which in turn shall activate the traffic controller preemptor preemption sequence. This shall establish and maintain the preemption condition during the time the highway railgrade crossing warning system is activated, except that when automaticerossing gates exist, the preemption condition shall not be maintained until terminated until the automatic erossing gates are energized to start their upward movement. When multiple or successive preemptions occur, trainactivation shall receive first priority.

Support: The following paragraphs added to improve clarity and consistency

The right-of-way transfer time is the amount of time needed prior to display of the track clearance interval. This includes any time needed by the railroad, light rail transit, busway, or highway traffic signal control equipment to react to a preemption call, and any traffic control signal green, pedestrian walk and clearance if used (see Section 4F.18), yellow change, and red clearance intervals for conflicting traffic.

A supervised preemption interconnection is one that incorporates both a normally-open and a normally-closed circuit from the grade crossing warning system to verify the proper operation of the interconnection.

Option:

<u>Instead of supervision, a double-break preemption interconnection circuit that uses two normally-closed circuits that open both the source and return energy circuits may be used.</u>

A preemption interconnection may incorporate both supervision and double-break circuits.

Guidance:

Where train detection circuits are present at a passive grade crossing, the operation of the preemption interconnection should be treated as if active traffic control devices exist at the crossing and the preemption operation should be determined by a Diagnostic Team.

Where left turns are permitted at a downstream highway-highway traffic control signal from the roadway approach that crosses the track and a delayed or impeded left-turn movement could prevent vehicles from clearing the track, a protected left-turn movement should be provided during the track clearance interval if green signal indications are displayed to the approach for track clearance.

The decision to implement simultaneous or advance preemption should include consideration of the right-of-way transfer time, the queue clearance time, and the separation time in order to determine the maximum preemption time. These time periods should be compared to and verified with the operation of the grade crossing traffic control devices in order to evaluate the operation of the highway traffic signal and the preemption operation. These factors should be considered regardless of whether simultaneous or advance preemption operation is implemented as they are based on traffic signal minimum timing, vehicle acceleration characteristics, and physical distances along the roadway.

Support:

Preemption time variability occurs when the traffic signal controller enters the preemption clearance interval with less than the maximum design right-of-way transfer time or when the speed of a train approaching the grade crossing varies.

The time interval between the initiation of advance preemption and the operation of the grade crossing warning system for rail traffic will decrease in situations when rail traffic is accelerating.

Guidance:

Where preemption is used and automatic gates are present, the possibility that an automatic gate might descend upon a vehicle should be analyzed.

If simultaneous preemption is used, an analysis of extended grade crossing warning times should be conducted, as this condition is frequently encountered with simultaneous preemption operation.

If advance preemption is used, an analysis of preemption operation and sequencing should be conducted to identify preemption time variability. The analysis should include both the condition requiring the longest amount of time to enter the track clearance interval and the condition requiring the shortest amount of time to enter the track clearance interval.

Support:

The condition requiring the shortest amount of time to enter the track clearance interval occurs when the currently-displayed signal indications are the same as the track clearance interval signal indications.

Standard:

Where automatic gates are present and green signal indications are displayed at the downstream traffic control signal during the track clearance interval, the preemption sequence shall be designed such that the green signal indications are not terminated until the automatic gate(s) that controls access over the grade crossing towards the downstream intersection is fully lowered.

49 Support

The following are two examples of mutually-exclusive methods to resolve preemption time variability:

- A. Gate down circuitry provides a means to hold the traffic signal controller sequence in the track clearance interval until the automatic gate(s) that controls access over the grade crossing towards the downstream intersection is fully lowered.
- B. Timing correction resolves preemption time variability by adding the right-of-way transfer time to the track clearance interval in the traffic signal controller unit and setting a fixed maximum period of time between the start of advance preemption and the operation of the flashing-light signals.

Standard:

Where gate down circuitry is used to resolve preemption time variability and an automatic gate is broken or is not fully lowered, the crossing control circuits shall not terminate the track clearance interval before the rail traffic has entered the grade crossing.

Where timing correction is used to resolve preemption time variability, a timing circuit shall be used to maintain a maximum time interval between the initiation of advance preemption and the operation of the grade crossing warning system when the approaching rail traffic is decelerating.

Guidance:

When a highway-highway intersection controlled by traffic control signals is interconnected with a grade crossing equipped with exit gates, advance preemption should be used because of the additional operating time that is required for the exit gates.

Where rail traffic routinely stops and re-starts within or just outside of the approaches to a grade crossing that is interconnected with highway traffic signals, the effects of rail traffic operations on the preemption operation should be analyzed.

Highway traffic signal control equipment should be capable of providing immediate re-service of successive requests for preemption from the railroad warning devices, even if the initial preemption sequence has not been completed. As appropriate, the highway traffic signal control equipment should be able to promptly return to the start of the track clearance interval at any time that the demand for preemption is cancelled and then reactivated. The highway traffic signal control equipment should have the ability to provide this immediate re-service at any point in the preemption sequence.

Standard:

Where traffic control signals are programmed to operate in a flashing mode during the preemption dwell interval (the period following the track clearance interval that lasts for the duration of the preemption interconnection activation), the beginning of the preemption dwell flashing mode shall not occur until the grade crossing equipment indicates that the rail traffic has entered the grade crossing.

At locations where conflicting preemption calls might be received to serve boats and trains, the Diagnostic Team shall determine which mode shall receive first priority when conflicting preemption calls occur. Where the boat and the train do not conflict with each other, the Diagnostic Team shall determine the preemption sequence when both preemption calls are occurring simultaneously. The United States Coast Guard or other appropriate authority that regulates the operation of the waterway shall be invited to participate on the Diagnostic Team and/or to provide input to the Diagnostic Team.

Support:

Section 4C.10 describes the Intersection Near a Grade Crossing signal warrant that is intended for use at a location where the proximity to the intersection of a grade crossing on an intersection approach controlled by a STOP or YIELD sign is the principal reason to consider installing a traffic control signal.

Section 4D.274F.19 describes additional considerations regarding preemption of traffic control signals at or near highway-rail-grade crossings.

Section 8B.08 8D.11 Turn Restrictions Movements Prohibited During Preemption This section has been relocated from existing Section 8B.08 and edited

46 Guidance:

At a signalized intersection that is located within 200-100 feet of a highway rail grade crossing,—measured from the edge of the track to the edge of the roadway, where and the intersection traffic control signals are preempted by the approach of a trainrail traffic, all existing permissive turning movements toward the highway rail grade crossing should be prohibited, steady red arrow signal indications should be shown to all existing protected-only turning movements toward the grade crossing, and red signal indications should be

shown to the straight-through movement toward the grade crossing during the signal preemption sequences.
 The prohibition of a permissive turning movement toward the grade crossing should be accomplished through the installation of a blank-out turn prohibition (R3-1a or R3-2a) sign. Edited to improve consistency

Option: Paragraphs added to improve consistency

All movements toward the track may be prohibited at a signalized intersection that is preempted by the approach of rail traffic, even if the clear storage distance is more than 100 feet.

Support:

Including the word "TRAIN" as part of the blank-out turn prohibition sign informs road users that the turn prohibition being displayed by the sign is in effect because rail traffic is approaching or occupying a nearby rail grade crossing, and that the turn prohibition will be terminated after the rail traffic has cleared the grade crossing.

Rail operations can include the use of activated blank-out turn prohibition (R3-1a or R3-2a) signs at unsignalized highway-highway intersections in the vicinity of grade crossings, such as where a semi-exclusive or mixed-use alignment is within or parallel to the roadway where road users are normally permitted to turn across the tracks.

Option: Deleted; replaced with Option and Support paragraphs above

A blank out or changeable message sign and/or appropriate highway traffic signal indication or other similar type sign may be used to prohibit turning movements toward the highway rail grade crossing during preemption. The R3-1a and R3-2a signs shown in Figure 8B-1 may be used for this purpose.

Support:

LRT operations can include the use of activated blank out sign technology for turn prohibition signs. The signs are typically used on roads paralleling a semi-exclusive or mixed use LRT alignment where road users might turn across the LRT tracks. A blank out sign displays its message only when activated. When not activated, the sign face is blank.

Guidance:

An LRT-activated blank-out turn prohibition (R3-1a or R3-2a) sign should be used where an intersection adjacent to a highway LRT crossing is controlled by STOP signs, or is controlled by traffic control signals with permissive turn movements for road users crossing the tracks. all three of the following conditions are present:

- A. There is no active warning system for the LRT grade crossing, and
- <u>B. Vehicles travelling along a parallel roadway would normally be permitted to turn left or right to travel across tracks that are located within 100 feet of the highway-highway intersection or within the median of the intersection, and</u>
- C. The drivers turning at the highway-highway intersection are not controlled by a traffic control signal.

 Edited to improve accuracy and consistency

Option: Deleted; redundant with Paragraphs 1-4

An LRT activated blank out turn prohibition (R3-1a or R3-2a) sign may be used for turning movements that cross the tracks.

As an alternative to LRT activated blank out turn prohibition signs at intersections with traffic control signals, exclusive traffic control signal phases such that all movements that cross the tracks have a steady redindication may be used in combination with No Turn on Red (R10-11, R10-11a, or R10-11b) signs (see Section 2B.53).

Standard:

Blank-out turn prohibition signs that are associated with preemption shall be visible or activated display their message only when the grade crossing restriction is in effect a preemption signal is being received from the railroad or LRT equipment. Edited to improve consistency

47 Support:

The provisions contained in Chapter 2L for blank-out signs are applicable to R3-1a and R3-2a signs.

Added to improve consistency

Section 8D.12 Pre-Signals at or Near Grade Crossings New Section with paragraphs from existing Section 8C.09 and edited to improve consistency

Guidance:

1 2

If a highway rail grade crossing is located within 50 feet (or within 75 feet for a highway that is regularly used by multi-unit highway vehicles) of in close proximity to an intersection controlled by a traffic control signal and the clear storage distance is less than the design vehicle length, the use of pre-signals to control traffic approaching the grade crossing in the direction towards the intersection should be considered.

If a grade crossing equipped with flashing-light signals, but without automatic gates, is located within 200 feet of an intersection controlled by a traffic control signal, a pre-signal should be provided.

Standard:

If used, the Pre-signals faces shall display a steady red signal indication during the track clearance portion interval of a the signal preemption sequence to prohibit additional highway vehicles from erossing the railroad track entering the minimum track clearance distance (see Section 8A.07).

Pre-signal faces shall not display green signal indications when the grade crossing flashing-light signal system is displaying flashing red indications.

Guidance:

Consideration should be given to using visibility-limited signal faces (see definition in Section <u>1A.131C.02</u>) at the intersection for the downstream signal faces that control the approach that is equipped with pre-signals.

A traffic control signal that is located downstream from a pre-signal should be evaluated for measures during normal (non-preempted) signal phasing that would minimize the possibility of left-turn vehicles queuing across the minimum track clearance distance (see Section 8A.07), such as providing an additional left-turn lane, reducing the cycle length, using split phasing or a lagging left-turn phase, and/or providing an extended green interval for the approach.

Option:

The duration of the extended green interval may be adjusted by vehicle detection located between the presignal and the downstream signalized intersection.

The pre-signal phase sequencing may be timed with an offset from the downstream signalized intersection such that the pre-signal's green signal indication terminates prior to the downstream intersection's green signal indication to minimize the possibility of stopping highway vehicles within the railroad track area and the area between the railroad track and the downstream signalized intersection minimum track clearance distance (see Section 8A.07) and the clear storage distance is generally kept clear of stopped highway vehicles.

Standard:

If pre-signals are used, the queue clearance time (see Section 8D.10) shall be long enough to allow a design vehicle of maximum length stopped just inside the minimum track clearance distance (see Section 8A.07) to start up and move through the intersection, or to clear the tracks if there is sufficient clear storage distance. Added to improve consistency with Queue Clearance Time definition in Part 1 Support:

The storage area for left-turn and right-turn lanes at signalized intersections that are downstream from grade crossings sometimes extends from the signalized intersection back to and across the grade crossing. In such cases, drivers that are in the turn lane are required to make a straight-through movement when they cross the track(s) and then are required to make a turning movement when they reach the downstream signalized intersection.

Guidance:

A separate pre-signal face for the left-turn lane and/or right-turn lane should be provided in addition to the pre-signal signal faces provided for the through movement where both of the following conditions are met:

A. The storage area for the turn lane extends from the downstream signalized intersection back to and across the grade crossing, and

B. The green interval for the turning movement at the downstream intersection does not always begin and end simultaneously with the green interval for the adjacent through movement at the downstream intersection.

Standard:

All of the signal faces at a pre-signal shall be capable of displaying the following signal indications: CIRCULAR RED, CIRCULAR YELLOW, and straight-through GREEN ARROW. Left-turn GREEN ARROW, right-turn GREEN ARROW, and CIRCULAR GREEN signal indications shall not be used in pre-signal faces.

If a separate signal face is provided at a pre-signal for a left-turn and/or right-turn lane that extends from the downstream signalized intersection back to and across the grade crossing, the separate signal face shall be devoted exclusively to controlling traffic in the turn lane and:

- A. Shall be visibility-limited from the adjacent through movement, or
- B. A LEFT (RIGHT) LANE SIGNAL (R10-10b) sign shall be mounted adjacent to the separate signal face controlling traffic in a single turn lane or in the turn lane that is farthest from the adjacent through lane(s) if multiple turn lanes are present for a particular turning movement, and a LEFT (RIGHT) TURN LANE SIGNAL (R10-10c) sign shall be mounted adjacent to the separate signal face controlling traffic in the other turn lanes if multiple turn lanes are present for a particular turning movement.

Support:

Because the signal faces at a pre-signal do not always display the same signal indications as the downstream signalized intersection, the approach to the pre-signal is considered to be a separate approach from the approach to the downstream signalized intersection. This means that the provisions in Sections 4D.04 through 4D.07 regarding the number of signal faces, the visibility and aiming of the signal faces, and the lateral and longitudinal positioning of the signal faces apply separately to the approach to the pre-signal.

The provisions in Section 4D.06 regarding the lateral positioning of separate turn signal faces are applicable to the separate signal faces that are provided at pre-signals for a turn lane that extends from the downstream signalized intersection back to and across the grade crossing.

Standard Guidance: Standard changed to Guidance

If a pre-signal is installed at an interconnected highway-rail grade crossing near a signalized intersection, A STOP HERE ON RED (R10-6 or R10-6a) sign shall should be installed near at the pre-signal's or at the stop line if used.

Standard:

If there is a nearby pre-signal is installed upstream from a signalized intersection—with insufficient clear storage distance for a design vehicle, or the highway-rail grade crossing does not have gates, a No Turn on Red (R10-11, R10-11a, or R10-11b) sign (see Section 2B.5464) shall be installed at the downstream intersection for the approach that crosses the railroad track; if applicable turns on red would otherwise be permitted.

Option:

DO NOT STOP ON TRACKS (R8-8) signs may be installed in conjunction with a pre-signal.

At locations where a highway rail grade crossing is located more than 50 feet (or more than 75 feet for a highway regularly used by multi-unit highway vehicles) from an intersection controlled by a traffic control-signal, a pre-signal may be used if an engineering study determines a need.

<u>Pre-signal faces may be located either upstream or downstream from the grade crossing in order to provide the most effective display to road users approaching the grade crossing.</u>

If pre-signal faces must be located within close proximity to the flashing-light signal system, the pre-signal faces may be mounted on the same overhead structure as the flashing-light signals.

Section 8D.13 Queue Cutter Signals at or Near Grade Crossings New Section to improve consistency

49 Support:

A queue cutter signal is a traffic control signal that controls one direction of traffic at a grade crossing to minimize the possibility of vehicles stopping within the minimum track clearance distance (see Section Notice of Proposed Amendments – Part 8 Page 721 of 781 December 2020

8A.07). Although a queue cutter signal has a similar purpose as a pre-signal (see Section 8D.12), the
 difference is that a queue cutter signal is operated independently from the downstream signalized intersection,

whereas a pre-signal is coordinated with the downstream signal.

Option:

At grade crossing locations where the queue from a bottleneck (usually a signalized intersection) that is downstream from the grade crossing frequently extends back to and across the grade crossing, a queue cutter signal may be installed.

A queue cutter signal may be operated in one of the following modes:

- A. Actuated mode the queue cutter signal operation is dependent on downstream detection of a growing queue.
- B. Non-actuated mode the queue cutter signal operates on a time-of-day plan based on anticipated downstream queues. This mode could be similar to the functional operation of a pre-signal.
- C. Variable mode the queue cutter signal operation varies between the actuated mode and the non-actuated mode based on the time of day, on queue detection, or both.

Support:

A pre-signal is generally used where the grade crossing is located less than 200 feet from a downstream signalized intersection. A non-actuated queue cutter signal is generally used where the grade crossing is located between 200 feet and 400 feet from a downstream bottleneck. An actuated queue cutter signal is generally used where the grade crossing is located more than 400 feet from a downstream bottleneck.

Standard:

All of the signal faces at a queue cutter signal shall be capable of displaying the following signal indications: CIRCULAR RED, CIRCULAR YELLOW, and straight-through GREEN ARROW. Left-turn GREEN ARROW, right-turn GREEN ARROW, and CIRCULAR GREEN signal indications shall not be used in queue cutter signal faces.

Option:

Queue cutter signal faces may be located either upstream or downstream from the grade crossing in order to provide the most effective display to road users approaching the grade crossing.

If queue cutter signal faces must be located within close proximity to the flashing-light signal system, the queue cutter signal faces may be mounted on the same overhead structure as the flashing-light signals.

Guidance:

A STOP HERE ON RED (R10-6 or R10-6a) sign should be installed at the queue cutter signal's stop line.

Option:

DO NOT STOP ON TRACKS (R8-8) signs may be installed in conjunction with a queue cutter signal. *Guidance:*

Where a queue cutter signal operates in an actuated mode based on vehicle presence detection, the queue detector should be located to provide adequate distance to detect a growing queue, permit the queue cutter signal to complete any programmed minimum green or yellow change interval time, and then allow a design vehicle that lawfully crosses the queue cutter signal's stop line during the yellow change interval to clear the minimum track clearance distance (see Section 8A.07) before the growing queue extends to the grade crossing.

A queue cutter signal that is operating in an actuated mode and that is displaying CIRCULAR RED signal indications should continue to display CIRCULAR RED signal indications as long as the downstream detection system continues to detect the presence of a vehicular queue at the detection point on the departure side of the grade crossing.

Where a queue cutter signal operates in actuated mode based on vehicle presence detection, consideration should be given to the potential for turning movements between the grade crossing and the downstream bottleneck that could create an intermediate queue of vehicles. Supplemental queue detectors should be considered to detect the formation of these intermediate queues to activate the queue cutter signal.

When a queue cutter signal is always operated in a non-actuated mode based on anticipated queues, consideration should be given to operating the queue cutter signal in a flashing mode at times when the downstream queues are not expected to extend back to and across the grade crossing.

When a queue cutter signal is operated in a non-actuated mode, consideration should be given to
 coordinating the queue cutter signal with adjacent signals to provide for the progressive movement of traffic.
 Option:

When a variable-mode queue cutter signal is operating in the non-actuated mode, the queue detector may be used to extend the display of the CIRCULAR RED signal indication as long as the downstream detection system continues to detect the presence of a vehicular queue at the detection point on the departure side of the grade crossing.

Standard:

A queue cutter signal shall be interconnected with the flashing-light signal system at the grade crossing.

Queue cutter signal faces shall not display green signal indications when the grade crossing flashing-light signal system is displaying flashing red indications.

When a queue cutter signal that is displaying straight-through GREEN ARROW signal indications (when operating in a steady, stop-and-go mode) or flashing CIRCULAR YELLOW signal indications (when operating in a flashing mode) is preempted by the approach of rail traffic, it shall immediately display steady CIRCULAR YELLOW signal indications during the yellow change interval (see Section 4F.17) followed by steady CIRCULAR RED signal indications. The queue cutter signal shall continue to display the steady CIRCULAR RED signal indications until the rail traffic clears the grade crossing and no other rail traffic is detected.

A queue cutter signal operating in an actuated mode shall display straight-through GREEN ARROW signal indications except when it receives an actuation from the downstream vehicle presence detection system or is preempted by the approach of rail traffic. When it receives an actuation from the vehicle presence detection system, the queue cutter signal shall finish timing any active minimum green interval, if used, and then display steady CIRCULAR YELLOW signal indications during the yellow change interval (see Section 4F.17) followed by steady CIRCULAR RED signal indications. When no preemption call is present and the queue length is such that no vehicles are detected in the detection zone of the downstream vehicle presence detection system, the queue cutter signal shall finish timing any active minimum red interval, if used, and then return to the display of straight-through GREEN ARROW signal indications.

The failure modes of the queue cutter signal control system and vehicle presence detection circuitry shall be evaluated and accounted for in the design of any such system. Fail-safe design techniques shall be used in the system design. The vehicle presence detection system shall incorporate health monitoring and self-check operation to validate the proper functioning of the system. If the queue detector fails to properly self-check or the health circuit indicates a fault, the queue cutter signal shall display flashing CIRCULAR RED signal indications until the normal functioning of the system is restored.

Support:

The storage area for left-turn and right-turn lanes at signalized intersections that are downstream from grade crossings sometimes extends from the signalized intersection back to and across the grade crossing. In such cases, drivers that are in the turn lane are required to make a straight-through movement when they cross the track(s) and then are required to make a turning movement when they reach the downstream signalized intersection.

Guidance:

A separate queue cutter signal face for the left-turn lane and/or right-turn lane should be provided in addition to the queue cutter signal faces provided for the through movement where both of the following conditions are met:

- A. The storage area for the turn lane extends from the downstream signalized intersection back to and across the grade crossing, and
- B. The green interval for the turning movement at the downstream intersection does not always begin and end simultaneously with the green interval for the adjacent through movement at the downstream intersection.
- **Standard:** Added to reflect Official Interpretation 8(09)-19(I)

If a separate signal face is provided at a queue cutter signal for a left-turn and/or right-turn lane that extends from the downstream signalized intersection back to and across the grade crossing, the separate signal face shall be devoted exclusively to controlling traffic in the turn lane and:

- A. Shall be visibility-limited from the adjacent through movement, or
- B. A LEFT (RIGHT) LANE SIGNAL (R10-10b) sign shall be mounted adjacent to the separate signal face controlling traffic in a single turn lane or in the turn lane that is farthest from the adjacent through lane(s) if multiple turn lanes are present for a particular turning movement, and a LEFT (RIGHT) TURN LANE SIGNAL (R10-10c) sign shall be mounted adjacent to the separate signal face controlling traffic in the other turn lanes if multiple turn lanes are present for a particular turning movement.

Support:

Because the signal faces at a queue cutter signal do not always display the same signal indications as the downstream signalized intersection, the approach to the queue cutter signal is considered to be a separate approach from the approach to the downstream signalized intersection. This means that the provisions in Sections 4D.04 through 4D.07 regarding the number of signal faces, the visibility and aiming of the signal faces, and the lateral and longitudinal positioning of the signal faces apply separately to the approach to the queue cutter signal.

The provisions in Section 4D.06 regarding the lateral positioning of separate turn signal faces are applicable to the separate signal faces that are provided at queue cutter signals for a turn lane that extends from the downstream signalized intersection back to and across the grade crossing.

While queue cutter signals and queue jumping signals have similar names, their purpose, design, and operation are quite different. Care must be taken to avoid confusion between queue cutter signals used in conjunction with a grade crossing and queue jumping signals used with transit operations.

Section 8D.14 Warning Beacons or LED-Enhanced Warning Signs at Grade Crossings New Section to improve consistency

Option:

Warning Beacons (see Section 4S.03) or LEDs within the legend, symbol, or border of the sign (see Section 2A.20) may be used to supplement warning signs installed at or on an approach to a grade crossing if additional emphasis is desired for the warning sign. The Warning Beacon or LED-enhanced sign may operate continuously or be activated upon the approach or presence of rail traffic.

Support:

Most of the warning signs that are used at or on an approach to a grade crossing warn of physical conditions that exist at the grade crossing regardless of whether rail traffic is approaching or occupying the grade crossing. In these cases, a Warning Beacon or LED-enhanced sign would typically be operated continuously to enhance the conspicuity of the sign.

Some warning signs, such as a BE PREPARED TO STOP (W3-4) sign (see Section 2C.36), if used in advance of a grade crossing and supplemented with a WHEN FLASHING (W16-13P) plaque, provide information that is typically not applicable except when rail traffic is approaching or occupying the grade crossing. Likewise, a special word message sign (see Section 2A.04) with a legend such as TRAIN WHEN FLASHING provides notice of a condition that only exists when rail traffic is approaching or occupying the grade crossing. These signs would not typically be operated continuously, but instead only when the condition is present.

Standard:

If a Warning Beacon or LEDs within the legend, symbol, or border of the sign is activated by the approach or presence of rail traffic in conjunction with a warning sign that includes the legend WHEN FLASHING either on the sign itself or on a supplemental plaque, the activation of the Warning Beacon or LEDs shall be accomplished by a supervised preemption interconnection using fail-safe design principles (see Section 8D.10) between the control circuits of the grade crossing warning system and the Warning Beacon or LED-enhanced sign.

50 Support:

In the event of a system failure, the normal fault state using a fail-safe interconnection for a Warning Beacon or LED-enhanced sign that is activated by the approach or presence of rail traffic at the grade crossing would be for the Warning Beacon or LEDs to operate when no rail traffic is present.

Option:

A Warning Beacon or LED-enhanced sign that is activated by the approach or presence of rail traffic at the grade crossing may continue to operate for a period of time following the passage of the rail traffic to permit the standing queue to dissipate.

Guidance:

If a Warning Beacon or LED-enhanced sign is activated by the approach or presence of rail traffic at the grade crossing, the Warning Beacon or LED-enhanced sign should begin operating prior to the activation of the flashing-light signals at the grade crossing based upon the typical travel time from the location of the Warning Beacon or LED-enhanced sign to the stop line for the grade crossing.

If a Warning Beacon or LED-enhanced sign that is activated by the approach or presence of rail traffic at the grade crossing is operated by commercial AC power, a back-up power system that is capable of providing a minimum operating period sufficient to allow the implementation of alternative traffic control measures should be provided.

Section 8C.10 8D.15 Traffic Control Signals at or Near Highway-LRT Grade Crossings Support:

There are two types of traffic control signals for controlling vehicular and LRT movements at interfaces of the two modes. The first is the standard traffic control signal described in Part 4, which is the focus of this Section. The other type of signal is referred to as an LRT signal and is discussed in Section 8C.118D.16.

Standard:

The provisions of Part 4 and Sections 8C.098D.09 through 8D.13 relating to traffic control signal design, installation, and operation, including interconnection with nearby automatic gates or flashing-light signals, shall be applicable as appropriate where traffic control signals are used at highway-LRT grade crossings.

If traffic control signals are in operation at an LRT grade crossing that is used by pedestrians, bicyclists, and/or other non-motorized road users, an audible device such as a bell shall also be provided and shall be operated in conjunction with the traffic control signals.

Guidance:

When a highway-LRT grade crossing equipped with a flashing-light signal system is located within 200 feet of an intersection or midblock location controlled by a traffic control signal, the traffic control signal should be provided with preemption in accordance with Section 4D.27. This text was relocated to new Section 8A.02

Coordination with the flashing-light signal system should be considered for traffic control signals located more than 200 feet from the crossing. Factors to be considered should include traffic volumes, highway vehicle mix, highway vehicle and LRT approach speeds, frequency of LRT traffic, and queue lengths.

Paragraph deleted; redundant with new Section 8D.10

If the highway traffic signal has emergency-vehicle preemption capability, it should be coordinated with LRT operation.

Where LRT operates in a wide median, highway vehicles crossing the tracks and being controlled by both near and far side traffic signal faces should receive a protected left-turn green phase from the far side signal face to clear highway vehicles from the crossing when LRT equipment traffic is approaching the crossing. Option:

Green indications may be provided during LRT phases for highway vehicle, pedestrian, and bicycle movements that do not conflict with LRT movements.

<u>A</u> traffic control signals may be installed in addition to <u>Four Quadrant Exit</u> Gate systems and automatic gates at a highway-LRT <u>grade</u> crossing if the crossing occurs within a highway-highway intersection and if the <u>installation of the</u> traffic control signals <u>meet can be justified based on</u> the warrants described in Chapter 4C.

At a location other than an intersection, when LRT speeds are less than 25 mph, traffic control signals alone may be used to control road users at highway-LRT grade crossings only when justified by an engineering study a Diagnostic Team.

Support:

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

27

28

29

30

31

32 33

34

35

3637

38

39

40

41

42

43 44

45

46 47

48

Typical circumstances may might include:

- A. Geometric conditions preclude the installation of highway-LRT grade crossing warning devices.
- B. LRT vehicles share the same roadway with road users.
- C. Traffic control signals already exist.

Support:

Section 4D.274F.18 contains information regarding traffic control signals at or near highway-LRT grade crossings that are not equipped with highway-LRT grade crossing warning devices.

Section 4C.10 describes the Intersection Near a Grade Crossing signal warrant that is intended for use at a location where the proximity to the intersection of a grade crossing on an intersection approach controlled by a STOP or YIELD sign is the principal reason to consider installing a traffic control signal.

Guidance:

When a highway-LRT grade crossing exists within a signalized intersection, consideration should be given to providing separate turn signal faces (see definition in Section 1A.131C.02) for the movements crossing the tracks.

Standard:

Separate turn signal faces that are provided for turn movements toward the crossing shall display a steady red indication during the approach and/or passage of LRT traffic.

Guidance:

When a signalized intersection that is located within 200 feet of a highway LRT grade crossing is preempted, all existing turning movements toward the highway LRT grade crossing should be prohibited.

Deleted; redundant with new Section 8D.11

26 Support:

Section <u>8B.088D.11</u> contains information regarding the prohibition of turning movements toward the crossing during preemption.

Part 4 contains information regarding signal phasing and timing requirements.

Section 8C.11 8D.16 Use of Traffic Control LRT Signals for Control of LRT Vehicles at Highway-LRT Grade Crossings

Guidance: Deleted to improve clarity and consistency

LRT movements in semi-exclusive alignments at non-gated grade crossings that are equipped with traffic control signals should be controlled by special LRT signal indications.

LRT traffic control signals that are used to control LRT movements only should display the signal-indications illustrated in Figure 8C-3.

Support:

Section 4D.27 contains information about the use of the signal indications shown in Figure 8C-3 for the control of exclusive bus movements at "queue jumper lanes" and for the control of exclusive bus rapid transit movements on semi-exclusive or mixed use alignments. Relocated to below

Option: Deleted to improve clarity and consistency

Standard traffic control signals may be used instead of LRT traffic control signals to control the movement of LRT vehicles (see Section 8C.10).

Option:

LRT signals <u>indications</u> may be used at grade crossings and at intersections in mixed-use alignments in conjunction with standard traffic control signals where special LRT signal phases are used to accommodate turning LRT vehicles or where additional LRT clearance time is desirable. Relocated from below

Standard: The order of these paragraphs has been reversed

If the LRT crossing control is separate from the intersection control, the two shall be interconnected. The LRT signal phase shall not be terminated until after the LRT vehicle has cleared the crossing or intersection.

If a separate set of standard traffic control signal indications (red, yellow, and green circular and arrow indications) is used to control LRT movements, the indications shall be positioned so they are not visible to motorists, pedestrians, and bicyclists (see Section 4D.1205).

Guidance:

If a signal face used to control LRT movements cannot be positioned where the indications are not visible.

If a signal face used to control LRT movements cannot be positioned where the indications are not visible to road users, the LRT signal indications shown in Figure 8D-3 should be used. Added to improve

10 consistency

9

11

12

13

14 15

16

21

22

23

24

25

26

Standard:

If special LRT signal indications such as those shown in Figure 8D-3 are used, the color of the signal indications shall be white. Added to improve consistency

Option:

If used, individual LRT signal sections may be displayed to form clustered signal faces or multiple LRT signal indications may be displayed in an individual housing.

17 Option:

18 LRT signals may be used at grade crossings and at intersections in mixed use alignments in conjunction with
19 standard traffic control signals where special LRT signal phases are used to accommodate turning LRT
20 vehicles or where additional LRT clearance time is desirable. Relocated to above

Guidance:

LRT signal faces should be separated located at least 3 feet vertically or horizontally from the nearest highway traffic signal face for the same approach by at least 3 feet measured either horizontally perpendicular to the approach between the centers of the signal faces or vertically from the center of the lowest signal indication of the top signal face to the center of the highest signal indication of the bottom signal face. Edited to improve clarity

2728

29

30

31 32

33

34

35

36

37

38

39

40

41 42

43

44

45

47

48

49

Support:

Section 4D.274F.18 contains information about the use of the <u>LRT</u> signal indications shown in Figure 8D-4 for the control of exclusive bus movements at "queue jumper lanes" and for the control of exclusive bus rapid transit movements on semi-exclusive or mixed-use alignments. Relocated from above

Figure 8D-3. Light Rail Transit Signals

Section 8C.12 Grade Crossings Within or In Close Proximity to Circular Intersections

This section has been relocated to new Section 8A.12

Section 8C.13 Pedestrian and Bicycle Signals and Crossings at LRT Grade Crossings

Guidance:

Where LRT tracks are immediately adjacent to other tracks or a road, pedestrian signalization should be designed to avoid having pedestrians wait between sets of tracks or between the tracks and the road. If adequate space exists for a pedestrian refuge and is justified based on engineering judgment, additional pedestrian signal heads, signing, and detectors should be installed (see Section 4E.08). The first sentence of this paragraph was relocated to new Section 8E.10 and the second sentence was relocated to new Section 8E.07

Standard:

When used at LRT crossings, pedestrian signal heads shall comply with the provisions of Section-4E.04. Deleted; redundant with new Section 8E.08

46 Guidance:

Flashing light signals (see Figure 8C-4) with a Crossbuck (R15-1) sign and an audible device should be installed at pedestrian and bicycle crossings where an engineering study has determined that the sight distance is not sufficient for pedestrians and bicyclists to complete their crossing prior to the arrival of the

1	LRT traffic at the crossing, or where LRT speeds exceed 35 mph. This paragraph was relocated to new
2	Section 8E.08
3	If an engineering study shows that flashing-light signals with a Crossbuck sign and an audible device
4	would not provide sufficient notice of an approaching LRT traffic, the LOOK (R15-8) sign (see Figure 8C-4)
5	and/or pedestrian gates should be considered (see Figures 8C-5 through 8C-7). This paragraph was
6	relocated to new Section 8E.08
7	Support:
8	A pedestrian gate is similar to an automatic gate except the gate arm is shorter. Deleted; redundant with
9	new Section 8E.09
10	The swing gate alerts pedestrians to the LRT tracks that are to be crossed. Swing gates are designed to
11	open away from the tracks, requiring users to pull the gate open to cross, but permitting a quick exit from the
12	trackway, and to automatically close. Deleted; redundant with new Section 8E.06
13	Option:
14	Swing gates may be installed across pedestrian and bicycle walkways (see Figure 8C-8). Deleted;
15	redundant with new Section 8E.06
16	Pedestrian barriers at offset crossings may be used at pedestrian and bicycle crossings as passive devices
17	that force users to face approaching LRT before entering the trackway (see Figures 8C-9 and 8C-10). This
18	paragraph was relocated to new Section 8E.06
19	

CHAPTER 8D8E. PATHWAY AND SIDEWALK GRADE CROSSINGS

Section 8D.01 8E.01 Purpose

Support:

Traffic control for pathway <u>and sidewalk</u> grade crossings includes all signs, signals, markings, other warning devices, and their supports at pathway <u>and sidewalk</u> grade crossings and along pathway <u>and sidewalk</u> approaches to grade crossings. The function of this traffic control is to promote safety and provide effective operation of both rail and pathway <u>or sidewalk</u> traffic at pathway <u>or sidewalk</u> grade crossings.

Except as specifically provided in this Chapter, sidewalks are considered to be part of a highway rail or highway LRT grade crossing rather than a pathway grade crossing, and are covered by the provisions of Chapters 8B and 8C rather than by the provisions of this Chapter. However, many of The Other physical treatments that are outlined described in this Chapter that are also applicable to pathways and sidewalks adjacent to highway rail or highway LRT at grade crossings, including such as detectable warnings, swing gates, and automatic gates fencing, provide increased safety for pathway and sidewalk users. Edited to reflect reorganization of Part 8

Crosswalks <u>markings</u> at intersections where pedestrians cross LRT tracks in mixed-use alignments are covered by the provisions of Chapter 3C rather than by the provisions of this Chapter.

Figure 8E-1 illustrates the difference between a pathway grade crossing and a sidewalk grade crossing. A pathway is frequently placed in its own right-of-way on an alignment that is independent of any roadway. If a pathway is built parallel to a roadway, it is physically separated from the roadway by an open space or barrier such that the traffic control devices for the roadway grade crossing do not exert an influence over or provide adequate warning to pathway users. A sidewalk runs parallel to a roadway within the highway right-of-way and is close enough to the edge of the roadway's traveled way that the traffic control devices for the roadway grade crossing can frequently exert an influence over or provide adequate warning to pathway users.

Pathways are typically used by both pedestrians and bicyclists, whereas sidewalks are typically used only by pedestrians.

Added to improve clarity and to support Figure 8E-1

Figure 8E-1. Example of Pathway and Sidewalk Placements

Section 8D.02 8E.02 Use of Standard Devices, Systems, and Practices

Guidance:

The pathway or sidewalk user's ability to detect the presence of approaching rail traffic should be considered in determining the type and placement of traffic control devices at pathway or sidewalk grade crossings.

The traffic control devices, including the appropriate traffic control system to be used, and other physical treatments at a pathway or sidewalk grade crossing should be designed and developed by a Diagnostic Team that includes the public agency with jurisdiction over the pathway or sidewalk and the regulatory agency with statutory authority, if applicable, should jointly determine the need and selection of devices at a pathway grade crossing, including the appropriate traffic control system to be used. Edited to improve consistency with next Guidance in Section 8A.01

At skewed grade crossings, the adjustment, re-alignment, or relocation of existing sidewalk grade crossings should be considered when determining the placement of traffic control devices for roadway users. Edited to improve consistency

Support: Paragraphs added to improve clarity consistency

Pedestrian safety is enhanced when pathways and sidewalks are designed such that they cross the tracks at as close to a right angle as practical. The casters of wheelchairs and the wheels of bicycles could fall into and might be constrained in the flangeway gap at a skewed crossing. The flangeway gap is typically 2.5 inches at LRT grade crossings and 3 inches at railroad grade crossings.

It is desirable that pathways and sidewalks be designed such that they maintain a relatively consistent horizontal alignment and profile from the nearest rail to the detectable warning (if present), from the nearest rail to the stop line (if present), or within 12 feet from the nearest rail, whichever distance is longer, on each approach to the crossing. Providing a pedestrian refuge area in advance of the stop line or the detectable warning surface so that pedestrians have a place to wait while rail traffic approaches and occupies the crossing can be beneficial to pedestrian safety.

When designing new sidewalk grade crossings, placing the sidewalk outside of the area occupied by grade crossing traffic control devices for vehicular traffic is desirable (see Figures 8E-2 and 8E-3). This includes making sure that the counterweights and support arms for the automatic gates for vehicular traffic do not obstruct the sidewalk when the gate is fully lowered.

Additional information regarding the design and alignment of pathways and sidewalks is contained in the "Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" (see Section 1A.05).

Figure 8E-2. Example of Sidewalk Placements Outside of a Grade Crossing Gate (Right Angle)

Figure 8E-3. Example of Sidewalk Placements Outside of a Grade Crossing Gate (Skewed Crossing)

Section 8D.03 8E.03 Pathway and Sidewalk Grade Crossing Signs and Markings Standard:

Pathway grade crossing signs shall be standard in shape, legend, and color.

Traffic control devices mounted adjacent to pathways at a height of less than 8 feet measured vertically from the bottom edge of the device to the elevation of the near edge of the pathway surface shall have a minimum lateral offset of 2 feet from the near edge of the device to the near edge of the pathway (see Figure 9B-1). Relocated to below

The minimum sizes of <u>sidewalk grade crossing signs that are intended to be viewed only by pedestrians and of pathway grade crossing signs shall be as shown in the shared-use path column in Tables 9B-1 and 9C-1. Relocated from below</u>

Guidance: Relocated from below, Standard changed to Guidance, and edited to improve clarity

Pathway grade crossing traffic control devices <u>shall</u> <u>should</u> be located <u>such that no portion of the physical</u> <u>features of the device, including the support hardware, is closer than a minimum of 12 feet from the center of the nearest track.</u>

Standard:

The minimum mounting height for post-mounted signs on adjacent to pathways and sidewalks shall be 4 feet, measured vertically from the bottom edge of the sign to the elevation of the near est edge of the pathway or sidewalk surface (see Figure 9AB-1).

Pathway grade crossing traffic control devices shall be located a minimum of 12 feet from the center of the nearest track, Relocated to above

The minimum sizes of pathway grade crossing signs shall be as shown in the shared-use path-column in Table 9B-1. Relocated to above

When If overhead traffic control devices are used on placed above pathways, the clearance from the bottom edge of the device to the pathway surface directly under the sign or device shall be at least 8 feet.

Guidance:

If overhead traffic control devices are placed above pathways that are used by equestrians, the clearance from the bottom edge of the device to the pathway surface directly under the sign or device should be at least 10 feet. Added to improve consistency

Standard:

If overhead traffic control devices are placed above sidewalks, the clearance from the bottom edge of the device to the sidewalk surface directly under the sign or device shall be at least 7 feet. Added to improve clarity and consistency

Traffic control devices mounted adjacent to pathways at a height of less than 8 feet measured vertically from the bottom edge of the device to the elevation of the nearest edge of the pathway surface shall have a minimum lateral offset of 2 feet from the nearest edge of the device to the nearest edge of the pathway (see Figure 9AB-1). Relocated from above

<u>Traffic control devices mounted adjacent to sidewalks at a height of less than 7 feet measured</u> vertically from the bottom edge of the device to the elevation of the nearest edge of the sidewalk surface

shall have a minimum lateral offset of 2 feet from the nearest edge of the device to the nearest edge of the sidewalk. Added to improve consistency

Guidance:

If pathway users include those who travel faster than pedestrians, such as bicyclists or skaters, the use of warning signs and pavement markings should be installed in advance of the pathway grade crossing (see Figure 8D-18E-4) should be considered.

Option:

The Skewed Crossing (W10-12) sign (see Section 8B.21) may be used at a skewed pathway or sidewalk grade crossing to warn pathway or sidewalk users that the tracks are not perpendicular to the pathway or sidewalk. Added to improve consistency

The LOOK (R15-8) sign may be used at a pathway or sidewalk grade crossing to inform pathway or sidewalk users to look in both directions prior to crossing the track(s). Added to improve consistency and due to deletion of existing Section 8B.17

Guidance:

If a LOOK (R15-8) sign is used at a pathway or sidewalk grade crossing, it should be mounted on a separate post that is further from the pathway or sidewalk than the Crossbuck sign or Crossbuck Assembly.

Added to increase consistency and due to deletion of existing Section 8B.17

Figure 8E-4. Example of Signing and Markings for a Pathway Grade Crossing

Section 8D.04 8E.04 Stop Lines, Edge Lines, and Detectable Warnings

Guidance: Added to improve consistency

If pathway users include those who travel faster than pedestrians, such as bicyclists or skaters, pavement markings should be installed in advance of the pathway grade crossing (see Figure 8E-4).

A stop line should be provided at a pathway grade crossing if the surface where the marking is to be applied is capable of retaining the application of the marking.

Option: Added to improve consistency

A stop line may be provided at a sidewalk grade crossing if the surface where the marking is to be applied is capable of retaining the application of the marking.

Guidance:

If used at pathway <u>or sidewalk</u> grade crossings, the pathway stop line should be a transverse line at the point where a pathway <u>or sidewalk</u> user is to stop. The pathway stop line should be placed at least 2 feet further upstream from the nearest rail than the <u>automatic</u> gate, counterweight, <u>or flashing-light signals</u>, <u>or Crossbuck assembly</u> (if any of these are present) is placed, and at least 12 feet from the nearest rail.

Option:

Edge lines (see Section 3B.069) to delineate the designated user route may be used on the approach to and across the tracks at a pathway grade crossing, a sidewalk at a highway rail or highway LRT grade crossing, or a station crossing to delineate the designated pathway user route if the surface where the marking is to be applied is capable of retaining the application of the marking. Edited to improve consistency

Support:

Edge line delineation can be beneficial where the distance across the tracks is long, commonly because of a skewed grade crossing or because of multiple tracks, or where the pathway <u>or sidewalk</u> surface is immediately adjacent to a traveled way.

Detectable warning surfaces (see Section 3B.18) that contrast visually with adjacent walking surfaces, either light on dark or dark on light, can be used to warn pedestrians about the locations of the tracks at a grade crossing. Information regarding the design and placement of detectable warning surfaces is contained in the "Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" (see Section 1A.1105) contains specifications for design and placement of detectable warning surfaces. Edited to

47 improve consistency

Standard: Edited to improve consistency

Detectable warnings (see Chapter 3C) shall be used at pathway grade crossings where pedestrian travel is permitted and at sidewalk grade crossings and shall extend across the full width of the pathway or sidewalk. **Guidance:** Added to improve consistency and support the dimensions in Figure 8E-5 The width of the detectable warning should be at least 2 feet. Detectable warnings should be placed immediately downstream from the pathway or sidewalk stop line (if a stop line is present) or should be incorporated into and made a part of the stop line. The downstream edge of the detectable warning should be located no less than 12 feet from the center of the nearest track (see Figures 8E-4). If the distance between the centers of two adjacent tracks at a sidewalk or pathway grade crossing is more

If the distance between the centers of two adjacent tracks at a sidewalk or pathway grade crossing is more than 38 feet, additional detectable warnings should be used to designate the limits of the pedestrian refuge area (see Figure 8E-5).

Figure 8E-5. Example of a Refuge Area and the Use of Markings on a Sidewalk Grade Crossing

Section 8D.05 8E.05 Passive Traffic Control Devices for Pathway Grade Crossings Crossbuck Assemblies

Standard:

Except as provided in Paragraph 2, where active traffic control devices are not used Where the nearest edge of a passive pathway or sidewalk grade crossing is located more than 25 feet from the center of the nearest traffic control warning device at a grade crossing, a Crossbuck Assembly (see Figure 8E-6) shall be installed on each approach to a the pathway or sidewalk grade crossing. The distance shall be measured perpendicular to the traveled way from the center of the support post of a Crossbuck Assembly at a passive grade crossing or from the center of the mast of an active traffic control warning device at an active grade crossing to the nearest edge of the pathway or sidewalk surface where it crosses the track(s) (see Figure 8E-2). Edited to improve clarity and support the dimensions in Figure 8E-2

Option:

The A Crossbuck Assembly may be omitted at station crossings and installed on the approaches to a pathway or sidewalk grade crossing that where the nearest edge of the pathway or sidewalk is located within 25 feet or less from of the traveled way center of the nearest traffic control warning device at a highway rail or highway LRT grade crossing. Edited to improve clarity

The Crossbuck Assembly may be omitted at station crossings. This sentence is being retained from Paragraph 2 of existing Section 8D.05

Guidance: These paragraphs relocated to new Section 8E.06

The pathway user's ability to detect the presence of approaching rail traffic should be considered in determining the type and placement of traffic control devices or design features (such as fencing or swinggates).

Nighttime visibility should be considered if design features (such as fencing or swing gates) are used to channelize pathway users.

If automatic gates and swing gates are used, the pathway should be channelized to direct users to the entrance to and exit from the pathway grade crossing.

Standard: This text was relocated to new Section 8E.06

If used, swing gates shall be designed to open away from the track(s) so that pathway users can quickly push the gate open when moving away from the track(s). If used, swing gates shall be designed to automatically return to the closed position after each use.

Option: These paragraphs relocated to new Section 8E.06

When used in conjunction with automatic gates at pathway grade crossings, swing gates may be equipped with a latching device that permits the gate to be opened only from the track side of the gate.

49 Support:

The "Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" (see Section 1A.11) contains information regarding spring hinges and door and gate opening forces for swing gates.

The retroreflective strip on the back of the support may be omitted on the Crossbuck support at a pathway or sidewalk grade crossing. Added to improve clarity

The minimum height, measured vertically from the bottom of the YIELD or STOP sign to the elevation of the near edge of the pathway or sidewalk, of Crossbuck Assemblies installed on pathways or sidewalks shall be 4 feet where the lateral offset to the nearest edge of the sign is at least 2 feet and shall be 7 feet where the lateral offset to the nearest edge of the sign is less than 2 feet (see Figure 8E-6).

The minimum lateral offset, measured horizontally from the nearest edge of the pathway or sidewalk to the nearest edge of the Crossbuck Assembly signs, shall be 0 feet for sidewalks and 2 feet for pathways (see Figure 8E-6).

Figure 8E-6. Example of a Crossbuck Assembly for a Pathway or Sidewalk Grade Crossing

Section 8E.06 Passive Traffic Control Devices – Swing Gates, Fencing, and Pedestrian

Barriers New section with paragraphs relocated from existing Section 8D.05

Guidance:

The pathway <u>or sidewalk</u> user's ability to detect the presence of approaching rail traffic should be considered in determining the type and placement of traffic control devices or design features (such as fencing or swing gates, fencing, and pedestrian barriers).

Nighttime visibility should be considered if design features (such as fencing or swing gates) are used to channelize pathway users. Deleted; redundant with new Support paragraph below

Support: Guidance changed to Support

Standard: Added to support dimensions in Figure 8E-6

If Where automatic gates and swing gates are used, it is desirable to design the pathway or sidewalk should be in a manner that channelizeds to or directs users to the entrance to and exit from the pathway or sidewalk grade crossing.

Standard: Standard changed to Support

If used, Swing gates (see Figures 8E-5, 8E-7, 8E-11, and 8E-12) shall be are designed to open away from the track(s) so that pathway or sidewalk users can quickly push the swing gate open when moving away from the track(s). If used, swing gates shall be designed, and to automatically return to the closed position after each use.

It is important to use retroreflective material, appropriate object markers (see Section 9C.09), and/or signs on swing gates, maze fencing, or pedestrian barriers that are placed at pathway or sidewalk grade crossings. Illumination of such areas can also be beneficial. Added to improve clarity

Option:

When used in conjunction with automatic gates at <u>a</u> pathway <u>or sidewalk</u> grade crossings, swing gates may be equipped with a latching device that permits the <u>swing</u> gate to be opened only from the track side of the <u>swing</u> gate.

Support:

Latching devices that are used on swing gates need to be designed in a manner such that they are operable by all users of the pathway or sidewalk. Added to improve consistency

Guidance:

A swing gate should be equipped with a PUSH TO EXIT (113-2) sign on the track side of the swing gate, and a DO NOT ENTER (R5-1) sign on the side of the swing gate facing away from the tracks. Added to improve consistency

47 Option:

A push bar, kick plate, or similar device may be used on a swing gate. Added to improve consistency

49 Support:

The "Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" (see Section 1A.1105) contains information regarding spring hinges and door and gate opening forces for the design of swing gates and related hardware.

Where fencing (see Figures 8E-7, 8E-8, and 8E-11) is installed to direct pathway or sidewalk users to the grade crossing, it is desirable that this fencing be connected to any continuous existing or new fencing or channelization that has been installed parallel to the track(s) to discourage pedestrians from circumventing the grade crossing. Added to support new figures

Pedestrian barriers at offset crossings may be used at pedestrian and bicycle crossings as passive devices that force or fencing, sometimes referred to as a "maze fencing," direct pathway or sidewalk users to face approaching LRT rail traffic before entering the trackway (see Figures 8C-9 and 8C-10 8E-8). This text was relocated from existing Section 8C.13

Where used, maze fencing or pedestrian barriers need to be designed to permit the passage of wheelchairs and power-assisted mobility devices, and if bicycles are permitted, to permit the passage of dismounted bicyclists with tandem bicycles or bicycles with trailers. Added to improve consistency

Figure 8E-7. Example of Pedestrian Gate and Emergency Exit Gate Placement for a Pathway Grade Crossing

Figure 8E-8. Example of Barriers at a Pedestrian-Only Pathway Grade Crossing

Section 8D.06 8E.07 Active Traffic Control Systems for Pathway Grade Crossings

Standard:

If used at a pathway <u>or sidewalk</u> grade crossing, an active traffic control system <u>(see Section 8D.01)</u> shall include flashing-light signals <u>for on</u> each <u>direction of the pathway.</u> <u>approach to the crossing and</u> a bell or other audible warning device <u>shall also be provided</u>(see Figure 8E-9).

Except as provided in Paragraph 4, at pathway-LRT and sidewalk-LRT grade crossings where
LRT operating speeds on a semi-exclusive alignment exceed 25 mph, active traffic control systems shall
be used. Added to improve consistency with new Section 8D.04

Except as provided in Paragraph 4, at pathway-LRT and sidewalk-LRT grade crossings where LRT operating speeds on a semi-exclusive alignment exceed 40 mph, active traffic control systems, including automatic gates, shall be used. Added to improve consistency with new Section 8D.04 Option:

Separate active traffic control-Flashing-light signals, bells, and other audible warning devices may be omitted at a pathway or sidewalk grade crossings that is are located within 25 feet of the traveled way of a highway rail or highway LRT grade crossing that is equipped with an active traffic control systemwarning device at a grade crossing that is equipped with those devices.

Additional pairs of flashing-light signals, bells, or other audible warning devices may be installed on the active traffic control devices at a grade crossing for pathway or sidewalk users approaching the grade crossing from the back side of those devices. Added to improve consistency

Guidance:

Where railroad or LRT tracks in a semi-exclusive alignment are immediately adjacent to a roadway and if adequate space exists, a pedestrian refuge area or island should be provided between the tracks and the roadway to permit pedestrians to stand clear of the tracks while waiting to cross the roadway and to stand clear of the roadway while waiting to cross the tracks. If adequate space exists for a pedestrian refuge area or island is provided and is justified based on engineering judgment, additional pedestrian features (see Chapter 41), such as signal heads, signing, and detectors, should be installed (see Section 4E.08) in the refuge area or on the island. This text was relocated from existing Section 8C.13

Figure 8E-9. Example of Flashing-Light Assembly for a Pathway or Sidewalk Grade Crossing Standard: These paragraphs relocated to new Section 8E.08

If used at pathway grade crossings, alternately flashing red lights shall be aligned horizontally and the light units shall have a diameter of at least 4 inches. The minimum mounting height of the flashing red lights shall be 4 feet, measured vertically from the bottom edge of the lights to the elevation of the near edge of the pathway surface.

Option:

2 Traffic control devices may be installed between the tracks at multiple track crossings at stations.

Standard:

The mounting height for flashing lights that are installed between the tracks at multiple track crossings at stations shall be a minimum of 1 foot, measured vertically from the bottom edge of the lights to the elevation of the near edge of the pathway surface.

These paragraphs relocated to new Section 8E.09

8 Option:

Automatic gates may be used at pathway grade crossings.

10 Guidance:

If used at a pathway grade crossing, the height of the automatic gate arm when in the down-position should be a minimum of 2.5 feet and a maximum of 4 feet above the sidewalk.

If used, the gate configuration, which might include a combination of automatic gates and swing gates, should provide for full width coverage of the pathway on both approaches to the track.

Standard:

Where a sidewalk is located between the edge of a roadway and the support for a gate arm that extends across the sidewalk and into the roadway, the location, placement, and height prescribed for vehicular gates shall be used (see Section 8C.04).

Guidance:

If a separate automatic gate is used for a sidewalk, the height of the gate arm when in the down-position should be a minimum of 2.5 feet and a maximum of 4 feet above the sidewalk.

If a separate automatic gate is used for a sidewalk at a highway-rail or highway-LRT grade crossing, instead of a supplemental or auxiliary gate arm installed as a part of the same mechanism as the vehicular gate, a separate mechanism should be provided for the sidewalk gate to prevent a pedestrian from raising the vehicular gate.

Section 8E.08 Active Traffic Control Devices – Signals New section with paragraphs from existing Section 8D.06

Support:

Pedestrian signal heads are typically used at highway-highway intersections where pedestrians have an expectation that motorists will sometimes be legally required to yield the right-of-way to them. At grade crossings where rail traffic does not stop, pedestrians will not have the right-of-way yielded to them. Therefore, pedestrian signal heads are not an appropriate traffic control device to use at a pathway or sidewalk grade crossing where rail traffic does not stop. Instead, the universal application of horizontally-aligned, alternately-flashing red lights are the uniform active traffic control device for all grade crossings where rail traffic does not stop including pathway and sidewalk grade crossings.

Added to improve consistency

Standard:

Except as provided in Paragraph 3, pedestrian signal heads as described in Chapter 4I comprised of Upraised Hand and Walking Person symbols shall not be used at a pathway or sidewalk grade crossing. Added to improve consistency

40 Option:

Pedestrian signal heads may be used at a pathway or sidewalk grade crossing where the movement of LRT vehicles is controlled by a traffic control signal or by special LRT signals (see Section 8D.16). Added to improve consistency

Standard:

If used at <u>a</u> pathway <u>or sidewalk</u> grade crossings, alternately flashing red lights shall be aligned horizontally and the light units shall have a diameter of at least 4 inches. <u>For 4-inch diameter light units</u>, the light centers shall be spaced approximately 16 inches apart and, if used, the flashing light unit backgrounds shall be at least 8 inches in diameter. Added to improve consistency

The red signal indications in the flashing-light signal shall flash alternately with each indication flashing at a rate of not less than 35 or more than 65 times per minute. Each indication shall be displayed for approximately the same length of time. The total time of display of each pair of indications shall be the entire operating time. Added to improve consistency

The minimum mounting height of the flashing red lights shall be 4 feet, measured vertically from the bottom edge of the lights to the elevation of the near<u>est</u> edge of the pathway <u>or sidewalk</u> surface.

Option:

 At station, pathway, or sidewalk grade crossings with multiple tracks, traffic control devices may be installed between the tracks at multiple track crossings at stations in compliance with any railroad clearance requirements.

Standard:

The mounting height for flashing lights that are installed between the tracks at multiple track crossings at stations shall be a minimum of 1 foot, measured vertically from the bottom edge of the lights to the elevation of the nearest edge of the pathway surface.

Guidance:

If a subsequent engineering study finds that a flashing-light signal with a Crossbuck sign and an audible device is still not resulting in appropriate pedestrian behavior, consideration should be given to also installing an automatic pedestrian gate (see Section 8E.09).

Flashing-light signals (see Figure &C-48E-9) with a Crossbuck (R15-1) sign and an audible device should be installed at pedestrian and bicycle along semi-exclusive LRT alignments at station, pathway, or sidewalk grade crossings where an engineering study has determined that the sight distance is not sufficient for pedestrians and bicyclists pathway or sidewalk users to complete their crossing prior to the arrival of the LRT traffic at the crossing, or where LRT speeds exceed 35 mph.

This text was relocated from existing Section 8C.13

If an engineering study shows that flashing-light signals with a Crossbuck sign and an audible device would not provide sufficient notice of an approaching LRT traffic, consideration should be given to also installing the LOOK (R15-8) sign (see Figure 8C-4) and/or an automatic pedestrian gates (see Section 8E.09) with appropriate channelization or fencing should be considered (see Figures 8C-5 through 8C-7). This text was relocated from existing Section 8C.13

Section 8E.09 Active Traffic Control Devices – Automatic Pedestrian Gates | New section with paragraphs from existing Section 8D.06

Option:

Automatic <u>pedestrian</u> gates <u>(see Figures 8E-7, 8E-10, 8E-13, and 8E-14)</u> may be used at pathway <u>or sidewalk</u> grade crossings.

Standard:

A pathway or sidewalk grade crossing across tracks where trains are permitted to travel at speeds of 80 mph or higher shall be equipped with a system of automatic pedestrian gates and an escape area with swing gates and fencing installed in the vicinity of the crossing to direct users to the pathway or sidewalk grade crossing (see Figure 8E-7) unless an engineering study determines that other safety treatments for the crossing would be more appropriate. Added to improve consistency

Guidance:

Where automatic pedestrian gates are installed across a pathway or sidewalk at a grade crossing, or where a sidewalk is located between the edge of a roadway and the support for an automatic gate arm that extends across the sidewalk and into the roadway, an emergency escape route (see Figures 8E-5, 8E-7, 8E-11 and 8E-12) should be provided to allow pedestrians to egress away from the track area when the automatic pedestrian gates are activated. Added to improve support new Figures

Standard:

Except as provided in Paragraph 6, automatic pedestrian gate arms shall be provided with at least one red light as shown in Figures 8E-10, 8E-12, 8E-13, and 8E-14. This light shall be continuously illuminated whenever the warning system is active. Added to improve consistency

4	If any red lights in addition to the continuously-illuminated red light that is required in Paragraph
	are provided on the automatic pedestrian gate arm, they shall be installed in pairs and shall be flashed ernately in unison with the other flashing-light units at the crossing. Added to improve consistency
	otion:
<u>U</u> ,	The red light on an automatic pedestrian gate arm may be omitted if the pathway or sidewalk grade
cr	ossing is located within 25 feet of the traveled way at a highway-rail or highway-LRT grade crossing that is
	uipped with active warning devices (see Figure 8E-13). Added to improve consistency
-	Figure 8E-10. Example of Pedestrian Gate Placement at a Pathway or Sidewalk Grade Crossing
	Figure 8E-11. Example of Placement of Pedestrian Gates at a Grade Crossing
	Figure 8E-12. Example of Existing Sidewalk Between the Roadway and a Grade Crossing Gate
	with Optional Swing Gate
	Figure 8E-13. Example of a Separate Pedestrian Gate
G_{i}	iidance:
	If used at a pathway or sidewalk grade crossing, the height of the automatic pedestrian gate arm when in
th	e down position should be a minimum of $\frac{2.5}{3}$ feet and a maximum of 4 feet above the <u>pathway or</u> sidewalk.
	If used at a pathway or sidewalk grade crossing, the gate configuration, which might include a
co	mbination of automatic <u>pedestrian</u> gates and swing gates, should provide for full-width coverage of the
	thway <u>or sidewalk</u> on both <u>each</u> approach es to the track <u>crossing</u> .
St	andard:
	Where a sidewalk is located between the edge of a roadway and the support for an automatic gate
	m that extends across the sidewalk and into the roadway, the location, placement, and height
19	escribed for vehicular gates shall be used (see Section 8D.03).
G	uidance:
	If a separate automatic gate is used for a sidewalk, the height of the gate arm when in the down position
	ould be a minimum of 2.5 feet and a maximum of 4 feet above the sidewalk. Combined with pathway
ł	idance statement above
	Except as provided in Paragraph 11, if a separate automatic <u>pedestrian</u> gate is used for a sidewalk at a
	ghway-rail or highway-LRT grade crossing, instead of a supplemental or auxiliary gate arm installed as a
	rt of the same mechanism as the vehicular gate, a separate mechanism (see Figure 8E-13) should be
	ovided for the sidewalk separate automatic pedestrian gate to prevent a pedestrian from raising so that if a
	destrian manually raises the pedestrian gate arm, it will have no effect on the vehicular gate. Edited to flect Official Interpretation 8(09)-3(I)
	otion:
<u>/</u>	
J.P.	A supplemental or auxiliary pedestrian gate arm installed as a part of the same mechanism as the hicular gate may be used if the operating mechanism is designed to prevent the vehicular gate from being
	sed as a result of a pedestrian manually raising the pedestrian gate arm. Added to reflect Official
	terpretation 8(09)-3(I)
_	A horizontal hanging bar (see Figure 8E-14) may be attached to an automatic pedestrian gate at a pathway
r	sidewalk grade crossing to inform pedestrians who have visual disabilities that the automatic pedestrian
	te is in the down position and to reduce the likelihood that pedestrians will violate a lowered crossing gate.
1	lded to reflect FRA research report Effect of Gate Skirts on Pedestrian Behavior at Highway-Rail
3	rade Crossings
3	<u>uidance:</u>
	If a horizontal hanging bar is attached to an automatic pedestrian gate, the height of the horizontal
	nging bar when in the down position should be a maximum of 15 inches above the pathway or sidewalk.
A	lded to support dimensions in new Figure
	Figure 8E-14. Example of Pedestrian Gate with Horizontal Hanging Bar at a Pathway or
	Sidewalk Grade Crossing
Se	ction 8E.10 Active Traffic Control Devices – Multiple-Track Pathway or Sidewalk Grade

50

Crossings New Section with text from existing Section 8C.13

1 <u>Guidance:</u>

Where <u>railroad or LRT</u> tracks are immediately adjacent to other tracks-<u>or a road</u>, <u>the traffic control</u>

devices that control pedestrian <u>signalization movements</u> should be designed to avoid having pedestrians wait between sets of tracks-<u>or between the tracks and the road</u>.

2

4

5

6

7

8

9 10

11

13

14

15

16

17

18 19

20 21

23

24

25

26

29

30

31

34

35 36

37

38

39

40

41

Section 9A.01 Requirements for Bicyclist Traffic Control Devices General

3 Support:

General information and definitions concerning traffic control devices are found in Part 1. Deleted (Not needed)

Part 9 covers signs, <u>and</u> pavement markings, <u>and highway traffic signals</u> specifically related to bicycle operation on <u>both</u>-roadways, <u>separated bikeways</u>, and shared-use paths. <u>Part 4 contains information on highway traffic signals and bicycle signal faces. Part 6 contains information on work zones for bicycle facilities and the mitigation of bicycle travel through work zones.</u>

Definitions and acronyms pertaining to Part 9 are provided in Sections <u>1A.13-1C.01</u> and <u>1A.14-1C.03</u>. Relocated from Section 9A.03

12 Section 9A.02 Scope Combined with Section 9A.01

Guidance:

Parts 1, 2 3 and 4 should be reviewed for general provisions, signs, pavement markings, and signals.

With only ew exceptions, such as when allowed to ride on a sidewalk or where some bicycle-specific traffic control devices are installed, bicycles are either legally defined as vehicles or give the operator of a bicycle the same into an operator of a motor vehicle.

Designing bievele facilities and the traffic control devices on those facilities in a manner that encourages predictable behavior and compliance with traffic laws can increase public acceptable of bicyclists from other road users. The use, or misuse of traffic control devices for improperly designed bicycle facilities can produce ineffective or counterproductive results.

22 Standard:

The absence of a marked bicycle lane or any of the other traffic control devices discussed in this Chapter on a particular roadway shall not be construed to mean that bicyclists are not permitted to travel on that roadway.

- Section 9A.03 Definitions Relating to Bicycles Combined with Section 9A.01
- 27 Section 9A.04 Maintenance Combined with Section 9A.01
- 28 Guidance:

All signs, signals, and markings, including those on bicycle facilities, should be properly maintained to command respect from both the motorist and the bicyclist. When installing signs and markings on bicycle facilities, an agency should be designated to maintain these devices.

32 Section 9A.05 Relation to Other Documents Section Deleted (not needed)

33 Support:

"The Uniform Vehicle Code and Model Traffic Ordinance" published by the National Committee on Uniform Traffic Laws and Ordinances (see Section 1A.11) has provisions for bicycles and is the basis for the traffic control devices included in this Manual.

Informational documents used during the development of the signing and marking recommendations in Part 9 include the following:

A. "Guide for Development of Bicycle Facilities," which is available from the American Association of State Highway and Transportation Officials (see Page i for the address); and

B. State and local government design guides.

Other publications that relate to the application of traffic control devices in general are listed in Section 43 1A.11.

- 44 Section 9A.06 Placement Authority Section Deleted (not needed)
- 45 Support:

Section 1A.08 contains information regarding placement authority for traffic control devices. 1 2 Section 9A.07 Meaning of Standard, Guidance, Option, and Support Section Deleted (not needed) 3 Support: 4 Paragraph 1 of Section 1A.13 contains information regarding the meaning of the headings Standard, 5 Guidance, Option, and Support, and the use of the words "shall," "should," and "may," Section 9A.08 Colors Section Deleted (not needed) 6 7 Support: 8 Section 1A.12 contains information regarding the color codes. 9 Section 9A.02 Standardization of Application for Signing These paragraphs are from existing Sections 9B.01 and 9B.02 10 11 Support: The instantion of nonstandard signing on bikeways or modifying standard signing in a manner 12 13 inconsistent with Chapter 2A to draw special attention, educate users or the community, or brand a bicycle 14 facility can contribute to public acceptance and enforcement problems. 15 Standard: 16 Bicycle signs shall be standard in shape, legend, and color. 17 All signs shall be retroreflectorized retroreflective for use on bikeways, including shared-use paths, 18 and bicycle lane facilities. 19 Where signs serve both bicyclists and other road users, vertical mounting height and lateral placement shall be as provided in Part 2. 20 21 Standard: Guidance: Standard changed to Guidance 22 Where used on a shared-use path, no portion of a sign or its support shall should be placed less than 2 23 feet laterally from the near edge of the path, or less than 8 feet vertically over the entire width of the shared-24 use path (see Figure 9B-1-9A-1). 25 Mounting height for post-mounted signs on shared-use paths shall-should be a minimum of 4 feet, 26 measured vertically from the bottom of the sign to the elevation of the near edge of the path surface (see 27 *Figure* 9B-1-9A-1). 28 Guidance: 29 Signs for the exclusive use of bicyclists should be located so that other road users are not confused by 30 them. 31 The clearance for overhead signs on shared-use paths should be adjusted when appropriate to 32 accommodate path users requiring more clearance, such as equestrians, or typical maintenance or emergency 33 vehicles. 34 Figure 9A-1. Sign Placement on Shared-Use Paths 35 **Standard:** 36 If the sign or plaque applies to motorists and bicyclists, then the size shall be as shown for 37 conventional roads in Tables 2B-1, 2C-21, or 2D-12. 38 The minimum sign and plaque sizes for signs specific to bicycle-only facilities and shared-use paths 39 shall be those shown in Tables 9B-1, 9C-1, and 9D-1; and shall be used only for signs and plaques 40 installed specifically for bicycle traffic applications. The minimum sign and plaque sizes for bicycle 41 facilities shall not be used for signs or plaques that are placed in a location that would have any 42 application to other vehicles. Table 9A-1. Bicycle Facility Sign and Plaque Minimum Sizes 43

44

Option:

1 Larger size signs and plaques may be used on bicycle facilities when appropriate (see Section 2A.11 2 2A.07). 3 Any diamond-shaped warning sign that is placed such that it is only applicable to bicyclists and 4 pedestrians may be 18" x 18". 5 Guidance: 6 Except for size, the design of signs and plaques for bicycle facilities should be identical to that provided in 7 this Manual for signs and plaques for streets and highways. 8 Support: 9 Uniformity in design of bicycle signs and plaques includes shape, color, symbols, arrows, wording, 10 lettering, and illumination or retroreflectivity retroreflectorization. Section 9A.03 Standardization of Application for Markings These paragraphs are from 11 existing Sections 9C.01 and 9C.02 12 13 Support: 14 Markings indicate the separation of the lanes for road users, assist the bicyclist by indicating assigned travel paths, indicate correct position for traffic control signal actuation, and provide advance information for 15 16 turning and crossing maneuvers. 17 Guidance: 18 Bikeway design guides (see Section 9A.05) should be used when designing markings for bicycle facilities. 19 Paragraph deleted (not needed) 20 **Standard:** 21 Markings used on bikeways shall be retroreflectorized. This paragraph relocated to later in this 22 Section and modified. 23 Guidance: 24 Pavement marking word messages, symbols, and/or arrows should be used in bikeways where 25 appropriate. 26 Consideration should be given to selecting pavement marking materials that will minimize loss of traction 27 for bicycles under wet conditions. Split into two paragraphs for clarity. 28 Standard: 29 Pavement markings on bicycle facilities that must be visible at night shall be retroreflective unless 30 the markings are adequately visible under provided lighting 31 The colors, width of lines, patterns of lines, symbols, and arrows used for marking bicycle facilities 32 shall be as defined in Sections 3A.05, 3A.06, and 3B.20Part 3. 33 Support: 34 Section 3H.06 contains information on green-colored payement for use with certain traffic control 35 devices for bicycles and bicycle facilities. Figures 9B-7 and 9C-1 through 9C-9 show examples of the application of lines, word messages, symbols, 36 37 and arrows on designated bikeways. 38 Option: 39 A dotted line may be used to define a specific path for a bicyclist crossing an intersection (see Figure 9C-1) as described in Sections 3A.06 and 3B.08. This provision was relocated to new Section 9E.03 40 Guidance: 41 Raised pavement mark hould not be used with bicycle lanes or shared-use paths. 42 If used around bicycle facilities, raised pavement markers should not be placed immediately adjacent to 43 44 the travel path of bicycles in a bicycle lane or on a shared-use path. 45 Support:

2	Section 9B.01 Application and Placement of Signs Paragraphs relocated to new Section 9A.02
3	Section 9B.02 Design of Bicycle Signs Paragraphs relocated to new Section 9A.02
4	Figure 9B-1 Regulatory Signs and Plaques for Bicycle Facilities
5	TABLE 9B-1 Bicycle Facility Sign and Plaque Minimum Sizes
6	Section 9B.03 9B.01 STOP and YIELD Signs (R1-1, R1-2)
7	Standard:
8 9	STOP (R1-1) signs (see Figure 9B-2) shall be installed on shared-use paths, separated bikeways, or other bicycle facilities at points where bicyclists are required to stop.
10	YIELD (R1-2) signs (see Figure 9B-2) shall be installed on shared-use paths, separated bikeways, or
11	other bicycle facilities at points where bicyclists have an adequate view of conflicting traffic as they
12	approach the sign, and where bicyclists are required to yield the right-of-way to that conflicting traffic.
13	A STOP sign or a YIELI n shall not be installed in conjunction with a bicycle signal face (see
14	Chapter 4H).
15	Option:
16 17	A 30 x 30-inch STOP sign or a 36 x 36 x 36-inch YIELD sign may be used on shared-use paths for added emphasis.
18	Guidance:
19 20	Where conditions require path users <u>or bicyclists on separated bikeways</u> , but not roadway users, to stop or yield, the STOP or YIELD sign should be placed or shielded so that it is not readily visible to road users.
21 22	When placement of STOP or YIELD signs is considered, priority at a shared-use path/roadway intersection should be assigned with consideration of the following:
23	A. Relative speeds of shared-use path and roadway users,
24	B. Relative volumes of shared-use path and roadway traffic, and
25	C. Relative importance of shared-use path and roadway.
26 27 28	Speed should not be the sole factor used to determine priority, as it is sometimes appropriate to give priority to a high-volume shared-use path crossing a low-volume street, or to a regional shared-use path crossing a minor collector street.
29 30	When priority is assigned, the least restrictive control that is appropriate should be placed on the lower priority approaches. STOP signs should not be used where YIELD signs would be acceptable.
31	Section 9B.02 Except Bicycles Plaque (R3-7bP)
32	Support:
33 34	There are circumstances where it might be appropriate to except bicyclists from regulatory restrictions applied to other traffic.
35	Guidance:
36	Where an engineering study demonstrates that it is appropriate to exempt bicyclists from the provisions of
37	a regulatory sign, the Except Bicycles plaque (R3-7bP) should be used.
38	Support:
39	Figure 9B-2 shows examples of how the Except Bicycles plaque can be applied.
40	Section 9C.05 contains information regarding the Except Bicycles plaque when applicable to a warning
41	<u>sign.</u>
42	Standard:
43	The Except Bic splaque shall not be used to circumvent the legal requirement of a STOP or
44 45	YIELD sign, Yield Here To Pedestrians Signs, Stop Here For Pedestrians Signs, or a traffic signal
45	indication.

1 Where a regulatory sign, such as the No Left Turn (R3-2) sign (see Section 2B.28), is not in conflict 2 with a Stop sign or a Yield sign and is installed to the same post or mounting as the Stop sign or Yield 3 sign, the Except Bicycles plaque shall not be installed in conjunction with the regulatory sign to that 4 post or mounting that includes the Stop sign or Yield sign. 5 The Except Bicycles plaque shall be placed below the regulatory sign to which it supplements. Figure 9B-2 Example of Applications of the Except Bicycles Regulatory Plaque (Sheet 1 of 6 7 8 Figure 9B-2 Example of Applications of the Except Bicycles Regulatory Plaque (Sheet 2 of 9 10 Section 9B.03 Advance Intersection Lane Control Signs for Bicycle Lanes (R3-8 Series) 11 Option: 12 Advance Intersection Lane Control (R3-8 Series) signs (see Section 2B.32) may display the arrangement 13 of a conventional, buffer-separated, or separated bicycle lane in relation to other lanes in the same direction 14 that are present on a roadway approach to an intersection. 15 Support: 16 The number and combination of permissible movements by both the motor vehicle and the bicycle on the 17 same approach to an intersection might be practically limited by the amount of information that can be legibly 18 displayed on signs or in signing sequences and still be readily comprehended by road users. The excessive 19 display of all movements by more than one mode can result in unwieldy signs that are difficult to locate and 20 install. 21 Guidance:

On an approach to an intersection with complex geometry that can include multiple through lanes and multiple turn lanes and also includes a bicycle lane, consideration should be given to displaying all allowable movements on separate signs, such as using Mandatory Movement Lane Control (R3-5) signs (see Section 2B.29) for the through lanes and Mandatory Movement Lane Control (R3-7) signs (see Section 2B.30) for the turn lanes, and guide signs for bicycle routes (see Section 9D.02 through 9D.07) and Bicycle Route Sign Auxiliary plaques (see Section 9D.08) for the bicycle movement.

Standard:

22

23

24

25

26

27

28

29

30

31

32

33

3435

36

37

38

39

40 41

42

The portion of the sign face for the bicycle lane shall be limited to the relationship of the bicycle lane to other lanes on the roadway approach to the intersection. The portion of the sign face for the bicycle lane shall not be modified to display specific, supplementary information about the bicycle lane such as bicycle lane extensions, contiguous buffer spaces, or other ancillary bicycle operations such as two-stage turn boxes or bicycle boxes.

Counter-flebicycle lanes shall not be displayed on Advance Intersection Lane Control signs.

Lanes shared between motor vehicles and bicycles and/or the shared-lane marking shall not be displayed on Advance Intersection Lane Control signs.

Physically-separated bikeways shall not be displayed on Advance Intersection Lane Control signs.

Advance In section Lane Control signs that display the bicycle lane shall use a contrasting white legend on a blan background for the bicycle lane. The portion of the display for the bicycle lane shall not use the color green on the sign face in an attempt to be consistent with green-color pavement that may be present on the intersection approach.

- Section 9B.04 Bike Lane Signs and Plaques (R3-17, R3-17aP, R3-5hP)
- 43 **Standard:**

The BIKE LANE (R3-17) sign and the R3-17aP and R3-5hP plaques (see Figure 9B-2) shall be used only in conjunction with marked bicycle lanes as described in Sections 9C.04-9E.01, 9E.06, and 9E.07.

46 Guidance:

1 If used, Bike Lane signs and plaques should be used in advance of at the upstream end beginning of the 2 bicycle lane, at and in advance of the downstream end of the bicycle lane., and at periodic intervals along the 3 bicycle lane as determined by engineering judgment based on prevailing speed of bicycle and other traffic, 4 block length, distances from adjacent intersections, and other considerations. Sentence changed from 5

Guidance to Option and edited

6 Option:

7

8

9 10

11

12

16

17

18

24

26

27

28 29

Bike Lane signs and plaques may be used at periodic intervals along the bicycle lane as determined by engineering judgment based on operating speed of bicycle and other traffic, block length, distances from adjacent intersections, and other considerations.

Other regulatory plaques such as BEGIN (M4-14) and END (M4-6) may be used with Bike Lane signs. Support:

Section 2B.35 contains information for the application of BEGIN and END plaques.

Section 9B.03 contains information on displaying the bicycle lane on Advance Intersection Lane Control 13 14 signs.

15 Option:

> Where two or more movements from a bicycle lane is allowed, or where the emphasis of allowed bicycle movements is needed, an Optional Movement Lane Control (see Section 2B.31) sign may be supplemented with a BIKE LANE plaque above the Optional Movement Lane Control sign.

19 Where bicycle lanes are located between travel lanes on intersection approaches or where only a single bicycle movement is permitted from a certain bicycle lane, a Mandatory Movement Lane Control sign (see 20 Section 2B.20) may be supplemented with a R3-5hP plaque to require a bicyclist in a particular bicycle lane at 21 22 an intersection to stay in the same lane and proceed straight through the intersection, or to indicate a required 23 turn from a particular bicycle lane.

Section 9B.05 BEGIN RIGHT TURN LANE YIELD TO BIKES Sign (R4-4)

25 Option:

> Where motor vehicles entering an exclusive right-turn lane must weave across bicycle traffic in bicycle lanes, the BEGIN RIGHT TURN LANE YIELD TO BIKES (R4-4) sign (see Figure 9B-2) may be used to inform both the motorist and the bicyclist of this weaving maneuver (see Figures 9C-1, 9C-4, and 9C-5-9E-3 and <u>9E-4</u>).

30 Guidance:

31 The R4-4 sign should not be used when bicyclists need to move left because of a right-turn lane drop 32 situation.

Section 9B.06 Bicycles May Use Full Lane Sign This section relocated to Section 9B.14 33

34 Section 9B.07 9B.06 Bicycle WRONG WAY Sign and RIDE WITH TRAFFIC Plaque (R5-1b, 35 **R9-3cP**)

36 Option:

37

38

41

42

The Bicycle WRONG WAY (R5-1b) sign and RIDE WITH TRAFFIC (R9-3cP) plaque (see Figure 9B-2) may be placed facing wrong-way bicycle traffic, such as on the left-hand side of a roadway.

39 This sign and plaque may be mounted back-to-back with other signs to minimize visibility to other traffic.

40 Guidance:

> The RIDE WITH TRAFFIC plaque should be used only in conjunction with the Bicycle WRONG WAY sign, and should be mounted directly below the Bicycle WRONG WAY sign.

43 Section 9B.08 9B.07 NO MOTOR VEHICLES Sign (R5-3)

44 Option:

45 The NO MOTOR VEHICLES (R5-3) sign (see Figure 9B-2) may be installed at the entrance to a shared-46 use path.

Section 9B.09 9B.08 Selective Exclusion Signs 1 2 Option: 3 Selective Exclusion signs (see Figure 9B-2) may be installed at the entrance to a roadway or facility to 4 notify road or facility users that designated types of traffic are excluded from using the roadway or facility. 5 6 If used, Selective Exclusion signs shall clearly indicate the type of traffic that is excluded. 7 Support: 8 Typical exclusion messages include: 9 A. No Bicycles (R5-6), 10 B. No Pedestrians (R9-3), 11 C. No Skaters (R9-13), and 12 D. No Equestrians (R9-14), and 13 E. No Snowmobiles (R5-15). 14 Option: 15 Where bicyclists, pedestrians, and motor-driven cycles are all prohibited, it may be more desirable to use 16 the R5-10a word message sign that is described in Section 2B.39 2B.52. Section 9B.109B.09 No Parking Bike Lane Signs (R7-9, R7-9a) 17 18 Standard: 19 If the installation of signs is necessary to restrict parking, standing, or stopping in a bicycle lane, appropriate signs as described in Sections 2B.46 2B.56 through 2B.48 2B.58, or the No Parking Bike 20 21 Lane (R7-9 or R7-9a) signs (see Figure 9B-2) shall be installed. 22 Section 9B.10 Back-In Parking Sign (R7-10) 23 Option: 24 The R7-10 sign (see Section 2B.54) may be used where back-in parking is required by motor vehicles 25 in the presence of a bicycle lane or movement. 26 Support: 27 Angled back-in curb parking is commonly applied on streets where a bicycle lane is present so that 28 the scanning behavior of a motorist typical with the back-in angle parking task, both entering and exiting the 29 parking space, would place a bicyclist in a bicycle lane in a more direct view of the motor vehicle operator. 30 Figure 9B-3 shows an example of where back-in parking signs can be used in conjunction with bicycle 31 lanes. Figure 9B-3. Examples of Applications of Bicycle Facilities Adjacent to Back-In Parking 32 33 Section 9B.11 Bievele Regulatory Signs Bicycles Use Ped Signal (R9-5, R9-6, R10-4, R10-24, 34 R10-25, and R10-26) 35 Option: 36 The Bicycles Use Ped Signal (R9-5) sign (see Figure 9B-2) may be used where the crossing of a street by 37 bicyclists is controlled by pedestrian signal indications. 38 Where it is not intended for bicyclists to be controlled by pedestrian signal indications, the R10-4, R10-39 24, or R10-26 sign (see Figure 9B-2 and Section 2B.52) may be used. Relocated to new Section 9B.19 40 Guidance: 41 If used, the R9-5, R10-4, R10-24, or R10-26 signs should be installed near the edge of the sidewalk in the 42 vicinity of where bicyclists will be crossing the street. Retained below and edited for consistency, and also 43 duplicated to new Section 9B.19

44

Option:

1 If bicyclists are crossing a roadway where In-Roadway Warning Lights (see Section 4N.02) or other 2 warning lights or beacons have been provided, the R10-25 sign (see Figure 9B-2) may be used. Relocated to 3 new Section 9B.19 4 The R9-6 sign (see Figure 9B-2) may be used where a bicyclist is required to cross or share a facility used by pedestrians and is required to yield to the pedestrians. Relocated to new Section 9B.12 5 In order to remind drivers who are making turns to yield to pedestrians or bicyclists, a Turning Vehicles 6 7 Yield to Pedestrians (R10-15) or Left Turns Yield to Bicycles (R10-12b) sign may be used. 8 Guidance: 9 If used, the R9-5 sign should be installed in the vicinity of where bicyclists will be crossing the street. 10 Support: 11 More information on the use of the Left Turns Yield to Bicycles (R10-12b) sign is provided in Section 12 9B.20. Section 9B.12 Bicycles Yield to Peds Sign (R9-6) 13 14 Option: 15 The Bicycles Yield to Peds (R9-6) sign (see Figure 9B-2) may be used at locations where a bicyclist is 16 required to cross or share a facility used by pedestrians and is required to yield to the pedestrians. Relocated from existing Section 9B.11 17 18 **Standard:** 19 Where the Bicycles Yield to Peds sign is supported by a yield line payement marking (see Section 20 3B.19) to establish the yielding point, the sign and the pavement marking shall be installed adjacent to 21 each other. The Bicycles Yie o Peds sign shall not be used in bicycle corridors to establish a programmatic 22 regulation where no yielding point exists. 23 The Bicycles ld to Peds sign shall not be used in conjunction with a STOP or YIELD sign, Yield 24 Here To Pedestrians Sign, or a Stop Here For Pedestrians Sign. 25 26 Support: 27 Figure 9B-4 shows examples of applying the Bicycles Yield to Peds sign with a yield line pavement marking. 28 29 Figure 9B-4 Example of Applications for the Bicycles Yield to Pedestrians Sign 30 Section 9B.12 9B.13 Shared-Use Path Restriction Sign (R9-7) 31 Option: 32 The Shared-Use Path Restriction (R9-7) sign (see Figure 9B-2) may be installed to supplement a solid white pavement marking line (see Section 9C.03 9E.13) on facilities that are to be shared by pedestrians and 33 34 bicycles in order to provide a separate designated pavement area for each mode of travel. The 35 symbols may be switched as appropriate. 36 Guidance: 37 If two-way operation is permitted on the facility for pedestrians and/or bicyclists, the designated 38 pavement area that is provided for each two-way mode of travel should be wide enough to accommodate both 39 directions of travel for that mode. 40 Section 9B.06 9B.14 Bicycles May Use Full Lane Sign (R4-11) 41 Support: 42 The Uniform Vehicle Code (UVC) defines a "substandard width lane" as a "lane that is too narrow for a 43 bicycle and a vehicle to travel safely side by side within the same lane." Relocated from later in this Section

Option:

44

The Bicycles May Use Full Lane (R4-11) sign (see Figure 9B-2) may be used on roadways where no bicycle lanes or adjacent shoulders usable by bicycles are present and where travel lanes are too narrow for bicyclists bicycles and motor vehicles to operate side by side.

The Bicycles May Use Full Lane sign may be used in locations where it is important to inform road users that bicycles might occupy the travel lane.

Section 9C.07-9E.08 describes a Sshared-Llane Mmarking that may be used in addition to or instead of the Bicycles May Use Full Lane sign to inform road users that bicycles bicycles might occupy the travel lane.

Section 9B.15 Bicycle Passing Clearance Sign (R4-19)

10 Option:

4

5

6

7

8

9

11

12

13

14

The Bicycle Passing Clearance (R4-19) sign may be used in jurisdictions that have defined in law or ordinance a specific clearance to be provided by motor vehicles passing bicycles.

The specific clearance displayed on the Bicycle Passing Clearance (R4-19) sign may be adjusted to reflect the applicable law or ordinance.

15 **Standard:**

The Bicycle Passing Clearance (R4-19) sign shall not be used in jurisdictions that do not have a specific passing clearance to be provided by motor vehicles passing bicycles, as defined in law or ordinance.

19 *Guidance*:

20 <u>The Bicycle Passing Clearance (R4-19) sign should not be used on roadways with bicycle lanes or with</u> 21 shoulders usable for bicycle travel.

22 <u>Section 9B.16 Bicycles Use Shoulder Only Sign (R9-21)</u>

23 Option:

26

27

29

30

31

34

35 36

37

38

The Bicycles Use Shoulder Only (R9-21) sign may be used to denote locations on a freeway or expressway where bicycles are permitted, but must remain on an available and usable shoulder.

The On Freeway plaque (R5-10dP) may be used with an appropriate Selective Exclusion sign to denote a prohibition on ramps leading to an adjacent or parallel freeway (see Figure 9B-5).

28 Guidance:

The Bicycles Use Shoulder Only sign should be limited to use on freeways and expressways.

The Bicycles Use Shoulder Only sign should be placed adjacent to the on-ramp or entrance to the freeway at or near the location where the full-width shoulder resumes beyond the entrance ramp taper.

32 Section 9B.17 Signing for Bicycles on Freeways and Expressways

33 **Standard:**

The Bicycles Must Exit (R9-22) sign shall be used in advance of a location where a freeway or expressway becomes prohibited to bicycle travel, and shall be placed in advance of the intersection or ramp prior to the prohibited segment of roadway (see Figure 9B-5). If the Bicycles Must Exit sign is used, a R5-6 No Bicycles sign shall be placed downstream from the intersection or ramp where the prohibited segment of freeway begins.

39 Option:

The Bicycles Must Exit sign may be used below a post-mounted Exit Direction sign.

41 **Standard:**

42 A No Bicycling sign (R5-6) shall be placed downstream from the ramp departure point where the 43 prohibited segment of freeway or expressway begins. The No Bicycling sign shall not be placed below 44 the Exit Gore sign if an Exit Gore sign is used.

45 Support:

1	Section 2B.52 contains information on regulatory signing for prohibiting bicycles from using particular
2	roadways or facilities.
3	Figure 9B-5. Signing for the Termination of Bicycle Access on Freeways and Expressways
4	Section 9B.18 Two-Stage Bicycle Turn Box Regulatory Signing (R9-23 series)
5	Support:
6	Where two-stage bicycle turn boxes are provided in an intersection, the design of an approach to that
7	intersection will determine if the use of a two-stage bicycle turn box is required by bicycles to facilitate a turn
8	Standard:
9	Situations in the a two-stage bicycle turn box is required to facilitate turns shall include, but are
10 11	not limited to those in which:
12	A. A separated bicycle facility is provided where upstream access to a lane used to facilitate turns by motor vehicle traffic is physically inaccessible to bicycles, or
13	B. All turns are prohibited at the intersection, or
14	C. Characteristics of the roadway approach to the intersection (volume, speed, number of lanes,
15	width, presence of rail tracks, etc.) make it practical to prohibit the bicycle from using a lane used by
16	motor vehicle traffic to facilitate turns.
17	Where bicycles are required to use a two-stage bicycle turn box, the Two-Stage Bicycle Turn Box
18	Regulatory sign series (see Figure 9B-6) shall be used.
19 20	Where bicycles are required to use a two-stage bicycle turn box, the All Turns From Bike Lane advance regulatory sign (R9-23) shall be mounted in advance of the intersection, and at least one
21	Bicycle Turn Must Use Turn Box sign (R9-23a, R9-23b) shall be used at the intersection.
22	Where used, the Bicycle Turn Must Use Turn Box sign (R9-23a) shall be mounted on the near side
23	of the intersection.
24	Where used, the Bicycle Turn Must Use Turn Box location sign (R9-23b) shall be mounted on the
25	far side of the intersection.
26	Where use of a two-stage bicycle turn box is optional, a the Two-Stage Bicycle Turn Box guide sign
27	series (D11-20 series, see Section 9D.13) may be used to provide directional information.
28	Option:
29 30	If used, an appropriately sized Street Name (see Section 2D.44) sign (D3-1) may be installed below the All Turns From Bike Lane sign to identify the cross street where the turn box will be available.
31	Support:
32	Section 9E.11 contains information regarding pavement markings for two-stage turn boxes.
33	Figure 9B-6. Example of Regulatory Signing for Two-Stage Bicycle Turn Boxes
34	Section 9B.19 Bicycle Jughandle Signs (R9-24, R9-25, R9-26, and R9-27 Series)
35	Support:
36	Bicycle jughandle turns can allow bicycles to use the traffic control provided for the cross street rather
37 38	than subjecting the bicycle to use the lane provided on the approach to motor vehicle traffic for facilitating a left turn (or right) or U-turn.
39	A bicycle jughandle turn initially made by a left turn would be conceivable for a bicycle lane on the left
40	side of a one-way street or for a counter-flow bicycle lane.
41	Option:
42	An R9-24 series sign may be used where all bicycles are required to use the bicycle jughandle turn in
43	order to facilitate all turns.

(see Figure 9B-7).

44 45

46

An R9-25 series sign may be used where bicycles are required to use a bicycle jughandle turn to facilitate

U and left turns and where right-turning bicycles are exempted or the right turn is not available or possible

An R9-26 series sign maybe used where bicycles are required to use a jughandle to facilitate a U-turn and 1 2 where left- and right-turning bicycles are exempted or the left or right turn is not available or possible. 3 An R9-27 series sign may be used where bicycles are required to use a jughandle to facilitate a left turn 4 and where U- and right-turning are exempted or the U or right turn is not available or possible (see Figure 9B-5 6 The legend RIGHT may be substituted for the legend LEFT on Bicycle Jughandle signs to represent 7 bicycle facilities on the left side of the roadway where facilitating a right turn would be applicable. 8 9 Applications of Bicycle Jughandle signs should be limited to brief independent alignments either through 10 physical separation or islands formed by payement markings. Bicycle Jughandle signs should not be used for the turning movement facilitated by two-stage turn boxes (see Section 9B.17). 11 12 Support: 13 Bicycle jughandle signs are designed to be mounted below conventional guide signs. 14 Section 9D.01 contains information regarding the use of Bicycle Destination signs that can be used for 15 jughandles. Figure 9B-7. Examples of Applications of Bicycle Jughandle Signs (2 sheets) 16 17 **Section 9B.20 Bicycle Actuation Signs (R10-4, R10-22, R10-24, R10-25, and R10-26) Section** created from paragraphs in existing Sections 9B.11 and 9B.13 18 19 Option: 20 Where it is not intended for bicycles to be controlled by pedestrian signal indications, the R10-4, 21 R10-24, or R10-26 sign (see Figure 9B-2 and Section 2B.52-2B.62) may be used. 22 23 If used, the R9-5,-R10-4, R10-24, or R10-26 signs should be installed near the edge of the sidewalk in the 24 vicinity of where bicyclist bicycles will be crossing the street. 25 Option: 26 If bicyclist bicycles are crossing a roadway where In-Roadway Warning Lights (see Section 4N.02 4U.02) 27 or other warning lights or beacons have been provided, the R10-25 sign (see Figure 9B-2) may be used. 28 The Bicycle Detector (R10-22) sign may be installed at signalized intersections where markings are used 29 to indicate the location where a bicycle is to be positioned to actuate the signal (see Section 9E.16). 30 Guidance: 31 If the Bicycle Detector sign is installed, it should be placed at the roadside adjacent to the marking to 32 emphasize the connection between the marking and the sign. 33 Section 9B.21 LEFT TURN YIELD TO Bicycles Sign (R10-12b) 34 Support: 35 The LEFT TURN YIELD TO Bicycles sign is used to emphasize the requirement for motorists to yield to 36 bicycles in situations where the motorist is turning across a bicycle movement that may be unexpected in 37 direction, location, or some other quality that would run counter to the typical bicycle lane. See Section 2B.61. 38 Section 9B.22 Bicycle SIGNAL Signs (R10-40, R10-40a, R10-41, R10-41a, R10-41b) 39 Support: 40

The primary purposes of the Bicycle SIGNAL sign are to inform road users that the signal indications in the bicycle signal face are intended only for bicycles, and to inform bicycles which specific bicycle

42 movements are controlled by the bicycle signal face.

Section 4H.04 contains additional information on bicycle signal signs.

44 **Standard:**

41

43

1 The Bicycle SIGNAL – Man ry Movement (R10-40, R10-40a) sign or the Bicycle SIGNAL – Optional Movement (R10-41. R1 a, or R10-41b) sign, if used, shall require bicycles to turn, shall 2 permit turns where such turns would otherwise not be allowed, shall require a bicycle to stay in the 3 4 same lane and proceed straight through an intersection, or shall indicate allowed movements when a 5 GREEN BICYCLE symbol is displayed on a bicycle signal face. Section 8B.17-9B.23 LOOK Sign (R15-8) This Section relocated from existing Section 8B.17 and 6 7 edited 8 Option: 9 At railroad or LRT grade crossings with shared-use paths or separated bikeways, the LOOK (R15-8) sign 10 (see Figure 8B-1)-may be mounted as a supplemental plaque on the Crossbuck support, or on a separate post in the immediate vicinity of the grade crossing on the railroad or LRT right-of-way. 11 12 Guidance: 13 A LOOK sign should not be mounted as a supplemental plaque on a Crossbuck Assembly that has a 14 YIELD or STOP sign mounted on the same support as the Crossbuck. Section 9B.14-9B.24 Other Regulatory Signs 15 16 Option: 17 Other regulatory signs described in Chapter 2B and Chapter 8B may be installed on bicycle facilities as 18 appropriate. 19 Section 9B.25 General Service Signing for Bikeways 20 21 General Service signs (See Chapter 2I) may be used on bikeways. 22 **Standard:** 23 General Service signs intended for viewing by both bicycles and other road users shall conform to the sizes in Table 2I-1 24 25 Option:

General Service signs intended for the exclusive use of bicycles may be of reduced size.

26

27

1	CHAPTER 9C. WARNING SIGNS AND OBJECT MARKERS
2	
3	Figure 9C-1. Warning Signs and Plaques and Object Markers for Bicycle Facilities
4	Section 9B.15 9C.01 Turn or Curve Warning Signs (W1 Series)
5	Guidance:
6 7	To warn bicyclists of unexpected changes in shared-use path direction, appropriate turn or curve (W1-1 through W1-7) signs (see Figure 9B-3) should be used.
8 9	The W1-1 through W1-5 signs should be installed at least 50 feet in advance of the beginning of the change of alignment.
10	Section 9B.16 9C.02 Intersection Warning Signs (W2 Series)
11	Option:
12 13 14	Intersection Warning (W2-1 through W2-5) signs (see Figure 9B-3) may be used on a roadway, street, or shared-use path in advance of an intersection to indicate the presence of an intersection and the possibility of turning or entering traffic.
15	Guidance:
16 17	When engineering judgment determines that the visibility of the intersection is limited on the shared-use path approach, Intersection Warning signs should be used.
18 19	Intersection Warning signs should not be used where the shared-use path approach to the intersection is controlled by a STOP sign, a YIELD sign, or a traffic control signal.
20	Section 9B.17-9C.03 Bicycle Surface Condition Warning Sign (W8-10)
21	Option:
22 23	The Bicycle Surface Condition Warning (W8-10) sign (see Figure 9B-3) may be installed where roadway or shared-use path conditions could cause a bicyclist to lose control of the bicycle.
242526	Signs warning of other conditions that might be of concern to bicyclists, including BUMP (W8-1), DIP (W8-2), PAVEMENT ENDS (W8-3), and any other word message that describes conditions that are of concern to bicyclists, may also be used.
27	A supplemental plaque may be used to clarify the specific type of surface condition.
28 29	Section 9B.18 9C.04 Bicycle Warning and Combined Bicycle/Pedestrian Signs (W11-1 and W11-15)
30	Support:
31 32 33	The Bicycle Warning (W11-1) sign (see Figure 9B-3) alerts the road user to unexpected entries into the roadway by bicycles, and other crossing activities that might cause conflicts. These conflicts might be relatively confined, or might occur randomly over a segment of roadway.
34 35	Section 9C.07 contains information for Bicycle Cross Traffic Warning plaques that can be used below Stop signs on cross streets or driveways that intersect with unconventional bicycle facilities.
36	Option:
37 38 39 40	The combined Bicycle/Pedestrian (W11-15) sign (see Figure 9B-3) may be used where both bicycles and pedestrians might be crossing the roadway, such as at an intersection with a shared-use path. A TRAIL X-ING (W11-15P) supplemental plaque (see Figure 9B-3) may be mounted below the W11-15 sign.
41 42	A supplemental plaque with the legend AHEAD or XX FEET may be used with the Bicycle Warning or combined Bicycle/Pedestrian sign.
43	Guidance:

If used in advance of a specific crossing point, the Bicycle Warning or combined Bicycle/Pedestrian sign should be placed at a distance in advance of the crossing location that conforms with the guidance given in Table 2C-34.

Standard:

Bicycle Warning and combined Bicycle/Pedestrian signs, when used at the location of the crossing, shall be supplemented with a diagonal downward pointing arrow (W16-7P) plaque (see Figure 9B-3) to show the location of the crossing.

8 Option:

4

5

6

7

9

10

12

13

14

17

18

22

25

27

28

30

31

33

34 35

36

37

38

39

A fluorescent yellow-green background color with a black legend and border may be used for Bicycle Warning and combined Bicycle/Pedestrian signs and supplemental plaques.

11 Guidance:

When the fluorescent yellow-green background color is used, a systematic approach featuring one background color within a zone or area should be used. The mixing of standard yellow and fluorescent yellow-green backgrounds within a zone or area should be avoided.

15 Section 9C.05 Except Bicycles Plaque (W16-20P)

16 Option:

Where it can be advantageous to notify bicyclists that the conditions or hazards depicted by a warning sign are not applicable to bicycles, the Except Bicycles (W16-20P) plaque may be used.

19 Support:

Examples of warning signs where an Except Bicycles plaque can be mounted include DEAD END (W14-1) and NO OUTLET (W14-2) signs (see Section 2C.25).

Sections 2C.57 and 2C.58 contain information on the design of supplemental warning plaques.

23 Section 9C.06 Bicycle Cross Traffic Warning Plaques (W16-21P)

24 **Standard:**

When used, the Bicycle Cross Traffic Warning plaque shall be installed below a STOP sign.

26 Option:

The Bicycle Cross Traffic Warning plaque may be used below STOP signs on cross streets and driveways to alert motor vehicle users of an unexpected bicycle movement.

29 Support

The Bicycle Cross Traffic Warning plaque can help avoid overuse and/or misapplication of other Warning signs such as the Bicycle warning (W11-1) sign.

32 *Guidance*:

The Bicycle Cross Traffic Warning plaque should be used in combination with a STOP sign when a counter-flow or two-way separated bicycle lane has an approach that is counter to the customary scanning behavior of a motorist at the stop sign.

The Bicycle Cross Traffic Warning plaque should be used at isolated locations and should not be used systematically on a bicycle facility that would encounter an excessive number of cross streets, driveways, or other conflict points.

Section 9C.07 Bicycle Lane Ends Warning Sign (W9-5) and Bicycles Merging Sign (W9-5a)

40 Support:

Where a warning sign is appropriate, the Bicycle Lane Ends Warning sign (W9-5) is intended to alert road users that a bicycle lane is ending and that bicycles will share or occupy the travel lane after merging.

43 Option:

The Bicycle Lane Ends Warning sign (see Figure 9C-X) may be used in advance of the end of a bicycle lane to warn that a bicycle lane will be ending.

- 1 The Bicycles Merging sign (W9-5a) may be used where a bicycle merging maneuver may occur. The
 2 Bicycles Merging sign (see Figure 9B-X) may be used in addition to the Bicycle Lane Ends Warning sign
 (W9-5).
- 4 Guidance:

To avoid excessive use of signs, the Bicycle Lane Ends Warning sign should not be used where a bicycle
 lane is dropped on the approach to an intersection and resumes immediately after the intersection.

7 Option:

8

9

14

1516

17 18

19

- A Bicycles May Use Full Lane sign (R4-11) and/or Shared Lane Markings (see Section 9C.07) may be installed downstream of the merge area.
- A W16-2aP Supplemental Warning Plaque may be used to inform road users of the distance to the end of the bicycle lane and/or the bicycle merge.

12 Section 9B.19 9C.08 Other Bicycle Warning Signs

13 Option:

Other bicycle warning signs (see Figure 9B-3) such as PATH NARROWS (W5-4a) and Hill (W7-5) may be installed on shared-use paths to warn bicyclists of conditions not readily apparent.

In situations where there is a need to warn motorists road users to watch for bicyclist bicycles traveling along the highway roadway, the BICYCLE warning sign (W11-1) may be used with the IN ROAD plaque (W16-1P and W16-1aP), the SHARE THE ROAD (W16-1P) plaque (see Figure 9B-3) may be used in conjunction with the W11-1 sign.

20 Guidance:

- If used, other advance bicycle warning signs should be installed at least 50 feet in advance of the beginning of the condition.
- Where temporary traffic control zones are present on bikeways, appropriate signs from Part 6 should be used.
- 25 Option:
- Other warning signs described in Chapter 2C <u>and Chapter 8C</u> may be installed on bicycle facilities as appropriate.
- 28 Section 9B.26-9C.09 Object Markers
- 29 Standard:
- Obstructions in the traveled way of a shared-use path shall be marked with retroreflectorized retroreflective material or appropriate object markers as described in Section 2C.69. Moved from later in Section
- 33 Option:

34

35

36 37

42

- Fixed objects adjacent to shared-use paths may be marked with Type 1, Type 2, or Type 3 object markers-(see Figure 9B-3)such as those described in Section 2C.63. Incorporated into the revision at the beginning of this Section If the object marker is not intended to also be seen by motorists, a smaller version of the Type 3 object marker may be used (see Table 9B-1-9A-1).
- 38 Standard:
- 39 All object markers shall be retroreflective.
- 40 On Type 3 object markers, the alternating black and retroreflective yellow stripes shall be sloped down at an angle of 45 degrees toward the side on which traffic is to pass the obstruction.

Section 9B.20 9D.01 Bicycle Guide Destination Signs (D1-1b, D1-1c, D1-2b, D1-2c, D1-3b, D1-3c, D11-1, D11-1e) Existing Section 9B.20 is separated into two Sections and sequence of paragraphs was changed

Support:

The purpose of Bicycle Destination signs is to deemphasize their messages to motor vehicle traffic when the direction(s) displayed provides access to routes or pathways where the use of motor vehicles is prohibited or discouraged. Examples include:

- A. Bicycles can go in a direction counter to conventional traffic, or
- B. Access to a separated bikeway or shared-use path from a street, or
- C. Access to a bicycle route, or
- D. Bicycles are directed to a lower class of roadway that facilitates a parallel or alternative route otherwise used by motor vehicle traffic to the same destination, or
 - E. Access to a sidewalk that provides connectivity between bicycle facilities.

Section 2D.36 contains information on Destination signs used for when the destinations listed would apply to both motor vehicle and bicycle traffic.

Guidance Standard: Guidance changed to Standard

Because of their smaller size, Bicycle Destination signs <u>should shall</u> not be used as a substitute for vehicular destination signs when the message is also intended to be <u>seen by applicable to motorist motor vehicles</u>.

Option:

Bike Route Guide (D11-1) signs (see Figure 9B-4) may be provided along designated bicycle routes to inform bicyclists of bicycle route direction changes and to confirm route direction, distance, and destination.

If used, Bike Route Guide signs may be repeated at regular intervals so that bicyclists entering from side streets will have an opportunity to know that they are on a bicycle route. Similar guide signing may be used for shared roadways with intermediate signs placed for bicyclist guidance.

Alternative Bike Route Guide (D11-1c) signs may be used to provide information on route direction, destination, and/or route name in place of the "BIKE ROUTE" wording on the D11-1 sign (see Figures 9B-4 and 9B-6). Paragraphs Relocated to new Section 9D.02

Destination (D1-1, D1-1a) signs, Street Name (D3-1) signs, or Bicycle Destination (D1-1b, D1-1c, D1-2b, D1-2c, D1-3b, D1-3c,) signs (see Figure 9B.4) may be installed to provide direction, destination, and distance information as needed for bicycle travel (see Figure 9D-1). If several destinations are to be shown at a single location, they may be placed on a single sign with an arrow (and the distance, if desired) for each name. If more than one destination lies in the same direction, a single arrow may be used for the destinations.

Destination (D1-1, D1-1a) signs (see Section 2D.36) and Street Name (D3-1) signs (see Section 2D.44) may be installed instead of or in addition to Bicycle Destination signs as needed if the Destination or Street Name sign applies to motor vehicles and bicycles.

Guidance:

Adequate separation should be made between any destination or group of destinations in one direction and those in other directions by suitable design of the arrow, spacing of lines of legend, heavy lines entirely across the sign, or separate signs.

Figure 9D-1. Guide Signs and Plaques for Bicycle Facilities (2 Sheets)

Standard:

An arrow pointing to the right, if used, shall be at the extreme right-hand side of the sign. An arrow pointing left or up, if used, shall be at the extreme left-hand side of the sign. The distance numerals, if used, shall be placed to the right of the destination names.

On Bicycle Destination signs, a Except as provided in Paragraph 9, a bicycle symbol shall be placed next to each destination or group of destinations. If an arrow is at the extreme left, the bicycle symbol shall be placed to the right of the respective arrow.

Option:

Option.

5

6 7

8

9

10

11

12 13

14

15

16

17

18

19

20

21

22

2324

25

26

27

28

29

30

31

32

33

34

35

36

3738

39

40

41

42

43

44

45

46

47

48

An oversized bicycle symbol may be displayed as the top line of a Bicycle Destination sign instead of individual bicycle symbols for each of the destination/distance lines.

Standard:

If an arrow is at the extreme left, the bicycle symbol shall be placed to the right of the respective arrow.

Guidance:

Where the arrow is at the extreme right, The the bicycle symbol should be to the left of the destination legend.

Unless a sloping arrow will convey a clearer indication of the direction to be followed, the directional arrows should be horizontal or vertical.

If several individual name signs are assembled into a group, all signs in the assembly should have the same horizontal width.

Support:

Figure 9B-5 shows an example of the signing for the beginning and end of a designated bicycle route on a shared use path. Figure 9B-6 shows an example of signing for an on-roadway bicycle route. Figure 9B-7 shows examples of signing and markings for a shared use path crossing.

Travel times should not be used on Bicycle Destination signs.

Section 9D.02 BIKE ROUTE Guide Signs (D11-1, D11-1c, D11-1d, D11-1e, D11-1f, D11-1g) Relocated paragraphs from existing Section 9B.20

Support:

BIKE ROUTE Guide (D11-1, D11-1d, D11-1e, D11-1f, D11-1g) signs are used where no unique designation of routes is desired. Sections 9D.04 through 9D.07 contain information for Bicycle Route signs where the bicycle route is designated by number, name, or both.

Option:

Bike Route BIKE ROUTE Guide (D11-1) signs (see Figure 9B.4) may be provided along designated non-numbered, unnamed bicycle routes to inform bicyclists of bicycle route direction changes and to confirm route direction, distance, and destination.

If used, <u>Bike Route BIKE ROUTE</u> Guide signs may be repeated at regular intervals so that <u>bicyclist bicycles</u> entering from side streets will have an opportunity to know that they are on a bicycle route. Similar guide signing may be used for shared roadways with intermediate signs placed for <u>bicyclist bicycle</u> guidance.

The <u>Bicycle Route BIKE ROUTE</u> Guide (D11-1) sign (see Figure 9B-4) may be installed where no unique designation of routes is desired. Relocated from existing Section 9B.21

<u>The Alternative Bike Route BIKE ROUTE</u> Guide (D11-1c) signs may be used <u>to display a word legend that provides</u> information on route direction, destination, and/or route name in place of the "BIKE ROUTE" <u>wording word legend</u> on the D11-1 sign (see Figures <u>9B 4-9D-3</u>).

Guidance:

Travel times should not be used on BIKE ROUTE Guide signs.

Support:

Figure 9B-5 shows an example of the signing for the beginning and end of a designated bicycle route on a shared use path. Figure 9B-6 shows an example of signing for an on roadway bicycle route. Figure 9B-7 shows examples of signing and markings for a shared use path crossing. Figure 9D-2 shows examples of guide sign applications for bicycle travel.

Figure 9D-2. Example of Bicycle Guide Signing (2 Sheets)

1	
2	Section 9D.03 BIKE ROUTE Plaque (D11-1bP)
3	Option:
4	The BIKE ROUTE (D11-1bP) plaque may be installed to supplement:
5	A. The Alternative Bike Route Guide (D11-1c) sign (see Section 9D.02), or
5	B. The Bicycle Directional (D11-1a) sign (see Section 9D.11) for use on a shared-use path, or
	C. A Street Name (D3-1) sign (see Section 2D.44).
	When installed above or below a Street Name sign, the D11-1bP supplemental plaque may include a
	bicycle symbol to the left of the BIKE ROUTE legend.
	Standard:
	The bicycle symbol ll not be used on a Street Name sign.
	Where a BIKE ROUTE plaque is used in conjunction with a Street Name sign to identify a street
	that is part of an overall bicycle network, one of the following signs shall also be used systematically to establish the designated bicycle route on the street identified by the BIKE ROUTE plaque:
	A. BIKE ROUTE Guide signs (see Section 9D.02), or
	B. Alternative BIKE ROUTE Guide (D11-1c) sign (see Section 9D.02), or
	C. State or Local Bicycle Route (M1-8, M1-8a) sign (see Section 9D.05), or
	D. Non-Numbered Bicycle Route (M1-8b, M1-8c) sign (see Section 9D.06), or
	E. United States Bicycle Route (M1-9) sign (see Section 9D.07).
	BIKE ROUTE plaques shall not incorporate replicas of the United States Bicycle Route, State or
	Local Bicycle Route, or Non-Numbered Bicycle Route sign to replace or supplement the bicycle symbol.
	Option:
	The BIKE ROUTE plaque and the Street Name sign may be different widths.
	Support:
	Figure 9D-3 shows an example of bicycle guide signing using the BIKE ROUTE plaque.
	Figure 9D-3. Example of Bicycle Route Signing
	Section 9D.04 Numbered Bikeway Systems
	Support:
	The purpose of numbering and signing bikeways and bicycle routes is to identify routes and facilitate
	<u>travel.</u>
	The United States Bicycle Routes are numbered by the American Association of State Highway
	Transportation Officials (AASHTO) upon recommendations of State highway organizations because the
	respective States own these systems. County and local bikeways and bicycle routes are numbered by the
	appropriate authorities.
	Bicycle routes are designated under the presumption that extensive pre-trip planning is done by the bicyclist. Sign systems can therefore be limited to junctions, accomplishing turns, the beginning of routes,
	and route termination points and still achieve the same navigational benefits and advantages. Extensive use o
	reassurance markers are typically not needed.
	Guidance:
	Establishing bicycle route systems described in Paragraph 2 and any other bicycle route system should
	be followed with effective communication between affected jurisdictions. County and local jurisdictions that
	are establishing numbered routes should coordinate with the respective State Department of Transportation.
	Care should be taken to avoid the use of numbers or other designations that have been assigned to U.S. Pipula Postagon at least some state of the same assagnment of the same assigned to u.S.
	<u>Bicycle Routes or other routes in the same geographical region or State. Overlapping numbered route should be kept to a minimum.</u>
	OC NODE TO BE INVESTIGATION

Bicycle routes, which might be a combination of various types of bikeways, should establish a continuous routing. Relocated from existing Section 9B.21

Standard:

All numbered bicycle routes shall be identified by route signs (see Sections 9D.04, Section 9D.05, and Section 9D.07) and auxiliary plaques (see Section 9D.08).

Multiple numbered bicycle route systems shall be given preference in this order: United States, State, and county or local. The preference shall be given by installing the highest priority legend on the top or the left of the sign assembly with other numbered overlapping bicycle routes.

Where applicable, multiple bicycle route systems with concurrency shall be signed in accordance with Figure 9D-4.

Figure 9D-4. Route Signing for Numbered or Named Bicycle Facilities

Guidance: Relocated from existing Section 9B.21

If used, the Bicycle Route or U.S. Bicycle Route signs should be placed at intervals frequent enough locations to keep bicyclists informed of changes in route direction and to remind motorists of the presence of bicyclists.

17 Option:

Bicycle Route or U.S. Bicycle Route signs may be installed on shared roadways, or on shared-use paths, or separated bikeways, to provide <u>navigational</u> guidance for bicyclists.

The Bicycle Route Guide (D11-1) sign (see Figure 9B-4 <u>9D-1</u>) may be installed where no unique designation of routes is desired. Relocated to new Section 9D.02

22 Section 9B.21 9D.05 State or Local Numbered Bicycle Route Signs (M1-8, M1-8a, M1-9)

23 Option:

To establish a unique identification (route designation) for a State or local bicycle route, the Bicycle Route (M1-8, M1-8a) sign (see Figure 9B-4) may be used.

Standard:

The Numbered Bicycle Route (M1-8) sign shall contain a route designation and shall have a green background with a retroreflectorized white legend and border. The Bicycle Route (M1-8a) sign shall contain the same information as the M1-8 sign and in addition shall include a pictograph or words that are associated with the route or with the agency that has jurisdiction over the route. Moved to separate paragraph

The <u>Numbered</u> Bicycle Route (M1-8a) signs shall contain the same information as the M1-8 sign and in addition shall include a pictograph or words <u>on the upper portion of the sign panel</u> that are associated with the route or with the agency that has jurisdiction over the route.

Guidance:

The pictograph or legend on a Numbered Bicycle Route (M1-8a) sign used on a roadway should incorporate a bicycle symbol or a word message that clearly identifies the route as a bicycle route.

Standard:

<u>If a Numbered Bicycle Route (M1-8, M1-8a) sign is used on a roadway, it shall include a bicycle symbol.</u>

Guidance:

If a pictograph is used on the M1-8a sign the maximum dimension (height or width) of the pictograph should not exceed two times the height of the route numeral, and should be contained within a green border. The minimum width of the graphic on the M1-xa or M1-xb sign should be 66% of the panel width, and the maximum width should be 90% of the panel width.

1 If a bicycle symbol is used on the M1-8a sign, it should have a minimum height of 25% of the M1-8a sign 2 panel height. 3 Guidance: 4 Bicycle routes, which might be a combination of various types of bikeways, should establish a continuous 5 routing. Relocated to new Section 9D.04 6 Where a designated bicycle route extends through two or more States, a coordinated submittal by the 7 affected States for an assignment of a U.S. Bicycle Route number designation should be sent to the American 8 Association of State Highway and Transportation Officials (see Page i for the address). Relocated to new 9 Section 9D.07 10 **Standard:** 11 The U.S. Bievele Route (M1-9) sign (see Figure 9B-4) shall contain the route designation as assigned 12 by AASHTO and shall have a black legend and border with a retroreflectorized white background. Relocated to new Section 9D.07 and edited 13 14 Guidance: 15 If used, the Bicycle Route or U.S. Bicycle Route signs should be placed at intervals frequent enough to 16 keep bicyclists informed of changes in route direction and to remind motorists of the presence of bicyclists.= Relocated to new Section 9D.04 and edited 17 18 Option: 19 Bicycle Route or U.S. Bicycle Route signs may be installed on shared roadways or on shared use paths to provide guidance for bicyclists. Relocated to Section 9D.04 and edited 20 21 The Bicycle Route Guide (D11-1) sign (see Figure 9B-4) may be installed where no unique designation of routes is desired. Relocated to new Section 9D.02 and edited 22 23 Section 9D.06 Non-Numbered Bicycle Route Sign (M1-8b, M1-8c) 24 **Standard:** Non-Numbered Bible Route (M1-8b, M1-8c) signs shall have a green background, a white border, 25 and shall include a pictograph or words identifying the route, or both a pictograph and legend. 26 27 Guidance: 28 The pictograph or legend on a Non-Numbered Bicycle Route (M1-8b, M1-8c) sign used on a roadway should incorporate a bicycle symbol or a word message that clearly identifies the route as a bicycle route. 29 30 Support: 31 Bicycle routes are sometimes designated specifically by name or established using a distinctive route 32 identity, but are not numbered or are intentionally excluded from an overall numbered bicycle route system. 33 Section 9D.02 contains information for Bicycle Route signs where no unique designation routes is 34 beneficial or desired. 35 Option: 36 Where a bicycle route is named or not numbered, the Non-Numbered Bicycle Route sign may be used. 37 Support: 38 Certain bicycle route systems can be uninterrupted, long-distance interstate routes that can be largely 39 contained to shared-use paths, or other off-roadway facilities. In order to achieve continuity, these bicycle 40 systems might have to share alignments with urban streets, rural highways, or water crossings. Long-distance interstate bicycle routes can be administered by non-transportation organizations subject to 41 42 independent goals and interests. 43 Guidance: 44 In order to provide signing on a facility managed by a transportation department, a statewide policy for

45

46

encouraging independent organizations to adopt the Non-Numbered Bicycle Route sign should be established.

Section 9D.07 U.S. Bicycle Route Sign (M1-9) Paragraphs relocated from existing Section 9B.21

Guidance:

Where a designated bicycle route extends through two or more States, a coordinated submittal by the affected States for an assignment of a U.S. Bicycle Route number designation should be sent to the American Association of State Highway and Transportation Officials (see Page i for the address).

5 Standard:

The U.S. Bicycle Route (M1-9) sign (see Figure 9B-4) shall contain the route designation as assigned by AASHTO and shall have a black legend and border with a retroreflectorized white background.

Section 9B.229D.08 Bicycle Route Sign Auxiliary Plaques

9 Support:

Section 2D.12 contains additional provisions for the design of route sign auxiliary plaques. Sections 2D.29 through 2D.34 contain additional provisions for the general application of route signs.

Standard:

If a designated or numbered bicycle route is concurrent with a numbered highway, the route sign and auxiliary plaques for the bikeway shall be installed as independent assemblies and shall not be installed with other Route signs or confirmation assemblies for the numbered or named highway.

Route signs for bikeways shall not be installed on guide signs or overhead.

Option: Paragraphs relocated from existing Section 9B.22

Route assemblies for a designated or numbered bicycle route may be installed at locations or distances other than those prescribed in Sections 2D.29 through 2D.34 if engineering judgment indicates that the operation or speed of the bicycle justifies alternate locations or distances.

Auxiliary plaques signs (See Figure 9D-1) may be used in conjunction with Bike Route Guide signs, Bicycle Route signs, or U.S. Bicycle Route signs as needed.

Guidance:

If used, Junction (M2-1), Cardinal Direction (M3 series), and Alternative Route (M4 series) auxiliary plaques signs (see Figure 9B-4) should be mounted above the appropriate Bike Route Guide signs, Bicycle Route signs, or U.S. Bicycle Route signs.

If used, Advance Turn Arrow (M5 series) and Directional Arrow (M6 series) auxiliary plaques signs (see Figure 9B-4)-should be mounted below the appropriate Bike Route Guide sign, Bicycle Route sign, or U.S. Bicycle Route signs.

Except for the M4-8 plaque, all route sign auxiliary signs should match the color combination of the route sign that they supplement.

Route sign auxiliary signs carrying word legends that are used on bicycle routes should have a minimum size of 12 x 6 inches. Route sign auxiliary plaques carrying arrow symbols that are used on bicycle routes should have a minimum size of 12 x 9 inches.

Standard:

If both the Junction (M2-1), Cardinal Direction (M3 series), or Alternative Route (M4 series) auxiliary plaque and the Advance Turn Arrow (M5 series) or Directional Arrow (M6 series) auxiliary plaques are used on the same sign assembly as a Bicycle Route sign, the Junction, Cardinal Direction, or Alternative Route auxiliary plaque shall be installed above the Bicycle Route sign, and the Advance Turn Arrow or Directional Arrow auxiliary plaque shall be installed below the Bicycle Route sign.

Except for the M4-8 plaque, all route sign auxiliary plaques should match the color combination of the route sign that they supplement.

Route sign auxiliary plaques carrying word legends that are used on bicycle routes should have a minimum size of 12 x 6 inches. Route sign auxiliary plaques carrying arrow symbols that are used on bicycle routes should have a minimum size of 12 x 9 inches.

Paragraphs relocated to guidance for this section

Option:

With route signs of larger sizes, auxiliary plaques signs may be suitably enlarged, but not such that they exceed the width of the route sign.

- 1 A route sign and any auxiliary plaques signs used with it may be combined on a single sign. 2 Destination (D1-1b and D1-1c) signs (see Figure 9B-4) may be mounted below Bike Route Guide signs, 3 Bicycle Route signs, or U.S. Bicycle Route signs to furnish additional information, such as directional 4 changes in the route, or intermittent distance and destination information. This Paragraph is deleted because 5 it is redundant with Paragraph 4 of existing Section 9D.20. Paragraph 4 of existing Section 9D.20 is 6 relocated to proposed new Section 9D.01 and edited. 7 Support: 8 An agency or jurisdiction can use several methods for bicycle route guidance, including maps, 9 information guides, or signing. 10 Figure 9D-3 shows typical placements of bicycle route signs. 11 Standard If Lead, a Bicycle Route Sign assembly shall consist of a route sign and auxiliary signs that identify 12 13 the route and indicate the direction. 14 Guidance: 15 If the bicycle route is signed, Bicycle Route Sign assemblies should be installed on all approaches where 16 that route intersects with other numbered bicycle routes. 17 **Standard:** 18 Within groups of assemblies, information for bicycle routes intersecting from the left shall on 19 mounted at the left in horizontal arrangements and at the top or center of vertical arrangements. 20 Similarly, information for bicycle routes intersecting from the right shall be at the right or bottom, and 21 for straight-through bicycle routes at the center in horizontal arrangements or top in vertical 22 arrangements. 23 Option: 24 The Bicycle Route Sign assemblies may be mounted on common supports with numbered highway routes 25 for general traffic. 26 **Standard:** 27 A Junction assembly shall consist of a Junction auxiliary sign and a bicycle route sign. The bicycle 28 route sign shall carry the number of the intersected or joined bicycle route (See Figure 9D-4) 29 Option: 30 The Junction assembly may be installed in advance of intersections where a numbered bicycle route is intersected or joined by another numbered bicycle route (See Figure 9D-4). 31 32 **Standard:** 33 An Advance Bicycle Route Turn assembly shall consist of a bicycle route sign, an Advance Turn 34 Arrow or word message auxiliary sign, and a Cardinal Direction auxiliary sign, if needed. If used, it 35 shall be installed in advance of an intersection where a turn must be made to remain on the indicated 36 route. Option: 38 The Advance Bicycle Route Turn assembly may be used in advance of intersecting routes. On the 39 40 used to pre-position turning bicycles in the correct lane position from which to make their turn. 41 **Standard:**
- 37

approach to an intersection with a numbered bicycle route, the Advance Bicycle Route Turn assembly may be

42 A Directional assembly shall consist of a Cardinal Direction auxiliary sign, if needed; a route sign; 43 and a Directional Arrow auxiliary sign.

Guidance:

44

45

46

47

The various uses of Directional assemblies should be as provided in Items A through D:

A: Turn movements should be marked by a Directional assembly with a route sign displaying the number of the turning route and a single-headed arrow pointing in the direction of the turn.

- 1 <u>B: The beginning of a route should be marked by a Directional assembly with a route sign displaying the number of that route and a single-headed arrow pointing in the direction of the route.</u>
 - C: An intersected route on a crossroad where the route is designated on both legs should be designated by:
 - 1. Two Directional assemblies, each with a route sign displaying the number of the intersected route, a Cardinal Direction auxiliary sign, and a single-headed arrow pointing in the direction of movement on that route; or
 - 2. A Directional assembly with a route sign displaying the number of the intersected route and a double-headed arrow, pointing at appropriate angles to the left, right, or ahead.
- D: An intersected route on a side road or on a crossroad where the route is designated only on one of the legs should be designated by a Directional assembly with a route sign displaying the number of the intersected route, a Cardinal Direction auxiliary sign, and a single-headed arrow pointing in the direction of
- intersected route, a Cardinal Direction auxiliary sign, and a single-headed arrow pointing in the direction of
 movement on that route.
- 14 Option:

3

4

5

6 7

8

9

18

19

20

21

22

24

25

28

29

- Straight-through movements may be indicated by a Directional assembly with a route sign displaying the number of the continuing route and a vertical arrow.
- 17 *Guidance*:
 - A Directional assembly should not be used for a straight-through movement in the absence of other assemblies indicating right or left turns, as the Confirming assembly sign beyond the intersection normally provides adequate guidance.
 - <u>Directional assemblies should be located on the near right corner of the intersection. Where unusual conditions exist, the location of a Directional assembly should be determined by engineering judgement.</u>
- 23 Support:
 - It is more important that guide signs be readable, and that the information and direction displayed thereon be readily understood, at the appropriate time and place than to be located with absolute uniformity.
- 26 Figure 9B-x shows typical placements of Directional assemblies.
- 27 *Guidance*:
 - If used, Confirming or Reassurance assemblies should consist of a Cardinal Direction auxiliary sign and a route sign. Where the Confirming or Reassurance assembly is for an alternative route, the appropriate auxiliary sign for an alternative route should also be included in the assembly.
- 31 If used, a Confirming assembly should be installed just beyond intersections of numbered routes.
- 32 <u>If used, Reassurance assemblies should be installed between intersections in urban areas as needed, and</u> 33 beyond the built-up area of any incorporated city or town.
- 34 <u>If used, Bicycle route signs for either confirming or reassurance purposes should be spaced at such</u> 35 intervals as necessary to keep bicyclists informed of their routes.
- 36 Section 9B.23 9D.09 Bicycle Parking Area Signs (D4-3, D4-4)
- 37 Support
- Bicycle parking areas include bicycle racks or stands, parking stations or structures, sharing systems, or
- 39 <u>lockers. These facilities can be either regulated or unregulated.</u>
- 40 Option:
- The Bicycle Parking Area (D4-3) sign (see Figure 9B-4) may be installed where it is desirable to show the direction to a designated bicycle parking area. The arrow may be reversed as appropriate.
- 43 Standard:
- The legend and border of the Bicycle Parking Area sign shall be green on a retroreflectorized white background.
- The Bicycle-Sharing Station (D4-4) sign may be installed to provide directional information to a designated bicycle sharing system.

Guidance:

1

7

8

9

10

11

13

14

15

16

17

18 19

20

21

22

23

24

2526

27

28

29

30

31 32

33

34

35

36

3738

39

40

41

42

43

44

45

47

If used, the Bicycle-Sharing Station sign should be used in conjunction with a regulated bicycle-sharing
 system such as one that requires the user to pre-register or provide a deposit in order to acquire a bicycle.
 Where it is determined that unregulated bicycle-sharing parking facilities necessitate a bicycle parking sign,
 the Bicycle Parking Area sign should be used.

6 **Standard:**

<u>In accordance with Section 1D.09, Bicycle Parking signs shall not include promotional advertising, business logos or other identification that would convey the involvement of a public-private partnership for operating the bicycle parking facility or sharing system.</u>

Section 9B.24 9D.10 Reference Location Signs (D10-1 through D10-3) and Intermediate Reference Location Signs (D10-1a through D10-3a)

12 Support:

There are two types of reference location signs:

- A. Reference Location (D10-1, 2, and 3) signs show an integer distance point along a shared-use path; and
- B. Intermediate Reference Location (D10-1a, 2a, and 3a) signs also show a decimal between integer distance points along a shared-use path.

Option

Reference Location (D10-1 to D10-3) signs (see Figure 9B-4)-may be installed along any section of a shared-use path to assist users in estimating their progress, to provide a means for identifying the location of emergency incidents and crashes, and to aid in maintenance and servicing.

To augment the reference location sign system, Intermediate Reference Location (D10-1a to D10-3a) signs (see Figure 9B-4), which show the tenth of a mile with a decimal point, may be installed at one tenth of a mile intervals, or at some other regular spacing.

Standard: Guidance: Standard changed to Guidance

If Intermediate Reference Location (D10-1a to D10-3a) signs are used to augment the reference location sign system, the reference location sign at the integer mile point shall-should display a decimal point and a zero numeral.

If placed on shared-use paths, reference location signs shall contain 4.5-inch white numerals on a green background that is at least 6 inches wide with a white border. The signs shall contain the word-MHLE in 2.25-inch white letters. Minimum sign sizes specified in Table; sign design details specified in Standard Highway Signs

Guidance:

Reference location signs for shared-use paths shall-should have a minimum mounting height of 2 feet, measured vertically from the bottom of the sign to the elevation of the near edge of the shared-use path, and shall should not be governed by the mounting height requirements prescribed in Section 9B.01., and should not be governed by the mounting height requirements prescribed in 9B.01.

Option:

Reference location signs may be installed on one side of the shared-use path only and may be installed back-to-back.

If a reference location sign cannot be installed in the correct location, it may be moved in either direction as much as 50 feet.

Guidance:

If a reference location sign cannot be placed within 50 feet of the correct location, it should be omitted. Zero distance should begin at the south and west terminus points of shared-use paths.

46 Support:

Section 2H.05-2H.10 contains additional information regarding reference location signs.

Section 9B.25 9D.11 Mode-Specific Directional Guide Signs for Shared-Use Paths (D11-1a, D11-2, D11-3, D11-4)

Option:

1

2

3

4

5

6 7

8

9

10

11 12

13

1415

16

17

18

19

21

22

23

25 26

28

29

31

32

34

35 36

37 38

40

42

43 44 Where separate pathways are provided for different types of users, Mode-Specific <u>Directional</u> Guide (D11-1a, D11-2, D11-3, D11-4) signs (see Figure 9B-4)-may be used to guide different types of users to the traveled way that is intended for their respective modes.

Mode-Specific <u>Directional</u> Guide signs may be installed at the entrance to shared-use paths where the signed mode(s) are permitted or encouraged, and periodically along these facilities as needed.

The Bicycles Permitted <u>Directional</u> (D11-1a) sign, when combined with the BIKE ROUTE supplemental plaque (D11-1bP), may be substituted for the D11-1 <u>Bicycle Bike</u> Route Guide sign on <u>shared-use</u> paths and shared roadways.

When some, but not all, non-motorized user types are encouraged or permitted on a shared-use path, Mode-Specific <u>Directional</u> Guide signs may be placed in combination with each other, and in combination with signs (see Section <u>9B.09-9B.08</u>) that prohibit travel by particular modes.

Support:

Figure 9B-8-9D-5 shows an example of signing where separate pathways are provided for different non-motorized user types.

Figure 9D-5. Example of Mod-Specific Guide Signing on a Shared-Use Path

Section 9D.12 Destination Guide Signs for Shared-Use Paths (D11-10a, D11-10b, D11-10c)

20 Support:

This Section contains information on the application of Destination Guide signs for shared-use paths.

<u>Chapter 9G contains information on applying Destination Guide signs for shared-use paths at alternative intersections.</u>

24 **Standard:**

Where bicycle traffic is allowed on the shared-use th, Destination Guide signs for shared-use paths and any identification enhancement markers shared-use be retroreflective.

27 *Guidance*:

<u>Destination Guide signs for shared-use paths should be installed on independent assemblies and should</u> not be combined with other regulatory and warning signs.

30 Option:

<u>Destination Guide signs for shared-use paths may use symbols in addition to the bicycle symbol to display</u> other modes on the shared-use path.

33 **Standard:**

Symbols used on Destination Guide signs for shared-use paths shall be limited to those where the symbol displayed is an allowable mode on the path or pathway alignment, and where the symbol is supported by other regulatory signs to convey the operation. Symbols unrelated to the allowable mode that would be otherwise display directional navigation to a facility, activity, point of interest, etc. shall not be used.

39 Support:

Chapter 2M contains information for symbol signs used for facilities, activities, and points of interest.

41 Guidance:

<u>Destination Guide signs for shared-use paths, exclusive of any identification marker used, should be rectangular in shape. Simplicity and uniformity in design, position, and application as described in Section 2A.04 are important and should be incorporated into the sign design.</u>

45 <u>Destination Guide signs for shared-use paths should be limited to three destinations per sign (see Section</u> 46 2D.06).

2	<u>Abbreviations (see Section 1D.10) should be kept to a minimum, and should include only those that are commonly recognized and understood.</u>
3	
	Support:
4	Figure 9D-6 shows a signing system of Destination Guide signs used on shared-use paths.
5	Figure 9D-6. Example of Destination Guide Signing on a Shared-Use Path
6	Standard:
7	The arrow location and priority order of destinations shapellow the provisions described in
8	Sections 2D.08 and 2D.36. Arrows shall be of the designs provided in Section 2D.08.
9	The lettering for destinations on Destination Guide signs for shared-use paths shall approximation of lawyer aggs letters with initial upper aggs letters (see Section 2D 04). All other word
10 11	combination of lower-case letters with initial upper-case letters (see Section 2D.04). All other word messages on Destination Guide signs for shared-use paths shall be in all upper-case letters.
12	Except as provided in Paragraph 15, the lettering yle used for destination and directional legends
13	on Destination Guide signs for shared-use paths shared-us
14	Option:
15	The distance to the place named may be displayed on the Destination Guide sign. If several destinations
16	are to be displayed at a single point, the several names may be placed on a single sign with an arrow (and the
17	distance, if desired) for each name. If more than one destination lies in the same direction, a single arrow may
18	be used for such a group of destinations.
19	A lettering style other than the Standard Alphabets provided in the "Standard Highway Signs and
20	Markings" book may be used on Destination Guide signs for shared-use paths if an engineering study
21	determines that the legibility and recognition values for the chosen lettering style at minimum letter heights
22	meet or exceed the values for the Standard Alphabets for the same legend height and stroke width.
23	Standard:
24	Where a shared-use pat within the roadway right-of-way or crosses a street or highway, an
25	alternative lettering style share of be used.
26	Option:
27	Pictographs (see definition in Section 1C.02) may be used on Destination Guide signs for shared-use
28	<u>paths.</u>
29	Standard:
30	If a pictograph is used, its height shalet exceed two times the height of the upper-case letters of
31	the principal legend on the sign.
32	Business logos, commercial graphics, or other forms of advertising (see Section 1D.09) show to be
33	used on Destination Guide signs for shared-use paths or sign assemblies.
34	Option:
35	An identification marker may be used in an assembly for Destination Guide signs applied to shared-use
36	paths, or may be incorporated into the overall design of Destination Guide sign, as a means of visually
37	identifying the sign as part of an overall system of signs.
38	Standard:
39	The size and shape of an identification marker shape esmaller than the Destination Guide sign.
40 41	<u>Identification markers shall not be designed to have an appearance that could be mistaken by road</u> users as being a traffic control device.
42	Guidance:
43	The area of the identification marker should not exceed 1/5 of the area of the Destination Guide sign with
44	which it is mounted in the same sign assembly.
45	Standard:
46 47	Except as provided in Paragraph 27, Destination Guide signs for ared-use paths shall ave a white legend and border on a green or brown background and shall consistent with the basic design
47 48	white legend and border on a green or brown background and shall consistent with the basic design principles for guide signs.
1 0	principles for guide signs.

Color coding or pict phs shall be used to distinguish between different types of destinations, 1 If used, color coding share accomplished by the use of different colored square or rectangular panels 2 3 on the face of the sign, each positioned to the left of the named geographic area to which the color-4 coding panel applies. The height of the colored square or rectangular panels shall not exceed two times 5 the height of the upper-case letters of the principal legend on the sign. 6 Option: 7 The different colored square or rectangular panels may include either a black or a white (whichever 8 provides the better contrast with the color of the panel) letter, numeral, or other appropriate designation to 9 identify the destination. 10 Except where a shared-use path is within the roadway right-of-way or crosses a street or highway, 11 Destination Guide signs for shared-use paths may use background colors other than green or brown in order to 12 provide a color identification for systematic destinations within the overall guide signing system. 13 **Standard:** 14 The standard colors of red, orange, yellow, purple, or the fluorescent versions thereof, fluorescent 15 vellow-green, and fluorescent pink shall not be used as background colors for Destination Guide signs for shared-use paths, in order to minimize possible confusion with critical, higher-priority regulatory 16 17 and warning sign color meanings readily understood by path users. 18 Option: 19 Destination Guide signs for shared-use paths may display phone numbers and Internet and e-mail 20 addresses, including domain names and uniform resource locators (URL). 21 **Standard:** 22 If used, the use of phone numbers and Internet and e-mail addresses shall be limited to direct 23 contact information of the jurisdiction with authority of the shared-use path, or contact information for 24 emergency service response, or both. Contact information for advertising purposes shall not be used. 25 Section 9D.13 Two-Stage Bicycle Turn Box Guide Signing (D11-20 series) 26 Support: 27 Two-stage bicycle turn boxes provide a way for a bicycle to make a turn wherein a merge across general 28 purpose lanes is not required. 29 Section 9B.18 provides situations when a two-stage bicycle turn box is required and also contains 30 information about the Two-Stage Bicycle Turn Box Regulatory sign (R9-23 series) 31 Section 9E.11 contains information regarding pavement markings for two-stage turn boxes. 32 **Standard:** Where a two-stage licycle turn box is provided, the Two-Stage Bicycle Turn Box Guide sign series 33 34 (see Figure 9D-7) shan be used. Where used, the Two-Stage Bicycle Turn Box Advance guide sign shape mounted in advance of 35 the intersection where the turn box is located. 36 Where used, the Two-Stage Bicycle Turn Box guide sign shape mounted on the far side of the 37 38 intersection. 39 Option: 40 Where the Two-Stage Bicycle Turn Box Advance guide sign is used, an additional Two-Stage Bicycle 41 Turn Box Advance guide sign may be mounted on the near side of the intersection where the turn box is 42 located. 43 If used, an appropriately sized Street Name (see Section 2D.44) sign (D3-1) may be installed below the 44 Two-Stage Bicycle Turn Box Advance guide sign to identify the cross street where the turn box will be 45 available. Figure 9D-7. Example of Signing for Two-Stage Bicycle Turn Boxes 46

44 Support:

Standard:

41

42.

43

left turn only lane.-Relocated to new Section 9E.02

A through bicycle lane shall not be positioned to the right of a right turn only lane or to the left of a

A bicyclist continuing straight through an intersection from the right of a right-turn lane or from the left of a left turn lane would be inconsistent with normal traffic behavior and would violate the expectations of right-or left turning motorists.-Relocated to new Section 9E.02

Guidance:

When the right through lane is dropped to become a right turn only lane, the bicycle lane markings should stop at least 100 feet before the beginning of the right turn lane. Through bicycle lane markings should resume to the left of the right turn only lane. Relocated to new Section 9E.02

An optional through right turn lane next to a right turn only lane should not be used where there is a through bicycle lane. If a capacity analysis indicates the need for an optional through right turn lane, the bicycle lane should be discontinued at the intersection approach. Relocated to new Section 9E.02

Posts or raised pavement markers should not be used to separate bicycle lanes from adjacent travel lanes. Relocated to new Section 9A.03 and new Section 9E.18

Support:

Using raised devices creates a collision potential for bicyclists by placing fixed objects immediately adjacent to the travel path of the bicyclist. In addition, raised devices can prevent vehicles turning right from merging with the bicycle lane, which is the preferred method for making the right turn. Raised devices used to define a bicycle lane can also cause problems in cleaning and maintaining the bicycle lane. Relocated to new Section 9A.03 and new Section 9E.18 was edited

Support:

Examples of bicycle lane markings at right turn lanes are shown in Figures 9C-1, 9C-4, and 9C-5.—

Relocated to new Section 9E.02 Examples of pavement markings for bicycle lanes on a two-way street are shown in Figure 9C-6-9E-2. Pavement word message, symbol, and arrow markings for bicycle lanes are shown in Figure 9C-3.

Figure 9E-2. Example of Pavement Markings for Bike Lanes on a Two-Way Street

Section 9E.02 Bicycle Lanes at Intersection Approaches Paragraphs relocated from existing Section 9C.04

27 Standard:

Except as provided in Paragraph 26a, A a through bicycle lane shall not be positioned to the right of a right turn only lane or to the left of a left turn only lane.

Option:

A through bicycle lane may be positioned to the right of a right-turn only lane or to the left of a left-turn only lane provided that the bicycle lane is controlled by a traffic signal that displays bicycle signal indications. Refer to Chapter 9F for Standard, Guidance and Options regarding bicycle signals and phasing.

Support:

<u>Unless controlled by a bicycle signal indication, a</u>A bicyclist continuing straight through an intersection from the right of a right-turn lane or from the left of a left-turn lane would be inconsistent with normal traffic behavior and would violate the expectations of right- or left-turning motorists.

Guidance:

When the right <u>(or left)</u> through lane is dropped to become a right-<u>(or left-)</u> turn only lane, the bicycle lane markings should stop at least 100 feet before the beginning of the right-<u>(or left-)</u> turn lane. Through bicycle lane markings should resume to the left <u>(or right)</u> of the right-<u>(or left-)</u> turn only lane.

An optional through-right (or through-left) turn lane next to a right- (or left-) turn only lane should not be used where there in through bicycle lane. If a capacity analysis indicates the need for an optional through-right turn lane, the ycle lane should be discontinued at the intersection approach.

Standard:

<u>Bicycle lanes located on an intersection approach between contiguous lanes for motor vehicle</u> <u>movements shall be marked with at least one bicycle symbol and at least one arrow pavement markings</u> <u>as provided in Paragraph 9 of Section 9E.01.</u>

1	Bicycle lanes shar not be marked within a general purpose lane, either with dotted or any other line
2	markings.
3	Option:
4	Where there is insufficient width in the roadway to include a bicycle lane and a general purpose turn lane,
5	bicycle travel may be accommodated through the turn lane using shared-lane markings.
6	Support:
7	Examples of bicycle lane markings at right turn lanes on approaches to intersections are shown in Figures
8	9C-1, 9C-4, and 9C-5-9E-3 and 9E-4.
9	Guidance:
10	The longitudinal line defining a bicycle lane should be dotted on approaches to intersections where
11	turning vehicles may cross the path of through-moving bicycles.
12	Figure 9E-3. Example of Bicycle Lane Markings on an Approach to an Intersection (3
13	Sheets)
14	Figure 9E-4. Example of Bicycle Lane Markings on an Approach to an Intersection that
5	Transitions to a Shared Lane
6	Support:
7	Buffer-separated and separated bicycle lanes require additional considerations at intersections, including
8	sight distances for bicycles and other road users, user expectations, and intersection geometry.
9	Option:
0	A buffer-separated or separated bicycle lane may be shifted closer to, or further away from the adjacent
1	general purpose lane depending upon site-specific conditions (see Figure 9E-7).
2	<u>Guidance</u> :
3	A buf reparated or separated bicycle lane should not be shifted away from the adjacent general
4	purpose lane at an intersection unless is there is sufficient space for a vehicle to queue between the general
5	purpose lane and the extension of the bicycle lane.
6	Support:
7 8	The purpose of shifting a buffer-separated or separated bicycle lane away from the adjacent general purpose lane is to allow the driver of a turning vehicle to undertake the tasks of turning and scanning for
9	bicycle cross traffic in isolation versus simultaneously. Sufficient sight distance for both vehicle and bicycle is
0	important in this design.
1	The purpose of shifting a buffer-separated or separated bicycle lane towards the adjacent general purpose
2	lane is to improve the visibility of bicycles to the adjacent traffic and avoid conflicts between turning vehicles
3	and bicycles.
4	Option:
5	Where a general purpose lane is needed at an intersection and the approach also include a separated or
6 7	buffer-separated bicycle lane, a mixing zone may be established to allow general purpose traffic to share the
	roadway space formerly occupied by the buffer and/or bicycle lane separation (see Figure 9E-5).
8	Standard:
9 0	Mixing shall be used only where the bicycle lane is one-way in the same direction of travel as the adjacent general purpose lane.
1 2	Mixing zones shall have yield markings indicating where general purpose traffic entering the combined bicycle lane and turn lane shall yield to bicycles in the bicycle lane.
3	Where a mixing zone continues to the intersection itself sharing space between the bicycle lane and
4	the general purpose turn lane, shared lane markings and turn arrows shall be provided in the lane.
5	Where a mixing zone allows for the re-establishment of a bicycle lane after bicycles and general
6	purpose lanes cross paths, a buffered or physically separated space should be provided between the
-7	bicycle lane and the adjacent general purpose lane (see Figure 9E-5).
48	Support:

1 Mixing zones require bicycles and general traffic to share space, interrupting a buffer-separated or 2 separated bicycle lane where bicycles are otherwise separated from general traffic. It is important to consider 3 the use of mixing zones in the context of a bicycle facility that is otherwise free of general traffic outside of 4 crossing points at intersections and driveways. 5 Figure 9E-5. Example of Mixing Zone at an Intersection 6 Section 9E.03 Extensions of Bicycle Lanes through Intersections 7 Support: 8 Extensions of bicycle lanes through intersections can help identify the paths of bicycles and guide them on 9 movements that could be difficult to discern. Extensions of bicycle lanes through intersections also assist other users of the intersection to identify where bicycles are expected to operate and to recognize potentially 10 11 unexpected conflict points. 12 The application of a bicycle lane extension in an intersection is important. The design, placement, and 13 maintenance of bicycle lane extensions through intersections, especially when contiguous to a crosswalk, have 14 the potential to confuse pedestrians with low visual acuity. 15 The width and color of lane extension markings are discussed in Section 3B.11. 16 Option: 17 The bicycle symbol, the arrow marking, pavement word markings, or a combination thereof may be used 18 in bicycle lane extensions through intersections. 19 Green colored pavement may be used in a bicycle lane extension consistent with Section 3H.06. 20 **Standard:** Shared-landmarkings or chevron markings shall not be used in bicycle lanes or bicycle lane 21 22 extensions (see Section 9B.08). 23 Extensions of bicycle lanes through intersections shall use dotted line patterns. 24 Lane extension markings shall be used to extend a buffer-separated or separated bicycle lane 25 through intersections and driveways. 26 Support: 27 Separated and buffer-separated bicycle lanes may have alignments that are not as obvious within an 28 intersection as a standard bicycle lane, therefore additional conspicuity is important where these types of 29 bicycle lanes cross intersections. 30 Guidance: 31 The extension of a bicycle lane through an intersection should use two lines defining both lateral limits of 32 the bicycle lane. 33 **Standard:** 34 Where the path of the bicycle lane through the intersection is contiguous to a crosswalk, two 35 longitudinal dotted lines shall be provided to establish the lateral limits of the bicycle lane extension. The transverse line establishing one side of the crosswalk, or the limit of a high-visibility crosswalk pattern (see Section 3C.05) that does not employ a transverse line, so not be used to demarcate one 36 37 38 side of the bicycle lane extension. 39 Section 9E.04 Bicycle Lanes at Driveways 40 Support: 41 Section 3B.11 contains information to determine if a driveway can be considered an intersection. 42 Option:

in bicycle lane extensions through driveways.

43

44

45

Bicycle lanes may be continued through a driveway using solid or dotted longitudinal line(s).

The bicycle symbol, the arrow marking, pavement word markings, or a combination thereof may be used

1 Green-colored pavement (see Section 3H.06) may be used as a background to enhance the conspicuity of 2 the rotated bicycle symbol at driveways. Section 9E.05 Bicycle Lanes at Circular Intersections Paragraphs relocated from existing Section 3 4 9C.04 5 **Standard:** Bicycle lanes summer not be provided on the circulatory roadway of a roundabout circular intersection 6 7 (see Chapter 3D). 8 Guidance: 9 Bicycle lane markings should stop at least 100 feet before the crosswalk, or if no crosswalk is provided, at 10 least 100 feet before the yield line, or if no yield line is provided, then at least 100 feet before the edge of the 11 circulatory roadway. 12 Support: 13 Section 9E.10 contains information on using shared-lane markings to facilitate the bicycle movement 14 through a circular intersection. 15 The "Guide for the Development of Bicycle Facilities" authored by the American Association of State 16 Highway and Transportation Officials (see Section 1A.05) contains information on designing for bicycles on 17 the sidewalk in lieu of, or in addition to, using shared-lane markings in the circular roadway of the 18 intersection. 19 Section 9E.06 Buffer-Separated Bicycle Lanes 20 Support: 21 Buffer-separated bike lanes provide additional lateral separation between a bicycle lane and a general 22 travel lane by a pattern of pavement markings without the presence of vertical elements or parked vehicles. 23 Providing a buffer space between a bicycle lane and a general purpose lane can reduce vehicle encroachment 24 into the bicycle lane. 25 Providing a buffer space between a bicycle lane and a parking lane can reduce crashes involving bicycles 26 and the opening of vehicle doors from the parking lane. 27 **Standard:** If used, and except as provided in Paragraph 5, a buffer space share marked with longitudinal 28 29 lines as follows: 30 A. A solid white line along both edges of the buffer space where crossing is prohibited, or 31 B. A broken single white line along one or both edges of the buffer space where crossing is allowed, 32 with a solid white line along the other edge of the buffer space. 33 Guidance: 34 Engineering judgment should be used to establish intermittent breaks or interruptions in the buffer space, 35 such as for driveways or on-street parallel parking lanes, in order to convey access points or an otherwise 36 general legal movement to cross the buffer space (see Figure 9E-6). 37 Option: 38 Buffer spaces may be established without specific longitudinal lines if contiguous facilities have 39 longitudinal lines or other pavement markings themselves that, when installed, automatically demarcate the 40 buffer space (see Drawings B and C of Figure 3E-3). 41 **Standard:** 42 Except as provided in Paragraph 8, a through buffer-separated bicycle lane shall not be positioned 43 to the right of a right turn only lane or to the left of a left turn only lane.

Notice of Proposed Amendments – Part 9

44

45

46

47

Option:

potential conflicts between the bicycle movement and the turning movement.

A buffer-separated bicycle lane may be placed to the right of a right-turn lane (or to the left of a left-turn

lane) only if a bicycle signal face (see Chapter 9F) is used and the signal phasing and signing eliminates any

1	~		•	7			
	G	u	la	la	n	c	e:

2 The width of the buffer space should be at least three times the width of the normal or wide longitudinal 3 line used to mark the buffer space.

4 Option:

5

6

8

9

11

13

16

17

21

22

24

25

26

27

28

29

30

31

33

34

42

43

44

46

47

Where a buffer space is less than three feet wide, one-directional diagonal markings or no markings at all in the buffer space can be applied.

7 **Standard:**

> If used, one-directional diagonal markings shall slant away from traffic in the adjacent travel lane for motor vehicle traffic.

10 Guidance:

Where used, the spacing of chevrons or one-directional diagonal markings should be 10 feet or greater.

12

Chevron and one-directional diagonal markings convey that the buffer space is not an additional bicycle 14 lane or other travel lane open to traffic.

15 **Standard:**

> A buffer space three feet or wider shall use chevron or one-directional diagonal markings within the buffer.

18 Guidance:

19 Lane extension markings should be used to extend a buffer-separated bicycle lane across intersections 20 and driveways.

Figure 9E-6. Example of Lane Markings for Buffer-Separated Bicycle Lanes

Section 9E.07 Separated Bicycle Lanes

23 Support:

> Separated bicycle lanes provide a physical separation between a general travel lane and a bicycle lane that contains vertical objects or vertical separation between the general travel lane and bicycle lane. Providing a physical separation between a bicycle lane and a general purpose lane can reduce vehicle encroachment into the bicycle lane beyond a marked buffer alone and can in some cases prevent that encroachment altogether.

Physical separation between general purpose lanes and bicycle lanes introduces additional design considerations over buffer-separated bicycle lanes, including the awareness of a potentially unexpected conflict point for turning vehicles and the provision of adequate sight distance for all users at intersections and driveway crossings.

32 Option:

> Vertical elements used to provide separation between general purpose lanes and bicycle lanes may include, but are not limited to tubular markers, medians, or parked vehicles.

35

36 Where on-street parking is provided in the buffer area of a separated bicycle lane, pedestrians will have to 37 access those vehicles.

Guidance: 38

39 BIKE LANE (R3-7) signing should be used where a separated bicycle lane may be confused for a general 40 purpose lane.

41 **Standard:**

> Where a parking lane serves as the separation between a general travel lane and a separated bicycle lane, a buffer space shall be provided between the parking lane and the bicycle lane to allow for opening doors of parked vehicles.

45 Support:

> Separated bicycle lanes may be designed for one-way or two-way bicycle travel. Providing one-way separated bicycle lanes in the same direction as and on the right side of the general purpose lane, whether on a

- 1 one-way or two-way roadway, accommodates the expectations of road users and may create fewer conflict 2 points at intersections or driveway crossings.
- 3 Option:

4

6

7

8

9

10

11

12

13 14

15

16

17 18 19

21 22

23

24

28

29

30

32

33

34

35

36

37

38

39

40

41

46

47

Separated bicycle lanes may be provided on one or both sides of a roadway or in a center median.

5 Support:

> The presence of two-way separated bicycle lanes on one side of a roadway or in a center median introduces additional challenges and conflict points. The "Guide for Development of Bicycle Facilities" authored by the American Association of State Highway and Transportation Officials (see Section 1A.05) contains information on design considerations when selecting the design for a separated bicycle lane.

Information regarding the design requirements for pedestrians who would interact with a separated bicycle lane can be found in the "Americans with Disabilities Act Accessibility Guidelines for Buildings and Facilities (ADAAG)" (see Section 1A.05) and the Public Rights-of-Way Accessibility Guidelines (PROWAG) (see Section 1A.05).

Standard:

The edge line and lane line colors used for separated bicycle lanes shall conform to the requirements in Chapter 3A (see Figure 9E-7).

Where two-way separated bicycle lanes provided on one side of a roadway or in a center median, conflicting vehicle traffic at signal intersections shall be prohibited by signal indications to cross the two-way separated bicycle lane when bicycle traffic is allowed to proceed through the 20 intersection.

Right turns on red s be prohibited across separated bicycle lanes while bicycle traffic is allowed to proceed through the intersection.

Directional arrows shall be used in conjunction with the bicycle lane symbol or word marking in separated bicycle lanes, placed downstream from the symbol or word marking.

25

26 Additional information on signals for bicycle facilities is found in Chapter 4H.

27 Guidance:

> Conflicting traffic at signalized intersections should be prohibited by signal indications to cross a oneway separated bicycle lane with the same direction of travel as the adjacent general purpose lane when bicycle traffic is allowed to proceed through the intersection.

31 **Standard:**

The buffer space for separated bicycle lane shall be marked with solid longitudinal lines.

A marked buffer space two feet or wider for a separated bicycle lane, including those buffer spaces where tubular markers are provided, shall use chevron or one-directional diagonal markings within the buffer, unless physical separation is provided that occupies the majority of the buffer space, such as medians or parked vehicles.

Guidance:

Where used in the buffer area of a separated bicycle lane, the spacing of chevrons or one-directional diagonal markings should be 10 feet or greater.

Crosswalks that cross a separated bicycle lane should be marked consistent with the style of crosswalk marking provided across the adjacent general purpose lane.

42 Support:

43 Where on-street parking is provided in the buffer area of a separated bicycle lane, the chevron or diagonal 44 marking provisions in Section 9E.06 apply to the area outside of the marked parking area within the buffer 45 (see Figure 9E-7).

Section 9B.20 contains information on the LEFT TURN YIELD TO Bicycles (R10-12b) sign used with traffic signals and counter-flow bicycle lanes.

1 2	<u>Intersection treatments for separated bicycle lanes can vary depending on the geometric and operational conditions at the intersection (see Section 9E.02).</u>
3	Figure 9E-7. Example of Lane Markings for Separated Bicycle Lanes
4	Section 9E.08 Counter-Flow Bicycle Lanes
5	Support:
6 7	Counter-flow bicycle lanes are one-directional and provide a lawful path of travel for bicycles in the opposite direction from general traffic on a roadway that allows general traffic to travel in only one direction.
8	Counter-flow bicycle lanes establish two-way traffic on a roadway.
9	Section 9B.20 contains information on the LEFT TURN YIELD TO Bicycles (R10-12b) sign used with
10	traffic signals and counter-flow bicycle lanes.
11	Guidance:
12	Where used, a counter-flow bicycle lane should be marked such that bicycles in the counter-flow lane
13	travel on their right-hand side of the road in accordance with normal rules of the road, with opposing traffic
14	on the left.
15	Standard:
16	Counter-flow bicycle lanes shall use double yellow center line pavement markings (see Section
17	3B.01) a painted median island, raised median island (see Section 3J.03) or some form of physical
18	separation where the speed limit is 30 mph or below.
19	For speed limits 35 mph or above, a buffer per Section 3B.24, a painted or raised median island, or
20	some form of physical separation shall be used to separate a counter-flow bicycle lane from the adjacen
21	travel lane.
22	Counter-flow bicycle lanes sha between a general purpose lane and an on-street
23	parallel parking lane for motor vehicles.
24	Support:
25 26	Since counter-flow bicycle movements can be unexpected, lane extension markings can help road users identify where counter-flow bicycle movements cross intersections.
27	Standard:
28	Where signs are provided to regulate turns from streets or driveways that intersect with a roadway
29	that has a counter-flow bicycle lane, ONE WAY signs (see Section 2B.51) shall not be used. Movement
30	Prohibition signs (see Section 2B.28) with supplemental Except Bicycles (R3-7bP) plaque(s) shall be
31	used (see Figure 9E-6).
32	If a DO NOT ENTER (R5-1) sign(s) is used at egress points for motor vehicle traffic, the Except
33 34	Bicycles plaque(s) shall be placed under the DO NOT ENTER sign (see Figure 9E-8) where a counterflow bicycle lane is used.
35	
36	Where intersection traffic controls are provided (e.g. stop or yield signs, traffic signals, etc.), appropriate devices shall be provided and oriented towards bicycles in the counter-flow lane.
37	At signalized locations, appropriate bicycle signalization (See Chapter 9F) shall be provided and
38	oriented toward cycles in the counter-flow lane, including a method for counter-flow bicycles to
39	actuate the green phase for the counter-flow movement.
40	Support:
41	Higher levels of traffic control or additional signalization, signing and/or pavement marking treatments
42	can be helpful for intersecting traffic where the counter-flow bicycle movement is unexpected.
43	Guidance:
44	An appropriate Bicycle Cross Traffic Warning plaque (see Section 9C.06) should be used below a STOP
45	sign on the cross-street at intersections where a counter-flow bicycle lane is provided on the primary street.
46	Figure 9E-8. Example of Counter-Flow Bicycle Lanes at an Intersection
	•
47	Section 9C.079E.09 Shared-Lane Marking

Option:

1

2

3

4

5

6

7

8

9

1011

12

13

14

15

17

23

24

25

26

27

28

29

30

31

32 33

34

35

36

37

38 39

40

41

42

44

45

46

The <u>Sshared_Llane Mmarking</u> shown in Figure <u>9C-99E-9</u> may be used to:

- A. Assist bicyclists with lateral positioning in a shared lane with on-street parallel parking in order to reduce the chance of a bicyclist's impacting the open door of a parked vehicle,
- B. Assist bicyclists with lateral positioning in lanes that are too narrow for a motor vehicle and a bicycle to travel side by side within the same traffic lane,
 - C. Alert road users of the lateral location bicyclist bicycles are likely to occupy within the traveled way,
 - D. Encourage safe passing of bieyelist bicycles by motorist motor vehicles, and
 - E. Reduce the incidence of wrong-way bicycling in the roadway.

Figure 9E-9. Example of Shared-Lane Markings on an Approach to an Intersection

Guidance:

The <u>Sshared_Llane Mmarking</u> should not be placed on roadways that have a speed limit <u>above 35 mph.of</u> <u>40 mph or more.</u>

Standard:

Shared-Llane Mmarkings shall not be used in: on shoulders or in designated bicycle lanes.

- 16 A. Shoulders,
 - B. Bicycle lanes or in designated extensions of bicycle lanes through intersections or driveways,
- 18 C. A travel lane that in which light-rail transit vehicles also travel,
- D. The transition area where a motor vehicle entering an exclusive turn lane must weave across bicycle traffic in bicycle lanes,
- 21 E. Two-stage turn boxes,
- F. Bicycle Boxes,
 - G. Shared-use paths or shared-use path crossings, or
 - H. Physically separated bikeways, either in the roadway or on an independent right-of-way
 - Green-colored pavement shall not be applied as a background to shared-lane markings (see Section 3H.06).

Guidance:

If used in a shared lane with on-street parallel parking, <u>Sshared_Llane Mmarkings</u> should be placed so that the centers of the markings are <u>at least 11a minimum of 12</u> feet from the face of the curb, or from the edge of the pavement where there is no curb.

If used on a street without on-street parking that has an outside travel lane that is less than 14 feet wide, the centers of the Sshared_Llane Mmarkings should be at least Shared Lane Markings should be placed so that the centers of the markings are a minimum of 4 feet from the face of the curb, or from the edge of the pavement where there is no curb.

If used, the shared-lane marking should be placed immediately after an intersection and spaced at intervals not greater than 250 feet thereafter. Where they are used in travel lanes that are too narrow for bicycles and motor vehicles to operate safely side-by-side, Shared Lane Markings should be placed in the center of the travel lane.

At non-intersection locations, the Shared Lane Marking should be spaced at intervals not less than 50 feet and not greater than 250 feet.

The first Shared Lane Marking downstream from an intersection should be placed no more than 50 feet from the intersection.

43 Option:

Section <u>9B.06-9B.14</u> describes a Bicycles May Use Full Lane sign that may be used in addition to or instead of the <u>Sshared_Llane Mmarking</u> to inform road users that <u>bicyclistbicycles</u> might occupy the travel lane.

47 <u>Guidance:</u>

The shared-lane marking may be used on approaches to intersections (See Figure 9E-4) in exclusive turn lanes to continue a bicycle lane where there is insufficient width in the roadway for both the bicycle lane and turn lane.

Section 9E.10 Shared-Lane Markings for Circular Intersections

11 Guidance:

7

8

9

10

15

16

17

19

21

22

23

24

25

26

27

2930

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

Shared-lane markings should not be used in the circulatory roadway of the circular intersection if the circulatory roadway is multi-lane.

14 Support:

The "Guide for Development of Bicycle Facilities" authored by the American Association of State

Highway and Transportation Officials (see Section 1A.05) contains information on designing for bicycles on

the sidewalk in lieu of, or in addition to, using shared-lane markings in the circular roadway of the

18 <u>intersection.</u>

Section 9E.11 Two-Stage Bicycle Turn Boxes

20 Support:

Two-stage bicycle turn boxes allow bicycles the opportunity to make turns at an intersection or crossing point that does not require them to merge into traffic upstream or to dismount and use a crosswalk at the intersection or crossing point.

Section 9B.17 contains information on regulatory signing that shall be used in conjunction with a two-stage bicycle turn box pavement marking where use of the turn box is required.

Section 9D.13 contains information on guide signing that can be used in conjunction with a two-stage bicycle turn box pavement marking where use of the turn box is optional.

28 **Standard:**

If used, two-stage bicycle turn boxes shar be located:

- A. In an area between the closest through bicycle or motor vehicle movement and the parallel crosswalk (see Drawing A of Figure 9E-10), or
- B. In an area between the through bicycle movement and the parallel pedestrian crossing movement if no crosswalk is established (see Drawing B of Figure 9E-10), or
- C. On the innermost side of the bicycle facility provided that the two-stage turn box is located in a portion of the intersection where parallel or motor vehicle traffic does not travel; such as projections of islands or parking lanes (see Drawing C of Figure 9E-10), or
- D. In an area between the through bicycle movement and a pedestrian facility for T-intersections (see Drawing D of Figure 9E-10).
- A two-stage bicycle turn box shall consist of at least one bicycle symbol pavement marking and at least one pavement marking arrow.

A turn arrow in the appropriate direction shall be used if a two-stage turn box is used with a one-way bicycle lane, and a through arrow in the appropriate direction shall be used if a two-stage turn box is used with a two-way bicycle lane (see Figure 9E-11). two-stage bicycle turn boxes that facilitate turns from a one-way bikeway, the bicycle symbol shall precede the pavement marking turn arrow in the direction of bicycle travel.

A two-stage bicycle turn box shall be bounded on all sides by a solid white line.

1 For two-stage bicycle turn boxes that facilitate turns from a one-way bikeway, the bicycle symbol 2 shall precede the pavement marking turn arrow in the direction of bicycle travel. 3 Passive detection of bicycles in the two-stage bicycle turn box shall be provided if the signal phase 4 that permits bicycles to enter the intersection during the second stage of their turn is actuated. 5 Figure 9E-10 Examples of Two-Stage Bicycle Turn Box Locations in Intersections 6 Figure 9E-11 Example of a Two-Stage Bicycle Turn Box in an Intersection with a Two-7 Way Separated Bicycle Lane 8 **Option:** 9 For two-stage turn boxes that facilitate turns from a two-way bikeway, a through arrow pavement marking 10 may be used to orientate bicycles in the direction of the movement to be accomplished by the second stage of 11 the turn (see Figure 9E-11). 12 Guidance: 13 Engineering judgment should be used to develop the size of the two-stage bicycle turn box. Factors 14 considered should include intersection geometry and keeping queued bicycles away from moving traffic, as 15 well as peak hour bicycle volumes so that overflow of the two-stage turn box does not subject any bicyclist to 16 conflicting movements. 17 Option: 18 The two-stage turn box may use green-colored pavement. 19 **Standard:** 20 If used, green-colored pavement shall encompass the full limit of the two-stage turn box. 21 Where the path of vehicles lawfully turning on red would pass through a two-stage bicycle turn box, 22 the cross street shall implement a full-time turns on red prohibition. 23 Section 9E.12 Bicycle Box 24 Option: 25 A bicycle box (see Figure 9E-12) may be used to increase the visibility of stopped bicycles on the 26 approach to a signalized intersection during the portion of the signal cycle when a red signal indication is 27 being displayed to motor vehicles in the approach lane(s) that is behind the box. 28 Guidance: 29 At intersections where a discernible number of conflicts between vehicles turning across through bicycles 30 in a bicycle lane has been demonstrated during the green interval of a signal, the bicycle box should not be 31 used. 32 Other treatments should be considered for conflicts between turning vehicles and through bicycles such as 33 using leading or exclusive signal phases, or separating turning traffic from through traffic through exclusive 34 turn lanes. 35 A bicycle lane should be used on the approach to a bicycle box. 36 A bicycle box should not be contiguous with a crosswalk. A stop line on the downstream end of the 37 bicycle box should be used to mark the location where bicycles are required to stop. 38 **Standard:** 39 If used, the distance from the upstream edge of the bicycle box that is nearest to the stop line for motor vehicles to the downstream edge of the bicycle box that is nearest the crosswalk or intersection 40 41 shall be at least 10 feet. At least one bicycle symbol marking (see Figure 9E-12) shall be used in the 42 bicycle box. 43 Where an existing stop line for motor vehicles is relocated upsum to install a new bicycle box, the yellow change and red clearance intervals (see Section 4F.17) shall be recalculated and if necessary, 44

reprogrammed to accommodate the length of the bicycle box.

1 Countdown pedestrian signals (see Section 4I.05) for the crosswalk or pedestrian crossing 2 movement that crosses the approach shall accompany bicycle boxes that extend across more than one 3 approach lane for motor vehicles. 4 Turns on red shall be prohibited from the lane where a bicycle box is placed. 5 **Guidance:** 6 Countdown pedestrian signals for the crosswalk or pedestrian crossing movement that crosses the 7 approach should accompany bicycle boxes where it is demonstrated that bicycles arrive at the intersection at 8 or near the end of the red signal indication being displayed to traffic in the approach lane(s) that is behind the 9 box. 10 Option: Green-colored pavement mobe used in a bicycle box. 11 12 **Standard:** 13 If used, green-colored pavement shall be used in the full limits of the bicycle box. 14 Support: 15 Section 9B.02 contains information on the Except Bicycles plaque that can be used below the STOP 16 HERE ON RED (R10-6 or R10-6a) sign (see Section 2B.63) to exempt the bicycle from the requirement of 17 the stop line. Figure 9E-12. Example of an Intersection Bicycle Box (2 Sheets) 18 19 Section 9C.03 9E.13 Marking Patterns and Colors on Shared-Use Paths 20 Option: 21 Where shared-use paths are of sufficient width to designate two minimum width lanes, a solid vellow 22 center line may be used to separate the two directions of travel where passing or traveling to the left of the line 23 is not permitted., and a A broken yellow center line may be used where passing is permitted (see Figure 9C-2 24 9E-13). Figure 9E-13. Examples of Center Line Markings for Shared-Use Paths 25 26 Guidance: 27 Broken lines used on shared-use paths should have the usual 1-to-3 segment-to-gap ratio. Aa nominal 3-28 foot segment with a 9-foot gap. should be used: 29 If conditions make it desirable to separate two directions of travel on shared-use paths at particular 30 locations, a solid yellow line should be used to indicate no passing and no traveling to the left of the line. 31 Markines as shown in Figure 9C 8 should be used at the location of obstructions in the center of the path. 32 including vertical elements intended to physically prevent unauthorized motor vehicles from entering the path. 33 Paragraph relocated to new Section 9E.17 34 Option: 35 A solid white line may be used on shared-use paths to separate different types of users in the same 36 direction. The R9-7 sign (see Section 9B.12-9B.13) may be used to supplement the solid white line. 37 Smaller size payement word markings and symbols may be used on shared-use paths. Where arrows are 38 needed on shared-use paths, half-size layouts of the arrows may be used (see Section 3B.20). 39 **Standard:** 40 Where a shared-use path crosses a roadway, crosswalk markings shall be used (see Chapter 3C). 41 Option: 42 Where pedestrian and bicycle movements on a shared-use path are separated on the approach to a roadway crossing, parallel bicycle and pedestrian crossing markings may be used as shown in Figure 9E-14. 43 44 Guidance: 45 If parallel bicycle and pedestrian crossing markings are used where a shared-use path crosses a roadway, crossing areas for bicycles should use green-colored pavement if the shared-use path crossing has a high 46

volume of either mode.

rigure 3E-14. Examples of Pavement Warkings for a Shared-Ose Path Crossing
Section 9E.14 Bicycle Route Pavement Markings
Option:
Pavement markings simulating guide signs for bicycle routes (see Section 9D.02 through 9D.07) and route
auxiliary plaques (see Section 9D.08) may be used to supplement guide signing to help bicyclists in
navigation (see Figure 9E-15).
Standard:
Pavement marking route markers have be limited to shared-use paths or separated bicycle lanes.
Pavement marking route markers not be used in standard bicycle lanes, buffer-separated bicycle lanes, or in shared lanes.
Except as provided in Paragraph 4, pavement markings simulating official guide signs for bicycle routes shall be supplemental to the sign(s) and shall not be a substitute for the sign(s).
Guidance:
A systematic methodology of locating the sign adjacent to the bicycle route pavement marking should be
used that includes locations where either the sign or the pavement marking can exist alone to avoid overuse o
the guide sign or the pavement marking.
The route marker pavement marking should not be elongated.
The location, size, and materials of the route marker pavement marking should be considered that will
minimize loss of traction for bicycles under wet conditions.
Figure 9E-15. Examples of Placement of Route Markers for Shared-Use Paths
Section 9C.05 9E. Bicycle Detector Symbol
Option:
A-The bicycle detector symbol (see Figure 9C-716) may be placed on the pavement indicating the
optimum position for a bicyclist bicycle to actuate the signal.
Appropriately sized WAIT HERE FOR GREEN word markings may be placed on the pavement
immediately below the bicycle detector symbol.
An A R10-22 sign (see Section 9B.13-9B.21 and Figure 9B-2) may be installed to supplement the bicycle
detector symbol pavement marking.
Support:
The Standard Highway Signs and Markings Book contains details for incorporating green-colored
pavement as a background enhancement to the bicycle detector symbol.
Figure 9E-1 Bicycle Detector Pavement Marking
Section <u>9C.06-9E.16</u> Pavement Markings for Obstructions
Guidance:
Markings as shown in Figure $\frac{9C-8-9E-17}{}$ should be used at the location of obstructions in the center of
the a shared-use path or physically separated bikeway, including vertical elements intended to physically
prevent unauthorized motor vehicles from entering the path. Paragraph relocated from new Section 9E.13
In roadway situations where it is not practical to eliminate a drain grate or other roadway obstruction
that is inappropriate for bicycle travel, white markings applied as shown in Figure $\frac{9C-8-9E-17}{9E-17}$ should be used to guide bicyclists around the condition.
Figure 9E-17. Examples of Obstruction Pavement Markings
Section 9E.17 Raised Devices
Support:
<u>oupport.</u>

<u>Chapter 3I contains information on using channelizing devices to emphasize pavement marking patterns associated with certain bicycle facilities. The most common application is the use of flexible raised devices in the buffer space of a buffer-separated bicycle lane (see Section 9E.06).</u>

Using <u>inflexible</u> raised devices <u>immediately adjacent to the travel path of the bicycle without a buffer</u> creates a collision potential for bicyclists. by placing fixed objects immediately adjacent to the travel path of the bicyclist. In addition, raised devices can prevent vehicles turning right from merging with the bicycle lane, which is the preferred method for making the right turn. Raised devices used to define a bicycle lane can also cause problems in cleaning and maintaining the bicycle lane.

Paragraph relocated from existing Section 9C.04 and edited

Option:

In accordance with Chapter 3I, channelizing devices may be used to emphasize a pavement marking pattern that establishes a bicycle lane or other bicycle facility provided that the installation of channelizing devices does not prevent motor vehicles from turning when the turn requires the motor vehicle to merge with the bicycle lane or facility as required by law or ordinance.

<u>Guidance:</u>

If used, channelizing devices for bicycle facilities should be tubular markers (see Section 31.02).

The selection of a raised device for use with bicycle facilities should consider the collision potential of the both the post and the base since the base may be present in the event the post is struck and missing.

Standard:

Channelizing devices that are used to emphasize the pavement marking patterns of bicycle facilities shall not incorporate the color green into either the device or its retroreflective element to supplement the presence of green-colored pavement.

23 Guidance:

If used in buffer-separated bicycle lanes, channelizing devices should be placed in the buffer space and at least one foot from the longitudinal bicycle lane pavement marking.

CHAPTER 9D.9F. SIGNALS

2 Section 9D.019F.01 Application

3 Support:

- 4 Part 4 contains information regarding signal warrants and other requirements relating to signal
- 5 installations.
- 6 Option:
- For purposes of signal warrant evaluation, bicyclist bicycles may be counted as either vehicles or pedestrians.
- 9 Section 9F.02 Bicycle Signal Face
- 10 Support:
- 11 Chapter 4H contains information on the design and application of bicycle signal faces. Section 9B.22
- 12 contains information for the Bicycle SIGNAL sign that is required to be installed with a bicycle signal face.
- 13 Section 9D.029F.03 Signal Operations for Bicycles
- 14 Standard:
- At installations where visibility-limited signal faces are used, signal faces shall be adjusted so bicyclists for whom the indications are intended can see the signal indications. If the visibility-limited signal faces cannot be aimed to serve the bicyclist, then separate signal faces shall be provided for the bicyclist.
- On bikeways, signal timing and actuation shall be reviewed and adjusted to consider the needs of bicyclists.

APPENDIX A1

CONGRESSIONAL LEGISLATIONACTIONS

<u>PUBLIC LAW 102-240-DEC. 18, 1991 (INTERMODAL SURFACE TRANSPORTATION EFFICIENCY ACT OF 1991)</u>

Section 1077. REVISION OF MANUAL — Not later than 90 days after the date of the enactment of this Act, the Secretary shall revise the Manual of Uniform Traffic Control Devices and such other regulations and agreements of the Federal Highway Administration as may be necessary to authorize States and local governments, at their discretion, to install stop or yield signs at any rail-highway grade crossing without automatic traffic control devices with 2 or more trains operating across the rail-highway grade crossing per day.

<u>PUBLIC LAW 102-388-OCT. 6, 1992 (DEPARTMENT OF TRANSPORTATION AND RELATED AGENCIES APPROPRIATIONS ACT, 1993)</u>

Section 406 — The Secretary of Transportation shall revise the Manual of Uniform Traffic Control Devices to include —

- (a) a standard for a minimum level of retroreflectivity that must be maintained for pavement markings and signs, which shall apply to all roads open to public travel; and
- (b) a standard to define the roads that must have a centerline or edge lines or both, provided that in setting such standard the Secretary shall consider the functional classification of roads, traffic volumes, and the number and width of lanes.

<u>PUBLIC LAW 104-59-NOV. 28, 1995 (NATIONAL HIGHWAY SYSTEM DESIGNATION ACT OF 1995)</u>

Section 205. RELIEF FROM MANDATES —

- (c) METRIC REQUIREMENTS
 - (1) PLACEMENT AND MODIFICATION OF SIGNS The Secretary shall not require the States to expend any Federal or State funds to construct, erect, or otherwise place or to modify any sign relating to a speed limit, distance, or other measurement on a highway for the purpose of having such sign establish such speed limit, distance, or other measurement using the metric system.
 - (2) OTHER ACTIONS Before September 30, 2000, the Secretary shall not require that any State use or plan to use the metric system with respect to designing or advertising, or preparing plans, specifications, estimates, or other documents, for a Federal-aid highway project eligible for assistance under title 23, United States Code.
 - (3) DEFINITIONS In this subsection, the following definitions apply:
 - (A) HIGHWAY The term 'highway' has the meaning such term has under section 101 of title 23. United States Code.
 - (B) METRIC SYSTEM the term 'metric system' has the meaning the term 'metric system of measurement' has under section 4 of the Metric Conversion Act of 1975 (15 U.S.C. 205c).

Section 306. MOTORIST CALL BOXES — Section 111 of title 23, United States Code, is amended by adding at the end the following:

(c) MOTORIST CALL BOXES —

(1) IN GENERAL — Notwithstanding subsection (a), a State may permit the placement of motorist call boxes on rights-of-way of the National Highway System. Such motorist call boxes may include the identification and sponsorship logos of such call boxes.

(2) SPONSORSHIP LOGOS —

- (A) APPROVAL BY STATE AND LOCAL AGENCIES All call box installations displaying sponsorship logos under this subsection shall be approved by the highway agencies having jurisdiction of the highway on which they are located.
- (B) SIZE ON BOX A sponsorship logo may be placed on the call box in a dimension not to exceed the size of the call box or a total dimension in excess of 12 inches by 18 inches.

- (C) SIZE ON IDENTIFICATION SIGN Sponsorship logos in a dimension not to exceed 12 inches by 30 inches may be displayed on a call box identification sign affixed to the call box post.
- (D) SPACING OF SIGNS Sponsorship logos affixed to an identification sign on a call box post may be located on the rights-of-way at intervals not more frequently than 1 per every 5 miles.
- (E) DISTRIBUTION THROUGHOUT STATE Within a State, at least 20 percent of the call boxes displaying sponsorship logos shall be located on highways outside of urbanized areas with a population greater than 50,000.
- (3) NONSAFETY HAZARDS The call boxes and their location, posts, foundations, and mountings shall be consistent with requirements of the Manual on Uniform Traffic Control Devices or any requirements deemed necessary by the Secretary to assure that the call boxes shall not be a safety hazard to motorists.

Section 353(a) SIGNS — Traffic control signs referred to in the experimental project conducted in the State of Oregon in December 1991 shall be deemed to comply with the requirements of Section 2B-4 of the Manual on Uniform Traffic Control Devices of the Department of Transportation.

Section 353(b) STRIPES — Notwithstanding any other provision of law, a red, white, and blue center line in the Main Street of Bristol, Rhode Island, shall be deemed to comply with the requirements of Section 3B-1 of the Manual on Uniform Traffic Control Devices of the Department of Transportation.

<u>PUBLIC LAW 115-141-MAR. 23, 2018 (CONSOLIDATED APPROPRIATIONS ACT, 2018)</u> DIVISION L, TITLE I

Section 125 -- For this fiscal year, the Federal Highway Administration shall reinstate Interim Approval IA-5, relating to the provisional use of an alternative lettering style on certain highway guide signs, as it existed before its termination, as announced in the Federal Register on January 25, 2016 (81 Fed. Reg. 4083).

Ontion:

Series E(modified)-Alternate may be used in place of Series E(modified) for the names of places, streets, and highways on freeway and expressway guide signs in accordance with the provisions of the following paragraph.

Standard:

The use of Series E(modified)-Alternate shall be limited to the display of names of places, streets, and highways on freeway and expressway guide signs. Words shall be composed of lower-case letters with initial upper-case letters. The design and spacing of the letters shall be as provided in the "Standard Highway Signs" publication (see Section 1A.11 of this Manual). The nominal loop height of the lower-case letters shall be 84 percent of the height of the initial upper-case letter. Interline spacing, measured from the baseline of the upper line of legend to the upper limit of the initial upper-case letter of the lower line of legend, shall be at least 96 percent of the initial upper-case letters (equivalent to 84 percent of the initial upper-case letter when measured from the baseline of the upper line of legend to the upper limit of the rising stems of the lower-case letters of the lower line of legend). Edge spacing shall be as provided in Section 2E.13 of this Manual. The size of the sign shall be suitably enlarged to accommodate the larger lower-case letters and interline spacing. When the name of a place, street, or highway contains numerals, the numerals shall be composed of the FHWA Standard Alphabet Series E(modified). Other lettering on the sign, such as for cardinal directions and distance or action messages, and all numerals or special characters, shall be composed of Series B, C, D, E, E(modified), or F of the FHWA Standard Alphabets as provided in this Manual.

Series E(modified)-Alternate shall not be used for any application other than as provided in the two preceding paragraphs.

APPENDIX A2 METRIC CONVERSIONS

Throughout this Manual all dimensions and distances are provided in English units. Tables A2-1 through A2-4 show the equivalent Metric (International System of Units) value for each of the English unit numerical values that are used in this Manual.