



Naive Bayes Classifiers

Difficulty Level : Medium • Last Updated : 24 Aug, 2022



This article discusses the theory behind the Naive Bayes classifiers and their implementation.

Naive Bayes classifiers are a collection of classification algorithms based on **Bayes' Theorem**. It is not a single algorithm but a family of algorithms where all of them share a common principle, i.e. every pair of features being classified is independent of each other.

To start with, let us consider a dataset.

Consider a fictional dataset that describes the weather conditions for playing a game of golf. Given the weather conditions, each tuple classifies the conditions as fit("Yes") or unfit("No") for playing golf.

Here is a tabular representation of our dataset.

	Outlook	Temperature	Humidity	Windy	Play Golf
0	Rainy	Hot	High	False	No
1	Rainy	Hot	High	True	No
2	Overcast	Hot	High	False	Yes
3	Sunny	Mild	High	False	Yes
4	Sunny	Cool	Normal	False	Yes
	Sunny	Cool	Normal	True	No



6	Overcast	Cool	Normal	True	Yes
7	Rainy	Mild	High	False	No
8	Rainy	Cool	Normal	False	Yes
9	Sunny	Mild	Normal	False	Yes
10	Rainy	Mild	Normal	True	Yes
11	Overcast	Mild	High	True	Yes
12	Overcast	Hot	Normal	False	Yes
13	Sunny	Mild	High	True	No

The dataset is divided into two parts, namely, **feature matrix** and the **response vector**.

- Feature matrix contains all the vectors(rows) of dataset in which each vector consists of the value of **dependent features**. In above dataset, features are 'Outlook', 'Temperature', 'Humidity' and 'Windy'.
- Response vector contains the value of **class variable**(prediction or output) for each row of feature matrix. In above dataset, the class variable name is 'Play golf'.

Assumption:

The fundamental Naive Bayes assumption is that each feature makes an:

- independent

contribution to the outcome.





Machine Learning Course

Beginner to Advance Level ★★★★★

Machines are evolving, so why do you wish to get left behind? Strengthen your ML and AI foundations today and become future-ready with Machine Learning Basic and Advanced - Self-Paced Course.

[Explore Now](#)

With relation to our dataset, this concept can be understood as:

- We assume that no pair of features are dependent. For example, the temperature being 'Hot' has nothing to do with the humidity or the outlook being 'Rainy' has no effect on the winds. Hence, the features are assumed to be **independent**.
- Secondly, each feature is given the same weight(or importance). For example, knowing only temperature and humidity alone can't predict the outcome accurately. None of the attributes is irrelevant and assumed to be contributing **equally** to the outcome.

Note: The assumptions made by Naive Bayes are not generally correct in real-world situations. In-fact, the independence assumption is never correct but often works well in practice.

Now, before moving to the formula for Naive Bayes, it is important to know about Bayes' theorem.

Bayes' Theorem

Bayes' Theorem finds the probability of an event occurring given the probability of another event that has already occurred. Bayes' theorem is stated mathematically as the following equation:

$$P(A|B) = \frac{P(B|A)P(A)}{P(B)}$$

where A and B are events and $P(B) \neq 0$.

- Basically, we are trying to find probability of event A, given the event B is true. Event B is also termed as **evidence**.

P(A) is the **priori** of A (the prior probability, i.e. Probability of event before



Start Your Coding Journey Now!

[Login](#)[Register](#)

- $P(A|B)$ is a posteriori probability of B, i.e. probability of event after evidence is seen.

Now, with regards to our dataset, we can apply Bayes' theorem in following way:

$$P(y|X) = \frac{P(X|y)P(y)}{P(X)}$$

where, y is class variable and X is a dependent feature vector (of size n) where:

$$X = (x_1, x_2, x_3, \dots, x_n)$$

Just to clear, an example of a feature vector and corresponding class variable can be:
(refer 1st row of dataset)

$X = (\text{Rainy}, \text{Hot}, \text{High}, \text{False})$

$y = \text{No}$

So basically, $P(y|X)$ here means, the probability of "Not playing golf" given that the weather conditions are "Rainy outlook", "Temperature is hot", "high humidity" and "no wind".

Naive assumption

Now, its time to put a naive assumption to the Bayes' theorem, which is, **independence** among the features. So now, we split **evidence** into the independent parts.

Now, if any two events A and B are independent, then,

$$P(A, B) = P(A)P(B)$$

Hence, we reach to the result:

$$P(y|x_1, \dots, x_n) = \frac{P(x_1|y)P(x_2|y)\dots P(x_n|y)P(y)}{P(x_1)P(x_2)\dots P(x_n)}$$

which can be expressed as:

$$P(y|x_1, \dots, x_n) = \frac{P(y) \prod_{i=1}^n P(x_i|y)}{P(x_1)P(x_2)\dots P(x_n)}$$

Now, as the denominator remains constant for a given input, we can remove that term:

$$P(y|x_1, \dots, x_n) \propto P(y) \prod_{i=1}^n P(x_i|y)$$

maximum probability. This can be expressed mathematically as:

$$y = \operatorname{argmax}_y P(y) \prod_{i=1}^n P(x_i|y)$$

So, finally, we are left with the task of calculating $P(y)$ and $P(x_i | y)$.

Please note that $P(y)$ is also called **class probability** and $P(x_i | y)$ is called **conditional probability**.

The different naive Bayes classifiers differ mainly by the assumptions they make regarding the distribution of $P(x_i | y)$.

Let us try to apply the above formula manually on our weather dataset. For this, we need to do some precomputations on our dataset.

We need to find $P(x_i | y_j)$ for each x_i in X and y_j in y . All these calculations have been demonstrated in the tables below:

Outlook					Temperature				
	Yes	No	P(yes)	P(no)		Yes	No	P(yes)	P(no)
Sunny	2	3	2/9	3/5	Hot	2	2	2/9	2/5
Overcast	4	0	4/9	0/5	Mild	4	2	4/9	2/5
Rainy	3	2	3/9	2/5	Cool	3	1	3/9	1/5
Total	9	5	100%	100%	Total	9	5	100%	100%

Humidity					Wind				
	Yes	No	P(yes)	P(no)		Yes	No	P(yes)	P(no)
High	3	4	3/9	4/5	False	6	2	6/9	2/5
Normal	6	1	6/9	1/5	True	3	3	3/9	3/5
Total	9	5	100%	100%	Total	9	5	100%	100%

Play			P(Yes)/P(No)
Yes	9		9/14
No	5		5/14
Total	14		100%

So, in the figure above, we have calculated $P(x_i | y_j)$ for each x_i in X and y_j in y manually in the tables 1-4. For example, probability of playing golf given that the temperature is cool, i.e $P(\text{temp.} = \text{cool} | \text{play golf} = \text{Yes}) = 3/9$.

Also, we need to find class probabilities ($P(y)$) which has been calculated in the table 5. For example, $P(\text{play golf} = \text{Yes}) = 9/14$.

So now, we are done with our pre-computations and the classifier is ready!

Let us test it on a new set of features (let us call it today):



today = (Sunny, Hot, Normal, False)



$$P(Yes|today) = \frac{P(SunnyOutlook|Yes)P(HotTemperature|Yes)P(NormalHumidity|Yes)P(NoWind|Yes)P(Yes)}{P(today)}$$

and probability to not play golf is given by:

$$P(No|today) = \frac{P(SunnyOutlook|No)P(HotTemperature|No)P(NormalHumidity|No)P(NoWind|No)P(No)}{P(today)}$$

Since, $P(today)$ is common in both probabilities, we can ignore $P(today)$ and find proportional probabilities as:

$$P(Yes|today) \propto \frac{2}{9} \cdot \frac{2}{9} \cdot \frac{6}{9} \cdot \frac{6}{9} \cdot \frac{9}{14} \approx 0.0141$$

and

$$P(No|today) \propto \frac{3}{5} \cdot \frac{2}{5} \cdot \frac{1}{5} \cdot \frac{2}{5} \cdot \frac{5}{14} \approx 0.0068$$

Now, since

$$P(Yes|today) + P(No|today) = 1$$

These numbers can be converted into a probability by making the sum equal to 1 (normalization):

$$P(Yes|today) = \frac{0.0141}{0.0141+0.0068} = 0.67$$

and

$$P(No|today) = \frac{0.0068}{0.0141+0.0068} = 0.33$$

Since

$$P(Yes|today) > P(No|today)$$

So, prediction that golf would be played is 'Yes'.


The method that we discussed above is applicable for discrete data. In case of continuous data, we need to make some assumptions regarding the distribution of values of each feature. The different naive Bayes classifiers differ mainly by the assumptions they make regarding the distribution of $P(x_i | y)$.

Now, we discuss one of such classifiers here.

Gaussian Naive Bayes classifier

In Gaussian Naive Bayes, continuous values associated with each feature are assumed to be distributed according to a **Gaussian distribution**. A Gaussian





The likelihood of the features is assumed to be Gaussian, hence, conditional probability is given by:

$$P(x_i|y) = \frac{1}{\sqrt{2\pi\sigma_y^2}} \exp\left(-\frac{(x_i - \mu_y)^2}{2\sigma_y^2}\right)$$

Now, we look at an implementation of Gaussian Naive Bayes classifier using scikit-learn.

```
# load the iris dataset
from sklearn.datasets import load_iris
iris = load_iris()

# store the feature matrix (X) and response vector (y)
X = iris.data
y = iris.target

# splitting X and y into training and testing sets
from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.4, random_

# training the model on training set
from sklearn.naive_bayes import GaussianNB
gnb = GaussianNB()
gnb.fit(X_train, y_train)

# making predictions on the testing set
y_pred = gnb.predict(X_test)

# comparing actual response values (y_test) with predicted response values (y_pre
from sklearn import metrics
print("Gaussian Naive Bayes model accuracy (in %):", metrics.accuracy_score(y_test
```

Gaussian Naive Bayes model accuracy(in %): 95.0

Other popular Naive Bayes classifiers are:

- **Multinomial Naive Bayes:** Feature vectors represent the frequencies with which certain events have been generated by a **multinomial distribution**. This is the event model typically used for document classification.
- **Bernoulli Naive Bayes:** In the multivariate Bernoulli event model, features are independent booleans (binary variables) describing inputs. Like the multinomial model, this model is popular for document classification tasks, where binary term occurrence (i.e. a word occurs in a document or not) features are used rather than term frequencies (i.e. frequency of a word in the document).

As we reach to the end of this article, here are some important points to ponder upon:

- In spite of their apparently over-simplified assumptions, naive Bayes classifiers have worked quite well in many real-world situations, famously document classification and spam filtering. They require a small amount of training data to estimate the necessary parameters.
- Naive Bayes learners and classifiers can be extremely fast compared to more sophisticated methods. The decoupling of the class conditional feature distributions means that each distribution can be independently estimated as a one dimensional distribution. This in turn helps to alleviate problems stemming from the curse of dimensionality.

References:

- https://en.wikipedia.org/wiki/Naive_Bayes_classifier
- http://gerardnico.com/wiki/data_mining/naive_bayes
- http://scikit-learn.org/stable/modules/naive_bayes.html

This blog is contributed by [Nikhil Kumar](#). If you like GeeksforGeeks and would like to contribute, you can also write an article using write.geeksforgeeks.org or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.



Start Your Coding Journey Now!

Login

Register

Master Advanced
Data Structures

DSA Live Classes For
Working Professionals

Enrol Now


GET HIRED



Like 111

< Previous

Next >

RECOMMENDED ARTICLES

Page : 1 2

- | | | | |
|----|---|----|---|
| 01 | Applying Multinomial Naive Bayes to NLP Problems
11, Jan 19 | 05 | ML Dummy classifiers using sklearn
23, May 19 |
| 02 | ML Naive Bayes Scratch Implementation using Python
03, Feb 20 | 06 | How to use built-in image classifiers of visual recognition module using IBM watson?
10, Jun 20 |
| 03 | Complement Naive Bayes (CNB) Algorithm
23, Jul 20 | 07 | How to build custom image classifiers using IBM Watson?
11, Jun 20 |
| 04 | Classification of Text Documents using the approach of Naive Bayes
01, Jun 22 | 08 | Passive Aggressive Classifiers
08, Jul 20 |



Start Your Coding Journey Now!

[Login](#)[Register](#)

Article Contributed By :



GeeksforGeeks

Vote for difficulty

Current difficulty : [Medium](#)

[Easy](#)[Normal](#)[Medium](#)[Hard](#)[Expert](#)

Improved By : [Sambhav_Khurana](#), [shivamraj74](#), [raunaksrivastava22](#), [germanshepherd48](#), [rkbhola5](#)

Article Tags : [Advanced Computer Subject](#), [Machine Learning](#), [Python](#)

Practice Tags : [Machine Learning](#), [python](#)

[Improve Article](#)[Report Issue](#)

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

[Load Comments](#)

GeeksforGeeks



A-143, 9th Floor, Sovereign Corporate Tower,
Sector-136, Noida, Uttar Pradesh - 201305



feedback@geeksforgeeks.org



Careers
In Media
Contact Us
Privacy Policy
Copyright Policy

Data Structures
SDE Cheat Sheet
Machine learning
CS Subjects
Video Tutorials
Courses

News

Top News
Technology
Work & Career
Business
Finance
Lifestyle
Knowledge

Languages

Python
Java
CPP
Golang
C#
SQL
Kotlin

Web Development

Web Tutorials
Django Tutorial
HTML
JavaScript
Bootstrap
ReactJS
NodeJS

Contribute

Write an Article
Improve an Article
Pick Topics to Write
Write Interview Experience
Internships
Video Internship

