DYBH-102

Shear Beam Load Cell

GRV Automation | CE Certified | Custom Configurations Available on Request

Application / Features

- High capacity shear beam for heavy industrial use
- Long-distance wireless reading capability
- Robust alloy steel construction
- High IP protection for outdoor use
- Suitable for large-range crane and hoisting
- Crane scales, weighbridges, industrial platforms

Rated range: 1T - 500T

Rated Capacity		**1T-500T**
Output Sensitivity	mV/V	**2.0+/-10%**
Non-linearity	%F.S.	**0.03**
Hysteresis	%F.S.	**0.03**
Repeatability	%F.S.	**0.02**
Creep (30 min)	%F.S.	**0.03**
Material		**Alloy Steel**
Input/Output Impedance	Ohm	**350+/-5 / 350+/-5**
Excitation Voltage	V	**5-15 (recommended 10)**
Operating Temp.	degC	**-30 to +70**
Safety Overload	%R.C.	**150**
IP Rating		**IP67**
Cable		**D6x5m, 4-wire**

1) High temperature sensors available (max. 150 deg C). 2) High impedance option (1000 Ohm) on request. 3) Specifications subject to change without prior notice.

GRV Automation | WeWork Latitude, Hebbal, Bengaluru - 560024, Karnataka, India
Tel: +91 9008 300 172 | info@grvautomation.com | www.grvautomation.com | We reserve the right to make technical alterations without prior notice.