DYBH-103

Shear Beam Load Cell

GRV Automation | CE Certified | Custom Configurations Available on Request

Application / Features

- Port crane and ship crane dynamometer
- High accuracy for heavy lifting applications
- Robust structural steel design
- Digital display option available
- Long-term reliable performance
- Port cranes, ship cranes, industrial hoisting

Rated range: 1T - 6T

Rated Capacity		**1T-6T**
Output Sensitivity	mV/V	**2.0+/-10%**
Non-linearity	%F.S.	**0.03**
Hysteresis	%F.S.	**0.03**
Repeatability	%F.S.	**0.02**
Material		**Alloy Steel / Structural Steel**
Input/Output Impedance	Ohm	**350+/-5 / 350+/-5**
Excitation Voltage	V	**5-15 (recommended 10)**
Operating Temp.	degC	**-30 to +70**
Safety Overload	%R.C.	**150**
IP Rating		**IP67**
Cable		**D6x5m, 4-wire**

1) High temperature sensors available (max. 150 deg C). 2) High impedance option (1000 Ohm) on request. 3) Specifications subject to change without prior notice.

GRV Automation | WeWork Latitude, Hebbal, Bengaluru - 560024, Karnataka, India
Tel: +91 9008 300 172 | info@grvautomation.com | www.grvautomation.com | We reserve the right to make technical alterations without prior notice.