DYMH-108

Spoke Type Load Cell

GRV Automation | CE Certified | Custom Configurations Available on Request

Application / Features

- Ultra-compact capsule design
- Tension and compression dual measurement
- High precision with low non-linearity
- Stainless steel for corrosion resistance
- Anti-interference stable output
- Automation, robot arms, medical testing

Rated range: 200kg - 1T

Rated Capacity		**200kg-1T**
Output Sensitivity	mV/V	**2.0+/-10%**
Non-linearity	%F.S.	**0.03**
Hysteresis	%F.S.	**0.03**
Repeatability	%F.S.	**0.02**
Material		**Stainless Steel**
Input/Output Impedance	Ohm	**350+/-5 / 350+/-5**
Excitation Voltage	V	**5-15 (recommended 10)**
Operating Temp.	degC	**-20 to +70**
Safety Overload	%R.C.	**150**
IP Rating		**IP67**
Cable		**D4x3m, 4-wire**

1) High temperature sensors available (max. 150 deg C). 2) High impedance option (1000 Ohm) on request. 3) Specifications subject to change without prior notice.

GRV Automation | WeWork Latitude, Hebbal, Bengaluru - 560024, Karnataka, India
Tel: +91 9008 300 172 | info@grvautomation.com | www.grvautomation.com | We reserve the right to make technical alterations without prior notice.