GLMA110

Multi-Axial Force Sensor

GRV Automation | CE Certified | Custom Configurations Available on Request

Application / Features

- Precision 6-axis multi-axis sensor
- 2 multi-torque measurement capability
- High precision for collaborative robots
- Compact size for small robot integration
- High-frequency dynamic response
- Collaborative robots, medical devices, precision testing

Rated range: 20N - 100N

Rated Capacity (Fz)	N	**20-100**
Torque Range (Mz)	N.m	**1-3**
Axes		**6 (Fx/Fy/Fz/Mx/My/Mz)**
Non-linearity	%F.S.	**0.5**
Material		**Alloy Steel / Stainless Steel**
Excitation Voltage	V	**5-15**
Operating Temp.	degC	**-20 to +70**
IP Rating		**IP65**
Output		**Analog or RS485 digital**
Cable		**D5x3m, multi-wire**

1) High temperature sensors available (max. 150 deg C). 2) High impedance option (1000 Ohm) on request. 3) Specifications subject to change without prior notice.

GRV Automation | WeWork Latitude, Hebbal, Bengaluru - 560024, Karnataka, India
Tel: +91 9008 300 172 | info@grvautomation.com | www.grvautomation.com | We reserve the right to make technical alterations without prior notice.