GLTN103

Tension Sensor

GRV Automation | CE Certified | Custom Configurations Available on Request

Application / Features

- Wire rope tension force clamp sensor
- Rated capacity 0-200kN
- Low-cost clamp-on design for easy installation
- High accuracy wire rope force measurement
- Suitable for continuous online tension monitoring
- Crane cables, elevator ropes, cable tension monitoring

Rated range: 0-200kN

Rated Capacity		**0-200kN**
Output Sensitivity	mV/V	**2.0+/-10%**
Non-linearity	%F.S.	**0.03**
Hysteresis	%F.S.	**0.03**
Repeatability	%F.S.	**0.02**
Material		**Alloy Steel**
Input/Output Impedance	Ohm	**350+/-5 / 350+/-5**
Excitation Voltage	V	**5-15 (recommended 10)**
Operating Temp.	degC	**-20 to +70**
Safety Overload	%R.C.	**150**
IP Rating		**IP67**
Cable		**D5x5m, 4-wire**

1) High temperature sensors available (max. 150 deg C). 2) High impedance option (1000 Ohm) on request. 3) Specifications subject to change without prior notice.

GRV Automation | WeWork Latitude, Hebbal, Bengaluru - 560024, Karnataka, India
Tel: +91 9008 300 172 | info@grvautomation.com | www.grvautomation.com | We reserve the right to make technical alterations without prior notice.