# GLCL103

## Column Type Load Cell

GRV Automation | CE Certified | Custom Configurations Available on Request

### Application / Features

- High precision gravity and force measurement
- Wide range 10kN to 150kN
- Robust alloy steel column design
- Long-term stability under continuous load
- Suitable for multi-column configurations
- Press monitoring, structural testing, industrial weighing

**Rated range: 10kN - 150kN**

| | | |
|---|---|---|
| **Rated Capacity** | | **10kN-150kN** |
| **Output Sensitivity** | mV/V | **1.5-2.5** |
| **Non-linearity** | %F.S. | **0.03** |
| **Hysteresis** | %F.S. | **0.03** |
| **Repeatability** | %F.S. | **0.02** |
| **Creep (30 min)** | %F.S. | **0.05** |
| **Material** | | **Alloy Steel** |
| **Input/Output Impedance** | Ohm | **350+/-5 / 350+/-5** |
| **Excitation Voltage** | V | **5-15 (recommended 10)** |
| **Operating Temp.** | degC | **-30 to +70** |
| **Safety Overload** | %R.C. | **150** |
| **IP Rating** | | **IP67** |
| **Cable** | | **D6x5m, 4-wire** |

*1) High temperature sensors available (max. 150 deg C). 2) High impedance option (1000 Ohm) on request. 3) Specifications subject to change without prior notice.*