GLSH307

Shear Beam Load Cell

GRV Automation | CE Certified | Custom Configurations Available on Request

Application / Features

- Single point shear beam for medium platforms
- OIML accuracy class C3
- Alloy steel construction
- Wide capacity range in one model
- Easy installation
- Platform scales, industrial scales

Rated range: 300g - 1000kg

Rated Capacity		**300g-1000kg**
Output Sensitivity	mV/V	**2.0+/-10%**
Accuracy Class		**C3 (OIML)**
Non-linearity	%F.S.	**0.017**
Hysteresis	%F.S.	**0.017**
Repeatability	%F.S.	**0.010**
Material		**Alloy Steel**
Input/Output Impedance	Ohm	**350+/-5 / 350+/-5**
Excitation Voltage	V	**5-15 (recommended 10)**
Operating Temp.	degC	**-10 to +40**
Safety Overload	%R.C.	**150**
IP Rating		**IP65**
Cable		**D4x2m, 4-wire**

1) High temperature sensors available (max. 150 deg C). 2) High impedance option (1000 Ohm) on request. 3) Specifications subject to change without prior notice.

GRV Automation | WeWork Latitude, Hebbal, Bengaluru - 560024, Karnataka, India
Tel: +91 9008 300 172 | info@grvautomation.com | www.grvautomation.com | We reserve the right to make technical alterations without prior notice.