DSA Data Science Web Tech Courses

Human Activity Recognition Using Smartphone Data

Human activity recognition using smartphone data involves using machine learning techniques to classify different physical activities based on data collected from the sensors in a smartphone. The experiments have been carried out with a group of 30 volunteers within an age bracket of 19–48 years. Each person performed six activities (WALKING, WALKINGUPSTAIRS, WALKINGDOWNSTAIRS, SITTING, STANDING, LAYING) wearing a smartphone (Samsung Galaxy S II) on the waist. Using its embedded accelerometer and gyroscope, we captured 3-axial linear acceleration and 3-axial linear acceleration and 3-axial angular velocity at a constant rate of 50Hz. The experiments have been video-recorded to label the data manually. The obtained dataset has been randomly partitioned into two sets, where 70% of the volunteers were selected for generating the training data and 30% the test data.

The sensor signals (accelerometer and gyroscope) were pre-processed by applying noise filters and then sampled in fixed-width sliding windows of 2.56 sec and 50% overlap (128 readings/window). The sensor acceleration signal, which has gravitational force is assumed to have only low frequency components, therefore a filter with 0.3 Hz cutoff frequency was used. From each window, a vector of features was obtained by calculating variables from the time and frequency domain.

The goal of the project is to use this data to train a machine learning model, such as a decision tree, random forest, support vector machine, or neural network. Finally, we can evaluate the performance of our model on a separate test dataset to see how well it generalizes to new examples of activities.

<u>Data pre-processing:</u>


 \Box

Articles

 \triangleright

In Data pre-processing we'll perform various activities like:

- Checking Duplicates
- Checking and removing NULL/missing values




Class Imbalance


After pre-processing we can perform EDA


have class imbalance problem.

<u>EDA</u>

EDA might involve visualizing the data to see how the different features vary across different activities, or computing summary statistics such as mean and standard deviation to understand the distribution of the data and identify any outliers or anomalies. We could also create scatter plots to see how the different features are correlated with each other, or create time series plots to see how the data varies over time.









Some Plots from the EDA part.

<u>Model:</u>

As the data is already divided in train and test dataset we just have to pass the dataset through different models tune these models(hyperparameter tuning) and cross validate them



Logistic Regression



≪ P

Decision Tree Data: https://github.com/AshishJangra27/Machine-Learning-with-Python-GFG/blob/main/Human%20Activity%20Recognition%20using%20Smartphone%20data/dataset.zip Code: https://github.com/AshishJangra27/Machine-Learning-with-Python- GFG/blob/main/Human%20Activity%20Recognition%20using%20Smartphone%20data/human_activity_recognition_using_smartphone_Y.ipynb Articles \triangleright Report An Issue If you are facing any issue on this page. Please let us know.

Mark as Read