

JMETER ASSESSMENT NO: 01

Name: Gaurav Nandgopal Deshmukh

USN: 72232433C

Problem statement: Create JMeter file doing jdbc connectivity with postgresQL and performing tasks such as creating, inserting, updating and deleting on sample database.

Steps:

1. Download (postgresql-42.7.7) JDBC connector .jar file and add to the jmeter/lib on our system.
2. Open apache jmeter and create test plan
3. Right click test plan -> add -> threads -> thread group
4. Right click thread group -> Add -> Config element -> JDBC connection Configuration
{ DatabaseUrl:- jdbc:postgresql://localhost:5432/jmeterdb
JDBC Driver class:-org.postgresql.driver
}
5. Add -> Sampler -> JDBC Request
6. Add -> Listener -> View Result Tree
7. Verify results along with PostgreSQL .

Solution:

PostgreSQL_JDBC	
Create Table	
JDBC Connection Configuration	
JDBC Request	
View Results Tree	
View Results in Table	
Insert Values	
Update Table	
Delete Record	

Variable Name Bound to Pool	
Variable Name for created pool:	mydb
Connection Pool Configuration	
Max Number of Connections:	0
Max Wait (ms):	10000
Time Between Eviction Runs (ms):	60000
Auto Commit:	True
Transaction Isolation:	DEFAULT
Pool Prepared Statements:	-1
Preinit Pool:	False
Init SQL statements separated by new line:	
1	

Connection Validation by Pool	
Test While Idle:	True
Soft Min Evictable Idle Time(ms):	5000
Validation Query:	

Database Connection Configuration	
Database URL:	jdbc:postgresql://localhost:5432/jmeterdb
JDBC Driver class:	org.postgresql.Driver
Username:	postgres
Password:	
Connection Properties:	10

1. Create Table:

The screenshot shows the JMeter configuration for a PostgreSQL JDBC connection. On the left, the 'PostgreSQL_JDBC' tree contains 'Create Table', 'JDBC Connection Configuration', 'JDBC Request', 'View Results Tree', 'View Results in Table', 'Insert Values', 'Update Table', and 'Delete Record'. The 'JDBC Request' sampler is selected, showing its configuration: Name: 'JDBC Request', Variable Name Bound to Pool: 'mydb', and SQL Query: 'CREATE TABLE test_table (id SERIAL PRIMARY KEY, name VARCHAR(50));'. The 'Query Type' is set to 'Update Statement'.

The screenshot shows the 'View Results Tree' sampler, which is selected in the left tree. It displays the results of the 'JDBC Request' sampler. The 'Response Body' tab shows the following text: 'shared:false, driver:org.postgresql.Driver, url:jdbc:postgresql://localhost:5432/jmeterdb, user:postgres'. The 'Log/Display Only' checkbox is checked for 'Errors'.

The screenshot shows the 'Query History' and 'Data Output' panels. The 'Query History' panel displays the SQL query: 'select * from test_table;'. The 'Data Output' panel shows the table structure for 'test_table' with columns 'id' (integer, primary key) and 'name' (character varying (50)).

id	name
----	------

2. Insert Values:

 PostgreSQL_JDBC	 Create Table	
	 Insert Values	
	 JDBC Connection Configuration	
	 JDBC Request	
	 View Results Tree	
	 View Results in Table	
	 Update Table	
	 Delete Record	
Variable Name Bound to Pool		
Variable Name for created pool: mydb		
Connection Pool Configuration		
Max Number of Connections: 0		
Max Wait (ms): 10000		
Time Between Eviction Runs (ms): 60000		
Auto Commit: True		
Transaction Isolation: DEFAULT		
Pool Prepared Statements: -1		
Preinit Pool: False		
Init SQL statements separated by new line:		
1		
Connection Validation by Pool		
Test While Idle: True		
Soft Min Evictable Idle Time(ms): 5000		
Validation Query:		
Database Connection Configuration		
Database URL: jdbc:postgresql://localhost:5432/jmeterdb		
JDBC Driver class: org.postgresql.Driver		
Username: postgres		
Password: ****		
Connection Properties: 10		

3. Update Table:

- PostgreSQL_JDBC
 - Create Table
 - Insert Values
 - Update Table
 - JDBC Connection Configuration
 - JDBC Request
 - View Results Tree
 - View Results in Table
 - Delete Record

JDBC Request

Name: JDBC Request

Comments:

Variable Name Bound to Pool

Variable Name of Pool declared in JDBC Connection Configuration: mydb

SQL Query

Query Type: Update Statement

Query:

```
1 UPDATE test_table SET name = 'Rameshwar Deshmukh' WHERE id = 2;
2
```

- Update Table
 - JDBC Connection Configuration
 - JDBC Request
 - View Results Tree
 - View Results in Table
- Delete Record

Comments:

Write results to file / Read from file

Filename

Search: ☐ Case sensitive ☐ Regular exp.

Text

- ✓ JDBC Request

Sampler result Request Response data

Response Body Response headers

1 updates

Query Query History

```
1 select * from test_table;  
2
```

Data Output



	id [PK] integer	name character varying (50)
1	2	Rameshwar Deshmukh

4. Delete Record:

The screenshot shows the 'JDBC Request' configuration window. On the left, a tree view under 'PostgreSQL_JDBC' includes 'Delete Record', 'JDBC Connection Configuration', 'JDBC Request' (selected), 'View Results Tree', and 'View Results in Table'. The main panel is titled 'JDBC Request' and contains the following fields:

- Name:** JDBC Request
- Comments:** (empty)
- Variable Name Bound to Pool:** (empty)
- Variable Name of Pool declared in JDBC Connection Configuration:** mydb
- SQL Query:**
 - Query Type:** Update Statement
 - SQL:**

```
1 DELETE FROM test_table WHERE id = 2;  
2
```

The screenshot shows the 'View Results Tree' window. On the left, a tree view includes 'Delete Record', 'JDBC Connection Configuration', 'JDBC Request' (selected), 'View Results Tree', and 'View Results in Table'. The main panel displays the execution results of the 'JDBC Request'.

Comments: (empty)

Write results to file / Read from file: (empty) **Filename:** (empty) **Browse...** **Log/Display Only**

Search: (empty) ☐ Case sensitive ☐ Regular exp. **Search** **Reset**

Text: (empty)

Sampler result: (empty)

Request: (empty)

Response data: (empty)

Request Body: (empty)

Request Headers: (empty)

SQL:

```
1 [Update Statement] DELETE FROM test_table WHERE id = 2;  
2  
3  
4
```

The screenshot shows the 'Query' and 'Query History' window. The 'Query' tab is active, displaying the following SQL query:

```
1 select * from test_table;  
2
```

The 'Query History' tab is also visible, showing the same query.

Data Output

id [PK] integer **name** character varying (50)

